

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12415363
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Hagiwara; Hiroyuki et al.

Liquid ejecting apparatus and filling method

Abstract

A liquid ejecting apparatus includes a filter that partitions a common liquid chamber communicating with a nozzles into an upstream chamber and a downstream chamber, an inlet, an outlet, a liquid storage section, a supply flow path, and a recovery flow path. A beam portion is provided inside the downstream chamber. A pressurization discharge operation for discharging the liquid from the nozzles and a circulation operation for circulating the liquid in a circulation path are performed. In the filling process of filling the circulation path with the liquid, after the first circulation operation is performed, a predetermined operation for moving the liquid inside the downstream chamber in a direction different from a direction in which the liquid inside the downstream chamber is moved by the circulation operation is performed, and thereafter, the pressurization discharge operation is performed.

Inventors: Hagiwara; Hiroyuki (Matsumoto, JP), Katsuie; Shun (Matsumoto, JP), Sokabe; Hidenori (Shiojiri, JP)

Applicant: SEIKO EPSON CORPORATION (Tokyo, JP)

Family ID: 1000008820251

Assignee: SEIKO EPSON CORPORATION (N/A, JP)

Appl. No.: 18/364683

Filed: August 03, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240042772 A1	Feb. 08, 2024

Foreign Application Priority Data

JP	2022-124596	Aug. 04, 2022
----	-------------	---------------

Publication Classification

Int. Cl.: B41J2/175 (20060101); B41J2/18 (20060101); B41J2/19 (20060101)

U.S. Cl.:

CPC B41J2/17563 (20130101); B41J2/18 (20130101); B41J2/19 (20130101); B41J2202/07 (20130101)

Field of Classification Search

CPC: B41J (2/14201); B41J (2/14233); B41J (2/17563); B41J (2/18); B41J (2/19); B41J (2202/07)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
11247460	12/2021	Sugiura	N/A	B41J 2/14233
11673400	12/2022	Moriyama	347/93	B41J 2/17506
2024/0042771	12/2023	Sokabe	N/A	B41J 2/17563

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2017-217612	12/2016	JP	N/A
2021-187003	12/2020	JP	N/A

Primary Examiner: Mruk; Geoffrey S

Attorney, Agent or Firm: Harness, Dickey & Pierce, P.L.C.

Background/Summary

(1) The present application is based on, and claims priority from JP Application Serial Number 2022-124596, filed Aug. 4, 2022, the disclosure of which is hereby incorporated by reference herein in its entirety.

BACKGROUND

1. Technical Field

(2) The present disclosure relates to a liquid ejecting apparatus and a filling method.

2. Related Art

(3) In the related art, a liquid ejecting apparatus for ejecting a liquid such as an ink from a plurality of nozzles is known. For example, JP-A-2017-217612 discloses a liquid ejecting apparatus including a liquid storage section capable of storing a liquid, a common liquid chamber communicating with a plurality of nozzles, a supply flow path for supplying the liquid from the liquid storage section to the common liquid chamber, and a recovery flow path for recovering the liquid from the common liquid chamber to the liquid storage section. The common liquid chamber of the liquid ejecting apparatus disclosed in JP-A-2017-217612 is partitioned into an upstream chamber and a downstream chamber by a filter. The upstream chamber is provided with an inlet for

communicating with the recovery flow path and introducing the liquid into the upstream chamber, and an outlet for communicating with the recovery flow path and causing the liquid to flow out.

(4) In addition, JP-A-2021-187003 discloses a liquid ejecting apparatus including a liquid storage section, a liquid ejecting head having a plurality of nozzles, a supply flow path for supplying a liquid from the liquid storage section to the liquid ejecting head, and a recovery flow path for recovering the liquid from the liquid ejecting head, in which the liquid is circulated between the liquid storage section and the liquid ejecting head. The liquid ejecting apparatus disclosed in JP-A-2021-187003 has an on-off valve capable of opening and closing the recovery flow path.

Furthermore, in JP-A-2021-187003, in a filling process of filling the supply flow path, the recovery flow path, and the liquid ejecting head with the liquid, a circulation operation is performed to circulate the liquid in a state where the recovery flow path is opened by the on-off valve.

Thereafter, a pressurization discharge operation is performed to discharge the liquid from the liquid ejecting head by causing the on-off valve to close the recovery flow path.

(5) In the liquid ejecting head disclosed in JP-A-2017-217612, it is conceivable that a beam portion extending in a direction intersecting with a direction in which the liquid flows from an inlet to a discharge port inside the common liquid chamber is provided in a flow path member forming the downstream chamber. In a case where the liquid ejecting head disclosed in JP-A-2017-217612 has the beam portion, when the filling process disclosed in JP-A-2021-187003 is performed, in some cases, air bubbles may stay between the filter and the beam portion due to the circulation operation.

SUMMARY

(6) According to a preferred aspect of the present disclosure, there is provided a liquid ejecting apparatus including a plurality of nozzles that eject a liquid in an ejection direction, a common liquid chamber that communicates with the plurality of nozzles and extends in a first direction orthogonal to the ejection direction, a filter that partitions the common liquid chamber into an upstream chamber and a downstream chamber, an inlet for introducing the liquid into the upstream chamber, an outlet for causing the liquid to flow out from the upstream chamber, a liquid storage section configured to store the liquid, a supply flow path that causes the inlet to communicate with the liquid storage section, and a recovery flow path that causes the outlet to communicate with the liquid storage section. A beam portion that couples a pair of inner walls for defining the downstream chamber is provided inside the downstream chamber. The pair of inner walls are separated in a direction intersecting with the first direction when viewed in the ejection direction. A pressurization discharge operation for discharging the liquid from the plurality of nozzles by pressurizing the supply flow path and a first circulation operation for circulating the liquid in a circulation path including the liquid storage section, the supply flow path, the common liquid chamber, and the recovery flow path, in order of the liquid storage section, the supply flow path, the common liquid chamber, the recovery flow path, and the liquid storage section are performed. In a filling process of filling the circulation path with the liquid, after the first circulation operation is performed, a predetermined operation for moving the liquid inside the downstream chamber in a direction different from a direction in which the liquid inside the downstream chamber is moved by the first circulation operation is performed, and after the predetermined operation is performed, the pressurization discharge operation is performed.

(7) According to another preferred aspect of the present disclosure, there is provided a filling method for a liquid ejecting apparatus including a plurality of nozzles that eject a liquid in an ejection direction, a common liquid chamber that communicates with the plurality of nozzles and extends in a first direction orthogonal to the ejection direction, a filter that partitions the common liquid chamber into an upstream chamber and a downstream chamber, an inlet for introducing the liquid into the upstream chamber, an outlet for causing the liquid to flow out from the upstream chamber, a liquid storage section configured to store the liquid, a supply flow path that causes the inlet to communicate with the liquid storage section, and a recovery flow path that causes the outlet to communicate with the liquid storage section. A beam portion that couples a pair of inner walls

for defining the downstream chamber is provided inside the downstream chamber, the pair of inner walls are separated in a direction intersecting with the first direction when viewed in the ejection direction, a pressurization discharge operation for discharging the liquid from the plurality of nozzles by pressurizing the supply flow path and a first circulation operation for circulating the liquid in a circulation path including the liquid storage section, the supply flow path, the common liquid chamber, and the recovery flow path, in order of the liquid storage section, the supply flow path, the common liquid chamber, the recovery flow path, and the liquid storage section are performed. The filling method includes performing a filling process of filling the circulation path with the liquid, in which after the first circulation operation is performed, a predetermined operation for moving the liquid inside the downstream chamber in a direction different from a direction in which the liquid inside the downstream chamber is moved by the first circulation operation is performed, and after the predetermined operation is performed, the pressurization discharge operation is performed.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a schematic view illustrating an example of a liquid ejecting apparatus according to a first embodiment.
- (2) FIG. 2 is a view for describing a circulation mechanism and an on-off valve.
- (3) FIG. 3 is a perspective view of a liquid ejecting head and a support body according to the first embodiment.
- (4) FIG. 4 is an exploded perspective view of the liquid ejecting head according to the first embodiment.
- (5) FIG. 5 is an exploded perspective view of a head chip.
- (6) FIG. 6 is a cross-sectional view taken along line VI-VI in FIG. 5.
- (7) FIG. 7 is a cross-sectional view taken along line VII-VII in FIG. 5.
- (8) FIG. 8 is a view illustrating a flow of an ink inside a common liquid chamber while a first circulation operation is performed in a state where a circulation path is not filled with the ink.
- (9) FIG. 9 is a view illustrating a flow of the ink inside the common liquid chamber while a pressurization discharge operation is performed after the first circulation operation.
- (10) FIG. 10 is a view illustrating a flowchart illustrating a filling process according to the first embodiment.
- (11) FIG. 11 is a view illustrating a flow of the ink inside the common liquid chamber while Step S8 is performed.
- (12) FIG. 12 is a view illustrating a flow of the ink inside the common liquid chamber while Step S10 is performed.
- (13) FIG. 13 is a view illustrating a flowchart illustrating a filling process according to a second embodiment.
- (14) FIG. 14 is a view illustrating a flow of the ink inside the common liquid chamber while Step S8-A is performed.
- (15) FIG. 15 is a view illustrating a flow of the ink inside the common liquid chamber while Step S10 is performed.
- (16) FIG. 16 is a view for describing a circulation mechanism and an on-off valve according to a third embodiment.
- (17) FIG. 17 is a view illustrating a flowchart illustrating a filling process according to the third embodiment.
- (18) FIG. 18 is a view illustrating a flow of the ink inside the common liquid chamber while Step S12 is performed.

- (19) FIG. **19** is a view illustrating a flow of the ink inside the common liquid chamber while a preliminary ejection operation is performed in a liquid ejecting apparatus according to a first modification example.
- (20) FIG. **20** is a view illustrating a flow of the ink inside the common liquid chamber while a pressurization discharge operation is performed in a liquid ejecting apparatus according to a second modification example.
- (21) FIG. **21** is a view for describing a liquid ejecting apparatus according to a third modification example.
- (22) FIG. **22** is a view for describing a liquid ejecting apparatus according to a fourth modification example.
- (23) FIG. **23** is a cross-sectional view taken along line XXIII-XXIII in FIG. **22**.
- (24) FIG. **24** is a view for describing a liquid ejecting apparatus according to a fifth modification example.
- (25) FIG. **25** is a view for describing an aspect in which the liquid ejecting apparatus performs the filling process according to the second embodiment.
- (26) FIG. **26** is a view for describing a liquid ejecting apparatus according to a sixth modification example.

DESCRIPTION OF EMBODIMENTS

1. First Embodiment

(27) Hereinafter, an embodiment for carrying out the present disclosure will be described with reference to the drawings. However, in each drawing, a dimension and a scale of each portion are appropriately different from actual ones. In addition, although the embodiment described below is a preferred specific example of the present disclosure, and thus, various technically preferable limitations are imposed. However, the scope of the present disclosure is not limited to these forms unless there is a description to such an effect that the present disclosure is particularly limited in the following description.

(28) For the sake of convenience, the following description will be made by appropriately using an X-axis, a Y-axis, and a Z-axis which intersect with each other. In addition, in the following description, one direction along the X-axis is an X1-direction, and a direction opposite to the X1-direction is an X2-direction. Similarly, mutually opposite directions along the Y-axis are a Y1-direction and a Y2-direction. In addition, mutually opposite directions along the Z-axis are a Z1-direction and a Z2-direction. In addition, viewing in a Z-axis direction may be simply referred to as a “plan view” in some cases. The Z2-direction is an example of an “ejection direction”. The Y1-direction or the Y2-direction is an example of a “first direction”. The X1-direction or the X2-direction is an example of a “third direction”.

(29) Here, typically, the Z-axis is a vertical axis, and in a first embodiment, the Z2-direction coincides with a gravity direction GV. In addition, the X-axis, the Y-axis, and the Z-axis are orthogonal to each other.

1-1. Schematic Configuration of Liquid Ejecting Apparatus

(30) FIG. **1** is a schematic view illustrating an example of a liquid ejecting apparatus **100** according to the first embodiment. The liquid ejecting apparatus **100** is an ink jet printing apparatus that ejects an ink which is an example of a “liquid” onto a medium PP as a droplet. For example, the liquid ejecting apparatus **100** has a substantially box shape, and is mounted on a mounting surface orthogonal to the gravity direction GV. The medium PP is typically a printing paper. The medium PP is not limited to the printing paper, and for example, may be a printing target formed of any material such as a resin film or a fabric.

(31) As illustrated in FIG. **1**, the liquid ejecting apparatus **100** has a main tank **10**, a pump **12**, a circulation mechanism **15**, an on-off valve **16**, a maintenance mechanism **18**, a control module **20**, a transport mechanism **30**, a moving mechanism **40**, and a liquid ejecting head **50**.

(32) The main tank **10** is a container for storing the ink. For example, specific aspects of the main

tank **10** include a cartridge attachable to and detachable from the liquid ejecting apparatus **100**, a bag-shaped ink pack formed of a flexible film, and a container such as an ink-refillable ink tank.

(33) Although not illustrated, the main tank **10** has a plurality of containers that store mutually different types of the ink. Although the ink stored in the plurality of containers are not particularly limited, for example, the ink includes a cyan ink, a magenta ink, a yellow ink, a black ink, a clear ink, a white ink, and a treatment liquid, and combinations of two or more types of these ink may be used. Each of the ink is not particularly limited in composition. For example, the ink may be a water-based ink in which a coloring material such as a dye and a pigment is dissolved in a water-based solvent, a solvent-based ink in which the coloring material is dissolved in an organic solvent, or an ultraviolet-curable ink.

(34) As an example, the present embodiment adopts a configuration in which four mutually different types of the ink are used. For example, the four types of the ink are mutually different color ink such as the cyan ink, the magenta ink, the yellow ink, and the black ink.

(35) The control module **20** controls an operation of each element of the liquid ejecting apparatus **100**. For example, the control module **20** includes a processing circuit such as a CPU and an FPGA, and a memory circuit such as a semiconductor memory. The CPU is an abbreviation for central processing unit. The FPGA is an abbreviation for field programmable gate array. The control module **20** outputs a drive signal Com and a control signal SI toward the liquid ejecting head **50**. The drive signal Com is a signal including a drive pulse for driving a drive element of the liquid ejecting head **50**. The control signal SI is a signal for designating whether or not to supply the drive signal Com to the drive element.

(36) The transport mechanism **30** transports the medium PP in a transport direction DM which is the Y1-direction, under the control of the control module **20**. The moving mechanism **40** causes the liquid ejecting head **50** to reciprocate in the X1-direction and the X2-direction under the control of the control module **20**. In an example illustrated in FIG. 1, the moving mechanism **40** has a substantially box-shaped support body **41** called a carriage that accommodates the liquid ejecting head **50**, and a transport belt **42** to which the support body **41** is fixed. In addition to the liquid ejecting head **50**, the above-described main tank **10** may be mounted on the support body **41**.

(37) The liquid ejecting head **50** has a plurality of head chips **54** as will be described later and, under the control of the control module **20**, the ink supplied from the main tank **10** is ejected from each of a plurality of nozzles N of each head chip **54** toward the medium PP in the Z2-direction which is the ejection direction. In the liquid ejecting apparatus **100**, the ink is ejected in parallel when the medium PP is transported by the transport mechanism **30** and the liquid ejecting head **50** is caused to reciprocate by the moving mechanism **40**, based on image data Img supplied from a host computer such as a personal computer and a digital camera. In this manner, a printing operation for forming an image indicated by the image data Img on a surface of the medium PP is performed.

(38) The maintenance mechanism **18** is a mechanism for performing a maintenance operation for maintaining the liquid ejecting head **50**. The maintenance mechanism **18** is provided in a region that does not overlap the medium PP when viewed in the direction along the Z-axis. The maintenance mechanism **18** includes a cap **181** and a liquid receiving section **182**. The cap **181** is a substantially box-shaped structure that opens in the Z2-direction. The cap **181** seals the plurality of nozzles N by covering an ejection surface on which the plurality of nozzles N are formed. The liquid receiving section **182** is a substantially box-shaped tank that opens in the Z2-direction. The liquid receiving section **182** is used to receive the ink ejected from the nozzle N. The liquid receiving section **182** may be configured in a substantially box shape as in the cap **181**.

(39) For example, the maintenance operation includes a flushing operation. The flushing operation is an operation for forcibly ejecting the ink that does not directly contribute to image formation from the plurality of nozzles N by driving a piezoelectric element **54f** (to be described later). The ink that does not directly contribute to the image formation means that the ink does not form the

image itself formed on the surface of the medium PP by the printing operation. In the flushing operation, the ink is ejected to the liquid receiving section **182**.

(40) The main tank **10** is coupled to the liquid ejecting head **50** via the circulation mechanism **15**. The circulation mechanism **15** is a mechanism that supplies the ink to each of the plurality of liquid ejecting heads **50** under the control of the control module **20**, and recovers the ink discharged from each of the plurality of liquid ejecting heads **50** to resupply the ink to the liquid ejecting head **50**. The circulation mechanism **15** and the on-off valve **16** are provided for each of the mutually different types of the ink. The circulation mechanism **15** and the on-off valve **16** will be described with reference to FIG. 2.

1-2. Circulation Mechanism **15** and On-Off Valve **16**

(41) FIG. 2 is a view for describing the circulation mechanism **15** and the on-off valve **16**. As illustrated in FIG. 2, the circulation mechanism **15** includes a sub tank **151** and a pump **159**. In FIG. 2, any one type of the ink in the plurality of types of the ink will be described. FIG. 2 illustrates only two head chips **54** to which one type of the ink is supplied in the plurality of head chips **54** so that the drawing is not complicated. Furthermore, FIG. 2 illustrates the inside of only one head chip **54** in the two head chips **54** so that the drawing is not complicated.

(42) The sub tank **151** is coupled to a supply flow path SF1 and a recovery flow path CF1, and stores the ink to be supplied to the plurality of liquid ejecting heads **50**. The sub tank **151** stores the ink to be supplied to the liquid ejecting head **50**, the ink recovered from the liquid ejecting head **50**, and the ink supplemented from the main tank **10**. The sub tank **151** is an example of a “liquid storage section”.

(43) The supply flow path SF1 causes an inlet Pin for introducing the ink into the head chip **54** to communicate with the sub tank **151**. The supply flow path SF1 has an in-device supply flow path SJ1 and an in-head supply flow path SH1. The in-device supply flow path SJ1 is a flow path provided outside the liquid ejecting head **50**, is coupled to the sub tank **151**, and communicates with a head inlet Qin for introducing the ink into the liquid ejecting head **50**. The in-head supply flow path SH1 is a flow path provided inside the liquid ejecting head **50**, and supplies the ink to each of the plurality of head chips **54**. The in-head supply flow path SH1 has a mainstream portion coupled to the in-device supply flow path SJ1 and a plurality of branch portions branched from the mainstream portion for each of the plurality of head chips **54**. In the present embodiment, an example in which the main tank **10** is provided for each of four types of the ink and one type of the ink is supplied to two head chips **54** as illustrated in FIG. 2 will be described. Furthermore, it is assumed that two types of the ink can be supplied to one head chip **54**. However, the liquid ejecting head **50** may supply any one type of the ink to three or more head chips **54** or may supply any one type of the ink to one head chip **54**.

(44) The recovery flow path CF1 causes an outlet Pout for causing the ink to flow out from the head chip **54** to communicate with the sub tank **151**. The recovery flow path CF1 has an in-device recovery flow path CJ1 and an in-head recovery flow path CH1. The in-device recovery flow path CJ1 is a flow path provided outside the liquid ejecting head **50**, is coupled to the sub tank **151**, and communicates with a head outlet Qout for causing the ink to flow out from the liquid ejecting head **50**. The in-head recovery flow path CH1 is a flow path provided inside the liquid ejecting head **50**, and recovers the ink from each of the plurality of head chips **54**. The in-head recovery flow path CH1 has a mainstream portion coupled to the in-device recovery flow path CJ1 and a plurality of branch portions for coupling the mainstream portion and each of the plurality of head chips **54**.

(45) The on-off valve **16** is provided in an intermediate portion of the in-device recovery flow path CJ1. The on-off valve **16** can close and open the in-device recovery flow path CJ1 under the control of the control module **20**. In the following description, closing the in-device recovery flow path CJ1 by the on-off valve **16** may be referred to as “closing the on-off valve **16**”, and opening the in-device recovery flow path CJ1 by the on-off valve **16** may be referred to as “opening the on-off valve **16**”. A device other than the control module **20** may control the on-off valve **16**. The on-

off valve **16** may be any valve as long as the valve can be controlled from a device such as the control module **20**, and for example, the valve may be a diaphragm valve, an electromagnetic valve, or an electric valve.

(46) In the present embodiment, the on-off valve **16** is provided in the intermediate portion of the in-device recovery flow path **CJ1**. However, the on-off valve **16** may be provided in the intermediate portion of the mainstream portion of the in-head recovery flow path **CH1**.

Alternatively, a plurality of the on-off valves **16** may be provided in the intermediate portion of each of the plurality of branch portions of the in-head recovery flow path **CH1**.

(47) The pump **159** is provided in the intermediate portion of the in-device supply flow path **SJ1**. The pump **159** causes a first ink of the sub tank **151** to flow to the liquid ejecting head **50** under the control of the control module **20**.

(48) The head chip **54** is provided with a common liquid chamber **R** that communicates with the plurality of nozzles **N**. The common liquid chamber **R** is partitioned into an upstream chamber **UR** and a downstream chamber **DR** by a filter **54o**. As illustrated in FIG. **2**, the inlet **Pin** and the outlet **Pout** are provided in the upstream chamber **UR**. The plurality of nozzles **N** communicate with the downstream chamber **DR**. Internal elements of the head chip **54** will be described later with reference to FIGS. **5**, **6**, and **7**.

(49) As described above, the liquid ejecting apparatus **100** has a circulation path **KJ** having the sub tank **151**, the supply flow path **SF1**, the common liquid chamber **R**, and the recovery flow path **CF1**. Under an instruction of the control module **20**, the liquid ejecting apparatus **100** can perform a first circulation operation for circulating the ink in the circulation path **KJ** in order of the sub tank **151**, the supply flow path **SF1**, the common liquid chamber **R**, the recovery flow path **CF1**, and the sub tank **151**.

(50) In addition, when the ink is ejected from the nozzle **N**, the amount of the ink in the sub tank **151** is reduced. Therefore, the pump **12** appropriately supplements the ink of the sub tank **151** by supplying the ink from the main tank **10** to the sub tank **151** under the control of the control module **20**. For example, at a timing for supplementing the ink of the sub tank **151**, the ink is supplemented when a height of the ink of the sub tank **151** is lower than a predetermined height.

1-3. Attachment State of Liquid Ejecting Head **50**

(51) FIG. **3** is a perspective view of the liquid ejecting head **50** and the support body **41** according to the first embodiment. As illustrated in FIG. **3**, the liquid ejecting head **50** is supported by the support body **41**. The support body **41** is a member that supports the liquid ejecting head **50** and, as described above, the support body **41** is a substantially box-shaped carriage in the present embodiment.

(52) Here, the support body **41** is provided with an opening **41a** and a plurality of screw holes **41b**. In the present embodiment, the support body **41** has a substantially box shape with a plate-shaped bottom portion. For example, the bottom portion is provided with the opening **41a** and the plurality of screw holes **41b**. The liquid ejecting head **50** is fixed to the support body **41** by screwing using the plurality of screw holes **41b** in a state of being inserted into the opening **41a**. As described above, the liquid ejecting head **50** is attached to the support body **41**.

(53) In an example illustrated in FIG. **3**, one liquid ejecting head **50** is attached to the support body **41**. Two or more liquid ejecting heads **50** may be attached to the support body **41**. In this case, for example, the support body **41** is appropriately provided with the openings **41a** corresponding to the numbers or shapes of the liquid ejecting heads **50**.

1-4. Configuration of Liquid Ejecting Head

(54) FIG. **4** is an exploded perspective view of the liquid ejecting head **50** according to the first embodiment. As illustrated in FIG. **4**, the liquid ejecting head **50** has a flow path structure **51**, a substrate unit **52**, a holder **53**, four head chips **54_1** to **54_4**, a fixing plate **55**, and a cover **58**. These are disposed to be aligned in order of the cover **58**, the substrate unit **52**, the flow path structure **51**, the holder **53**, the four head chips **54**, and the fixing plate **55** in the **Z2**-direction.

Hereinafter, each portion of the liquid ejecting head **50** will be described.

(55) The flow path structure **51** is a structure internally provided with a flow path for supplying the ink stored in the above-described main tank **10** to the four head chips **54**. The flow path structure **51** has a flow path member **51a** and eight coupling pipes **51b**.

(56) Although not illustrated, the flow path structure **51** is provided with four in-head supply flow paths **SH1** provided for each of four types of the ink and four in-head recovery flow paths **CH1** provided for each of four types of the ink. Each of the four in-head supply flow paths **SH1** has one head inlet **Qin** that receives the ink from the in-device supply flow path **SJ1** and two discharge ports that discharge the ink toward the inlet **Pin** of the head chip **54**. Each of the four in-head recovery flow paths **CH1** has two inlets that receive the ink from the outlet **Pout** of the head chip **54** and one head outlet **Qout** that discharges the ink to the in-device recovery flow path **CJ1**. Each of the plurality of coupling pipes **51b** is either the head inlet **Qin** or the head outlet **Qout**, and is provided on a surface of the flow path member **51a** facing the **Z1**-direction. In contrast, each of the discharge port of each in-head supply flow path **SH1** and the inlet of each in-head recovery flow path **CH1** is provided on a surface of the flow path member **51a** facing the **Z2**-direction.

(57) In addition, a plurality of wiring holes **51c** are provided in the flow path member **51a**. Each of the plurality of wiring holes **51c** is a hole through which a wiring substrate **54i** (to be described later) of the head chip **54** passes toward the substrate unit **52**. A side surface of the flow path member **51a** is provided with cutout portions at two locations in a circumferential direction. In addition, the flow path member **51a** is provided with a hole (not illustrated), and is fixed to the holder **53** by screwing using the hole.

(58) Although not illustrated, the flow path member **51a** has a configuration of a stacked body in which a plurality of substrates are stacked in a direction along the **Z**-axis.

(59) Grooves and holes for forming the above-described in-head supply flow path **SH1** and in-head recovery flow path **CH1** are appropriately provided in each of the plurality of substrates. For example, these are joined to each other by using an adhesive, welding, or screwing.

(60) Each of the eight coupling pipes **51b** is a pipe body protruding from the surface of the flow path member **51a** facing the **Z1**-direction. The eight coupling pipes **51b** correspond to the above-described four in-head supply flow paths **SH1** and the four in-head recovery flow paths **CH1**. The above-described eight coupling pipes **51b** are used by being coupled to the above-described sub tank **151** via a tube forming the in-device supply flow path **SJ1** and the in-device recovery flow path **CJ1**.

(61) The substrate unit **52** is an assembly having a mounting component for electrically coupling the liquid ejecting head **50** to the control module **20**. The substrate unit **52** has a circuit substrate **52a**, a connector **52b**, and a support plate **52c**.

(62) The circuit substrate **52a** is a printed wiring substrate such as a rigid wiring substrate having wiring for electrically coupling each head chip **54** and the connector **52b**. The circuit substrate **52a** is disposed on the flow path structure **51** via the support plate **52c**, and the connector **52b** is installed on the surface of the circuit substrate **52a** facing the **Z1**-direction.

(63) The connector **52b** is a coupling component for electrically coupling the liquid ejecting head **50** and the control module **20**. The support plate **52c** is a plate-shaped member for attaching the circuit substrate **52a** to the flow path structure **51**. The circuit substrate **52a** is mounted on one surface of the support plate **52c**, and the circuit substrate **52a** is fixed to the support plate **52c** by screwing.

(64) The holder **53** is a structure that accommodates and supports the four head chips **54**. The holder **53** is a structure that accommodates and supports the four head chips **54**. The holder **53** has a substantially tray shape, and has a recess **53a**, a plurality of wiring holes **53c**, a plurality of recesses **53d**, a plurality of holes **53e**, a plurality of screw holes **53i**, and a plurality of screw holes **53k**. The recess **53a** is open in the **Z1**-direction, and is a space in which the above-described flow path member **51a** is disposed. Each of the plurality of wiring holes **53c** is a hole through which the

wiring substrate **54i** of the head chip **54** passes toward the substrate unit **52**. Each of the plurality of recesses **53d** is open in the Z2-direction, and is a space in which the head chip **54** is disposed. The plurality of holes **53e** are through holes for coupling each of the plurality of inlets Pin and outlet Pout which are provided in the plurality of head chips **54** (to be described later) and each of the discharge port of the in-head supply flow path SH1 and the inlet of the in-head recovery flow path CH1 which are formed in the flow path member **51a**. The plurality of screw holes **53i** are screw holes for screwing the holder **53** to the support body **41**. The plurality of screw holes **53k** are screw holes for screwing the cover **58** to the holder **53**.

(65) Each head chip **54** ejects the ink. Each head chip **54** has the plurality of nozzles N ejecting a first ink and the plurality of nozzles N ejecting a second ink different in type from the first ink. Here, the first ink and the second ink are two of the above-described four types of the ink. For example, each of the head chip **54_1** and the head chip **54_2** uses two of the four types of the ink as the first ink and the second ink. Each of the head chip **54_3** and the head chip **54_4** uses the other remaining two of the four types of the ink. Each head chip **54** is provided with the wiring substrate **54i**. FIG. 4 illustrates a configuration of each head chip **54** in a simplified manner. The configuration of the head chip **54** will be described in detail with reference to FIG. 5 (to be described later).

(66) The fixing plate **55** is a plate-shaped member to which the four head chips **54** and the holder **53** are fixed. Specifically, the fixing plate **55** is disposed in a state where the four head chips **54** are pinched between the holder **53** and the fixing plate **55**, and each head chip **54** and the holder **53** are fixed by using an adhesive. The fixing plate **55** is provided with a plurality of opening portions **55a** exposing nozzle surfaces FN of the four head chips **54**. In an example illustrated in FIG. 4, the plurality of opening portions **55a** are individually provided for each head chip **54**. For example, the fixing plate **55** is made of a metal material such as stainless steel, titanium, and magnesium alloy.

(67) The cover **58** is a box-shaped member that accommodates the substrate unit **52**.

(68) The cover **58** is provided with eight through holes **58a** and an opening portion **58b**. The eight through holes **58a** correspond to the eight coupling pipes **51b** of the flow path structure **51**, and the corresponding coupling pipes **51b** are inserted into the respective through holes **58a**. The above-described connector **52b** passes through the opening portion **58b** from the inside to the outside of the cover **58**.

1-5. Configuration of Head Chip

(69) FIG. 5 is an exploded perspective view of the head chip **54**. FIG. 6 is a cross-sectional view taken along line VI-VI in FIG. 5. FIG. 7 is a cross-sectional view taken along line VII-VII in FIG. 5. However, in FIG. 7, the wiring substrate **54i** is omitted in illustration so that the drawing is not complicated. As illustrated in FIGS. 5 and 6, the head chip **54** has the plurality of nozzles N arranged in the direction along the Y-axis. The plurality of nozzles N are divided into a first nozzle row L1 and a second nozzle row L2 aligned apart from each other in the direction along the X-axis. Each of the first nozzle row L1 and the second nozzle row L2 is a set of the plurality of nozzles N linearly arranged in the direction along the Y-axis. Hereinafter, the first nozzle row L1 and the second nozzle row L2 may be collectively referred to as a “nozzle row Ln”. The first nozzle row L1 and the second nozzle row L2 are examples of a “nozzle row”.

(70) The head chips **54** are configured to be substantially symmetrical to each other in the direction along the X-axis. However, positions of the plurality of nozzles N of the first nozzle row L1 and the plurality of nozzles N of the second nozzle row L2 in the direction along the Y-axis may coincide with or may be different from each other. As an example, FIG. 6 illustrates a configuration in which the positions of the plurality of nozzles N of the first nozzle row L1 and the plurality of nozzles N of the second nozzle row L2 coincide with each other in the direction along the Y-axis.

(71) As illustrated in FIGS. 5 and 6, the head chip **54** has a flow path forming member **54a**, a pressure chamber substrate **54b**, a nozzle plate **54c**, a vibration absorber **54d**, a diaphragm **54e**, a plurality of piezoelectric elements **54f**, a protective substrate **54g**, the wiring substrate **54i**, a drive

circuit **54j**, a frame body **54k**, a case **54n**, and a filter **54o**. However, in FIG. 5, the pressure chamber substrate **54b**, the diaphragm **54e**, the plurality of piezoelectric elements **54f**, the vibration absorber **54d**, the wiring substrate **54i**, the drive circuit **54j**, and the frame body **54k** are omitted in illustration so that the drawing is not complicated.

(72) The flow path forming member **54a** and the pressure chamber substrate **54b** are stacked in the Z1-direction in this order to form a flow path for supplying the ink to the plurality of nozzles N. The filter **54o**, the pressure chamber substrate **54b**, the diaphragm **54e**, the plurality of piezoelectric elements **54f**, the protective substrate **54g**, the case **54n**, the wiring substrate **54i**, and the drive circuit **54j** are installed in a region located in the Z1-direction with respect to the flow path forming member **54a**. On the other hand, the nozzle plate **54c**, the vibration absorber **54d**, and the frame body **54k** are installed in a region located in the Z2-direction with respect to the flow path forming member **54a**. Each element of the head chip **54** is schematically a plate-shaped member elongated in the Y-direction, and the elements are joined to each other by using an adhesive, for example. Hereinafter, each element of the head chip **54** will be described in order.

(73) The nozzle plate **54c** is a plate-shaped member provided with the plurality of nozzles N of each of the first nozzle row L1 and the plurality of nozzles N of the second nozzle row L2. Each of the plurality of nozzles N is a through hole through which the ink passes. Here, a surface of the nozzle plate **54c** facing the Z2-direction is the nozzle surface FN. That is, a normal direction of the nozzle surface FN is a direction of a normal vector of the nozzle surface FN, and is the Z2-direction which is the ejection direction.

(74) The flow path forming member **54a** is provided with a downstream chamber DR, a plurality of coupling flow paths Ra, and a plurality of communication flow paths Na (to be described later), for each of the first nozzle row L1 and the second nozzle row L2. Here, the downstream chamber DR communicating with the plurality of nozzles N of the first nozzle row L1 will be referred to as a downstream chamber DR[L1]. The downstream chamber DR communicating with the plurality of nozzles N of the second nozzle row L2 will be referred to as a downstream chamber DR[L2].

(75) The downstream chamber DR[L1] includes an opening DR1[L1] penetrating the flow path forming member **54a** in the Z-axis direction, an opening DR2[L1] penetrating the flow path forming member **54a** in the Z-axis direction, and a coupling flow path Xa[L1]. The opening DR1[L1] and the opening DR2[L1] are divided by a beam portion BR[L1] extending in the X-axis direction. Each of the opening DR1[L1] and the opening DR2[L1] extends in the Y-axis direction. Similarly, the downstream chamber DR[L2] includes an opening DR1[L2] penetrating the flow path forming member **54a** in the Z-axis direction, an opening DR2[L2] penetrating the flow path forming member **54a** in the Z-axis direction, and a coupling flow path Xa[L2]. The opening DR1[L2] and the opening DR2[L2] are divided by a beam portion BR[L2] extending in the X-axis direction. Each of the opening DR1[L2] and the opening DR2[L2] extends in the Y-axis direction.

(76) Here, when the openings DR1[L1] and DR1[L2] are not particularly distinguished, the openings will be simply referred to as an opening DR1. In addition, when the coupling flow path Xa[L1] and the coupling flow path Xa[L2] are not particularly distinguished, the coupling flow paths will be simply referred to as a coupling flow path Xa. Furthermore, when the openings DR2[L1] and DR2[L2] are not particularly distinguished, the openings will be simply referred to as an opening DR2. When the beam portion BR[L1] and the beam portion BR[L2] are not particularly distinguished, the beam portions will be simply referred to as a beam portion BR.

(77) The beam portion BR extends along the X-axis, and couples inner walls wDR of the downstream chamber DR. The inner walls wDR are separated in the direction along the X-axis. However, an extending direction of the beam portion BR may be a direction intersecting with the Y-axis, and is not limited to the X-axis. The beam portion BR is a portion of the flow path forming member **54a**. The beam portion BR is provided at a position substantially at the center in the direction along the Y-axis. Therefore, in FIG. 6, when a cross section taken along line VI-VI is viewed in the Y2-direction, the beam portion BR is originally visible. However, the opening DR1 is

not illustrated to easily understand the opening DR1. Although one beam portion BR is provided corresponding to each of the first nozzle row L1 and the second nozzle row L2 in an example in FIG. 5, a plurality of the beam portions BR may be provided corresponding to the first nozzle row L1 and the second nozzle row L2. It can be said that the direction along the X-axis is a direction intersecting with the direction along the Y-axis. The direction along the X-axis is an example of “a direction intersecting with the first direction”.

(78) The coupling flow path Xa communicates with the plurality of coupling flow paths Ra in one end in the X-axis direction, and communicates with both the opening DR1 and the opening DR2 in the other end in the X-axis direction. That is, the ink passing through the openings DR1 and DR2 flows to the plurality of coupling flow paths Ra via the coupling flow path Xa. Each of the coupling flow path Ra and the communication flow path Na is a through hole formed for each nozzle N.

(79) As illustrated in FIG. 6, a common liquid chamber R communicating with the plurality of nozzles N is provided for each of the first nozzle row L1 and the second nozzle row L2. The common liquid chamber R extends in a direction along the Y-axis orthogonal to the Z2-direction which is the ejection direction. In the following description, the common liquid chamber R communicating with the plurality of nozzles N of the first nozzle row L1 may be referred to as a common liquid chamber R[L1]. The common liquid chamber R communicating with the plurality of nozzles N of the second nozzle row L2 may be referred to as a common liquid chamber R[L2]. The common liquid chamber R stores the ink to be supplied to a plurality of pressure chambers CB. The common liquid chamber R is defined by a vibration absorber 54d, the flow path forming member 54a, the filter 54o, and the case 54n. The filter 54o partitions the common liquid chamber R into an upstream chamber UR and the downstream chamber DR. The flow path forming member 54a defines a portion of the downstream chamber DR.

(80) The pressure chamber substrate 54b is a plate-shaped member provided with the plurality of pressure chambers CB for each of the first nozzle row L1 and the second nozzle row L2. The plurality of pressure chambers CB are arranged in the direction along the Y-axis. Each pressure chamber CB is an elongated space formed for each nozzle N and extending in the direction along the X-axis in a plan view. As in the above-described nozzle plate 54c, each of the flow path forming member 54a and the pressure chamber substrate 54b is manufactured by processing a silicon single crystal substrate by using a semiconductor manufacturing technique, for example. However, other known methods and materials may be appropriately used for manufacturing each of the flow path forming member 54a and the pressure chamber substrate 54b.

(81) In addition, it is preferable that the flow path forming member 54a and the beam portion BR are formed of an integral silicon single crystal substrate. However, after each of the flow path forming member 54a and the beam portion BR is separately manufactured, the beam portion BR may be welded to the flow path forming member 54a.

(82) The pressure chamber CB is a space located between the flow path forming member 54a and the diaphragm 54e. The plurality of pressure chambers CB are arranged in the direction along the Y-axis for each of the first nozzle row L1 and the second nozzle row L2. In addition, the pressure chamber CB communicates with each of the communication flow path Na and the coupling flow path Ra. Accordingly, the pressure chamber CB communicates with the nozzle N via the communication flow path Na, and communicates with the downstream chamber DR via the coupling flow path Ra.

(83) The diaphragm 54e is disposed on a surface of the pressure chamber substrate 54b facing the Z1-direction. The diaphragm 54e is a plate-shaped member capable of vibrating elastically. For example, the diaphragm 54e has a first layer and a second layer, and the first layer and the second layer are stacked in the Z1-direction in this order. For example, the first layer is an elastic film made of silicon oxide. For example, the elastic film is formed by thermally oxidizing one surface of a silicon single crystal substrate. For example, the second layer is an insulating film made of

zirconium oxide. For example, the insulating film is formed by forming a zirconium layer by sputtering and thermally oxidizing the layer. The diaphragm **54e** is not limited to a configuration resulting from the stacking of the first layer and the second layer described above, and for example, may be configured to have a single layer, or may be configured to have three or more layers.

(84) The plurality of piezoelectric elements **54f** mutually corresponding to the nozzles **N** are disposed as drive elements for each of the first nozzle row **L1** and the second nozzle row **L2** on the surface of the diaphragm **54e** facing the **Z1**-direction. Each piezoelectric element **54f** is a passive element deformed by the supply of the drive signal **Com**. Each piezoelectric element **54f** has an elongated shape extending in the direction along the **X**-axis in a plan view. The plurality of piezoelectric elements **54f** are arranged in the direction along the **Y**-axis to correspond to the plurality of pressure chambers **CB**. The piezoelectric element **54f** overlaps the pressure chamber **CB** in a plan view.

(85) Although not illustrated, each piezoelectric element **54f** has a first electrode, a piezoelectric layer, and a second electrode, and these are stacked in the **Z1**-direction in this order. One of the first electrode and the second electrode is an individual electrode disposed apart from each other for each piezoelectric element **54f**, and the drive signal **Com** is applied to the one electrode. The other of the first electrode and the second electrode is a strip-shaped common electrode extending in the direction along the **Y**-axis to be continuous over the plurality of piezoelectric elements **54f**, and a predetermined reference potential is supplied to the other electrode. For example, metal materials of these electrodes include metal materials such as platinum, aluminum, nickel, gold, and copper. Among these materials, one can be used alone, or two or more can be used in combination in an aspect of alloy or stacking. The piezoelectric layer is made of a piezoelectric material such as lead zirconate titanate, and for example, has a strip shape extending in the direction along the **Y**-axis to be continuous over the plurality of piezoelectric elements **54f**. However, the piezoelectric layer may be integrated over the plurality of piezoelectric elements **54f**. In this case, on the piezoelectric layer, a through hole penetrating the piezoelectric layer and extending in the direction along the **X**-axis is provided in a region corresponding to a gap between the pressure chambers **CB** adjacent to each other in a plan view. When the diaphragm **54e** vibrates in conjunction with the deformation of the piezoelectric element **54f**, a pressure inside the pressure chamber **CB** fluctuates to eject the ink from the nozzle **N**. The piezoelectric element **54f** is an example of a “drive element”. Alternatively, as the drive element, a heating element for heating the ink inside the pressure chamber **CB** may be used instead of the piezoelectric element **54f**.

(86) The protective substrate **54g** is a plate-shaped member installed on the surface of the diaphragm **54e** facing the **Z1**-direction, protects the plurality of piezoelectric elements **54f**, and reinforces mechanical strength of the diaphragm **54e**. As illustrated in FIGS. 5 and 6, the protective substrate **54g** is provided with an opening **h1**. The opening **h1** is a hole through which the wiring substrate **54i** passes. In addition, on the surface of the protective substrate **54g** facing the **Z2**-direction, two recesses recessed in the **Z1**-direction are formed corresponding to each of the two first nozzle row **L1** and second nozzle row **L2**. The plurality of piezoelectric elements **54f** are accommodated between the recess of the protective substrate **54g** and the diaphragm **54e**. For example, the protective substrate **54g** is configured to have a silicon single crystal substrate.

(87) The filter **54o** is a plate-shaped or sheet-shaped member stacked on the surface of the flow path forming member **54a** facing the **Z1**-direction. The filter **54o** captures foreign matters mixed in the ink while allowing passage of the ink.

(88) The filter **54o** is provided with a plurality of filter holes **h23** through which the ink passes and an opening **h21**. The opening **h21** is a through hole through which the pressure chamber substrate **54b** passes. The plurality of filter holes **h23** are provided inside a filter hole region **FR**. In the following description, the filter hole region **FR** provided with the filter hole **h23** communicating with the downstream chamber **DR[L1]** may be referred to as a filter hole region **FR[L1]**, and the filter hole region **FR** provided with the filter hole **h23** communicating with the downstream

chamber DR[L2] may be referred to as a filter hole region FR[L2]. The filter hole h23 provided in the filter hole region FR[L1] may be referred to as a filter hole h23[L1], and the filter hole h23 provided in the filter hole region FR[L2] may be referred to as a filter hole h23[L2]. The filter hole region FR is configured to have an electroformed filter. For example, a material forming the electroformed filter is Ni—Pd alloy. Alternatively, the material forming the electroformed filter may be stainless steel.

(89) The case 54n is a member stacked on the surface of the filter 54o facing the Z1-direction. The case 54n defines the upstream chamber UR. The case 54n is provided with an opening h41, the upstream chamber UR communicating with the plurality of nozzles N of the first nozzle row L1, the upstream chamber UR communicating with the plurality of nozzles N of the second nozzle row L2, the inlet Pin provided in each of the two upstream chambers UR, and the outlet Pout provided in each of the two upstream chambers UR. The opening h41 is a hole through which the wiring substrate 54i passes. In the following description, the upstream chamber UR included in the common liquid chamber R[L1] may be referred to as an upstream chamber UR[L1], and the upstream chamber UR included in the common liquid chamber R[L2] may be referred to as an upstream chamber UR[L2]. The upstream chamber UR is formed in such a manner that the case 54n is recessed in the Z1-direction from a surface SZ2 facing the Z2-direction.

(90) The case 54n is made of a resin material such as a modified polyphenylene ether resin, a polyphenylene sulfide resin, and a polypropylene resin. Alternatively, the case 54n may be made of a metal material.

(91) The vibration absorber 54d is also called a compliance substrate, is a flexible resin film forming a wall surface of the common liquid chamber R, and absorbs pressure fluctuations of the ink inside the common liquid chamber R. The vibration absorber 54d may be a flexible thin plate made of metal. A surface of the vibration absorber 54d facing the Z1-direction is joined to the flow path forming member 54a by using an adhesive. On the other hand, the frame body 54k is joined to the surface of the vibration absorber 54d facing the Z2-direction by using an adhesive. The frame body 54k is a frame-shaped member along an outer periphery of the vibration absorber 54d, and comes into contact with the above-described fixing plate 55. Here, for example, the frame body 54k is made of a metal material such as stainless steel, aluminum, titanium, and magnesium alloy.

(92) The wiring substrate 54i is mounted on the surface of the diaphragm 54e facing the Z1-direction, and is a mounting component for electrically coupling the control module 20 and the head chip 54. For example, the wiring substrate 54i is a flexible wiring substrate such as COF, FPC, or FFC. The COF is an abbreviation for Chip On Film. The FPC is an abbreviation for Flexible Printed Circuit. The FFC is an abbreviation for Flexible Flat Cable. The drive circuit 54j for supplying a drive voltage to each piezoelectric element 54f is mounted on the wiring substrate 54i of the present embodiment. The drive circuit 54j is a circuit that switches whether or not to supply at least a portion of a waveform included in the drive signal Com as a drive pulse, based on the control signal SI.

1-6. Regarding Beam Portion BR

(93) Rigidity of the flow path forming member 54a tends to be lower than rigidity of the case 54n. Specifically, the case 54n has an outer wall in the Z1-direction. Therefore, the rigidity can be maintained to some extent. On the other hand, the flow path forming member 54a has an elongated opening extending in the direction along the Y-axis. Therefore, the rigidity decreases. As the rigidity of the case 54n decreases, there is a possibility that the flow path forming member 54a may be deformed due to pressurization in a case of adhesive hardening, for example. Therefore, in the present embodiment, the beam portion BR is provided in the flow path forming member 54a. In this manner, it is possible to prevent a decrease in the rigidity of the flow path forming member 54a.

(94) In accordance with the beam portion BR located at the center of the downstream chamber DR on the Y-axis, it is possible to further prevent a decrease in the rigidity of the flow path forming

member **54a**. Specifically, as illustrated in FIG. 7, the beam portion BR is included in a range YDR2 located at the center of a range YDR1, the range YDR2, and a range YDR3 when the downstream chamber DR is equally divided into three by a plane parallel to an XZ-plane. Furthermore, although not illustrated in FIG. 7, it is preferable that the beam portion BR is included in a range located at the center when the downstream chamber DR is equally divided into five by a plane parallel to the XZ-plane.

(95) The inlet Pin and the outlet Pout are respectively provided in both end portions of the common liquid chamber R in the direction along the Y-axis. For example, the reason is as follows. When the inlet Pin and the outlet Pout are provided at the center of the common liquid chamber R in the direction along the Y-axis, the ink stagnates in both end portions of the common liquid chamber R in the direction along the Y-axis, and there is a high possibility that air bubbles may stay. Therefore, inevitably, as understood from FIGS. 5 and 7, the beam portion BR is located between the inlet Pin and the outlet Pout when viewed in the direction along the Z-axis. More specifically, positions of the beam portion BR, the inlet Pin, and the outlet Pout will be described by using a range YR1, a range YR2, and a range YR3 when the common liquid chamber R is equally divided into three by a plane parallel to the XZ-plane. As illustrated in FIG. 7, the width of the upstream chamber UR in the direction along the Y-axis is longer than the width of the downstream chamber DR in the direction along the Y-axis, and when viewed in the direction along the Z-axis, all of the downstream chamber DR overlap the upstream chamber UR. Therefore, a range YR1, a range YR2, and a range YR3 coincide with a range when the upstream chamber UR is equally divided into three by a plane parallel to the XZ-plane. The beam portion BR is included in the range YR2 located at the center of the range YR1, the range YR2, and the range YR3. A fact that the inlet Pin and the outlet are provided in both end portions of the common liquid chamber R in the direction along the Y-axis means that the inlet Pin and the outlet Pout are included in any of the ranges located in both ends of three or more ranges, when the common liquid chamber R is equally divided into three or more by a plane parallel to the XZ-plane. The number of the equally divided common liquid chamber R by the plane parallel to the XZ-plane is not limited to three, and is preferably four or five. Therefore, it is preferable that the inlet Pin and the outlet Pout are included in any of the ranges located in both ends of the equally divided four or five ranges. When the range YR1, the range YR2, and the range YR3 are used, the inlet Pin is included in the range YR3 located closest in the Y2-direction among the range YR1, the range YR2, and the range YR3. The outlet Pout is included in the range YR1 located closest in the Y1-direction, in the range YR1, the range YR2, and the range YR3.

(96) As illustrated in FIG. 7, a surface SB1 of the beam portion BR facing the case **54n** is flush with a surface SB2 of the flow path forming member **54a** facing the case **54n**. The flush means that there is no step between two surfaces. Therefore, no gap is formed between the beam portion BR and the filter **54o** in the direction along the Z-axis. The beam portion BR supports a portion of the filter **54o**, specifically, a portion that overlaps the beam portion BR when viewed along the Z-axis.

1-7. Filling Process

(97) As a method for filling the circulation path KJ with the ink in a state where the circulation path KJ is not filled with the ink, for example, it is conceivable to adopt the following aspect. After a first circulation operation is performed, the on-off valve **16** is closed, and the supply flow path SF1 is pressurized by the pump **159**. In this manner, a pressurization discharge operation for discharging the ink from the plurality of nozzles N is performed. However, the inventors have found the followings through experiments. In an aspect in which the common liquid chamber R has the filter **54o** and the flow path forming member **54a** has the beam portion BR, in the filling process in which the pressurization discharge operation is performed after the first circulation operation is performed, the first circulation operation causes the air bubbles to stay in a region pinched between the filter **54o** and the beam portion BR or at a corner of the beam portion BR. Furthermore, the air bubbles combine with other air bubbles at a position where the air bubbles stay, and grow into large

air bubbles. The region pinched between the two members means that one member of the two members is in contact with this region in one direction, and that the other member of the two members is in contact with this region in the other direction different from the one direction. The staying of the air bubbles in the region pinched between the filter 540 and the beam portion BR or at the corner of the beam portion BR will be described with reference to FIGS. 8 and 9.

(98) FIG. 8 is a view illustrating a flow of the ink inside the common liquid chamber R while the first circulation operation is performed in a state where the circulation path KJ is not filled with the ink. However, in FIG. 8, and FIGS. 9, 11, 12, 14, 15, 18, 19, 20, 21, 22, 24, 25, and 26 (to be described later), the common liquid chamber R is illustrated as a rectangular shape to easily indicate the flow of the ink. Furthermore, in FIGS. 8, 9, 11, 12, 14, 15, 18, 19, 20, 21, 22, 24, 25, and 26, in order to intuitively indicate the flow of the ink, the flow of the ink is illustrated by increasing a size of an arrow indicating the flow of the ink as a flow rate of the ink increases. Furthermore, in FIGS. 8, 9, 11, 12, 14, 15, 18, 19, 20, 21, 22, 24, 25, and 26, a range filled with the ink is illustrated by shading with a broken line in a horizontal direction. Furthermore, in FIGS. 8, 9, 11, 12, 14, 15, 18, 19, 20, 21, 22, 24, 25, and 26, in order to indicate a positional relationship between the common liquid chamber R and the nozzle N, a contour of the nozzle N is illustrated by a broken line. Furthermore, FIGS. 8, 9, 11, 12, 14, 15, 18, 19, 20, 21, 22, 24, 25, and 26 illustrate a gravity direction GV. As described above, in the first embodiment, the gravity direction GV coincides with the Z2-direction. Therefore, a horizontal plane HF and the nozzle surface FN are parallel. Furthermore, in FIGS. 8, 9, 11, 12, 14, 15, 18, 19, 20, 21, 22, 24, 25, and 26, in order to facilitate understanding, in a state where the on-off valve 16 is open, the on-off valve 16 is illustrated as a white-outlined figure, and in a state where the on-off valve 16 is closed, the on-off valve 16 is illustrated as a black-painted figure. As illustrated in FIG. 8, the on-off valve 16 is open during the first circulation operation.

(99) As illustrated in FIG. 8, the ink introduced from the inlet Pin flows inside the upstream chamber UR, and is discharged from the outlet Pout. Furthermore, a portion of the ink introduced from the inlet Pin flows into the downstream chamber DR via the filter hole h23, and flows inside the downstream chamber DR. The flow rate of the ink inside the downstream chamber DR is lower than the flow rate of the ink inside the upstream chamber UR by the amount passing through the filter hole h23. Furthermore, as illustrated in FIG. 8, the ink flowing inside the downstream chamber DR collides with the beam portion BR, and branches in the Z2-direction and the Z1-direction.

(100) The ink flows into the circulation path KJ in a state where the circulation path KJ is not filled with the ink. Therefore, the air filling the circulation path KJ becomes the air bubbles, and the air bubbles are generated in the common liquid chamber R. With regard to the pressure of the ink flowing through the common liquid chamber R while the first circulation operation is performed, a strong negative pressure acts in the vicinity of the outlet Pout. Therefore, the air bubbles are less likely to stay, and the air bubbles in the vicinity of the outlet Pout are easily discharged from the outlet Pout. On the other hand, a negative pressure is less likely to act between the inlet Pin and the outlet Pout, compared to the vicinity of the outlet Pout. Therefore, the flow rate of the ink decreases. Furthermore, as described above, the flow rate of the ink inside the downstream chamber DR is lower than the flow rate of the ink inside the upstream chamber UR. Therefore, the air bubbles inside the downstream chamber DR are less affected by the flow of the ink in the first circulation operation, and are relatively greatly affected by a buoyant force. Therefore, while moving in the Y1-direction, the air bubbles move in the Z1-direction which is an opposite direction of the gravity direction GV. As described above, the air bubbles located in the Y2-direction with respect to the beam portion BR inside the downstream chamber DR tend to grow after being gathered in the region pinched between the filter 540 and the beam portion BR or at the corner of the beam portion BR. FIG. 8 illustrates an air bubble BL located in the Y2-direction with respect to the beam portion BR and grown after being gathered in the region pinched between the filter 540

and the beam portion BR. It can be said that the position in the Y2-direction with respect to the beam portion BR is a position closer to the inlet Pin in the two directions along the Y-axis with respect to the beam portion BR.

(101) FIG. 9 is a view illustrating a flow of the ink inside the common liquid chamber R while the pressurization discharge operation is performed after the first circulation operation. In the pressurization discharge operation, the on-off valve 16 is closed, and the supply flow path SF1 is pressurized to discharge the ink from the plurality of nozzles N. Therefore, as illustrated in FIG. 9, the on-off valve 16 is closed during the pressurization discharge operation. In the pressurization discharge operation, the discharge port of the ink is only the nozzle N. Therefore, the ink is discharged from the nozzle N. As illustrated in FIG. 9, a droplet DP is discharged from each of the plurality of nozzles N. As illustrated in FIG. 9, the flow of the ink inside the upstream chamber UR reaches the downstream chamber DR via the filter hole h23 of the filter 54o. As illustrated in FIG. 9, a flowing direction of the ink inside the downstream chamber DR is a direction substantially parallel to the Z2-direction. A degree of the flow generated by the pressurization discharge operation cancels out the buoyant force acting on the air bubble BL, and the air bubble BL tends to stay as it is in the region pinched between the filter 54o and the beam portion BR or at the corner of the beam portion BR.

(102) When a printing operation is performed while the air bubble BL stays, a large negative pressure acts on the common liquid chamber R in a case where a large amount of the ink is consumed for solid printing. In this manner, the air bubble BL is drawn into the nozzle N from the common liquid chamber R, thereby causing a possibility of poor ejection.

(103) Therefore, in the filling process according to the present embodiment, the liquid ejecting apparatus 100 performs the first circulation operation, performs the first pressurization discharge operation after the first circulation operation, performs an air bubble moving operation after the first pressurization discharge operation, and performs the second pressurization discharge operation after the air bubble moving operation. The air bubble moving operation is an operation for moving the ink inside the downstream chamber DR in a direction different from a direction in which the ink inside the downstream chamber DR is moved by the first circulation operation. In the air bubble moving operation, the ink is moved in the direction different from the direction in which the ink inside the downstream chamber DR is moved by the first circulation operation. In this manner, the air bubbles BL staying inside the downstream chamber DR can be moved by the first circulation operation. As illustrated in FIG. 8, the direction in which the ink inside the downstream chamber DR is moved by the first circulation operation is the Y1-direction. The air bubble moving operation is an example of a “predetermined operation”.

(104) The air bubble moving operation according to the first embodiment is a preliminary ejection operation for ejecting the ink that does not directly contribute to image formation from all of the plurality of nozzles N. In the preliminary ejection operation according to the first embodiment, as in the flushing operation, the ink is ejected to the liquid receiving section 182 from all of the plurality of nozzles N by supplying the drive signal Com to the piezoelectric element 54f. The ink does not land on the medium PP by ejecting the ink to the liquid receiving section 182. Therefore, it can be said that the preliminary ejection operation is an operation for ejecting the ink that does not directly contribute to the image formation. For example, the drive signal Com at the time of the preliminary ejection operation and the drive signal Com at the time of the flushing operation are signals having the same contents.

1-8. Filling Process According to First Embodiment

(105) FIG. 10 is a flowchart illustrating the filling process according to the first embodiment. In Step S2, the liquid ejecting apparatus 100 opens the on-off valve 16 and performs the first circulation operation in a state where the circulation path KJ is not filled with the ink. A state inside the common liquid chamber R in Step S2 coincides with a state illustrated in FIG. 8.

(106) After Step S2 is completed, the liquid ejecting apparatus 100 closes the on-off valve 16 in

Step **S4**, and performs the first pressurization discharge operation in Step **S6**. A state inside the common liquid chamber **R** in Step **S6** coincides with a state illustrated in FIG. **9**. Since the first pressurization discharge operation is performed, the plurality of nozzles **N** are filled with the ink. As described above, the air bubbles **BL** cannot be moved in the pressurization discharge operation. (107) After Step **S6** is completed, the liquid ejecting apparatus **100** performs the preliminary ejection operation in Step **S8**.

(108) FIG. **11** is a view illustrating a flow of the ink inside the common liquid chamber **R** while Step **S8** is performed. As illustrated in FIG. **11**, a direction in which the ink inside the downstream chamber **DR** is moved by the preliminary ejection operation is the **Z2**-direction, and is different from the **Y1**-direction which is the direction in which the ink inside the downstream chamber **DR** is moved by the first circulation operation. A strong negative pressure acts inside the common liquid chamber **R** by performing the preliminary ejection operation. Therefore, as illustrated in FIG. **11**, the air bubbles **BL** move to the nozzle **N**, and the air bubbles **BL** are discharged together with the ink from the nozzle **N**.

(109) After Step **S8** is completed, the liquid ejecting apparatus **100** performs the second pressurization discharge operation in Step **S10**.

(110) FIG. **12** is a view illustrating a flow of the ink inside the common liquid chamber **R** while Step **S10** is performed. The amount of the ink discharged from the plurality of nozzles **N** by the second pressurization discharge operation may be smaller than the amount of the ink discharged from the plurality of nozzles **N** by the first pressurization discharge operation. The amount of the ink discharged from the plurality of nozzles **N** is a total amount of the ink discharged from each of the plurality of nozzles **N**. For example, the control module **20** sets a period required for the second pressurization discharge operation to be shorter than a period required for the first pressurization discharge operation. Since the second pressurization discharge operation is performed, a liquid level of the nozzle **N** disturbed by the preliminary ejection operation, that is, a meniscus can be adjusted.

(111) After Step **S10** is completed, the liquid ejecting apparatus **100** completes a series of processes illustrated in FIG. **10**.

1-9. Summary of First Embodiment

(112) As described above, the liquid ejecting apparatus **100** according to the first embodiment includes the plurality of nozzles **N** that eject the ink in the **Z2**-direction which is the ejection direction, the common liquid chamber **R** that communicates with the plurality of nozzles **N** and extends in the direction along the **Y**-axis orthogonal to the direction along the **Z**-axis, the filter **540** that partitions the common liquid chamber **UR** into the upstream chamber **R** and the downstream chamber **DR**, the inlet **Pin** for introducing the ink into the upstream chamber **UR**, the outlet **Pout** for causing the ink to flow out from the upstream chamber **UR**, the sub tank **151** capable of storing the ink, the supply flow path **SF1** that causes the inlet **Pin** to communicate with the sub tank **151**, and the recovery flow path **CF1** that causes the outlet **Pout** to communicate with the sub tank **151**. A beam portion **BR** that couples the pair of inner walls **wDR** defining the downstream chamber **DR** is provided inside the downstream chamber **DR**. The pair of inner walls **wDR** are separated in the direction along the **X**-axis intersecting with the direction along the **Y**-axis when viewed in the **Z2**-direction. The pressurization discharge operation for discharging the ink from the plurality of nozzles **N** by pressurizing the supply flow path **SF1** and the first circulation operation for circulating the ink in the circulation path **KJ** including the sub tank **151**, the supply flow path **SF1**, the common liquid chamber **R**, and the recovery flow path **CF1**, in order of the sub tank **151**, the supply flow path **SF1**, the common liquid chamber **R**, the recovery flow path **CF1**, and the sub tank **151** are performed. In the filling process of filling the circulation path **KJ** with the ink, after the first circulation operation is performed, the preliminary ejection operation which is the air bubble moving operation for moving the ink inside the downstream chamber **DR** in the direction different from the direction in which the ink inside the downstream chamber **DR** is moved by the first

circulation operation is performed. After the air bubble moving operation is performed, the pressurization discharge operation is performed.

(113) In the air bubble moving operation, the ink inside the downstream chamber DR is moved in the direction different from the direction in which the ink inside the downstream chamber DR is moved by the first circulation operation. Therefore, the air bubbles BL staying in the region pinched between the beam portion BR and the filter **54o** can be moved by the first circulation operation. The air bubbles BL can be discharged from the common liquid chamber R by moving the air bubbles BL. Therefore, it is possible to reduce a possibility that the air bubbles BL may remain in the common liquid chamber R after the pressurization discharge operation after the air bubble moving operation.

(114) In addition, the liquid ejecting apparatus **100** forms an image on the medium PP by ejecting the ink onto the medium PP from all or a part of the plurality of nozzles N, and further includes a plurality of piezoelectric elements **54f** each driven to eject the ink from the plurality of nozzles N. The filling process performs a pressurization discharge operation between the first circulation operation and the preliminary ejection operation. In the preliminary ejection operation, the ink that does not directly contribute to the image formation is ejected from all of the plurality of nozzles N.

(115) Since a negative pressure can be generated in the downstream chamber DR by the preliminary ejection operation, the air bubbles BL staying in the region pinched between the beam portion BR and the filter **54o** can be moved.

(116) In addition, in the filling process, the amount of the ink discharged from the plurality of nozzles N by the second pressurization discharge operation performed after the preliminary ejection operation may be smaller than the amount of the ink discharged from the plurality of nozzles N by the first pressurization discharge operation performed between the first circulation operation and the preliminary ejection operation.

(117) As described above, the second pressurization discharge operation is performed to adjust the meniscus. The amount of the ink required for adjusting the meniscus is smaller than the amount of the ink required for filling the plurality of nozzles N. Therefore, in the liquid ejecting apparatus **100** according to the first embodiment, compared to an aspect in which the amount of the ink discharged from the plurality of nozzles N by the second pressurization discharge operation is larger than the amount of the ink discharged from the plurality of nozzles N by the first pressurization discharge operation, while the meniscus is adjusted, the amount of the ink consumed in the filling process can be reduced.

2. Second Embodiment

(118) In the filling process of the first embodiment, the preliminary ejection operation is performed for all of the plurality of nozzles N, but the present disclosure is not limited thereto. Hereinafter, a second embodiment will be described.

2-1. Filling Process According to Second Embodiment

(119) FIG. **13** is a flowchart illustrating a filling process according to the second embodiment. The filling process according to the second embodiment is different from the filling process according to the first embodiment in that a process in Step **S8-A** is performed instead of a process in Step **S8**.

(120) After Step **S6** is completed, the liquid ejecting apparatus **100** according to the second embodiment performs the preliminary ejection operation for an end portion nozzle group in Step **S8-A**. In the second embodiment, the preliminary ejection operation for the end portion nozzle group corresponds to the air bubble moving operation. The end portion nozzle group will be described with reference to FIG. **14**.

(121) FIG. **14** is a view illustrating a flow of the ink inside the common liquid chamber R while Step **S8-A** is performed. As illustrated in FIG. **14**, the liquid ejecting apparatus **100** ejects the ink that does not directly contribute to the image formation from the plurality of nozzles N belonging to an end portion nozzle group GN1 in the plurality of nozzles N. The end portion nozzle group GN1 is located in an end portion of the plurality of nozzles N in the Y2-direction. The end portion

nozzle group GN1 and a non-ejection nozzle group GN2 illustrated in FIG. 14 are nozzle groups obtained by dividing a nozzle group GN0 illustrated in FIG. 14 into two nozzle groups. The nozzle group GN0 is a nozzle group disposed closer to the inlet Pin than the beam portion BR in all of the plurality of nozzles N belonging to one nozzle row Ln of either the first nozzle row L1 or the second nozzle row L2 of the head chip 54 when viewed in the direction along the Z-axis. The end portion nozzle group GN1 includes a nozzle N-1 disposed closest to the inlet Pin in the nozzle group GN0. The non-ejection nozzle group GN2 includes a nozzle N-2 disposed closest to the beam portion BR in the nozzle group GN0. The end portion nozzle group GN1 corresponds to a “first nozzle group”, and the non-ejection nozzle group GN2 corresponds to a “second nozzle group”.

(122) The number of nozzles belonging to the nozzle group GN0, the end portion nozzle group GN1, and the non-ejection nozzle group GN2 is two or more. The plurality of nozzles N belonging to the nozzle group GN0, the end portion nozzle group GN1, and the non-ejection nozzle group GN2 are continuously disposed along the Y-axis. Therefore, the end portion nozzle group GN1 is a nozzle group close to the inlet Pin in the two nozzle groups obtained by dividing the nozzle group GN0 by a plane parallel to the XZ-plane, and it can be said that the non-ejection nozzle group GN2 is a nozzle group close to the beam portion BR.

(123) The control module 20 supplies the drive signal Com having the same content as the drive signal Com at the time of the flushing operation to the piezoelectric elements 54f corresponding to each of the plurality of nozzles N belonging to the end portion nozzle group GN1, and supplies the drive signal Com having a constant potential to the piezoelectric element 54f corresponding to each of the nozzles N that do not belong to the end portion nozzle group GN1. The nozzle N that does not belong to the end portion nozzle group GN1 includes the nozzle N belonging to the non-ejection nozzle group GN2.

(124) The end portion of the downstream chamber DR in the Y2-direction has a negative pressure by ejecting the ink from the plurality of nozzles N belonging to the end portion nozzle group GN1. Therefore, the ink inside the downstream chamber DR can be moved in the Y2-direction. In the preliminary ejection operation for the end portion nozzle group GN1, which is the air bubble moving operation in the second embodiment, the ink is moved in the Y2-direction different from the Y1-direction in which the ink inside the downstream chamber DR is moved by the first circulation operation. In accordance with the flow of the ink in the Y2-direction, the air bubbles BL also move to the end portion of the downstream chamber DR in the Y2-direction.

(125) In order to generate a force for moving the air bubbles BL to the end portion of the downstream chamber DR in the Y2-direction, one nozzle N belonging to the end portion nozzle group GN1 is not sufficient, and the plurality of nozzles N are required. On the other hand, as the number of the nozzles N belonging to the end portion nozzle group GN1 is small, that is, as the end portion nozzle group GN1 is closer to the Y2-direction, the air bubbles BL can be closer to the end portion of the downstream chamber DR in the Y2-direction. Therefore, compared to the preliminary ejection operation for all of the plurality of nozzles N, it is possible to reduce consumption of the ink. The number of the nozzles N belonging to the end portion nozzle group GN1 is set by an experiment or an experience of a developer of the liquid ejecting apparatus 100. For example, the number of the nozzles N belonging to the end portion nozzle group GN1 is smaller than half the number of the nozzles N belonging to the nozzle group GN0. Furthermore, the number of the nozzles N belonging to the end portion nozzle group GN1 may be smaller than one-third of the number of the nozzles N belonging to the nozzle group GN0 in some cases, or may be smaller than one-fourth in some cases.

(126) After Step S8-A is completed, the liquid ejecting apparatus 100 performs the second pressurization discharge operation in Step S10.

(127) FIG. 15 is a view illustrating a flow of the ink inside the common liquid chamber R while Step S10 is performed. As illustrated in FIG. 15, in the pressurization discharge operation

performed in Step **S10**, the flow of the ink inside the region **R1** of the common liquid chamber **R** close to the inlet **Pin** is less likely to be dispersed, compared to the flow of the ink inside the region **R2** close to the beam portion **BR**. More specifically, the wall surface of the common liquid chamber **R** exists in the **Y2**-direction of the region **R1**. Therefore, in the region **R1**, the ink flows in the **Z2**-direction along the wall surface. In contrast, the beam portion **BR** exists in the region **R2**. Therefore, the flow of the ink is dispersed in the **Z2**-direction and the **Y1**-direction by the beam portion **BR**. As a result that the flow of the ink is not dispersed, a force for moving the air bubbles **BL** in the **Z2**-direction inside the region **R1** is greater than a force for moving the air bubbles **BL** in the **Z2**-direction inside the region **R2**. Therefore, in Step **S10**, the air bubbles **BL** can be moved in the **Z2**-direction, and the air bubbles **BL** can be discharged from the downstream chamber **DR**. (128) After Step **S10** is completed, the liquid ejecting apparatus **100** completes a series of processes illustrated in FIG. **13**.

2-2. Summary of Second Embodiment

(129) As described above, in the second embodiment, the plurality of nozzles **N** are arranged in the direction along the **Y**-axis to form the nozzle row **Ln**. The inlet **Pin** is disposed in an end portion of the upstream chamber **UR** in the direction along the **Y**-axis. The nozzle group **GN0** disposed closer to the inlet **Pin** than the beam portion **BR** in the plurality of nozzles **N** is divided into the end portion nozzle group **GN1** including the nozzle **N-1** closest to the inlet **Pin** and the non-ejection nozzle group **GN2** including the nozzle **N-2** closest to the beam portion **BR**. In the preliminary ejection operation as the air bubble moving operation, the ink that does not directly contribute to the image formation is ejected from the plurality of nozzles **N** belonging to the end portion nozzle group **GN1**.

(130) The liquid ejecting apparatus **100** according to the second embodiment can move the air bubbles **BL** inside the downstream chamber **DR** to the end portion of the common liquid chamber **R** away from the beam portion **BR** by ejecting the ink from the plurality of nozzles **N** belonging to the end portion nozzle group **GN1**. Therefore, the air bubbles **BL** can be discharged by the pressurization discharge operation after the preliminary ejection operation. Furthermore, the liquid ejecting apparatus **100** according to the second embodiment performs the preliminary ejection operation only for the end portion nozzle group **GN1** in the plurality of nozzles **N**. Therefore, compared to an aspect in which the preliminary ejection operation is performed for all of the plurality of nozzles **N** as in the first embodiment, it is possible to reduce consumption of the ink.

3. Third Embodiment

(131) In the first embodiment and the second embodiment, the air bubbles **BL** inside the downstream chamber **DR** are moved by the preliminary ejection operation, but the present disclosure is not limited thereto. Hereinafter, a third embodiment will be described.

3-1. Configuration of Liquid Ejecting Apparatus **100-B** According to Third Embodiment

(132) FIG. **16** is a view for describing a circulation mechanism **15-B** and the on-off valve **16** according to the third embodiment. The liquid ejecting apparatus **100-B** according to the third embodiment is different from the liquid ejecting apparatus **100** in that the circulation mechanism **15-B** is provided instead of the circulation mechanism **15**. The circulation mechanism **15-B** is different from the circulation mechanism **15** in that a pump **158** is provided. The pump **158** is provided in an intermediate portion of the in-device recovery flow path **CJ1**. In addition, as illustrated in FIG. **16**, the pump **158** is provided between the sub tank **151** and the on-off valve **16**.

(133) In the first circulation operation, the pump **158** generates a negative pressure with respect to the outlet **Pout**. In this manner, the ink can be circulated faster, compared to the liquid ejecting apparatus **100** according to the first embodiment.

(134) Furthermore, in the pressurization discharge operation, the supply flow path **SF1** is pressurized by the pump **159**, and the recovery flow path **CF1** is pressurized by the pump **158** to generate a flow **FR1-B** in which the ink flows in order of the supply flow path **SF1**, the common liquid chamber **R**, and the plurality of nozzles **N** and a flow **FR2-B** in which the ink flows in order

of the recovery flow path CF1, the common liquid chamber R, and the plurality of nozzles N. The liquid ejecting apparatus **100-B** according to the third embodiment generates the flow FR1-B and the flow FR2-B. In this manner, a larger ink flow can be generated, compared to the liquid ejecting apparatus **100** according to the first embodiment. Therefore, more air bubbles can be discharged in the pressurization discharge operation.

(135) Furthermore, in the liquid ejecting apparatus **100-B**, the pump **159** stops pressurizing the supply flow path SF1, and the pump **158** pressurizes the recovery flow path CF1. In this manner, it is possible to perform the second circulation operation for circulating the ink in a direction opposite to the direction in which the ink is moved by the first circulation operation. Specifically, in the second circulation operation, the ink is circulated in the circulation path KJ in order of the sub tank **151**, the recovery flow path CF1, the common liquid chamber R, the supply flow path SF1, and the sub tank **151**. For example, when the pump **158** and the pump **159** are tube pumps, the supply flow path SF1 may be decompressed by rotating the pump **159** in the opposite direction in the second circulation operation. In this manner, the ink may be circulated faster.

3-2. Filling Process According to Third Embodiment

(136) FIG. **17** is a flowchart illustrating a filling process according to a third embodiment. In the filling process according to the third embodiment, a process after the process in Step S2 is different from the filling process according to the first embodiment.

(137) After Step S2 is completed, the liquid ejecting apparatus **100-B** performs the second circulation operation in Step S12 in a state where the on-off valve **16** is open. In the third embodiment, the second circulation operation corresponds to the air bubble moving operation.

(138) FIG. **18** is a view illustrating a flow of the ink inside the common liquid chamber R while Step S12 is performed. As illustrated in FIG. **18**, a direction in which the ink inside the downstream chamber DR is moved by the second circulation operation is the Y2-direction different from the Y1-direction which is the direction in which the ink inside the downstream chamber DR is moved by the first circulation operation. As illustrated in FIG. **18**, the ink inside the downstream chamber DR is moved in the Y2-direction by the second circulation operation. Therefore, the air bubbles BL can also be moved in the Y2-direction, and can be moved to the end portion of the downstream chamber DR in the Y2-direction.

(139) An object of performing the second circulation operation is only to move the air bubbles BL pinched between the beam portion BR and the filter **54o** to the end portion of the downstream chamber DR in the Y2-direction. Therefore, a period during which the second circulation operation is performed may be shorter than a period during which the first circulation operation performed in Step S2 is performed.

(140) After Step S12 is completed, the liquid ejecting apparatus **100** closes the on-off valve **16** in Step S14, and performs the pressurization discharge operation in Step S16. The flow of the ink inside the common liquid chamber R while Step S16 is performed is substantially the same as the flow of the ink inside the common liquid chamber R while the second pressurization discharge operation of the second embodiment is performed, which is illustrated in FIG. **15**. Therefore, the illustration will be omitted.

(141) As in the second pressurization discharge operation for the second embodiment, in the pressurization discharge operation performed in Step S16, compared to the flow of the ink inside the region R2 close to the beam portion BR, the flow of the ink inside the region R1 close to the inlet Pin in the common liquid chamber R is less likely to be dispersed. In Step S16, the air bubbles BL can also be moved in the Z2-direction, and can be discharged from the downstream chamber DR.

3-3. Summary of Third Embodiment

(142) As described above, the air bubble moving operation in the third embodiment is the second circulation operation for circulating the liquid in the direction opposite to the direction in the first circulation operation.

(143) The liquid ejecting apparatus **100-B** according to the third embodiment can move the air bubbles BL inside the downstream chamber DR to the end portion close to the inlet Pin of the downstream chamber DR away from the beam portion BR. Therefore, the air bubbles BL can be discharged from the downstream chamber DR by the pressurization discharge operation after the second circulation operation.

(144) In addition, the period during which the second circulation operation is performed is shorter than the period during which the first circulation operation is performed.

(145) In the liquid ejecting apparatus **100-B** according to the third embodiment, compared to an aspect in which the period during which the second circulation operation is performed is longer than the period during which the first circulation operation is performed, while the air bubbles BL are discharged from the downstream chamber DR, it is possible to shorten the period during which the filling process is performed.

4. Modification Examples

(146) Each form described above as an example can be modified in various ways. Specific modification aspects will be described below as examples. Any two or more aspects selected from the following examples can be combined as appropriate within a mutually consistent range.

4-1. First Modification Example

(147) In each of the above-described aspects, the Z2-direction coincides with the gravity direction GV, but the present disclosure is not limited thereto.

(148) FIG. **19** is a view illustrating a flow of the ink inside the common liquid chamber R while the preliminary ejection operation is performed in a liquid ejecting apparatus **100-C** according to a first modification example. The liquid ejecting apparatus **100-C** is different from the liquid ejecting apparatus **100** according to the first embodiment in that the Y2-direction coincides with the gravity direction GV. Therefore, in the first modification example, the nozzle surface FN is inclined by 90 degrees with respect to the horizontal plane HF. In other words, in the common liquid chamber R according to the first modification example, the liquid ejecting apparatus **100-C** can be used in a state where the common liquid chamber R according to the first embodiment is rotated counterclockwise around the X-axis as the central axis by 90 degrees when viewed in the X2-direction from the X1-direction.

(149) In the first modification example, the filling process according to the first embodiment illustrated in FIG. **10** is performed. FIG. **19** illustrates a flow of the ink inside the common liquid chamber R while the preliminary ejection operation which is the process in Step S8 is performed. The air bubbles BL pinched between the filter **54o** and the beam portion BR in Step S6 is moved in the Z2-direction by the preliminary ejection operation in Step S8, and is discharged from the nozzle N. As described above, the liquid ejecting apparatus **100-C** according to the first modification example can reduce the air bubbles BL staying in the downstream chamber DR by performing the preliminary ejection operation according to the first embodiment.

(150) In addition, in the first modification example, an aspect has been described in which the liquid ejecting apparatus **100-C** is used in a state where the common liquid chamber R is rotated counterclockwise around the X-axis as the central axis by 90 degrees when viewed in the X2-direction from the X1-direction. However, the aspect in which the liquid ejecting apparatus **100** is used is not limited to the first modification example. For example, even in an aspect in which the liquid ejecting apparatus **100** is used in a state where the common liquid chamber R is rotated counterclockwise around the X-axis as the central axis by an angle larger than zero degrees and smaller than 90 degrees when viewed in the X2-direction from the X1-direction, it is possible to reduce the air bubbles BL staying in the downstream chamber DR by performing the preliminary ejection operation according to the first embodiment.

4-2. Second Modification Example

(151) In the first embodiment to the third embodiment, the distances between the inlet Pin and the outlet Pout from the horizontal plane HF are the same, and in the first modification example, the

distance from the horizontal plane HF to the inlet Pin is shorter than the distance from the horizontal plane HF to the outlet Pout. However, the distance from the horizontal plane HF to the inlet Pin may be longer than the distance from the horizontal plane HF to the outlet Pout.

(152) FIG. **20** is a view illustrating a flow of the ink inside the common liquid chamber R while the pressurization discharge operation is performed in a liquid ejecting apparatus **100-D** according to a second modification example. The liquid ejecting apparatus **100-D** is different from the liquid ejecting apparatus **100** according to the first embodiment in that a V1-direction orthogonal to the X-axis and obtained by rotating the Z2-direction counterclockwise by 15 degrees when viewed in the X2-direction from the X1-direction coincides with the gravity direction GV. FIG. **20** illustrates a state where the liquid ejecting apparatus **100-D** is used in a state where the common liquid chamber R is rotated clockwise around the X-axis as the central axis by 15 degrees when viewed in the X2-direction from the X1-direction.

(153) In the second modification example, the filling process according to the first embodiment illustrated in FIG. **10** is performed. In the second modification example, in some cases, a force for moving the air bubbles in the Y1-direction by the first circulation operation may be greater than a force of moving the air bubbles in the Y2-direction by the buoyant force. However, in the liquid ejecting apparatus **100-D** according to the second modification example, the air bubbles BL pinched between the filter **54o** and the beam portion BR in Step **S6** are moved in the Z2-direction by the preliminary ejection operation in Step **S8**, and are discharged from the nozzle N. As described above, the liquid ejecting apparatus **100-D** according to the second modification example can reduce the air bubbles BL staying in the downstream chamber DR by performing the preliminary ejection operation according to the first embodiment.

(154) In addition, in FIG. **20**, although the liquid ejecting apparatus **100-D** performs the filling process according to the first embodiment, the filling process according to the second embodiment may be performed, or the filling process according to the third embodiment may be performed. When the liquid ejecting apparatus **100-D** performs the filling process according to the second embodiment or the filling process according to the third embodiment, the air bubbles BL are moved in the Y2-direction, and thereafter, are moved in the Z2-direction to be discharged from the inside of the downstream chamber DR.

(155) In addition, in the second modification example, an aspect has been described in which the liquid ejecting apparatus **100-D** is used in a state where the common liquid chamber R is rotated clockwise around the X-axis as the central axis by 15 degrees when viewed in the X2-direction from the X1-direction. However, the aspect of using the liquid ejecting apparatus **100** is not limited to the second modification example. For example, in an aspect in which the liquid ejecting apparatus **100** is used in a state where the common liquid chamber R is rotated around the X-axis as the central axis by an angle larger than zero degrees and smaller than 15 degrees clockwise when viewed in the X2-direction from the X1-direction, compared to the aspect of performing the pressurization discharge operation after the circulation operation is performed, it is possible to reduce the possibility that the air bubbles may remain in the common liquid chamber R after the circulation operation.

4-3. Third Modification Example

(156) In the first modification example and the second modification example, the aspect has been described in which the liquid ejecting apparatus **100** is used in a state where the common liquid chamber R is rotated around the X-axis as the central axis. However, the aspect of using the liquid ejecting apparatus **100** is not limited thereto. For example, even in an aspect in which the liquid ejecting apparatus **100** is used in a state where the common liquid chamber R is rotated around the Y-axis as the central axis, it is possible to reduce the air bubbles in the downstream chamber DR which stay in the first circulation operation.

(157) FIG. **21** is a view for describing a liquid ejecting apparatus **100-E** according to a third modification example. However, in FIG. **21**, the head chip **54** according to the third modification

example is illustrated only in the X2-direction of the wiring substrate **54i**, in a cross section parallel to the XZ-plane and cut along the plane passing through the beam portion BR. The liquid ejecting apparatus **100-E** is different from the liquid ejecting apparatus **100** according to the first embodiment in that the X1-direction coincides with the gravity direction GV. FIG. **21** illustrates an aspect in which the liquid ejecting apparatus **100-E** is used in a state where the common liquid chamber R is rotated clockwise around the Y-axis as the central axis by 90 degrees when viewed in the Y1-direction from the Y2-direction.

(158) In the third modification example, the filling process according to the first embodiment illustrated in FIG. **10** is performed. The air bubbles BL pinched between the filter **54o** and the beam portion BR in Step **S6** is moved in the Z2-direction by the preliminary ejection operation in Step **S8**, and is discharged from the nozzle N. As described above, the liquid ejecting apparatus **100-C** according to the third modification example can reduce the air bubbles BL staying in the downstream chamber DR by performing the preliminary ejection operation according to the first embodiment.

(159) In addition, in FIG. **21**, although the liquid ejecting apparatus **100-E** performs the filling process according to the first embodiment, the filling process according to the second embodiment may be performed, or the filling process according to the third embodiment may be performed.

4-4. Fourth Modification Example

(160) In each of the above-described aspects, a gap is not formed between the filter **54o** and the beam portion BR in the direction along the Z-axis, but the gap may be formed.

(161) FIG. **22** is a view for describing a liquid ejecting apparatus **100-F** according to a fourth modification example. FIG. **23** is a cross-sectional view taken along line XXIII-XXIII in FIG. **22**. The head chip **54** according to the fourth modification example is different from the head chip **54** according to the first embodiment in that a flow path forming member **54a-F** is provided instead of the flow path forming member **54a**. The flow path forming member **54a-F** is different from the flow path forming member **54a** in that a beam portion BR-F is provided instead of the beam portion BR.

(162) As illustrated in FIGS. **22** and **23**, a surface SB1-F of the beam portion BR-F facing the case **54n** is located in the Z2-direction with respect to a surface SB2 of the flow path forming member **54a** facing the case **54n**. Therefore, a gap GP is formed between the filter **54o** and the beam portion BR-F in the direction along the Z-axis.

(163) As illustrated in FIGS. **22** and **23**, the liquid ejecting apparatus **100-F** according to the fourth modification example has the gap GP. When a dimension CZ of the gap GP in the direction along the Z-axis is shorter than at least any one of a distance DZ between the beam portion BR-D and the bottom surface of the downstream chamber DR, a dimension BX of the beam portion BR-D in the direction along the X-axis, a dimension BZ of the beam portion BR-D in the direction along the Z-axis, and a dimension BY of the beam portion BR-D in the direction along the Y-axis, the air bubbles are less likely to pass through the gap GP. As a result, as illustrated in FIGS. **22** and **23**, in some cases, the air bubbles BL may grow, and the air bubbles BL may stay inside the downstream chamber DR.

(164) Therefore, the liquid ejecting apparatus **100-F** according to the fourth modification example performs any one filling process of the filling process according to the first embodiment, the filling process according to the second embodiment, and the filling process according to the third embodiment. In this manner, the air bubbles BL can be prevented from staying inside the downstream chamber DR.

4-5. Fifth Modification Example

(165) The common liquid chamber R according to each of the above-described aspects is provided with one inlet Pin and one outlet Pout, but the present disclosure is not limited thereto.

(166) FIG. **24** is a view for describing a liquid ejecting apparatus **100-G** according to a fifth modification example. The liquid ejecting apparatus **100-G** is different from the liquid ejecting

apparatus **100** according to the first embodiment in that a case **54n-G** is provided instead of the case **54n** and the head chip **54** having a flow path forming member **54a-G** is provided instead of the flow path forming member **54a**. A common liquid chamber R-G is formed by the case **54n-G** and the flow path forming member **54a-G**. The common liquid chamber R-G is different from the common liquid chamber R in that an upstream chamber UR-G is provided instead of the upstream chamber UR and a downstream chamber DR-G is provided instead of the downstream chamber DR.

(167) The case **54n-G** is different from the case **54n** in that the case **54n-G** is provided with an inlet Pin-G1 and an inlet Pin-G2 instead of the inlet Pin and is provided with an outlet Pout-G instead of the outlet Pout. Hereinafter, in some cases, the inlet Pin-G1 and the inlet Pin-G2 may be collectively referred to as an inlet Pin-G. As illustrated in FIG. 21, the inlet Pin-G1 is provided in an end portion of the upstream chamber UR-G in the Y1-direction. The inlet Pin-G2 is provided in an end portion of the upstream chamber UR-G in the Y2-direction. The outlet Pout-G is provided between the inlet Pin-G1 and the inlet Pin-G2, and more specifically, is provided in the vicinity of the center of the upstream chamber UR-G.

(168) As illustrated in FIG. 24, the inlet Pin-G1 is coupled to the in-head supply flow path SH1-G1, and the inlet Pin-G2 is coupled to the in-head supply flow path SH1-G2. The in-head supply flow path SH1-G1 and the in-head supply flow path SH1-G2 are flow paths inside the liquid ejecting head **50** according to the fifth modification example, and are flow paths provided instead of the in-head supply flow path SH1. Each of the in-head supply flow path SH1-G1 and the in-head supply flow path SH1-G2 is coupled to a mainstream portion coupled to the head inlet Qin. The outlet Pout-G is coupled to the in-head recovery flow path CH1.

(169) The flow path forming member **54a-G** is different from the flow path forming member **54a** in that the beam portion BR-G1 and the beam portion BR-G2 are provided instead of the beam portion BR in the flow path forming member **54a-G**. As understood from FIG. 24, the beam portion BR-G1 is provided between the inlet Pin-G1 and the outlet Pout-G when viewed in the direction along the Z-axis. The beam portion BR-G2 is provided between the inlet Pin-G2 and the outlet Pout-G when viewed in the direction along the Z-axis.

(170) FIG. 24 illustrates a flow of the ink in the first circulation operation in the fifth modification example. As illustrated in FIG. 24, the ink supplied from the inlets Pin-G provided in each of both end portions of the upstream chamber UR-G in the direction along the Y-axis is discharged from the outlet Pout-G provided at the center of the upstream chamber UR-G. Furthermore, in the ink supplied from the inlet Pin-G, the ink flowing into the downstream chamber DR-G via the filter **54o** is also discharged from the outlet Pout-G at the center of the downstream chamber DR-G via the upstream chamber UR-G.

(171) In the fifth modification example, the liquid ejecting apparatus **100-G** performs the filling process according to the first embodiment illustrated in FIG. 10. The ink flows from each inlet Pin-G to the outlet Pout-G by the first circulation operation. Therefore, there is a possibility that air bubbles BL-G1 and BL-G2 may stay as illustrated in FIG. 24. The air bubbles BL-G1 are located in the Y1-direction with respect to the beam portion BR-G1, and are pinched between the beam portion BR-G1 and the filter **54o**. The air bubbles BL-G2 are located in the Y2-direction with respect to the beam portion BR-G2, and are pinched between the beam portion BR-G2 and the filter **54o**.

(172) In the liquid ejecting apparatus **100-G**, the preliminary ejection operation according to the first embodiment is performed after the first circulation operation. In this manner, the air bubbles BL-G1 and BL-G2 can be moved in the Z2-direction, and the air bubbles BL-G1 and BL-G2 can be discharged from the downstream chamber DR-G.

(173) In addition, the liquid ejecting apparatus **100-G** according to the fifth modification example may perform the filling process according to the second embodiment or the filling process according to the third embodiment instead of the filling process according to the first embodiment.

An aspect in which the liquid ejecting apparatus **100-G** performs the filling process according to the second embodiment will be described with reference to FIG. **25**.

(174) FIG. **25** is a view for describing the aspect in which the liquid ejecting apparatus **100-G** performs the filling process according to the second embodiment. FIG. **25** illustrates a flow of the ink inside the common liquid chamber R-G while the preliminary ejection operation is performed for the end portion nozzle group in Step **S8-A**.

(175) As illustrated in FIG. **25**, the liquid ejecting apparatus **100-G** ejects the ink that does not directly contribute to the image formation from the plurality of nozzles N belonging to the end portion nozzle group GN1-G1 and the end portion nozzle group GN1-G2 in the plurality of nozzles N.

(176) The end portion nozzle group GN1-G1 and the non-ejection nozzle group GN2-G1 illustrated in FIG. **25** are nozzle groups obtained by dividing the nozzle group GN0-G1 illustrated in FIG. **25** into two nozzle groups. When viewed in the direction along the Z-axis, the nozzle group GN0-G1 is a nozzle group disposed closer to the inlet Pin-G1 than the beam portion BR-G1 in all of the plurality of nozzles N belonging to the nozzle row Ln of the head chip **54** according to the fifth modification example. The end portion nozzle group GN1-G1 includes a nozzle N-G1 disposed closest to the inlet Pin in the nozzle group GN0-G1. The non-ejection nozzle group GN2-G1 includes a nozzle N-G2 disposed closest to the beam portion BR-G1 in the nozzle group GN0-G1.

(177) The end portion nozzle group GN1-G2 and the non-ejection nozzle group GN2-G2 illustrated in FIG. **25** are nozzle groups obtained by dividing the nozzle group GN0-G2 illustrated in FIG. **25** into two nozzle groups. When viewed in the direction along the Z-axis, the nozzle group GN0-G2 is a nozzle group disposed closer to the inlet Pin-G2 than the beam portion BR-G2 in all of the plurality of nozzles N belonging to the nozzle row Ln of the head chip **54** according to the fifth modification example. The end portion nozzle group GN1-G2 includes a nozzle N-G3 disposed closest to the inlet Pin in the nozzle group GN0-G2. The non-ejection nozzle group GN2-G2 includes a nozzle N-G4 disposed closest to the beam portion BR-G2 in the nozzle group GN0-G2.

(178) The control module **20** supplies the drive signal Com having the same content as the drive signal Com at the time of the flushing operation to the piezoelectric elements **54f** corresponding to each of the plurality of nozzles N belonging to the end portion nozzle group GN1-G1 and the end portion nozzle group GN1-G2, and supplies the drive signal Com having a constant potential to the piezoelectric element **54f** corresponding to each of the nozzles N that do not belong to the end portion nozzle group GN1-G1 or the end portion nozzle group GN1-G2. The nozzle N that does not belong to the end portion nozzle group GN1-G1 or the end portion nozzle group GN1-G2 includes the nozzle N belonging to the non-ejection nozzle group GN2-G1 and the non-ejection nozzle group GN2-G2.

(179) The end portion of the downstream chamber DR-G in the Y1-direction has a negative pressure by ejecting the ink from the plurality of nozzles N belonging to the end portion nozzle group GN1-G1. Therefore, the ink inside the downstream chamber DR-G can be moved in the Y1-direction. The air bubbles BL-G1 are also moved to the end portion of the downstream chamber DR-G in the Y1-direction in accordance with the flow of the ink in the Y1-direction.

(180) Furthermore, since the ink is ejected from the plurality of nozzles N belonging to the end portion nozzle group GN1-G2, the end portion of the downstream chamber DR-G in the Y2-direction has the negative pressure. Therefore, the ink inside the downstream chamber DR-G can be moved in the Y2-direction. The air bubbles BL-G2 are also moved to the end portion of the downstream chamber DR-G in the Y2-direction in accordance with the flow of the ink in the Y2-direction.

(181) After Step **S8-A** is completed, the liquid ejecting apparatus **100-G** performs the second pressurization discharge operation in Step **S10**. In this manner, the air bubbles BL-G1 and the air bubbles BL-G2 can be moved in the Z2-direction, and can be discharged from the downstream chamber DR-G.

(182) In the above-described aspect, since the ink is discharged from the plurality of nozzles N belonging to the end portion nozzle group GN1-G1 and the end portion nozzle group GN1-G2, the end portion of the downstream chamber DR-G in the Y2-direction has the negative pressure. Therefore, there is a possibility that the movement of the air bubbles BL-G1 in the Y1-direction may be hindered. Therefore, in Step S8-A, the control module 20 may supply the drive signal Com having the same content as the drive signal Com at the time of the flushing operation to the piezoelectric elements 54f corresponding to each of the plurality of nozzles N belonging to the end portion nozzle group GN1-G1, and the control module 20 may supply the drive signal Com having a constant potential to the piezoelectric element 54f corresponding to each of the nozzles N that do not belong to the end portion nozzle group GN1-G1. The liquid ejecting apparatus 100-G performs the pressurization discharge operation, and thereafter, the control module 20 supplies the drive signal Com having the same content as the drive signal Com at the time of the flushing operation to the piezoelectric elements 54f corresponding to each of the plurality of nozzles N belonging to the end portion nozzle group GN1-G2, and supplies the drive signal Com having a constant potential to the piezoelectric element 54f corresponding to each of the nozzles N that do not belong to the end portion nozzle group GN1-G2. Thereafter, the pressurization discharge operation is performed.

(183) Although not illustrated, even when the liquid ejecting apparatus 100-G according to the fifth modification example performs the filling process according to the third embodiment, the air bubbles BL-G1 and the air bubbles BL-G2 can be discharged from the downstream chamber DR-G.

4-6. Sixth Modification Example

(184) In the fifth modification example, two inlets Pin are provided for one common liquid chamber R, and one outlet Pout is provided for one common liquid chamber R, but the present disclosure is not limited thereto.

(185) FIG. 26 is a view for describing a liquid ejecting apparatus 100-H according to a sixth modification example. The liquid ejecting apparatus 100-H is different from the liquid ejecting apparatus 100-G in that one inlet Pin-H is provided for a common liquid chamber R-H according to the sixth modification example, and an outlet Pout-H1 and an outlet Pout-H2 are provided. Hereinafter, in some cases, the outlet Pout-H1 and the outlet Pout-H2 may be collectively referred to as an outlet Pout-H. A shape of the head chip 54 according to the sixth modification example is the same as a shape of the head chip 54 according to the fifth modification example. In the sixth modification example, the common liquid chamber R-H is formed by the case 54n-G and the flow path forming member 54a-G. The common liquid chamber R-H is different from the common liquid chamber R-G in that an upstream chamber UR-H is provided instead of the upstream chamber UR-G.

(186) In the upstream chamber UR-H, an opening that functions as the inlet Pin-G1 functions as an outlet Pout-H1 in the upstream chamber UR-G, an opening that functions as the inlet Pin-G2 functions as an outlet Pout-H2 in the upstream chamber UR-G, and an opening that functions as the outlet Pout-G functions as an inlet Pin-H in the upstream chamber UR-G.

(187) As illustrated in FIG. 26, the outlet Pout-H1 is coupled to the in-head recovery flow path CH1-H1, and the outlet Pout-H2 is coupled to the in-head recovery flow path CH1-H2. The in-head recovery flow path CH1-H1 and the in-head recovery flow path CH1-H2 are flow paths inside the liquid ejecting head 50 according to the sixth modification example, and are flow paths provided instead of the in-head recovery flow path CH1. Each of the in-head recovery flow path CH1-H1 and the in-head recovery flow path CH1-H2 is coupled to a mainstream portion coupled to the head outlet Qout. The inlet Pin-H is coupled to the in-head supply flow path SH1.

(188) In the sixth modification example, the liquid ejecting apparatus 100-H performs the filling process according to the first embodiment illustrated in FIG. 10. The ink is caused to flow from the inlet Pin-H to each outlet Pout-H by the first circulation operation.

(189) Therefore, the ink supplied from the inlet Pin-H provided at the center of the upstream

chamber UR-H in the direction along the Y-axis is discharged from the outlets Pout-H provided in each of both end portions of the upstream chamber UR-H in the direction along the Y-axis.

(190) Furthermore, in the ink supplied from the inlet Pin-H, the ink flowing into the downstream chamber DR-G via the filter **54o** is also discharged from the outlet Pout-H in each of both end portions of the downstream chamber DR-G via the upstream chamber UR-H.

(191) As illustrated in FIG. **26**, there is a possibility that the air bubbles BL-H1 and the air bubbles BL-H2 may stay due to the first circulation operation. The air bubbles BL-H1 are located in the Y2-direction with respect to the beam portion BR-H1, and are pinched between the beam portion BR-G1 and the filter **54o**. The air bubbles BL-H2 are located in the Y1-direction with respect to the beam portion BR-H2, and are pinched between the beam portion BR-G2 and the filter **54o**.

(192) The liquid ejecting apparatus **100-H** performs the preliminary ejection operation according to the first embodiment after the first circulation operation. In this manner, the air bubbles BL-H1 and BL-H2 can be moved in the Z2-direction, and the air bubbles BL-H1 and BL-H2 can be discharged from the downstream chamber DR-G.

4-7. Seventh Modification Example

(193) In each of the above-described aspects, the serial type liquid ejecting apparatus **100** in which the liquid ejecting head **50** reciprocates in the direction along the X-axis has been described as an example, but the present disclosure is not limited to this aspect. The liquid ejecting apparatus may be a line-type liquid ejecting apparatus in which the plurality of nozzles N are distributed over the entire width of the medium PP.

4-8. Eighth Modification Example

(194) In the above-described first embodiment, the circulation mechanism **15** includes one sub tank **151**, but the present disclosure is not limited to this aspect. Instead of the sub tank **151**, the circulation mechanism **15** of the liquid ejecting apparatus **100** may include a supply-side tank coupled to the supply flow path SF1 and storing the ink to be supplied to the liquid ejecting head **50**, a recovery-side tank coupled to the recovery flow path SC1 and storing the ink recovered from the liquid ejecting head **50**, a pressurization section that pressurizes the inside of the supply-side tank, a decompression section that decompresses the inside of the recovery-side tank, a relay flow path that causes the supply-side tank to communicate with the recovery-side tank, and a relay pump provided in an intermediate portion of the relay flow path and moving the ink from the recovery-side tank to the supply-side tank via the relay flow path. For example, the pressurization section is a compressor. For example, the decompression section is a vacuum pump. In the circulation mechanism **15** configured in this way, the supply-side tank is set to the positive pressure by driving the pressurization section, the recovery-side tank is set to the negative pressure by driving the decompression section, and the relay pump is driven. In this manner, the first circulation operation can be performed to circulate the ink in order of the supply-side tank, the supply flow path SF1, the head chip **54**, the recovery flow path SC1, the recovery-side tank, the relay flow path, and the supply-side tank. In addition, in this configuration, the pressurization discharge operation may be performed in such a manner that the supply flow path SF1 is pressurized by the pressurization section instead of the pump **159**. In the present modification example, the supply-side tank and the recovery-side tank are examples of a “liquid storage section”.

4-9. Ninth Modification Example

(195) The above-described liquid ejecting apparatus may be a 3D printer for three-dimensional modeling which ejects a photocurable resin liquid as a liquid by using an ink jet method to form a three-dimensional object. In this case, an operation for ejecting the liquid that does not form the three-dimensional object itself is an example of the preliminary ejection operation.

4-10. Other Modification Examples

(196) The liquid ejecting apparatus described above can be adopted in various equipment such as a facsimile machine and a copier, in addition to a device dedicated to printing. However, an application of the liquid ejecting apparatus of the embodiments of the present disclosure is not

limited to the printing. For example, the liquid ejecting apparatus for ejecting a solution of a coloring material is used as a manufacturing apparatus for forming a color filter of a liquid crystal display device. In addition, a liquid ejecting apparatus that ejects a solution of a conductive material is used as a manufacturing apparatus forming wiring and electrodes of a wiring substrate.

Claims

1. A liquid ejecting apparatus comprising: a plurality of nozzles configured to eject a liquid in an ejection direction; a common liquid chamber that communicates with the plurality of nozzles and extends in a first direction orthogonal to the ejection direction; a filter that partitions the common liquid chamber into an upstream chamber and a downstream chamber; an inlet for introducing the liquid into the upstream chamber; an outlet for causing the liquid to flow out from the upstream chamber; a liquid storage tank configured to store the liquid; a supply flow path that causes the inlet to communicate with the liquid storage tank; a recovery flow path that causes the outlet to communicate with the liquid storage tank; a beam that couples a pair of inner walls for defining the downstream chamber and is provided inside the downstream chamber, the pair of inner walls being separated in a second direction intersecting with the first direction when viewed in the ejection direction; and a processor configured to be programed to: perform a filling operation in which the liquid is filled in a circulation path, the circulation path including the liquid storage tank, the supply flow path, the common liquid chamber, and the recovery flow path; perform a first circulation operation in which the liquid is circulated in the circulation path; perform a pressurization discharge operation in which the liquid is discharged from the plurality of nozzles by pressurizing the supply flow path; and perform a predetermined operation in which the liquid moves inside the downstream chamber in a direction different from a direction in which the liquid inside the downstream chamber is moved by the first circulation operation, wherein the processor is configured to, in the filling operation, perform the predetermined operation after the first circulation operation is performed; and perform the pressurization discharge operation after predetermined operation is performed.
2. The liquid ejecting apparatus according to claim 1, wherein in the filling process, the pressurization discharge operation is also performed between the first circulation operation and the predetermined operation, and the predetermined operation is a preliminary ejection operation for ejecting the liquid from all or a part of the plurality of nozzles.
3. The liquid ejecting apparatus according to claim 2, wherein in the preliminary ejection operation as the predetermined operation, the liquid is ejected from all of the plurality of nozzles.
4. The liquid ejecting apparatus according to claim 2, wherein the plurality of nozzles are arranged in the first direction to form a nozzle row, the inlet is disposed in an end portion of the upstream chamber in the first direction, when viewed in the ejection direction, a nozzle group disposed closer to the inlet than the beam portion in the plurality of nozzles is divided into a first nozzle group including the nozzle disposed closest to the inlet in the nozzle group and a second nozzle group including the nozzle disposed closest to the beam portion in the nozzle group, and in the preliminary ejection operation as the predetermined operation, the liquid is ejected from the plurality of nozzles belonging to the first nozzle group.
5. The liquid ejecting apparatus according to claim 2, wherein in the filling process, the amount of the liquid discharged from the plurality of nozzles by the pressurization discharge operation performed after the predetermined operation is smaller than the amount of the liquid discharged from the plurality of nozzles by the pressurization discharge operation performed between the first circulation operation and the predetermined operation.
6. The liquid ejecting apparatus according to claim 1, wherein the predetermined operation is a second circulation operation for circulating the liquid in a direction opposite to a direction in which the liquid is moved by the first circulation operation.

7. The liquid ejecting apparatus according to claim 6, wherein in the filling process, a period during which the second circulation operation is performed is shorter than a period during which the first circulation operation is performed.
