

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12417453
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Livingston; Edward Neil et al.

Methods and systems of using sub-domains to federate device credentials scoped to a common domain

Abstract

A computer-implemented method for authenticating a user device via a device credential scoped to a common domain shared among a plurality of payment networks may be provided. The method may include receiving, by a server of a payment network, a first request redirected from a sub-domain assigned to the payment network to a domain name associated with the payment network, responsive to the first request, transmitting, to the user device, an authentication request comprising a challenge, a user identifier that identifies the user, and the common domain to which the device credential is scoped, receiving, from the user device, a response, accessing the device credential, the device credential having been stored by the payment network, validating the response based on the device credential, and causing, by the server, the user identifier and the device credential to be federated to the other ones of the plurality of payment networks based on the validating.

Inventors: Livingston; Edward Neil (Fife, GB), Macdonald; Rory (Cumbernauld, GB), Ouellette; Robert (Westwood, NJ), Lim; Grace (Morganville, NJ), Pacher; Fred M. (Williston Park, NY)

Applicant: MASTERCARD INTERNATIONAL INCORPORATED (Purchase, NY)

Family ID: 1000008820267

Assignee: MASTERCARD INTERNATIONAL INCORPORATED (Purchase, NY)

Appl. No.: 18/523393

Filed: November 29, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240095729 A1	Mar. 21, 2024

Related U.S. Application Data

Publication Classification

Int. Cl.: G06Q20/38 (20120101); G06Q20/40 (20120101)

U.S. Cl.:

CPC G06Q20/388 (20130101); G06Q20/3829 (20130101); G06Q20/401 (20130101); G06Q2220/00 (20130101)

Field of Classification Search

CPC: G06Q (20/388); G06Q (20/3829); G06Q (20/401)

USPC: 705/75

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2014/0136309	12/2013	Goldman et al.	N/A	N/A
2019/0139044	12/2018	Piel	N/A	N/A

OTHER PUBLICATIONS

International Search Report and Written Opinion issued in corresponding International Application No. PCT/US2021/064267, dated Apr. 19, 2022. cited by applicant

Primary Examiner: Jones; Courtney P

Attorney, Agent or Firm: Pillsbury Winthrop Shaw Pittman LLP

Background/Summary

CROSS REFERENCE TO RELATED APPLICATION (1) This application is a divisional of U.S. Non-Provisional patent application Ser. No. 17/140,818; filed on Jan. 4, 2021, and entitled “METHODS AND SYSTEMS OF USING SUB-DOMAINS TO FEDERATE DEVICE CREDENTIALS SCOPED TO A COMMON DOMAIN”, the entire contents of which is incorporated herein by reference in its entirety.

BACKGROUND

(1) A remote commerce transaction is a payment transaction in which a user does not interact with a physical payment terminal, such as when making an online purchase. Processing the remote commerce transaction may involve obtaining payment information and authenticating a user. Processing techniques may vary from one merchant to another merchant and even from one payment network to another payment network, delivering an inconsistent experience for the user that may be vulnerable to phishing and other types of attacks.

(2) One way to secure the remote commerce transaction is to perform multi-factor authentication,

which may include authenticating user on their device to conduct the remote commerce transaction. Authenticating the user device may involve registering the user device to create a device credential and then later authenticating the device credential. However, in order to prevent phishing and other attacks, the registering party and the authenticating party may be required to be on the same domain or sub-domain. Put another way, the device credential may be scoped to the domain or sub-domain. The result is that a user may be required to register the user device for each merchant or payment network which are more disruptive to the end user.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) Features of the present disclosure may be illustrated by way of example and not limited in the following figure(s), in which like numerals indicate like elements, in which:
- (2) FIG. 1 illustrates an example of a system of creating and federating a device credential scoped to a common domain and authenticating a user device across parties that use the federated device credential;
- (3) FIG. 2 illustrates a data flow diagram of redirecting from sub-domains respectively assigned to payment networks to domain names of the payment networks to facilitate the federation of a scoped credential across the payment networks;
- (4) FIGS. 3A and 3B illustrate data flow diagrams that together are an example of registering a user device to generate a device credential to be federated;
- (5) FIG. 4 illustrates a data flow diagram of an example of user-facing creation of a device credential based on sub-domains;
- (6) FIGS. 5A and 5B illustrate data flow diagrams that together are an example of authenticating a user device based on a federated device credential;
- (7) FIG. 6 illustrates a data flow diagram of an example of user-facing authentication of a device credential based on sub-domains of the common domain;
- (8) FIG. 7 illustrates an example of an architecture for federating a device credential based on sub-domains of the common domain;
- (9) FIG. 8 illustrates a data flow diagram of an example of processing a remote commerce payment transaction;
- (10) FIG. 9 illustrates an example of a computer system;
- (11) FIG. 10 illustrates an example of a method of creating a device credential scoped to the common domain and federating the device credential; and
- (12) FIG. 11 illustrates an example of a method of authenticating a user device based on the federated device credential scoped to the common domain.

DETAILED DESCRIPTION

(13) The disclosure herein relates to methods and systems of federating scoped device credentials among relying parties by assigning each relying party to a sub-domain of a common domain. A relying party may refer to a registering party that registers a device to create a device credential or an authenticating party that authenticates the user device based on the device credential. A relying party may include a payment network, a merchant, and/or other participating parties that may register or authenticate a user device. Such registration or authentication may be in connection with a remote commerce transaction involving the user device.

(14) The methods and systems disclosed herein may leverage the security offered by a scoped device credential and facilitate federation across relying parties despite the scope limitation, improving the efficiency of the registration and authentication process. For example, a scoped device credential may be resistant to phishing attacks since a user is unable to inadvertently release the device credential and a malicious actor would be unable to otherwise access the device

credential because of the scope limitation. Federation of the scoped device credential may improve the efficiency of the registration and authentication because a user device may be registered to create and federate a device credential at any participating registering party. Likewise, once registered, the user device may be authenticated by any participating authenticating party. Thus, federation of the scoped device credential may eliminate having to register the user device for each merchant, payment network or other relying party, such as when processing remote commerce transactions.

(15) To federate a scoped device credential, an entity may establish a common domain. A sub-domain of the common domain may be assigned to each participating relying party. The assignment may be made by the entity or a trusted participating relying party. A participating relying party may map its assigned sub-domain name to a domain name (such as a universal resource locator that resolves to an IP address) associated with the participating relying party. The participating relying party may then expose an authentication interface at the domain name. Requests made to the sub-domain may be redirected, such as via a Domain Name System (DNS) lookup, to the domain name. Thus, requests made to the sub-domain may be redirected to the authentication interface exposed by the relying party.

(16) The authentication interface may then perform registration and/or authentication operations by specifying the common name as a relying party identifier. Because a sub-domain is within the scope of a parent domain name (in this case, the common domain), the device credential scoped to the common domain may be enforced when communicating with any authentication interface that is reachable at its assigned sub-domain.

(17) When a relying party registers a user device, the relying party may federate the resulting device credential, which may be scoped to the common domain, to other relying parties. Thus, the user device need not be registered at other participating relying parties. In some examples, each relying party may trust the registering party's registration. In other examples, each relying party may independently authenticate the federated device credential without having to re-register the user device. To illustrate scope enforcement, registration, and authentication, an example of a network authentication combination, the WebAuthn standard and the FIDO2 specification, will be described. Other authentication standards and techniques that use scoped device credentials may be used as well or instead of the WebAuthn standard and the FIDO2 specification.

(18) A user device implementing the WebAuthn standard may include an agent such as a web browser that includes a WebAuthn Application Programming Interface (API) that communicates with an authenticator. The authenticator may include a platform authenticator that authenticates a user through biometric and/or other authentication technique enabled on the device. The platform authenticator may be used for other user authentication functions such as to unlock the user device. The authenticator may generate a FIDO2 credential to register user device. The FIDO2 credential may be scoped to a domain name of a participating registering party.

(19) When an unregistered user device communicates with a merchant who is a participating relying party or uses another participating relying party that acts on behalf of the merchant, the merchant may trigger device authentication by making an API create call to the WebAuthn API. The API create call may specify the common domain as the relying party identification (RPID) for scoping purposes. Responsive to the API create call, the WebAuthn API may cause the authenticator to authenticate the user and generate a FIDO2 credential. When returning the FIDO2 credential to the relying party, the authenticator and/or the agent may enforce the scope by inspecting an origin of the outbound transmission back to the calling party (the merchant) to ensure that the origin is within the scope of the common name. In this case, the sub-domain assigned to the merchant will be within the scope of the common name.

(20) The FIDO2 credential may be federated by the merchant to the other relying parties, such as via a JavaScript Object Notation (JSON) web token. After the FIDO2 credential is federated, when the user device visits another relying party or the same relying party, that relying party may,

through its authentication interface, trigger an authentication of the device credential. For example, the other relying party may transmit an API get call to the WebAuthn API for authentication. The relying party may then authenticate a response to the API get call to verify the identity of the user device. Having described a brief description of examples of the methods and systems described herein, attention will now turn to an example of a system that facilitates federation of a scoped device credential.

(21) FIG. 1 illustrates an example of a system **100** of creating and federating a device credential scoped to a common domain and authenticating a user device across relying parties that use the federated device credential. The system **100** may implement a network authentication specification, which may specify use of a scoped credential that limits who or what may access and use the scoped credential. The network authentication specification may include the WebAuthn/FIDO2 specification (in which case the device credential may include a FIDO2 credential), although other network authentication specifications that employ scoped credentials may be used as well. The system may also employ interoperability between various relying parties to facilitate “click-to-pay” functionality in which a user's payment information such as credit card numbers and other forms of payment identifiers may be registered and stored in a user profile, thereby establishing a virtual wallet. These and other benefits may be generally referred to as “secure remote commerce” (SRC) processing. SRC processing may be combined with the network authentication specification and federation of scoped credentials to provide improved secure and seamless remote commerce transactions such as click-to-pay functionality with federated device credentials across various relying parties. It should be noted, however, that the term “SRC” in various system components described herein does not intend to be limited to any specific authentication implementation. Rather, the term SRC may denote that the component participates in remote commerce transaction integration with other relying parties.

(22) Furthermore, in the examples disclosed herein throughout, the payment networks **130** are illustrated as both relying and authenticating parties for illustrative convenience. It should be noted, however, that other parties such as the merchant **120** may be a relying and/or authenticating party. In these examples (not illustrated), the merchant **120** and/or others may implement some or all of the illustrated features of the payment network **130**.

(23) The system **100** may include a user device **110**, a plurality of merchants **120** (individually illustrated as merchants **120A, B, N**), one or more Secure Remote Commerce (SRC) Initiators (SRCI) **122** (individually illustrated as SRCI **122A,B,N**), a plurality of payment networks **130** (individually illustrated as payment networks **130A, B, N**), a Domain Name System (DNS) **140**, a mapping table **142**, and/or other components. The components of the system **100** may be connected to one another via a communication network **107**, which may include the Internet, an intranet, a PAN (Personal Area Network), a LAN (Local Area Network), a WAN (Wide Area Network), a SAN (Storage Area Network), a MAN (Metropolitan Area Network), a wireless network, a cellular communications network, a Public Switched Telephone Network, and/or other network through which system **100** components may communicate.

(24) The user device **110** may include a device such as a smartphone, a tablet device, a wearable device, a personal computer, and/or other device having computational and storage capabilities to generate, store, and use device credentials that are federated across the payment networks **130**. The user device **110** may facilitate purchase transactions with one or more merchants **120** via one or more of the payment networks **130**. For example, a user may use the user device **110** to purchase goods and/or services at a digital shopping application such as a remote commerce webpage of the merchant **120** over the communication network **107**.

(25) The user device **110** may include an agent **112**, an authentication Application Programming Interface (API) **114** (illustrated as Auth. API **114**), and an authenticator **116**. The agent **112** may include an application such as a web browser of the user device **110**. The agent **112** may include the authentication API **114**. The authentication API **114** may expose API calls that may control

operations of the authenticator **116**. For example, a remote application may transmit, via the communication network **107**, client-side scripts such as JavaScript executing on the agent **112** that makes the API calls. The API calls may include, among others, an API create call and an API get call.

(26) Responsive to the API create call, the authenticator **116** may generate a key pair that includes a public key **103** (which may serve the basis for the device credential) and a private key **105** (which may be used to authenticate the user device **110** by showing possession of the private key **105**). The public key **103** may be shared with the calling party (such as the remote interface) or others. The private key **105** may not be shared. Instead, the private key **105** may be stored at the user device **110** such as by the authenticator **116**. Data digitally signed (cryptographically encrypted) using the private key **105** of the key pair may be decrypted by the public key **103** of the key pair to obtain the unsigned, original, data. Thus, decryption of digitally signed data using the public key **103** may provide proof that the signing authority (the authenticator **116**) has possession of the private key **105** and therefore is a trusted source of the key pair. In some examples, the authenticator **116** may generate a FIDO2 credential used as the device credential. Other types of device credentials may be used as well, so long as they may be scoped as described herein.

(27) In addition to generating device credentials, the authenticator **116** may include hardware and/or software to authenticate an identity of a user of the user device **110**. In some examples, the authenticator **116** may include a platform authenticator integrated with the user device **110**. In these examples, the authenticator **116** may authenticate a user to perform authentication functions such as unlocking the user device **110** that depend on user identity authentication. Also, in these examples, the authenticator **116** may authenticate the user based on biometric authentication such as a fingerprint, face identification, or other biometric information, a Personal Identification Number (PIN), and/or other authentication techniques that are integrated with the user device **110**. In some examples, the authenticator **116** may include a roaming authenticator that is a standalone device, such as a key fob style token device that communicates with the agent **112**.

(28) In some examples, the agent **112** and/or the authenticator **116** may enforce the scope of the device credential. For example, the agent **112** and/or the authenticator **116** may ensure that inbound communications originate from a domain name that matches the scope of the device credential. Alternatively, or additionally, the agent **112** and/or the authenticator **116** may ensure that outbound communications are destined to a domain name that matches the scope of the device credential.

(29) The agent **112** may be used to browse a purchase interface of a merchant **120**. Each merchant **120** may be a registered SRC merchant. A registered SRC merchant may refer to a merchant that is registered to accept SRC payment transactions. An SRC payment transaction may refer to a payment transaction facilitated by the SRC servers **134A-N** and processed through the relevant payment networks **130A-N**. The purchase interface of the merchant **120** may include an SRC payment option that when selected invokes an SRCI **122** that may initiate SRC payments on behalf of the merchant **120**. For example, each merchant **120** may encode in their webpage an option that invokes its corresponding SRCI **122**.

(30) An SRCI **122** may refer to an interface (such as instructions that encode a graphical user interface or portion thereof) that initiates SRC payment transactions. The SRCI **122** may be operated by the merchant **120** directly or may be operated by another entity acting on behalf of the merchant **120** such as a payment service provider, a payment gateway, a payment acquirer, and/or other entities. Regardless of which entity operates the SRCI **122**, the SRCI **122** may interact with a digital payment application (DPA) operating at the purchase interface of the merchant **120** and SRC server **134A** (or equivalents at payment networks **130B,N**) to initiate and complete checkout on behalf of the merchant **120**. An SRCI **122** may also facilitate discovery and selection of payment options such as payment cards.

(31) Upon selection of the SRCI payment option (such as selection of a “c-2-pay” option), the SRCI **122** may determine whether the consumer and their device (or browser) is recognized. If so,

and a device credential exists for the device **110**, the device credential may be authenticated as described herein. Upon authentication of the device credential, the payment cards stored with the consumer's user profile (stored at user profile database **139**) are displayed. If the device is unrecognized, the SRCI checkout process will ask the cardholder for their email address, then communicate with a payment network **130** (via the common JavaScript library) participating in SRC to establish which, if any, the cardholder has registered to use. If the cardholder has used an SRC checkout on the device before (and accepted a "Remember me" option) then a browser cookie may be used to identify the returning user.

(32) The SRCI **122** may then transfer the flow to the appropriate Digital Card Facilitator (DCF). API calls will also be made between the SRCI **122** and the appropriate SRC entity, such as a payment network **130**.

(33) In some examples, the SRCI **122** may integrate with one or more interfaces of the payment networks **130**, which may include payment card networks such as the Mastercard® network and other payment card networks. For illustrative convenience, only payment network **130** (payment network **130A**) is illustrated with further detail in FIG. **1**. It should be noted that the other payment networks **130B,N** may be similarly configured and may each operate similarly to authenticate, federate and use a device credential. An example of processing payments via a payment network **130** is illustrated at FIG. **8**.

(34) To facilitate the creation and use of a federated device credential, the payment network **130A** may include one or more servers, a user profile database (DB) **139**, and/or other components. The one or more servers may include a digital card facilitator (DCF) **132A**, an SRC server **134A**, an authentication server **138A** (illustrated as auth. server **138A**), and/or other servers.

(35) The DCF **132A** may provide an interface for adding, removing, or updating a user profile of a user, which may be stored at the user profile database **139A** along with other user profiles of other users. A user profile of a user may refer to information that may be prestored to facilitate payment transactions of a user through the payment networks **130**. For example, a user profile of a user may include user identifying information, a payment credential that includes payment information (such as credit card numbers, expiration dates, and CCV codes), shipping addresses, device credential identifiers associated with the user, and/or other information to facilitate user payment transactions through the payment networks **130**. It should be noted that, through the DCF **132A**, a user may add multiple forms of payment, such as multiple credit cards, to a user profile of the user.

(36) The SRC server **134A** may provide interfaces to link together various components of the system **100** to register and authenticate a scoped device credential for the user device **110** to facilitate payment transactions over the payment networks **130**. For example, the SRC server **134A** may expose an authentication interface **136A** that is reachable through the domain name **131A**. The authentication interface **136A** may communicate with the agent **112** through API calls to the authenticator API **114** to control operations of the authenticator **116**. The authentication interface **136A** may communicate responses to the API calls to the authentication server **138A**, which may authenticate the responses to authenticate the device credential from the authenticator **116**. Upon authentication, the authentication server **138A** may notify the SRC server **134A** of such authentication.

(37) In response, the SRC server **134A** may generate a token and federate the token using any of various federation techniques. In some examples, the SRC server **134A** may transmit the token to the SRCI **122**, which may federate the token after device credential authentication. In some examples, the token may be updated to include authentication information such as the user identification of an authenticated user, the challenge and the credential details. The token may be digitally signed by the SRC server **134A** using a private key (similar to the private key **105**) of the SRC server **134A**. Other SRC servers of other payment networks **130B,N** may authenticate the token via a public key (similar to the public key **103**) of the SRC server **134A**. In a particular example, the SRC server **134A** may update a JSON web token (JWT) with the challenge and

credential details. The JWT may then be provided to other relying parties, such other payment networks **130A-N**, through various JSON interfaces. Other types of tokens that may convey the token information between the payment networks **130** may be used as well. In another example, to federate the device credential, the SRC server **134A** may store the challenge and credential details to a federated DBMS accessible to the payment networks **130**. Based on the federated token, other payment networks **130B,N** may independently authenticate the user device **110** without the user registering the user device **110** for each of the other payment networks **130B,N**.

(38) However, a payment network **130** may be unable to independently authenticate the user device **110** based on the now federated device credential that may be scoped to the domain name **131** of another payment network **130** that caused creation of the device credential because of the payment networks **130** may be associated with respective domain names **131**. For example, payment network **130A** may include the Mastercard® network. In this example, the payment network **130A** may be associated with the domain name **131A**, which may include “mastercard(.)com” with parentheses added. Similarly, payment network **130B** corresponding to another payment card network may be associated with the domain name **131B**, which may include “paymentcard(.)com” with parentheses added, and so on. Because of these different domain names, federation of a scoped credential across the payment networks **130** may not be possible.

(39) To federate a scoped credential across the payment networks **130**, an entity may establish a common domain **101**, which the payment networks **130** may use to scope the creation of the device credential. The entity may include one or more operators of the payment networks **130** or others. The entity may assign each payment network **130A-N** with a respective sub-domain **111** (individually illustrated as sub-domains **111A, B, N**). For example, the payment network **130A** may be assigned with sub-domain **111A**, the payment network **130B** may be assigned with sub-domain **111B**, and the payment network **130N** may be assigned with sub-domain **111N**. Each of the sub-domains **111A-N** may be a sub-domain of a common domain **101**. Accordingly, each sub-domain **111** may be within the same scope of the common domain **101**. The entity may be responsible for adding other sub-domains for other payment networks **130** that wish to participate in the federated credentialing described herein. A mapping table **142** (or portion of the mapping) between the sub-domains **111** and respective domain names **131** may be maintained, stored, or otherwise accessed by each of the payment networks **130A**.

(40) To facilitate redirection of the sub-domains **111** to an appropriate domain name **131A**, the entity may set up a canonical name (CNAME) record in a Domain Name System (DNS) **140**. For example, a CNAME record may specify the sub-domain **111A** as an alias of domain name **131A**, which is a canonical name for the sub-domain. In turn, the domain name **131A** may be an alias to an Internet Protocol (IP) address that resolves to an authentication interface **136A** of the payment network **130A**. When a DNS resolver of the DNS **140** receives the sub-domain name **111A** and queries a DNS table or cache for the sub-domain name **111A**, the DNS resolver may access the Canonical Name (CNAME) record and determine that it is an alias of a canonical name (the domain name **131A**). The DNS resolver may then search for the domain name **131A** and determine that it is an alias of an IP address, which resolves to the authentication interface **136A**. Thus, the DNS **140** may redirect requests from the sub-domain **111A** to the domain name **131A** (ultimately to the IP address aliased by the domain name **131A**). The entity may maintain the common domain **101** to ensure that unwanted parties (such as malicious actors) are unable to add sub-domains to the common domain **101**.

(41) FIG. 2 illustrates a data flow diagram **200** of redirecting from sub-domains **111A-N** respectively assigned to payment networks **130** to domain names of the payment networks to facilitate the federation of a scoped credential across the payment networks **130**. In the illustrated examples of FIG. 2, the agent **112** may be instructed to browse to a sub-domain **111A**, which may include the sub-domain “srcA(.).example(.).com” with the parentheses omitted. The sub-domain **111A** may be assigned to the payment network **130A**. The agent **112** may browse to the sub-domain

111A by, for example, transmitting a Hyper Text Transfer Protocol (HTTP) request directed to the sub-domain **111A**. The sub-domain **111A** may be redirected to the domain name **131A**, such as by the DNS **140** illustrated in FIG. 1. The domain name **131A** may resolve to an authentication interface **136A** provided by the payment network **130A**.

(42) The authentication interface **136A** may transmit API calls to the authentication API **114** operating at the agent **112**. In other examples, the agent **112** may be instructed to browse to a sub-domain **111B**, which may include the sub-domain “srcB(.)example(.)com” with the parentheses omitted. The agent **112** may browse to the sub-domain **111B**, which may be redirected to the domain name **131B**, such as by the DNS **140** illustrated in FIG. 1. The domain name **131B** may resolve to an authentication interface **136B** (similar to the authentication interface **136A** illustrated in FIG. 1) of the payment network **130B**. Likewise, the agent **112** may be instructed to browse to a sub-domain **111N**, which may include the sub-domain “srcN(.)example(.)com” with the parentheses omitted. The agent **112** may browse to the sub-domain **111N**, which may be redirected to the domain name **131N**, such as by the DNS **140** illustrated in FIG. 1. The domain name **131N** may resolve to an authentication interface **136N** (similar to the authentication interface **136A** illustrated in FIG. 1) of the payment network **130N**.

(43) The API calls from any of the authentication interfaces **136A-N** may include the common domain **101** as the value of the RPID and may be made through respective sub-domains **111A-N**. Thus, API create calls may result in the generation of a public key **103** that is scoped to a credential on the common domain **101**. Likewise, API get calls may be used to authenticate device credentials scoped to the common domain.

(44) FIGS. 3A and 3B illustrate data flow diagrams **300A** and **300B** that together are an example of registering a user device **110** to generate a device credential to be federated. As used in the examples that follow, the term “transfer” may refer to one component providing an instruction to a receiving component to communicate with an intended destination. For example, a server may cause a browser to “transfer” to a destination URL by providing instructions, or scripts, for the browser to do so. An example of such instruction to transfer may include an HTTP redirect instruction, which is not to be confused with the redirect, which may be facilitated by the DNS **140**, from a sub-domain **111** to a domain name **131**. The term “invoke” may refer to a component initiating functionality of another component. For example, a web browser may make a request to a destination URL to access functionality of an application of the destination URL.

(45) Referring first to FIG. 3A, at **302**, a purchase interface associated with the merchant **120** may be transmitted to the agent **112** of the user device **110**. For example, a website checkout of the merchant **120** may be transmitted to a web browser of the user device **110** to complete an online purchase transaction. The purchase interface may include an option to enroll in SRC payments so that the user may use “c-2-pay” functionality with SRC payments.

(46) At **304**, upon selection by the user of the option to enroll in SRC payments, the agent **112** may be transferred to an SRCI **122** that initiates SRC payments on behalf of the merchant **120**. For example, the agent **112** may browse to an address such as a URL of the SRCI **122**. The transfer may include a checkout payload, which may include purchase details such as item identifiers that identify items to be purchased in an electronic cart, which may be retained through various transfers described in the data flow diagrams **300A,B** so that the checkout payload may be returned back to the purchase interface once the user has enrolled in SRC payments and/or the user device **110** has been registered to generate a device credential.

(47) At **306**, the SRCI **122** may transfer the agent **112** to the DCF **132A** of an appropriate payment network **130** with which the SRCI **122** may be integrated.

(48) At **308**, the DCF **132A** may collect payment and user profile information. For example, the DCF **132A** may provide one or more interfaces to the agent **112** that provide user inputs that receive payment information, such as credit card number, expiration date, and Card Verification Value (CVV) code. The one or more interfaces may also provide user inputs that receive user

profile information such as user identifying information, billing information, shipping information, and/or other information.

(49) At **310**, the DCF **132A** may store the payment and user profile information in the user profile database **139A** (illustrated in FIG. 3A as “**139A**” for convenience). The user profile database **139A** may be consulted after the user is enrolled to automatically recall the payment information, user profiling information, and/or other information collected by the DCF **132A** at block **308**. In some examples, the DCF **132A** may perform authentication via one-time-password or other authentication.

(50) In some examples, after or in conjunction with collection and storage of the payment and user profile information, and in some instances after authentication, the DCF **132A** may provide an input option to register the user device **110** to enable device authentication.

(51) At **312**, the agent **112** may transmit a request to the DCF **132A** to register the user device **110** for device authentication upon user selection of the input option, indicating verification to register.

(52) At **314**, the DCF **132A** may identify the sub-domain **111A** assigned to the payment network **130A**. For example, the DCF **132A** may store all or a portion of the mapping table **142** illustrated in FIG. 1 and/or may otherwise access the mapping table **142**. In particular, the DCF **132A** may determine that the sub-domain **111A** has been assigned to the network **130A** and the DCF **132A** may route the agent **112** to the identified sub-domain **111A**. For example, the DCF **132A** may provide instructions to the agent **112** to browse to the sub-domain **111A**.

(53) At **316**, the sub-domain **111A** may be redirected to domain name **131A**. The domain name **131A** may resolve to the authentication interface **136A**. The authentication interface **136A** may make API calls to the authentication API **114** to create a device credential to be federated to other payment networks **130B,N**.

(54) Referring now to the data flow **300B** illustrated at FIG. 3B, at **318**, the authentication interface **136A** may transmit, to the authentication API **114**, an API create call to generate a device credential. The API create call may include, among other things, a challenge, an RPID, user identifying information such as a user identifier used in the user profile database **139A**, and/or other information for configuring parameters of credential creation. The challenge may include a randomly generated string. The authentication server **138A** may set the value of the RPID to be the common domain **101**.

(55) An example of the API create call appears in pseudocode below. It should be noted that the API create call (and other examples API calls illustrated herein) may include different or other values and code. The pseudocode is therefore provided for illustrated purposes to show the types of data that may be conveyed by the API call:

(56) TABLE-US-00001 navigator.credentials.create ({ publicKey: { challenge: “4f79bba7-ff66-4910-b2de-250991d89db6”, timeout: 20000, authenticatorSelection: { userVerification: “required”, authenticatorAttachment: “platform” } attestation: “direct”, user: { id: “07b4cfcf-a841-441e-b9be-b36c55df881c”, name: “name@emaildotcom”, displayName: “name@emaildotcom” }, pubKeyCredParams: [{ alg: -7, type: “public-key” }], rp: { name: “SRC” id: “example(.)com” } } })

(57) At **320**, the authentication API **114** may transmit a credential create request to the authenticator **116**.

(58) At **322**, the authenticator **116** may authenticate the user. For example, the authenticator **116** may require the user to input authentication information such as by inputting biometric information (such as a fingerprint, facial feature, retinal feature, and/or other biometric information), secret information such as a PIN, and/or other authentication information. If the user fails to authenticate, the authenticator **116** may return an error response (not illustrated).

(59) At **324**, the authenticator **116** may generate a new key pair, such as the public key **103** and the private key **105**. Generation of the new key pair may indicate that the user has been authenticated by the authenticator **116** (at **322**). Thus, the key pair may be associated with the user identifier that

identifies the user. The authenticator **116** may also generate a credential identifier that identifies the public key **103**. The public key **103** may serve as the basis for the device credential to be federated. The private key **105** may be stored by the authenticator **116**, and not shared outside the authenticator **116**. To establish trust that the authenticator **116** created the new key pair, the authenticator **116** may digitally, such as cryptographically, sign the challenge from the API create call with a private key (similar in terms of key cryptography to the private key **105**) of the authenticator **116**. A relying party may then determine whether the authenticator **116** signed the challenge based on a corresponding public key of the authenticator **116**.

(60) In some examples, the authenticator **116** may enforce the scope of the public key **103** (and therefore the scope of the device credential) by comparing the RPID included in the API create call and the create request with a domain name from which the API create call was made. Because the domain name is made by the authentication server **138A** (which was redirected from the sub-domain **111A** of the common domain **101**), the authenticator **116** may validate that the origin of the API create call matches the RPID. In this way, the authenticator **116** may ensure that an entity that made the API create call has not provided (maliciously or mistakenly) an RPID that does not match an origin domain name. In these examples, responsive to such validation, the authenticator **116** may store the public key **103** in association with the newly created credential for the RPID to ensure that the public key **203** is scoped to the RPID, the value of which may be the common domain **101**. It should be noted that communications to or from the authenticator **116**, the authentication API **114** (and therefore the agent **112** where the authentication API **114** is part of the agent **112**) may be similarly validated for scope. Thus, the authenticator **116** and the agent **112** may individually or together enforce the scope of device credentials.

(61) At **326A** and **326B**, the authenticator **116**, via the authentication API **114**, may transmit an attestation response that may include the public key **103**, the digitally signed data based on the challenge, the credential identifier, and/or other data back to the authentication interface **136A**. For example, the attestation response may include a WebAuthn attestation response that encodes user and/or credential objects according to the FIDO2 or other credential generated by other credential specifications.

(62) At **328**, the authentication interface **136A** may provide the attestation response to the authentication server **138A**, which may decode the attestation response according to the FIDO2 or other credential specification. The authentication server **138A** may validate the device credential (such as the public key **103**) by decrypting the all or a portion of the decoded attestation response to ensure that the challenge was properly returned. Upon validation of the device credential, the authenticator server **328A** may provide a notification of such validation to the SRC server **134A** (not shown in FIG. 3A or 3B). Responsive to the notification, the SRC server **134A** may generate and share token information with payment networks **130B,N**. The token information may include the device credential, the credential identifier, the user identifier, any attestation data from the authenticator **116**, and/or other information relating to the public key **103**. In some examples, the SRC server **134A** may generate a JSON web token (JWT) based on the token information and share the JWT with other payment networks **130B,N**, such as through the SRCI **122**.

(63) At **330**, the authentication interface **136A** may return the checkout payload back to the merchant **120** so that the merchant **120** may complete the purchase transaction with the user device **110**.

(64) FIG. 4 illustrates a data flow diagram **400** of an example of user-facing creation and federation of a device credential based on sub-domains. The data flow diagram **400** illustrates various interfaces and therefore experience of a user while enrolling in SRC payments and registered the user device **110** for authenticating the user device as shown in data flow diagrams **300A** and **300B** respectively illustrated at FIGS. 3A and 3B.

(65) At **402**, the merchant **120A** may provide an application interface **401** to the user device **110** to make the purchase. The application interface **401** may include a website rendered by the agent **112**

(such as a web browser) of the user device **110**. The application interface **401** may include a selection option **405** associated with SRC payments (such as a “c-2-pay” button).

(66) At **404**, upon selection of the selection option **405** (such as a user clicking the c-2-pay button), the application interface **401** may cause the agent **112** to transfer to the appropriate SRCI **122**, which facilitates SRC payments on behalf of the merchant **120**. As previously noted, the merchant **120** may operate the SRCI **122**, such as from a server or other device of the merchant **120**, or the SRCI **122** may be operated by another entity such as payment service provider to execute SRC transactions on behalf of the merchant **120**.

(67) At **406**, the SRCI **122** may determine that the user device **110** has not enrolled to participate in SRC payments. For example, the SRCI **122** may determine whether a cookie or other data is stored at the user device **110** to indicate enrollment to participate in SRC payments. If the user device **110** is not enrolled to participate in SRC payments, the SRCI **122** may provide the user device **110** with an interface (which may be displayed via the agent **112**) to obtain payment information **413** from the user. The payment information may include a credit card number, an expiration date, and/or other payment information to be used for SRC payments. It should be noted that if the user device **110** is enrolled to participate in SRC payments, then processing may proceed as described in data flow diagrams **500A** and **500B** respectively illustrated at FIGS. **5A** and **5B**.

(68) Still referring to **406**, the SRCI **122** may identify an appropriate DCF **132** based on the payment information. For example, the payment information may include a Mastercard® credit card number, in which case the SRCI **122** may identify the DCF **132A** that corresponds to the Mastercard® payment network. If the payment information included a credit card number associated with another payment network, then the SRCI **122** may identify another DCF **132** (such as DCF **132B** or **N**) corresponding to the other payment network.

(69) At **408**, the SRCI **122** may transfer the user device **110** to the identified DCF **132A**.

(70) At **410**, the DCF **132A** may provide the user device **110** with an interface **411** (which may be displayed via the agent **112**) to obtain user profile information **415** relating to the user. The user profile information may include a billing address, a shipping address, a user identification, a user electronic mail address, a phone number, and/or other user information. It should be noted that the payment information **413** and the profile information **415** may be collected from the user using different interfaces. In some examples, the payment and profile information may be stored in the user profile database **139A**. In some examples, a cookie or other data may be stored at the user device **110** to indicate enrollment in SRC payments responsive to collection of the payment and profile information. In some examples, the DCF **132A** may perform one-time password or other authentication via a user electronic mail address, SMS text message, or other secondary user identity authentication.

(71) At **412**, upon completion of the user profile information and any authentication of the user profile information, the DCF **132A** may provide an interface **421** to the user device **110**. The interface **421** may include a continue to checkout option (illustrated as “checkout option **423**” for illustrative convenience) or an enroll option **425**. Selection of the checkout option **423** may cause the DCF **132A** to direct the user device **110** to the application interface **401** without enrolling in federated credential authentication (only enrolling payment and profile information).

(72) At **414**, responsive to selection of the enroll option **425**, the DCF **132A** may transfer the user device **110** to the assigned sub-domain **111A** of the payment network **130A**. For example, the DCF **132A** may provide the agent **112** of the user device **110** with the sub-domain **111A** and an instruction to browse to the sub-domain **111A**. In response, the agent **112** may transmit a request, such as an HTTP request, directed to the sub-domain **111A**. The request may be redirected from the sub-domain **111A** to the domain name **141A**, as illustrated in FIG. **2**, for example. The redirection may be facilitated by the DNS **140** or via DNS table accessible to the user device **110**. The domain name **141A** may resolve to the authentication interface **136A**.

(73) At **416**, the authentication interface **136A** may make API calls to the authentication API **114** of

the agent **112**. Through the API calls and responses to the API calls, the authentication application **136A** may cause the user device **110** to authenticate the user via fingerprint or other user identity. The authentication application **136A** may provide the user device **110** with a confirmation interface **341** to indicate identity authentication.

(74) At **418**, the authentication interface **136A** may make further API calls to create and provide a device credential, which may then be federated by the SRC server **134A** to other ones of the payment networks **130B,N**. An example of generation and federation of a device credential is described further with respect to the data flow diagrams **300A** and **300B** respectively illustrated in FIGS. **3A** and **3B**. At **420**, the SRC server **134A** may return a checkout payload to the purchase interface **401** of the merchant to complete the checkout via a confirm order input **407**.

(75) FIGS. **5A** and **5B** illustrate data flow diagrams **500A** and **500B** that together are an example of authenticating a user device based on a federated device credential.

(76) With reference first to FIG. **5A**, at **502**, a purchase interface associated with the merchant **120** may be transmitted to the agent **112** of the user device **110**. For example, a website checkout of the merchant **120** may be transmitted to a web browser of the user device **110** to complete an online purchase transaction. The purchase interface may include an option to select an SRC payment option for which the user has enrolled. It should be noted that the user may enroll one or more SRC payment options for one or more payment networks **130A-N**. Such enrollment may have been made via the data flow diagrams **300A** and **300B** respectively illustrated in FIGS. **3A** and **3B**.

(77) At **504**, the agent **112** may receive a selection of an SRC payment option, such as a particular credit card of a user processed on a payment card network like the Mastercard® network processed through the SRC server **134A**.

(78) At **506**, the agent **112** may invoke the SRCI **122** associated with the merchant **120** and/or the SRC server **134A** associated with the SRC payment option selected at **504**. The SRCI **122** may route the agent **112** to the sub-domain **111A** assigned to the SRC server **134A**.

(79) At **508**, the sub-domain **111A** may be redirected to domain name **131A**. This redirection may be similar to the way in which redirection occurs at block **316** illustrated at FIG. **3A**.

(80) At **510**, the authentication interface **136A** may transmit an API get call to authenticate the user device **110**. The API get call may include, among other things, a challenge, an RPID, and binding information (such as a credential identifier and/or a type of credential to be authenticated) to identify a device credential to be authenticated. The challenge may include a randomly generated string. The authentication server **138A** may set the value of the RPID to be the common domain **101**.

(81) The API get call may cause the authenticator **116** to provide the public key **103** scoped to the common domain **101**.

(82) TABLE-US-00002 navigator.credentials.get({ publicKey: { challenge: “4f47f90-
f0b0-40eb-9716-a123495e38f”, timeout: 20000, userVerification: “required”,
allowCredentials: [{ id:
“AdIfzEqbCpLFuu0zLdSyH80fAQx1Kkf31lIYh1lc_8JQBcx4...”, type: “public-key”,
transport: “internal” }], rpId: “example(.)com” } })

(83) At **512**, the authentication API **114** may transmit a credential get request to the authenticator **116** based on the API get call.

(84) Referring now to the data flow diagram **500B** illustrated at FIG. **5B**, at **514**, the authenticator **116** may verify the identity of the user. Such user identity verification may be similar to the manner in which the authenticator authenticates a user at block **322** illustrated at FIG. **3B**.

(85) At **516**, the authenticator **116** may enforce the scope of the RPID included with the API get call. The authenticator may access the private key **105** generated for credential during registration (such as at block **324** illustrated at FIG. **3B**). Using the private key **105**, the authenticator **116** may digitally sign the challenge and/or other data included in the API get call.

(86) At **518A** and **518B**, through the authentication API **114**, the authenticator **116** may transmit an

assertion response back to the authentication interface **136A**. The assertion response may include encoded data that includes a digitally signed challenge.

(87) At **520**, the authentication interface **136A** may provide the assertion response to the authentication server **138A**, which may decode and validate the assertion response according to the WebAuthn and FIDO2 specification or other authentication and credential specification that may be used. Validation of the assertion response may indicate that the user identified by the user identifier has been authenticated because the authenticator **116** would not have provided the assertion response if the user was not authenticated. Validation of the assertion response may further indicate that the device credential is valid based on digital signature verification of the assertion response according to the WebAuthn and FIDO2 specification or other authentication and credential specification that may be used. Upon validation of the assertion response, the authentication server **138A** may notify the SRC server **134A** (not illustrated) that the device credential has been authenticated. The SRC server **134A** may then generate or update a token (such as based on token information included in a JWT described at **328B** of FIG. 3B) that includes the challenge and credential details such as the device credential, the user identifier, the assertion response, validation of the assertion response, and/or other information.

(88) At **522**, the authentication interface **136A** may invoke the SRCI **122A** for further SRC payment processing responsive to the authentication using the federated device credential (public key **103**). In some examples, the authentication interface **136A** may transmit the token to the SRCI **122A**, which may federate the token. Federation of the token may cause the user identifier and the device credential to be federated to other relying parties, such as other payment networks **130**. Using the federated token, each relying party may then independently validate the user and the device associated with the federated token.

(89) At **524**, the SRCI **122A** may present a listing of SRC payment options (such as through the agent **112**) and identify an SRC payment option that is selected by the user to make the SRC payment. The SRCI **122A** may then invoke the DCF **132A**. In some examples, the SRCI **122A** may transmit the token to the DCF **132A**.

(90) At **526**, the DCF **132A** may prompt the user to verify payment information by presenting an interface via the agent **112**.

(91) At **528**, the SRCI **122A** may provide the selected payment credential to the merchant **120** for completing the purchase transaction via SRC payment. In some examples, the DCF **132A** or the SRCI **122A** may transmit the token to the merchant **120** for the SRC payment, which may be processed by another SRC server **134**.

(92) At **530**, the merchant **120** may provide the agent **112** with an interface to confirm completion of the SRC purchase transaction. It should be noted that the merchant **120** may then submit the SRC purchase transaction for payment via payment network **130A**. An example of such payment is illustrated at FIG. 8.

(93) FIG. 6 illustrates a data flow diagram **600** of an example of user-facing authentication of a device credential based on sub-domains of the common domain. The data flow diagram **400** illustrates various interfaces and therefore experience of a user while authenticating the user and the user device **110** as shown in data flow diagrams **500A** and **500B** respectively illustrated at FIGS. 5A and 5B.

(94) At **602**, a purchase interface **601** associated with the merchant **120** may be transmitted to the agent **112** (not illustrated) of the user device **110**. For example, a website checkout of the merchant **120** may be transmitted to a web browser of the user device **110** to complete an online purchase transaction. The purchase interface **601** may include a selection option **503** associated with SRC payments (such as a “c-2-pay” button).

(95) At **604**, upon selection of the selection option **605** (such as a user clicking the c-2-pay button), the purchase interface **601** may cause the agent **112** to invoke the appropriate SRCI **122**, which redirects the agent **112** to an authentication interface of the authentication server **138A**. As

previously noted, the merchant **120** may operate the SRCI **122**, such as from a server or other device of the merchant **120**, or the SRCI **122** may be operated by another entity such as payment service provider to execute SRC transactions on behalf of the merchant **120**. The SRCI **122** may transfer to an authentication interface **136A**.

(96) The authentication interface **136A** may transmit an API get call (an example of which is illustrated at block **510** of FIG. **5A**) to the authentication API **114**, which may cause a prompt to the user to perform user authentication such as through biometric authentication, PIN authentication, and/or other user authentication that may be used by the user device **110** to authenticate the user for screen unlocking or other purposes.

(97) At **606**, upon authentication of the user, an enrolled user may be provided with an interface **621** that indicates such verification. For example, the authentication interface **136A** may provide the interface **621** to indicate that the user has been authenticated.

(98) At **608**, the digitally signed device credential received from the API get call may be validated. Because this validation may occur in the background, interface **621** may continue to be displayed at the user device **110**.

(99) At **610**, the user device **110** may be redirected to the SRCI **122**, which may present a list of available SRC payment options (such as payment cards) to process the SRC payment. Upon selection of an available SRC payment option, the SRCI **122** may redirect to the DCF **132A**. In the illustrated example, only one SRC payment option (associated with the SRC server **134A**) is shown. Thus, the SRCI **122** may select that SRC payment option.

(100) At **612**, the DCF **132A** may transmit an interface **631** to the user device. The interface **631** may include the selected SRC payment option and include an input option **607** (“confirm” button) to confirm the use of the selected SRC payment option.

(101) At **614**, upon confirmation of the selected SRC payment option, the DCF **132A** may redirect the agent **112** to the purchase interface **601** along with the checkout payload. the purchase interface **601** may include an input option **609** (“checkout” button) to complete the purchase and initiate an SRC payment transaction.

(102) FIG. **7** illustrates an example of an architecture **700** for federating a device credential based on sub-domains of the common domain. In some examples, an SRCI **122A** may interface with the authentication interface **136A** and the authentication interface **136B**. Thus, the SRCI **122A** may interface with different payment networks **130** to initiate SRC payments and to initiate device authentication by various payment networks such as payment network **130A** and **130B** (via their respective authentication interfaces **136A** and **136B**). The SRCI **122A** may also interact with various other parts of the payment networks **130**. For example, the SRCI **122A** may obtain enrolled payment card information from DCF **132A** and from DCF **132B**. In this manner, if a user has enrolled payment cards from different payment networks **130**, the SRCI **122A** may be able to identify all enrolled payment cards (and/or other forms of enrolled payments). Likewise, the SRCI **122A** may be able to interface with SRC servers **134A** and **134B** to access user profile database **139A** and **139B**. As such, the SRCI **122A** may be able to initiate device authentication and also SRC payments. In some examples, such device authentication may occur before an enrolled payment card is selected for processing an SRC payment.

(103) FIG. **8** illustrates a data flow diagram of an example of processing a remote commerce payment transaction. At **801A**, the DCF **134** may provide, through a purchase interface of the merchant **120**, with payment options. The payment options may include payment card options stored in a user profile database **139**. At **801B**, the user device **110** may transmit a selection of a payment option for an SRC transaction.

(104) At **803**, upon submission of the SRC payment transaction, a digital purchase application of the purchase interface may capture the customer's account information associated with the selected payment option and transmits the account information to the merchant's acquirer **810**. At **805**, the acquirer **810** transmits, to the payment network **130**, a request to obtain authorization from the

customer's issuing bank **830**.

(105) At **807**, payment network **130** may transmit, to the issuing bank **830**, an authorization request. At **809**, the issuing bank **830** may authorize the transaction and route the authorization response back to the merchant **120**. If the transaction is not authorized, a rejection response may be routed back to the merchant **120**. At **811**, the issuing bank **830** may route the payment to the merchant's acquirer **810**, which deposits the payment into the merchant's account.

(106) FIG. **9** illustrates an example of a computer system **900**. The computer system **900** may be part of or include the system **100** to perform the functions and features described herein. For example, various ones of the devices of system **100** may be implemented based on some or all of the computer system **900**. For example, the user device **110**, each of the merchant devices **120A-N**, the DCF **132A**, the SRC server **134**, and the authentication server **138** may implement some or all of the computer system **900**.

(107) The computer system **900** may include, among other things, an interconnect **910**, a processor **912**, a multimedia adapter **914**, a network interface **916**, a system memory **918**, and a storage adapter **920**.

(108) The interconnect **910** may interconnect various subsystems, elements, and/or components of the computer system **900**. As shown, the interconnect **910** may be an abstraction that may represent any one or more separate physical buses, point-to-point connections, or both, connected by appropriate bridges, adapters, or controllers. In some examples, the interconnect **910** may include a system bus, a peripheral component interconnect (PCI) bus or PCI-Express bus, a HyperTransport or industry standard architecture (ISA)) bus, a small computer system interface (SCSI) bus, a universal serial bus (USB), IIC (I2C) bus, or an Institute of Electrical and Electronics Engineers (IEEE) standard 1394 bus, or "firewire," or other similar interconnection element.

(109) In some examples, the interconnect **910** may allow data communication between the processor **912** and system memory **918**, which may include read-only memory (ROM) or flash memory (neither shown), and random-access memory (RAM) (not shown). It should be appreciated that the RAM may be the main memory into which an operating system and various application programs may be loaded. The ROM or flash memory may contain, among other code, the Basic Input-Output system (BIOS) which controls basic hardware operation such as the interaction with one or more peripheral components.

(110) The processor **912** may control operations of the computing system **900**. In some examples, the processor **912** may do so by executing instructions such as software or firmware stored in system memory **918** or other data via the storage adapter **920**. In some examples, the processor **912** may be, or may include, one or more programmable general-purpose or special-purpose microprocessors, digital signal processors (DSPs), programmable controllers, application specific integrated circuits (ASICs), programmable logic device (PLDs), trust platform modules (TPMs), field-programmable gate arrays (FPGAs), other processing circuits, or a combination of these and other devices.

(111) The multimedia adapter **914** may connect to various multimedia elements or peripherals. These may include devices associated with visual (e.g., video card or display), audio (e.g., sound card or speakers), and/or various input/output interfaces (e.g., mouse, keyboard, touchscreen).

(112) The network interface **916** may provide the computer system **900** with an ability to communicate with a variety of remote devices over a network such as the communication network **107** illustrated in FIG. **1**. The network interface **916** may include, for example, an Ethernet adapter, a Fibre Channel adapter, and/or other wired- or wireless-enabled adapter. The network interface **916** may provide a direct or indirect connection from one network element to another, and facilitate communication and between various network elements.

(113) The storage adapter **920** may connect to a standard computer readable medium for storage and/or retrieval of information, such as a fixed disk drive (internal or external).

(114) Other devices, components, elements, or subsystems (not illustrated) may be connected in a

similar manner to the interconnect **910** or via a network such as the communication network **107**. The devices and subsystems can be interconnected in different ways from that shown in FIG. **9**. Instructions to implement various examples and implementations described herein may be stored in computer-readable storage media such as one or more of system memory **918** or other storage. Instructions to implement the present disclosure may also be received via one or more interfaces and stored in memory. The operating system provided on computing system **900** may be MS-DOS®, MS-WINDOWS®, OS/2®, OS X®, IOS®, ANDROID®, UNIX®, Linux®, or another operating system.

(115) FIG. **10** illustrates an example of a method **1000** of creating a device credential scoped to the common domain **101** and federating the device credential.

(116) At **1002**, the method **1000** may include accessing a registration request to register a user device, the registration request being redirected from a sub-domain (such as sub-domain **111A**) assigned to the payment network (such as payment network **130A**) to a domain name (such as the domain name **131A**) associated with the payment network.

(117) At **1004**, the method **1000** may include transmitting, to the user device, a create request comprising the common domain to which the device credential is to be scoped. The common domain may be different than the domain name associated with the payment network and the sub-domain assigned to the payment network may be a sub-domain of the common domain. As described herein, the foregoing may permit different payment networks to federate and authenticate a scoped device credential. In some examples, transmitting the create request may include transmitting an API call, such as an API create call, to an authenticator API (such as the authenticator API **114**) of the user device, and controlling, based on the API call, an authenticator (such as the authenticator **116**) of the user device to create the key pair.

(118) At **1006**, the method **1000** may include receiving, from the user device, a response that encodes the device credential and a credential identifier that identifies the device credential, the device credential having a scope that is limited to the common domain, and the payment network being assigned with the sub-domain of the common domain to share the scope of the device credential with other ones of the plurality of payment networks.

(119) At **1008**, the method **1000** may include validating the response. In some examples, the device credential may be created as part of a key pair that includes a private key. In these examples, validating the response may include receiving, from the user device, digitally signed data signed with the private key of the authenticator and determining, based on a public key of the authenticator and the challenge, that the digitally signed data was digitally signed by the authenticator. In this way, the relying party may trust that the authenticator provided the response.

(120) At **1010**, the method **1000** may include storing an indication of the validated response. In some examples, the method **1000** may include federating the device credential to other ones of the payment networks responsive to the validation of the response. Once federated, a payment transaction may be processed through the payment network or other payment network of a payment option selected by the user.

(121) FIG. **11** illustrates an example of a method **1100** of authenticating the user device **110** based on the federated device credential scoped to the common domain **101**. The method **1100** may be performed in connection with a purchase transaction between the user device **110** and a merchant, such as a merchant **120A**.

(122) At **1102**, the method **1100** may include receiving a first request redirected from a sub-domain, such as the sub-domain **111A**, assigned to the payment network (such as the payment network **130A**) to a domain name (such as the domain name **131A**) associated with the payment network. In some examples, the first request may be received via an authentication interface (such as authentication interface **136A**) of the payment network. The sub-domain may resolve to the authentication interface based on the redirection from the sub-domain to the domain name.

(123) In some examples, the first request may be received from an SRCI (such as the SRCI **122**)

that initiates payment transactions on behalf of the merchant **120A**. In these examples, the payment network may implement the SRC specification, which may facilitate SRC payments through the plurality of payment networks **130**. Also, in these examples, accessing the request to authenticate the user device may include receiving the first request to authenticate the user device from an SRC initiator that initiates the payment transaction as an SRC payment and transmits the request to the sub-domain assigned to the payment network.

(124) At **1104**, the method **1100** may include responsive to the first request, transmitting an authentication request comprising a challenge, a user identifier that identifies the user, and the common domain to which the device credential is scoped. In some examples, the authentication request may be transmitted as an API call (such as an API get call) to an authenticator API (such as the authenticator API **114**). Through the API call, the method **1100** may control, an authenticator (such as the authenticator **116**) of the user device **110** to digitally sign data comprising the challenge using credential's private key. In some examples, the authentication request may be transmitted via a communication session that identifies the common domain as an origin of the authentication request so that the user device **110** may determine the origin.

(125) At **1106**, the method **1100** may include receiving, from the user device, a response.

(126) At **1108**, the method **1100** may include accessing the device credential, the device credential having been stored by the payment network, the payment network being assigned with the sub-domain of the common domain to share the scope with other ones of the plurality of payment networks.

(127) At **1110**, the method **1100** may include validating the response based on the device credential. In some examples, the response may include the digitally signed data signed based on the challenge and a private key (such as the private key **105**) created with the device credential as a key pair. In these examples, validating the response may include decrypting the digitally signed data based on the device credential and verifying that the user device has possession of the private key based on the decrypting.

(128) In some examples, the response may encode the origin of the authentication request. In these examples, validating the response may include determining that the origin encoded in the response matches the common domain even though the common domain is different from the domain name associated with the payment network. A relying party, such as a payment network, may determine that a mismatch between the origin and the domain of the relying party may indicate a phishing attack. However, as described herein, because the payment network shares the common domain with other payment networks to share the scope of the device credential, the payment network may expect the origin to be equal to the common domain.

(129) At **1112**, the method **1100** may include causing the user identifier the device credential to be federated to other ones of the plurality of networks based on the validating. For example, the method **1100** may conclude that the user identified by the user identifier has been authenticated and user device has been previously registered based on the validated device authentication. In some examples, after validating the response, the user identifier and the device credential may be federated to other SRC systems prior to initiating a payment transaction. In some examples, the user identifier and the device credential may be federated to other SRC systems through a token, such as the JWT token described herein. In some examples, after authenticating the user device and, in some examples, after federating the device credential to other SRC systems, a payment transaction may be initiated and processed through the payment network or other payment network of a payment option selected by the user.

(130) The mapping table **142** and/or the user profile database **139A** described herein may be, include, or interface to, for example, an Oracle™ relational database sold commercially by Oracle Corporation. Other databases, such as Informix™, DB2 or other data storage, including file-based, or query formats, platforms, or resources such as OLAP (On Line Analytical Processing), SQL (Structured Query Language), a SAN (storage area network), Microsoft Access™ or others may

also be used, incorporated, or accessed. The database may comprise one or more such databases that reside in one or more physical devices and in one or more physical locations. The database may include cloud-based storage solutions. The database may store a plurality of types of data and/or files and associated data or file descriptions, administrative information, or any other data. The various databases may store predefined and/or customized data described herein.

(131) Throughout the disclosure, the terms “a” and “an” may be intended to denote at least one of a particular element. As used herein, the term “includes” means includes but not limited to, the term “including” means including but not limited to. The term “based on” means based at least in part on. In the Figures, the use of the letter “N” to denote plurality in reference symbols is not intended to refer to a particular number. For example, “120A, B, N” does not refer to 3 instances of 120, but rather “two or more.”

(132) The systems and processes are not limited to the specific embodiments described herein. In addition, components of each system and each process can be practiced independent and separate from other components and processes described herein. Each component and process also can be used in combination with other assembly packages and processes. The flow charts and descriptions thereof herein should not be understood to prescribe a fixed order of performing the method blocks described therein. Rather the method blocks may be performed in any order that is practicable including simultaneous performance of at least some method blocks. Furthermore, each of the methods may be performed by one or more of the system components illustrated in FIG. 1.

(133) Having described aspects of the disclosure in detail, it will be apparent that modifications and variations are possible without departing from the scope of aspects of the disclosure as defined in the appended claims. As various changes could be made in the above constructions, products, and methods without departing from the scope of aspects of the disclosure, it is intended that all matter contained in the above description and shown in the accompanying drawings shall be interpreted as illustrative and not in a limiting sense.

(134) While the disclosure has been described in terms of various specific embodiments, those skilled in the art will recognize that the disclosure can be practiced with modification within the spirit and scope of the claims.

(135) As will be appreciated based on the foregoing specification, the above-described embodiments of the disclosure may be implemented using computer programming or engineering techniques including computer software, firmware, hardware or any combination or subset thereof. Any such resulting program, having computer-readable code means, may be embodied or provided within one or more computer-readable media, thereby making a computer program product, i.e., an article of manufacture, according to the discussed embodiments of the disclosure. Example computer-readable media may be, but are not limited to, a flash memory drive, digital versatile disc (DVD), compact disc (CD), fixed (hard) drive, diskette, optical disk, magnetic tape, semiconductor memory such as read-only memory (ROM), and/or any transmitting/receiving medium such as the Internet or other communication network or link. By way of example and not limitation, computer-readable media comprise computer-readable storage media and communication media. Computer-readable storage media are tangible and non-transitory and store information such as computer-readable instructions, data structures, program modules, and other data. Communication media, in contrast, typically embody computer-readable instructions, data structures, program modules, or other data in a transitory modulated signal such as a carrier wave or other transport mechanism and include any information delivery media. Combinations of any of the above are also included in the scope of computer-readable media. The article of manufacture containing the computer code may be made and/or used by executing the code directly from one medium, by copying the code from one medium to another medium, or by transmitting the code over a network.

(136) This written description uses examples to disclose the embodiments, including the best mode, and also to enable any person skilled in the art to practice the embodiments, including making and using any devices or systems and performing any incorporated methods. The patentable scope of

the disclosure is defined by the claims, and may include other examples that occur to those skilled in the art. Such other examples are intended to be within the scope of the claims if they have structural elements that do not differ from the literal language of the claims, or if they include equivalent structural elements with insubstantial differences from the literal languages of the claims.

Claims

1. A system of registering a user device to be authenticated by a device credential scoped to a common domain shared among a plurality of payment networks, each payment network having a respective domain name different than the common domain and each payment network being assigned with a respective sub-domain of the common domain, the system comprising: a server of a payment network of the plurality of payment networks, the server to: access a registration request to register a user device, the registration request being redirected from a sub-domain assigned to the payment network to a domain name associated with the payment network; transmit, to the user device, a create request comprising the common domain to which the device credential is to be scoped, the common domain being different than the domain name associated with the payment network, and a sub-domain assigned to the payment network being a sub-domain of the common domain; receive, from the user device, a response that encodes the device credential and a credential identifier that identifies the device credential, the device credential having a scope that is limited to the common domain, and the payment network being assigned with the sub-domain of the common domain to share the scope of the device credential with other ones of the plurality of payment networks; validate the response; and store an indication of the validated response.
2. The system of claim 1, wherein the create request includes a challenge and wherein the device credential was created as part of a key pair that includes a private key, and wherein to validate the response, the server is further to: receive, from the user device, digitally signed data signed with a private key of an authenticator of the user device that generated the key pair; and determine, based on a public key associated with the authenticator device and the challenge, that the digitally signed data was digitally signed by the authenticator.
3. The system of claim 2, wherein to transmit the create request, the server is further to: transmit an application programming interface (API) call to an authenticator API of the user device; and control, based on the API call, an authenticator of the user device to create the key pair.
4. The system of claim 1, wherein the registration request is associated with a purchase transaction, and wherein the server is further to: access a checkout payload associated with a payment transaction; transmit the checkout payload to a purchase interface associated with a merchant to complete the payment transaction; and process the payment transaction through the payment network.
5. The system of claim 1, wherein the server is further to: federate the device credential and a user identifier associated with the device credential to other ones of the payment networks responsive to the validation of the response.
6. The system of claim 1, further comprising: a second server of a relying party other than the payment network, the second server to register a second user device based on a second sub-domain of the common domain to generate a second device credential scoped to the common domain, the second sub-domain being assigned to the relying party other than the payment network to participate in registering or authenticating the second device credential scoped to the common domain.
7. The system of claim 6, wherein the relying party is a merchant.
8. The system of claim 6, wherein the relying party is a party other than a merchant or the payment network.
9. The system of claim 6, wherein the server is further to: federate the device credential and a user

identifier associated with the device credential to the second server responsive to the validation of the response, wherein the second server of the relying party other than the payment network is to authenticate the device credential to authenticate the user device registered by the server of the payment network.

10. A method of registering a user device to be authenticated by a device credential scoped to a common domain shared among a plurality of payment networks, each payment network having a respective domain name different than the common domain and each payment network being assigned with a respective sub-domain of the common domain, the method comprising: accessing, by a server of a payment network of the plurality of payment networks, a registration request to register a user device, the registration request being redirected from a sub-domain assigned to the payment network to a domain name associated with the payment network; transmitting, by the server of the payment network, to the user device, a create request comprising the common domain to which the device credential is to be scoped, the common domain being different than the domain name associated with the payment network, and the sub-domain assigned to the payment network being a sub-domain of the common domain; receiving, by the server of the payment network, from the user device, a response that encodes the device credential and a credential identifier that identifies the device credential, the device credential having a scope that is limited to the common domain, and the payment network being assigned with the sub-domain of the common domain to share the scope of the device credential with other ones of the plurality of payment networks; validating, by the server of the payment network, the response; and storing, by the server of the payment network, an indication of the validated response.

11. The method of claim 10, wherein the create request includes a challenge and wherein the device credential was created as part of a key pair that includes a private key, and wherein validating the response comprises: receiving, by the server, from the user device, digitally signed data signed with a private key of an authenticator of the user device that generated the key pair; and determining, by the server, based on a public key associated with the authenticator device and the challenge, that the digitally signed data was digitally signed by the authenticator.

12. The method of claim 11, wherein transmitting the create request comprises: transmitting an application programming interface (API) call to an authenticator API of the user device; and controlling, based on the API call, an authenticator of the user device to create the key pair.

13. The method of claim 10, wherein the registration request is associated with a purchase transaction, the method further comprising: accessing, by the server, a checkout payload associated with a payment transaction; transmitting, by the server, the checkout payload to a purchase interface associated with a merchant to complete the payment transaction; and processing, by the server, the payment transaction through the payment network.

14. The method of claim 10, further comprising: federating, by the server, the device credential and a user identifier associated with the device credential to other ones of the payment networks responsive to the validation of the response.

15. The method of claim 10, further comprising: registering, by a second server of a relying party other than the payment network, a second user device based on a second sub-domain of the common domain to generate a second device credential scoped to the common domain, the second sub-domain being assigned to the relying party other than the payment network to participate in registering or authenticating the second device credential scoped to the common domain.

16. The method of claim 15, wherein the relying party is a merchant.

17. The method of claim 15, wherein the relying party is a party other than a merchant or the payment network.

18. The method of claim 15, further comprising: federating, by the server, the device credential and a user identifier associated with the device credential to the second server responsive to the validation of the response; authenticating, by the second server of the relying party other than the payment network, the device credential to authenticate the user device registered by the server of

the payment network.

19. A non-transitory computer readable medium storing instructions for registering a user device to be authenticated by a device credential scoped to a common domain shared among a plurality of payment networks, each payment network having a respective domain name different than the common domain and each payment network being assigned with a respective sub-domain of the common domain, the instructions, when executed by a server of a payment network, cause the server to: access a registration request to register a user device, the registration request being redirected from a sub-domain assigned to the payment network to a domain name associated with the payment network; transmit, to the user device, a create request comprising the common domain to which the device credential is to be scoped, the common domain being different than the domain name associated with the payment network, and the sub-domain assigned to the payment network being a sub-domain of the common domain; receive, from the user device, a response that encodes the device credential and a credential identifier that identifies the device credential, the device credential having a scope that is limited to the common domain, and the payment network being assigned with the sub-domain of the common domain to share the scope of the device credential with other ones of the plurality of payment networks; validate the response; and store an indication of the validated response.

20. The non-transitory computer readable medium of claim 19, wherein the instructions, when executed by the server, further cause the server to: federate the device credential and a user identifier associated with the device credential to other ones of the payment networks responsive to the validation of the response.
