

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12418504
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Boyd; Nathan Kenneth et al.

Media content playback and comments management

Abstract

A method and a system include receiving a request from a client device to view a media content item, determining at least one comment associated with a respective user profile from a set of connected profiles, generating a summary comments selectable item based at least in part on the respective user profile, causing a display of playback of the media content item and the summary comments selectable item in response to the request to view the media content item, and during the playback of the media content item at the particular time, causing a display of at least one comment.

Inventors: Boyd; Nathan Kenneth (Los Angeles, CA), Voss; Jeremy Baker (Los Angeles, CA)

Applicant: Snap Inc. (Santa Monica, CA)

Family ID: 1000008820264

Assignee: Snap Inc. (Santa Monica, CA)

Appl. No.: 18/521428

Filed: November 28, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240098058 A1	Mar. 21, 2024

Related U.S. Application Data

continuation parent-doc US 17008376 20200831 US 11863513 child-doc US 18521428

Publication Classification

Int. Cl.: H04L51/56 (20220101); G06F3/04817 (20220101); H04L51/52 (20220101); H04L67/306 (20220101)

U.S. Cl.:

CPC H04L51/52 (20220501); G06F3/04817 (20130101); H04L67/306 (20130101);

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5604843	12/1996	Shaw et al.	N/A	N/A
5689559	12/1996	Park	N/A	N/A
5880731	12/1998	Liles et al.	N/A	N/A
6023270	12/1999	Brush, II et al.	N/A	N/A
RE36919	12/1999	Park	N/A	N/A
RE37052	12/2000	Park	N/A	N/A
6223165	12/2000	Lauffer	N/A	N/A
6650793	12/2002	Lund et al.	N/A	N/A
6772195	12/2003	Hatlelid et al.	N/A	N/A
6804417	12/2003	Lund et al.	N/A	N/A
6842779	12/2004	Nishizawa	N/A	N/A
7342587	12/2007	Danzig et al.	N/A	N/A
7468729	12/2007	Levinson	N/A	N/A
7636755	12/2008	Blattner et al.	N/A	N/A
7639251	12/2008	Gu et al.	N/A	N/A
7775885	12/2009	Van Luchene et al.	N/A	N/A
7859551	12/2009	Bulman et al.	N/A	N/A
7885931	12/2010	Seo et al.	N/A	N/A
7925703	12/2010	Dinan et al.	N/A	N/A
8088044	12/2011	Tchao et al.	N/A	N/A
8095878	12/2011	Bates et al.	N/A	N/A
8108774	12/2011	Finn et al.	N/A	N/A
8117281	12/2011	Robinson et al.	N/A	N/A
8130219	12/2011	Fleury et al.	N/A	N/A
8146005	12/2011	Jones et al.	N/A	N/A
8151191	12/2011	Nicol	N/A	N/A
RE43993	12/2012	Park	N/A	N/A
8384719	12/2012	Reville et al.	N/A	N/A
RE44054	12/2012	Kim	N/A	N/A
RE44068	12/2012	Park	N/A	N/A
RE44106	12/2012	Park	N/A	N/A
8396708	12/2012	Park et al.	N/A	N/A
RE44121	12/2012	Park	N/A	N/A
8425322	12/2012	Gillo et al.	N/A	N/A

8458601	12/2012	Castelli et al.	N/A	N/A
8462198	12/2012	Lin et al.	N/A	N/A
8484158	12/2012	Deluca et al.	N/A	N/A
8495503	12/2012	Brown et al.	N/A	N/A
8495505	12/2012	Smith et al.	N/A	N/A
8504926	12/2012	Wolf	N/A	N/A
8559980	12/2012	Pujol	N/A	N/A
8564621	12/2012	Branson et al.	N/A	N/A
8564710	12/2012	Nonaka et al.	N/A	N/A
8581911	12/2012	Becker et al.	N/A	N/A
8597121	12/2012	del Valle	N/A	N/A
8601051	12/2012	Wang	N/A	N/A
8601379	12/2012	Marks et al.	N/A	N/A
8632408	12/2013	Gillo et al.	N/A	N/A
8648865	12/2013	Dawson et al.	N/A	N/A
8659548	12/2013	Hildreth	N/A	N/A
8683354	12/2013	Khandelwal et al.	N/A	N/A
8692830	12/2013	Nelson et al.	N/A	N/A
8810513	12/2013	Ptucha et al.	N/A	N/A
8812171	12/2013	Filev et al.	N/A	N/A
8832201	12/2013	Wall	N/A	N/A
8832552	12/2013	Arrasvuori et al.	N/A	N/A
8839327	12/2013	Amento et al.	N/A	N/A
8890926	12/2013	Tandon et al.	N/A	N/A
8892999	12/2013	Nims et al.	N/A	N/A
8924250	12/2013	Bates et al.	N/A	N/A
8963926	12/2014	Brown et al.	N/A	N/A
8989786	12/2014	Feghali	N/A	N/A
9086776	12/2014	Ye et al.	N/A	N/A
9105014	12/2014	Collet et al.	N/A	N/A
9241184	12/2015	Weerasinghe	N/A	N/A
9256860	12/2015	Herger et al.	N/A	N/A
9298257	12/2015	Hwang et al.	N/A	N/A
9314692	12/2015	Konoplev et al.	N/A	N/A
9330483	12/2015	Du et al.	N/A	N/A
9357174	12/2015	Li et al.	N/A	N/A
9361510	12/2015	Yao et al.	N/A	N/A
9378576	12/2015	Bouaziz et al.	N/A	N/A
9402057	12/2015	Kaytaz et al.	N/A	N/A
9412192	12/2015	Mandel et al.	N/A	N/A
9460541	12/2015	Li et al.	N/A	N/A
9489760	12/2015	Li et al.	N/A	N/A
9503845	12/2015	Vincent	N/A	N/A
9508197	12/2015	Quinn et al.	N/A	N/A
9532364	12/2015	Fujito	N/A	N/A
9544257	12/2016	Ogundokun et al.	N/A	N/A
9576400	12/2016	Van Os et al.	N/A	N/A
9589357	12/2016	Li et al.	N/A	N/A
9592449	12/2016	Barbalet et al.	N/A	N/A
9648376	12/2016	Chang et al.	N/A	N/A

9697635	12/2016	Quinn et al.	N/A	N/A
9706040	12/2016	Kadirvel et al.	N/A	N/A
9744466	12/2016	Fujioka	N/A	N/A
9746990	12/2016	Anderson et al.	N/A	N/A
9749270	12/2016	Collet et al.	N/A	N/A
9792714	12/2016	Li et al.	N/A	N/A
9839844	12/2016	Dunstan et al.	N/A	N/A
9883838	12/2017	Kaleal, III et al.	N/A	N/A
9898849	12/2017	Du et al.	N/A	N/A
9911073	12/2017	Spiegel et al.	N/A	N/A
9936165	12/2017	Li et al.	N/A	N/A
9959037	12/2017	Chaudhri et al.	N/A	N/A
9980100	12/2017	Charlton et al.	N/A	N/A
9990373	12/2017	Fortkort	N/A	N/A
10039988	12/2017	Lobb et al.	N/A	N/A
10097492	12/2017	Tsuda et al.	N/A	N/A
10116598	12/2017	Tucker et al.	N/A	N/A
10155168	12/2017	Blackstock et al.	N/A	N/A
10158589	12/2017	Collet et al.	N/A	N/A
10242477	12/2018	Charlton et al.	N/A	N/A
10242503	12/2018	McPhee et al.	N/A	N/A
10262250	12/2018	Spiegel et al.	N/A	N/A
10348662	12/2018	Baldwin et al.	N/A	N/A
10362219	12/2018	Wilson et al.	N/A	N/A
10432559	12/2018	Baldwin et al.	N/A	N/A
10454857	12/2018	Blackstock et al.	N/A	N/A
10475225	12/2018	Park et al.	N/A	N/A
10504266	12/2018	Blattner et al.	N/A	N/A
10573048	12/2019	Ni et al.	N/A	N/A
10656797	12/2019	Alvi et al.	N/A	N/A
10657695	12/2019	Chand et al.	N/A	N/A
10657701	12/2019	Osman et al.	N/A	N/A
10762174	12/2019	Denton et al.	N/A	N/A
10805248	12/2019	Luo et al.	N/A	N/A
10872451	12/2019	Sheth et al.	N/A	N/A
10880246	12/2019	Baldwin et al.	N/A	N/A
10895964	12/2020	Grantham et al.	N/A	N/A
10896534	12/2020	Smith et al.	N/A	N/A
10933311	12/2020	Brody et al.	N/A	N/A
10938758	12/2020	Allen et al.	N/A	N/A
10964082	12/2020	Amitay et al.	N/A	N/A
10979752	12/2020	Brody et al.	N/A	N/A
10984575	12/2020	Assouline et al.	N/A	N/A
10992619	12/2020	Antmen et al.	N/A	N/A
11010022	12/2020	Alvi et al.	N/A	N/A
11030789	12/2020	Chand et al.	N/A	N/A
11036781	12/2020	Baril et al.	N/A	N/A
11063891	12/2020	Voss	N/A	N/A
11069103	12/2020	Blackstock et al.	N/A	N/A

11080917	12/2020	Monroy-hernández et al.	N/A	N/A
11128586	12/2020	Al Majid et al.	N/A	N/A
11188190	12/2020	Blackstock et al.	N/A	N/A
11189070	12/2020	Jahangiri et al.	N/A	N/A
11199957	12/2020	Alvi et al.	N/A	N/A
11218433	12/2021	Baldwin et al.	N/A	N/A
11229849	12/2021	Blackstock et al.	N/A	N/A
11245658	12/2021	Grantham et al.	N/A	N/A
11249614	12/2021	Brody	N/A	N/A
11263254	12/2021	Baril et al.	N/A	N/A
11270491	12/2021	Monroy-Hernández et al.	N/A	N/A
11284144	12/2021	Kotsopoulos et al.	N/A	N/A
2002/0067362	12/2001	Agostino Nocera et al.	N/A	N/A
2002/0169644	12/2001	Greene	N/A	N/A
2005/0162419	12/2004	Kim et al.	N/A	N/A
2005/0206610	12/2004	Cordelli	N/A	N/A
2006/0294465	12/2005	Ronen et al.	N/A	N/A
2007/0113181	12/2006	Blattner et al.	N/A	N/A
2007/0168863	12/2006	Blattner et al.	N/A	N/A
2007/0176921	12/2006	Iwasaki et al.	N/A	N/A
2008/0158222	12/2007	Li et al.	N/A	N/A
2009/0016617	12/2008	Bregman-amitai et al.	N/A	N/A
2009/0055484	12/2008	Vuong et al.	N/A	N/A
2009/0070688	12/2008	Gyorfi et al.	N/A	N/A
2009/0099925	12/2008	Mehta et al.	N/A	N/A
2009/0106672	12/2008	Burstrom	N/A	N/A
2009/0158170	12/2008	Narayanan et al.	N/A	N/A
2009/0164904	12/2008	Horowitz	715/723	G06F 16/739
2009/0177976	12/2008	Bokor et al.	N/A	N/A
2009/0202114	12/2008	Morin et al.	N/A	N/A
2009/0265604	12/2008	Howard et al.	N/A	N/A
2009/0300525	12/2008	Jolliff et al.	N/A	N/A
2009/0303984	12/2008	Clark et al.	N/A	N/A
2010/0011422	12/2009	Mason et al.	N/A	N/A
2010/0023885	12/2009	Reville et al.	N/A	N/A
2010/0095211	12/2009	Kenvin et al.	N/A	N/A
2010/0115426	12/2009	Liu et al.	N/A	N/A
2010/0162149	12/2009	Sheleheda et al.	N/A	N/A
2010/0203968	12/2009	Gill et al.	N/A	N/A
2010/0227682	12/2009	Reville et al.	N/A	N/A
2011/0093780	12/2010	Dunn	N/A	N/A
2011/0115798	12/2010	Nayar et al.	N/A	N/A
2011/0148864	12/2010	Lee et al.	N/A	N/A
2011/0161987	12/2010	Huang et al.	N/A	N/A
2011/0239136	12/2010	Goldman et al.	N/A	N/A

2012/0113106	12/2011	Choi et al.	N/A	N/A
2012/0124458	12/2011	Cruzada	N/A	N/A
2012/0130717	12/2011	Xu et al.	N/A	N/A
2012/0150997	12/2011	Mcclements, IV	N/A	N/A
2012/0158753	12/2011	He et al.	N/A	N/A
2013/0103760	12/2012	Golding et al.	N/A	N/A
2013/0201187	12/2012	Tong et al.	N/A	N/A
2013/0249948	12/2012	Reitan	N/A	N/A
2013/0257877	12/2012	Davis	N/A	N/A
2014/0043329	12/2013	Wang et al.	N/A	N/A
2014/0055554	12/2013	Du et al.	N/A	N/A
2014/0125678	12/2013	Wang et al.	N/A	N/A
2014/0129343	12/2013	Finster et al.	N/A	N/A
2015/0206349	12/2014	Rosenthal et al.	N/A	N/A
2015/0245097	12/2014	Agrawal	N/A	N/A
2016/0057092	12/2015	Liao	N/A	N/A
2016/0134840	12/2015	Mcculloch	N/A	N/A
2016/0234149	12/2015	Tsuda et al.	N/A	N/A
2017/0080346	12/2016	Abbas	N/A	N/A
2017/0087473	12/2016	Siegel et al.	N/A	N/A
2017/0113140	12/2016	Blackstock et al.	N/A	N/A
2017/0118145	12/2016	Aittoniemi et al.	N/A	N/A
2017/0139920	12/2016	Ball et al.	N/A	N/A
2017/0199855	12/2016	Fishbeck	N/A	N/A
2017/0235848	12/2016	Van Deusen et al.	N/A	N/A
2017/0310934	12/2016	Du et al.	N/A	N/A
2017/0312634	12/2016	Ledoux et al.	N/A	N/A
2018/0047200	12/2017	O'hara et al.	N/A	N/A
2018/0048603	12/2017	Barajas Gonzalez et al.	N/A	N/A
2018/0113587	12/2017	Allen et al.	N/A	N/A
2018/0115503	12/2017	Baldwin et al.	N/A	N/A
2018/0198743	12/2017	Blackstock et al.	N/A	N/A
2018/0205692	12/2017	Zunger	N/A	G06Q 10/107
2018/0315076	12/2017	Andreou	N/A	N/A
2018/0315133	12/2017	Brody et al.	N/A	N/A
2018/0315134	12/2017	Amitay et al.	N/A	N/A
2018/0331842	12/2017	Faulkner	N/A	H04N 7/15
2019/0001223	12/2018	Blackstock et al.	N/A	N/A
2019/0057616	12/2018	Cohen et al.	N/A	N/A
2019/0097958	12/2018	Collet et al.	N/A	N/A
2019/0188920	12/2018	Mcphee et al.	N/A	N/A
2019/0280997	12/2018	Baldwin et al.	N/A	N/A
2020/0111173	12/2019	Benfield et al.	N/A	N/A
2020/0306637	12/2019	Baldwin et al.	N/A	N/A
2020/0372127	12/2019	Denton et al.	N/A	N/A
2020/0410575	12/2019	Grantham et al.	N/A	N/A
2021/0074047	12/2020	Sheth et al.	N/A	N/A
2021/0089179	12/2020	Grantham et al.	N/A	N/A

2021/0104087	12/2020	Smith et al.	N/A	N/A
2021/0168108	12/2020	Antmen et al.	N/A	N/A
2021/0170270	12/2020	Brody et al.	N/A	N/A
2021/0192823	12/2020	Amitay et al.	N/A	N/A
2021/0209825	12/2020	Assouline et al.	N/A	N/A
2021/0225058	12/2020	Chand et al.	N/A	N/A
2021/0240315	12/2020	Alvi et al.	N/A	N/A
2021/0243482	12/2020	Baril et al.	N/A	N/A
2021/0243503	12/2020	Kotsopoulos et al.	N/A	N/A
2021/0266277	12/2020	Allen et al.	N/A	N/A
2021/0281897	12/2020	Brody et al.	N/A	N/A
2021/0285774	12/2020	Collins et al.	N/A	N/A
2021/0286840	12/2020	Amitay et al.	N/A	N/A
2021/0306290	12/2020	Voss	N/A	N/A
2021/0306451	12/2020	Heikkinen et al.	N/A	N/A
2021/0385180	12/2020	Al Majid et al.	N/A	N/A
2021/0405831	12/2020	Mourkogiannis et al.	N/A	N/A
2021/0409535	12/2020	Mourkogiannis et al.	N/A	N/A
2022/0012929	12/2021	Blackstock et al.	N/A	N/A
2022/0070129	12/2021	Boyd et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
109863532	12/2018	CN	N/A
110168478	12/2018	CN	N/A
116438788	12/2022	CN	N/A
2184092	12/2009	EP	N/A
2001230801	12/2000	JP	N/A
5497931	12/2013	JP	N/A
101445263	12/2013	KR	N/A
WO-2003094072	12/2002	WO	N/A
WO-2004095308	12/2003	WO	N/A
WO-2006107182	12/2005	WO	N/A
WO-2007134402	12/2006	WO	N/A
WO-2012139276	12/2011	WO	N/A
WO-2013027893	12/2012	WO	N/A
WO-2013152454	12/2012	WO	N/A
WO-2013166588	12/2012	WO	N/A
WO-2014031899	12/2013	WO	N/A
WO-2014194439	12/2013	WO	N/A
WO-2016090605	12/2015	WO	N/A
WO-2018081013	12/2017	WO	N/A
WO-2018102562	12/2017	WO	N/A
WO-2018129531	12/2017	WO	N/A
WO-2019089613	12/2018	WO	N/A
WO-2022047477	12/2021	WO	N/A

OTHER PUBLICATIONS

U.S. Appl. No. 17/008,376, filed Aug. 31, 2020, Media Content Playback and Comments Management. cited by applicant

“U.S. Appl. No. 17/008,376, Examiner Interview Summary mailed Aug. 7, 2023”, 2 pgs. cited by applicant

“U.S. Appl. No. 17/008,376, Final Office Action mailed Sep. 30, 2022”, 20 pgs. cited by applicant

“U.S. Appl. No. 17/008,376, Non Final Office Action mailed Mar. 21, 2022”, 18 pgs. cited by applicant

“U.S. Appl. No. 17/008,376, Non Final Office Action mailed May 4, 2023”, 22 pgs. cited by applicant

“U.S. Appl. No. 17/008,376, Notice of Allowance mailed Aug. 21, 2023”, 7 pgs. cited by applicant

“U.S. Appl. No. 17/008,376, Response filed Jan. 30, 2023 to Final Office Action mailed Sep. 30, 2022”, 11 pgs. cited by applicant

“U.S. Appl. No. 17/008,376, Response filed Jul. 21, 2022 to Non Final Office Action mailed Mar. 21, 2022”, 10 pgs. cited by applicant

“U.S. Appl. No. 17/008,376, Response filed Aug. 4, 2023 to Non Final Office Action mailed May 4, 2023”, 13 pgs. cited by applicant

“Bitmoji”, Snapchat Support, [Online] Retrieved from the Internet: <URL: <https://web.archive.org/web/20190503063620/https://support.snapchat.com/en-US/a/bitmoji>>, (captured May 3, 2019), 2 pgs. cited by applicant

“Bitmoji Chrome Extension”, [Online] Retrieved from the Internet: <URL: <https://web.archive.org/web/20200919024925/https://support.bimoji.com/hc/en-us/articles/360001494066>>, (Sep. 19, 2020), 5 pgs. cited by applicant

“Bitmoji Customize text”, [Online] Retrieved from the Internet: <URL: <https://web.archive.org/web/20210225200456/https://support.bitmoji.com/hc/en-us/articles/360034632291-Customize-Text-on-Bitmoji-Stickers>>, (captured Feb. 25, 2021), 3 pgs. cited by applicant

“Bitmoji Family”, Snapchat Support, [Online] Retrieved from the Internet: <URL: <https://web.archive.org/web/20190503063620/https://support.snapchat.com/en-US/article/bitmoji-family>>, (captured May 3, 2019), 4 pgs. cited by applicant

“Chinese Application Serial No. 202180052923.X, Notification to Make Rectification mailed Apr. 3, 2023”, W/ English Machine Translation, 3 pgs. cited by applicant

“Instant Comics Starring You & Your Friends”, Bitstrips Inc, [Online] Retrieved from the Internet: <URL: <https://web.archive.org/web/20150206000940/http://company.bitstrips.com/bitstrips-app.html>>, (captured Feb. 6, 2015), 3 pgs. cited by applicant

“International Application Serial No. PCT/US2021/071276, International Preliminary Report on Patentability mailed Mar. 9, 2023”, 8 pgs. cited by applicant

“International Application Serial No. PCT/US2021/071276, International Search Report mailed Nov. 18, 2021”, 5 pgs. cited by applicant

“International Application Serial No. PCT/US2021/071276, Written Opinion mailed Nov. 18, 2021”, 6 pgs. cited by applicant

“Manage Your Bitmoji”, Snapchat Support, [Online] Retrieved from the Internet: <URL: <https://web.archive.org/web/20190503063620/https://support.snapchat.com/en-US/a/manage-bitmoji>>, (captured May 3, 2019), 3 pgs. cited by applicant

“Your Own Personal Emoji”, Bitstrips Inc, [Online] Retrieved from the Internet: <URL: <https://web.archive.org/web/20150205232004/http://bitmoji.com/>>, (captured Feb. 5, 2015), 3 pgs. cited by applicant

Carnahan, Daniel, “Snap is Offering Personalized Video Content Through Bitmoji TV”, Business Insider, [Online] Retrieved from the Internet: <URL: <https://www.businessinsider.com/snap-offers-personalized-video-content-through-bitmoji-tv-2019-12>>, (2019), 10 pgs. cited by applicant

Constine, Josh, "Snapchat launches Bitmoji merch and comic strips starring your avatar", TechCrunch, [Online] Retrieved from the Internet: <URL: <https://techcrunch.com/2018/11/13/bitmoji-store/>>, (Nov. 13, 2018), 16 pgs. cited by applicant

Constine, Josh, "Snapchat Launches Bitmoji TV: Zany 4-min Cartoons of Your Avatar", TechCrunch, [Online] Retrieved from the Internet: <URL: <https://techcrunch.com/2020/01/30/bitmoji-tv/>>, (Jan. 30, 2020), 13 pgs. cited by applicant

MacMillan, Douglas, "Snapchat Buys Bitmoji App for More Than \$100 Million", The Wallstreet Journal, [Online] Retrieved from the Internet: <URL: <https://www.wsj.com/articles/snapchat-buys-bitmoji-app-for-more-than-100-million-1458876017>>, (Mar. 25, 2016), 5 pgs. cited by applicant

Newton, Casey, "Your Snapchat friendships now have their own profiles—and merchandise", The Verge, [Online] Retrieved from the Internet: <URL: <https://www.theverge.com/2018/11/13/18088772/snapchat-friendship-profiles-bitmoji-merchandise-comics>>, (Nov. 13, 2018), 5 pgs. cited by applicant

Ong, Thuy, "Snapchat takes Bitmoji deluxe with hundreds of new customization options", The Verge, [Online] Retrieved from the Internet on Nov. 2, 2018: <URL: <https://www.theverge.com/2018/1/30/16949402/bitmoji-deluxe-snapchat-customization>>, (Jan. 30, 2018), 2 pgs. cited by applicant

Reign, Ashley, "How To Add My Friend's Bitmoji To My Snapchat", Women.com, [Online] Retrieved from the Internet: <URL: <https://www.women.com/ashleyreign/lists/how-to-add-my-friends-bitmoji-to-my-snapchat>>, (Jun. 30, 2017), 7 pgs. cited by applicant

Tumbokon, Karen, "Snapchat Update: How To Add Bitmoji To Customizable Geofilters", International Business Times, [Online] Retrieved from the Internet : <URL: <https://www.ibtimes.com/snapchat-update-how-add-bitmoji-customizable-geofilters-2448152>>, (Nov. 18, 2016), 6 pgs. cited by applicant

"European Application Serial No. 21772935.9, Communication Pursuant to Article 94(3) EPC mailed Nov. 29, 2024", 5 pgs. cited by applicant

"Korean Application Serial No. 10-2023-7010659, Notice of Preliminary Rejection mailed Jul. 1, 2025", W/ English Translation, 9 pgs. cited by applicant

Primary Examiner: Sison; June

Attorney, Agent or Firm: Schwegman Lundberg & Woessner, P.A.

Background/Summary

CLAIM OF PRIORITY (1) This application is a continuation of U.S. patent application Ser. No. 17/008,376, filed on Aug. 31, 2020, which is incorporated herein by reference in its entirety.

BACKGROUND

(1) Electronic messaging, particularly instant messaging, continues to grow globally in popularity. Users are quickly able to share with one another electronic media content items including text, electronic images, audio, and video instantly.

(2) With the increasing number of users on social networking systems, each user also has a growing network of individuals that she follows. Therefore, in order to maintain the user engagement on social networking systems, it is paramount that the systems have the ability to present to each user the media content items that are most interesting or relevant to her. The social networking systems are presented with the challenge of presenting a user the media content items that have been

commented by her friends, for the reason that such media content items are the most interesting and relevant to the user.

Description

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

- (1) In the drawings, which are not necessarily drawn to scale, like numerals may describe similar components in different views. To easily identify the discussion of any particular element or act, the most significant digit or digits in a reference number refer to the figure number in which that element is first introduced. Some embodiments are illustrated by way of example, and not limitation, in the figures of the accompanying drawings in which:
- (2) FIG. 1 is a diagrammatic representation of a networked environment in which the present disclosure may be deployed, in accordance with some examples.
- (3) FIG. 2 is a diagrammatic representation of a messaging system, in accordance with some examples, that has both client-side and server-side functionality.
- (4) FIG. 3 is a diagrammatic representation of a data structure as maintained in a database, in accordance with some examples.
- (5) FIG. 4 is a diagrammatic representation of a message, in accordance with some examples.
- (6) FIG. 5 is a flowchart for an access-limiting process, in accordance with some examples.
- (7) FIG. 6 illustrates a process **600** of generating a playback of a media content item in accordance with one embodiment.
- (8) FIG. 7 illustrates a user interface **700** displayed on a client device in accordance with one embodiment.
- (9) FIG. 8 illustrates a user interface **800** displayed on a client device in accordance with one embodiment.
- (10) FIG. 9 illustrates a user interface **900** displayed on a client device in accordance with one embodiment.
- (11) FIG. 10 illustrates a user interface **1000** displayed on a client device in accordance with one embodiment.
- (12) FIG. 11 illustrates a user interface **1100** displayed on a client device in accordance with one embodiment.
- (13) FIG. 12 is a diagrammatic representation of a machine in the form of a computer system within which a set of instructions may be executed for causing the machine to perform any one or more of the methodologies discussed herein, in accordance with some examples.
- (14) FIG. 13 is a block diagram showing a software architecture within which examples may be implemented.
- (15) FIG. 14 is a diagrammatic representation of a processing environment, in accordance with some examples.

DETAILED DESCRIPTION

- (16) In messaging systems, users are connected to a variety of other users with whom they have different levels and types of relationships. For example, a user can be socially connected to a group of users who are close friends, co-workers, acquaintances, as well as people the user does not know outside of the messaging system. The social connection a user can establish with another user in the messaging system may include a unilateral friendship relationship and a bilateral friendship relationship.
- (17) The social networking systems are presented with the challenge of providing a user media content items without a showing of comments made by individuals unknown by the user, as such unknown individuals may post irrelevant or sometimes emotionally distressing comments to the media content items shared with the user, negatively affecting user experience. In addition, the

social networking systems are also presented with the challenge of withholding a complete comment thread to a user, in view of the fact the user may experience some degree of emotional distress if she fails to receive a further comment from her friends in response to her comment in the thread.

(18) Embodiments of the present disclosure improve the functionality of electronic messaging software and systems by recognizing that a user may want to receive media content items associated with comments only coming from other users with whom the user has established a social relationship (e.g., friendship) on the messaging system. Specifically, the embodiments of the present disclosure relate to generating a playback of media content items available on the messaging system with comments created only by friends of a viewing user. The viewing user may post comments to the media content item. Each comment is associated with a timestamp representing the temporal position during the time of playback when the comment was created. Each comment is displayed during the playback at respective temporal position (e.g., timeline marker), so that the viewing user may experience the creations of the comments from friends.

(19) In some embodiments, upon selection of a comment, the messaging system may direct the user to a private messaging user interface to engage in a private conversation with the comment creator. Therefore, no comment thread is generated for media content items. It helps to advance the goal of avoiding the generation of a complete comment thread viewable by all users, inadvertently causing emotional distress to certain affected users.

(20) The present disclosure also relates to generating notifications of a comment created by a friend of the user associated with a media content item. A pre-determined time period (e.g., a cool-down period) is determined and assessed between the generation of notifications on a client device.

(21) In some embodiments, the user may post comments at any time during the display of a media content item. The user may mention other friends in the comments, which may be shared by the messaging system with friends mentioned in the comments. In some embodiments, the media content items are created by commercial content creators or designated users whose user profile is not connected with the viewing user in an entity graph stored in the messaging system. For example, a designated user is not a friend with the user who requests to view the media content item that the designated user has created.

(22) Networked Computing Environment

(23) FIG. 1 is a block diagram showing an example messaging system **100** for exchanging data (e.g., messages and associated content) over a network. The messaging system **100** includes multiple instances of a client device **102**, each of which hosts a number of applications, including a messaging client **104**. Each messaging client **104** is communicatively coupled to other instances of the messaging client **104** and a messaging server system **108** via a network **106** (e.g., the Internet).

(24) A messaging client **104** is able to communicate and exchange data with another messaging client **104** and with the messaging server system **108** via the network **106**. The data exchanged between messaging client **104**, and between a messaging client **104** and the messaging server system **108**, includes functions (e.g., commands to invoke functions) as well as payload data (e.g., text, audio, video or other multimedia data).

(25) The messaging server system **108** provides server-side functionality via the network **106** to a particular messaging client **104**. While certain functions of the messaging system **100** are described herein as being performed by either a messaging client **104** or by the messaging server system **108**, the location of certain functionality either within the messaging client **104** or the messaging server system **108** may be a design choice. For example, it may be technically preferable to initially deploy certain technology and functionality within the messaging server system **108** but to later migrate this technology and functionality to the messaging client **104** where a client device **102** has sufficient processing capacity.

(26) The messaging server system **108** supports various services and operations that are provided to the messaging client **104**. Such operations include transmitting data to, receiving data from, and

processing data generated by the messaging client **104**. This data may include message content, client device information, geolocation information, media augmentation and overlays, message content persistence conditions, social network information, and live event information, as examples. Data exchanges within the messaging system **100** are invoked and controlled through functions available via user interfaces (UIs) of the messaging client **104**.

(27) Turning now specifically to the messaging server system **108**, an Application Program Interface (API) server **110** is coupled to, and provides a programmatic interface to, application servers **112**. The application servers **112** are communicatively coupled to a database server **118**, which facilitates access to a database **120** that stores data associated with messages processed by the application servers **112**. Similarly, a web server **124** is coupled to the application servers **112** and provides web-based interfaces to the application servers **112**. To this end, the web server **124** processes incoming network requests over the Hypertext Transfer Protocol (HTTP) and several other related protocols.

(28) The Application Program Interface (API) server **110** receives and transmits message data (e.g., commands and message payloads) between the client device **102** and the application servers **112**. Specifically, the Application Program Interface (API) server **110** provides a set of interfaces (e.g., routines and protocols) that can be called or queried by the messaging client **104** in order to invoke functionality of the application servers **112**. The Application Program Interface (API) server **110** exposes various functions supported by the application servers **112**, including account registration, login functionality, the sending of messages, via the application servers **112**, from a particular messaging client **104** to another messaging client **104**, the sending of media files (e.g., images or video) from a messaging client **104** to a messaging server **114**, and for possible access by another messaging client **104**, the settings of a collection of media data (e.g., story), the retrieval of a list of friends of a user of a client device **102**, the retrieval of such collections, the retrieval of messages and content, the addition and deletion of entities (e.g., friends) to an entity graph (e.g., a social graph), the location of friends within a social graph, and opening an application event (e.g., relating to the messaging client **104**).

(29) The application servers **112** host a number of server applications and subsystems, including for example a messaging server **114**, an image processing server **116**, and a social network server **122**. The messaging server **114** implements a number of message processing technologies and functions, particularly related to the aggregation and other processing of content (e.g., textual and multimedia content) included in messages received from multiple instances of the messaging client **104**. As will be described in further detail, the text and media content from multiple sources may be aggregated into collections of content (e.g., called stories or galleries). These collections are then made available to the messaging client **104**. Other processor and memory intensive processing of data may also be performed server-side by the messaging server **114**, in view of the hardware requirements for such processing.

(30) The application servers **112** also include an image processing server **116** that is dedicated to performing various image processing operations, typically with respect to images or video within the payload of a message sent from or received at the messaging server **114**.

(31) The social network server **122** supports various social networking functions and services and makes these functions and services available to the messaging server **114**. To this end, the social network server **122** maintains and accesses an entity graph **306** (as shown in FIG. 3) within the database **120**. Examples of functions and services supported by the social network server **122** include the identification of other users of the messaging system **100** with which a particular user has relationships or is “following,” and also the identification of other entities and interests of a particular user.

(32) System Architecture

(33) FIG. 2 is a block diagram illustrating further details regarding the messaging system **100**, according to some examples. Specifically, the messaging system **100** is shown to comprise the

messaging client **104** and the application servers **112**. The messaging system **100** embodies a number of subsystems, which are supported on the client-side by the messaging client **104** and on the sever-side by the application servers **112**. These subsystems include, for example, an ephemeral timer system **202**, a collection management system **204**, an augmentation system **206**, a map system **208**, and a game system **210**.

(34) The ephemeral timer system **202** is responsible for enforcing the temporary or time-limited access to content by the messaging client **104** and the messaging server **114**. The ephemeral timer system **202** incorporates a number of timers that, based on duration and display parameters associated with a message, or collection of messages (e.g., a story), selectively enable access (e.g., for presentation and display) to messages and associated content via the messaging client **104**. Further details regarding the operation of the ephemeral timer system **202** are provided below. In one embodiment, the ephemeral timer system **202** is also responsible for determining a pre-determined duration of time for playback of media content items, such as the media content item **702** as shown in FIG. 7. In one embodiment, the ephemeral timer system **202** is further responsible for determining a pre-determined time duration of the display of a comment during the playback of a media content item.

(35) The collection management system **204** is responsible for managing sets or collections of media (e.g., collections of text, image video, and audio data). A collection of content (e.g., messages, including images, video, text, and audio) may be organized into an “event gallery” or an “event story.” Such a collection may be made available for a specified time period, such as the duration of an event to which the content relates. For example, content relating to a music concert may be made available for the duration of that music concert. The collection management system **204** may also be responsible for publishing an icon that provides notification of the existence of a particular collection to the user interface of the messaging client **104**.

(36) The collection management system **204** furthermore includes a curation interface **212** that allows a collection manager to manage and curate a particular collection of content. For example, the curation interface **212** enables an event organizer to curate a collection of content relating to a specific event (e.g., delete inappropriate content or redundant messages). Additionally, the collection management system **204** employs machine vision (or image recognition technology) and content rules to automatically curate a content collection. In certain examples, compensation may be paid to a user for the inclusion of user-generated content into a collection. In such cases, the collection management system **204** operates to automatically make payments to such users for the use of their content.

(37) In one embodiment, collection management system **204** is responsible for managing a collection of media content items that can be viewed and commented by users in the messaging server system **108**. The collection of media content items may include media content items created by commercial content creators or designated users. The commercial content creator may be a third party publisher, such as New York Times, Vice, etc. The designated users may include users who have a large number of followers. User profiles may be stored as profile data **308** in the entity table **304** in the database **120**. The number of followers is determined by a number of user profiles being unilaterally connected to the designated user profile in the entity table **304**. Specifically, the type of connections between two user profiles may include a bilateral connection and a unilateral connection, respectively represented by a bilateral connection identifier and a unilateral connection identifier associated with each user profile in the entity table **304**. The bilateral connection indicates the connected users have each responded to a friendship request sent from the other user via a client device **102**. The unilateral connection indicates only one of the two connected users has requested friendship connection, but the requested user has not responded to or has denied such request. The number of followers of the designated user is determined by the number of unilaterally connected user profiles associated with users who have requested friendship connection with the designated user, but the designated user has not responded to or has denied the request. A number

of friends of a user may be determined by a number of bilaterally connected user profiles in the entity table **304**.

(38) In one embodiment, the designated user is determined by an administrator of the messaging server system **108**. The user profile associated with the designated user is absent from the set of connected profiles. Specifically, the designated user has not established a bilateral connection with the user who requests to view the media content item the designated user has created.

(39) In one embodiment, the collection management system **204** is responsible for causing a display of only the comments created by friends of a user who requests to view a media content item. In one embodiment, when the collection management system **204** causes a client device **102** to playback a media content item (e.g., a video or an image), an image is displayed within a pre-determined duration of time, such as five seconds. A video displays for the duration the video lasts. Each comment created by a user for a media content item is associated with a user profile and a timestamp representing a time within the duration of time displaying a media content item in which each comment was created.

(40) The augmentation system **206** provides various functions that enable a user to augment (e.g., annotate or otherwise modify or edit) media content associated with a message. For example, the augmentation system **206** provides functions related to the generation and publishing of media overlays for messages processed by the messaging system **100**. The augmentation system **206** operatively supplies a media overlay or augmentation (e.g., an image filter) to the messaging client **104** based on a geolocation of the client device **102**. In another example, the augmentation system **206** operatively supplies a media overlay to the messaging client **104** based on other information, such as social network information of the user of the client device **102**. A media overlay may include audio and visual content and visual effects. Examples of audio and visual content include pictures, texts, logos, animations, and sound effects. An example of a visual effect includes color overlaying. The audio and visual content or the visual effects can be applied to a media content item (e.g., a photo) at the client device **102**. For example, the media overlay may include text or image that can be overlaid on top of a photograph taken by the client device **102**. In another example, the media overlay includes an identification of a location overlay (e.g., Venice beach), a name of a live event, or a name of a merchant overlay (e.g., Beach Coffee House). In another example, the augmentation system **206** uses the geolocation of the client device **102** to identify a media overlay that includes the name of a merchant at the geolocation of the client device **102**. The media overlay may include other indicia associated with the merchant. The media overlays may be stored in the database **120** and accessed through the database server **118**.

(41) In some examples, the augmentation system **206** provides a user-based publication platform that enables users to select a geolocation on a map and upload content associated with the selected geolocation. The user may also specify circumstances under which a particular media overlay should be offered to other users. The augmentation system **206** generates a media overlay that includes the uploaded content and associates the uploaded content with the selected geolocation.

(42) In other examples, the augmentation system **206** provides a merchant-based publication platform that enables merchants to select a particular media overlay associated with a geolocation via a bidding process. For example, the augmentation system **206** associates the media overlay of the highest bidding merchant with a corresponding geolocation for a predefined amount of time.

(43) The map system **208** provides various geographic location functions and supports the presentation of map-based media content and messages by the messaging client **104**. For example, the map system **208** enables the display of user icons or avatars (e.g., stored in profile data **308**) on a map to indicate a current or past location of “friends” of a user, as well as media content (e.g., collections of messages including photographs and videos) generated by such friends, within the context of a map. For example, a message posted by a user to the messaging system **100** from a specific geographic location may be displayed within the context of a map at that particular location to “friends” of a specific user on a map interface of the messaging client **104**. A user can

furthermore share his or her location and status information (e.g., using an appropriate status avatar) with other users of the messaging system **100** via the messaging client **104**, with this location and status information being similarly displayed within the context of a map interface of the messaging client **104** to selected users.

(44) The game system **210** provides various gaming functions within the context of the messaging client **104**. The messaging client **104** provides a game interface providing a list of available games that can be launched by a user within the context of the messaging client **104**, and played with other users of the messaging system **100**. The messaging system **100** further enables a particular user to invite other users to participate in the play of a specific game, by issuing invitations to such other users from the messaging client **104**. The messaging client **104** also supports both the voice and text messaging (e.g., chats) within the context of gameplay, provides a leaderboard for the games, and also supports the provision of in-game rewards (e.g., coins and items).

(45) Data Architecture

(46) FIG. 3 is a schematic diagram illustrating data structures **300**, which may be stored in the database **120** of the messaging server system **108**, according to certain examples. While the content of the database **120** is shown to comprise a number of tables, it will be appreciated that the data could be stored in other types of data structures (e.g., as an object-oriented database).

(47) The database **120** includes message data stored within a message table **302**. This message data includes, for any particular one message, at least message sender data, message recipient (or receiver) data, and a payload. Further details regarding information that may be included in a message, and included within the message data stored in the message table **302** is described below with reference to FIG. 4.

(48) An entity table **304** stores entity data, and is linked (e.g., referentially) to an entity graph **306** and profile data **308**. Entities for which records are maintained within the entity table **304** may include individuals, corporate entities, organizations, objects, places, events, and so forth. Regardless of entity type, any entity regarding which the messaging server system **108** stores data may be a recognized entity. Each entity is provided with a unique identifier, as well as an entity type identifier (not shown).

(49) The entity graph **306** stores information regarding relationships and associations between entities. Such relationships may be social, professional (e.g., work at a common corporation or organization) interested-based or activity-based, merely for example.

(50) The profile data **308** stores multiple types of profile data about a particular entity. The profile data **308** may be selectively used and presented to other users of the messaging system **100**, based on privacy settings specified by a particular entity. Where the entity is an individual, the profile data **308** includes, for example, a user name, telephone number, address, settings (e.g., notification and privacy settings), as well as a user-selected avatar representation (or collection of such avatar representations). A particular user may then selectively include one or more of these avatar representations within the content of messages communicated via the messaging system **100**, and on map interfaces displayed by messaging clients **104** to other users. The collection of avatar representations may include “status avatars,” which present a graphical representation of a status or activity that the user may select to communicate at a particular time.

(51) Where the entity is a group, the profile data **308** for the group may similarly include one or more avatar representations associated with the group, in addition to the group name, members, and various settings (e.g., notifications) for the relevant group.

(52) The database **120** also stores augmentation data, such as overlays or filters, in an augmentation table **310**. The augmentation data is associated with and applied to videos (for which data is stored in a video table **314**) and images (for which data is stored in an image table **316**).

(53) Filters, in one example, are overlays that are displayed as overlaid on an image or video during presentation to a recipient user. Filters may be of various types, including user-selected filters from a set of filters presented to a sending user by the messaging client **104** when the sending user is

composing a message. Other types of filters include geolocation filters (also known as geo-filters), which may be presented to a sending user based on geographic location. For example, geolocation filters specific to a neighborhood or special location may be presented within a user interface by the messaging client **104**, based on geolocation information determined by a Global Positioning System (GPS) unit of the client device **102**.

(54) Another type of filter is a data filter, which may be selectively presented to a sending user by the messaging client **104**, based on other inputs or information gathered by the client device **102** during the message creation process. Examples of data filters include current temperature at a specific location, a current speed at which a sending user is traveling, battery life for a client device **102**, or the current time.

(55) Other augmentation data that may be stored within the image table **316** includes augmented reality content items (e.g., corresponding to applying Lenses or augmented reality experiences). An augmented reality content item may be a real-time special effect and sound that may be added to an image or a video.

(56) As described above, augmentation data includes augmented reality content items, overlays, image transformations, AR images, and similar terms refer to modifications that may be applied to image data (e.g., videos or images). This includes real-time modifications, which modify an image as it is captured using device sensors (e.g., one or multiple cameras) of a client device **102** and then displayed on a screen of the client device **102** with the modifications. This also includes modifications to stored content, such as video clips in a gallery that may be modified. For example, in a client device **102** with access to multiple augmented reality content items, a user can use a single video clip with multiple augmented reality content items to see how the different augmented reality content items will modify the stored clip. For example, multiple augmented reality content items that apply different pseudorandom movement models can be applied to the same content by selecting different augmented reality content items for the content. Similarly, real-time video capture may be used with an illustrated modification to show how video images currently being captured by sensors of a client device **102** would modify the captured data. Such data may simply be displayed on the screen and not stored in memory, or the content captured by the device sensors may be recorded and stored in memory with or without the modifications (or both). In some systems, a preview feature can show how different augmented reality content items will look within different windows in a display at the same time. This can, for example, enable multiple windows with different pseudorandom animations to be viewed on a display at the same time.

(57) Data and various systems using augmented reality content items or other such transformation systems to modify content using this data can thus involve detection of objects (e.g., faces, hands, bodies, cats, dogs, surfaces, objects, etc.), tracking of such objects as they leave, enter, and move around the field of view in video frames, and the modification or transformation of such objects as they are tracked. In various embodiments, different methods for achieving such transformations may be used. Some examples may involve generating a three-dimensional mesh model of the object or objects, and using transformations and animated textures of the model within the video to achieve the transformation. In other examples, tracking of points on an object may be used to place an image or texture (which may be two dimensional or three dimensional) at the tracked position. In still further examples, neural network analysis of video frames may be used to place images, models, or textures in content (e.g., images or frames of video). Augmented reality content items thus refer both to the images, models, and textures used to create transformations in content, as well as to additional modeling and analysis information needed to achieve such transformations with object detection, tracking, and placement.

(58) Real-time video processing can be performed with any kind of video data (e.g., video streams, video files, etc.) saved in a memory of a computerized system of any kind. For example, a user can load video files and save them in a memory of a device, or can generate a video stream using sensors of the device. Additionally, any objects can be processed using a computer animation

model, such as a human's face and parts of a human body, animals, or non-living things such as chairs, cars, or other objects.

(59) In some examples, when a particular modification is selected along with content to be transformed, elements to be transformed are identified by the computing device, and then detected and tracked if they are present in the frames of the video. The elements of the object are modified according to the request for modification, thus transforming the frames of the video stream.

Transformation of frames of a video stream can be performed by different methods for different kinds of transformation. For example, for transformations of frames mostly referring to changing forms of object's elements characteristic points for each element of an object are calculated (e.g., using an Active Shape Model (ASM) or other known methods). Then, a mesh based on the characteristic points is generated for each of the at least one element of the object. This mesh used in the following stage of tracking the elements of the object in the video stream. In the process of tracking, the mentioned mesh for each element is aligned with a position of each element. Then, additional points are generated on the mesh. A first set of first points is generated for each element based on a request for modification, and a set of second points is generated for each element based on the set of first points and the request for modification. Then, the frames of the video stream can be transformed by modifying the elements of the object on the basis of the sets of first and second points and the mesh. In such method, a background of the modified object can be changed or distorted as well by tracking and modifying the background.

(60) In some examples, transformations changing some areas of an object using its elements can be performed by calculating characteristic points for each element of an object and generating a mesh based on the calculated characteristic points. Points are generated on the mesh, and then various areas based on the points are generated. The elements of the object are then tracked by aligning the area for each element with a position for each of the at least one element, and properties of the areas can be modified based on the request for modification, thus transforming the frames of the video stream. Depending on the specific request for modification properties of the mentioned areas can be transformed in different ways. Such modifications may involve changing color of areas; removing at least some part of areas from the frames of the video stream; including one or more new objects into areas which are based on a request for modification; and modifying or distorting the elements of an area or object. In various embodiments, any combination of such modifications or other similar modifications may be used. For certain models to be animated, some characteristic points can be selected as control points to be used in determining the entire state-space of options for the model animation.

(61) In some examples of a computer animation model to transform image data using face detection, the face is detected on an image with use of a specific face detection algorithm (e.g., Viola-Jones). Then, an Active Shape Model (ASM) algorithm is applied to the face region of an image to detect facial feature reference points.

(62) In other examples, other methods and algorithms suitable for face detection can be used. For example, in some embodiments, features are located using a landmark, which represents a distinguishable point present in most of the images under consideration. For facial landmarks, for example, the location of the left eye pupil may be used. If an initial landmark is not identifiable (e.g., if a person has an eyepatch), secondary landmarks may be used. Such landmark identification procedures may be used for any such objects. In some examples, a set of landmarks forms a shape. Shapes can be represented as vectors using the coordinates of the points in the shape. One shape is aligned to another with a similarity transform (allowing translation, scaling, and rotation) that minimizes the average Euclidean distance between shape points. The mean shape is the mean of the aligned training shapes.

(63) In some examples, a search for landmarks from the mean shape aligned to the position and size of the face determined by a global face detector is started. Such a search then repeats the steps of suggesting a tentative shape by adjusting the locations of shape points by template matching of

the image texture around each point and then conforming the tentative shape to a global shape model until convergence occurs. In some systems, individual template matches are unreliable, and the shape model pools the results of the weak template matches to form a stronger overall classifier. The entire search is repeated at each level in an image pyramid, from coarse to fine resolution.

(64) A transformation system can capture an image or video stream on a client device (e.g., the client device **102**) and perform complex image manipulations locally on the client device **102** while maintaining a suitable user experience, computation time, and power consumption. The complex image manipulations may include size and shape changes, emotion transfers (e.g., changing a face from a frown to a smile), state transfers (e.g., aging a subject, reducing apparent age, changing gender), style transfers, graphical element application, and any other suitable image or video manipulation implemented by a convolutional neural network that has been configured to execute efficiently on the client device **102**.

(65) In some examples, a computer animation model to transform image data can be used by a system where a user may capture an image or video stream of the user (e.g., a selfie) using a client device **102** having a neural network operating as part of a messaging client application **104** operating on the client device **102**. The transformation system operating within the messaging client **104** determines the presence of a face within the image or video stream and provides modification icons associated with a computer animation model to transform image data, or the computer animation model can be present as associated with an interface described herein. The modification icons include changes that may be the basis for modifying the user's face within the image or video stream as part of the modification operation. Once a modification icon is selected, the transformation system initiates a process to convert the image of the user to reflect the selected modification icon (e.g., generate a smiling face on the user). A modified image or video stream may be presented in a graphical user interface displayed on the client device **102** as soon as the image or video stream is captured, and a specified modification is selected. The transformation system may implement a complex convolutional neural network on a portion of the image or video stream to generate and apply the selected modification. That is, the user may capture the image or video stream and be presented with a modified result in real-time or near real-time once a modification icon has been selected. Further, the modification may be persistent while the video stream is being captured, and the selected modification icon remains toggled. Machine taught neural networks may be used to enable such modifications.

(66) The graphical user interface, presenting the modification performed by the transformation system, may supply the user with additional interaction options. Such options may be based on the interface used to initiate the content capture and selection of a particular computer animation model (e.g., initiation from a content creator user interface). In various embodiments, a modification may be persistent after an initial selection of a modification icon. The user may toggle the modification on or off by tapping or otherwise selecting the face being modified by the transformation system and store it for later viewing or browse to other areas of the imaging application. Where multiple faces are modified by the transformation system, the user may toggle the modification on or off globally by tapping or selecting a single face modified and displayed within a graphical user interface. In some embodiments, individual faces, among a group of multiple faces, may be individually modified, or such modifications may be individually toggled by tapping or selecting the individual face or a series of individual faces displayed within the graphical user interface.

(67) A story table **312** stores data regarding collections of messages and associated image, video, or audio data, which are compiled into a collection (e.g., a story or a gallery). The creation of a particular collection may be initiated by a particular user (e.g., each user for which a record is maintained in the entity table **304**). A user may create a "personal story" in the form of a collection of content that has been created and sent/broadcast by that user. To this end, the user interface of the messaging client **104** may include an icon that is user-selectable to enable a sending user to add specific content to his or her personal story.

(68) A collection may also constitute a “live story,” which is a collection of content from multiple users that is created manually, automatically, or using a combination of manual and automatic techniques. For example, a “live story” may constitute a curated stream of user-submitted content from various locations and events. Users whose client devices have location services enabled and are at a common location event at a particular time may, for example, be presented with an option, via a user interface of the messaging client **104**, to contribute content to a particular live story. The live story may be identified to the user by the messaging client **104**, based on his or her location. The end result is a “live story” told from a community perspective.

(69) A further type of content collection is known as a “location story,” which enables a user whose client device **102** is located within a specific geographic location (e.g., on a college or university campus) to contribute to a particular collection. In some examples, a contribution to a location story may require a second degree of authentication to verify that the end user belongs to a specific organization or other entity (e.g., is a student on the university campus).

(70) As mentioned above, the video table **314** stores video data that, in one example, is associated with messages for which records are maintained within the message table **302**. Similarly, the image table **316** stores image data associated with messages for which message data is stored in the entity table **304**. The entity table **304** may associate various augmentations from the augmentation table **310** with various images and videos stored in the image table **316** and the video table **314**. In one embodiment, the image table **316** stores image data associated with an image-type media content item and the comments associated with the image. The video table **314** stores video data associated with a video-type media content item and the comments associated with the video.

(71) Data Communications Architecture

(72) FIG. 4 is a schematic diagram illustrating a structure of a message **400**, according to some examples, generated by a messaging client **104** for communication to a further messaging client **104** or the messaging server **114**. The content of a particular message **400** is used to populate the message table **302** stored within the database **120**, accessible by the messaging server **114**. Similarly, the content of a message **400** is stored in memory as “in-transit” or “in-flight” data of the client device **102** or the application servers **112**. A message **400** is shown to include the following example components: message identifier **402**: a unique identifier that identifies the message **400**. message text payload **404**: text, to be generated by a user via a user interface of the client device **102**, and that is included in the message **400**. message image payload **406**: image data, captured by a camera component of a client device **102** or retrieved from a memory component of a client device **102**, and that is included in the message **400**. Image data for a sent or received message **400** may be stored in the image table **316**. message video payload **408**: video data, captured by a camera component or retrieved from a memory component of the client device **102**, and that is included in the message **400**. Video data for a sent or received message **400** may be stored in the video table **314**. message audio payload **410**: audio data, captured by a microphone or retrieved from a memory component of the client device **102**, and that is included in the message **400**. message augmentation data **412**: augmentation data (e.g., filters, stickers, or other annotations or enhancements) that represents augmentations to be applied to message image payload **406**, message video payload **408**, or message audio payload **410** of the message **400**. Augmentation data for a sent or received message **400** may be stored in the augmentation table **310**. message duration parameter **414**: parameter value indicating, in seconds, the amount of time for which content of the message (e.g., the message image payload **406**, message video payload **408**, message audio payload **410**) is to be presented or made accessible to a user via the messaging client **104**. message geolocation parameter **416**: geolocation data (e.g., latitudinal and longitudinal coordinates) associated with the content payload of the message. Multiple message geolocation parameter **416** values may be included in the payload, each of these parameter values being associated with respect to content items included in the content (e.g., a specific image into within the message image payload **406**, or a specific video in the message video payload **408**). message story identifier

418: identifier values identifying one or more content collections (e.g., “stories” identified in the story table **312**) with which a particular content item in the message image payload **406** of the message **400** is associated. For example, multiple images within the message image payload **406** may each be associated with multiple content collections using identifier values. **message tag 420:** each message **400** may be tagged with multiple tags, each of which is indicative of the subject matter of content included in the message payload. For example, where a particular image included in the message image payload **406** depicts an animal (e.g., a lion), a tag value may be included within the message tag **420** that is indicative of the relevant animal. Tag values may be generated manually, based on user input, or may be automatically generated using, for example, image recognition. **message sender identifier 422:** an identifier (e.g., a messaging system identifier, email address, or device identifier) indicative of a user of the client device **102** on which the message **400** was generated and from which the message **400** was sent. **message receiver identifier 424:** an identifier (e.g., a messaging system identifier, email address, or device identifier) indicative of a user of the client device **102** to which the message **400** is addressed.

(73) The contents (e.g., values) of the various components of message **400** may be pointers to locations in tables within which content data values are stored. For example, an image value in the message image payload **406** may be a pointer to (or address of) a location within an image table **316**. Similarly, values within the message video payload **408** may point to data stored within a video table **314**, values stored within the message augmentations data **412** may point to data stored in an augmentation table **310**, values stored within the message story identifier **418** may point to data stored in a story table **312**, and values stored within the message sender identifier **422** and the message receiver identifier **424** may point to user records stored within an entity table **304**.

(74) Time-Based Access Limitation Architecture

(75) FIG. 5 is a schematic diagram illustrating an access-limiting process **500**, in terms of which access to content (e.g., an ephemeral message **502**, and associated multimedia payload of data) or a content collection (e.g., an ephemeral message group **504**) may be time-limited (e.g., made ephemeral).

(76) An ephemeral message **502** is shown to be associated with a message duration parameter **506**, the value of which determines an amount of time that the ephemeral message **502** will be displayed to a receiving user of the ephemeral message **502** by the messaging client **104**. In one example, an ephemeral message **502** is viewable by a receiving user for up to a maximum of 10 seconds, depending on the amount of time that the sending user specifies using the message duration parameter **506**. In one embodiment, the ephemeral message **502** may include a media content item, such as the media content item **702** as shown in FIG. 7. The ephemeral message **502** may include a comment displayed during the playback of a media content item.

(77) The message duration parameter **506** and the message receiver identifier **424** are shown to be inputs to a message timer **512**, which is responsible for determining the amount of time that the ephemeral message **502** is shown to a particular receiving user identified by the message receiver identifier **424**. In particular, the ephemeral message **502** will only be shown to the relevant receiving user for a time period determined by the value of the message duration parameter **506**. The message timer **512** is shown to provide output to a more generalized ephemeral timer system **202**, which is responsible for the overall timing of display of content (e.g., an ephemeral message **502**) to a receiving user. In one embodiment, the message duration parameter **506** includes a pre-determined duration of time of media content playback, a pre-defined time duration for a display of a comment during a media content playback.

(78) The ephemeral message **502** is shown in FIG. 5 to be included within an ephemeral message group **504** (e.g., a collection of messages in a personal story, or an event story). The ephemeral message group **504** has an associated group duration parameter **508**, a value of which determines a time duration for which the ephemeral message group **504** is presented and accessible to users of the messaging system **100**. The group duration parameter **508**, for example, may be the duration of

a music concert, where the ephemeral message group **504** is a collection of content pertaining to that concert. Alternatively, a user (either the owning user or a curator user) may specify the value for the group duration parameter **508** when performing the setup and creation of the ephemeral message group **504**.

(79) Additionally, each ephemeral message **502** within the ephemeral message group **504** has an associated group participation parameter **510**, a value of which determines the duration of time for which the ephemeral message **502** will be accessible within the context of the ephemeral message group **504**. Accordingly, a particular ephemeral message group **504** may “expire” and become inaccessible within the context of the ephemeral message group **504**, prior to the ephemeral message group **504** itself expiring in terms of the group duration parameter **508**. The group duration parameter **508**, group participation parameter **510**, and message receiver identifier **424** each provide input to a group timer **514**, which operationally determines, firstly, whether a particular ephemeral message **502** of the ephemeral message group **504** will be displayed to a particular receiving user and, if so, for how long. Note that the ephemeral message group **504** is also aware of the identity of the particular receiving user as a result of the message receiver identifier **424**.

(80) Accordingly, the group timer **514** operationally controls the overall lifespan of an associated ephemeral message group **504**, as well as an individual ephemeral message **502** included in the ephemeral message group **504**. In one example, each and every ephemeral message **502** within the ephemeral message group **504** remains viewable and accessible for a time period specified by the group duration parameter **508**. In a further example, a certain ephemeral message **502** may expire, within the context of ephemeral message group **504**, based on a group participation parameter **510**. Note that a message duration parameter **506** may still determine the duration of time for which a particular ephemeral message **502** is displayed to a receiving user, even within the context of the ephemeral message group **504**. Accordingly, the message duration parameter **506** determines the duration of time that a particular ephemeral message **502** is displayed to a receiving user, regardless of whether the receiving user is viewing that ephemeral message **502** inside or outside the context of an ephemeral message group **504**.

(81) The ephemeral timer system **202** may furthermore operationally remove a particular ephemeral message **502** from the ephemeral message group **504** based on a determination that it has exceeded an associated group participation parameter **510**. For example, when a sending user has established a group participation parameter **510** of 24 hours from posting, the ephemeral timer system **202** will remove the relevant ephemeral message **502** from the ephemeral message group **504** after the specified 24 hours. The ephemeral timer system **202** also operates to remove an ephemeral message group **504** when either the group participation parameter **510** for each and every ephemeral message **502** within the ephemeral message group **504** has expired, or when the ephemeral message group **504** itself has expired in terms of the group duration parameter **508**.

(82) In certain use cases, a creator of a particular ephemeral message group **504** may specify an indefinite group duration parameter **508**. In this case, the expiration of the group participation parameter **510** for the last remaining ephemeral message **502** within the ephemeral message group **504** will determine when the ephemeral message group **504** itself expires. In this case, a new ephemeral message **502**, added to the ephemeral message group **504**, with a new group participation parameter **510**, effectively extends the life of an ephemeral message group **504** to equal the value of the group participation parameter **510**.

(83) Responsive to the ephemeral timer system **202** determining that an ephemeral message group **504** has expired (e.g., is no longer accessible), the ephemeral timer system **202** communicates with the messaging system **100** (and, for example, specifically the messaging client **104**) to cause an indicium (e.g., an icon) associated with the relevant ephemeral message group **504** to no longer be displayed within a user interface of the messaging client **104**. Similarly, when the ephemeral timer system **202** determines that the message duration parameter **506** for a particular ephemeral message

502 has expired, the ephemeral timer system **202** causes the messaging client **104** to no longer display an indicium (e.g., an icon or textual identification) associated with the ephemeral message **502**.

(84) Media Content Playback and Comments Management

(85) In one embodiment, a user associated with the first client device **102** may send a request to the messaging server system **108** to view a media content item. The messaging server system **108** determines, based on connections of user profiles in entity graph **306**, at least one comment from a connected user profile (e.g., friends) at a particular time in which the one comment was created during the playback of the media content item.

(86) FIG. **6** illustrates a process **600** of generating a playback of a media content item in accordance with one embodiment. The operations of process **600** may be performed by any number of different systems, such as the messaging server **114** or the messaging client **104** described herein, or any portion thereof, such as a processor included in any of the systems.

(87) At operation **602**, the processor receives a request from a client device **102** to view a playback of a media content item. The media content item can be images, pictures, videos, text, or any combination thereof. FIG. **7** illustrates user interface **700** that can be displayed on the first client device **102**. The media content item **702** as shown in FIG. **7** is an image or a video of a person. The user interface **700** also includes a summary comments selectable item **704**, a playback progress bar **706**, and a plurality of timeline markers **708**. The creator name item **718** indicates the entity (e.g., XYZ) who created the media content item **702**. In one embodiment, the entity XYZ is either a commercial content creator or a designated user.

(88) The client device **102** is associated with a user. The user is associated with a viewer profile in the entity graph **306**. The media content item is associated with a set of comments represented by the summary comments selectable item **704**. The media content item **702** has a duration of time for playback. The duration of time is represented by the playback progress bar **706**. The duration of playback for image type media content may be five seconds, for example. The duration for video type media content is however long the video lasts. Each comment associated with a media content item is associated with a user profile and a timestamp representing a particular time within the duration of playback in which each comment was created. The plurality of timeline markers **708** represent the points in time when the comments included by the summary comments selectable item **704** was created.

(89) A user profile may be associated with an entity identifier representing a user. The viewer profile of the user is associated with a set of connected profiles representing connected users in the entity graph **306** in FIG. **3**. In one embodiment, the connections between the viewer profile and the connected profiles are bilateral connections (e.g., friendship connections), such that the summary comments selectable item **704** is generated only based on comments that were created by a friend or friends of the user who requests to view the media content item **702**.

(90) At operation **604**, the processor determines at least one comment associated with a respective user profile from the set of connected profiles, that the at least one comment associated with a particular time within the duration of time in which the at least one comment was created. For example, the first user created the first comment at the temporal position represented by the timeline marker **708**. When a requesting user views the playback of the media content item **702**, the first comment is displayed only at the timeline marker **708** during the playback of the media content item **702**. In one embodiment, the temporal position at the timeline marker **708** is identified by a timestamp associated with the comment stored in the video table **314** or the image table **316** in database **120**. In one embodiment, the display of a particular comment lasts for a pre-defined time duration, or up to a display of an immediate later created comment, provided that the later created comment was created before the pre-defined time duration elapses.

(91) In one embodiment, in response to detecting a user selection of comments creation button **712** as shown in user interface **700**, the processor may cause a display of text input item **714** for the user

to enter a comment for the media content item **702**. After the user inputs a comment in the text input item **714**, the user may post or upload the comment to the messaging server system **108** by selecting the post button **716**. The comment can be added to the comments display **802** as shown in FIG. **8**. In one embodiment, the user may input the text of a user's name associated with the user profile as a portion of a comment or as a comment. The processor may generate a notification on the client device **102** associated with the user being mentioned.

(92) At operation **606**, the processor generates a summary comments selectable item **704** in the user interface **700** based at least in part on the user profile of the first user. The summary comments selectable item **704** includes at least one profile icon or avatars corresponding to the connected user profiles. As shown in FIG. **7**, the summary comments selectable item **704** includes two profile icons **710**, each profile icon includes an avatar of the user who created a comment for the media content item **702**. A profile icon can be an image of a silhouette of the user. The summary comment selectable item **704**, once selected by a user, is expandable into a comments display **802** as shown in FIG. **8**. In one embodiment, if the summary comment selectable item **704** is generated based on more than a threshold number of comments, the comments display **802** only displays the threshold number of comments at a time. The user may interact with the user interface **800** using hand gestures (e.g., scrolling up and down) to locate additional comments not shown in the comments display **802**. The threshold number of comments may be determined base on a plurality of factors, including the allowable length of each comment, the number of comments, etc.

(93) At operation **608**, in response to the request from the user to view the media content item **702**, the processor causes a display of playback of the media content item **702** and a display of the summary comments selectable item **704** in the user interface **700**. In one embodiment, prior to the display of the playback of the media content item **702** and the display of the summary comments selectable item **704**, the user interface **700** may briefly display (e.g., for two seconds) at least one profile icon above each corresponding timeline marker **708** to indicate which user has created comments in which temporal position.

(94) At operation **610**, the processor causes a display of the at least one comment at the particular time or temporal position represented by the timeline marker **708** during the playback of the media content item **702**. As shown in FIG. **7**, if there is more than one comment during the playback, each comment is associated with a timeline marker **708** distributed based on the temporal positions on the progress bar **706**. The comments are displayed in chronological order as they were created during the playback of the media content item **702**.

(95) At operation **612**, the processor receives a selection of the first comment from the at least one comment. In one embodiment, the selection of a comment can be made from choosing a comment in the list of comments display **802**, or the selection can be made from choosing a comment chronologically displayed during the playback of the media content item **702**. For example, as shown in FIG. **8**, a user may select the first comment **804** to activate a private messaging interface to engage in a private conversation with the creator of the first comment **804**, e.g., Bella.

(96) At operation **614**, the processor causes a display of a private messaging user interface, such as the user interface **900** as shown in FIG. **9**. The private messaging user interface **900** may include a quotation comments selectable item **902** corresponding to the selected first comment **804** and the media content item **702**. The private messaging user interface **900** is a one-on-one conversation user interface with the creator of the selected comment **804**. As shown in FIG. **8**, the creator of the comment is Bella, also indicated by a text display **906** "replying to Bella's comment." The viewing user with whom Bella engages in a private conversation is "Evan," as indicated by the name item **910**. This way, all replies to comments are conducted in a private conversation with the comment creator, the messaging server system **108** may avoid generating a complete comment thread for a display that may inadvertently cause emotional distress, such as embarrassment, to certain users.

(97) In one embodiment, the processor may generate a user interface **1000** as shown in FIG. **10**. The user interface **1000** includes a summary comments display **1002**, a text display **1004**, and a

plurality of media content items **1006**, **1008**, and **1010**. Each media content item is associated with a collection of profile icons that are associated with comments created by users who are connected to the viewing user. In one embodiment, the profile icons are displayed in an order based on a ranking of a score of relationship affinity. For example, among the bilaterally connected users (e.g., friends), the viewing user may identify certain users as “close friends.” The identified users may be associated with an affinity identifier in the respective user profile that indicates a score of relationship affinity. The affinity identifier can be stored in entity graph **306**. The scores of relationship affinity may also be determined by other factors, such as the number of messages and the associated content exchanged between users, the amount of time of audio or video communication, the amount of media content items exchanged or referred between users, or other interactive activities conducted between users on the respective client device **102**. The processor ranks the scores of the relationship affinity associated with each connected user who created comments. A profile icon of a connected user with the highest score or may be displayed at the first place in the summary comments display **1002** or in the summary comments selectable item **704**.

(98) In one embodiment, as shown in FIG. **11**, an “in-app” notification **1102** may be displayed when a viewing user received comments from connected users who made comments to a media content item. The notification **1102** includes a profile icon and the name of the connected user, and a title or caption of the media content item. In one embodiment, if the processor determines there are multiple comments created by multiple connected users, the notification **1102** may only display the profile icon of the connected user with the highest score of relationship affinity.

(99) In one embodiment, the notification **1102** displays a number of connected users who created comments associated with a media content item. For example, as shown in user interface **1100**, the number of connected users or friends associated with the media content item titled “What is it like to adopt puppies” is three, including “Amy” and two other comments indicated by the text display “+2.”

(100) In one embodiment, a media content item, the processor determines if a pre-determined time period has elapsed since a previous notification associated with the media content item has been generated on the client device **102**, the previous notification corresponding to a second comment. Upon detecting the pre-determined time period has elapsed, the processor generates a subsequent notification on the client device in response to receiving a third comment for the media content item. The pre-determined time period represents a cool-down period, such as three hours. The second comment is associated with a second user profile from the set of connected profiles, and the third comment is associated with a third user profile from the set of connected profiles.

(101) In one embodiment, if the second comment and the third comments are both generated by the same user from the set of the connected profiles, and this same user is determined to be associated with an affinity identifier corresponding to a high score, the processor may generate the subsequent notification before the pre-determined time period has elapsed.

(102) FIG. **7** illustrates a user interface **700** displayed on a client device in accordance with one embodiment. The user interface **700** is caused to be displayed on a client device **102** when a user requests to view a playback of a media content item **702**. A user may select the summary comments selectable item **704** to activate the comments display **802** in FIG. **8**. A user may create comments by selecting comments creation button **712**, and input comments in the text input item **714**, and posts or upload the comments by selecting post button **716**. The uploaded comments will be subsequently displayed in the comments display **802**. The user interface **700** includes a progress bar **706** and a plurality of timeline markers **708**. The progress bar **706** represents the duration of time for playback of the media content item **702**. The plurality of timeline markers **708** represent the points in time when the comments included by the summary comments selectable item **704** was created.

(103) FIG. **8** illustrates a user interface **800** displayed on a client device in accordance with one embodiment. The user interface **800** includes the comments display **802**. A user may view all

comments referred by the summary comments selectable item **704**. The user may also select any of the comments, such as the first comment **804**, to activate a private messaging user interface **900**, and engage in a private conversation with the creator of the selected comment.

(104) FIG. **9** illustrates a user interface **900** displayed on a client device in accordance with one embodiment. The user interface **900** is a private messaging user interface. In response to detecting a user selection of the first comment **804**, the user may respond individually to the creator (e.g., Bella) of the first comment. The private messaging user interface **900** may include a quotation comments selectable item **902** corresponding to the selected first comment **804** and the media content item **702**. The quotation comments selectable item **902** includes a quotation of the selected first comment **804**, and a pictorial overview of the media content item **702**. The quotation comments selectable item **902** is associated with an HTTP link that may direct the user back to the user interface **700** once the link is activated by a user selection of item **902**.

(105) FIG. **10** illustrates a user interface **1000** displayed on a client device in accordance with one embodiment. The user interface **1000** includes a summary comments display **1002**, a text display **1004**, and a plurality of media content items **1006**, **1008**, and **1010**. Each media content item is associated with a collection of profile icons that are associated with comments created by users who are connected to the viewing user. In an embodiment, each media content item is embedded with an HTTP link that once activated upon user selection, may direct the user to a media content playback user interface, such as the user interface **700** as shown in FIG. **7**.

(106) FIG. **11** illustrates a user interface **1100** displayed on a client device in accordance with one embodiment. The user interface **1100** includes an “in-app” notification **1102**. The notification **1102** includes a profile icon and the name of the connected user, the name of the media content creator, and a title or caption of the media content item. In an embodiment, the notification **1102** is embedded with an HTTP link that, once activated upon user selection, may direct the user to a media content playback user interface associated with the media content item referred by in the notification, such as the media content item **1104** created by content creator “DEF” as shown in FIG. **11**.

(107) Machine Architecture

(108) FIG. **12** is a diagrammatic representation of the machine **1200** within which instructions **1208** (e.g., software, a program, an application, an applet, an app, or other executable code) for causing the machine **1200** to perform any one or more of the methodologies discussed herein may be executed. For example, the instructions **1208** may cause the machine **1200** to execute any one or more of the methods described herein. The instructions **1208** transform the general, non-programmed machine **1200** into a particular machine **1200** programmed to carry out the described and illustrated functions in the manner described. The machine **1200** may operate as a standalone device or may be coupled (e.g., networked) to other machines. In a networked deployment, the machine **1200** may operate in the capacity of a server machine or a client machine in a server-client network environment, or as a peer machine in a peer-to-peer (or distributed) network environment. The machine **1200** may comprise, but not be limited to, a server computer, a client computer, a personal computer (PC), a tablet computer, a laptop computer, a netbook, a set-top box (STB), a personal digital assistant (PDA), an entertainment media system, a cellular telephone, a smartphone, a mobile device, a wearable device (e.g., a smartwatch), a smart home device (e.g., a smart appliance), other smart devices, a web appliance, a network router, a network switch, a network bridge, or any machine capable of executing the instructions **1208**, sequentially or otherwise, that specify actions to be taken by the machine **1200**. Further, while only a single machine **1200** is illustrated, the term “machine” shall also be taken to include a collection of machines that individually or jointly execute the instructions **1208** to perform any one or more of the methodologies discussed herein. The machine **1200**, for example, may comprise the client device **102** or any one of a number of server devices forming part of the messaging server system **108**. In some examples, the machine **1200** may also comprise both client and server systems, with

certain operations of a particular method or algorithm being performed on the server-side and with certain operations of the particular method or algorithm being performed on the client-side.

(109) The machine **1200** may include processors **1202**, memory **1204**, and input/output I/O components **1238**, which may be configured to communicate with each other via a bus **1240**. In an example, the processors **1202** (e.g., a Central Processing Unit (CPU), a Reduced Instruction Set Computing (RISC) Processor, a Complex Instruction Set Computing (CISC) Processor, a Graphics Processing Unit (GPU), a Digital Signal Processor (DSP), an Application Specific Integrated Circuit (ASIC), a Radio-Frequency Integrated Circuit (RFIC), another processor, or any suitable combination thereof) may include, for example, a processor **1206** and a processor **1210** that execute the instructions **1208**. The term “processor” is intended to include multi-core processors that may comprise two or more independent processors (sometimes referred to as “cores”) that may execute instructions contemporaneously. Although FIG. **12** shows multiple processors **1202**, the machine **1200** may include a single processor with a single-core, a single processor with multiple cores (e.g., a multi-core processor), multiple processors with a single core, multiple processors with multiples cores, or any combination thereof.

(110) The memory **1204** includes a main memory **1212**, a static memory **1214**, and a storage unit **1216**, both accessible to the processors **1202** via the bus **1240**. The main memory **1204**, the static memory **1214**, and storage unit **1216** store the instructions **1208** embodying any one or more of the methodologies or functions described herein. The instructions **1208** may also reside, completely or partially, within the main memory **1212**, within the static memory **1214**, within machine-readable medium **1218** within the storage unit **1216**, within at least one of the processors **1202** (e.g., within the processor's cache memory), or any suitable combination thereof, during execution thereof by the machine **1200**.

(111) The I/O components **1238** may include a wide variety of components to receive input, provide output, produce output, transmit information, exchange information, capture measurements, and so on. The specific I/O components **1238** that are included in a particular machine will depend on the type of machine. For example, portable machines such as mobile phones may include a touch input device or other such input mechanisms, while a headless server machine will likely not include such a touch input device. It will be appreciated that the I/O components **1238** may include many other components that are not shown in FIG. **12**. In various examples, the I/O components **1238** may include user output components **1224** and user input components **1226**. The user output components **1224** may include visual components (e.g., a display such as a plasma display panel (PDP), a light-emitting diode (LED) display, a liquid crystal display (LCD), a projector, or a cathode ray tube (CRT)), acoustic components (e.g., speakers), haptic components (e.g., a vibratory motor, resistance mechanisms), other signal generators, and so forth. The user input components **1226** may include alphanumeric input components (e.g., a keyboard, a touch screen configured to receive alphanumeric input, a photo-optical keyboard, or other alphanumeric input components), point-based input components (e.g., a mouse, a touchpad, a trackball, a joystick, a motion sensor, or another pointing instrument), tactile input components (e.g., a physical button, a touch screen that provides location and force of touches or touch gestures, or other tactile input components), audio input components (e.g., a microphone), and the like.

(112) In further examples, the I/O components **1238** may include biometric components **1228**, motion components **1230**, environmental components **1232**, or position components **1234**, among a wide array of other components. For example, the biometric components **1228** include components to detect expressions (e.g., hand expressions, facial expressions, vocal expressions, body gestures, or eye-tracking), measure biosignals (e.g., blood pressure, heart rate, body temperature, perspiration, or brain waves), identify a person (e.g., voice identification, retinal identification, facial identification, fingerprint identification, or electroencephalogram-based identification), and the like. The motion components **1230** include acceleration sensor components (e.g.,

accelerometer), gravitation sensor components, rotation sensor components (e.g., gyroscope). (113) The environmental components **1232** include, for example, one or cameras (with still image/photograph and video capabilities), illumination sensor components (e.g., photometer), temperature sensor components (e.g., one or more thermometers that detect ambient temperature), humidity sensor components, pressure sensor components (e.g., barometer), acoustic sensor components (e.g., one or more microphones that detect background noise), proximity sensor components (e.g., infrared sensors that detect nearby objects), gas sensors (e.g., gas detection sensors to detection concentrations of hazardous gases for safety or to measure pollutants in the atmosphere), or other components that may provide indications, measurements, or signals corresponding to a surrounding physical environment.

(114) With respect to cameras, the client device **102** may have a camera system comprising, for example, front cameras on a front surface of the client device **102** and rear cameras on a rear surface of the client device **102**. The front cameras may, for example, be used to capture still images and video of a user of the client device **102** (e.g., “selfies”), which may then be augmented with augmentation data (e.g., filters) described above. The rear cameras may, for example, be used to capture still images and videos in a more traditional camera mode, with these images similarly being augmented with augmentation data. In addition to front and rear cameras, the client device **102** may also include a 360° camera for capturing 360° photographs and videos.

(115) Further, the camera system of a client device **102** may include dual rear cameras (e.g., a primary camera as well as a depth-sensing camera), or even triple, quad or penta rear camera configurations on the front and rear sides of the client device **102**. These multiple cameras systems may include a wide camera, an ultra-wide camera, a telephoto camera, a macro camera and a depth sensor, for example.

(116) The position components **1234** include location sensor components (e.g., a GPS receiver component), altitude sensor components (e.g., altimeters or barometers that detect air pressure from which altitude may be derived), orientation sensor components (e.g., magnetometers), and the like.

(117) Communication may be implemented using a wide variety of technologies. The I/O components **1238** further include communication components **1236** operable to couple the machine **1200** to a network **1220** or devices **1222** via respective coupling or connections. For example, the communication components **1236** may include a network interface component or another suitable device to interface with the network **1220**. In further examples, the communication components **1236** may include wired communication components, wireless communication components, cellular communication components, Near Field Communication (NFC) components, Bluetooth® components (e.g., Bluetooth® Low Energy), Wi-Fi® components, and other communication components to provide communication via other modalities. The devices **1222** may be another machine or any of a wide variety of peripheral devices (e.g., a peripheral device coupled via a USB).

(118) Moreover, the communication components **1236** may detect identifiers or include components operable to detect identifiers. For example, the communication components **1236** may include Radio Frequency Identification (RFID) tag reader components, NFC smart tag detection components, optical reader components (e.g., an optical sensor to detect one-dimensional bar codes such as Universal Product Code (UPC) bar code, multi-dimensional bar codes such as Quick Response (QR) code, Aztec code, Data Matrix, Dataglyph, MaxiCode, PDF417, Ultra Code, UCC RSS-2D bar code, and other optical codes), or acoustic detection components (e.g., microphones to identify tagged audio signals). In addition, a variety of information may be derived via the communication components **1236**, such as location via Internet Protocol (IP) geolocation, location via Wi-Fi® signal triangulation, location via detecting an NFC beacon signal that may indicate a particular location, and so forth.

(119) The various memories (e.g., main memory **1212**, static memory **1214**, and memory of the processors **1202**) and storage unit **1216** may store one or more sets of instructions and data

structures (e.g., software) embodying or used by any one or more of the methodologies or functions described herein. These instructions (e.g., the instructions **1208**), when executed by processors **1202**, cause various operations to implement the disclosed examples.

(120) The instructions **1208** may be transmitted or received over the network **1220**, using a transmission medium, via a network interface device (e.g., a network interface component included in the communication components **1236**) and using any one of several well-known transfer protocols (e.g., hypertext transfer protocol (HTTP)). Similarly, the instructions **1208** may be transmitted or received using a transmission medium via a coupling (e.g., a peer-to-peer coupling) to the devices **1222**.

(121) Software Architecture

(122) FIG. **13** is a block diagram **1300** illustrating a software architecture **1304**, which can be installed on any one or more of the devices described herein. The software architecture **1304** is supported by hardware such as a machine **1302** that includes processors **1320**, memory **1326**, and I/O components **1338**. In this example, the software architecture **1304** can be conceptualized as a stack of layers, where each layer provides a particular functionality. The software architecture **1304** includes layers such as an operating system **1312**, libraries **1310**, frameworks **1308**, and applications **1306**. Operationally, the applications **1306** invoke API calls **1350** through the software stack and receive messages **1352** in response to the API calls **1350**.

(123) The operating system **1312** manages hardware resources and provides common services. The operating system **1312** includes, for example, a kernel **1314**, services **1316**, and drivers **1322**. The kernel **1314** acts as an abstraction layer between the hardware and the other software layers. For example, the kernel **1314** provides memory management, processor management (e.g., scheduling), component management, networking, and security settings, among other functionality. The services **1316** can provide other common services for the other software layers. The drivers **1322** are responsible for controlling or interfacing with the underlying hardware. For instance, the drivers **1322** can include display drivers, camera drivers, BLUETOOTH® or BLUETOOTH® Low Energy drivers, flash memory drivers, serial communication drivers (e.g., USB drivers), WI-FI® drivers, audio drivers, power management drivers, and so forth.

(124) The libraries **1310** provide a common low-level infrastructure used by the applications **1306**. The libraries **1310** can include system libraries **1318** (e.g., C standard library) that provide functions such as memory allocation functions, string manipulation functions, mathematic functions, and the like. In addition, the libraries **1310** can include API libraries **1324** such as media libraries (e.g., libraries to support presentation and manipulation of various media formats such as Moving Picture Experts Group-4 (MPEG4), Advanced Video Coding (H.264 or AVC), Moving Picture Experts Group Layer-3 (MP3), Advanced Audio Coding (AAC), Adaptive Multi-Rate (AMR) audio codec, Joint Photographic Experts Group (JPEG or JPG), or Portable Network Graphics (PNG)), graphics libraries (e.g., an OpenGL framework used to render in two dimensions (2D) and three dimensions (3D) in a graphic content on a display), database libraries (e.g., SQLite to provide various relational database functions), web libraries (e.g., WebKit to provide web browsing functionality), and the like. The libraries **1310** can also include a wide variety of other libraries **1328** to provide many other APIs to the applications **1306**.

(125) The frameworks **1308** provide a common high-level infrastructure that is used by the applications **1306**. For example, the frameworks **1308** provide various graphical user interface (GUI) functions, high-level resource management, and high-level location services. The frameworks **1308** can provide a broad spectrum of other APIs that can be used by the applications **1306**, some of which may be specific to a particular operating system or platform.

(126) In an example, the applications **1306** may include a home application **1336**, a contacts application **1330**, a browser application **1332**, a book reader application **1334**, a location application **1342**, a media application **1344**, a messaging application **1346**, a game application **1348**, and a broad assortment of other applications such as a third-party application **1340**. The

applications **1306** are programs that execute functions defined in the programs. Various programming languages can be employed to create one or more of the applications **1306**, structured in a variety of manners, such as object-oriented programming languages (e.g., Objective-C, Java, or C++) or procedural programming languages (e.g., C or assembly language). In a specific example, the third-party application **1340** (e.g., an application developed using the ANDROID™ or IOS™ software development kit (SDK) by an entity other than the vendor of the particular platform) may be mobile software running on a mobile operating system such as IOS™, ANDROID™, WINDOWS® Phone, or another mobile operating system. In this example, the third-party application **1340** can invoke the API calls **1350** provided by the operating system **1312** to facilitate functionality described herein.

(127) Processing Components

(128) Turning now to FIG. **14**, there is shown a diagrammatic representation of a processing environment **1400**, which includes a processor **1402**, a processor **1406**, and a processor **1408** (e.g., a GPU, CPU or combination thereof).

(129) The processor **1402** is shown to be coupled to a power source **1404**, and to include (either permanently configured or temporarily instantiated) modules, namely a collection management component **1410** and an ephemeral timer component **1412**. The collection management component **1410** operationally generates media content items and comments, manage the playback of the media content items and the display of the associated comments, and generates private messaging user interfaces in response to detecting a user selection of comments. The ephemeral timer component **1412** operationally manages the pre-determined duration of time of media content playback, and a pre-defined time duration for a display of a comment during a media content playback. As illustrated, the processor **1402** is communicatively coupled to both the processor **1406** and the processor **1408**.

Glossary

(130) “Carrier signal” refers to any intangible medium that is capable of storing, encoding, or carrying instructions for execution by the machine, and includes digital or analog communications signals or other intangible media to facilitate communication of such instructions. Instructions may be transmitted or received over a network using a transmission medium via a network interface device.

(131) “Client device” refers to any machine that interfaces to a communications network to obtain resources from one or more server systems or other client devices. A client device may be, but is not limited to, a mobile phone, desktop computer, laptop, portable digital assistants (PDAs), smartphones, tablets, ultrabooks, netbooks, laptops, multi-processor systems, microprocessor-based or programmable consumer electronics, game consoles, set-top boxes, or any other communication device that a user may use to access a network.

(132) “Communication network” refers to one or more portions of a network that may be an ad hoc network, an intranet, an extranet, a virtual private network (VPN), a local area network (LAN), a wireless LAN (WLAN), a wide area network (WAN), a wireless WAN (WWAN), a metropolitan area network (MAN), the Internet, a portion of the Internet, a portion of the Public Switched Telephone Network (PSTN), a plain old telephone service (POTS) network, a cellular telephone network, a wireless network, a Wi-Fi® network, another type of network, or a combination of two or more such networks. For example, a network or a portion of a network may include a wireless or cellular network and the coupling may be a Code Division Multiple Access (CDMA) connection, a Global System for Mobile communications (GSM) connection, or other types of cellular or wireless coupling. In this example, the coupling may implement any of a variety of types of data transfer technology, such as Single Carrier Radio Transmission Technology (1×RTT), Evolution-Data Optimized (EVDO) technology, General Packet Radio Service (GPRS) technology, Enhanced Data rates for GSM Evolution (EDGE) technology, third Generation Partnership Project (3GPP) including 3G, fourth generation wireless (4G) networks, Universal Mobile Telecommunications

System (UMTS), High Speed Packet Access (HSPA), Worldwide Interoperability for Microwave Access (WiMAX), Long Term Evolution (LTE) standard, others defined by various standard-setting organizations, other long-range protocols, or other data transfer technology.

(133) “Component” refers to a device, physical entity, or logic having boundaries defined by function or subroutine calls, branch points, APIs, or other technologies that provide for the partitioning or modularization of particular processing or control functions. Components may be combined via their interfaces with other components to carry out a machine process. A component may be a packaged functional hardware unit designed for use with other components and a part of a program that usually performs a particular function of related functions. Components may constitute either software components (e.g., code embodied on a machine-readable medium) or hardware components. A “hardware component” is a tangible unit capable of performing certain operations and may be configured or arranged in a certain physical manner. In various example embodiments, one or more computer systems (e.g., a standalone computer system, a client computer system, or a server computer system) or one or more hardware components of a computer system (e.g., a processor or a group of processors) may be configured by software (e.g., an application or application portion) as a hardware component that operates to perform certain operations as described herein. A hardware component may also be implemented mechanically, electronically, or any suitable combination thereof. For example, a hardware component may include dedicated circuitry or logic that is permanently configured to perform certain operations. A hardware component may be a special-purpose processor, such as a field-programmable gate array (FPGA) or an application specific integrated circuit (ASIC). A hardware component may also include programmable logic or circuitry that is temporarily configured by software to perform certain operations. For example, a hardware component may include software executed by a general-purpose processor or other programmable processor. Once configured by such software, hardware components become specific machines (or specific components of a machine) uniquely tailored to perform the configured functions and are no longer general-purpose processors. It will be appreciated that the decision to implement a hardware component mechanically, in dedicated and permanently configured circuitry, or in temporarily configured circuitry (e.g., configured by software), may be driven by cost and time considerations. Accordingly, the phrase “hardware component” (or “hardware-implemented component”) should be understood to encompass a tangible entity, be that an entity that is physically constructed, permanently configured (e.g., hardwired), or temporarily configured (e.g., programmed) to operate in a certain manner or to perform certain operations described herein. Considering embodiments in which hardware components are temporarily configured (e.g., programmed), each of the hardware components need not be configured or instantiated at any one instance in time. For example, where a hardware component comprises a general-purpose processor configured by software to become a special-purpose processor, the general-purpose processor may be configured as respectively different special-purpose processors (e.g., comprising different hardware components) at different times. Software accordingly configures a particular processor or processors, for example, to constitute a particular hardware component at one instance of time and to constitute a different hardware component at a different instance of time. Hardware components can provide information to, and receive information from, other hardware components. Accordingly, the described hardware components may be regarded as being communicatively coupled. Where multiple hardware components exist contemporaneously, communications may be achieved through signal transmission (e.g., over appropriate circuits and buses) between or among two or more of the hardware components. In embodiments in which multiple hardware components are configured or instantiated at different times, communications between such hardware components may be achieved, for example, through the storage and retrieval of information in memory structures to which the multiple hardware components have access. For example, one hardware component may perform an operation and store the output of that operation in a memory device to which it is

communicatively coupled. A further hardware component may then, at a later time, access the memory device to retrieve and process the stored output. Hardware components may also initiate communications with input or output devices, and can operate on a resource (e.g., a collection of information). The various operations of example methods described herein may be performed, at least partially, by one or more processors that are temporarily configured (e.g., by software) or permanently configured to perform the relevant operations. Whether temporarily or permanently configured, such processors may constitute processor-implemented components that operate to perform one or more operations or functions described herein. As used herein, “processor-implemented component” refers to a hardware component implemented using one or more processors. Similarly, the methods described herein may be at least partially processor-implemented, with a particular processor or processors being an example of hardware. For example, at least some of the operations of a method may be performed by one or more processors **1406** or processor-implemented components. Moreover, the one or more processors may also operate to support performance of the relevant operations in a “cloud computing” environment or as a “software as a service” (SaaS). For example, at least some of the operations may be performed by a group of computers (as examples of machines including processors), with these operations being accessible via a network (e.g., the Internet) and via one or more appropriate interfaces (e.g., an API). The performance of certain of the operations may be distributed among the processors, not only residing within a single machine, but deployed across a number of machines. In some example embodiments, the processors or processor-implemented components may be located in a single geographic location (e.g., within a home environment, an office environment, or a server farm). In other example embodiments, the processors or processor-implemented components may be distributed across a number of geographic locations.

(134) “Computer-readable storage medium” refers to both machine-storage media and transmission media. Thus, the terms include both storage devices/media and carrier waves/modulated data signals. The terms “machine-readable medium,” “computer-readable medium” and “device-readable medium” mean the same thing and may be used interchangeably in this disclosure.

(135) “Ephemeral message” refers to a message that is accessible for a time-limited duration. An ephemeral message may be a text, an image, a video and the like. The access time for the ephemeral message may be set by the message sender. Alternatively, the access time may be a default setting or a setting specified by the recipient. Regardless of the setting technique, the message is transitory.

(136) “Machine storage medium” refers to a single or multiple storage devices and media (e.g., a centralized or distributed database, and associated caches and servers) that store executable instructions, routines and data. The term shall accordingly be taken to include, but not be limited to, solid-state memories, and optical and magnetic media, including memory internal or external to processors. Specific examples of machine-storage media, computer-storage media and device-storage media include non-volatile memory, including by way of example semiconductor memory devices, e.g., erasable programmable read-only memory (EPROM), electrically erasable programmable read-only memory (EEPROM), FPGA, and flash memory devices; magnetic disks such as internal hard disks and removable disks; magneto-optical disks; and CD-ROM and DVD-ROM disks. The terms “machine-storage medium,” “device-storage medium,” “computer-storage medium” mean the same thing and may be used interchangeably in this disclosure. The terms “machine-storage media,” “computer-storage media,” and “device-storage media” specifically exclude carrier waves, modulated data signals, and other such media, at least some of which are covered under the term “signal medium.”

(137) “Non-transitory computer-readable storage medium” refers to a tangible medium that is capable of storing, encoding, or carrying the instructions for execution by a machine.

(138) “Signal medium” refers to any intangible medium that is capable of storing, encoding, or carrying the instructions for execution by a machine and includes digital or analog communications

signals or other intangible media to facilitate communication of software or data. The term “signal medium” shall be taken to include any form of a modulated data signal, carrier wave, and so forth. The term “modulated data signal” means a signal that has one or more of its characteristics set or changed in such a manner as to encode information in the signal. The terms “transmission medium” and “signal medium” mean the same thing and may be used interchangeably in this disclosure.

Claims

1. A method comprising: receiving, from a device, a request to view a media content item, the media content item having a duration of time for playback and being associated with a plurality of comments, each comment being created at a timestamp within the duration of time; identifying a plurality of user profiles associated with the plurality of comments; in response to identifying the plurality of user profiles, automatically generating, based on the plurality of user profiles, a selectable user interface (UI) item that represents a summary of the plurality of comments, the selectable UI item, upon being displayed, including a display of a plurality of profile avatars and a plurality of names associated with the plurality of profile avatars, the generating of the selectable UI item representing the summary of the plurality of comments comprises: determining an affinity score for each user profile in the plurality of user profiles, and arranging an order of the summary of the plurality of comments based on the affinity score for each user profile; and causing display of a playback of the media content item in a user interface of the device, the user interface including the selectable UI item that represents the summary of the plurality of comments arranged in the order based on the affinity score for each user profile.
2. The method of claim 1, wherein the user interface comprises a progress bar that includes a plurality of time markers, each time marker corresponding to a respective comment from the plurality of comments created at a respective timestamp represented by the each time marker.
3. The method of claim 2, comprising: during the playback of the media content item, causing display of each comment from the plurality of comments above the progress bar at a respective time marker when each comment was created.
4. The method of claim 1, wherein the user interface is a first user interface, comprising: detecting a user selection of the selectable user interface (UI) item; generating a second user interface that includes a list of the plurality of comments, each comment being displayed with a respective profile avatar and a respective name associated with the respective profile avatar; and causing display of the second user interface on the device.
5. The method of claim 4, comprising: receiving, via the second user interface, an indication of a selection of a comment from the plurality of comments; and causing display of a private messaging user interface with a user profile associated with the comment, the private messaging user interface including a quotation comments selectable item that corresponds to the comment.
6. The method of claim 1, wherein the display of the plurality of profile avatars is configured in an order based on a score ranking of relationship affinity between the plurality of user profiles and a user profile of the device.
7. The method of claim 1, comprising: determining that a first further comment is created for the media content item by a first connected user profile; generating a first notification that includes the first further comment; and causing display of the first notification on the device.
8. The method of claim 7, comprising: determining that a second further comment is created for the media content item by a second connected user profile; determining that a time period has elapsed since the first notification is displayed on the device; generating a second notification that includes the second further comment; and causing display of the second notification on the device.
9. The method of claim 1, wherein the media content item is generated by a designated user profile not connected to a user profile of the device.
10. The method of claim 9, wherein the designated user profile is associated with a publisher

having a number of followers exceeding a threshold value.

11. A system comprising: one or more hardware processors; and at least one non-transitory machine-readable medium for storing instructions that, when executed by the one or more hardware processors, cause the one or more hardware processors to perform operations comprising: receiving, from a device, a request to view a media content item, the media content item having a duration of time for playback and being associated with a plurality of comments, each comment being created at a timestamp within the duration of time; identifying a plurality of user profiles associated with the plurality of comments; in response to identifying the plurality of user profiles, automatically generating, based on the plurality of user profiles, a selectable user interface (UI) item that represents a summary of the plurality of comments, the selectable UI item, upon being displayed, including a display of a plurality of profile avatars and a plurality of names associated with the plurality of profile avatars, the generating of the selectable UI item representing the summary of the plurality of comments comprises: determining an affinity score for each user profile in the plurality of user profiles, and arranging an order of the summary of the plurality of comments based on the affinity score for each user profile; and causing display of a playback of the media content item in a user interface of the device, the user interface including the selectable UI item that represents the summary of the plurality of comments arranged in the order based on the affinity score for each user profile.

12. The system of claim 11, wherein the user interface comprises a progress bar that includes a plurality of time markers, each time marker corresponding to a respective comment from the plurality of comments created at a respective timestamp represented by the each time marker.

13. The system of claim 12, wherein the operations comprise: during the playback of the media content item, causing display of each comment from the plurality of comments above the progress bar at a respective time marker when each comment was created.

14. The system of claim 11, wherein the user interface is a first user interface, and wherein the operations comprise: detecting a user selection of the selectable user interface (UI) item; generating a second user interface that includes a list of the plurality of comments, each comment being displayed with a respective profile avatar and a respective name associated with the respective profile avatar; and causing display of the second user interface on the device.

15. The system of claim 14, wherein the operations comprise: receiving, via the second user interface, an indication of a selection of a comment from the plurality of comments; and causing display of a private messaging user interface with a user profile associated with the comment, the private messaging user interface including a quotation comments selectable item that corresponds to the comment.

16. The system of claim 11, wherein the display of the plurality of profile avatars is configured in an order based on a score ranking of relationship affinity between the plurality of user profiles and a user profile of the device.

17. The system of claim 11, wherein the operations comprise: determining that a first further comment is created for the media content item by a first connected user profile; generating a first notification that includes the first further comment; and causing display of the first notification on the device.

18. The system of claim 17, wherein the operations comprise: determining that a second further comment is created for the media content item by a second connected user profile; determining that a time period has elapsed since the first notification is displayed on the device; generating a second notification that includes the second further comment; and causing display of the second notification on the device.

19. The system of claim 11, wherein the media content item is generated by a designated user profile not connected to a user profile of the device, and wherein the designated user profile is associated with a publisher having a number of followers exceeding a threshold value.

20. A machine-readable non-transitory storage medium for storing instructions that, when executed

by one or more hardware processors, cause the one or more hardware processors to perform operations comprising: receiving, from a device, a request to view a media content item, the media content item having a duration of time for playback and being associated with a plurality of comments, each comment being created at a timestamp within the duration of time; identifying a plurality of user profiles associated with the plurality of comments; in response to identifying the plurality of user profiles, automatically generating, based on the plurality of user profiles, a selectable user interface (UI) item that represents a summary of the plurality of comments, the selectable UI item, upon being displayed, including a display of a plurality of profile avatars and a plurality of names associated with the plurality of profile avatars, the generating of the selectable UI item representing the summary of the plurality of comments comprises: determining an affinity score for each user profile in the plurality of user profiles, and arranging an order of the summary of the plurality of comments based on the affinity score for each user profile; and causing display of a playback of the media content item in a user interface of the device, the user interface including the selectable UI item that represents the summary of the plurality of comments arranged in the order based on the affinity score for each user profile.
