

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12418613
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Everman; Bradford R. et al.

Apparatus and methods for monitoring human trustworthiness

Abstract

An apparatus for monitoring human trustworthiness, comprising at least an interface configured to facilitate telecommunication for a participant, a plurality of sensors configured to detect a plurality of signals from the participant, and at least a computing device configured to receive the plurality of signals from the plurality of sensors, generate a participant trustworthiness classifier using at least a training sample by training the participant trustworthiness classifier using the at least a training sample, determine a participant trustworthiness as a function of the plurality of signals using the trained participant trustworthiness classifier, and generate a confidence metric associated with the determined participant trustworthiness.

Inventors: Everman; Bradford R. (Haddonfield, NJ), Bradke; Brian (Brookfield, VT)

Applicant: GMECI, LLC (Beavercreek, OH)

Family ID: 1000008820270

Appl. No.: 18/524696

Filed: November 30, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240179239 A1	May. 30, 2024

Related U.S. Application Data

continuation parent-doc US 18072446 20221130 US 11882237 child-doc US 18524696

Publication Classification

Int. Cl.: H04M3/22 (20060101); G10L25/27 (20130101); G10L25/51 (20130101)

U.S. Cl.:

CPC **H04M3/2281** (20130101); **G10L25/27** (20130101); **G10L25/51** (20130101);

Field of Classification Search

CPC: G10L (25/51); G10L (25/27); H04M (3/2281)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3572331	12/1970	Kissen	N/A	N/A
4775116	12/1987	Klein	N/A	N/A
6032065	12/1999	Brown	N/A	N/A
7040319	12/2005	Kelly et al.	N/A	N/A
7082946	12/2005	Farin et al.	N/A	N/A
7383105	12/2007	Conroy	N/A	N/A
8164464	12/2011	Matos	N/A	N/A
8281787	12/2011	Burton	N/A	N/A
8517018	12/2012	Wenzel et al.	N/A	N/A
8548547	12/2012	Vij	N/A	N/A
9038626	12/2014	Yamada et al.	N/A	N/A
9549982	12/2016	Moneymaker et al.	N/A	N/A
9808185	12/2016	Arnold et al.	N/A	N/A
9913997	12/2017	Kearney-Fischer et al.	N/A	N/A
9950201	12/2017	Zimmerman et al.	N/A	N/A
9994317	12/2017	Sharma	N/A	N/A
10182787	12/2018	Waele et al.	N/A	N/A
10278634	12/2018	Cogill et al.	N/A	N/A
10335569	12/2018	Beard et al.	N/A	N/A
10342942	12/2018	Tatkov et al.	N/A	N/A
10419053	12/2018	Ruttler et al.	N/A	N/A
10537279	12/2019	Bassin	N/A	N/A
10595758	12/2019	Buza	N/A	N/A
10725007	12/2019	Bartosz et al.	N/A	N/A
10786693	12/2019	Opperman et al.	N/A	N/A
10874346	12/2019	Lisy et al.	N/A	N/A
10877444	12/2019	Roach et al.	N/A	N/A
11308316	12/2021	Ali	N/A	G06V 40/10
11382510	12/2021	Khare et al.	N/A	N/A
11596334	12/2022	Everman et al.	N/A	N/A
12229234	12/2024	Sutherland	N/A	G06F 21/602
2002/0139368	12/2001	Bachinski	N/A	N/A
2005/0202375	12/2004	Nevo et al.	N/A	N/A
2010/0274102	12/2009	Teixeira	N/A	N/A
2012/0245439	12/2011	Andre	N/A	N/A
2013/0327330	12/2012	Fromage	N/A	N/A

2014/0003659	12/2013	Hoffmann et al.	N/A	N/A
2014/0347197	12/2013	Boomgarden et al.	N/A	N/A
2015/0151838	12/2014	Kerns et al.	N/A	N/A
2016/0074615	12/2015	Beard	N/A	N/A
2016/0256660	12/2015	Austin et al.	N/A	N/A
2016/0272341	12/2015	Horn et al.	N/A	N/A
2017/0251952	12/2016	Harshman et al.	N/A	N/A
2018/0107943	12/2017	White et al.	N/A	N/A
2018/0107962	12/2017	Lundin et al.	N/A	N/A
2018/0126194	12/2017	Salin et al.	N/A	N/A
2019/0080698	12/2018	Miller	N/A	N/A
2019/0110754	12/2018	Rao et al.	N/A	N/A
2019/0172458	12/2018	Mishra et al.	N/A	N/A
2019/0282839	12/2018	Wenzel et al.	N/A	N/A
2019/0298242	12/2018	Jungmann	N/A	N/A
2019/0298947	12/2018	Trivikram	N/A	N/A
2019/0381263	12/2018	Siska et al.	N/A	N/A
2019/0385711	12/2018	Shriberg et al.	N/A	N/A
2020/0015708	12/2019	Uplinger et al.	N/A	N/A
2020/0037942	12/2019	Howard	N/A	N/A
2020/0090661	12/2019	Ackerman	N/A	G10L 17/06
2020/0093399	12/2019	Miller	N/A	N/A
2020/0160870	12/2019	Baughman et al.	N/A	N/A
2020/0160877	12/2019	Gauduin et al.	N/A	N/A
2020/0215361	12/2019	Delprat et al.	N/A	N/A
2020/0261009	12/2019	Everman et al.	N/A	N/A
2020/0338289	12/2019	Schwaibold et al.	N/A	N/A
2021/0162261	12/2020	Neumann	N/A	N/A
2021/0221404	12/2020	Reiner et al.	N/A	N/A
2021/0236754	12/2020	Feldhahn et al.	N/A	N/A
2021/0280322	12/2020	Frank et al.	N/A	N/A
2021/0299379	12/2020	Merchia	N/A	N/A
2021/0350602	12/2020	Ye	N/A	G06V 40/172
2022/0039687	12/2021	Everman et al.	N/A	N/A
2022/0076694	12/2021	Pijl	N/A	N/A
2022/0080229	12/2021	Everman et al.	N/A	N/A
2022/0225917	12/2021	Ambeck-Madsen et al.	N/A	N/A
2022/0292431	12/2021	Singh	N/A	H04M 3/58
2022/0301666	12/2021	Shluzas et al.	N/A	N/A
2022/0338798	12/2021	Sherpa	N/A	N/A
2022/0378319	12/2021	Everman et al.	N/A	N/A
2023/0041272	12/2022	Álvarez et al.	N/A	N/A
2023/0080048	12/2022	Mohiuddin	N/A	N/A
2023/0144166	12/2022	Alford et al.	N/A	N/A
2024/0028353	12/2023	Elliott	N/A	H04L 67/306
2024/0046612	12/2023	Panetta	N/A	G06T 7/0004

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2924663	12/2016	CA	N/A
702633	12/2010	CH	N/A
108272463	12/2017	CN	N/A
102014012792	12/2015	DE	N/A
0875258	12/2003	EP	N/A
3937170	12/2021	EP	N/A
2962006	12/1998	JP	N/A
2010107805	12/2009	WO	N/A
2015106202	12/2014	WO	N/A
2018096335	12/2017	WO	N/A
2020171720	12/2019	WO	N/A
2021024257	12/2020	WO	N/A
2021050950	12/2020	WO	N/A
2021183903	12/2020	WO	N/A

OTHER PUBLICATIONS

Zakeri, Physiological correlates of cognitive load in laparoscopic surgery, (journal), Jul. 31, 2020, Scientific Reports, vol. 10, Article No. 12927, 2020, p. 1-13. cited by applicant

Waitt; Cobham VigilOX™ Pilot Breathing Sensors Fly on F-18 and T-45, Aug. 28, 2018. cited by applicant

Primary Examiner: Phuong; Dai

Attorney, Agent or Firm: Caldwell Intellectual Property Law

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of Non-provisional application Ser. No. 18/072,446 filed on Nov. 30, 2022, and entitled “AN APPARATUS AND METHODS FOR MONITORING HUMAN TRUSTWORTHINESS,” the entirety of which is incorporated herein by reference.

FIELD OF THE INVENTION

(1) The present invention generally relates to the field of monitoring the trustworthiness of an individual. In particular, the present invention is directed to providing monitoring of a participant's trustworthiness in a teleconference based on a real-time metric.

BACKGROUND

(2) A teleconference is a live audio and/or audiovisual meetings between two or more participants. It is becoming one of the most popular virtual telecommunication channels. However, lack of trust among participants is very concerning.

SUMMARY OF THE DISCLOSURE

(3) In an aspect an apparatus for monitoring human trustworthiness is disclosed. The apparatus includes at least an interface configured to facilitate telecommunication for a participant, a plurality of sensors configured to detect a plurality of signals from the participant, and at least a computing device includes at least a processor, and a memory communicatively connected to the at least a processor, wherein the memory contains instructions configuring the at least a processor to receive a plurality of signals, generate a participant trustworthiness classifier using at least a training sample, wherein generating the participant trustworthiness classifier includes training the

participant trustworthiness classifier using the at least a training sample, wherein the at least a training sample includes a plurality of visible feedback signal and auditory feedback signal as input correlated to a plurality of responses of known trustworthiness as output. The processor is further configured to determine a participant trustworthiness as a function of the plurality of signals using the trained participant trustworthiness classifier and generate a confidence metric associated with the determined participant trustworthiness.

(4) In another aspect, a method for monitoring human trustworthiness is disclosed. The method includes facilitating, by at least an interface, telecommunication for a participant, detecting, by a plurality of sensors, a plurality of signals from the participant, receiving, by at least a processor, the plurality of signals, generating, by the at least a processor, a participant trustworthiness classifier using at least a training sample, wherein generating the participant trustworthiness classifier includes training the participant trustworthiness classifier using the at least a training sample, wherein the at least a training sample includes a plurality of visible feedback signal and auditory feedback signal as input correlated to a plurality of responses of known trustworthiness as output. The method further includes determining, by the at least a processor, a participant trustworthiness as a function of the plurality of signals using the trained participant trustworthiness classifier and generating, by the at least a processor, a confidence metric associated with the determined participant trustworthiness.

(5) These and other aspects and features of non-limiting embodiments of the present invention will become apparent to those skilled in the art upon review of the following description of specific non-limiting embodiments of the invention in conjunction with the accompanying drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) For the purpose of illustrating the invention, the drawings show aspects of one or more embodiments of the invention. However, it should be understood that the present invention is not limited to the precise arrangements and instrumentalities shown in the drawings, wherein:
- (2) FIG. 1 is a block diagram illustrating an apparatus for monitoring human trustworthiness;
- (3) FIG. 2 is a schematic diagram illustrating an exemplary embodiment of a near-infrared spectroscopy sensor;
- (4) FIG. 3 is a schematic diagram illustrating an exemplary embodiment of a combined exhaled air and environmental gas sensor;
- (5) FIG. 4A is a schematic diagram illustrating an exemplary embodiment of a housing of the combined exhaled air and environment gas sensor;
- (6) FIG. 4B is a schematic diagram illustrating an exemplary embodiment of a housing of the combined exhaled air and environment gas sensor;
- (7) FIG. 5 is a block diagram illustrating an exemplary embodiment of an inhalation sensor;
- (8) FIG. 6 is a schematic diagram illustrating an exemplary embodiment of a cutaneous sensor;
- (9) FIG. 7 is a diagram illustrating a placement of an electromyography sensor;
- (10) FIG. 8 is a block diagram of an exemplary embodiment of a machine-learning process;
- (11) FIG. 9 is a schematic diagram of an exemplary embodiment of a neural network;
- (12) FIG. 10 is a schematic diagram of an exemplary embodiment of a node of a neural network;
- (13) FIG. 11 is a graph representing an exemplary embodiment of a fuzzy set comparison;
- (14) FIG. 12 is a flow diagram of an exemplary method for monitoring human trustworthiness; and
- (15) FIG. 13 is a block diagram of a computing system that can be used to implement any one or more of the methodologies disclosed herein and any one or more portions thereof.
- (16) The drawings are not necessarily to scale and may be illustrated by phantom lines, diagrammatic representations and fragmentary views. In certain instances, details that are not

necessary for an understanding of the embodiments or that render other details difficult to perceive may have been omitted.

DETAILED DESCRIPTION

(17) At a high level, aspects of the present disclosure are directed to an apparatus and methods for monitoring human trustworthiness based on a plurality of signals and/or feedbacks detected by a plurality of sensors. In an embodiment, the plurality of sensors may include a near-infrared (NIR) spectroscopy sensor, an exhalation sensor, an inhalation sensor, a cutaneous sensor, a speech sensor, and an eye movement sensor.

(18) Aspects of the present disclosure are directed to provide a real-time metric correlated to the trustworthiness of a participant in a telecommunication (e.g., Zoom, Team, and the like).

(19) Aspects of the present disclosure are also directed to an automated assessment of the participant's trustworthiness using a machine-learning process without the need of an expert's input or additional third-party inputs. In one embodiment, the machine-learning process may be trained using the participant's biometrics (e.g., circulatory, respiratory, cutaneous parameters, and the like.) In one embodiment, the machine-learning process may be trained using biometrics from the participant's interlocutor. In one embodiment, the machine-learning process may be trained using what can be seen and heard in the telecommunication. In one embodiment, the machine-learning process may be trained in accordance with responses to questions with known correct/incorrect answers provided by the participant. Exemplary embodiments illustrating aspects of the present disclosure are described below in the context of several specific examples.

(20) Referring now to FIG. 1, an exemplary embodiment of an apparatus **100** for monitoring human trustworthiness is illustrated. A “trustworthiness,” as used in this disclosure, is a level of a human's ability to be relied on as honest or truthful in a telecommunication. Apparatus **100** includes at least a computing device **104**. Computing device **104** may include any computing device as described in this disclosure, including without limitation a microcontroller, microprocessor, digital signal processor (DSP) and/or system on a chip (SoC) as described in this disclosure. Computing device **104** includes at least a processor **108** and a memory **112** communicatively connected to processor **108**, wherein memory **112** contains instructions configuring processor **108** to carry out a plurality of process for monitoring human trustworthiness. In one embodiment, computing device **104** may include, be included in, and/or communicate with a mobile device such as a mobile telephone or smartphone. Processor **108** may include a single computing device operating independently, or may include two or more computing device operating in concert, in parallel, sequentially or the like; two or more computing devices may be included together in a single computing device or in two or more computing devices. Processor **108** may interface or communicate with one or more additional devices as described below in further detail via a network interface device. Network interface device may be utilized for connecting processor **108** to one or more of a variety of networks, and one or more devices. Examples of a network interface device include, but are not limited to, a network interface card (e.g., a mobile network interface card, a LAN card), a modem, and any combination thereof. Examples of a network include, but are not limited to, a wide area network (e.g., the Internet, an enterprise network), a local area network (e.g., a network associated with an office, a building, a campus or other relatively small geographic space), a telephone network, a data network associated with a telephone/voice provider (e.g., a mobile communications provider data and/or voice network), a direct connection between two computing devices, and any combinations thereof. A network may employ a wired and/or a wireless mode of communication. In general, any network topology may be used. Information (e.g., data, software and the like.) may be communicated to and/or from a computer and/or a computing device. Processor **108** may include but is not limited to, for example, a computing device or cluster of computing devices in a first location and a second computing device or cluster of computing devices in a second location. Processor **108** may include one or more computing devices dedicated to data storage, security, distribution of traffic for load balancing, and the like. Processor **108** may

distribute one or more computing tasks as described below across a plurality of computing devices of computing device, which may operate in parallel, in series, redundantly, or in any other manner used for distribution of tasks or memory between computing devices. Processor **108** may be implemented using a “shared nothing” architecture in which data is cached at the worker, in an embodiment, this may enable scalability of apparatus **100** and/or computing device.

(21) Still referring to FIG. **1**, processor **108** may be designed and/or configured to perform any method, method step, or sequence of method steps in any embodiment described in this disclosure, in any order and with any degree of repetition. For instance, processor **108** may be configured to perform a single step or sequence repeatedly until a desired or commanded outcome is achieved; repetition of a step or a sequence of steps may be performed iteratively and/or recursively using outputs of previous repetitions as inputs to subsequent repetitions, aggregating inputs and/or outputs of repetitions to produce an aggregate result, reduction or decrement of one or more variables such as global variables, and/or division of a larger processing task into a set of iteratively addressed smaller processing tasks. Processor **108** may perform any step or sequence of steps as described in this disclosure in parallel, such as simultaneously and/or substantially simultaneously performing a step two or more times using two or more parallel threads, processor cores, or the like; division of tasks between parallel threads and/or processes may be performed according to any protocol suitable for division of tasks between iterations. Persons skilled in the art, upon reviewing the entirety of this disclosure, will be aware of various ways in which steps, sequences of steps, processing tasks, and/or data may be subdivided, shared, or otherwise dealt with using iteration, recursion, and/or parallel processing.

(22) With continued reference to FIG. **1**, as used in this disclosure, “communicatively connected” means connected by way of a connection, attachment, or linkage between two or more relata which allows for reception and/or transmittance of information therebetween. For example, and without limitation, this connection may be wired or wireless, direct, or indirect, and between two or more components, circuits, devices, systems, apparatus and the like, which allows for reception and/or transmittance of data and/or signal(s) therebetween. Data and/or signals therebetween may include, without limitation, electrical, electromagnetic, magnetic, video, audio, radio and microwave data and/or signals, combinations thereof, and the like, among others. A communicative connection may be achieved, for example and without limitation, through wired or wireless electronic, digital or analog, communication, either directly or by way of one or more intervening devices or components. Further, communicative connection may include electrically coupling or connecting at least an output of one device, component, or circuit to at least an input of another device, component, or circuit. For example, and without limitation, via a bus or other facility for intercommunication between elements of a computing device. Communicative connecting may also include indirect connections via, for example and without limitation, wireless connection, radio communication, low power wide area network, optical communication, magnetic, capacitive, or optical coupling, and the like. In some instances, the terminology “communicatively coupled” may be used in place of communicatively connected in this disclosure.

(23) Still referring to FIG. **1**, in one embodiment, apparatus **100** includes at least an interface **152** configured to facilitate telecommunication for a participant **140**. As used in this disclosure, an “interface”, is a software and/or hardware device configured to facilitate a telecommunication between one or more participants and one or more interlocutors. Interface **152** may include a graphical user interface, command line interface (CLI), menu-driven user interface, touch user interface, voice user interface (VUI), form-based user interface, natural language user interface, and the like. For example, interface **152** may provide an interconnection between one or more participants and a communication device, such as a computer screen, a television, radio, speaker, a projector and the like; in some cases, a display may comprise an audio-visual display and thereby may additionally include at least an audio transducer (e.g., speakers). Exemplary non-limiting displays include liquid crystal displays, cathode ray tube displays, light emitting diode displays,

organic light emitting diode displays, quantum dot displays, micro-electromechanical system (MEMS) projector, virtual reality headset, head mounted display, and the like. In some embodiments, interface **152** may communicate content to one or more participants remotely. As described in this disclosure, “content” is any media (e.g., visual and/or audio) which contains information intended to be communicated to an audience. Exemplary content includes course a document, slide show, spreadsheet, diagram, video, audio, images, interactive media, a question, text, and the like. “Telecommunication,” as used in this disclosure, is the exchange of information over significant distances by electronic means which may include all types of voice, data, and/or video transmission such as teleconference (e.g., Zoom, Team, and the like) using a wide range of information-transmitting technologies and communications infrastructures, such as wire phones, mobile devices, microwave communications, fiber optics, satellites, radio and television broadcasting, internet, and telegraphs. In addition, as disclosed herein, a “participant” is an individual who is actively involved in the telecommunication. For instance, participant **140** may be a person who is attending a teleconference via Zoom, Team, or the like. A “question,” as used in this disclosure, is an interrogative expression used to evaluate the trustworthiness of participant **140** and/or test veracity. For example, a question may be, as non-limiting examples, a verbal, written, typed, interrogative expression. Questions may be related to content presented to participant **140** through interface **152**. For example, a picture of a flowerpot may be communicated to participant **140** through interface **152** along with a question asking participant **140** whether he or she recognizes the flowerpot in the image. In some embodiments, questions may be related to one another may be communicated to participant **140** without the aid of content. For example, “what is your name,” “what is your address,” “were you at this address on the night of September 4^{sup.th},” and the like. In some additional embodiments, apparatus **100** may be used with a live instructor (i.e., teacher, professor, trainer, supervisor, and the like), for example taking place of interface **152** or being presented by way of interface **152**. In some cases, questions may be used for professional training, scholastic education, military training, physical training, satisfying one's curiosity, sport's training, self-help, therapy, meditation, mindfulness training, and the like. In some additional embodiments, questions may include material interacted with by a subject, for example in service of a job or task. As an example, questions may include security camera footage and a subject viewing the questions may include security personnel. In another non-limiting embodiment, questions may be delivered substantially with or without a display. For example, questions may be delivered through audio or through a live scene (e.g., live presenter).

(24) Still referring to FIG. **1**, in some embodiments, computing device **104** may additionally be configured to control at least a display parameter for interface **152**. As used in this disclosure, a “display parameter” is a controllable characteristic of a display. Exemplary non-limiting display parameters may include visual parameters, audio parameters, and/or content parameters. As used in this disclosure, “audio parameters” is a controllable sound characteristic. Exemplary non-limiting audio parameters may include audio volume, audio mixer settings (e.g., treble, mid, bass, etc.), audio balance settings (e.g., left, right, etc.), audio fade settings (e.g., front, back, etc.), audio content settings (e.g., white noise, pink noise, etc.), and the like. In some cases, an audio parameter may include at least a change to audio content. For example, in some cases content may be augmented with audio intended to have an effect on a state of participant **140**; for instance, a precipitous and loud sound may be inserted in order to increase alertness of participant **140**. In some cases, display parameter may include a speed of presentation of content and questions. For example, speed of presentation may be varied continuously and/or discretely from $0.5\times$ to $3.0\times$ speed of presentation.

(25) Continuing to refer to FIG. **1**, apparatus **100** includes a plurality of sensors **116** configured to detect a plurality of signals from the participant. As used in this disclosure, a “sensor” is any electronic device configured to detect and/or transmit signals **120**, which may include biological and/or physical signals of participant **140** and any surrounding elements associated with participant

140. For instance, the plurality of sensors **116** may include sensors configured to detect biofeedback signals, visible and auditory feedback signals from participant **140** such as a NIR spectroscopy sensor (NIRS), an exhalation sensor, an inhalation sensor, a cutaneous sensor, a speech sensor, an eye movement sensor, and the like. A “biofeedback signal,” as disclosed herein, is biological parameter that is indicative of a response. As non-limiting examples, biological parameters may include circulatory, respiratory, cutaneous, and the like. A “visible feedback signal,” as used in this disclosure, is visual movements that is indicative of a response. As non-limiting examples, visual movements may include eye movement, blinks, facial expressions, body movements, and the like. An “auditory feedback signal,” as used in this disclosure, is sound captured that is indicative of a response. In a non-limiting example, sound may include participant's voice, speech, pitch, breathing, background noise, interlocutor's voice, and the like. A “surrounding element,” as used in this disclosure, is any external and/or peripheral conditions and/or elements related to participant **140**. For instance, in a non-limiting example, a surrounding element may include biometrics and/or response signals from the participant's interlocutor **148**. In another non-limiting example, a surrounding element may include the geographic location of participant **140** and/or weather conditions at the geographic location. As used in this disclosure, a “signal” is a representation of at least an element of data. A signal may include an analog signal, a digital signal, an electrical signal, an optical signal, and the like. In some cases, a signal may be represented according to one or more protocols, for example without limitation universal asynchronous receiver-transmitter (UART), serial communication protocols, parallel communication protocols, and/or Ethernet protocols. In some embodiments, signals **120** may be correlated to the trustworthiness of participant **140**. In some embodiments, the NIRS, the exhalation sensor, the inhalation sensor, and the cutaneous sensor may be consistent with any NIRS, exhalation sensor, inhalations sensor, and cutaneous sensor disclosed in U.S. patent application Ser. No. 17/959,593, filed on Oct. 4, 2022, entitled “APPARATUS AND METHODS FOR DETERMINING HUMAN PERFORMANCE,” the entirety of which is incorporated herein by reference.

(26) Still referring to FIG. **1**, a “NIR spectroscopy sensor,” as used in this disclosure, is an optical sensor capable of detecting light emitted, reflected, or passing through human tissue. More specifically, a NIRS, as used herein, is a sensor that detects signals in the near-infrared electromagnetic spectrum region, having wavelengths between 780 nanometers and 2,500 nanometers. An “exhalation sensor,” as used in this disclosure, is any device configured to detect the amount and/or pattern of an exhalation of breath. The exhalation sensor, in one embodiment, and without limitation, may be configured to recognize such a pattern and identify the pattern as indicative of a current exhalation of participant **140**. An “inhalation sensor,” as used in this disclosure, is any device configured to detect the amount and/or pattern of an inhalation of breath. The inhalation sensor, in one embodiment, and without limitation, may be configured to recognize such a pattern and identify the pattern as indicative of a current inhalation of participant **140**. A “cutaneous sensor,” as disclosed herein, is any device configured to detect any biofeedback signals relating to or affecting the skin of participant **140**. In one embodiment, and without limitation, the cutaneous sensor may be a skin temperature sensor and/or skin galvanic sensor which may be configured to detect skin temperature and/or blood circulation. In some embodiments, and without limitation, the biometrics of interlocutor **148** of participant **140** may be detected using any of the sensors described in this disclosure in order to monitor the trustworthiness of participant **140** as described further below. In a non-limiting example, the biometrics of interlocutor **148** may include circulatory, respiratory, cutaneous parameters, and the like.

(27) Continuing to refer to FIG. **1**, a “speech sensor,” is any device that is configured or adapted to detect a speech parameter. A “speech parameter” is an element of information associated with speech. An exemplary non-limiting speech parameter is a representation of at least a portion of audible speech, for instance a digital representation of audible speech. In some cases, a speech parameter may be transmitted or represented by a speech signal. A speech signal may include any

signal described in this disclosure. As used in this disclosure, a “speech parameter” may include any observable parameter associated with speech, including without limitation audible response and/or acoustic response. Speech response may include pressure changes, for instance audible pressure changes as detectable by a microphone. In some cases, speech parameter may not be directly related to speech, and may include response related to breathing. For example, breathing sounds may be detected by the speech sensor and used as speech parameter. In some embodiments, the speech sensor may include a bone conductance transducer. In some cases, bone conductance transducer may be configured to detect at least a speech parameter as a function of at least a speech parameter. In some cases, apparatus **100** may utilize speech parameters of a participant's interlocutor **148** instead of the participant's speech parameters to monitor the trustworthiness of the participant as described further below. For instance, in some cases, the participant may be in audible communication with the interlocutor **148**, through communication microphones. These communication signals may be used by apparatus **100** as speech parameters. In one embodiment, processor **108** is configured to determine a speech pattern as a function of the speech parameters. As used in this disclosure, a “speech pattern” is a representation of a speech-related behavioral parameter. In some cases, a speech pattern may be derived or otherwise determined from the speech parameter. Exemplary speech patterns include timber, pitch, and cadence of speech. In some cases, speech pattern may be unrelated to content of an actor's speech. Instead, in some cases, speech pattern may be related to changes audible characteristics of actor's speech. In some cases, speech pattern may be derived through analysis of speech parameters, for instance audio analysis described above. Speech pattern may include one or more prosodic variables. As used in this disclosure, “prosodic variables” are variables that relate to spoken syllables or larger speech units. In some cases, speech pattern may include audible variables, for instance pitch, change in pitch, length of units of speech such as syllables, volume, loudness, relative volume of a unit speech, timbre, quality of sound, and the like. In some cases, speech pattern may include acoustic terms. Acoustic terms may include without limitation fundamental frequency, duration, intensity, sound pressure, spectral characteristics, and the like. Speech pattern may include speech tempo. As used in this disclosure, “speech tempo” is a measure of a number of speech units within a certain amount of time. Speech tempo may vary within speech of one person, for instance according to context and emotional factors. Speech tempo may have units of syllables per second.

(28) Still referring to FIG. **1**, an “eye movement sensor,” as used in this disclosure, is any device configured to detect and/or track eye movements and/or blinks. For instance, in one embodiment, and without limitation, the eye movement sensor is an electromyography (EMG) sensor configured to detect electrical activity of extraocular muscles as described further below. In one embodiment, the eye movement sensor may be configured to detect an eye pattern based on eye movements and/or blinks. As used in this disclosure, an “eye pattern” is a representation of an eye-related behavioral parameter. For instance, an eye pattern may be derived or otherwise determined using the EMG sensor based on eye movements. Eye movements may be divided into fixations and saccades. Fixations may occur when eye gaze pauses in a certain position. Saccades may occur when eye gaze moves to another position. A resulting series of fixations and saccades may be called a scan path. Smooth pursuit describes a scan path of an eye following a moving object. Fixational eye movements include micro saccades: small, involuntary saccades that occur during attempted fixation. Most information from an eye is made available to a viewer during a fixation or smooth pursuit, but not during a saccade. Scan paths may be useful for analyzing cognitive intent, interest, and salience. Other biological factors may affect the scan path as well. In some cases, eye parameter may include blink rate. As used in this disclosure, is any time related variable associated with movement of an eyelid. Exemplary, blink rates include number of blinks over a certain time, average frequency of blinks, amount of time per blink, delay time between stimulation and a blink, and the like. In some embodiments, eye movements of interlocutor **148** of participant **140** may be detected using the eye movement sensor in order to monitor the trustworthiness of participant **140**

as described further below.

(29) Continuing to refer to FIG. 1, in some embodiments, sensors **116** may include a body movement sensor. A “body movement sensor,” as used in this disclosure, is any device configured to detect and/or track a participant's posture, position, body movements, and the like. For instance, in an unlimiting exemplary embodiment, a machine vision camera may be deployed to detect the participant's body movements and the like. Alternatively or additionally, in some cases, range-imaging or 3D camera may be used for this purpose. An exemplary range-imaging camera that may be included as an at least a sensor is Intel® RealSense™ D430 Module, from Intel® of Mountainview, California, U.S.A. D430 Module comprises active infrared (IR) illumination and a stereoscopic camera, having global shutters and frame rate of up to 90 fps. D430 Module provide a field of view (FOV) of 85.2° (horizontal) by 58° (vertical) and an image resolution of 0×720. Range-sensing camera may be operated independently by dedicated hardware, or, in some cases, range-sensing camera may be operated by a computing device. In some cases, range-sensing camera may include software and firmware resources (for execution on hardware, such as without limitation dedicated hardware or a computing device). D430 Module may be operating using software resources including Intel® RealSense™ SDK 2.0, which include opensource cross platform libraries. In one embodiment, the body movement sensor is configured to detect and/or track participant's interlocutor's posture, position, body movements and the like in order to monitor the participant's trustworthiness as described further below.

(30) Still referring to FIG. 1, in some embodiments, sensors **116** may perform one or more processing steps on signals **120**. For instance, in a non-limiting example, sensors **116** may analyze, modify, and/or synthesize signals **120** to improve the signal, for instance by improving transmission, storage efficiency, and/or signal to noise ratio. Exemplary methods of signal processing may include analog, continuous time, discrete time, digital, nonlinear, and statistical. Analog signal processing may be performed on non-digitized or analog signals. Exemplary analog processes may include passive filters, active filters, additive mixers, integrators, delay lines, compandors, multipliers, voltage-controlled filters, voltage-controlled oscillators, and phase-locked loops. Continuous-time signal processing may be used, in some cases, to process signals which vary continuously within a domain, for instance time. Exemplary non-limiting continuous time processes may include time domain processing, frequency domain processing (Fourier transform), and complex frequency domain processing. Discrete time signal processing may be used when a signal is sampled non-continuously or at discrete time intervals (i.e., quantized in time). Analog discrete-time signal processing may process a signal using the following exemplary circuits: sample and hold circuits, analog time-division multiplexers, analog delay lines and analog feedback shift registers. Digital signal processing may be used to process digitized discrete-time sampled signals. Commonly, digital signal processing may be performed by a computing device or other specialized digital circuits, such as without limitation an application specific integrated circuit (ASIC), a field-programmable gate array (FPGA), or a specialized digital signal processor (DSP). Digital signal processing may be used to perform any combination of typical arithmetical operations, including fixed-point, floating-point, real-valued, and/or complex-valued multiplication and addition. Digital signal processing may additionally operate circular buffers and lookup tables. Further non-limiting examples of algorithms that may be performed according to digital signal processing techniques include fast Fourier transform (FFT), finite impulse response (FIR) filter, infinite impulse response (IIR) filter, and adaptive filters such as the Wiener and Kalman filters. Statistical signal processing may be used to process a signal as a random function (i.e., a stochastic process), utilizing statistical properties. For instance, in some embodiments, a signal may be modeled with a probability distribution indicating noise, which then may be used to reduce noise in a processed signal. In some cases, signals **120** may be correlated to certain levels of participant trustworthiness. In some cases, participant trustworthiness may be quantitatively represented by way of a real-time metric **132** such as a confidence metric. As used in this disclosure, a “confidence

metric” is a real-time probability measurement of a participant's trustworthiness. In a non-limiting example, the confidence metric of the participant's trustworthiness may include honest, dishonest, and the like. In one embodiment, real-time metric **132** may be generated using fuzzy sets as described further below.

(31) Still referring to FIG. **1**, processor **108** is configured to receive a plurality of signals **120** from sensors **116**. As used in this disclosure, “receive” means to accept, collect, or otherwise gather input from a user and/or device. In some embodiments, signals **120** may be in various format such as, without limitation, image, video, audio, biometrics, txt file, JSON file, word document, pdf file, excel sheet, and the like thereof. In other cases, signals **120** may be present in any data structure described in this disclosure.

(32) Continuing to refer to FIG. **1**, in some embodiments, signals **120** may be present as a vector. As used in this disclosure, a “vector” is a data structure that represents one or more quantitative values and/or measures of signals **120**. A vector may be represented as an n-tuple of values, where n is one or more values, as described in further detail below; a vector may alternatively or additionally be represented as an element of a vector space, defined as a set of mathematical objects that can be added together under an operation of addition following properties of associativity, commutativity, existence of an identity element, and existence of an inverse element for each vector, and can be multiplied by scalar values under an operation of scalar multiplication compatible with field multiplication, and that has an identity element is distributive with respect to vector addition, and is distributive with respect to field addition. Each value of n-tuple of values may represent a measurement or other quantitative value associated with a given category of data, or attribute, examples of which are provided in further detail below; a vector may be represented, without limitation, in n-dimensional space using an axis per category of value represented in n-tuple of values, such that a vector has a geometric direction characterizing the relative quantities of attributes in the n-tuple as compared to each other. Two vectors may be considered equivalent where their directions, and/or the relative quantities of values within each vector as compared to each other, are the same; thus, as a non-limiting example, a vector represented as [5, 10, 15] may be treated as equivalent, for purposes of this disclosure, as a vector represented as [1, 2, 3]. Vectors may be more similar where their directions are more similar, and more different where their directions are more divergent, for instance as measured using cosine similarity as computed using a dot product of two vectors; however, vector similarity may alternatively or additionally be determined using averages of similarities between like attributes, or any other measure of similarity suitable for any n-tuple of values, or aggregation of numerical similarity measures for the purposes of loss functions as described in further detail below. Any vectors as described herein may be scaled, such that each vector represents each attribute along an equivalent scale of values. Each vector may be “normalized,” or divided by a “length” attribute, such as a length attribute l as derived using a Pythagorean norm: $l = \sqrt{\sum_{i=0}^{n-1} a_{i,sub}^2}$, where $a_{i,sub}$ is attribute number i of the vector. Scaling and/or normalization may function to make vector comparison independent of absolute quantities of attributes, while preserving any dependency on similarity of attributes.

(33) With continued reference to FIG. **1**, in some embodiments, signals **120** may be present as a dictionary. As used in this disclosure, a “dictionary” is a data structure containing an unordered set of key value pairs. In this disclosure, a “key value pair” is a data representation of a data element such as, without limitation, biofeedback signals, visible and auditory feedback signals of participant **140**. For instance, in a non-limiting exemplary embodiment, signals **120** may include circulatory feedback, respiratory feedback, skin temperature feedback, eye movement feedback, body movement feedback, voice feedback, and the like associated with participant **140** and/or the interlocutor **148** of participant **140**. In some cases, dictionary may be an associative memory, or associative arrays, or the like thereof. In a non-limiting example, dictionary may be a hash table. In an embodiment, key value pair may include a unique key, wherein the unique key may associate

with one or more values. In another embodiment, key value pair may include a value, wherein the value may associate with a single key. In some cases, each key value pair of set of key value pairs in dictionary may be separated by a separator, wherein the separator is an element for separating two key value pairs. In a non-limiting example, separator may be a comma in between each key value pairs of plurality of key value pairs within dictionary. In another non-limiting example, a dictionary may be expressed as “{first key value pair, second key value pair},” wherein the first key value pair and the second key value pair may be separate by a comma separator, and wherein both first key value pair and second key value pair may be expressed as “first/second key: first/second value.” In a further non-limiting example, signals **120** may be present as a dictionary: “{1: A, 2: B, 3: C},” wherein A may be a first user related data correspond to a first data object, B may be a second user related data correspond to a second data object, and C may be a third user related data correspond to a third data object. Signals **120** may include any kind of information related to participant **140** and/or the interlocutor **148** of participant **140** such as, without limitation, information associated with biofeedback, visible feedback, auditory feedback, and the like thereof. Additionally, or alternatively, dictionary may include a term index, wherein the term index is a data structure to facilitate fast lookup of signals **120** (i.e., index). In some cases, without limitation, term index may use a zero-based indexing, wherein the zero-based indexing may configure dictionary to start with index 0. In some cases, without limitation, term index may use a one-based indexing, wherein the one-based indexing may configure dictionary to start with index 1. In other cases, without limitation, term index may use a n-based indexing, wherein the n-based indexing may configure dictionary to start with any index from 0 to n. Further, term index may be determined/calculated using one or more hash algorithms. Hash algorithms may be any hash algorithm described above in this disclosure.

(34) With continued reference to FIG. **1**, in other embodiments, signals **120** may be present as any other data structure such as, without limitation, tuple, single dimension array, multi-dimension array, list, linked list, queue, set, stack, dequeue, stream, map, graph, tree, and the like thereof. In some embodiments, signals **120** may be present as a combination of more than one above data structures. In a non-limiting example, signals **120** may be a dictionary of lists. As will be appreciated by persons having ordinary skill in the art, after having read the entirety of this disclosure, the foregoing list is provided by way of example and other data structures can be added as an extension or improvements of apparatus **100** disclosed herein. In some embodiments, without limitation, signals **120** may be an immutable data collection, wherein the immutable data collection is a data collection that cannot be changed, modified, and/or updated once the data collection is received. In other embodiments, without limitation, signals **120** may be a mutable data collection, wherein the mutable data collection is a data collection that can be changed, modified, and/or updated once the data collection is received.

(35) Still referring to FIG. **1**, processor **108** is configured to generate a participant trustworthiness classifier **124** as a function of a participant trustworthiness machine-learning algorithm; train the participant trustworthiness classifier **124** using at least a training sample **128**, wherein the at least a training sample **128** correlates the plurality of signals **120** to responses of known trustworthiness; and generate a participant trustworthiness **136** as a function of the participant trustworthiness classifier **124**. A “classifier,” as used in this disclosure is a machine-learning model, such as a mathematical model, neural net, or program generated by a machine learning algorithm known as “classification algorithm,” as described in further detail below, that parses inputs into categories or bins of data, outputting the categories or bins of data and/or labels associated therewith. A classifier may be configured to output at least a datum that labels or otherwise identifies a set of data that are clustered together, found to be close under a distance metric as described below, or the like. A “participant trustworthiness classifier,” as used in this disclosure, is a classifier that takes the plurality of signals **120** detected by sensors **116** from participant **140** as input to output a real-time metric **132** correlated to participant trustworthiness **136** in telecommunications such as, without

limitation, a teleconference. In some embodiment, a teleconference may be a Zoom meeting, a Team meeting, or the like. In a non-limiting example, the plurality of signals **120** may include biofeedback signals, visible feedback signals, auditory feedback signals, and the like. Participant trustworthiness classifier **124** may include any machine-learning model and/or classifier described in this disclosure. A “machine-learning model,” as used in this disclosure, involves a process that automatically uses training samples to generate an algorithm and/or model performed by processor **108** to produce outputs given data provided as inputs, for instance and without limitation as described in further detail below. This is in contrast to a non-machine learning software program where the commands to be executed are determined in advance by a user and written in a programming language. A “training sample,” as disclosed herein, is data including correlations and/or examples usable by a machine learning algorithm to generate machine-learning models and/or to be operated on by a lazy learning algorithm as described below. As used in this disclosure, a “participant trustworthiness machine-learning algorithm” is a machine-learning algorithm that is used to generate participant trustworthiness classifier **124**. The participant trustworthiness machine-learning algorithm may include any machine-learning algorithm and/or process described in this disclosure.

(36) Still referring to FIG. **1**, training sample **128** may be obtained by processor **108** in any manner and/or form as described anywhere in this disclosure, including and without limitation retrieving from a data store **144** such as, and without limitation, a database. Database may alternatively or additionally be implemented using a distributed data storage protocol and/or data structure, such as a distributed hash table or the like. Database may include a plurality of data entries and/or records as described above. Data entries in a database may be flagged with or linked to one or more additional elements of information, which may be reflected in data entry cells and/or in linked tables such as tables related by one or more indices in a relational database. Persons skilled in the art, upon reviewing the entirety of this disclosure, will be aware of various ways in which data entries in a database may store, retrieve, organize, and/or reflect data and/or records as used herein, as well as categories and/or populations of data consistently with this disclosure.

(37) Continuing to refer to FIG. **1**, in one embodiment, participant trustworthiness classifier **124** may be trained by training sample **128** which may include biofeedback signals collected by at least a NIRS, an exhalation sensor, an inhalation sensor, cutaneous sensor, and the like from participant **140**. The biofeedback signals may be correlated to feedback, response, and/or answers of known trustworthiness. In an exemplary embodiment, participant **140** may be asked questions with known answers. Biometrics of participant **140** may be recorded as feedback, response, and/or answers of labeled and known answers to train participant trustworthiness classifier **124**. For instance, and without limitation, participant **140** may be asked to provide his full name truthfully and then untruthfully. Biofeedback signals, such as heart rate, blood pressure, inhalation and exhalation patterns, skin temperature, skin dryness, and the like may be recorded for training purposes. In some embodiments, prior information based on studies and/or research regarding biofeedback signals based on common features when a participant answers a question truthfully or untruthfully may be collected as training sample **128**.

(38) Still referring to FIG. **1**, in one embodiment, participant trustworthiness classifier **124** may be trained by training sample **128** which may include biofeedback signals collected from interlocutor **148** of participant **140** such that the interlocutor's own biofeedback signals may help to train the classifier. The biofeedback signals of the interlocutor may be correlated to his reaction in response to participant's **140** feedback, response, and/or answers of known trustworthiness. For instance, the interlocutor **148** may be told participant's **140** name prior to participant **140** answering the question of what his full name is. In some embodiments, interlocutor **148**'s own biofeedback signals in response to participant **140** may help train the classifier. As a non-limiting example, certain biofeedback signals may indicate that interlocutor **148** believes that participant is lying. For example, this may include elevated heart rate, narrowed eyes, among others. For instance,

biometrics of the interlocutor's biofeedback signals, such as heart rate, blood pressure, inhalation and exhalation patterns, skin temperature, skin dryness, and the like may be recorded and correlated to answers of known trustworthiness. In some embodiments, the biofeedback signals of more than one interlocutor **148** may be recorded.

(39) Still referring to FIG. **1**, in one embodiment, participant trustworthiness classifier **124** may be trained by training sample **128** which may include what can be seen and heard during a teleconference. In some embodiments, what can be seen may include visible feedback signals and what can be heard may include auditory feedback signals. In one embodiment, training sample **128** may include a speech and/or speech pattern of participant **140** and/or the interlocutor **148** detected by a speech sensor, posture, position, body movement, and the like of participant **140** and/or the interlocutor **148** detected by a body movement sensor, and eye movement and/or blink detected by an eye movement sensor. The visible and auditory feedback signals may be correlated to feedback, response, and/or answers of known trustworthiness. In one embodiment, visible and auditory feedback signals of participant **140** and/or the interlocutor **148** may be recorded as feedback, response, and/or answers of labeled and known answers to train participant trustworthiness classifier **124**. For instance, and without limitation, participant **140** may be again asked to provide his full name truthfully and then untruthfully. Visible feedback signals, such as blinks rates over a certain period of time, delay time between stimulation and a blink, fixational eye movement, eye shut, movements of body parts such as head, shoulder, arms, upper body, legs, fingers, hands, and the like may be recorded to correlate visible feedback signals to truthful response and/or untruthful response. In some embodiments, visible feedback signals as described above may be recorded for the interlocutor **148**. Auditory feedback signals, such as change in pitch, length of units of speech, volume, prominence, quality of sound, and the like may be recorded to correlate auditory feedback signals to truthful response and/or untruthful response. In some embodiments, prior information based on studies and/or research regarding visible and auditory signals based on common features when a participant answers a question truthfully or untruthfully may be collected as training sample **128**.

(40) Still referring to FIG. **1**, in one embodiment, processor **108** may be configured to determine at least an eye pattern using one or more machine learning processes. For example, in some cases, processor **108** may receive an eye pattern training data. As used in this disclosure, an “eye pattern training data” is a training set that correlates eye parameters to eye patterns. In some cases, eye pattern training data may be compiled from historic information, for instance by participant **140**. In some cases, eye pattern training data may be compiled by an unsupervised machine learning process. Eye pattern training data may use eye parameters correlated to eye patterns for participant **140**. Historic information may include information from eye-related study. Processor **108** may input eye pattern training data into an eye pattern machine learning algorithm. As used in this disclosure, an “eye pattern machine learning algorithm” is any machine learning algorithm that is configured to train an eye pattern machine learning model using eye pattern training data. Processor **108** may train an eye pattern machine learning model, as a function of eye pattern machine learning algorithm. As used in this disclosure, “eye pattern machine learning model” is a machine learning model that is configured to take as input at least an eye parameter and output at least a correlated eye pattern. Processor **108** may determine at least an eye pattern as a function of eye pattern machine learning model and at least an eye parameter.

(41) Still referring to FIG. **1**, in some embodiments, processor **108** may be configured to determine a speech pattern by using one or more machine learning processes. For example, in some cases, processor **108** may receive a speech pattern training data. As used in this disclosure, a “speech pattern training data” is a training set that correlates speech parameters to speech patterns. In some cases, speech pattern training data may be compiled from historic information, for instance by participant **140**. In some cases, speech pattern training data may be compiled by an unsupervised machine learning process. Speech pattern training data may use speech parameters correlated to

speech patterns for participant **140**. Historic information may include information from speech-related study. In some cases, historical information may include information captured from use of apparatus **100**. Processor **108** may input speech pattern training data into a speech pattern machine learning algorithm. As used in this disclosure, a “speech pattern machine learning algorithm” is any machine learning algorithm that is configured to train a speech pattern machine learning model using speech pattern training data. Processor **108** may train a speech pattern machine learning model, as a function of speech pattern machine learning algorithm. As used in this disclosure, “speech pattern machine learning model” is a machine learning model that is configured to take as input at least a speech parameter and output at least a correlated speech pattern. Processor **108** may determine at least a speech pattern as a function of speech pattern machine learning model and at least a speech parameter. Processor **108** may determine an eye pattern and speech using one or more machine learning processes as described in U.S. Nonprovisional patent application Ser. No. 17/731,935, entitled “SYSTEMS AND METHODS FOR DETERMINING ACTOR STATUS ACCORDING TO BEHAVIORAL PHENOMENA,” the entirety of which is incorporated herein by reference.

(42) Continuing to refer to FIG. **1**, in some embodiments, participant trustworthiness classifier **124** may be trained in accordance with responses to questions with known correct/incorrect answers provided by participant **140**. In one embodiment, participant **140** may be required to provide a list of responses to questions with known correct and/or incorrect answers. Any biofeedback, visible, and/or auditory feedback signals may be collected as training sample **128** which correlate the signals to known trustworthiness. Once participant trustworthiness classifier is trained, visible and/or auditory feedback signals captured during a teleconference would be sufficient and no biofeedback signals would be required to generate participant trustworthiness **136** as a function of participant trustworthiness classifier **124**.

(43) Still referring to FIG. **1**, processor **108** may be additionally configured to generate a confidence metric associated with determining participant trustworthiness **136**. As used in this disclosure, a “confidence metric” is a quantified score that is associated with a process, for example a fit or probability of a classification. Confidence metric may be generated and/or output from any machine-learning process as described in this disclosure. In one embodiment, the confidence metric may be displayed with participant trustworthiness **136** to interlocutor **148** and/or third-party observers of the teleconference in real time and/or after the conclusion of the teleconference. In one embodiment, confidence metric may be generated using fuzzy sets as described further below. In some embodiments, processor **108** may determine the trustworthiness of a participant using one or more machine learning processes as described in U.S. patent application Ser. No. 18/072,397, entitled “APPARATUSES AND METHODS FOR INDIVIDUALIZED POLYGRAPH TESTING”, the entirety of which is incorporated herein by reference.

(44) Referring now to FIG. **2**, FIG. **2** illustrates an exemplary embodiment of a NIRS **200** against an exterior body surface, which may include skin. NIRS **200** may include a light source **204**, which may include one or more light-emitting diodes (LEDs) or similar element. Light source **204** may, as a non-limiting example, convert electric energy into near-infrared electromagnetic signals. Light source **204** may include one or more lasers. NIRS **200** may include one or more detectors **208** configured to detect light in the near-infrared spectrum. Although the wavelengths described herein are infrared and near-infrared, light source **204** may alternatively or additionally emit light in one or more other wavelengths, including without limitation blue, green, ultraviolet, or other light, which may be used to sense additional physiological parameters. In an embodiment, light source may include one or more multi-wavelength light emitters, such as one or more multi-wavelength LEDs, permitting detection of blood-gas toxicology. Additional gases or other blood parameters so detected may include, without limitation CO₂ saturation levels, state of hemoglobin as opposed to blood oxygen saturation generally. One or more detectors **208** may include, without limitation, charge-coupled devices (CCDs) biased for photon detection, indium gallium arsenide (InGaAs)

photodetectors, lead sulfide (PbS) photodetectors, or the like. NIRS **200** may further include one or more intermediary optical elements (not shown), which may include dispersive elements such as prisms or diffraction gratings, or the like. In an embodiment, NIRS **200** may be used to detect one or more circulatory parameters. A “circulatory parameter,” also referred to as a blood parameter, as used in this disclosure, is a parameter describing the state of blood vessels. For example, arteries, veins, or capillaries, any datum describing the rate, volume, pressure, pulse rate, or other state of flow of blood or other fluid through such blood vessels, chemical state of such blood or other fluid, or any other parameter relative to health or current physiological state of a participant as it pertains to the cardiovascular system. As a non-limiting example, at least a circulatory parameter may include a blood oxygenation level of user's blood. At least a circulatory parameter may include a pulse rate a “pulse rate,” as used in this disclosure, is the rate at which a person's heart beats. At least a circulatory parameter may include a blood pressure level. A “blood pressure level,” as used in this disclosure, is the measurement of the force of circulating blood on the walls of the arteries. At least a circulatory parameter may include heart rate variability and rhythm. “Heart rate variability,” as used in this disclosure, is a measure of the variation in time between each heartbeat. “Heart rate rhythm,” as used in this disclosure, is the time pattern in which a heart beats. At least a circulatory parameter may include a plethysmograph describing the blood-flow of a participant; in an embodiment, plethysmograph may describe a reflectance of red or near-infrared light from blood. One circulatory parameter may be used to determine, detect, or generate another circulatory parameter; for instance, a plethysmograph may be used to determine pulse oxygen level (for instance by detecting plethysmograph amplitude), pulse rate (for instance by detecting plethysmograph frequency), heart rate variability and rhythm (for instance by tracking pulse rate and other factors over time), and blood pressure, among other things. Further disclosure related to NIRS **200** may be found in U.S. patent application Ser. No. 16/859,483, filed on Apr. 27, 2020, entitled “HUMAN PERFORMANCE OXYGEN SENSOR”, the entirety of which is incorporated herein by reference.

(45) Referring now to FIG. 3, FIG. 3 illustrates an exemplary embodiment of combined exhaled air and environmental gas sensor apparatus **300** for mobile respiratory equipment is illustrated. Apparatus **300** includes a housing **304**, within which one or more electronic components are positioned. One or more electric components include sensors **116**. Sensors **116** may include an exhaled air and environmental gas sensor. Housing **304** may be constructed of any suitable material or combination of materials, including without limitation metal, metal such as aluminum, titanium, steel, or the like, plant materials including bamboo and/or wood, polymer materials such as polycarbonate, polymethyl methacrylate, acrylonitrile butadiene styrene (ABS), or the like, synthetic fibers such as carbon fiber, silicon carbide fiber, metallic fiber, or the like, composite materials such as fiberglass, laminated fiberglass, plywood, or the like, or any combination of the above. Housing **304** may be manufactured in any suitable process including molding such as injection molding, additive manufacturing such as “three-dimensional printing” and/or stereolithography, subtractive processes such as machining, and/or any other process or combination of processes. Housing **304** may include a sensor-bearing surface on or to which one or more electrical components including sensor **116** may be attached. A sensor-bearing surface may be positioned opposite a port aperture as described in further detail below.

(46) Referring now to FIG. 4A, a perspective view of an exemplary embodiment of a housing **304** is illustrated. Housing **304** may include an exterior surface **400**, an interior surface **404**, an interior space surrounded by interior surface **404**, and one or more apertures. Housing **304** may have any suitable shape, including a shape of a cap to be placed over a respiratory exhaust port as described in further detail below. Housing **304** may be substantially cylindrical and may have one or more rounded edges. Housing **304** includes a port aperture **408**. Port aperture **408** is an aperture that receives exhaled breath from a respiratory exhaust port as described in further detail below, admitting the exhaled breath into interior space of housing **304**. Housing **304** further includes a

connector **412**, which may be located at port aperture **408**. A “connector,” as used in this disclosure, is a structural feature and/or component that affixes one aperture, opening, port, or the like to another in a way that permits flow of fluids such as liquid and/or gases to flow from one aperture, opening, port, or the like to another. Connector **412** is configured to attach port aperture **408** to exhaust port. Connector **412** may include, without limitation, a rim that fits and/or snaps over a feature of exhaust port to affix port aperture **408** thereto; connector **412** may alternatively or additionally include fastener, such as a bolt or screw that inserts through a hole in housing **304** and screws into a reciprocally threaded hole in exhaust port. Connector **412** may include threading around port aperture **408** that engages reciprocal threading at exhaust port. Connector **412** may include and/or be combined with adhesives, sealants, or the like. Connector **412** may permit repeated detachment and reattachment or may affect a permanent connection between port aperture **408** and exhaust port. Persons skilled in the art, upon reviewing the entirety of this disclosure, will be aware of various alternative or additional structures and/or components that may be used for connector **412**. Port aperture **408** may be located opposite a sensor-bearing surface; for instance, the sensor-bearing surface may be located on interior surface **404** at a distal end of housing **304**, while port aperture **408** may be located at a proximal end of housing **304**.

(47) Referring now to FIG. **4B**, housing **304** includes at least an ambient aperture **416** connecting to an exterior environment. An “exterior environment,” as used in this disclosure, means air that is exterior to an element of mobile respiratory equipment as described below; for instance, where mobile respiratory equipment is a respirator mask, exterior environment may include air outside of the mask and around a person wearing the mask, as opposed to air or gas between the mask and mouth or nose of the person. At least an ambient aperture **416** includes an opening connecting interior space to exterior environment. At least an ambient aperture **416** may permit air to travel freely between interior space and exterior environment. Further disclosure related to the combined exhaled air and environmental gas sensor **400** may be found in U.S. patent application Ser. No. 17/536,867, filed on Nov. 29, 2021, entitled “RESPIRATION SYSTEM AND METHOD OF USE,” which is a continuation-in-part of Non-Provisional application Ser. No. 17/333,169 filed on May 28, 2021 entitled “SYSTEMS AND METHODS FOR INSPIRATE SENSING TO DETERMINE A PROBABILITY OF AN EMERGENT PHYSIOLOGICAL STATE” and is a continuation-in-part of Non-provisional application Ser. No. 17/501,653 filed on Oct. 14, 2021 entitled “COMBINED EXHALED AIR AND ENVIRONMENTAL GAS SENSOR APPARATUS,” which is a continuation-in-part of Non-provisional application Ser. No. 16/933,680 filed on Jul. 20, 2020 of the same title; the entirety of each application is incorporated herein by reference.

(48) Referring now to FIG. **5**, an exemplary inspirate sensor **500** is illustrated. Sensor **116** may include inspiration sensor **500**. In some embodiments, inspirate sensor **500** may include a processor **504** for making determinations as a function of sensed parameters associated with at least an inspirate **508**. In some cases, at least a portion of an at least an inspirate **508** is contained within a fluidic channel **512**. An exemplary inhalation sensor module **516** is shown in fluid communication with fluidic channel **512**. In some cases, inhalation sensor module may include at least a gas concentration sensor **520**. In some cases, inhalation sensor module **516** may include at least an inspirate pressure sensor **524**. Inspirate gas concentration sensor **520** may include any gas concentration sensor, for instance those described in this application. In some cases, inspirate gas concentration sensor **520** may include an optical gas concentration sensor. Non-limiting optical gas concentration sensors include infrared transmission and/or absorbance spectroscopy type sensors and fluorescence excitation type sensors. Commonly, an optical gas concentration sensor may include a radiation source **528** and a radiation detector **532**. In some versions, radiation source **528** may include a light source **528** that may generate a light and illuminate at least a portion of at least an inspirate **508**. Radiation source **528** may generate any of a non-limiting list of lights, including coherent light, non-coherent light, narrowband light, broadband light, pulsed light, continuous wave light, pseudo continuous wave light, ultraviolet light, visible light, and infrared light. In some

cases, radiation source **528** may include an electromagnetic radiation source that may generate an electromagnetic radiation and irradiate at least a portion of at least an inspire **508**. Radiation source **528** may generate any of a non-limiting list of radiations including radio waves, microwaves, infrared radiation, optical radiation, ultraviolet radiation, X-rays, gamma-rays, and light. Non-limiting examples of radiation sources **528** include lasers, light emitting diodes (LEDs), light emitting capacitors (LECs), flash lamps, antennas, and the like. In some cases, radiation detector **532** may be configured to detect light and/or radiation that has interacted directly or indirectly with at least a portion of at least an inspire **508**. Non-limiting examples of radiation detectors **532** include photodiodes, photodetectors, thermopiles, pyrolytic detectors, antennas, and the like. In some cases, a radiation amount detected by radiation detector **532** may be indicative of a concentration of a particular gas in at least a portion of at least an inspire **508**. For example, in some exemplary embodiments, radiation source **528** may include an infrared light source operating at a wavelength about $4.6\ \mu\text{m}$ and radiation detector may include a photodiode sensitive over a range encompassing $4.6\ \mu\text{m}$. An exemplary infrared light source may include an LED comprising InAsSb/InAsSbP heterostructures, for example LED46 from Independent Business Scientific Group (IBSG) of Saint Petersburg, Russia. An exemplary infrared detector may include a mercury cadmium telluride photodiode, for example UM-I-6 HgCdTe from Boston Electronics of Brookline, Massachusetts. In some cases, an amount of radiation at least a specific wavelength absorbed, scatter, attenuated, and/or transmitted may be indicative of a gas concentration.

(49) With continued reference to FIG. 5, in some cases, inspire concentration sensor **520** may include an infrared point sensor. An infrared (IR) point sensor may use radiation passing through a known volume of gas, for example at least an inspire **508**. In some cases, detector **532** may be configured to detect radiation after passing through gas at a specific spectrum. As energy from infrared may be absorbed at certain wavelengths, depending on properties of at least an inspire **520**. For example, carbon monoxide absorbs wavelengths of about $4.2\text{--}4.5\ \mu\text{m}$. In some cases, detected radiation within a wavelength range may be compared to a wavelength outside of the wavelength range. A difference in detected radiation between these two wavelength ranges may be found to be proportional to a concentration of gas present. In some embodiments, an infrared image sensor may be used for active and/or passive imaging. For active sensing, radiation source **528** may include a coherent light source which may be scanned across a field of view of a scene and radiation detector **532** may be configured to detect backscattered light at an absorption wavelength of a specific target gas. In some cases, radiation detector **532** may include an image sensor, for example a two-dimensional array of radiation sensitive devices, for example arranged as pixels. Passive IR imaging sensors may measure spectral changes at each pixel in an image and look for specific spectral signatures that indicate presence and/or concentration of target gases.

(50) With continued reference to FIG. 5, in some cases, inspire gas concentration sensor **520** may include an oxygen sensor. An exemplary oxygen sensor may include an electro-galvanic sensor. For example, an electro-galvanic oxygen sensor may be used to measure a concentration of oxygen within at least an inspire **508**. In some cases, an electro-galvanic oxygen sensor may include a lead/oxygen galvanic cell, within which oxygen molecules are dissociated and reduced to hydroxyl ions at a cathode. Hydroxyl ions may diffuse through an electrolyte and oxidize a lead anode. A current proportional to a rate of oxygen consumption may be generated when cathode and anode are electrically connected through a resistor. Current may be sensed by known current sensing methods, for example without limitation those described in this disclosure, to produce an electrical signal proportional to a concentration of oxygen, for example oxygen within at least an inspire. Another exemplary oxygen sensor may include a lambda sensor, for example a zirconia sensor, a wideband zirconia sensor, and/or a titania sensor. A lambda sensor may be configured to sense a quantity of oxygen in a gas such as at least an inspire **508**, relative another gas, for example air within an environment such as cabin air and transmit an analog voltage correlated to the sensed relative quantity of oxygen. Analog voltage transmitted by a lambda sensor may be processed by

any data or signal processing methods discussed herein, for example through amplification and/or analog-to-digital conversion.

(51) In another exemplary embodiment, inspire concentration sensor **520** may include an optical sensor configured to sense oxygen concentration. In some cases, a chemical film is configured to be in contact with a gas. Chemical film may have fluorescence properties which are dependent upon presence and/or concentration of oxygen. Radiation detector **532** may be positioned and configured, such that it is in sensed communication with chemical film. Radiation source **528** may irradiate and/or illuminate chemical film with radiation and/or light having properties consistent with exciting fluorescence within the chemical film. For instance, in a non-limiting example, the properties may include wavelength, energy, pulse duration, and the like. In some cases, fluorescence may be at a maximum when there is no oxygen present. For example, oxygen molecules may collide with chemical film and quench photoluminescence resulting from fluorescent excitation. A number of O₂ molecules colliding with chemical film may be correlated with a concentration of oxygen within a gas. Fluorescence properties as sensed by optical detector **532** may therefore be related to oxygen concentration. Fluorescence properties may include emission duration, fluorescence energy, and the like. In some cases, detected optical signal (fluorescence) to oxygen concentration may not be linear. For instance, an optical oxygen sensor may be most sensitive at low oxygen concentration; that is, sensitivity decreases as oxygen concentration increases, following a known Stern-Volmer relationship. In some cases, an optical oxygen sensor is advantageous as substantially no oxygen may be consumed, during sensing. In some cases, planar optical oxygen sensors such as optodes may be used to detect a spatial distribution of oxygen concentrations over an area, for example as a two-dimensional image. Based on the same principle, radiation detector **532** may include a digital camera that may be used to capture fluorescence intensities over a specific area.

(52) With continued reference to FIG. **5**, inhalation sensor module **516** may include at least an inspire pressure sensor **524**, which is fluidic communication with at least an inspire **508**, for example by way of at least a fluidic channel **512**. In some cases, at least an inspire pressure sensor **516** may be configured to sense and transmit at least an inspire pressure parameter as a function of a pressure of at least an inspire **508**. In some cases, inhalation pressure sensor **524** may include any type of pressure sensor described in this disclosure. Inhalation pressure sensor **524** may be a force collector type pressure sensor. Alternatively, in some case, inhalation pressure sensor **524** may be a pressure sensor type that does not use force collection. Further disclosure related to the inhalation sensor may be found in U.S. patent application Ser. No. 17/333,169, filed on May 28, 2021, entitled “SYSTEMS AND METHODS FOR INSPIRATE SENSING TO DETERMINE A PROBABILITY OF AN EMERGENT PHYSIOLOGICAL STATE,” the entirety of which is incorporated herein by reference.

(53) Referring now to FIG. **6**, an exemplary embodiment of a headset **600** which may include a cutaneous sensor **616** is illustrated. In an embodiment, housing **604** may include a rigid outer shell **604**. Rigid outer shell **604** may be configured to protect internal elements of headset **600** from damage and maintain them in a proper position on participant **140**. Housing **204** may be inserted on a head of participant **140**. In one embodiment, and without limitation, housing **204** may cover the ears of participant **140**. As a non-limiting example, exterior body surface may be a surface, such as a surface of the head, face, or neck of user, which is wholly or partially covered by helmet, as described for example in further detail below. As a further non-limiting example, housing **604** may be formed to have a similar or identical shape to a standard-issue “ear cup” incorporated in an aviation helmet, so that housing **604** can replace ear cup **608** after ear cup **608** has been removed.

(54) Continuing to refer to FIG. **6**, cutaneous sensor **616** may further include a skin temperature sensor and a skin galvanic sensor. In one embodiment, cutaneous sensor **616** may be incorporated into an ear protection **608** of headset **600** such that cutaneous sensor **616** is positioned to make direct contact with a participant's skin just behind the ear at a local skeletal eminence. Cutaneous

sensor **616** may additionally be connected electrically to another element within housing **604**. In some embodiment, housing **604** including cutaneous sensor **616** such as the skin temperature sensor and the skin galvanic sensor may be mounted to an exterior body surface of a participant, wherein exterior body surface may include, without limitation, skin, hair, an interior surface of an orifice such as the mouth, nose, or ears, or the like. Exterior body surface and/or locus may include an exterior body surface of user's head, face, or neck. In another embodiment, cutaneous sensor **616** may be configured to contact a locus on the exterior body surface where substantially no muscle is located between the exterior body surface and an underlying bone structure. Location at a locus where muscle is not located between exterior body surface and underlying bone structure may decrease reading interference and/or inaccuracies created by movement and flexing of muscular tissue. In one embodiment, cutaneous sensor **616** may contact a locus having little or no hair on top of skin. In one embodiment, cutaneous sensor **116** may contact a locus near to a blood vessel, such as a locus where a large artery such as the carotid artery or a branch thereof, or a large vein such as the jugular vein, runs near to skin or bone at the location. In another embodiment, such a position may permit cutaneous sensor **616** to detect a participant's biometrics such as circulatory parameters.

(55) Still referring to FIG. 6, seal **612** may be substantially pliable; seal **612** may be constructed of elastomeric, elastic, or flexible materials including without limitation flexible, elastomeric, or elastic rubber, plastic, silicone including medical grade silicone, gel, and the like. Substantially pliable seal **612** may include any combination of materials demonstrating flexible, elastomeric, or elastic properties, including without limitation foams covered with flexible membranes or sheets of polymer, leather, or textile material. As a non-limiting example, substantially pliable seal **612** may include any suitable pliable material for placement over a user's ear, including without limitation any pliable material or combination of materials suitable for use on headphones, headsets, earbuds, or the like. In an embodiment, substantially pliable seal **612** advantageously aids in maintaining ear cup **608** and/or other components of headset **600** against exterior body surface; for instance, where exterior body surface has elastomeric properties and may be expected to flex, stretch, or otherwise alter its shape or position to during operation, substantially pliable seal **612** may also stretch, flex, or otherwise alter its shape similarly under similar conditions. Seal **612** may be attached to housing **604** by any suitable means, including without limitation adhesion, fastening by stitching, stapling, or other penetrative means, snapping together or otherwise engaging interlocking parts, or the like. Seal **612** may be removably attached to ear cup **608**, where removable attachment signifies attachment according to a process that permits repeated attachment and detachment without noticeable damage to housing **604** and/or seal **612**, and without noticeable impairment of an ability to reattach again by the same process. As a non-limiting example, substantially pliable seal **612** may be placed on an ear cup of the housing **604**. Further disclosure related to cutaneous sensor **616** may be found in U.S. patent application Ser. No. 17/892,542, filed on Aug. 22, 2022, entitled "SYSTEMS AND METHODS FOR CORRELATING CUTANEOUS ACTIVITY WITH HUMAN PERFORMANCE," the entirety of which is incorporated herein by reference.

(56) Referring now to FIG. 7, an exemplary placement of an EMG sensor **700** is illustrated. In some cases, EMG may be an electrodiagnostic medicine technique for evaluating and recording electrical activity produced by skeletal muscles. EMG may be performed using an instrument called an electromyograph to produce a record called an electromyogram. An electromyograph may detect electric potential generated by muscle cells, for instance when these cells are electrically or neurologically activated. Resulting electromyographic signals can be analyzed to detect medical abnormalities, activation level, or recruitment order, or to analyze the biomechanics of human or animal movement. In some cases, EMG may also be used as middleware in gesture recognition towards allowing input of physical action to a computing device or as a form of human-computer interaction. An EMG sensor **700** may include at least a ground electrode **704** and at least an EMG electrode **708**. In some cases, a ground electrode **704** may be placed substantially away from an eye

and/or extraocular muscles. In some cases, a ground electrode **704** may be electrically isolated, thereby allowing detection of muscular electrical activity relative the body rather than relative a ground or other reference. In some cases, EMG signals may be substantially made up of superimposed motor unit action potentials (MUAPs) from several motor units including muscles. EMG signals can be decomposed into their constituent MUAPs. MUAPs from different motor units tend to have different characteristic shapes, while MUAPs recorded by the same electrode from the same motor unit are typically similar. Notably MUAP size and shape depend on where the electrode is located with respect to muscle fibers and so can appear different if an electrode **704**, **708** moves position. EMG decomposition may involve any signal processing methods described in this disclosure, including those below.

(57) With continued reference to FIG. 7, in some case EMG signal rectification may include translation of a raw EMG signal to a signal with a single polarity, for instance positive. In some cases, rectifying an EMG signal may be performed to ensure the EMG signal does not average to zero, as commonly a raw EMG signal may have positive and negative components. According to some embodiments, substantially two types of EMG signal rectification may be used full-wave and half-wave rectification. As used in this disclosure, “full-wave rectification” may add EMG signal below a baseline to the EMG signal above the baseline, thereby resulting in a conditioned EMG signal that is all positive. For example, if baseline of EMG signal is zero, full-wave rectification would be equivalent to taking an absolute value of the EMG signal. According to some embodiments, full-wave rectification may conserve substantially all of EMG signal energy for analysis. As used in this disclosure, “half-wave rectification” discards a portion of EMG signal below baseline. As a result of half-wave rectification, average of EMG signal may no longer be zero; therefore, an EMG signal conditioned by half-wave rectification can be used in further statistical analyses.

(58) Still referring to FIG. 7, in some embodiments, EMG sensor **700** may be used to detect a gaze of participant **140** and/or the gaze of participant **140** over time. As used in this disclosure, “gaze” is a direction participant **140** is looking. As used in this disclosure “gaze vector” is a directional vector having a point located at a participant's eye which represents a gaze of participant **140**. In a non-limiting example, the participant's eye may include pupil, retina, or the like. In some cases, an EMG sensor **700** may be used to detect a gaze of participant **140** over time and this information may be used as input for one or more machine-learning models described herein. For example, in some cases, participant's whose gaze is infrequently directed at interface **152** may be found to have a relatively lower confidence than those whose gaze is fixed on the interface **152**. Alternatively or additionally, in some cases, participant's blink rate as detected by EMG sensor **700** may be used as an input for one or more machine-learning described herein as participant **140** who blink more frequently may be less trustworthy than those who blink less.

(59) Still referring to FIG. 7, in some embodiments, similar gaze tracking and/or blink tracking functionality may be performed by using camera and machine vision software. An exemplary machine vision camera that may be included is an OpenMV Cam H7 from OpenMV, LLC of Atlanta, Georgia, U.S.A. OpenMV Cam comprises a small, low power, microcontroller which allows execution of machine vision applications. OpenMV Cam may comprise an ARM Cortex M7 processor and a 640×480 image sensor operating at a frame rate up to 150 fps. OpenMV Cam may be programmed with Python using a Remote Python/Procedure Call (RPC) library. OpenMV CAM may be used to operate image classification and segmentation models, such as without limitation by way of TensorFlow Lite; detection motion, for example by way of frame differencing algorithms; marker detection, for example blob detection; object detection, for example face detection; eye tracking; person detection, for example by way of a trained machine learning model; camera motion detection, for example by way of optical flow detection; code (barcode) detection and decoding; image capture; and video recording. Further disclosure related to EMG sensor **700** may be found in U.S. patent application Ser. No. 17/731,935, filed on Apr. 28, 2022, entitled

“SYSTEMS AND METHODS FOR DETERMINING ACTOR STATUS ACCORDING TO BEHAVIORAL PHENOMENA,” the entirety of which is incorporated herein by reference.

(60) Referring now to FIG. 8, an exemplary embodiment of a machine-learning module **800** that may perform one or more machine-learning processes as described in this disclosure is illustrated. Machine-learning module may perform determinations, classification, and/or analysis steps, methods, processes, or the like as described in this disclosure using machine learning processes. A “machine learning process,” as used in this disclosure, is a process that automatically uses training data **804** to generate an algorithm that will be performed by a computing device/module to produce outputs **808** given data provided as inputs **812**; this is in contrast to a non-machine learning software program where the commands to be executed are determined in advance by a user and written in a programming language.

(61) Still referring to FIG. 8, “training data,” as used herein, is data containing correlations that a machine-learning process may use to model relationships between two or more categories of data elements. For instance, and without limitation, training data **304** may include a plurality of data entries, each entry representing a set of data elements that were recorded, received, and/or generated together; data elements may be correlated by shared existence in a given data entry, by proximity in a given data entry, or the like. Multiple data entries in training data **804** may evince one or more trends in correlations between categories of data elements; for instance, and without limitation, a higher value of a first data element belonging to a first category of data element may tend to correlate to a higher value of a second data element belonging to a second category of data element, indicating a possible proportional or other mathematical relationship linking values belonging to the two categories. Multiple categories of data elements may be related in training data **804** according to various correlations; correlations may indicate causative and/or predictive links between categories of data elements, which may be modeled as relationships such as mathematical relationships by machine-learning processes as described in further detail below. Training data **804** may be formatted and/or organized by categories of data elements, for instance by associating data elements with one or more descriptors corresponding to categories of data elements. As a non-limiting example, training data **804** may include data entered in standardized forms by persons or processes, such that entry of a given data element in a given field in a form may be mapped to one or more descriptors of categories. Elements in training data **804** may be linked to descriptors of categories by tags, tokens, or other data elements; for instance, and without limitation, training data **304** may be provided in fixed-length formats, formats linking positions of data to categories such as comma-separated value (CSV) formats and/or self-describing formats such as extensible markup language (XML), JavaScript Object Notation (JSON), or the like, enabling processes or devices to detect categories of data.

(62) Alternatively or additionally, and continuing to refer to FIG. 8, training data **804** may include one or more elements that are not categorized; that is, training data **804** may not be formatted or contain descriptors for some elements of data. Machine-learning algorithms and/or other processes may sort training data **804** according to one or more categorizations using, for instance, natural language processing algorithms, tokenization, detection of correlated values in raw data and the like; categories may be generated using correlation and/or other processing algorithms. As a non-limiting example, in a corpus of text, phrases making up a number “n” of compound words, such as nouns modified by other nouns, may be identified according to a statistically significant prevalence of n-grams containing such words in a particular order; such an n-gram may be categorized as an element of language such as a “word” to be tracked similarly to single words, generating a new category as a result of statistical analysis. Similarly, in a data entry including some textual data, a person's name may be identified by reference to a list, dictionary, or other compendium of terms, permitting ad-hoc categorization by machine-learning algorithms, and/or automated association of data in the data entry with descriptors or into a given format. The ability to categorize data entries automatically may enable the same training data **804** to be made applicable for two or more distinct

machine-learning algorithms as described in further detail below. Training data **304** used by machine-learning module **300** may correlate any input data as described in this disclosure to any output data as described in this disclosure.

(63) Further referring to FIG. **8**, training data may be filtered, sorted, and/or selected using one or more supervised and/or unsupervised machine-learning processes and/or models as described in further detail below; such models may include without limitation a training data classifier **816**. Training data classifier **816** may include a “classifier,” which as used in this disclosure is a machine-learning model as defined below, such as a mathematical model, neural net, or program generated by a machine learning algorithm known as a “classification algorithm,” as described in further detail below, that sorts inputs into categories or bins of data, outputting the categories or bins of data and/or labels associated therewith. A classifier may be configured to output at least a datum that labels or otherwise identifies a set of data that are clustered together, found to be close under a distance metric as described below, or the like. Machine-learning module **800** may generate a classifier using a classification algorithm, defined as a process whereby a computing device and/or any module and/or component operating thereon derives a classifier from training data **804**. Classification may be performed using, without limitation, linear classifiers such as without limitation logistic regression and/or naïve Bayes classifiers, nearest neighbor classifiers such as k-nearest neighbors classifiers, support vector machines, least squares support vector machines, fisher's linear discriminant, quadratic classifiers, decision trees, boosted trees, random forest classifiers, learning vector quantization, and/or neural network-based classifiers.

(64) Still referring to FIG. **8**, machine-learning module **800** may be configured to perform a lazy-learning process **820** and/or protocol, which may alternatively be referred to as a “lazy loading” or “call-when-needed” process and/or protocol, may be a process whereby machine learning is conducted upon receipt of an input to be converted to an output, by combining the input and training set to derive the algorithm to be used to produce the output on demand. For instance, an initial set of simulations may be performed to cover an initial heuristic and/or “first guess” at an output and/or relationship. As a non-limiting example, an initial heuristic may include a ranking of associations between inputs and elements of training data **804**. Heuristic may include selecting some number of highest-ranking associations and/or training data **804** elements. Lazy learning may implement any suitable lazy learning algorithm, including without limitation a K-nearest neighbors algorithm, a lazy naïve Bayes algorithm, or the like; persons skilled in the art, upon reviewing the entirety of this disclosure, will be aware of various lazy-learning algorithms that may be applied to generate outputs as described in this disclosure, including without limitation lazy learning applications of machine-learning algorithms as described in further detail below.

(65) Alternatively or additionally, and with continued reference to FIG. **8**, machine-learning processes as described in this disclosure may be used to generate machine-learning models **824**. A “machine-learning model,” as used in this disclosure, is a mathematical and/or algorithmic representation of a relationship between inputs and outputs, as generated using any machine-learning process including without limitation any process as described above and stored in memory; an input is submitted to a machine-learning model **824** once created, which generates an output based on the relationship that was derived. For instance, and without limitation, a linear regression model, generated using a linear regression algorithm, may compute a linear combination of input data using coefficients derived during machine-learning processes to calculate an output datum. As a further non-limiting example, a machine-learning model **824** may be generated by creating an artificial neural network, such as a convolutional neural network including an input layer of nodes, one or more intermediate layers, and an output layer of nodes. Connections between nodes may be created via the process of “training” the network, in which elements from a training data **804** set are applied to the input nodes, a suitable training algorithm (such as Levenberg-Marquardt, conjugate gradient, simulated annealing, or other algorithms) is then used to adjust the connections and weights between nodes in adjacent layers of the neural network to produce the

desired values at the output nodes. This process is sometimes referred to as deep learning.

(66) Still referring to FIG. 8, machine-learning algorithms may include at least a supervised machine-learning process **828**. At least a supervised machine-learning process **828**, as defined herein, include algorithms that receive a training set relating several inputs to outputs, and seek to find one or more mathematical relations relating inputs to outputs, where each of the one or more mathematical relations is optimal according to some criterion specified to the algorithm using some scoring function. For instance, a supervised learning algorithm may include inputs and outputs described through this disclosure, and a scoring function representing a desired form of relationship to be detected between inputs and outputs; scoring function may, for instance, seek to maximize the probability that a given input and/or combination of elements inputs is associated with a given output to minimize the probability that a given input is not associated with a given output. Scoring function may be expressed as a risk function representing an “expected loss” of an algorithm relating inputs to outputs, where loss is computed as an error function representing a degree to which a prediction generated by the relation is incorrect when compared to a given input-output pair provided in training data **804**. Persons skilled in the art, upon reviewing the entirety of this disclosure, will be aware of various possible variations of at least a supervised machine-learning process **828** that may be used to determine relation between inputs and outputs. Supervised machine-learning processes may include classification algorithms as defined above.

(67) Further referring to FIG. 8, machine learning processes may include at least an unsupervised machine-learning processes **832**. An unsupervised machine-learning process, as used herein, is a process that derives inferences in datasets without regard to labels; as a result, an unsupervised machine-learning process may be free to discover any structure, relationship, and/or correlation provided in the data. Unsupervised processes may not require a response variable; unsupervised processes may be used to find interesting patterns and/or inferences between variables, to determine a degree of correlation between two or more variables, or the like.

(68) Still referring to FIG. 8, machine-learning module **800** may be designed and configured to create a machine-learning model **824** using techniques for development of linear regression models. Linear regression models may include ordinary least squares regression, which aims to minimize the square of the difference between predicted outcomes and actual outcomes according to an appropriate norm for measuring such a difference (e.g., a vector-space distance norm); coefficients of the resulting linear equation may be modified to improve minimization. Linear regression models may include ridge regression methods, where the function to be minimized includes the least-squares function plus term multiplying the square of each coefficient by a scalar amount to penalize large coefficients. Linear regression models may include least absolute shrinkage and selection operator (LASSO) models, in which ridge regression is combined with multiplying the least-squares term by a factor of one divided by double the number of samples. Linear regression models may include a multi-task lasso model wherein the norm applied in the least-squares term of the lasso model is the Frobenius norm amounting to the square root of the sum of squares of all terms. Linear regression models may include the elastic net model, a multi-task elastic net model, a least angle regression model, a LARS lasso model, an orthogonal matching pursuit model, a Bayesian regression model, a logistic regression model, a stochastic gradient descent model, a perceptron model, a passive aggressive algorithm, a robustness regression model, a Huber regression model, or any other suitable model that may occur to persons skilled in the art upon reviewing the entirety of this disclosure. Linear regression models may be generalized in an embodiment to polynomial regression models, whereby a polynomial equation such as a quadratic, cubic or higher-order equation providing a best predicted output/actual output fit is sought; similar methods to those described above may be applied to minimize error functions, as will be apparent to persons skilled in the art upon reviewing the entirety of this disclosure.

(69) Continuing to refer to FIG. 8, machine-learning algorithms may include, without limitation, linear discriminant analysis. Machine-learning algorithm may include quadratic discriminate

analysis. Machine-learning algorithms may include kernel ridge regression. Machine-learning algorithms may include support vector machines, including without limitation support vector classification-based regression processes. Machine-learning algorithms may include stochastic gradient descent algorithms, including classification and regression algorithms based on stochastic gradient descent. Machine-learning algorithms may include nearest neighbors algorithms. Machine-learning algorithms may include various forms of latent space regularization such as variational regularization. Machine-learning algorithms may include Gaussian processes such as Gaussian Process Regression. Machine-learning algorithms may include cross-decomposition algorithms, including partial least squares and/or canonical correlation analysis. Machine-learning algorithms may include naïve Bayes methods. Machine-learning algorithms may include algorithms based on decision trees, such as decision tree classification or regression algorithms. Machine-learning algorithms may include ensemble methods such as bagging meta-estimator, forest of randomized trees, AdaBoost, gradient tree boosting, and/or voting classifier methods. Machine-learning algorithms may include neural net algorithms, including convolutional neural net processes.

(70) Referring now to FIG. 9, an exemplary embodiment of neural network **900** is illustrated. A neural network **900** also known as an artificial neural network, is a network of “nodes,” or data structures having one or more inputs, one or more outputs, and a function determining outputs based on inputs. Such nodes may be organized in a network, such as without limitation a convolutional neural network, including an input layer of nodes **904**, one or more intermediate layers **908**, and an output layer of nodes **912**. Connections between nodes may be created via the process of “training” the network, in which elements from a training dataset are applied to the input nodes, a suitable training algorithm (such as Levenberg-Marquardt, conjugate gradient, simulated annealing, or other algorithms) is then used to adjust the connections and weights between nodes in adjacent layers of the neural network to produce the desired values at the output nodes. This process is sometimes referred to as deep learning. Connections may run solely from input nodes toward output nodes in a “feed-forward” network or may feed outputs of one layer back to inputs of the same or a different layer in a “recurrent network.”

(71) Referring now to FIG. 10, an exemplary embodiment of a node **1000** of a neural network is illustrated. A node **1000** may include, without limitation, a plurality of inputs $x_{sub.i}$ that may receive numerical values from inputs to a neural network containing the node and/or from other nodes. Node **1000** may perform a weighted sum of inputs using weights $w_{sub.i}$ that are multiplied by respective inputs $x_{sub.i}$. Additionally or alternatively, a bias b may be added to the weighted sum of the inputs such that an offset is added to each unit in the neural network layer that is independent of the input to the layer. The weighted sum may then be input into a function ϕ , which may generate one or more outputs y . Weight $w_{sub.i}$ applied to an input $x_{sub.i}$ may indicate whether the input is “excitatory,” indicating that it has strong influence on the one or more outputs y , for instance by the corresponding weight having a large numerical value, and/or a “inhibitory,” indicating it has a weak effect influence on the one more inputs y , for instance by the corresponding weight having a small numerical value. The values of weights $w_{sub.i}$ may be determined by training a neural network using training data, which may be performed using any suitable process as described above.

(72) Referring to FIG. 11, an exemplary embodiment of fuzzy set comparison **1100** is illustrated. A first fuzzy set **1104** may be represented, without limitation, according to a first membership function **1108** representing a probability that an input falling on a first range of values **1112** is a member of the first fuzzy set **1104**, where the first membership function **1108** has values on a range of probabilities such as without limitation the interval $[0,1]$, and an area beneath the first membership function **1108** may represent a set of values within first fuzzy set **1104**. Although first range of values **1112** is illustrated for clarity in this exemplary depiction as a range on a single number line or axis, first range of values **1112** may be defined on two or more dimensions,

representing, for instance, a Cartesian product between a plurality of ranges, curves, axes, spaces, dimensions, or the like. First membership function **1108** may include any suitable function mapping first range **1112** to a probability interval, including without limitation a triangular function defined by two linear elements such as line segments or planes that intersect at or below the top of the probability interval. As a non-limiting example, triangular membership function may be defined as:

$$(73) \ y(x, a, b, c) = \begin{cases} 0, & \text{for } x > c \text{ and } x < a \\ \frac{x-a}{b-a}, & \text{for } a \leq x < b \\ \frac{c-x}{c-b}, & \text{if } b < x \leq c \end{cases}$$

a trapezoidal membership function may be defined as:

$$(74) \ y(x, a, b, c, d) = \max(\min(\frac{x-a}{b-a}, 1, \frac{d-x}{d-c}), 0)$$

a sigmoidal function may be defined as:

$$(75) \ y(x, a, c) = \frac{1}{1 + e^{-a(x-c)}}$$

a Gaussian membership function may be defined as:

$$(76) \ y(x, c) = e^{\frac{1}{2}(\frac{x-c}{\sigma})^2}$$

and a bell membership function may be defined as:

$$(77) \ y(x, a, b, c) = [1 + \text{Math}.\frac{x-c}{a-c}.\text{Math}.\frac{2b}{a-c}]^{-1}$$

Persons skilled in the art, upon reviewing the entirety of this disclosure, will be aware of various alternative or additional membership functions that may be used consistently with this disclosure.

(78) Still referring to FIG. **11**, first fuzzy set **1104** may represent any value or combination of values as described above, including output from one or more machine-learning models and signals **120** from sensor **116**, a predetermined class, such as without limitation a participant trustworthiness **136**. Participant trustworthiness **136**, in a non-limiting example, may include honest, dishonest, or the like. A second fuzzy set **1116**, which may represent any value which may be represented by first fuzzy set **1104**, may be defined by a second membership function **1120** on a second range **1124**; second range **1124** may be identical and/or overlap with first range **1112** and/or may be combined with first range via Cartesian product or the like to generate a mapping permitting evaluation overlap of first fuzzy set **1104** and second fuzzy set **1116**. Where first fuzzy set **1104** and second fuzzy set **1116** have a region **1128** that overlaps, first membership function **1108** and second membership function **1120** may intersect at a point **1132** representing a probability, as defined on probability interval, of a match between first fuzzy set **1104** and second fuzzy set **1116**.

Alternatively or additionally, a single value of first and/or second fuzzy set may be located at a locus **1136** on first range **1112** and/or second range **1124**, where a probability of membership may be taken by evaluation of first membership function **1108** and/or second membership function **1120** at that range point. A probability at **1128** and/or **1132** may be compared to a threshold **1140** to determine whether a positive match is indicated. Threshold **1140** may, in a non-limiting example, represent a degree of match between first fuzzy set **1104** and second fuzzy set **1116**, and/or single values therein with each other or with either set, which is sufficient for purposes of the matching process; for instance, threshold may indicate a sufficient degree of overlap between an output from one or more machine-learning models and/or a signal **120** and a predetermined class, such as without limitation a participant trustworthiness **136**, for combination to occur as described above. Alternatively or additionally, each threshold may be tuned by a machine-learning and/or statistical process, for instance and without limitation as described in further detail below.

(79) Further referring to FIG. **11**, in an embodiment, a degree of match between fuzzy sets may be used to classify signal **120** with participant trustworthiness **136**. For instance, if a biofeedback signal has a fuzzy set matching participant trustworthiness **136** fuzzy set by having a degree of overlap exceeding a threshold, processor **108** may classify the biofeedback signal as honest for participant trustworthiness. Where multiple fuzzy matches are performed, degrees of match for

each respective fuzzy set may be computed and aggregated through, for instance, addition, averaging, or the like, to determine an overall degree of match.

(80) Still referring to FIG. 11, in an embodiment, signal 120 may be compared to multiple participant trustworthiness 136 fuzzy sets. For instance, a visible feedback signal may be represented by a fuzzy set that is compared to each of the multiple participant trustworthiness 136 fuzzy sets; and a degree of overlap exceeding a threshold between the visible feedback signal fuzzy set and any of the multiple participant trustworthiness 136 fuzzy sets may cause processor 108 to classify the visible feedback signal as belonging to participant trustworthiness as dishonest. For instance, in one embodiment there may be two participant trustworthiness fuzzy sets, representing honest and dishonest respectively. Honest may have an honest state fuzzy set; dishonest may have a dishonest state fuzzy set; and the visible feedback signal of signals 120 may have a visible feedback signal fuzzy set. Processor 108, for example, may compare the visible feedback signal fuzzy set with each of honest state fuzzy set and dishonest state fuzzy set, as described above, and classify a visible feedback fuzzy set to either, both, or neither of honest state nor dishonest state. Machine-learning methods as described throughout may, in a non-limiting example, generate coefficients used in fuzzy set equations as described above, such as without limitation x, c, and o of a Gaussian set as described above, as outputs of machine-learning methods. Likewise, signals 120 may be used indirectly to determine a fuzzy set, as a visible feedback signal fuzzy set may be derived from outputs of one or more machine-learning models that take the visible feedback signal fuzzy set directly or indirectly as inputs.

(81) Referring now to FIG. 12, a flow diagram of an exemplary method 1200 for monitoring human trustworthiness is illustrated. At step 1205, method 1200 includes facilitating, by at least an interface, telecommunication for a participant. In some embodiments, telecommunication may include the exchange of information over significant distances by electronic means which may include all types of voice, data, and/or video transmission such as teleconference using a wide range of information-transmitting technologies and communications infrastructures, such as wire phones, mobile devices, microwave communications, fiber optics, satellites, radio and television broadcasting, internet, and telegraphs. This may be implemented as described and with reference to FIGS. 1-11.

(82) Still referring to FIG. 12, at step 1210, method 1200 includes detecting, by a plurality of sensors, a plurality of signals from the participant. In some embodiments, the plurality of sensors may be configured to detect signals related to biofeedback, visible feedback, auditory feedback, and the like. In some embodiments, the plurality of sensors may include at least a NIRS, an exhalation sensor, an inhalation sensor, a cutaneous sensor, a speech sensor, and an eye movement sensor. This may be implemented as described and with reference to FIGS. 1-11.

(83) Continuing to refer to FIG. 12, at step 1215, method 1200 includes receiving, by at least a processor, the plurality of signals. In one embodiment, the plurality of signals is stored in a data store such as, with no limitation, a database. This may be implemented as described and with reference to FIGS. 1-11.

(84) Still referring to FIG. 12, at step 1220, method 1200 includes generating, by the at least a processor, a participant trustworthiness classifier as a function of a participant trustworthiness machine-learning algorithm. This may be implemented as described and with reference to FIGS. 1-11.

(85) Still referring to FIG. 12, at step 1225, method 1200 includes training, by the at least a processor, the participant trustworthiness classifier using at least a training sample, wherein the at least a training sample correlates the plurality of signals to responses of known trustworthiness. In one embodiment, the machine-learning process may be trained using the participant's biometrics. In one embodiment, the machine-learning process may be trained using biometrics from the participant's interlocutor. In one embodiment, the machine-learning process may be trained using what can be seen and heard in the telecommunication. In one embodiment, the machine-learning

process may be trained in accordance with responses to questions with known correct/incorrect answers provided by the participant. This may be implemented as described and with reference to FIGS. 1-11.

(86) Continuing to refer to FIG. 12, at step 1230, method 1200 includes generating, by the at least a processor, a participant trustworthiness as a function of the participant trustworthiness classifier. In some embodiments, a confidence metric associated with the participant trustworthiness may be created by the at least a processor. This may be implemented as described and with reference to FIGS. 1-11.

(87) It is to be noted that any one or more of the aspects and embodiments described herein may be conveniently implemented using one or more machines (e.g., one or more computing devices that are utilized for an electronic document, one or more server devices, such as a document server, etc.) programmed according to the teachings of the present specification, as will be apparent to those of ordinary skill in the computer art. Appropriate software coding can readily be prepared by skilled programmers based on the teachings of the present disclosure, as will be apparent to those of ordinary skill in the software art. Aspects and implementations discussed above employing software and/or software modules may also include appropriate hardware for assisting in the implementation of the machine executable instructions of the software and/or software module.

(88) Such software may be a computer program product that employs a machine-readable storage medium. A machine-readable storage medium may be any medium that is capable of storing and/or encoding a sequence of instructions for execution by a machine (e.g., a computing device) and that causes the machine to perform any one of the methodologies and/or embodiments described herein. Examples of a machine-readable storage medium include, but are not limited to, a magnetic disk, an optical disc (e.g., CD, CD-R, DVD, DVD-R, etc.), a magneto-optical disk, a read-only memory “ROM” device, a random-access memory “RAM” device, a magnetic card, an optical card, a solid-state memory device, an EPROM, an EEPROM, and any combinations thereof. A machine-readable medium, as used herein, is intended to include a single medium as well as a collection of physically separate media, such as, for example, a collection of compact discs or one or more hard disk drives in combination with a computer memory. As used herein, a machine-readable storage medium does not include transitory forms of signal transmission.

(89) Such software may also include information (e.g., data) carried as a data signal on a data carrier, such as a carrier wave. For example, machine-executable information may be included as a data-carrying signal embodied in a data carrier in which the signal encodes a sequence of instruction, or portion thereof, for execution by a machine (e.g., a computing device) and any related information (e.g., data structures and data) that causes the machine to perform any one of the methodologies and/or embodiments described herein.

(90) Examples of a computing device include, but are not limited to, an electronic book reading device, a computer workstation, a terminal computer, a server computer, a handheld device (e.g., a tablet computer, a smartphone, etc.), a web appliance, a network router, a network switch, a network bridge, any machine capable of executing a sequence of instructions that specify an action to be taken by that machine, and any combinations thereof. In one example, a computing device may include and/or be included in a kiosk.

(91) FIG. 13 shows a diagrammatic representation of one embodiment of a computing device in the exemplary form of a computer system 1300 within which a set of instructions for causing a control system to perform any one or more of the aspects and/or methodologies of the present disclosure may be executed. It is also contemplated that multiple computing devices may be utilized to implement a specially configured set of instructions for causing one or more of the devices to perform any one or more of the aspects and/or methodologies of the present disclosure. Computer system 1300 includes a processor 1304 and a memory 1308 that communicate with each other, and with other components, via a bus 1312. Bus 1312 may include any of several types of bus structures including, but not limited to, a memory bus, a memory controller, a peripheral bus, a

local bus, and any combinations thereof, using any of a variety of bus architectures.

(92) Processor **1304** may include any suitable processor, such as without limitation a processor incorporating logical circuitry for performing arithmetic and logical operations, such as an arithmetic and logic unit (ALU), which may be regulated with a state machine and directed by operational inputs from memory and/or sensors; processor **1304** may be organized according to Von Neumann and/or Harvard architecture as a non-limiting example. Processor **1304** may include, incorporate, and/or be incorporated in, without limitation, a microcontroller, microprocessor, digital signal processor (DSP), Field Programmable Gate Array (FPGA), Complex Programmable Logic Device (CPLD), Graphical Processing Unit (GPU), general purpose GPU, Tensor Processing Unit (TPU), analog or mixed signal processor, Trusted Platform Module (TPM), a floating-point unit (FPU), and/or system on a chip (SoC).

(93) Memory **1308** may include various components (e.g., machine-readable media) including, but not limited to, a random-access memory component, a read only component, and any combinations thereof. In one example, a basic input/output system **1316** (BIOS), including basic routines that help to transfer information between elements within computer system **1300**, such as during start-up, may be stored in memory **1308**. Memory **1308** may also include (e.g., stored on one or more machine-readable media) instructions (e.g., software) **1320** embodying any one or more of the aspects and/or methodologies of the present disclosure. In another example, memory **1308** may further include any number of program modules including, but not limited to, an operating system, one or more application programs, other program modules, program data, and any combinations thereof.

(94) Computer system **1300** may also include a storage device **1324**. Examples of a storage device (e.g., storage device **1324**) include, but are not limited to, a hard disk drive, a magnetic disk drive, an optical disc drive in combination with an optical medium, a solid-state memory device, and any combinations thereof. Storage device **1324** may be connected to bus **1312** by an appropriate interface (not shown). Example interfaces include, but are not limited to, SCSI, advanced technology attachment (ATA), serial ATA, universal serial bus (USB), IEEE 1394 (FIREWIRE), and any combinations thereof. In one example, storage device **1324** (or one or more components thereof) may be removably interfaced with computer system **1300** (e.g., via an external port connector (not shown)). Particularly, storage device **1324** and an associated machine-readable medium **1328** may provide nonvolatile and/or volatile storage of machine-readable instructions, data structures, program modules, and/or other data for computer system **1300**. In one example, software **1320** may reside, completely or partially, within machine-readable medium **1328**. In another example, software **1320** may reside, completely or partially, within processor **1304**.

(95) Computer system **1300** may also include an input device **1332**. In one example, a user of computer system **1300** may enter commands and/or other information into computer system **1300** via input device **1332**. Examples of an input device **1332** include, but are not limited to, an alphanumeric input device (e.g., a keyboard), a pointing device, a joystick, a gamepad, an audio input device (e.g., a microphone, a voice response system, etc.), a cursor control device (e.g., a mouse), a touchpad, an optical scanner, a video capture device (e.g., a still camera, a video camera), a touchscreen, and any combinations thereof. Input device **1332** may be interfaced to bus **1312** via any of a variety of interfaces (not shown) including, but not limited to, a serial interface, a parallel interface, a game port, a USB interface, a FIREWIRE interface, a direct interface to bus **1312**, and any combinations thereof. Input device **1332** may include a touch screen interface that may be a part of or separate from display **1336**, discussed further below. Input device **1332** may be utilized as a user selection device for selecting one or more graphical representations in a graphical interface as described above.

(96) A user may also input commands and/or other information to computer system **1300** via storage device **1324** (e.g., a removable disk drive, a flash drive, etc.) and/or network interface device **1340**. A network interface device, such as network interface device **1340**, may be utilized

for connecting computer system **1300** to one or more of a variety of networks, such as network **1344**, and one or more remote devices **1348** connected thereto. Examples of a network interface device include, but are not limited to, a network interface card (e.g., a mobile network interface card, a LAN card), a modem, and any combination thereof. Examples of a network include, but are not limited to, a wide area network (e.g., the Internet, an enterprise network), a local area network (e.g., a network associated with an office, a building, a campus or other relatively small geographic space), a telephone network, a data network associated with a telephone/voice provider (e.g., a mobile communications provider data and/or voice network), a direct connection between two computing devices, and any combinations thereof. A network, such as network **1344**, may employ a wired and/or a wireless mode of communication. In general, any network topology may be used. Information (e.g., data, software **1320**, etc.) may be communicated to and/or from computer system **1300** via network interface device **1340**.

(97) Computer system **1300** may further include a video display adapter **1352** for communicating a displayable image to a display device, such as display device **1336**. Examples of a display device include, but are not limited to, a liquid crystal display (LCD), a cathode ray tube (CRT), a plasma display, a light emitting diode (LED) display, and any combinations thereof. Display adapter **1352** and display device **1336** may be utilized in combination with processor **1304** to provide graphical representations of aspects of the present disclosure. In addition to a display device, computer system **1300** may include one or more other peripheral output devices including, but not limited to, an audio speaker, a printer, and any combinations thereof. Such peripheral output devices may be connected to bus **1312** via a peripheral interface **1356**. Examples of a peripheral interface include, but are not limited to, a serial port, a USB connection, a FIREWIRE connection, a parallel connection, and any combinations thereof.

(98) The foregoing has been a detailed description of illustrative embodiments of the invention. Various modifications and additions can be made without departing from the spirit and scope of this invention. Features of each of the various embodiments described above may be combined with features of other described embodiments as appropriate in order to provide a multiplicity of feature combinations in associated new embodiments. Furthermore, while the foregoing describes a number of separate embodiments, what has been described herein is merely illustrative of the application of the principles of the present invention. Additionally, although particular methods herein may be illustrated and/or described as being performed in a specific order, the ordering is highly variable within ordinary skill to achieve methods, systems, and software according to the present disclosure. Accordingly, this description is meant to be taken only by way of example, and not to otherwise limit the scope of this invention.

(99) Exemplary embodiments have been disclosed above and illustrated in the accompanying drawings. It will be understood by those skilled in the art that various changes, omissions and additions may be made to that which is specifically disclosed herein without departing from the spirit and scope of the present invention.

Claims

1. An apparatus for monitoring human trustworthiness, wherein the apparatus comprises: at least an interface configured to facilitate telecommunication for a participant; a plurality of sensors configured to detect a plurality of signals from the participant; and at least a computing device comprising: at least a processor; and a memory communicatively connected to the at least a processor, wherein the memory contains instructions configuring the at least a processor to: receive the plurality of signals from the plurality of sensors; generate a participant trustworthiness classifier using at least a training sample, wherein generating the participant trustworthiness classifier comprises: training the participant trustworthiness classifier using the at least a training sample, wherein the at least a training sample comprises a plurality of visible feedback signals and auditory

feedback signals as input correlated to a plurality of responses of known trustworthiness as output; determine a participant trustworthiness as a function of the plurality of signals using the trained participant trustworthiness classifier; and generate a confidence metric associated with the determined participant trustworthiness.

2. The apparatus of claim 1, wherein the plurality of signals comprises one or more biofeedback signals.

3. The apparatus of claim 1, wherein the plurality of signals comprises a geographic location signal associated with the participant.

4. The apparatus of claim 1, wherein the plurality of sensors comprising at least a sensor selected from a group consisting a near-infrared (NIR) spectroscopy sensor, an exhalation sensor, an inhalation sensor, a cutaneous sensor, a speech sensor, an eye movement sensor, and a body movement sensor.

5. The apparatus of claim 1, wherein receiving the plurality of signals comprises: receiving the plurality of signals from the plurality of sensors during a teleconference between the participant and an interlocutor.

6. The apparatus of claim 1, wherein the memory contains instructions further configuring the at least a processor to: train at least a machine learning model using eye pattern training data, wherein the eye pattern training data comprises a plurality of eye parameters as input correlated to a plurality of eye patterns as output; and determine at least an eye pattern as a function of the plurality of signals using the at least a machine learning model.

7. The apparatus of claim 6, wherein generating the confidence metric comprises: generating the confidence metric associated with the participant trustworthiness as a function of the at least an eye pattern, wherein the at least an eye pattern comprises a frequency of gaze at the at least an interface associated with the participant.

8. The apparatus of claim 1, wherein the memory contains instructions further configuring the at least a processor to: train at least a machine learning model using speech pattern training data, wherein the speech pattern training data comprises a plurality of speech parameters as input correlated to a plurality of speech patterns as output; and determine at least a speech pattern as a function of the plurality of signals using the at least a machine learning model.

9. The apparatus of claim 8, wherein determining the participant trustworthiness comprises: determining the participant trustworthiness as a function of the at least a speech pattern, wherein the at least a speech pattern comprises a plurality of prosodic variables.

10. The apparatus of claim 1, wherein the memory contains instructions further configuring the at least a processor to: modify at least a display parameter associated with the at least an interface as a function of the participant trustworthiness and the confidence metric.

11. A method for monitoring human trustworthiness, the method comprising: facilitating, by at least an interface, telecommunication for a participant; detecting, by a plurality of sensors, a plurality of signals from the participant; receiving, by at least a processor, the plurality of signals from the plurality of sensors; generating, by the at least a processor, a participant trustworthiness classifier using at least a training sample, wherein generating the participant trustworthiness classifier comprises: training the participant trustworthiness classifier using the at least a training sample, wherein the at least a training sample comprises a plurality of visible feedback signals and auditory feedback signals as input correlated to a plurality of responses of known trustworthiness as output; determining, by the at least a processor, a participant trustworthiness as a function of the plurality of signals using the trained participant trustworthiness classifier; and generating, by the at least a processor, a confidence metric associated with the determined participant trustworthiness.

12. The method of claim 11, wherein the plurality of signals comprises one or more biofeedback signals.

13. The method of claim 11, wherein the plurality of signals comprises a geographic location signal associated with the participant.

14. The method of claim 11, wherein the plurality of sensors comprising at least a sensor selected from a group consisting a near-infrared (NIR) spectroscopy sensor, an exhalation sensor, an inhalation sensor, a cutaneous sensor, a speech sensor, an eye movement sensor, and a body movement sensor.

15. The method of claim 11, wherein receiving the plurality of signals comprises: receiving the plurality of signals from the plurality of sensors during a teleconference between the participant and an interlocutor.

16. The method of claim 11, further comprises: training, by the at least a processor, at least a machine learning model using eye pattern training data, wherein the eye pattern training data comprises a plurality of eye parameters as input correlated to a plurality of eye patterns as output; and determining, by the at least a processor, at least an eye pattern as a function of the plurality of signals using the at least a machine learning model.

17. The method of claim 16, wherein generating the confidence metric comprises: generating the confidence metric associated with the participant trustworthiness as a function of the at least an eye pattern, wherein the at least an eye pattern comprises a frequency of gaze at the at least an interface associated with the participant.

18. The method of claim 11, further comprises: training, by the at least a processor, at least a machine learning model using speech pattern training data, wherein the speech pattern training data comprises a plurality of speech parameters as input correlated to a plurality of speech patterns as output; and determining, by the at least a processor, at least a speech pattern as a function of the plurality of signals using the at least a machine learning model.

19. The method of claim 18, wherein determining the participant trustworthiness comprises: determining the participant trustworthiness as a function of the at least a speech pattern, wherein the at least a speech pattern comprises a plurality of prosodic variables.

20. The method of claim 11, further comprises: modifying, by the at least a processor, at least a display parameter associated with the at least an interface as a function of the participant trustworthiness and the confidence metric.
