

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12419146
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Choi; Seung Ri et al.

Light emitting diode package

Abstract

A light emitting module unit includes a circuit board and a light emitting device. The light emitting device includes a plurality of light emitting elements electrically coupled through the circuit board, one or more electrodes arranged on a first surface of the plurality of light emitting elements, a surface barrier formed on a second surface of one or more of the plurality of light emitting elements, and an encapsulation portion disposed above a third surface of the plurality of light emitting elements. The surface barrier is disposed between the encapsulation portion and the second surface of one or more of the plurality of light emitting elements.

Inventors: Choi; Seung Ri (Ansan-si, KR), Kim; Hyuck Jun (Ansan-si, KR), Bang; Se Min (Ansan-si, KR), Woo; Do Choul (Ansan-si, KR), Tae; Se Won (Ansan-si, KR)

Applicant: SEOUL SEMICONDUCTOR CO., LTD. (Ansan-si, KR)

Family ID: 1000008820338

Assignee: SEOUL SEMICONDUCTOR CO., LTD. (Ansan-si, KR)

Appl. No.: 18/626684

Filed: April 04, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240313174 A1	Sep. 19, 2024

Foreign Application Priority Data

KR	10-2017-0105644	Aug. 21, 2017
KR	10-2018-0004648	Jan. 12, 2018

Related U.S. Application Data

continuation parent-doc US 17724864 20220420 US 11978837 child-doc US 18626684
continuation parent-doc US 17086736 20201102 US 11335837 20220517 child-doc US 17724864
continuation parent-doc US 16670778 20191031 US 10825969 20201103 child-doc US 17086736
continuation parent-doc US 15974612 20180508 US 10615321 20200407 child-doc US 16670778

Publication Classification

Int. Cl.: H10H20/854 (20250101); H01L25/075 (20060101); H10H20/83 (20250101);
H10H20/85 (20250101); H10H20/851 (20250101); H10H20/853 (20250101);
H10H20/856 (20250101); H10H20/857 (20250101); H10H20/858 (20250101)

U.S. Cl.:

CPC H10H20/854 (20250101); H10H20/83 (20250101); H10H20/851 (20250101);
H10H20/853 (20250101); H10H20/856 (20250101); H10H20/857 (20250101);
H10H20/858 (20250101); H01L25/0753 (20130101); H10H20/8506 (20250101)

Field of Classification Search

CPC: H10H (20/854); H10H (20/853); H10H (20/851); H10H (20/857); H10H (20/83); H10H
(20/858); H10H (20/856); H10H (20/8506); H01L (25/0753)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9065031	12/2014	Katoh	N/A	H01L 33/62
10615321	12/2019	Choi et al.	N/A	N/A
10825969	12/2019	Choi et al.	N/A	N/A
11335837	12/2021	Choi et al.	N/A	N/A
2008/0048203	12/2007	Son	N/A	N/A
2009/0294780	12/2008	Chou et al.	N/A	N/A
2010/0090231	12/2009	Jung et al.	N/A	N/A
2014/0238243	12/2013	Jardine et al.	N/A	N/A
2015/0034979	12/2014	Lee et al.	N/A	N/A
2016/0126209	12/2015	Hinata	N/A	N/A
2017/0148718	12/2016	Morita	N/A	N/A
2019/0058095	12/2018	Choi et al.	N/A	N/A
2020/0066950	12/2019	Choi et al.	N/A	N/A
2021/0050492	12/2020	Choi et al.	N/A	N/A
2022/0246808	12/2021	Choi et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
101276873	12/2007	CN	N/A
106463470	12/2016	CN	N/A
106558597	12/2016	CN	N/A
108807639	12/2017	CN	N/A
2008277782	12/2007	JP	N/A

2013110210	12/2012	JP	N/A
2015207754	12/2014	JP	N/A
2015220426	12/2014	JP	N/A
2016001697	12/2015	JP	N/A
1020130110131	12/2012	KR	N/A
201721912	12/2016	TW	N/A

OTHER PUBLICATIONS

Office Action(s) from corresponding Chinese Patent Application No. 201810586507.8 (Jan. 12, 2024). cited by applicant

Office Action(s) from corresponding Chinese Patent Application No. 201911391399.X (Jan. 13, 2024). cited by applicant

English translation of Office Action from corresponding Japanese Patent Application No. 2018113526 dated Oct. 12, 2022 (6 pages). cited by applicant

Office Action {6 pages) and Search Report {1 page) issued in corresponding TW Application 107129035, issued Jul. 15, 2022. cited by applicant

Primary Examiner: Jang; Bo B

Attorney, Agent or Firm: Perkins Coie LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 17/724,864, filed on Apr. 20, 2022, which is a continuation of U.S. patent application Ser. No. 17/086,736, filed on Nov. 2, 2020, which is a continuation of U.S. patent application Ser. No. 16/670,778, filed on Oct. 31, 2019, which is a continuation of U.S. patent application Ser. No. 15/974,612, filed on May 8, 2018, which claims priority to and benefit of Korean Patent Application No. 10-2017-0105644, filed on Aug. 21, 2017, and Korean Patent Application No. 10-2018-0004648, filed on Jan. 12, 2018. The aforementioned applications are incorporated herein by reference in their entireties.

TECHNICAL FIELD

(1) This patent document relates to a light emitting diode package including a side-view light emitting diode package.

BACKGROUND

(2) Generally, light emitting diode packages can be classified into top type light emitting diode packages and side-view light emitting diode packages. A side-view light emitting diode package is generally used as a light source for a backlight unit of a display apparatus, which emits light toward a side surface of a light guide plate.

SUMMARY

(3) According to one or more embodiments of the present disclosure, a light emitting module unit includes a circuit board and a light emitting device. The light emitting device includes a plurality of light emitting elements electrically coupled through the circuit board, one or more electrodes arranged on a first surface of the plurality of light emitting elements, a surface barrier formed on a second surface of one or more of the plurality of light emitting elements, and an encapsulation portion disposed above a third surface of the plurality of light emitting elements. The surface barrier is disposed between the encapsulation portion and the second surface of one or more of the plurality of light emitting elements.

- (4) In at least one variant, the light emitting device further includes a wavelength converter arranged on the third surface of each of the plurality of light emitting elements and the encapsulation portion covers the wavelength converter and the plurality of light emitting elements.
- (5) In another variant, the encapsulation portion includes an epoxy resin or a silicone resin for sealing.
- (6) In another variant, the light emitting module unit further includes a housing that includes the circuit board and the light emitting device;
- (7) In another variant, the light emitting device further includes a wavelength converter arranged on each of the plurality of light emitting elements and the encapsulation portion fills in a space of the housing that is not covered by the wavelength converter.
- (8) In another variant, the surface barrier includes SiO_2 or TiO_2 .
- (9) In another variant, the surface barrier includes a smoother surface than a surface of a light emitting element of the plurality of light emitting elements such that a material for the encapsulation portion flows along the surface of the surface barrier.
- (10) In another variant, the encapsulation portion and the surface barrier form a dual structure for blocking penetration of moisture and dust to the plurality of light emitting elements.
- (11) According to one or more embodiments of the present disclosure, a light emitting module unit includes a circuit board, a plurality of electrodes formed on one surface of the circuit board, and a plurality of light emitting elements. A light emitting element of the plurality of light emitting elements includes a light emitting structure electrically coupled to the circuit board and including Group III-V based semiconductors, an encapsulation portion covering an upper surface of the light emitting element, and a reflective layer disposed on a side surface of the light emitting structure of the light emitting element and configured to reflect light emitted through the side surface of the light emitting structure. The reflective layer is disposed between the light emitting structure and the encapsulation portion. The reflective layer is formed of a material having high thermal conductivity and reflectivity.
- (12) In at least one variant, the reflective layer further includes a single layer structure.
- (13) In another variant, the reflective layer further includes a multilayer structure including at least one of Ag, Al, Ni, Ti, a distributed Bragg reflector, or an omnidirectional reflector.
- (14) In another variant, at least two electrodes among the plurality of electrodes are formed on a lower surface of the light emitting structure. The light emitting structure further includes an n-type semiconductor layer, an active layer and a p-type semiconductor layer.
- (15) In another variant, the light emitting module unit further includes a first pad and a second pad arranged on an opposite surface of the circuit board to which the at least two electrodes are arranged. The first pad and the second pad are electrically connected to the at least two electrodes via at least two via-holes formed in the circuit board.
- (16) In another variant, the second pad is electrically connected to at least two light emitting elements to act as a common electrode.
- (17) In another variant, the plurality of light emitting elements further include a first light emitting element and a second light emitting element arranged side by side. The light emitting module unit further includes a first pad, a second pad, and a third pad arranged on an opposite surface of the circuit board to which the plurality of electrodes are arranged. The first light emitting element is electrically coupled to the first pad and the second pad via a first via-hole and the second light emitting element is electrically coupled to the second pad and the third pad via a second via-hole.
- (18) In another variant, the first light emitting element operates individually or independently of the second light emitting element.
- (19) In another variant, the first light emitting element emits a first color and the second light emitting element emits a second color different from the first color.
- (20) According to one or more embodiments of the present disclosure, a light emitting module unit includes a plurality of electrodes and a light emitting element. The light emitting element includes a

light emitting structure including Group III-V based semiconductors, an encapsulation portion covering an upper surface of the light emitting element, and a reflective layer disposed on a side surface of the light emitting structure of each light emitting element. The reflective layer is disposed between the light emitting structure and the encapsulation portion, and the reflective layer reflects the light emitted through the side surface of the light emitting structure.

(21) In at least one variant, the encapsulation portion includes a wavelength converter and fills in a space on and above the light emitting element.

(22) In another variant, the reflective layer is disposed between the light emitting structure and the encapsulation portion, and the reflective layer is formed of a material having high thermal conductivity and reflectivity. The reflective layer is configured to reflect light emitted through the side surface of the light emitting structure.

(23) In another variant, the light emitting module unit further includes a circuit board and a housing formed on the circuit board. The housing is configured to house at least two light emitting elements. The at least two light emitting elements operable to emit light of different colors. The at least two light emitting elements are electrically coupled to a plurality of pads arranged on an opposite surface of the circuit board via a plurality of via-holes.

(24) Exemplary embodiments described in the present document provide a side-view light emitting diode package that can be tightly coupled to an exterior substrate.

(25) In one embodiment, a light emitting diode package includes an upper housing and a lower housing. The upper housing includes a first light emitting diode (LED) chip arranged therein, a second LED chip arranged to be spaced apart from the first LED chip in a first direction, two light discharge structures, each light discharge structure corresponding to an upper surface of each LED chip and emitting light from each LED chip therethrough, first electrodes formed on a lower surface of the first LED chip, and second electrodes formed on a lower surface of the second LED chip. The lower housing includes at least three grooves at a lower surface thereof. A first groove corresponds to the first LED chip, a second groove corresponds to the second LED chip, and a third groove is arranged between the first groove and the second groove in the first direction. The lower housing further includes three or more pads, each pad corresponding to each groove and covering at least a portion of each groove, a first pair of via-holes and a second pair of via-holes. The first pair of via-holes are arranged to connect the first electrodes to one or more of the pads in a second direction perpendicular to the first direction. The second pair of via-holes are arranged to connect the second electrodes to one or more of the pads in the second direction. The third groove is formed at a position between one of the first pair of via-holes and one of the second pair of via-holes.

(26) In some embodiments, the first pair of via-holes face each other over the first groove. The second pair of via-holes face each other over the second groove. One of the first pair of via-holes is connected to one of the pads and the other of the first pair of via-holes is connected to a different pad.

(27) In some embodiments, a distance between two facing ends of the two light discharge structures is smaller than a distance between one of the first pair of via-holes and one of the second pair of via-holes, one of the first pair of via-holes facing one of the second pair of via-holes over the third groove. In some embodiments, a distance from one end of the light discharge structure to one of sidewalls of the upper housing is smaller than a distance from one of the second pair of via-holes to one of sidewalls of the lower housing.

(28) In some embodiments, one end of the light discharge structure is proximate to one of the sidewalls of the upper housing, and one end of the second pair of via-holes is proximate to one of the sidewalls of the lower housing. In some embodiments, a protective layer is arranged between two adjacent pads.

(29) In another embodiment, a light emitting diode package includes a first LED chip structure and a second LED chip structure. The first LED chip structure includes a first LED chip, a first wavelength converter arranged on an upper surface of the first LED chip; and a first pair of

electrodes arranged on a lower surface of the LED chip. The second LED chip structure includes a second LED chip, a second wavelength converter arranged on an upper surface of the second LED chip, and a second pair of electrodes arranged on a lower surface of the LED chip. The light emitting diode package further includes an upper housing comprising the first LED chip structure and the second LED chip structure arranged side by side with a predetermined space interposed therebetween, a set of grooves comprising a first groove associated with the first LED chip structure, a second groove associated with the second LED chip structure, and a third groove disposed between the first groove and the second groove. The light emitting diode package further includes a first set of via-holes connecting the first LED chip structure to a first pad and a second pad, a second set of via-holes connecting the second LED chip structure to the second pad and a third pad, and a lower housing comprising the set of grooves formed at a lower surface, the first set of via-holes and the second set of via-holes.

(30) In some embodiments, a distance between two different via-holes over the third groove is larger than a shortest distance between the first wavelength converter and the second wavelength converter. A distance from an inner surface of one sidewall of the upper housing to the second wavelength converter proximate to the one sidewall of the upper housing is smaller than a distance from an inner surface of one sidewall of the lower housing to one of the second set of via-holes proximate to the one sidewall of the lower housing.

(31) In some embodiments, no groove is arranged in a space between one sidewall of the lower housing and one of the second set of via-holes proximate to the one sidewall of the lower housing. In some embodiments, no groove is formed between the other sidewall of the lower housing and one of the first set of via-holes proximate to the other sidewall of the lower housing.

(32) In some embodiments, a shortest distance between the first and the second wavelength converters is smaller than a shortest distance between the first and the second LED chips. The light emitting diode package further includes a protective layer formed at the lower surface of the lower housing and partially overlaps with one or more pads.

(33) In some embodiments, an outer surface of the one sidewall of the upper housing and an outer surface of the one sidewall of the lower housing are coplanar.

(34) In accordance with one embodiment, a light emitting diode package includes: at least one light emitting diode chip; a housing on which the at least one light emitting diode chip is mounted, the housing being open at at least one surface thereof to allow light emitted from the at least one light emitting diode chip to be discharged through the open surface of the housing; and a plurality of pads disposed on a second surface of the housing different from a first surface of the housing through which light is discharged, the plurality of pads being electrically connected to the at least one light emitting diode chip, wherein the housing has a plurality of grooves formed on a third surface thereof adjacent to the second surface.

(35) The pads may be formed at locations corresponding to the grooves, respectively, and each of the pads and the grooves may be coated with an electrically conductive material.

(36) The at least one light emitting diode chip may include a light emitting structure emitting light, and first and second electrodes electrically connected to the light emitting structure, wherein the first and second electrodes may be electrically connected to the plurality of pads, respectively.

(37) The at least one light emitting diode chip may include at least two light emitting diode chips, in which a first electrode of one of the at least two light emitting diode chips may be electrically connected to one of the plurality of pads, a second electrode of the other light emitting diode chip may be electrically connected to another pad, and the first electrode of one of the at least two light emitting diode chips may be electrically connected to the second electrode of the other light emitting diode chip.

(38) The first and second electrodes may be electrically connected to the plurality of pads through a conductive material filling via-holes formed in the housing, respectively.

(39) The pads may be separated a predetermined distance from each other so as to be electrically

insulated from each other.

(40) Each of the pads may be disposed so as to have a predetermined area on the second surface of the housing.

(41) The grooves may be formed over the second surface of the housing on which the plurality of pads is disposed and the third surface thereof adjacent to the second surface thereof.

(42) The grooves may be formed over the second surface of the housing on which the plurality of pads is disposed, the third surface thereof adjacent to the second surface thereof, and a fourth surface thereof adjacent to the third surface thereof.

(43) The housing may be coupled to an exterior substrate such that the third surface of the housing adjoins the exterior substrate.

(44) The housing may be coupled to the exterior substrate such that each of the plurality of pads can be electrically connected thereto via a solder.

(45) The housing may be coupled to the exterior substrate such that the solder fills at least part of each of the plurality of grooves.

(46) The light emitting diode package may further include a protective layer disposed between the pads to expose the grooves.

(47) The protective layer may cover at least part of the pads.

(48) The solder may be deposited on the pads exposed through the protective layer.

(49) The light emitting diode package may further include a reflective layer surrounding a side surface of the light emitting diode chip and reflecting light emitted through the side surface of the light emitting diode chip.

(50) The light emitting diode package may further include a wavelength converter disposed above the light emitting diode chip.

(51) The light emitting diode package may further include a surface barrier disposed to surround a side surface of the light emitting diode chip and upper and side surfaces of the wavelength converter.

(52) The light emitting diode package may further include a surface barrier disposed to surround upper and side surfaces of the light emitting diode chip.

(53) The housing may have an inner wall concavely recessed toward an outer wall thereof.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The accompanying drawings, which are included to provide a further understanding of the disclosed technology, and are incorporated in and constitute a part of this specification, illustrate exemplary embodiments of the disclosed technology, and together with the description serve to describe the principles of the disclosed technology.

(2) FIG. 1 is a perspective view of a light emitting diode package according to a first exemplary embodiment of the disclosed technology.

(3) FIG. 2 is a rear perspective view of the light emitting diode package according to the first exemplary embodiment of the disclosed technology.

(4) FIGS. 3A to 3C show front, side and rear views of the light emitting diode package according to the first exemplary embodiment of the disclosed technology.

(5) FIG. 4 is a side view of the light emitting diode package according to the first exemplary embodiment of the disclosed technology.

(6) FIG. 5 is a cross-sectional view of the light emitting diode package according to the first exemplary embodiment of the disclosed technology.

(7) FIG. 6 is a perspective view of a light emitting diode package according to a second exemplary embodiment of the disclosed technology.

- (8) FIG. 7 is a perspective view of a light emitting diode package according to a third exemplary embodiment of the disclosed technology.
- (9) FIG. 8 is a perspective view of a light emitting diode package according to a fourth exemplary embodiment of the disclosed technology.
- (10) FIG. 9 is a perspective view of a light emitting diode package according to a fifth exemplary embodiment of the disclosed technology.
- (11) FIG. 10 is a perspective view of a light emitting diode package according to a sixth exemplary embodiment of the disclosed technology.
- (12) FIG. 11 to FIG. 13 illustrate a light emitting diode package according to a seventh exemplary embodiment of the disclosed technology, where
- (13) FIG. 11 is a side sectional view of the light emitting diode package according to the seventh exemplary embodiment.
- (14) FIG. 12 is a side view of the light emitting diode package according to the seventh exemplary embodiment.
- (15) FIG. 13 is a rear view of the light emitting diode package according to the seventh exemplary embodiment.
- (16) FIG. 14 is a sectional view of a light emitting diode package according to an eighth exemplary embodiment of the disclosed technology.
- (17) FIG. 15 is a sectional view of a light emitting diode package according to a ninth exemplary embodiment of the disclosed technology.
- (18) FIG. 16 is a sectional view of a light emitting diode package according to a tenth exemplary embodiment of the disclosed technology.
- (19) FIG. 17 is a sectional view of a light emitting diode package according to an eleventh exemplary embodiment of the disclosed technology.
- (20) FIG. 18 is a sectional view of a backlight unit according to a first exemplary embodiment of the disclosed technology.
- (21) FIG. 19 is a sectional view of a backlight unit according to a second exemplary embodiment of the disclosed technology.
- (22) FIG. 20 is a sectional view of a backlight unit according to a third exemplary embodiment of the disclosed technology.

DETAILED DESCRIPTION

- (23) Exemplary embodiments will be described in more detail with reference to the accompanying drawings. The following embodiments are provided by way of example to facilitate the understanding of examples of the disclosed technology. In the drawings, widths, lengths, thicknesses, and the like of elements can be exaggerated for clarity and descriptive purposes. Throughout the specification, the same or like reference numerals denote the same or like elements.
- (24) Various implementations of the disclosed technology provide a light emitting diode package that has an improved coupling with an external substrate. In conventional light emitting diode packages, for example, side-view type light emitting diode packages, a light emitting diode chip is received in a cavity formed on an upper surface of a housing and is electrically connected to leads that extend to the outside of the housing through a lower surface of the housing. The side-view light emitting diode package is coupled to an exterior substrate via solders, which can make it difficult to achieve tight coupling between the light emitting diode package and the exterior substrate due to thickness thereof.
- (25) FIG. 1 is a perspective view of a light emitting diode package according to a first exemplary embodiment of the disclosed technology and FIG. 2 is a rear perspective view of the light emitting diode package according to the first exemplary embodiment of the disclosed technology. FIGS. 3A to 3C are front, side and rear views of the light emitting diode package according to the first exemplary embodiment of the disclosed technology, FIG. 4 is another side view of the light emitting diode package according to the first exemplary embodiment of the disclosed technology,

and FIG. 5 is a cross-sectional view of the light emitting diode package according to the first exemplary embodiment of the disclosed technology.

(26) The light emitting diode package **100** according to the first exemplary embodiment of the disclosed technology includes a housing **110**, light emitting diode chips **120**, first and second wavelength converters **142**, **144**, and first to third pads **132**, **134**, **136**.

(27) As shown in FIG. 5, the housing **110** is formed to surround the light emitting diode chips **120**. In this exemplary embodiment, the housing **110** includes an upper housing **110a** and a lower housing **110b**. Although the upper housing **110a** may be integrally formed with the lower housing **110b**, the following description will be given to each of the upper housing **110a** and the lower housing **110b** for convenience of description.

(28) The housing **110** may be formed of or include a thermosetting material, such as EMC or white silicone, in order to improve light resistance and thermal resistance. The housing may also be formed of or include a thermoplastic material, for example, PA materials.

(29) The housing **110** defines an outer appearance of the light emitting diode package **100**. The upper housing **110a** may have a surface open in one direction from a surface on which the light emitting diode chips **120** are mounted. For example, the upper housing **110a** may have openings on its surface that faces the light emitting diode chips **120**. Accordingly, light emitted from the light emitting diode chips **120** can be discharged through the open surface of the upper housing **110a**. In this exemplary embodiment, the open surface of the upper housing **110a** faces in a front direction thereof, as shown in FIG. 1.

(30) In this exemplary embodiment, the lower housing **110b** may be provided at a lower portion thereof with first to third pads **132**, **134**, **136** to be coupled to an exterior substrate. The first to third pads **132**, **134**, **136** may be coupled to the exterior substrate via a solder to be electrically connected to the exterior substrate. In this exemplary embodiment, the first to third pads **132**, **134**, **136** are formed at a back surface of the lower housing **110b**, as shown in FIG. 1 and FIG. 2.

(31) Further, the lower housing **110b** may have first to third grooves H1, H2, H3 formed on a lower surface thereof. The first to third pads **132**, **134**, **136** may be located on the lower surface of the lower housing **110b** to cover the first to third grooves H1, H2, H3, respectively. Referring to FIG. 2 that shows the rear perspective view of the exemplary light emitting diode package, the lower surface is at the top and the back surface is on the side. The first to third grooves H1, H2, H3 are formed at locations corresponding to the first to third pads **132**, **134**, **136** and may have a predetermined depth. Although the first to third grooves H1, H2, H3 are illustrated as having a semi-cylindrical shape in FIG. 1 and FIG. 2 in this exemplary embodiment, the grooves H1, H2, H3 may have various shapes. Further, each of the first to third grooves H1, H2, H3 formed on the lower surface of the lower housing **110b** may be extended to be open at the back surface of the lower housing **110b**. Thus, the first to third grooves H1, H2, H3 may be formed over the lower surface and the back surface of the lower housing **110b**.

(32) As described above, the first to third grooves H1, H2, H3 are placed corresponding to the first to third pads **132**, **134**, **136**, respectively. In this exemplary embodiment, inner surfaces of the first to third grooves H1, H2, H3 and the first to third pads **132**, **134**, **136** may be plated (coated) with a conductive material such as a metal. With this structure, the first to third pads **132**, **134**, **136** may be electrically connected to the exterior substrate when coupled thereto via the solder.

(33) Referring to FIG. 2 and FIG. 3C, the first to third pads **132**, **134**, **136** may be formed on the back surface of the lower housing **110b** with a predetermined shape and a predetermined size. Here, the first to third pads **132**, **134**, **136** may have various shapes, and may be separated a predetermined distance from one another so as to be electrically insulated from one another. For the reference, FIG. 2 shows the light emitting diode package in a front-to-back and upside-down state of the light emitting diode package shown in FIG. 1.

(34) The first to third pads **132**, **134**, **136** are disposed in a backside region of the housing **110**. In addition, the first to third grooves H1, H2, H3 are formed over the lower surface and the back

surface of the housing **110** so as to be disposed in the regions of the first to third pads **132, 134, 136** on the back surface of the housing **110**. Accordingly, the first to third grooves **132, 134, 136** are not exposed on a side surface of the housing **110**.

(35) Referring to FIG. 3B and FIG. 4, in this exemplary embodiment, the first to third pads **132, 134, 136** may be formed to a predetermined thickness 't' on the back surface of the lower housing **110b**. That is, as described above, the first to third pads **132, 134, 136** may be coupled to the lower housing **110b** by a conductive material such as a metal instead of being plated on the surface of the lower housing **110b**. In some implementations, a plating may be additionally performed to improve electrical conductivity after the first to third pads **132, 134, 136** are coupled to the lower housing **110b**.

(36) Electrical connection between the light emitting diode chips **120** and the first to third pads **132, 134, 136** in this exemplary embodiment will be described with reference to FIG. 5. The light emitting diode chips **120** are received in accommodation spaces of the housing **110**, each open at one side thereof, and the first and second wavelength converters **142, 144** may be disposed to cover the light emitting diode chips **120**, respectively.

(37) The first and second wavelength converters **142, 144** serve to allow the light emitting diode package **100** to emit white light through wavelength conversion of light emitted from the light emitting diode chip **120**. To this end, each of the first and second wavelength converters **142, 144** may contain at least one type of phosphor.

(38) Each of the light emitting diode chips **120** includes a light emitting structure **122** and first and second electrodes **124, 126** formed on a lower surface of the light emitting structure **122**. The light emitting structure **122** includes an n-type semiconductor layer, an active layer and a p-type semiconductor layer, each of which includes Group III-V based semiconductors. By way of example, the n-type semiconductor layer, the active layer and the p-type semiconductor layer may include nitride semiconductors such as (Al, Ga, In)N. Further, the active layer may be interposed between the n-type semiconductor layer and the p-type semiconductor layer.

(39) The n-type semiconductor layer may be a conductive semiconductor layer containing n-type dopants (for example, Si) and the p-type semiconductor layer may be a conductive semiconductor layer containing p-type dopants (for example, Mg). The active layer may include a multi-quantum well (MQW) structure and the composition ratio of the active layer may be determined to allow the light emitting diode chip to emit light having a desired peak wavelength.

(40) The first and second electrodes **124, 126** may be electrically connected to the n-type semiconductor layer and the p-type semiconductor layer, respectively. In some implementations, the connection sequence therebetween can be changed.

(41) The lower housing **110b** may be formed with via-holes VC under the first and second electrodes **124, 126** at a location of the light emitting diode chip **120**. Thus, the via-holes VC extend from the surface of the lower housing **110b**, on which the light emitting diode chip **120** is mounted, to the back surface of the lower housing **110b**. In addition, the first to third pads **132, 134, 136** are disposed on the back surface of the lower housing **110b** and the via-holes VC may be filled with a conductive material. With this structure, the first and second electrodes **124, 126** of the light emitting diode chips **120** can be electrically connected to the first to third pads **132, 134, 136** on the back surface of the lower housing **110b** by the conductive material filling the via-holes VC.

(42) In this exemplary embodiment, the light emitting diode package **100** includes two light emitting diode chips **120** that are arranged along a direction parallel to a surface of the lower housing **110b**. Thus, referring to FIG. 3, the first pad **132** is electrically connected to the first electrode **124** of the light emitting diode chip **120** disposed at the left side of the light emitting diode package and the second pad **134** is electrically connected to the second electrode **126** of the light emitting diode chip **120** disposed at the left side of the light emitting diode package. In addition, the second pad **134** is electrically connected to the first electrode **124** of the light emitting diode chip **120** disposed at the right side of the light emitting diode package and the third pad **136**

is electrically connected to the second electrode **126** of the light emitting diode chip **120** disposed at the right side of the light emitting diode package. That is, the second pad **134** is electrically connected to the two light emitting diode chips **120** to act as a common electrode, which electrically connects the two light emitting diode chips **120** to each other in series.

(43) In addition, with the two light emitting diode chips **120** disposed in the upper housing **110a**, the upper housing **110a** may have two open portions on a surfaces of the upper housing **110a**. In some implementations, the two open portions may be located above the two light emitting diode chips **120**, respectively, as shown in FIG. 1 and FIG. 3A. In this exemplary embodiment, the light emitting diode package **100** is illustrated as including the two light emitting diode chips **120**.

However, it should be understood that the number of light emitting diode chips **120** included in the light emitting diode package **100** is not limited thereto. The light emitting diode package **100** may include various numbers of light emitting diode chips **120**. In this structure, the upper housing **110a** may a surface with open portions disposed above the light emitting diode chips **120**. The number of open portions of the surface of the upper housing **110a** may be determined based on the number of light emitting diode chips **120**. In some implementations, the number of open portions of the surface of the upper housing **110a** may be same as the number of light emitting diode chips **120**.

(44) As described above, the first to third pads **132**, **134**, **136** are formed on the housing **110** of the light emitting diode package **100** and the first to third grooves H1, H2, H3 are formed at the locations of the housing **110** corresponding to the first to third pads **132**, **134**, **136** such that a solder can fill the first to third grooves H1, H2, H3 when the light emitting diode package **100** is coupled to the exterior substrate using the solder. Since the solder contacts the first to third pads **132**, **134**, **136** while filling the first to third grooves H1, H2, H3, the light emitting diode package **100** can be more closely coupled to the exterior substrate. For example, the light emitting diode package **100** can be closely coupled to the exterior substrate through the solder filled in the first to third grooves H1, H2, H3. In this exemplary embodiment, the surface of the light emitting diode package **100** adjoining the exterior substrate is a lower surface of the housing **110** where the first to third grooves H1, H2, H3 are formed.

(45) In addition, the contact area between the solder and the light emitting diode package **100** through the first to third grooves H1, H2, H3 is increased. With this structure, the light emitting diode package **100** can be more firmly coupled to the exterior substrate.

(46) Further, since the solder couples the light emitting diode package to the exterior substrate while filling the first to third grooves H1, H2, H3, the solder does not flow to the side surface of the light emitting diode package **100**. Accordingly, in a structure wherein other light emitting diode chip **120** is disposed on the side surface of the light emitting diode chip **120**, the light emitting diode package **100** can be coupled to the exterior substrate with a minimized distance between adjacent light emitting diode chips **120**, without being obstructed by the solder connecting the light emitting diode chips **120** to the exterior substrate.

(47) FIG. 6 is a perspective view of a light emitting diode package according to a second exemplary embodiment of the disclosed technology.

(48) The light emitting diode package **100** according to the second exemplary embodiment includes a housing **110**, light emitting diode chips **120**, wavelength converters **140**, and first to fourth pads **132**, **134**, **136**, **138**. In the following description, description of the same components as those of the first exemplary embodiment will be omitted.

(49) In this exemplary embodiment, the first to fourth pads **132**, **134**, **136**, **138** are formed on the lower surface of the lower housing **110b**, as shown in FIG. 6. In addition, the lower housing **110b** has first to fourth grooves H1, H2, H3, H4 at locations corresponding to the first to fourth pads **132**, **134**, **136**, **138**. The first to fourth pads **132**, **134**, **136**, **138** may be separated from one another so as to be electrically insulated from each other.

(50) Accordingly, one of two light emitting diode chips **120** may be electrically connected to the first and second pads **132**, **134** and the other light emitting diode chip **120** may be electrically

connected to the third and fourth pads **136, 138**.

(51) FIG. 7 is a perspective view of a light emitting diode package according to a third exemplary embodiment of the disclosed technology.

(52) The light emitting diode package **100** according to the third exemplary embodiment includes a housing **110**, a light emitting diode chip **120**, a wavelength converter **140**, and first to third pads **132, 134, 136**.

(53) In this exemplary embodiment, the light emitting diode package **100** includes one light emitting diode chip **120**. Accordingly, the light emitting diode package **100** includes one wavelength converter **140** formed on a front surface thereof, as shown in FIG. 7. With this structure, the upper housing **110a** may have a surface with a single open portion. Thus, the one light emitting diode chip **120** may be electrically connected to each of the first to third pads **132, 134, 136**. Here, the second pad **134** can serve to couple the light emitting diode package **100** to an exterior substrate. Further, the second pad **134** may act to dissipate heat generated from the light emitting diode package **100**.

(54) In addition, the second pad **134** may be omitted, as needed. In this case, the second groove H2 may not be formed in the lower housing **110b**.

(55) FIG. 8 is a perspective view of a light emitting diode package according to a fourth exemplary embodiment of the disclosed technology.

(56) The light emitting diode package **100** according to the fourth exemplary embodiment includes a housing **110**, light emitting diode chips **120**, wavelength converters **140**, and first and second pads **132, 134**.

(57) In this exemplary embodiment, the first and second pads **132, 134** may be disposed on the back surface of the housing **110** and the lower housing **110b** has first and second grooves H1, H2 at locations corresponding to the first and second pads **132, 134**. In this exemplary embodiment, the first and second grooves H1, H2 may have a relatively large size, unlike the first exemplary embodiment. For example, the first and second grooves H1, H2 may be formed to have a larger area on the lower surface of the lower housing **110b** adjoining an exterior substrate than on the back surface thereof.

(58) In this exemplary embodiment, each of the first and second grooves H1, H2 has a shape which has curved corners and a linear segment between the curved corners to form a relatively large space. With this structure, the first and second grooves H1, H2 can be filled with a relatively large amount of solders.

(59) In the structure wherein the light emitting diode package according to this exemplary embodiment includes two light emitting diode chips **120** as in the first exemplary embodiment, these light emitting diode chips **120** may be connected to each other in series within the housing **110**. In addition, the first electrode **124** of one of the two light emitting diode chips **120** may be electrically connected to the first pad **132** and the second electrode **126** of the other light emitting diode chip **120** may be electrically connected to the second pad **134**.

(60) In the structure wherein the light emitting diode package according to this exemplary embodiment includes one light emitting diode chip **120** as in the third exemplary embodiment, the first electrode **124** of the light emitting diode chip **120** may be electrically connected to the first pad **132** and the second electrode **126** thereof may be electrically connected to the second pad **134**.

(61) FIG. 9 is a perspective view of a light emitting diode package according to a fifth exemplary embodiment of the disclosed technology.

(62) The light emitting diode package **100** according to the fifth exemplary embodiment includes a housing **110**, light emitting diode chips **120**, wavelength converters **140**, and first to third pads **132, 134, 136**. The light emitting diode package **100** according to this embodiment is a modification of the first to third pads **132, 134, 136** in the first exemplary embodiment and description of the same components as those of the first exemplary embodiment will be omitted.

(63) In this exemplary embodiment, the second pad **134** may have a smaller area than the second

pad of the first exemplary embodiment. In addition, the first and third pads **132**, **136** may have a larger area than those of the first exemplary embodiment. As such, since the first and third pads **132**, **136** have relatively large areas, a larger amount of solders can be provided between the exterior substrate and the first and third pads **132**, **136** when coupling the exterior substrate to the light emitting diode package **100**. Accordingly, the first and third pads **132**, **136** electrically connected to the exterior substrate can be more firmly coupled to the exterior substrate than the second pad **134**.

(64) Furthermore, as in the first exemplary embodiment, the second pad **134** according to this exemplary embodiment may act as a common electrode, which electrically connects the two light emitting diode chips **120** to each other in series without electrical connection to the exterior substrate.

(65) FIG. **10** is a perspective view of a light emitting diode package according to a sixth exemplary embodiment of the disclosed technology.

(66) The light emitting diode package **100** according to the sixth exemplary embodiment includes a housing **110**, light emitting diode chips **120**, first and second wavelength converters **142**, **144**, and first to third pads **132**, **134**, **136**. In the following description, description of the same components as those of the above exemplary embodiments will be omitted.

(67) In this exemplary embodiment, the second pad **134** is the same as that of the fifth exemplary embodiment and thus description thereof will be omitted.

(68) The first to third pads **132**, **134**, **136** are disposed on the back surface of the lower housing **110b** and the first and third pads **132**, **136** partially extend to a corner at which a lower surface of the lower housing **110b** adjoins a side surface thereof. Further, in this exemplary embodiment, the lower housing **110b** may have first to third grooves **H1**, **H2**, **H3**, in which the first and third grooves **H1** and **H3** are placed corresponding to the first and third pads **132**, **136**. Each of the first and third grooves **H1**, **H3** may be formed over the lower surface and the back surface of the lower housing **110b**. Thus, the first and third grooves **H1**, **H3** may extend from the lower surface of the lower housing **110b** to both corners thereof. Referring to FIG. **10**, the first and third grooves **H1**, **H3** may be located at the corners or nodes of the lower housing **110b** at two opposite sides. In this implementation, the first and third grooves **H1**, **H3** are formed over the lower surface, back surface, and the side surface of the lower housing **110b**, while the second groove **H2** is formed over the lower surface and the back surface of the lower housing **110b**. In this exemplary embodiment, the first and third grooves **H1**, **H3** are exposed on the side surface of the housing **110**, unlike those of the light emitting diode packages of the above exemplary embodiments.

(69) The structure of the first and third grooves **H1**, **H3** formed at the corners of the lower housing **110b** secures solderability upon coupling the light emitting diode package **100** to the exterior substrate via solders. As such, according to this exemplary embodiment, the first and third grooves **H1**, **H3** are formed at the corners extending from the lower surface to the side surface of the lower housing **110b** and the first and third pads **132**, **136** are formed on the back surface of the lower housing **110b** and connected to the first and third grooves **H1**, **H3**, whereby the light emitting diode package **100** can be more firmly coupled to the exterior substrate.

(70) FIG. **11** to FIG. **13** are views of a light emitting diode package according to a seventh exemplary embodiment of the disclosed technology.

(71) FIG. **11** is a side sectional view of the light emitting diode package according to the seventh exemplary embodiment. FIG. **12** is a side view of the light emitting diode package according to the seventh exemplary embodiment. FIG. **13** is a rear view of the light emitting diode package according to the seventh exemplary embodiment.

(72) The light emitting diode package **200** according to the seventh exemplary embodiment includes a housing **110**, light emitting diode chips **120**, first and second wavelength converters **144**, **144**, first to third pads **132**, **134**, **136**, and a protective layer **210**. In the following description, description of the same components as those of the above exemplary embodiments will be omitted.

(73) The protective layer **210** is formed on the back surface of the light emitting diode package **200**. The protective layer **210** is disposed between the first pad **132**, the second pad **134** and the third pad **136**. In addition, the protective layer **210** may be formed to cover part of the first pad **132**, the second pad **134** and the third pad **136**, as shown in FIG. **11** and FIG. **12**. The first to third pads **132**, **134**, **136** are exposed through spaces between the protective layers **210**. Solders are supplied to the first pad **132** to the third pad **136** exposed by the protective layer **210**.

(74) In a structure wherein the light emitting diode package does not include the protective layer **210**, there can be a problem of short circuit between the pads when excess solder is deposited on the first to third pads **132**, **134**, **136**. Upon curing the solder for bonding the light emitting diode package **200** to a circuit board (not shown), large stress is generated from the first and third grooves **H1**, **H3**, on which a relatively large amount of solder is deposited. Accordingly, even when the housing **110** is attached to a circuit board **710** such that a front surface of the housing **110** becomes parallel to the circuit board **710**, the housing **110** can be slanted by stress of the solder such that the front surface of the housing **110** becomes perpendicular to the circuit board.

(75) The protective layer **210** restricts a region to be deposited with the solder, thereby preventing the first pad **132** to the third pad **136** from receiving excess solder. That is, the protective layer **210** can control the amount of solder to be deposited on the first pad **132** to the third pad **136** and the deposition location of the solders. Thus, the light emitting diode package **200** according to this exemplary embodiment can prevent short circuit between the pads and displacement of the housing **110** due to deposition of excess solder.

(76) According to this exemplary embodiment, the light emitting diode package **200** may be configured such that the first pad **132** and the second pad **134** may be connected to power sources having different polarities. In this exemplary embodiment, one electrode of one of the two light emitting diode chips **120** is connected to another electrode of the other light emitting diode chip **120** by the second pad **134**, in which the other electrode has a different polarity from the one electrode. That is, the two light emitting diode chips **120** can be connected to each other in series by the second pad **134**. The light emitting diode package **200** allows simultaneous operation of the two light emitting diode chips **120**. For a light emitting device such as a backlight unit including a plurality of light emitting diode packages **200**, the plurality of light emitting diode packages **200** can be controlled through simple operation and a drive circuit for control can also be simplified.

(77) In an alternative embodiment, the first pad **132** and the third pad **136** of the light emitting diode package **200** are connected to power sources having the same polarity. In this exemplary embodiment, an electrode of one of the two light emitting diode chips **120** is connected to an electrode of the other light emitting diode chip **120** by the second pad **134**, in which both electrodes have the same polarity. In addition, the second pad **134** is connected to a power source having a different polarity than the first pad **132** and the third pad **136**. That is, the two light emitting diode chips **120** can be connected to each other in parallel. In this exemplary embodiment, the light emitting diode package **200** allows individual operation of the two light emitting diode chips **120**. Since the two light emitting diode chips **120** can be independently operated, it is possible to achieve easy control of color reproducibility, color temperature, brightness, and others. Further, defective light emitting diode chips **120** can be easily selected upon testing of the light emitting diode package **200**.

(78) FIG. **14** is a sectional view of a light emitting diode package according to an eighth exemplary embodiment of the disclosed technology.

(79) Referring to FIG. **14**, the light emitting diode package **300** according to the eighth exemplary embodiment includes a housing **110**, light emitting diode chips **120**, first and second wavelength converters **142**, **144**, and first to fourth pads **132**, **134**, **136**, **138**. In the following description, description of the same components as those of the above exemplary embodiments will be omitted.

(80) In this exemplary embodiment, the first to fourth pads **132**, **134**, **136**, **138** are formed on the lower surface of the lower housing **110b**. In addition, the lower housing **110b** is formed with first to

fourth grooves **H1**, **H2**, **H3**, **H4** (see FIG. **6**) at locations corresponding to the first to fourth pads **132**, **134**, **136**, **138**. The first to fourth pads **132**, **134**, **136**, **138** may be separated from each other so as to be electrically insulated from each other.

(81) With the structure of this exemplary embodiment, one of the two light emitting diode chips **120** may be electrically connected to the first and second pads **132**, **132** and the other light emitting diode chip **120** may be electrically connected to the third and fourth pads **136**, **138**. That is, the two light emitting diode chips **120** can be individually operated.

(82) The first wavelength converter **142** and the second wavelength converter **144** can convert wavelengths of light emitted from the light emitting diode chips **120** into different wavelengths. That is, the first wavelength converter **142** and the second wavelength converter **144** may contain different types of phosphors. Accordingly, light having passed through the first wavelength converter **142** may have a different color from light having passed through the second wavelength converter **144**.

(83) The light emitting diode package **300** according to this exemplary embodiment can emit various colors through emission of different colors from one package. With such a light emitting diode package **300** applied to a backlight unit, a display apparatus can provide high color reproducibility.

(84) In the light emitting diode package **300**, the light emitting diode chips **120** can be independently operated, thereby allowing easy control of color temperature and brightness of the display apparatus corresponding to surrounding environments such as day, night, interior, and exterior environments.

(85) FIG. **15** is a sectional view of a light emitting diode package according to a ninth exemplary embodiment of the disclosed technology.

(86) Referring to FIG. **15**, the light emitting diode package **400** according to the ninth exemplary embodiment includes a reflective layer **410** formed on a side surface of each of the light emitting diode chips **120**. The other features of the light emitting diode package **400** according to the ninth exemplary embodiment are the same as those of the light emitting diode package **400** according to the first to eighth exemplary embodiments and description thereof will be omitted.

(87) In some implementations, the reflective layer **410** is formed on sides of each of the light emitting diode chip **120**. The reflective layer **410** is formed to surround the side surface of the light emitting diode chip **120**.

(88) The reflective layer **410** reflects light emitted through the side surface of the light emitting diode chip **120**. The reflective layer **410** prevents the light emitted from the light emitting diode chips **120** from traveling towards a side surface of the housing **110**. Accordingly, the reflective layer **410** prevents the light emitting diode package **400** from suffering from light bleeding after passing through the side surface of the housing **110**.

(89) In the above exemplary embodiments, heat generated from the light emitting diode chips **120** can be discharged through lower sides of the light emitting diode chips **120** via the electrodes **124**, **126**, the conductive material filling the via-holes **VC**, and the first to third electrode pads **132**, **134**, **136**.

(90) In this exemplary embodiment, the reflective layer **410** serves to perform heat dissipation on the side surface of the light emitting diode chip **120**. Heat generated from the light emitting diode chips **120** can be transferred to the first and second wavelength converters **142**, **144** through the reflective layer **410**. Since the reflective layer **410** is formed of a metal having high thermal conductivity, the reflective layer **410** can rapidly transfer the heat from the light emitting diode chips **120** to the first and second wavelength converters **142**, **144**. The heat transferred to the first and second wavelength converters **142**, **144** can be directly discharged from the light emitting diode package **400** or can be discharged therefrom through the housing **110**. Thus, the light emitting diode package **400** according to this exemplary embodiment can discharge heat from the light emitting diode chips **120** not only through the lower surface of the light emitting diode chip

120 but also through the side surface thereof.

(91) For example, the reflective layer **410** may have a single layer structure or a multilayer structure including at least one of Ag, Al, Ni, Ti, a distributed Bragg reflector, or an omnidirectional reflector.

(92) As such, in the light emitting diode package **400** according to this exemplary embodiment, the reflective layer **410** formed on the side surface of the light emitting diode chips **120** can prevent a light bleeding phenomenon while improving heat dissipation efficiency.

(93) FIG. **16** is a sectional view of a light emitting diode package according to a tenth exemplary embodiment of the disclosed technology.

(94) Referring to FIG. **16**, the light emitting diode package **500** according to the tenth exemplary embodiment includes a housing **110**, light emitting diode chips **120**, wavelength converters **510**, first to third pads **132**, **134**, **136**, an encapsulation portion **530**, and surface barriers **520**. In the following description, description of the same components as those of the above exemplary embodiments will be omitted.

(95) The wavelength converter **510** is disposed to cover an upper surface of the light emitting diode chip **120**. Although not shown in FIG. **16**, a bonding agent is interposed between the wavelength converter **510** and the light emitting diode chip **120**. In the implementation as shown in FIG. **16**, the upper surface of the wavelength converter **510** is located lower than the upper surface of the housing **110**.

(96) The encapsulation portion **530** fills the remaining portion of the housing **110** that is not covered by the wavelength converter **510**. For example, the encapsulation portion is located between the upper surfaces of the wavelength converter **510** and the housing **110**. In the implementation shown in FIG. **16**, the encapsulation portion **530** covers side surfaces of the wavelength converters **510** and side surfaces of the light emitting structure **122**. The encapsulation portion surrounds the wavelength converters **510** and the light emitting diode chips **120**. The encapsulation portion **530** can protect the light emitting diode chips **120** by preventing moisture and dust from entering the housing **110**. The encapsulation portion **530** may be formed of an epoxy resin or a silicone resin, which is generally used to seal a light emitting package.

(97) The surface barrier **520** is formed on a side surface of the light emitting diode chip **120** and upper and side surfaces of the wavelength converter **510**. The surface barrier **520** can protect the light emitting diode chips **120** and the wavelength converters **510** from the outside. With this structure, the surface barrier **520** can prevent moisture and dust entering the encapsulation portion **530** from entering the light emitting diode chips **120** and the wavelength converter **510**.

(98) For example, the surface barrier **520** may be formed of SiO.sub.2, TiO.sub.2, and the like. The surface barrier **520** may be formed by various methods such as deposition, spraying, sputtering, and the like.

(99) Since the surface barrier **520** has a smoother surface than the light emitting diode chips **120** or the wavelength converters **510**, the encapsulation portion **530** has improved flowability. That is, when the housing is filled with a material for the encapsulation portion **530**, the material for the encapsulation portion flows along the surface of the surface barrier **520** since the surface barrier **520** has a smooth surface. Accordingly, when the housing is filled with a material for the encapsulation portion **530**, it is possible to minimize generation of a gap or bubbles between the surface barrier **520** and the encapsulation portion **530**. Thus, the light emitting diode package **500** can have improved light extraction efficiency by minimizing generation of a gap or bubbles between the surface barrier **520** and the encapsulation portion **530**.

(100) Since the light emitting diode package **500** according to this exemplary embodiment includes the encapsulation portion **530** and the surface barrier **520** to form a dual structure for blocking penetration of moisture and dust, the light emitting diode package **500** can prevent deterioration in performance of the light emitting diode chips **120** or discoloration of the wavelength converters **510** due to contact with moisture. Accordingly, the light emitting diode package **500** has improved

reliability through suppression of failure due to moisture and dust.

(101) FIG. **17** is a sectional view of a light emitting diode package according to an eleventh exemplary embodiment of the disclosed technology.

(102) Referring to FIG. **17**, the light emitting diode package **600** according to the eleventh exemplary embodiment includes a housing **110**, light emitting diode chips **120**, wavelength converters **510**, first to third pads **132**, **134**, **136**, an encapsulation portion **530**, and surface barriers **520**. In the following description, description of the same components as those of the above exemplary embodiments will be omitted.

(103) In this exemplary embodiment, the surface barrier **520** is formed on the upper and side surfaces of the light emitting diode chip **120**. For example, a portion of the surface barrier **520** is disposed between the light emitting diode chip **120** and the wavelength converter **510**.

(104) A bonding agent **610** is deposited on an upper surface of the surface barrier **520** to bond the light emitting diode chip **120** to the wavelength converter **510**.

(105) The surface barrier **520** improves flowability of the bonding agent **610** deposited on the upper surface thereof. As the flowability of the bonding agent **610** is improved, it is possible to prevent generation of bubbles in the bonding agent **610** deposited on the surface barrier **520**. Further, the bonding agent **610** may be deposited to have a uniform thickness. Accordingly, the surface barrier **520** can prevent the wavelength converter **510** from being slanted on the light emitting diode chip **120**. With this structure, the light emitting diode package **600** can prevent bubble generation in the bonding agent **610**, thereby improving adhesion between the wavelength converters **510** and the light emitting diode chips **120**. In addition, the light emitting diode package **600** can prevent light traveling toward the wavelength converters **510** from returning back to the light emitting diode chips **120** due to reflection by bubbles in the bonding agent **610**. Further, the light emitting diode package **600** includes the bonding agent **610** deposited to a uniform thickness to prevent the wavelength converter **510** from being slanted, thereby enabling uniform wavelength conversion over the entire light exit surface.

(106) FIG. **18** is a sectional view of a backlight unit according to a first exemplary embodiment of the disclosed technology.

(107) Referring to FIG. **18**, the backlight unit **700** according to this exemplary embodiment includes a light emitting diode package **740**, a circuit board **710**, and a light guide plate **720**.

(108) The light emitting diode package **740** is disposed on the circuit board **710**. Here, a front surface of the light emitting diode package **740** is perpendicular to an upper surface of the circuit board **710** and a side surface of the light emitting diode package **740** is bonded to the upper surface of the circuit board **710** by a solder **730**.

(109) The light emitting diode package **740** may be selected from any light emitting diode packages according to the first to eleventh exemplary embodiments. The solder **730** is deposited on the light emitting diode package **740** to fill grooves H formed in the housing **110**. The groove H shown in FIG. **18** is one of the grooves H1 to H4 formed on the pads described in the above exemplary embodiments.

(110) The light guide plate **720** is disposed such that a light incident surface of the light guide plate faces the front surface of the light emitting diode package **740** where the wavelength converter **140** is disposed.

(111) In this exemplary embodiment, the side surface of the light emitting diode package **740** is bonded to the upper surface of the circuit board **710**. Accordingly, the backlight unit **700** according to this exemplary embodiment allows light emitted from the light emitting diode package **740** to directly enter the light incident surface of the light guide plate **720** without separate formation of the circuit board **710**.

(112) Such a backlight unit **700** does not require a separate formation process, such as bending of the circuit board **710**, thereby enabling process simplification and cost reduction.

(113) Although not shown in this exemplary embodiment, the backlight unit **700** may further

include other components for a typical backlight unit.

(114) FIG. **19** is a sectional view of a backlight unit according to a second exemplary embodiment of the disclosed technology.

(115) Referring to FIG. **19**, the backlight unit **800** according to the second exemplary embodiment includes a light emitting diode package **810**, a circuit board **710**, and a light guide plate **720**. In the following description, description of the same components of the backlight unit **800** according to the first exemplary embodiment will be omitted.

(116) The light emitting diode package **810** according to a twelfth exemplary embodiment includes a housing **820** having a different structure than that of the other exemplary embodiments. The other components of the light emitting diode package **810** according to the twelfth exemplary embodiment are the same as those of the light emitting diode packages according to the first to eleventh exemplary embodiment and thus detailed description thereof will be omitted.

(117) According to this exemplary embodiment, the housing **820** of the light emitting diode package **810** has a recessed inner wall. A central portion of the housing **820** is further recessed from an outer wall of the housing **820**. For example, the housing **820** has an inner wall separated from the outer wall of the housing **820** by a varying distance along the inner wall. In the implementation shown in FIG. **19**, the central portion of the housing **820** has a smaller thickness t_3 than a thickness t_4 of an upper portion of the housing **820**. The inner wall of the housing **820** has a lower portion **821** and an upper portion **822** such that the lower portion **821** becomes closer to the outer wall of the housing **820** along a direction from the light emitting diode chip **120** toward the upper surface of the housing **820** and that the upper portion **822** becomes further away from the outer wall of the housing **820** along the direction.

(118) The lower portion **821** of the inner wall of the housing **820** partially adjoins a side surface of the light emitting diode chip **120**. With this structure, the housing **820** disposed on the side surface of the light emitting diode chip **120** has a large thickness, thereby preventing light emitted from the side surface of the light emitting diode chip **120** from being leaked through the housing **820**. In addition, a distance between the other portion of the lower portion **832** of the inner wall of the housing **820** and the side surface of the light emitting diode chip **120** gradually increases.

Accordingly, a gap is formed between the side surface of the light emitting diode chips **120** and a portion of the lower portion **821** of the inner wall of the housing **820** and is filled with the wavelength converter **140**. The portion of the lower portion **821** of the inner wall of the housing **820** separated from the side surface of the light emitting diode chip **120** may have a flat structure, a concave structure or a convex structure. An upper portion **822** of the inner wall of the housing **820** is connected to the lower portion **821** of the inner wall of the housing **820** to extend to an entrance of an opening of the housing **820**. The upper portion **822** of the inner wall of the housing **820** has a flat structure. Alternatively, the upper portion **822** of the inner wall of the housing **820** may have a curved structure such as a convex or concave structure.

(119) Light emitted through the side surface of the light emitting diode chip **120** is reflected by the inner wall of the housing **820**. In the structure wherein the inner wall of the housing has a linear structure from an upper side thereof to a lower side thereof, some of light reflected by the inner wall of the housing can travel in other directions instead of traveling to a light exit surface corresponding to the entrance of the opening of the housing **820** of the light emitting diode package **810**. However, according to this exemplary embodiment, the recessed inner wall of the housing is formed by the sidewall having different thicknesses t_3 , t_4 at the upper and lower portions thereof such that the housing **820** can reflect light toward the light exit surface of the light emitting diode package **810**. Some of light emitted through the side surface of the light emitting diode chip **120** is reflected by the lower portion **821** of the inclined inner wall of the housing **820** so as to be directed toward the light exit surface of the light emitting diode chip. In addition, the upper portion **822** of the inner wall of the housing **820** serves to guide light emitted from the light emitting diode chip **120** and light reflected by the lower portion **821** of the inner wall of the housing **820** to be directed

toward the light exit surface.

(120) As such, in the backlight unit **800** according to this exemplary embodiment, light reflected by the recessed inner wall of the housing **820** is guided to travel toward the light incident surface of the light guide plate **720**, thereby improving light extraction efficiency.

(121) Although the inner wall of the housing **820** is illustrated as a recessed flat structure in FIG. **19**, the inner wall of the housing **820** may have a concavely curved structure.

(122) FIG. **20** is a sectional view of a backlight unit according to a third exemplary embodiment of the disclosed technology.

(123) Referring to FIG. **20**, the backlight unit **900** according to this exemplary embodiment includes a plurality of light emitting diode packages **740**, a circuit board **710**, and a light guide plate **720**.

(124) Each of the light emitting diode packages **740** includes a protective layer **210** formed on a back surface of a housing **110** thereof.

(125) The plurality of light emitting diode packages **740** may be arranged in a line on an upper surface of the circuit board **710**. In addition, the light emitting diode packages **740** are secured to the circuit board **710** by a solder **730**. The protective layer **210** prevents the solder **730** deposited on each of the light emitting diode packages **740** from contacting another light emitting diode package **740** adjacent thereto. In some implementations, the solder is deposited on each of the light emitting diode packages **740** by the protective layer.

(126) As such, since short circuit between the light emitting diode packages **740** by the solders **730** is prevented by the protective layer **210**, the plurality of light emitting diode packages **740** can be arranged as close as possible.

(127) Since the light emitting diode packages **740** can be arranged as close as possible, a non-luminous region between the light emitting diode packages **740** can be reduced. In addition, the backlight unit **900** according to this exemplary embodiment prevents generation of dark spots between adjacent light emitting diode packages **740** due to intersection of light emitted from the light emitting diode packages **740**. Accordingly, the backlight unit **900** allows uniform incidence of light over the entire light incident surface of the light guide plate **720**, thereby improving uniformity of light emitted through the light guide plate **720**. In addition, since the light emitting diode packages **740** are disposed close to each other, the backlight unit **900** according to this exemplary embodiment allows a greater number of light emitting diode packages **740** to be mounted on the circuit board **710**. As such, in the backlight unit **900** according to this exemplary embodiment, the light emitting diode packages **740** are arranged close to each other by the protective layer **210**, thereby improving uniformity and brightness of light.

(128) Although some exemplary embodiments have been described herein, it should be understood by those skilled in the art that these exemplary embodiments are given by way of illustration only. In addition, although the exemplary embodiments described herein are provided as separate embodiments, these exemplary embodiments may be combined to provide a separate exemplary embodiment. Therefore, the scope of the present disclosure should be limited only by the accompanying claims and equivalents thereto.

Claims

1. A light emitting apparatus, comprising: a circuit board; a first light emitter and a second light emitter that are disposed on the circuit board; a light guide plate including an incident surface receiving light emitted from the first light emitter and the second light emitter; and a first pad and a second pad that are disposed on the circuit board, the second pad electrically connected to the first light emitter and the second light emitter; wherein each of the first light emitter and the second light emitter includes: a light source including Group III-V based layers; a reflective layer disposed on the light source and including multilayers including at least one of Ag, Al, Ni, Ti, a distributed

Bragg reflector, or an omnidirectional reflector; an encapsulation covering the light source and the reflective layer; and a housing surrounding the encapsulation.

2. The light emitting apparatus of claim 1, wherein each of the first light emitter and the second light emitter includes a groove disposed between the housing and the circuit board, the groove including metal material.

3. The light emitting apparatus of claim 2, wherein the groove has a depth and the groove contacts with the housing.

4. The light emitting apparatus of claim 1, wherein the reflective layer includes a material having high thermal conductivity and reflectivity.

5. The light emitting apparatus of claim 1, wherein the light source further includes a surface barrier disposed on the light source, and the encapsulation covers the surface barrier including SiO₂.

6. The light emitting apparatus of claim 5, wherein a lower region of the housing has a different thickness from a thickness of an upper region of the housing.

7. The light emitting apparatus of claim 1, wherein the first light emitter and the second light emitter are electrically connected in series.

8. A light emitting apparatus, comprising: a circuit board; a first light emitter and a second light emitter disposed on the circuit board; a first pad and a second pad that are disposed on the circuit board, the second pad being electrically connected to the first light emitter and the second light emitter; and a light guide plate including an incident surface configured to receive light emitted from the first light emitter and the second light emitter, wherein each of the first light emitter and the second light emitter includes: a light source including Group III-V based layers, a reflective layer disposed on the light source and including multilayers including at least one of Ag, Al, Ni, Ti, a distributed Bragg reflector, or an omnidirectional reflector, an encapsulation covering the light source, and a housing surrounding the encapsulation, and wherein the reflective layer is disposed between the light source and the encapsulation.

9. The light emitting apparatus of claim 8, wherein each of the first light emitter and the second light emitter includes a groove disposed between the housing and the circuit board, the groove including metal material.

10. The light emitting apparatus of claim 9, wherein the groove has a depth and the groove contacts with the housing.

11. The light emitting apparatus of claim 8, wherein the reflective layer includes a material having high thermal conductivity and reflectivity.

12. The light emitting apparatus of claim 8, wherein the light source further includes a surface barrier disposed on the light source, and the encapsulation covers the surface barrier including SiO₂.

13. The light emitting apparatus of claim 12, wherein a lower region of the housing has a different thickness from a thickness of an upper region of the housing.

14. The light emitting apparatus of claim 8, wherein the first light emitter and the second light emitter are electrically connected in series.

15. A light emitting apparatus, comprising: a circuit board; a first light emitter and a second light emitter that are disposed on the circuit board; a first pad and a second pad that are disposed on the circuit board, the second pad electrically connected to the first light emitter and the second light emitter; and a light guide plate including an incident surface receiving light emitted from the first light emitter and the second light emitter, wherein each of the first light emitter and the second light emitter includes: a light source including an active layer, a reflective layer disposed on the light source, an encapsulation covering the light source and the reflective layer, the reflective layer including at least one of Ag, Al, Ni, Ti, a distributed Bragg reflector, or an omnidirectional reflector, and a housing surrounding the encapsulation.

16. The light emitting apparatus of claim 15, wherein each of the first light emitter and the second

light emitter includes a groove disposed between the housing and the circuit board, the groove including metal material.

17. The light emitting apparatus of claim 16, wherein the groove has a depth and the groove contacts with the housing.

18. The light emitting apparatus of claim 15, wherein the reflective layer includes a material having high thermal conductivity and reflectivity, and wherein the first light emitter and the second light emitter are electrically connected in series.

19. The light emitting apparatus of claim 15, wherein the light source further includes a surface barrier disposed on the light source, and the encapsulation covers the surface barrier including SiO.sub.2.

20. The light emitting apparatus of claim 19, wherein a lower region of the housing has a different thickness from a thickness of an upper region of the housing.
