

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250283288

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

Kaufman; Kevin et al.

MODULAR HELICAL PIER FOUNDATION SUPPORT SYSTEMS, ASSEMBLIES AND METHODS WITH SNAP-LOCK COUPLINGS

Abstract

Improved couplers for a building foundation support system include helical ribs and helical grooves in combination with an integrated spring retainer element that automatically snaps into place as the couplers are engaged. Rotational and axial interlocking attachment of support piles is therefore possible without utilizing separately provided fasteners such as bolts.

Inventors: Kaufman; Kevin (Des Peres, MO), Wilkis; Michael D. (Ellisville, MO)

Applicant: PIER TECH SYSTEMS LLC (Chesterfield, MO)

Family ID: 1000008619436

Appl. No.: 19/214542

Filed: May 21, 2025

Related U.S. Application Data

parent US continuation 17174805 20210212 parent-grant-document US 12338598 child US 19214542

us-provisional-application US 62976442 20200214

Publication Classification

Int. Cl.: E02D5/52 (20060101)

U.S. Cl.:

CPC E02D5/526 (20130101); E02D2600/20 (20130101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation of U.S. application Ser. No. 17/174,805 filed Feb. 12, 2021, which claims the benefit of U.S. Provisional Application Ser. No. 62/976,442 filed Feb. 14, 2020, the entire disclosure of which is hereby incorporated by reference in its entirety.

BACKGROUND OF THE INVENTION

[0002] The present invention relates generally to building foundation support systems including assemblies of structural support shaft components, and more specifically to couplers for foundation support shaft components such as helical piers with integrated snap-lock coupler elements.

[0003] If a building foundation moves or settles in the course of construction, or at any time after construction is completed, such movement or settlement may affect the integrity of the building structure and lead to costly repairs. While much care is taken to construct stable foundations in new building projects, certain soil types or other building site conditions, or certain types of buildings or structures, may present particular concerns that call for additional measures to ensure the stability of building foundations.

[0004] Helical piers, also known as anchors, piles or screw piles, are deep foundation solutions commonly used when standard foundation solutions are problematic. Helical piers are driven into the ground with reduced installation time and little soil disturbance compared to large excavation work that may otherwise be required by standard foundation techniques, and a number of helical piers may be installed at designated locations to transfer and distribute the weight of the building structure to load bearing soil to prevent the foundation from moving or shifting. Lifting elements, support brackets or load-bearing caps may be used in combination with the helical piers to construct various types of foundation support systems meeting different needs for both foundation repair and new construction applications.

[0005] When properly designed and when properly installed, existing foundation support systems are effective. Existing foundation support systems, however, tend to be rather difficult to install and are disadvantaged in ways that have yet to completely meet the needs of the marketplace. Improvements are therefore desired.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0006] Non-limiting and non-exhaustive embodiments are described with reference to the following Figures, wherein like reference numerals refer to like parts throughout the various drawings unless otherwise specified.

[0007] FIG. 1 illustrates a perspective view of a conventional foundation support system interacting with a building structure.

[0008] FIG. 2 is a perspective view of an exemplary embodiment of a first coupler and support shaft for a foundation support system according to the present invention.

[0009] FIG. 3 is a side elevational view of the first coupler and support shaft shown in FIG. 2.

[0010] FIG. 4 is a cross-sectional view of the first coupler and support shaft shown in FIG. 3.

[0011] FIG. 5 is a first end view of the first coupler and support shaft shown in FIG. 3.

[0012] FIG. 6 is a second end view of the first coupler and support shaft shown in FIG. 3.

[0013] FIG. 7 is a perspective of the first coupler without the support shaft as shown in FIG. 2.

[0014] FIG. 8 is a perspective view of an exemplary embodiment of a second coupler and support shaft for a foundation support system according to the present invention.

[0015] FIG. 9 is a side elevational view of the second coupler and support shaft shown in FIG. 8.

[0016] FIG. **10** is a cross sectional view of the second coupler and support shaft shown in FIG. **9**.
[0017] FIG. **11** is a first end view of the second coupler and support shaft shown in FIG. **9**.
[0018] FIG. **12** is a second end view of the second coupler and support shaft shown in FIG. **9**.
[0019] FIG. **13** is a perspective of the second coupler without the support shaft shown in FIG. **8**.
[0020] FIG. **14** is a side view of the first coupler and support shaft mated with the second coupler and support shaft.
[0021] FIG. **15** is a cross sectional view of the mated components shown in FIG. **14**.
[0022] FIG. **16** is an end view of the mated components shown in FIG. **14**.
[0023] FIG. **17** is another perspective view of the second coupler shown in FIG. **13**.
[0024] FIG. **18** is another perspective view of the second coupler shown in FIG. **17** when mated to the first coupler.
[0025] FIG. **19** is a perspective view of another exemplary embodiment of a first coupler for a foundation support system according to the present invention.
[0026] FIG. **20** is a perspective view of another exemplary embodiment of a second coupler for use with the first coupler shown in FIG. **19**.
[0027] FIG. **21** is a perspective assembly view of the first and second couplers shown in FIGS. **19** and **20**.
[0028] FIG. **22** is a side view of the mated first and second couplers shown in FIG. **21**.
[0029] FIG. **23** is an end view of the mated first and second couplers shown in FIG. **21**.
[0030] FIG. **24** is a first perspective assembly view of another embodiment of first and second couplers for a foundation support system according to the present invention.
[0031] FIG. **25** is a second perspective assembly view of the couplers shown in FIG. **24**.
[0032] FIG. **26** is an end view of the mated first and second couplers shown in FIGS. **24** and **25**.
[0033] FIG. **27** is a first perspective assembly view of another embodiment of first and second couplers for a foundation support system according to the present invention.
[0034] FIG. **28** is a second perspective assembly view the couplers shown in FIG. **27**.
[0035] FIG. **29** is an end view of the mated first and second couplers shown in FIGS. **27** and **28**.
[0036] FIG. **30** is a first perspective assembly view of another embodiment of first and second couplers for a foundation support system according to the present invention.
[0037] FIG. **31** is a second perspective assembly view of the first and second couplers shown in FIG. **30**.
[0038] FIG. **32** is an end view of the mated first and second couplers shown in FIGS. **31** and **32**.
[0039] FIG. **33** is a first perspective assembly view of another embodiment of first and second couplers for a foundation support system according to the present invention.
[0040] FIG. **34** is a second perspective assembly view of the first and second couplers shown in FIG. **33**.
[0041] FIG. **35** is an end view of the mated first and second couplers shown in FIGS. **33** and **34**.

DETAILED DESCRIPTION OF THE INVENTION

[0042] In order to understand the inventive concepts described herein to their fullest extent, some discussion of the state of the art and certain problems and disadvantages that exist is set forth below, followed by exemplary embodiments of improved foundation support systems and components therefore which overcome such problems and disadvantages in the art.
[0043] FIG. **1** illustrates a perspective view of a conventional foundation support system **100** in combination with a building foundation **102** which in turn supports a structure in residential, commercial or industrial construction. The structure being supported by the building foundation **102** may include various types of buildings, homes, edifices, etc. in real estate developments and improvements. The foundation support system **100** may be applied in the new construction of the building foundation **102** prior to the structure being completed, or may alternatively be applied for maintenance and repair purposes in a retrofit manner to a pre-existing building foundation at any desired time after the foundation **102** and building structure are initially constructed. While

exemplary structures are mentioned above, the foundation support system **100** may be used in a similar manner to provide foundation support for various different types of structures and to securely support anticipated structural loads without more extensive excavation than standard building foundations otherwise require to provide a similar degree of support.

[0044] Primary piles or pipe shafts (hereinafter collectively referred to as a “pile” or “piles”) **104** of appropriate size and dimension may be selected and may be driven into the ground or earth at a location proximate or near the foundation **102** using known methods and techniques. The size of the primary pile **104** and the insertion depth needed to provide the desired support may be determined according to known engineering methodology and analysis of the construction site and the particular structure that is to be supported. The primary piles **104** typically consist of a long shaft **106** that is driven into the ground to the desired depth, and a support element such as a plate or bracket (not shown) or a lifting element such as a lifting assembly **108** may be assembled to the shaft **106** proximate the foundation **102**. The shaft **106** of the primary pile **104** may also include one or more lateral projections such as a helical auger **110**. Such helical steel piles **104** are available from, for example, Pier Tech Systems (www.piertech.com) of Chesterfield, Missouri.

[0045] The helical auger **110** may in some embodiments be separately provided from the piling **104** and attached to the piling **104** by welding to a sleeve **112** including the auger **110** provided as a modular element fitting. As such, the sleeve **112** of the modular fitting may be slidably inserted over an end of the shaft **106** of the piling shaft **104** and secured into place with fasteners such as bolts as shown in FIG. 1. In such an embodiment, the sleeve **112** includes one or more pairs of fastener holes or openings for attachment to the piling shaft **106** with the fasteners shown. In the embodiment illustrated there are two pairs of fastener holes formed in the sleeve **112**, which are aligned with corresponding fastener holes in the shaft **106** to accept orthogonally-oriented fasteners and establish a cross-bolt connection between the shaft **106** and the sleeve **112**. To make a primary pile **104** with a particular length one merely slides the sleeve **112** onto a piling shaft **106** of the desired length and affixes the sleeve **112** in place. In the illustrated embodiment, the end of the piling shaft **106** is provided with a beveled tip **114** to better penetrate the ground during installation of the pile **104**. In different embodiments, the tapered tip **114** may be provided on the shaft **106** of the piling **104**, or alternatively, the tip **114** may be a feature of the modular fitting including the sleeve **112** and the auger **110**.

[0046] The lifting assembly **108** may be attached to an upper end of the primary pile **104** after being driven into the ground. If the primary pile **104** is not sufficiently long enough to be driven far enough into the ground to provide the necessary support to the foundation **102**, one or more extension piles **116** can be added to the primary pile **104** to extend its length in the assembly. The lifting assembly **108** may then be attached to one of the extension piles **116**.

[0047] As shown in FIG. 1, the lifting assembly **108** interacts with the foundation **102** to support and lift the building foundation **102**. In a contemplated embodiment, the lifting assembly **108** may include a bracket body **118**, one or more bracket clamps **120** and accompanying fasteners, a slider block **122**, and one or more supporting bolts **124** (comprising allthread rods, for example) and accompanying hardware. In another suitable embodiment the lifting assembly **108** may also include a jack **126** and a jacking block **128**. Suitable lifting assemblies may correspond to those available from Pier Tech Systems (www.piertech.com) of Chesterfield, Missouri, including for example only the TRU-LIFT® bracket of Pier Tech Systems, although other lifting assemblies, lift brackets, and lift components from other providers may likewise be utilized in other embodiments.

[0048] The bracket body **118** in the example shown includes a generally flat lift plate **130**, one or more optional gussets **132**, and a generally cylindrical housing **134**. The lift plate **130** is inserted under and interacts with the foundation or other structure **102** that is to be lifted or supported. The lift plate **130** includes an opening, with which the cylindrical housing **134** is aligned to accommodate one of the primary pile **104** or an extension pile **116**. The housing **134** is generally perpendicular to the surface of lift plate **130** and extends above and below the plane of lift plate

130.

[0049] In the example shown, one or more gussets **132** are attached to the bottom surface of the lift plate **130** as well as to the lower portion of the housing **134** to increase the holding strength of the lift plate **130**. In one embodiment, the gussets **132** are attached to the housing **134** by welding, although other secure means of attachment are encompassed within this invention.

[0050] In the example shown, the bracket clamps **120** include a generally Ω -shaped piece having a center hole at the apex of the " Ω " to accommodate a fastener. The Ω -shaped bracket clamp **120** includes ends **136**, extending laterally, that include openings to accommodate fasteners. The fasteners extending through the openings in the ends **136** are attached to the foundation **102**, while the fastener extending through the center opening at the apex of the " Ω " extends into an opening in the housing **134**. In one embodiment the fastener extending through the center opening in the bracket clamp **120** and into the housing **134** further extends through one of the primary pile **104** or the extension pile **116** and into an opening on the opposite side of the housing **134**, and then anchors into the foundation **102**. In such cases, however, the fastener is not inserted through one of the primary pile **104** or the extension pile **116** until jacking or lifting has been completed, since bracket body **118** must be able to move relative to pile **104** or **116** in order to effect lifting of the foundation **102**.

[0051] In one embodiment, the bracket body **118** is raised by tightening a pair of nuts **138** attached to the top ends of the supporting bolts **124**. The nuts **138** may be tightened simultaneously, or alternatively, in succession in small increments with each step, so that the tension on the bolts **124** is kept roughly equal throughout the lifting process. In another suitable embodiment, the jack **126** is used to lift the bracket body **118**. In this embodiment, longer support bolts **124** are provided and are configured to extend high enough above the slider block **122** to accommodate the jack **126** resting on the slider block **122**, the jacking block **128**, and the nuts **138**.

[0052] When all of the components are in place as shown and sufficiently tightened, the jack **126** (of any type, although a hydraulic jack is preferred) is activated so as to lift the jacking plate **128**. As the jacking plate **128** is lifted, force is transferred from the jacking plate **128** to the support bolts **124** and in turn to the lift plate **130** of the bracket body **118**. When the foundation **102** has been lifted to the desired elevation, the nuts immediately above the slider block **122** (which are raised along with support bolts **124** during jacking) are tightened down, with approximately equal tension placed on each nut. At this point, the jack **126** can then be lowered while the bracket body **118** will be held at the correct elevation by the tightened nuts on the slider block **122**. The jacking block **128** can then be removed and reused. The extra support bolt material above the nuts at the slider block **122** can be removed as well, using conventional cutting techniques.

[0053] The lifting assembly **108** and related methodology is not required in all implementations of the foundation support system **100**. In certain installations, the foundation **102** is desirably supported and held in place but not moved or lifted, and in such installations the lifting assembly shown and described may be replaced by a support plate, support bracket or other element known in the art to hold the foundation **102** in place without lifting it first. Support plates, support brackets, support caps, and or other support components to hold a foundation in place are available from Pier Tech Systems (www.piertech.com) of Chesterfield, Missouri and other providers, any of which may be utilized in other embodiments of the foundation support system.

[0054] As mentioned, it is sometimes necessary to extend the length of a piling by connecting one or more shafts which in combination may provide support that extends deeper into the ground than the shafts individually can otherwise reach. For example, a first helical pier component, referred to as a primary pile, may be driven nearly fully into the ground at the desired location, and a connection component such as an extension pile may then be attached to the end of the primary pile in order to drive the primary pile deeper into the ground while supporting the building foundation at an end of the extension pile. More than one extension pile may be required depending on the lengths of the piles available and/or particular soil conditions.

[0055] However, attaching an extension pile to a primary pile to increase the length of the completed piling needed for the job can, be challenging. In conventional foundation support systems, including but not limited to the example shown in FIG. 1, the connection between the primary pile and extension pile is typically made via one or more bolts inserted through fastener holes in the ends of the primary pile and the extension pile. Conventionally, such fastener holes in some cases may be drilled on site as needed, or may be pre-formed in respective couplers that are attached to the primary pile and the extension pile. In either case, because the extension piece may be many feet long and is rather heavy, completing the desired connection to the primary pile with bolts presents a number of complications to an efficient and proper installation of the foundation support system.

[0056] As an initial matter, the primary pile and the extension pile must be properly aligned with one another so that the bolts can be inserted, and the bolts must then be tightened while the proper alignment is maintained. If the fastener holes to make the connections are not properly formed or are not properly aligned, difficulties in inserting the bolts are realized, especially so when the fastener holes are threaded and require precise and nearly exact alignment in order to install the bolts. Some trial and error positioning and repositioning of the extension pile is therefore typically required to align the primary pile and the extension pile so that the bolts can be installed, increasing the time and labor costs required to install a piling including the primary pile and the extension pile. When more than one extension pile is needed, such difficulties may be repetitively incurred with each extension pile and will cumulatively increase the time and labor costs required to install the foundation support system. Indeed, in some cases, installers may spend more time installing the bolts than driving the piles into the ground. Also, the difficulty incurred in aligning an extension pile to make the bolted connection to the primary pile can result in a bolted connection being completed, but in a suboptimal manner that can be compromise the integrity of the support system to provide the proper level of support and undesirably affect the support system capacity and reliability.

[0057] For example, the fastener holes may elongate or otherwise deform, or the bolts can be damaged, via any attempt to force-fit the bolts when difficulties are encountered or when subsequent torque is applied to drive the piling further into the ground. Any such damage or deformation of fastener holes can reduce the structural strength or capacity of the foundation support system. Likewise, the bolts may not be properly loaded if they are not installed as intended (e.g., if the bolts are installed at unintended angles), which can cause overstress and deformation of the fastener holes when subjected to torsional forces to drive the extension pile and primary pile into the ground.

[0058] Any deformation of the fastener holes, or misalignment of the bolts, may further cause a possibility of the joined ends of the primary pile and the extension pile to move relative to one another. Such relative movement is sometimes referred to herein as “play”, and is inherently undesirable and detrimental to the intended support for the foundation that the piling is supposed to present. Any play in the components during assembly may also introduce additional alignment difficulties and complications in completing a proper installation of the foundation system altogether, and may undesirably increase time and labor costs to complete the installation of the foundation support system.

[0059] More recent foundation support systems and components therefor have been developed to reduce the difficulties of interconnecting the foundation support components in the installation of a foundation support system, including but not necessarily limited to a primary pile and an extension pile. For example, patented, self-aligning coupler assemblies are available from Pier Tech Systems (www.piertech.com) of Chesterfield, Missouri that have greatly reduced the difficulties in establishing bolted connections in an installation of a foundation support system. See, e.g., U.S. Pat. Nos. 9,506,214; 9,863,114; and 10,294,623. The patented Pier Tech couplers include elongated axially extending ribs and elongated axially extending grooves that are mated to one another to

establish torque transmitting connections therebetween, with self-alignment of the fastener holes as the couplers are mated to more easily complete the desired bolted connections. The bolts are also mechanically isolated in the patented Pier Tech couplers from torque transmission forces both for ease of installation and to prevent deformation of the fastener holes. Simpler, easier and more reliable installation of foundation support systems is therefore possible with the patented Pier Tech couplers, but further room for improvement exists.

[0060] For example, the bolts utilized to complete the foundation support connections with the desired strength are relatively large and expensive items which not only add to the cost of providing and installing foundation support systems, but introduce opportunity for installation error and complications apart from the alignment issues discussed above. For instance, if the bolts are improperly tightened (e.g., too loose or too tight) unintended results and effects may be realized that would desirably be avoided. Likewise, if the bolts are damaged or stripped either prior to or in the course of installation of a foundation support system, undesirable time and labor will be incurred to attend to such issues.

[0061] Finally, the bolts may be dropped, temporarily mislaid, or even lost in transit to a job site or in the course of any given installation of a foundation support system. Any damaged, dropped, mislaid or lost bolts introduces undesirable delays and increased labor costs to find them, repair them or locate replacement bolts, which may or may not readily be available on the job site. Even when no bolts are damaged, mislaid or lost, and when the alignment issues are resolved to complete the necessary connections of primary piles and extension piles, the time required to completely install all of the bolts required to complete the installation of any given foundation support system can still be undesirably high and therefore costly from a labor perspective. Especially when considered over the course of a number of pilings needed on the same or different job sites, accrued installation time to complete bolted connections can be substantial and significantly add to the costs of installing foundation support systems.

[0062] The patented Pier Tech couplers discussed above do not necessarily require bolted connections to complete an installation of a foundation support system and therefore present a partial solution to the problems above. When mated, the patented Pier Tech couplers are interlocked in the circumferential direction and are therefore fully capable of transmitting torque between them to drive the primary and extension piles into the ground, whether or not they are bolted together. The patented Pier Tech couplers, however, will not be positively interlocked or fastened to one another in the axial direction in the absence of separately provided bolts. As such, when the bolts are not utilized the couplers may be subject to an inadvertent separation when subjected to uplift forces that would tend to pull the couplers apart, potentially compromising the entire foundation support system.

[0063] Axially directed uplift forces on the pilings may be caused by wind and other conditions that are somewhat unpredictable and therefore can arise unexpectedly. Any separation of the couplers due to uplift forces that occur below ground would be very difficult to detect or correct. Therefore, while simply not utilizing the bolts would simplify the assembly and installation of a foundation support system including the patented Pier Tech couplers, this is not an entirely satisfactory solution.

[0064] Foundation support systems are also known including coupler features that are designed to be freely attachable and detachable to one another without utilizing separately provided fasteners such as bolts. For example, U.S. Patent Application Publication No. 2004/0076479 teaches a coupler arrangement including a socket and a spigot having respective axially and circumferentially oriented recesses and axially and circumferentially oriented protuberances that engage with another via an initial axial mating of the socket and spigot, followed by a rotation to interlockingly transmit forward and reverse drive of torque in respectively different orientations of the recesses and protuberances. When rotated circumferentially to an intermediate position between the rotationally interlocked positions, however, the couplers are freely detachable in the axial direction. Since there

is no positive locking to prevent relative rotation of the couplers, however, the couplers may be inadvertently rotated to the intermediate position and possibly detached in the course of installation, or subject to separation due to uplift forces at a location below ground that would be very difficult to detect or correct. Therefore, while such couplers avoid bolted connections, they are not an entirely satisfactory solution.

[0065] For the reasons above, existing foundation support systems continue to be disadvantaged, and the needs of the marketplace have yet to be fully met. Foundation support systems that may be more quickly and easily installed with improved reliability are therefore desired to meet longstanding and unfulfilled needs in the art, especially from the perspective of the couplings needed to interconnect the support piles.

[0066] Exemplary embodiments of inventive coupler components and component assemblies to attach structural shaft elements such as a primary pile and an extension pile to one another in the installation of a foundation support system are described hereinbelow that address and overcome the deficiencies of existing foundation support systems in the aspects described above. Inventive methods of assembling, connecting installing and supporting building foundation elements are also described hereinbelow that address the problems and disadvantages in the art as discussed above.

[0067] More specifically, an interlocking self-aligning and torque transmitting coupler assembly of the present invention facilitates a simplified alignment and interlocking connection between, for example, a primary pile and an extension pile during assembly and installation of a building foundation support system. The interconnection is realized via first and second couplers that are designed for snap-lock engagement to one another which avoids any need for separately provided fasteners such as bolts, and therefore avoids the difficulties that such separately provided fasteners present, while importantly providing a positive interlock not only in the rotational direction to transmit torque as pilings are driven into the ground, but also in the axial direction to avoid any tendency of the couplers to separate when uplift forces exist.

[0068] In a contemplated embodiment the axial interlocking is realized via a retaining spring element that is integrated or built-in to the design of one of the first and second couplers instead of being separately provided and assembled to the coupler for installation. The retaining spring element automatically snaps into place and interlocks the couplers in the axial direction when the couplers are sufficiently engaged to a predetermined amount or degree. When desired, a tool may be used to dislodge the retaining spring element and separate the couplers as desired or as needed. Beneficially, the retaining spring element is intended to be permanently attached to one of the couplers and its automatic engagement to the second coupler as the couplers are mated to one another requires no separate action by the installer to establish the desired axial interlock in the connection established through the couplers. Specifically, and unlike separately provided fasteners in conventional foundation support systems, the built-in spring retainer element is less susceptible to being mislaid, lost, or damaged before, during or after any effort to install the foundation support system.

[0069] Also, in one example each of the first and second couplers features a plurality of helically extending ribs or grooves on the respective inner and outer surfaces thereof, which when engaged to one another provide a rotationally interlocked, torque transmitting connection as the pilings are driven into the ground, but the helical ribs and grooves also provide some degree of axial interlocking to more evenly distribute uplift forces in the mating surface of the couplers. As such, axially directed uplift forces are not borne solely on the retaining spring element, and a comparatively smaller and lower cost retaining spring element may be utilized that is easier to snap or un-snap with a reduced amount of force than would otherwise be required to engage or disengage a larger, stronger and more expensive retaining spring element. The helically extending ribs or grooves may be formed and shaped with ramp features that gradually cause an annular retaining spring element to expand or enlarge its diameter as the ribs and grooves are received and mated with one another. Circumferential retaining spaces such as grooves are also formed in each

of the couplers, defining a space for the retaining spring element to reside and snap-lock into place and achieve the desired axial interlocking.

[0070] The helically extending ribs and grooves, coupled with tapered ends on the inner and outer surface realize a mostly self-guided engagement of ribs and grooves provided on the couplers, avoiding any need by an installer to precisely align the couplers to complete the connections. By partially mating the couplers and rotating one of the couplers about an axis of the coupler (corresponding to a longitudinal axis of a pile attached to the coupler), the helically ribs and grooves will engage via gravitational force with both vertical and rotational displacement. A pitch of the helically extending ribs or grooves is large such the couplers may be fully engaged, for example, with only about $\frac{1}{4}$ turn about the axis of the coupler, allowing quick and easy snap-lock connection that requires no bolts to complete.

[0071] By avoiding bolts and the issues presented by bolts, adequate lifting strength and support is reliably established with a much simpler installation that may be completed in significantly less time than a typical installation of an existing foundation support system requiring bolted connections that are considerably more difficult to complete to attach support piles to one another. By virtue of the inventive couplers of the present invention, improved foundation support elements may therefore be assembled more quickly and more reliably than before, while beneficially reducing labor costs and simultaneously improving system reliability. Method aspects of the inventive concepts will be in part apparent and in part explicitly discussed in the following description.

[0072] Referring now to FIGS. 2-18, exemplary embodiments of snap-lock couplers for foundation support shafts such as primary piles and extension piles according to the present invention include a first or male coupler **200** attachable to a first pile **202** (FIGS. 2-7) and a second or female coupler **250** attachable to a second pile **252** (FIGS. 8-13). The couplers **200**, **250** may be utilized in lieu of the couplers designed for bolted connections in a foundation support system like the system **100** described above to provide the desired support to a building foundation, but with a much simpler, quicker and more reliable installation.

[0073] In contemplated embodiments, the first and second piles **202**, **252** may be a primary pile and an extension pile, or alternatively may be two extension piles of the same or different length. The couplers **200**, **250** may be separately manufactured from the piles **202**, **252** in certain embodiments, and thereafter attached to each pile **250**, **252** in a known manner, including but not necessarily limited to welding. Alternatively, the couplers **200**, **250** may be integrally formed on respective ends of the piles **202**, **252** via casting, forging and swaging processes instead of separately provided and attached elements. The couplers **200**, **250** and the piles **202**, **252** may each be fabricated from high strength steel or another suitable material according to known techniques.

[0074] As shown in FIGS. 2-6, the first coupler **200** is generally cylindrical and hollow, and is formed to include a generally round and larger diameter pile receiving end **204** that receives an end of the pile **202**. In a contemplated embodiment, the pile **202** is an elongated, hollow, and round shaft having an outer diameter of 2.875 inches that fits snugly in the pile receiving end **204** up to a short distance before reaching a smaller diameter stop **206** formed in the coupler **200**. Greater or lesser outer diameters of pile shafts may be accommodated in other embodiments, however. The coupler **200** also includes a relatively smaller diameter round main body **208** extending from the pile receiving end **204**, and a tapered distal end **210** extending from the main body **208** opposite the pile receiving end **204**.

[0075] The main body **208** is formed with a number of outwardly projecting spaced apart and helically extending ribs **212** as best shown in FIGS. 2, 3, 5 and 7. In the example shown, four helical ribs **212** are provided that are spaced about 90° apart from one another on the round main body **208**. The helical ribs **212** extend upon the outer surface of the main body with a relatively large pitch (i.e., the end-to-end vertical rise of the helical ribs in FIG. 3 is large compared to the angular path of the helical ribs in the radial or circumferential direction). In the illustrated example,

the pitch of the helical ribs **212** is such that, from the base of the pile receiving end **204** to the distal end of each rib **212**, about a quarter turn of a helix is completed. The helical ribs **212** extend as thread-like members on the outer surface of the main body **208**, but are specifically distinguished from a more conventional threaded connection including small pitch helical threads that define multiple turns of a helix. While a specific geometry and a specific number of helical ribs **212** is shown and described, it is appreciated that alternative numbers and/or alternative geometries of ribs **212** is possible in another embodiment as demonstrated by the further examples of the couplers shown and described below in relation to FIGS. **19-23**.

[0076] As best seen in FIG. **3**, each helical rib **212** further includes a ramp **214** on exterior surface thereof. The ramp **214** has a variable but increasing outer diameter relative to a distal end portion of the rib **212** having a smaller but constant outer diameter. A shoulder **216** is located adjacent the ramp **214** in each rib **212**, and a retaining groove **218** is located adjacent the shoulder in each of the ribs **212**. A larger diameter retaining shoulder **220** extends on the other side of the retaining groove **218** in each rib **212** adjacent the pile receiving end **204**. The diameter of the retaining shoulder is just a bit larger than the diameter of the pile receiving end **204** in the example shown, although variations are possible.

[0077] As shown in FIGS. **7-13**, the second coupler **250** is also generally cylindrical and is formed to include an open pile receiving end **254** that receives an end of the pile **252**. In a contemplated embodiment, the pile **252** is a hollow round shaft having an outer diameter of 2.875 inches that fits snugly in the pile receiving end **254** up to a short distance before reaching a smaller diameter stop **256** formed in the coupler **250**. Greater or lesser outer diameters of shafts may be accommodated in other embodiments, however. The coupler **250** further includes a smaller diameter, hollow and round main body **258** extending from the pile receiving end **254**.

[0078] The main body **258** is formed with central passageway or bore having an inner surface with an inner diameter about equal to, but slightly larger than the outer diameter of the main body **208** of the coupler **200**. A tapered end **260** is formed in the coupler **250** that extends at a distance from an open distal end **264**. The inner surface of the main body **258** is formed with a number of inwardly depending, spaced apart helically extending grooves **262**. In the example shown, four helical grooves **262** are provided that are spaced about 90° apart from one another on the inner surface of the main body **258**. The helical grooves **262** have a complementary size and shape to the helical ribs **212** of the coupler **200**, and the helical grooves therefore also have large pitch that is equal to the pitch of the ribs **212** on the coupler **200**, such that from a base of the open distal end **264** to the distal end of each groove **262** about a quarter turn of a helix is completed in each groove. The helical grooves **262** extend as thread-like members on the inner surface of the main body **258**. While a specific geometry and specific number of helical grooves is shown and described, it is appreciated that alternative numbers and/or alternative geometries of grooves **262** is possible with otherwise similar benefits in other embodiments.

[0079] As best seen in FIG. **10**, the coupler **250** also includes a circumferential retaining groove **266** formed in its outer surface adjacent the distal end **264**. The retaining groove **266** is interrupted at the locations of the helical grooves **262**. An annular spring retainer element **270** (FIGS. **14, 15, 16, 17**) is received in and extend around the retaining groove **266** of the coupler **250**, and extends across the retaining grooves **266**. The spring retainer element **270** also extends around the circumference of the retaining groove **266** for a radial distance less than 360° in the example shown, and is generally planar in shape rather than helical in shape as a conventional spring would be. While one spring retainer element **270** is shown, more than one spring element could be provided with otherwise similar function and effect.

[0080] The spring retainer element **270** in a contemplated embodiment may be fabricated from a resiliently deflectable metal material, metal alloy or another suitable material allowing the spring retainer element **270** to elastically expand in the radial dimension from an initial diameter to a larger diameter when subjected to an outwardly directed force, and return to its initial diameter

when the force outwardly directed force is removed. In some embodiments, the spring retainer element **270** may likewise grip the circumference of the retaining groove **266** with a predetermined amount of force in the initial position. Beneficially, the spring element **270** is permanently attached to the coupler **250** (i.e., the spring retainer element **270** is not intended to be removed) and is therefore integrated into the coupler design. This allows the coupler **250** to be provided to the installer with the spring retainer element **270** already in place, eliminating any need for an installer to locate a separately provided fastener (or fasteners) including but not necessarily limited to conventional bolts to attach piles to one another in conventional foundation support systems. Also, the spring retainer element **270** is pre-aligned in the retaining groove **266** such that the installer need not be concerned with the orientation of the spring retainer element **270** when assembling and installing the foundation support system.

[0081] As illustrated in FIGS. **14-16**, the spring retainer element **270** is resiliently deflectable in the radial direction when engaged by the ramps **214** in the ribs **212** of the coupler **200** as the ribs and the grooves in the couplers **250**, **200** are engaged. The engagement of the ribs and the grooves may be simply made via partial insertion of the coupler **200** into the coupler **250** (or via partly inserting the coupler **250** over the coupler **200**). After such partial engagement, the coupler that is partially inserted may be simply rotated relative to the other coupler that is fixed in place on the end of a pile that has been driven into the ground until the ribs fall into the grooves or until the grooves fall over the ribs, at which point the coupler being inserted will fall into engagement via gravitational force until the tapered ends **210**, **260** seat or engage one another. Because the ribs and grooves are helical, vertical and rotational displacement of the coupler being inserted will occur relative to the other stationary coupler as the assembly is completed. Engagement of the tapered ends **210**, **260** beneficially reduces “play” in the connection that may otherwise result. Reduction or elimination of play in the joint in turn tightens the joint to beneficially increase the rotational stiffness and reduce stress in the assembly.

[0082] Initially, the smaller outer diameter of the ribs **212** will pass by and through the spring retainer element **270**. As the ribs and grooves are more fully received to complete the mating of the couplers **200**, **250**, the ramps **214** in the ribs make contact with the spring retainer element **270** and gradually enlarge and expand the diameter of the spring retainer element **270** as the ribs **212** continue to descend into the grooves **262** or vice versa. Given that the example couplers illustrated involve four ribs **212** being received in four grooves **262**, the diameter of the spring retainer element **270** is enlarged at four locations to evenly expand the diameter of the spring element around the circumference of each of the couplers. The expansion of the spring retainer element **270** by the ribs **212** is further assisted by the combination of vertical and rotational movement of the ramps **214** as they make contact with the spring retainer element **270**.

[0083] Once the expanded spring retainer element **270** clears the shoulder **216** in the ribs **212**, the circumferential retaining grooves **218** in the ribs **212** of the coupler **200** now align with the retaining groove **266** of the coupler **250**. The ribs **212** no longer contact the spring retainer element **270** as expanded, and the spring retainer element **270** now freely and resiliently returns back to a reduced diameter within the confines of the aligned retaining grooves **218** and **266** in the respective couplers **200**, **250**. Snap-action engagement is therefore accomplished via the self-alignment of the couplers **200**, **250** and gravitational forces acting upon the spring retainer element **270** until the alignment of the retaining grooves **218** and **266** is obtained, wherein the spring retainer element **270** automatically engages and snaps into place without the installer having to take any specific action to complete the connection with a fastener such as a bolt.

[0084] Once engaged, the spring retainer element **270** provides an axial interlock of the engaged couplers **200**, **250** while the ribs and grooves simultaneously provide both axial and rotational interlock of the couplers **200**, **250**. Because the helical ribs and grooves distribute any uplift forces in the mated outer and inner surfaces of the couplers, the spring retainer element **270** may be smaller and lighter than it otherwise may need to be if it exclusively bore all of the uplift forces that

may be presented. The mated helical ribs **212** and grooves **262** in the couplers **200**, **250** also provide secure rotational interlock to transmit torque in either direction (forward or reverse) to drive a piling deeper into the ground or to partially or completely withdraw it from the ground, without requiring a separately fastener such as a bolt to complete the torque transmitting connection.

[0085] If and when desired, a tool or tools such as a screwdriver(s) may be used to pry the spring retainer element **270** open (i.e., enlarge its diameter) until it clears the shoulders **216** in the ribs and therefore allow the ribs **212** to disengage from the grooves **262** and the couplers **200**, **250** to be separated from one another in the axial direction. In certain contemplated embodiments, a custom-fabricated tool may be supplied to disengage the snap-lock spring element in an easier manner when desired.

[0086] When mated together as described the couplers **200**, **250** may rather simply slidably engage one another in a manner that does not require precise positioning for an installed to complete the connection with a separately provided fastener. That is, for the exemplary embodiments illustrated, one of the couplers **200**, **250** positioned above the other may be partly inserted into the other (or over the other) and gently rotated until the ribs **212** and grooves **262** become aligned with one another. Thereafter, the coupler positioned above will rather naturally fall into place as the ribs and grooves receive one another with slidable movement occurring simultaneously in each of the axial and rotational directions.

[0087] The snap-lock connection, via the retaining spring element **270**, is automatically established once the couplers **200**, **250** reach a predetermined amount or degree of engagement determined by the positions of the ramps **214** and the clearance shoulders **216**, and also by the locations of the retaining grooves **218**, **266** in the couplers **200**, **250**. Such locations are predetermined so that the retaining spring retainer element **270** snaps into place just after, or at about the same time, as the ribs **212** and grooves **262** become fully engaged. The spring element **270**, once engaged in the retaining grooves **218**, **266**, establishes a positive interlocking engagement in combination with the ribs **212** and grooves **262** of the couplers **200**, **250** in rotational and axial directions. As used herein, the axial direction refers to a direction that is parallel to an axial centerline of the couplers **200**, **250** (e.g., a vertical centerline in the views of FIGS. 3, 4, 9 and 10 as drawn), while the rotational direction refers to a simple rotation or spinning about the axial centerline of the couplers while the axial centerline itself remains in place. The axial centerline of each coupler, in turn, coincides with a longitudinal axis of the respective piles **202**, **252** being connected.

[0088] In one example embodiment, the first coupler **200** is attached to a first pile (either a primary pile or an extension pile) that has been driven into the ground and is therefore fixed in position at a location just above the surface of the ground, and the second coupler **250** is attached to a second pile (an extension pile) that is to be connected to the first pile. In another embodiment, however, the second coupler **250** is attached to a first pile (either a primary pile or an extension pile) that has been driven into the ground and is therefore fixed in position at a location just above the surface of the ground, and the first coupler **200** is attached to a pile (an extension pile) that is to be connected to the first pile. Either way, the couplers **200**, **250** provide positive interlocking in the rotational direction to transmit torque between the couplers **200**, **250** to drive the first and second piles **202**, **252** into the ground, while positive locking in the axial interlocking afforded by the retaining spring element **270** distributes uplift forces whenever present and ensures that the couplers **200**, **250** remain engaged at all times.

[0089] Via the couplers **200**, **250**, neither fastener holes nor bolts are required to complete the connections of the piles **202**, **252** and the drawbacks of conventional bolts and fastener holes are avoided while otherwise providing a highly reliable foundation support system. Additionally, through-holes need not be formed in the couplers **200**, **250** to receive fasteners such as bolts, and the manufacture of the couplers **200**, **250** may accordingly be simplified. Difficulties and reliability issues associated with through-holes are avoided. Expenses of threaded fasteners and/or threaded

fastener holes are likewise avoided, as are installation difficulties presented by threaded fasteners or holes.

[0090] While exemplary embodiments of couplers **200**, **250** are illustrated and described, numerous variations are possible. For example, instead of outwardly depending ribs projecting from an outer surface in one coupler and inwardly depending grooves extending on an inner surface of the other coupler, contemplated embodiments could instead include grooves extending on an outward surface on one coupler and projecting ribs extending from an inner surface of the other coupler. Likewise, each of the couplers could include a combination of ribs and grooves to be mated within complementary ribs and grooves in the other coupler, instead of only ribs being provided in one coupler and only grooves being provided in the other.

[0091] While helical ribs and grooves in the couplers **200**, **250** are beneficial for the reasons stated, the snap-lock action could be realized with ribs and grooves that are not helical. So long as the ramps are provided to engage the retaining spring retainer element **270** and so long as retaining grooves **218**, **266** are provided in each coupler, the snap-lock engagement can be obtained regardless of the actual shape of the ribs or grooves. Likewise, ramps or other features serving to extend the diameter of the spring element and/or the retaining grooves could be employed on portions of the couplers other than the ribs as described above in relation to the coupler **200**. It is recognized that similar snap-lock functionality may be achieved in different portions of the couplers and the examples shown and described are set forth for illustration rather than limitation.

[0092] The couplers **200**, **250** in different embodiments may be separately provided and attached to primary piles or extension piles, or in other cases may be integrally formed with the piles themselves via, for example only, casting, swaging or forging processes. In some cases, couplers **200** and **250** may be pre-attached to both ends of the same pile or otherwise formed on the opposing ends of the same pile, or alternatively only one coupler may be provided only on one end of a pile.

[0093] The cross-sectional shape of the piles attachable through the couplers **200**, **250** can be circular, square, hexagonal, or another shape as desired via modification of the pile receiving openings on the ends of the couplers **200**, **250**. Likewise, couplers **200**, **250** can be adapted for use to attach one type of pile (e.g., having a round cross section) to another type of pile having a different cross section (e.g., square). Likewise, piles of different diameters can be coupled through the couplers **200**, **250** when the couplers are adapted to receive the piles of each diameter.

[0094] The piles **202**, **252** can be made to different lengths as the application requires, or provided as modular sets of shafts having predetermined lengths that can be assembled to create a piling including coupled shafts of any desired length. Such shafts of different lengths may be prefabricated to include the couplers **200**, **250** such that the modular shafts can be mixed and matched on site as needs dictate, avoiding otherwise custom fabrication of shafts to non-standard lengths that has conventionally been employed.

[0095] The piles connected through the couplers **200**, **250** can be hollow or filled with a substance such as concrete, chemical grout, or another known suitable cementitious material or substance familiar to those in the art to enhance the structural strength and capacity of the pilings in use. The pilings may be prefilled with cementitious material in certain contemplated embodiments.

[0096] Likewise, in other contemplated embodiments, cementitious material, including but not necessarily limited to grout material familiar to those in the art, may be mixed into the soil around the piles as they are being driven into the ground, creating a column of cementitious material around the pilings for further structural strength and capacity to support a building foundation. Grout and cementitious material may be pumped through the hollow pilings under pressure as the pilings are advanced into the ground, causing the hollow pilings to fill with grout, some of which is released exterior to the pilings to mix with the soil at the installation site. Openings and the like can be formed in the piles to direct a flow of cementitious material through the piles and at selected locations into the surrounding soil.

[0097] The couplers **200**, **250** may facilitate a modular assembly of piles as well as other components in a foundation support system (e.g., helical auger elements, tapered ends or cutting ends, lift brackets, support brackets, support caps, and drive elements for coupling to machinery utilized to generate the torque to drive the pilings into the ground) that are provided with complementary ribs or grooves to quickly complete connections in the installation of a foundation support system. Also, various sizes of couplers **200**, **250** may be provided to attach foundation support system components other than primary pile and extension piles as needed or desired. Different versions of couplers and components can be provided in kit form for selective use by an installer to create a number of different variations of foundation support systems using a relatively small number of modular parts.

[0098] While described in the context of foundation support systems and support piles therefore, it is recognized that the couplers **200**, **250** may be utilized to connect other structural shaft elements in another application apart from foundation support that presents similar issues and/or that would confer similar benefits. The foregoing description is therefore provided for the sake of illustration rather than limitation. That is, the shafts being connected with the couplers **200**, **250** need not be shafts of piles or piers or any of the components shown and described in the foundation support system described above, but instead the shafts may be other structural elements for other purposes. Provided that the ends of the structural elements being connected are shaped to complement the features of the couplers **200**, **250** the structural elements need not even necessarily be shafts.

[0099] FIGS. **19-23** illustrate another embodiment of a snap-lock coupler assembly **300** that may be used in lieu of or in addition to the coupler assembly including the couplers **200**, **250** described and illustrated in FIGS. **1-18** in a foundation support system. The coupler assembly **300** provides at least some of the same benefits to those described above but with different torque transmitting features.

[0100] As shown, the coupler assembly **300** (FIGS. **21-23**) includes a first coupler **302** (FIG. **19**) and a second coupler **304** (FIG. **20**). Each of the first and second couplers **302**, **304** are attachable to foundation support elements such as primary piles and extension piles as described above. Following the above example, the coupler **302**, sometimes referred to as a male coupler, is attachable to the first pile **202** (FIGS. **2-7**) and the second coupler **304**, sometimes referred to as a female coupler, is attachable to a second pile **252** (FIGS. **8-13**). The couplers **302**, **304** may be separately manufactured from the piles **202**, **252** in certain embodiments, and thereafter attached to each pile **202**, **252** in a known manner, including but not necessarily limited to welding.

Alternatively, the couplers **302**, **304** may be integrally formed on respective ends of the piles **202**, **252** via casting, forging and swaging processes instead of separately provided and attached elements. The couplers **200**, **250** and the piles **202**, **252** may each be fabricated from high strength steel or another suitable material according to known techniques. Like the couplers **200**, **250** the couplers **302**, **304** may be utilized in lieu of conventional couplers designed for bolted connections to piles in a foundation support system like the system **100** described above to provide the desired support to a building foundation, but with a much simpler, quicker and more reliable installation.

[0101] The first coupler **302** (FIGS. **19**, **21** and **22**) includes a hollow, cylindrical and rounded main body **306** that is formed with a number of outwardly projecting spaced apart and longitudinally extending ribs **308a**, **308b** and **308c**. In the example shown, three generally elongated, linearly extending ribs **308**, **308b** and **308c** are provided that extend axially on the main body **306** and are spaced unevenly apart from one another on the rounded main body **306**. Unlike the helical ribs described above in the couplers **200**, **250**, the linearly extending ribs **308a**, **308b**, **308c** have no pitch and therefore do not extend as thread-like members on the outer surface of the main body **306**.

[0102] In the example shown, and as best seen in FIGS. **19** and **21**, the ribs **308b** and **308c** on the main body **306** of the coupler **302** are relatively close to one another while also being spaced from the rib **308a** by a relatively large amount on the circumference of the main body **306**. The main

body **306** is also tapered in the axial direction such that its outer circumference gradually decreases along the axial centerline of the main body **306** toward its distal end that is slidably inserted into the second coupler **304** as shown in FIGS. **21** and **22**. The ribs **308a**, **308b** and **308c** are also tapered in the widthwise direction such that the width of the ribs gradually decreases along the axial centerline of each rib **308a**, **308b** and **308c** toward the distal open end of the first coupler **302** that is slidably inserted into the second coupler **304** as shown in FIGS. **21** and **22**.

[0103] The second coupler **304** is also formed to include a hollow, cylindrical and round main body **310**. The main body **310** is formed with a central passageway or bore **312** having an inner surface with an inner diameter about equal to, but slightly larger than the outer diameter of the main body **306** of the coupler **302**. The inner surface is formed with a number of inwardly depending, spaced apart linearly extending grooves **314a**, **314b**, **314c** having a complementary size and shape to the ribs **308a**, **308b** and **308c** of the first coupler **302**. The main body **310** and grooves **314a**, **314b**, **314c** are tapered to receive the main body **306** and the ribs **308a**, **308b** and **308c** as the couplers are mated as shown in FIGS. **21** and **22**. The axial tapering of each coupler **302**, **304** allows the couplers to be easily mated with one another in a self-aligning manner via initial insertion of the smaller diameter distal end of the coupler **302** into the larger diameter distal end of the coupler **304** with the ribs and grooves more gradually mating with one another as the couplers are more fully mated, culminating in a snug engagement when the couplers are fully mated.

[0104] The coupler **304** also includes a circumferential retaining groove **316** formed in its outer surface, and the annular spring retainer element **270** is received in and extends around the retaining groove **316** of the coupler **304**. The spring retainer element **270** is permanently attached to the coupler **304** (i.e., the spring retainer element **270** is not intended to be removed from the coupler **304**) and is therefore integrated into the coupler design and provides similar benefits to those described above.

[0105] As the ribs **308a**, **308b** and **308c** are mated with the grooves **314a**, **314b**, **314c** the spring retainer element **270** is eventually engaged by the ribs once the ribs and grooves are engaged to a predetermined degree. Engagement of the ribs to the spring retainer element **270**, in turn, causes a gradual enlargement and expansion of the inner diameter of the spring retainer element **270**. Once the expanded spring retainer element **270** clears the retaining grooves **218** in the ribs **308a**, **308b** and **308c** as the couplers are further mated, the ribs no longer contact the spring retainer element **270** as expanded and the spring retainer element **270** now freely and resiliently returns back to a reduced diameter within the confines of the aligned retaining grooves **218** and **316** in each of the couplers **302**, **304**. An automatic, snap-action engagement of the couplers **302**, **304** is therefore accomplished with benefits similar to that described above. Engagement of the axially tapered main bodies **306**, **310** in the couplers **302**, **304** beneficially reduces “play” in the connection that may otherwise result. Reduction or elimination of play in the joint in turn tightens the joint to beneficially increase the rotational stiffness and reduce stress in the assembly.

[0106] Relative to the couplers **200**, **250** including helical ribs and grooves, the couplers **302**, **304** include simpler shaped ribs and grooves and also a reduced number of ribs and grooves and therefore may be provided at lower cost. Axial interlocking is automatically established by the spring retainer element **270** while rotational interlocking is established via the ribs and grooves in the couplers **302**, **304**. Since axial interlocking is borne by the spring retainer element **270** in this embodiment, a larger and higher cost retaining spring retainer element **270** may be required relative to the couplers **200**, **250**.

[0107] FIGS. **24-26** illustrate another embodiment of a snap-lock coupler assembly **330** that may be used in lieu of or in addition to the coupler assemblies described above in a foundation support system. The coupler assembly **330** provides at least some of the same benefits to those described above but with different torque transmitting features.

[0108] As shown in the figures, the coupler assembly **330** includes a first coupler **332** and a second coupler **334**. Each of the first and second couplers **332**, **334** are attachable to foundation support

elements such as primary piles and extension piles as described above. Following the above example, the coupler **332**, sometimes referred to as a male coupler, is attachable to the first pile **202** (FIGS. 2-7) and the second coupler **334**, sometimes referred to as a female coupler, is attachable to a second pile **252** (FIGS. 8-13). The couplers **332**, **334** may be separately manufactured from the piles **202**, **252** in certain embodiments, and thereafter attached to each pile **202**, **252** in a known manner, including but not necessarily limited to welding. Alternatively, the couplers **332**, **334** may be integrally formed on respective ends of the piles **202**, **252** via casting, forging and swaging processes instead of separately provided and attached elements. The couplers **332**, **354** and the piles **202**, **252** may each be fabricated from high strength steel or another suitable material according to known techniques. Like the couplers **200**, **250** the couplers **332**, **334** may be utilized in lieu of conventional couplers designed for bolted connections to piles in a foundation support system like the system **100** described above to provide the desired support to a building foundation, but with a much simpler, quicker and more reliable installation.

[0109] The first coupler **332** includes a hollow, polygonal (i.e., non-rounded) main body **336** that is formed with a number of outwardly projecting spaced apart and longitudinally extending ribs **338a**, **338b**, **338c**, **338d**, **338e** and **338f** at an end of the main body **336**. The polygonal main body **336** is hexagonal in the example shown (i.e., has six sides) with six truncated axial and linearly extending ribs **338a**, **338b**, **338c**, **338d**, **338e** and **338f** extending over the intersection of each side of the polygonal outer surface. The ribs **338a**, **338b**, **338c**, **338d**, **338e** and **338f** are spaced evenly from one another on the main body **336**. Unlike the helical ribs described above, the linearly extending ribs **338a**, **338b**, **338c**, **338d**, **338e** and **338f** have no pitch and therefore do not extend as thread-like members on the outer surface of the main body **336**. The main body **336** is also tapered such that its outer circumference gradually decreases along the axis of the main body **336** toward its distal open end that is inserted into the second coupler **304** as shown. The tapered main body **336** provides ease of assembly, with the hexagonal sides being self-aligning with mating surfaces of the second coupler **334** while the couplers **332**, **334** are mated.

[0110] The second coupler **334** is formed to include a hollow and round main body **340**. The main body **340** is formed with central passageway or bore **342** having an inner surface with an inner circumference about equal to, but slightly larger than the outer circumference of the main body **336** of the coupler **332**. The inner surface is formed with a hexagonal receiving area and a number of inwardly depending, spaced apart linearly extending grooves **344a**, **344b**, **344c**, **344d**, **344e** and **334f** having a complementary size and shape to the ribs **338a**, **338b**, **338c**, **338d**, **338e** and **338f** of the first coupler **332**.

[0111] The coupler **334** also includes a circumferential retaining groove **346** formed in its outer surface, and the annular spring retainer element **270** is received in and extends around the retaining groove **346** of the coupler **334**. The spring retainer element **270** is permanently attached to the coupler **334** (i.e., the spring retainer element **270** is not intended to be removed from the coupler **334**) and is therefore integrated into the coupler design and provides similar benefits to those described above.

[0112] As the ribs **338a**, **338b**, **338c**, **338d**, **338e** and **338f** are mated with the grooves **344a**, **344b**, **344c**, **344d**, **344e** and **334f** the spring retainer element **270** is eventually engaged by the ribs once a predetermined degree of mating engagement of the couplers **332**, **334** has been accomplished. The engagement of the ribs to the spring retainer element **270** thereafter causes the spring retainer element **270** to gradually enlarge and the inner diameter of the spring retainer element **270** is expanded as the couplers are further engaged to one another. Once the expanded spring retainer element **270** clears the retaining grooves **218** in the ribs **338a**, **338b**, **338c**, **338d**, **338e** and **338f** the ribs no longer contact the spring retainer element **270** as expanded, and the spring retainer element **270** now freely and resiliently returns back to a reduced diameter within the confines of the aligned retaining grooves **218** and **346** in each of the couplers. Automatic, snap-action engagement is therefore accomplished with benefits similar to that described above. Engagement of the tapered

main bodies **336**, **340** in the couplers **332**, **334** beneficially reduces “play” in the connection that may otherwise result. Reduction or elimination of play in the joint in turn tightens the joint to beneficially increase the rotational stiffness and reduce stress in the assembly.

[0113] Relative to the couplers **200**, **250** including helical ribs and grooves, the couplers **302**, **304** include smaller and simpler shaped ribs and grooves, albeit a larger number of ribs and grooves. The hexagonal feature reduces material in the coupler **332** relative to the coupler **250**, but complicates the structure of the coupler **334** relative to the coupler **250**. Axial interlocking is automatically established by the spring retainer element **270** while rotational interlocking is established via the ribs and grooves in the couplers **332**, **334** and also the polygonal surfaces of the mated couplers **332**, **334**. Since axial interlocking is borne by the spring retainer element **270** in this embodiment, a larger and higher cost retaining spring retainer element **270** may be required relative to the couplers **200**, **250**.

[0114] FIGS. **27-29** illustrate another embodiment of a snap-lock coupler assembly **360** that may be used in lieu of or in addition to the coupler assemblies described above in a foundation support system. The coupler assembly **360** provides at least some of the same benefits to those described above but with different torque transmitting features. Like features of the coupler assembly **360** and the previously described coupler assemblies are indicated with like reference characters in FIGS. **27-29**.

[0115] As shown in the figures, the coupler assembly **360** includes a first coupler **362** and a second coupler **364**. Each of the first and second couplers **362**, **364** are attachable to foundation support elements such as primary piles and extension piles as described above. Following the above example, the coupler **362**, sometimes referred to as a male coupler, is attachable to the first pile **202** (FIGS. **2-7**) and the second coupler **364**, sometimes referred to as a female coupler, is attachable to a second pile **252** (FIGS. **8-13**). The couplers **362**, **364** may be separately manufactured from the piles **202**, **252** in certain embodiments, and thereafter attached to each pile **202**, **252** in a known manner, including but not necessarily limited to welding. Alternatively, the couplers **362**, **364** may be integrally formed on respective ends of the piles **202**, **252** via casting, forging and swaging processes instead of separately provided and attached elements. The couplers **362**, **364** and the piles **202**, **252** may each be fabricated from high strength steel or another suitable material according to known techniques. Like the couplers **200**, **250** the couplers **362**, **364** may be utilized in lieu of conventional couplers designed for bolted connections to piles in a foundation support system like the system **100** described above to provide the desired support to a building foundation, but with a much simpler, quicker and more reliable installation.

[0116] The first coupler **362** includes a hollow, polygonal (i.e., non-rounded) main body **366** that is formed with a number of outwardly projecting spaced apart and longitudinally extending ribs **368a**, **368b**, **368c** and **368d** at an end of the main body **366**. The polygonal main body **366** is square in the example shown (i.e., has four sides) with four truncated linearly extending ribs **368a**, **368b**, **368c** and **368d** extending over the intersection of each side of the polygonal outer surface. The ribs **368a**, **368b**, **368c** and **368d** are spaced evenly from one another on the main body **366**. Unlike the helical ribs described above, the linearly extending ribs **368a**, **368b**, **368c**, **368d** have no pitch and therefore do not extend as thread-like members on the outer surface of the main body **366**. The main body **366** is also tapered such that its outer circumference gradually decreases along the axial centerline of the main body **366** toward its distal end that is slidably inserted into the second coupler **364** as shown.

[0117] The second coupler **364** is formed to include a hollow and round main body **370**. The main body **370** is formed with central passageway or bore **372** having an inner surface with an inner circumference about equal to, but slightly larger than the outer circumference of the main body **366** of the coupler **362**. The inner surface is formed with a tapered square receiving surface and a number of inwardly depending, spaced apart linearly extending grooves **374a**, **374b**, **374c** and **374d** having a complementary size and shape to the ribs **368a**, **368b**, **368c** and **368d** of the first coupler

362.

[0118] The coupler **364** also includes a circumferential retaining groove **376** formed in its outer surface, and the annular spring retainer element **270** is received in and extends around the retaining groove **376** of the coupler **364**. The spring retainer element **270** is permanently attached to the coupler **364** (i.e., the spring retainer element **270** is not intended to be removed from the coupler **364**) and is therefore integrated into the coupler design and provides similar benefits to those described above.

[0119] As the ribs **368a**, **368b**, **368c** and **368d** are mated with the grooves **374a**, **374b**, **374c** and **374d** the spring retainer element **270** is eventually engaged by the ribs which gradually enlarge and expand the diameter of the spring retainer element **270**. As the couplers **362**, **364** are further engaged, once the expanded spring retainer element **270** clears the retaining grooves **218** in the ribs **368a**, **368b**, **368c** and **368d** the ribs no longer contact the spring retainer element **270** as expanded, and the spring retainer element **270** now freely and resiliently returns back to a reduced diameter within the confines of the aligned retaining grooves **218** and **376** in each of the couplers.

Automatic, snap-action engagement is therefore accomplished with benefits similar to that described above. Engagement of the tapered main bodies **366**, **370** in the couplers **362**, **364** beneficially reduces “play” in the connection that may otherwise result. Reduction or elimination of play in the joint in turn tightens the joint to beneficially increase the rotational stiffness and reduce stress in the assembly.

[0120] Relative to the couplers **332**, **334** described above, the couplers **362**, **364** are more simply shaped and includes fewer ribs and grooves and therefore may be provided at lower cost with otherwise similar benefits.

[0121] FIGS. **30-32** illustrate another embodiment of a snap-lock coupler assembly **390** that may be used in lieu of or in addition to the coupler assemblies described above in a foundation support system. The coupler assembly **390** provides at least some of the same benefits to those described above but with different torque transmitting features. Like features of the coupler assembly **390** and the previously described coupler assemblies are indicated with like reference characters in FIGS. **30-32**.

[0122] As shown in the figures, the coupler assembly **390** includes a first coupler **392** and a second coupler **394**. Each of the first and second couplers **392**, **394** are attachable to foundation support elements such as primary piles and extension piles as described above. Following the above example, the coupler **392**, sometimes referred to as a male coupler, is attachable to the first pile **202** (FIGS. **2-7**) and the second coupler **394**, sometimes referred to as a female coupler, is attachable to a second pile **252** (FIGS. **8-13**). The couplers **392**, **394** may be separately manufactured from the piles **202**, **252** in certain embodiments, and thereafter attached to each pile **202**, **252** in a known manner, including but not necessarily limited to welding. Alternatively, the couplers **392**, **394** may be integrally formed on respective ends of the piles **202**, **252** via casting, forging and swaging processes instead of separately provided and attached elements. The couplers **392**, **394** and the piles **202**, **252** may each be fabricated from high strength steel or another suitable material according to known techniques. Like the couplers **200**, **250** the couplers **392**, **394** may be utilized in lieu of conventional couplers designed for bolted connections to piles in a foundation support system like the system **100** described above to provide the desired support to a building foundation, but with a much simpler, quicker and more reliable installation.

[0123] The first coupler **392** includes a hollow, cylindrical and rounded main body **396** that is formed with a number of outwardly projecting spaced apart and longitudinally extending ribs **398a** and **398b**. The ribs **398a**, **398b** are spaced evenly from one another on the main body **396**. Unlike the helical ribs described above, the linearly extending ribs **398a**, **398b** have no pitch and therefore do not extend as thread-like members on the outer surface of the main body **396**.

[0124] The second coupler **394** is formed to include a hollow and round main body **400**. The main body **400** is formed with central passageway or bore **402** having an inner surface with an inner

conference about equal to, but slightly larger than the outer circumference of the main body **396** of the coupler **392**. The inner surface is formed with a number of inwardly depending, spaced apart linearly extending grooves **404a** and **404b** having a complementary size and shape to the ribs **398a**, **398b** of the first coupler **392**.

[0125] The coupler **394** also includes a circumferential retaining groove **406** formed in its outer surface, and the annular spring retainer element **270** is received in and extends around the retaining groove **406** of the coupler **394**. The spring retainer element **270** is permanently attached to the coupler **394** (i.e., the spring retainer element **270** is not intended to be removed from the coupler **394**) and is therefore integrated into the coupler design and provides similar benefits to those described above.

[0126] As the ribs **398a**, **398b** are mated with the grooves **404a**, **404b** the spring retainer element **270** is eventually engaged by the ribs which gradually enlarge and expand the diameter of the spring retainer element **270** as the couplers are further mated to one another. Once the expanded spring retainer element **270** clears the retaining grooves **218** in the ribs **398a**, **398b**, the ribs no longer contact the spring retainer element **270** as expanded, and the spring retainer element **270** now freely and resiliently returns back to a reduced diameter within the confines of the aligned retaining grooves **218** and **406** in each of the couplers. Automatic, snap-action engagement is therefore accomplished with benefits similar to that described above.

[0127] Optionally, the main body of each coupler may be axially tapered like some of the couplers described above to beneficially simplify ease of assembly in a self-aligning manner while still reducing “play” in the connection that may otherwise result. Reduction or elimination of play in the joint in turn tightens the joint to beneficially increase the rotational stiffness and reduce stress in the assembly.

[0128] FIGS. **33-35** illustrate another embodiment of a snap-lock coupler assembly **420** that may be used in lieu of or in addition to the coupler assemblies described above in a foundation support system. The coupler assembly **420** provides at least some of the same benefits to those described above but with different torque transmitting features. Like features of the coupler assembly **420** and the previously described coupler assemblies are indicated with like reference characters in FIGS. **33-35**.

[0129] As shown in the figures, the coupler assembly **420** includes a first coupler **422** and a second coupler **424**. Each of the first and second couplers **422**, **424** are attachable to foundation support elements such as primary piles and extension piles as described above. Following the above example, the coupler **422**, sometimes referred to as a male coupler, is attachable to the first pile **202** (FIGS. **2-7**) and the second coupler **424**, sometimes referred to as a female coupler, is attachable to a second pile **252** (FIGS. **8-13**). The couplers **422**, **424** may be separately manufactured from the piles **202**, **252** in certain embodiments, and thereafter attached to each pile **202**, **252** in a known manner, including but not necessarily limited to welding. Alternatively, the couplers **422**, **424** may be integrally formed on respective ends of the piles **202**, **252** via casting, forging and swaging processes instead of separately provided and attached elements. The couplers **422**, **424** and the piles **202**, **252** may each be fabricated from high strength steel or another suitable material according to known techniques. Like the couplers **200**, **250** the couplers **422**, **424** may be utilized in lieu of conventional couplers designed for bolted connections to piles in a foundation support system like the system **100** described above to provide the desired support to a building foundation, but with a much simpler, quicker and more reliable installation.

[0130] The first coupler **422** includes a hollow, rounded main body **426** that is formed with a number of outwardly projecting spaced apart and axially extending ribs **428a**, **428b**, **428c** and **428d**. The ribs **428a**, **428b**, **428c** and **428d** are spaced evenly from one another on the main body **426**. Unlike the helical ribs described above, the linearly extending ribs **428a**, **428b**, **428c** and **428d** have no pitch and therefore do not extend as thread-like members on the outer surface of the main body **426**. The axially extending ribs **428a**, **428b**, **428c** and **428d** are further tapered in the axial

direction as shown.

[0131] The second coupler **424** is formed to include a hollow and round main body **430**. The main body **430** is formed with central passageway or bore **432** having an inner surface with an inner circumference about equal to, but slightly larger than the outer circumference of the main body **426** of the coupler **422**. The inner surface is formed with a number of inwardly depending, spaced apart linearly extending grooves **434a**, **434b**, **434c** and **434b** having a complementary size and shape to the ribs **428a**, **428b**, **428c** and **428b** of the first coupler **422**.

[0132] The coupler **424** also includes a circumferential retaining groove **436** formed in its outer surface, and the annular spring retainer element **270** is received in and extends around the retaining groove **436** of the coupler **324**. The spring retainer element **270** is permanently attached to the coupler **424** (i.e., the spring retainer element **270** is not intended to be removed from the coupler **424**) and is therefore integrated into the coupler design and provides similar benefits to those described above.

[0133] As the ribs **428a**, **428b**, **428c** and **428b** are mated with the grooves **434a**, **434b**, **434c** and **434d** the spring retainer element **270** is eventually engaged by the ribs which gradually enlarge and expand the diameter of the spring retainer element **270**. Once the expanded spring retainer element **270** clears the retaining grooves **218** in the ribs **428a**, **428b**, **428c** and **428b**, the ribs no longer contact the spring retainer element **270** as expanded, and the spring retainer element **270** now freely and resiliently returns back to a reduced diameter within the confines of the aligned retaining grooves **218** and **436** in each of the couplers. Automatic, snap-action engagement is therefore accomplished with benefits similar to that described above. The tapered ribs and grooves of each coupler provide simple and self-alignment of the couplers while beneficially reducing “play” in the connection that may otherwise result. Reduction or elimination of play in the joint in turn tightens the joint to beneficially increase the rotational stiffness and reduce stress in the assembly.

[0134] The couplers shown and described in relation to FIGS. **19-35** may be modified to reverse the arrangement of ribs and grooves on the couplers, or to include combinations of ribs and grooves in each coupler while still realizing similar effects and benefits. While a number of exemplary shapes and geometries are shown in the exemplary couplers described and illustrated, others are still possible while realizing similar effects and advantages.

[0135] It should be realized that aspects of the coupler assemblies described may be combined to provide still further variants of coupler assemblies realizing similar effects and advantages. As one example, the couplers **200**, **250** including the helical ribs and grooves could be provided with axial tapered features in the main bodies and in the ribs and grooves. As another example, the polygonal mating surfaces could be provided without the axial taper in some of the embodiments described. Numerous variations are possible in this regard to realize varying degrees of self-alignment and axial interlocking at various price points.

[0136] It should also be realized that some aspects of the coupler assemblies described may be omitted to produce further variants of couplers at different price points. For example, the automatic snap-lock feature does not necessarily require a self-alignment feature in the couplers, and as such the self-alignment features may be omitted for certain end use of the couplers while still providing the axial interlocking benefits with simplified assembly. Other variations are likewise possible by omitting some of the features described in the exemplary embodiments while otherwise realizing some of the benefits provided by remaining features.

[0137] In some cases, couplers such as those shown in FIGS. **19-35** may be pre-attached to both ends of the same pile or otherwise formed on the opposing ends of the same pile, or alternatively only one coupler may be provided only on one end of a pile. The cross-sectional shape of the piles attachable through the couplers shown in FIGS. **19-35** can be circular, square, hexagonal, or another shape as desired via modification of the pile receiving openings on the ends of the couplers. Likewise, the couplers shown in FIGS. **19-29** can be adapted for use to attach one type of pile (e.g., having a round cross section) to another type of pile having a different cross section (e.g.,

square). Likewise, piles of different diameters can be coupled through the couplers shown in FIGS. **19-35** when the couplers are adapted to receive the piles of each diameter.

[0138] The piles **202**, **252** including couplers as shown in FIGS. **19-35** can be made to different lengths as the application requires, or provided as modular sets of shafts having predetermined lengths that can be assembled to create a piling including coupled shafts of any desired length. Such shafts of different lengths may be prefabricated to include the couplers such that the modular shafts can be mixed and matched on site as needs dictate, avoiding otherwise custom fabrication of shafts to non-standard lengths that has conventionally been employed.

[0139] The piles connected through the couplers shown in FIGS. **19-36** can be hollow or filled with a substance such as concrete, chemical grout, or another known suitable cementitious material or substance familiar to those in the art to enhance the structural strength and capacity of the pilings in use. The pilings may be prefilled with cementitious material in certain contemplated embodiments.

[0140] Likewise, in other contemplated embodiments, cementitious material, including but not necessarily limited to grout material familiar to those in the art, may be mixed into the soil around the piles as they are being driven into the ground, creating a column of cementitious material around the pilings for further structural strength and capacity to support a building foundation. Grout and cementitious material may be pumped through the hollow pilings under pressure as the pilings are advanced into the ground, causing the hollow pilings to fill with grout, some of which is released exterior to the pilings to mix with the soil at the installation site. Openings and the like can be formed in the piles to direct a flow of cementitious material through the piles and at selected locations into the surrounding soil.

[0141] The couplers shown in FIGS. **19-35** may facilitate a modular assembly of piles as well as other components in a foundation support system (e.g., helical auger elements, tapered ends or cutting ends, lift brackets, support brackets, support caps, and drive elements for coupling to machinery utilized to generate the torque to drive the pilings into the ground) that are provided with complementary ribs or grooves to quickly complete connections in the installation of a foundation support system. Also, various sizes of couplers may be provided to attach foundation support system components other than primary pile and extension piles as needed or desired. Different versions of couplers and components can be provided in kit form for selective use by an installer to create a number of different variations of foundation support systems using a relatively small number of modular parts.

[0142] While described in the context of foundation support systems and support piles therefore, it is recognized that the couplers shown in FIGS. **19-35** may be utilized to connect other structural shaft elements in another application apart from foundation support that presents similar issues and/or that would confer similar benefits. The foregoing description is therefore provided for the sake of illustration rather than limitation. That is, the shafts being connected with the couplers shown in FIGS. **19-35** need not be shafts of piles or piers or any of the components shown and described in the foundation support system described above, but instead the shafts may be other structural elements for other purposes. Provided that the ends of the structural elements being connected are shaped to complement the features of the couplers shown in FIGS. **19-35** the structural elements need not even necessarily be shafts. The benefits and advantages of the inventive concepts described herein are now believed to have been amply illustrated in relation to the exemplary embodiments disclosed.

[0143] An embodiment of a foundation support system has been disclosed including a first coupler, a second coupler configured to rotationally interlock with the first coupler, and a spring retainer element configured to automatically engage and axially interlock the first coupler and the second coupler with snap-fit engagement as the first and second couplers are mated. The axial interlock avoids a separation of the first and second couplers at a below ground location due to axially directed uplift forces when the foundation support system is installed in a building site to support the foundation.

[0144] Optionally, each of the first and second couplers may include a plurality of ribs or a plurality of grooves, with the plurality of ribs and the plurality of grooves being rotationally interlocked when the first and second couplers are mated. The plurality of ribs may be respectively formed with a retainer groove, and the retainer groove may receive a portion of the spring retainer element with snap-fit engagement when the first and second couplers are mated. The plurality of ribs or the plurality of grooves may include a plurality of helical ribs or a plurality of helical grooves. Each helical rib or helical groove may complete only about $\frac{1}{4}$ turn on a surface of the respective first or second coupler. The first coupler may include four helical ribs and the second coupler may include four helical grooves.

[0145] As further options, the spring retainer element may be permanently attached to one of the first and second couplers. The spring retainer element may reside within a circumferential groove of one of the first and second couplers. The spring retainer element may be a planar element fabricated from a resiliently deflectable material, and further may be an annular element having an expandable inner diameter.

[0146] As still further options, each of the plurality of ribs may include a first portion having a first outer diameter passing through an initial inner diameter of the spring retainer element when the first and second couplers are partly mated. Each of the plurality of ribs further may also be formed with a ramp at an end of the first portion, and the ramp in each rib may contact the inner diameter of the spring retainer element and expand the initial inner diameter of the spring retainer element to a larger diameter when the first and second couplers are further mated. Each of the plurality of ribs may further be formed with a second portion having a second outer diameter greater than the first outer diameter, the second outer diameter passing through the larger inner diameter of the spring retainer element when the first and second couplers are further mated. Each of the plurality of ribs may also be formed with a retainer groove in the second portion, and the spring retainer element may resiliently return back to the initial diameter in the respective retaining grooves of the plurality of ribs when the first and second couplers are fully mated. As further options, the plurality of ribs or the plurality of grooves may include a plurality of linear ribs or a plurality of linear grooves. The plurality of ribs may include three ribs spaced unevenly from one another. Each of the first coupler and the second coupler may include a main body, with the plurality of ribs or the plurality of grooves extending on the main body of the first coupler and the second coupler. The main body of one of the first coupler and the second coupler may be polygonal, and more specifically may be hexagonal or square. The main body may also be axially tapered, and the ribs or grooves may also be axially tapered.

[0147] The main body of the first coupler and the second coupler may also each be round, and the main body of the first coupler and the second coupler may each be tapered. Alternatively, the main body of the first coupler may be non-round and wherein the main body of the second coupler may be round. The main body of the first coupler may be polygonal, and the ribs may be located at an intersection of each side of the polygonal main body.

[0148] The foundation support system may also include a first pile and a second pile rotationally interlocked to one another through the first and second coupler. One of the first and second piles may include a helical auger. The foundation support system may also include a bracket, a plate, or a lifting assembly for supporting the foundation. The first pile and the second pile may be filled with a cementitious material. Neither of the first or second coupler may include a fastener hole, and the axial interlock may be realized solely by the spring retainer element without any threaded fastener.

[0149] This written description uses examples to disclose the invention, including the best mode, and also to enable any person skilled in the art to practice the invention, including making and using any devices or systems and performing any incorporated methods. The patentable scope of the invention is defined by the claims, and may include other examples that occur to those skilled in the art. Such other examples are intended to be within the scope of the claims if they have structural elements that do not differ from the literal language of the claims, or if they include

equivalent structural elements with insubstantial differences from the literal languages of the claims.

Claims

1. A foundation support system comprising: a first coupler having a first outer circumference and a first inner circumference; a second coupler having a second outer circumference and a second inner circumference; and a resilient spring extending partly on each of the first outer circumference and the second outer circumference, the resilient spring being configured to automatically engage and axially interlock the first and second outer circumferences with snap-fit engagement as the first and second couplers are mated; wherein the axial interlock avoids a separation of the first and second couplers at a below ground location due to axially directed uplift forces when the foundation support system is installed in a building site to support the foundation.
2. The foundation support system of claim 1, wherein each of the first and second outer circumference is formed with a retainer groove thereon to respectively receive a portion of the resilient spring.
3. The foundation support system of claim 1, wherein the first outer circumference is configured to establish a rotational interlock with the second inner circumference when the first and second couplers are mated.
4. The foundation support system of claim 3, wherein the first outer circumference includes a plurality of ribs or a plurality of grooves, wherein the second inner circumference includes a plurality of ribs or a plurality of grooves, and the rotational interlock is established between the ribs or grooves in the first outer circumference or the second outer circumference.
5. The foundation support system of claim 4, wherein the plurality of ribs define a retainer groove receiving a portion of the resilient spring in the snap-fit engagement.
6. The foundation support system of claim 4, wherein the plurality of ribs are helical ribs.
7. The foundation support system of claim 4, wherein the plurality of ribs are spaced unevenly from one another.
8. The foundation support system of claim 3, wherein the first outer circumference includes a polygonal body having a number of sides, and wherein the second inner circumference defines a receiving area complementary to the polygonal body.
9. The foundation support system of claim 8, wherein the polygonal body has six sides.
10. The foundation support system of claim 8, wherein the polygonal body has four sides.
11. The foundation support system of claim 3, wherein the first outer circumference and the second inner circumference are at least partly tapered along an axial centerline of the first coupler or the second coupler.
12. The foundation support system of claim 1, wherein the resilient spring is permanently attached to one of the first and second couplers.
13. The foundation support system of claim 1, wherein the resilient spring extends around the first outer circumference of the first coupler and around the second outer circumference of the second coupler for a radial distance less than 360°.
14. The foundation support system of claim 13, wherein the resilient spring is an annular spring.
15. The foundation support system of claim 13, wherein the first outer circumference defines at least one ramp causing the resilient spring element to expand as the first and second couplers are mated.
16. The foundation support system of claim 1, further comprising a first pile and a second pile rotationally interlocked to one another through the first and second coupler.
17. The foundation support system of claim 16, wherein one of the first and second piles includes a helical auger.
18. The foundation support system of claim 16, further comprising one of a bracket, a plate, or a

lifting assembly for supporting the foundation.

19. The foundation support system of claim 16, wherein the first pile and the second pile are filled with a cementitious material.

20. The foundation support assembly of claim 1, wherein neither of the first or second coupler includes a fastener hole.

21. The foundation support assembly of claim 1, wherein the axial interlock is realized solely by the spring retainer element without any threaded fastener.

22. A foundation support system comprising: a first coupler having a first outer circumference and a first inner circumference; a second coupler having a second outer circumference and a second inner circumference; and a resiliently deflectable spring extending around the first outer circumference and around the second outer circumference for a radial distance less than 360° and being configured to automatically engage and axially interlock the first outer circumference and the second outer circumference with snap-fit engagement as the first and second couplers are mated; wherein the first outer circumference defines at least one ramp causing a diameter of the resiliently deflectable spring to expand and a retaining groove for the resiliently deflectable spring to return to a reduced diameter as the first and second couplers are mated; and wherein the axial interlock avoids a separation of the first and second couplers at a below ground location due to axially directed uplift forces when the foundation support system is installed in a building site to support the foundation.

23. The foundation support assembly of claim 22, wherein neither of the first or second coupler includes a fastener hole.

24. The foundation support assembly of claim 22, wherein the axial interlock is realized solely by the spring retainer element without any threaded fastener.

25. The foundation support system of claim 22, wherein the resilient spring is permanently attached to the second coupler.

26. The foundation support system of claim 22, wherein the first outer circumference is configured to establish a rotational interlock with the second inner circumference when the first and second couplers are mated.

27. The foundation support system of claim 22, further comprising a first pile and a second pile rotationally interlocked to one another through the first and second coupler.

28. The foundation support system of claim 27, wherein one of the first and second piles includes a helical auger.

29. A foundation support system comprising: a first coupler having a first outer circumference and a first inner circumference; a second coupler having a second outer circumference and a second inner circumference; a resilient spring extending on the second outer circumference and having an expandable diameter; wherein the first outer circumference is configured to cause the diameter of the resilient spring element to expand when the first outer circumference is partly mated to the second inner circumference; and wherein the first outer circumference is configured to receive a portion of the resilient spring at a reduced diameter with snap-fit engagement, thereby automatically establish an axial interlock of the first and second outer circumference when the first outer circumference is fully mated to the second inner circumference; wherein the axial interlock avoids a separation of the first and second couplers at a below ground location due to axially directed uplift forces when the foundation support system is installed in a building site to support the foundation.

30. The foundation support assembly of claim 29, wherein neither of the first or second coupler includes a fastener hole.

31. The foundation support assembly of claim 29, wherein the axial interlock is realized solely by the spring retainer element without any threaded fastener.
