

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250283370

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

Ohrstrom; Rolf et al.

WINDOW ASSEMBLY FOR MITIGATING FLUID INGRESS

Abstract

A window assembly for mitigating fluid ingress between adjacent frame members is disclosed. The assembly has a first frame member of a first frame, and a second frame member of a second frame. The first frame member includes a seal-receiving channel first counterpart, and the second frame member includes a seal-receiving channel second counterpart. The first and second frame members are co-operatively configured such that, while the first counterpart of the seal-receiving channel is disposed opposite to the second counterpart of the seal-receiving channel, the seal-receiving channel is defined. The sealing interface is defined while the seal is disposed in the seal-receiving channel, and while the first and second frame members are disposed in a sealing interface-defining proximity. While the sealing interface is defined between the first and second frame members, the sealing interface resists fluid communication or fluid ingress between the first and second frame members.

Inventors: Ohrstrom; Rolf (Woodbridge, CA), Feil; Don (Woodbridge, CA)

Applicant: VISION EXTRUSIONS GROUP LIMITED (Woodbridge, CA)

Family ID: 1000008619442

Appl. No.: 19/214593

Filed: May 21, 2025

Related U.S. Application Data

parent US continuation 17152713 20210119 parent-grant-document US 12338678 child US 19214593

us-provisional-application US 62962596 20200117

Publication Classification

Int. Cl.: E06B3/663 (20060101); E06B3/06 (20060101); E06B3/263 (20060101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION [0001] This application claims the benefits of priority to U.S. Provisional Patent Application No. 62/962,596, filed Jan. 17, 2020, titled WINDOW ASSEMBLY FOR MITIGATING FLUID INGRESS, the contents of which are hereby expressly incorporated into the present application by reference in their entirety.

FIELD

[0002] The present disclosure relates to a window assembly, in particular, to a window assembly for mitigating fluid ingress between frame members.

BACKGROUND

[0003] There are a number of different styles of windows, including tilt and turn windows, casement windows, awning windows, and single and double hung windows. Windows typically include a frame, and one or more window panes that are received in the frame, with the frame members of the frame surrounding the panes. The frame may define a drainage channel, such that condensation may be collected and drained out of the window. The frame may also define one or more channels to receive a glass stop, which is configured to support the pane. The frame may also include a seal, which, while the pane is received in the frame, is co-operatively configured with the pane to define a sealing interface such that fluid communication through the frame is resisted or absent.

[0004] Windows may be installed in a room in order to, for example, introduce light into the room, or to provide a line of sight between the inside of the room and the outside of the room. It may be desirable to install two or more windows adjacent to each other to increase the amount of light that may enter into the room, or to increase the line of sight. The windows may be installed next to each other, or above one another.

[0005] One way to install the windows adjacent to each other is by connecting a frame member of one window frame to a frame member of an adjacent window frame. Various connection systems have been developed to connect the frame members, such as, for example, adhesive or double-sided tape. Unfortunately, existing connection systems do not provide a reliable connection between the frame members, such that the frame members, and thus the window frames, may be susceptible to separation. In addition, the connection between the frame members may not resist fluid communication through the space between the frame members. Moreover, the connection may define a region of relatively poor insulation for the room in which the windows are installed, such that relatively warm air from the room may exit to the outside through the region, or relatively warm air from the outside may enter the room through the region. This may require the room to be excessively heated or cooled in order to maintain a desired temperature. Debris or liquid may also enter the room from the outside through the connection between the frame members, or may collect between the frame members. Additionally, design and cost limitations of the existing connection systems disincentive the manufacturing of larger window frames.

SUMMARY

[0006] In one aspect, there is provided a kit for a window assembly, comprising: a first frame member that includes: a seal-receiving channel first counterpart; an exterior wall; an interior wall that is disposed on an opposite side of the first frame member relative to the exterior wall; and a pane-receiving space, defined by the interior wall, that is configured to receive a glass pane; a second frame member that includes: a seal-receiving channel second counterpart; an exterior wall;

an interior wall that is disposed on an opposite side of the second frame member relative to the exterior wall; and a pane-receiving space, defined by the interior wall, that is configured to receive a glass pane; wherein: the first and second frame members are co-operatively configured such that, while the exterior wall of the first frame member is disposed opposite to the exterior wall of the second frame member, a seal receiving channel is defined by at least the first and second counterparts; and the seal-receiving channel is configured for disposition of a seal therein.

[0007] In another aspect, there is provided a kit for a window assembly, comprising: a first frame member that includes: a seal-receiving channel first counterpart; an exterior wall; an interior wall that is disposed on an opposite side of the first frame member relative to the exterior wall; and a glass stop-receiving channel, defined by the interior wall, that is configured to receive a glass stop; a second frame member that includes: a seal-receiving channel second counterpart; an exterior wall; an interior wall that is disposed on an opposite side of the second frame member relative to the exterior wall; and a glass stop-receiving channel, defined by the interior wall, that is configured to receive a glass stop; wherein: the first and second frame members are co-operatively configured such that, while the exterior wall of the first frame member is disposed opposite to the exterior wall of the second frame member, the seal receiving channel is defined by at least the first and second counterparts; and the seal-receiving channel is configured for disposition of a seal disposed therein.

[0008] In another aspect, there is provided a window assembly, comprising: a first frame member that includes: a seal-receiving channel first counterpart; an exterior wall; an interior wall that is disposed on an opposite side of the first frame member relative to the exterior wall; and a pane-receiving space, defined by the interior wall, that is configured to receive a glass pane; a second frame member that includes: a seal-receiving channel second counterpart; an exterior wall; an interior wall that is disposed on an opposite side of the second frame member relative to the exterior wall; and a pane-receiving space, defined by the interior wall, that is configured to receive a glass pane; wherein the first and second frame members are co-operatively configured such that, while the exterior wall of the first frame member is disposed opposite to the exterior wall of the second frame member, a seal receiving channel is defined by at least the first and second counterparts; and a seal that is disposed in the seal receiving channel.

[0009] In another aspect, there is provided a window assembly, comprising: a first frame member that includes: a seal receiving channel first counterpart; an exterior wall; an interior wall that is disposed on an opposite side of the first frame member relative to the exterior wall; and a glass stop-receiving channel, defined by the interior wall, that is configured to receive a glass stop; a second frame member that includes: a seal receiving channel first counterpart; an exterior wall; an interior wall that is disposed on an opposite side of the second frame member relative to the exterior wall; and a glass stop-receiving channel, defined by the interior wall, that is configured to receive a glass stop; wherein the first and second frame members are co-operatively configured such that, while the exterior wall of the first frame member is disposed opposite to the exterior wall of the second frame member, the seal receiving channel is defined by at least the first and second counterparts; and a seal that is disposed in the seal receiving channel.

[0010] In another aspect, there is provided a frame member, comprising: a seal-receiving channel counterpart that is configured to be disposed in opposition to a seal-receiving channel counterpart of an adjacent frame member, the seal-receiving channel configured for disposition a seal disposed therein; wherein, while the seal-receiving channel counterpart is disposed in opposition to the seal-receiving channel counterpart of the adjacent frame member, a seal-receiving channel is defined by at least the seal receiving channel counterpart of the frame member and the seal receiving channel counterpart of the adjacent frame member.

[0011] Other aspects will be apparent from the description and drawings provided herein.

Description

BRIEF DESCRIPTION OF DRAWINGS

[0012] In the figures, which illustrate example embodiments,

[0013] FIG. 1 is a perspective view of a window assembly;

[0014] FIG. 2 is a top view of the window assembly of FIG. 1;

[0015] FIG. 3 is a top exploded view of the window assembly of FIG. 1;

[0016] FIG. 4 is an enlarged partial top view of the window assembly of FIG. 1;

[0017] FIG. 5 is an enlarged partial top exploded view of the window assembly of FIG. 1;

[0018] FIG. 6 is a schematic of a seal;

[0019] FIG. 7 is a flow chart depicting a method of assembling a window assembly;

[0020] FIG. 8 is a perspective view of another window assembly;

[0021] FIG. 9 is a top view of the window assembly of FIG. 8;

[0022] FIG. 10 is a top exploded view of the window assembly of FIG. 8;

[0023] FIG. 11 is a top exploded view of the window assembly of FIG. 8, without the seals disposed in the seal-receiving channel;

[0024] FIG. 12 is an enlarged partial top view of the window assembly of FIG. 8;

[0025] FIG. 13 is a schematic of a window with a window frame that includes the frame member of FIG. 1.

DETAILED DESCRIPTION

[0026] A window assembly for mitigating fluid ingress between adjacent window frame members is disclosed. The window assembly has a first frame member of a first window frame, and a second frame member of a second window frame. The first and second frame members may be moulded, such as blow moulded or injection moulded, or may be extruded. The first frame member includes a seal-receiving channel first counterpart, and the second frame member includes a seal-receiving channel second counterpart. The seal-receiving channel is configured to have a seal disposed therein. The first frame member and the second frame member are co-operatively configured such that, while the first counterpart of the seal-receiving channel is disposed opposite to the second counterpart of the seal-receiving channel, the seal-receiving channel is defined. The sealing interface is defined while the seal is disposed in the seal-receiving channel, and while the first frame member and the second frame member are disposed in a sealing interface-defining proximity. While the sealing interface is defined between the first and second frame members, the sealing interface resists fluid communication or fluid ingress between the first and second frame members. In this regard, the window assembly may promote insulation of the room in which the window assembly is installed via the sealing interface defined between the first window frame and the second window frame, and collection of debris between the first and second window frames may be resisted. In addition, window assemblies of various sizes and configurations may be manufactured.

[0027] FIG. 13 depicts a window 70. In some embodiments, for example, the window 70 includes a frame 40, a sash 50, and one or more glass panes 116. In some embodiments, for example, the window frame 40 includes one or more frame members 100 that are co-operatively configured to define the window frame 40. As depicted, the glass pane 116 is disposed in the sash 50, and the sash 50 is disposed in the window frame 40. In some embodiments, for example, the frame 40 supports the sash 50, which supports the glass pane 116.

[0028] FIG. 1 depicts an example window assembly 10. The window assembly 10 comprises one or more frame members 100. As depicted in FIG. 1, the window assembly 10 comprises a first frame member 100A and a second frame member 100B. The first frame member 100A is a frame member of a first window frame, and the second frame member 100B is a frame member of a second window frame. In some embodiments, for example, the first frame member 100A and the second frame member 100B are manufactured by extrusion, blow moulding, or injection moulding. In some embodiments, for example, the first frame member 100A and the second frame member

100B are extruded lineals.

[0029] The first frame member **100A** and the second frame member **100B** comprise an external wall **102**, an internal wall **104**, an exterior wall **106**, and an interior wall **108**. As depicted in FIG. 1, FIG. 2, and FIG. 3, in some embodiments, for example, the internal wall **104** is disposed on an opposite side of the frame member **100** relative to the external wall **102**, and the interior wall **108** is disposed on an opposite side of the frame member **100** relative to the exterior wall **106**. In some embodiments, for example, while the frame member **100** is installed, for example, in a wall of a room, the external wall **102** is facing the outside of the room, the internal wall **104** is facing the inside of the room, the exterior wall **106** is facing away from a pane-receiving space **124** defined by the frame for receiving the window glass pane, and the interior wall **108** is facing the pane-receiving space **124** defined by the frame for receiving the window glass pane. In some embodiments, for example, while the frame member **100** is installed, for example, in a wall of a room, the external wall **102** and the internal wall **104** are visible, while the exterior wall **106** and the interior wall **108** are obscured from view, for example, by surrounding drywall or other construction materials.

[0030] As depicted in FIG. 1, in some embodiments, for example, the frame member **100** includes a drainage channel **110** and a glass stop-receiving channel **112**. The drainage channel **110** is configured to receive and drain condensation or fluid that has collected in the window, and the glass stop-receiving channel **112** is configured to receive a glass stop **114** that supports one or more glass panes **116** in the frame. In some embodiments, for example, the frame, having the frame member **100**, is configured to support one or more glass panes **116**. As depicted in FIG. 1, the frame is supporting two glass panes **116** that are separated by a spacer **117**. As depicted in FIG. 1, in some embodiments, for example, the drainage channel **110** and the glass stop-receiving channel **112** are defined by the interior wall **108** of the frame member **100**.

[0031] In some embodiments, for example, the frame member **100** includes a seal or flex **118** that is co-operatively configured with the pane **116** to define a sealing interface between the frame member **100** and the pane **116**. As depicted in FIG. 1 and FIG. 2, the flex **118** is connected to the frame member **100** and facing towards the glass stop-receiving channel **112** and towards the pane-receiving space **124**. In some embodiments, for example, where the frame member **100** is an extruded lineal, the seal or flex **118** may be co-extruded with the frame member **100**.

[0032] In some embodiments, for example, the frame member **100** includes one or more supporting ribs **119**. In some embodiment, for example, the supporting rib **119** extends along the length of the frame member **100**. As depicted in FIG. 1 and FIG. 2, in some embodiments, for example, the supporting rib **119** extends between one of the external wall **102**, the internal wall **104**, the exterior wall **106**, and the interior wall **108**, and another of the walls. As depicted in FIG. 1, the external wall **102**, the internal wall **104**, the exterior wall **106**, the interior wall **108**, and the supporting rib **119**, or intersecting supporting ribs **119**, define a channel **121** in the frame member **100**. In some embodiments, for example, then channel **121** extends along the length of the frame member **100**.

[0033] In some embodiments, for example, as depicted in FIG. 2, the frame member **100** includes a hinge **120** that is configured to pivot a moveable portion of the frame member relative to a stationary portion of the frame member **100**. In this regard, in some embodiments, for example, the moveable portion of the frame member **100** includes the pane **116**, and the stationary portion of the frame member **100** does not include the pane **116**. While the moveable portion is moved relative to the stationary portion, the pane **116** also moves relative to the stationary portion. The moveable portion of the frame member **100** is moveable between an open position and a close position. While the moveable portion of the frame member is in the closed position, the pane **116** is disposed relative to the frame such that fluid communication through the frame is resisted by the pane **116** or absent. While the moveable portion of the frame member **100** is in the open position, the pane **116** is disposed relative to the frame such that fluid communication through the frame is present. As depicted in FIG. 2, in some embodiments, for example, the hinge **120** is disposed in one of the

internal channels **121** of the frame member **100**. In some embodiments, for example, as depicted in FIG. 2, the frame member **100B** has a hinge **120**, while the frame member **100A** does not have a hinge **120**. In this regard, in some embodiments, for example, the frame member **100B** is the operable frame member, and the frame member **100A** is the fixed frame member.

[0034] In some embodiments, for example, as depicted in FIG. 1 and FIG. 2, the frame member **100** includes weather stripping **122** to define a seal between portions of the frame member **100**, for example, to prevent or mitigate incursion of debris or fluid into the frame member **100**.

[0035] In some embodiments, for example, the frame member **100** includes a screen **123**. In some embodiments, for example, as depicted in FIG. 1 and FIG. 2, one of the frame members **100**, such as the frame member **100B**, of the window assembly **10** includes the screen **123**, and the screen **123** is offset relative to the panes **116**. The screen **123** is configured to filter debris while fluid communication is permitted through the window, for example, while the moveable portion of the frame member **100** is in the open position.

[0036] In some embodiments, for example, as depicted in FIGS. 1 to 3, the interior wall **108** defines a pane-receiving space **124**. The pane-receiving space **124** is configured to receive the glass pane **116**. In some embodiments, for example, the pane-receiving space **124** is configured to receive a sitting block **126**. While the one or more panes **116** is received in the frame, such as in the pane-receiving space **124**, and supported by the glass stop **114**, the sitting block **126** is interposed between the panes **116** and the drainage channel **110** such that the panes **116** are offset from the drainage channel **110**. While the pane **116** is received in the window frame, for example, in the pane receiving space **124**, the pane **116** may be connected to the frame member **100** using, for example, an adhesive, such as glue, or double-sided tape.

[0037] As depicted in FIGS. 1 to 3, the window assembly **10** includes the first frame member **100A** and the second frame member **100B**. In some embodiments, for example, as depicted in FIG. 3, the first frame member **100A** includes a seal-receiving channel first counterpart **132**, and the second frame member **100B** includes a seal-receiving channel second counterpart **134**. The seal-receiving channel **130** is configured for disposition of a seal **150** therein. FIGS. 1 to 5 depict the seal **150** disposed in the seal-receiving channel **130**.

[0038] As depicted in FIG. 5, in some embodiments, for example, the seal-receiving channel first counterpart **132** includes side walls **1322** and a base wall **1324**, and the seal-receiving channel second counterpart **134** includes side walls **1342** and a base wall **1344**.

[0039] In some embodiments, for example, as depicted in FIGS. 1 to 5, the first frame member **100A** and the second frame member **100B** are co-operatively configured such that, while the seal-receiving channel first counterpart **132** is disposed opposite to the seal-receiving channel second counterpart **134**, the seal-receiving channel **130** is defined, for example, by at least the first counterpart **132** and the second counterpart **134**.

[0040] In some embodiments, for example, as depicted in FIGS. 1 to 5, the first frame member **100A** and the second frame member **100B** are co-operatively configured such that, while the exterior wall **106** of the first frame member **100A** is disposed opposite to the exterior wall **106** of the second frame member **100B**, the seal-receiving channel **130** is defined, for example, by at least the first counterpart **132** and the second counterpart **134**.

[0041] In some embodiments, for example, the disposition of the first frame member **100A** opposite to the second frame member **100B**, with effect that the definition of the seal-receiving channel **130** is defined, is such that the seal-receiving channel first counterpart **132** is disposed in alignment with the seal-receiving channel second counterpart **134**. While the first counterpart **132** is disposed in alignment with the second counterpart **134**, the seal-receiving channel **130** is defined.

[0042] As depicted in FIG. 3, the seal-receiving channel first counterpart **132** is defined on the exterior wall **106** of the first frame member **100A**. In some embodiments, for example, the seal-receiving channel first counterpart **132** is extending from the exterior wall **106** of the first frame member **100A**. In some embodiments, for example, the seal-receiving channel first counterpart **132**

is a recess defined on the exterior wall **106** of the first frame member **100A**.

[0043] In some embodiments, for example, as depicted in FIG. 5, a surface of the exterior wall **106** of the first frame member **100A** defines a normal axis **140**, and the first counterpart **132** of the seal-receiving channel **130** defines a longitudinal axis **142** that is disposed parallel relative to the normal axis **140** defined by the surface of the exterior wall **106** of the first frame member **100A**. In some embodiments, for example, as depicted in FIG. 11, the longitudinal axis **142** defined by the first counterpart **132** of the seal-receiving channel **130** is disposed at an acute angle θ between 0 degrees and 60 degrees, for example, between 0 degrees and 45 degrees, for example, between 5 degrees and 50 degrees, for example, between 10 degrees and 40 degrees, relative to the normal axis **140** defined by the surface of the exterior wall **106** of the first frame member **100A**. In some embodiments, for example, the angle θ is 30 degrees. In some embodiments, for example, the angle θ is 45 degrees. In some embodiments, for example, the angle θ is 60 degrees.

[0044] In some embodiments, for example, the first counterpart **132** of the seal-receiving channel **130** has an opening with a width of at least 0.125", for example, at least 0.15", for example, at least 0.175", for example, at least 0.20", for example, at least 0.225", for example, at least 0.40". In some embodiments, for example, the first counterpart **132** of the seal-receiving channel **130** has an opening with a width between 0.25" and 0.375", for example, 0.275", for example, 0.30", for example, 0.325", for example, 0.35".

[0045] Similarly, as depicted in FIG. 3, the seal-receiving channel second counterpart **134** is defined on the exterior wall **106** of the second frame member **100B**. In some embodiments, for example, the seal-receiving channel second counterpart **134** is extending from the exterior wall **106** of the second frame member **100B**. In some embodiments, for example, the second counterpart **134** of the seal-receiving channel **130** is a recess defined on the exterior wall **106** of the second frame member **100B**.

[0046] In some embodiments, for example, as depicted in FIG. 5, a surface of the exterior wall **106** of the second frame member **100B** defines a normal axis **144**, and the second counterpart **134** of the seal-receiving channel **130** defines a longitudinal axis **146** that is disposed parallel relative to the normal axis **144** defined by the surface of the exterior wall **106** of second first frame member **100B**. In some embodiments, for example, as depicted in FIG. 11, the longitudinal axis **146** defined by the second counterpart **134** of the seal-receiving channel **130** is disposed at an acute angle β between 0 degrees and 60 degrees, for example, between 0 degrees and 45 degrees, for example, between 5 degrees and 50 degrees, for example, between 10 degrees and 40 degrees, relative to the normal axis **144** defined by the surface of the exterior wall **106** of the second frame member **100B**. In some embodiments, for example, the angle β is 30 degrees. In some embodiments, for example, the angle β is 45 degrees. In some embodiments, for example, the angle β is 60 degrees.

[0047] In some embodiments, for example, the angles θ and β have the same magnitude. In some embodiments, for example, the angles θ and β have different magnitudes.

[0048] In some embodiments, for example, the second counterpart **134** of the seal-receiving channel **130** has an opening with a width of at least 0.125", for example, at least 0.15", for example, at least 0.175", for example, at least 0.20", for example at least 0.225", for example, at least 0.40". In some embodiments, for example, the second counterpart **134** of the seal-receiving channel **130** has an opening with a width between 0.25" and 0.375", for example, 0.275", for example, 0.30", for example, 0.325", for example, 0.35".

[0049] As depicted in FIGS. 1 to 5, the seal-receiving channel **130** is configured to have a seal **150** disposed therein. While the seal **150** is disposed in the seal-receiving channel **130**, a sealing interface **160** is definable between the seal **150** and at least one of the first frame member **100A** and the second frame member **100B**, as depicted in FIG. 4. In some embodiments, for example, the sealing interface **160** is definable between the seal **150** and at least one of the first counterpart **132** of the seal-receiving channel **130** of the first frame member **100A** and the second counterpart **134** of the seal-receiving channel **130** of the second frame member **100B**.

[0050] In some embodiments, for example, as depicted in FIGS. 1, 2, and 4, the first and second frame members **100A**, **100B** are further co-operatively configured such that, while: (i) the exterior wall **106** of the first frame member **100A** is disposed opposite to the exterior wall **106** of the second frame member **100B** such that the definition of the seal-receiving channel **130** is effected, (ii) the first counterpart **132** of the first frame member **100A** and the second counterpart **134** of the second frame member **100B** are disposed in a sealing interface-defining proximity, and (iii) the seal **150** is disposed in the seal-receiving channel **130**, a sealing interface **160** is established between the first and second frame members **100A**, **100B**. In some embodiments, for example, the first counterpart **132** of the first frame member **100A** and the second counterpart **134** of the second frame member **100B** are relatively disposed such that, while the seal **150** is disposed in the seal-receiving channel **130**, at least one of the first counterpart **132** of the first frame member **100A** and the second counterpart **134** of the second frame member **100B** defines the sealing interface **160** with the seal **150**. In some embodiments, for example, the sealing interface-defining proximity is a range of distances between the first counterpart **132** of the first frame member **100A** and the second counterpart **134** of the second frame member **100B** that the sealing interface **160** is defined between the seal **150** and at least one of the first counterpart **132** of the first frame member **100A** and the second counterpart **134** of the second frame member **100B**. In some embodiments, for example, such range of distances between the first counterpart **132** of the first frame member **100A** and the second counterpart **134** of the second frame member **100B** such that the first counterpart **132** of the first frame member **100A** and the second counterpart **134** of the second frame member **100B** is in the sealing interface-defining proximity is defined, in part, by: (i) the characteristics of the seal **150**, such as the dimensions and compression ratio of the seal **150**, and (ii) the characteristics of the first counterpart **132** and the second counterpart **134**, such as the shapes, geometry, and dimensions of the first counterpart **132** and the second counterpart **134**. In some embodiments, for example, where the sealing interface-defining proximity is a range, the upper extreme of the sealing interface-defining proximity is the greatest distance between the first counterpart **132** of the first frame member **100A** and the second counterpart **134** of the second frame member **100B** where the sealing interface **160** is defined between the seal **150** and at least one of the first counterpart **132** of the first frame member **100A** and the second counterpart **134** of the second frame member **100B**. In some embodiments, for example, the lower extreme of the sealing interface-defining proximity is the shortest distance between the first counterpart **132** of the first frame member **100A** and the second counterpart **134** of the second frame member **100B** where the sealing interface **160** is defined between the seal **150** and at least one of the first counterpart **132** of the first frame member **100A** and the second counterpart **134** of the second frame member **100B**.

[0051] In some embodiments, for example, while: (i) the seal **150** is disposed in the seal-receiving channel **130**, (ii) the first counterpart **132** of the first frame member **100A** and the second counterpart **134** of the second frame member **100B** are disposed in the sealing interface-defining proximity, and (iii) the sealing interface **160** is defined with the seal **150** and at least one of the first counterpart **132** of the first frame member **100A** and the second counterpart **134** of the second frame member **100B**, the first frame member **100A** and the second frame member **100B** are co-operatively configured to resist removal of the seal **150** from the seal-receiving channel **130**, such that the sealing interface **160** is maintained in the seal-receiving channel **130**. In some embodiments, for example, the first counterpart **132** and the second counterpart **134** are co-operatively configured to resist removal of the seal **150** from the seal-receiving channel **130**, such that the sealing interface **160** is maintained in the seal-receiving channel **130**.

[0052] In some embodiments, for example, while the seal **150** is disposed in the seal-receiving channel **130**, the sealing interface **160** is definable between the seal **150**, the first counterpart **132** of the seal-receiving channel **130** of the first frame member **100A**, and the second counterpart **134** of the seal-receiving channel **130** of the second frame member **100B**, as depicted in FIG. 4. In some

embodiments, for example, the defining of the sealing interface **160** is defined effected between the seal **150**, the first counterpart **132** of the first frame member **100A**, and the second counterpart **134** of the second frame member **100B**.

[0053] In some embodiments, for example, as depicted in FIG. 5, the first counterpart **132** of the seal-receiving channel **130** of the first frame member **100A** includes a sealing interface-defining wall **170**, and the sealing interface **160** is definable between the seal **150** and the sealing interface-defining wall **170** of the first counterpart **132** of the seal-receiving channel **130**. As depicted in FIG. 5, in some embodiments, for example, the sealing interface-defining wall **170** is disposed proximate the opening of the first counterpart **132** of the seal-receiving channel **130** of the first frame member **100A**.

[0054] As depicted in FIG. 5, in some embodiments, for example, the sealing interface-defining wall **170** of the first counterpart **132** of the seal-receiving channel **130** of the first frame member **100A** extends between the side wall **1322** of the first counterpart **132** of the seal-receiving channel **130** and the exterior wall **106** of the first frame member **100A**.

[0055] In some embodiments, for example, as depicted in FIG. 5, the second counterpart **134** of the seal-receiving channel **130** of the second frame member **100B** includes a sealing interface-defining wall **174**, and the sealing interface **160** is definable between the seal **150** and the sealing interface-defining wall **174** of the second counterpart **134** of the seal-receiving channel **130**. As depicted in FIG. 5, in some embodiments, for example, the sealing interface-defining wall **174** is disposed proximate the opening of the second counterpart **134** of the seal-receiving channel **130** of the second frame member **100B**.

[0056] As depicted in FIG. 5, in some embodiments, for example, the sealing interface-defining wall **174** of the second counterpart **134** of the seal-receiving channel **130** of the second frame member **100B** extends between the side wall **1342** of the second counterpart **134** of the seal-receiving channel **130** and the exterior wall **106** of the second frame member **100B**.

[0057] In some embodiments, for example, the sealing interface **160** is definable between the seal **150**, the sealing interface-defining wall **170** of the first counterpart **132**, and the sealing interface-defining wall **174** of the second counterpart **134**.

[0058] In some embodiments, for example, the first counterpart **132** includes a first sealing interface-defining wall **170** and a second sealing interface-defining wall **172**, and the sealing interface **160** is definable between the seal **150**, the first sealing interface-defining wall **170** of the first counterpart **132**, and the second sealing interface-defining wall **172** of the first counterpart **132**. As depicted in FIG. 5, in some embodiments, for example, the first sealing interface-defining wall **170** and the second sealing interface-defining wall **172** are disposed proximate the opening of the first counterpart **132** of the seal-receiving channel **130** of the first frame member **100A**, with the first sealing interface-defining wall **170** disposed opposite to the second sealing interface-defining wall **172**.

[0059] As depicted in FIG. 5, in some embodiments, for example, the first sealing interface-defining wall **170** and the second sealing interface-defining wall **172** of the first counterpart **132** of the seal-receiving channel **130** of the first frame member **100A** extends between the side walls **1322** of the first counterpart **132** of the seal-receiving channel **130** and the exterior wall **106** of the first frame member **100A**.

[0060] In some embodiments, for example, the second counterpart **134** includes a first sealing interface-defining wall **174** and a second sealing interface-defining wall **176**, and the sealing interface **160** is definable between the seal **150**, the first sealing interface-defining wall **174** of the second counterpart **134**, and the second sealing interface-defining wall **176** of the second counterpart **134**. As depicted in FIG. 5, in some embodiments, for example, the first sealing interface-defining wall **174** and the second sealing interface-defining wall **176** are disposed proximate the opening of the second counterpart **134** of the seal-receiving channel **130** of the second frame member **100B**, with the first sealing interface-defining wall **174** disposed opposite to

the second sealing interface-defining wall **176**.

[0061] As depicted in FIG. 5, in some embodiments, for example, the first sealing interface-defining wall **174** and the second sealing interface-defining wall **176** of the second counterpart **134** of the seal-receiving channel **130** of the second frame member **100B** extends between the side walls **1342** of the second counterpart **134** of the seal-receiving channel **130** and the exterior wall **106** of the second frame member **100B**.

[0062] In some embodiments, for example, as depicted in FIG. 5, the first counterpart **132** of the seal-receiving channel **130** includes the first sealing interface-defining wall **170** and the second sealing interface-defining wall **172**, and the second counterpart **134** of the seal-receiving channel **130** includes the first sealing interface-defining wall **174** and the second sealing interface-defining wall **176**. In such embodiments, the sealing interface **160** is definable between the seal **150**, the first sealing interface-defining wall **170** of the first counterpart **132**, the second sealing interface-defining wall **172** of the first counterpart **132**, the first sealing interface-defining wall **174** of the second counterpart **134**, and the second sealing interface-defining wall **176** of the second counterpart **134**.

[0063] In some embodiments, for example, the seal-receiving channel **130** is configured to have more than one seal **150**, for example, two seals **150**, disposed therein, as depicted in FIG. 10. While the first seal **150** and the second seal **150** are disposed in the seal-receiving channel **130**, a sealing interface **160** is definable between the first seal **150** and the second seal **150**. In some embodiments, for example, the sealing interface **160** is definable between the first seal **150** and the second seal **150**, and between: (a) the first seal **150** and the second seal **150**, and (b) at least one of the first counterpart **132** of the seal-receiving channel **130** of the first frame member **100A** and the second counterpart **134** of the seal-receiving channel **130** of the second frame member **100B**.

[0064] In some embodiments, for example, the first and second frame members **100A**, **100B** are co-operatively configured such that, while: (i) the exterior wall **106** of the first frame member **100A** is disposed opposite to the exterior wall **106** of the second frame member **100B** such that the definition of the seal-receiving channel **130** is effected, (ii) the first counterpart **132** of the first frame member **100A** and the second counterpart **134** of the second frame member **100B** are disposed in a sealing interface-defining proximity, and (iii) the first and second seals **150** are disposed in the seal-receiving channel **130**, a sealing interface **160** is established between the first and second frame members **100A**, **100B** and the first seal **150** and the second seal **150**, for example, between the first frame member **100A** and the first seal **150**, between the second frame member **100B** and the second seal **150**, and between the first seal **150** and the second seal **150**.

[0065] In some embodiments, for example, while: (i) the first seal **150** and the second seal **150** are disposed in the seal-receiving channel **130**, (ii) the first counterpart **132** of the first frame member **100A** and the second counterpart **134** of the second frame member **100B** are disposed in the sealing interface-defining proximity, and (iii) the sealing interface **160** is defined between the first seal **150** and the second seal **150**, and between: (a) the first seal **150** and the second seal **150**, and (b) at least one of the first counterpart **132** of the first frame member **100A** and the second counterpart **134** of the second frame member **100B**, the first frame member **100A** and the second frame member **100B** are co-operatively configured to resist removal of the first seal **150** and the second seal **150** from the seal-receiving channel **130**, such that the sealing interfaces **160** are maintained in the seal-receiving channel **130**. In some embodiments, for example, the first counterpart **132** and the second counterpart **134** are co-operatively configured to resist removal of the first seal **150** and the second seal **150** from the seal-receiving channel **130**, such that the defined sealing interfaces **160** are maintained in the seal receiving channel **130**.

[0066] In some embodiments, for example, while the first seal **150** and the second seal **150** are disposed in the seal-receiving channel **130**, the sealing interface **160** is definable between the first seal **150** and the second seal **150**, and between: (a) the first seal **150** and the second seal **150**, (b) the first counterpart **132** of the seal-receiving channel **130** of the first frame member **100A**, and (c)

the second counterpart **134** of the seal-receiving channel **130** of the second frame member **100B**. In some embodiments, for example, the defining of the sealing interface **160** is effected between the first and second seals **150**, the first counterpart **132** of the first frame member **100A**, and the second counterpart **134** of the second frame member **100B**.

[0067] In some embodiments, for example, the sealing interface **160** is definable between the first seal **150** and the second seal **150**, and between: (a) the first seal **150** and the second seal **150**, and (b) the sealing interface-defining wall **170** of the first counterpart **132** of the seal-receiving channel **130**.

[0068] In some embodiments, for example, the sealing interface **160** is definable between the first seal **150** and the second seal **150**, and between: (a) the first seal **150** and the second seal **150**, and (b) the sealing interface-defining wall **174** of the second counterpart **134** of the seal-receiving channel **130**.

[0069] In some embodiments, for example, the sealing interface **160** is definable between the first seal **150** and the second seal **150**, and between: (a) the first seal **150** and the second seal **150**, (b) the sealing interface-defining wall **170** of the first counterpart **132**, and (c) the sealing interface-defining wall **174** of the second counterpart **134**.

[0070] In some embodiments, for example, the sealing interface **160** is definable between the first seal **150** and the second seal **150**, and between: (a) the first seal **150** and the second seal **150**, (b) the first sealing interface-defining wall **170** of the first counterpart **132**, and (c) the second sealing interface-defining wall **172** of the first counterpart **132**.

[0071] In some embodiments, for example, the sealing interface **160** is definable between the first seal **150** and the second seal **150**, and between: (a) the first seal **150** and the second seal **150**, (b) the first sealing interface-defining wall **174** of the second counterpart **134**, and (c) the second sealing interface-defining wall **176** of the second counterpart **134**.

[0072] In some embodiments, for example, the sealing interface **160** is definable between the first seal **150** and the second seal **150**, and between: (a) the first seal **150** and the second seal **150**, (b) the first sealing interface-defining wall **170** of the first counterpart **132**, (c) the second sealing interface-defining wall **172** of the first counterpart **132**, (d) the first sealing interface-defining wall **174** of the second counterpart **134**, and (e) the second sealing interface-defining wall **176** of the second counterpart **134**.

[0073] In some embodiments, for example, as depicted in FIG. 4, FIG. 5, FIG. 10, and FIG. 12, while the first counterpart **132** of the first frame member **100A** and the second counterpart **134** of the second frame member **100B** are disposed in the sealing interface-defining proximity, the first frame member **100A** and the second frame member **100B** are connectable. The first frame member **100A** and the second frame member **100B** are configured to be connected, such that while the first frame member **100A** and the second frame member **100B** are connected, the first counterpart **132** is disposed in opposition to the second counterpart **134** to define the seal-receiving channel **130**.

[0074] In some embodiments, for example, the first frame member **100A** and the second frame member **100B** are connected together using appropriate fasteners, such as nuts and bolts, screws, nails, pegs, adhesives, welding, and the like, or connected together using a snap-fit connection, a friction fit connection, an interference connection, and the like.

[0075] In some embodiments, for example, as depicted in FIG. 5, a connecting mechanism **180** is configured to connect the first frame member **100A** and the second frame member **100B**. As depicted in FIG. 5, in some embodiments, for example, the first frame member **100A** and the second frame member **100B** include a first counterpart **182** of the connecting mechanism **180**, and a coupler **186** includes a second counterpart **184** of the connecting mechanism **180**, where the second counterpart **184** of the connecting mechanism **180** is complementary to the first counterpart **182** of the connecting mechanism. The first counterpart **182** and the second counterpart **184** of the connecting mechanism **180** are engageable, such that the first counterpart **182** and the second counterpart **184** become retained. As depicted in FIG. 5, in some embodiments, for example, the

first counterpart **182** includes an attachment leg **188** that extends from the frame member **100**, such as the exterior wall **106**. In some embodiments, for example, the end of the attachment leg **188** includes a barb **190**. In some embodiments, for example, the attachment leg **188** is resilient, or include one or more resilient portions, so that it is moveable between: (i) a first position for facilitating engagement or interaction of the first counterpart **182** and the second counterpart **184**, and (ii) a second position for retention of the first counterpart **182** and the second counterpart **184**. In some embodiments, for example, the first counterpart **182** includes a slot **192**. As depicted in FIG. 5, the slot **192** is defined between the attachment leg **188**, and the internal wall **104** of the frame member **100**. In some embodiments, for example, the coupler **186** includes an attachment leg **194**.

[0076] In some embodiments, for example, the end of the attachment leg **194** includes a barb **196**. As depicted in FIG. 5, the coupler **186** includes two attachment legs **194** with barbs **196**. In some embodiments, for example, the attachment legs **194** are resilient, or include one or more resilient portions, so that it is moveable between: (i) a first position for facilitating engagement or interaction of the first counterpart **182** and the second counterpart **184**, and (ii) a second position for retention of the first counterpart **182** and the second counterpart **184**. In some embodiments, for example, the coupler **186** includes a slot **198**. In some embodiments, for example, the slot **198** is defined between the two attachment legs **194** of the coupler.

[0077] The first counterpart **182** and the second counterpart **184** are co-operatively configured to connect the first frame member **100A** and the second frame member **100B** upon engagement of the first counterpart **182** and the second counterpart **184**. In some embodiments, for example, while the first frame member **100A** and the second frame member **100B** are disposed in the sealing interface-defining proximity, the first counterpart **182** of the first frame member **100A**, the first counterpart **182** of the second frame member **100B**, and the coupler **186** are co-operatively configured to connect the first frame member **100A** and the second frame member **100B**.

[0078] While the first frame member **100A** and the second frame member **100B** are disposed in the sealing interface-defining proximity, the first counterpart **182**, such as the attachment leg **188**, the barb **190**, and the slot **192**, of the first frame member **100A** and the first counterpart **182**, such as the attachment leg **188**, the barb **190**, and the slot **192**, of the second frame member **100B** are aligned and parallel, as depicted in FIG. 2 and FIG. 4. While the first counterpart **182** of the first frame member **100A** is aligned with the first counterpart **182** of the second frame member **100B**, the attachment leg **188** and the barb **190** are disposed in alignment with the slot **198** of the coupler **186**, and the attachment leg **194** and the barb **196** are disposed in alignment with the slots **192** of the first frame member **100A** and the second frame member **100B**, the coupler **186** is pushed towards the first frame member **100A** and the second frame member **100B**, such that the attachment leg **188** and the barb **190** of the first frame member **100A** and the attachment leg **188** and barb **190** of the second frame member **100B** are inserted into the slot **198** of the coupler **186**, as depicted in FIG. 2 and FIG. 4.

[0079] While the attachment leg **188** and the barb **190** of the first frame member **100A** and the attachment leg **188** and the barb **190** of the second frame member **100B** are being inserted into the slot **198** of the coupler **186**, the attachment legs **194** and the barb **196** of the coupler **186** are resiliently displaced to accommodate insertion of the attachment leg **188** and the barb **190** of the first frame member **100A** and the attachment leg **188** and the barb **190** of the second frame member **100B** into the slot **198** of the coupler **186**.

[0080] While the coupler **186** is pushed against the first frame member **100A** and the second frame member **100B**, the attachment legs **194** and the barbs **196** of the coupler **186** are being inserted into the slot **192** of the first frame member **100A** and the slot **192** of the second frame member **100B**. While the attachment legs **194** and the barbs **196** of the coupler **186** are being inserted into the slot **192** of the first frame member **100A** and the slot **192** of the second frame member **100B**, the attachment leg **188** and the barb **190** of the first frame member **100A** and the attachment leg **188**

and the barb **190** of the second frame member **100B** are resiliently displaced to accommodate insertion the attachment legs **194** and the barb **196** of the coupler **186** into the slot **192** of the first frame member **100A** and the slot **192** of the second frame member **100B**.

[0081] In some embodiments, for example, the angled surface of the barb **190** of the attachment leg **188** of the first counterpart **182** functions as a cam surface to guide the barb **190** as it is inserted into the slot **198** of the coupler **186**. In some embodiments, for example, the angled surface of the barb **196** of the attachment legs **194** of the second counterpart **184** functions as a cam surface to guide the barb **196** as it is inserted into the slots **192** of the first frame member **100A** and the second frame member **100B**.

[0082] Upon: (i) insertion of the attachment leg **188** and the barb **190** of the first frame member **100A** and the attachment leg **188** and the barb **190** of the second frame member **100B** into the slot **198** of the coupler **186**, and (ii) insertion of the attachment legs **194** and the barbs **196** of the coupler **186** into the slot **192** of the first frame member **100A** and the slot **192** of the second frame member **100B**, the first counterpart **182** and the second counterpart **184** engage to retain the first frame member **100A**, the second frame member **100B**, and the coupler **186**, as depicted in FIG. 2 and FIG. 4. In some embodiments, for example, in response to a force applied to the first frame member **100A**, the second frame member **100B**, or the coupler **186**, to separate the first frame member **100A**, the second frame member **100B**, and the coupler **186**, the barbs **190**, for example, the vertical surface of the barbs **190** that extends from the angled surface of the barbs **190**, of the first counterpart **182** of the first frame member **100A** and the second frame member **100B** engage with the barbs **196**, for example, the vertical surface of the barbs **196** that extends from the angled surface of the barbs **196**, of the second counterpart **184** of the coupler **186** to resist separation of the coupler **186** from the first frame member **100A** and the second frame member **100B**, thereby retaining the first frame member **100A**, the second frame member **100B**, and the coupler **186**. In this regard, the first frame member **100A** and the second frame member **100B** are connected together using the coupler **186**.

[0083] As depicted in FIG. 1, FIG. 2, and FIG. 3, in some embodiments, for example, the first frame member **100A** and the second frame member **100B** include two first counterparts **182** of the connecting mechanism **180**, with the first counterparts **182** disposed on opposite sides of the first frame member **100A** and the second frame member **100B**, for example, the opposite sides of the first frame member **100A** and the second frame member **100B** having the external surfaces **102** and the internal surfaces **104**, respectively. As depicted in FIGS. 1 to 3, the attachment legs **188** of the first counterparts **182** extend from the exterior wall **106**, with the barbs **190** of the first counterparts **182** directed away from each other. In such embodiments, while the first frame member **100A** and the second frame member **100B** are disposed in the sealing interface-defining proximity, the first counterparts **182** of the first frame member **100A** and the first counterparts **182** of the second frame member **100B** are aligned and parallel, such that the first frame member **100A** and the second frame member **100B** are connectable using two couplers **186**, as depicted in FIG. 1 and FIG. 2.

[0084] As depicted in FIG. 1 and FIG. 2, while the first frame member **100A** and the second frame member **100B** are connected, in some embodiments, for example, the internal surface **104** of the first frame member **100A** is parallel to, or co-planar to, the internal surface **104** of the second frame member **100B**. As depicted in FIG. 1 and FIG. 2, while the first frame member **100A** and the second frame member **100B** are connected, in some embodiments, for example, the external surface **102** of the first frame member **100A** is parallel to, or co-planar to, the external surface **102** of the second frame member **100B**.

[0085] As depicted in FIG. 1 and FIG. 2, in some embodiments, for example, while the first frame member **100A** and the second frame member **100B** are connected, the internal walls **104** of the first frame member **100A** and the second frame member **100B** are co-planar. As depicted in FIG. 1 and FIG. 2, in some embodiments, for example, while the first frame member **100A** and the second frame member **100B** are connected, the external walls **102** of the first frame member **100A** and the

second frame member **100B** are co-planar. In some embodiments, for example, while the coupler **186** is connecting the first frame member **100A** and the second frame member **100B**, with the coupler **186** disposed on the side of the first frame member **100A** and the second frame member **100B** having the internal wall **104**, a surface **200** of the coupler **186** is disposed relative to the co-planar walls of the first frame member **100A** and the second frame member **100B**, such as the surface **200** is co-planar with the co-planar walls of the first frame member **100A** and the second frame member **100B**, as depicted in FIG. 2 and FIG. 4. In some embodiments, for example, the surface **200** is co-planar with the internal walls **104** of the first frame member **100A** and the second frame member **100B**. This may provide the appearance that the internal wall **104** of the first frame member **100A** and the internal wall **104** of the second frame member **100B** is a single continuous internal wall **104**. This may also provide the appearance that no coupler **186** is used or may obscure the coupler **186** from view.

[0086] In some embodiments, for example, the surface **200** is parallel but offset from co-planar walls of the first frame member **100A** and the second frame member **100B** while the first frame member **100A** and the second frame member **100B** are connected. In some embodiments, for example, as depicted in FIG. 1 and FIG. 2, while the coupler **186** is connecting the first frame member **100A** and the second frame member **100B**, with the coupler **186** disposed on the side of the first frame member **100A** and the second frame member **100B** having the external wall **102**, the surface **200** is parallel to but offset from co-planar external walls **102** of the first frame member **100A** and the second frame member **100B**.

[0087] In some embodiments, for example, the first and second frame members **100A**, **100B** are co-operatively configured such that, while: (i) the exterior wall **106** of the first frame member **100A** is disposed opposite to the exterior wall **106** of the second frame member **100B** such that the definition of the seal-receiving channel **130** is effected, (ii) the seal **150** is disposed in the seal-receiving channel **130** as depicted in FIG. 2 and FIG. 4, or the seals **150** are disposed in the seal-receiving channel **130** as depicted in FIG. 9 and FIG. 12, (iii) the one or more seals **150** include a deformable portion **154** configured for deformation in response to compression of the one or more seals **150**; and (iv) the first counterpart **132** of the first frame member **100A** and the second counterpart **134** of the second frame member **100B** are disposed in a sealing interface-defining proximity, compressing of the one or more seals **150** is effected to define a compressed seal **152** such that a sealing interface **160** is established. The one or more compressed seals **152** has at least one deformable portion **154**, as depicted in FIG. 2, FIG. 4, FIG. 9, and FIG. 12. In some embodiments, for example, the deformable portion **154** is a portion of the seal **150** that is configured to extend, protrude, deflect, or deform from the seal **150** due to compression of the seal **150** while the first counterpart **132** of the seal-receiving channel **130** of the first frame member **100A** and the second counterpart **134** of the seal-receiving channel **130** of the second frame member **100B** are disposed in the sealing interface-defining proximity.

[0088] In some embodiments, for example, the one or more compressed seals **152** are compressed at a compression ratio of at least 5%. In some embodiments, for example, the one or more compressed seals **152** are compressed at a compression ratio between 25% and 35%. In some embodiments, for example, the one or more compressed seal **152** are compressed at a compression ratio of 30%.

[0089] In some embodiments, for example, while the first counterpart **132** of the first frame member **100A** and the second counterpart **134** of the second frame member **100B** are disposed in the sealing interface-defining proximity, the deformable portion **154** of the one or more compressed seals **152** are disposed in the seal-receiving channel **130**. In some embodiments, for example, the seal-receiving channel **130** is configured to receive the deformable portion **154** of the one or more compressed seals **152**. In such embodiments, for example, while the first counterpart **132** of the first frame member **100A** and the second counterpart **134** of the second frame member **100B** are disposed in the sealing interface-defining proximity, the deformable portion **154** of the one or more

compressed seals **152** is received in the seal-receiving channel **130**. In some embodiments, for example, the first counterpart **132** of the seal-receiving channel **130** is configured to receive the deformable portion **154** of the one or more compressed seals **152**. In some embodiments, for example, the second counterpart **134** of the seal-receiving channel **130** is configured to receive the deformable portion **154** of the one or more compressed seals **152**. In some embodiments, for example, both the first counterpart **132** and the second counterpart **134** of the seal-receiving channel **130** are configured to receive the deformable portion **154** of the one or more compressed seals **152**. In some embodiments, for example, where two seals **150** are disposed in the seal-receiving channel **130**, as depicted in FIG. **9** and FIG. **12**, the first counterpart **132** of the seal-receiving channel **130** is configured to receive the deformable portion **154** of the first compressed seal **152**, and the second counterpart **134** of the seal-receiving channel **130** is configured to receive the deformable portion **154** of the second compressed seal **152**.

[0090] In some embodiments, for example, the compression of the one or more seals **150** defines the one or more compressed seals **152** having more than one deformable portion **154**. In some embodiments, for example, while the first counterpart **132** of the first frame member **100A** and the second counterpart **134** of the second frame member **100B** are disposed in the sealing interface-defining proximity, the deformable portions **154** are disposed in the seal-receiving channel **130**. In some embodiments, for example, the seal-receiving channel **130** is configured to receive the deformable portions **154** of the one or more compressed seals **152**. In such embodiments, for example, while the first counterpart **132** of the first frame member **100A** and the second counterpart **134** of the second frame member **100B** are disposed in the sealing interface-defining proximity, the deformable portions **154** are received in the seal-receiving channel **130**. In some embodiments, for example, the first counterpart **132** of the seal-receiving channel **130** is configured to receive the deformable portions **154** of the one or more compressed seals **152**. In some embodiments, for example, the second counterpart **134** of the seal-receiving channel **130** is configured to receive the deformable portions **154** of the one or more compressed seals **152**. In some embodiments, for example, both the first counterpart **132** and the second counterpart **134** of the seal-receiving channel **130** are configured to receive the deformable portions **154** of the one or more compressed seals **152**. In some embodiments, for example, where two seals **150** are disposed in the seal-receiving channel **130**, as depicted in FIG. **9** and FIG. **12**, the first counterpart **132** of the seal-receiving channel **130** is configured to receive the deformable portions **154** of the first compressed seal **152**, and the second counterpart **134** of the seal-receiving channel **130** is configured to receive the deformable portions **154** of the second compressed seal **152**.

[0091] In some embodiments, for example, the first frame member **100A** and the second frame member **100B** are co-operatively configured such that while: (i) the one or more seals **150** are disposed in the seal-receiving channel **130**, and the first counterpart **132** of the seal-receiving channel **130** of the first frame member **100A** and the second counterpart **134** of the seal-receiving channel **130** of the second frame member **100B** are disposed in the sealing interface-defining proximity to define the sealing interface **160**, (ii) the one or more seals **150** are compressed to define the one or more compressed seals **152**, and (iii) the deformable portion **154** is received in the seal-receiving channel **130**, the exterior wall **106** of the first frame member **100A** and the exterior wall **106** of the second frame member **100B** are aligned. In some embodiments, for example, the exterior wall **106** of the first frame member **100A** and the exterior wall **106** of the second frame member **100B** are co-operatively configured to align the first frame member **100A** and the second frame member **100B**. While the exterior wall **106** of the first frame member **100A** and the exterior wall **106** of the second frame member **100B** are aligned, the exterior wall **106** of the first frame member **100A** and the exterior wall **106** of the second frame member **100B** are parallel. In some embodiments, for example, while the first frame member **100A** and the second frame member **100B** are aligned, a longitudinal axis **101A** defined by the first frame member **100A** and a longitudinal axis **101B** defined by the second frame member **100B** are parallel.

[0092] In some embodiments, for example, the first frame member **100A** and the second frame member **100B** are co-operatively configured such that while: (i) the one or more seals **150** are disposed in the seal-receiving channel **130**, and the first counterpart **132** of the seal-receiving channel **130** of the first frame member **100A** and the second counterpart **134** of the seal-receiving channel **130** of the second frame member **100B** are disposed in the sealing interface-defining proximity to define the sealing interface **160**, (ii) the one or more seals **150** are compressed to define the one or more compressed seals **152**, and (iii) the seal deformation portion **154** is received in the seal-receiving channel **130**, the exterior wall **106** of the first frame member **100A** and the exterior wall **106** of the second frame member **100B** are co-operatively configured to resist relative moment of one of the first frame member **100A** and the second frame member **100B** towards the other of the first frame member **100A** and the second frame member **100B**.

[0093] In some embodiments, for example, the first frame member **100A** and the second frame member **100B** are co-operatively configured such that while: (i) the one or more seals **150** are disposed in the seal-receiving channel **130**, and the first counterpart **132** of the seal-receiving channel **130** of the first frame member **100A** and the second counterpart **134** of the seal-receiving channel **130** of the second frame member **100B** are disposed in the sealing interface-defining proximity to define the sealing interface **160**, (ii) the one or more seals **150** are compressed to define the one or more compressed seals **152**, and (iii) the deformable portion **154** is received in the seal-receiving channel **130**, the exterior wall **106** of the first frame member **100A** and the exterior wall **106** of the second frame member **100B** are disposed in an engagement relationship, for example, in an abutting relationship. With the first frame member **100A** and the exterior wall **106** of the second frame member **100B** are disposed in an engagement relationship, for example, in an abutting relationship, the first frame member **100A** and the second frame member **100B** are relatively disposed to remain in such relative disposition, such that the first frame member **100A** and the second frame member **100B** are connectable together, and to facilitate installation of a first window frame, having the first frame member **100A**, adjacent to a second window frame, having the second frame member **100B**. In some embodiments, for example, the first frame member **100A** and the second frame member **100B** are co-operatively configured such that, while the sealing interface **160** is established, the exterior wall **106** of the first frame member **100A** and the exterior wall **106** of the second frame member **100B** are disposed in an abutting relationship.

[0094] In some embodiments, for example, the seal-receiving channel **130**, by being configured to receive the one or more deformable portions **154** of the one or more compressed seals **152**, permits the exterior wall **106** of the first frame member **100A** and the exterior wall **106** of the second frame member **100B** to be disposed in the engagement relationship, for example, in the abutting relationship.

[0095] In this regard, while: (i) the one or more seals **150** are disposed in the seal-receiving channel **130**, and the first counterpart **132** of the seal-receiving channel **130** of the first frame member **100A** and the second counterpart **134** of the seal-receiving channel **130** of the second frame member **100B** are disposed in the sealing interface-defining proximity to define the sealing interface **160**, (ii) the one or more seals **150** are compressed to define the one or more compressed seals **152**, and (iii) the deformable portion **154** is received in the seal-receiving channel **130**, the first frame member **100A** and the second frame member **100B** are relatively disposed to remain in such relative disposition, such that the first frame member **100A** and the second frame member **100B** are connectable together, and to facilitate installation of a first window frame, having the first frame member **100A**, adjacent to a second window frame, having the second frame member **100B**.

[0096] As depicted in FIGS. 2 to 6, 10, and 12, in some embodiments, for example, at least one of the first counterpart **132** of the first frame member **100A** and the second counterpart **134** of the second frame member **100B** includes a slot **136** for retaining a seal **150** relative to the respective at least one of the first and second frame members **100A**, **100B**. The first and second frame members **100A**, **100B** are co-operatively configured such that, while: (i) the exterior wall **106** of the first

frame member **100A** is disposed opposite to the exterior wall **106** of the second frame member **100B** such that the definition of the seal-receiving channel **130** is effected, (ii) the first counterpart **132** of the first frame member **100A** and the second counterpart **134** of the second frame member **100B** are disposed in a sealing interface-defining proximity, (iii) the seal **150** is disposed in the seal-receiving channel **130**; and (iv) the retention of the seal **150** is being effected by the slot **136**, the sealing interface is established between the first and second frame members **100A** and **100B**. In some embodiments, for example, where at least one of the first frame member **100A** and the second frame member **100B** includes the slot **136**, the at least one of the first frame member **100A** and the second frame member **100B** is connectable with the seal **150** via an interaction of the slot **136** and the connector **156** of the seal **150**.

[0097] As depicted in FIGS. **2** to **6**, **10**, and **12**, in some embodiments, for example, the seal **150** includes a connector **156**, and at least one of the first counterpart **132** of the seal-receiving channel **130** of the first frame member **100A** and the second counterpart **134** of the seal-receiving channel **130** of the second frame member **100B** includes the slot **136** that is configured to receive the connector **156** of the seal **150** for effecting retention of the seal **150** relative to the at least one of the first and second frame members **100A**, **100B**. In some embodiments, for example, while the connector **156** of the seal **150** is received in the slot **136**, the seal **150** is connected to the at least one of the first frame member **100A** and the second frame member **100B** that includes the slot **136**.

[0098] In some embodiments, for example, the first and second frame members **100A**, **100B** are co-operatively configured such that, while: (i) the exterior wall **106** of the first frame member **100A** is disposed opposite to the exterior wall **106** of the second frame member **100B** such that the definition of the seal-receiving channel **130** is effected, and (ii) and the retention of the seal **150** relative to the at least one of the first and second frame members **100A**, **100B** is effected, the seal **150** is disposed in the seal receiving channel **130**.

[0099] In some embodiments, for example, the slot **136** is configured to releasably receive the connector **156** of the seal **150** for effecting retention of the seal **150** relative to the at least one of the first and second frame members **100A**, **100B**, such that after the connector **156** is received in the slot **136**, the connector **156** may be removed or released from the slot **136**.

[0100] In some embodiments, for example, the slot **136** of the at least one of the first counterpart **132** of the first frame member **100A** and the second counterpart **134** of the second frame member **100B** is configured to slidably receive the connector **156** of the seal **150** for effecting retention of the seal **150** relative to the at least one of the first and second frame members **100A**, **100B**.

[0101] In some embodiments, for example, the connector **156** is pushed into the slot **136** to connect the frame member **100** and the seal **150**, and the connector **156** is pulled out of the slot **136** to disconnect the frame member **100** and the seal **150**.

[0102] In some embodiments, for example, the connector **156** of the seal **150** is a t-shaped connector, and the slot **136** of the at least one of the first counterpart **132** of the first frame member **100A** and the second counterpart **134** of the second frame member is **100B** a t-slot. In such embodiments, for example, the t-shaped connector may be slidably received in the t-slot and may be slidably removed or released from the t-slot.

[0103] While the connector **156** of the seal **150** is received in the slot **136** of the at least one of the first counterpart **132** of the first frame member **100A** and the second counterpart **134** of the second frame member **100B** such that the retention of the seal **150** relative to the at least one of the first and second frame members **100A**, **100B** is effected, in some embodiments, for example, the sealing interface **160** is defined between the seal **150** and the at least one of the first counterpart **132** of the first frame member **100A** and the second counterpart **134** of the second frame member **100B**.

[0104] In some embodiments, for example, both of the first frame member **100A** and the second frame member **100B** include the slot **136**, as depicted in FIGS. **2** to **5**, for effecting retention of one or more seals **150** relative to the first and second frame members **100A**, **100B**. In such embodiments, either one of the first frame member **100A** and the second frame member **100B** is

connectable with the seal **150** via an interaction of the slot **136** of the first frame member **100A** and the second frame member **100B** and the connector **156** of the seal **150**. In some embodiments, for example, the seal **150** includes two connectors **156**, such that the seal **150** is connectable with both of the first frame member **100A** and the second frame member **100B** via: (i) a first interaction of the slot **136** of the first frame member **100A** and a first connector **156** of the seal **150**, and (ii) a second interaction of the slot **136** of the second frame member **100B** and a second connector **156** of the seal **150**. In some embodiments, for example, the connectors **156** are slidably received in the slots **136** of the first frame member **100A** and the second frame member **100B** for effecting retention of the seal **150** relative to the first and second frame members **100A**, **100B**.

[0105] In some embodiments, for example, where both of the first frame member **100A** and the second frame member **100B** include the slot **136**, as depicted in FIGS. 9-12, for effecting retention of one or more seals **150** relative to the first and second frame members **100A**, **100B**, each of the first frame member **100A** and the second frame member **100B** are connectable with a respective seal **150**, via an interaction of the slot **136** of the first frame member **100A** and the connector **156** of the first seal **150**, and via an interaction of the slot **136** of the second frame member **100B** and the connector **156** of the second seal **150**.

[0106] In some embodiments, for example, the seal **150** is a bulb seal, a gasket seal, an o-shape seal, a push-in seal, a push-in extruded seal, a t-slot mount seal, a weather strip, and the like.

[0107] FIG. 7 is a flow chart depicting a method **300** of assembling a window assembly.

[0108] At **302**, the first frame member **100A** and the second frame member **100B** are relatively disposed to define the seal-receiving channel **130**. In some embodiments, for example, the exterior wall **106** of the first frame member **100A** is disposed opposite to the exterior wall **106** of the second frame member **100B** to define the seal-receiving channel **130**.

[0109] At **304**, while the seal-receiving channel **130** is defined, the seal **150** is disposed in the seal-receiving channel **130**. In some embodiments, for example, the seal **150** is connected to at least one of the first frame member **100A** and the second frame member **100B** for retaining the seal **150** relative to at least one of the first frame member **100A** and the second frame member **100B**, such that the seal **150** remains disposed in the seal-receiving channel **130**. In some embodiments, for example, the seal **150** includes at least one connector **156**, and at least one, or both, of the first frame member **100A** and the second frame member **100B** includes the slot **136** for effecting retention of the seal **150** relative to the first frame member **100A** and the second frame member **100B**. In such embodiments, the seal **150** is connectable to at least one, or both, of the first frame member **100a** and the second frame member **100B** via interaction with the at least one connector **156** and the at least one slot **136**. In some embodiments, for example, the seal **150** is connected to at least one of the first frame member **100a** and the second frame member **100B** prior to relative disposition of the first frame member **100A** and the second frame member **100B** to define the seal-receiving channel **130**.

[0110] At **306**, with the seal **150** disposed in the seal-receiving channel **130**, the first frame member **100A** and the second frame member **100B** are disposed in the sealing interface-defining proximity to define the sealing interface **160**. In some embodiments, for example, the sealing interface **160** is defined between at least one of the first counterpart **132** of the seal-receiving channel **130** and the second counterpart **134** of the seal-receiving channel **130**. In some embodiments, for example, one or more sealing interfaces **160** are defined between at least one of the first counterpart **132** of the seal-receiving channel **130** and the second counterpart **134** of the seal-receiving channel **130**. In some embodiments, for example, the sealing interface **160** is defined between both of the first counterpart **132** of the seal-receiving channel **130** and the second counterpart **134** of the seal-receiving channel **130**. In some embodiments, for example, one or more sealing interfaces **160** are defined between both of the first counterpart **132** of the seal-receiving channel **130** and the second counterpart **134** of the seal-receiving channel **130**.

[0111] In some embodiments, for example, while the seal **150** is disposed in the seal-receiving

channel **130**, and the first counterpart **132** of the first frame member **100A** and the second counterpart **134** of the second frame member **100B** are disposed in the sealing interface-defining proximity, to define the sealing interface **160**, the seal **150** is compressed to define the compressed seal **152**, the compressed seal **152** having the one or more deformable portions **154**.

[0112] With the first counterpart **132** of the first frame member **100A** and the second counterpart **134** of the second frame member **100B** are disposed in the sealing interface-defining proximity, and with the sealing interface **160** defined, the window assembly is assembled.

[0113] While the seal **150** is compressed to define the compressed seal **152**, in some embodiments, for example, the one or more deformable portions **154** is received in the seal-receiving channel **130**, such that the exterior wall **106** of the first frame member **100A** and the exterior wall **106** of the second frame member **100B** are disposable in an abutting relationship.

[0114] At **308**, while the seal **150** is compressed to define the compressed seal **152**, and while the exterior wall **106** of the first frame member **100A** and the exterior wall **106** of the second frame member **100B** are disposed in an abutting relationship, the first frame member **100A** and the second frame member **100B** are connectable together, for example, using appropriate fasteners, such as nuts and bolts, screws, nails, pegs, adhesives, welding, and the like, or connected together using a snap-fit connection, a friction fit connection, an interference connection, and the like. In some embodiments, for example, the first frame member **100A** and the second frame member **100B** include the first counterpart **182** of the connecting mechanism **180**, the coupler **186** has the second counterpart **184** of the connecting mechanism **180**, and the first frame member **100A** and the second frame member **100B** are connectable via the coupler **186**.

[0115] In some embodiments, for example, where the first frame member **100A** and the second frame member **100B** are part of adjacent first and second window frames to be installed in a wall of a room, the first frame member **100A** and the second frame member **100B** may be disposed in a side-by-side relationship, or may be disposed one above the other.

[0116] In some embodiments, for example, a kit for a window assembly or parts for a window assembly includes the first frame member **100A** and the second frame member **100B**.

[0117] In some embodiments, for example, while the seal **150** is disposed in the seal-receiving channel **130**, and the first frame member **100A** and the second frame member **100B** are installed as part of first and second window frames, the sealing interface **160** defined between the first frame member **100A** and the second frame member **100B** may resist fluid communication through the space between the frame members **100** between the inside of the room and the outside of the room. In some embodiments, for example, while the seal **150** is disposed in the seal-receiving channel **130**, and the first frame member **100A** and the second frame member **100B** are installed as part of first and second window frames, the sealing interface **160** defined between the first frame member **100A** and the second frame member **100B** may resist fluid ingress through the space between the frame members **100** between the inside of the room and the outside of the room.

[0118] In addition, while the sealing interface **160** defined between the first frame member **100A** and the second frame member **100B**, the quality of insulation between the first frame member **100A** and the second frame member **100B** may be improved, such that excessive heating or cooling of the room to maintain a desired temperature may be avoided, thereby saving the energy that may be used for said excessive heating or cooling of the room.

[0119] Moreover, the seal **150** disposed in the seal-receiving channel **130** may prevent or mitigate ingress of debris between the frame members **100** and into the room.

[0120] Further, the connection system used to connect the first frame member **100A** and the second frame member **100B** may provide a connection between the first frame member **100A** and the second frame member **100B** that may be more reliable than those provided by existing connection systems between frame members.

[0121] Additionally, a connection system other than existing connection systems may be used to connect the first frame member **100A** and the second frame member **100B**. By being able to use a

connection system to connect the first frame member **100A** and the second frame member **100B** that may be different from existing connection systems, the design and cost limitations of such existing connecting systems may be absent, such that windows frames of different sizes and configurations may be designed.

[0122] FIGS. **8** to **12** depict an example window assembly **50**, which includes a first frame member **500A** and a second frame member **500B**. The first frame member **500A** substantially corresponds to the first frame member **100A**, and the second frame member **500B** substantially corresponds to the second frame member **100B**, except the first frame member **500A** has a first counterpart **532** of the seal-receiving channel **130** that is at an angled configuration relative to the exterior wall **106** of the first frame member **500A**, and the second frame member **500B** has a second counterpart **534** of the seal-receiving channel **130** that is at an angled configuration relative to the second counterpart **134** of the second frame member **100B**. As depicted in FIG. **11**, a longitudinal axis **542** defined by the first counterpart **532** of the seal-receiving channel **130** is disposed at an acute angle θ between 0 degrees and 60 degrees, for example, between 0 degrees and 45 degrees, for example, between 5 degrees and 50 degrees, for example, between 10 degrees and 40 degrees, relative to the normal axis **140** of the exterior wall **106** of the first frame member **500A**, and the longitudinal axis **546** defined by a second counterpart **534** of the seal-receiving channel **130** is disposed at an acute angle β between 0 degrees and 60 degrees, for example, between 0 degrees and 45 degrees, for example, between 5 degrees and 50 degrees, for example, between 10 degrees and 40 degrees, relative to the normal axis **144** of the exterior wall **106** of the second frame member **500B**. In some embodiments, for example, the angles θ and β have the same magnitude. In some embodiments, for example, the angles θ and β have different magnitudes. In some embodiments, for example, the angle θ is 30 degrees. In some embodiments, for example, the angle θ is 45 degrees. In some embodiments, for example, the angle θ is 60 degrees. In some embodiments, for example, the angle β is 30 degrees. In some embodiments, for example, the angle β is 45 degrees. In some embodiments, for example, the angle β is 60 degrees.

[0123] As depicted in FIGS. **9**, **10**, and **12**, at least one, or both, of the first frame member **500A** and the second frame member **500B** includes the slot **536** that is configured to receive the connector **156** of the seal **150**, for effecting retention of one or more seals **150** relative to the first and second frame members **500A**, **500B**. The slot **536** of the first frame member **500A** and the second frame member **500B** substantially corresponds to the slot **136** of the first frame member **100A** and the second frame member **100B**.

[0124] As depicted in FIG. **10**, the first counterpart **532** of the seal-receiving channel **130** of the first frame member **500A** includes a first sealing interface-defining wall **570** and a second sealing interface-defining wall **572**, and the second counterpart **534** of the seal-receiving channel **130** of the second frame member **500B** includes a first sealing interface-defining wall **574** and a second sealing interface-defining wall **576**. The first sealing interface-defining wall **570** and a second sealing interface-defining wall **572** of the first frame member **500A** substantially correspond to the first sealing interface-defining wall **170** and a second sealing interface-defining wall **172** of the first frame member **100A**, and the first sealing interface-defining wall **574** and the second sealing interface-defining wall **576** of the second frame member **500B** substantially correspond to the first sealing interface-defining wall **174** and the second sealing interface-defining wall **176** of the second frame member **100B**.

[0125] In some embodiments, for example, a seal **150** is disposable within the seal-defining channel **130** defined by the first frame member **500A** and the second frame member **500A**, such that the sealing interface **160** is definable between the seal **150** and at least one of, or both of, the first counterpart **532** of the seal-receiving channel **130** and the second counterpart **534** of the seal-receiving channel **130**. As depicted in FIGS. **9** to **12**, in some embodiments, for example, two seals **150** are disposable in the seal-receiving channel **130**. In such embodiments, for example, the sealing interface **160** is definable between the first seal **150** and the second seal **150**, and between:

(a) the first seal **150** and the second seal **150**, and (b) at least one of, or both of, the first counterpart **532** of the seal-receiving channel **130** and the second counterpart **534** of the seal-receiving channel **130**.

[0126] As depicted in FIG. **10**, the first counterpart **532** of the seal-receiving channel **130** of the first frame member **500A** includes a first sealing interface-defining wall **570** and a second sealing interface-defining wall **572**, and the second counterpart **534** of the seal-receiving channel **130** of the second frame member **500B** includes a first sealing interface-defining wall **574** and a second sealing interface-defining wall **576**. The first sealing interface-defining wall **570** and a second sealing interface-defining wall **572** of the first frame member **500A** substantially correspond to the first sealing interface-defining wall **170** and a second sealing interface-defining wall **172** of the first frame member **100A**, and the first sealing interface-defining wall **574** and the second sealing interface-defining wall **576** of the second frame member **500B** substantially correspond to the first sealing interface-defining wall **174** and the second sealing interface-defining wall **176** of the second frame member **100B**. In some embodiments, for example, the sealing interface **160** is definable between the one or more seals **150** disposed in the seal-receiving channel **130**, and one or more of the first sealing interface-defining wall **570**, the second sealing interface-defining wall **572**, the first sealing interface-defining wall **574**, and the second sealing interface-defining wall **576**.

[0127] The preceding discussion provides many example embodiments. Although each embodiment represents a single combination of inventive elements, other examples may include all suitable combinations of the disclosed elements. Thus if one embodiment comprises elements A, B, and C, and a second embodiment comprises elements B and D, other remaining combinations of A, B, C, or D, may also be used.

[0128] The term “connected” or “coupled to” may include both direct coupling (in which two elements that are coupled to each other contact each other) and indirect coupling (in which at least one additional element is located between the two elements).

[0129] Although the embodiments have been described in detail, it should be understood that various changes, substitutions and alterations could be made herein.

[0130] Moreover, the scope of the present application is not intended to be limited to the particular embodiments of the process, machine, manufacture, and composition of matter, means, methods and steps described in the specification. As one of ordinary skill in the art will readily appreciate from the disclosure of the present invention, processes, machines, manufacture, compositions of matter, means, methods, or steps, presently existing or later to be developed, that perform substantially the same function or achieve substantially the same result as the corresponding embodiments described herein may be utilized. Accordingly, the appended claims are intended to include within their scope such processes, machines, manufacture, compositions of matter, means, methods, or steps.

[0131] As can be understood, the examples described above and illustrated are intended to be examples only. The invention is defined by the appended claims.

Claims

1.-69. (Canceled)

70. A kit for a window assembly, comprising: a first frame member that includes: an exterior wall, defining: a seal-receiving channel first counterpart that includes a first seal retainer; and an outermost surface; an interior wall that is disposed on an opposite side of the first frame member relative to the exterior wall; and a pane-receiving space, defined by the interior wall, that is configured to receive a glass pane; a second frame member that includes: an exterior wall, defining: a seal-receiving channel second counterpart that includes a second seal retainer; and an outermost surface; an interior wall that is disposed on an opposite side of the second frame member relative to the exterior wall; and a pane-receiving space, defined by the interior wall, that is configured to

receive a glass pane; wherein: the first seal retainer of the first frame member is configured for interacting with a seal to effectuate retention of the seal to the first frame member, and the second seal retainer of the second frame member is configured for interacting with the seal to effectuate retention of the seal to the second frame member, such that the seal is retainable to either one of: (a) the first frame member via the first seal retainer, and (b) the second frame member via the second seal retainer; the first and second frame members are co-operatively configured such that, while the exterior wall of the first frame member is disposed opposite to the exterior wall of the second frame member for assembling the window assembly: the seal-receiving channel first counterpart is disposed opposite to the seal-receiving channel second counterpart, and co-operate to define a seal receiving channel; the outermost surface of the exterior wall of the first frame member is disposed adjacent to the outermost surface of the exterior wall of the second frame member, and co-operate such that relative rotation, between the first frame member and the second frame member, about an axis of rotation that is parallel to a longitudinal axis of the first frame member, is opposed by the outermost surface of the exterior wall of the first frame member and the outermost surface of the exterior wall of the second frame member; and the seal-receiving channel is configured for disposition of the seal therein.

71. The kit of claim 70, wherein: the first and second frame members are further co-operatively configured such that, while: (i) the exterior wall of the first frame member is disposed opposite to the exterior wall of the second frame member for assembling the window assembly, such that the definition of the seal-receiving channel is effected, and the relative rotation, between the first frame member and the second frame member, about the axis of rotation, is opposed by the outermost surface of the exterior wall of the first frame member and the outermost surface of the exterior wall of the second frame member, (ii) the seal-receiving channel first counterpart of the first frame member and the seal-receiving channel second counterpart of the second frame member are disposed in a sealing interface-defining proximity, (iii) the seal is retained to the either one of: (a) the first frame member via the first seal retainer, and (b) the second frame member via the second seal retainer, and (iv) the seal is disposed in the seal-receiving channel: a sealing interface is established between the first and second frame members.

72. The kit of claim 71, wherein: the first frame member and the second frame member are further co-operatively configured such that, while the sealing interface is established, the outermost surface of the exterior wall of the first frame member and the outermost surface of the exterior wall of the second frame member are disposed in contact engagement.

73. The kit of claim 71, wherein: the defining of the sealing interface is effected between the seal, the seal-receiving channel first counterpart of the first frame member, and the seal-receiving channel second counterpart of the second frame member.

74. The kit of claim 71, wherein: while the seal-receiving channel first counterpart of the first frame member and the seal-receiving channel second counterpart of the second frame member are disposed in the sealing interface-defining proximity, the first frame member and the second frame member are connectable.

75. The kit of claim 70, wherein: the first and second frame members are further co-operatively configured such that, while: (i) the exterior wall of the first frame member is disposed opposite to the exterior wall of the second frame member for assembling the window assembly, such that the definition of the seal-receiving channel is effected, and the relative rotation, between the first frame member and the second frame member, about the axis of rotation, is opposed by the outermost surface of the exterior wall of the first frame member and the outermost surface of the exterior wall of the second frame member, (ii) the seal is retained to the either one of: (a) the first frame member via the first seal retainer, and (b) the second frame member via the second seal retainer, (iii) the seal is disposed in the seal-receiving channel, (iv) the seal includes a deformable portion configured for deformation in response to compression of the seal, and the seal-receiving channel is configured to receive the deformable portion of the compressed seal; and (v) the seal-receiving channel first

counterpart of the first frame member and the seal-receiving channel second counterpart of the second frame member are disposed in a sealing interface-defining proximity: compressing of the seal is effected to define a compressed seal such that a sealing interface is established; and the deformable portion of the seal is deformed, and is received in the seal-receiving channel.

76. The kit of claim 70, wherein the first frame member and the second frame member are extruded lineals.

77. The kit of claim 70, wherein the first frame member is a frame member of a first frame, and the second frame member is a frame member of a second frame.

78. The kit of claim 70, wherein: the retainability of the seal to the either one of: (a) the first frame member via the first seal retainer, and (b) the second frame member via the second seal retainer, is such that the seal is retainable to both of: (a) the first frame member via the first seal retainer, and (b) the second frame member via the second seal retainer.

79. The kit of claim 70, wherein: the seal is a first seal; the first seal retainer of the first frame member is configured for interacting with the first seal to effectuate retention of the first seal to the first frame member, the second seal retainer of the second frame member is configured for interacting with a second seal to effectuate retention of the second seal to the second frame member, such that the first seal is retainable to the first frame member via the first seal retainer, and the second seal is retainable to the second frame member via the second seal retainer; the seal receiving channel is configured for disposition of the first seal and the second seal therein; and the first and second frame members are further co-operatively configured such that, while: (i) the exterior wall of the first frame member is disposed opposite to the exterior wall of the second frame member for assembling the window assembly, such that the definition of the seal-receiving channel is effected, and the relative rotation, between the first frame member and the second frame member, about the axis of rotation, is opposed by the outermost surface of the exterior wall of the first frame member and the outermost surface of the exterior wall of the second frame member, (ii) the seal-receiving channel first counterpart of the first frame member and the seal-receiving channel second counterpart of the second frame member are disposed in a sealing interface-defining proximity, (iii) the first seal is retained to the first frame member via the first seal retainer and the second seal is retained to the second frame member via the second seal retainer, and (iv) the first seal and the second seal are disposed in the seal-receiving channel: a sealing interface is established between the first and second seals.

80. The kit of claim 70, wherein: the opposition of the relative rotation, between the first frame member and the second frame member, about the axis of rotation, by the outermost surface of the exterior wall of the first frame member and the outermost surface of the exterior wall of the second frame member, is a prevention of the relative rotation, between the first frame member and the second frame member, about the axis of rotation, by the outermost surface of the exterior wall of the first frame member and the outermost surface of the exterior wall of the second frame member.

81. A kit for a window assembly, comprising: a first frame member that includes: an exterior wall, defining: a seal-receiving channel first counterpart that includes a first seal retainer; and an outermost surface; an interior wall that is disposed on an opposite side of the first frame member relative to the exterior wall; and a glass stop-receiving channel, defined by the interior wall, that is configured to receive a glass stop; a second frame member that includes: an exterior wall, defining: a seal-receiving channel second counterpart that includes a second seal retainer; and an outermost surface; an interior wall that is disposed on an opposite side of the second frame member relative to the exterior wall; and a glass stop-receiving channel, defined by the interior wall, that is configured to receive a glass stop; wherein: the first seal retainer of the first frame member is configured for interacting with a seal to effectuate retention of the seal to the first frame member, and the second seal retainer of the second frame member is configured for interacting with the seal to effectuate retention of the seal to the second frame member, such that the seal is retainable to either one of: (a) the first frame member via the first seal retainer, and (b) the second frame member via the

second seal retainer; the first and second frame members are co-operatively configured such that, while the exterior wall of the first frame member is disposed opposite to the exterior wall of the second frame member for assembling the window assembly: the seal-receiving channel first counterpart is disposed opposite to the seal-receiving channel second counterpart, and co-operate to define a seal receiving channel; the outermost surface of the exterior wall of the first frame member is disposed adjacent to the outermost surface of the exterior wall of the second frame member, and co-operate such that relative rotation, between the first frame member and the second frame member, about an axis of rotation that is parallel to a longitudinal axis of the first frame member, is opposed by the outermost surface of the exterior wall of the first frame member and the outermost surface of the exterior wall of the second frame member; and the seal-receiving channel is configured for disposition of the seal disposed therein.

82. The kit of claim 81, wherein: the retainability of the seal to the either one of: (a) the first frame member via the first seal retainer, and (b) the second frame member via the second seal retainer, is such that the seal is retainable to both of: (a) the first frame member via the first seal retainer, and (b) the second frame member via the second seal retainer.

83. The kit of claim 81, wherein: the opposition of the relative rotation, between the first frame member and the second frame member, about the axis of rotation, by the outermost surface of the exterior wall of the first frame member and the outermost surface of the exterior wall of the second frame member, is a prevention of the relative rotation, between the first frame member and the second frame member, about the axis of rotation, by the outermost surface of the exterior wall of the first frame member and the outermost surface of the exterior wall of the second frame member.

84. A window assembly, comprising: a first frame member that includes: an exterior wall, defining: a seal-receiving channel first counterpart that includes a first seal retainer; and an outermost surface; an interior wall that is disposed on an opposite side of the first frame member relative to the exterior wall; and a pane-receiving space, defined by the interior wall, that is configured to receive a glass pane; a second frame member that includes: an exterior wall, defining: a seal-receiving channel second counterpart that includes a second seal retainer; and an outermost surface; an interior wall that is disposed on an opposite side of the second frame member relative to the exterior wall; and a pane-receiving space, defined by the interior wall, that is configured to receive a glass pane; wherein: the first seal retainer of the first frame member is configured for interacting with a seal to effectuate retention of the seal to the first frame member, and the second seal retainer of the second frame member is configured for interacting with the seal to effectuate retention of the seal to the second frame member, such that the seal is retainable to either one of: (a) the first frame member via the first seal retainer, and (b) the second frame member via the second seal retainer; the first and second frame members are co-operatively configured such that, while the exterior wall of the first frame member is disposed opposite to the exterior wall of the second frame member for assembling the window assembly: the seal-receiving channel first counterpart is disposed opposite to the seal-receiving channel second counterpart, and co-operate to define a seal receiving channel; the outermost surface of the exterior wall of the first frame member is disposed adjacent to the outermost surface of the exterior wall of the second frame member, and co-operate such that relative rotation, between the first frame member and the second frame member, about an axis of rotation that is parallel to a longitudinal axis of the first frame member, is opposed by the outermost surface of the exterior wall of the first frame member and the outermost surface of the exterior wall of the second frame member; and while: (i) the seal is retained to the either one of: (a) the first frame member via the first seal retainer, and (b) the second frame member via the second seal retainer, and (ii) the exterior wall of the first frame member is disposed opposite to the exterior wall of the second frame member, such that the seal receiving channel is defined and the relative rotation, between the first frame member and the second frame member, about the axis of rotation, is opposed, by the outermost surface of the exterior wall of the first frame member and the outermost surface of the exterior wall of the second frame member, the seal is disposed in the seal

receiving channel.

85. The window assembly of claim 84, wherein: the retainability of the seal to the either one of: (a) the first frame member via the first seal retainer, and (b) the second frame member via the second seal retainer, is such that the seal is retainable to both of: (a) the first frame member via the first seal retainer, and (b) the second frame member via the second seal retainer; and while: (i) the seal is retained to the both of: (a) the first frame member via the first seal retainer, and (b) the second frame member via the second seal retainer, and (ii) the exterior wall of the first frame member is disposed opposite to the exterior wall of the second frame member for assembling the window assembly such that the seal receiving channel is defined, the seal is disposed in the seal receiving channel.

86. The window assembly of claim 84, wherein: the opposition of the relative rotation, between the first frame member and the second frame member, about the axis of rotation, by the outermost surface of the exterior wall of the first frame member and the outermost surface of the exterior wall of the second frame member, is a prevention of the relative rotation, between the first frame member and the second frame member, about the axis of rotation, by the outermost surface of the exterior wall of the first frame member and the outermost surface of the exterior wall of the second frame member.

87. A window assembly, comprising: a first frame member, including an exterior wall that defines a seal-receiving channel first counterpart that includes a first seal retainer and further defines an outermost surface, and a second frame member, including an exterior wall that defines a seal-receiving channel second counterpart that includes a second seal retainer and further defines an outermost surface; the seal-receiving channel first counterpart of the first frame member is configured to be disposed in opposition to the seal-receiving channel second counterpart of the second frame member, with effect that: a seal-receiving channel is defined, the seal-receiving channel configured for disposition of a seal therein; and the outermost surface of the exterior wall of the first frame member is configured to be disposed adjacent to the outermost surface of the exterior wall of the second frame member, with effect that: the outermost surface of the exterior wall of the first frame member and the outermost surface of the exterior wall of the second frame member co-operate such that relative rotation, between the first frame member and the second frame member, about an axis of rotation that is parallel to a longitudinal axis of the first frame member, is opposed by the outermost surface of the exterior wall of the first frame member and the outermost surface of the exterior wall of the second frame member; wherein: the first seal retainer of the first frame member is configured for interacting with the seal to effectuate retention of the seal to the first frame member, and the second seal retainer of the second frame member is configured for interacting with the seal to effectuate retention of the seal to the second frame member, such that the seal is retainable to either one of: (a) the first frame member via the first seal retainer, and (b) the second frame member via the second seal retainer; and while: (i) the seal is retained to the either one of: (a) the first frame member via the first seal retainer, and (b) the second frame member via the second seal retainer, and (ii) the one of the first frame member and the second frame member is disposed, relative to the other one of the first frame member and the second frame member, for assembling the window assembly, such that the seal-receiving channel first counterpart of the first frame member is disposed in opposition to the seal-receiving channel second counterpart of the second frame member such that the seal-receiving channel is defined, and the outermost surface of the exterior wall of the first frame member is disposed adjacent to the outermost surface of the exterior wall of the second frame member, such that the relative rotation, between the first frame member and the second frame member, about the axis of rotation, is opposed by the exterior wall of the first frame member and the exterior wall of the second frame member, the seal is disposed in the seal receiving channel.

88. The window assembly of claim 87, wherein: the retainability of the seal to the either one of: (a) the first frame member via the first seal retainer, and (b) the second frame member via the second

seal retainer, is such that the seal is retainable to both of: (a) the first frame member via the first seal retainer, and (b) the second frame member via the second seal retainer; and while: (i) the seal is retained to the both of: (a) the first frame member via the first seal retainer, and (b) the second frame member via the second seal retainer, and (ii) the exterior wall of the first frame member is disposed opposite to the exterior wall of the second frame member for assembling the window assembly such that the seal receiving channel is defined, the seal is disposed in the seal receiving channel.

89. The window assembly of claim 87, wherein: the opposition of the relative rotation, between the first frame member and the second frame member, about the axis of rotation, by the outermost surface of the exterior wall of the first frame member and the outermost surface of the exterior wall of the second frame member, is a prevention of the relative rotation, between the first frame member and the second frame member, about the axis of rotation, by the outermost surface of the exterior wall of the first frame member and the outermost surface of the exterior wall of the second frame member.
