

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250284545

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

Cheung; Dennis et al.

SYSTEMS AND METHODS FOR DETERMINING TARGET ALLOCATION PARAMETERS FOR INITIATING TARGETED COMMUNICATIONS IN COMPLEX COMPUTING NETWORKS

Abstract

This disclosure is directed to systems and methods for determining target allocation parameters for initiating targeted communications in complex computing networks, which may be associated with the allocation of allocatables in execution events over a period of time. The systems and methods may include receiving a desired allocation; determining a first available allocation at a first time; generating allocation information for a second period comprising the first time; determining a second available allocation at a second time; determining a remaining available allocation, based on the allocation information and the second available allocation; and determining one or more target allocation parameters for initiating a targeted communication to a computing device after the second time.

Inventors: Cheung; Dennis (Belmont, CA), Karampelas; Konstantinos (London, GB),
Schaefer; Alexander L. (Boulder, CO), Sourbut; Oliver J.S. (Bath, GB)

Applicant: THE TRADE DESK, INC. (Ventura, CA)

Family ID: 1000008619491

Appl. No.: 19/214907

Filed: May 21, 2025

Related U.S. Application Data

parent US continuation 19007241 20241231 parent-grant-document US 12353918 child US
19214907

parent US continuation 18830410 20240910 parent-grant-document US 12260254 child US
19007241

parent US continuation 18587648 20240226 parent-grant-document US 12099877 child US
18830410

parent US continuation 18214321 20230626 parent-grant-document US 11915052 child US 18587648
parent US continuation 17228569 20210412 parent-grant-document US 11687371 child US 18214321
parent US continuation 16716453 20191216 parent-grant-document US 10977084 child US 17228569

Publication Classification

Int. Cl.: **G06F9/50** (20060101); **G06F9/48** (20060101); **G06F11/30** (20060101)

U.S. Cl.:

CPC **G06F9/5027** (20130101); **G06F9/4837** (20130101); **G06F9/5016** (20130101);
G06F11/3006 (20130101); G06F2209/503 (20130101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This U.S. application claims priority to, and is a continuation of U.S. patent application Ser. No. 19/007,241, filed on Dec. 31, 2024, which claims priority to, and is a continuation of U.S. patent application Ser. No. 18/830,410, filed on Sep. 10, 2024, now U.S. Pat. No. 12,260,254, issued on Mar. 25, 2025, which claims priority to, and is a continuation of U.S. patent application Ser. No. 18/587,648, filed on Feb. 26, 2024, now U.S. Pat. No. 12,099,877, issued on Sep. 24, 2024, which claims priority to, and is a continuation of U.S. patent application Ser. No. 18/214,321, filed on Jun. 26, 2023, now U.S. Pat. No. 11,915,052, issued on Feb. 27, 2024, which claims priority to, and is a continuation of U.S. patent application Ser. No. 17/228,569, filed on Apr. 12, 2021, now U.S. Pat. No. 11,687,371, issued on Jun. 27, 2023, which claims priority to, and is a continuation of U.S. patent application Ser. No. 16/716,453, filed on Dec. 16, 2019, now U.S. Pat. No. 10,977,084, issued on Apr. 13, 2021, all the disclosures of which are incorporated by reference herein in their entirety for all purposes.

TECHNICAL FIELD

[0002] Generally, the present disclosure relates to targeted communications in complex computing networks.

BACKGROUND

[0003] Execution of operations requires resources. These resources may include material, energy, currency, data, computing power, computing storage, computing memory, etc., which may be finite in nature. For example, only a limited quantity of resources may be available. As another example, the resources may be available only during a limited period of time. Therefore, efficient usage of resources is important for successful execution of operations.

SUMMARY

[0004] An allocatable (e.g., material, energy, currency, data, computing power, computing storage, computing memory, etc.) may be allocated from an allocation pool over time (t) in a series of execution events (data transfers, data/signal processing operations, spending operations, targeted communications, computing resource allocations, etc.), each of which may be defined by one or more allocation parameters (e.g., timing, frequency, quantity (absolute or relative with regard to total allocatables), etc.). The initiated execution events may initiate, comprise, or be associated with targeted communications.

[0005] According to some embodiments, a method for determining one or more target allocation parameters for initiating targeted communications, comprises establishing a first network communication channel with a first computing device; receiving, using one or more computing device processors, from the first computing device, on the first network communication channel, a desired allocation for a first period comprising a first time, a second time, and a third time, wherein the third time is an end time of the first period; establishing a second network communication channel with a second computing device; receiving, using one or more computing device processors, from the second computing device, on the second network communication channel, data associated with a first execution event; determining, using the one or more computing device processors, and based on the data associated with the first execution event, a first instantaneous available allocation at the first time; generating, using the one or more computing device processors, and based on at least the first instantaneous available allocation, an allocation graph for a second period comprising the first time and not the second time; establishing a third network communication channel with the second computing device or a third computing device; receiving, using the one or more computing device processors, from the second computing device or the third computing device, on the third network communication channel, data associated with a second execution event; determining, using the one or more computing device processors, and based on the data associated with the second execution event, a second instantaneous available allocation at the second time after the first time, wherein the second instantaneous available allocation is not used to generate the allocation graph associated with the second period comprising the first time and not the second time; establishing a first communication channel with a database or a memory; initiating transmission of, using the one or more computing device processors, on the first communication channel with the database or the memory, the second instantaneous available allocation for storage in the database or the memory; determining, using the one or more computing device processors, and based on the allocation graph for the second period comprising the first time, and not the second time, and the second instantaneous available allocation at the second time, a remaining available allocation at the second time; and determining, using the one or more computing device processors, and based on the remaining available allocation and the desired allocation, the one or more target allocation parameters for initiating a targeted communication to a fourth computing device, different from the second computing device and the third computing device, during at least a portion of a third period between the second time and the third time.

[0006] According to some embodiments, each of the data associated with the first execution event and the data associated with the second execution event comprises data associated with one or more of: an opportunity to allocate as a part of an execution event, an attempted execution event, and a successful execution event.

[0007] According to some embodiments, each of the first execution event and the second execution event comprises one or more of: a data transfer, a data or signal processing operation, a data allocation, a material resource allocation, an energy resource allocation, a targeted communication, and a computing resource allocation.

[0008] According to some embodiments, the method further comprises initiating transmission of, using the one or more computing device processors, on the first communication channel with the database or the memory, the first instantaneous available allocation for storage in the database or the memory.

[0009] According to some embodiments, the method further comprises initiating retrieval of, using the one or more computing device processors, on the first communication channel with the database or the memory, the first instantaneous available allocation stored in the database or the memory.

[0010] According to some embodiments, the method further comprises generating, using the one or more computing device processors, a data compilation, wherein the data compilation comprises the first instantaneous available allocation.

[0011] According to some embodiments, the method further comprises establishing a second communication channel with the database or the memory; and initiating retrieval of, using the one or more computing device processors, on the second communication channel with the database or the memory, the first instantaneous available allocation stored in the database or the memory.

[0012] According to some embodiments, the database comprises a cloud-based database.

[0013] According to some embodiments, the targeted communication is associated with a third execution event.

[0014] According to some embodiments, the third execution event comprises one or more of: a data transfer, a data allocation operation, a data or signal processing operation, a material resource allocation, an energy resource allocation, and a computing resource allocation.

[0015] According to some embodiments, the method further comprises establishing a fourth network communication channel with a fifth computing device; and initiating transmission of, using the one or more computing device processors, on the fourth network communication channel with the fifth computing device, the allocation graph.

[0016] According to some embodiments, the fifth computing device comprises a streaming platform.

[0017] According to some embodiments, the method further comprises initiating retrieval of, using the one or more computing device processors, the allocation graph from the fifth computing device.

[0018] According to some embodiments, a computing system for determining one or more operation parameters associated with determining target allocation parameters for initiating targeted communications in complex computing networks comprises at least one memory comprising instructions; one or more computing device processors for executing the instructions, wherein the instructions cause the one or more computing device processors to perform operations of: establishing a first network communication channel with a first computing device; receiving, using one or more computing device processors, from the first computing device, on the first network communication channel, a desired allocation for a first period comprising a first time, a second time, and a third time, wherein the third time is an end time of the first period; establishing a second network communication channel with a second computing device; receiving, using one or more computing device processors, from the second computing device, on the second network communication channel, data associated with a first execution event; determining, using the one or more computing device processors, and based on the data associated with the first execution event, a first instantaneous available allocation at the first time; generating, using the one or more computing device processors, and based on at least the first instantaneous available allocation, allocation data for a second period comprising the first time and not the second time; establishing a third network communication channel with the second computing device or a third computing device; receiving, using the one or more computing device processors, from the second computing device or the third computing device, on the third network communication channel, data associated with a second execution event; determining, using the one or more computing device processors, and based on the data associated with the second execution event, a second instantaneous available allocation at the second time after the first time, wherein the second instantaneous available allocation is not used to generate the allocation data associated with the second period comprising the first time and not the second time; establishing a first communication channel with a database or a memory; initiating transmission of, using the one or more computing device processors, on the first communication channel with the database or the memory, the second instantaneous available allocation for storage in the database or the memory; determining, using the one or more computing device processors, and based on the allocation data for the second period comprising the first time, and not the second time, and the second instantaneous available allocation at the second time, a remaining available allocation for allocating at the second time or after the second time; and determining, using the one or more computing device processors, and based on the remaining available allocation and the desired allocation, the one or more target allocation parameters for

initiating a targeted communication to a fourth computing device, different from the second computing device and the third computing device, during at least a portion of a third period between the second time and the third time.

[0019] According to some embodiments, the instructions further cause the one or more computing device processors to perform initiating transmission of, using the one or more computing device processors, on the first communication channel with the database or the memory, the first instantaneous available allocation for storage in the database or the memory.

[0020] According to some embodiments, the instructions further cause the one or more computing device processors to perform initiating retrieval of, using the one or more computing device processors, on the first communication channel with the database or the memory, the first instantaneous available allocation stored in the database or the memory.

[0021] According to some embodiments, the first network communication channel, the second network communication channel, the third network communication channel, and the first channel are part of the same communication interface or are part of different communication interfaces.

[0022] According to some embodiments, the instructions further cause the one or more computing device processors to perform: establishing a second communication channel with the database or the memory; and initiating retrieval of, using the one or more computing device processors, on the second communication channel with the database or the memory, the first instantaneous available allocation stored in the database or the memory.

[0023] According to some embodiments, the instructions further cause the one or more computing device processors to perform: establishing a fourth network communication channel with a fifth computing device; and initiating transmission of, using the one or more computing device processors, on the fourth network communication channel with the fifth computing device, the allocation data.

[0024] According to some embodiments, a non-transitory computer-readable medium for initiating an adjustment of the operation associated with the system for determining target allocation parameters for initiating targeted communications in complex computing networks, the non-transitory computer-readable medium may comprise code configured for: establishing a first network communication channel with a first computing device; receiving, using one or more computing device processors, from the first computing device, on the first network communication channel, a desired allocation for a first period comprising a first time, a second time, and a third time, wherein the third time is an end time of the first period; establishing a second network communication channel with a second computing device; receiving, using one or more computing device processors, from the second computing device, on the second network communication channel, data associated with a first execution event; determining, using the one or more computing device processors, and based on the data associated with the first execution event, a first instantaneous available allocation at the first time; generating, using the one or more computing device processors, and based on at least the first instantaneous available allocation, allocation data for a second period comprising the first time and not the second time; establishing a third network communication channel with the second computing device or a third computing device; receiving, using the one or more computing device processors, from the second computing device or the third computing device, on the third network communication channel, data associated with a second execution event; determining, using the one or more computing device processors, and based on the data associated with the second execution event, a second instantaneous available allocation at the second time after the first time, wherein the second instantaneous available allocation is not used to generate the allocation data associated with the second period comprising the first time and not the second time; establishing a first communication channel with a database or a memory; initiating transmission of, using the one or more computing device processors, on the first communication channel with database or the memory, the second instantaneous available allocation for storage in the database or the memory; determining, using the one or more computing device processors, and

based on the allocation data for the second period comprising the first time, and not the second time, and the second instantaneous available allocation at the second time, a remaining available allocation at the second time or for allocating at or after the second time; and determining, using the one or more computing device processors, and based on the remaining available allocation and the desired allocation, the one or more target allocation parameters for initiating a targeted communication to a fourth computing device, different from the second computing device and the third computing device, during at least a portion of a third period between the second time and the third time.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0025] FIG. 1 shows a schematic block diagram of a system for determining target allocation parameters for initiating targeted communications in complex computing networks in accordance with some disclosed embodiments.

[0026] FIG. 2 shows a functional block diagram of a server for control and manipulation of data and processes associated with disclosed systems and methods for determining target allocation parameters for initiating targeted communications in complex computing networks in accordance with some disclosed embodiments.

DETAILED DESCRIPTION

[0027] In the following detailed description, numerous specific details are set forth by way of examples in order to provide a thorough understanding of the relevant teachings. However, the present teachings may be practiced with or without such specific details. In other instances, well-known methods, procedures, components, and/or circuitry have been described at a relatively high level, without detail, in order to avoid unnecessarily obscuring aspects of the present teachings. The various technologies described in this specification generally relate to targeted communications in complex computing networks, which may be used to monitor, used to initiate, or may be otherwise associated with execution events.

[0028] It is understood that any features of any embodiment described herein may be incorporated into any other embodiment described herein. Features of different embodiments can be combined to form new embodiments. Further, any one or more of the steps, operations, etc., described herein may be performed in the order described or in any order. Any one or more of the steps, operations, etc., described herein may be removed and additional steps may be added. Although the present disclosure is related to targeted communications in complex computing networks, it should also be understood that any one or more of the methods, systems, operations, etc., described herein may be associated with other types of communications and networks. The terms communication channel and network communication channel may be used interchangeably. It is understood that any reference to a communication channel (e.g., first communication channel, second communication channel, third communication channel) or to a network communication channel (e.g., first network communication channel, second network communication channel, etc.)

[0029] could mean any communication channel. For example, a first communication channel and a second communication channel could be the same communication channel or different communication channels.

[0030] A target allocation parameter may be associated with a current (i.e., instantaneous) or future execution event and may be determined using the disclosed systems and methods. According to some embodiments, a system for determining one or more target allocation parameters may comprise one or more servers, which may comprise at least one memory and one or more computing device processors. The at least one memory may comprise computing instructions and the one or more computing device processors may be configured to execute the instructions. The

instructions may cause the one or more computing device processors to perform the operations of establishing a first network communication channel with a first computing device; receiving, on the first network communication channel, a desired allocation for a first period comprising a first time, a second time, and a third time, wherein the third time is an end time of the first period; establishing a second network connection channel with a second computing device; receiving, on the second network communication channel, data associated with a first execution event; determining, based on the data associated with the first execution event, a first instantaneous available allocation at the first time; generating, based on at least the first instantaneous available allocation, allocation data for a second period comprising the first time and not the second time; establishing a third network connection channel with the second computing device or a third computing device; receiving, on the third network communication channel, data associated with a second execution event; determining, based on the data associated with the second execution event, a second instantaneous available allocation at the second time after the first time, wherein the second instantaneous available allocation is not used to generate the allocation data associated with the second period comprising the first time and not the second time; initiating transmission of, on the communication channel with database or the memory, the second instantaneous available allocation for storage in the database or the memory; determining, based on the allocation data for the second period comprising the first time, and not the second time, and the second instantaneous available allocation at the second time, a remaining available allocation at the second time; and determining, based on the remaining available allocation and the desired allocation, the one or more target allocation parameters for initiating a targeted communication to a fourth computing device, different from the first computing device, the second computing device and the third computing device, during at least a portion of a third period between the second time and the third time.

[0031] As shown in FIG. 1, a system **100** for determining target allocation parameters for initiating targeted communications in complex computing networks may comprise a server **102**, a cloud-based database **104**, one or more databases **106**, and one or more platforms **108**. It is understood that a server **102** may comprise multiple components (e.g., a computing device processor, memory, input/output (I/O), communications center, etc.) and that any operation said to be performed by a server **102** herein may be performed by any one or a combination of any components which may comprise the server **102**. For example, any operation said to be executed by a server **102** may be executed by one or more computing device processors associated with the server **102**.

[0032] According to some embodiments, a server **102**, using one or more computing device processors, may establish a network communication channel (e.g., first network communication channel, second network communication channel, third network communication channel, etc.) with a computing device, (e.g., first computing device, second computing device, third computing device, fourth computing device, etc.). A server **102** may receive, using one or more computing device processors, a desired allocation **110** from the computing device. A desired allocation **110**, according to some embodiments, may be a total allocation (e.g., allocation pool) of allocatables over a first period of time comprising a first time, a second time, and a third time. A third time, in some embodiments, may be the end of the first period.

[0033] According to some embodiments, a server **102**, using one or more computing device processors, may establish a network communication channel (e.g., first network communication channel, second network communication channel, third network communication channel, etc.) with a computing device, (e.g., first computing device, second computing device, third computing device, fourth computing device, etc.), on which it may receive, using one or more computing device processors, data associated with an execution event (e.g., first execution event, second execution event, third execution event, etc.). In some embodiments, a server **102** may receive data associated with a first execution event. Data associated with a first execution event may comprise any information (e.g., data) about the execution event. For example, according to some

embodiments, data associated with a first execution event may comprise data associated with an opportunity to allocate as a part of an execution event, an attempted execution event, a successful execution event, etc. An execution event may, according to some embodiments, comprise an allocation (e.g., data transfers, data and/or signal processing operations, data allocations, material resource allocations, energy resource allocations, spending operations, targeted communications, computing resource allocations, etc.) of an allocatable (e.g., material, energy, currency, data, computing power, computing storage, computing memory, communications, computing resource, etc.).

[0034] According to some embodiments, a server **102**, using one or more computing device processors, may determine a first instantaneous available allocation **112** at a first time. A first instantaneous available allocation **112** may be based on data associated with a first execution event. A first instantaneous available allocation **112** may comprise all or a portion of a desired allocation **110** and may comprise a total availability of an allocatable (e.g., in a desired allocation **110**) at the first time. According to some embodiments, instantaneous available allocations (e.g., a first instantaneous available allocation **112**) may be captured over time. A server **102**, using one or more computing device processors, may generate a data compilation **118**, which may, according to some embodiments, comprise multiple instantaneous available allocations captured over time. A data compilation **118** may comprise a first instantaneous available allocation **112**.

[0035] A server **102**, using one or more computing device processors, may establish any number of communication channels with cloud-based database **104**, a database **106**, or a memory. According to some embodiments, a communication channel may comprise a first communication channel, a second communication channel, a third communication channel, etc. In some embodiments, a server **102**, using one or more computing device processors, may establish at least a first communication channel with a cloud-based database **104**, a database **106**, or a memory. Using the communication channel, a server **102**, using one or more computing device processors, may initiate transmission of a first instantaneous available allocation **112** for storage.

[0036] In some embodiments, a server **102**, using one or more computing device processors, may initiate transmission of a data compilation **116**, which may comprise a first instantaneous available allocation **112**, for storage. A server **102**, using one or more computing device processors, may initiate retrieval a first instantaneous available allocation **112** stored in a cloud-based database **104**, a database **106**, or a memory. In some embodiments, an initiated retrieval of a first instantaneous available allocation **112** may be on a communication channel, (e.g., first communication channel, second communication channel, third communication channel, etc.) with a cloud-based database **104**, a database **106**, or a memory. In other embodiments, a server **102**, using one or more computing device processors, may establish a second communication channel with a cloud-based database **104**, a database **106**, or a memory, and an initiated retrieval of a first instantaneous available allocation **112** may be on the second communication channel.

[0037] A server **102**, using one or more computing device processors, may generate an allocation graph **118** for a second period. An allocation graph **118** may be based on at least a first instantaneous available allocation **112**. A second period may comprise a first time of a first period and not a second time of a first period. For example, according to some embodiments, a first period may comprise a week (e.g., 7-day period), a second period may comprise a previous day (e.g., 24-hour period) in the week, and a first time may comprise a time during the previous day (e.g., second period) when an instantaneous available allocation **112** was captured. An allocation graph **118** may be generated for a second period (e.g., the previous day), and may be based on at least a first instantaneous available allocation **112** captured at a first time during the second period. An allocation graph **118**, according to some embodiments, may be based on a collection of instantaneous available allocations (e.g., a first instantaneous available allocation **112**) captured at different times (e.g. a first time) throughout a previous day (e.g., a second period) in a week (e.g. a first period).

[0038] In some embodiments, a server **102**, using one or more computing device processors, may generate allocation data associated with a second period. Allocation data may comprise any type or form (e.g., visual or non-visual, graphical or non-graphical, time-based plot/trace, other variable-based plot/trace, curve, etc.) of data associated with the second period. Allocation data may comprise, among other data, an allocation graph **118**, an allocation curve, an allocation trace, an allocation plot, or raw or processed data associated with a second period. In some embodiments, any instances of allocation graph as used in any part of this disclosure may include allocation data, as defined in this disclosure.

[0039] In some embodiments, a server **102**, using one or more computing device processors, may establish a network communication channel (e.g., first communication channel, second communication channel, third communication channel, fourth communication channel, fifth communication channel, etc.) with a fifth computing device. A fifth computing device may comprise a streaming platform **108** (e.g., a distributed streaming platform, a synchronization medium). A server **102**, using one or more computing device processors, may initiate transmission of an allocation graph **118** to a fifth computing device on the network communication channel. In some embodiments, a server **102**, using one or more computing device processors, may initiate retrieval of an allocation graph **118** from a fifth computing device (e.g., platform **108**, synchronization medium) on a network communication channel (e.g., first network communication channel, second network communication channel, third network communication channel, fourth network communication channel, fifth network communication channel, etc.) with a fifth computing device. In some embodiments, a server **102**, using one or more computing device processors, may receive an allocation graph **118** from a fifth computing device (e.g., platform **108**, synchronization medium) on the fourth network communication channel or the fifth network communication channel.

[0040] A server **102**, using one or more computing device processors, may establish a third network communication channel with a second computing device or a third computing device and may receive data associated with a second execution event on the third network communication channel. In some embodiments, the data associated with a second execution event may be received from a second computing device. In other embodiments, the data associated with a second execution event may be received from a third computing device. In other embodiments still, data associated with a second execution event may be received from any combination of a second computing device, a third computing device, and other computing devices. Data associated with a second execution event may comprise any information (e.g., data) about the second execution event. For example, according to some embodiments, data associated with a second execution event may comprise data associated with an opportunity to allocate as a part of an execution event, an attempted execution event, a successful execution event, etc.

[0041] A server **102**, using one or more computing device processors, may determine a second instantaneous available allocation **124**. In some embodiments, a second instantaneous available allocation **124** may be based on data associated with a second execution event. A second instantaneous available allocation **124** may be associated with a second time, which may be after a first time. For example, if a first period (e.g., a week) comprises a first time (e.g., a time at which an instantaneous available allocation **112** was captured), a second time, and a third time (e.g., end of the period), and a first time is a time during the second period (e.g., previous day), then a second time may comprise any time after the end of the second period, but before a third time which ends the first period (e.g., end of the week). A second instantaneous available allocation **124** at a second time, according to some embodiments, is not used to generate an allocation graph. Data associated with a second execution event, according to some embodiments, may comprise data associated with an opportunity to allocate as a part of an execution event, an attempted execution event, a successful execution event, etc.

[0042] According to some embodiments, a server **102**, using one or more computing device

processors, may initiate transmission of a second instantaneous available allocation **124** for storage in a cloud-based database **104**, a database **106**, or a memory. An initiated transmission may use a communication channel (e.g., first communication channel, second communication channel, third communication channel, etc.) or a network communication channel to transmit a second instantaneous available allocation **124**. In some embodiments, a server **102** initiates transmission of a second instantaneous available allocation **124** on a communication channel (e.g., first communication channel, second communication channel, first network communication channel, second network communication channel, etc.) or a network communication channel. A server **102**, using one or more computing device processors, may retrieve a stored second instantaneous available allocation **124** from a cloud-based database **104**, a database **106**, or a memory, on a communication channel (e.g., first communication channel, second communication channel, third communication channel, etc.) or a network communication channel.

[0043] A server **102**, using one or more computing device processors, may determine a remaining available allocation **120**. In some embodiments, a remaining available allocation **120** may be associated with a second time, as the second time is described above, or associated with a period after the second time (e.g., up to an end time of a period associated with a desired allocation). A remaining available allocation **120** may be based on one or more of an allocation graph for a second period and a second instantaneous available allocation **124** at a second time. In some embodiments, a remaining available allocation **120** may be associated with the availability of an allocatable to be allocated during a period (e.g., first period, second period, third period, etc.).

[0044] A server **102**, using one or more computing device processors, may determine one or more target allocation parameters **126** for initiating a targeted communication to a computing device (e.g., first computing device, second computing device, third computing device, fourth computing device, etc.). A targeted communication may comprise a message, instructions, identification data, content, advertisement data, or any other data described in this disclosure, including those associated with execution events. The one or more target allocation parameters **126** for initiating a targeted communication to a computing device may comprise one or more allocation parameters (e.g., timing, frequency, quantity (absolute or relative with regard to total allocatables), etc.) and may be determined based on any combination of a remaining available allocation **120**, a desired allocation **110**, and other information. The one or more target allocation parameters may be associated with at least a portion of a period (e.g., first period, second period, third period, etc.). In some embodiments, the one or more target allocation parameters **126** may be associated with initiating a targeted communication during at least a portion of a third period, which may comprise a period between a second time and a third time (e.g., end of the first period). A targeted communication may be, according to some embodiments, associated with an execution event, which may comprise one or more of: a data transfer, a data allocation operation, a data or signal processing operation, a material resource allocation, an energy resource allocation, and a computing resource allocation

[0045] Referring now to FIG. 2, an operating system for determining target allocation parameters for initiating targeted communications in complex computing networks may comprise or may be implemented in one or more servers **102**, where the one or more servers **102** may comprise any combination of at least one memory **280** comprising server instructions, and at least one processing device **260** (e.g., computing device processors) configured for executing the server instructions, an input/output (I/O) **290**, and communications center **295**. A computing system or server associated with for determining target allocation parameters for initiating targeted communications in complex computing networks may be one or more local or remote systems. Any one or more of the subsystems described below may be optional and may be present in the same computing system or in disparate, e.g. local or remote, computing systems which may be in network communication with each other. As described in present embodiments, each of the processor **260**, the memory **280**, the I/O **260**, and communication center **295** may include a plurality of respective units, subunits,

and/or elements. Furthermore, each of the processor **260**, the memory **280**, the I/O **290**, and the communication center **295** may be operatively or otherwise communicatively coupled with each other so as to facilitate the methods and techniques described herein.

[0046] The processor **260** may control any one or more of the memory **280**, the I/O **290**, the communication center **295**, or any other unit which may include the server **102**, as well as any included subunits, elements, components, devices, or functions performed by each or a combination of the memory **280**, the I/O **290**, the communication center **295** or any other unit which may include the server **102**. Any of the elements or sub-elements of the server **102** presented here may also be included in a similar fashion in any of the other units, subunits, and devices included in the system of FIG. **1**. Additionally, any actions described herein as being performed by a processor **260** may be taken by the processor **260** alone, or by the processor **260** in conjunction with one or more additional processors, units, subunits, elements, components, devices, and the like. Additionally, while only one processor **260** may be shown in the figures included here, multiple processors may be present or otherwise included in the server **102** or elsewhere in the system of FIG. **1**. Thus, while instructions may be described as being executed by the processor **260** or the various subunits of the processor **261**, **262**, **263**, **264**, **265**, the instructions may be executed simultaneously, serially, or otherwise by one or more multiple processors **260**.

[0047] In some embodiments, a processor **260** may be implemented as one or more computer processor (CPU) chips, graphical processor (GPU) chips, or some combination of CPU chips and GPU chips, and may include a hardware device capable of executing computer instructions. The processor **260** may execute any combination of instructions, codes, computer programs, and scripts. The instructions, codes, computer programs, and scripts may be received from, stored in, or received from and stored in any combination of the memory **280**, the I/O **290**, the communication center **295**, subunits of the previously described elements, other devices, other computing environments.

[0048] In some embodiments, the processor **260** may include, among other elements, subunits. Subunits may include any combination of a profile manager **261**, a content manager **262**, a geolocation finder **263**, a graphical processor **264**, and a resource allocator **265**. Each of these subunits of the processor **260** may be communicatively or otherwise operably coupled with each other.

[0049] The profile manager **261** may facilitate any combination of generation, modification, analysis, transmission, and presentation of a profile associated with a user or with a computing device (e.g., first computing device, second computing device, third computing device, etc.). The profile manager **261** may also control or utilize an element of the I/O **290** to enable a user or a computing device to associate an identifier, location, etc. with itself. The profile manager **261** may receive, process, analyze, organize, transform, or any combination of these, any received from the user or another computing element as to generate a profile of a user or a computing device. For example, in some embodiments, a computing device (e.g., second computing device, third computing device, etc.) may have a profile that identifies the computing device and its location. In some embodiments, a profile manager **261** may be able to generate a profile associated with a user of a computing device (e.g., first computing device, second computing device, etc.). A computing device and/or user may be associated with a desired spend.

[0050] The content manager **262** may facilitate any combination of generation, modification, analysis, transmission, and presentation of any media content associated with systems and methods for determining target allocation parameters for initiating targeted communications in complex computing networks. For example, the content manager **262** may facilitate media content associated with a user interface with any one or more computing devices associated with the system.

[0051] The geolocation finder **263**, particularly in communication with geolocation information provided by available GPS subsystems which may be present elsewhere in the described systems,

may facilitate any combination of detection, generation, modification, analysis, transmission, and presentation of location information. Location information may include any combination of global positioning system (GPS) coordinates, an internet protocol (IP) address, a media access control (MAC) address, geolocation information, an address, a port number, a zip code, a server number, a proxy name, a proxy number, device information, serial numbers, and the like. In some embodiments, the geolocation finder **263** may include any one or a combination of various sensors, specifically-purposed hardware elements for enabling the geolocation finder **263** to acquire, measure, and transform location information. For example, the geolocation finder **263** may facilitate the processing of geolocation data associated with computing devices associated with a desired allocation, data associated with an execution event, and/or streaming platform.

[0052] The graphical processor (GPU) **264** may facilitate any combination of generation, modification, analysis, processing, transmission, and presentation of visual content. In some embodiments, the GPU **264** may be configured to receive images associated with a system and methods for determining target allocation parameters for initiating targeted communications in complex computing networks. Further, the GPU **264** may be configured to facilitate adjustments to videos and images. The GPU **264** may also be configured to render visual content for presentation on a device and/or to analyze visual content for metadata associated with a component of any one or more of the systems described. In some embodiments, this visual content may include a real-time image. The GPU **264** may include multiple GPUs and may therefore be configured to perform and/or execute multiple processes in parallel.

[0053] The resource allocator **265** may facilitate any one or combination of the determination, monitoring, analysis, and allocation of resources throughout the server **102**, any one or more of the disclosed systems, any component of the system, or other computing environments. For example, the resource allocator **265** may facilitate interaction between the server **102**, any subunit of the server **102**, and a high volume (e.g. multiple) of users, inputs, computing devices, etc. As such, computing resources of the server **102** utilized by any one or a combination of the processor **260**, the memory **280**, the I/O **290**, the communication center **295**, and any subunit of these units, such as processing power, data storage space, network bandwidth, and the like may be in high demand at various times during operation. Accordingly, the resource allocator **265** may be configured to manage the allocation of various computing resources as they are required by particular units or particular subunits of the server **102**.

[0054] In some embodiments, the resource allocator **265** may include sensors and/or other specially-purposed hardware for monitoring performance of each unit and/or subunit of the server **102**, as well as hardware for responding to the computing resource needs of each unit or subunit. In some embodiments, the resource allocator **265** may utilize computing resources of a second computing environment separate and distinct from the server **102** to facilitate a desired operation.

[0055] In some embodiments, factors affecting the allocation of computing resources by the resource allocator **265** may include the number of ongoing connections, network communication channels, and/or other communication channel connections, a duration during which computing resources are required by one or more elements of the server **102**, and/or the like. In some embodiments, computing resources may be allocated to and/or distributed amongst a plurality of second computing environments included in the server **102** based on one or more factors mentioned above. In some embodiments, the allocation of computing resources of the resource allocator **265** may include one or more resource allocators **265** flipping a switch, adjusting processing power, adjusting memory size, partitioning a memory element, transmitting data, controlling one or more input and/or output devices, modifying various communication protocols, and the like. In some embodiments, the resource allocator **265** may facilitate utilization of parallel processing techniques such as dedicating a plurality of GPUs included in the processor **260** for processing high-quality analysis and manipulation of, for example, allocation graphs, instantaneous available allocations, remaining allocations, etc.

[0056] In some embodiments, the memory **280** may be utilized for one or any combination of storing, recalling, receiving, transmitting, and/or accessing various files and/or information during operation of the server **102**. For example, the memory **280** may be utilized for storing available allocations, allocation graphs, desired allocations, etc., associated with systems and methods of determining target allocation parameters for initiating targeted communications in complex computing networks. The memory **280** may additionally be used for storing, recalling, and/or updating user or other system information and the like. The memory **280** may include various types of data storage media such as solid state storage media, hard disk storage media, and any other type of data storage medium which may be known to a person of ordinary skill in the art.

[0057] The memory **280** may include dedicated hardware elements such as hard drives and/or servers, as well as software elements such as cloud-based storage drives. For example, the memory unit **280** may include various subunits such as an operating system unit **281**, an application data unit **282**, an application programming interface (API) unit **283**, a profile storage unit **284**, a content storage unit **285**, a video storage unit **286**, a secure enclave **287**, a cache storage unit **288**, and/or an allocation stack **289**.

[0058] The memory **280** and any of its subunits described here may include any one or any combination of random access memory (RAM), read only memory (ROM), and various forms of secondary storage. RAM may be used to store volatile data and/or to store instructions that may be executed by the processor **260**. For example, the data stored may be any one or a combination of a command, a current operating state of the server **102**, an intended operating state of the server **102**, and the like. As a further example, data stored in the memory **280** may include instructions related to various methods and/or functionalities described here. ROM may be a non-volatile memory device that may have a smaller memory capacity than the memory capacity of a secondary storage. ROM may be used to store instructions and/or data that may be read during execution of computer instructions. In some embodiments, access to both RAM and ROM may be faster than access to secondary storage. Secondary storage may include one or more disk drives and/or tape drives and may be used for non-volatile storage of data or as an over-flow data storage device if RAM is not large enough to hold all working data. Secondary storage may be used to store programs that may be loaded into RAM when such programs are selected for execution. In some embodiments, the memory **280** may include one or more databases for storing any data described here. Additionally or alternatively, one or more secondary databases located remotely from the server **102** may be utilized and/or accessed by the memory **280**.

[0059] The operating system unit **281** may facilitate deployment, storage, access, execution, and/or utilization of an operating system utilized by the server **102** and/or any other computing environment described herein. In some embodiments, the operating system may include various hardware and/or software elements that serve as a structural framework for enabling the processor **260** to execute various operations such as the analysis of data (e.g., data associated with an execution event), generation of data and/or parameters (e.g. an instantaneous available allocation, a target allocation parameter, etc.). The operating system unit **281** may further store various pieces of information and/or data associated with operation of the operating system and/or the server **102** as a whole, such as a status of computing resources (e.g., processing power, memory availability, resource utilization, and/or the like), runtime information, modules to direct execution of operations described herein, user permissions, security credentials, and the like.

[0060] The application data unit **282** may facilitate deployment, storage, access, execution, and/or utilization of an application utilized by the server **102** or any other computing environment described herein. For example, it may be desirable for a user to download, access, and/or otherwise utilize a software application on a user device such as a smartphone or other internet-enabled device in order to monitor any one or more of the various operations described herein to be performed. As such, the application data unit **282** may store any information and/or data associated with the application which may allow the application and/or user device to monitor, initiate, or

otherwise access the methods and systems associated with initiating adjustment of an operation associated with any one or more of the systems described herein. As such, information included in the application data unit **282** may enable a user to execute various operations described. The application data unit **282** may further store various pieces of information and/or data associated with operation of the application and/or the server **102** as a whole, such as a status of computing resources (e.g., processing power, memory availability, resource utilization, and/or the like), runtime information, modules to direct execution of operations described herein, user permissions, security credentials, and the like.

[0061] The application programming interface (API) unit **283** may facilitate deployment, storage, access, execution, and/or utilization of information associated with APIs of the server **102** and/or any other computing environment described herein (e.g., a computing device, system component, etc.). For example, server **102** may include one or more APIs for enabling various devices, applications, and/or computing environments to communicate with the server **102**, multiple other servers, databases, or other user devices. Accordingly, the API unit **283** may include API databases containing information that may be accessed and/or utilized by applications and/or operating systems of other devices, components, and/or computing environments associated with determining target allocation parameters for initiating targeted communications in complex computing networks. An API may direct communications between any component of the described systems and the server **102**. In some embodiments, each API database may be associated with a customized physical circuit included in the memory unit **280** and/or the API unit **283**. Additionally, each API database may be public and/or private, and so authentication credentials may be required to access information in an API database.

[0062] The profile storage unit **284** may facilitate deployment, storage, access, and/or utilization of information associated with any user and/or computing device (e.g., a first computing device, second computing device, third computing device, etc.) profiles of any system user by the server **102** and any other computing environment described here (e.g., a computing device, system components, etc.). For example, the profile storage unit **284** may store one or more of a user's contact information, authentication credentials, user preferences, user history, personal information, and metadata. The profile storage unit **284** may store information about a specific computing device (e.g., location, etc.). The profile storage unit **284** may store any data associated with a particular or group of users, systems, and/or computing devices for analysis, etc. In some embodiments, the profile storage unit **284** may communicate with the profile manager **261** to receive and/or transmit information associated with a user's and/or a computing device's profile.

[0063] The content storage unit **285** may facilitate deployment, storage, access, and/or utilization of information associated with requested content by the server **102** and/or any other computing environment described here. For example, the content storage unit **285** may store one or more of images, text, analytical data, historical data, metadata, etc. to be utilized during operations described herein. In some embodiments, the content storage unit **285** may communicate with the content manager **262** to receive and/or transmit content files.

[0064] The media storage unit **286** may facilitate one or more of deployment, storage, access, analysis, and utilization of media content by the server **102** and any other computing environment described herein. Media content may be images, videos, audio files, graphs, and any other form of communicative media. For example, the media storage unit **286** may store one or more representations of allocation graphs which may be utilized in association with determining target allocation parameters for initiating targeted communications in complex computing networks. Further, the media storage unit **286** may store one or more images which have been manipulated by any unit or subunit of a server **102** or other component of a system for determining target allocation parameters for initiating targeted communications in complex computing networks. Media content generated or used in performing any of the methods disclosed here may be stored in the media storage unit **286** so that the media content may be analyzed by various components of the server

102 both in real time and at a time after receipt of the media content. In some embodiments, the media storage unit **286** may communicate with the GPUs **264** to facilitate any of the processes described here. In some embodiments, media content may include audio, images, text, video feeds, analytical results, graphical representations of results and/or analyses, and/or any other media content associated with systems and methods of determining target allocation parameters for initiating targeted communications in complex computing networks.

[0065] The secure enclave **287** may facilitate secure storage of data. In some embodiments, the secure enclave **287** may include a partitioned portion of storage media included in the memory unit **280** that is protected by various security measures. For example, the secure enclave **287** may be hardware secured. In other embodiments, the secure enclave **287** may include one or more firewalls, encryption mechanisms, and/or other security-based protocols. Authentication credentials may be required prior to providing access to data stored within the secure enclave **287**. In some embodiments, the secure enclave **287** may store sensitive information associated with any of the systems or methods described herein.

[0066] The cache storage unit **288** may facilitate short-term deployment, storage, access, analysis, and/or utilization of data. In some embodiments, the cache storage unit **288** may serve as a short-term storage location for data so that the data stored in the cache storage unit **288** may be accessed quickly. In some embodiments, the cache storage unit **288** may include RAM and/or other storage media types that enable quick recall of stored data. The cache storage unit **288** may include a partitioned portion of storage media included in the memory **280**. In some embodiments, the cache storage unit **288** may store data associated with initiating adjustment of an operation associated with a system for determining target allocation parameters for initiating targeted communications in complex computing networks, computational instructions for analysis of data associated with determining target allocation parameters for initiating targeted communications in complex computing networks, or other data which may be frequently used in any of the processes, method, etc., associated with the systems or methods described herein.

[0067] A memory **280** may comprise, according to some embodiments, an allocation stack **289**. An allocation stack **289** may be utilized to store instructions relating to the processing, distribution, managing, storing, and other functions related to allocation data. In some embodiments, an allocation stack **289** may store instructions related to processing allocation data prior to determining a remaining available allocation.

[0068] The I/O unit **290** may include hardware and/or software elements for enabling the server **102** to receive, transmit, and/or present information. For example, elements of the I/O unit **290** may be used to receive input from a component of a system for determining target allocation parameters for initiating targeted communications in complex computing networks (e.g., a computing device, a data source, etc.), present data, manipulated data, allocation graphs, etc. As described, the I/O unit **290** may include subunits such as one or a combination of an I/O device **291**, I/O calibration unit **292**, and/or media driver **293**.

[0069] The I/O device **290** may facilitate any one or any combination of the receipt, transmission, processing, presentation, display, input, and output of information as a result of executed processes described here. In some embodiments, the I/O device **290** may include a plurality of I/O devices. In some embodiments, the I/O device **290** may include one or more elements of any one or a combination of a component of a system for determining target allocation parameters for initiating targeted communications in complex computing networks, a computing system, a server **102**, and a similar device.

[0070] The I/O device **291** may include a variety of elements that enable a user or a component of a system for determining target allocation parameters for initiating targeted communications in complex computing networks to interface with the server **102**. For example, the I/O device **291** may include a keyboard, a touchscreen, a button, a sensor, a biometric scanner, a laser, a microphone, a camera, an internet-enabled device, and/or another element for receiving and/or

collecting input from a user or from a component of any of the systems described herein. Additionally and/or alternatively, the I/O device **291** may include a display, a screen, a sensor, a vibration mechanism, a light emitting diode (LED), a speaker, a radio frequency identification (RFID) scanner, and/or another element for presenting and/or otherwise outputting data to a user or to a component of any of the systems described herein, including a means to send instructions to any one or more components which may be associated with a determining target allocation parameters for initiating targeted communications in complex computing networks. In some embodiments, the I/O device **291** may communicate with one or more elements of the processor **260** and/or the memory unit **280** to execute operations described herein.

[0071] The I/O calibration unit **292** may facilitate the calibration of the I/O device **291**. For example, the I/O calibration unit **292** may detect and/or determine one or more settings of the I/O device **291**, and then adjust and/or modify settings so that the I/O device **291** may operate more efficiently. In some embodiments, the I/O calibration unit **292** may utilize a media driver **293** (or multiple media drivers) to calibrate the I/O device **291**. The media driver **293** may be installed on a user device so that the user device may recognize and/or integrate with the I/O device **291**, thereby enabling media content to be displayed, received, generated, and the like. In some embodiments, the I/O device **291** may be calibrated by the I/O calibration unit **292** by based on information included in the media driver **293**.

[0072] The communication center **295** may facilitate establishment, maintenance, monitoring, and/or termination of communications between the server **102** and other components of a system for determining target allocation parameters for initiating targeted communications in complex computing networks, other computing environments, third party server systems, and the like. The communication center **295** may further enable communication between various elements (e.g., units and/or subunits) of the server **102** as needed to carry out any one or more of the functions associated with the systems and methods described herein. In some embodiments, the communication center **295** may include a network protocol unit **296**, an API gateway **297**, an encryption engine **298**, and/or a communication device **299**. The communication center **295** may include hardware and/or software elements.

[0073] The network protocol unit **296** may facilitate establishment, maintenance, and/or termination of a communication connection (e.g., communication channel, network communication channel) between the server **102** and any other component of a system for determining target allocation parameters for initiating targeted communications in complex computing networks and/or another device by way of a network. For example, the network protocol unit **296** may detect and/or define a communication protocol required by a particular network and/or network type. Communication protocols utilized by the network protocol unit **296** may include Wi-Fi protocols, Li-Fi protocols, cellular data network protocols, Bluetooth® protocols, WiMAX protocols, Ethernet protocols, power line communication (PLC) protocols, and the like. In some embodiments, facilitation of communication between the server **102** and any other component and/or other device, as well as any element internal to the server **102**, may include transforming and/or translating data from being compatible with a first communication protocol to being compatible with a second communication protocol. In some embodiments, the network protocol unit **296** may determine and/or monitor an amount of data traffic to consequently determine which particular network protocol is to be used for establishing a connection with a component, device, transmitting data, and/or performing other operations described herein.

[0074] The API gateway **297** may facilitate the enablement of other devices and/or computing environments to access the API unit **283** of the memory **280** of the server **102**. For example, a user device may access the API unit **283** via the API gateway **297**. In some embodiments, the API gateway **297** may be required to validate user credentials associated with a user or a computing device (e.g., first computing device, second computing device, etc.) prior to providing access to the API unit **283** to the user or computing device. The API gateway **297** may include instructions for

enabling the server **102** to communicate with another device.

[0075] The encryption engine **298** may facilitate any one or any combination of translation, encryption, encoding, decryption, and decoding of information received, transmitted, and/or stored by the server **102**. For example, the encryption engine **298** may encrypt data associated with a component of a system for determining target allocation parameters for initiating targeted communications in complex computing networks, historical and/or analytical data, images, instantaneous data, etc. Using the encryption engine, each transmission of data may be encrypted, encoded, and/or translated for security reasons, and any received data may be encrypted, encoded, and/or translated prior to its processing and/or storage. In some embodiments, the encryption engine **298** may generate any one or combination of an encryption key, an encoding key, a translation key, and the like, which may be transmitted along with any data content.

[0076] The communication device **299** may include a variety of hardware and/or software specifically purposed to enable communication between the server **102** and another component of a system for determining target allocation parameters for initiating targeted communications in complex computing networks, and/or other device, as well as communication between elements of the server **102**. In some embodiments, the communication device **299** may include one or more radio transceivers, chips, analog front end (AFE) units, antennas, processors, memory, other logic, and/or other components to implement communication protocols (wired or wireless) and related functionality for facilitating communication between the server **102** and any other device and/or component. Additionally and/or alternatively, the communication device **299** may include a modem, a modem bank, an Ethernet device such as a router or switch, a universal serial bus (USB) interface device, a serial interface, a token ring device, a fiber distributed data interface (FDDI) device, a wireless local area network (WLAN) device and/or device component, a radio transceiver device such as code division multiple access (CDMA) device, a global system for mobile communications (GSM) radio transceiver device, a universal mobile telecommunications system (UMTS) radio transceiver device, a long term evolution (LTE) radio transceiver device, a worldwide interoperability for microwave access (WiMAX) device, and/or another device used for communication purposes.

[0077] As used herein, the term “signal” may refer to a single signal or multiple signals. The term “signals” may refer to a single signal or multiple signals. Any reference to a signal may be a reference to an attribute of the signal.

[0078] Any transmission, reception, connection, or communication may occur using any short-range (e.g., Bluetooth, Bluetooth Low Energy, near field communication, Wi-Fi Direct, etc.) or long-range communication mechanism (e.g., Wi-Fi, cellular, etc.). Additionally or alternatively, any transmission, reception, connection, or communication may occur using wired technologies. Any transmission, reception, or communication may occur directly between systems or indirectly via one or more systems such as servers.

[0079] The present disclosure provides several important technical advantages that will be readily apparent to one skilled in the art from the figures, descriptions, and claims. Moreover, while specific advantages have been enumerated above, various embodiments may include all, some, or none of the enumerated advantages. Any sentence or statement in this disclosure may be associated with one or more embodiments.

[0080] While various embodiments in accordance with the disclosed principles have been described above, it should be understood that they have been presented by way of example only, and are not limiting. Furthermore, any reference in this disclosure to “invention” in the singular should not be used to argue that there is only a single point of novelty in this disclosure. Multiple inventions may be set forth herein.

Claims

1. A method for determining one or more allocation parameters for initiating targeted communications, the method comprising: establishing a first network communication channel with a first computing device; receiving, using one or more computing device processors, from the first computing device, on the first network communication channel, a desired allocation associated with a first period; establishing a second network communication channel with a second computing device; receiving, using the one or more computing device processors, from at least one of the second computing device on the second network communication channel or the first computing device on the first network communication channel, first data associated with a first execution event; determining, using the one or more computing device processors, and based on the first data associated with the first execution event, a first available allocation; generating or modifying, using the one or more computing device processors, and based on at least the first available allocation, allocation information associated with a second period; generating or modifying, using the one or more computing device processors, based on at least the first available allocation, a first visual display of the allocation information associated with the second period; establishing a third network communication channel with the second computing device or a third computing device; receiving, using the one or more computing device processors, from at least one of the second computing device on the second network communication channel, the third computing device on the second network communication channel or the third network communication channel, or the first computing device on the first network communication channel, second data associated with the first execution event or a second execution event; determining, using the one or more computing device processors, and based on the second data associated with the first execution event or the second execution event, a second available allocation, wherein the second available allocation is not used to generate the allocation information associated with the second period; determining, using the one or more computing device processors, and based on the allocation information associated with the second period and the second available allocation, a remaining available allocation; generating or modifying, using the one or more computing device processors, a data compilation, wherein the data compilation comprises or is based on at least one of: the first available allocation, the second available allocation, or the remaining available allocation; generating or modifying, using the one or more computing device processors, a second visual display of the data compilation; and determining, using the one or more computing device processors, and based on the data compilation and the desired allocation associated with the first period, one or more allocation parameters for initiating a first targeted communication to a fourth computing device, during at least a portion of a third period, wherein at least one of the first data associated with the first execution event, the second data associated with the second execution event, or the first targeted communication comprises or is associated with third data associated with one or more of: an execution event, an opportunity to allocate as a part of the execution event, a current execution event, a future execution event, an attempted execution event, and a successful execution event, and wherein the first execution event or the second execution event comprises one or more of: a first data transfer, a first data or signal processing operation, a first data allocation, a first material resource allocation, a first energy resource allocation, the first targeted communication, a second communication, and a first computing resource allocation.

2. The method of claim 1, further comprising initiating transmission of, using the one or more computing device processors, on a first communication channel with a database or a memory, at least one of the first available allocation, the second available allocation, the desired allocation associated with the first period, the allocation information associated with the second period, or the data compilation for storage in the database or the memory.

3. The method of claim 1, further comprising initiating retrieval of, using the one or more computing device processors, on a first communication channel with a database or a memory, at least one of the first available allocation, the second available allocation, the desired allocation

associated with the first period, the allocation information associated with the second period, or the data compilation stored in the database or the memory.

4. The method of claim 1, further comprising: establishing a first communication channel with a database or a memory; and initiating retrieval or transmission of, using the one or more computing device processors, on the first communication channel with the database or the memory, at least one of the first available allocation, the second available allocation, the desired allocation associated with the first period, the allocation information associated with the second period, or the data compilation.

5. The method of claim 1, wherein a database comprises a cloud-based database.

6. The method of claim 1, wherein the first targeted communication is associated with a third execution event.

7. The method of claim 6, wherein the third execution event comprises one or more of: a second data transfer, a second data allocation operation, a second data or signal processing operation, a second material resource allocation, a second energy resource allocation, and a second computing resource allocation.

8. The method of claim 1, further comprising: establishing a fourth network communication channel with a fifth computing device; and initiating transmission of, using the one or more computing device processors, on the fourth network communication channel with the fifth computing device, the allocation information associated with the second period or the second visual display of the allocation information associated with the second period.

9. The method of claim 8, wherein the fifth computing device comprises a streaming platform.

10. The method of claim 8, further comprising initiating retrieval of, using the one or more computing device processors, the allocation information associated with the second period from the fifth computing device.

11. A computing system for determining one or more operation parameters associated with determining allocation parameters for initiating targeted communications in complex computing networks, the computing system comprising: at least one memory comprising instructions; and one or more computing device processors for executing the instructions, wherein the instructions cause the one or more computing device processors to perform operations of: establishing a first network communication channel with a first computing device, receiving, from the first computing device, on the first network communication channel, a desired allocation associated with a first period, establishing a second network communication channel with a second computing device, receiving, from at least one of the second computing device on the second network communication channel or the first computing device on the first network communication channel, first data associated with a first execution event, determining, based on the first data associated with the first execution event, a first available allocation, generating or modifying, based on at least the first available allocation, allocation information associated with a second period, generating or modifying, based on at least the first available allocation, a first visual display of the allocation information associated with the second period, establishing a third network communication channel with the second computing device or a third computing device, receiving, from at least one of the second computing device on the second network communication channel, the third computing device on the second network communication channel or the third network communication channel, or the first computing device on the first network communication channel, second data associated with the first execution event or a second execution event, determining, based on the second data associated with the first execution event or the second execution event, a second available allocation, wherein the second available allocation is not used to generate the allocation information associated with the second period, determining, based on the allocation information associated with the second period and the second available allocation, a remaining available allocation, generating or modifying a data compilation, wherein the data compilation comprises or is based on at least one of: the first available allocation, the second available allocation, or the remaining available allocation,

generating or modifying a second visual display of the data compilation; and determining, based on the data compilation and the desired allocation associated with the first period, one or more allocation parameters for initiating a targeted communication to a fourth computing device, during at least a portion of a third period, wherein at least one of the first data associated with the first execution event, the second data associated with the first execution event or the second execution event, or the targeted communication comprises or is associated with third data associated with one or more of: an execution event, an opportunity to allocate as a part of the execution event, a current execution event, a future execution event, an attempted execution event, and a successful execution event, and wherein the first execution event or the second execution event comprises one or more of: a data transfer, a data or signal processing operation, a data allocation, a material resource allocation, an energy resource allocation, the targeted communication, a second communication, and a computing resource allocation.

12. The computing system of claim 11, wherein the instructions further cause the one or more computing device processors to perform initiating transmission of, on a first communication channel with a database or a memory, at least one of the first available allocation, the second available allocation, the desired allocation associated with the first period, the allocation information associated with the second period, or the data compilation for storage in the database or the memory.

13. The computing system of claim 11, wherein the instructions further cause the one or more computing device processors to perform initiating retrieval of, on a first communication channel with a database or a memory, at least one of the first available allocation, the second available allocation, the desired allocation associated with the first period, the allocation information associated with the second period, or the data compilation stored in the database or the memory.

14. The computing system of claim 11, wherein the first network communication channel, the second network communication channel, and the third network communication channel are part of the same communication interface or are part of different communication interfaces.

15. The computing system of claim 11, wherein the instructions further cause the one or more computing device processors to perform: establishing a first communication channel with a database or a memory, and initiating retrieval or transmission of, on the first communication channel with the database or the memory, at least one of the first available allocation, the second available allocation, the desired allocation associated with the first period, the allocation information associated with the second period, or the data compilation.

16. The computing system of claim 11, wherein the instructions further cause the one or more computing device processors to perform: establishing a fourth network communication channel with a fifth computing device, and initiating transmission of, on the fourth network communication channel with the fifth computing device, the allocation information associated with the second period or the second visual display of the allocation information associated with the second period.

17. A non-transitory computer-readable medium for determining allocation parameters for initiating targeted communications in complex computing networks, the non-transitory computer-readable medium comprising code configured for: establishing a first network communication channel with a first computing device; receiving, from the first computing device, on the first network communication channel, a desired allocation associated with a first period; establishing a second network communication channel with a second computing device; receiving, from at least one of the second computing device on the second network communication channel or the first computing device on the first network communication channel, first data associated with a first execution event; determining, based on the first data associated with the first execution event, a first available allocation; generating or modifying, based on at least the first available allocation, allocation information associated with a second period; generating or modifying, based on at least the first available allocation, a first visual display of the allocation information associated with the second period; establishing a third network communication channel with the second computing device or a

third computing device; receiving, from at least one of the second computing device on the second network communication channel, the third computing device on the second network communication channel or the third network communication channel, or the first computing device on the first network communication channel, second data associated with the first execution event or a second execution event; determining, based on the second data associated with the first execution event or the second execution event, a second available allocation, wherein the second available allocation is not used to generate the allocation information associated with the second period; determining, based on the allocation information associated with the second period and the second available allocation, a remaining available allocation; generating or modifying a data compilation, wherein the data compilation comprises or is based on at least one of: the first available allocation, the second available allocation, and the remaining available allocation; generating or modifying a second visual display of the data compilation; and determining, based on the data compilation and the desired allocation associated with the first period, one or more allocation parameters for initiating a targeted communication to a fourth computing device, during at least a portion of a third period, wherein at least one of the first data associated with the first execution event, the second data associated with the first execution event or the second execution event, or the targeted communication comprises or is associated with third data associated with one or more of: an execution event, an opportunity to allocate as a part of the execution event, a current execution event, a future execution event, an attempted execution event, and a successful execution event, and wherein the first execution event or the second execution event comprises one or more of: a data transfer, a data or signal processing operation, a data allocation, a material resource allocation, an energy resource allocation, the targeted communication, a second communication, and a computing resource allocation.

18. The method of claim 1, wherein the first available allocation comprises a first instantaneous available allocation and the second available allocation comprises a second instantaneous available allocation.

19. The method of claim 1, wherein at least one of: the allocation information comprises an allocation graph, or the one or more allocation parameters comprise one or more target allocation parameters.

20. The method of claim 1, wherein the one or more computing device processors are comprised in one or more computing systems, wherein the one or more computing systems are located in one or more locations.
