

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250284793

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

TATE; Kristopher Andrew

EXECUTION CODE PROVISION METHOD AND SOFTWARE DEVELOPMENT SYSTEM

Abstract

A solution that can ensure the security of an application program is provided. An execution code provision method includes: a step of generating a source code according to a user operation; a step of generating an intermediate representation from the source code; a step of verifying whether or not the intermediate representation satisfies a predetermined rule or regulation; and a step of realizing execution of an execution code generated from the intermediate representation when the intermediate representation satisfies the predetermined rule or regulation.

Inventors: TATE; Kristopher Andrew (Kyoto-shi, JP)

Applicant: connectFree Corporation (Kyoto-shi, JP)

Family ID: 74060407

Assignee: connectFree Corporation (Kyoto-shi, JP)

Appl. No.: 19/216372

Filed: May 22, 2025

Foreign Application Priority Data

JP	2019-119106	Jun. 26, 2019
----	-------------	---------------

Related U.S. Application Data

parent US continuation 17622573 20211223 parent-grant-document US 12332994 WO
continuation PCT/JP2020/024799 20200624 child US 19216372

Publication Classification

Int. Cl.: G06F21/51 (20130101); G06F8/60 (20180101)

U.S. Cl.:

CPC G06F21/51 (20130101); G06F8/60 (20130101); G06F2221/033 (20130101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is a Continuation of U.S. application Ser. No. 17/622,573, filed Dec. 23, 2021 which is a National Stage Entry of PCT/JP2020/024799, filed Jun. 24, 2020, which claims priority to Japanese Patent Application No. 2019-119106, filed Jun. 26, 2019, which applications are incorporated herein by reference. To the extent appropriate, a claim of priority is made to each of the above-disclosed applications.

TECHNICAL FIELD

[0002] The present disclosure relates to an execution code provision method and a software development system.

BACKGROUND ART

[0003] The development of information and communication technology (ICT) has been remarkable in recent years, and devices connected to a network, such as the Internet, are not limited to information processing devices, such as conventional personal computers or smartphones, and are spreading to various things. Such a technology trend is called “IoT (Internet of Things)”, and various technologies and services have been proposed and put into practical use. In the future, a world is envisioned in which billions of people on Earth and tens of billions or trillions of devices are connected at the same time. In order to realize such a networked world, it is necessary to provide a solution that is simpler, safer, and more freely connected.

[0004] With the intelligentization of devices used in IoT (also referred to as “edge devices”), it is possible to execute various kinds of application programs in the edge devices. On the other hand, it is not easy to increase the security for edge devices to the same level as the security for servers or personal computers due to resource constraints and the like. Therefore, it is important to verify the application programs installed on the edge devices. For example, JP 2014-174577 A (Patent Document 1) discloses an improvement of a static analysis tool for verifying the vulnerability of a Web application at the source code level. [0005] Patent Document 1: JP 2014-174577 A

SUMMARY OF THE INVENTION

[0006] Application programs used in edge devices and the like are often distributed as intermediate representations before the generation of execution code, not in the form of source code. By adopting such an intermediate representation, there is an advantage that the know-how and the like included in the source code can be concealed and the amount of data can be reduced.

[0007] As disclosed in Patent Document 1 described above, it is common to analyze the source code to evaluate a security hole or vulnerability, but it is not easy to evaluate security hole or vulnerability in formats other than the source code.

[0008] A typical object of the present disclosure is to provide a solution that can ensure the security of an application program, which is suitable for an edge device or the like.

Means for Solving Problem

[0009] An execution code provision method according to an aspect of the present disclosure includes: a step of generating a source code according to a user operation; a step of generating an intermediate representation from the source code; a step of verifying whether or not the intermediate representation satisfies a predetermined rule or regulation; and a step of realizing execution of an execution code generated from the intermediate representation when the

intermediate representation satisfies the predetermined rule or regulation.

[0010] The step of realizing the execution of the execution code may include a step of generating the execution code from the intermediate representation on condition that the intermediate representation satisfies the predetermined rule or regulation.

[0011] The step of realizing the execution of the execution code may include a step of allowing the execution of the execution code generated from the intermediate representation on condition that the intermediate representation satisfies the predetermined rule or regulation.

[0012] The execution code provision method may further include a step of evaluating validity of the execution code based on the certificate issued in association with the intermediate representation, from which the execution code has been generated, when a controller in which the execution code is executed is started.

[0013] The verification step may include a step of issuing a certificate associated with the intermediate representation when the intermediate representation satisfies the predetermined rule or regulation, and the step of allowing the execution of the execution code generated from the intermediate representation may include a step of determining whether or not the execution code is executable based on the certificate.

[0014] The verification step may include a step of notifying a user of a content that the predetermined rule or regulation is not satisfied when the intermediate representation does not satisfy the predetermined rule or regulation.

[0015] A software development system according to another aspect of the present disclosure includes: a software development device for supporting generation of a source code; and a verification server accessible from the software development device. The software development device includes a means for generating an intermediate representation from the source code. The verification server includes a means for verifying whether or not the intermediate representation satisfies a predetermined rule or regulation. When the intermediate representation satisfies the predetermined rule or regulation, execution of an execution code generated from the intermediate representation is realized.

Effect of the Invention

[0016] According to the present disclosure, it is possible to provide a solution that can ensure the security of an application program.

Description

BRIEF DESCRIPTION OF DRAWINGS

[0017] FIG. 1 is a diagram for describing an overview of processing in a software development system according to the present embodiment;

[0018] FIG. 2 is a diagram showing an overview of a procedure for generating an execution code from a source code in the software development system according to the present embodiment;

[0019] FIG. 3 is a diagram showing an overview of a procedure for generating an execution code from a source code in the software development system according to the present embodiment;

[0020] FIG. 4 is a schematic diagram showing a hardware configuration example of a software development device according to the present embodiment;

[0021] FIG. 5 is a schematic diagram showing a hardware configuration example of a verification server according to the present embodiment; and

[0022] FIG. 6 is a flowchart showing an example of a processing procedure in the software development system according to the present embodiment.

MODE(S) FOR CARRYING OUT THE INVENTION

[0023] An embodiment according to the present disclosure will be described in detail with reference to the diagrams. In addition, the same or corresponding portions in the diagrams are

denoted by the same reference numerals, and the description thereof will not be repeated.

<A. Overview>

[0024] First, an overview of processing in a software development system **1** according to the present embodiment will be described. In the present embodiment, an intermediate representation **20** itself generated from a source code **10** is verified, and the generation of a corresponding execution code **30** or the execution of the generated execution code **30** is allowed on condition that the verification result is appropriate. In the verification of the intermediate representation **20**, it is determined that the intermediate representation **20** is appropriate when a predetermined rule or regulation is satisfied.

[0025] In this specification, the “intermediate representation” includes a machine language for a corresponding virtual machine, which is generated from a source code written in an arbitrary programming language (usually a high-level language) by targeting a specific virtual machine, in a compiler base. However, the “intermediate representation” does not necessarily have to be in a binary format, and may be expressed in a format similar to the natural language such as an assembler language. In addition, the “intermediate representation” may adopt any representation format as long as the “intermediate representation” is generated by targeting a specific virtual machine.

[0026] Typically, the “intermediate representation” is generated independently of the platform and architecture on which the execution code **30** is executed. A static compiler may be used to generate the intermediate representation **20** from the source code **10**. In addition, the “intermediate representation” may be compiled as the execution code **30** directed to a specific platform and architecture. The “intermediate representation” and the “execution code” are generated as a set. In the “intermediate representation”, the amount of data is reduced as compared with the original source code, and the described processing itself can be made more efficient.

[0027] The generation of the intermediate representation **20** from the source code **10** is basically a one-way conversion, and accordingly, it is difficult to completely restore the source code **10** from the intermediate representation **20**. Bidirectional conversion is also possible between the intermediate representation **20** and the execution code **30**. FIG. **1** is a diagram for describing an overview of processing in the software development system **1** according to the present embodiment. FIG. **1(A)** shows an example in which the successful verification of the intermediate representation **20** generated from the source code **10** is the generation condition of the execution code **30**. FIG. **1(B)** shows an example in which the successful verification of the intermediate representation **20** generated from the source code **10** is the execution condition of the execution code **30** generated from the intermediate representation **20**.

[0028] As shown in FIGS. **1(A)** and **1(B)**, the intermediate representation **20** generated from the source code **10** is verified by an arbitrary subject. In the examples shown in FIGS. **1(A)** and **1(B)**, an example in which a verification server **200** verifies the intermediate representation **20** is shown, but the invention is not limited thereto, and the verification may be performed by any subject.

[0029] Referring to FIG. **1(A)**, when the verification result from the verification server **200** is appropriate, the verification server **200** gives authentication to the intermediate representation **20**. The execution code **30** is generated from the intermediate representation **20** with authentication for the intermediate representation **20** as a generation condition. Thus, the verification for the intermediate representation **20** may be included in the generation condition of the execution code **30**. By adopting such a generation condition, the security of the generated execution code **30** can be enhanced.

[0030] Referring to FIG. **1(B)**, when the verification result from the verification server **200** is appropriate, the verification server **200** issues a certificate **40** including authentication for the intermediate representation **20**. At the same time, the execution code **30** is generated from the intermediate representation **20**. The generated execution code **30** may be executed on condition that the corresponding certificate **40** is present. Thus, the presence of the certificate **40** for the

intermediate representation **20** may be included in the execution condition of the execution code **30**. By adopting such an execution condition, it is possible to reduce the possibility that the execution code **30** is executed in a state in which the security is not ensured.

[0031] As described above, in a series of processes in the present embodiment, when the intermediate representation **20** satisfies a predetermined rule or regulation (when the verification result is appropriate), authentication is given to allow the generation or execution of the execution code **30** corresponding to the intermediate representation **20**. On the contrary, when the intermediate representation **20** does not satisfy a predetermined rule or regulation (when the verification result is not appropriate), authentication is not given and accordingly, the execution code **30** corresponding to the intermediate representation **20** cannot be generated or executed. That is, when the intermediate representation **20** satisfies a predetermined rule or regulation, the execution of the execution code **30** generated from the intermediate representation **20** is realized.

[0032] As a process for realizing the execution of the execution code **30**, as shown in FIG. 1(A), a process of generating the execution code **30** from the intermediate representation **20** may be adopted on condition that the intermediate representation **20** satisfies a predetermined rule or regulation. Alternatively, as a process for realizing the execution of the execution code **30**, as shown in FIG. 1(B), a process of allowing the execution of the execution code **30** generated from the intermediate representation **20** may be adopted on condition that the intermediate representation **20** satisfies a predetermined rule or regulation. At this time, whether or not to allow the execution of the execution code **30** generated from the intermediate representation **20** may be determined based on the certificate **40** associated with the intermediate representation **20**. In addition, whether or not the execution is possible may be determined according to the execution environment of the execution code **30** (a processor or a microcomputer including a processor).

[0033] As described above, in the present embodiment, by verifying the intermediate representation **20** instead of the source code **10**, safety risks included in the application program can be more efficiently found in a state in which the know-how and the like included in the source code **10** are concealed. In addition, by verifying the intermediate representation **20**, it is not necessary to prepare a plurality of verification rule sets according to the type of programming language used in the description of the source code **10**. As a result, it is possible to realize efficient verification.

[0034] Next, an example of a procedure for generating the execution code **30** using the software development system **1** according to the present embodiment will be described. FIGS. 2 and 3 are diagrams showing an overview of a procedure for generating the execution code **30** from the source code **10** in the software development system **1** according to the present embodiment.

[0035] Referring to FIG. 2, the software development system **1** includes one or more software development devices **100** and the verification server **200** accessible from the software development device **100** through the Internet **2** or the like.

[0036] The software development device **100** supports the creation of an application program executed by a controller **300** included in an edge device **4**. However, the technical scope of the invention is not limited to the creation of an application program executed by the edge device **4**, and can be applied to the creation of an application program executed by any computing device.

[0037] An integrated development environment (IDE) is provided for the software development device **100**, so that the user can create an arbitrary application program in the integrated development environment.

[0038] The controller **300** included in the edge device **4** is an example of a computing device, and includes a processor. The edge device **4** may be any device, but typically, factory facilities, various devices in the home, social infrastructure equipment, movable bodies such as vehicles, arbitrary portable devices, and the like are assumed. As will be described later, the controller **300** has a processor, so that it is possible to execute an application program from the software development device **100**.

[0039] First, the user generates a source code by using the software development device **100** ((1)

Source code generation). Then, the generated source code is compiled by the software development device **100** to generate the intermediate representation **20** ((2) Intermediate representation generation).

[0040] The intermediate representation **20** is verified before the execution code **30** is generated from the intermediate representation **20**. In the example shown in FIG. 2, the generated intermediate representation **20** is transmitted to the verification server **200** ((3) Intermediate representation verification request). Then, the verification server **200** verifies the intermediate representation **20** from the software development device **100** ((4) Verification of intermediate representation). The verification server **200** responds to the software development device **100** with the verification result. If the target intermediate representation **20** passes all the verifications, the verification server **200** transmits an authentication indicating that the verification results are appropriate to the software development device **100**.

[0041] When the software development device **100** receives the authentication indicating that the verification results are appropriate from the verification server **200** ((5) Reception of verification result (authentication)), the software development device **100** generates the execution code **30** from the intermediate representation **20** ((6) Execution code generation).

[0042] Then, the software development device **100** transmits the generated execution code **30** to the controller **300** of the edge device **4** ((7) Execution code transmission). Then, the controller **300** of the edge device **4** executes the transmitted execution code **30** as needed ((8) Execution of execution code).

[0043] Due to the series of processes shown in FIGS. 2 and 3, a secure application program can be executed in the controller **300** of the edge device **4**.

B. Hardware Configuration Example

[0044] Next, a hardware configuration example of a main device configuring the software development system **1** according to the present embodiment will be described.

(b1: Software Development Device **100**)

[0045] The software development device **100** is typically realized by a general-purpose computer.

[0046] FIG. 4 is a schematic diagram showing a hardware configuration example of the software development device **100** according to the present embodiment. Referring to FIG. 4, the software development device **100** includes a processor **102**, a main memory **104**, an input unit **106**, a display **108**, a hard disk **110**, and a communication interface **122** as main components. These components are connected to each other through an internal bus **120**.

[0047] The processor **102** may be, for example, a CPU (Central Processing Unit) or a GPU (Graphics Processing Unit). A plurality of processors **102** may be disposed, or the processor **102** having a plurality of cores may be adopted.

[0048] The main memory **104** is a volatile storage device, such as a DRAM (Dynamic Random Access Memory) or a SRAM (Static Random Access Memory). The hard disk **110** holds various programs executed by the processor **102** or various kinds of data. In addition, instead of the hard disk **110**, a non-volatile storage device such as an SSD (Solid State Drive) or a flash memory may be adopted. Among the programs stored in the hard disk **110**, a designated program code is loaded to the main memory **104**, and the processor **102** sequentially executes computer-readable instructions included in the program code loaded to the main memory **104** to realize various functions described later.

[0049] Typically, the hard disk **110** stores the source code **10** arbitrarily generated by the user, a software development program **114** for realizing an integrated development environment, and the execution code **30** generated from the source code **10**. The software development program **114** generates the execution code **30** from the source code **10** arbitrarily generated by the user through the intermediate representation **20**, and includes a module for providing an application program development environment. However, the generation or execution of the corresponding execution code **30** is allowed on condition that the verification result of the intermediate representation **20** is

appropriate.

[0050] The input unit **106** receives an input operation of the user who operates the software development device **100**. The input unit **106** may be, for example, a keyboard, a mouse, a touch panel disposed on a display device, or an operation button disposed on the housing of the software development device **100**.

[0051] The display **108** displays the processing result of the processor **102** and the like. The display **108** may be, for example, an LCD (Liquid Crystal Display) or an organic EL (Electro-Luminescence) display.

[0052] The communication interface **122** is in charge of data exchange with the verification server **200**. The communication interface **122** may include, for example, an Ethernet (registered trademark) port for communication over the Internet.

[0053] In addition, the entirety or part of the software development device **100** may be realized by using a hard-wired circuit such as an ASIC (Application Specific Integrated Circuit) in which a circuit corresponding to computer-readable instructions is provided. In addition, the entirety or part of the software development device **100** may be realized by using a circuit corresponding to computer-readable instructions on an FPGA (field-programmable gate array). In addition, the entirety or part of the software development device **100** may be realized by appropriately combining the processor **102**, a main memory, an ASIC, an FPGA, and the like.

[0054] The software development device **100** may further include a component for reading the stored program or the like from the non-transitory media that stores the software development program **114** including computer-readable instructions. The media may be, for example, an optical medium, such as a DVD (Digital Versatile Disc), or a semiconductor medium, such as a USB memory.

[0055] In addition, the software development program **114** may not only be installed on the software development device **100** through the media, but also be provided from a distribution server on the network.

(b2: Verification Server **200**)

[0056] The verification server **200** is also typically realized by a general-purpose computer. FIG. 5 is a schematic diagram showing a hardware configuration example of the verification server **200** according to the present embodiment. Referring to FIG. 5, the verification server **200** includes one or more processors **202**, a main memory **204**, an input unit **206**, a display **208**, a hard disk **210**, and a communication interface **222** as main components. These components are connected to each other through an internal bus **220**.

[0057] The processor **202** is, for example, a CPU or a GPU. A plurality of processors **202** may be disposed, or the processor **202** having a plurality of cores may be adopted.

[0058] The main memory **204** is a volatile storage device, such as a DRAM or an SRAM. The hard disk **210** holds various kinds of data or various programs executed by the processor **202**. In addition, instead of the hard disk **210**, a non-volatile storage device such as an SSD or a flash memory may be adopted. Among the programs stored in the hard disk **210**, a designated program code is loaded to the main memory **204**, and the processor **202** sequentially executes computer-readable instructions included in the program code loaded to the main memory **204** to realize various functions described later.

[0059] Typically, the hard disk **210** stores an evaluation engine **212** for executing evaluation processing in response to a request from the outside, a certificate issuing engine **214** for issuing a certificate according to the evaluation result from the evaluation engine **212**, and an evaluation rule **216** used for the evaluation processing of the evaluation engine **212**. The evaluation engine **212** verifies whether or not the intermediate representation **20** satisfies a predetermined rule or regulation. The certificate issuing engine **214** issues the certificate **40** associated with the intermediate representation **20** when the intermediate representation **20** satisfies a predetermined rule or regulation. Details of the operations, data structures, and the like of these elements will be

described later.

[0060] The input unit **206** receives an input operation of a user who operates the controller **300**. The display **208** displays the processing result of the processor **202** and the like. The communication interface **222** is in charge of data exchange with the software development device **100**. The communication interface **222** may include, for example, an Ethernet (registered trademark) port for communication over the Internet.

[0061] In addition, the entirety or part of the verification server **200** may be realized by using a hard-wired circuit such as an ASIC in which a circuit corresponding to computer-readable instructions is provided. In addition, alternatively, the entirety or part of the verification server **200** may be realized by using a circuit corresponding to computer-readable instructions on the FPGA. In addition, the entirety or part of the verification server **200** may be realized by appropriately combining the processor **202**, a main memory, an ASIC, an FPGA, and the like.

[0062] In addition, a program required for execution may not only be installed on the verification server **200** through the media but also be provided from a distribution server on the network.

<C. Verification Process>

[0063] Next, a verification process in the software development system **1** according to the present embodiment will be described.

[0064] As described above, the verification of the intermediate representation **20** in the present embodiment includes a process of determining whether or not the intermediate representation **20** satisfies a predetermined rule or regulation.

[0065] The predetermined rule or regulation includes conditions for the application program (intermediate representation **20** and corresponding execution code **30**) to be secure. Typical conditions for such security include the following. [0066] (1) Does not include a memory operation (or dangerous memory operation) whose security cannot be confirmed (or such a memory operation is not compilable) [0067] (2) There is no undefined operation in the code [0068] (3) Error handling syntax is not missing (error handling syntax is properly included) [0069] (4) Does not include disordered error handling

[0070] The memory operation (or dangerous memory operation) for which the security in the above (1) cannot be confirmed includes memory access to the system area or secure area and memory operations, such as block erasure or block writing for the memory area.

[0071] The undefined operation in the above (2) includes a procedure or a function for which processing is not defined in the code.

[0072] The error handling syntax in the above (3) includes a description that defines processing when an exception occurs.

[0073] The disordered error handling in the above (4) includes excessive error handling when an exception occurs.

[0074] In addition, the predetermined rule or regulation includes that a so-called backdoor is not present in the application program (intermediate representation **20** and corresponding execution code **30**). The backdoor is a function or connection port for a (usually malicious) third party to access the application program in a way that the user of the application program does not recognize. In the verification of the intermediate representation **20**, it is determined whether or not the access route from the outside is included in the intermediate representation **20**.

[0075] The verification process as described above may be realized by referring to the evaluation rule **216** (FIG. 5) including a predetermined rule or regulation, or a verification model for realizing the verification process may be sequentially updated by using machine learning, such as so-called AI (Artificial Intelligence).

[0076] The verification process in the software development system **1** according to the present embodiment may be executed by the verification server **200** or may be executed by the software development device **100**. When the verification process is executed by the verification server **200**, this may be implemented in the form of cloud computing. In addition, when the verification

process is executed by the software development device **100**, the evaluation rule **216** certified by an external certification authority may be used.

[0077] Regarding the verification process in the software development system **1** according to the present embodiment, the user or the like may be notified of the details of the content determined not to satisfy the predetermined rule or regulation.

<D. Processing Procedure>

[0078] Next, a processing procedure in the software development system **1** according to the present embodiment will be described.

[0079] FIG. **6** is a flowchart showing an example of a processing procedure in the software development system **1** according to the present embodiment. The process executed by the software development device **100** shown in FIG. **6** may be typically realized by the processor **102** of the software development device **100** executing the software development program **114**. Similarly, the process executed by the verification server **200** may be typically realized by the processor **202** of the verification server **200** executing a necessary program.

[0080] Referring to FIG. **6**, the software development device **100** generates the source code **10** according to the user operation (step **S100**). After generating the source code **10**, the software development device **100** compiles the source code **10** according to the user operation to generate the intermediate representation **20** from the source code **10** (step **S102**).

[0081] The software development device **100** requests the verification server **200** to verify the generated intermediate representation **20** (step **S104**), and waits for a response from the verification server **200** (step **S106**). In response to the verification request from the software development device **100**, the verification server **200** verifies the requested intermediate representation **20** (step **S200**).

[0082] That is, in steps **S104** and **S200**, a process of verifying whether or not the intermediate representation **20** satisfies a predetermined rule or regulation is executed.

[0083] If the verification result is appropriate (YES in step **S202**), the software development device **100** responds to the software development device **100** with the authentication for the intermediate representation **20** (step **S204**). On the other hand, if the verification result is not appropriate (NO in step **S202**), the software development device **100** does not give authentication to the intermediate representation **20** and responds to the software development device **100** that the verification result is inappropriate (step **S206**).

[0084] When the verification server **200** responds with the authentication for the intermediate representation **20** (YES in step **S108**), the software development device **100** generates the execution code **30** from the target intermediate representation **20** (step **S110**). Then, the software development device **100** transmits the generated execution code **30** to the target controller **300** (step **S112**). Then, the process ends.

[0085] Thus, when the intermediate representation **20** satisfies a predetermined rule or regulation, the execution of the execution code **30** generated from the intermediate representation **20** is realized.

[0086] On the other hand, if the verification server **200** does not respond with the authentication for the intermediate representation **20** (NO in step **S108**), the software development device **100** notifies the user that the source code **10** or the intermediate representation **20** does not satisfy the predetermined rule or regulation (step **S114**). Thus, when the intermediate representation **20** does not satisfy a predetermined rule or regulation, a process of notifying the user of the content that the predetermined rule or regulation is not satisfied may be adopted. Then, the process ends.

<E. Execution Environment>

[0087] The execution code **30** generated in the software development system **1** according to the present embodiment is preferably stored in the secure area of a processor or a microcomputer configuring the controller **300** at the distribution destination. That is, it is preferable to take some measures in the execution environment so that the execution code **30** generated on condition that

the intermediate representation **20** is authenticated is not falsified.

[0088] In addition, a signature (for example, a hash value generated from the authenticated intermediate representation **20**) common to both the certificate **40** for the intermediate representation **20** generated in the software development system **1** according to the present embodiment and the execution code **30** generated from the intermediate representation **20** may be embedded, and the condition may be the presence of the corresponding certificate **40**. In this case, in the environment in which the execution code **30** is executed (typically, the firmware of the microcomputer), a process of checking the match between the signature included in the execution code **30** and the signature included in the corresponding certificate **40** may be implemented.

[0089] In addition, in the execution environment, the evaluation (determination of validity) of whether or not to execute the execution code **30** may be performed at any timing, but typically, may be performed when the controller **300**, which is the execution environment, is started (during firmware startup or before the start of application execution immediately after the startup). That is, when the controller **300** in which the execution code **30** is executed is started, the validity of the execution code **30** may be evaluated based on the certificate **40** issued in association with the intermediate representation **20** from which the execution code **30** has been generated. By checking that the execution code **30** of the application program is authenticated when the controller **300** is started, it is possible to avoid a situation in which an unfavorable process is executed by the controller **300** or the like.

F. Modification Example

[0090] When the software development device **100** requests the verification server **200** to verify the intermediate representation **20**, the target intermediate representation **20** may be encrypted. As a result, it is possible to prevent falsification of the intermediate representation **20** exchanged between the software development device **100** and the verification server **200**.

[0091] The certificate **40** issued by the verification server **200** may be given a signature from a certificate authority or the like. As a result, it is possible to prevent fraudulent acts such as falsification of the certificate **40** issued by the verification server **200**.

[0092] In the above description, a configuration example in which the software development device **100** executes the process of generating the source code **10**, the process of generating the intermediate representation **20**, and the process of generating the execution code **30** has been described. However, these processes may be executed in a distributed manner by a plurality of computing devices.

[0093] The framework for verifying the intermediate representation **20** and issuing the certificate **40** showing the verification result according to the present embodiment can also be applied to a mechanism for selling or distributing the application. For example, when an application developer uploads an application program (execution code **30**) to an application distribution server, the application developer is requested to upload the application program (execution code **30**) together with the corresponding intermediate representation **20** and/or certificate **40**, so that the execution code **30** to be distributed can be directly or indirectly verified on the application distribution server side. In this manner, by introducing the mechanism according to the present embodiment, it is possible to avoid a situation in which an application program having a backdoor or the like is distributed.

<G. Advantages>

[0094] In the present embodiment, by verifying the intermediate representation **20** instead of the source code **10**, the security risk included in the application program can be more efficiently found in a state in which the know-how and the like included in the source code **10** are concealed. In addition, by verifying the intermediate representation **20**, it is not necessary to prepare a plurality of verification rule sets according to the type of programming language used in the description of the source code **10**. As a result, it is possible to realize efficient verification.

[0095] It should be considered that the embodiment disclosed is an example in all points and not

restrictive. The scope of the invention is defined by the claims rather than the above description, and is intended to include all modifications within the scope and meaning equivalent to the claims.
Explanations of Letters or Numerals

[0096] **1** SOFTWARE DEVELOPMENT SYSTEM [0097] **2** INTERNET [0098] **4** EDGE DEVICE [0099] **10** SOURCE CODE [0100] **20** INTERMEDIATE REPRESENTATION [0101] **30** EXECUTION CODE [0102] **40** CERTIFICATE [0103] **100** SOFTWARE DEVELOPMENT DEVICE [0104] **102, 202** PROCESSOR [0105] **104, 204** MAIN MEMORY [0106] **106, 206** INPUT UNIT [0107] **108, 208** DISPLAY [0108] **110, 210** HARD DISK [0109] **114** SOFTWARE DEVELOPMENT PROGRAM [0110] **120, 220** INTERNAL BUS [0111] **122, 222** COMMUNICATION INTERFACE [0112] **200** VERIFICATION SERVER [0113] **212** EVALUATION ENGINE [0114] **214** CERTIFICATE ISSUING ENGINE [0115] **216** EVALUATION RULE [0116] **300** CONTROLLER

Claims

1. An execution code provision method, comprising: a step of generating a source code according to a user operation; a step of generating an intermediate representation from the source code; a step of verifying whether or not the intermediate representation satisfies a predetermined rule or regulation; and a step of realizing execution of an execution code generated from the intermediate representation when the intermediate representation satisfies the predetermined rule or regulation.
2. The execution code provision method according to claim 1, wherein the step of realizing the execution of the execution code includes a step of generating the execution code from the intermediate representation on condition that the intermediate representation satisfies the predetermined rule or regulation.
3. The execution code provision method according to claim 1, wherein the step of realizing the execution of the execution code includes a step of allowing the execution of the execution code generated from the intermediate representation on condition that the intermediate representation satisfies the predetermined rule or regulation.
4. The execution code provision method according to claim 3, wherein the verification step includes a step of issuing a certificate associated with the intermediate representation when the intermediate representation satisfies the predetermined rule or regulation, and the step of allowing the execution of the execution code generated from the intermediate representation includes a step of determining whether or not the execution code is executable based on the certificate.
5. The execution code provision method according to claim 4, further comprising: a step of evaluating validity of the execution code based on the certificate issued in association with the intermediate representation, from which the execution code has been generated, when a controller in which the execution code is executed is started.
6. The execution code provision method according to claim 1, wherein the verification step includes a step of notifying a user of a content that the predetermined rule or regulation is not satisfied when the intermediate representation does not satisfy the predetermined rule or regulation.
7. A software development system, comprising: a software development device for supporting generation of a source code; and a verification server accessible from the software development device, wherein the software development device includes a means for generating is configured to generate an intermediate representation from the source code, the verification server includes a means for verifying is configured to verify whether or not the intermediate representation satisfies a predetermined rule or regulation, and when the intermediate representation satisfies the predetermined rule or regulation, execution of an execution code generated from the intermediate representation is realized.
8. The software development system according to claim 7, wherein the software development device is configured to generate the execution code from the intermediate representation on

condition that the intermediate representation satisfies the predetermined rule or regulation.

9. The software development system according to claim 7, wherein the software development device is configured to allow the execution of the execution code generated from the intermediate representation on condition that the intermediate representation satisfies the predetermined rule or regulation.

10. The software development system according to claim 9, wherein the verification server is configured to issue a certificate associated with the intermediate representation when the intermediate representation satisfies the predetermined rule or regulation, and the software development device is configured to determine whether or not the execution code is executable based on the certificate.

11. The software development system according to 9, wherein validity of the execution code is evaluated based on the certificate issued in association with the intermediate representation, from which the execution code has been generated, when a controller in which the execution code is executed is started.

12. The software development system according to claim 7, wherein the verification server is configured to notify a user of a content that the predetermined rule or regulation is not satisfied when the intermediate representation does not satisfy the predetermined rule or regulation.
