

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250286999

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

FUKUSHIMA; Shigeru et al.

PICTURE ENCODING DEVICE, PICTURE ENCODING METHOD, AND PICTURE ENCODING PROGRAM, AND PICTURE DECODING DEVICE, PICTURE DECODING METHOD, AND PICTURE DECODING PROGRAM

Abstract

Provided is a picture encoding device that divides a picture into blocks and performs encoding for each of the divided blocks. A primary signal block divider divides a primary signal of the picture into rectangles having a predetermined size, and generates a primary signal block. A secondary signal block divider divides a secondary signal of the picture into rectangles having a predetermined size, and generates a secondary signal block. A primary signal predictor predicts a primary signal, and a secondary signal predictor predicts a secondary signal. The secondary signal predictor can perform inter prediction of predicting a secondary signal from an encoded primary signal, and the inter prediction is restricted based on at least one of a size of the primary signal block and a size of the secondary signal block.

Inventors: FUKUSHIMA; Shigeru (Yokohama-shi, JP), NAKAMURA; Hiroya (Yokohama-shi, JP), KUMAKURA; Toru (Yokohama-shi, JP)

Applicant: Godo Kaisha IP Bridge1 (Tokyo, JP)

Family ID: 63918195

Appl. No.: 19/216512

Filed: May 22, 2025

Foreign Application Priority Data

JP 2017-089252 Apr. 28, 2017

Related U.S. Application Data

parent US continuation 18594555 20240304 parent-grant-document US 12335475 child US 19216512
parent US continuation 17968219 20221018 parent-grant-document US 11973946 child US 18594555
parent US continuation 17197495 20210310 parent-grant-document US 11523114 child US 17968219
parent US continuation 16665031 20191028 parent-grant-document US 10979710 child US 17197495
parent WO continuation PCT/JP2018/011953 20180326 PENDING child US 16665031

Publication Classification

Int. Cl.: **H04N19/119** (20140101); **H04N19/176** (20140101); **H04N19/186** (20140101);
H04N19/50 (20140101); **H04N19/96** (20140101)

U.S. Cl.:

CPC **H04N19/119** (20141101); **H04N19/176** (20141101); **H04N19/186** (20141101);
H04N19/50 (20141101); **H04N19/96** (20141101);

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION [0001] This application is a continuation of U.S. Ser. No. 18/594,555, filed Mar. 4, 2024; which is a continuation of U.S. Ser. No. 17/968,219, filed Oct. 18, 2022, now U.S. Pat. No. 11,973,946, issued Apr. 30, 2024; which is a continuation U.S. Ser. No. 17/197,495, filed Mar. 10, 2021, now U.S. Pat. No. 11,523,114, issued Dec. 6, 2022; which is a continuation of U.S. Ser. No. 16/665,031, filed Oct. 28, 2019, now U.S. Pat. No. 10,979,710, issued Apr. 13, 2021; which is a continuation of International Application No. PCT/JP2018/011953, filed Mar. 26, 2018; which claims the benefit of priority from the prior Japanese Patent Application No. 2017-089252, filed Apr. 28, 2017, the entire contents of which are incorporated herein by reference.

BACKGROUND OF THE INVENTION

1. Field of the Invention

[0002] The present invention relates to a technique of dividing a picture into blocks, and performing encoding and decoding for each of the divided blocks.

2. Description of the Related Art

[0003] In picture encoding and decoding, a picture is divided into blocks being a groups each including a predetermined number of pixels, and encoding and decoding are performed for each block. By performing appropriate division of blocks, encoding efficiency of intra prediction and inter prediction is enhanced. In addition, in the intra prediction, by predicting a secondary signal from a decoded picture of a primary signal, encoding efficiency is enhanced.

[0004] [patent document 1] JP2013-90015 A

[0005] Nevertheless, if a secondary signal is predicted from a decoded picture of a primary signal, a processing amount increases and dependence relationship between processing on the primary signal and processing on the secondary signal is generated, and it becomes difficult to perform parallel processing.

SUMMARY OF THE INVENTION

[0006] The present invention has been devised in view of such a situation, and the object of the

present invention is to provide a technique of enhancing encoding efficiency by performing block division suitable for picture encoding and decoding.

[0007] For solving the above-described issues, a picture encoding device according to one embodiment of the present invention is a picture encoding device that divides a picture into blocks and performs encoding for each of the divided blocks, and the picture encoding device includes a primary signal block divider (**101**) structured to divide a primary signal of the picture into rectangles having a predetermined size, and generate a primary signal block, a secondary signal block divider (**101**) structured to divide a secondary signal of the picture into rectangles having a predetermined size, and generate a secondary signal block, a primary signal predictor (**102**) structured to predict a primary signal, and a secondary signal predictor (**102**) structured to predict a secondary signal. The secondary signal predictor (**102**) can perform inter prediction of predicting a secondary signal from an encoded primary signal, and the inter prediction is restricted based on at least one of a size of the primary signal block and a size of the secondary signal block.

[0008] Another embodiment of the present invention is a picture encoding method. The method is a picture encoding method that divides a picture into blocks and performs encoding for each of the divided blocks, and the picture encoding method includes a primary signal block division step of dividing a primary signal of the picture into rectangles having a predetermined size, and generating a primary signal block, a secondary signal block division step of dividing a secondary signal of the picture into rectangles having a predetermined size, and generating a secondary signal block, a primary signal prediction step of predicting a primary signal, and a secondary signal prediction step of predicting a secondary signal. The secondary signal prediction step can perform inter prediction of predicting a secondary signal from an encoded primary signal, and the inter prediction is restricted based on at least one of a size of the primary signal block and a size of the secondary signal block.

[0009] Yet another embodiment of the present invention is a picture decoding device. The device is a picture decoding device that divides a picture into blocks and performs decoding for each of the divided blocks, and the picture decoding device includes a primary signal block divider (**202**) structured to divide a primary signal of the picture into rectangles having a predetermined size, and generate a primary signal block, a secondary signal block divider (**202**) structured to divide a secondary signal of the picture into rectangles having a predetermined size, and generate a secondary signal block, a primary signal predictor (**204**) structured to predict a primary signal, and a secondary signal predictor (**204**) structured to predict a secondary signal. The secondary signal predictor (**204**) can perform inter prediction of predicting a secondary signal from a decoded primary signal, and the inter prediction is restricted based on at least one of a size of the primary signal block and a size of the secondary signal block.

[0010] Yet another embodiment of the present invention is a picture decoding method. The method is a picture decoding method that divides a picture into blocks and performs decoding for each of the divided blocks, and the picture decoding method includes a primary signal block division step of dividing a primary signal of the picture into rectangles having a predetermined size, and generating a primary signal block, a secondary signal block division step of dividing a secondary signal of the picture into rectangles having a predetermined size, and generating a secondary signal block, a primary signal prediction step of predicting a primary signal, and a secondary signal prediction step of predicting a secondary signal. The secondary signal prediction step can perform inter prediction of predicting a secondary signal from a decoded primary signal, and the inter prediction is restricted based on at least one of a size of the primary signal block and a size of the secondary signal block.

[0011] In addition, any combination of the above-described constituent elements, and an aspect obtained by converting a wording in the present invention between a method, an apparatus, a system, a recording medium, a computer program, and the like are also effective as an aspect of the present invention.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0012] Embodiments will now be described, by way of example only, with reference to the accompanying drawings which are meant to be exemplary, not limiting, and wherein like elements are numbered alike in several Figures, in which:

[0013] FIG. 1 is a configuration diagram of a picture encoding device according to a first embodiment;

[0014] FIG. 2 is a configuration diagram of a picture decoding device according to the first embodiment;

[0015] FIG. 3 is a flowchart illustrating division into tree blocks and division of each tree block;

[0016] FIG. 4 is a diagram illustrating a state in which an input picture is divided into tree blocks;

[0017] FIG. 5 is a diagram illustrating z-scan;

[0018] FIG. 6 is a diagram illustrating a tree block divided into four in horizontal and vertical directions;

[0019] FIG. 7 is a diagram illustrating a tree block divided into two in the horizontal direction;

[0020] FIG. 8 is a diagram illustrating a tree block divided into two in the vertical direction;

[0021] FIG. 9 is a flowchart illustrating processing on each divided block when a tree block is divided into four in the horizontal and vertical directions;

[0022] FIG. 10 is a flowchart illustrating processing on each divided block when a tree block is divided into two in the horizontal direction;

[0023] FIG. 11 is a diagram illustrating a state of redivision of divided block when a tree block is divided into two in the horizontal direction;

[0024] FIG. 12 is a flowchart illustrating processing on each divided block when a tree block is divided into two in the vertical direction;

[0025] FIG. 13 is a diagram illustrating a state of redivision of divided block when a tree block is divided into two in the vertical direction;

[0026] FIG. 14 is a diagram illustrating an example of a syntax regarding block division of the first embodiment;

[0027] FIGS. 15A, 15B, 15C, and 15D, are a diagram illustrating intra prediction;

[0028] FIG. 16 is a diagram illustrating inter prediction;

[0029] FIGS. 17A, 17B, and 17C are a diagram illustrating a color difference format;

[0030] FIG. 18 is a diagram illustrating luminance color difference intra prediction;

[0031] FIG. 19 is a flowchart illustrating luminance color difference intra prediction;

[0032] FIGS. 20A and 20B are a diagram illustrating a case where a size of a color difference block is larger than a size of a luminance block;

[0033] FIGS. 21A and 21B are a diagram illustrating a case where a size of a color difference block is smaller than a size of a luminance block;

[0034] FIG. 22 is a diagram illustrating an example of a syntax of an intra color difference prediction mode;

[0035] FIG. 23 is a diagram illustrating an example of restricting intra color difference prediction by replacing a neighboring pixel; and

[0036] FIGS. 24A, 24B, and 24C are a diagram illustrating luminance color difference intra prediction that is based on a difference in size of a luminance block.

DETAILED DESCRIPTION OF THE INVENTION

[0037] The invention will now be described by reference to the preferred embodiments. This does not intend to limit the scope of the present invention, but to exemplify the invention.

[0038] An embodiment of the present invention provides a picture encoding technique of dividing a picture into rectangular blocks, and encoding/decoding a divided block.

First Embodiment

[0039] A picture encoding device **100** and a picture decoding device **200** according to a first embodiment of the present invention will be described.

[0040] FIG. **1** is a configuration diagram of the picture encoding device **100** according to the first embodiment. Here, FIG. **1** illustrates only a flow of data regarding a picture signal, and a flow of data regarding additional information is not illustrated. Each constituent element supplies the additional information other than a picture signal, such as a motion vector or a prediction mode, to a bitstream generator **105**, and the bitstream generator **105** generates corresponding encoded data.

[0041] A block divider **101** divides a picture into encoding target blocks each serving as an encoding processing unit, and supplies a picture signal in an encoding target block to a residual error signal generator **103**. In addition, the block divider **101** supplies the picture signal in the encoding target block to a prediction picture generator **102** for evaluating a coincidence degree of a prediction picture.

[0042] The block divider **101** generates an encoding target block by recursively dividing a picture into rectangles having a predetermined size. The block divider **101** includes four dividers that generate four blocks by dividing a target block in recursive division into four in the horizontal and vertical directions, and two dividers that generate two blocks by dividing a target block in recursive division into two in the horizontal direction or the vertical direction. The detailed operation of the block divider **101** will be described later.

[0043] The prediction picture generator **102** performs intra prediction or inter prediction based on a prediction mode from a decoded picture signal supplied from a decoded picture memory **108**, and generates a prediction picture signal. A picture signal in an encoding target block that is supplied from the block divider **101** is used for evaluation in intra prediction and inter prediction. In the intra prediction, using a picture signal of an encoding target block that is supplied from the block divider **101**, and a picture signal of a neighboring encoded block neighboring an encoding target block existing in the same picture as an encoding target block supplied from the decoded picture memory **108**, a prediction picture signal is generated. In the inter prediction, using a picture signal of an encoding target block that is supplied from the block divider **101**, an encoded picture stored in the decoded picture memory **108** and provided anterior to or posterior to a picture including an encoding target block (encoding picture) in chronological order is regarded as a reference picture, block coincidence degree evaluation such as block matching is performed between the encoding picture and the reference picture, a motion vector indicating a motion amount is obtained, motion compensation is performed from the reference picture based on the motion amount, and a prediction picture signal is generated. The prediction picture generator **102** supplies the prediction picture signal generated in this manner, to the residual error signal generator **103**.

[0044] The residual error signal generator **103** generates a residual error signal by performing subtraction of a picture signal to be encoded and a prediction signal generated by the prediction picture generator **102**, and supplies the residual error signal to an orthogonal transducer/quantizer **104**.

[0045] The orthogonal transducer/quantizer **104** performs orthogonal transform and quantization of the residual error signal supplied from the residual error signal generator **103**, and supplies the residual error signal subjected to orthogonal transform and quantization, to the bitstream generator **105** and an inverse orthogonal transducer/inverse quantizer **106**.

[0046] The bitstream generator **105** generates a bitstream for the residual error signal subjected to orthogonal transform and quantization that is supplied from the orthogonal transducer/quantizer **104**. In addition, the bitstream generator **105** generates a corresponding bitstream as for additional information such as motion vector, a prediction mode, or block division information.

[0047] The inverse orthogonal transducer/inverse quantizer **106** performs inverse quantization and inverse orthogonal transform of the residual error signal subjected to orthogonal transform and quantization that is supplied from the orthogonal transducer/quantizer **104**, and supplies the

residual error signal subjected to inverse quantization and inverse orthogonal transform, to a decoded picture signal superimposer **107**.

[0048] The decoded picture signal superimposer **107** generates a decoded picture by superimposing the prediction picture signal generated by the prediction picture generator **102**, and the residual error signal subjected to inverse quantization and inverse orthogonal transform by the inverse orthogonal transducer/inverse quantizer **106**, and stores the decoded picture in the decoded picture memory **108**. In addition, in some cases, filtering processing for reducing block distortion caused by encoding is performed on the decoded picture, and the resultant decoded picture is stored in the decoded picture memory **108**.

[0049] FIG. **2** is a configuration diagram of the picture decoding device **200** according to the first embodiment. Here, FIG. **2** illustrates only a flow of data regarding a picture signal, and a flow of data regarding additional information is not illustrated. A bitstream decoder **201** supplies the additional information other than a picture signal, such as a motion vector or a prediction mode, to each constituent element, and uses the additional information for corresponding processing.

[0050] The bitstream decoder **201** decodes a supplied bitstream and supplies a residual error signal subjected to orthogonal transform and quantization, to a block divider **202**.

[0051] The block divider **202** decides the shape of a decoding target block based on decoded block division information, and supplies a residual error signal of the decided decoding target block that has been subjected to orthogonal transform and quantization, to an inverse orthogonal transducer/inverse quantizer **203**.

[0052] The block divider **202** generates a decoding target block by recursively dividing a picture into rectangles having a predetermined size, based on the decoded block division information. The block divider **202** includes four dividers that generate four blocks by dividing a target block in recursive division into four in the horizontal and vertical directions, and two dividers that generate two blocks by dividing a target block in recursive division into two in the horizontal direction or the vertical direction. The detailed operation of the block divider **202** will be described later.

[0053] The inverse orthogonal transducer/inverse quantizer **203** performs inverse orthogonal transform and inverse quantization on the supplied residual error signal subjected to orthogonal transform and quantization, and obtains a residual error signal subjected to inverse orthogonal transform and inverse quantization.

[0054] A prediction picture generator **204** generates a prediction picture signal from a decoded picture signal supplied from a decoded picture memory **206**, and supplies the prediction picture signal to a decoded picture signal superimposer **205**.

[0055] The decoded picture signal superimposer **205** generates a decoded picture signal by superimposing the prediction picture signal generated by the prediction picture generator **204**, and the residual error signal subjected to inverse orthogonal transform and inverse quantization by the inverse orthogonal transducer/inverse quantizer **203**, outputs the decoded picture signal, and stores the decoded picture signal into the decoded picture memory **206**. In addition, in some cases, filtering processing for reducing block distortion caused by encoding is performed on the decoded picture, and the resultant decoded picture is stored in the decoded picture memory **206**.

[0056] An operation of the block divider **101** of the picture encoding device **100** will be described in detail. FIG. **3** is a flowchart illustrating division into tree blocks and division of each tree block.

[0057] First of all, an input picture is divided into tree blocks having a predetermined size (**S1000**). For example, a tree block includes 128 pixels×128 pixels. Nevertheless, the size of the tree block is not limited to 128 pixels×128 pixels, and any size and shape may be used as long as the tree block is rectangular. In addition, as for the size and shape of the tree block, fixed values may be defined in an encoding device and a decoding device. Alternatively, the encoding device may decide a block size and record the block size in a bitstream, and the decoding device may use the recorded block size. FIG. **4** illustrates a state in which an input picture is divided into tree blocks. Tree blocks are encoded and decoded in a raster scan order, that is to say, from the left to the right and

from the top to the bottom.

[0058] Each tree block is further divided into rectangular blocks. Each tree block is encoded and decoded in a z-scan order. FIG. 5 illustrates the z-scan order. In the z-scan, encoding and decoding are performed in the order of upper left, upper right, lower left, and the lower right. Each tree block can be divided into four or two, and each tree block is divided into four in the horizontal and vertical directions. Each tree block is divided into two in the horizontal direction or the vertical direction. FIG. 6 is a diagram illustrating a tree block divided into four in horizontal and vertical directions. FIG. 7 is a diagram illustrating a tree block divided into two in the horizontal direction. FIG. 8 is a diagram illustrating a tree block divided into two in the vertical direction.

[0059] The description will be continued referring back to FIG. 3. It is determined whether or not to divide the tree block into four in the horizontal and the vertical directions (S1001).

[0060] When it is determined that each tree block is divided into four (S1001: Yes), each tree block is divided into four (S1002), and each process of blocks divided into four in the horizontal and vertical directions is performed (S1003). Redivision processing of blocks divided into four will be described later (FIG. 9).

[0061] When it is determined that each tree block is not divided into four (S1001: No), it is determined whether or not to divide each tree block into two (S1004).

[0062] When it is determined that each tree block is divided into two (S1004: Yes), it is determined whether or not to set a direction in which each tree block is divided into two, to the horizontal direction (S1005).

[0063] When it is determined that a direction in which each tree block is divided into two is set to the horizontal direction (S1005: Yes), each tree block is divided into two in the horizontal direction (S1006), and each process of blocks divided into two in the horizontal direction is performed (S1007). Redivision processing of blocks divided into two in the horizontal direction will be described later (FIG. 10).

[0064] When it is determined that a direction in which each tree block is divided into two is set not to the horizontal direction but to the vertical direction (S1005: No), each tree block is divided into two in the vertical direction (S1008), and each process of blocks divided into two in the vertical direction is performed (S1009). Redivision processing of blocks divided into two in the horizontal direction will be described later (FIG. 11).

[0065] When it is determined that each tree block is not divided into two (S1004: No), each tree block is not divided and block division processing ends (S1010).

[0066] Subsequently, processing on each divided block when a tree block is divided into four in the horizontal and vertical directions will be described using a flowchart in FIG. 9.

[0067] It is determined whether or not to redive each block into four in the horizontal and the vertical directions (S1101).

[0068] When it is determined that each block is redivided into four (S1101: Yes), each block is redivided into four (S1102), and each process of blocks divided into four in the horizontal and vertical directions is performed (S1103).

[0069] When it is determined that each block is not redivided into four (S1101: No), it is determined whether or not to divide each block into two (S1104).

[0070] When it is determined that each block is divided into two (S1104: Yes), it is determined whether or not to set a direction in which each block is divided into two, to the horizontal direction (S1105).

[0071] When it is determined that a direction in which each block is divided into two is set to the horizontal direction (S1105: Yes), each block is divided into two in the horizontal direction (S1106), and each process of blocks divided into two in the horizontal direction is performed (S1107).

[0072] When it is determined that a direction in which each block is divided into two is set not to the horizontal direction but to the vertical direction (S1105: No), each block is divided into two in

the vertical direction (**S1108**), and each process of blocks divided into two in the vertical direction is performed (**S1109**).

[0073] When it is determined that each block is not divided into two (**S1104**: No), each block is not divided and block division processing ends (**S1110**).

[0074] The processing illustrated in the flowchart in FIG. 9 is executed on each of the blocks divided into four. Each of the blocks divided into four is also encoded and decoded in the z-scan order.

[0075] Subsequently, processing on each divided block when a tree block is divided into two in the horizontal direction will be described using a flowchart in FIG. 10.

[0076] When a tree block is divided into two in the horizontal direction, first of all, it is determined whether or not to divide each of the blocks divided into two, into four in the horizontal and the vertical directions (**S1201**).

[0077] When it is determined that each block is divided into four (**S1201**: Yes), each block is divided into four (**S1202**), and each process of blocks divided into four in the horizontal and vertical directions is performed (**S1203**).

[0078] When it is determined that each block is not divided into four (**S1201**: No), it is determined whether or not to redivide each block into two (**S1204**).

[0079] When it is determined that each block is redivided into two (**S1204**: Yes), each block is divided in the vertical direction (**S1205**), and each process of blocks divided into two in the vertical direction is performed (**S1206**).

[0080] When it is determined that each block is not redivided into two (**S1204**: No), each block is not redivided and block division processing ends (**S1207**).

[0081] FIG. 11 illustrates a state of redivision of divided block when a tree block is divided into two in the horizontal direction. Here, when a tree block serving as a parent block is divided into two in the horizontal direction, in the redivision into two of the divided block, the divided block is allowed to be divided into two only in the vertical direction, and is automatically divided into two in the vertical direction. In addition, when a tree block serving as a parent block is divided into two, a child block can also be strictly prohibited from being divided into four. This can prohibit a block from being divided in the same direction as a parent block. It is therefore possible to prevent block division that makes an oblong more elongated in a transverse direction, and facilitate processing of encoding and decoding.

[0082] The processing illustrated in the flowchart in FIG. 10 is executed on each of the blocks divided into two in the horizontal direction. Each of the blocks divided into two is also encoded and decoded in the order of top and down.

[0083] Subsequently, processing on each divided block when a tree block is divided into two in the vertical direction will be described using a flowchart in FIG. 12.

[0084] When a tree block is divided into two in the vertical direction, first of all, it is determined whether or not to divide each of the blocks divided into two, into four in the horizontal and the vertical directions (**S1301**).

[0085] When it is determined that each block is divided into four (**S1301**: Yes), each block is divided into four (**S1302**), and each process of blocks divided into four in the horizontal and vertical directions is performed (**S1303**).

[0086] When it is determined that each block is not divided into four (**S1301**: No), it is determined whether or not to redivide each block into two (**S1304**).

[0087] When it is determined that each block is redivided into two (**S1304**: Yes), each block is divided in the horizontal direction (**S1305**), and each process of blocks divided into two in the horizontal direction is performed (**S1306**).

[0088] When it is determined that each block is not redivided into two (**S1304**: No), each block is not redivided and block division processing ends (**S1307**).

[0089] FIG. 13 illustrates a state of redivision of divided block when a tree block is divided into

two in the vertical direction. Here, when a tree block serving as a parent block is divided into two in the vertical direction, in the redivision into two of the divided block, the divided block is allowed to be divided into two only in the horizontal direction, and is automatically divided into two in the horizontal direction. In addition, when a tree block serving as a parent block is divided into two, a child block can also be strictly prohibited from being divided into four. This can prohibit a block from being divided in the same direction as a parent block. It is therefore possible to prevent block division that makes an oblong more elongated in a longitudinal direction, and facilitate processing of encoding and decoding.

[0090] The processing illustrated in the flowchart in FIG. 12 is executed on each of the blocks divided into two in the vertical direction. Each of the blocks divided into two is also encoded and decoded in the order of left and right.

[0091] In addition, the redivision of a divided block performed when a tree block is divided has been described, but a parent block needs not be a tree block. For example, when a tree block (128×128) is divided into four and each of the blocks (64×64) divided into four is further divided into four or two, the above-described processing is applied also to the division of a redivided block.

[0092] Next, an operation of the block divider 202 of the picture decoding device 200 will be described. The block divider 202 divides a block using the same processing procedure as the block divider 101 of the picture encoding device 100, but the processing procedure partially differs in the following manner. While the block divider 101 of the picture encoding device 100 selects a pattern of block division and outputs selected block division information, the block divider 202 of the picture decoding device has a syntax structure of dividing a block using block division information decoded from a bitstream, and not transmitting unselectable information in a bitstream under a situation in which the redivision in the same direction is prohibited, when decoding block division information from a bitstream.

[0093] FIG. 14 illustrates an example of a syntax (syntactic rule of bitstream) related to the block division of the first embodiment. For the division of each tree block, first of all, a flag indicating whether or not to divide each tree block into four (4_division_flag) is transmitted and received. When each tree block is divided into four (4_division_flag indicates 1), each tree block is divided into four, and the processing ends. After that, each of the blocks divided into four is redivided using the syntax illustrated in FIG. 14 again. When each tree block is not divided into four (4_division_flag indicates 0), a flag indicating whether or not to divide each tree block into two (2_division_flag) is transmitted and received. When each tree block is divided into two (2_division_flag indicates 1), a flag indicating a direction in which each tree block is divided into two (2_division_direction) is further transmitted and received. When the flag 2_division_direction indicates 1, the flag indicates the division in the vertical direction, and when the flag 2_division_direction indicates 0, the flag indicates the division in the horizontal direction. After that, each of the blocks divided into two is redivided using the syntax illustrated in FIG. 14 again. When each tree block is not divided into two (2_division_flag is 0), each tree block is not divided, and the processing ends.

[0094] Here, processing of redividing each of the blocks divided into four or two will be described. The processing of redividing each block also uses the syntax illustrated in FIG. 14, but differs from the processing performed when a tree block is divided, in that a division direction in which each block is divided into two is restricted. More specifically, when a tree block is divided into two, when each of the blocks divided into two is redivided, division in the same direction as a division direction in which the tree block is divided into two is prohibited. This can prevent the divided block from becoming a more elongated oblong, and prevent an increase in memory bandwidth required in intra prediction or inter prediction. The details of the prevention of an increase in memory bandwidth will be described later.

[0095] In addition, it should be appreciated that the number of times a block is divided into two in the same direction may be counted, and division in the same direction may be restricted when the

counted number exceeds a predetermined time. For example, while a block is allowed to be divided into two in the same direction twice or less, a block is prohibited from being divided into two in the same direction three times or more.

[0096] FIG. **14** illustrates a syntax in which division into four is preferentially selected and information indicating whether or not to divide into four is transmitted and received earlier than information indicating whether or not to divide into two. On the other hand, when division into two is preferentially selected, a syntax of transmitting and receiving information indicating whether or not to divide into two, earlier than information indicating whether or not to divide into four can be employed. This is because an encoding amount to be transmitted as a bitstream becomes smaller if an event that is more likely to occur stochastically is transmitted and received earlier. More specifically, which of the division into four and the division into two is more likely to occur may be estimated in advance, and a syntax of transmitting and receiving division information more likely to occur, earlier may be employed. For example, by transmitting and receiving whether or not to prioritize division into four or division into two, using header information of a picture, an encoding device can adaptively decide a prioritized division number having high encoding efficiency, and a decoding device can divide each tree block using a syntax that is based on the selected prioritized division number.

[0097] In the picture encoding device **100** and the picture decoding device **200**, intra prediction and inter prediction are performed using a divided block. Both of the intra prediction and inter prediction involve the copy of pixels from a memory.

[0098] FIGS. **15(a)** to **15(d)** illustrate an example of intra prediction. FIGS. **15(a)** and **15(b)** illustrate a prediction direction and a mode number of intra prediction. As illustrated in FIGS. **15(c)** and **15(d)**, intra prediction generates a prediction picture of an encoding/decoding target block by copying pixels from encoded/decoded pixels neighboring the encoding/decoding target block. In intra prediction, because prediction picture generation to encoding/decoding pixel generation are repeated for each block, a processing order becomes sequential for each block, and as each block is divided into smaller blocks, load on the entire processing increases. In addition, as the shape of the block becomes a more elongated oblong, processing of pixel copy from a memory becomes larger. In addition, because orthogonal transform of a residual error signal is performed for encoding and decoding, as the number of types of the size of a rectangle increases, the number of types of required orthogonal transform increases, and a circuit size is consequently increased. Thus, when each block is divided into two, by restricting division into two in the same direction as a division method of a parent block, an increase in memory bandwidth required for intra prediction can be prevented.

[0099] FIG. **16** illustrates an example of inter prediction. The inter prediction generates a prediction picture of an encoding/decoding target block by copying pixels for each block from pixels included in an encoded/decoded picture. In the inter prediction, when a pixel is copied from a reference picture for each block, a device often has a configuration requiring the acquisition in the management unit of a memory including a required pixel. Thus, as a block is divided into smaller blocks, and in addition, as the shape of the block becomes a more elongated oblong, load on the entire processing increases. In addition, when motion compensation with decimal accuracy is performed on a reference picture using an interpolation filter, it is necessary to copy pixels by adding several pixels to pixels included in a block, and as the size of the block becomes smaller, a relative rate of several pixels to be added increases, and load on the entire processing increases. Thus, when each block is divided into two, by restricting division into two in the same direction as a division direction of a parent block, an increase in memory bandwidth required for inter prediction can be prevented.

[0100] Subsequently, a relationship between a luminance signal and a color difference signal in intra prediction will be described. As a format of a luminance signal and a color difference signal, 4:2:0, 4:2:2, 4:4:4, and the like have been conventionally known. While the 4:2:0 format illustrated

in FIG. 17(a) performs sampling of two pixels both in the horizontal/vertical direction for a luminance signal, the 4:2:0 format performs sampling of one pixel both in the horizontal/vertical direction for a color difference signal. Because human eyes can perceive a luminance signal more sensitively than a color difference signal, an information amount of the color difference signal is made smaller than that of the luminance signal. While a 4:2:2 format illustrated in FIG. 17(b) performs sampling of two pixels in the horizontal direction for a luminance signal, the 4:2:2 format performs sampling of one pixel in the horizontal direction for a color difference signal. Regarding the vertical direction, the 4:2:2 format performs sampling of two pixels in the vertical direction for a luminance signal, the 4:2:2 format performs sampling of two pixels in the vertical direction for a color difference signal. While a 4:4:4 format illustrated in FIG. 17(c) performs sampling of two pixels in the horizontal/vertical direction for a luminance signal, the 4:4:4 format performs sampling of two pixels both in the horizontal/vertical directions for a color difference signal.

[0101] The present embodiment will be described using the 4:2:0 format used in picture encoding most widely as an example. The block divider **101** or **202** includes a luminance block divider that generates a luminance block by dividing a luminance signal of a picture, and a color difference block divider that generates a color difference block by dividing a color difference signal of a picture, and in the intra prediction, independently divides a luminance signal and a color difference signal into blocks. More specifically, in the intra prediction, a size of a luminance block and a size of a color difference block are independently decided. In the intra prediction, because a luminance signal and a color difference signal each copy pixel values from neighboring pixels, if the luminance signal and the color difference signal are independently divided into blocks, prediction efficiency is enhanced. In contrast this, as for inter prediction, a luminance signal and a color difference signal are divided into blocks in company with each other. More specifically, in the inter prediction, a size of a luminance block and a size of a color difference block are the same. This is because there is no need to distinguish between luminance and a color difference in motion compensation in the inter prediction.

[0102] The prediction picture generator **102** or **204** includes a luminance signal predictor that predicts a luminance signal and a color difference signal predictor that predicts a color difference signal, and the color difference signal predictor performs luminance color difference intra prediction of predicting a color difference signal from an encoded/decoded pixel of a luminance signal for enhancing prediction efficiency of a color difference signal in the intra prediction. In the luminance color difference intra prediction, a primary signal is encoded/decoded prior to a secondary signal, and the secondary signal is predicted using the encoded/decoded primary signal. Here, because an information amount of a luminance signal is larger than that of a color difference signal in the 4:2:0 format and the 4:2:2 format, a luminance signal is regarded as a primary signal and a color difference signal is regarded as a secondary signal. In the 4:4:4 format, information amounts of a luminance signal and a color difference signal are the same, but it is normal that a luminance signal is regarded as a primary signal and a color difference signal is regarded as a secondary signal similarly to the other formats.

[0103] FIG. 18 is a diagram illustrating luminance color difference intra prediction and FIG. 19 is a flowchart illustrating luminance color difference intra prediction.

[0104] As illustrated in FIG. 18, luminance color difference intra prediction is performed based on a correlation degree between encoded/decoded neighboring pixels **12a** and **12b** of a luminance block **10** and encoded/decoded neighboring pixels **16a** and **16b** of a color difference block **14**. Because the luminance color difference intra prediction predicts a color difference signal, neighboring pixels serving as calculation targets of a correlation degree are defined based on neighboring pixels of an encoding/decoding target color difference block. In other words, neighboring pixels of a luminance block at the same position as neighboring pixels decided for a color difference block become calculation targets of a correlation degree.

[0105] First of all, a correlation degree between neighboring pixels of an encoded/decoded

luminance signal and neighboring pixels of a color difference signal is calculated (S1901). Subsequently, downsampling of an encoded/decoded luminance signal of an encoding/decoding target block is performed (S1902). Here, a plurality of filter types of downsampling may be prepared and a filter type may be selected. For example, a plurality of filter types may be selected by preparing filters having different intensities, or a plurality of filter types may be selected by preparing filters having different filter lengths. A filter type may be automatically selected using a correlation degree between neighboring pixels or a filter type may be transmitted into a bitstream with being encoded/decoded. In addition, unless a downsampling filter of a luminance signal of an encoding/decoding target block is decided using a correlation degree between neighboring pixels, the processing in step S1901 and the processing in step S1902 are performed in any order, and the processing in step S1901 and the processing in step S1902 can be performed in parallel.

[0106] Lastly, based on a correlation degree between neighboring pixels, a color difference signal is predicted from the downsampled luminance signal (S1903). The downsampling is $\frac{1}{2}$ in the horizontal/vertical direction in the case of the 4:2:0 format. In the case of the 4:2:2 format, downsampling is $\frac{1}{2}$ in the horizontal direction and downsampling is not performed in the vertical direction. The downsampling is not performed in both of the horizontal/vertical directions in the case of the 4:4:4 format.

[0107] In the luminance color difference intra prediction, after the encoding/decoding of a luminance signal of an encoding/decoding target block is completed, prediction processing of a color difference signal can be started. Thus, a timing at which prediction processing of a color difference signal can be started depends on the size of a luminance block and the size of a color difference block.

[0108] FIGS. 20(a) and 20(b) are diagrams illustrating luminance color difference intra prediction in a case where a size of a color difference block is larger than a size of a luminance block. The number of pixels of first to fourth luminance blocks 20a, 20b, 20c, and 20d divided into four that are illustrated in FIG. 20(a) is 16×16 , and the number of pixels of a color difference block 20e illustrated in FIG. 20(b) is 16×16 .

[0109] Here, the comparison between the sizes of the luminance block and the color difference block is not comparison between the numbers of pixels in the blocks but the comparison between areas considering a color difference format. More specifically, in the 4:2:0 format, because an area occupied by a luminance block is $\frac{1}{2}$ of an area occupied by a color difference block, when the number of pixels of the luminance block is 16×16 and the number of pixels of the color difference block is 16×16 , the size of the luminance block is smaller. In the 4:2:0 format, when the number of pixels of the luminance block is 16×16 and the number of pixels of the color difference block is 8×8 , areas occupied by the both blocks are the same, and the luminance block and the color difference block have the same size.

[0110] For performing the comparison between sizes of a luminance block and a color difference block, not by the comparison between areas of the blocks but by the comparisons between the numbers of pixels in the blocks, the number of pixels of the color difference block is only required to be converted into the number of pixels of the luminance block at a ratio between the luminance signal and the color difference signal in the color difference format. In the case of the 4:2:0 format, because the number of pixels of the luminance signal is twice as larger as the number of pixels of the color difference signal, by doubling the numbers of pixels in height and the width of the color difference block, the numbers of pixels are converted into the numbers of pixels in height and the width of the luminance block. For example, in the 4:2:0 format, when the size of the luminance block is 16×16 and the size of the color difference block is 16×16 , the converted size of the color difference block that has been converted into the number of pixels of the luminance block is 32×32 , and it can be seen that the size of the color difference block is larger.

[0111] In the intra prediction, after decoding processing is completed for each block, prediction processing of a subsequent block is enabled. More specifically, after the decoding of the first

luminance block **20a** is completed, the decoding of the second luminance block **20b** is enabled, after the decoding of the second luminance block **20b** is completed, the decoding of the third luminance block **20c** is enabled, and after the decoding of the third luminance block **20c** is completed, the decoding of the fourth luminance block **20d** is enabled.

[0112] When the size of the color difference block is larger than the size of the luminance block, neighboring pixels necessary of prediction processing of the color difference block **20e** exist before the decoding of the four luminance blocks **20a**, **20b**, **20c**, and **20d** for both of a luminance pixel and a color difference pixel, and a correlation degree between neighboring pixels of a luminance signal and neighboring pixels of a color difference signal can be calculated in step **S1901** of FIG. **19** without waiting for the decoding of the four luminance blocks **20a**, **20b**, **20c**, and **20d**.

[0113] Next, after the completion of the decoding of the first luminance block **20a**, downsampling of a luminance signal is executed in step **S1902** of FIG. **19**. Without waiting for the decoding completion of the second luminance block **20b**, it is possible to predict pixels of the color difference block **20e** that correspond to the position of the first luminance block **20a**. Similarly, after the decoding completion of the second luminance block **20b**, downsampling of a luminance signal is executed, and without waiting for the decoding completion of the third luminance block **20c**, pixels of the color difference block **20e** that correspond to the position of the second luminance block **20b** are predicted. Furthermore, after the decoding completion of the third luminance block **20c**, downsampling of a luminance signal is executed, and without waiting for the decoding completion of the fourth luminance block **20d**, pixels of the color difference block **20e** that correspond to the position of the third luminance block **20c** are predicted. Lastly, after the decoding completion of the fourth luminance block **20d**, downsampling of a luminance signal is executed, and pixels of the color difference block **20e** that correspond to the position of the fourth luminance block **20d** are predicted.

[0114] FIGS. **21(a)** and **21(b)** are diagrams illustrating luminance color difference intra prediction in a case where a size of a color difference block is smaller than a size of a luminance block. The number of pixels of a luminance block **21a** illustrated in FIG. **21(a)** is 16×16 , and the number of pixels of first to fourth color difference blocks **21b**, **21c**, **21d**, and **21e** divided into four that are illustrated in FIG. **21(b)** is 4×4 .

[0115] In the 4:2:0 format, because an area occupied by a luminance block is $\frac{1}{2}$ of an area occupied by a color difference block, when the number of pixels of the luminance block is 16×16 and the number of pixels of the color difference block is 4×4 , the size of the color difference block is smaller. For performing the comparison between sizes of a luminance block and a color difference block, not by the comparison between areas of the blocks but by the comparisons between the numbers of pixels in the blocks, in the case of the 4:2:0 format, the numbers of pixels in height and width of the color difference block are doubled and converted into the numbers of pixels in height and width of the luminance block. In the 4:2:0 format, when the size of the luminance block is 16×16 and the size of the color difference block is 4×4 , the converted size of the color difference block that has been converted into the number of pixels of the luminance block is 8×8 , and it can be seen that the size of the color difference block is smaller.

[0116] When the size of the color difference block is smaller than the size of the luminance block, neighboring pixels of the first color difference block **21b** can be used before the decoding of the luminance block **21a** both for the luminance pixel and the color difference pixel, but neighboring pixels of the second to fourth color difference blocks **21c**, **21d**, and **21e** cannot be used unless the decoding of the luminance block **21a** is completed. More specifically, unless the decoding of the luminance block **21a** is completed and the decoding of the first color difference block **21b** is completed, a correlation degree between neighboring pixels of the luminance signal and neighboring pixels of the color difference signal cannot be calculated in step **S1901** of FIG. **19** for the second color difference block **21c**. Similarly, as for the third color difference block **21d**, unless the decoding of the luminance block **21a** is completed and the decoding of the first and second

color difference blocks **21b** and **21c** is completed, a correlation degree between neighboring pixels of the luminance signal and neighboring pixels of the color difference signal cannot be calculated for the third color difference block **21d**. Similarly, as for fourth color difference block **21e**, unless the decoding of the luminance block **21a** is completed and the decoding of the first to third color difference blocks **21b**, **21c**, and **21d** is completed, a correlation degree between neighboring pixels of the luminance signal and neighboring pixels of the color difference signal cannot be calculated for the fourth color difference block **21e**.

[0117] In this manner, when the size of the color difference block is smaller than the size of the luminance block, if luminance color difference intra prediction is performed, in the prediction processing of a color difference block, dependence relationship of processing is generated between the luminance block and the color difference block and between color difference blocks, which is not suitable for parallel processing. Thus, when a size of a color difference block is smaller than a size of a luminance block, luminance color difference intra prediction is restricted. As methods of restricting luminance color difference intra prediction, there are (1) a method of restricting using a syntax, (2) a method of replacing an intra color difference mode, and (3) a method of replacing neighboring pixels.

[0118] FIG. **22** illustrates an example of a syntax of an intra color difference prediction mode. When the number of the color difference prediction mode is 0, the same intra prediction mode as the luminance prediction mode is used as a color difference prediction mode. For example, when a luminance prediction mode is a horizontal prediction mode, a color difference prediction mode also becomes a horizontal prediction mode. When the number of the color difference prediction mode is 1, an average value mode (DC mode) is used. The DC mode performs intra prediction using an average value of neighboring pixels. When the number of the color difference prediction mode is 2, a luminance color difference intra prediction mode is used.

[0119] As a method of restricting luminance color difference intra prediction, when (1) the luminance color difference intra prediction is restricted using a syntax, because a mode 2 indicates the luminance color difference intra prediction, the mode 2 becomes unselectable. In other words, the mode 2 is not transmitted and the intra color difference mode is selected from the mode 0 and the mode 1.

[0120] As a method of restricting luminance color difference intra prediction, when (2) an intra color difference mode is replaced, when the number of the color difference prediction mode is designated as the mode 2, a vertical prediction mode is used in place of a luminance color difference intra prediction mode. Nevertheless, a prediction mode to be replaced with is not limited to the vertical prediction mode and may be another prediction mode. In addition, the luminance prediction mode of the mode 0 and the mode of replacing with the mode 2 become the same, and it is preferable that modes to be used are not redundant.

[0121] As a method of restricting luminance color difference intra prediction, when (3) neighboring pixels are replaced, neighboring pixels for calculating a correlation degree between neighboring pixels of a luminance signal and neighboring pixels of a color difference signal in step **S1901** of FIG. **19** are replaced. Also in the second to fourth color difference blocks **21c**, **21d**, and **21e** in FIG. **21**, it becomes possible to calculate a correlation degree between neighboring pixels without waiting for the decoding of the luminance block **21a**.

[0122] FIG. **23** illustrates an example of replacement of neighboring pixels. As neighboring pixels of the left side of the second color difference block **21c**, pixels in the first color difference block **21b** are normally used, but for using pixels in the first color difference block **21b**, it is necessary to wait for the decoding completion of the luminance block **21a** and the first color difference block **21b**. Thus, a region **21f** that can be used without waiting for the decoding completion of the luminance block **21a** is used as neighboring pixels of the second color difference block **21c**. Similarly, as for the third color difference block **21d**, the region **21f** that can be used without waiting for the decoding completion of the luminance block **21a** is used as neighboring pixels of

the third color difference block **21d**. Similarly, as for the fourth color difference block **21e**, the region **21f** that can be used without waiting for the decoding completion of the luminance block **21a** is used as neighboring pixels of the fourth color difference block **21e**.

[0123] In this manner, in the first embodiment, when luminance color difference intra prediction is performed, when the size of the color difference block is smaller than the size of the luminance block, by restricting luminance color difference intra prediction, it becomes possible to ease dependence relationship of processing between the luminance block and the color difference block. This enables parallel processing of the luminance block and the color difference block, and can reduce a processing amount of encoding and decoding.

Second Embodiment

[0124] A second embodiment of the present invention will be described. The second embodiment differs from the first embodiment in that the size of the luminance block and the size of the color difference block are individually evaluated and luminance color difference intra prediction is restricted, without using a size relationship between the size of the luminance block and the size of the color difference block, and other configurations and operations are similar to those in the first embodiment.

[0125] First of all, restriction that is based on the size of the luminance block will be described. FIGS. **24(a)** to **24(c)** illustrate luminance color difference intra prediction that is based on a difference in size of a luminance block. As illustrated in FIGS. **24(a)** and **24(b)**, a first luminance block **24a** corresponds to a position of a first color difference block **24e**, a second luminance block **24b** corresponds to a position of a second color difference block **24f**, a third luminance block **24c** corresponds to a position of a third color difference block **24g**, and a fourth luminance block **24d** corresponds to a position of a fourth color difference block **24h**. In addition, a luminance block **24i** in FIG. **24(c)** corresponds to the positions of the first to fourth color difference blocks **24e**, **24f**, **24g**, and **24h** in FIG. **24(b)**.

[0126] A dependence relationship between the luminance block and the color difference block will be described. When the size of the luminance block is small as in FIG. **24(a)**, if the decoding of the first luminance block **24a** is completed, the decoding of the first color difference block **24e** is enabled. If the decoding of the second luminance block **24b** is completed, the decoding of the second color difference block **24f** is enabled. If the decoding of the third luminance block **24c** is completed, the decoding of the third color difference block **24g** is enabled. If the decoding of the fourth luminance block **24d** is completed, the decoding of the fourth color difference block **24h** is enabled.

[0127] On the other hand, when the size of the luminance block is larger as in FIG. **24(c)**, unless the decoding of the luminance block **24i** is completed, the decoding of all the first to fourth color difference blocks **24e**, **24f**, **24g**, and **24h** is not enabled.

[0128] In the case of independently deciding the division of the luminance block and the division of the color difference block, if an absolute size of the luminance block is large, a possibility that the size of the color difference block becomes smaller than the size of the luminance block increases. Thus, when an absolute size of the luminance block is larger than or equal to a predetermined size, luminance color difference intra prediction of a corresponding color difference block is restricted.

[0129] Similarly, if an absolute size of the color difference block is small, a possibility that the size of the color difference block becomes smaller than the size of the luminance block increases. Thus, when an absolute size of the color difference block is smaller than or equal to a predetermined size, luminance color difference intra prediction of the color difference block is restricted.

[0130] A restriction method of luminance color difference intra prediction is similar to that in the first embodiment.

[0131] In this manner, in the second embodiment, when an absolute size of the luminance block is larger than a threshold, or when an absolute size of the color difference block is smaller than a

threshold, luminance color difference intra prediction is restricted. It becomes possible to stochastically ease dependence relationship of processing between the luminance block and the color difference block, by restricting luminance color difference intra prediction while predicting a case where the size of the color difference block is smaller than the size of the luminance block.

Third Embodiment

[0132] A third embodiment of the present invention will be described. The third embodiment is different from the first embodiment in that the block divider **101** divides a color difference block in such a manner that the size of the color difference block does not become smaller than the size of the luminance block, and other configurations and operations are similar to those in the first embodiment. When the block divider **101** divides a color difference block, division that makes the size of the color difference block smaller than the size of a luminance block is prohibited. This prevents the size of the color difference block from becoming smaller than the size of the luminance block in luminance color difference intra prediction, and parallel processing of the luminance block and the color difference block is always enabled.

[0133] A bitstream of a picture to be output by a picture encoding device of the above-described embodiments includes a specific data format so that decoding can be performed in accordance with an encoding method used in the embodiment, and a picture decoding device corresponding to the picture encoding device can decode a bitstream having the specific data format.

[0134] When a wired or wireless network is used for exchanging bitstream between a picture encoding device and a picture decoding device, a bitstream may be converted into a data format suitable for a transmission mode of a communication path. In this case, a transmission device that converts a bitstream output by the picture encoding device, into encoded data having a data format suitable for a transmission mode of a communication path, and transmits the encoded data to the network, and a receiving device that receives the encoded data from the network, restores the encoded data into a bitstream, and supplies the bitstream to the picture decoding device are provided.

[0135] The transmission device includes a memory that buffers the bitstream output by the picture encoding device, a packet processor that packetizes the bitstream, and a transmitter that transmits the packetized encoded data via the network. The receiving device includes a receiver that receives the packetized encoded data via the network, a memory that buffers the received encoded data, and a packet processor that generates a bitstream by performing packet processing of the encoded data and provides the bitstream to the picture decoding device.

[0136] In addition, by adding a display that displays a picture decoded by the picture decoding device to a configuration, a display device can be provided. In this case, the display reads a decoded picture signal that is generated by the decoded picture signal superimposer **205** and stored in the decoded picture memory **206**, and displays the decoded picture signal on a screen.

[0137] In addition, by adding an imager to a configuration and inputting a captured picture to the picture encoding device, an imaging device can be provided. In this case, the imager inputs a captured picture signal to the block divider **101**.

[0138] The above-described processing related to encoding and decoding can be of course implemented as transmission, accumulation, and receiving devices that use hardware, and can also be implemented by firmware stored in a read-only memory (ROM), a flash memory, or the like, or software of a computer or the like. The firmware program and the software program can also be provided with being recorded on a computer-readable recording medium, provided from a server via a wired or wireless network, and provided as datacasting of ground-based or satellite digital broadcasting.

[0139] The present invention has been described above based on the embodiments. These embodiments are examples, and the one skilled in the art understands that various modifications can be made on combinations of constituent elements and processing processes of these, and such modifications are included in the scope of the present invention.

Claims

1. A picture encoding device that divides a picture into blocks, performs encoding for each of the divided blocks and generates a bitstream, the picture encoding device comprising: a primary signal block divider structured to divide a primary signal of the picture into rectangular blocks and generate a primary signal block; a secondary signal block divider structured to divide a secondary signal of the picture into rectangular blocks and generate a secondary signal block; a primary signal predictor structured to predict a primary signal; a secondary signal predictor structured to predict a secondary signal; and wherein the primary signal is a luminance signal and the secondary signal is a color difference signal, wherein the secondary signal predictor can select a cross-component intra prediction of predicting a secondary signal from an encoded primary signal, wherein the primary signal block and the secondary signal block are divided independent of each other in case of intra prediction, but the cross-component intra prediction is restricted if a size of the primary signal block is greater than or equal to a predetermined size, and wherein the secondary signal predictor downsamples the primary signal depending on a format of the primary signal and the secondary signal in the cross-component intra prediction.
2. A picture encoding method that divides a picture into blocks, performs encoding for each of the divided blocks and generates a bitstream, the picture encoding method comprising: a primary signal block division step of dividing a primary signal of the picture into rectangular blocks and generating a primary signal block; a secondary signal block division step of dividing a secondary signal of the picture into rectangular blocks and generating a secondary signal block; a primary signal prediction step of predicting a primary signal; a secondary signal prediction step of predicting a secondary signal; and wherein the primary signal is a luminance signal and the secondary signal is a color difference signal, wherein the secondary signal prediction step can select a cross-component intra prediction of predicting a secondary signal from an encoded primary signal, wherein the primary signal block and the secondary signal block are divided independent of each other in case of intra prediction, but the cross-component intra prediction is restricted if a size of the primary signal block is greater than or equal to a predetermined size, and wherein the secondary signal prediction step includes downsampling the primary signal depending on a format of the primary signal and the secondary signal in the cross-component intra prediction.
3. A picture decoding device that performs decoding for each of blocks into which a picture is divided, the picture decoding device comprising: a primary signal block divider structured to divide a primary signal of the picture into rectangular blocks and generate a primary signal block; a secondary signal block divider structured to divide a secondary signal of the picture into rectangular blocks and generate a secondary signal block; a primary signal predictor structured to predict a primary signal; and a secondary signal predictor structured to predict a secondary signal, wherein the primary signal is a luminance signal and the secondary signal is a color difference signal, wherein the secondary signal predictor can select a cross-component intra prediction of predicting a secondary signal from a decoded primary signal, wherein the primary signal block and the secondary signal block are divided independent of each other in case of intra prediction, but the cross-component intra prediction is restricted if a size of the primary signal block is greater than or equal to a predetermined size, and wherein the secondary signal predictor downsamples the primary signal depending on a format of the primary signal and the secondary signal in the cross-component intra prediction.
4. A picture decoding method that performs decoding for each of blocks into which a picture is divided, the picture decoding method comprising: a primary signal block division step of dividing a primary signal of the picture into rectangular blocks and generating a primary signal block; a secondary signal block division step of dividing a secondary signal of the picture into rectangular blocks and generating a secondary signal block; a primary signal prediction step of predicting a

primary signal; and a secondary signal prediction step of predicting a secondary signal, wherein the primary signal is a luminance signal and the secondary signal is a color difference signal, wherein the secondary signal prediction step can select a cross-component intra prediction of predicting a secondary signal from a decoded primary signal, wherein the primary signal block and the secondary signal block are divided independent of each other in case of intra prediction, but the cross-component intra prediction is restricted if a size of the primary signal block is greater than or equal to a predetermined size, and wherein the secondary signal prediction step includes downsampling the primary signal depending on a format of the primary signal and the secondary signal in the cross-component intra prediction.

5. A method of transmitting a bitstream generated by a picture encoding method according to claim 2.

6. A method of storing a bitstream generated by a picture encoding method according to claim 2 on a computer-readable recording medium.

7. A non-transitory computer-readable recording medium storing a bitstream generated by a picture encoding method according to claim 2.
