

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12397870
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Li; Qianjin et al.

Straddle-type vehicle

Abstract

A straddle-type vehicle (**100**) includes a frame (**20**) and an engine (**10**) mounted on the frame (**20**), the engine (**10**) includes a cylinder head (**11**) positioned toward the rear end of the frame, and located below a saddle seat (**80**). The cylinder head faces toward the rear end of the frame, which allows the heated cylinder head of the engine and the exhaust pipe connected to the cylinder head to avoid contact with the vehicle the user's legs while riding the vehicle, so the effect of heat emitted from the cylinder head on the rider's experience is reduced.

Inventors: Li; Qianjin (Hangzhou, CN), Chen; Zhiyong (Hangzhou, CN), He; An (Hangzhou, CN), Fang; Ying (Hangzhou, CN)

Applicant: Zhejiang CFMOTO Power Co., Ltd. (Zhejiang, CN)

Family ID: 1000008781947

Assignee: Zhejiang CFMoto Power Co., Ltd. (Zhejiang, CN)

Appl. No.: 18/595190

Filed: March 04, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240208599 A1	Jun. 27, 2024

Foreign Application Priority Data

CN	201911029709.3	Oct. 28, 2019
----	----------------	---------------

Related U.S. Application Data

continuation parent-doc US 17738893 20220506 US 11919603 20240305 child-doc US 18595190
continuation parent-doc US 17465535 20210902 US 11332211 child-doc US 17738893

Publication Classification

Int. Cl.: **B60K5/04** (20060101); **B60K13/02** (20060101); **B60K13/04** (20060101); **B62J35/00** (20060101); **B62J40/00** (20200101); **B62J43/20** (20200101); **B62K5/01** (20130101); **B62K11/04** (20060101); **B62M9/04** (20060101); **F01N1/02** (20060101); **F01N3/28** (20060101); **F02M35/10** (20060101)

U.S. Cl.:

CPC **B62K5/01** (20130101); **B60K5/04** (20130101); **B60K13/02** (20130101); **B60K13/04** (20130101); **B62J35/00** (20130101); **B62J40/00** (20200201); **B62J43/20** (20200201); **B62K11/04** (20130101); **B62M9/04** (20130101); **F01N1/02** (20130101); **F01N3/2885** (20130101); **F02M35/10091** (20130101);

Field of Classification Search

CPC: B62K (5/01); B62K (5/04); B62K (11/04); B62J (43/20); B62J (40/00); B62J (35/00); B60K (13/02); B60K (13/04); B62M (9/04); F01N (1/02); F01N (3/2885); F02M (35/10091)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2189424	12/1939	Leadbetter	181/266	F01N 13/007
4050903	12/1976	Bailey et al.	N/A	N/A
4650025	12/1986	Igarashi et al.	N/A	N/A
4673052	12/1986	Shinozake et al.	N/A	N/A
4828069	12/1988	Hatsuyama	N/A	N/A
5044646	12/1990	Iiga et al.	N/A	N/A
6040266	12/1999	Fay, III	502/178	B01J 35/56
6626260	12/2002	Gagnon et al.	N/A	N/A
7377552	12/2007	Miyabe	180/68.5	B62J 35/00
8684119	12/2013	Metzger et al.	N/A	N/A
9327802	12/2015	Chang et al.	N/A	N/A
2001/0027890	12/2000	Bria et al.	N/A	N/A
2002/0005305	12/2001	Hirayama et al.	N/A	N/A
2002/0040822	12/2001	Gagnon et al.	N/A	N/A
2002/0088661	12/2001	Gagnon et al.	N/A	N/A
2002/0144852	12/2001	Shimizu et al.	N/A	N/A
2005/0255804	12/2004	Steelberg et al.	N/A	N/A
2006/0254849	12/2005	Kalsnes et al.	N/A	N/A
2007/0144828	12/2006	Galligan	N/A	N/A
2008/0283326	12/2007	Bennett et al.	N/A	N/A
2009/0038875	12/2008	Michalke et al.	N/A	N/A
2009/0145689	12/2008	Han	N/A	N/A
2014/0116796	12/2013	Poulin et al.	N/A	N/A

2014/0262584	12/2013	Lovold et al.	N/A	N/A
2015/0300234	12/2014	Hirukawa	N/A	N/A
2016/0375757	12/2015	Danielson et al.	N/A	N/A
2018/0009500	12/2017	Lovold et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2467537	12/2002	CA	N/A
2640894	12/2003	CN	N/A
101746474	12/2009	CN	N/A
103184956	12/2012	CN	N/A
203612147	12/2013	CN	N/A
104265414	12/2014	CN	N/A
104265414	12/2014	CN	N/A
205047274	12/2015	CN	N/A
205779127	12/2015	CN	N/A
107269346	12/2016	CN	N/A
207393290	12/2017	CN	N/A
208220865	12/2017	CN	N/A
209650472	12/2018	CN	N/A
209650472	12/2018	CN	N/A
110588868	12/2018	CN	N/A
210310698	12/2019	CN	N/A
210555333	12/2019	CN	N/A
210653498	12/2019	CN	N/A
3006705	12/1979	DE	N/A
19912466	12/1998	DE	N/A
1031451	12/1999	EP	N/A
3366563	12/2017	EP	N/A
481480	12/1937	GB	N/A
S59 162685	12/1983	JP	N/A
S61 117786	12/1985	JP	N/A
S64 14491	12/1988	JP	N/A
1989115795	12/1988	JP	N/A
H01115795	12/1988	JP	N/A
5570400	12/2013	JP	N/A
6306482	12/2017	JP	N/A
2019173942	12/2018	JP	N/A
101268835	12/2012	KR	N/A
1275512	12/2006	TW	N/A
WO-2020147417	12/2019	WO	N/A
2020238112	12/2019	WO	N/A

OTHER PUBLICATIONS

European Patent Office, Supplemental European Search Report, App. No. 23 16 2765, Jun. 21, 2023. cited by applicant

European Patent Office, Supplementary Partial European Search Report in App. No. EP 20 88 1094, Jun. 17, 2022. cited by applicant

Wikipedia Article: “Feststellbremse”, with translation “Parking brake”,
<https://de.wikipedia.org/w/index.php?title=Feststellbremse&oldid=241159870>. cited by applicant

Wikipedia Article: “Shock mount”, https://en.wikipedia.org/w/index.php?title=Shock_mount&oldid=895823027. cited by applicant
Wikipedia Article: “Schalldämpfer”, with translation “Silencer”,
<https://de.wikipedia.org/w/index.php?title=Schalld%C3%A4mpfer&oldid=242899420>. cited by applicant
IP Australia, Examination Report No. 1 for Standard Patent Application, App. No. 2020373949 of Zhejiang CMoto Power Co. Ltd., dated Nov. 18, 2021. cited by applicant
Autogazette: Motorrad: Bei Austausch-Endschalldämpfern auf KAT achten,
<https://autogazette.de/motorrad/kat/auspuff/motorrad-bei-austauschendschalldaempfern-auf-kat-achten-318521.html>, veröffentlicht am: May 8, 2011. cited by applicant
Wikipedia Article, “Bremse”, with translation “Brake”, <https://de.wikipedia.org/w/index.php?title=Bremse&oldid=192745901>. cited by applicant

Primary Examiner: Evans; Bryan A

Attorney, Agent or Firm: Shewchuk IP Services, LLC

Background/Summary

RELATED APPLICATION INFORMATION (1) The present application is a continuation of U.S. patent application Ser. No. 17/738,893, filed May 6, 2022 and entitled “Straddle-Type Vehicle”, now U.S. Pat. No. 11,919,603, which was a continuation of U.S. patent application Ser. No. 17/465,535, filed Sep. 2, 2021 and entitled “Straddle-Type Vehicle”, now U.S. Pat. No. 11,332,211, which was a by-pass continuation claiming the benefits of priority to International Application Number PCT/CN2020/124543, filed on Oct. 28, 2020, which is based upon and claims priority to Chinese Patent Application No. 201911029709.3, filed with the Chinese Patent Office on Oct. 28, 2019. The entire contents of the above-referenced applications are incorporated herein by reference.

FIELD OF THE DISCLOSURE

(1) The present application relates to a straddle-type vehicle.

BACKGROUND OF THE DISCLOSURE

(2) The background discussion provided herein is intended to facilitate understanding of the technical content of the present application, and is not necessarily admitted prior art.

(3) The English meaning of ATV is All-terrain vehicle, which is a means of transportation suitable for all terrain, and is abbreviated to ATV; ATVs may also be called “beach vehicles”, and are also known as “all-terrain four-wheel off-road locomotives”. The vehicle is simple and practical with good off-road performance. ATVs are equipped with wide tires to increase the area that the tires make contact with the ground, generating greater friction and reducing the pressure of the vehicle on the ground, making it easy to drive on beaches, riverbeds, woodland trails, streams and harsh desert terrain.

(4) It is difficult to express the meaning of an all-terrain vehicle in a simple Chinese name. According to its appearance, it can be translated into “all-terrain four-wheel off-road locomotive”, but such a translation still feels confusing. On soft sand, the ATV's wide tires can increase the area that the tires contact the ground, thereby generating greater friction, and unique tread patterns make spinning and skidding of the tires more difficult, making the vehicle easy to drive on the sand. But in fact, a good, high-performance ATV can not only be driven on beaches but also on riverbeds, woodland trails, streams and even on harsher desert terrain. ATVs are great for transporting people or goods, making the ATV a full function all-purpose vehicle of action.

(5) Depending on the displacement size and the external characteristics of the vehicle, ATVs are commonly divided into:

(6) Utility type, with its shape being square and upright a bit like a Willys Jeep (It's called "jeep type" in Taiwan), its most pronounced feature is to be provided with front and rear shelves or carriers; making the vehicle multi-functional and extremely practical. It can be used for carrying goods, farming, hunting, etc.

(7) Sport type, with a streamlined appearance that is very sporty, which is suitable for high-speed driving, leaps, stunts, etc. ATV races are mainly based on sport type ATVs.

(8) Military type, referring to a vehicle that can travel on any terrain. The most distinctive feature is that it can travel freely over terrain that is difficult for ordinary vehicles to be maneuvered. Classified by travelling mode, all-terrain vehicles have two types: wheeled and tracked. The military potential of ATVs has been recognized by more and more military forces, and its development is ascendant. The military type family is huge, with but a variety of models and novel styles.

(9) At present, all-terrain vehicles are more and more popular among consumers. One style is the straddle type vehicle, which is generally equipped with a single-cylinder engine. The existing arrangement of the engine of the straddle type vehicle arranges the cylinder head of the engine near the front. This arrangement results in an exhaust pipe and tubular muffler running the whole length of the vehicle, which makes it hotter near the driver's body, especially near the legs, thus the driver's riding comfort is reduced.

(10) In summary, how to improve the driver's comfort while driving a straddle vehicle has become a technical problem for those skilled in the art which urgently needs to be solved.

SUMMARY OF THE INVENTION

(11) The purpose of the present application is to disclose a straddle-type vehicle with improves the driving comfort and driving experience of the driver.

(12) In order to achieve the above purpose, the present application adopts the following technical solution: a straddle vehicle includes: a frame; a wheel assembly including front and rear wheels arranged under the frame; an engine mounted on the frame for providing power for the vehicle, the engine including a main body and a cylinder head connected to the main body and positioned above the main body; an intake and exhaust system, including an intake assembly for supplying air to the engine and an exhaust assembly for discharging exhaust gas generated by the engine; a brake system associated with the wheel assembly, including a parking component and a brake component; a transmission system installed on the frame for transmitting power from the engine to the wheel assembly; a fuel system arranged toward the front of the frame for providing fuel to the engine; and a saddle seat supported on the frame and located above the engine. The engine is oriented with its cylinder head positioned toward the rear of the frame. A projection of the cylinder head on a vertical plane where side walls of the front and rear wheels on the same side of the vehicle are positioned is located at the rear side of a projection of the midpoint of an imaginary line connecting centers of the front and rear wheels on the vertical plane, and the cylinder head is closer to the rear end of the frame.

(13) Optionally, the fuel system includes a fuel tank located toward the front end of the frame.

(14) Optionally, a projection of the center point of the fuel tank on the vertical plane where side walls of the front and rear wheels are positioned is located below a projection of the highest point of the cylinder head on the vertical plane.

(15) Optionally, the intake assembly includes an air filter; an air intake pipe connected to the air filter for air to enter into the air filter, and an air outlet pipe matched with the air filter for the filtered air to enter into the cylinder head. The air filter is located above the fuel tank.

(16) Optionally, the inlet of the air intake pipe faces toward the rear end of the frame.

(17) Optionally, the exhaust assembly includes a tubular muffler mounted on the frame, inside of which is a catalyst for promoting redox of exhaust gas. An exhaust pipe is located between the

tubular muffler and the cylinder head, one end of which is connected to the cylinder head, and the other end is connected to a middle portion of the tubular muffler.

(18) Optionally, the tubular muffler defines a resonance cavity, an exhaust cavity, and an air intake cavity arranged between the resonance cavity and the exhaust cavity. The exhaust pipe is connected to the air intake cavity. Exhaust gas enters into the resonance cavity through the air intake cavity, and then flows into the exhaust cavity through an internal pipeline.

(19) Optionally, a plurality of resonance tubes are provided inside of the resonance cavity. The side wall of each resonance tube defines a plurality of resonance holes for exhaust gas to enter into the resonance cavity.

(20) Optionally, a portion of the internal pipe located in the resonance cavity defines a plurality of air holes for exhaust gas to enter into the pipe.

(21) Optionally, the tubular muffler defines a partial pressure chamber adjacent to the resonance cavity. One end of the internal pipe is positioned in the partial pressure chamber, and exhaust gas enters into the internal pipe through a pipe port.

(22) Optionally, the engine also includes a transmission arranged on one side of the main body of the engine. The straddle vehicle further includes a battery, and the frame is provided with a battery mounting position arranged on the side away from the transmission.

(23) Optionally, the battery mounting position is a battery support plate arranged at a front lower position of the frame.

(24) Optionally, the battery support plate defines at least one hole for heat dissipation.

(25) Optionally, the frame includes an engine mounting position for supporting the engine, and the bottom of the main body is provided with an inclined shock absorber connected to the engine mounting position to form an inverted v-shaped support for the engine.

(26) Optionally, the engine mounting position is a bottom plate arranged on the lower portion of the frame, and the bottom plate has at least one flat surface.

(27) Optionally, a cross-section of the bottom plate is an inverted v-shaped structure.

(28) Optionally, the bottom plate defines a plurality of holes.

(29) Optionally, the parking component includes: a parking mechanism for braking the vehicle while parked, a handbrake cable connected to the parking mechanism, and a handle. One end of the handle is hinged to the frame, the handle being connected to the handbrake cable and arranged on one side of the frame.

(30) The present application also discloses a straddle vehicle, including: a frame; a wheel assembly including front and rear wheels arranged under the frame; an engine mounted on the frame for providing power to the vehicle, which includes a main body and a cylinder head connected to the main body and positioned above the main body; an intake and exhaust system, including an intake assembly for supplying air to the engine and an exhaust assembly for discharging exhaust gas generated by the engine; a brake system associated with the wheel assembly, including a parking component and a brake component; a transmission system installed on the frame for transmitting power from the engine to the wheel assembly; a fuel system arranged at a front end of the frame for providing fuel to the engine; and a saddle seat supported on the frame and located above the engine. The engine is oriented with its cylinder head positioned toward the rear of the frame. A projection of the center of gravity of the vehicle on a vertical plane where side walls of the front and rear wheels on the same side of the vehicle are positioned is located further forward than a projection of the center of gravity of the engine on the vertical plane.

(31) Optionally, the fuel system includes a fuel tank located toward the front end of the frame. A projection of a center of the fuel tank on a vertical plane is located further forward than a projection of the center of gravity of the vehicle on the vertical plane.

(32) Optionally, the projection of the center point of the fuel tank on a vertical plane is located below a projection of the highest point of the cylinder head on the vertical plane.

(33) Optionally, the intake assembly includes an air filter; an air intake pipe connected to the air

filter for allowing air to enter into the air filter, and an air outlet pipe matched with the air filter for the filtered air to enter into the cylinder head. The air filter is located above the fuel tank.

(34) Optionally, the inlet of the air intake pipe faces toward the rear end of the frame.

(35) Optionally, the exhaust assembly includes a tubular muffler mounted on the frame, inside of which is a catalyst for promoting redox of exhaust gas. An exhaust pipe is located between the tubular muffler and the cylinder head, one end of which is connected to the cylinder head, and the other end is connected to a middle portion of the tubular muffler.

(36) Optionally, the tubular muffler defines a resonance cavity, an exhaust cavity, and an air intake cavity arranged between the resonance cavity and the exhaust cavity. The exhaust pipe is connected to the air intake cavity. Exhaust gas enters into the resonance cavity through the air intake cavity, and then flows into the exhaust cavity through an internal pipe.

(37) Optionally, a plurality of resonance tubes are provided inside of the resonance cavity. The side wall of each resonance tube defines a plurality of resonance holes for exhaust gas to enter into the resonance cavity.

(38) Optionally, a portion of the internal pipe located in the resonance cavity defines a plurality of air holes for the exhaust gas to enter into the pipe.

(39) Optionally, the tubular muffler defines a partial pressure chamber adjacent to the resonance cavity. One end of the internal pipe is positioned in the partial pressure chamber, and exhaust gas enters into the pipe through a pipe port.

(40) Optionally, the straddle vehicle further includes a battery.

(41) The frame includes a battery mounting position arranged on the side away from the transmission.

(42) Optionally, the battery mounting position is a battery support plate arranged at a front lower position of the frame.

(43) Optionally, the battery support plate defines at least one hole for heat dissipation.

(44) Optionally, the frame includes an engine mounting position for supporting the engine, and the bottom of the main body is provided with an inclined shock absorber connected to the engine mounting position to form an inverted v-shaped support for the engine.

(45) Optionally, the engine mounting position is a bottom plate arranged on the lower portion of the frame, and the bottom plate has at least one flat surface.

(46) Optionally, a cross-section of the bottom plate is an inverted v-shaped structure.

(47) Optionally, the bottom plate defines a plurality of holes.

(48) Optionally, the parking component includes: a parking mechanism for braking the vehicle while parked, a handbrake cable connected to the parking mechanism and a handle. One end of the handle is hinged to the frame, the handle being connected to the handbrake cable and arranged on one side of the frame.

(49) The present application also discloses a straddle vehicle, including: a frame; a wheel assembly including front and rear wheels arranged under the frame; an engine mounted on the frame for providing power to the vehicle, the engine including a main body and a cylinder head connected to the main body and positioned above the main body; an intake and exhaust system, including an intake assembly for supplying air to the engine and an exhaust assembly for discharging exhaust gas generated by the engine; a brake system associated with the wheel assembly, including a parking component and a brake component; a transmission system installed on the frame for transmitting power from the engine to the wheel assembly; a fuel system arranged toward the front of the frame for providing fuel to the engine; and a saddle seat supported on the frame and located above the engine. A center line of the vehicle is defined along the length direction of the vehicle. A projection of the cylinder head on an imaginary plane including center lines of the two front wheels and the two rear wheels of the vehicle is located above a projection of the center line of vehicle on the imaginary plane.

(50) Optionally, the fuel system includes a fuel tank, a fuel pipe for conveying fuel from the fuel

tank to the engine, and a fuel pump for pumping fuel from the fuel tank to the fuel pipe. The fuel tank is located toward the front end of the frame.

(51) Optionally, a projection of the center point of the fuel tank on a vertical plane where side walls of the front and rear wheels are positioned is located below a projection of the highest point of the cylinder head on the vertical plane.

(52) Optionally, the intake assembly includes an air filter; an air intake pipe connected to the air filter for air to enter into the air filter, and an air outlet pipe matched with the air filter for the filtered air to enter into the cylinder head. The air filter is located above the fuel tank.

(53) Optionally, the inlet of the air intake pipe faces toward the rear end of the frame.

(54) Optionally, the exhaust assembly includes: a tubular muffler mounted on the frame, inside of which is a catalyst for promoting redox of exhaust gas. An exhaust pipe is located between the tubular muffler and the cylinder head, one end of which is connected to the cylinder head, and the other end is connected to a middle portion of the tubular muffler.

(55) Optionally, the tubular muffler defines a resonance cavity, an exhaust cavity, and an air intake cavity arranged between the resonance cavity and the exhaust cavity. The exhaust pipe is connected to the air intake cavity. Exhaust gas enters into the resonance cavity through the air intake cavity, and then flows into the exhaust cavity through an internal pipe.

(56) Optionally, a plurality of resonance tubes are provided. A side wall of each resonance tube defines a plurality of resonance holes for exhaust gas to enter into the resonance cavity.

(57) Optionally, a portion of the internal pipe located in the resonance cavity defines a plurality of air holes for exhaust gas to enter into the pipe.

(58) Optionally, the tubular muffler defines a partial pressure chamber adjacent to the resonance cavity. One end of the internal pipe is positioned in the partial pressure chamber, and exhaust gas enters into the internal pipe through a pipe port.

(59) Optionally, the frame includes a battery mounting position arranged on the side away from the transmission.

(60) Optionally, the battery mounting position is a battery support plate arranged at a front lower position of the frame.

(61) Optionally, the battery support plate defines at least one hole for heat dissipation.

(62) Optionally, the frame includes an engine mounting position for supporting the engine, and the bottom of the main body is provided with an inclined shock absorber connected to the engine mounting position to form an inverted v-shaped support for the engine.

(63) Optionally, the engine mounting position is a bottom plate arranged on the lower portion of the frame, and the bottom plate has at least one flat surface.

(64) Optionally, a cross-section of the bottom plate is an inverted v-shaped structure.

(65) Optionally, the bottom plate defines a plurality of holes.

(66) Optionally, the parking component includes: a parking mechanism for braking the vehicle while parked, a handbrake cable connected to the parking mechanism, and a handle. One end of the handle is hinged to the frame, the handle being connected to the handbrake cable and arranged on one side of the frame.

(67) The present application also discloses a straddle vehicle including an engine mounted on a frame, wherein, the side of the cylinder head of the engine is closer to the rear end of the frame than to the front end of the frame, and the connecting port on the cylinder head for connecting the exhaust pipe faces toward the rear end of the frame.

(68) Optionally, the exhaust pipe is provided with a tubular muffler including an air inlet and an air outlet, with the air inlet being located in the middle of a circumferential wall of the tubular muffler.

(69) Optionally, the air outlet is arranged at a rear lower end of the circumferential wall of the tubular muffler.

(70) Optionally, the tubular muffler includes a tubular body. A middle portion of the tubular body defines an air intake chamber directly connected to the air inlet. The tubular body defines a front

muffling chamber at the front end of the air intake chamber and a rear muffling chamber at the back end of the air intake chamber. The air intake chamber communicates with the front muffling chamber, the front muffling chamber communicates with the rear muffling chamber through a connecting pipe, and the air outlet communicates with the rear muffling chamber.

(71) Optionally, an inner portion of both the front muffling chamber and the rear muffling chamber includes a porous structure for sound absorption.

(72) Optionally, a connecting position for fixing the engine is arranged on the frame at a position corresponding to the bottom of the engine.

(73) Optionally, the connecting position includes a front connecting position arranged nearer to the front end of the frame and a rear connecting position arranged nearer to the back end of the frame.

(74) Optionally, a predetermined inclination angle is defined between a connection plane of the front connection position and/or the rear connection position and a bottom plane of the engine.

(75) Optionally, the predetermined inclination angle is in the range from 15° to 45° .

(76) Optionally, the straddle vehicle further includes: a wheel assembly, including front and rear wheels arranged under the frame; an intake and exhaust system, including an intake assembly for supplying air to the engine and an exhaust assembly for discharging exhaust gas generated by the engine; a transmission system mounted on the frame for transmitting power from the engine to the wheel assembly; and a fuel system arranged toward the front end of the frame for providing fuel to the engine.

(77) Optionally, a projection of the cylinder head on a vertical plane where side walls of the front and rear wheels on the same side of the vehicle are positioned is located at the rear side of a projection of a midpoint of an imaginary line connecting centers of the front and rear wheels on the vertical plane, and the cylinder head is closer to the rear end of the frame.

(78) Optionally, the engine is oriented with its cylinder head positioned toward the rear of the frame, and a projection of the center of gravity of the vehicle on a vertical plane where side walls of the front and rear wheels on the same side of the vehicle are positioned is located further forward than a projection of the center of gravity of the engine on the vertical plane.

(79) Optionally, a center line of the vehicle is defined along the length direction of the vehicle. A projection of the cylinder head on an imaginary plane including center lines of the two front wheels and the two rear wheels of the vehicle is located above a projection of the center line of vehicle on the imaginary plane.

(80) Optionally, the cylinder head is positioned toward the rear end of the frame. Defining a horizontal distance between the center of the cylinder head and a front axle of the vehicle as $L_{sub.e}$, and defining a horizontal distance between the center of the cylinder head and a rear axle of the vehicle as $L_{sub.f}$, $L_{sub.e} \geq L_{sub.f}$, and more preferably $L_{sub.e} \geq 2L_{sub.f}$.

(81) Optionally, the connecting port on the cylinder head for connecting the exhaust pipe faces toward the tubular muffler.

(82) The present application also discloses a straddle vehicle, including: a frame; a wheel assembly including front and rear wheels arranged under the frame; an engine mounted on the frame for providing power to the vehicle, the engine including a main body and a cylinder head connected to the main body and positioned above the main body; an intake and exhaust system, including an intake assembly for supplying air to the engine and an exhaust assembly for discharging exhaust gas generated by the engine; a brake system associated with the wheel assembly, including a parking component and a brake component; a transmission system mounted on the frame for transmitting power from the engine to the wheel assembly; a fuel system arranged toward the front of the frame for providing fuel to the engine; and a saddle seat supported on the frame and located above the engine. The engine is oriented with its cylinder head positioned toward the rear of the frame. Defining a horizontal distance between a center of the cylinder head and a front axle of the vehicle as $L_{sub.e}$, and defining a horizontal distance between the center of the cylinder head and a rear axle of the vehicle as $L_{sub.f}$, $L_{sub.e} \geq L_{sub.f}$, and more preferably $L_{sub.e} \geq 2L_{sub.f}$.

(83) Optionally, the fuel system includes a fuel tank located toward the front end of the frame.

(84) Optionally, a projection of the center point of the fuel tank on the vertical plane where side walls of the front and rear wheels are positioned is located below a projection of the highest point of the cylinder head on that plane.

(85) Optionally, the intake assembly includes an air filter; an air intake pipe connected to the air filter for air to enter into the air filter, and an air outlet pipe matched with the air filter for the filtered air to enter into the cylinder head. The air filter is located above the fuel tank.

(86) Optionally, the inlet of the air intake pipe faces toward the rear end of the frame.

(87) Optionally, the exhaust assembly includes a tubular muffler mounted on the frame, inside of which is a catalyst for promoting redox of exhaust gas. An exhaust pipe is located between the tubular muffler and the cylinder head, one end of which is connected to the cylinder head, and the other end is connected to a middle portion of the tubular muffler.

(88) Optionally, the tubular muffler defines a resonance cavity, an exhaust cavity, and an air intake cavity arranged between the resonance cavity and the exhaust cavity. The exhaust pipe is connected to the air intake cavity. Exhaust gas enters into the resonance cavity through the air intake cavity, and then flows into the exhaust cavity through an internal pipe.

(89) Optionally, a plurality of resonance tubes are provided inside of the resonance cavity. The side wall of each resonance tube defines a plurality of resonance holes for exhaust gas to enter into the resonance cavity.

(90) Optionally, a portion of the internal pipe located in the resonance cavity defines a plurality of air holes for exhaust gas to enter into the pipe.

(91) Optionally, the tubular muffler defines a partial pressure chamber adjacent to the resonance cavity. One end of the internal pipe is positioned in the partial pressure chamber, and exhaust gas enters into the internal pipe through a pipe port.

(92) Optionally, the engine also includes a transmission arranged on one side of the main body. The straddle vehicle also includes a battery, and the frame is provided with a battery mounting position arranged on the side away from the transmission.

(93) Optionally, the battery mounting position is a battery support plate arranged at a front lower portion of the frame.

(94) Optionally, the battery support plate defines at least one hole for heat dissipation.

(95) Optionally, the frame includes an engine mounting position for supporting the engine, and the bottom of the main body is provided with an inclined shock absorber connected to the engine mounting position to form an inverted v-shaped support for the engine.

(96) Optionally, the engine mounting position is a bottom plate arranged on a lower portion of the frame, and the bottom plate has at least one flat surface.

(97) Optionally, a cross-section of the bottom plate is an inverted v-shaped structure.

(98) Optionally, the bottom plate defines a plurality of holes.

(99) Optionally, the parking component includes: a parking mechanism for braking the vehicle while parked, a handbrake cable connected to the parking mechanism, and a handle. One end of the handle is hinged to the frame, the handle being connected to the handbrake cable and arranged on one side of the frame.

(100) The present application also discloses a straddle vehicle, including: a frame; a wheel assembly including front and rear wheels arranged under the frame; an engine mounted on the frame for providing power to the vehicle, which includes a main body and a cylinder head connected to the main body and positioned above the main body; the cylinder head including an exhaust port for discharging exhaust gas; an intake and exhaust system, including an intake assembly for supplying air to the engine and an exhaust assembly for discharging exhaust gas generated by the engine; the exhaust assembly including an exhaust pipe connected to the cylinder head and a tubular muffler connected to the exhaust pipe; a brake system associated with the wheel assembly, including a parking component and a brake component; a transmission system mounted

on the frame for transmitting power from the engine to the wheel assembly; a fuel system arranged at the front end of the frame for providing fuel to the engine; and a saddle seat supported on the frame and located above the engine. The engine is oriented with its cylinder head positioned toward the rear of the frame, and the opening direction of the exhaust port faces toward the tubular muffler.

(101) Optionally, the fuel system includes a fuel tank located toward a front end of the frame.

(102) Optionally, a projection of the center point of the fuel tank on the vertical plane where side walls of the front and rear wheels are positioned is located below a projection of the highest point of the cylinder head on that plane.

(103) Optionally, the intake assembly includes an air filter, an air intake pipe connected to the air filter for air to enter into the air filter, and an air outlet pipe matched with the air filter for the filtered air to enter into the cylinder head. The air filter is located above the fuel tank.

(104) Optionally, the inlet of the air intake pipe faces toward the rear end of the frame.

(105) Optionally, one end of an exhaust pipe is connected to the cylinder head, and the other end is connected to a middle portion of the tubular muffler.

(106) Optionally, the tubular muffler defines a resonance cavity, an exhaust cavity, and an air intake cavity arranged between the resonance cavity and the exhaust cavity. The exhaust pipe is connected to the air intake cavity. Exhaust gas enters into the resonance cavity through the air intake cavity, and then flows into the exhaust cavity through an internal pipe.

(107) Optionally, a plurality of resonance tubes are provided inside of the resonance cavity. The side wall of each resonance tube defines a plurality of resonance holes for exhaust gas to enter into the resonance cavity.

(108) Optionally, a portion of the internal pipe located in the resonance cavity defines a plurality of air holes for exhaust gas to enter into the pipe.

(109) Optionally, the tubular muffler defines a partial pressure chamber adjacent to the resonance cavity. One end of the internal pipe is positioned in the partial pressure chamber, and exhaust gas enters into the internal pipe through a pipe port.

(110) Optionally, the engine also includes a transmission arranged on one side of the main body of the engine. The straddle vehicle also includes a battery, and the frame is provided with a battery mounting position arranged on the side away from the transmission.

(111) Optionally, the battery mounting position is a battery support plate arranged at a front lower portion of the frame.

(112) Optionally, the battery support plate defines at least one hole for heat dissipation.

(113) Optionally, the frame includes an engine mounting position for supporting the engine, and a bottom of the main body is provided with an inclined shock absorber connected to the engine mounting position to form an inverted v-shaped support for the engine.

(114) Optionally, the engine mounting position is a bottom plate arranged on the lower portion of the frame, and the bottom plate has at least one flat surface.

(115) Optionally, a cross-section of the bottom plate is an inverted v-shaped structure.

(116) Optionally, the bottom plate defines a plurality of holes.

(117) Optionally, the parking component includes: a parking mechanism for braking the vehicle while parked, a handbrake cable connected to the parking mechanism, and a handle. One end of the handle is hinged to the frame, the handle being connected to the handbrake cable and arranged on one side of the frame.

(118) The present application also discloses a straddle vehicle, including: a frame; an engine for providing power to the vehicle, including a transmission, a main body and a cylinder head connected to the main body and positioned above the main body, the cylinder head including a cylinder head portion and a cylinder head cover; an intake and exhaust system including an intake assembly for providing air to the engine and an exhaust assembly for exhausting waste gas generated by the engine; the exhaust assembly including an exhaust pipe and a tubular muffler arranged at the rear end of the frame; a brake system including a parking component and a brake

component; a transmission system mounted on the frame for transmitting engine power to the wheels; a fuel system arranged at the front end of the frame for providing fuel to the power system; and a saddle seat system supported on the frame and located above the engine. The opening direction of the exhaust channel on the cylinder cover faces toward the tubular muffler.

(119) Optionally, the fuel system includes: a fuel tank arranged at the front end of the frame.

(120) Optionally, a center point of the fuel tank is positioned below the cylinder cover.

(121) Optionally, the intake assembly includes an air filter, an air intake pipe connected to the air filter for air to enter into the air filter, and an air outlet pipe matched with the air filter for the filtered air to enter into the cylinder head. The air filter is located above the fuel tank.

(122) Optionally, the inlet of the air intake pipe faces toward the rear end of the frame.

(123) Optionally, one end of the exhaust pipe is connected to the cylinder head, and the other end is connected to a middle portion of the tubular muffler.

(124) Optionally, the tubular muffler defines a resonance cavity, an exhaust cavity, and an air intake cavity arranged between the resonance cavity and the exhaust cavity. The exhaust pipe is connected to the air intake cavity. Exhaust gas enters into the resonance cavity through the air intake cavity, and then flows into the exhaust cavity through an internal pipe.

(125) Optionally, a plurality of resonance tubes are provided inside of the resonance cavity. The side wall of each resonance tube defines a plurality of resonance holes for exhaust gas to enter into the resonance cavity.

(126) Optionally, a portion of the internal pipe located in the resonance cavity defines a plurality of air holes for exhaust gas to enter into the pipe.

(127) Optionally, the tubular muffler defines a partial pressure chamber adjacent to the resonance cavity. One end of the internal pipe is positioned in the partial pressure chamber, and exhaust gas enters into the internal pipe through a pipe port.

(128) Optionally, the frame is provided with a battery mounting position arranged on the side away from the transmission.

(129) Optionally, the battery mounting position is a battery support plate arranged at a front lower position of the frame.

(130) Optionally, the battery support plate defines at least one hole for heat dissipation.

(131) Optionally, the frame is provided with an engine mounting position for supporting the engine, and a bottom of the main body is provided with an inclined shock absorber connected to the engine mounting position to form an inverted v-shaped support for the engine. The engine mounting position is a bottom plate arranged on a lower portion of the frame, and the bottom plate has at least one flat surface. A cross-section of the bottom plate is an inverted v-shaped structure. The bottom plate defines a plurality of holes.

(132) Optionally, the parking component includes: a parking mechanism for braking the vehicle while parked, a handbrake cable connected to the parking mechanism, and a handle. One end of the handle is hinged to a frame, the handle being connected to the handbrake cable and arranged on one side of the frame.

(133) In summary, compared to the background technical introduction, the engine arrangement structure of the above-mentioned straddle-type vehicle includes the engine mounted on the frame. In the engine arrangement structure, the cylinder head is arranged on the side of the engine closer to the rear end of the frame, and the connecting port on the cylinder head for connecting to the exhaust pipe faces toward the rear end of the frame. By arranging the cylinder head on one side of the engine nearer to the rear end of the frame, and arranging the connection port on the cylinder head for connecting to the exhaust pipe to face toward the rear end of the frame, the exhaust pipe and the tubular muffler need not be run through the length of the vehicle, and the exhaust pipe does not pass through the riding position of the driver located in the middle of the frame, so the temperature of the riding position of the driver is significantly reduced, and driving comfort is improved.

(134) In addition, the present application also provides a straddle-type vehicle, which includes an engine arrangement structure as described in any of the above solutions. As the engine arrangement structure of the above straddle-type vehicle has the above technical effects, the straddle vehicle with the above engine arrangement structure should also have the corresponding technical effects, which will not be repeated here.

(135) In the present application, the position of the cylinder head is close to the rear wheel of the vehicle, which allows the heated cylinder head of the engine and the exhaust pipe connected to the cylinder head to further spaced from the position where the legs contact with the vehicle while the user is driving the vehicle, so the effect of heat emitted from the cylinder head on the rider's comfort is reduced.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a perspective view of a straddle-type vehicle in an embodiment of the application.

(2) FIG. 2 is a right side view of the straddle-type vehicle in FIG. 1.

(3) FIG. 3 is a right side view of the engine and exhaust components of the straddle-type vehicle in FIG. 1 on the frame.

(4) FIG. 4 is a plan view of the cylinder head in FIG. 1 projected on a Cartesian coordinate system x-y.

(5) FIG. 5 is a right side view of the engine in FIG. 1 on the frame.

(6) FIG. 6 is a plan view of the cylinder head in FIG. 1 projected on a Cartesian coordinate system a-b.

(7) FIG. 7 is a plan view of the horizontal distance between the cylinder head and the front axle of vehicle and of the horizontal distance between the cylinder head and the rear axle of the vehicle in FIG. 1.

(8) FIG. 8 is a top view of the engine in FIG. 1 on the frame.

(9) FIG. 9 is a schematic diagram of the structure of the engine, fuel system and intake and exhaust system on the frame in FIG. 1.

(10) FIG. 10 is a perspective view of the fuel system and air intake components on the frame in FIG. 9.

(11) FIG. 11 is a structural schematic diagram of the fuel system and air intake components of FIG. 9 from another angle on the frame.

(12) FIG. 12 is a perspective view of the structure of the frame system in FIG. 5.

(13) FIG. 13 is a schematic diagram of the structure of the bottom plate on the frame system in FIG. 12.

(14) FIG. 14 is a schematic view of the structure of the shock absorber in FIG. 5.

(15) FIG. 15 is a perspective view of the engine, fuel system and intake and exhaust systems in FIG. 6.

(16) FIG. 16 is a perspective view of the engine, fuel system, and intake and exhaust system in FIG. 6 from another angle.

(17) FIG. 17 is a schematic diagram of the structure of the tubular muffler in FIG. 21.

(18) FIG. 18 is a partial cross-sectional view of the tubular muffler in FIG. 21.

(19) FIG. 19 is a schematic front view of an engine arrangement structure of a straddle-type vehicle provided in an embodiment of the present application.

(20) FIG. 20 is a top schematic view of the engine arrangement structure of a straddle-type vehicle provided by an embodiment of the present application.

(21) FIG. 21 is a side schematic view of the tubular muffler provided by an embodiment of the present application.

(22) FIG. 22 is a top schematic view of the tubular muffler provided by an embodiment of the present application.

(23) FIG. 23 is a schematic diagram of the internal structure of a tubular muffler provided by an embodiment of the present application.

DETAILED DESCRIPTION

(24) In order to enable those skilled in the art to better understand the present invention, the technical solutions in the embodiments of the present application are clearly and completely described below in conjunction with the accompanying drawings of the embodiments of the present application, and the structure or the related technical terms used in the present application are further described below. Any technical terms in the following should be understood and interpreted in accordance with their general usage within the field unless otherwise specified.

(25) Referring to FIGS. 1-2 and 11-14, a straddle-type vehicle 100 provided by an embodiment of the present application includes engine 10, a frame 20, a wheel assembly 30, an intake and exhaust system 40, a brake system 50, a transmission system 60, a fuel system 70, a saddle seat 80, and an electrical system 90. The engine 10 is arranged on the frame 20 for providing power to the whole vehicle. The frame 20 may be a metallic frame used for supporting the engine 10, the intake and exhaust system 40, the brake system 50, the transmission system 60, the fuel system 70, the saddle seat 80, and a plastic housing, etc. The wheel assembly 30 includes a front wheel 31 and a rear wheel 32 arranged below the frame 20. The intake and exhaust system 40 is connected to the engine 10. The brake system 50 is associated with the wheel assembly 30 for brake control. The transmission system 60 is mounted on the frame 20 and is able to transmit the power of engine 10 to the wheel assembly 30. The fuel system 70 is arranged at the front end of the frame to provide fuel to the engine 10. The saddle seat 80 is supported on the frame 20 and positioned above the engine 10.

(26) Referring to FIGS. 1-4 and 11-14, in the present embodiment, the engine 10 includes an engine main body 14 and a cylinder head 11 connected to the main body 14 and located above the main body 14. The engine 10 is mounted on the frame 20 and located at a lower portion of the frame 20, thereby the center of gravity of the entire vehicle 100 is effectively lowered. Specifically, an engine mounting position is provided on the frame 20. The engine mounting position is composed of two bottom plates 201 with spacing which are arranged at the lower portion of the frame 20. The bottom plate 201 may be an inverted V-shaped structure defining a plurality of mounting holes 2011 for receiving bolts. Of course, it may also have other shapes, for example, an inclined flat plate, or a metal tube with an inclined plane. Four shock absorbers 141 are connected to the bottom of the engine body 14. The shock absorbers 141 can absorb the vibration of the engine 20 to improve the stability of the vehicle 100 and reduce noise. Two shock absorbers 141 are mounted on one of the bottom plates 201 and the other two shock absorbers 141 are mounted on the other bottom plate 201. The shock absorbers 141 are inclined with a predetermined angle in the range from 15° to 45°. Specifically, the shock absorber 141 includes an upper connecting plate 1411, a lower connecting plate 1412 and a shock-absorbing damping block 1413. The upper connecting plate 1411 is connected to a shaft at the bottom of the main body 14. The shock-absorbing damping block 1413 is arranged between the upper connecting plate 1411 and the lower connecting plate 1412. An upper end surface of the shock-absorbing damping block 1413 is glued or otherwise connected to the upper connecting plate 1411, and a bottom surface of the shock-absorbing damping block 1413 is glued or otherwise connected to the lower connecting plate 1412. There is no direct connection between the lower connecting plate 1412 and the upper connecting plate 1411. The lower connecting plate 1412 may be connected to a base plate 201 by bolts.

(27) The engine 10 further includes a transmission 13 located on one side of the engine main body 11. In the present embodiment, the transmission 13 is a CVT transmission. It is understood that other types of transmissions can alternatively be used. After the engine 10 is mounted on the frame 20, the engine cylinder is non-vertically slanted with the cylinder head 11 facing toward the rear

end of the frame **20**. The cylinder head **11** is located below the saddle seat **80**, which keeps the cylinder head **11** away from the rider's legs, and the heat emitted from the cylinder head **11** is insulated by the saddle seat **80**. Therefore, the heat emitted from the cylinder head **11** is not transferred to the rider, which ensures the rider's comfort and also enhances the rider's safety while driving the vehicle **100**.

(28) As shown in FIGS. **1-4**, the wheel assembly **30** includes a front wheel **31** adjacent to the front end of the frame **20** and a rear wheel **32** adjacent to the rear end of the frame **20**. The front wheel **31** is connected to the transmission system **60** through the front axle **311**, and the rear wheel **32** is connected to the transmission system **60** through the rear axle **321**. A Cartesian coordinate system x-y is established parallel to a plane where side walls of the front wheel **31** and rear wheel **32** are positioned. Both the center of the front wheel **31** and the center of the rear wheel **32** are points on the axis x, and the midpoint of an imaginary line connecting the centers of the front wheel **31** and the rear wheel **32** defines the origin O of Cartesian coordinate system x-y. The projection of cylinder head **11** onto the plane of the Cartesian coordinate system is located in the first quadrant of the Cartesian coordinate system x-y; that is, the cylinder head **11** is located rearwardly from the midpoint of the imaginary line connecting the centers of the front wheel **31** and the rear wheel **32**, and is therefore closer to the rear end of the frame **20** than to the front end of the frame **20**.

(29) As shown in FIGS. **9-10**, the fuel system **70** includes a fuel tank **701** mounted on the frame **20**. The fuel tank **701** is a thin-walled tank with its fuel tank position on the front end of the frame **20**, mounted by two spaced support bars **202** on the frame **20**. The width between the two support bars **221** is suitable for supporting the fuel tank **701**. The fuel tank **701** is positioned on the two support bars **221** and supported by the support bars **221** to fix the position of the fuel tank **701** on the frame **20** so the fuel tank **701** has high stability. The projection of the fuel tank **701** onto the plane of the Cartesian coordinate system x-y is located in the second quadrant of the Cartesian coordinate system x-y. As such, the fuel tank **701** is away from the cylinder head **11** and away from the heat source of the engine **10**, resulting in less heating of the fuel tank **701** and increased safety of the fuel tank when mounted on the frame **20**. The positioning keeps the fuel temperature in the fuel tank **701** low, resulting in less fuel volatilization. The projection of the center point of the fuel tank **701** on the plane of the Cartesian coordinate system is located below the projection of the highest point of the cylinder head **11** on the plane of the Cartesian coordinate system, nearer to the front end of the frame. The positioning results in a lower mounting height of the fuel tank **701** on the frame **20**, thereby reducing the center of gravity of the whole vehicle, so the vehicle has high stability during turning of the vehicle.

(30) As shown in FIGS. **9-11**, the intake and exhaust system **40** includes an intake assembly **41** and an exhaust assembly **42**. The intake assembly is used to provide clean air to the engine **10** to maintain efficient combustion of fuel in the combustion chamber of the engine **10**. The intake assembly **41** includes an air filter **411**, an air intake pipe **412** and an air outlet pipe **413**, wherein the air intake pipe **412** is connected to the air filter **411** to allow air to enter into the air filter **411** to filter out impurities in the air. The air outlet pipe **413** is connected to the engine **10**, and the filtered air is transmitted to the engine **10** through the air outlet pipe **413**, so as to provide oxygen for the fuel. In particular, the air filter **411** is located above the fuel tank **701** and fixed on the frame **20** by bolts. This positioning increases the mounting height of the air filter **411** on the vehicle, resulting in cleaner air entering into the air filter **411** and a longer service life of the air filter **411**. At the same time, the air intake pipe **412** is arranged at the front end of the air filter **411**, and the air intake pipe **412** is curved such that the inlet **412a** of the air intake pipe **412** faces rearwardly. Orienting the inlet **412a** rearwardly helps to prevent solid particles in the air from being passively poured into the air filter **411** during vehicle driving, and ensures that the air intake of the air filter **411** is reasonable.

(31) As shown in FIGS. **15-18**, the exhaust assembly **42** includes a tubular muffler **421** and an exhaust pipe **422** connected to the tubular muffler **421** and cylinder head **11**. The tubular muffler **421** is arranged at the rear end of the frame **20**. A connecting block **424** is provided on the tubular

muffler **421**. The connecting block **424** is a metal block closely attached to the outer wall of the tubular muffler **421** which indirectly connects the tubular muffler **421** to the frame **20**. The tubular muffler **421** defines a resonance cavity **4212**, an exhaust cavity **4213**, an air intake cavity **4214** and a partial pressure chamber **4215**. Exhaust gas enters the air intake cavity **4214** through the exhaust pipe **422**, and then flows from the air intake cavity **4214** into the resonance cavity **4212**. Exhaust gas is internally piped both from the resonance cavity **4212** and from the partial pressure chamber **4215** into the exhaust cavity **4213**. The air intake cavity **4214** may be located in a middle portion of the tubular muffler **421**. The volume of the air intake cavity **4214** is larger than any of the volumes of the resonance cavity **4212**, the exhaust cavity **4213** or the partial pressure chamber **4215**. A catalyst is provided within the air intake cavity **4214** for promoting exhaust gas redox. The exhaust pipe **422** is connected to the middle portion of the tubular muffler **421**, that is, the exhaust pipe **422** is connected to the air intake cavity **4214**. This positioning extends the length of the exhaust pipe **422**, reduces the curvature of the exhaust pipe **422**, and reduces the resistance of the exhaust flow. Further, the partial pressure chamber **4215** is located at the front of the tubular muffler **421**, and the resonance cavity **4212** is located between the air intake cavity **4214** and the partial pressure chamber **4215**. The exhaust cavity **4213** is located at the rear of the tubular muffler **421**, with the exhaust cavity **4213** being adjacent to the air intake cavity **4214**.

(32) In particular, a plurality of resonance tubes **4216** with openings at both ends are arranged in the resonance cavity **4212**, and the resonance tubes **4216** communicate with the air intake cavity **4214** and the partial pressure chamber **4215**. A plurality of resonance holes **4217** are defined on the side wall of the resonance tube **4216**. The exhaust gas in the air intake cavity **4214** flows in through one end of the resonance tube **4216**, and then one portion of the exhaust gas flows into the resonance cavity **4212** through the resonance holes **4217**, and the other portion of the exhaust gas flows into the partial pressure chamber **4215** through the other end of the resonance tube **4216**. A pipe **4218** within the tubular muffler **421** connects the resonance cavity **4212** and the exhaust cavity **4213** and also connects the partial pressure chamber **4215** and the exhaust cavity **4213**. The pipe **4218** has openings on both ends, and a plurality of air holes are arranged on the side wall of the portion of the pipe **4218** located in the resonance cavity **4212**. The exhaust gas in the resonance cavity **4212** enters the pipe **4218** through the air holes, and then flows into the exhaust cavity **4213**. One end of the pipe **4218** is positioned in the partial pressure chamber **4215**. The exhaust gas in the partial pressure chamber **4215** flows into the pipe **4218** through one end of the pipe **4218**, and flows into the exhaust cavity **4213** through the pipe **4218**.

(33) Further, the tubular muffler **421** is provided with a tail gas pipe **423** which is connected to the exhaust cavity **4213**, and the exhaust gas entering the exhaust cavity **4213** is discharged into the outside air through the tail gas pipe **423**. The position of the tail gas pipe **423** is preferably at a lower end of the circumferential wall of the tubular muffler **421**. Specifically, the tail gas pipe **423** is curved, and the outlet for exhaust gas of the tail gas pipe **423** is inclined and aligned with the bottom plane of the lower end. One end where the tail gas pipe **423** is connected to the exhaust cavity **4213** is inserted into the exhaust cavity **4213** extends vertically within the exhaust cavity **4213**.

(34) As shown in FIGS. **11-12**, the electrical system **90** includes a battery **91** for providing power for ignition of the engine **10** as well as other electrical elements of the vehicle. The battery **91** is located at the front lower portion of the frame **20** and is close to the engine **10**. The battery **91** is located on the side away from the transmission **13**, so that the heat of the transmission **13** is not transmitted to the battery **91**, which lowers the working temperature of the battery **91**, increases the working life of the battery **91**, and eliminates the potential safety hazard of the battery **91** exploding due to overheating. In particular, a battery mounting position is provided on the frame **20**, which includes a battery support plate **203** fixed on the frame **20**. The battery support plate **203** is located at the lower portion of the frame **20** and on the side away from the transmission **13**. The battery **91** is placed on the battery support plate **203**. The edges of the battery support plate **203** are upturned

to form a flange **2031** such that battery movement is limited by the flange **2031**. The flange **2031** enables heat dissipation from the battery **91** and ensures the battery **91** is stable and is not easily moved. The center of the battery support plate **203** can additionally define a heat dissipation hole **2032** to increase the heat dissipation of the battery **91** and keep the battery **91** working at normal temperature.

(35) As shown in FIGS. **1-2**, the brake system **50** includes a parking component or assembly **51** to prevent the vehicle **100** from moving after the vehicle **100** has been parked. The parking assembly **51** includes a parking mechanism **511**, a handbrake cable **512** and a handle **513**. One end of the handbrake cable **512** is connected to the parking mechanism **511**, and the other end is connected to the handle **513**. By pulling the handle **513**, the force on the handle **513** is transmitted to the parking mechanism **511** through the handbrake cable **512**, thereby engaging a parking brake for the vehicle **100**. In particular, one end of the handle **513** is indirectly and rotatably connected to one side of the frame **20**. When using the handle **513**, only one end of the handle **513** needs to be pulled so that the handle can be rotated to a certain angle. The handle **513** is arranged on one side of the fuel tank **701** of the vehicle **100** and is close to the front end of the saddle seat **80**, a position which is convenient and easy for pulling the handle **513**, saving time and effort. A shift lever **601** is indirectly arranged on the frame **20** and close to the front end of the saddle seat **80**. The position of the shift lever **601** corresponds to the position of the handle **513**, that is, the shift lever **601** is arranged on one side of the frame, and the handle **513** is arranged on the other side of the frame, which is convenient for manual gear shifting when driving the vehicle.

(36) As shown in FIGS. **1-3** and **5**, point A is the center of gravity of the vehicle **100**, and point B is the center of gravity of the engine **10**. The projection of point A on the plane of the Cartesian coordinate system x-y is located on the front side of the projection of point B on the plane of the Cartesian coordinate system x-y, that is, the horizontal distance between point B and the axle center of the rear wheels **32** is less than the horizontal distance between point A and the axle center of the rear wheels **32**. FIGS. **3** and **5** show only portions of the preferred embodiment, which are understood to include structures identical or similar to those of other Figures, the description of which is not repeated here.

(37) As shown in FIGS. **1-3** and **8**, a distance between a center of the cylinder head **11** of the engine **10** and the front axle **311** is $L_{sub.e}$, and a distance between a center of the cylinder head **11** and the rear axle **321** is $L_{sub.f}$, wherein $L_{sub.e} \geq L_{sub.f}$, and more preferably $L_{sub.e} \geq 2L_{sub.f}$. FIGS. **3** and **8** show only portions of the preferred embodiment, which are understood to include structures identical or similar to those of other Figures, the description of which is not repeated here.

(38) As shown in FIGS. **1-3** and **6**, the Cartesian coordinate system a-b is established on a plane of imaginary lines connecting the centers of the two front wheels **31** and the centers of the two rear wheels **32** of the vehicle **100**, wherein, axis a is the horizontal axis of the Cartesian coordinate system a-b, axis b is the vertical axis as drawn, and the origin is the intersection point. The projection of the wheelbase centerline along the length direction of the vehicle **100** on the plane of the Cartesian coordinate system coincides with axis a, and the projection of the vehicle centerline along the width direction of the vehicle on the plane of the Cartesian coordinate system a-b coincides with the axis b. The projection of the midpoint c of the cylinder head **11** on the plane of the Cartesian coordinate system a-b is located in the first quadrant of the Cartesian coordinate system a-b above the wheelbase centerline. FIGS. **3** and **6** show only portions of the preferred embodiment, which are understood to include structures identical or similar to those of other Figures, the description of which is not repeated here.

(39) As shown in FIGS. **1-3** and **8**, the opening direction of the exhaust port on the cylinder head **11** faces toward the tubular muffler **421**. FIGS. **3** and **8** show only portions of the preferred embodiment, which are understood to include structures identical or similar to those of other Figures, the description of which is not repeated here.

(40) As shown in FIGS. **1-5** and **19-23**, the present embodiment of the invention provides an engine

arrangement structure for a straddle-type vehicle, including a frame **25** and an engine **15** fixed on the frame **25**. The cylinder is slanted with the cylinder head **151** of the engine **15** is positioned toward the rear of the frame **25**. The connection port for connecting the exhaust pipe **152** to the cylinder head **151** faces toward the rear of the frame **25**.

(41) By arranging the cylinder head **151** of the engine **15** toward the rear of the frame, and arranging the connection port of the cylinder head **151** to the exhaust pipe **152** facing toward the rear of the frame **25**, the exhaust pipe **152** and the tubular muffler **35** need not run the whole length of the vehicle. The exhaust pipe does not pass through the riding position of the driver located in the middle of the frame **25**, so the temperature of the riding position of the driver is significantly reduced, and driving comfort is improved.

(42) It should be noted here that for those skilled in this art, straddle-type vehicles are generally provided with single-cylinder engines, and the cylinder head **151** of the single-cylinder engine is connected to an exhaust pipe **152** through which exhaust gas is discharged.

(43) In more preferred embodiments, the cylinder head **151** of the engine **15** is positioned toward the rear end of the frame **25**, and the connection port of the cylinder head **151** which connects to the exhaust pipe **152** is also facing rearwardly. These orientations reduce the space available for the muffler. In order to meet the space requirements for the muffler, the muffler is preferably a tubular muffler **35** including an air inlet **36** and an air outlet **37**, with the air inlet **36** of the tubular muffler **35** arranged in the middle portion of the circumferential wall of the tubular muffler **35**. Thereby, the arrangement space of the muffler can be effectively saved.

(44) In more preferred embodiments, the air outlet **37** of the tubular muffler **35** is arranged at a rear lower end of the circumferential wall of the tubular muffler **35**. This arrangement can prevent precipitation from entering the inside of the tubular muffler **35**, extending the normal service life of the tubular muffler. Of course, it should be noted that the method of arranging the air outlet **37** at the rear lower end of the circumferential wall of the tubular muffler **35** is only a most preferred embodiment of the present invention. In other embodiments, the air outlet **37** may also be arranged at the rear end face of the tubular muffler **35**, or may be arranged at another position according to demand requirements.

(45) It should be noted here that, as shown in FIG. **23**, the above-discussed tubular muffler **35** includes a tubular body **351**, the middle portion of which is provided with an air intake chamber **3511** which is directly connected to the air inlet **36**. The tubular muffler **35** includes a front muffling chamber **3512** at the front end of the air intake chamber **3511** and a rear muffling chamber **3513** at the back end of the air intake chamber **3511**. The air intake chamber **3511** communicates with the front muffling chamber **3512**, the front muffling chamber **3512** communicates with the rear muffling chamber **3513** through a connecting pipe **3514**, and the air outlet **37** communicates with the rear muffling chamber **3513**. Through this structure of the tubular muffler **35**, the exhaust gas path is that the exhaust gas enters into the air intake chamber **3511** from the air inlet port **36**, and then flows into the front muffler chamber **3512** for preliminary muffling, and then the exhaust gas in the front muffling chamber **3512** is introduced into the rear muffling chamber **3513** through the connecting pipe **3514** for muffling again, and finally the exhaust gas is discharged through the air outlet **37** connected to the rear muffling chamber **3513**. By adopting this structure of the tubular muffler **35**, the arrangement space of the muffler can be reduced. The double muffling structure also better enhances the silencing effect of the muffler. It should also be noted that the top of the tubular body of the tubular muffler **35** is generally provided with a mounting position **38** for convenient installation on the vehicle body. The specific structure of the mounting position **38** can adopt a double lifting lug structure, or the other structures commonly used by those skilled in this art and not specified here. A double-layered sandwich structure of sound-absorbing materials is generally arranged on the wall of the tubular body to ensure good silencing effect of the muffler. The structure of the wall of the tubular body may include a double-layer stainless steel plate, the middle of which is filled with sound-absorbing cotton and other sound-absorbing materials. In

addition, it should be noted that the inner portions of both the front muffling chamber 3512 and the rear muffling chamber 3513 are generally provided with a porous structure for sound absorption 350, which belongs to the prior art known to those skilled in this field and is not further described in detail here.

(46) In some more specific embodiments, a connection position 251 for fixing the engine 15 is arranged on the frame 25 at a position corresponding to the bottom of the engine 15. Of course, it should be understood that locating the connecting position at the bottom of the engine is only a preferred embodiment of the present invention, and the connecting position can be located elsewhere according to demand requirements.

(47) In a preferred embodiment, the connection position 251 includes a front connection position 2511 arranged nearer to the front end of the frame 25 and a rear connection position 2512 arranged nearer to the rear end of the frame 25. In order to improve the stability of the engine 15 fixed on the frame 25 and avoided the lateral movement of the engine 15 relative to the frame 25, a predetermined inclination angle is defined between the connection plane of the front connection position 2511 and/or the rear connection position 2512 and the bottom plane of engine 15. By setting a predetermined inclination angle, the connecting plane of connection position 251 can support and fix the engine 15 through an inclined plane while laterally limiting the engine 15 relative to the engine frame 25 at the same time, which makes the fixation more stable and reliable.

(48) In a further technical solution, the predetermined inclination angle is generally preferred to be in the range from 15° to 45°. Of course, it can be understood that this is only the preferred example of the specific numerical value for the predetermined inclination angle, and an alternative predetermined angle value can be selected according to demand requirements.

(49) In addition, the present invention also provides a straddle-type vehicle which includes the engine arrangement structure as described in any of the embodiments. As the engine arrangement structure of the above straddle-type vehicle results in the above described technical benefits, a straddle-type vehicle with such an engine arrangement structure also results in the corresponding technical benefits, which will not be repeated here.

(50) The straddle-type vehicle and the arrangement structure of the engine provided by the present invention are described in detail above. It should be noted that each embodiment of the present specification is described in a progressive manner, and each description focuses on differences from the other embodiments. Similar aspects between the various embodiments can be implied by reference to descriptions of other embodiments.

(51) It should also be noted that, in this description, terms such as “including”, “containing” or any other variations are intended to be a non-exclusive inclusion, so that items or equipment including a series of elements include not only those elements but also other elements that are not explicitly listed but are inherent to such items or equipment. In the absence of more restrictions, the element modified by the statement “including a” does not exclude such non-listed items or equipment.

(52) All patents and publications referred to in this application specification are publicly available technologies in the field, which may be used to modify the preferred embodiments in this application. All the patents and publications cited in the references could also be used to modify the preferred structures individually referred to herein. The present application can be implemented in the absence of any one or more elements or one or more restrictions which are not specified in the independent claims. The terms and expressions used herein are for description of the most preferred embodiments only, and the invention is not limited by such descriptions of any preferred embodiments, nor is there any intention to indicate that the terms and interpretations described in this application specification exclude any equivalent features. Instead, workers skilled in the art know that any appropriate improvements or modifications may be made within the scope of this application and claims. Understandably, the embodiments described in the present application are some preferred embodiments and features, and any general technical personnel in this art can make some improvements and modifications in accordance with the spirit described in this application.

Such improvements and modifications are also deemed to fall into the scopes both of this application and of the limitations of the independent and dependent claims.

Claims

1. A straddle-type vehicle comprising: a frame defining a front end and a rear end; wheels including front and rear wheels supporting the frame; an engine mounted on the frame for providing power to the vehicle, which comprises a main body and a cylinder head connected to the main body and positioned above the main body, the cylinder head having an exhaust channel for discharging exhaust gas; an intake and exhaust system, comprising an intake assembly for supplying air to the engine and an exhaust assembly for discharging exhaust gas generated by the engine, the exhaust assembly having an exhaust pipe connected to the cylinder head and a muffler connected to the exhaust pipe; a brake system associated with the wheels; a transmission system on the frame for transmitting power from the engine to the wheels; a fuel system for providing fuel to the engine, wherein the fuel system comprises a fuel tank located forwardly of the engine; and a saddle seat supported on the frame and located above the engine; wherein the engine is oriented with its cylinder head positioned toward the rear end of the frame, and the opening direction of the exhaust channel faces toward the muffler; wherein a center point of the fuel tank is located at an elevation lower than a highest point of the cylinder head; and wherein the muffler defines: a resonance cavity; an exhaust cavity; and an air intake cavity located between the resonance cavity and the exhaust cavity; wherein the exhaust pipe is connected to the air intake cavity such that exhaust gas enters into the resonance cavity through the air intake cavity, and then flows into the exhaust cavity.
2. The straddle-type vehicle of claim 1, wherein a catalyst is provided inside the muffler for promoting redox of exhaust gas.
3. The straddle-type vehicle of claim 1, wherein a plurality of resonance tubes are provided inside of the resonance cavity, each side wall of which defines a plurality of resonance holes for exhaust gas to enter into the resonance cavity.
4. The straddle-type vehicle of claim 1, wherein a portion of an internal pipe located in the resonance cavity defines a plurality of air holes for allowing exhaust gas to enter into the internal pipe.
5. The straddle-type vehicle of claim 4, wherein the muffler defines a partial pressure chamber adjacent to the resonance cavity, one end of the internal pipe being positioned in the partial pressure chamber, with exhaust gas entering into the internal pipe through a pipe port.
6. A straddle-type vehicle comprising: a frame defining a front end and a rear end; wheels including front and rear wheels supporting the frame; an engine mounted on the frame for providing power to the vehicle which comprises a main body and a cylinder head connected to the main body and positioned above the main body, the cylinder head having an exhaust channel for discharging exhaust gas; an intake and exhaust system, comprising an intake assembly for supplying air to the engine and an exhaust assembly for discharging exhaust gas generated by the engine, the exhaust assembly having an exhaust pipe connected to the cylinder head and a muffler connected to the exhaust pipe; a brake system associated with the wheels; a transmission system on the frame for transmitting power from the engine to the wheels; a fuel system for providing fuel to the engine, wherein the fuel system comprises a fuel tank located forwardly of the engine; and a saddle seat supported on the frame and located above the engine; wherein the engine is oriented with its cylinder head positioned toward the rear end of the frame, and the opening direction of the exhaust channel faces toward the muffler; wherein a center point of the fuel tank is located at an elevation lower than a highest point of the cylinder head; and wherein the straddle-type vehicle further comprises a battery, with the main body positioned between a transmission of the transmission system and the battery.
7. The straddle-type vehicle of claim 6, wherein the battery is mounted on a battery support plate at

a front lower part of the frame.

8. The straddle-type vehicle of claim 7, wherein the battery support plate defines at least one hole for heat dissipation.

9. The straddle-type vehicle of claim 6, wherein a bottom of the main body is provided with an inclined shock absorber for supporting the engine.

10. The straddle-type vehicle of claim 9, wherein a bottom plate with at least one flat surface supports the engine from a lower portion of the frame.

11. A straddle-type vehicle comprising: a frame defining a front end and a rear end; wheels including front and rear wheels supporting the frame; an engine mounted on the frame for providing power to the vehicle, which comprises a main body and a cylinder head connected to the main body and positioned above the main body, the cylinder head having an exhaust channel for discharging exhaust gas; an intake and exhaust system, comprising an intake assembly for supplying air to the engine and an exhaust assembly for discharging exhaust gas generated by the engine, the exhaust assembly having an exhaust pipe connected to the cylinder head and a muffler connected to the exhaust pipe; a brake system associated with the wheels; a transmission system on the frame for transmitting power from the engine to the wheels; a fuel system for providing fuel to the engine, wherein the fuel system comprises a fuel tank located forwardly of the engine; and a saddle seat supported on the frame and located above the engine; wherein the engine is oriented with its cylinder head positioned toward the rear end of the frame. and the opening direction of the exhaust channel faces toward the muffler; wherein a center point of the fuel tank is located at an elevation lower than a highest point of the cylinder head; and wherein a bottom of the main body is provided with an inclined shock absorber for supporting the engine, wherein a bottom plate with at least one flat surface supports the engine from a lower portion of the frame, and wherein a cross-section of the bottom plate has an inverted v-shape.

12. The straddle-type vehicle of claim 11, wherein the bottom plate defines a plurality of holes.

13. The straddle-type vehicle of claim 12, wherein the brake system comprises a handle, one end of which is hinged to the frame, connected to a handbrake cable.

14. A straddle-type vehicle comprising: a frame defining a front end and a rear end; wheels including front and rear wheels supporting the frame; an engine mounted on the frame for providing power to the vehicle, which comprises a main body and a cylinder head connected to the main body and positioned above the main body, the cylinder head having an exhaust channel for discharging exhaust gas; an intake and exhaust system, comprising an intake assembly for supplying air to the engine and an exhaust assembly for discharging exhaust gas generated by the engine, the exhaust assembly having an exhaust pipe connected to the cylinder head and a muffler connected to the exhaust pipe; a brake system associated with the wheels; a transmission system on the frame for transmitting power from the engine to the wheels; a fuel system for providing fuel to the engine; and a saddle seat supported on the frame and located above the engine; wherein the engine is oriented with its cylinder head positioned toward the rear end of the frame. and the opening direction of the exhaust channel faces toward the muffler; wherein a center point of the fuel tank is located at an elevation lower than a highest point of the cylinder head; and wherein the muffler defines; a resonance cavity; an exhaust cavity; and an air intake cavity between the resonance cavity and the exhaust cavity; wherein the exhaust pipe is connected to the air intake cavity; and wherein exhaust gas enters into the resonance cavity through the air intake cavity, and then flows into the exhaust cavity.

15. The straddle-type vehicle of claim 14, wherein the fuel system comprises: a fuel tank located forwardly of the engine.

16. The straddle-type vehicle of claim 14, wherein the intake assembly comprises: an air filter; an air intake pipe connected to the air filter for air to enter into the air filter; and an air outlet pipe connected with the air filter for filtered air to enter into the cylinder head; the air filter being located above the fuel tank.

17. The straddle-type vehicle of claim 16, wherein an inlet of the air intake pipe faces rearwardly.
 18. The straddle-type vehicle of claim 14, wherein a plurality of resonance tubes are provided inside of the resonance cavity, each side wall of which defines a plurality of resonance holes for exhaust gas to enter into the resonance cavity.
 19. The straddle-type vehicle of claim 14, wherein a portion of an internal pipe located in the resonant cavity defines a plurality of air holes for the exhaust gas to enter into the internal pipe.
 20. The straddle-type vehicle of claim 14, wherein the muffler defines a partial pressure chamber adjacent to the resonance cavity, with exhaust gas entering into the partial pressure chamber through a pipe port of an internal pipe.
 21. A straddle-type vehicle comprising: a frame defining a front end and a rear end; wheels including front and rear wheels supporting the frame; an engine mounted on the frame for providing power to the vehicle, which comprises a main body and a cylinder head connected to the main body and positioned above the main body, the cylinder head having an exhaust channel for discharging exhaust gas; an intake and exhaust system, comprising an intake assembly for supplying air to the engine and an exhaust assembly for discharging exhaust gas generated by the engine, the exhaust assembly having an exhaust pipe connected to the cylinder head and a muffler connected to the exhaust pipe; a brake system associated with the wheels; a transmission system on the frame for transmitting power from the engine to the wheels; a fuel system for providing fuel to the engine; and a saddle seat supported on the frame and located above the engine; wherein the engine is oriented with its cylinder head positioned toward the rear end of the frame, and the opening direction of the exhaust channel faces toward the muffler; wherein a center point of the fuel tank is located at an elevation lower than a highest point of the cylinder head; and wherein the transmission system comprises a transmission and wherein the straddle-type vehicle further comprises a battery mounted from the frame on a side of the main body opposite from the transmission.
 22. The straddle-type vehicle of claim 21, wherein the battery is mounted on a battery support plate defining at least one hole for heat dissipation.
 23. The straddle-type vehicle of claim 21, wherein the fuel system comprises: a fuel tank located forwardly of the cylinder head.
 24. The straddle-type vehicle of claim 23, wherein a center point of the fuel tank is located at an elevation lower than a highest point of the cylinder head.
 25. The straddle-type vehicle of claim 24, wherein the intake assembly comprises: an air filter located at least partially higher than the fuel tank; an air intake pipe connected to the air filter for air to enter into the air filter; and an air outlet pipe connected with the air filter for filtered air to enter into the cylinder head.
 26. The straddle-type vehicle of claim 25, wherein an inlet of the air intake pipe faces rearwardly.
-