

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12398633
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Watson; Arthur Ignatius et al.

High pressure resistant and partial discharge reduced MLE

Abstract

An electric submersible pump (ESP) system. The ESP system may comprise a motor, a pothead coupled to the motor, and a cable coupled to the pothead via a motor lead extension (MLE) to provide power to the motor.

Inventors: Watson; Arthur Ignatius (Houston, TX), Singh; Shivam Kumar (Lawrence, KS), Brady; Josh (Lawrence, KS), Ma; Patrick Zhiyuan (Lawrence, KS)

Applicant: Schlumberger Technology Corporation (Sugar Land, TX)

Family ID: 1000008782033

Assignee: Schlumberger Technology Corporation (Sugar Land, TX)

Appl. No.: 18/652584

Filed: May 01, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240368970 A1	Nov. 07, 2024

Related U.S. Application Data

us-provisional-application US 63499320 20230501

Publication Classification

Int. Cl.: E21B43/12 (20060101); E21B17/02 (20060101)

U.S. Cl.:

Field of Classification Search

CPC: E21B (43/128); E21B (43/12); E21B (43/121)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2009/0068037	12/2008	Shaw et al.	N/A	N/A
2017/0018989	12/2016	Reeves	N/A	F04D 13/086
2017/0244294	12/2016	Holzmueller	N/A	H02K 5/132
2017/0350198	12/2016	Ma	N/A	E21B 17/028
2018/0202271	12/2017	Semple et al.	N/A	N/A
2019/0237900	12/2018	Frey et al.	N/A	N/A
2020/0091652	12/2019	Golberg	N/A	N/A
2022/0056767	12/2021	Part	N/A	E21B 17/026

OTHER PUBLICATIONS

Schlumberger—Trident—Extreme conditions motor lead extension Accessed via wayback machine <https://web.archive.org/web/20220121201713/https://www.slb.com/-/media/files/al/product-sheet/reda-maximus-trident-ps.ashx> (Year: 2017). cited by examiner

Schlumberger—Trident—Extreme conditions motor lead extension <https://www.slb.com/products-and-services/innovating-in-oil-and-gas/completions/artificial-lift/power-systems-and-cables/trident-motor-lead-extension> (Year: 2023). cited by examiner

International Search Report and Written Opinion in corresponding PCT/US2024/027269 issued Aug. 19, 2024. cited by applicant

Primary Examiner: Carroll; David

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) The present application claims the benefit of U.S. Provisional Application No. 63/499,320, filed May 1, 2023, the entirety of which is incorporated by reference herein and should be considered part of this specification.

BACKGROUND

(1) Various types of artificial lift equipment and methods are available, for example, electric submersible pumps (ESPs). An ESP includes multiple centrifugal pump stages mounted in series, each stage including a rotating impeller and a stationary diffuser mounted on a shaft, which is coupled to a motor. In use, the motor rotates the shaft, which in turn rotates the impellers within the diffusers. Well fluid flows into the lowest stage and passes through the first impeller, which centrifuges the fluid radially outward such that the fluid gains energy in the form of velocity. Upon exiting the impeller, the fluid flows into the associated diffuser, where fluid velocity is converted to pressure. As the fluid moves through the pump stages, the fluid incrementally gains pressure until the fluid has sufficient energy to travel to the well surface.

Description

BRIEF DESCRIPTION OF THE FIGURES

- (1) Certain embodiments, features, aspects, and advantages of the disclosure will hereafter be described with reference to the accompanying drawings, wherein like reference numerals denote like elements. It is emphasized that, in accordance with standard practice in the industry, various features are not drawn to scale. In fact, the dimensions of various features may be arbitrarily increased or reduced for clarity of discussion. It should be understood that the accompanying figures illustrate the various implementations described herein and are not meant to limit the scope of various technologies described herein.
- (2) FIG. 1 is a schematic view of an electric submersible pump (ESP) system according to an embodiment of the disclosure;
- (3) FIG. 2 is a cross-sectional view of the pump the ESP of FIG. 1;
- (4) FIG. 3 is a schematic view of a motor lead extension (MLE) according to an embodiment of the disclosure; and
- (5) FIG. 4 is another schematic view of an MLE according to an embodiment of the disclosure.

DETAILED DESCRIPTION

(6) In the following description, numerous details are set forth to provide an understanding of some embodiments of the present disclosure. It is to be understood that the following disclosure provides many different embodiments, or examples, for implementing different features of various embodiments. Specific examples of components and arrangements are described below to simplify the disclosure. These are, of course, merely examples and are not intended to be limiting. In addition, the disclosure may repeat reference numerals and/or letters in the various examples. This repetition is for the purpose of simplicity and clarity and does not in itself dictate a relationship between the various embodiments and/or configurations discussed. However, it will be understood by those of ordinary skill in the art that the system and/or methodology may be practiced without these details and that numerous variations or modifications from the described embodiments are possible. This description is not to be taken in a limiting sense, but rather made merely for the purpose of describing general principles of the implementations. The scope of the described implementations should be ascertained with reference to the issued claims.

(7) As used herein, the terms “connect”, “connection”, “connected”, “in connection with”, and “connecting” are used to mean “in direct connection with” or “in connection with via one or more elements”; and the term “set” is used to mean “one element” or “more than one element”. Further, the terms “couple”, “coupling”, “coupled”, “coupled together”, and “coupled with” are used to mean “directly coupled together” or “coupled together via one or more elements”. As used herein, the terms “up” and “down”; “upper” and “lower”; “top” and “bottom”; and other like terms indicating relative positions to a given point or element are utilized to more clearly describe some elements. Commonly, these terms relate to a reference point at the surface from which drilling operations are initiated as being the top point and the total depth being the lowest point, wherein the well (e.g., wellbore, borehole) is vertical, horizontal or slanted relative to the surface.

(8) Various types of artificial lift equipment and methods are available, for example, electric submersible pumps (ESP). As shown in the example embodiment of FIG. 1, an ESP **110** typically includes a motor **116**, a protector **115**, a pump **112**, a pump intake **114**, and one or more cables **111**, which can include an electric power cable. The motor **116** can be powered and controlled by a surface power supply and controller, respectively, via the cables **111**. In one or more embodiments, the power cables **111** are coupled to a pothead housing (e.g., pothead) via a motor lead extension (MLE) **118**, as described in more detail below, which, in turn, is coupled to the motor **116**. In some configurations, the ESP **110** also includes gas handling features **113** and/or one or more sensors **117** (e.g., for temperature, pressure, current leakage, vibration, etc.). As shown, the well **100** may

include one or more well sensors **120**.

(9) The pump **112** includes multiple centrifugal pump stages mounted in series within a housing **230**, as shown in FIG. 2. Each stage includes a rotating impeller **210** and a stationary diffuser **220**. One or more spacers **204** can be disposed axially between sequential impellers **210**. A shaft **202** extends through the pump **112** (e.g., through central hubs or bores or the impellers **210** and diffusers **220**) and is operatively coupled to the motor **116**. The shaft **202** can be coupled to the protector **115** (e.g., a shaft of the protector), which in turn can be coupled to the motor **116** (e.g., a shaft of the motor). The impellers **210** are rotationally coupled, e.g., keyed, to the shaft **202**. The diffusers **220** are coupled, e.g., rotationally fixed, to the housing **230**. In use, the motor **116** causes rotation of the shaft **202** (for example, by rotating the protector **115** shaft, which rotates the pump shaft **202**), which in turn rotates the impellers **210** relative to and within the stationary diffusers **220**. The pump **112** may comprise an endplay gap **250**, a bearing sleeve or shaft sleeve **252**, a radial bearing or bushing **254**, a lock ring and/or upthrust ring **256**, a compliant mount elastomer ring or o-ring **258**, and a bearing housing diffuser **260**.

(10) In use, well fluid flows into the first (lowest) stage of the ESP **110** and passes through an impeller **210**, which centrifuges the fluid radially outward such that the fluid gains energy in the form of velocity. Upon exiting the impeller **210**, the fluid makes a sharp turn to enter a diffuser **220**, where the fluid's velocity is converted to pressure. The fluid then enters the next impeller **210** and diffuser **220** stage to repeat the process. As the fluid passes through the pump stages, the fluid incrementally gains pressure until the fluid has sufficient energy to travel to the well surface.

(11) Turning now to FIG. 3, FIG. 3 is a motor lead extension (MLE) **118** for High Pressure applications. The MLE **118** may comprise an O-ring **302**, pothead housing **304** (e.g., pothead), backup ring **306**, solder joint **308**, insulation (e.g., PEEK) **310**, lead portion **312**, copper portion **314** (e.g., cable or cable portion), and a location of oil **316** within pothead housing **304**. A pressure differential can break the barrier in an MLE **118** and cause it to fail. Partial discharge failure is a common failure mode for devices which are subject to high electrical voltage. This application includes the introduction of a dielectric oil that reduces the likelihood of PD (Partial Discharge) in the pothead housing **304** as well as providing the needed additional support to the Solder Joint required due to the high-pressure differential across the joint. Before soldering the lead and pothead housing **304** together, a seal will be created behind (e.g., on the backside of) the pothead housing **304**, to contain the oil. After the injection of oil using a special tool, the oil will reside in the clearance gap between the insulation and the pothead housing **304** and between the backup ring and the solder joint. An area of importance is shown by the dotted-oval area in FIG. 3.

(12) FIG. 4 shows another motor lead extension (MLE) **118** for High Pressure applications. The MLE **118** may comprise O rings **406**, **422**, elements **412**, **424**, **416**, **410**, **414**, **418**, **420**, **402**, **408**, **404**, and location of oil within pothead housing **426** (e.g., pothead). The oil is held in place by the seal on the top of the insulation **310** and below the flared end **318** of the lead barrier **312** (also known as lead layer **312**). This flared area will then go around the outside of the pothead housing tail **320** and will be soldered to complete the metal-to-metal seal. The seal and the internal O-ring contain the oil and prevent it from penetrating throughout the length of the lead layer. Once the MLE **118** experiences increased pressure the compression will start to compress the lead layer and provide another barrier to stop the oil from penetrating, as shown in FIG. 4.

(13) Language of degree used herein, such as the terms “approximately,” “about,” “generally,” and “substantially” as used herein represent a value, amount, or characteristic close to the stated value, amount, or characteristic that still performs a desired function or achieves a desired result. For example, the terms “approximately,” “about,” “generally,” and “substantially” may refer to an amount that is within less than 10% of, within less than 5% of, within less than 1% of, within less than 0.1% of, and/or within less than 0.01% of the stated amount. As another example, in certain embodiments, the terms “generally parallel” and “substantially parallel” or “generally perpendicular” and “substantially perpendicular” refer to a value, amount, or characteristic that

departs from exactly parallel or perpendicular, respectively, by less than or equal to 15 degrees, 10 degrees, 5 degrees, 3 degrees, 1 degree, or 0.1 degree.

(14) Although a few embodiments of the disclosure have been described in detail above, those of ordinary skill in the art will readily appreciate that many modifications are possible without materially departing from the teachings of this disclosure. Accordingly, such modifications are intended to be included within the scope of this disclosure as defined in the claims. It is also contemplated that various combinations or sub-combinations of the specific features and aspects of the embodiments described may be made and still fall within the scope of the disclosure. It should be understood that various features and aspects of the disclosed embodiments can be combined with, or substituted for, one another in order to form varying modes of the embodiments of the disclosure. Thus, it is intended that the scope of the disclosure herein should not be limited by the particular embodiments described above.

Claims

1. An electric submersible pump (ESP) system, the ESP system comprising: a motor; and a motor lead extension (MLE) coupled to the motor, wherein the MLE comprises a pothead, a cable configured to provide power to the motor, and a dielectric oil that reduces a likelihood of a partial discharge (PD) in the pothead, wherein the dielectric oil is disposed in a clearance gap within the pothead.
2. The ESP system of claim 1, wherein the dielectric oil is configured to provide support to a solder joint.
3. The ESP system of claim 1, comprising a seal located behind the pothead, the seal at least partially containing the dielectric oil.
4. The ESP system of claim 1, comprising insulation disposed about the cable within the pothead, wherein the dielectric oil is disposed in the clearance gap radially between the pothead and the insulation.
5. The ESP system of claim 1, wherein the MLE is configured to house the dielectric oil in the clearance gap axially between a backup ring and a solder joint.
6. The ESP system of claim 1, comprising a seal, an insulation, and a flared end of a lead barrier, wherein the seal is configured to hold the dielectric oil in place on a top of the insulation and below the flared end of the lead barrier.
7. The ESP system of claim 1, wherein a flared end of a lead barrier is positioned radially on top of a pothead housing tail of the pothead housing and affixed thereto in order to create a metal-to-metal seal.
8. The ESP system of claim 1, comprising a seal and an internal O-ring, wherein the seal and the internal O-ring are configured to house the dielectric oil and prevent the dielectric oil from penetrating throughout a length of a lead layer.
9. The ESP system of claim 1, wherein the MLE is configured to, when the MLE experiences increased pressure, compress a lead layer and provide a barrier to stop the dielectric oil from discharging.
10. A method comprising: disposing an electric submersible pump (ESP) system within a wellbore; and operating the ESP system via power provided to a motor of the ESP system via a motor lead extension (MLE) coupled to the motor, wherein the MLE comprises a pothead, a cable configured to provide the power to the motor, and a dielectric oil that reduces a likelihood of a partial discharge (PD) in the pothead, wherein the dielectric oil is disposed in a clearance gap within the pothead.
11. The method of claim 10, comprising providing support to a solder joint via the dielectric oil.
12. The method of claim 10, comprising containing the dielectric oil via a seal located behind the pothead.

13. The method of claim 10, comprising housing an insulation disposed about the cable within the pothead, wherein the dielectric oil is disposed in the clearance gap radially between the pothead and the insulation.
 14. The method of claim 10, comprising housing, by the MLE, the dielectric oil in the clearance gap axially between a backup ring and a solder joint.
 15. The method of claim 10, comprising holding, by a seal, the dielectric oil in place on a top of an insulation and below a flared end of a lead barrier.
 16. The method of claim 10, comprising creating a metal-to-metal seal via a flared end of a lead barrier that is positioned around an outside of a pothead housing tail and affixed thereto.
 17. The method of claim 10, comprising housing, by a seal and an internal O-ring, the dielectric oil and preventing the dielectric oil from penetrating throughout a length of a lead layer.
 18. The method of claim 10, comprising compressing, by the MLE, when the MLE experiences increased pressure, a lead layer and providing a barrier to stop the dielectric oil from discharging.
 19. The ESP system of claim 1, wherein the MLE is directly coupled to the motor.
-