

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12398820
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Ewers; Benny

Insert arrangement and a method of assembling a damping arrangement

Abstract

The present application relates to an insert arrangement for engaging with a solenoid arrangement and for closing a valve cavity of a damping arrangement. The insert arrangement comprises: an armature member adapted in shape and size to provide a base portion and an axial portion extending out of the base portion in a direction parallel to a first axis, a casing member adapted to extend around the axial portion to define a receiving space between the axial portion and the casing member. The solenoid arrangement is at least partly arrangeable in said receiving space, and the casing member is further adapted with a magnetically conducting material for substantially closing a magnetic field generated by the solenoid arrangement. The insert arrangement further comprises fixating means for fixating the armature member to the damping arrangement, wherein said fixating means are arranged on the casing member.

Inventors:	Ewers; Benny (Upplands Väsby, SE)
Applicant:	Advanced Suspension Technology LLC (Northville, MI)
Family ID:	1000008782007
Assignee:	Advanced Suspension Technology LLC (Northville, MI)
Appl. No.:	18/370601
Filed:	September 20, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240102576 A1	Mar. 28, 2024

Foreign Application Priority Data

EP	22197427	Sep. 23, 2022
----	----------	---------------

Publication Classification

Int. Cl.: F16K27/02 (20060101); F16F15/03 (20060101); F16K31/06 (20060101)

U.S. Cl.:

CPC F16K27/029 (20130101); F16F15/03 (20130101); F16K31/0655 (20130101);
F16F2222/06 (20130101)

Field of Classification Search

USPC: 251/129.01; 251/129.15; 251/366; 188/322.2

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4809749	12/1988	Ichihashi	N/A	N/A
5467851	12/1994	Handke	267/179	F16F 9/465
5651433	12/1996	Wirth	188/266.6	F16F 9/325
6000508	12/1998	Forster	188/299.1	F16F 9/46
7604101	12/2008	Park	188/315	F16F 9/465
8181757	12/2011	Heyn	188/266.2	F16F 9/46
8220604	12/2011	Jee	188/266.6	F16F 9/325
8469162	12/2012	Nishimura	188/266.2	F16F 9/325
8770363	12/2013	Sonsterod	251/337	F16F 9/34
2016/0195152	12/2015	Mori et al.	N/A	N/A
2016/0223043	12/2015	Hagidaira et al.	N/A	N/A
2018/0266514	12/2017	Mori	N/A	N/A
2021/0033163	12/2020	Nakano et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
112020006079	12/2021	DE	N/A
2613798	12/1987	FR	N/A

Primary Examiner: Jellett; Matthew W

Attorney, Agent or Firm: Harness, Dickey & Pierce, P.L.C.

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION

(1) This application claims the benefit and priority of European application number 22197427.2 filed Sep. 23, 2022. The entire disclosure of the above application is incorporated herein by reference.

FIELD

(2) The present disclosure relates to an insert arrangement for engaging with a solenoid

arrangement and for closing a valve cavity of a damping arrangement, a damping arrangement comprising such an insert arrangement and a method of assembling a damping arrangement.

BACKGROUND

(3) Damping characteristics of damping arrangements can be actively controlled by means of a solenoid arrangement. A solenoid arrangement is typically adapted to be arranged into an armature member to be inserted into an end of a valve cavity. Typically, the armature member is fixated to the valve cavity using threads that engage with corresponding threads located on an inner wall of the valve cavity. To minimize magnetic losses, it is preferable to enclose the magnetic field by means of a casing member comprising a magnetically conducting material.

(4) There are generally two solutions of incorporating such a casing member in a damping arrangement.

(5) In one known solution, the casing member can be incorporated in the wall of a valve cavity of the damping arrangement. This solution limits materials that can be used in the wall of the valve cavity, for instance it cannot be made in aluminum. Moreover, this solution also requires very tight air gap tolerances between armature and cavity wall so as to hinder hydraulic fluid leakage.

(6) Alternatively, the casing member may be integrated in a base portion of the armature member. This solution however requires the armature member to be manufactured in a plurality of pieces to be assembled together after manufacturing, thereby increasing cost of manufacturing and assembly. Moreover, this solution requires that there are very tight air gap tolerances between casing member and cavity wall so as to hinder hydraulic fluid leakage.

(7) There is thus a need for an improved solution of how to incorporate a casing member in a damping arrangement that is both cost effective and easy to assemble.

SUMMARY

(8) It is an object of the present disclosure to provide an improved solution that alleviates the mentioned drawbacks with present solutions. Furthermore, it is an object to provide an insert arrangement comprising a casing member and armature member for arrangement to a damping arrangement, which insert arrangement is easy to assemble in place. An additional object is to provide an insert arrangement can be manufactured cost effectively. A further object is to provide a method of arranging an insert arrangement to a damping arrangement.

(9) According to a first aspect of the disclosure, an insert arrangement for engaging with a solenoid arrangement and for closing a valve cavity of a damping arrangement is provided. The insert arrangement comprises: an armature member adapted in shape and size to provide a base portion and an axial portion extending out of the base portion in a direction parallel to a first axis. The base portion is adapted to provide a mating surface for mating with an inner wall of the valve cavity when the insert arrangement is arranged to close the valve cavity. The axial portion is adapted to define an inner space for receiving and allowing an actuation member to be axially moveable therein to interact with a valve arrangement of the damping arrangement under influence of a magnetic field generated by the solenoid arrangement. The insert arrangement further comprises a casing member adapted to extend around the axial portion to define a receiving space between the axial portion and the casing member, and the solenoid arrangement is at least partly arrangeable in said receiving space. The casing member is further adapted with a magnetically conducting material for substantially closing a magnetic field generated by the solenoid arrangement. The insert arrangement further comprises fixating means for fixating the armature member to the damping arrangement. Said fixating means are arranged on the casing member. Said mating surface is axially located between an insert end of the insert arrangement and said fixating means.

(10) A first advantage is a facilitated assembly of the insert arrangement in a damping arrangement. Conventionally, fixating means such as threads are located on a base portion of the armature member. By rather arranging them on the casing member, which is arranged to engage with the armature member, the insert arrangement is securable by operation of the casing member. This allows direct line of sight of verifying if the insert arrangement is correctly placed before securing

it to the damping arrangement. Another advantage is that, by removing the fixation means from the armature member, a relatively larger mating surface for mating with the inner wall of the valve cavity is provided. This mating surface may for instance be used for providing a groove for holding a sealing member to seal the valve cavity. Another advantage of providing the threads on a casing member rather than on the base portion of the armature member is that the armature member has simpler design and may thus be formed as a single part.

(11) For the purpose of clarifying some terms and wordings used herein, some clarifications are provided in the following.

(12) In the context of this application, by the term “part”, it may be meant a separate element. For example, a first feature and a second feature, when referenced as different parts, may be understood as being structurally separate features, either separated in space or arranged together with a distinct boundary therebetween. By the term “portion”, it may be meant an area or a region of an element. For example, a first feature and a second feature, when referenced as different portions, may be understood as being different and optionally non-overlapping regions of a single element. By the phrase “at least partly” or “at least partially”, it may refer to one or more parts and/or one or more portion of an element. For example, an element at least partly moveable may be understood to have one or more parts or one or more portions that is moveable relative to some other referenced feature.

(13) By fluidly arranged, coupled, or connected or the like, it may be meant that a first feature and a second feature are directly or indirectly connected so as to establish a fluid flow path between the first feature and the second feature, and not that a first feature is floating relative a second feature.

(14) By restricting, it may be meant an act of adjusting the dimensions of a fluid flow opening. The dimensions of the fluid flow opening may be increased or decreased, thereby impacting the hydraulic fluid flow flowing through the fluid flow opening. A restriction may therefore be understood as a dimension-adjustable fluid flow opening. A restriction may be an adjustable space between two or more elements which can be mutually moved relative each other to adjust said adjustable space.

(15) Additional optional features of the disclosure according to the first aspect is detailed in the following.

(16) The insert arrangement is adapted to be at least partly inserted in a valve cavity. The valve cavity may be formed by a damping arrangement, or the like. The valve cavity may be defined by a valve cavity wall. The valve cavity wall may be a part or portion of the damping arrangement. The valve cavity wall may be a part or portion of a cylinder member. The cylinder member may be a part or portion of the damping arrangement. The cylinder member may define a center axis. The valve cavity wall of the cylinder member may be substantially cylindrical about the center axis. The cylinder member may define an insert opening at one axial end. The insert arrangement may be adapted to be inserted at least partly or fully into the valve cavity via said insert opening. The valve cavity wall may define a first inner wall portion axially displaced from a second inner wall portion. The first inner wall portion and the second inner wall portion may be radially offset each other from a center axis. The valve cavity may be fluidly connected to a working chamber of a damping arrangement, such as a shock absorber.

(17) The armature member is adapted for engaging with the solenoid arrangement. The armature member may be adapted in shape and size to provide a base portion. The armature member may be adapted in shape and size to provide an axial portion extending out of the base portion. The axial portion may extend out of the base portion in a direction parallel to a first axis. The first axis may be parallel and optionally concentric with aforementioned centre axis of the valve cavity. The base portion may comprise a substantially cylindrical shape. The axial portion may comprise a substantially cylindrical shape. The axial portion may be concentric with the base portion.

(18) The base portion may be adapted to provide a mating surface for mating with an inner wall of the valve cavity when the insert arrangement is arranged to close the valve cavity. By mating

surface, it may be meant a surface adapted to engage with an inner wall surface so that the gap there between is less than a predetermined gap distance. The predetermined gap distance may be less than 1 mm, for instance be in the interval of 0.1 mm-0.2 mm, 0.2 mm-0.3 mm, 0.3 mm-0.4 mm, 0.4 mm-0.5 mm, 0.5 mm-0.6 mm, 0.6 mm-0.7 mm, 0.7 mm-0.8 mm, 0.8 mm-0.9 mm, or 0.9 mm-1.0 mm, or in an interval formed from a combination of the above intervals. The mating surface may extend in a direction parallel to a centre axis of the armature member. The mating surface may extend partly or fully in a circumferential direction of the base portion. In the case of the base portion having a substantially cylindrical shape, the mating surface may extend in a circumferential direction of the base portion at a constant radius.

(19) The insert arrangement is adapted for closing a valve cavity of a damping arrangement. The damping arrangement may be a damping arrangement for controlling pressure of a hydraulic fluid for flowing in a cylinder of a damping arrangement, such as a shock absorber.

(20) The insert arrangement comprises a casing member. The casing member may be adapted for engaging with or connecting to the armature member. The casing member may be adapted to be a separate member from the armature member. The casing member may be adapted to have a generally cylindrical shape with a first axial end for engaging with the armature member and a second axial end for engaging with the solenoid arrangement. The casing member may be adapted with a receiving portion arranged on an inner side of the casing member defining a through hole through which the axial portion of the armature member may be inserted.

(21) According to one embodiment, the insert arrangement is further adapted with a groove in the mating surface for receiving a sealing member therein. The sealing member is adapted to hinder hydraulic fluid from leaking out of the valve cavity when the insert arrangement is arranged to close the valve cavity. By providing a sealing member as such, gap tolerances between the mating surface and inner wall of the valve cavity may be less strict. By hinder hydraulic fluid from leaking, it may mean that it reduces the leakage or substantially stop it fully. Over time, the sealing member may degrade, thereby reducing its ability to hinder leakage.

(22) According to one embodiment, the base portion and the axial portion of the armature member are formed as a single part. By this, the armature member may be more easily manufactured which may reduce cost. Further, no additional assembly is required of the armature member.

(23) According to one embodiment, the casing member is a separate part from the armature member. By this, the casing member may be enabled to move relative the armature member in order to secure the insert arrangement to a damper arrangement.

(24) According to one embodiment, the fixating means comprise threads adapted to engage with corresponding threads arranged on the inner wall of the valve cavity. By this, the casing member is capable of securing the insert arrangement to a damping arrangement by means of rotating the casing member about a center axis of the insert arrangement. Fixing and securing may be used interchangeably in this application text. The fixating means may be referenced as securing means.

(25) According to one embodiment, the insert arrangement further comprises a sealing member adapted to be arranged in the groove of the mating surface and to hinder hydraulic fluid from leaking out of the valve cavity when the insert arrangement is arranged to close the valve cavity. By incorporating the sealing member as well, the insert arrangement may be provided as a pre-assembled kit of parts for insertion into a valve cavity of a damping arrangement.

(26) According to one embodiment, the casing member and the base portion of the armature member are adapted with substantially cylindrical geometry, and the casing member and the base portion are characterized by respective outer diameters wherein the outer diameter of the casing member is larger than the outer diameter of the base member.

(27) According to one embodiment, the base portion and the axial portion are concentric. By this, the casing member may be arranged concentrically about a center axis, thereby facilitating it to rotatably secure the insert arrangement to a damping arrangement by means of threads.

(28) According to one embodiment, the axial portion is adapted with a latch recess for receiving a

latch member of the solenoid member. By this, the solenoid arrangement may be secured in place to the insert arrangement. Alternatively, or in combination, the solenoid arrangement may be adapted to be secured to the insert arrangement by other fixation means such as threads.

(29) According to one embodiment, the casing member is adapted to engage with the base portion of the armature member in a press fit manner.

(30) According to a second aspect of the disclosure, a damping arrangement is provided. The damping arrangement comprises: a valve cavity, an insert arrangement according to the first aspect or any embodiments thereof, which insert arrangement is arranged to close the valve cavity; a solenoid arrangement arranged at least partly in the receiving space of the insert arrangement; a valve arrangement, and an actuation member axially moveable in the inner space of the axial portion of the armature member to interact with the valve arrangement under influence of a magnetic field generated by the solenoid arrangement. The damping arrangement may comprise a solenoid arrangement arranged to engage with the insert arrangement.

(31) According to one embodiment, the damping arrangement further comprises a sealing member arranged in the groove located in the mating surface of the base portion of the armature member for hindering hydraulic fluid from leaking out of the valve cavity when the insert arrangement is arranged to close the valve cavity.

(32) According to a third aspect, a method of assembling a damping arrangement is provided. The method comprises the steps of: providing a damping arrangement adapted with a valve cavity; providing an insert arrangement comprising an armature member and a valve arrangement; inserting the insert arrangement into the valve cavity such that a mating surface of a base portion of the armature member mates with an inner wall of the valve cavity, thereby closing the valve cavity in a closing position; fixating the insert arrangement in the closing position by means of fixating means provided on a casing member adapted for engaging with threads provided on an inner wall of the valve cavity; arranging a solenoid arrangement in a receiving space formed between the casing member and an axial portion extending out of the base portion of the armature member.

(33) According to one embodiment, the method further comprises the step of providing, prior to the step of inserting the insert arrangement into the valve cavity, a sealing member in a groove located in the mating surface.

(34) According to one embodiment, the method further comprises the step of providing, prior to inserting the insert arrangement in the valve cavity, an assembly element into the valve cavity to cover said threads in the valve cavity and removing the assembly element before fixating the insert arrangement in the closing position by means of said fixating means. The assembly element may protect the threads of the insert arrangement or the damping arrangement during assembly. The assembly element may be a protective cover which may have deformable characteristics. By this, it may be deformed to conform with the geometry of the valve cavity and/or the insert arrangement. The assembly element may be adapted to be removed after the insert arrangement has been inserted but prior to rotating the casing member to fixate or secure the insert arrangement via said threads.

(35) The disclosure is defined by the appended independent claims, with embodiments being set forth in the appended dependent claims, in the following description and in the drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The disclosure will in the following be described in more detail with reference to the enclosed drawings, wherein:

(2) FIG. 1 shows a cross sectional side view of the insert arrangement according to one embodiment of the disclosure;

(3) FIG. 2 shows a cross sectional exploded view of the insert arrangement according to one

embodiment of the disclosure;

(4) FIG. 3 shows a cross sectional side view of the insert arrangement according to one embodiment of the disclosure;

(5) FIG. 4 shows a cross sectional side view of the insert arrangement according to one embodiment of the disclosure;

(6) FIG. 5 shows a cross sectional side view of the insert arrangement according to one embodiment of the disclosure;

(7) FIG. 6 shows a shock absorber according to one embodiment of the disclosure;

(8) FIG. 7 shows a shock absorber according to one embodiment of the disclosure;

(9) FIG. 8 shows a flow chart of a method of assembling the insert arrangement according to one embodiment of the disclosure.

DESCRIPTION

(10) The present disclosure will be described more fully hereinafter with reference to the accompanying drawings, in which preferred embodiments of the disclosure are shown. This disclosure may, however, be embodied in many different forms and should not be construed as limited to the embodiments set forth herein; rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the disclosure to those skilled in the art. In the drawings, like numbers refer to like elements.

(11) In the drawings and specification, there have been disclosed preferred embodiments and examples of the disclosure and, although specific terms are employed, they are used in a generic and descriptive sense only and not for the purpose of limitation, the scope of the disclosure being set forth in the following claims.

(12) According to a first aspect, the disclosure relates to an insert arrangement **1** adapted for engaging with a solenoid arrangement **50** and for closing a valve cavity **60** of a damping arrangement. Such an insert arrangement **1** is illustrated in e.g., FIG. 1 which shows a cross sectional side view of the insert arrangement **1** according to one embodiment of the disclosure. The insert arrangement **1** may comprise a general elongated shape extending in a direction parallel to a first axis A. The first axis A may be a center axis A. A first axial end of the insert arrangement **1** can be inserted into a damping arrangement for closing a valve cavity **60** thereof. Moreover, the opposite axial end of the insert arrangement **1** may engage with a solenoid arrangement **50** when arranged to engage with the insert arrangement **1**.

(13) Generally, a solenoid arrangement **50** comprises a solenoid housing **51** and means **52** for generating a magnetic field, wherein said solenoid housing **51** is housing said means **52**. Such means **52** may for example be one or more coils for conducting an electric current to generate said magnetic field. The solenoid arrangement **50** may comprise a first portion **53** in which the means **52** for generating a magnetic field are arranged. The first portion **53** may extend from an inner surface of the solenoid housing **51** in a direction substantially parallel to an axis. Said first portion **53** may be a portion of the housing **51**. Said axis may be a center axis which, when the solenoid arrangement **50** is arranged to engage with the insert arrangement **1**, is parallel to a center axis A of the insert arrangement **1**. The first portion **53** may be adapted in shape and size to define a central opening for receiving a portion of the insert arrangement **1** when the solenoid arrangement **50** is arranged to engage with the insert arrangement **1**. The solenoid arrangement **50** may further comprise a second portion **54** adapted in shape and size to engage with the damping arrangement so that the insert arrangement may close said valve cavity **60**. Said second portion **54** may be a portion of the solenoid housing **51**. Either or both of the first portion **53** and the second portion **54** may extend in a circumferential direction about the center axis. The second portion **54** may be located at a greater radial distance than the first portion **53**. The first portion **53** and the second portion **54** may be adapted in shape and size to define a gap between them. The gap may allow a part or portion of the insert arrangement **1** to be received, such as a casing member **10**.

(14) The insert arrangement **1** is adapted for closing a valve cavity **60** of a damping arrangement.

The insert arrangement **1** comprises an armature member **20** adapted in shape and size to provide a base portion **21** and an axial portion **22** extending out of the base portion in a direction parallel to a first axis A. The first axis A may be a center axis A of the insert arrangement **1**. The base portion **21** is adapted to provide a mating surface **211** for mating with an inner wall of the valve cavity **60** when the insert arrangement **1** is arranged to close the valve cavity. By mating, it may be meant that a gap between the mating surface and the wall of the valve cavity is within a predetermined distance tolerance. The predetermined distance tolerance may be in the interval of 0.1-1 mm. The mating surface **211** may extend in a circumferential direction about the first axis A. The mating surface **211** may have a shape corresponding to a shape of the wall of the valve cavity **60**. As an example, the wall of the valve cavity **60** may have a cylindrical shape in which case the mating surface **211** may have a cylindrical shape also.

(15) The axial portion **22** is adapted to define an inner space for receiving and allowing an actuation member **70** to be axially moveable therein to interact with a valve arrangement **40** of the damping arrangement under influence of a magnetic field generated by the solenoid arrangement **50**. One or more guiding portions may be adapted to be arranged in said inner space to guide the actuation member **70** to move therein between a retracted and extended position. The actuation member **70** may in the extended position engage with a first valve member **41** of a valve arrangement **40**. The actuation member **70** may be displaced from the first valve member **41** in the retracted position. The actuation member **70** may be moveable between an extended position and a retracted position in response to the magnetic field generated by the solenoid arrangement **50**.

(16) The valve arrangement **40** may comprise a first valve member **41** adapted to be engageable with a first valve seat member **42**. The first valve member **41** may be the first valve member **41** referenced above. The first valve member **41** may be adapted to be displaceable in a direction parallel to a center axis of the insert arrangement **1**. The actuation member **70** may be displaceable to come in contact with the first valve member **41** to engage with the first valve seat **42**. The first valve member **41** may be a spring shim comprising a first pair of spring shim portions axially moveable relative each other. The first valve member **41** may be at least locally attached between the first valve seat **42** and the armature member **20**. The spring shim may comprise a second pair of spring shim portions axially moveable relative each other. The spring shim may comprise three or more spring shim portions axially moveable relative each other. The first valve seat member **42** may comprise a plurality of valve seat surfaces axially displaced relative each other to define a respective valve seat portion. Each spring shim portion may be adapted to abut with a respective valve seat portion.

(17) As shown in e.g., FIG. 2, the first valve seat member **42** may define an inner space. The first valve seat member **42** may comprise an opening leading into the inner space. The valve arrangement **40** may comprise a second valve member **43** adapted to be arranged to be moveable in said inner space between a first position and a second position. The valve arrangement **40** may comprise a second valve seat member **44**. The second valve member **43** may in the second position be seated on the second valve seat member **44** when in the second position and be displaced therefrom when in the first position. The second valve member **43** may be adapted to move axially between the first position and the second position. The valve arrangement **40** may comprise a biasing member **45** for biasing the second valve member **42** to move towards the second valve seat member **44**. The biasing member **45** may be a helical spring with one axial end being arranged in contact with the second valve seat member **43** while the other axial end of the helical spring is arranged in contact with the first valve seat member **42**. The second valve member **43** may comprise a through-hole connecting to opposite surfaces of the second valve member **43**. The through-hole may enable hydraulic fluid flow through the second valve member **43**. The second valve seat member **44** may comprise a through-hole connecting two opposite sides of the second valve seat member **44**.

(18) As shown in e.g., FIG. 1, the insert arrangement **1** further comprises a casing member **10**

adapted to extend around the axial portion **22** to define a receiving space between the axial portion **22** and the casing member **10**. The casing member **10** and the armature member **20** may be separate parts and can be assembled by inserting the armature member **20** into the casing member **10**.

(19) The casing member **10** may comprise a generally cylindrical shape. The casing member **10** may define an inner space. A portion of the inner space may constitute the receiving space when the armature member is arranged to extend into the casing member **10**. The solenoid arrangement **50** is adapted to be at least partly arrangeable in said receiving space when arranged to the insert arrangement **1**.

(20) The casing member **10** is further adapted with a magnetically conducting material for substantially closing a magnetic field generated by the solenoid arrangement **50**. Such magnetic materials may include any applicable metallic type material and nonmetallic type material.

(21) The casing member **10** may have a first axial opening and a second axial opening into the inner space. The casing member **10** may comprise an inner receiving portion adapted in shape and size to receive the armature member **20** when inserted into the casing member **10**. The inner receiving portion may be adapted with a planar surface with a surface normal parallel to a center axis of the insert arrangement **1**. The inner receiving portion may define a through hole with a side wall adapted in shape and size to mate with a corresponding surface of the armature member **20**. The receiving space of the insert arrangement **1** may be adapted in size and shape for receiving the solenoid arrangement **50**, and preferably in particular the first portion wherein the means for generating magnetic field is arranged. The axial portion **22** of the armature member **20** may be adapted to extend in the inner space defined by the first portion **53** of the solenoid arrangement **50**. The axial portion **22** and the first portion **53** of the solenoid arrangement **50** may engage in a close fit manner.

(22) A sealing member **55** may be provided to seal between the solenoid arrangement **50** and the casing member **10** of the insert arrangement **1** or to seal between the solenoid arrangement **50** and the cavity wall of the damping arrangement. The sealing member **55** may be arranged at an outer side of the casing member **10** after assembly.

(23) The armature member **20** is adapted to be secured or securable to the valve cavity wall of the damping arrangement when closing the insert arrangement **1** is arranged to close the valve cavity **60**. For this, the insert arrangement **1** comprises fixating means **11** for fixating the armature member **20** to the damping arrangement. The fixating means **11** may be arranged on the casing member **10**. Thus, the armature member **20** may be secured to the valve cavity wall via the casing member **10** to which it is coupled, which casing member **10** is secured to the valve cavity wall via said fixating means of the casing member **10**. Preferably, the fixating means **11** include threads arranged on an outer surface of the casing member **10** which are adapted to engage with corresponding threads arranged at an inner wall of the valve cavity **60**. The mating surface **211** is axially located between an insert end of the insert arrangement **1** and said fixating means **11**.

(24) The advantage of the fixating the armature member **20** to the damping arrangement by means of the casing member **10** in this fashion is that it allows the armature member **20** to be manufactured in one piece which reduces manufacturing complexity and thereby associated costs. Moreover, it also provides the mating surface axially inward from the fixating means. This may enable a tighter mating between the mating surface **211** and the valve cavity wall. It may also enable less strict tolerance between the mating surface **211** and the valve cavity wall, as a sealing member **30** may be arranged in a groove **212** to hinder hydraulic fluid leakage. An additional advantage is that it may facilitate assembly since the casing member **10** is more accessible during assembly. Conventionally, the fixating means, such as threads, are arranged at the base portion **21** of the armature member **20** and needs to be carefully mounted in place without any direct line of sight. The present disclosure thus provides a better solution for securing the insert arrangement **1** to a damping arrangement.

(25) As indicated in e.g., FIGS. **1** and **2**, the insert arrangement **1** may be further adapted with a

groove **212** in the mating surface **211** for receiving a sealing member **30** therein. The sealing member **30** is adapted to hinder hydraulic fluid from leaking out of the valve cavity **60** when the insert arrangement **1** is arranged to close the valve cavity. The groove **212** may extend in a circumferential direction along the mating surface **211** around the base portion **21** of the armature member **20**. The base portion **21** may comprise a curved portion between the mating surface **211** and a bottom side of the base portion **21**. By this, the armature member **20** may be more easily guided into the valve cavity **60** of the damping arrangement.

(26) According to one embodiment, the base portion **21** and the axial portion **22** are formed as a single part. The axial portion **22** and the base portion **21** may respectively comprise generally cylindrical shapes. The axial portion **22** and the base portion **21** may be arranged concentrically.

(27) Moreover, according to one embodiment, the casing member **10** is a separate part from the armature member **20**. The casing member **10** may be made from a magnetically conducting material. The armature member **20** may be made from a material different from the casing member **10**.

(28) The fixating means **11** comprise threads adapted to engage with corresponding threads arranged on the inner wall of the valve cavity **60**.

(29) The insert arrangement **1** further comprises a sealing member **30** adapted to be arranged in the groove **212** and to hinder hydraulic fluid from leaking out of the valve cavity **60** when the insert arrangement **1** is arranged to close the valve cavity **60**.

(30) The casing member **10** and the base portion **21** of the armature member **20** are adapted with substantially cylindrical geometry. The casing member **10** and the base portion **21** are characterized by respective outer diameters wherein the outer diameter of the casing member **10** is larger than the outer diameter of the base portion **21**.

(31) According to one embodiment, the casing member **10** is adapted to engage with the base portion **21** of the armature member **20** in a press fit manner. This feature is however an optional feature but indeed facilitates the casing member **10** to secure the armature member **20** in place when the insert arrangement **1** is arranged to close the valve cavity **60** of the damping arrangement.

(32) FIGS. **3** and **4** show two different ways of assembling the insert arrangement **1** to close the valve cavity **60** of the damping arrangement. According to one embodiment, the armature member **20** and the casing member **10** are first assembled before the insert arrangement **1** is arranged to the damping arrangement **1** to close the valve cavity **60**. The casing member **10** is then rotated to secure the armature member **10**. This is shown in FIG. **3**. Alternatively, the armature member **20** is first arranged to the damper device in the valve cavity **60** and thereafter the casing member **10** is arranged to secure the armature member **20** so that the insert arrangement closes the valve cavity **60** of the damping arrangement. This is shown in FIG. **4**. An assembly element may be inserted to protect the threads of the damping arrangement during insertion of the insert arrangement **1** and may be removed before the casing member **10** is rotated to fixate the insert arrangement **1** to the damping arrangement.

(33) FIG. **5** shows an embodiment of the disclosure wherein the casing member comprises an engaging portion **12**. The engaging portion **12** is adapted in shape and size to facilitate insertion of the insert arrangement **1** into the valve cavity **60**. As exemplified, the engaging portion **12** is characterized by a smaller outer diameter than a second portion of the casing member **10**. The engaging portion **12** may have a tapered portion from the engaging portion and the second portion of the casing member **12**. The engaging portion **12** may be adapted in shape and size to correspond to an inner shape of the valve cavity wall of the damping arrangement. By this, the insert arrangement **1** may be more easily inserted into a valve cavity **60**. Moreover, it may improve stability of the insert arrangement **1** as well.

(34) FIG. **6** shows a first embodiment of a damping arrangement such as a shock absorber **1000a** comprising a valve device **100**. The valve device **100** comprises a valve cavity and a valve arrangement and an insert arrangement **1** according to the disclosure. A solenoid arrangement is

also shown in FIG. 5. The valve device **100** may be fluidly connected to a damping chamber of the shock absorber for enabling control of damping characteristics during compression and/or rebound. (35) FIG. 7 shows a second embodiment of a damping arrangement such as a shock absorber **1000b** comprising two valve devices **100a**, **100b**. One or both of the valve devices **100** comprises a valve arrangement and an insert arrangement **1** according to the disclosure. Respective solenoid arrangements are also shown in FIG. 6. One of the two valve devices **100a**, **100b** may be fluidly connected to the shock absorber to control damping characteristics during compression and the other of the two valve devices **100a**, **100b** may be fluidly connected to a damping chamber of the shock absorber for enabling control of damping characteristics during rebound.

(36) FIG. 8 shows a flow chart of a method of assembling a damping arrangement, comprising the steps of: providing S1 a damping arrangement adapted with a valve cavity **60**; providing S2 an insert arrangement **1** comprising an armature member **20** and a valve arrangement **40**; inserting S3 the insert arrangement **1** into the valve cavity **60** such that a mating surface **211** of a base portion **21** of the armature member **20** mates with an inner wall of the valve cavity **60**, thereby closing the valve cavity **60** in a closing position; fixating S4 the insert arrangement **1** in the closing position by means of fixating means **11** provided on a casing member **10** of the insert arrangement **1** adapted for engaging with threads provided on an inner wall of the valve cavity **60**; arranging S5 a solenoid arrangement **50** in a receiving space formed between the casing member **10** and an axial portion **22** extending out of the base portion **21** of the armature member **20**.

(37) The method further comprises the step of providing S6, prior to the step of inserting the insert arrangement **1** into the valve cavity **60**, a sealing member **30** in a groove located in the mating surface **211**.

(38) The method further comprises the step of providing S7, prior to inserting the insert arrangement **1** in the valve cavity, an assembly element into the valve cavity to cover said threads in the valve cavity **60** and removing the assembly element before fixating the insert arrangement **1** in the closing position by means of said fixating means **11**.

(39) In the drawings and specification, there have been disclosed preferred embodiments and examples of the disclosure and, although specific terms are employed, they are used in a generic and descriptive sense only and not for the purpose of limitation, the scope of the disclosure being set forth in the following claims.

Claims

1. An insert arrangement for engaging with a solenoid arrangement and for closing a valve cavity of a damping arrangement, the insert arrangement comprising: an armature member adapted in shape and size to provide a base portion and an axial portion extending out of the base portion in a direction parallel to a first axis, wherein the base portion is adapted to provide a mating surface for mating with an inner wall of the valve cavity when the insert arrangement is arranged to close the valve cavity, the axial portion is adapted to define an inner space for receiving and allowing an actuation member to be axially moveable therein to interact with a valve arrangement of the damping arrangement under influence of a magnetic field generated by the solenoid arrangement, a casing member adapted to extend around the axial portion to define a receiving space between the axial portion and the casing member, and the solenoid arrangement including a first portion at least partly arrangeable in said receiving space, the casing member further adapted with a magnetically conducting material for substantially closing a magnetic field generated by the solenoid arrangement, the solenoid arrangement including a second portion circumscribing the first portion with a gap therebetween, the casing member being at least partially positioned in the gap and fixating means for fixating the armature member to the damping arrangement, wherein said fixating means are arranged on the casing member, said mating surface being axially located between an insert end of the insert arrangement and said fixating means.

2. The insert arrangement according to claim 1, further adapted with a groove in the mating surface for receiving a sealing member therein, which sealing member is adapted to hinder hydraulic fluid from leaking out of the valve cavity when the insert arrangement is arranged to close the valve cavity.
 3. The insert arrangement according to claim 1, wherein the base portion and the axial portion are formed as a single part.
 4. The insert arrangement according to claim 1, wherein the casing member is a separate part from the armature member.
 5. The insert arrangement according to claim 1, wherein the fixating means comprise threads adapted to engage with corresponding threads arranged on the inner wall of the valve cavity.
 6. The insert arrangement according to claim 2, further comprising a sealing member adapted to be arranged in the groove and to hinder hydraulic fluid from leaking out of the valve cavity when the insert arrangement is arranged to close the valve cavity.
 7. The insert arrangement according to claim 1, wherein the casing member and the base portion of the armature member are adapted with substantially cylindrical geometry, wherein an outer diameter of the casing member is larger than an outer diameter of the base portion.
 8. The insert arrangement according to claim 7, wherein the base portion and the axial portion are concentric.
 9. The insert arrangement according to claim 1, wherein the casing member is adapted to engage with the base portion of the armature member in a press fit manner.
 10. The insert arrangement according to claim 1, wherein the fixation means are adapted for securing the casing member to the inner wall of the valve cavity.
 11. A damping arrangement comprising: a valve cavity; an insert arrangement according to claim 1 arranged to close the valve cavity; a solenoid arrangement arranged at least partly in the receiving space of the insert arrangement; a valve arrangement; and an actuation member axially moveable in the inner space of the axial portion of the armature member to interact with the valve arrangement under influence of a magnetic field generated by the solenoid arrangement.
 12. The damping arrangement according to claim 11, further comprising a sealing member arranged in a groove or the groove located in the mating surface of the base portion of the armature member for hindering hydraulic fluid from leaking out of the valve cavity when the insert arrangement is arranged to close the valve cavity.
 13. A method of assembling a damping arrangement, comprising the steps of: providing a damping arrangement adapted with a valve cavity; providing an insert arrangement comprising an armature member and a valve arrangement, said valve arrangement comprising a first valve seat member and a first valve member adapted to be engageable with the first valve seat member; inserting the insert arrangement into the valve cavity such that a mating surface of a base portion of the armature member mates with an inner wall of the valve cavity, thereby closing the valve cavity in a closing position; fixating the insert arrangement in the closing position by means of fixating means provided on a casing member adapted for engaging with threads provided on the inner wall of the valve cavity; arranging a first portion of a solenoid arrangement in a receiving space formed between the casing member and an axial portion extending out of the base portion of the armature member, and positioning at least a portion of the casing within a gap located between the first portion and a second portion of the solenoid arrangement that circumscribes the first portion.
 14. The method according to claim 13, further comprising the step of providing, prior to the step of inserting the insert arrangement into the valve cavity, a sealing member in a groove located in the mating surface.
-