





Related U.S. Application Data

continuation of application No. 16/820,932, filed on Mar. 17, 2020, now Pat. No. 11,321,039, which is a continuation of application No. 14/284,793, filed on May 22, 2014, now Pat. No. 10,628,103.

- (51) **Int. Cl.**
G06F 3/147 (2006.01)
G09G 5/14 (2006.01)
- (52) **U.S. Cl.**
 CPC **G09G 5/14** (2013.01); **G09G 2320/0686** (2013.01); **G09G 2340/04** (2013.01); **G09G 2340/0407** (2013.01); **G09G 2380/02** (2013.01)
- (58) **Field of Classification Search**
 CPC G09G 2320/0686; G09G 2340/04; G09G 2340/0407; G09G 2380/02; Y02E 10/549
 See application file for complete search history.

(56) References Cited**U.S. PATENT DOCUMENTS**

6,819,304 B2 11/2004 Branson
 6,933,532 B2 8/2005 Arnold et al.
 7,184,006 B2 2/2007 Kim
 7,636,794 B2 12/2009 Ramos et al.
 7,714,801 B2 5/2010 Kimmel
 8,319,725 B2 11/2012 Okamoto et al.
 8,368,677 B2 2/2013 Yamamoto
 8,377,762 B2 2/2013 Eguchi et al.
 8,405,605 B2 3/2013 Sugahara
 8,482,086 B2 7/2013 Shimoyama et al.
 8,543,166 B2 9/2013 Choi et al.
 8,547,197 B2 10/2013 Byun et al.
 8,581,859 B2 11/2013 Okumura et al.
 8,723,824 B2 5/2014 Myers et al.
 8,780,071 B2 7/2014 Chen et al.
 8,803,816 B2 8/2014 Kilpatrick, II et al.
 8,836,611 B2 9/2014 Kilpatrick, II et al.
 8,860,632 B2 10/2014 Kilpatrick, II et al.
 8,860,765 B2 10/2014 Kilpatrick, II et al.
 8,863,038 B2 10/2014 King et al.
 8,866,840 B2 10/2014 Dahl et al.
 8,872,797 B2 10/2014 Lee et al.
 8,899,791 B2 12/2014 Liu
 8,933,874 B2 1/2015 Lundqvist et al.
 8,947,320 B2 2/2015 King et al.
 8,947,462 B2 2/2015 Joo
 8,976,141 B2 3/2015 Myers et al.
 9,009,984 B2 4/2015 Caskey et al.
 9,013,884 B2 4/2015 Fukuma et al.
 9,323,446 B2 4/2016 Seo et al.
 9,411,451 B2 8/2016 Myers et al.
 9,489,078 B2 11/2016 Seo et al.
 9,489,079 B2 11/2016 Seo et al.
 9,489,080 B2 11/2016 Seo et al.
 9,495,094 B2 11/2016 Kang et al.
 9,541,958 B2 1/2017 Seo et al.
 9,626,938 B2 4/2017 Abe
 9,666,820 B2 5/2017 Eguchi et al.
 9,791,949 B2 10/2017 Myers et al.
 9,818,370 B2 11/2017 Joo
 9,823,833 B2 11/2017 Grant et al.
 9,939,953 B2 4/2018 Abe
 10,055,039 B2 8/2018 Myers et al.
 10,254,887 B2 4/2019 Abe
 10,318,029 B2 6/2019 Myers et al.
 10,374,184 B2 8/2019 Eguchi et al.
 10,521,034 B2 12/2019 Myers et al.
 10,628,103 B2 4/2020 Iwaki et al.
 10,936,136 B2 3/2021 Myers et al.
 11,171,298 B2 11/2021 Eguchi et al.
 11,237,685 B2 2/2022 Myers et al.

11,416,042 B2 8/2022 Kang et al.
 11,469,387 B2 10/2022 Eguchi et al.
 11,997,859 B2 5/2024 Eguchi et al.
 12,131,087 B2* 10/2024 Iwaki G06F 3/14
 2004/0052044 A1 3/2004 Mochizuki et al.
 2005/0093868 A1 5/2005 Hinckley
 2006/0146488 A1 7/2006 Kimmel
 2006/0222971 A1 10/2006 Seo et al.
 2008/0303782 A1 12/2008 Grant et al.
 2010/0001639 A1 1/2010 Kim et al.
 2010/0060664 A1 3/2010 Kilpatrick, II et al.
 2010/0064244 A1 3/2010 Kilpatrick, II et al.
 2010/0064536 A1 3/2010 Caskey et al.
 2010/0066643 A1 3/2010 King et al.
 2010/0079355 A1 4/2010 Kilpatrick, II et al.
 2010/0085274 A1 4/2010 Kilpatrick, II et al.
 2010/0085382 A1 4/2010 Lundqvist et al.
 2010/0164888 A1 7/2010 Okumura et al.
 2010/0220077 A1 9/2010 Fukunaga et al.
 2011/0043976 A1 2/2011 Visser et al.
 2011/0050645 A1 3/2011 Lee et al.
 2011/0126141 A1 5/2011 King et al.
 2011/0134144 A1 6/2011 Moriwaki
 2011/0205178 A1 8/2011 Yoshida et al.
 2011/0216064 A1 9/2011 Dahl et al.
 2012/0038570 A1 2/2012 Delaporte
 2012/0217516 A1 8/2012 Hatano et al.
 2012/0235894 A1 9/2012 Phillips
 2012/0242599 A1 9/2012 Seo et al.
 2012/0306782 A1 12/2012 Seo et al.
 2012/0307423 A1 12/2012 Bohn et al.
 2012/0329528 A1 12/2012 Song
 2013/0010405 A1 1/2013 Rothkopf et al.
 2013/0050270 A1 2/2013 Joo
 2013/0127918 A1 5/2013 Kang et al.
 2014/0015743 A1 1/2014 Seo et al.
 2014/0098028 A1 4/2014 Kwak et al.
 2017/0052698 A1 2/2017 Seo et al.
 2017/0116965 A1 4/2017 Kwak et al.
 2019/0196648 A1 6/2019 Abe
 2022/0155907 A1 5/2022 Myers et al.
 2024/0306410 A1 9/2024 Eguchi et al.

FOREIGN PATENT DOCUMENTS

CN 101782804 A 7/2010
 CN 102087824 A 6/2011
 CN 102150095 A 8/2011
 CN 102723058 A 10/2012
 CN 202602738 U 12/2012
 CN 202790058 U 3/2013
 CN 103050064 A 4/2013
 CN 202887612 U 4/2013
 EP 1463117 A 9/2004
 EP 2202624 A 6/2010
 EP 2224319 A 9/2010
 EP 2333761 A 6/2011
 EP 2354908 A 8/2011
 EP 2500898 A 9/2012
 EP 2565866 A 3/2013
 EP 2573644 A 3/2013
 EP 2674834 A 12/2013
 EP 2755459 A 7/2014
 EP 3057385 A 8/2016
 EP 3125508 A 2/2017
 EP 3190476 A 7/2017
 EP 3860099 A 8/2021
 JP 2002-278515 A 9/2002
 JP 2004-303731 A 10/2004
 JP 2005-141715 A 6/2005
 JP 2006-091462 A 4/2006
 JP 2006-208424 A 8/2006
 JP 2006-243621 A 9/2006
 JP 2006-338022 A 12/2006
 JP 2007-333797 A 12/2007
 JP 2008-149681 A 7/2008
 JP 2009-222415 A 10/2009
 JP 2009-231183 A 10/2009
 JP 2010-050173 A 3/2010

(56)

References Cited

FOREIGN PATENT DOCUMENTS

JP	2010-157060	A	7/2010
JP	2010-529555		8/2010
JP	2010-198575	A	9/2010
JP	2010-224480	A	10/2010
JP	2011-054929	A	3/2011
JP	2011-085923	A	4/2011
JP	2011-118245	A	6/2011
JP	2011-215904	A	10/2011
JP	2012-502370		1/2012
JP	2012-190794	A	10/2012
JP	2013-050547	A	3/2013
JP	2013-105312	A	5/2013
JP	2013-225052	A	10/2013
JP	2015-015018	A	1/2015
KR	2008-0035709	A	4/2008
KR	2011-0053269	A	5/2011
KR	2011-0055718	A	5/2011
KR	2011-0063298	A	6/2011
KR	2013-0024085	A	3/2013
KR	2013-0056674	A	5/2013
TW	201024977		7/2010
TW	201128502		8/2011
TW	201203196		1/2012
TW	201212768		3/2012
WO	WO-2006/072670		7/2006
WO	WO-2008/150600		12/2008
WO	WO-2010/028394		3/2010
WO	WO-2010/028397		3/2010
WO	WO-2010/028399		3/2010

WO	WO-2010/028402	3/2010
WO	WO-2010/028403	3/2010
WO	WO-2010/028404	3/2010
WO	WO-2010/028405	3/2010
WO	WO-2010/028406	3/2010
WO	WO-2010/028407	3/2010
WO	WO-2011/034068	3/2011
WO	WO-2012/108668	8/2012
WO	WO-2012/108715	8/2012
WO	WO-2012/108722	8/2012
WO	WO-2012/108723	8/2012
WO	WO-2012/108729	8/2012
WO	WO-2013/048881	4/2013
WO	WO-2013/077537	5/2013
WO	WO-2013/191488	12/2013
WO	WO-2014/196485	12/2014

OTHER PUBLICATIONS

Written Opinion (Application No. PCT/JP2014/064557) Dated Jul. 22, 2014.

Taiwanese Office Action (Application No. 103118444) Dated Jan. 24, 2018.

Chinese Office Action (Application No. 201480032026.2) Dated Mar. 20, 2018.

Chinese Office Action (Application No. 201480032026.2) Dated Nov. 15, 2018.

Chinese Office Action (Application No. 202010938999.X) Dated Apr. 17, 2024.

* cited by examiner

FIG. 1A




FIG. 1B1




FIG. 1B2




FIG. 2A




FIG. 2B




FIG. 3




FIG. 4A




FIG. 4B




FIG. 4C




FIG. 4D1





FIG. 4D2








FIG. 6A




FIG. 6B1




FIG. 6B2




FIG. 7A




FIG. 7B




FIG. 8A




FIG. 8B




FIG. 8C




FIG. 9A

400B




FIG. 9B





FIG. 9C



SEMICONDUCTOR DEVICE COMPRISING BENDABLE TOUCH PANEL

TECHNICAL FIELD

The present invention relates to an object, a method, or a manufacturing method. In addition, the present invention relates to a process, a machine, manufacture, or a composition of matter. In particular, the present invention relates to, for example, a human interface, a semiconductor device, a display device, a light-emitting device, a power storage device, a driving method thereof, or a manufacturing method thereof. In particular, the present invention relates to, for example, a method and a program for processing and displaying image data, and a device including a recording medium in which the program is recorded. In particular, the present invention relates to, for example, a method for processing and displaying image data by which an image including information processed by an information processor provided with a display portion is displayed, a program for displaying an image including information processed by an information processor provided with a display portion, and an information processor including a recording medium in which the program is recorded.

BACKGROUND ART

Display devices with large screens can display many pieces of information. Therefore, such display devices are excellent in browsability and suitable for information processors.

The social infrastructures relating to means for transmitting information have advanced. This has made it possible to acquire, process, and send out many pieces and various kinds of information with the use of an information processor not only at home or office but also at other visiting places.

With this being the situation, portable information processors are under active development.

For example, portable information processors are often used outdoors, and force might be accidentally applied by dropping to the information processors and display devices included in them. As an example of a display device that is not easily broken, a display device having high adhesiveness between a structure body by which a light-emitting layer is divided and a second electrode layer is known (Patent Document 1).

REFERENCE

Patent Document

[Patent Document 1] Japanese Published Patent Application No. 2012-190794

DISCLOSURE OF INVENTION

One embodiment of the present invention is made in view of the foregoing technical background. One object is to provide a novel bendable and highly portable information processor. Another object is to provide a novel information processor capable of displaying information or the like on a seamless large screen.

Note that the descriptions of these objects do not preclude the existence of other objects. In one embodiment of the present invention, there is no need to achieve all the objects.

Other objects will be apparent from and can be derived from the description of the specification, the drawings, the claims, and the like.

One embodiment of the present invention is an information processor including: an arithmetic device that receives bend position data and an operation instruction including a display termination instruction and supplies image data; and an input/output device that receives the image data and supplies the bend position data and the operation instruction. The arithmetic device includes an arithmetic unit and a storage unit that stores a program to be executed by the arithmetic unit. The input/output device includes a bendable display unit and a bend position sensor that senses a position where the display unit is bent and supplies the bend position data.

The program includes: a first step of initializing a timer or the like; a second step of allowing interrupt processing; a third step of displaying an image that has been generated in the interrupt processing; a fourth step of returning to the third step when the display termination instruction has not been input in the interrupt processing and proceeding to a fifth step when the display termination instruction has been input in the interrupt processing; and the fifth step of terminating the program.

The interrupt processing includes: a sixth step of receiving the display termination instruction and the bend position data; a seventh step of proceeding to an eighth step when the bend position data has not been supplied in the sixth step and proceeding to a ninth step when the bend position data has been supplied in the sixth step; the eighth step of generating an image that is not divided and is to be displayed in the display unit; the ninth step of generating an image that is divided into a first region and a second region at the bend position; and a tenth step of recovering from the interrupt processing.

The above information processor of one embodiment of the present invention displays a divided image on the display unit when the display unit is bent. Thus, one display unit can be divided into two regions at the bend position, and consequently, different images can be displayed in the respective regions.

Furthermore, a novel bendable and highly portable information processor can be provided. In addition, a novel information processor capable of displaying information or the like on a seamless large screen can be provided. Note that an "image" in this specification includes information that can be perceived visually, such as characters and symbols.

Another embodiment of the present invention is the above information processor. The program includes, instead of the above interrupt processing, interrupt processing that includes: a sixth step of receiving the display termination instruction and the bend position data; a seventh step of proceeding to an eighth step when the bend position data has not been supplied in the sixth step and proceeding to a tenth step when the bend position data has been supplied in the sixth step; the eighth step of selecting one image; a ninth step of generating an image that is not divided and is to be displayed in the display unit from the one image selected in the eighth step; the tenth step of selecting two images; an eleventh step of generating an image that is divided into a first region and a second region at the bend position from the two images selected in the tenth step; and a twelfth step of recovering from the interrupt processing.

In the above information processor of one embodiment of the present invention, one display region can be divided into two regions at the bend position, and an image to be

displayed in one of the regions can be selected. In addition, one or a plurality of images can be selected to be displayed depending on how the display region is bent.

Furthermore, a novel bendable and highly portable information processor can be provided. In addition, a novel information processor capable of displaying information or the like on a seamless large screen can be provided.

Another embodiment of the present invention is the above information processor. The program includes, instead of the above interrupt processing, interrupt processing that includes: a sixth step of receiving the display termination instruction and the bend position data; a seventh step of proceeding to an eleventh step when the bend position data has not been supplied in the sixth step and proceeding to an eighth step when the bend position data has been supplied in the sixth step; the eighth step of proceeding to the eleventh step when the display unit has not been bent outward and proceeding to a ninth step when the display unit has been bent outward; the ninth step of identifying the bend position that is closest to a center of the display unit; a tenth step of generating an image in which pixels values of pixels between the bend position and an edge that is on a side closer to the bend position are 0; and the eleventh step of recovering from the interrupt processing.

In the above information processor of one embodiment of the present invention, the display unit can be bent outward, and a portion between the bend position and the edge farther therefrom can be used for display and display in a portion between the bend position and the edge closer thereto can be stopped. Thus, power consumed by a region that is not used by a user can be reduced. Further, it is possible to prevent others from secretly looking at information displayed in the region that is not used by the user.

Another embodiment of the present invention is a program that is stored in a storage unit of an information processor and is to be executed by an arithmetic unit of the information processor. The information processor includes: an input/output device that includes a bendable display unit and a bend position sensor configured to sense a position where the display unit is bent and supply bend position data, receives image data, and supplies the bend position data and an operation instruction including a display termination instruction; and an arithmetic device that includes an arithmetic unit and a storage unit, receives the bend position data and the operation instruction, and supplies the image data.

The program includes: a first step of initializing a timer or the like; a second step of allowing interrupt processing; a third step of displaying an image that has been generated in the interrupt processing; a fourth step of returning to the third step when a display termination instruction has not been input in the interrupt processing and proceeding to a fifth step when the display termination instruction has been input in the interrupt processing; and the fifth step of terminating the program. The interrupt processing includes: a sixth step of receiving the display termination instruction and the bend position data; a seventh step of proceeding to an eighth step when the bend position data has not been supplied in the sixth step and proceeding to a ninth step when the bend position data has been supplied in the sixth step; the eighth step of generating an image that is not divided and is to be displayed in the display unit; the ninth step of generating an image that is divided into a first region and a second region at the bend position; and a tenth step of recovering from the interrupt processing.

In accordance with the above program of one embodiment of the present invention, a divided image can be displayed on the display unit depending on how the display region is

bent. Thus, one display unit can be divided into two regions at the bend position, and consequently, different images can be displayed in the respective regions.

Another embodiment of the present invention is the above program including, instead of the above interrupt processing, interrupt processing that includes: a sixth step of receiving the display termination instruction and the bend position data; a seventh step of proceeding to an eighth step when the bend position data has not been supplied in the sixth step and proceeding to a tenth step when the bend position data has been supplied in the sixth step; the eighth step of selecting one image; a ninth step of generating an image that is not divided and is to be displayed in the display unit from the one image selected in the eighth step; the tenth step of selecting two images; an eleventh step of generating an image that is divided into a first region and a second region at the bend position from the two images selected in the tenth step; and a twelfth step of recovering from the interrupt processing.

In accordance with the above program of one embodiment of the present invention, one display region can be divided into two regions at the bend position, and an image to be displayed in one of the regions can be selected. In addition, one or a plurality of images can be selected to be displayed depending on how the display region is bent.

Another embodiment of the present invention is the above program including, instead of the above interrupt processing, interrupt processing that includes: a sixth step of receiving the display termination instruction and the bend position data; a seventh step of proceeding to an eleventh step when the bend position data has not been supplied in the sixth step and proceeding to an eighth step when the bend position data has been supplied in the sixth step; the eighth step of proceeding to the eleventh step when the display unit has not been bent outward and proceeding to a ninth step when the display unit has been bent outward; the ninth step of identifying the bend position that is closest to a center of the display unit; a tenth step of generating an image in which pixels values of pixels between the bend position and an edge that is on a side closer to the bend position are 0; and the eleventh step of recovering from the interrupt processing.

In accordance with the above program of one embodiment of the present invention, the display unit can be bent outward, and a portion between the bend position and the edge farther therefrom can be used for display and display in a portion between the bend position and the edge closer thereto can be stopped. Thus, power consumed by a region that is not used by a user can be reduced. Further, it is possible to prevent others from secretly looking at information displayed in the region that is not used by the user.

Note that a light-emitting device in this specification means an image display device or a light source (including a lighting device). In addition, the light-emitting device includes any of the following modules in its category: a module in which a connector such as a flexible printed circuit (FPC) or a tape carrier package (TCP) is attached to a light-emitting device; a module having a TCP provided with a printed wiring board at the end thereof; and a module having an integrated circuit (IC) directly mounted on a substrate over which a light-emitting element is formed by a chip on glass (COG) method.

According to one embodiment of the present invention, a novel bendable and highly portable information processor can be provided. In addition, a novel information processor capable of displaying information or the like on a seamless large screen can be provided.

5

BRIEF DESCRIPTION OF DRAWINGS

FIGS. 1A, 1B1, and 1B2 are a block diagram and schematic views illustrating a structure of an information processor of one embodiment.

FIGS. 2A and 2B are flow charts illustrating a method for driving an information processor of one embodiment.

FIG. 3 is a flow chart illustrating a method for driving an information processor of one embodiment.

FIGS. 4A, 4B, 4C, 4D1, and 4D2 illustrate an information processor of one embodiment.

FIGS. 5A to 5C illustrate a structure of an input/output device that can be used for an information processor of one embodiment.

FIGS. 6A, 6B1, and 6B2 are a flow chart and schematic views illustrating a method for driving an information processor of one embodiment.

FIGS. 7A and 7B illustrate a structure of a touch panel that can be used in an information processor of one embodiment.

FIGS. 8A to 8C illustrate structures of a touch panel that can be used in an information processor of one embodiment.

FIGS. 9A to 9C illustrate structures of a touch panel that can be used in an information processor of one embodiment.

BEST MODE FOR CARRYING OUT THE INVENTION

Embodiments will be described in detail with reference to drawings. Note that the present invention is not limited to the description below, and it is easily understood by those skilled in the art that various changes and modifications can be made without departing from the spirit and scope of the present invention. Therefore, the present invention should not be construed as being limited to the description in the following embodiments. Note that in the structures of the invention described below, the same portions or portions having similar functions are denoted by the same reference numerals in different drawings, and description of such portions is not repeated.

Embodiment 1

In this embodiment, a structure of an information processor of one embodiment of the present invention will be described with reference to FIGS. 1A, 1B1, and 1B2, FIGS. 2A and 2B, and FIG. 3.

FIG. 1A is a block diagram illustrating the structure of the information processor of one embodiment of the present invention.

FIGS. 1B1 and 1B2 are schematic views illustrating the structure of the information processor of one embodiment of the present invention. FIG. 1B2 is a schematic view illustrating the information processor in FIG. 1B1 in a bent state.

FIGS. 2A and 2B are flow charts illustrating a program to be executed by an arithmetic unit of the information processor of one embodiment of the present invention.

FIG. 3 is a flow chart showing a modification example of the program to be executed by the arithmetic unit of the information processor of one embodiment of the present invention.

<Information Processor>

An information processor **100** described in this embodiment includes an arithmetic device **110**. The arithmetic device **110** receives bend position data SENS and an operation instruction INPUT including a display termination instruction, and supplies image data VIDEO. The arithmetic

6

device **110** includes an arithmetic unit **111** and a storage unit **112** that stores a program to be executed by the arithmetic unit **111** (see FIG. 1A).

The information processor **100** also includes an input/output device **120**. The input/output device **120** receives image data VIDEO, and supplies bend position data SENS and an operation instruction INPUT including a display termination instruction. The input/output device **120** includes a bendable display unit **122** and a bend position sensor **123** that senses the position at which the display unit **122** is bent and supplies bend position data SENS (see FIG. 1B1).

<<Program>>

The program to be executed by the arithmetic unit **111** includes the following steps (see FIGS. 2A and 2B).

In a first step, a timer or the like is initialized (see (S1) in FIG. 2A). Note that this initialization step also includes the operation of reading image data that is to be used in an interrupt processing which is described later.

In a second step, the interrupt processing is allowed. When the interrupt processing is allowed, the main processing can be stopped and the interrupt processing described later can be executed (see (S2) in FIG. 2A).

In a third step, an image that has been generated in the interrupt processing allowed in the second step is displayed (see (S3) in FIG. 2A).

In a fourth step, the operation returns to the third step in the case where a display termination instruction has not been input in the interrupt processing, and proceeds to a fifth step in the case where a display termination instruction has been input in the interrupt processing (see (S4) in FIG. 2A).

In the fifth step, the program is terminated (see (S5) in FIG. 2A).

The interrupt processing will be described (see FIG. 2B). Note that when the interrupt processing is allowed, the arithmetic unit can receive an instruction to execute the interrupt processing. The arithmetic unit that has received the instruction to execute the interrupt processing stops the main processing and executes the interrupt processing. For example, the arithmetic unit that has received an event associated with the instruction executes the interrupt processing and stores the execution result in the storage unit. Then, the arithmetic unit that has recovered from the interrupt processing can resume the main processing on the basis of the execution result of the interrupt processing.

In a sixth step, a display termination instruction and bend position data SENS are received. A user of the information processor **100** can input a display termination instruction with, for example, an input unit **121** (see (T6) in FIG. 2B).

In a seventh step, the operation proceeds to an eighth step in the case where bend position data SENS has not been supplied in the sixth step, and proceeds to a ninth step in the case where bend position data SENS has been supplied in the sixth step (see (T7) in FIG. 2B). For example, when the display unit **122** that has been in a bent state is put in a non-bent state and thus supply of bend position data SENS is stopped, the operation proceeds to the eighth step. Conversely, when the display unit **122** is put in a bent state and thus bend position data SENS is supplied, the operation proceeds to the ninth step.

In the eighth step, an image to be displayed on the display unit **122** is generated. Note that the image generated in this step is not divided at a position where the display unit **122** can be bent. The image can be generated from, for example, the image data that has been read in the first step (see (T8) in FIG. 2B).

In the ninth step, an image that is divided into a first region **122(a)** and a second region **122(b)** at the bend position is generated (see FIG. **1B2** and (T9) in FIG. **2B**). Note that a broken line **100F** indicates the bend position.

Although the case where the display unit **122** is bent once along one line is described in this embodiment, one embodiment of the present invention is not limited to this case. For example, the display unit **122** may be bent more than once along more than one lines, and an image that is divided at the bend positions may be displayed.

In a tenth step, the operation recovers from the interrupt processing (see (T10) in FIG. **2B**).

In the information processor **100** of one embodiment of the present invention, a display region is divided into the first region **122(a)** and the second region **122(b)** and image data are displayed in the respective regions when the display unit **122** is bent. In this manner, one display region can be divided into two regions at the bend position. Consequently, different images or images for different purposes, for example, can be displayed in the respective regions.

Furthermore, a novel bendable and highly portable information processor can be provided. In addition, a novel information processor capable of displaying information or the like on a seamless large screen can be provided. Note that an "image" in this specification includes information that can be perceived visually, such as characters and symbols.

The arithmetic device **110** described as an example in this embodiment includes an input/output interface **115** and a transmission path **114**.

The input/output interface **115** can supply data to the input/output device **120** and receive data supplied from the input/output device **120**.

The transmission path **114** can supply data to the arithmetic unit **111**, the storage unit **112**, and the input/output interface **115**. In addition, the arithmetic unit **111**, the storage unit **112**, and the input/output interface **115** can supply data to the transmission path **114**.

The input/output device **120** includes the input unit **121**. The input unit **121** can supply a display termination instruction and the like.

Note that the display termination instruction is an instruction to terminate the program.

Note that these units cannot be clearly distinguished and one unit also serves as another unit or include part of another unit in some cases. For example, a touch panel serves as the input unit **121** as well as the display unit **122**.

Individual components included in the information processor **100** of one embodiment of the present invention are described below.

<<Input/Output Device>>

The input/output device **120** is connected to the transmission path **114** via the input/output interface **115**. The input/output device **120** can supply data.

<<Display Unit>>

The display unit **122** has flexibility and therefore can be bent. FIG. **1B1** illustrates the display unit **122** that is opened flat, and FIG. **1B2** illustrates the display unit **122** that is bent to have one bend. Note that the number of bends is not limited to one; the display unit **122** can be bent to have n bends (n is a natural number of 1 or more).

A specific structure of the flexible display unit **122** is described in detail in Embodiment 2.

<<Bend Position Sensor>>

The bend position sensor **123** senses the position at which the display unit **122** is bent and supplies bend position data SENS. For example, in the case where the bend position is

determined in advance, a sensor is provided at that position. In the case where there are a plurality of positions where the display unit can be bent, a plurality of sensors are arranged in a line or a matrix, so that coordinates of the bend position can be identified.

For example, the bend position sensor **123** can be provided along the periphery of the display unit **122**. In the information processor **100** illustrated in FIG. **1B1**, the bend position sensor **123** is provided along the longitudinal direction of the display unit **122**. Alternatively, the bend position sensor **123** may be provided along the lateral direction, for example.

Note that the bend position sensor **123** that is provided to surround the display unit **122** can sense bend positions in various (e.g., lateral, longitudinal, and diagonal) directions across the display unit **122**. Thus, the display unit **122** can be divided at various positions.

The bend position sensor **123** can be composed of, for example, a switch, a MEMS pressure sensor, a pressure sensor, or the like.

Specifically, a mechanical contact switch, a magnetic switch, or the like may be provided on the display unit **122** to be opened and closed in accordance with the operations of opening and bending the display unit **122**.

Alternatively, a plurality of pressure sensors may be provided on the display unit **122**. Specifically, a film-like piezoelectric element can be attached to the display unit **122**. A rise of pressure with the bending operation is sensed with the pressure sensor, whereby the bend position can be found.

As the piezoelectric element, for example, an organic piezoelectric film can be used. Specifically, a piezoelectric film including polyamino acid, a piezoelectric film including polyvinylidene fluoride, a piezoelectric film including polyester, a piezoelectric film including a chiral polymer, or the like can be used.

Note that the piezoelectric element can serve as both an element for the bend position sensor **123** and an element for a pressure-sensing touch panel.

<<Input Unit>>

As the input unit **121**, for example, a human interface or the like can be used. Specifically, a keyboard, a mouse, a touch panel, or the like can be used.

For example, a user of the information processor **100** can input, with the input unit **121**, an operation instruction including a display termination instruction, an instruction to select an image, or the like. The user can also input an instruction to select a region, a page turning instruction, or the like.

Furthermore, pseudo bend position data SENS may be input with the input unit **121**. Thus, one display unit can be divided into two regions at a position corresponding to the position data input with the input unit **121**. Consequently, different images can be displayed in the respective regions, for example.

<<Other Structures>>

As the input/output device **120**, for example, a camera, a microphone, a read-only external memory, an external memory, a communication device, a scanner, a speaker, a printer, or the like can be used.

Specifically, examples of a camera include a digital camera and a digital video camera.

Examples of an external memory include a hard disk and a removable memory. Examples of a read-only external memory include a CD-ROM and a DVD-ROM.

Examples of a communication device include a network connection device and a modem.

As a usage example of the information processor **100**, a software keyboard may be displayed in the second region **122(b)** of the display unit **122** that is divided into two regions.

For example, the first region **122(a)** can be used for displaying images, and the second region **122(b)** can be used as the input unit **121**. Specifically, game software is operated with the software keyboard; thus, the information processor **100** can be used as a game machine.

In the case where the display unit **122** includes light-emitting elements as display elements, it is preferable to display a Character Palette with a color brighter than that of the background, in which case power consumption can be reduced.

Since a seamless display unit is divided into two regions, a user can easily follow, with his/her eyes, the movement of an image from one region to the other region. Consequently, discomfort in operations between the two regions, for example, can be reduced.

In addition, a user can easily follow, with his/her eyes, an image displayed to move from one region to the other region by the arithmetic device **110**. Consequently, the user can accurately predict the position of an image that moves between the two regions.

For example, in a game or the like, the movement of a character between the two regions can be predicted accurately.

Modification Example 1

An information processor that is shown as Modification Example 1 in this embodiment will be described with reference to FIG. 3.

FIG. 3 is a flow chart showing a modification example of the program to be executed by the arithmetic unit **111** of the information processor of one embodiment of the present invention.

The information processor shown as Modification Example 1 in this embodiment differs from the information processor described with reference to FIGS. 2A and 2B in the interrupt processing of the program to be executed by the arithmetic unit **111**. The portions that differ will be described in detail below. Refer to the above description for portions where the same structures can be employed.

In Modification Example 1 in this embodiment, the program includes the following interrupt processing instead of the above-described interrupt processing. In a sixth step, a display termination instruction and bend position data SENS are received (see (U6) in FIG. 3).

In a seventh step, the operation proceeds to an eighth step in the case where bend position data SENS has not been supplied in the sixth step, and proceeds to a tenth step in the case where bend position data SENS has been supplied in the sixth step (see (U7) in FIG. 3).

In the eighth step, one image is selected from a plurality of images. For example, a plurality of image data are read in the first step, and the image data are displayed in a tiled pattern on the display unit **122** as initial images. A user can select the one image with the input unit **121** (see (U8) in FIG. 3).

In a ninth step, an image that is not divided and is to be displayed on the display unit is generated from the one image selected in the eighth step (see (U9) in FIG. 3).

In the tenth step, two images are selected from a plurality of images. For example, a plurality of image data read in the

first step are displayed in a tiled pattern and the user can select the two images with the input unit **121** (see (U10) in FIG. 3).

In an eleventh step, an image that is divided into the first region **122(a)** and the second region **122(b)** at the bend position is generated from the two images selected in the tenth step (see (U11) in FIG. 3).

In a twelfth step, the operation recovers from the interrupt processing (see (U12) in FIG. 3).

In the information processor shown as a modification example in this embodiment, one display region can be divided into two regions at the bend position, and an image to be displayed on the display unit **122** can be selected.

Modification Example 2

An information processor that is shown as Modification Example 2 in this embodiment will be described with reference to FIGS. 6A, 6B1, and 6B2.

FIGS. 6A, 6B1, and 6B2 are a flow chart and schematic views showing a modification example of the program to be executed by the arithmetic unit **111** of the information processor of one embodiment of the present invention.

The information processor shown as Modification Example 2 in this embodiment differs from the information processor described with reference to FIGS. 2A and 2B in the interrupt processing of the program to be executed by the arithmetic unit **111**. Thus, different portions will be described in detail below. Refer to the above description for portions where the same structures can be employed.

In Modification Example 2 in this embodiment, the program includes the following interrupt processing instead of the above-described interrupt processing. In a sixth step, a display termination instruction and bend position data SENS are received (see (V6) in FIG. 6A).

In a seventh step, the operation proceeds to an eleventh step in the case where bend position data SENS has not been supplied in the sixth step, and proceeds to an eighth step in the case where bend position data SENS has been supplied in the sixth step (see (V7) in FIG. 6A).

In the eighth step, the operation proceeds to the eleventh step in the case where the display unit **122** has not been bent outward, and proceeds to a ninth step in the case where the display unit **122** has been bent outward (see (V8) in FIG. 6A).

Note that whether the display unit **122** has been bent outward or inward can be found by using, for example, an acceleration sensor, a shear force sensor, or the like.

Specifically, acceleration sensors **100S** provided at the four corners of the display unit **122** are used to sense the acceleration that the four corners undergo when the display unit **122** is bent; thus, the tracks of the four corners of the display unit can be calculated (see FIG. 6B1). In this manner, it can be found whether the display unit has been bent outward or inward (see FIG. 6B2).

It is also possible to use a shear force sensor provided on the display unit **122** to find whether the display unit **122** has been bent outward or inward.

In the ninth step, the bend position F that is closest to the center C of the display unit **122** is identified (see (V9) in FIG. 6A).

The bend position F can be identified from bend position data SENS that is supplied by the bend position sensor. For example, in the case where a bend position sensor in which a plurality of pressure sensors are arranged in a line is used, the bend position F may be the position that is closest to the

11

center C of the display unit **122** and where the pressure sensor has sensed a pressure higher than a predetermined value (see FIG. **6B2**).

In a tenth step, an image in which pixel values of pixels between the bend position F and an edge E that is on the side closer to the bend position F are 0 is generated (see (V10) in FIG. **6A**).

Specifically, a region between the bend position F and the edge E on the side closer to the bend position F is the second region **122(b)**, and the other region is the first region **122(a)**. An image in which pixel values of pixels in the second region are 0, for example, is generated so that an image without shape, pattern, or color is displayed in the second region (see FIG. **6B2**). Note that an image including various information can be displayed in the first region **122(a)**.

In the eleventh step, the operation recovers from the interrupt processing (see (V11) in FIG. **6A**).

In the information processor shown as a modification example in this embodiment, the display unit can be bent outward, and a portion between the bend position and the edge farther therefrom can be used for display and display in a portion between the bend position and the edge closer thereto can be stopped. Thus, power consumed by a region that is not used by a user can be reduced. Further, it is possible to prevent others from secretly looking at information displayed in the region that is not used by the user.

This embodiment can be combined with any of the other embodiments in this specification as appropriate.

Embodiment 2

In this embodiment, an information processor of one embodiment of the present invention will be described with reference to FIGS. **4A**, **4B**, **4C**, **4D1**, and **4D2**.

FIG. **4A** is a plan view illustrating a structure of an information processor **200** of one embodiment of the present invention, and FIG. **4B** is a side view illustrating the structure of the information processor **200**. Note that the arrows in the drawings indicate the side where display is performed.

FIG. **4C** is a side view illustrating a structure of part of a bending member **281** illustrated in FIG. **4A**.

FIGS. **4D1** and **4D2** are side views illustrating examples in which a display unit **222** is divided into two regions at the position where an input/output device **220** is bent.

<Plan View>

The information processor **200** includes an arithmetic device **210** that receives bend position data and an operation instruction and supplies image data. The information processor **200** also includes the input/output device **220** that receives image data and supplies bend position data and an operation instruction (see FIG. **4A**).

<Side View>

The input/output device **220** includes the bending member **281** and the display unit **222** that is supported so as to be bent in accordance with bending of the bending member **281**. Note that the display unit **222** is positioned roughly at the center of the bending member **281** when seen from the side (see FIG. **4B**).

The bending member **281** is provided along each of opposite sides of the display unit **222**.

The bending member **281** includes one or more hinge components **282** (see FIG. **4C**). Thus, the bending member **281** can be bent at one or a plurality of positions. Note that the hinge component **282** may be provided with a ratchet mechanism, a unit to prevent slipping, or the like so that the bend angle can be adjusted as appropriate.

12

FIGS. **4D1** and **4D2** each illustrate a state where the bending member **281** is bent at a position **200F** and the display unit **222** is divided into a first region **222(a)** and a second region **222(b)**.

In FIG. **4D1**, for example, the bending member **281** is bent inward such that the first region **222(a)** faces a user and the second region **222(b)** faces upward.

In accordance with a program for the arithmetic device **210**, the display unit **222** is divided into the first region **222(a)** and the second region **222(b)** on the basis of bend position data that is supplied by the input/output device **220**.

For example, a display screen of software by which e-mails can be sent and received is displayed in the first region **222(a)**, and a software keyboard is displayed in the second region **222(b)**. Thus, an e-mail that is composed with the software keyboard displayed in the second region **222(b)** can be displayed and checked in the first region **222(a)**.

In this manner, the information processor **200** can be used as an e-mail sending/receiving device.

In FIG. **4D2**, for example, the bending member **281** is bent outward such that the first region **222(a)** faces a user and the second region **222(b)** faces downward.

In accordance with a program for the arithmetic device **210**, the display unit **222** is divided into the first region **222(a)** and the second region **222(b)** on the basis of bend position data that is supplied by the input/output device **220**.

For example, a display screen of software by which images can be viewed is displayed in the first region **222(a)**, and display in the second region **222(b)** is stopped. Thus, the first region **222(a)** can be kept at an angle such that the user can easily view images displayed in the first region **222(a)**.

In this manner, the information processor **200** can be used as a digital photo frame, a moving image reproducing device, or the like.

This embodiment can be combined with any of the other embodiments in this specification as appropriate.

Embodiment 3

In this embodiment, a structure of an input/output device that can be used for the information processor of one embodiment of the present invention will be described with reference to FIGS. **5A** to **5C**.

FIG. **5A** is a plan view illustrating the structure of an input/output device that can be used in the information processor of one embodiment of the present invention.

FIG. **5B** is a cross-sectional view taken along line A-B and line C-D in FIG. **5A**.

FIG. **5C** is a cross-sectional view taken along line E-F in FIG. **5A**.

<Plan View>

An input/output device **300** described as an example in this embodiment includes a display portion **301** (see FIG. **5A**).

The display portion **301** includes a plurality of pixels **302** and a plurality of imaging pixels **308**. The imaging pixels **308** can sense a touch of a finger or the like on the display portion **301**. Thus, a touch sensor can be formed using the imaging pixels **308**.

Each of the pixels **302** includes a plurality of sub-pixels (e.g., a sub-pixel **302R**). In addition, in the sub-pixels, light-emitting elements and pixel circuits that can supply electric power for driving the light-emitting elements are provided.

The pixel circuits are electrically connected to wirings through which selection signals are supplied and wirings through which image signals are supplied.

13

Furthermore, the input/output device **300** is provided with a scan line driver circuit **303g(1)** that can supply selection signals to the pixels **302** and an image signal line driver circuit **303s(1)** that can supply image signals to the pixels **302**.

The imaging pixels **308** include photoelectric conversion elements and imaging pixel circuits that drive the photoelectric conversion elements.

The imaging pixel circuits are electrically connected to wirings through which control signals are supplied and wirings through which power supply potentials are supplied.

Examples of the control signals include a signal for selecting an imaging pixel circuit from which a recorded imaging signal is read, a signal for initializing an imaging pixel circuit, and a signal for determining the time it takes for an imaging pixel circuit to detect light.

The input/output device **300** is provided with an imaging pixel driver circuit **303g(2)** that can supply control signals to the imaging pixels **308** and an imaging signal line driver circuit **303s(2)** that reads out imaging signals.

<Cross-Sectional View>

The input/output device **300** includes a substrate **310** and a counter substrate **370** that faces the substrate **310** (see FIG. 5B).

The substrate **310** is a stacked body in which a flexible substrate **310b**, a barrier film **310a** that prevents diffusion of unintentional impurities to the light-emitting elements, and an adhesive layer **310c** that attaches the barrier film **310a** to the substrate **310b** are stacked.

The substrate **310b** includes a substrate **310b(1)** provided with a plurality of electrodes **310Y**, a substrate **310b(2)** provided with a plurality of electrodes **310X**, and a flexible printed circuit (FPC **309(2)**) through which the plurality of electrodes **310Y** and the plurality of electrodes **310X** can supply signals (see FIGS. 5B and 5C).

The electrode **310Y** and the electrode **310X** are provided to intersect with each other, and a functional polymer **310p** is provided between the electrode **310Y** and the electrode **310X**.

The electrode **310Y**, the electrode **310X**, and the functional polymer **310p** provided between the electrode **310Y** and the electrode **310X** form a pressure sensor. Thus, pressure sensors are provided in a matrix to form a bend position sensor.

Note that a structure may be employed in which electrical resistance between the electrode **310Y** and the electrode **310X** is changed by deformation due to pressure. For example, a piezoelectric polymer can be used as the functional polymer **310p**. Specifically, the functional polymer **310p** is deformed by pressure and the contact area between the electrode **310Y** and the electrode **310X** is increased, whereby the electrical resistance is reduced.

The counter substrate **370** is a stacked body including a flexible substrate **370b**, a barrier film **370a** that prevents diffusion of unintentional impurities to the light-emitting elements, and an adhesive layer **370c** that attaches the barrier film **370a** to the substrate **370b** (see FIG. 5B).

A sealant **360** attaches the counter substrate **370** to the substrate **310**. The sealant **360**, also serving as an optical adhesive layer, has a refractive index higher than that of air. The pixel circuits and the light-emitting elements (e.g., a first light-emitting element **350R**) are provided between the substrate **310** and the counter substrate **370**.

<<Structure of Pixel>>

Each of the pixels **302** includes a sub-pixel **302R**, a sub-pixel **302G**, and a sub-pixel **302B** (see FIG. 5C). The sub-pixels **302R**, **302G**, and **302B** can, for example, emit red

14

light, green light, and blue light, respectively. The sub-pixel **302R** includes a light-emitting module **380R**, the sub-pixel **302G** includes a light-emitting module **380G**, and the sub-pixel **302B** includes a light-emitting module **380B**.

For example, the sub-pixel **302R** includes the first light-emitting element **350R** and the pixel circuit that can supply electric power to the first light-emitting element **350R** and includes a transistor **302t** (see FIG. 5B). Furthermore, the light-emitting module **380R** includes the first light-emitting element **350R** and an optical element (e.g., a first coloring layer **367R**). The first light-emitting element **350R** includes a first lower electrode **351R**, an upper electrode **352**, and a layer **353** containing a light-emitting organic compound between the first lower electrode **351R** and the upper electrode **352**.

The layer **353** containing a light-emitting organic compound includes a light-emitting unit **353a**, a light-emitting unit **353b**, and an intermediate layer **354** between the light-emitting units **353a** and **353b**.

The light-emitting module **380R** includes the first coloring layer **367R** on the counter substrate **370**. The coloring layer transmits light of a particular wavelength and is, for example, a layer that selectively transmits light of red, green, or blue color. A region that transmits light emitted from the light-emitting element as it is may be provided as well.

The light-emitting module **380R**, for example, includes the sealant **360** that also serves as an optical adhesive layer and is in contact with the first light-emitting element **350R** and the first coloring layer **367R**.

The first coloring layer **367R** is positioned in a region overlapping with the first light-emitting element **350R**. Accordingly, part of light emitted from the first light-emitting element **350R** passes through the sealant **360** that also serves as an optical adhesive layer and through the first coloring layer **367R** and is emitted to the outside of the light-emitting module **380R** as indicated by arrows in FIGS. 5B and 5C.

<<Structure of Display Panel>>

The input/output device **300** includes a light-blocking layer **367BM** on the counter substrate **370**. The light-blocking layer **367BM** is provided so as to surround the coloring layer (e.g., the first coloring layer **367R**).

The input/output device **300** includes an anti-reflective layer **367p** positioned in a region overlapping with the display portion **301**. As the anti-reflective layer **367p**, a circular polarizing plate can be used, for example.

The input/output device **300** includes an insulating film **321**. The insulating film **321** covers the transistor **302t**. Note that the insulating film **321** can be used as a layer for planarizing unevenness caused by the pixel circuits. An insulating film on which a layer that can prevent diffusion of impurities to the transistor **302t** and the like is stacked can be used as the insulating film **321**.

The input/output device **300** includes the light-emitting elements (e.g., the first light-emitting element **350R**) over the insulating film **321**.

The input/output device **300** includes, over the insulating film **321**, a partition wall **328** that overlaps with an end portion of the first lower electrode **351R** (see FIG. 5C). In addition, a spacer **329** that controls the distance between the substrate **310** and the counter substrate **370** is provided on the partition wall **328**.

<<Structure of Image Signal Line Driver Circuit>>

The image signal line driver circuit **303s(1)** includes a transistor **303t** and a capacitor **303c**. Note that the driver circuit can be formed in the same process and over the same substrate as those of the pixel circuits.

<<Structure of Imaging Pixel>>

The imaging pixels **308** each include a photoelectric conversion element **308p** and an imaging pixel circuit for sensing light received by the photoelectric conversion element **308p**. The imaging pixel circuit includes a transistor **308t**.

For example, a PIN photodiode can be used as the photoelectric conversion element **308p**.

<<Other Structures>>

The input/output device **300** includes a wiring **311** through which a signal can be supplied. The wiring **311** is provided with a terminal **319**. Note that an FPC **309(1)** through which a signal such as an image signal or a synchronization signal can be supplied is electrically connected to the terminal **319**.

Note that a printed wiring board (PWB) may be attached to the FPC **309(1)**.

This embodiment can be combined with any of the other embodiments in this specification as appropriate.

Embodiment 4

In this embodiment, a structure of a bendable touch panel that can be used in the information processor of one embodiment of the present invention will be described with reference to FIGS. 7A and 7B and FIGS. 8A to 8C.

FIGS. 7A and 7B are perspective views illustrating typical components of a touch panel of one embodiment of the present invention. FIG. 7A is a perspective view of a touch panel **400**, and FIG. 7B is a perspective view illustrating the components of the touch panel **400** in a separated state.

FIGS. 8A to 8C are cross-sectional views of the touch panel **400** taken along line X1-X2 in FIG. 7A.

The touch panel **400** includes a display portion **401** and a touch sensor **495** (see FIG. 7B). Furthermore, the touch panel **400** includes a substrate **410**, a substrate **470**, and a substrate **490**. Note that the substrate **410**, the substrate **470**, and the substrate **490** each have flexibility.

The display portion **401** includes the substrate **410**, a plurality of pixels over the substrate **410**, and a plurality of wirings **411** through which signals are supplied to the pixels. The plurality of wirings **411** is led to a peripheral portion of the substrate **410**, and part of the plurality of wirings **411** forms a terminal **419**. The terminal **419** is electrically connected to an FPC **409(1)**.

<Touch Sensor>

The substrate **490** includes the touch sensor **495** and a plurality of wirings **498** electrically connected to the touch sensor **495**. The plurality of wirings **498** is led to a peripheral portion of the substrate **490**, and part of the plurality of wirings **498** forms a terminal. The terminal is electrically connected to an FPC **409(2)**. Note that in FIG. 7B, electrodes, wirings, and the like of the touch sensor **495** provided on the back side of the substrate **490** (the side opposite to the viewer side) are indicated by solid lines for clarity.

As the touch sensor **495**, a capacitive touch sensor can be used. Examples of the capacitive touch sensor are a surface capacitive touch sensor and a projected capacitive touch sensor.

Examples of the projected capacitive touch sensor are a self capacitive touch sensor and a mutual capacitive touch sensor, which differ mainly in the driving method. The use of a mutual capacitive type is preferable because multiple points can be sensed simultaneously.

An example of using a projected capacitive touch sensor is described below with reference to FIG. 7B.

Note that a variety of sensors that can sense the closeness or the contact of a sensing target such as a finger, can be used.

The projected capacitive touch sensor **495** includes electrodes **491** and electrodes **492**. The electrodes **491** are electrically connected to any of the plurality of wirings **498**, and the electrodes **492** are electrically connected to any of the other wirings **498**.

The electrodes **492** each have a shape of a plurality of quadrangles arranged in one direction with one corner of a quadrangle connected to one corner of another quadrangle as illustrated in FIGS. 7A and 7B.

A plurality of electrodes **491** each have a quadrangular shape and are arranged in a direction intersecting with the direction in which the electrodes **492** extend.

A wiring **494** electrically connects two electrodes **491** between which the electrode **492** is positioned. The intersecting area of the electrode **492** and the wiring **494** is preferably as small as possible. Such a structure allows a reduction in the area of a region where the electrodes are not provided, reducing unevenness in transmittance. As a result, unevenness in luminance of light from the touch sensor **495** can be reduced.

Note that the shapes of the electrodes **491** and the electrodes **492** are not limited to the above-mentioned shapes and can be any of a variety of shapes. For example, the plurality of electrodes **491** may be provided so that space between the electrodes **491** are reduced as much as possible, and a plurality of electrodes **492** may be provided with an insulating layer sandwiched between the electrodes **491** and the electrodes **492** and may be spaced apart from each other to form a region not overlapping with the electrodes **491**. In that case, between two adjacent electrodes **492**, it is preferable to provide a dummy electrode which is electrically insulated from these electrodes, whereby the area of a region having a different transmittance can be reduced.

A structure of the touch sensor **495** will be described with reference to FIGS. 8A to 8C.

The touch sensor **495** includes the substrate **490**, the electrodes **491** and the electrodes **492** provided in a staggered arrangement on the substrate **490**, an insulating layer **493** covering the electrodes **491** and the electrodes **492**, and the wiring **494** that electrically connects the adjacent electrodes **491** to each other.

A resin layer **497** attaches the substrate **490** to the substrate **470** so that the touch sensor **495** overlaps with the display portion **401**.

The electrodes **491** and the electrodes **492** are formed using a light-transmitting conductive material. As a light-transmitting conductive material, a conductive oxide such as indium oxide, indium tin oxide, indium zinc oxide, zinc oxide, or zinc oxide to which gallium is added can be used. Note that a film including graphene may be used as well. The film including graphene can be formed, for example, by reducing a film containing graphene oxide. As a reducing method, a method with application of heat or the like can be employed.

The electrodes **491** and the electrodes **492** may be formed by depositing a light-transmitting conductive material on the substrate **490** by a sputtering method and then removing an unnecessary portion by any of various patterning techniques such as photolithography.

Examples of a material for the insulating layer **493** are a resin such as acrylic or epoxy resin, a resin having a siloxane bond, and an inorganic insulating material such as silicon oxide, silicon oxynitride, or aluminum oxide.

Furthermore, openings reaching the electrodes **491** are formed in the insulating layer **493**, and the wiring **494** electrically connects the adjacent electrodes **491**. A light-transmitting conductive material can be favorably used as the wiring **494** because the aperture ratio of the touch panel can be increased. Moreover, a material with higher conductivity than the conductivities of the electrodes **491** and **492** can be favorably used because electric resistance can be reduced.

One electrode **492** extends in one direction, and a plurality of electrodes **492** is provided in the form of stripes.

The wiring **494** intersects with the electrode **492**.

Adjacent electrodes **491** are provided with one electrode **492** provided therebetween. The wiring **494** electrically connects the adjacent electrodes **491**.

Note that the plurality of electrodes **491** is not necessarily arranged in the direction orthogonal to one electrode **492** and may be arranged to intersect with one electrode **492** at an angle of less than 90 degrees.

One wiring **498** is electrically connected to any of the electrodes **491** and **492**. Part of the wiring **498** serves as a terminal. For the wiring **498**, a metal material such as aluminum, gold, platinum, silver, nickel, titanium, tungsten, chromium, molybdenum, iron, cobalt, copper, or palladium or an alloy material containing any of these metal materials can be used.

Note that an insulating layer that covers the insulating layer **493** and the wiring **494** may be provided to protect the touch sensor **495**.

Furthermore, a connection layer **499** electrically connects the wiring **498** to the FPC **409(2)**.

As the connection layer **499**, any of various anisotropic conductive films (ACF), anisotropic conductive pastes (ACP), or the like can be used.

The resin layer **497** has a light-transmitting property. For example, a thermosetting resin or an ultraviolet curable resin can be used; specifically, a resin such as acrylic, urethane, epoxy resin, or a resin having a siloxane bond can be used.

<Display Portion>

The display portion **401** includes a plurality of pixels arranged in a matrix. Each of the pixels includes a display element and a pixel circuit for driving the display element.

In this embodiment, an example of using an organic electroluminescent element that emits white light as a display element will be described; however, the display element is not limited to such element.

For example, organic electroluminescent elements that emit light of different colors may be included in sub-pixels so that the light of different colors can be emitted from the respective sub-pixels.

Other than organic electroluminescent elements, any of various display elements such as display elements (electronic ink) that perform display by an electrophoretic method, an electronic liquid powder method, an electrowetting method, or the like; MEMS shutter display elements; optical interference type MEMS display elements; and liquid crystal elements can be used. Furthermore, this embodiment can be used in a transmissive liquid crystal display, a transmissive liquid crystal display, a reflective liquid crystal display, a direct-view liquid crystal display, or the like. In the case of a transmissive liquid crystal display or a reflective liquid crystal display, some of or all of pixel electrodes function as reflective electrodes. For example, some or all of pixel electrodes are formed to contain aluminum, silver, or the like. In such a case, a memory circuit such as an SRAM can be provided under the reflective electrodes, leading to

lower power consumption. A structure suitable for employed display elements can be selected from among a variety of structures of pixel circuits.

In the display portion, an active matrix method in which an active element is included in a pixel or a passive matrix method in which an active element is not included in a pixel can be used.

In an active matrix method, as an active element (a non-linear element), not only a transistor but also various active elements (non-linear elements) can be used. For example, an MIM (metal insulator metal), a TFD (thin film diode), or the like can also be used. Since these elements can be formed with a smaller number of manufacturing steps, manufacturing cost can be reduced or yield can be improved. Furthermore, since the size of these elements is small, the aperture ratio can be improved, so that power consumption can be reduced or higher luminance can be achieved.

As a method other than an active matrix method, a passive matrix method in which an active element (a non-linear element) is not used can also be used. Since an active element (a non-linear element) is not used, the number of manufacturing steps is small, so that manufacturing cost can be reduced or yield can be improved. Furthermore, since an active element (a non-linear element) is not used, the aperture ratio can be improved, so that power consumption can be reduced or higher luminance can be achieved, for example.

Flexible materials can be favorably used for the substrate **410** and the substrate **470**. Materials with which unintended passage of impurities is inhibited can be favorably used for the substrate **410** and the substrate **470**. For example, materials with a vapor permeability of lower than or equal to 10^{-5} g/m²-day, preferably lower than or equal to 10^{-6} g/m²-day can be favorably used.

The substrate **410** can be favorably formed using a material whose coefficient of linear expansion is substantially equal to that of the substrate **470**. For example, the coefficient of linear expansion of the materials are preferably lower than or equal to 1×10^{-3} /K, further preferably lower than or equal to 5×10^{-5} /K, and still further preferably lower than or equal to 1×10^{-5} /K.

The substrate **410** is a stacked body in which a flexible substrate **410b**, a barrier film **410a** that prevents diffusion of unintentional impurities to light-emitting elements, and a resin layer **410c** that attaches the barrier film **410a** to the substrate **410b** are stacked.

For example, materials that include polyester, polyolefin, polyamide (e.g., nylon, aramid), polyimide, polycarbonate, acrylic, urethane, epoxy resin, or a resin having a siloxane bond can be used for the resin layer **410c**.

The substrate **470** is a stacked body in which a flexible substrate **470b**, a barrier film **470a** that prevents diffusion of unintentional impurities to the light-emitting elements, and a resin layer **470c** that attaches the barrier film **470a** to the substrate **470b** are stacked.

A sealant **460** attaches the substrate **470** to the substrate **410**. The sealant **460** has a refractive index higher than that of air. In the case of extracting light to the sealant **460** side, the sealant **460** serves as an optical adhesive layer. The pixel circuits and the light-emitting elements (e.g., a first light-emitting element **450R**) are provided between the substrate **410** and the substrate **470**.

<<Structure of Pixel>>

A pixel includes a sub-pixel **402R**, and the sub-pixel **402R** includes a light-emitting module **480R**.

The sub-pixel **402R** includes the first light-emitting element **450R** and the pixel circuit that can supply electric

power to the first light-emitting element **450R** and includes a transistor **402t**. Furthermore, the light-emitting module **480R** includes the first light-emitting element **450R** and an optical element (e.g., a first coloring layer **467R**).

The first light-emitting element **450R** includes a lower electrode, an upper electrode, and a layer containing a light-emitting organic compound between the lower electrode and the upper electrode.

The light-emitting module **480R** includes the first coloring layer **467R** on the light extraction side. The coloring layer transmits light of a particular wavelength and is, for example, a layer that selectively transmits light of red, green, or blue color. Note that in another sub-pixel, a region that transmits light emitted from the light-emitting element as it is may be provided as well.

In the case where the sealant **460** is provided on the light extraction side, the sealant **460** is in contact with the first light-emitting element **450R** and the first coloring layer **467R**.

The first coloring layer **467R** is positioned in a region overlapping with the first light-emitting element **450R**. Accordingly, part of light emitted from the first light-emitting element **450R** passes through the first coloring layer **467R** and is emitted to the outside of the light-emitting module **480R** as indicated by an arrow in FIG. **8A**.

<<Structure of Display Portion>>

The display portion **401** includes a light-blocking layer **467BM** on the light extraction side. The light-blocking layer **467BM** is provided so as to surround the coloring layer (e.g., the first coloring layer **467R**).

The display portion **401** includes an anti-reflective layer **467p** positioned in a region overlapping with pixels. As the anti-reflective layer **467p**, a circular polarizing plate can be used, for example.

The display portion **401** includes an insulating film **421**. The insulating film **421** covers the transistor **402t**. Note that the insulating film **421** can be used as a layer for planarizing unevenness caused by the pixel circuits. A stacked film including a layer that can prevent diffusion of impurities can be used as the insulating film **421**. This can prevent the reliability of the transistor **402t** or the like from being lowered by diffusion of unintentional impurities.

The display portion **401** includes the light-emitting elements (e.g., the first light-emitting element **450R**) over the insulating film **421**.

The display portion **401** includes, over the insulating film **421**, a partition wall **428** that overlaps with an end portion of the lower electrode. In addition, a spacer that controls the distance between the substrate **410** and the substrate **470** is provided on the partition wall **428**.

<<Structure of Scan Line Driver Circuit>>

A scan line driver circuit **403g(1)** includes a transistor **403t** and a capacitor **403c**. Note that the driver circuit can be formed in the same process and over the same substrate as those of the pixel circuits.

<<Other Structures>>

The display portion **401** includes the wirings **411** through which signals can be supplied. The wirings **411** are provided with the terminal **419**. Note that the FPC **409(1)** through which a signal such as an image signal or a synchronization signal can be supplied is electrically connected to the terminal **419**.

Note that a printed wiring board (PWB) may be attached to the FPC **409(1)**.

The display portion **401** includes wirings such as scan lines, signal lines, and power supply lines. Any of various conductive films can be used as the wirings.

Specifically, a metal element selected from aluminum, chromium, copper, tantalum, titanium, molybdenum, tungsten, nickel, yttrium, zirconium, silver, and manganese; an alloy including any of the above-described metal elements; an alloy including any of the above-described metal elements in combination; or the like can be used. In particular, one or more elements selected from aluminum, chromium, copper, tantalum, titanium, molybdenum, and tungsten are preferably included. In particular, an alloy of copper and manganese is suitably used in microfabrication with the use of a wet etching method.

Specifically, a two-layer structure in which a titanium film is stacked over an aluminum film, a two-layer structure in which a titanium film is stacked over a titanium nitride film, a two-layer structure in which a tungsten film is stacked over a titanium nitride film, a two-layer structure in which a tungsten film is stacked over a tantalum nitride film or a tungsten nitride film, a three-layer structure in which a titanium film, an aluminum film, and a titanium film are stacked in this order, or the like can be used.

Specifically, a stacked structure in which a film of an element selected from titanium, tantalum, tungsten, molybdenum, chromium, neodymium, and scandium, an alloy film including some of these elements, or a nitride film of any of these elements is stacked over an aluminum film can be used.

Alternatively, a light-transmitting conductive material including indium oxide, tin oxide, or zinc oxide may be used.

Modification Example 1 of Display Portion

Any of various kinds of transistors can be used in the display portion **401**.

A structure in the case of using bottom-gate transistors in the display portion **401** is illustrated in FIGS. **8A** and **8B**.

For example, a semiconductor layer containing an oxide semiconductor, amorphous silicon, or the like can be used in the transistor **402t** and the transistor **403t** illustrated in FIG. **8A**. For example, a film represented by an In-M-Zn oxide that contains at least indium (In), zinc (Zn), and M (M is a metal such as Al, Ga, Ge, Y, Zr, Sn, La, Ce, or Hf) is preferably included. Alternatively, both In and Zn are preferably contained.

As a stabilizer, gallium (Ga), tin (Sn), hafnium (Hf), aluminum (Al), zirconium (Zr), or the like can be used. As another stabilizer, lanthanoid such as lanthanum (La), cerium (Ce), praseodymium (Pr), neodymium (Nd), samarium (Sm), europium (Eu), gadolinium (Gd), terbium (Tb), dysprosium (Dy), holmium (Ho), erbium (Er), thulium (Tm), ytterbium (Yb), or lutetium (Lu) can be used.

As an oxide semiconductor included in an oxide semiconductor film, any of the followings can be used, for example: an In—Ga—Zn-based oxide, an In—Al—Zn-based oxide, an In—Sn—Zn-based oxide, an In—Hf—Zn-based oxide, an In—La—Zn-based oxide, an In—Ce—Zn-based oxide, an In—Pr—Zn-based oxide, an In—Nd—Zn-based oxide, an In—Sm—Zn-based oxide, an In—Eu—Zn-based oxide, an In—Gd—Zn-based oxide, an In—Tb—Zn-based oxide, an In—Dy—Zn-based oxide, an In—Ho—Zn-based oxide, an In—Er—Zn-based oxide, an In—Tm—Zn-based oxide, an In—Yb—Zn-based oxide, an In—Lu—Zn-based oxide, an In—Sn—Ga—Zn-based oxide, an In—Hf—Ga—Zn-based oxide, an In—Al—Ga—Zn-based oxide, an In—Sn—Al—Zn-based oxide, an In—Sn—Hf—Zn-based oxide, an In—Hf—Al—Zn-based oxide, and an In—Ga-based oxide.

21

Note that here, for example, an “In—Ga—Zn-based oxide” means an oxide containing In, Ga, and Zn as its main components and there is no limitation on the ratio of In:Ga:Zn. The In—Ga—Zn oxide may contain another metal element in addition to In, Ga, and Zn.

For example, a semiconductor layer containing polycrystalline silicon that is obtained by crystallization process such as laser annealing can be used in the transistor **402t** and the transistor **403t** illustrated in FIG. **8B**.

A structure in the case of using top-gate transistors in the display portion **401** is illustrated in FIG. **8C**.

For example, a semiconductor layer including a polycrystalline silicon film, a single crystal silicon film that is transferred from a single crystal silicon substrate, or the like can be used in the transistor **402t** and the transistor **403t** illustrated in FIG. **8C**.

This embodiment can be combined with any of the other embodiments in this specification as appropriate.

Embodiment 5

In this embodiment, a structure of a bendable touch panel that can be used in the information processor of one embodiment of the present invention will be described with reference to FIGS. **9A** to **9C**.

FIGS. **9A** to **9C** are cross-sectional views illustrating a structure of a touch panel **400B**.

The touch panel **400B** described in this embodiment differs from the touch panel **400** described in Embodiment 4 in that the display portion **401** displays received image data on the side where the transistors are provided and that the touch sensor is provided on the substrate **410** side of the display portion. Different structures will be described in detail below, and the above description is referred to for the other similar structures.

<Display Portion>

The display portion **401** includes a plurality of pixels arranged in a matrix. Each of the pixels includes a display element and a pixel circuit for driving the display element. <Structure of Pixel>

A pixel includes the sub-pixel **402R**, and the sub-pixel **402R** includes the light-emitting module **480R**.

The sub-pixel **402R** includes the first light-emitting element **450R** and the pixel circuit that can supply electric power to the first light-emitting element **450R** and includes the transistor **402t**.

The light-emitting module **480R** includes the first light-emitting element **450R** and an optical element (e.g., the first coloring layer **467R**).

The first light-emitting element **450R** includes a lower electrode, an upper electrode, and a layer containing a light-emitting organic compound between the lower electrode and the upper electrode.

The light-emitting module **480R** includes the first coloring layer **467R** on the light extraction side. The coloring layer transmits light of a particular wavelength and is, for example, a layer that selectively transmits light of red, green, or blue color. Note that in another sub-pixel, a region that transmits light emitted from the light-emitting element as it is may be provided as well.

The first coloring layer **467R** is positioned in a region overlapping with the first light-emitting element **450R**. The first light-emitting element **450R** illustrated in FIG. **9A** emits light to the side where the transistor **402t** is provided. Accordingly, part of light emitted from the first light-emitting element **450R** passes through the first coloring

22

layer **467R** and is emitted to the outside of the light-emitting module **480R** as indicated by an arrow in FIG. **9A**.

<<Structure of Display Portion>>

The display portion **401** includes the light-blocking layer **467BM** on the light extraction side. The light-blocking layer **467BM** is provided so as to surround the coloring layer (e.g., the first coloring layer **467R**).

The display portion **401** includes the insulating film **421**. The insulating film **421** covers the transistor **402t**. Note that the insulating film **421** can be used as a layer for planarizing unevenness caused by the pixel circuits. A stacked film including a layer that can prevent diffusion of impurities can be used as the insulating film **421**. This can prevent reliability of the transistor **402t** or the like from being lowered by diffusion of unintentional impurities from the first coloring layer **467R**.

<Touch Sensor>

The touch sensor **495** is provided on the substrate **410** side of the display portion **401** (see FIG. **9A**).

The resin layer **497** is provided between the substrate **410** and the substrate **490** and attaches the touch sensor **495** to the display portion **401**.

Modification Example 1 of Display Portion

Any of various kinds of transistors can be used in the display portion **401**.

A structure in the case of using bottom-gate transistors in the display portion **401** is illustrated in FIGS. **9A** and **9B**.

For example, a semiconductor layer containing an oxide semiconductor, amorphous silicon, or the like can be used in the transistor **402t** and the transistor **403t** illustrated in FIG. **9A**. In the transistors, a channel formation region may be sandwiched between upper and lower gate electrodes, in which case variations in characteristics of the transistors can be prevented and thus the reliability can be increased.

For example, a semiconductor layer containing polycrystalline silicon or the like can be used in the transistor **402t** and the transistor **403t** illustrated in FIG. **9B**.

A structure in the case of using top-gate transistors in the display portion **401** is illustrated in FIG. **9C**.

For example, a semiconductor layer including a polycrystalline silicon film, a transferred single crystal silicon film, or the like can be used in the transistor **402t** and the transistor **403t** illustrated in FIG. **9C**.

This embodiment can be combined with any of the other embodiments in this specification as appropriate.

EXPLANATION OF REFERENCE

100: information processor, **100F**: broken line, **100S**: acceleration sensor, **110**: arithmetic device, **111**: arithmetic unit, **112**: storage unit, **114**: transmission path, **115**: input/output interface, **120**: input/output device, **121**: input unit, **122**: display unit, **122(a)**: first region, **122(b)**: second region, **123**: position sensor, **200**: information processor, **200F**: position, **210**: arithmetic device, **220**: input/output device, **222**: display unit, **222(a)**: first region, **222(b)**: second region, **281**: bending member, **282**: hinge component, **300**: input/output device, **301**: display portion, **302**: pixel, **302B**: sub-pixel, **302G**: sub-pixel, **302R**: sub-pixel, **302t**: transistor, **303c**: capacitor, **303g(1)**: scan line driver circuit, **303g(2)**: imaging pixel driver circuit, **303s(1)**: image signal line driver circuit, **303s(2)**: imaging signal line driver circuit, **303t**: transistor, **308**: imaging pixel, **308p**: photoelectric conversion element, **308t**: transis-

23

tor, 309: FPC, 310: substrate, 310a: barrier film, 310b: substrate, 310c: adhesive layer, 310p: functional polymer, 310X: electrode, 310Y: electrode, 311: wiring, 319: terminal, 321: insulating film, 328: partition wall, 329: spacer, 350R: light-emitting element, 351R: lower electrode, 352: upper electrode, 353: layer containing a light-emitting organic compound, 353a: light-emitting unit, 353b: light-emitting unit, 354: intermediate layer, 360: sealant, 367BM: light-blocking layer, 367p: anti-reflective layer, 367R: coloring layer, 370: counter substrate, 370a: barrier film, 370b: substrate, 370c: adhesive layer, 380B: light-emitting module, 380G: light-emitting module, 380R: light-emitting module, 400: touch panel, 400B: touch panel, 401: display portion, 402R: sub-pixel, 402t: transistor, 403c: capacitor, 403g: scan line driver circuit, 403t: transistor, 409: FPC, 410: substrate, 410a: barrier film, 410b: substrate, 410c: resin layer, 411: wiring, 419: terminal, 421: insulating film, 428: partition wall, 450R: light-emitting element, 460: sealant, 467BM: light-blocking layer, 467p: anti-reflective layer, 467R: coloring layer, 470: substrate, 470a: barrier film, 470b: substrate, 470c: resin layer, 480R: light-emitting module, 490: substrate, 491: electrode, 492: electrode, 493: insulating layer, 494: wiring, 495: touch sensor, 497: resin layer, 498: wiring, 499: connection layer, C: center, E: edge closer to the center, F: bend position.

This application is based on Japanese Patent Application serial no. 2013-120654 filed with Japan Patent Office on Jun. 7, 2013, the entire contents of which are hereby incorporated by reference.

The invention claimed is:

1. A semiconductor device comprising:

a bendable touch panel, the bendable touch panel comprising:
a display portion;
a touch sensor overlapping with the display portion;
and
a bending member comprising a plurality of hinge components,

wherein a barrier film is provided over a resin layer,

wherein a first conductive film, a second conductive film, and a third conductive film are provided over the barrier film,

wherein the first conductive film comprises a region configured to function as a first gate electrode of a first transistor,

wherein the second conductive film comprises a region configured to function as a first electrode of a first capacitor,

wherein the third conductive film comprises a region configured to function as a second gate electrode of a second transistor,

wherein a first insulating film is provided over the first conductive film, the second conductive film, and the third conductive film,

wherein a first semiconductor layer is provided over the first insulating film,

wherein the first semiconductor layer comprises a region configured to function as a first channel formation region of the first transistor,

wherein a fourth conductive film is provided over and in contact with the first semiconductor layer,

wherein a fifth conductive film is provided over and overlapping with the second conductive film,

24

wherein the fourth conductive film comprises a region configured to function as one of a source electrode and a drain electrode of the first transistor,

wherein the fifth conductive film comprises a region configured to function as a second electrode of the first capacitor,

wherein a second insulating film is provided over the fourth conductive film and the fifth conductive film,

wherein a sixth conductive film is provided over the second insulating film,

wherein the sixth conductive film overlaps with the first semiconductor layer, the first conductive film, and the fourth conductive film,

wherein a third insulating film is provided over the sixth conductive film,

wherein a seventh conductive film is provided over the third insulating film,

wherein the seventh conductive film comprises a region configured to function as a first electrode of a light-emitting element,

wherein the bendable touch panel is supported by the bending member,

wherein the display portion comprises a first region, a second region, and a third region,

wherein, in a bent state, the first region and the second region overlap with each other with the third region provided therebetween,

wherein, in the bent state, the third region is bent, and

wherein the semiconductor device is configured to display an image seamlessly in the first to third regions, when the display portion is in a non-bent state.

2. The semiconductor device according to claim 1, wherein an area of a first hinge component of the plurality of hinge components which is provided at one end of the plurality of hinge components is larger than an area of a second hinge component of the plurality of hinge components provided in the third region.

3. The semiconductor device according to claim 1,

wherein a space is present between each of the plurality of hinge components,

wherein the plurality of hinge components comprises 3 or more hinge components,

wherein a first hinge component of the plurality of hinge components overlaps with the first region,

wherein a second hinge component of the plurality of hinge components overlaps with the second region, and wherein a third hinge component of the plurality of hinge components overlaps with the third region.

4. The semiconductor device according to claim 1,

wherein the plurality of hinge components comprises 5 or more hinge components.

5. The semiconductor device according to claim 4,

wherein the 5 or more hinge components are connected to each other, and

wherein the 5 or more hinge components are configured to bend in a same direction.

6. A semiconductor device comprising:

a bendable touch panel, the bendable touch panel comprising:

a display portion;

a touch sensor overlapping with the display portion;

and

a bending member comprising a plurality of hinge components,

wherein a resin layer is provided over a flexible substrate,

wherein a barrier film is provided over the resin layer,

25

wherein a first conductive film, a second conductive film, and a third conductive film are provided over the barrier film,
 wherein the first conductive film comprises a region configured to function as a first gate electrode of a first transistor, 5
 wherein the second conductive film comprises a region configured to function as a first electrode of a first capacitor,
 wherein the third conductive film comprises a region configured to function as a second gate electrode of a second transistor, 10
 wherein a first insulating film is provided over the first conductive film, the second conductive film, and the third conductive film, 15
 wherein a first semiconductor layer is provided over the first insulating film,
 wherein the first semiconductor layer comprises a region configured to function as a first channel formation region of the first transistor, 20
 wherein a fourth conductive film is provided over and in contact with the first semiconductor layer,
 wherein a fifth conductive film is provided over and overlapping with the second conductive film, 25
 wherein the fourth conductive film comprises a region configured to function as one of a source electrode and a drain electrode of the first transistor,
 wherein the fifth conductive film comprises a region configured to function as a second electrode of the first capacitor, 30
 wherein a second insulating film is provided over the fourth conductive film and the fifth conductive film,
 wherein a sixth conductive film is provided over the second insulating film, 35
 wherein a third insulating film is provided over the sixth conductive film,
 wherein a seventh conductive film is provided over the third insulating film, 40
 wherein the seventh conductive film comprises a region configured to function as a first electrode of a light-emitting element,
 wherein the bendable touch panel is supported by the bending member, 45
 wherein the display portion comprises a first region, a second region, and a third region,
 wherein, in a bent state, the first region and the second region overlap with each other with the third region provided therebetween, 50
 wherein, in the bent state, the third region is bent, and wherein the semiconductor device is configured to display an image seamlessly in the first to third regions, when the display portion is in a non-bent state.

7. The semiconductor device according to claim 6, 55
 wherein an area of a first hinge component of the plurality of hinge components which is provided at one end of the plurality of hinge components is larger than an area of a second hinge component of the plurality of hinge components provided in the third region. 60

8. The semiconductor device according to claim 6,
 wherein a space is present between each of the plurality of hinge components,
 wherein the plurality of hinge components comprises 3 or more hinge components,
 wherein a first hinge component of the plurality of hinge components overlaps with the first region, 65

26

wherein a second hinge component of the plurality of hinge components overlaps with the second region, and wherein a third hinge component of the plurality of hinge components overlaps with the third region.

9. The semiconductor device according to claim 6,
 wherein the plurality of hinge components comprises 5 or more hinge components.

10. The semiconductor device according to claim 9,
 wherein the 5 or more hinge components are connected to each other, and
 wherein the 5 or more hinge components are configured to bend in a same direction.

11. A semiconductor device comprising:
 a bendable touch panel, the bendable touch panel comprising:
 a display portion;
 a touch sensor overlapping with the display portion; and
 a bending member comprising a plurality of hinge components,
 wherein a barrier film is provided over a resin layer,
 wherein a first conductive film, a second conductive film, and a third conductive film are provided over the barrier film,
 wherein the first conductive film comprises a region configured to function as a first gate electrode of a first transistor,
 wherein the second conductive film comprises a region configured to function as a first electrode of a first capacitor,
 wherein the third conductive film comprises a region configured to function as a second gate electrode of a second transistor,
 wherein a first insulating film is provided over the first conductive film, the second conductive film, and the third conductive film,
 wherein a first semiconductor layer is provided over the first insulating film,
 wherein the first semiconductor layer comprises a region configured to function as a first channel formation region of the first transistor,
 wherein a fourth conductive film is provided over and in contact with the first semiconductor layer,
 wherein a fifth conductive film is provided over and overlapping with the second conductive film,
 wherein the fourth conductive film comprises a region configured to function as one of a source electrode and a drain electrode of the first transistor,
 wherein the fifth conductive film comprises a region configured to function as a second electrode of the first capacitor,
 wherein the bendable touch panel is supported by the bending member,
 wherein the display portion comprises a first region, a second region, and a third region,
 wherein, in a bent state, the first region and the second region overlap with each other with the third region provided therebetween,
 wherein, in the bent state, the third region is bent, and wherein the semiconductor device is configured to display an image seamlessly in the first to third regions, when the display portion is in a non-bent state.

12. The semiconductor device according to claim 11,
 wherein an area of a first hinge component of the plurality of hinge components which is provided at one end of the plurality of hinge components is larger than an area of a

second hinge component of the plurality of hinge components provided in the third region.

13. The semiconductor device according to claim **11**, wherein a space is present between each of the plurality of hinge components, 5
wherein the plurality of hinge components comprises 3 or more hinge components,
wherein a first hinge component of the plurality of hinge components overlaps with the first region,
wherein a second hinge component of the plurality of 10
hinge components overlaps with the second region, and
wherein a third hinge component of the plurality of hinge components overlaps with the third region.

14. The semiconductor device according to claim **11**, wherein the plurality of hinge components comprises 5 or 15
more hinge components.

15. The semiconductor device according to claim **14**, wherein the 5 or more hinge components are connected to each other, and
wherein the 5 or more hinge components are configured 20
to bend in a same direction.

* * * * *