

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12400389
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Al Majid; Newar Husam et al.

Animated expressive icon

Abstract

Embodiments described herein include an expressive icon system to present an animated graphical icon, wherein the animated graphical icon is generated by capture facial tracking data at a client device. In some embodiments, the system may track and capture facial tracking data of a user via a camera associated with a client device (e.g., a front facing camera, or a paired camera), and process the facial tracking data to animate a graphical icon.

Inventors: Al Majid; Newar Husam (New York, NY), Boyd; Nathan Kenneth (Los Angeles, CA), Chang; Sheldon (Venice, CA), Samaranayake; Chamal (Venice, CA), Voss; Jeremy (Los Angeles, CA)

Applicant: Snap Inc. (Santa Monica, CA)

Family ID: 1000008781889

Assignee: Snap Inc. (Santa Monica, CA)

Appl. No.: 18/541369

Filed: December 15, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240119652 A1	Apr. 11, 2024

Related U.S. Application Data

continuation parent-doc US 18184283 20230315 US 11880923 child-doc US 18541369
continuation parent-doc US 17864152 20220713 US 11688119 child-doc US 18184283
continuation parent-doc US 17376457 20210715 US 11468618 child-doc US 17864152
continuation parent-doc US 16946463 20200623 US 11120601 child-doc US 17376457
continuation parent-doc US 15908422 20180228 US 10726603 child-doc US 16946463

Publication Classification

Int. Cl.: **G06T13/40** (20110101); **G06F3/04817** (20220101); **G06V40/16** (20220101);
H04L67/306 (20220101); **H04M1/72427** (20210101); **H04M1/7243** (20210101);
H04M1/72469 (20210101)

U.S. Cl.:

CPC **G06T13/40** (20130101); **G06F3/04817** (20130101); **G06V40/161** (20220101);
G06V40/168 (20220101); **G06V40/171** (20220101); **H04L67/306** (20130101);
H04M1/72427 (20210101); **H04M1/7243** (20210101); **H04M1/72469** (20210101);
H04M2201/42 (20130101)

Field of Classification Search

CPC: **G06T** (13/40); **H04M** (1/72469); **H04M** (1/72427); **H04M** (1/7243); **H04M** (2201/42);
G06V (40/168); **G06V** (40/171); **G06V** (40/161); **G06F** (3/04817); **H04L** (67/306)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5754939	12/1997	Herz et al.	N/A	N/A
5880731	12/1998	Liles et al.	N/A	N/A
6023270	12/1999	Brush, II et al.	N/A	N/A
6038295	12/1999	Mattes	N/A	N/A
6158044	12/1999	Tibbetts	N/A	N/A
6167435	12/1999	Druckenmiller et al.	N/A	N/A
6205432	12/2000	Gabbard et al.	N/A	N/A
6223165	12/2000	Lauffer	N/A	N/A
6310694	12/2000	Okimoto et al.	N/A	N/A
6484196	12/2001	Maurille	N/A	N/A
6487586	12/2001	Ogilvie et al.	N/A	N/A
6665531	12/2002	Soderbacka et al.	N/A	N/A
6701347	12/2003	Ogilvie	N/A	N/A
6711608	12/2003	Ogilvie	N/A	N/A
6757713	12/2003	Ogilvie et al.	N/A	N/A
6772195	12/2003	Hatlelid et al.	N/A	N/A
6842779	12/2004	Nishizawa	N/A	N/A
6980909	12/2004	Root et al.	N/A	N/A
6990452	12/2005	Ostermann et al.	N/A	N/A
7124164	12/2005	Chemtob	N/A	N/A
7149893	12/2005	Leonard et al.	N/A	N/A
7173651	12/2006	Knowles	N/A	N/A
7243163	12/2006	Friend et al.	N/A	N/A
7278168	12/2006	Chaudhury et al.	N/A	N/A
7342587	12/2007	Danzig et al.	N/A	N/A
7356564	12/2007	Hartselle et al.	N/A	N/A

7376715	12/2007	Cunningham et al.	N/A	N/A
7411493	12/2007	Smith	N/A	N/A
7468729	12/2007	Levinson	N/A	N/A
7478402	12/2008	Christensen et al.	N/A	N/A
7496347	12/2008	Puranik	N/A	N/A
7519670	12/2008	Hagale et al.	N/A	N/A
7535890	12/2008	Rojas	N/A	N/A
7607096	12/2008	Oreizy et al.	N/A	N/A
7636755	12/2008	Blattner et al.	N/A	N/A
7639251	12/2008	Gu et al.	N/A	N/A
7703140	12/2009	Nath et al.	N/A	N/A
7775885	12/2009	Van et al.	N/A	N/A
7859551	12/2009	Bulman et al.	N/A	N/A
7885931	12/2010	Seo et al.	N/A	N/A
7912896	12/2010	Wolovitz et al.	N/A	N/A
7925703	12/2010	Dinan et al.	N/A	N/A
8088044	12/2011	Tchao et al.	N/A	N/A
8095878	12/2011	Bates et al.	N/A	N/A
8108774	12/2011	Finn et al.	N/A	N/A
8117281	12/2011	Robinson et al.	N/A	N/A
8130219	12/2011	Fleury et al.	N/A	N/A
8131597	12/2011	Hudetz	N/A	N/A
8146005	12/2011	Jones et al.	N/A	N/A
8151191	12/2011	Nicol	N/A	N/A
8170957	12/2011	Richard	N/A	N/A
8199747	12/2011	Rojas et al.	N/A	N/A
8212821	12/2011	Kopylov	345/473	G06T 13/80
8214443	12/2011	Hamburg	N/A	N/A
8238947	12/2011	Lottin et al.	N/A	N/A
8244593	12/2011	Klinger et al.	N/A	N/A
8312097	12/2011	Siegel et al.	N/A	N/A
8332475	12/2011	Rosen et al.	N/A	N/A
8384719	12/2012	Reville et al.	N/A	N/A
RE44054	12/2012	Kim	N/A	N/A
8396708	12/2012	Park et al.	N/A	N/A
8425322	12/2012	Gillo et al.	N/A	N/A
8458601	12/2012	Castelli et al.	N/A	N/A
8462198	12/2012	Lin et al.	N/A	N/A
8484158	12/2012	Deluca et al.	N/A	N/A
8495503	12/2012	Brown et al.	N/A	N/A
8495505	12/2012	Smith et al.	N/A	N/A
8504926	12/2012	Wolf	N/A	N/A
8559980	12/2012	Pujol	N/A	N/A
8564621	12/2012	Branson et al.	N/A	N/A
8564710	12/2012	Nonaka et al.	N/A	N/A
8570907	12/2012	Garcia, Jr. et al.	N/A	N/A
8581911	12/2012	Becker et al.	N/A	N/A
8597121	12/2012	del Valle	N/A	N/A
8601051	12/2012	Wang	N/A	N/A
8601379	12/2012	Marks et al.	N/A	N/A

8632408	12/2013	Gillo et al.	N/A	N/A
8648865	12/2013	Dawson et al.	N/A	N/A
8659548	12/2013	Hildreth	N/A	N/A
8683354	12/2013	Khandelwal et al.	N/A	N/A
8692830	12/2013	Nelson et al.	N/A	N/A
8718333	12/2013	Wolf et al.	N/A	N/A
8724622	12/2013	Rojas	N/A	N/A
8745132	12/2013	Obradovich	N/A	N/A
8810513	12/2013	Ptucha et al.	N/A	N/A
8812171	12/2013	Filev et al.	N/A	N/A
8832201	12/2013	Wall	N/A	N/A
8832552	12/2013	Arrasvuori et al.	N/A	N/A
8839327	12/2013	Amento et al.	N/A	N/A
8874677	12/2013	Rosen et al.	N/A	N/A
8890926	12/2013	Tandon et al.	N/A	N/A
8892999	12/2013	Nims et al.	N/A	N/A
8909679	12/2013	Root et al.	N/A	N/A
8909714	12/2013	Agarwal et al.	N/A	N/A
8909725	12/2013	Sehn	N/A	N/A
8914752	12/2013	Spiegel	N/A	N/A
8924250	12/2013	Bates et al.	N/A	N/A
8963926	12/2014	Brown et al.	N/A	N/A
8989786	12/2014	Feghali	N/A	N/A
8995433	12/2014	Rojas	N/A	N/A
9040574	12/2014	Wang et al.	N/A	N/A
9055416	12/2014	Rosen et al.	N/A	N/A
9083770	12/2014	Drose et al.	N/A	N/A
9086776	12/2014	Ye et al.	N/A	N/A
9094137	12/2014	Sehn et al.	N/A	N/A
9100806	12/2014	Rosen et al.	N/A	N/A
9100807	12/2014	Rosen et al.	N/A	N/A
9105014	12/2014	Collet et al.	N/A	N/A
9113301	12/2014	Spiegel et al.	N/A	N/A
9148424	12/2014	Yang	N/A	N/A
9191776	12/2014	Root et al.	N/A	N/A
9204252	12/2014	Root	N/A	N/A
9225805	12/2014	Kujawa et al.	N/A	N/A
9225897	12/2014	Sehn et al.	N/A	N/A
9237202	12/2015	Sehn	N/A	N/A
9241184	12/2015	Weerasinghe	N/A	N/A
9256860	12/2015	Herger et al.	N/A	N/A
9264463	12/2015	Rubinstein et al.	N/A	N/A
9276886	12/2015	Samaranayake	N/A	N/A
9294425	12/2015	Son	N/A	N/A
9298257	12/2015	Hwang et al.	N/A	N/A
9314692	12/2015	Konoplev et al.	N/A	N/A
9330483	12/2015	Du et al.	N/A	N/A
9357174	12/2015	Li et al.	N/A	N/A
9361510	12/2015	Yao et al.	N/A	N/A
9378576	12/2015	Bouaziz et al.	N/A	N/A

9385983	12/2015	Sehn	N/A	N/A
9396354	12/2015	Murphy et al.	N/A	N/A
9402057	12/2015	Kaytaz et al.	N/A	N/A
9407712	12/2015	Sehn	N/A	N/A
9407816	12/2015	Sehn	N/A	N/A
9412192	12/2015	Mandel et al.	N/A	N/A
9430783	12/2015	Sehn	N/A	N/A
9443227	12/2015	Evans et al.	N/A	N/A
9460541	12/2015	Li et al.	N/A	N/A
9482882	12/2015	Hanover et al.	N/A	N/A
9482883	12/2015	Meisenholder	N/A	N/A
9489661	12/2015	Evans et al.	N/A	N/A
9489760	12/2015	Li et al.	N/A	N/A
9491134	12/2015	Rosen et al.	N/A	N/A
9503845	12/2015	Vincent	N/A	N/A
9508197	12/2015	Quinn et al.	N/A	N/A
9532171	12/2015	Allen et al.	N/A	N/A
9537811	12/2016	Allen et al.	N/A	N/A
9544257	12/2016	Ogundokun et al.	N/A	N/A
9560006	12/2016	Prado et al.	N/A	N/A
9576400	12/2016	Van Os et al.	N/A	N/A
9589357	12/2016	Li et al.	N/A	N/A
9592449	12/2016	Barbalet et al.	N/A	N/A
9628950	12/2016	Noeth et al.	N/A	N/A
9648376	12/2016	Chang et al.	N/A	N/A
9652896	12/2016	Jurgenson et al.	N/A	N/A
9659244	12/2016	Anderton et al.	N/A	N/A
9693191	12/2016	Sehn	N/A	N/A
9697635	12/2016	Quinn et al.	N/A	N/A
9705831	12/2016	Spiegel	N/A	N/A
9706040	12/2016	Kadirvel et al.	N/A	N/A
9742713	12/2016	Spiegel et al.	N/A	N/A
9744466	12/2016	Fujioka	N/A	N/A
9746990	12/2016	Anderson et al.	N/A	N/A
9749270	12/2016	Collet et al.	N/A	N/A
9785796	12/2016	Murphy et al.	N/A	N/A
9792714	12/2016	Li et al.	N/A	N/A
9825898	12/2016	Sehn	N/A	N/A
9839844	12/2016	Dunstan et al.	N/A	N/A
9854219	12/2016	Sehn	N/A	N/A
9883838	12/2017	Kaleal, III et al.	N/A	N/A
9898849	12/2017	Du et al.	N/A	N/A
9911073	12/2017	Spiegel et al.	N/A	N/A
9936165	12/2017	Li et al.	N/A	N/A
9959037	12/2017	Chaudhri et al.	N/A	N/A
9961520	12/2017	Brooks et al.	N/A	N/A
9980100	12/2017	Charlton et al.	N/A	N/A
9990373	12/2017	Fortkort	N/A	N/A
10039988	12/2017	Lobb et al.	N/A	N/A
10097492	12/2017	Tsuda et al.	N/A	N/A

10116598	12/2017	Tucker et al.	N/A	N/A
10140757	12/2017	Gaiter	N/A	N/A
10155168	12/2017	Blackstock et al.	N/A	N/A
10242477	12/2018	Charlton et al.	N/A	N/A
10242503	12/2018	McPhee et al.	N/A	N/A
10262250	12/2018	Spiegel et al.	N/A	N/A
10362219	12/2018	Wilson et al.	N/A	N/A
10475225	12/2018	Park et al.	N/A	N/A
10504266	12/2018	Blattner et al.	N/A	N/A
10573048	12/2019	Ni et al.	N/A	N/A
10657701	12/2019	Osman et al.	N/A	N/A
10726603	12/2019	Al Majid et al.	N/A	N/A
11120601	12/2020	Al Majid et al.	N/A	N/A
11468618	12/2021	Al Majid et al.	N/A	N/A
11688119	12/2022	Al Majid	345/473	G06F 3/04845
11880923	12/2023	Al Majid et al.	N/A	N/A
2002/0047868	12/2001	Miyazawa	N/A	N/A
2002/0067362	12/2001	Agostino Nocera et al.	N/A	N/A
2002/0144154	12/2001	Tomkow	N/A	N/A
2002/0169644	12/2001	Greene	N/A	N/A
2003/0052925	12/2002	Daimon et al.	N/A	N/A
2003/0126215	12/2002	Udell	N/A	N/A
2003/0217106	12/2002	Adar et al.	N/A	N/A
2004/0203959	12/2003	Coombes	N/A	N/A
2005/0097176	12/2004	Schatz et al.	N/A	N/A
2005/0162419	12/2004	Kim et al.	N/A	N/A
2005/0198128	12/2004	Anderson	N/A	N/A
2005/0206610	12/2004	Cordelli	N/A	N/A
2005/0223066	12/2004	Buchheit et al.	N/A	N/A
2005/0248574	12/2004	Ashtekar et al.	N/A	N/A
2006/0242239	12/2005	Morishima et al.	N/A	N/A
2006/0270419	12/2005	Crowley et al.	N/A	N/A
2006/0294465	12/2005	Ronen et al.	N/A	N/A
2007/0038715	12/2006	Collins et al.	N/A	N/A
2007/0064899	12/2006	Boss et al.	N/A	N/A
2007/0073823	12/2006	Cohen et al.	N/A	N/A
2007/0113181	12/2006	Blattner et al.	N/A	N/A
2007/0168863	12/2006	Blattner et al.	N/A	N/A
2007/0176921	12/2006	Iwasaki et al.	N/A	N/A
2007/0214216	12/2006	Carrer et al.	N/A	N/A
2007/0233801	12/2006	Eren et al.	N/A	N/A
2008/0055269	12/2007	Lemay et al.	N/A	N/A
2008/0120409	12/2007	Sun et al.	N/A	N/A
2008/0158222	12/2007	Li et al.	N/A	N/A
2008/0163074	12/2007	Tu	N/A	N/A
2008/0207176	12/2007	Brackbill et al.	N/A	N/A
2008/0270938	12/2007	Carlson	N/A	N/A
2008/0306826	12/2007	Kramer et al.	N/A	N/A

2008/0313346	12/2007	Kujawa et al.	N/A	N/A
2009/0016617	12/2008	Bregman-amitai et al.	N/A	N/A
2009/0042588	12/2008	Lottin et al.	N/A	N/A
2009/0055484	12/2008	Vuong et al.	N/A	N/A
2009/0070688	12/2008	Gyorfi et al.	N/A	N/A
2009/0099925	12/2008	Mehta et al.	N/A	N/A
2009/0106672	12/2008	Burstrom	N/A	N/A
2009/0132453	12/2008	Hangartner et al.	N/A	N/A
2009/0158170	12/2008	Narayanan et al.	N/A	N/A
2009/0177976	12/2008	Bokor et al.	N/A	N/A
2009/0202114	12/2008	Morin et al.	N/A	N/A
2009/0265604	12/2008	Howard et al.	N/A	N/A
2009/0300525	12/2008	Jolliff et al.	N/A	N/A
2009/0303984	12/2008	Clark et al.	N/A	N/A
2010/0011422	12/2009	Mason et al.	N/A	N/A
2010/0023885	12/2009	Reville et al.	N/A	N/A
2010/0082427	12/2009	Burgener et al.	N/A	N/A
2010/0115426	12/2009	Liu et al.	N/A	N/A
2010/0131880	12/2009	Lee et al.	N/A	N/A
2010/0162149	12/2009	Sheleheda et al.	N/A	N/A
2010/0185665	12/2009	Horn et al.	N/A	N/A
2010/0203968	12/2009	Gill et al.	N/A	N/A
2010/0227682	12/2009	Reville et al.	N/A	N/A
2010/0306669	12/2009	Della Pasqua	N/A	N/A
2011/0007077	12/2010	Kamath et al.	N/A	N/A
2011/0093780	12/2010	Dunn	N/A	N/A
2011/0099507	12/2010	Nesladek et al.	N/A	N/A
2011/0115798	12/2010	Nayar et al.	N/A	N/A
2011/0145564	12/2010	Moshir et al.	N/A	N/A
2011/0148864	12/2010	Lee et al.	N/A	N/A
2011/0202598	12/2010	Evans et al.	N/A	N/A
2011/0213845	12/2010	Logan et al.	N/A	N/A
2011/0239136	12/2010	Goldman et al.	N/A	N/A
2011/0286586	12/2010	Saylor et al.	N/A	N/A
2011/0296324	12/2010	Goossens et al.	N/A	N/A
2011/0320373	12/2010	Lee et al.	N/A	N/A
2012/0005209	12/2011	Rinearson et al.	N/A	N/A
2012/0028659	12/2011	Whitney et al.	N/A	N/A
2012/0113106	12/2011	Choi et al.	N/A	N/A
2012/0124458	12/2011	Cruzada	N/A	N/A
2012/0130717	12/2011	Xu et al.	N/A	N/A
2012/0184248	12/2011	Speede	N/A	N/A
2012/0209921	12/2011	Adafin et al.	N/A	N/A
2012/0209924	12/2011	Evans et al.	N/A	N/A
2012/0254325	12/2011	Majeti et al.	N/A	N/A
2012/0278692	12/2011	Shi	N/A	N/A
2012/0304080	12/2011	Wormald et al.	N/A	N/A
2013/0071093	12/2012	Hanks et al.	N/A	N/A
2013/0103760	12/2012	Golding et al.	N/A	N/A

2013/0194301	12/2012	Robbins et al.	N/A	N/A
2013/0201187	12/2012	Tong et al.	N/A	N/A
2013/0249948	12/2012	Reitan	N/A	N/A
2013/0257877	12/2012	Davis	N/A	N/A
2013/0290443	12/2012	Collins et al.	N/A	N/A
2014/0032682	12/2013	Prado et al.	N/A	N/A
2014/0043329	12/2013	Wang et al.	N/A	N/A
2014/0055554	12/2013	Du et al.	N/A	N/A
2014/0122787	12/2013	Shalvi et al.	N/A	N/A
2014/0125678	12/2013	Wang et al.	N/A	N/A
2014/0129343	12/2013	Finster et al.	N/A	N/A
2014/0160149	12/2013	Blackstock et al.	N/A	N/A
2014/0173430	12/2013	Clavel et al.	N/A	N/A
2014/0201527	12/2013	Krivorot	N/A	N/A
2014/0228055	12/2013	Karaoguz	455/456.3	H04W 4/02
2014/0282096	12/2013	Rubinstein et al.	N/A	N/A
2014/0325383	12/2013	Brown et al.	N/A	N/A
2014/0359024	12/2013	Spiegel	N/A	N/A
2014/0359032	12/2013	Spiegel et al.	N/A	N/A
2015/0199082	12/2014	Scholler et al.	N/A	N/A
2015/0206349	12/2014	Rosenthal et al.	N/A	N/A
2015/0227602	12/2014	Ramu et al.	N/A	N/A
2016/0042224	12/2015	Liu	382/203	G06V 10/987
2016/0085773	12/2015	Chang et al.	N/A	N/A
2016/0085863	12/2015	Allen et al.	N/A	N/A
2016/0086670	12/2015	Gross et al.	N/A	N/A
2016/0099901	12/2015	Allen et al.	N/A	N/A
2016/0134840	12/2015	Mcculloch	N/A	N/A
2016/0179967	12/2015	Sa et al.	N/A	N/A
2016/0180887	12/2015	Sehn	N/A	N/A
2016/0234149	12/2015	Tsuda et al.	N/A	N/A
2016/0277419	12/2015	Allen et al.	N/A	N/A
2016/0321708	12/2015	Sehn	N/A	N/A
2016/0359957	12/2015	Laliberte	N/A	N/A
2016/0359987	12/2015	Laliberte	N/A	N/A
2017/0080346	12/2016	Abbas	N/A	N/A
2017/0087473	12/2016	Siegel et al.	N/A	N/A
2017/0113140	12/2016	Blackstock et al.	N/A	N/A
2017/0118145	12/2016	Aittoniemi et al.	N/A	N/A
2017/0161382	12/2016	Ouimet et al.	N/A	N/A
2017/0193280	12/2016	Huang et al.	N/A	N/A
2017/0199855	12/2016	Fishbeck	N/A	N/A
2017/0235848	12/2016	Van Dusen et al.	N/A	N/A
2017/0263029	12/2016	Yan et al.	N/A	N/A
2017/0287006	12/2016	Azmoodeh et al.	N/A	N/A
2017/0295250	12/2016	Samaranayake et al.	N/A	N/A
2017/0308290	12/2016	Patel	N/A	N/A
2017/0310934	12/2016	Du et al.	N/A	N/A

2017/0312634	12/2016	Ledoux et al.	N/A	N/A
2017/0353416	12/2016	Brooks et al.	N/A	N/A
2017/0372056	12/2016	Narasimhan	N/A	N/A
2017/0374003	12/2016	Allen et al.	N/A	N/A
2017/0374508	12/2016	Davis et al.	N/A	N/A
2018/0018079	12/2017	Monastyrshyn et al.	N/A	N/A
2018/0025004	12/2017	Koenig	N/A	N/A
2018/0026925	12/2017	Kennedy	715/753	G06V 40/174
2018/0046518	12/2017	Shear et al.	N/A	N/A
2018/0047200	12/2017	O'hara et al.	N/A	N/A
2018/0113587	12/2017	Allen et al.	N/A	N/A
2018/0115503	12/2017	Baldwin et al.	N/A	N/A
2018/0130459	12/2017	Paradiso et al.	N/A	N/A
2018/0137383	12/2017	Yao et al.	N/A	N/A
2018/0157399	12/2017	Cansino et al.	N/A	N/A
2018/0188905	12/2017	Tran et al.	N/A	N/A
2018/0315076	12/2017	Andreou	N/A	N/A
2018/0315133	12/2017	Brody et al.	N/A	N/A
2018/0315134	12/2017	Amitay et al.	N/A	N/A
2019/0001223	12/2018	Blackstock et al.	N/A	N/A
2019/0057616	12/2018	Cohen et al.	N/A	N/A
2019/0188920	12/2018	Mcphee et al.	N/A	N/A
2020/0320767	12/2019	Al Majid et al.	N/A	N/A
2021/0343061	12/2020	Al Majid	N/A	G06F 3/04817
2022/0351453	12/2021	Al Majid et al.	N/A	N/A
2023/0215072	12/2022	Al Majid et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2887596	12/2014	CA	N/A
109863532	12/2018	CN	N/A
110168478	12/2018	CN	N/A
2184092	12/2009	EP	N/A
2001230801	12/2000	JP	N/A
5497931	12/2013	JP	N/A
101445263	12/2013	KR	N/A
WO-2003094072	12/2002	WO	N/A
WO-2004095308	12/2003	WO	N/A
WO-2006107182	12/2005	WO	N/A
WO-2007134402	12/2006	WO	N/A
WO-2012000107	12/2011	WO	N/A
WO-2012139276	12/2011	WO	N/A
WO-2013008251	12/2012	WO	N/A
WO-2013027893	12/2012	WO	N/A
WO-2013152454	12/2012	WO	N/A
WO-2013166588	12/2012	WO	N/A

WO-2014031899	12/2013	WO	N/A
WO-2014194262	12/2013	WO	N/A
WO-2014194439	12/2013	WO	N/A
WO-2015192026	12/2014	WO	N/A
WO-2016054562	12/2015	WO	N/A
WO-2016065131	12/2015	WO	N/A
WO-2016090605	12/2015	WO	N/A
WO-2016/112299	12/2015	WO	N/A
WO-2016179166	12/2015	WO	N/A
WO-2016179235	12/2015	WO	N/A
WO-2017176739	12/2016	WO	N/A
WO-2017176992	12/2016	WO	N/A
WO-2018005644	12/2017	WO	N/A
WO-2018081013	12/2017	WO	N/A
WO-2018102562	12/2017	WO	N/A
WO-2018129531	12/2017	WO	N/A
WO-2019089613	12/2018	WO	N/A

OTHER PUBLICATIONS

“U.S. Appl. No. 15/908,422, Examiner Interview Summary mailed May 13, 2019”, 4 pgs. cited by applicant

“U.S. Appl. No. 15/908,422, Examiner Interview Summary mailed Nov. 30, 2018”, 4 pgs. cited by applicant

“U.S. Appl. No. 15/908,422, Final Office Action mailed Mar. 14, 2019”, 15 pgs. cited by applicant

“U.S. Appl. No. 15/908,422, Final Office Action mailed Nov. 27, 2019”, 17 pgs. cited by applicant

“U.S. Appl. No. 15/908,422, Non Final Office Action mailed Jun. 20, 2019”, 15 pgs. cited by applicant

“U.S. Appl. No. 15/908,422, Non Final Office Action mailed Sep. 6, 2018”, 13 pgs. cited by applicant

“U.S. Appl. No. 15/908,422, Notice of Allowance mailed Mar. 23, 2020”, 8 pgs. cited by applicant

“U.S. Appl. No. 15/908,422, Response filed Feb. 27, 2020 to Final Office Action mailed Nov. 27, 2019”, 10 pgs. cited by applicant

“U.S. Appl. No. 15/908,422, Response filed Nov. 28, 2018 to Non Final Office Action mailed Sep. 6, 2018”, 11 pgs. cited by applicant

“U.S. Appl. No. 15/908,422, Response filed May 9, 2019 to Final Office Action mailed Mar. 14, 2019”, 11 pgs. cited by applicant

“U.S. Appl. No. 15/908,422, Response filed Aug. 22, 2019 to Non-Final Office Action mailed Jun. 20, 2019”, 12 pgs. cited by applicant

“U.S. Appl. No. 16/946,463, Final Office Action mailed Dec. 3, 2020”, 15 pgs. cited by applicant

“U.S. Appl. No. 16/946,463, Non Final Office Action mailed Feb. 19, 2021”, 14 pgs. cited by applicant

“U.S. Appl. No. 16/946,463, Non Final Office Action mailed Aug. 28, 2020”, 12 pgs. cited by applicant

“U.S. Appl. No. 16/946,463, Notice of Allowance mailed May 14, 2021”, 8 pgs. cited by applicant

“U.S. Appl. No. 16/946,463, Response filed Feb. 3, 2021 to Final Office Action mailed Dec. 3, 2020”, 9 pgs. cited by applicant

“U.S. Appl. No. 16/946,463, Response filed Apr. 28, 2021 to Non Final Office Action mailed Feb. 19, 2021”, 10 pgs. cited by applicant

“U.S. Appl. No. 16/946,463, Response filed Sep. 1, 2020 to Non Final Office Action mailed Aug. 28, 2020”, 12 pgs. cited by applicant

“U.S. Appl. No. 17/376,457, Non Final Office Action mailed Mar. 1, 2022”, 13 pgs. cited by applicant

“U.S. Appl. No. 17/376,457, Notice of Allowance mailed May 16, 2022”, 8 pgs. cited by applicant

“U.S. Appl. No. 17/376,457, Response filed Apr. 28, 2022 to Non Final Office Action mailed Mar. 1, 2022”, 10 pgs. cited by applicant

“U.S. Appl. No. 17/864,152, Non Final Office Action mailed Nov. 22, 2022”, 20 pgs. cited by applicant

“U.S. Appl. No. 17/864,152, Notice of Allowance mailed Feb. 16, 2023”, 8 pgs. cited by applicant

“U.S. Appl. No. 17/864,152, Response filed Jan. 18, 2023 to Non Final Office Action mailed Nov. 22, 2022”, 10 pgs. cited by applicant

“U.S. Appl. No. 18/184,283, Non Final Office Action mailed Jul. 14, 2023”, 10 pgs. cited by applicant

“U.S. Appl. No. 18/184,283, Notice of Allowance mailed Sep. 1, 2023”, 8 pgs. cited by applicant

“U.S. Appl. No. 18/184,283, Response filed Aug. 10, 2023 to Non Final Office Action mailed Jul. 14, 2023”, 8 pgs. cited by applicant

Castelluccia, Claude, et al., “EphPub: Toward robust Ephemeral Publishing”, 19th IEEE International Conference on Network Protocols (ICNP), (Oct. 17, 2011), 18 pgs. cited by applicant

Fajman, “An Extensible Message Format for Message Disposition Notifications”, Request for Comments: 2298, National Institutes of Health, (Mar. 1998), 28 pgs. cited by applicant

Leyden, John, “This SMS will self-destruct in 40 seconds”, [Online] Retrieved from the Internet: <URL: <http://www.theregister.co.uk/2005/12/12/stealthtext/>>, (Dec. 12, 2005), 1 pg. cited by applicant

Melanson, Mike, “This text message will self destruct in 60 seconds”, [Online] Retrieved from the Internet: <URL: http://readwrite.com/2011/02/11/this_text_message_will_self_destruct_in_60_seconds>, (Feb. 18, 2015), 4 pgs. cited by applicant

Sawers, Paul, “Snapchat for iOS Lets You Send Photos to Friends and Set How long They're Visible For”, [Online] Retrieved from the Internet: <URL: <https://thenextweb.com/news/snapchat-for-ios-lets-you-send-photos-to-friends-and-set-how-long-theyre-visible-for>>, (May 7, 2012), 5 pgs. cited by applicant

Shein, Esther, “Ephemeral Data”, Communications of the ACM, vol. 56, No. 9, (Sep. 2013), 3 pgs. cited by applicant

Vaas, Lisa, “StealthText, Should You Choose to Accept It”, [Online] Retrieved from the Internet: <URL: <https://www.eweek.com/enterprise-apps/stealthtext-should-you-choose-to-accept-it/>>, (Dec. 13, 2005), 3 pgs. cited by applicant

Primary Examiner: Merouan; Abderrahim

Attorney, Agent or Firm: Schwegman Lundberg & Woessner, P.A.

Background/Summary

CLAIM OF PRIORITY (1) This application is a continuation of U.S. patent application Ser. No. 18/184,283, filed Mar. 15, 2023, which application is a continuation of U.S. patent application Ser. No. 17/864,152, filed Jul. 13, 2022, now issued as U.S. Pat. No. 11,688,119, which application is a continuation of U.S. patent application Ser. No. 17/376,457, filed Jul. 15, 2021, now issued as U.S. Pat. No. 11,468,618, which application is a continuation of U.S. patent application Ser. No. 16/946,463, filed on Jun. 23, 2020, now issued as U.S. Pat. No. 11,120,601, which is a continuation

TECHNICAL FIELD

(1) Embodiments of the present disclosure relate generally to mobile computing technology and, more particularly, but not by way of limitation, to systems for presenting an animated expressive graphical icon.

BACKGROUND

(2) Research has shown that facial tracking and performance capturing technology have had significant impacts in a broad range of fields that include computer gaming, animations, entertainment, human-computer interface. For example, some of the research has shown that users interacting with a digital avatar, such as an animated face, are 30% more trustworthy than compared with the same interactions with text-only scripts.

(3) Increased prevalence of mobile devices has resulted in “social networking” to become an important part in the day-to-day activities of many people's lives. Today, hundreds of millions of people use their virtual identities to communicate and interact with other people over the web, internet and the like via Social networking sites. In addition, these virtual identities are used to play games over the web, internet and the like.

(4) While social networking provides the ability for contact between people any time of day or night, it is often difficult to ascertain exactly how people are feeling by looking at their virtual identity, or through reading text messages alone.

Description

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

(1) To easily identify the discussion of any particular element or act, the most significant digit or digits in a reference number refer to the figure number in which that element is first introduced.

(2) FIG. 1 is a block diagram showing an example messaging system for exchanging data (e.g., messages and associated content) over a network in accordance with some embodiments, wherein the messaging system includes a chat presence system.

(3) FIG. 2 is block diagram illustrating further details regarding a messaging system, according to example embodiments.

(4) FIG. 3 is a block diagram illustrating various modules of an expressive icon system, according to certain example embodiments.

(5) FIG. 4 is a depiction of facial tracking data captured by an expressive icon system, according to certain example embodiments.

(6) FIG. 5 is a flow diagram illustrating operations performed by an expressive icon system, in receiving video data in real-time, tracking facial landmarks from the video data, and generating and display an animated expressive graphical icon based on the tracked facial landmarks, according to certain example embodiments.

(7) FIG. 6 depicts a method for presenting an expressive animated graphical icon based on real-time facial tracking data, according to certain example embodiments.

(8) FIG. 7 is an interface diagram illustrating an interface to display an expressive animated icon, according to certain example embodiments.

(9) FIG. 8 is a block diagram illustrating a representative software architecture, which may be used in conjunction with various hardware architectures herein described and used to implement various embodiments.

(10) FIG. 9 is a block diagram illustrating components of a machine, according to some example embodiments, able to read instructions from a machine-readable medium (e.g., a machine-readable storage medium) and perform any one or more of the methodologies discussed herein.

DETAILED DESCRIPTION

(11) Embodiments described herein relate to an expressive icon system (hereinafter referred to as the system) to present an animated graphical icon, wherein the animated graphical icon is generated by capture facial tracking data at a client device. In some embodiments, the system may track and capture facial tracking data of a user via a camera associated with a client device (e.g., a front facing camera, or a paired camera), and process the facial tracking data to animate a graphical icon. In further embodiments, the system facilitates the distribution and sharing of the animated graphical icon, for example by attaching the animated graphical icon to a message to be distributed to a plurality of users, such that the animated graphical icon tracks the facial tracking data of the user in real-time, or by publishing the animated graphical icon at a location accessible through a network (e.g., a user profile picture of a user).

(12) In some example embodiments, the system captures facial tracking data and audio data in real time at a first client device, and generates and presents the audio and an animated graphical icon based on the real-time facial tracking data, at a second client device. For example, a user of the first client device may request an initiation of a communication session with a user of a second client device. In response to receiving an authorization to initiate the communication session, the first client device captures facial tracking data of the user via a camera associated with the client device (e.g., a front facing camera of a client device), and causes a presentation of an animated graphical icon in real-time based on the facial tracking data at the second client device.

(13) In some example embodiments, the system generates an expressive animated icon at the first client device based on the facial tracking data, renders a flattened animation of the expressive animated icon at the first client device, and causes display of the flattened animation of the expressive animated icon to the second client device. In such embodiments, the generation and rendering of the expressive animated icon occurs separate from the recipient device (e.g., the second client device), similar to a thin client.

(14) In further embodiments, the system captures the facial tracking data at a first client device, in real-time, and transmits the real-time facial tracking data to a second client device, where the facial tracking data is transposed onto a graphical icon. In this way, the second client device may generate and display an animated graphical icon based on received facial tracking data.

(15) In some example embodiments, a user provides a selection of the graphical icon to be animated by the system. For example, the system may display a set of graphical icons at a client device, and receive a selection of the graphical icon from among the set of graphical icons. The system receives facial tracking data and transposes the facial tracking data upon the selected graphical icon in real-time.

(16) A user may select and associate a graphical icon with a user profile, such that facial tracking data received from a device associated with the user profile are transposed to the selected graphical icon. In further embodiments, a user may select or change the graphical icon in real-time, and in response the system transposes the facial tracking data to the selected graphical icon, and causes display of the selected graphical icon at the client device.

(17) In some example embodiments, facial tracking is performed by the system through the identification of various 2D and 3D facial landmarks correspond to semantic facial features of a human face, such as the contour of eyes, lips and eyebrows, the tip of a nose, etc. The system transposes the tracked facial landmarks onto a graphical icon, resulting in an expressive icon that depicts the shape of the user's different expressions in real-time.

(18) Consider an illustrative example from a user perspective. A first user of a first client device may initiate a communication session with a second user of a second client device. In response to initiating the communication session between the first client device and the second client device, the first client device captures facial tracking data from the first user, via a front facing camera.

(19) The system generates and causes display of a presentation of an animated expressive icon at the second client device, wherein the animated expressive icon is animated based on the facial

tracking data captured at the first client device, in real-time. In some embodiments, as discussed herein, the system may generate a flattened video of the animated expressive icon based on the facial tracking data at the first client device, and transmit the flattened video of the animated expressive icon to the second client device, where it is presented to the second user. In further embodiments, the system captures the facial tracking data at the first client device, transmits the facial tracking data to the second client device in real-time, and the second client device animates the animated expressive icon in real-time, based on the facial tracking data captured at the first client device. In this way, users may communicate with one another via presentations of animated expressive icons.

(20) FIG. 1 is a block diagram showing an example messaging system **100** for exchanging data (e.g., messages and associated content) over a network. The messaging system **100** includes multiple client devices **102**, each of which hosts a number of applications including a messaging client application **104**. Each messaging client application **104** is communicatively coupled to other instances of the messaging client application **104** and a messaging server system **108** via a network **106** (e.g., the Internet).

(21) Accordingly, each messaging client application **104** is able to communicate and exchange data with another messaging client application **104** and with the messaging server system **108** via the network **106**. The data exchanged between messaging client applications **104**, and between a messaging client application **104** and the messaging server system **108**, includes functions (e.g., commands to invoke functions) as well as payload data (e.g., text, audio, video or other multimedia data).

(22) The messaging server system **108** provides server-side functionality via the network **106** to a particular messaging client application **104**. While certain functions of the messaging system **100** are described herein as being performed by either a messaging client application **104** or by the messaging server system **108**, it will be appreciated that the location of certain functionality either within the messaging client application **104** or the messaging server system **108** is a design choice. For example, it may be technically preferable to initially deploy certain technology and functionality within the messaging server system **108**, but to later migrate this technology and functionality to the messaging client application **104** where a client device **102** has a sufficient processing capacity.

(23) The messaging server system **108** supports various services and operations that are provided to the messaging client application **104**. Such operations include transmitting data to, receiving data from, and processing data generated by the messaging client application **104**. In some embodiments, this data includes, message content, client device information, geolocation information, media annotation and overlays, message content persistence conditions, social network information, and live event information, as examples. In other embodiments, other data is used. Data exchanges within the messaging system **100** are invoked and controlled through functions available via GUIs of the messaging client application **104**.

(24) Turning now specifically to the messaging server system **108**, an Application Program Interface (API) server **110** is coupled to, and provides a programmatic interface to, an application server **112**. The application server **112** is communicatively coupled to a database server **118**, which facilitates access to a database **120** in which is stored data associated with messages processed by the application server **112**.

(25) Dealing specifically with the Application Program Interface (API) server **110**, this server receives and transmits message data (e.g., commands and message payloads) between the client device **102** and the application server **112**. Specifically, the Application Program Interface (API) server **110** provides a set of interfaces (e.g., routines and protocols) that can be called or queried by the messaging client application **104** in order to invoke functionality of the application server **112**. The Application Program Interface (API) server **110** exposes various functions supported by the application server **112**, including account registration, login functionality, the sending of messages,

via the application server **112**, from a particular messaging client application **104** to another messaging client application **104**, the sending of media files (e.g., images or video) from a messaging client application **104** to the messaging server application **114**, and for possible access by another messaging client application **104**, the setting of a collection of media data (e.g., story), the retrieval of a list of friends of a user of a client device **102**, the retrieval of such collections, the retrieval of messages and content, the adding and deletion of friends to a social graph, the location of friends within a social graph, opening and application event (e.g., relating to the messaging client application **104**).

(26) The application server **112** hosts a number of applications and subsystems, including a messaging server application **114**, an image processing system **116**, a social network system **122**, and an expressive icon system **124**. The messaging server application **114** implements a number of message processing technologies and functions, particularly related to the aggregation and other processing of content (e.g., textual and multimedia content) included in messages received from multiple instances of the messaging client application **104**. As will be described in further detail, the text and media content from multiple sources may be aggregated into collections of content (e.g., called stories or galleries). These collections are then made available, by the messaging server application **114**, to the messaging client application **104**. Other processor and memory intensive processing of data may also be performed server-side by the messaging server application **114**, in view of the hardware requirements for such processing.

(27) The application server **112** also includes an image processing system **116** that is dedicated to performing various image processing operations, typically with respect to images or video received within the payload of a message at the messaging server application **114**.

(28) The social network system **122** supports various social networking functions services, and makes these functions and services available to the messaging server application **114**. To this end, the social network system **122** maintains and accesses an entity graph **304** within the database **120**. Examples of functions and services supported by the social network system **122** include the identification of other users of the messaging system **100** with which a particular user has relationships or is “following,” and also the identification of other entities and interests of a particular user.

(29) The application server **112** is communicatively coupled to a database server **118**, which facilitates access to a database **120** in which is stored data associated with messages processed by the messaging server application **114**.

(30) FIG. 2 is block diagram illustrating further details regarding the messaging system **100**, according to example embodiments. Specifically, the messaging system **100** is shown to comprise the messaging client application **104** and the application server **112**, which in turn embody a number of some subsystems, namely an ephemeral timer system **202**, a collection management system **204** and an annotation system **206**.

(31) The ephemeral timer system **202** is responsible for enforcing the temporary access to content permitted by the messaging client application **104** and the messaging server application **114**. To this end, the ephemeral timer system **202** incorporates a number of timers that, based on duration and display parameters associated with a message, collection of messages (e.g., a SNAPCHAT story), or graphical element, selectively display and enable access to messages and associated content via the messaging client application **104**. Further details regarding the operation of the ephemeral timer system **202** are provided below.

(32) The collection management system **204** is responsible for managing collections of media (e.g., collections of text, image video and audio data). In some examples, a collection of content (e.g., messages, including images, video, text and audio) may be organized into an “event gallery” or an “event story.” Such a collection may be made available for a specified time period, such as the duration of an event to which the content relates. For example, content relating to a music concert may be made available as a “story” for the duration of that music concert. The collection

management system **204** may also be responsible for publishing an icon that provides notification of the existence of a particular collection to the user interface of the messaging client application **104**.

(33) The collection management system **204** furthermore includes a curation interface **208** that allows a collection manager to manage and curate a particular collection of content. For example, the curation interface **208** enables an event organizer to curate a collection of content relating to a specific event (e.g., delete inappropriate content or redundant messages). Additionally, the collection management system **204** employs machine vision (or image recognition technology) and content rules to automatically curate a content collection. In certain embodiments, compensation may be paid to a user for inclusion of user generated content into a collection. In such cases, the curation interface **208** operates to automatically make payments to such users for the use of their content.

(34) The annotation system **206** provides various functions that enable a user to annotate or otherwise modify or edit media content associated with a message. For example, the annotation system **206** provides functions related to the generation and publishing of media overlays for messages processed by the messaging system **100**. The annotation system **206** operatively supplies a media overlay (e.g., a SNAPCHAT filter) to the messaging client application **104** based on a geolocation of the client device **102**. In another example, the annotation system **206** operatively supplies a media overlay to the messaging client application **104** based on other information, such as, social network information of the user of the client device **102**. A media overlay may include audio and visual content and visual effects. Examples of audio and visual content include pictures, texts, logos, animations, and sound effects, as well as animated facial models, such as those generated by the expressive icon system **124**. An example of a visual effect includes color overlaying. The audio and visual content or the visual effects can be applied to a media content item (e.g., a photo) at the client device **102**. For example, the media overlay including text that can be overlaid on top of a photograph generated taken by the client device **102**. In another example, the media overlay includes an identification of a location overlay (e.g., Venice beach), a name of a live event, or a name of a merchant overlay (e.g., Beach Coffee House). In another example, the annotation system **206** uses the geolocation of the client device **102** to identify a media overlay that includes the name of a merchant at the geolocation of the client device **102**. The media overlay may include other indicia associated with the merchant. The media overlays may be stored in the database **120** and accessed through the database server **118**.

(35) In one example embodiment, the annotation system **206** provides a user-based publication platform that enables users to select a geolocation on a map, and upload content associated with the selected geolocation. The user may also specify circumstances under which a particular media overlay should be offered to other users. The annotation system **206** generates a media overlay that includes the uploaded content and associates the uploaded content with the selected geolocation.

(36) In another example embodiment, the annotation system **206** provides a merchant-based publication platform that enables merchants to select a particular media overlay associated with a geolocation via a bidding process. For example, the annotation system **206** associates the media overlay of a highest bidding merchant with a corresponding geolocation for a predefined amount of time

(37) FIG. 3 is a block diagram illustrating components of the expressive icon system **124** that configure the expressive icon system **124** to capture facial tracking data, assign the facial tracking data to a graphical icon (e.g., a bitmoji, an animated expressive icon), and present the graphical icon based on the facial tracking data, according to some example embodiments. The expressive icon system **124** is shown as including a facial tracking module **302**, a graphical icon module **304**, a communication module **306**, and presentation module **308**, all configured to communicate with each other (e.g., via a bus, shared memory, or a switch). Any one or more of these modules may be implemented using one or more processors **310** (e.g., by configuring such one or more processors

to perform functions described for that module) and hence may include one or more of the processors **310**.

(38) Any one or more of the modules described may be implemented using hardware alone (e.g., one or more of the processors **310** of a machine) or a combination of hardware and software. For example, any module described of the expressive icon system **124** may physically include an arrangement of one or more of the processors **310** (e.g., a subset of or among the one or more processors of the machine) configured to perform the operations described herein for that module. As another example, any module of the expressive icon system **124** may include software, hardware, or both, that configure an arrangement of one or more processors **310** (e.g., among the one or more processors of the machine) to perform the operations described herein for that module. Accordingly, different modules of the expressive icon system **124** may include and configure different arrangements of such processors **310** or a single arrangement of such processors **310** at different points in time. Moreover, any two or more modules of the expressive icon system **124** may be combined into a single module, and the functions described herein for a single module may be subdivided among multiple modules. Furthermore, according to various example embodiments, modules described herein as being implemented within a single machine, database, or device may be distributed across multiple machines, databases, or devices.

(39) FIG. **4** is a depiction of facial tracking data captured by the facial tracking module **302** of the expressive icon system **124**, according to certain example embodiments. In some example embodiments, as seen in FIG. **4**, the tracked facial landmarks **404** and **408** comprises a set of points, wherein each point corresponds to a facial landmark identified by the expressive icon system **124**, based on image or video data (e.g., image or video data **402**, **406**).

(40) In some embodiments, the expressive icon system **124** receives video data **404** and **406** in real-time via front facing camera of a client device **102**, and tracks the facial tracking data that includes facial landmarks **404** and **408**, wherein the facial landmarks **502** and **508** correspond to the semantic facial features of a human face, such as the contour of eyes, lips, nose, and eyebrows.

(41) FIG. **5** is a flow diagram **500** illustrating operations performed by the expressive icon system **124**, in receiving video data in real-time, tracking facial landmarks from the video data, and generating and display an animated expressive graphical icon based on the tracked facial landmarks, according to certain example embodiments.

(42) At operation **502**, the facial tracking module **302** receives image or video data that includes a depiction of a face. For example, the facial tracking module **302** may access a front facing camera of a client device **102**, and capture video data depicting a user of the client device **102**.

(43) At operation **504**, the facial tracking module **302** captures facial tracking data in real-time, wherein the facial tracking data includes a set of points that identify facial landmarks, as described in FIG. **4**.

(44) At operation **506**, the graphical icon module **306** generates and causes display of an expressive animated icon based on the facial tracking data, in real-time. The animated graphical icon therefore depicts a real-time expression of the user, based on the real-time facial tracking data collected by the facial tracking module **302**.

(45) FIG. **6** depicts a method **600** for presenting an expressive animated graphical icon based on real-time facial tracking data, according to certain example embodiments. Operations of the method **600** may be performed by the modules described above with respect to FIG. **3**. As shown in FIG. **6**, the method **600** includes one or more operations **602**, **604**, **606**, and **608**.

(46) At operation **602**, the facial tracking module **302** captures facial tracking data (e.g., real-time facial tracking data **504** of FIG. **5**, facial tracking data **404** of FIG. **4**) at a first client device (e.g., client device **102A** of FIG. **1**). For example, the client device **102A** may include a front facing camera. In response to receiving an initiation of a communication session between a first user of the first client device **102A**, and a second user of a second client device **102B**, the facial tracking module **302** activates a front facing camera of the client device **102A**, to capture real-time video

data that includes video and images depicting the first user. The facial tracking module **302** extracts the facial tracking data from the videos or images by performing one or more facial landmark identification methods. For example, the facial tracking module **302** captures facial tracking data by identifying one or more facial landmarks of the first user in the video data received through the front facing camera, as seen in FIG. 4 and FIG. 5.

(47) At operation **604**, the graphical icon module **304** assigns the facial tracking data to a graphical icon. In some embodiments, the first user may select or define a graphical icon to transpose the facial tracking data upon, within a user profile associated with the first user. The first user may predefine selections of graphical icons based on one or more context conditions, such that the graphical icon module **304** selects an appropriate graphical icon based on the detection of certain context conditions. The context conditions may include a location, an identity of a recipient of the graphical icon, a time of day, a current season, identification of a holiday or event.

(48) In some example embodiments, the graphical icon module **304** may select a graphical icon from among a set of graphical icons based on a destination of the graphical icon. For example, the graphical icon module **304** may retrieve user profile information of a user (e.g., the second user) associated with the second client device **102B**, in response to the initiation of the communication session. The first user may predefine a specific graphical icon (e.g., a bitmoji) to be used in communication sessions with the second user. The graphical icon module **304** may select the graphical icon based on an identifier associated with the second user (e.g., phone number, user identifier, facial tracking data of the second user).

(49) In some example embodiments, the graphical icon module **304** may select a graphical icon from among a set of graphical icons based on a current location of the first client device. For example, the graphical icon module **304** may retrieve location data that identified a current location of the first client device **102A** or **102B**, in response to the initiation of the communication session. An administrator or the first user may predefine a specific graphical icon (e.g., a bitmoji) to be used in communication sessions wherein one or more client devices associated with the communication session are located at a predefined location, or within a geo-fenced area. The graphical icon module **304** may select the graphical icon based on an identifier associated with a location of the first client device **102** or the second client device **102B** (e.g., GPS coordinates, presence within a geo-fence).

(50) In some example embodiments, the graphical icon module **304** may select a graphical icon from among a set of graphical icons based on a current temporal period (e.g., time, day, season) of the communication session. For example, the graphical icon module **304** may receive an identification of a temporal period, in response to the initiation of the communication session. An administrator or the first user may predefine one or more graphical icons for specific temporal periods (e.g., time, date, national holiday, birthday, local holiday, local event/concert, spring, winter). The graphical icon module **304** may select the graphical icon based on the identification of the current temporal period.

(51) In further embodiments, the graphical icon may be selected or changed based on an input from the first user or the second user. For example, the first user or the second user may select the graphical icon from among a set of graphical icons, and in response, the graphical icon module **304** transposes the facial tracking data to the selected graphical icon.

(52) At operation **606**, the communication module **306** delivers the graphical icon to the second client device **102B**, from the first client device **102A**. In some embodiments, the communication module **306** may deliver a message that contains an identification of the graphical icon, and the facial tracking data to the second client device **102B**. The second client device **102B** generates an expressive animated icon based on the tracking data and the selection of the graphical icon, and displays the expressive animated icon at the second client device **102B** at operation **608**.

(53) In further embodiments, the graphical icon module **304** generates a real-time video at the first client device **102A**, based on the facial tracking data and the selection of the graphical icon. The communication module **306** may flatten the real-time video at the first client device **102A**, and

deliver the flattened video to the second client device **102B**. At operation **608**, the communication module present the flattened video at the second client device **102B**.

(54) FIG. **7** is an interface diagram illustrating an interface **700** to display an expressive animated icon **702**, according to certain example embodiments. As seen in FIG. **7**, the interface **700** may display a message **704** of a communication session (e.g., between a first client device **102A** and a second client device **102B**). In some embodiments, the animated expressive icon **702** may be displayed within a portion of the interface **700**, and in conjunction with a message (e.g., the message **704**) of a communication session. In further embodiments, the message **704** may include an ephemeral message, as discussed and illustrated above in FIGS. **2** and **3**.

(55) As discussed herein, the expressive animated icon **704** may emote in real-time, based on facial tracking data collected by the expressive icon system **124**. In further embodiments, the expressive animated icon **704** may be created by a user (e.g., the first user), and assigned to a home page or user profile page associated with the user, such that accessing and displaying the home page or user profile page causes the expressive icon system **124** to retrieve a sequence of facial tracking data, and transpose the sequence of facial tracking data onto a graphical icon to be presented at a client device. For example, the expressive animated icon **704** may be used as an avatar associated with the user, wherein the avatar is animated based on the sequence of facial tracking data.

(56) Software Architecture

(57) FIG. **8** is a block diagram illustrating an example software architecture **806**, which may be used in conjunction with various hardware architectures herein described. FIG. **8** is a non-limiting example of a software architecture and it will be appreciated that many other architectures may be implemented to facilitate the functionality described herein. The software architecture **806** may execute on hardware such as machine **900** of FIG. **9** that includes, among other things, processors **904**, memory **914**, and I/O components **918**. A representative hardware layer **852** is illustrated and can represent, for example, the machine **800** of FIG. **8**. The representative hardware layer **852** includes a processing unit **854** having associated executable instructions **804**. Executable instructions **804** represent the executable instructions of the software architecture **806**, including implementation of the methods, components and so forth described herein. The hardware layer **852** also includes memory and/or storage modules memory/storage **856**, which also have executable instructions **804**. The hardware layer **852** may also comprise other hardware **858**.

(58) In the example architecture of FIG. **8**, the software architecture **806** may be conceptualized as a stack of layers where each layer provides particular functionality. For example, the software architecture **806** may include layers such as an operating system **802**, libraries **820**, applications **816** and a presentation layer **814**. Operationally, the applications **816** and/or other components within the layers may invoke application programming interface (API) API calls **808** through the software stack and receive a response as in response to the API calls **808**. The layers illustrated are representative in nature and not all software architectures have all layers. For example, some mobile or special purpose operating systems may not provide a frameworks/middleware **818**, while others may provide such a layer. Other software architectures may include additional or different layers. The applications **816** may include applications related to and including the expressive icon system **124**.

(59) The operating system **802** may manage hardware resources and provide common services. The operating system **802** may include, for example, a kernel **822**, services **824** and drivers **826**. The kernel **822** may act as an abstraction layer between the hardware and the other software layers. For example, the kernel **822** may be responsible for memory management, processor management (e.g., scheduling), component management, networking, security settings, and so on. The services **824** may provide other common services for the other software layers. The drivers **826** are responsible for controlling or interfacing with the underlying hardware. For instance, the drivers **826** include display drivers, camera drivers, Bluetooth® drivers, flash memory drivers, serial communication drivers (e.g., Universal Serial Bus (USB) drivers), Wi-Fi® drivers, audio drivers, power

management drivers, and so forth depending on the hardware configuration.

(60) The libraries **820** provide a common infrastructure that is used by the applications **816** and/or other components and/or layers. The libraries **820** provide functionality that allows other software components to perform tasks in an easier fashion than to interface directly with the underlying operating system **802** functionality (e.g., kernel **822**, services **824** and/or drivers **826**). The libraries **820** may include system libraries **844** (e.g., C standard library) that may provide functions such as memory allocation functions, string manipulation functions, mathematical functions, and the like. In addition, the libraries **820** may include API libraries **846** such as media libraries (e.g., libraries to support presentation and manipulation of various media format such as MPREG4, H.264, MP3, AAC, AMR, JPG, PNG), graphics libraries (e.g., an OpenGL framework that may be used to render 2D and 3D in a graphic content on a display), database libraries (e.g., SQLite that may provide various relational database functions), web libraries (e.g., WebKit that may provide web browsing functionality), and the like. The libraries **820** may also include a wide variety of other libraries **848** to provide many other APIs to the applications **816** and other software components/modules.

(61) The frameworks/middleware **818** (also sometimes referred to as middleware) provide a higher-level common infrastructure that may be used by the applications **816** and/or other software components/modules. For example, the frameworks/middleware **818** may provide various graphic user interface (GUI) functions, high-level resource management, high-level location services, and so forth. The frameworks/middleware **818** may provide a broad spectrum of other APIs that may be utilized by the applications **816** and/or other software components/modules, some of which may be specific to a particular operating system **802** or platform.

(62) The applications **816** include built-in applications **838** and/or third-party applications **840**. Examples of representative built-in applications **838** may include, but are not limited to, a contacts application, a browser application, a book reader application, a location application, a media application, a messaging application, and/or a game application. Third-party applications **840** may include an application developed using the ANDROID™ or IOS™ software development kit (SDK) by an entity other than the vendor of the particular platform, and may be mobile software running on a mobile operating system such as IOS™, ANDROID™, WINDOWS® Phone, or other mobile operating systems. The third-party applications **840** may invoke the API calls **808** provided by the mobile operating system (such as operating system **802**) to facilitate functionality described herein.

(63) The applications **816** may use built in operating system functions (e.g., kernel **822**, services **824** and/or drivers **826**), libraries **820**, and frameworks/middleware **818** to create user interfaces to interact with users of the system. Alternatively, or additionally, in some systems interactions with a user may occur through a presentation layer, such as presentation layer **814**. In these systems, the application/component “logic” can be separated from the aspects of the application/component that interact with a user.

(64) FIG. **9** is a block diagram illustrating components of a machine **900**, according to some example embodiments, able to read instructions from a machine-readable medium (e.g., a machine-readable storage medium) and perform any one or more of the methodologies discussed herein. Specifically, FIG. **9** shows a diagrammatic representation of the machine **900** in the example form of a computer system, within which instructions **910** (e.g., software, a program, an application, an applet, an app, or other executable code) for causing the machine **900** to perform any one or more of the methodologies discussed herein may be executed. As such, the instructions **910** may be used to implement modules or components described herein. The instructions **910** transform the general, non-programmed machine **900** into a particular machine **900** programmed to carry out the described and illustrated functions in the manner described. In alternative embodiments, the machine **900** operates as a standalone device or may be coupled (e.g., networked) to other machines. In a networked deployment, the machine **900** may operate in the capacity of a server machine or a client machine in a server-client network environment, or as a peer machine in a peer-

to-peer (or distributed) network environment. The machine **900** may comprise, but not be limited to, a server computer, a client computer, a personal computer (PC), a tablet computer, a laptop computer, a netbook, a set-top box (STB), a personal digital assistant (PDA), an entertainment media system, a cellular telephone, a smart phone, a mobile device, a wearable device (e.g., a smart watch), a smart home device (e.g., a smart appliance), other smart devices, a web appliance, a network router, a network switch, a network bridge, or any machine capable of executing the instructions **910**, sequentially or otherwise, that specify actions to be taken by machine **900**. Further, while only a single machine **900** is illustrated, the term “machine” shall also be taken to include a collection of machines that individually or jointly execute the instructions **910** to perform any one or more of the methodologies discussed herein.

(65) The machine **900** may include processors **904**, memory memory/storage **906**, and I/O components **918**, which may be configured to communicate with each other such as via a bus **902**. The memory/storage **906** may include a memory **914**, such as a main memory, or other memory storage, and a storage unit **916**, both accessible to the processors **904** such as via the bus **902**. The storage unit **916** and memory **914** store the instructions **910** embodying any one or more of the methodologies or functions described herein. The instructions **910** may also reside, completely or partially, within the memory **914**, within the storage unit **916**, within at least one of the processors **904** (e.g., within the processor's cache memory), or any suitable combination thereof, during execution thereof by the machine **900**. Accordingly, the memory **914**, the storage unit **916**, and the memory of processors **904** are examples of machine-readable media.

(66) The I/O components **918** may include a wide variety of components to receive input, provide output, produce output, transmit information, exchange information, capture measurements, and so on. The specific I/O components **918** that are included in a particular machine **900** will depend on the type of machine. For example, portable machines such as mobile phones will likely include a touch input device or other such input mechanisms, while a headless server machine will likely not include such a touch input device. It will be appreciated that the I/O components **918** may include many other components that are not shown in FIG. **9**. The I/O components **918** are grouped according to functionality merely for simplifying the following discussion and the grouping is in no way limiting. In various example embodiments, the I/O components **918** may include output components **926** and input components **928**. The output components **926** may include visual components (e.g., a display such as a plasma display panel (PDP), a light emitting diode (LED) display, a liquid crystal display (LCD), a projector, or a cathode ray tube (CRT)), acoustic components (e.g., speakers), haptic components (e.g., a vibratory motor, resistance mechanisms), other signal generators, and so forth. The input components **928** may include alphanumeric input components (e.g., a keyboard, a touch screen configured to receive alphanumeric input, a photo-optical keyboard, or other alphanumeric input components), point based input components (e.g., a mouse, a touchpad, a trackball, a joystick, a motion sensor, or other pointing instrument), tactile input components (e.g., a physical button, a touch screen that provides location and/or force of touches or touch gestures, or other tactile input components), audio input components (e.g., a microphone), and the like.

(67) In further example embodiments, the I/O components **918** may include biometric components **930**, motion components **934**, environmental environment components **936**, or position components **938** among a wide array of other components. For example, the biometric components **930** may include components to detect expressions (e.g., hand expressions, facial expressions, vocal expressions, body gestures, or eye tracking), measure biosignals (e.g., blood pressure, heart rate, body temperature, perspiration, or brain waves), identify a person (e.g., voice identification, retinal identification, facial identification, fingerprint identification, or electroencephalogram based identification), and the like. The motion components **934** may include acceleration sensor components (e.g., accelerometer), gravitation sensor components, rotation sensor components (e.g., gyroscope), and so forth. The environment components **936** may include, for example, illumination

sensor components (e.g., photometer), temperature sensor components (e.g., one or more thermometer that detect ambient temperature), humidity sensor components, pressure sensor components (e.g., barometer), acoustic sensor components (e.g., one or more microphones that detect background noise), proximity sensor components (e.g., infrared sensors that detect nearby objects), gas sensors (e.g., gas detection sensors to detection concentrations of hazardous gases for safety or to measure pollutants in the atmosphere), or other components that may provide indications, measurements, or signals corresponding to a surrounding physical environment. The position components **938** may include location sensor components (e.g., a Global Position system (GPS) receiver component), altitude sensor components (e.g., altimeters or barometers that detect air pressure from which altitude may be derived), orientation sensor components (e.g., magnetometers), and the like.

(68) Communication may be implemented using a wide variety of technologies. The I/O components **918** may include communication components **940** operable to couple the machine **900** to a network **932** or devices **920** via coupling **922** and coupling **924** respectively. For example, the communication components **940** may include a network interface component or other suitable device to interface with the network **932**. In further examples, communication components **940** may include wired communication components, wireless communication components, cellular communication components, Near Field Communication (NFC) components, Bluetooth® components (e.g., Bluetooth® Low Energy), Wi-Fi® components, and other communication components to provide communication via other modalities. The devices **920** may be another machine or any of a wide variety of peripheral devices (e.g., a peripheral device coupled via a Universal Serial Bus (USB)).

(69) Moreover, the communication components **940** may detect identifiers or include components operable to detect identifiers. For example, the communication components **940** may include Radio Frequency Identification (RFID) tag reader components, NFC smart tag detection components, optical reader components (e.g., an optical sensor to detect one-dimensional bar codes such as Universal Product Code (UPC) bar code, multi-dimensional bar codes such as Quick Response (QR) code, Aztec code, Data Matrix, Dataglyph, MaxiCode, PDF417, Ultra Code, UCC RSS-2D bar code, and other optical codes), or acoustic detection components (e.g., microphones to identify tagged audio signals). In addition, a variety of information may be derived via the communication components **940**, such as, location via Internet Protocol (IP) geo-location, location via Wi-Fi® signal triangulation, location via detecting a NFC beacon signal that may indicate a particular location, and so forth.

Glossary

(70) “CARRIER SIGNAL” in this context refers to any intangible medium that is capable of storing, encoding, or carrying instructions for execution by the machine, and includes digital or analog communications signals or other intangible medium to facilitate communication of such instructions. Instructions may be transmitted or received over the network using a transmission medium via a network interface device and using any one of a number of well-known transfer protocols.

(71) “CLIENT DEVICE” in this context refers to any machine that interfaces to a communications network to obtain resources from one or more server systems or other client devices. A client device may be, but is not limited to, a mobile phone, desktop computer, laptop, portable digital assistants (PDAs), smart phones, tablets, ultra books, netbooks, laptops, multi-processor systems, microprocessor-based or programmable consumer electronics, game consoles, set-top boxes, or any other communication device that a user may use to access a network.

(72) “COMMUNICATIONS NETWORK” in this context refers to one or more portions of a network that may be an ad hoc network, an intranet, an extranet, a virtual private network (VPN), a local area network (LAN), a wireless LAN (WLAN), a wide area network (WAN), a wireless WAN (WWAN), a metropolitan area network (MAN), the Internet, a portion of the Internet, a portion of

the Public Switched Telephone Network (PSTN), a plain old telephone service (POTS) network, a cellular telephone network, a wireless network, a Wi-Fi® network, another type of network, or a combination of two or more such networks. For example, a network or a portion of a network may include a wireless or cellular network and the coupling may be a Code Division Multiple Access (CDMA) connection, a Global System for Mobile communications (GSM) connection, or other type of cellular or wireless coupling. In this example, the coupling may implement any of a variety of types of data transfer technology, such as Single Carrier Radio Transmission Technology (1×RTT), Evolution-Data Optimized (EVDO) technology, General Packet Radio Service (GPRS) technology, Enhanced Data rates for GSM Evolution (EDGE) technology, third Generation Partnership Project (3GPP) including 3G, fourth generation wireless (4G) networks, Universal Mobile Telecommunications System (UMTS), High Speed Packet Access (HSPA), Worldwide Interoperability for Microwave Access (WiMAX), Long Term Evolution (LTE) standard, others defined by various standard setting organizations, other long range protocols, or other data transfer technology.

(73) “EMPIERAL MESSAGE” in this context refers to a message that is accessible for a time-limited duration. An ephemeral message may be a text, an image, a video and the like. The access time for the ephemeral message may be set by the message sender. Alternatively, the access time may be a default setting or a setting specified by the recipient. Regardless of the setting technique, the message is transitory.

(74) “MACHINE-READABLE MEDIUM” in this context refers to a component, device or other tangible media able to store instructions and data temporarily or permanently and may include, but is not be limited to, random-access memory (RAM), read-only memory (ROM), buffer memory, flash memory, optical media, magnetic media, cache memory, other types of storage (e.g., Erasable Programmable Read-Only Memory (EEPROM)) and/or any suitable combination thereof. The term “machine-readable medium” should be taken to include a single medium or multiple media (e.g., a centralized or distributed database, or associated caches and servers) able to store instructions. The term “machine-readable medium” shall also be taken to include any medium, or combination of multiple media, that is capable of storing instructions (e.g., code) for execution by a machine, such that the instructions, when executed by one or more processors of the machine, cause the machine to perform any one or more of the methodologies described herein. Accordingly, a “machine-readable medium” refers to a single storage apparatus or device, as well as “cloud-based” storage systems or storage networks that include multiple storage apparatus or devices. The term “machine-readable medium” excludes signals per se.

(75) “COMPONENT” in this context refers to a device, physical entity or logic having boundaries defined by function or subroutine calls, branch points, application program interfaces (APIs), or other technologies that provide for the partitioning or modularization of particular processing or control functions. Components may be combined via their interfaces with other components to carry out a machine process. A component may be a packaged functional hardware unit designed for use with other components and a part of a program that usually performs a particular function of related functions. Components may constitute either software components (e.g., code embodied on a machine-readable medium) or hardware components. A “hardware component” is a tangible unit capable of performing certain operations and may be configured or arranged in a certain physical manner. In various example embodiments, one or more computer systems (e.g., a standalone computer system, a client computer system, or a server computer system) or one or more hardware components of a computer system (e.g., a processor or a group of processors) may be configured by software (e.g., an application or application portion) as a hardware component that operates to perform certain operations as described herein. A hardware component may also be implemented mechanically, electronically, or any suitable combination thereof. For example, a hardware component may include dedicated circuitry or logic that is permanently configured to perform certain operations. A hardware component may be a special-purpose processor, such as a

Field-Programmable Gate Array (FPGA) or an Application Specific Integrated Circuit (ASIC). A hardware component may also include programmable logic or circuitry that is temporarily configured by software to perform certain operations. For example, a hardware component may include software executed by a general-purpose processor or other programmable processor. Once configured by such software, hardware components become specific machines (or specific components of a machine) uniquely tailored to perform the configured functions and are no longer general-purpose processors. It will be appreciated that the decision to implement a hardware component mechanically, in dedicated and permanently configured circuitry, or in temporarily configured circuitry (e.g., configured by software) may be driven by cost and time considerations. Accordingly, the phrase “hardware component” (or “hardware-implemented component”) should be understood to encompass a tangible entity, be that an entity that is physically constructed, permanently configured (e.g., hardwired), or temporarily configured (e.g., programmed) to operate in a certain manner or to perform certain operations described herein. Considering embodiments in which hardware components are temporarily configured (e.g., programmed), each of the hardware components need not be configured or instantiated at any one instance in time. For example, where a hardware component comprises a general-purpose processor configured by software to become a special-purpose processor, the general-purpose processor may be configured as respectively different special-purpose processors (e.g., comprising different hardware components) at different times. Software accordingly configures a particular processor or processors, for example, to constitute a particular hardware component at one instance of time and to constitute a different hardware component at a different instance of time. Hardware components can provide information to, and receive information from, other hardware components. Accordingly, the described hardware components may be regarded as being communicatively coupled. Where multiple hardware components exist contemporaneously, communications may be achieved through signal transmission (e.g., over appropriate circuits and buses) between or among two or more of the hardware components. In embodiments in which multiple hardware components are configured or instantiated at different times, communications between such hardware components may be achieved, for example, through the storage and retrieval of information in memory structures to which the multiple hardware components have access. For example, one hardware component may perform an operation and store the output of that operation in a memory device to which it is communicatively coupled. A further hardware component may then, at a later time, access the memory device to retrieve and process the stored output. Hardware components may also initiate communications with input or output devices, and can operate on a resource (e.g., a collection of information). The various operations of example methods described herein may be performed, at least partially, by one or more processors that are temporarily configured (e.g., by software) or permanently configured to perform the relevant operations. Whether temporarily or permanently configured, such processors may constitute processor-implemented components that operate to perform one or more operations or functions described herein. As used herein, “processor-implemented component” refers to a hardware component implemented using one or more processors. Similarly, the methods described herein may be at least partially processor-implemented, with a particular processor or processors being an example of hardware. For example, at least some of the operations of a method may be performed by one or more processors or processor-implemented components. Moreover, the one or more processors may also operate to support performance of the relevant operations in a “cloud computing” environment or as a “software as a service” (SaaS). For example, at least some of the operations may be performed by a group of computers (as examples of machines including processors), with these operations being accessible via a network (e.g., the Internet) and via one or more appropriate interfaces (e.g., an Application Program Interface (API)). The performance of certain of the operations may be distributed among the processors, not only residing within a single machine, but deployed across a number of machines. In some example embodiments, the processors or processor-implemented

components may be located in a single geographic location (e.g., within a home environment, an office environment, or a server farm). In other example embodiments, the processors or processor-implemented components may be distributed across a number of geographic locations.

(76) “PROCESSOR” in this context refers to any circuit or virtual circuit (a physical circuit emulated by logic executing on an actual processor) that manipulates data values according to control signals (e.g., “commands”, “op codes”, “machine code”, etc.) and which produces corresponding output signals that are applied to operate a machine. A processor may, for example, be a Central Processing Unit (CPU), a Reduced Instruction Set Computing (RISC) processor, a Complex Instruction Set Computing (CISC) processor, a Graphics Processing Unit (GPU), a Digital Signal Processor (DSP), an Application Specific Integrated Circuit (ASIC), a Radio-Frequency Integrated Circuit (RFIC) or any combination thereof. A processor may further be a multi-core processor having two or more independent processors (sometimes referred to as “cores”) that may execute instructions contemporaneously.

(77) “TIMESTAMP” in this context refers to a sequence of characters or encoded information identifying when a certain event occurred, for example giving date and time of day, sometimes accurate to a small fraction of a second.

(78) “LIFT” in this context is a measure of the performance of a targeted model at predicting or classifying cases as having an enhanced response (with respect to a population as a whole), measured against a random choice targeting model.

(79) “PHONEME ALIGNMENT” in this context, a phoneme is a unit of speech that differentiates one word from another. One phoneme may consist of a sequence of closure, burst, and aspiration events; or, a diphthong may transition from a back vowel to a front vowel. A speech signal may therefore be described not only by what phonemes it contains, but also the locations of the phonemes. Phoneme alignment may therefore be described as a “time-alignment” of phonemes in a waveform, in order to determine an appropriate sequence and location of each phoneme in a speech signal.

(80) “AUDIO-TO-VISUAL CONVERSION” in this context refers to the conversion of audible speech signals into visible speech, wherein the visible speech may include a mouth shape representative of the audible speech signal.

(81) “TIME DELAYED NEURAL NETWORK (TDNN)” in this context, a TDNN is an artificial neural network architecture whose primary purpose is to work on sequential data. An example would be converting continuous audio into a stream of classified phoneme labels for speech recognition.

(82) “BI-DIRECTIONAL LONG-SHORT TERM MEMORY (BLSTM)” in this context refers to a recurrent neural network (RNN) architecture that remembers values over arbitrary intervals. Stored values are not modified as learning proceeds. RNNs allow forward and backward connections between neurons. BLSTM are well-suited for the classification, processing, and prediction of time series, given time lags of unknown size and duration between events.

Claims

1. A method comprising: receiving an input that correlates a graphical icon from among a set of graphical icons with a contextual condition by a first client device associated with a first user account; initiating a communication session between the first client device and a second client device associated with a second user account; capturing image data depicting the first user from a camera associated with the first client device based on the communication session; identifying a set of facial landmarks in the image data, each facial landmark corresponding to a facial feature of the first user; generating facial tracking data comprising a set of points, each point corresponding to the identified set of facial landmarks; detecting the contextual condition; and transposing the set of points upon a display of the graphical icon correlated with the contextual condition at the second

client device.

2. The method of claim 1, wherein the graphical icon includes a graphical avatar.

3. The method of claim 1, wherein the contextual condition include one or more of: attributes of the client device; location data; and a time of day.

4. The method of claim 1, further comprising: generating a message that includes a presentation of the graphical icon based on the transposing the set of points upon the display of the graphical icon at the second client device.

5. The method of claim 1, further comprising: receiving additional facial tracking from the first client device; and animating the graphical icon based on the transposing the set of points upon the display of the graphical icon and the additional facial tracking data.

6. A system comprising: a memory; and at least one hardware processor coupled to the memory and comprising instructions that causes the system to perform operations comprising: receiving an input that correlates a graphical icon from among a set of graphical icons with a contextual condition by a first client device associated with a first user account; initiating a communication session between the first client device and a second client device associated with a second user account; capturing image data depicting the first user from a camera associated with the first client device based on the communication session; identifying a set of facial landmarks in the image data, each facial landmark corresponding to a facial feature of the first user; generating facial tracking data comprising a set of points, each point corresponding to the identified set of facial landmarks; detecting the contextual condition; and transposing the set of points upon a display of the graphical icon correlated with the contextual condition at the second client device.

7. The system of claim 6, wherein the graphical icon includes a graphical avatar.

8. The system of claim 6, wherein the contextual factors include one or more of: attributes of the client device; location data; and a time of day.

9. The system of claim 6, further comprising: generating a message that includes a presentation of the graphical icon based on the transposing the set of points upon the display of the graphical icon at the second client device.

10. The system of claim 6, further comprising: receiving additional facial tracking from the first client device; and animating the graphical icon based on the transposing the set of points upon the display of the graphical icon and the additional facial tracking data.

11. A non-transitory machine-readable storage medium comprising instructions that, when executed by one or more processors of a machine, cause the machine to perform operations comprising: receiving an input that correlates a graphical icon from among a set of graphical icons with a contextual condition by a first client device associated with a first user account; initiating a communication session between the first client device and a second client device associated with a second user account; capturing image data depicting the first user from a camera associated with the first client device based on the communication session; identifying a set of facial landmarks in the image data, each facial landmark corresponding to a facial feature of the first user; generating facial tracking data comprising a set of points, each point corresponding to the identified set of facial landmarks; detecting the contextual condition; and transposing the set of points upon a display of the graphical icon correlated with the contextual condition at the second client device.

12. The non-transitory machine-readable storage medium of claim 11, wherein the graphical icon includes a graphical avatar.

13. The non-transitory machine-readable storage medium of claim 11, wherein the contextual factors include one or more of: attributes of the client device; location data; and a time of day.

14. The non-transitory machine-readable storage medium of claim 11, further comprising: generating a message that includes a presentation of the graphical icon based on the transposing the set of points upon the display of the graphical icon at the second client device.
