

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12401131
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Seo; Yunsik et al.

Radar antenna

Abstract

Disclosed is a radar antenna which has a shielding space corresponding to each antenna of an antenna body by using an accommodation hole of a shielding member to prevent mutual coupling between antennas. The disclosed radar antenna comprises an antenna body which has a first surface and a second surface and in which a plurality first slot groups are formed to be spaced apart from each other on the first surface, and a shielding member which is stacked on the first surface of the antenna body and in which a plurality of accommodation holes are formed to respectively overlap the plurality of first slot groups.

Inventors:	Seo; Yunsik (Cheonan-si, KR), Baek; Hyungil (Cheonan-si, KR), Lee; Seho (Cheonan-si, KR), Park; Hyunjoo (Cheonan-si, KR)
Applicant:	AMOSENSE CO., LTD. (Cheonan-si, KR)
Family ID:	1000008781941
Assignee:	AMOSENSE CO., LTD. (Cheonan-si, KR)
Appl. No.:	18/034696
Filed (or PCT Filed):	October 28, 2021
PCT No.:	PCT/KR2021/015265
PCT Pub. No.:	WO2022/092830
PCT Pub. Date:	May 05, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230395982 A1	Dec. 07, 2023

Foreign Application Priority Data

Publication Classification**Int. Cl.:** H01Q13/10 (20060101); G01S7/03 (20060101); H01Q1/52 (20060101)**U.S. Cl.:****CPC** H01Q13/106 (20130101); G01S7/03 (20130101); H01Q1/526 (20130101);**Field of Classification Search****CPC:** H01Q (13/106); H01Q (1/526); H01Q (1/521); H01Q (21/064); H01Q (1/3233); G01S (7/03); G01S (7/038); G01S (13/931)

References Cited**U.S. PATENT DOCUMENTS**

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
11923609	12/2023	Park	N/A	H01Q 13/18
2002/0101385	12/2001	Huor	343/770	H01Q 21/005
2008/0316124	12/2007	Hook	343/705	H01Q 21/064
2017/0244173	12/2016	Moon	N/A	H01Q 13/106
2020/0059000	12/2019	Kamo et al.	N/A	N/A
2023/0231314	12/2022	Lim	342/175	H01Q 21/005

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
103811877	12/2013	CN	N/A
2007-013531	12/2006	JP	N/A
2017-175595	12/2016	JP	N/A
2020-031426	12/2019	JP	N/A

OTHER PUBLICATIONS

KR Office Action dated Oct. 27, 2022 as received in Application No. 10-2020-0142690. cited by applicant

Primary Examiner: Tran; Hai V

Attorney, Agent or Firm: Maschoff Brennan

Background/Summary**TECHNICAL FIELD**

(1) The present disclosure relates to an antenna, and more particularly, to a radar antenna.

BACKGROUND ART

(2) It is on trend to use a radar antenna for signal transmission and reception for detecting an object

around a vehicle. The radar antenna radiates radio waves onto an object, and makes it possible to detect the existence/nonexistence, distance, movement direction, movement speed, identification, and classification of the object by means of reflected waves or scattered waves having bounced off the object.

(3) Recently, for an advancement of anti-collision radar of an autonomous vehicle to cope with a driverless vehicle era, technologies to widen the detection range and to heighten the performance of such a radar antenna have been researched.

(4) In the radar antenna in the related art, since a plurality of radiators that play different roles are arranged, mutual coupling occurs among the radiators to cause independent performances of the radiators to deteriorate or to cause the radiation performance of the antenna to deteriorate.

(5) The above matter described as a background technology is to help understanding of the background of the present disclosure, and may include the matter that is not the technology in the related art already known to those of ordinary skill in the art to which the present disclosure pertains.

DISCLOSURE

Technical Problem

(6) The present disclosure has been proposed to solve the above-described problems, and an object of the present disclosure is to provide a radar antenna, which can prevent mutual coupling between antennas by forming a shielding space corresponding to each antenna of an antenna body by using accommodation holes of shielding members.

Technical Solution

(7) In order to achieve that above object, a radar antenna according to an embodiment of the present disclosure includes: an antenna body which has a first surface and a second surface and in which a plurality of first slot groups are formed to be spaced apart from one another on the first surface; and a shielding member which is stacked on the first surface of the antenna body and in which a plurality of accommodation holes are formed to overlap the plurality of first slot groups, respectively.

(8) The first slot group may include a plurality of first slots in a matrix arrangement, and the first surface of the antenna body may include a plurality of areas in which the plurality of first slots are disposed. In this case, the plurality of accommodation holes may overlap the plurality of areas in which the plurality of first slots are disposed.

(9) The first surface of the antenna body and inner walls of the accommodation holes of the shielding member may form shielding spaces, and the inner walls of the accommodation holes may be spaced apart from outer circumference of areas occupied by the first slot group over a predetermined distance. In other words, the inner walls of the accommodation holes may be spaced apart from the outer circumference of the areas formed by the plurality of first slots included in the first slot group over the predetermined distance.

(10) The shielding member may include a plurality of shielding plates stacked on the antenna body to be spaced apart from one another, two or more accommodation holes may be formed on the shielding plates of the shielding member, and the shielding plates of the shielding member may be stacked on the antenna body so as to overlap two or more of the plurality of first slot groups. In this case, a protrusion part extending in an outward direction or a groove part formed in an inward direction of the shielding plates may be formed on at least one of the plurality of shielding plates.

(11) The shielding member may include a plurality of shielding blocks stacked on the antenna body to be spaced apart from one another, one accommodation hole may be formed on the shielding blocks of the shielding member, and the shielding blocks of the shielding member may be stacked on the antenna body so as to overlap one of the plurality of first slot groups.

(12) The shielding member may include a chamfer part chamfered along a corner formed by the accommodation hole, and the chamfer part may be formed by chamfering the corner in a direction of the first surface of the shielding member.

(13) The radar antenna according to an embodiment of the present disclosure may further include a slot member formed in a metal frame shape and configured to be inserted into the first slot formed on the antenna body.

Advantageous Effects

(14) According to the present disclosure, the radar antenna has the effect of being able to prevent the mutual coupling among the antennas formed on the antenna body since the shielding spaces corresponding to the respective antennas of the antenna body are formed by using the accommodation holes of the shielding member. That is, according to the radar antenna, since the shielding member on which the accommodation holes are formed is stacked on the antenna body on which the plurality of antennas (slots) are formed, the antennas can be disposed in the shielding spaces formed by the accommodation holes and the antenna body, and thus the mutual coupling with other antennas can be prevented.

(15) Further, since the radar antenna can prevent the mutual coupling among the antennas through stacking of the shielding member on the antenna body, the independent antenna performances of the plurality of antennas formed on the antenna body can be maintained, and thus the radiation performance of the radar antenna can be prevented from being degraded.

Description

DESCRIPTION OF DRAWINGS

(1) FIG. 1 is a perspective view of a radar antenna according to an embodiment of the present disclosure.

(2) FIG. 2 is an exploded perspective view of a radar antenna when viewed in a direction of a first surface of the radar antenna according to an embodiment of the present disclosure.

(3) FIG. 3 is an exploded perspective view of a radar antenna when viewed in a direction of a second surface that faces a first surface of the radar antenna according to an embodiment of the present disclosure.

(4) FIG. 4 is a view explaining a first slot formed on the antenna body of FIG. 1.

(5) FIG. 5 is a view explaining a second slot formed on the antenna body of FIG. 1.

(6) FIGS. 6 and 7 are views explaining a waveguide formed on the antenna body of FIG. 1.

(7) FIG. 8 is a view explaining a modified example of the antenna body of FIG. 1.

(8) FIGS. 9 and 10 are views explaining the shielding member of FIG. 1.

(9) FIG. 11 is a view explaining accommodation grooves of the shielding member of FIG. 9.

(10) FIGS. 12 and 13 are views explaining a first modified example of the shielding member of FIG. 1.

(11) FIG. 14 is a view explaining a second modified example of the shielding member of FIG. 1.

(12) FIG. 15 is a view explaining an example of a chamfered surface formed in accommodation holes of the shielding member of FIG. 1.

(13) FIGS. 16 to 19 are views explaining an example of the chamfered surface of FIG. 1 formed in different shapes.

MODE FOR INVENTION

(14) For detailed explanation to the extent that those of ordinary skill in the art to which the present disclosure pertains can easily embody the technical idea of the present disclosure, the most preferred embodiment of the present disclosure will be described with reference to the accompanying drawings. First, in giving reference numerals to constituent elements of the respective drawings, it is to be noted that the same constituent elements have possibly the same reference numerals although they are denoted in different drawings. Further, in describing the present disclosure, detailed explanation of related known constitutions or functions will be omitted in case that such detailed explanation may obscure the subject matter of the present disclosure.

(15) Referring to FIGS. 1 to 3, a radar antenna **100** according to an embodiment of the present disclosure is configured to include antennas and a shielding member **140**.

(16) An antenna body **120** forms an appearance of the radar antenna **100**, and is formed in a flat plate shape having a predetermined thickness. The antenna body **120** has a first surface **F1** and a second surface **F2** facing the first surface **F1**. In this case, a board is disposed on the second surface **F2** of the antenna body **120**. The board **10** transmits radio waves to outside through the radar antenna **100**, and receives and performs signal processing of the radio waves received through the radar antenna **100**. Here, it is exemplified that the first surface **F1** is a front surface of the antenna body **120**, and the second surface **F2** is a rear surface of the antenna body **120**.

(17) Referring to FIG. 4, a plurality of first slots **121** are formed on the first surface **F1** of the antenna body **120**. The plurality of first slots **121** formed on the first surface **F1** of the antenna body **120** are classified into a plurality of first slot groups, and the plurality of first slot groups constitute respective antennas. In this case, the first slot group **121** constitutes one of an antenna for radiation and an antenna for reception. Here, the antenna for radiation is an antenna that radiates radio waves, and the antenna for reception is an antenna that receives the radio waves bounced and reflected from an object hit by the radio waves radiated from the antenna for radiation.

(18) As an example, referring to FIG. 4, on the first surface **F1** of the antenna body **120**, a plurality of the (1-1)-th slots **121a**, a plurality of the (1-2)-th slots **121b**, a plurality of the (1-3)-th slots **121c**, a plurality of the (1-4)-th slots **121d**, a plurality of the (1-5)-th slots **121e**, and a plurality of the (1-6)-th slots **121f** are formed, and 6 antennas are formed.

(19) The plurality of the (1-1)-th slots **121a** constitute a first antenna through matrix arrangement in a first area **A1**. The first area **A1** is a partial area of the first surface **F1** of the antenna body **120**, and is an area adjacent to a first side surface **S1** and a fourth side surface **S4** of the antenna body **120**.

(20) The plurality of the (1-2)-th slots **121b** constitute a second antenna through matrix arrangement in a second area **A2**. The second area **A2** is a partial area of the first surface **F1** of the antenna body **120**, and is an area adjacent to a third side surface **S3** and spaced apart for a predetermined distance from the first area **A1** downward.

(21) The plurality of the (1-3)-th slots **121c** constitute a third antenna through matrix arrangement in a third area **A3**. The third area **A3** is a partial area of the first surface **F1** of the antenna body **120**, and is an area adjacent to a first side surface **S1** and spaced apart for a predetermined distance from the first area **A1** rightward.

(22) The plurality of the (1-4)-th slots **121d** constitute a fourth antenna through matrix arrangement in a fourth area **A4**. The fourth area **A4** is a partial area of the first surface **F1** of the antenna body **120**, and is an area adjacent to the third side surface **S3**, spaced apart for a predetermined distance from the second area **A2** rightward, and spaced apart for a predetermined distance from the third area **A3** downward.

(23) The plurality of the (1-5)-th slots **121e** constitute a fifth antenna through matrix arrangement in a fifth area **A5**. The fifth area **A5** is a partial area of the first surface **F1** of the antenna body **120**, and is an area adjacent to the first side surface **S1** and the second side surface **S2**, and spaced apart for a predetermined distance from the third area **A3** rightward.

(24) The plurality of the (1-6)-th slots **121f** constitute a sixth antenna through matrix arrangement in a sixth area **A6**. The sixth area **A6** is a partial area of the first surface **F1** of the antenna body **120**, and is an area adjacent to the second side surface **S2** and the third side surface **S3**, spaced apart for a predetermined distance from the fourth area **A4** rightward, and spaced apart for a predetermined distance from the fifth area **A5** downward.

(25) In this case, the first to sixth antennas operate as radiation antennas radiating the radio waves or reception antennas receiving the radio waves bounced and reflected from the object hit by the radio waves radiated from the radiation antenna.

(26) Here, although it is exemplified that 6 antennas are formed in order to explain the antenna body **120** in FIG. 4, the number of antennas may be changed depending on the required antenna

characteristic, and thus is not limited thereto.

(27) A plurality of second slots **122** are formed on the second surface F2 of the antenna body **120**. The plurality of second slots **122** constitute a reception port and a transmission port. That is, the plurality of second slots **122** are configured as the transmission port connected to a transmission terminal of the board **10**, or are configured as the reception port that is connected to a reception terminal of the board **10**.

(28) The plurality of second slots **122** are configured to match the antennas formed on the first surface F1 of the antenna body **120**. One or more second slots **122** match the antennas formed on the first surface F1 of the antenna body **120**. Accordingly, the number of second slots **122** is equal to or larger than the number of antennas formed on the first surface F1 of the antenna body **120**.

(29) As an example, referring to FIG. 5, on the second surface F2 of the antenna body **120**, the (2-1)-th slot **122a**, the (2-2)-th slot **122b**, the (2-3)-th slot **122c**, the (2-4)-th slot **122d**, the (2-5)-th slot **122e**, and the (2-6)-th slot **122f** are formed.

(30) The (2-1)-th slot **122a** is formed on the second surface F2 of the antenna body **120**, but is formed to overlap the first area A1 on the first surface F1 of the antenna body **120**.

(31) The (2-2)-th slot **122b** is formed on the second surface F2 of the antenna body **120**, but is formed to overlap the second area A2 on the first surface F1 of the antenna body **120**.

(32) The (2-3)-th slot **122c** is formed on the second surface F2 of the antenna body **120**, but is formed to overlap the third area A3 on the first surface F1 of the antenna body **120**.

(33) The (2-4)-th slot **122d** is formed on the second surface F2 of the antenna body **120**, but is formed to overlap the fourth area A4 on the first surface F1 of the antenna body **120**.

(34) The (2-5)-th slot **122e** is formed on the second surface F2 of the antenna body **120**, but is formed to overlap the fifth area A5 on the first surface F1 of the antenna body **120**.

(35) The (2-6)-th slot **122f** is formed on the second surface F2 of the antenna body **120**, but is formed to overlap the sixth area A6 on the first surface F1 of the antenna body **120**.

(36) A plurality of waveguides **123** that are paths for moving the radio waves are formed inside the antenna body **120**. The waveguides **123** form radio wave movement paths which connect the plurality of first slots **121** and the plurality of second slots **122** to each other, and move the radio waves between the first slots **121** and the second slots **122**.

(37) As an example, referring to FIGS. 6 and 7, the waveguide **123** is formed inside the antenna body **120**, and forms the radio wave movement path for moving (radiating) the radio waves output from the board **10** to an outside of the radar antenna **100** or moving the radio waves reflected from an object to the board **10** (i.e., reception terminal).

(38) Meanwhile, since the radar antenna is an antenna composed of a plurality of slots, the antenna performance is sensitively changed depending on the dimensions (size) of the slots in a high frequency band of about 76.5 GHz.

(39) In case that the radar antenna is produced of plastic to lower the product unit price (production unit price), the radar antenna has the problems in that it is difficult to precisely process the dimensions (size) of the slots due to the production tolerance, and it is difficult to implement the constant antenna performance due to the dimension change of the slots.

(40) Accordingly, referring to FIG. 8, the radar antenna **100** according to an embodiment of the present disclosure may further include a plurality of slot members **150** inserted into the first slots **121**.

(41) The slot member **150** is formed of a metal material, and is formed in the shape of a frame in which the slot is formed. The slot member **150** is fixedly inserted into the first slot **121** of the antenna body **120**. For this, the slot member **150** is formed to have the same dimensions as the design dimensions of the first slot **121**.

(42) In the radar antenna **100**, since the slot member **150** is inserted in a manner of being fitted into the first slot **121**, the production tolerance can be reduced, and thus the dimensions of the first slot **121** can be constantly formed.

(43) Further, in case that dimension inferiority of the first slot **121** occurs, the dimensions can be constantly maintained by replacing the slot member **150**, and thus the radar antenna **100** has an additional effect of heightening the yield.

(44) Further, the radar antenna **100** can constantly implement the antenna performance by making the dimensions of the first slot **121** constant.

(45) The above-described antenna body **120** may operate as the radar antenna **100** by itself.

However, since the antenna body **120** includes a plurality of antennas which transmit/receive the frequency band to/from each other or operate for frequency transmission or reception, mutual coupling among the antennas may occur to deteriorate independent antenna performances.

(46) Accordingly, the radar antenna **100** according to an embodiment of the present disclosure further includes the shielding member **140** stacked on the first surface **F1** of the antenna body **120** to prevent the mutual coupling among the antennas.

(47) The shielding member **140** is stacked on the first surface **F1** of the antenna body **120** on which the plurality of first slots **121** are formed. The shielding member **140** may be formed of a metal that shields signals to prevent the mutual coupling between the antennas formed by the plurality of first slots **121**. However, the shielding member **140** may be replaced by another material other than the metal, or another metal depending on the antenna specifications required in the radar antenna **100**.

(48) Further, the thickness of the shielding member **140** and the gap between the first slot **121** and the shielding member **140** may differ depending on the antenna characteristics, antenna sizes, and surrounding environments. Accordingly, in an embodiment of the present disclosure, the material, shape, thickness, and gap of the shielding member **140** are not limited to numbers.

(49) Referring to FIGS. **9** and **10**, the shielding member **140** has a first surface **F3** and a second surface **F4**, and the second surface **F4** is stacked on the first surface **F1** of the antenna body **120**.

(50) A plurality of accommodation holes **141** for accommodating the first slots **121** are formed on the shielding member **140**. The accommodation holes **141** accommodate some of the plurality of first slots **121**, but accommodate the plurality of first slots **121** belonging to the same slot group. The accommodation holes **141** are formed to penetrate the shielding member **140** in the shape of a flat plate, and are formed in the shape of a quadrangle when viewed in a direction of the first surface **F1** of the antenna body **120**. In this case, the accommodation holes **141** may be formed in another shape, such as in the shape of a circle, depending on the required antenna specifications.

(51) The shielding member **140** forms shielding spaces for preventing the mutual coupling among the antennas formed by the plurality of first slots **121**. As the shielding member **140** is stacked on the antenna body **120**, the accommodation holes **141** and the first surface **F1** of the antenna body **120** form the shielding spaces. The inner walls of the accommodation holes **141** form shielding walls that are outer walls of the shielding spaces for shielding between the antennas formed by the first slots **121**, and the first surface **F1** of the antenna body **120** forms the bottom surface of the shielding spaces. Accordingly, the antenna body **120** and the shielding member **140** form the shielding spaces being open in the direction of the first surface **F3** of the shielding member **140**. Through this, the shielding member **140** can prevent the mutual coupling among the antennas being formed by the plurality of first slots **121**.

(52) As an example, the plurality of accommodation holes **141** include a first accommodation hole **141a**, a second accommodation hole **141b**, a third accommodation hole **141c**, a fourth accommodation hole **141d**, a fifth accommodation hole **141e**, and a sixth accommodation hole **141f**.

(53) The first accommodation hole **141a** is formed in an area that overlaps the first area **A1** of the antenna body **120** on which a plurality of the (1-1)-th slots **121a** are formed. As the shielding member **140** is stacked on the antenna body **120**, the first accommodation hole **141a** accommodates the plurality of the (1-1)-th slots **121a**. On the inner wall of the first accommodation hole **141a** and the first surface **F1** of the antenna body **120**, the first area **A1** forms first shielding spaces **SA1**, and since the first shielding spaces **SA1** are open in the direction of the first surface **F3** of the shielding

member **140**, the first shielding spaces **SA1** do not exert an influence on the radiation and reception of the radio waves, and block the mutual coupling between the first antenna being formed by the plurality of the (1-1)-th slots **121a** and other antennas.

(54) The second accommodation hole **141b** is formed in an area that overlaps the second area **A2** of the antenna body **120** on which a plurality of the (1-2)-th slots **121b** are formed. As the shielding member **140** is stacked on the antenna body **120**, the second accommodation hole **141b** accommodates the plurality of the (1-2)-th slots **121b**. On the inner wall of the second accommodation hole **141b** and the first surface **F1** of the antenna body **120**, the second area **A2** forms second shielding spaces **SA2**, and since the second shielding spaces **SA2** are open in the direction of the first surface **F3** of the shielding member **140**, the second shielding spaces **SA2** do not exert an influence on the radiation and reception of the radio waves, and block the mutual coupling between the second antenna being formed by the plurality of the (1-2)-th slots **121b** and other antennas.

(55) The third accommodation hole **141c** is formed in an area that overlaps the third area **A3** of the antenna body **120** on which a plurality of the (1-3)-th slots **121c** are formed. As the shielding member **140** is stacked on the antenna body **120**, the third accommodation hole **141c** accommodates the plurality of the (1-3)-th slots **121c**. On the inner wall of the third accommodation hole **141c** and the first surface **F1** of the antenna body **120**, the third area **A3** forms third shielding spaces **SA3**, and since the third shielding spaces **SA3** are open in the direction of the first surface **F3** of the shielding member **140**, the third shielding spaces **SA3** do not exert an influence on the radiation and reception of the radio waves, and block the mutual coupling between the third antenna being formed by the plurality of the (1-3)-th slots **121c** and other antennas.

(56) The fourth accommodation hole **141d** is formed in an area that overlaps the fourth area **A4** of the antenna body **120** on which a plurality of the (1-4)-th slots **121d** are formed. As the shielding member **140** is stacked on the antenna body **120**, the fourth accommodation hole **141d** accommodates the plurality of the (1-4)-th slots **121d**. On the inner wall of the fourth accommodation hole **141d** and the first surface **F1** of the antenna body **120**, the fourth area **A4** forms fourth shielding spaces **SA4**, and since the fourth shielding spaces **SA4** are open in the direction of the first surface **F3** of the shielding member **140**, the fourth shielding spaces **SA4** do not exert an influence on the radiation and reception of the radio waves, and block the mutual coupling between the fourth antenna being formed by the plurality of the (1-4)-th slots **121d** and other antennas.

(57) The fifth accommodation hole **141e** is formed in an area that overlaps the fifth area **A5** of the antenna body **120** on which a plurality of the (1-5)-th slots **121e** are formed. As the shielding member **140** is stacked on the antenna body **120**, the fifth accommodation hole **141e** accommodates the plurality of the (1-5)-th slots **121e**. On the inner wall of the fifth accommodation hole **141e** and the first surface **F1** of the antenna body **120**, the fifth area **A5** forms fifth shielding spaces **SA5**, and since the fifth shielding spaces **SA5** are open in the direction of the first surface **F3** of the shielding member **140**, the fifth shielding spaces **SA5** do not exert an influence on the radiation and reception of the radio waves, and block the mutual coupling between the fifth antenna being formed by the plurality of the (1-5)-th slots **121e** and other antennas.

(58) The sixth accommodation hole **141f** is formed in an area that overlaps the sixth area **A6** of the antenna body **120** on which a plurality of the (1-6)-th slots **121f** are formed. As the shielding member **140** is stacked on the antenna body **120**, the sixth accommodation hole **141f** accommodates the plurality of the (1-6)-th slots **121f**. On the inner wall of the sixth accommodation hole **141f** and the first surface **F1** of the antenna body **120**, the sixth area **A6** forms sixth shielding spaces **SA6**, and since the sixth shielding spaces **SA6** are open in the direction of the first surface **F3** of the shielding member **140**, the sixth shielding spaces **SA6** do not exert an influence on the radiation and reception of the radio waves, and block the mutual coupling between the sixth antenna being formed by the plurality of the (1-6)-th slots **121f** and other antennas.

(59) Meanwhile, if the inner walls of the accommodation holes and the outer circumference of the area in which the first slots **121** are formed are spaced apart from each other below a predetermined gap, the radiation or reception performance of the radio waves may deteriorate.

(60) Accordingly, referring to FIG. **11**, the inner walls of the accommodation holes **141** are disposed to be spaced apart from the first slots **121** formed on the first surface **F1** of the antenna body **120** over a predetermined gap **d**. That is, the inner walls of the accommodation holes **141** are disposed to be spaced apart from the outer circumference of the area in which the first slots **121** are formed over the predetermined gap (predetermined distance) **d**. Here, the predetermined gap **d** may differ depending on the size of the radar antenna **100** and the antenna characteristics, and is not limited to numbers.

(61) Referring to FIG. **12**, the shielding member **140** may include a plurality of shielding plates **142**. That is, the shielding member **140** may include a first shielding plate **142a**, a second shielding plate **142b**, and a third shielding plate **142c**.

(62) The first shielding plate **142a** is stacked on the first surface **F1** of the antenna body **120**, but is stacked to overlap the first area **A1** and the second area **A2** of the antenna body **120**. The first accommodation hole **141a** and the second accommodation hole **141b** are formed on the first shielding plate **142a**, and the first shielding plate **142a** forms the first shielding space **SA1** and the second shielding space **SA2** as being stacked on the antenna body **120**.

(63) The second shielding plate **142b** is stacked on the first surface **F1** of the antenna body **120**, but is stacked to overlap the third area **A3** and the fourth area **A4** of the antenna body **120**. The third accommodation hole **141c** and the fourth accommodation hole **141d** are formed on the second shielding plate **142b**, and the second shielding plate **142b** forms the third shielding space **SA3** and the fourth shielding space **SA4** as being stacked on the antenna body **120**.

(64) The third shielding plate **142c** is stacked on the first surface **F1** of the antenna body **120**, but is stacked to overlap the fourth area **A4** and the fifth area **A5** of the antenna body **120**. The fifth accommodation hole **141e** and the sixth accommodation hole **141f** are formed on the third shielding plate **142c**, and the third shielding plate **142c** forms the fifth shielding space **SA5** and the sixth shielding space **SA6** as being stacked on the antenna body **120**.

(65) In this case, referring to FIG. **13**, a protrusion part **143** or a groove part **144** may be further formed on the first shielding plate **142a** to the third shielding plate **142c** in accordance with the antenna specifications. Here, it is exemplified that the protrusion part **143** is an area extending in an outward direction (or lateral direction) on the shielding plate **142**, and the groove part **144** is an area formed in an inward direction of the shielding plate **142** through removal of a part of the shielding plate **142**.

(66) Referring to FIG. **14**, the shielding member may be composed of a plurality of shielding blocks **145**.

(67) As an example, the shielding member **140** may include a first shielding block **145a**, a second shielding block **145b**, a third shielding block **145c**, a fourth shielding block **145d**, a fifth shielding block **145e**, and a sixth shielding block **145f**.

(68) The first shielding block **145a** is stacked on the first surface **F1** of the antenna body **120**, but is stacked to overlap the first area **A1** of the antenna body **120**. The first accommodation hole **141a** is formed on the first shielding block **145a**, and the first shielding block **145a** forms the first shielding space **SA1** as being stacked on the antenna body **120**.

(69) The second shielding block **145b** is stacked on the first surface **F1** of the antenna body **120**, but is stacked to overlap the second area **A2** of the antenna body **120**. The second accommodation hole **141b** is formed on the second shielding block **145b**, and the second shielding block **145b** forms the second shielding space **SA2** as being stacked on the antenna body **120**.

(70) The third shielding block **145c** is stacked on the first surface **F1** of the antenna body **120**, but is stacked to overlap the third area **A3** of the antenna body **120**. The third accommodation hole **141c** is formed on the third shielding block **145c**, and the third shielding block **145c** forms the third

shielding space SA3 as being stacked on the antenna body 120.

(71) The fourth shielding block 145d is stacked on the first surface F1 of the antenna body 120, but is stacked to overlap the fourth area A4 of the antenna body 120. The fourth accommodation hole 141d is formed on the fourth shielding block 145d, and the fourth shielding block 145d forms the fourth shielding space SA4 as being stacked on the antenna body 120.

(72) The fifth shielding block 145e is stacked on the first surface F1 of the antenna body 120, but is stacked to overlap the fifth area A5 of the antenna body 120. The fifth accommodation hole 141e is formed on the fifth shielding block 145e, and the fifth shielding block 145e forms the fifth shielding space SA5 as being stacked on the antenna body 120.

(73) The sixth shielding block 145f is stacked on the first surface F1 of the antenna body 120, but is stacked to overlap the sixth area A6 of the antenna body 120. The sixth accommodation hole 141f is formed on the sixth shielding block 145f, and the sixth shielding block 145f forms the sixth shielding space SA6 as being stacked on the antenna body 120.

(74) Referring to FIG. 15, in order to improve a gain of the radar antenna 100, a chamfer part 146 may be formed on the shielding member 140. The chamfer part 146 is formed by chamfering the corner of the area in which the accommodation holes 141 are formed on the shielding member 140. The chamfer part 146 is formed along the upper corner of the shielding member 140.

(75) In this case, the chamfer part 146 may be formed in various shapes in accordance with the antenna characteristics.

(76) As an example, referring to FIG. 16, the chamfer part 146 is formed in a diagonal shape based on a cutting plane obtained by cutting the shielding member 140 based on line A-A', but is chamfered to form a predetermined angle $\theta 1$ with the upper surface of the shielding member 140.

(77) In this case, referring to FIG. 17, the chamfer part 146 is formed in a diagonal shape based on a cutting plane obtained by cutting the shielding member 140 based on line A-A', but is chamfered to form another predetermined angle $\theta 2$ with the upper surface of the shielding member 140.

(78) As another example, referring to FIG. 18, the chamfer part 146 may be formed in the shape of an annular surface obtained by chamfering round the corners based on the cutting plane obtained by cutting the shielding member 140 based on line A-A'.

(79) As another example, referring to FIG. 19, the chamfer part 146 may be formed in the shape of a concave surface obtained by concavely chamfering the corners based on the cutting plane obtained by cutting the shielding member 140 based on line A-A'.

(80) Here, although FIGS. 16 to 19 are exemplarily illustrated for easy explanation of the chamfer part 146, the chamfer part 146 is not limited thereto, and may be modified in various shapes in accordance with the characteristics and the purpose of the antenna.

(81) As described above, although a preferred embodiment according to the present disclosure has been described, it is understood that various modifications are possible, and those of ordinary skill in the corresponding technical field can make various modifications and correction examples without deviating from the claims of the present disclosure.

Claims

1. A radar antenna comprising: an antenna body which has a first surface and a second surface and in which a plurality of first slot groups are formed to be spaced apart from one another on the first surface; a shielding member which is stacked on the first surface of the antenna body and in which a plurality of accommodation holes are formed to overlap the plurality of first slot groups, respectively; and a slot member formed in a metal frame shape and configured to be inserted into a first slot formed on the antenna body.

2. The radar antenna of claim 1, wherein each first slot group of the plurality of first slot groups comprises a plurality of first slots in a matrix arrangement.

3. The radar antenna of claim 1, wherein the first surface of the antenna body comprises a plurality

of areas in which a plurality of first slots are disposed.

4. The radar antenna of claim 3, wherein the plurality of accommodation holes overlap the plurality of areas in which the plurality of first slots are disposed.
 5. The radar antenna of claim 1, wherein the first surface of the antenna body and inner walls of the accommodation holes of the shielding member form shielding spaces.
 6. The radar antenna of claim 1, wherein the inner walls of the accommodation holes are spaced apart from outer peripheries of areas occupied by a first slot group over a predetermined distance.
 7. The radar antenna of claim 1, wherein inner walls of the accommodation holes are spaced apart from the outer peripheries of the areas formed by a plurality of first slots included in a first slot group over the predetermined distance.
 8. The radar antenna of claim 1, wherein the shielding member comprises a plurality of shielding plates stacked on the antenna body to be spaced apart from one another, two or more accommodation holes are formed on a shielding plate of the shielding member, and the shielding plate of the shielding member is stacked on the antenna body so as to overlap two or more first slot groups of the plurality of first slot groups.
 9. The radar antenna of claim 8, wherein a protrusion part extending in an outward direction is formed on at least one of the plurality of shielding plates.
 10. The radar antenna of claim 8, wherein a part of at least one of the plurality of shielding plates is removed, and a groove part formed in an inward direction of the shielding plates is formed thereon.
 11. The radar antenna of claim 1, wherein the shielding member comprises a plurality of shielding blocks stacked on the antenna body to be spaced apart from one another, one accommodation hole is formed on a shielding block of the shielding member, and the shielding block of the shielding member is stacked on the antenna body so as to overlap one first slot group of the plurality of first slot groups.
 12. The radar antenna of claim 1, wherein the shielding member comprises a chamfer part chamfered along a corner formed by an accommodation hole.
 13. The radar antenna of claim 12, wherein the chamfer part is formed by chamfering the corner in a direction of the first surface of the shielding member.
-