

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12401892
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Nishimura; Tomonori

Electronic apparatus capable of detecting a line of sight

Abstract

An electronic apparatus according to the present invention includes at least one memory and at least one processor which function as: a detection unit configured to detect a line-of-sight position of a user within a display region; and a display control unit configured to control such that a first indicator is displayed on a basis of the line-of-sight position detected by the detection unit and an item is displayed at a position that does not overlap a range indicated by the first indicator when a predetermined condition is satisfied and is within a predetermined range from the range in response to the predetermined condition being satisfied.

Inventors:	Nishimura; Tomonori (Tokyo, JP)
Applicant:	CANON KABUSHIKI KAISHA (Tokyo, JP)
Family ID:	1000008781923
Assignee:	CANON KABUSHIKI KAISHA (Tokyo, JP)
Appl. No.:	18/298483
Filed:	April 11, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230345114 A1	Oct. 26, 2023

Foreign Application Priority Data

JP	2022-070192	Apr. 21, 2022
----	-------------	---------------

Publication Classification

Int. Cl.: H04N23/63 (20230101); H04N23/611 (20230101)

U.S. Cl.:

CPC **H04N23/635** (20230101); **H04N23/611** (20230101); **H04N23/631** (20230101);

Field of Classification Search

CPC: H04N (23/635); H04N (23/611); H04N (23/631); H04N (23/745); H04N (23/675); H04N (23/633); H04N (23/634); H04N (23/63); H04N (23/61); H04N (23/60); G06F (3/013); G06F (3/0482); G06F (3/012); G06F (3/038); G02B (7/287); G02B (27/0093)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9892689	12/2017	Kang	N/A	G09G 3/3406
11023038	12/2020	Yasuda	N/A	G06F 3/038
11960647	12/2023	Niioka	N/A	G06F 3/14
12086310	12/2023	Tamaki	N/A	G06F 3/013
2011/0170066	12/2010	Sugio	348/78	A61B 5/6803
2016/0224109	12/2015	Lee	N/A	G06F 3/005
2020/0382693	12/2019	Fujiwara	N/A	H04N 23/633

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
05-56313	12/1992	JP	N/A

Primary Examiner: Tissire; Abdelaaziz

Attorney, Agent or Firm: Cowan, Liebowitz & Latman, P.C.

Background/Summary

BACKGROUND OF THE INVENTION

Field of the Invention

(1) The present invention relates to an electronic apparatus, and more particularly to an electronic apparatus capable of detecting a line of sight.

Description of the Related Art

(2) In an electronic viewfinder of a digital camera, an item (information or a warning) for assisting photographing is displayed together with a live view image. Such an item is often disposed on the periphery of a screen in order not to disturb checking of the live view image.

(3) When a line of sight is moved to the periphery of the screen to check an item, a photo opportunity may be missed, and thus a method for enabling an item to be checked with a small amount of movement of the line of sight has been proposed. For example, Japanese Patent Application Laid-open No. H05-56313 discloses a technique for displaying an item at the line-of-sight position of a user.

(4) However, in the technique disclosed in Japanese Patent Application Laid-open No. H05-56313, since the item is displayed at the line-of-sight position, the item disturbs checking of the live view image (an object at the line-of-sight position), and thus the user may miss a shutter chance.

SUMMARY OF THE INVENTION

(5) The present invention provides a technique capable of displaying an item such that a user can check the item without being disturbed and with a small amount of movement of a line of sight.

(6) An electronic apparatus according to the present invention includes at least one memory and at least one processor which function as: a detection unit configured to detect a line-of-sight position of a user within a display region; and a display control unit configured to control such that a first indicator is displayed on a basis of the line-of-sight position detected by the detection unit and an item is displayed at a position that does not overlap a range indicated by the first indicator when a predetermined condition is satisfied and is within a predetermined range from the range in response to the predetermined condition being satisfied.

(7) Further features of the present invention will become apparent from the following description of exemplary embodiments with reference to the attached drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIGS. 1A and 1B are external views of a digital camera;

(2) FIG. 2 is a block diagram of the digital camera;

(3) FIGS. 3A and 3B are flowcharts of photographing mode processing;

(4) FIGS. 4A to 4C are flowcharts of a modification example of the photographing mode processing;

(5) FIG. 5A is an external view of a display control apparatus;

(6) FIG. 5B is a block diagram of the display control apparatus;

(7) FIG. 5C is an external view of VR goggles; and

(8) FIGS. 6A to 6I are diagrams showing screen examples.

DESCRIPTION OF THE EMBODIMENTS

External View of Digital Camera 100

(9) Hereinafter, embodiments of the present invention will be described with reference to the drawings. FIGS. 1A and 1B are external views of a digital camera 100 as an example of an electronic apparatus to which the present invention can be applied. FIG. 1A is a front perspective view of the digital camera 100, and FIG. 1B is a rear perspective view of the digital camera 100.

(10) A display unit 28 is a display unit provided on the rear surface of the digital camera 100 and displays an image and various types of information. A touch panel 70a can detect a touch operation on a display surface (a touch operation surface; a touch operation member) of the display unit 28. A non-finder display unit 43 is a display unit provided on the upper surface of the digital camera 100 and displays various setting values of the digital camera 100 such as a shutter speed and an opening degree of an aperture. A shutter button 61 is an operation member for giving a photographing instruction (an imaging instruction). A mode changeover switch 60 is an operation member for switching between various modes. A terminal cover 40 is a cover that protects a connector (not shown) that connects the digital camera 100 to an external apparatus.

(11) A main electronic dial 71 is a rotary operation member, and by rotating the main electronic dial 71, the setting values such as a shutter speed and an opening degree of an aperture can be changed. A power switch 72 is an operation member for switching between ON and OFF of the power of the digital camera 100. A sub-electronic dial 73 is a rotary operation member, and by rotating the sub-electronic dial 73, a selection frame (a cursor) can be moved and the image can be transferred. A 4-direction key 74 is configured such that up, down, left, and right portions can be pushed, and processing can be performed according to the pushed portion of the 4-direction key 74. A SET button 75 is a push button and is mainly used for determining a selection item. A multi-controller (hereinafter referred to as MC) 65 can receive direction instructions in eight directions and a push

operation in the central portion.

(12) A moving image button **76** is used to instruct start and stop of moving image photographing (recording). An AE lock button **77** is a push button, and an exposure state can be fixed by pressing the AE lock button **77** in a photographing standby state. An enlargement button **78** is an operation button for switching between ON and OFF of an enlargement mode in live view display (LV display) of a photographing mode. By operating the main electronic dial **71** after turning on the enlargement mode, a live view image (an LV image) can be enlarged or reduced. In a reproduction mode, the enlargement button **78** functions as an operation button for enlarging a reproduced image or increasing an enlargement ratio. A reproduction button **79** is an operation button for switching between the photographing mode and the reproduction mode. By pressing the reproduction button **79** during the photographing mode, the mode transitions to the reproduction mode, and the latest image among images recorded in a recording medium **200** (which will be described later) can be displayed on the display unit **28**. A menu button **81** is a push button used to perform an instruction operation for displaying a menu screen. When the menu button **81** is pushed, a menu screen on which various settings can be made is displayed on the display unit **28**. A user can intuitively perform various settings using the menu screen displayed on the display unit **28** and the 4-direction key **74**, the SET button **75**, or the MC **65**. A line-of-sight confirmation button **82** is an operation member included in an operation unit **70** and is a push button for instructing execution or cancelation of selection of an object based on a position of a line-of-sight pointer, which will be described later. The line-of-sight confirmation button **82** is disposed at a position where it can be easily operated even in a state where the user is looking through a finder (a state where the eye of the user is in proximity to an eyepiece part **16**) and is disposed at a position where it can be operated with the thumb of the right hand holding a grip portion **90**.

(13) A communication terminal **10** is a communication terminal for the digital camera **100** to communicate with a lens unit **150** (which will be described later; detachable). The eyepiece part **16** is an eyepiece part of an eyepiece finder (a looking-in type finder), and the user can visually recognize a video displayed on an internal EVF **29** (which will be described later; an electronic viewfinder) through the eyepiece part **16**. An eye proximity detection unit **57** is an eyepiece detection sensor that detects whether or not the eye of the user (a photographer) is in proximity to the eyepiece part **16**. A lid **202** is a lid for a slot in which a recording medium **200** (which will be described later) is stored. The grip portion **90** is a holding portion shaped such that the user can easily hold it with his or her right hand when holding the digital camera **100**. The shutter button **61** and the main electronic dial **71** are disposed at positions where they can be operated with the index finger of the right hand in a state where the digital camera **100** is held by gripping the grip portion **90** with the little finger, the ring finger, and the middle finger of the right hand. Further, in the same state, the sub-electronic dial **73** and the line-of-sight confirmation button **82** are disposed at positions where they can be operated with the thumb of the right hand.

Configuration Block Diagram of Digital Camera **100**

(14) FIG. **2** is a block diagram showing a configuration example of the digital camera **100**. A lens unit **150** is a lens unit in which an interchangeable photographing lens is installed. Although a lens **103** is normally constituted by a plurality of lenses, only one lens is shown in FIG. **2** for the sake of simplicity. A communication terminal **6** is a communication terminal for the lens unit **150** to communicate with the digital camera **100**, and the communication terminal **10** is a communication terminal for the digital camera **100** to communicate with a lens unit **150**. The lens unit **150** communicates with a system control unit **50** via these communication terminals **6** and **10**. Then, the lens unit **150** controls an aperture **1** via an aperture driving circuit **2** by a lens system control circuit **4** inside. Further, the lens unit **150** focuses by displacing the lens **103** via an AF driving circuit **3** by the lens system control circuit **4**.

(15) A shutter **101** is a focal plane shutter that can freely control the exposure time of an imaging unit **22** under the control of the system control unit **50**.

(16) The imaging unit **22** is an imaging element configured by a CCD, a CMOS device, or the like that converts an optical image into an electrical signal. The imaging unit **22** may have an imaging surface phase difference sensor that outputs defocus amount information to the system control unit **50**.

(17) An image processing unit **24** performs predetermined processing (pixel interpolation, resize processing such as reduction, color conversion processing, or the like) on data from an A/D converter **23** or data from a memory control unit **15**. Further, the image processing unit **24** performs predetermined arithmetic processing using captured image data, and the system control unit **50** performs exposure control and distance measurement control on the basis of the arithmetic results obtained by the image processing unit **24**. As a result, autofocus (AF) processing of a through-the-lens (TTL) type, automatic exposure (AE) processing, flash-free light emission (EF) processing, and the like are performed. The image processing unit **24** further performs predetermined arithmetic processing using the captured image data and performs auto white balance (AWB) processing of the TTL type on the basis of the obtained arithmetic results.

(18) The memory control unit **15** controls transmission and reception of data among the A/D converter **23**, the image processing unit **24**, and a memory **32**. Output data from the A/D converter **23** is written in the memory **32** via the image processing unit **24** and the memory control unit **15**. Alternatively, the output data from the A/D converter **23** is written in the memory **32** via the memory control unit **15** without passing through the image processing unit **24**. The memory **32** stores image data obtained by the imaging unit **22** and converted into digital data by the A/D converter **23** and image data to be displayed on the display unit **28** and the EVF **29**. The memory **32** has a storage capacity sufficient to store a predetermined number of still images, a moving image and an audio for a predetermined period of time.

(19) The memory **32** also serves as an image display memory (a video memory). The display image data written in the memory **32** is displayed by the display unit **28** or the EVF **29** via the memory control unit **15**. Each of the display unit **28** and the EVF **29** performs display according to a signal from the memory control unit **15** on a display device such as an LCD or organic EL. The data A/D-converted by the A/D converter **23** and stored in the memory **32** is sequentially transferred to the display unit **28** or the EVF **29** for display, and thus live view display (LV) is performed. An image displayed in the live view display is hereinafter referred to as a live view image (an LV image). In a case where the live view display is performed on the display unit **28** or the EVF **29**, the user can visually recognize an imaging range of the digital camera **100** via a display region of the display unit **28** or the EVF **29**.

(20) A line-of-sight detection unit **160** (a receiving unit) detects the line of sight of the eye of the user, which is in proximity to the eyepiece part **16**, looking at the EVF **29**. The line-of-sight detection unit **160** is constituted by a dichroic mirror **162**, an image forming lens **163**, a line-of-sight detection sensor **164**, a line-of-sight detection circuit **165**, and an infrared light emitting diode **166**.

(21) The infrared light emitting diode **166** is a light emitting element for detecting the line-of-sight position of the user within a finder screen (within the display region of the EVF **29**) and irradiates an eyeball (an eye) **161** of the user with infrared light. The infrared light emitted from the infrared light emitting diode **166** is reflected by the eyeball (the eye) **161**, and the reflected infrared light reaches the dichroic mirror **162**. The dichroic mirror **162** reflects only the infrared light and transmits visible light. The reflected infrared light whose optical path has been changed forms an image on an imaging surface of the line-of-sight detection sensor **164** via the image forming lens **163**. The image forming lens **163** is an optical member that constitutes a line-of-sight detection optical system. The line-of-sight detection sensor **164** is constituted by an imaging device such as a CCD type image sensor.

(22) The line-of-sight detection sensor **164** photoelectrically converts the incident reflected infrared light into an electric signal and outputs the electric signal to the line-of-sight detection circuit **165**.

The line-of-sight detection circuit **165** detects the line-of-sight position of the user from the movement of the eyeball (the eye) **161** of the user on the basis of the output signal from the line-of-sight detection sensor **164** and outputs the detection information to the system control unit **50** and a gaze determination unit **170**.

(23) The gaze determination unit **170** determines that in a case where a period during which the line of sight of the user is fixed on a certain region exceeds a predetermined threshold value, the user is gazing at that region on the basis of the detection information received from the line-of-sight detection circuit **165**. Therefore, it can be said that the region is a gaze position (a gaze region), which is a position to where gazing is performed. "The line of sight is fixed in a certain region" means, for example, that an average position of the movement of the line of sight is within the region and a variation (a dispersion) is less than a predetermined value until a predetermined period elapses. The predetermined threshold value can be arbitrarily changed by the system control unit **50**. Further, the gaze determination unit **170** may not be provided as an independent block, and the system control unit **50** may execute the same function as the gaze determination unit **170** on the basis of the detection information received from the line-of-sight detection circuit **165**.

(24) In the present embodiment, the line-of-sight detection unit **160** detects the line of sight using a method called a corneal reflection method. The corneal reflection method is a method of detecting an orientation and a position of the line of sight from a positional relationship between the reflected light obtained by reflecting the infrared light emitted from the infrared light emitting diode **166** by the eyeball (the eye) **161** (especially the cornea) and the pupil of the eyeball (the eye) **161**. The method of detecting the line of sight (the direction and position of the line of sight) is not particularly limited, and methods other than the above may be used. For example, a method called a sclera reflection method, which utilizes a difference in light reflectance between the iris and the white of the eye, may be used.

(25) The various setting values of the camera, such as a shutter speed and an opening degree of an aperture, are displayed on the non-finder display unit **43** via a non-finder display unit driving circuit **44**.

(26) A non-volatile memory **56** is an electrically erasable/recordable memory such as a Flash-ROM. A constant, a program, and the like for operating the system control unit **50** are recorded in the non-volatile memory **56**. The program mentioned here is a program for executing various flowcharts which will be described later in the present embodiment.

(27) The system control unit **50** is a control unit constituted by at least one processor or circuit and controls the entire digital camera **100**. The system control unit **50** executes the program recorded in the non-volatile memory **56** described above, and thus each processing of the present embodiment which will be described later is realized. A system memory **52** is, for example, a RAM, and the system control unit **50** develops a constant and a variable for operating the system control unit **50**, the program read from the non-volatile memory **56**, and the like into the system memory **52**. Further, the system control unit **50** also performs display control by controlling the memory **32**, the display unit **28**, and the like.

(28) A system timer **53** is a timer that measures the time used for various controls and the time of a built-in clock.

(29) A power supply control unit **80** is constituted by a battery detection circuit, a DC-DC converter, a switch circuit for switching blocks to be energized, and the like and detects whether or not a battery is installed, the type of a battery, and a remaining amount of a battery. Further, the power supply control unit **80** controls the DC-DC converter on the basis of the detection results and instructions from the system control unit **50** and supplies a necessary voltage to each unit including a recording medium **200** for a necessary period. A power supply unit **30** is constituted by a primary battery such as an alkaline battery or a lithium battery, a secondary battery such as a NiCd battery, a NiMH battery, or a Li battery, an AC adapter, and the like.

(30) A recording medium I/F **18** is an interface with the recording medium **200** such as a memory

card or a hard disk. The recording medium **200** is a recording medium such as a memory card for recording a photographed image and is constituted by a semiconductor memory, a magnetic disk, and the like.

(31) A communication unit **54** transmits and receives a video signal and an audio signal to and from an external apparatus connected wirelessly or through a wired cable. The communication unit **54** can be connected to a wireless local area network (LAN) and the Internet. Further, the communication unit **54** can communicate with an external apparatus using Bluetooth (a registered trademark) or Bluetooth Low Energy. The communication unit **54** can transmit an image (including an LV image) captured by the imaging unit **22** and an image recorded in the recording medium **200** and can receive image data and other various types of information from an external apparatus.

(32) An orientation detection unit **55** detects the orientation of the digital camera **100** with respect to a direction of gravity. It is possible to determine whether the image photographed by the imaging unit **22** is an image photographed with the digital camera **100** held horizontally or an image photographed with the digital camera **100** held vertically on the basis of the orientation detected by the orientation detection unit **55**. The system control unit **50** can add orientation information corresponding to the orientation detected by the orientation detection unit **55** to an image file of the image captured by the imaging unit **22**, or rotate the image for recording. An acceleration sensor, a gyro sensor, or the like can be used as the orientation detection unit **55**. It is also possible to detect the movement (pan, tilt, lift, whether or not it is stationary, or the like) of the digital camera **100** using an acceleration sensor or a gyro sensor, which is the orientation detection unit **55**.

(33) The eye proximity detection unit **57** is an eye proximity detection sensor that detects the approach (eye proximity) and departure (eye separation) of the eye (an object) **161** from the eyepiece part **16** of the eyepiece finder (hereinafter simply referred to as a “finder”) (approach detection). The system control unit **50** switches display (a display state)/non-display (a non-display state) of the display unit **28** and the EVF **29** according to the state detected by the eye proximity detection unit **57**. More specifically, at least in the photographing standby state and in a case where the switching of the display destination is automatic switching, during non eye proximity, the display destination is set to the display unit **28** and the display is turned on, and the EVF **29** is in non-display. In addition, during eye proximity, the display destination is set to the EVF **29** and the display is turned on, and the display unit **28** is in non-display. For example, an infrared proximity sensor can be used as the eye proximity detection unit **57**, and it is possible to detect the approach of any object to the eyepiece part **16** of the finder having the EVF **29** built-in. In a case where an object approaches, an infrared ray projected from a light projecting part (not shown) of the eye proximity detection unit **57** is reflected by the object and received by a light receiving part (not shown) of the infrared proximity sensor. It is also possible to determine how close the object is from the eyepiece part **16** (an eye contact distance) on the basis of the amount of the received infrared ray. In this manner, the eye proximity detection unit **57** performs eye proximity detection for detecting the proximity distance of the object to the eyepiece part **16**. It is assumed that in a case where the object approaching the eyepiece part **16** within a predetermined distance is detected from a non-eye-proximity state (a non-approach state), it is detected that the eye is in proximity to the eyepiece part **16**. It is assumed that in a case where the object whose approach has been detected moves away from the eye proximity state (the approach state) by a predetermined distance or more, it is detected that the eye has been separated from the eyepiece part. A threshold for detecting the eye proximity and a threshold value for detecting the eye separation may be different from each other, for example, by providing hysteresis. Further, it is assumed that after the eye proximity is detected, the eye proximity state is maintained until the eye separation is detected. It is assumed that after eye separation is detected, the eye is in a non-eye-proximity state until the eye proximity is detected. The infrared proximity sensor is only an example, and other sensors may be employed as the eye proximity detection unit **57** as long as they can detect the approach of an eye or an object that can be regarded as the eye proximity.

(34) The system control unit **50** can detect the following line-of-sight states toward the EVF **29** by controlling the line-of-sight detection unit **160**. A state in which the line of sight that was not directed to the EVF **29** was newly directed to the EVF **29**. That is, the start of line-of-sight input. A state in which the line-of-sight input to the EVF **29** is being performed. A state in which the user is gazing at a certain position of the EVF **29**. A state in which the line of sight directed to the EVF **29** was removed. That is, the end of line-of-sight input. A state in which no line of sight is input to the EVF **29** (a state in which the user does not look the EVF **29**).

(35) The system control unit **50** is notified of these operations/states and the position (the direction) where the line of sight is directed to the EVF **29** via an internal bus, and the system control unit **50** determines what kind of line-of-sight input is performed on the basis of the notified information.

(36) The operation unit **70** is an input unit that receives an operation from a user (a user operation) and is used to input various operation instructions to the system control unit **50**. As shown in FIG. 2, the operation unit **70** includes the mode changeover switch **60**, the shutter button **61**, the power switch **72**, the touch panel **70a**, and the like. The operation unit **70** also includes other operation members **70b** such as the main electronic dial **71**, the sub-electronic dial **73**, the 4-direction key **74**, the SET button **75**, the moving image button **76**, the AE lock button **77**, the enlargement button **78**, the reproduction button **79**, the menu button **81**, MC **65**, and the like.

(37) The mode changeover switch **60** switches the operation mode of the system control unit **50** between a still image photographing mode, a moving image photographing mode, a reproduction mode, and the like. Modes included in the still image photographing mode are an auto photographing mode, an auto scene determination mode, a manual mode, an aperture priority mode (an Av mode), a shutter speed priority mode (a Tv mode), and a program AE mode (a P mode). In addition, there are various scene modes which are photographing settings for each photographing scene, a custom mode, and the like. The mode changeover switch **60** allows the user to directly switch to any of these modes. Alternatively, after once switching to the photographing mode list screen with the mode changeover switch **60**, it is possible to selectively switch to any of the displayed plural modes using another operation member. Similarly, the moving image photographing mode may also include a plurality of modes.

(38) The shutter button **61** includes a first shutter switch **62** and a second shutter switch **64**. The first shutter switch **62** is turned on when the shutter button **61** is being operated, that is, when the shutter button **61** is half-pressed (a photographing preparation instruction) and generates a first shutter switch signal SW1. The system control unit **50** starts photographing preparation operations such as autofocus (AF) processing, auto exposure (AE) processing, auto white balance (AWB) processing, and flash-free light emission (EF) processing in response to the first shutter switch signal SW1. The second shutter switch **64** is turned on when the operation of the shutter button **61** is completed, that is, when the shutter button **61** is fully pressed (photographing instruction) and generates a second shutter switch signal SW2. The system control unit **50** starts a series of photographing processing operations from signal reading from the imaging unit **22** to writing of the photographed image as an image file in the recording medium **200** in response to the second shutter switch signal SW2.

(39) The touch panel **70a** and the display unit **28** can be configured integrally with each other. For example, the touch panel **70a** is configured such that the light transmittance does not interfere with the display of the display unit **28** and is attached to the upper layer of the display surface of the display unit **28**. Then, the input coordinates on the touch panel **70a** and the display coordinates on the display surface of the display unit **28** are associated with each other. This makes it possible to provide a graphical user interface (GUI) as if the user can directly operate the screen displayed on the display unit **28**.

(40) The system control unit **50** can detect the following operations or states on the touch panel **70a**. A state in which the touch panel **70a** is newly touched by a finger or pen that has not touched the touch panel **70a**, that is, the start of touch (hereinafter referred to as touch-down). A state in

which the touch panel **70a** is touched with a finger or a pen (hereinafter referred to as touch-on). A state in which the finger or pen is moving while touching the touch panel **70a** (hereinafter referred to as touch-move). A state in which the finger or pen touching the touch panel **70a** is separated (released) from the touch panel **70a**, that is, the end of touch (hereinafter referred to as touch-up). A state in which nothing is touched on the touch panel **70a** (hereinafter referred to as touch-off).

(41) When the touch-down is detected, the touch-on is also detected at the same time. After the touch-down, the touch-on normally continues to be detected unless the touch-up is detected. Even in a case where the touch-move is detected, the touch-on is detected at the same time. Even if the touch-on is detected, the touch-move is not detected if the touch position does not move. After it is detected that all the finger and pen that have touched have touched up, it is the touch-off.

(42) The system control unit **50** is notified of these operations/states and the coordinates of the position where the finger or pen touches the touch panel **70a** through the internal bus. Then, the system control unit **50** determines what kind of operation (touch operation) is performed on the touch panel **70a** on the basis of the notified information. As for the touch-move, the moving direction of the finger or pen moving on the touch panel **70a** can also be determined for each vertical component/horizontal component on the touch panel **70a** on the basis of the change in the position coordinates. In a case where it is detected that the touch-move has been performed for a predetermined distance or more, it is determined that a slide operation is performed. An operation of touching the touch panel **70a** with the finger and quickly moving it by a certain distance and then releasing it as it is, is called a flick. The flick is, in other words, an operation of quickly tracing the touch panel **70a** as if the finger flicks on the touch panel **70a**. It can be determined that the flick is performed when the touch-move of a predetermined distance or more at a predetermined speed or more is detected and the touch-up is detected as it is (it can be determined that the flick occurs following the slide operation). Further, a touch operation of touching (multi-touching) a plurality of locations (for example, two points) together to bring the touch positions closer to each other is referred to as pinch-in, and a touch operation of moving the touch positions away from each other is referred to as pinch-out. The pinch-out and the pinch-in are collectively referred to as a pinch operation (or simply pinch). The touch panel **70a** may be any one of various types of touch panels such as a resistive film type, a capacitive type, a surface acoustic wave type, an infrared type, an electromagnetic induction type, an image recognition type, an optical sensor type, and the like. There are a method of detecting that there is a touch when there is contact with the touch panel, and a method of detecting that there is a touch when there is an approach of the finger or pen to the touch panel, but any one method may be used.

(43) The digital camera **100** may be provided with an audio input unit (not shown) for transmitting audio signal obtained from a built-in microphone or an audio input apparatus connected to the digital camera **100** via an audio input terminal to the system control unit **50**. In this case, the system control unit **50** selects the input audio signal as necessary, performs analog-to-digital conversion, performs level optimization processing, specific frequency reduction processing, and the like, and generates an audio signal.

(44) In the present embodiment, the user can set a method of specifying a position of a position index (for example, an AF frame) in a case where the touch-move is performed in the eye proximity state to any one of an absolute position specifying method and a relative position specifying method. The absolute position specifying method is a method in which the input coordinates on the touch panel **70a** and the display coordinates on the display surface of the EVF **29** are associated with each other. In the case of the absolute position specifying method, when there is a touch-down on the touch panel **70a**, the AF frame is set at a position associated with the touched position (the position whose coordinates are input) even if there is no touch-move (the position of the AF frame moves from the position before the touch-down). The position set by the absolute position specifying method is a position based on the touched-down position regardless of the position set before the touch-down. Further, if there is the touch-move after the touch-down, the

position of the AF frame also moves on the basis of the touch position after the touch-move. The relative position specifying method is a method in which the input coordinates on the touch panel **70a** and the display coordinates on the display surface of the EVF **29** are not associated with each other. In the case of the relative position specifying method, when there is only a touch-down on the touch panel **70a** and there is no touch-move, the position of the AF frame does not move from the position before the touch-down. If there is the touch-move after that, regardless of the touch-down position, the position of the AF frame moves from the position of the currently set AF frame (the position set before the touch-down) by a distance according to the amount of movement of the touch-move in a movement direction of the touch-move.

(45) As an AF method (an AF frame setting method), any one of a plurality of AF methods including “single-point AF” and “face+tracking priority AF” can be set. The “single-point AF” is a method in which the user specifies one location as a position for performing AF using a single-point AF frame. The “face+tracking priority AF” is a method in which the AF position is automatically set on the basis of automatic selection conditions in a case where the user does not specify a tracking target. In the automatic AF position setting, if a human face is detected from the LV image, the face is preferentially selected as an AF target object. If the pupil is detected inside the face, the pupil can be preferentially selected as the AF target object. In case where a plurality of human faces are detected, one face is selected according to priority such as the size of the face being large, the position of the face being close to the digital camera **100** (on the closest side), the position of the face being close to the center in the image, or the face being a face of a pre-registered individual, and the selected face is set as the AF target object. If the human face is not detected, an object other than the face is selected as the AF target object according to priority such as the object being close to the digital camera **100** (on the closest side), the object being high in contrast, the object being high priority object such as an animal or vehicle, or the object being a moving object, and the selected object is set as the AF target object. In a case where an object to be tracked is specified by the user, the object to be tracked is set as the AF target object. That is, the automatic selection conditions are weighted using at least one element condition among element conditions which will be shown in an example below, and the conditions are that the obtained score is equal to or greater than a predetermined threshold value or the obtained score is the highest. It is the face of a detected human. The size of the face is large. The position of the face is close to the digital camera **100** (on the closest side). The position of the face is close to the center in the image. It is the face of a pre-registered individual. It is close to the digital camera **100** (on the closest side). It is high in contrast. It is a high-priority object such as an animal or vehicle. It is a moving object.

Photographing Mode Processing

(46) FIGS. **3A** and **3B** are flowcharts of photographing mode processing in the digital camera **100**. This processing is realized by the system control unit **50** developing the program stored in the non-volatile memory **56** into the system memory **52** and executing the program. When the digital camera **100** is activated in the photographing mode, flags, control variables, and the like are initialized, and the processing of FIGS. **3A** and **3B** is started.

(47) In **S301**, the system control unit **50** starts capturing the live view image (the LV image) with the imaging unit **22** and displays the captured LV image on the display unit **28** or the EVF **29**. The LV image is displayed on the EVF **29** during the eye proximity (in a case where the eye proximity is detected by the eye proximity detection unit **57**), and the LV image is displayed on the display unit **28** during the non eye proximity (in a case where the eye proximity is not detected by the eye proximity detection unit **57**).

(48) In **S302**, the system control unit **50** performs processing for changing settings related to photographing in accordance with the user's operation. The settings related to photographing include, for example, setting whether the AF target object to be prioritized is the face or the pupil, setting the shutter speed, setting whether or not to display the line-of-sight pointer, and setting whether or not to display an item (information or a warning) near the line-of-sight position.

(49) In **S303**, the system control unit **50** displays the AF frame (an indicator indicating the AF target object) on the display unit **28** or the EVF **29** on the basis of the settings related to photographing. For example, the AF frame is displayed to show the face closest to the center of the LV image. The AF target object may be a pupil, a human, an animal, a vehicle, or the like.

(50) In **S304**, the system control unit **50** determines whether or not the line of sight (the line-of-sight position) is detected by the line-of-sight detection circuit **165**. In a case where the line of sight is detected, the process proceeds to **S305**, and otherwise, the process proceeds to **S323**. This determination is repeated during the processing of **S305** to **S322**, and when the line-of-sight detection circuit **165** no longer detects the line of sight, the process proceeds from **S305** to **S322** to **S323**.

(51) In **S305**, the system control unit **50** determines whether or not the line-of-sight pointer display (setting to display the line-of-sight pointer) is enabled. In a case where the line-of-sight pointer display is enabled, the process proceeds to **S306**, and otherwise, the process proceeds to **S323**. The line-of-sight pointer is an indicator that indicates the line-of-sight position of the user and is, for example, a translucent indicator made up of a point and a circle surrounding the point. A portion of the line-of-sight pointer (for example, only the point) may be translucent, or the entirety thereof may be opaque.

(52) In **S306**, the system control unit **50** displays the line-of-sight pointer on the EVF **29** on the basis of the line-of-sight position detected by the line-of-sight detection circuit **165**.

(53) In **S307**, the system control unit **50** determines whether or not a predetermined condition such as the occurrence of an error and the change of a setting value is satisfied in the digital camera **100**. In a case where the predetermined condition is satisfied, the process proceeds to **S308**, and otherwise, the process proceeds to **S323**. For example, in a case where flicker is detected in the LV image, or in a case where the shutter speed (a Tv value) is changed according to the operation of the main electronic dial **71**, the process proceeds to **S308**.

(54) In **S308**, the system control unit **50** determines whether or not display near the line-of-sight position (setting for displaying the item (the warning or the information) indicating an error or a setting value near the line-of-sight position) is enabled. In a case where the display near the line-of-sight position is enabled, the process proceeds to **S309**, and otherwise, the process proceeds to **S323**.

(55) In **S309**, the system control unit **50** determines whether or not upper right display (setting for displaying the item (the warning or the information) indicating an error or a setting value on the upper right of the line-of-sight position) is enabled. In a case where the upper right display is enabled, the process proceeds to **S310**, and otherwise, the process proceeds to **S311**.

(56) In **S310**, the system control unit **50** determines whether or not the item is cut off at the right end of the display region of the EVF **29** when the item is displayed on the upper right of the line-of-sight position on the basis of the line-of-sight position detected by the line-of-sight detection circuit **165**. For example, the system control unit **50** determines whether or not the display position of the item (for example, the center position of the item) is on the right side from the display region. In a case where the item is cut off at the right end of the display region, the process proceeds to **S313**, and otherwise, the process proceeds to **S312**.

(57) In **S311**, the system control unit **50** determines whether or not the item is cut off at the lower end of the display region of the EVF **29** when the item is displayed below (directly below) the line-of-sight position on the basis of the line-of-sight position detected by the line-of-sight detection circuit **165**. For example, the system control unit **50** determines whether or not the display position of the item is below the display region. In a case where the item is cut off at the lower end of the display region, the process proceeds to **S315**, and otherwise, the process proceeds to **S314**.

(58) In **S312**, the system control unit **50** determines whether or not the item is cut off at the upper end of the display region of the EVF **29** when the item is displayed on the upper right of the line-of-sight position on the basis of the line-of-sight position detected by the line-of-sight detection

circuit **165**. For example, the system control unit **50** determines whether or not the display position of the item is above the display region. In a case where the item is cut off at the upper end of the display region, the process proceeds to **S317**, and otherwise, the process proceeds to **S316**.

(59) In **S313**, the system control unit **50** determines whether or not the item is cut off at the upper end of the display region of the EVF **29** when the item is displayed on the upper left of the line-of-sight position on the basis of the line-of-sight position detected by the line-of-sight detection circuit **165**. For example, the system control unit **50** determines whether or not the display position of the item is above the display region. In a case where the item is cut off at the upper end of the display region, the process proceeds to **S319**, and in a case where the item is not cut off at the upper end of the display region, the process proceeds to **S318**.

(60) In **S314** to **S319**, the system control unit **50** displays the item indicating an error, a setting value, or the like at a position based on the determination results of **S309** to **S313** in the display region of the EVF **29**. When the predetermined condition in **S307** is satisfied, the item is displayed at a position that does not overlap a range indicated by the line-of-sight pointer and is within a predetermined range from the range indicated by the line-of-sight pointer. The range indicated by the line-of-sight pointer is, for example, a region including the line-of-sight pointer such as a region of the line-of-sight pointer or a rectangular region circumscribing the line-of-sight pointer.

(61) In **S314**, the system control unit **50** displays the item below (directly below) the line-of-sight pointer (the line-of-sight position). In **S315**, the system control unit **50** displays the item above (directly above) the line-of-sight pointer. In **S316**, the system control unit **50** displays the item on the upper right of the line-of-sight pointer. In **S317**, the system control unit **50** displays the item on the lower right of the line-of-sight pointer. In **S318**, the system control unit **50** displays the item on the upper left of the line-of-sight pointer. In **S319**, the system control unit **50** displays the item on the lower left of the line-of-sight pointer.

(62) In **S320**, the system control unit **50** fixes the display position of the item indicating an error, a setting value, or the like not to follow the line-of-sight position detected by the line-of-sight detection circuit **165**. In this way, after the item is displayed near the line-of-sight position in response to the predetermined condition in **S307** being satisfied, the display position of the item will not be changed unless the predetermined condition is satisfied again. In a case where the line-of-sight pointer is moved to the display position of the item, the line-of-sight pointer may be displayed to be superimposed on the item, or the item may be displayed to be superimposed on the line-of-sight pointer.

(63) In **S321**, the system control unit **50** hides the item after a predetermined period of time (for example, 1 second, 3 seconds, 5 seconds, or the like) has elapsed since the item indicating an error or a setting value was displayed. For example, the item is hidden after a predetermined period of time has elapsed since the display of the item started.

(64) In **S322**, the system control unit **50** determines whether or not a predetermined condition such as the occurrence of an error and the change of a setting value is satisfied again in the digital camera **100**. In a case where the predetermined condition is satisfied, the process proceeds to **S308**, and otherwise, the process proceeds to **S323**.

(65) In **S323**, the system control unit **50** determines whether or not the shutter button **61** is fully pressed to perform a photographing instruction (whether or not the second shutter switch **64** is turned on to output the signal SW2). In a case where the photographing instruction is performed, the process proceeds to **S324**, and otherwise, the process proceeds to **S325**.

(66) In **S324**, the system control unit **50** performs a series of pieces of photographing processing from exposure in the imaging unit **22** to recording the captured still image on the recording medium **200** as an image file. Video recording is started as photographing start processing of the still image. The item may be hidden in response to photographing the still image (the photographing processing).

(67) In **S325**, the system control unit **50** determines whether or not another operation is performed

on the operation unit **70**. In a case where the other operation is performed, the process proceeds to **S326**, and otherwise, the process proceeds to **S327**. The other operation includes, for example, an operation temporarily hiding the LV image such as pressing the menu button **81**.

(68) In **S326**, the system control unit **50** performs processing (another processing) according to the operation in **S325**.

(69) In **S327**, the system control unit **50** determines whether or not there is an end event of the photographing mode (an instruction to transition to another operation mode such as a power-off operation or a reproduction mode). In a case where there is no end event, the process proceeds to **S302**, and in a case where there is an end event, the photographing mode processing ends.

Modification Example

(70) FIGS. **4A** to **4C** are flowcharts of photographing mode processing in the digital camera **100**. This processing is realized by the system control unit **50** developing the program stored in the non-volatile memory **56** into the system memory **52** and executing the program. When the digital camera **100** is activated in the photographing mode, flags, control variables, and the like are initialized, and the processing of FIGS. **4A** to **4C** is started. The processing of **S401** to **S422** is the same as the processing of **S301** to **S322** in FIGS. **3A** and **3B**, and the processing of **S441** to **S445** is the same as the processing of **S323** to **S327** in FIGS. **3A** and **3B**.

(71) In **S423**, the system control unit **50** determines whether or not an AF frame moving operation to move the AF frame on the basis of the line-of-sight position is performed. This AF frame moving operation is, for example, half-pressing of the shutter button **61** (a photographing preparation instruction; an operation of turning on the first shutter switch **62**). In a case where the AF frame moving operation is performed, the process proceeds to **S424**, and otherwise, the process proceeds to **S441**.

(72) In **S424**, the system control unit **50** moves the AF frame on the basis of the line-of-sight position detected by the line-of-sight detection circuit **165** (a change of the display position of the AF frame). Without performing the processing of **S403**, in response to a first photographing preparation instruction, the AF frame may be displayed at a position based on the line-of-sight position such as the line-of-sight position detected by the line-of-sight detection circuit **165** or the position of the object closest to the line-of-sight position. Then, the AF frame may be moved to a position based on the line-of-sight position detected by the line-of-sight detection circuit **165** in response to second and subsequent photographing preparation instructions (AF frame moving operations). The AF frame may follow the AF target object in a case where the AF frame moving operation is not performed.

(73) In **S425**, the system control unit **50** determines whether or not display near the AF frame (setting for displaying the item indicating a setting value or the like near the AF frame) is enabled. In a case where the display near the AF frame is enabled, the process proceeds to **S426**, and otherwise, the process proceeds to **S441**. For example, enabling/disabling of the display near the AF frame is also set by the user in the same way as enabling/disabling of the display near the line-of-sight position.

(74) In **S426**, the system control unit **50** determines whether or not pupil AF is performed (whether or not the AF target object is the pupil). The pupil AF is AF that is performed on the eye (the pupil) which is a detected human organ. In a case where the pupil AF is performed, the process proceeds to **S428**, and otherwise, the process proceeds to **S427**.

(75) In **S427**, the system control unit **50** determines whether or not the AF frame is larger than the item displayed near the AF frame. In a case where the AF frame is larger than the item, the process proceeds to **S429**, and otherwise, the process proceeds to **S430**. This determination may be determining whether or not the image size (the number of pixels) of the AF frame is a predetermined number of times (a predetermined amount) or more of the item, or determining whether or not the image size of the AF frame is larger than a threshold value (whether or not the number of pixels of the AF frame is greater than a threshold value).

(76) In **S428**, the system control unit **50** determines whether or not the eye for which the AF is performed (the AF target object) is a left eye. In a case where the AF is performed for the left eye, the process proceeds to **S431**, and otherwise, the process proceeds to **S432**.

(77) In **S429**, the system control unit **50** determines whether or not the pupil is detected within the AF frame. In a case where the pupil is detected within the AF frame, the process proceeds to **S433**, and otherwise, the process proceeds to **S434**.

(78) In **S430**, the system control unit **50** determines whether or not upper right display (setting for displaying the item indicating a setting value or the like on the upper right of the AF frame) is enabled. In a case where the upper right display is enabled, the process proceeds to **S435**, and otherwise, the process proceeds to **S436**.

(79) In **S431** to **S436**, the system control unit **50** displays the item indicating a setting value or the like at a position based on the determination results of **S425** to **S430** in the display region of the EVF **29**. The item is displayed at a position that does not overlap a range indicated by the AF frame and is within a predetermined range from the range indicated by the AF frame. The range indicated by the AF frame is, for example, a region including the AF frame such as a region of the AF frame or a rectangular region circumscribing the AF frame. In a case where the line-of-sight pointer is moved to the display position of the item, the line-of-sight pointer may be displayed to be superimposed on the item, or the item may be displayed to be superimposed on the line-of-sight pointer. After the item is displayed near the AF frame, the item is displayed on the basis of the display position of the AF frame regardless of the line-of-sight position.

(80) In **S431**, the system control unit **50** displays the item on the right side of the AF frame (the left eye). In **S432**, the system control unit **50** displays the item on the left side of the AF frame (the right eye). In **S433**, the system control unit **50** displays the item within the AF frame avoiding a region (a position) of the detected pupil (eye). In **S434**, the system control unit **50** displays the item at a predetermined position (the upper right or the bottom) within the AF frame. In **S435**, the system control unit **50** displays the item on the upper right of the AF frame. In **S436**, the system control unit **50** displays the item below (directly below) the AF frame. As the processing of **S430**, **S435**, and **S436**, the processing of replacing the “line-of-sight pointer” in the processing of **S409** to **S419** with the “AF frame” may be performed.

(81) In **S437**, the system control unit **50** determines whether or not a predetermined condition such as the change of a setting value is satisfied in the digital camera **100**. In a case where the predetermined condition is satisfied, the process proceeds to **S438**, and otherwise, the process proceeds to **S441**.

(82) In **S438**, the system control unit **50** emphasizes the item indicating a setting value or the like. For example, the system control unit **50** displays the item indicating a setting value. Then, in response to the operation of changing the setting value being performed on the operation unit **70**, the system control unit **50** updates the item to indicate the changed setting value and emphasizes the item. Emphasizing the item is, for example, processing of reducing transparency, blinking, or displaying an outline to increase visibility and saliency.

(83) In **S439**, the system control unit **50** cancels the emphasizing of the item after a predetermined period of time (for example, 1 second, 3 seconds, 5 seconds, or the like) has elapsed since the item indicating a setting value or the like was emphasized. For example, the emphasizing of the item is canceled after a predetermined period of time has elapsed since the emphasis display of the item started.

(84) In **S440**, the system control unit **50** determines whether or not a predetermined condition such as the change of a setting value is satisfied again in the digital camera **100**. In a case where the predetermined condition is satisfied, the process proceeds to **S438**, and otherwise, the process proceeds to **S441**.

(85) FIGS. **6A** to **6H** show examples of screens displayed on the EVF **29** in still image photographing mode.

(86) In FIG. 6A, an LV image **601** and information **602** regarding the still image photographing are displayed. Further, a line-of-sight pointer **603** is displayed to be superimposed on the LV image **601**. Then, in response to the detection of the flicker, an item **604** indicating that the flicker is occurring is displayed on the upper right of the line-of-sight pointer **603**. When the item **604** is displayed near the line-of-sight pointer **603**, the user can check the item **604** with a small amount of movement of the line of sight. Further, since the line-of-sight pointer **603** and the item **604** are not superimposed on each other (the object that the user is looking at is not hidden by the item **604**), the item **604** does not disturb the user. FIG. 6A corresponds to the state after the processing of S316 of FIG. 3B or S416 of FIG. 4B.

(87) When the user moves his eye from the state of FIG. 6A, the state transitions to a state of FIG. 6B. In FIG. 6B, the display position of the line-of-sight pointer **603** is changed from that in FIG. 6A, but the display position of the item **604** is fixed (S320 in FIG. 3B and S420 in FIG. 4B) and is the same as that in FIG. 6A. When the item **604** is displayed near the line-of-sight pointer **603** (the line-of-sight position of the user), the line of sight of the user tends to turn toward the item **604**. Since the line-of-sight pointer **603** does not move, it is possible to prevent the item **604** from being continuously displayed near the line-of-sight pointer **603** and to prevent the line of sight from turning toward the item **604** against the intention of the user.

(88) FIG. 6C corresponds to the state after the photographing preparation instruction (the AF frame moving operation) is performed. In FIG. 6C, the LV image **601** and the information **602** are displayed as in FIG. 6A and the like. In FIG. 6C, unlike in FIG. 6A and the like, an AF frame **605** is displayed to be superimposed on the LV image **601**. An item **606** indicating a setting value is displayed on the upper right of the AF frame **605**. When the item **606** is displayed near the AF frame **605**, the user can check the item **606** with a small amount of movement of the line of sight in a case where the user is looking at the AF target object (the object indicated by the AF frame **605**). Further, since the AF frame **605** and the item **606** are not superimposed on each other (the object indicated by the AF frame **605** is not hidden by the item **606**), the item **606** does not disturb the user. FIG. 6C corresponds to the state after the processing of S435 of FIG. 4C. In FIG. 6C, the line-of-sight pointer **603** is not displayed, but may be displayed.

(89) When an operation to change the setting value is performed in the state of FIG. 6C, the state transitions to a state of FIG. 6D. In FIG. 6D, the setting value indicated by the item **606** is the changed value (similarly, the information **602** has been updated). Further, the item **606** is emphasized. In this way, the user can immediately notice that the setting value is changed and can immediately check the changed setting value (with a small amount of movement of the line of sight). FIG. 6D corresponds to the state after the processing of S438 of FIG. 4C.

(90) In FIG. 6E, the LV image **601**, the information **602**, the AF frame **605**, and the item **606** are displayed as in FIG. 6C and the like. In FIG. 6E, the AF frame **605** is larger than that in FIG. 6C, and the item **606** is displayed within the AF frame **605**. The user often looks at the vicinity of the center of the AF frame **605** when looking at the AF target object. Therefore, in a case where the AF frame **605** is large, the user needs to move his/her eye largely to see the outside of the AF frame **605**. When the item **606** is displayed within the AF frame **605**, the user can check the item **606** with a small amount of movement of the line of sight. Since the AF frame **605** is large, even if the item **606** is displayed within the AF frame **605**, the item **606** does not disturb the user. In a case where the pupil is detected within the AF frame **605**, the item **606** is displayed not to overlap the pupil. FIG. 6E corresponds to the state after the processing of S433 or S434 of FIG. 4C.

(91) In FIG. 6F, the LV image **601**, the information **602**, the AF frame **605**, and the item **606** are displayed as in FIG. 6C and the like. In FIG. 6F, the object indicated by the AF frame **605** is the right eye, and the item **606** is displayed on the left side (the upper left) of the AF frame **605**. In this way, the item **606** can be displayed not to overlap not only the right eye of the AF target object but also the left eye. FIG. 6F corresponds to the state after the processing of S432 of FIG. 4C.

(92) In FIG. 6G, the LV image **601**, the information **602**, the AF frame **605**, and the item **606** are

displayed as in FIG. 6C and the like. In FIG. 6G, a plurality of objects are detected. In a state of FIG. 6G, when the AF target object is changed with the operation of the 4-direction key **74** or the like, the state transitions to a state of FIG. 6H. Since the item **606** also moves as the AF frame **605** moves, the user can check the item **606** with a small amount of movement of the line of sight even after the AF frame **605** moves. Further, as in FIG. 6C and the like, the item **606** does not disturb the user. FIG. 6G or 6H corresponds to the state after the processing of **S435** or the like of FIG. 4C.

(93) As described above, according to the present embodiment, an item is displayed near an indicator (such as the line-of-sight pointer or the AF frame) that the user is likely to pay attention to so as not to overlap the indicator. In this way, it is possible to check the item with a small amount of movement of the line of sight, and it is possible to prevent the item from disturbing the user.

(94) The various controls described above that are performed by the system control unit **50** may be performed by one piece of hardware, or a plurality of pieces of hardware (for example, a plurality of processors or circuits) may share the processing to perform the control of the entire apparatus.

(95) Further, although the embodiments of the present invention have been described in detail, the present invention is not limited to these specific embodiments, and various forms without departing the scope of the present invention are also included in the present invention. Furthermore, each embodiment described above merely shows one embodiment of the present invention, and it is also possible to combine the embodiments as appropriate. For example, the specific operation for displaying (moving) the AF frame on the basis of the line-of-sight position may not be the half-pressing of the shutter button **61**.

(96) Further, in the above-described embodiments, the case where the present invention is applied to an imaging apparatus (a digital camera) has been described as an example, but the present invention is not limited to this example and can be applied to any electronic apparatus capable of detecting a line of sight. For example, the present invention can be applied to personal computers, PDAs, mobile phone terminals, portable image viewers, printing apparatuses, digital photo frames, music players, game machines, electronic book readers, and the like. In addition, the present invention is can be applied to video players, display apparatuses (including projection apparatuses), tablet terminals, smartphones, AI speakers, home appliances, vehicle-mounted apparatuses, and the like.

Other Embodiments

(97) FIG. 5A is an external view of a display control apparatus **500** as an example of an electronic apparatus to which the present invention can be applied. The display control apparatus **500** is, for example, a display apparatus such as a smartphone. A display **505** is a display unit that displays images and various types of information. The display **505** is configured integrally with a touch panel **506a** and is made such that a touch operation on the display surface of the display **505** can be detected. The display control apparatus **500** is capable of VR-displaying a virtual reality (VR) image (a VR content) on the display **505**. An operation unit **506b** is a power button that receives an operation for switching the power of the display control apparatus **500** between on and off. An operation unit **506c** and an operation unit **506d** are volume buttons for increasing or decreasing the volume of an audio output from a speaker **512b**, an earphone or an external speaker connected to an audio output terminal **512a**, or the like. An operation unit **506e** is a home button for displaying a home screen on the display **505**. The audio output terminal **512a** is an earphone jack and is a terminal for outputting an audio signal to an earphone, an external speaker, or the like. The speaker **512b** is a built-in speaker for outputting sound.

(98) FIG. 5B is a block diagram showing a configuration example of the display control apparatus **500**. A CPU **501**, a memory **502**, a non-volatile memory **503**, an image processing unit **504**, a display **505**, an operation unit **506**, a recording medium I/F **507**, an external I/F **509**, and a communication I/F **510** are connected to an internal bus **550**. Further, an audio output unit **512** and an orientation detection unit **513** are also connected to the internal bus **550**. Each unit connected to the internal bus **550** is capable of exchanging data with each other via the internal bus **550**.

(99) The CPU **501** is a control unit that controls the entire display control apparatus **500** and is constituted by at least one processor or circuit. The memory **502** is, for example, a RAM (such as a volatile memory using a semiconductor element). The CPU **501** uses the memory **502** as a work memory to control each unit of the display control apparatus **500** according to the program stored in the non-volatile memory **503**, for example. The non-volatile memory **503** stores image data, audio data, other data, various programs for the CPU **501** to operate, and the like. The non-volatile memory **503** is constituted by, for example, a flash memory or a ROM.

(100) The image processing unit **504** executes various types of image processing with respect to an image stored in the non-volatile memory **503** or a recording medium **508**, a video signal obtained via the external I/F **509**, an image obtained via the communication I/F **510**, or the like on the basis of the control of the CPU **501**. The image processing performed by the image processing unit **504** includes A/D conversion processing, D/A conversion processing, image data encoding processing, image data compression processing, image data decoding processing, enlargement/reduction processing (resizing), noise reduction processing, color conversion processing, and the like. Further, various types of image processing such as panorama development, mapping processing, and conversion of the VR image that is an omnidirectional image or a wide-range image having a wide-range video even if it is not omnidirectional are also performed. The image processing unit **504** may be constituted by a dedicated circuit block for executing specific image processing. Further, depending on the type of image processing, the CPU **501** can execute image processing according to the program without using the image processing unit **504**.

(101) The display **505** displays an image, a GUI screen that forms a graphical user interface (GUI), and the like on the basis of the control of the CPU **501**. The CPU **501** controls each unit of the display control apparatus **500** to generate a display control signal according to the program, to generate a video signal for display on the display **505**, and to output the video signal to the display **505**. The display **505** displays a video on the basis of the generated/output video signal. The display control apparatus **500** itself may include an interface for outputting the video signal for display on the display **505**, and the display **505** may be configured by an external monitor (a television, an HMD, or the like).

(102) The operation unit **506** is an input device for accepting user operations, including a character information input device such as a keyboard, a pointing device such as a mouse or a touch panel, a button, a dial, a joystick, a touch sensor, a touch pad, and the like. In the present embodiment, the operation unit **506** includes the touch panel **506a** and the operation units **506b**, **506c**, **506d**, and **506e**.

(103) The recording medium **508** such as a memory card, CD, or DVD can be detachably attached to the recording medium I/F **507**. The recording medium I/F **507** reads data from the attached recording medium **508** and writes data to the recording medium **508** on the basis of the control of the CPU **501**. The recording medium **508** stores data such as an image to be displayed on the display **505**. The external I/F **509** is an interface that is connected to an external apparatus via a wired cable (such as a USB cable) or wirelessly for performing input/output (data communication) of the video signal and the audio signal. The communication I/F **510** is an interface that communicates (wirelessly communicates) with an external apparatus, the Internet **511**, or the like for performing transmission/reception of various types of data such as files and commands (data communication).

(104) The audio output unit **512** outputs an audio of a moving image or music data reproduced by the display control apparatus **500**, operation sounds, ringtones, various notification sounds, and the like. The audio output unit **512** includes the audio output terminal **512a** for connecting an earphone or the like and the speaker **512b**, but the audio output unit **512** may output audio data to an external speaker through wireless communication or the like.

(105) The orientation detection unit **513** detects the orientation (the inclination) of the display control apparatus **500** with respect to a direction of gravity and the orientation of the display

control apparatus **500** with respect to each axis of a yaw direction, a pitch direction, and a roll direction, and notifies the CPU **501** of the orientation information. It is possible to determine whether the display control apparatus **500** is held horizontally, is held vertically, is directed upward, is directed downward, is in an oblique orientation, or the like on the basis of the orientation detected by the orientation detection unit **513**. In addition, it is possible to determine whether or not the display control apparatus **500** is tilted in the rotation directions such as the yaw direction, the pitch direction, and the roll direction; the degree of the tilt; whether the display control apparatus **500** is rotated in the rotation direction; and the like. One sensor or a combination of a plurality of sensors among an acceleration sensor, a gyro sensor, a geomagnetic sensor, an orientation sensor, an altitude sensor, and the like can be used as the orientation detection unit **513**.

(106) As described above, the operation unit **506** includes the touch panel **506a**. The touch panel **506a** is an input device which is superimposed on the display **505** and configured in a plane and from which coordinate information is output according to the touched position. The CPU **501** can detect the following operations or states on the touch panel **506a**. A state in which the touch panel **506a** is newly touched by a finger or pen that has not touched the touch panel **506a**, that is, the start of touch (hereinafter referred to as touch-down). A state in which the touch panel **506a** is touched with a finger or a pen (hereinafter referred to as touch-on). A state in which the finger or pen is moving while touching the touch panel **506a** (hereinafter referred to as touch-move). A state in which the finger or pen touching the touch panel **506a** is separated from the touch panel **506a**, that is, the end of touch (hereinafter referred to as touch-up). A state in which nothing is touched on the touch panel **506a** (hereinafter referred to as touch-off).

(107) When the touch-down is detected, the touch-on is also detected at the same time. After the touch-down, the touch-on normally continues to be detected unless the touch-up is detected. Even in a case where the touch-move is detected, the touch-on is detected at the same time. Even if the touch-on is detected, the touch-move is not detected if the touch position does not move. When it is detected that all the finger and pen that have touched have touched up, the touch-off is detected.

(108) The CPU **501** is notified of these operations/states and the coordinates of the position where the finger or pen touches the touch panel **506a** through the internal bus, and then, the CPU **501** determines what kind of operation (touch operation) is performed on the touch panel **506a** on the basis of the notified information. As for the touch-move, the moving direction of the finger or pen moving on the touch panel **506a** can also be determined for each vertical component/horizontal component on the touch panel **506a** on the basis of the change in the position coordinates. In a case where it is detected that the touch-move has been performed for a predetermined distance or more, it is determined that a slide operation is performed. An operation of touching the touch panel **506a** with the finger and quickly moving it by a certain distance and then releasing it as it is, is called a flick. The flick is, in other words, an operation of quickly tracing the touch panel **506a** as if the finger flicks on the touch panel **506a**. It can be determined that the flick is performed when the touch-move of a predetermined distance or more at a predetermined speed or more is detected and the touch-up is detected as it is (it can be determined that the flick occurs following the slide operation). Further, a touch operation of touching a plurality of locations (for example, two points) at the same time to bring the touch positions closer to each other is referred to as pinch-in, and a touch operation of moving the touch positions away from each other is referred to as pinch-out. The pinch-out and the pinch-in are collectively referred to as a pinch operation (or simply pinch). As the touch panel **506a**, any one of various types of touch panels such as a resistive film type, a capacitive type, a surface acoustic wave type, an infrared type, an electromagnetic induction type, an image recognition type, an optical sensor type, and the like may be used. There are a method of detecting that there is a touch when there is contact with the touch panel, and a method of detecting that there is a touch when there is an approach of the finger or pen to the touch panel, but any one method may be used.

(109) FIG. 5C is an external view of VR goggles (a head mount adapter) **530** to which the display

control apparatus **500** can be attached. The display control apparatus **500** can also be used as a head mounted display (HMD) by being attached to the VR goggles **530**. An insertion slot **531** is an insertion slot for inserting the display control apparatus **500**. The entire display control apparatus **500** can be inserted into the VR goggles **530** with the display surface of the display **505** facing a side (that is, the user side) of a headband **532** for fixing the VR goggles **530** to the user's head. The user can visually recognize the display **505** without holding the display control apparatus **500** by hand while wearing the VR goggles **530**, to which the display control apparatus **500** is attached, on the user's head. In this case, when the user moves the head or the whole body, the orientation of the display control apparatus **500** also changes. The orientation detection unit **513** detects the orientation change of the display control apparatus **500** at this time, and the CPU **501** performs processing for VR display on the basis of this orientation change. In this case, detection of the orientation of the display control apparatus **500** by the orientation detection unit **513** is equivalent to detection of the orientation of the user's head (a direction in which the line of sight of the user is directed). The display control apparatus **500** itself may be an HMD that can be worn on the head without the VR goggles. The display control apparatus **500** may have a configuration (a line-of-sight detection unit) that detects the line of sight of the user in more detail.

(110) In a case where the present invention is applied to the display control apparatus **500**, the image displayed on the display **505** may not be an LV image. The image displayed on the display **505** may be a computer graphic (CG) image such as a game screen. An image of xR such as virtual reality (VR), augmented reality (AR), or mixed reality (MR) may be displayed on the display **505**. In this case as well, an item is displayed near an indicator that the user is likely to pay attention to so as not to overlap the indicator. The indicator is, for example, an indicator that indicates a line-of-sight position or an indicator that indicates a CG object.

(111) FIG. **6I** is an example of a screen displayed on the display **505**. In FIG. **6I**, a VR image **607** is displayed, and an icon **608** indicating the line-of-sight position of the user is superimposed on the VR image **607**. Further, in response to the user's gaze on an object (a bronze statue), simple information **609** on the object is displayed. An item **610** for displaying detailed information on the object that the user is gazing at is displayed near the simple information **609** not to overlap the simple information **609** in response to an operation on the operation unit **506**. When the item **610** is displayed near the simple information **609** displayed in association with the object that the user is gazing at, the user can check the item **610** with a small amount of movement of the line of sight. Further, since the simple information **609** and the item **610** are not superimposed on each other, the user can check the simple information **609** without being disturbed by the item **610**. In this way, the forms of the simple information **609** and the items **610** are not particularly limited, and they may not be rectangular.

(112) The various controls described above that are performed by the CPU **501** may be performed by one piece of hardware, or a plurality of pieces of hardware (for example, a plurality of processors or circuits) may share the processing to perform the control of the entire apparatus.

(113) According to the present invention, it is possible to display an item such that the user can check the item without being disturbed and with a small amount of movement of the line of sight.

OTHER EMBODIMENTS

(114) Embodiment(s) of the present invention can also be realized by a computer of a system or apparatus that reads out and executes computer executable instructions (e.g., one or more programs) recorded on a storage medium (which may also be referred to more fully as a 'non-transitory computer-readable storage medium') to perform the functions of one or more of the above-described embodiment(s) and/or that includes one or more circuits (e.g., application specific integrated circuit (ASIC)) for performing the functions of one or more of the above-described embodiment(s), and by a method performed by the computer of the system or apparatus by, for example, reading out and executing the computer executable instructions from the storage medium to perform the functions of one or more of the above-described embodiment(s) and/or controlling

the one or more circuits to perform the functions of one or more of the above-described embodiment(s). The computer may comprise one or more processors (e.g., central processing unit (CPU), micro processing unit (MPU)) and may include a network of separate computers or separate processors to read out and execute the computer executable instructions. The computer executable instructions may be provided to the computer, for example, from a network or the storage medium. The storage medium may include, for example, one or more of a hard disk, a random-access memory (RAM), a read only memory (ROM), a storage of distributed computing systems, an optical disk (such as a compact disc (CD), digital versatile disc (DVD), or Blu-ray Disc (BD)TM), a flash memory device, a memory card, and the like.

(115) While the present invention has been described with reference to exemplary embodiments, it is to be understood that the invention is not limited to the disclosed exemplary embodiments. The scope of the following claims is to be accorded the broadest interpretation so as to encompass all such modifications and equivalent structures and functions.

(116) This application claims the benefit of Japanese Patent Application No. 2022-070192, filed on Apr. 21, 2022, which is hereby incorporated by reference herein in its entirety.

Claims

1. An electronic apparatus comprising at least one memory and at least one processor which function as: a detection unit configured to detect a line-of-sight position of a user within a display region; and a display control unit configured to control such that a first indicator is displayed on a basis of the line-of-sight position detected by the detection unit and an item is displayed at a position that does not overlap a range indicated by the first indicator when a predetermined condition is satisfied and is within a predetermined range from the range in response to the predetermined condition being satisfied, wherein the predetermined condition is occurrence of an error or a change in a setting value, and wherein the item indicates the error or the setting value.
2. The electronic apparatus according to claim 1, wherein the first indicator is a line-of-sight pointer that indicates the line-of-sight position detected by the detection unit.
3. The electronic apparatus according to claim 1, wherein, after the display control unit controls such that the item is displayed at a position that does not overlap a range indicated by the first indicator when the predetermined condition is satisfied and is within the predetermined range from the range, the display control unit does not change a display position of the item unless the predetermined condition is satisfied.
4. The electronic apparatus according to claim 1, wherein the display control unit controls such that the first indicator is displayed to overlap the item in a case of controlling such that the first indicator is displayed at a display position of the item.
5. The electronic apparatus according to claim 1, wherein the display control unit controls such that the item is hidden after a predetermined time has elapsed since the item was displayed.
6. The electronic apparatus according to claim 1, wherein the display control unit controls such that the first indicator indicating an object and a second indicator indicating the line-of-sight position are displayed on a basis of the line-of-sight position detected by the detection unit.
7. The electronic apparatus according to claim 1, wherein the item indicates a setting value.
8. The electronic apparatus according to claim 1, wherein the display control unit controls such that the first indicator is displayed in response to a specific operation.
9. The electronic apparatus according to claim 1, wherein the user is capable of visually recognizing an imaging range of an imaging apparatus through the display region, and wherein the first indicator indicates an object region of the imaging apparatus in the imaging range.
10. The electronic apparatus according to claim 1, wherein the user is capable of visually recognizing an imaging range of an imaging apparatus through the display region, and wherein the display control unit controls such that the first indicator is displayed in response to a half-press of a

shutter button of the imaging apparatus.

11. The electronic apparatus according to claim 1, wherein the first indicator indicates a graphic displayed in the display region.

12. The electronic apparatus according to claim 1, wherein, after the display control unit controls such that the item is displayed at a position that does not overlap a range indicated by the first indicator and is within the predetermined range from the range, the display control unit controls such that the item is displayed on a basis of a display position of the first indicator regardless of the line-of-sight position.

13. The electronic apparatus according to claim 1, wherein the display control unit controls such that the item is emphasized in response to the predetermined condition being satisfied.

14. The electronic apparatus according to claim 13, wherein the predetermined condition is a change in a setting value, and wherein the item indicates the setting value.

15. The electronic apparatus according to claim 13, wherein the display control unit controls such that the emphasizing of the item is canceled after a predetermined time has elapsed since the item was emphasized.

16. A control method of an electronic apparatus, comprising: detecting a line-of-sight position of a user within a display region; and controlling such that a first indicator is displayed on a basis of the detected line-of-sight position and an item is displayed at a position that does not overlap a range indicated by the first indicator when a predetermined condition is satisfied and is within a predetermined range from the range in response to the predetermined condition being satisfied, wherein the predetermined condition is occurrence of an error or a change in a setting value, and wherein the item indicates the error or the setting value.

17. A non-transitory computer readable medium that stores a program, wherein the program causes a computer to execute a control method of an electronic apparatus, comprising: detecting a line-of-sight position of a user within a display region; and controlling such that a first indicator is displayed on a basis of the detected line-of-sight position and an item is displayed at a position that does not overlap a range indicated by the first indicator when a predetermined condition is satisfied and is within a predetermined range from the range in response to the predetermined condition being satisfied, wherein the predetermined condition is occurrence of an error or a change in a setting value, and wherein the item indicates the error or the setting value.
