

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12396903
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Chen; Yuan-Yi et al.

Anti-stain absorption pad for underpants and underpants comprising the same

Abstract

An anti-stain absorption pad for underpants and an underpants including the same are provided. The absorption pad includes a waterproof layer, at least one absorption layer and two fixing structures; wherein the waterproof layer includes a main body and two inverse-folded parts respectively provided at two opposite sides of the main body; the at least one absorption layer is disposed on the main body, and the at least one absorption layer is used for absorbing a liquid; and the two fixing structures are respectively disposed at the two inverse-folded parts, and fix the two inverse-folded parts on the at least one absorption layer. Therefore, in the present invention, since the fixing structures are covered by the waterproof layer due to the structure of the inverse-folded parts, backflow and secondary leakage of menstrual blood can be avoided, thereby achieving a complete leakproof effect.

Inventors:	Chen; Yuan-Yi (Kaohsiung, TW), Shih; Wen-Fei (Kaohsiung, TW)
Applicant:	Artemis Medical Devices Co., Ltd. (Kaohsiung, TW)
Family ID:	1000008780407
Assignee:	Artemis Medical Devices Co., Ltd. (Kaohsiung, TW)
Appl. No.:	17/814670
Filed:	July 25, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230051812 A1	Feb. 16, 2023

Foreign Application Priority Data

TW	110209385	Aug. 10, 2021
----	-----------	---------------

Publication Classification

Int. Cl.: A61F13/53 (20060101); A61F13/534 (20060101); A61F13/539 (20060101)

U.S. Cl.:

CPC A61F13/53409 (20130101); A61F13/539 (20130101); A61F2013/53966 (20130101)

Field of Classification Search

CPC: A61F (13/53409); A61F (2013/53966)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4145763	12/1978	Abrams	2/403	A41D 13/129
4280230	12/1980	LaFleur	2/408	A61F 13/70
4338939	12/1981	Daville	604/399	A61F 5/4401
4644945	12/1986	Thorner	2/403	A61F 5/4401
5135522	12/1991	Fahrenkrug	604/401	A61F 13/64
5435014	12/1994	Moretz	2/403	A61F 13/15699
5549593	12/1995	Ygge	604/391	A61F 13/72
5669902	12/1996	Sivilich	604/397	A61F 13/471
5853405	12/1997	Suprise	604/385.29	A61F 13/49413
6807685	12/2003	Hasegawa	2/400	A61F 13/505
7344526	12/2007	Yang	2/919	A61F 13/505
7491196	12/2008	Franke	604/397	A61F 13/496
7875014	12/2010	Hendren	604/396	A61F 13/565
7993322	12/2010	Brud	604/397	A61F 13/66
8282618	12/2011	Nordness	604/385.27	A61F 13/496
8361049	12/2012	Coenen	604/394	A61F 13/505
9700079	12/2016	Franke	N/A	A41B 9/001
10165801	12/2018	Blibech	N/A	A41B 9/02
10478351	12/2018	Alligood	N/A	A61F 13/474
11950988	12/2023	Alligood	N/A	A61F 13/476
2005/0131382	12/2004	Brud	604/401	A61F 13/66
2006/0206085	12/2005	Gegelys	604/395	A61F 13/471
2006/0243378	12/2005	Alberts	156/204	A61F 13/15739
2006/0247599	12/2005	Mullen	604/402	A61F 13/496
2016/0367410	12/2015	Alligood	N/A	A61F 13/47236
2019/0117471	12/2018	Brownlee	N/A	A61F 13/49017
2020/0085639	12/2019	Alligood	N/A	A61F 13/471
2022/0313502	12/2021	Brownlee	N/A	A61F 13/5519
2023/0051812	12/2022	Chen	N/A	A61F 5/44

Primary Examiner: Townsend; Guy K

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION

(1) This application claims the priority of Taiwanese patent application No. 110209385, filed on Aug. 10, 2021, which is incorporated herewith by reference.

BACKGROUND OF THE INVENTION

1. Field of the Invention

(2) The present invention relates to an absorption pad and an underpants comprising the same, and more particularly, to an anti-stain absorption pad for underpants, which is applied in the structure of the underpants worn by women during the menstrual period for preventing leakage of menstrual blood, and an underpants comprising the same.

2. The Prior Arts

(3) Absorption pad is a structure for absorbing liquid, which is generally disposed on the bottom of women's underpants for absorbing the menstrual blood generated during women's menstrual period, so as to prevent the menstrual blood from leaking and contaminating the clothes or bed sheets.

(4) Conventional absorption pads are disposable and must be discarded after use. And, since the conventional absorption pads belong to non-recyclable waste and cannot be decomposed naturally, they must be processed by landfill treatment or incinerators, thereby causing the risk of generating toxic substances such as dioxin and polychlorinated biphenyls, which leads to serious environmental pollution. Therefore, the amount of garbage after a long time use will also cause a considerable burden to the environment.

(5) In order to reduce the increasing amount of garbage, there are also period underwears on the market in which the structure of the underpants is designed to have waterproof function, or in which the underpants is provided with an absorption pad thereon so as to have the functions of barring and absorbing menstrual blood. However, in the structure of the conventional underpants, the absorption pad is fixed on the underpants in such a way that the absorption pad and the underpants are fixed together with sutures by means of general machine sewing or hand sewing, such that enables the conventional underpants to have functions of barring and absorbing menstrual blood. However, in the case of adopting such fixing way, since the sutures are mostly cotton yarn or made of other materials with water-absorbing function, when the menstrual blood is absorbed by the absorption pad, the sutures connecting the absorption pad and the underpants are prone to contact with the menstrual blood, such that a siphon phenomenon of the menstrual blood occurs at the suture, and causing the menstrual blood, which has flowed out and been absorbed by the absorption pad, to flow back via the sutures and contaminate the human body, thereby causing discomfort to the user. Also, when the menstrual blood is in an excessive amount, the menstrual blood flowing back from the fixing structures due to the siphon phenomenon may cause secondary leakage, thereby the conventional underpants cannot achieve a complete leakproof function.

(6) In addition, for the structure of the conventional underpants, the sutures connecting the absorption pad and the underpants are prone to contact with the human skin after the underpants is worn for a long time, thereby, after long time contacting and rubbing, it is prone to cause discomfort to the human body, or even cause more severe circumstances such as skin abrasion or inflammation.

SUMMARY OF THE INVENTION

(7) A primary objective of the present invention is to provide an anti-stain absorption pad for underpants, which is applied in the structure of the underpants worn by women during the menstrual period for preventing leakage of menstrual blood; and an underpants comprising the same.

- (8) Another objective of the present invention is to provide an anti-stain absorption pad for underpants, which prevents the human from rubbing their skin against the sutures when wearing the underpants, thereby improving the wearing touch and achieving a more comfortable wearing; and an underpants comprising the same.
- (9) For achieving the foregoing objectives, an anti-stain absorption pad for underpants, which comprises a waterproof layer, at least one absorption layer and two fixing structures, is provided in the present invention.
- (10) The waterproof layer comprises a main body and two inverse-folded parts, wherein the main body includes a first surface and a second surface, the two inverse-folded parts are respectively provided at two opposite sides of the main body, and each of the two inverse-folded parts includes a third surface and a fourth surface.
- (11) The at least one absorption layer includes a first absorption surface and a second absorption surface, the at least one absorption layer is disposed on the main body, the first absorption surface is arranged on the second surface of the waterproof layer, the third surfaces of the two inverse-folded parts are arranged on the second absorption surface, and the at least one absorption layer is used for absorbing a liquid.
- (12) The two fixing structures are respectively disposed at the two inverse-folded parts, and fix the two inverse-folded parts on the at least one absorption layer.
- (13) In some embodiments, each of the two inverse-folded parts further comprises a folded portion, each of the folded portions includes a fifth surface and a sixth surface, and the two fixing structures respectively penetrate through the fifth surface, the sixth surface, the fourth surface, the third surface, the second absorption surface, and the first absorption surface in sequence.
- (14) In some embodiments, an underpants comprising the aforementioned anti-stain absorption pad is provided, wherein the underpants comprises a front crotch part and a rear crotch part, and two opposite sides of the waterproof layer are connected to the front crotch part and the rear crotch part, respectively.
- (15) In some embodiments, the underpants further comprises a bottom crotch part, two opposite sides of the bottom crotch part are connected to the front crotch part and the rear crotch part, respectively, and the first surface of the waterproof layer is located adjacent to the bottom crotch part.
- (16) In some embodiments, the underpants further comprises a bottom crotch part, two opposite sides of the bottom crotch part are connected to the front crotch part and the rear crotch part, respectively, and the first surface of the waterproof layer is disposed on the bottom crotch part.
- (17) In some embodiments, an underpants comprising the aforementioned anti-stain absorption pad is provided, wherein the underpants comprises a front crotch part, a rear crotch part and a bottom crotch part, and the first surface of the waterproof layer is disposed on the bottom crotch part and the rear crotch part.
- (18) In some embodiments, the anti-stain absorption pad for underpants comprises a plurality of the absorption layers.
- (19) In some embodiments, the two fixing structures are sutures.
- (20) The effects of the present invention are in those, since the fixing structures can be covered by the waterproof layer due to the structure of the inverse-folded parts, it is possible to prevent the liquid from flowing back via the fixing structures due to the siphon phenomenon and contaminating the human body, thereby causing discomfort to the user. Also, when the menstrual blood is in an excessive amount, it is possible to avoid the secondary leakage caused by the menstrual blood flowing back from the fixing structures due to the siphon phenomenon, thereby achieving a complete leakproof effect.
- (21) In addition, in the present invention, the fixing structures can be covered by the waterproof layer, which prevents the human skin from contacting with and rubbing against the fixing structures

for a long time when the user wears the underpants, thereby improving the wearing touch and achieving a more comfortable wearing.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The present invention will be apparent to those skilled in the art by reading the following detailed description of a preferred embodiment thereof, with reference to the attached drawings, in which:
- (2) FIG. 1 is a perspective view of an anti-stain absorption pad for underpants according to a first embodiment of the present invention.
- (3) FIG. 2 is an exploded view of the anti-stain absorption pad for underpants according to the first embodiment of the present invention.
- (4) FIG. 3 is a cross-sectional view of the anti-stain absorption pad for underpants according to the first embodiment of the present invention.
- (5) FIG. 4 is a schematic diagram illustrating the liquid absorption of the anti-stain absorption pad for underpants according to a first embodiment of the present invention.
- (6) FIG. 5 is a cross-sectional view of an anti-stain absorption pad for underpants according to a second embodiment of the present invention.
- (7) FIG. 6 is a cross-sectional view of an anti-stain absorption pad for underpants according to a third embodiment of the present invention.
- (8) FIG. 7 is an exploded view of an anti-stain absorption pad for underpants according to a fourth embodiment of the present invention.
- (9) FIG. 8 is a perspective view of an anti-stain absorption pad for underpants according to a fifth embodiment of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

- (10) The following description provides a further understanding of the embodiments of the present invention in conjunction with the drawings and the reference numerals, in order that those skilled in the art can implement them after studying the present specification.
- (11) FIG. 1 is a perspective view of an anti-stain absorption pad for underpants according to a first embodiment of the present invention. FIG. 2 is an exploded view of the anti-stain absorption pad for underpants according to the first embodiment of the present invention. FIG. 3 is a cross-sectional view of the anti-stain absorption pad for underpants according to the first embodiment of the present invention. As shown in FIGS. 1 to 3, an anti-stain absorption pad for underpants, which comprises a waterproof layer 10, at least one absorption layer 20 and two fixing structures 30, is provided in the present invention.
- (12) The waterproof layer 10 comprises a main body 11 and two inverse-folded parts 12, wherein the main body 11 includes a first surface 111 and a second surface 112. The two inverse-folded parts 12 are respectively provided at two opposite sides of the main body 11, and each of the two inverse-folded parts 12 includes a third surface 121 and a fourth surface 122. Specifically, in the first embodiment of the present invention, the main body 11 is in a shape of sheet, and the bottom and top surfaces of the main body 11 are respectively defined as the first surface 111 and the second surface 112, the two inverse-folded parts 12 are respectively provided at the two opposite sides of the main body 11, and the bottom and top surfaces of each of the two inverse-folded parts 12 are respectively defined as the third surface 121 and the fourth surface 122.
- (13) The first surface 111 of the main body 11 is continued with the third surfaces 121 of the two inverse-folded parts 12, and the second surface 112 of the main body 11 is continued with the fourth surfaces 122 of the two inverse-folded parts 12. However, the arrangement of the first surface 111, the second surface 112, the third surface 121 and the fourth surface 122 is not limited

thereto, and can be changed according to requirements. For example, the first surface **111** of the main body **11** can be continued with the four surfaces **122** of the two inverse-folded parts **12**, and the second surface **112** of the main body **11** can be continued with the third surfaces **121** of the two inverse-folded parts **12**.

(14) Preferably, the main body **11** is in a shape of rectangle in which two long sides of the rectangle are concave inward to fit the curvature of the inner thigh of the human body, such that the main body **11** can provide fitter and more comfortable wearing.

(15) Preferably, in the first embodiment of the present invention, the waterproof layer **10** is made of a waterproof fabric with functions of waterproof, breathability, windbreak and/or thermal wearing. However, the function of the waterproof layer **10** is not limited thereto, and can be changed according to requirements.

(16) The at least one absorption layer **20** includes a first absorption surface **21** and a second absorption surface **22**. The at least one absorption layer **20** is disposed on the main body **11**. The first absorption surface **21** of the at least one absorption layer **20** is arranged on the second surface **112** of the waterproof layer **10**. The third surfaces **121** of the two inverse-folded parts **12** are arranged on the second absorption surface **22**. The at least one absorption layer **20** is used for absorbing a liquid **90** (as shown in FIG. 4).

(17) Specifically, in the first embodiment of the present invention, the at least one absorption layer **20** is in a shape of sheet, and the bottom and top surfaces of the at least one absorption layer **20** are respectively defined as the first absorption surface **21** and the second absorption surface **22**, and the first absorption surface **21** of the at least one absorption layer **20** is arranged on the second surface **112** of the waterproof layer **10**.

(18) Referring to FIG. 3, preferably, the at least one absorption layer **20** is in a shape of rectangle, and the overall size of the at least one absorption layer **20** is equal to or slightly smaller than the overall size of the waterproof layer **10**, such that the waterproof layer **10** can be inversely folded at two opposite sides along two opposite sides of the at least one absorption layer **20**, respectively, thereby the third surfaces **121** of the two inverse-folded parts **12** are arranged on the second absorption surface **22** of the at least one absorption layer **20**.

(19) Both the first absorption surface **21** and the second absorption surface **22** of the at least one absorption layer **20** can be used for absorbing the liquid **90**. However, the structure of the absorption layer **20** is not limited thereto, and can be changed to a structure wherein only one of the absorption surfaces has the function of absorbing the liquid **90** according to requirements.

(20) In the first embodiment of the present invention, there is only one absorption layer **20**. However, the number of the absorption layer **20** is not limited thereto, and can be increased according to requirements. For example, a plurality of absorption layers **20** can be provided on the waterproof layer **10**, so as to increase the effect of the anti-stain absorption pad for underpants in terms of absorbing the liquid **90**.

(21) The two fixing structures **30** are respectively disposed at the two inverse-folded parts **12**, and fix the two inverse-folded parts **12** on the at least one absorption layer **20**. In the first embodiment of the present invention, the two fixing structures **30** are respectively sutures, wherein the sutures are used to fix the two inverse-folded parts **12** and the at least one absorption layer **20** together by means of hand sewing or machine sewing.

(22) Specifically, in the first embodiment of the present invention, the two fixing structures **30** respectively penetrate through the fourth surface **122** of the two inverse-folded parts **12**, the third surface **121** of the two inverse-folded parts **12**, the second absorption surface **22** of the absorption layer **20**, and the first absorption surface **21** of the absorption layer **20** in sequence, thereby fixing the waterproof layer **10** and the absorption layer **20** together.

(23) In the first embodiment of the present invention, an underpants **91** comprising the aforementioned anti-stain absorption pad is further provided. The underpants **91** comprises a front crotch part **92**, a rear crotch part **93** and a bottom crotch part **94**. Two opposite sides of the bottom

crotch part **94** are respectively connected to the front crotch part **92** and the rear crotch part **93**, the waterproof layer **10** is disposed on the bottom crotch part **94**, and the first surface **111** of the main body **11** of the waterproof layer **10** is fixed on the bottom crotch part **94**. In this way, when the underpants **91** is worn, the liquid **90** can be absorbed by the second absorption surface **22** of the absorption layer **20**. In the first embodiment of the present invention, the liquid **90** is menstrual blood, but the liquid **90** to be absorbed is not limited thereto.

(24) Specifically, the first surface **111** of the main body **11** of the waterproof layer **10** can be attached to the bottom crotch part **94** of the underpants **91** by means of adhering or sewing, such that the first surface **111** of the main body **11** of the waterproof layer **10** can completely fit the bottom crotch part **94** of the underpants **91**. However, the disposing position of the waterproof layer **10** on the underpants **91** is not limited thereto. The waterproof layer **10** can be further disposed on the rear crotch part **93** of the underpants **91**, or further disposed on the front crotch part **92** and the rear crotch part **93** of the underpants **91** simultaneously.

(25) Referring to FIGS. **3** and **4**, wherein FIG. **4** is a schematic diagram illustrating the use of the anti-stain absorption pad for underpants according to a first embodiment of the present invention. When there is liquid **90** flowing to the absorption layer **20**, the liquid **90** will be absorbed by the second absorption surface **22** of the absorption layer **20**. When the liquid **90** is in an excessive amount and thus flows from the second absorption surface **22** to the first absorption surface **21** of the absorption layer **20**, since the waterproof layer **10** is provided at the outer side of the first absorption surface **21** of the absorption layer **20**, it is possible to prevent the liquid **90** from further infiltrating into the bottom crotch part **94** of the underpants **91**, thereby avoiding the leakage of the liquid **90** and achieving the anti-stain effect.

(26) It is noted that in the present invention, since the fixing structures **30** are covered by the waterproof layer **10** due to the structure of the inverse-folded parts **12**, even if the liquid **90** is absorbed by the fixing structures **30** due to the siphon phenomenon, the human body can be prevented from contacting with the liquid **90** flowing back along the fixing structures **30**, thereby achieving a cleaner effect. Also, this prevents the circumstance in the conventional fixing structures **30** that the liquid **90** from flowing back to the absorption layer **20** due to the siphon phenomenon, thereby causing discomfort to the human body arisen from contacting with the liquid **90** and causing the leakage of the liquid **90**.

(27) In addition, since the fixing structures **30** are covered by the waterproof layer **10**, when the user wears the underpants, the human skin can be prevented from contacting with and rubbing against the fixing structures **30** for a long time, thereby a more comfortable wearing touch and a simple and aesthetic appearance can be achieved.

(28) FIG. **5** is a cross-sectional view of an anti-stain absorption pad for underpants according to a second embodiment of the present invention. As shown in FIG. **5**, in the present invention, the second embodiment is different from the first embodiment in that the anti-stain absorption pad for underpants comprises a plurality of absorption layers **20**. The plurality of absorption layers **20** (for example, three absorption layers **20**) are disposed on the waterproof layer **10**. The second absorption surface **22a** of the topmost absorption layer **20a** faces upward, and the first absorption surface **21a** of the topmost absorption layer **20a** is arranged on the second absorption surface **22a** of another absorption layer **20a**. The first absorption surface **21a** of the middle absorption layer **20a** is arranged on the second absorption surface **22a** of the bottommost absorption layer **20a**. The first absorption surface **21a** of the bottom absorption layer **20a** is located adjacent to the second surface **112a** of the waterproof layer **10a**. The waterproof layer **10a** are inversely folded at two opposite sides thereof, such that the third surfaces **121a** of the two inverse-folded parts **12a** are arranged on the second surface **22a** of the topmost absorption layer **20a**. In this way, the effect of the anti-stain absorption pad for underpants in terms of absorbing the liquid **90** can be increased.

(29) FIG. **6** is a cross-sectional view of an anti-stain absorption pad for underpants according to a third embodiment of the present invention. As shown in FIG. **6**, in the present invention, the third

embodiment is different from the first embodiment in that each of the two inverse-folded parts **12b** further include a folded portion **13**, and the bottom and top surfaces of each of the folded portions **13** are respectively defined as a fifth surface **131** and a sixth surface **132**. Preferably, the fifth surface **131** is continued with the third surface **121b**, and the sixth surface **132** is continued with the fourth surface **122b**.

(30) The two fixing structures **30b** respectively penetrate through the fifth surface **131**, the sixth surface **132**, the fourth surface **122b**, the third surface **121b**, the second absorption surface **22b** and the first absorption surface **21b** in sequence. In this way, the effect of fixing the waterproof layer **10b** and the absorption layer **20b** together can be increased, and the effect of providing the fixing structures **30b** can be further enhanced, that is, this prevent the waterproof layer **10b** from being separated from the absorption layer **20b** due to the breakage of the inverse-folded parts **12b**.

(31) FIG. 7 is an exploded view of an anti-stain absorption pad for underpants according to a fourth embodiment of the present invention. As shown in FIG. 7, in the present invention, the fourth embodiment is different from the first embodiment in that the underpants **91c** only includes a front crotch part **92c** and a rear crotch part **93c**, and two opposite sides of the waterproof layer **10c** are respectively connected to the front crotch part **92c** and rear crotch part **93c**. In this way, it is possible to avoid the stuffiness caused by the underpants **91c** with a excessive thickness, thereby achieving a better breathable effect.

(32) FIG. 8 is a perspective view of an anti-stain absorption pad for underpants according to a fifth embodiment of the present invention. As shown in FIG. 8, in the present invention, the fifth embodiment is different from the first embodiment in that only two opposite sides of the waterproof layer **10d** are respectively connected to the front crotch part **92d** and the rear crotch part **93d**, while the first surface **111d** of the waterproof layer **10d** is separated from and not fixedly attached to the bottom crotch part **94d**. In this way, it is more convenient for the user to perform cleaning.

(33) In the embodiments of the present invention, the underpants **91** is briefs. However, the type of the underpants **91** is not limited thereto, and can be changed to boxers or other types of underpants according to requirements.

(34) As described above, in the present invention, since the fixing structures **30** are covered by the waterproof layer **10** due to the structure of the inverse-folded parts **12**, it is possible to prevent the liquid **90** from flowing back via the fixing structures **30** due to the siphon phenomenon and contaminating the human body, thereby causing discomfort to the user. Also, when the menstrual blood is in an excessive amount, it is possible to prevent the secondary leakage caused by the menstrual blood flowing back from the fixing structures **30** due to the siphon phenomenon, thereby achieving a complete leakproof effect.

(35) In addition, in the present invention, the fixing structures **30** can be covered by the waterproof layer **10**, which prevents the human skin from contacting with and rubbing against the fixing structures **30** for a long time when the user wears the underpants, thereby improving the wearing touch and achieving a more comfortable wearing touch.

(36) The above descriptions are only provided to explain the preferred embodiments of the present invention, it is not intended to limit the present invention in any form. Therefore, any modifications and changes made without departing from the spirit of the present invention should be included within the scope as claimed in the present invention.

Claims

1. An anti-stain absorption pad for underpants, comprising: a waterproof layer comprising a main body and two inverse-folded parts, wherein the main body includes a first surface and a second surface, the two inverse-folded parts are respectively provided at two opposite sides of the main body, and each of the two inverse-folded parts includes a third surface and a fourth surface; at least

one absorption layer comprising a first absorption surface and a second absorption surface, wherein the at least one absorption layer is disposed on the main body, the first absorption surface is arranged on the second surface of the waterproof layer, the third surfaces of the two inverse-folded parts are arranged on the second absorption surface, and the at least one absorption layer is used for absorbing a liquid; and two fixing structures, which are respectively disposed at the two inverse-folded parts, and fix the two inverse-folded parts on the at least one absorption layer.

2. The anti-stain absorption pad for underpants according to claim 1, wherein each of the two inverse-folded parts comprises a folded portion, each of the folded portions includes a fifth surface and a sixth surface, and the two fixing structures respectively penetrate through the fifth surface, the sixth surface, the fourth surface, the third surface, the second absorption surface, and the first absorption surface in sequence.

3. An underpants comprising the anti-stain absorption pad according to claim 1, wherein the underpants comprises a front crotch part and a rear crotch part, and two opposite sides of the waterproof layer are connected to the front crotch part and the rear crotch part, respectively.

4. The underpants according to claim 3, wherein the underpants further comprises a bottom crotch part, two opposite sides of the bottom crotch part are connected to the front crotch part and the rear crotch part, respectively, and the first surface of the waterproof layer is located adjacent to the bottom crotch part.

5. The underpants according to claim 3, wherein the underpants further comprises a bottom crotch part, two opposite sides of the bottom crotch part are connected to the front crotch part and the rear crotch part, respectively, and the first surface of the waterproof layer is disposed on the bottom crotch part.

6. An underpants comprising the anti-stain absorption pad according to claim 1, wherein the underpants comprises a front crotch part, a rear crotch part and a bottom crotch part, and the first surface of the waterproof layer is disposed on the bottom crotch part and the rear crotch part.

7. The anti-stain absorption pad for underpants according to claim 1, comprising a plurality of the absorption layers.

8. The anti-stain absorption pad for underpants according to claim 1, wherein the two fixing structures are sutures.
