

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12385237
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Chung; Chanseol

Container filling faucet

Abstract

A faucet includes a spout, a water level sensor, and a controller. The spout includes a water outlet having a first set of nozzles oriented at an angle with respect to a central axis defined by the water outlet such that water discharged from the first set of nozzles converges at the central axis at a focal distance from the water outlet. The water level sensor is disposed on the spout and is configured to detect a distance between the water outlet and a level of water in a container disposed below the water outlet. The controller is configured to control the flow of water through the water outlet based on a comparison between the detected distance and the focal distance.

Inventors:	Chung; Chanseol (Milwaukee, WI)
Applicant:	Kohler Co. (Kohler, WI)
Family ID:	67683847
Assignee:	Kohler Co. (Kohler, WI)
Appl. No.:	18/421716
Filed:	January 24, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240247468 A1	Jul. 25, 2024

Related U.S. Application Data

continuation parent-doc US 17812467 20220714 US 11913200 child-doc US 18421716
continuation parent-doc US 17172835 20210210 US 11401705 20220802 child-doc US 17812467
continuation parent-doc US 16284697 20190225 US 10947708 20210316 child-doc US 17172835
us-provisional-application US 62636324 20180228

Publication Classification

Int. Cl.: E03C1/04 (20060101)

U.S. Cl.:

CPC E03C1/0404 (20130101); Y10T137/9464 (20150401)

Field of Classification Search

CPC: E03C (1/0404); E03C (1/055); E03C (1/04); E03C (1/052); E03C (1/057); Y10T (137/9464); G08B (3/10); G08B (21/20)

USPC: 137/801

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4446896	12/1983	Campagna	N/A	N/A
4869287	12/1988	Pepper	N/A	N/A
4905743	12/1989	Gray	N/A	N/A
4917155	12/1989	Koblasz	N/A	N/A
5491333	12/1995	Skell	N/A	N/A
5549273	12/1995	Aharon	N/A	N/A
5782035	12/1997	Locke	N/A	N/A
6227101	12/2000	Rabadi	N/A	N/A
6305267	12/2000	Rolfes	N/A	N/A
6681585	12/2003	Stagg	N/A	N/A
6789585	12/2003	Janke	N/A	N/A
7059342	12/2005	Crimmins	N/A	N/A
7742883	12/2009	Dayton	N/A	N/A
8171843	12/2011	Heffington	N/A	N/A
8355822	12/2012	Jonte	N/A	N/A
8408517	12/2012	Jonte	N/A	N/A
8614414	12/2012	Davidson	N/A	N/A
8695646	12/2013	Agam	N/A	N/A
8994812	12/2014	Giordano	N/A	N/A
9470563	12/2015	DeVerse	N/A	N/A
9603482	12/2016	McHale	N/A	N/A
10947708	12/2020	Chung	N/A	N/A
2010/0108165	12/2009	Rodenbeck	N/A	N/A
2016/0024766	12/2015	Sawaski	N/A	N/A
2016/0069053	12/2015	Belz et al.	N/A	N/A
2016/0136659	12/2015	Erickson	N/A	N/A
2016/0137480	12/2015	Ashrafzadeh	N/A	N/A
2016/0207753	12/2015	Choi	N/A	N/A
2016/0355388	12/2015	Willis	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
101688386	12/2011	CN	N/A
103574156	12/2015	CN	N/A
107477237	12/2016	CN	N/A
105597949	12/2017	CN	N/A
10 2012 221 456	12/2012	DE	N/A
WO 2017006341	12/2016	WO	N/A

OTHER PUBLICATIONS

CN Second Office Action CN Application No. 201910151779.X, dated Oct. 23, 2020, 16 pages. cited by applicant

Dutta 2016; Faucet Add-On Water Supply Management System Using Smart Sensors; 4 pgs. cited by applicant

Garun 2012; New GE Refrigerators Will Recognize When to Stop Filling Containers With Water; 14 pgs. cited by applicant

Chinese Third Office Action on CN Patent Application No. 201910151779.X dated Mar. 17, 2021 4 Pages. cited by applicant

Foreign Action other than Search Report on CN 201910151779.X dated Mar. 23, 2020. cited by applicant

Primary Examiner: Barry; Daphne M

Attorney, Agent or Firm: Husch Blackwell LLP

Background/Summary

PRIORITY CLAIM (1) The present application is a Continuation of U.S. application Ser. No. 17/812,468, filed Jul. 14, 2022, which is a Continuation of U.S. application Ser. No. 17/172,835 filed Feb. 10, 2021, now U.S. Pat. No. 11,401,705, which is a Continuation of U.S. application Ser. No. 16/284,697 filed Feb. 25, 2019, now U.S. Pat. No. 10,947,708, which claims priority from U.S. Provisional Application No. 62/636,324, filed Feb. 28, 2018, each of which is hereby fully incorporated herein by reference in its entirety.

BACKGROUND

(1) Faucets are typically controlled through a handle assembly including a valve. To initiate water flow, a user adjusts the orientation of the handle from an “off” position to open the valve. Once a desired amount of water has been discharged, the user re-orientes the handle to the “off” position to prevent further flow. Such a process may render it difficult for users to precisely fill containers. For example, if the user orients the handle such that water flows from the faucet at a high rate, the user must shut the water flow off at just the right time to get the desired amount of water. Oftentimes, the user overfills the container and has to pour the excess water out of the container, wasting water.

SUMMARY

(2) One embodiment relates to a faucet. The faucet includes a base, a spout, a water level sensor, and a controller. The spout is coupled to the base and includes a first portion proximate to the base and a second portion adjustable relative to the first portion. The second portion includes a water outlet. The water level sensor is disposed on the second portion, and is configured to detect a distance between the water outlet and a level of water in a container disposed below the water outlet. The controller is configured to control the flow of water through the water outlet based on the detected distance between the water outlet and the level of water.

(3) Another embodiment relates to a faucet. The faucet includes a base, a spout, a water level sensor, and a controller. The spout is coupled to the base and includes a water outlet. The water outlet includes a first set of nozzles and a second set of nozzles. The first set of nozzles are oriented at an angle with respect to a central axis defined by the water outlet such that water discharged from the first set of nozzles reaches the central axis at a focal distance from the water outlet. The second set of nozzles are oriented substantially parallel to the central axis such that water discharged from the second set of nozzles is substantially parallel to the central axis. The water level sensor is disposed on the spout, and is configured to detect a distance between the water outlet and a level of water in a container disposed below the water outlet. The controller is configured to control the flow of water through the water outlet based on the detected distance between the water outlet and the level of water.

(4) Another embodiment relates to a method of controlling the flow of water through a faucet. The method includes receiving, by a controller associated with the faucet, a first input to discharge water from a water outlet of the faucet until the water reaches a predetermined distance from the water outlet, wherein the water outlet includes a first set of nozzles and a second set of nozzles. The method further includes providing, by the controller in response to the first input, a control signal to a valve to discharge water from the first set of nozzles, wherein the first set of nozzles are oriented at an angle with respect to a central axis defined by the water outlet such that water discharged by the first set of nozzles reaches the central axis at the predetermined distance.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a perspective view of a faucet body according to an exemplary embodiment.

(2) FIGS. 2-3 are perspective views of the faucet body shown in FIG. 1 in different configurations, according to various exemplary embodiments.

(3) FIG. 4 is a perspective view of a magnetic joint used to rotatably couple segments of a faucet body to one another, according to an exemplary embodiment.

(4) FIG. 5 is a perspective view of an end of a waterway tube including a water level sensor, according to an exemplary embodiment.

(5) FIGS. 6-8 are schematic side views of a faucet including a system including a faucet, according to various exemplary embodiments.

(6) FIG. 9 is a perspective view of an articulating faucet, according to an exemplary embodiment.

(7) FIG. 10 is a flow diagram of a method of controlling the flow of a faucet to fill a container to a desired level, according to an exemplary embodiment.

DETAILED DESCRIPTION OF THE DRAWINGS

(8) Referring generally to the FIGURES, disclosed herein are faucets that include a water level sensor. The faucets also include a controller and multi-configuration spray head. The controller is configured to control flow through the spray head based on inputs received from a user as well as the water level sensor. Specifically, in response to an input indicating the presence of a container beneath an outlet assembly of the faucet, the controller is configured to provide a control signal to a flow control device (e.g., a valve, etc.) to discharge water via a first set of nozzles of the outlet assembly. The first set of nozzles may be oriented such that the discharged water converges to a point a predetermined distance from the outlet assembly.

(9) Additionally, through the water level sensor, the controller tracks the level of water in the container and, upon the water level reaching the predetermined distance from the faucet, prevents further water flow from the faucet. As such, the converging water flow from the spray head provides the user with a visual indication as to the amount of water that will be dispensed. Additionally, since water flow automatically shuts off upon the water level reaching the desired

level, the faucet disclosed herein facilitates the conservation of water by preventing users from overfilling containers.

(10) Referring now to FIG. 1 a faucet body **100** is shown, according to an example embodiment. It should be understood that the faucet body **100** is exemplary only. The present disclosure is applicable to any type of faucet body. In the example shown, the faucet body **100** includes eight segments **102, 104, 106, 108, 110, 112, 114, and 116**. It should be understood that, in various alternative embodiments, the faucet body **100** may include any number of segments without departing from the scope of the present disclosure. For example, in one embodiment, the faucet body **100** includes only two segments.

(11) As shown, each of the segments **102, 104, 106, 108, 110, 112, 114, and 116** is substantially cylindrical-shaped. The segments **102, 104, 106, 108, 110, 112, 114, and 116** each include a cavity defining a waterway through which water from a water supply may be provided to an outlet assembly **118** of the segment **116**. For example, in one embodiment, the cavities of the segments **102, 104, 106, 108, 110, 112, 114, and 116** are substantially cylindrical-shaped to define a tubular waterway.

(12) The outlet assembly **118** is configured to discharge water from the faucet body **100** to an area of interest (e.g., a sink basin, etc.) in response to various inputs described herein. As shown, the outlet assembly includes a spray head **124**. In the embodiment shown, the spray head **124** includes a first set of nozzles **126** and a second set of nozzles **128**. The spray head **124** also includes a valve assembly disposed therein to direct water to either the first set of nozzles **126** or the second set of nozzles **128**. In various embodiments, the valve disposed within the spray head **124** is structured similar to that disclosed in U.S. patent application Ser. No. 14/547,913 filed on Nov. 19, 2014 and entitled “Multi-Function Sprayhead,” incorporated by reference herein in its entirety. For example, the valve may include a fluid inlet configured to receive water flowing through the waterway defined by the segments **102, 104, 106, 108, 110, 112, 114, and 116**, a body that defines a first chamber and a second chamber, and a movable diverter. The diverter may be configured to be moved from a first configuration, in which the first set of nozzles **126** is fluidly coupled to the fluid inlet via the first chamber, and a second configuration, in which the second set of nozzles **128** is fluidly coupled to the fluid inlet via the second chamber. In one embodiment, the valve is a solenoid valve and is movable from the first configuration to the second configuration in response to control signals received from a controller. According to other exemplary embodiments, the valve assembly is located remotely from the spray head **124**.

(13) In some embodiments, the first set of nozzles **126** includes a plurality of openings in a cap that extend in a direction that is substantially parallel to a central axis **130** of the outlet assembly **118**. In one embodiment, the first set of nozzles **126** are equally distributed throughout the cap. As such, when the valve is placed in the first configuration, water is discharged in a uniform flow including a plurality of individual streams travelling substantially parallel to the central axis **130**. The second set of nozzles **128** includes another plurality of openings in the cap that extend at an angle to the central axis **130**. In an embodiment, each nozzle in the second set of nozzles **128** is radially displaced from the central axis **130** and the angle is chosen such that axes of each of the nozzles intersects the central axis **130** a predetermined distance (herein referred to as the “focal distance”) from the cap. As such, when the valve is placed in the second configuration, water is discharged in a flow including a plurality of individual streams that converge towards the central axis **130** until colliding with one another at the focal distance. As described herein, such an output flow may be used to indicate an eventual stopping point of the output flow to the user.

(14) As shown in FIG. 1, the segment **116** further includes a water level sensor **132** disposed on an outer face thereof. In some embodiments, the water level sensor **132** includes a transmitter and a receiver. The transmitter is configured to discharge an electromagnetic signal (e.g., an ultrasonic signal) that reflects off a water surface (e.g., in a container beneath the outlet assembly **118**) and is received by the transmitter. In various embodiments, the water level sensor **132** includes circuitry

configured to calculate the delay between the emission of the electromagnetic signal and the receipt by the receiver. Based on the delay, the distance between the water level and the water level sensor **132** may be determined. As described herein, the controller may control water flow through the faucet based on the determined distance. For example, in one embodiment, the controller is configured to prevent further water flow (e.g., by closing an intake valve) through the faucet when the water level is a predetermined distance (e.g., the focal distance) from the water level sensor **132**.

(15) Still referring to FIG. **1**, each of the segments **102**, **104**, **106**, **108**, **110**, **112**, **114**, and **116** includes a tapered or angled end. At such angled ends, joints **122** are formed between successive ones of the segments **102**, **104**, **106**, **108**, **110**, **112**, **114**, and **116**. As described with respect to FIG. **4**, in some embodiments, the angled ends include angular brackets including a set of magnetic elements therein that facilitate the rotation of segments **102**, **104**, **106**, **108**, **110**, **112**, **114**, and **116** with respect to one another. Such rotation of individual ones of the segments facilitates placing the faucet body **100** in a number of different configurations.

(16) Referring now to FIGS. **2-3**, perspective views where the faucet body **100** is mounted to a base **134** affixed to a mounting surface **136** (e.g., a counter top) are shown, according to example embodiments. For example, in various embodiments, the segment **102** is fixedly mounted to the base **134**. In an alternative embodiment, the segment **102** is rotatably coupled to the base **134**. As a result of the coupling with the base **134**, water from the water supply is discharged from the outlet assembly **118** in response to an intake valve being placed in an open position. As shown, the valve of the outlet assembly **118** is placed in the first configuration such that a plurality of parallel streams are discharged upon turning water flow on. Additionally, the faucet body **100** extends over a basin **138** and discharges water into the basin **138**. In various embodiments, a user may place a container (e.g., a pot, cup, bowl, etc.) beneath the outlet assembly **118** to fill the container.

(17) In the configuration shown in FIG. **2**, the segment **106** has been rotated with respect to the segment **104** such that the segment **106** extends in a direction that is substantially perpendicular to a direction of extension of the segment **102**. Additionally, the segment **110** has been rotated such that the segment **110** extends substantially parallel to the segment **108**. As such, the faucet body **100** extends a relatively large distance into or toward the basin **138**. In the configuration shown in FIG. **3**, the segment **104** has been rotated with respect to the segment **102** such that the segment **104** is inclined at a smaller angle than in the configuration shown in FIG. **2**. Additionally, the segment **110** has been rotated with respect to the segment **108** such that the segment **110** extends at an angle to the segment **108**. As a result, the outlet assembly **118** is higher above the basin **138** than in the configuration shown in FIG. **2**.

(18) Thus, the unique arrangement of the faucet body **100** enables the user to place the faucet body **100** in various configurations where the outlet assembly **118** is placed at different distances from a surface (e.g., a lower surface) of the basin **138**. Such flexibility facilitates complete utilization of the water level sensor **132**. As described herein, the controller is configured to close a water intake valve in response to a detected water level being a predetermined distance from the water outlet assembly **118**. As such, the ability to rotate the segments **102**, **104**, **106**, **108**, **110**, **112**, **114**, and **116** with respect to one another enables the user to fill up different containers to different water levels automatically, as described with respect to FIGS. **6-8**.

(19) It should be understood that the faucet body **100** may differ from the example depicted in FIGS. **1-3**. For example, a faucet body of any external shape may include the outlet assembly **118** and the water level sensor **132** to provide the automatic container-filling functionalities described herein.

(20) Referring now to FIG. **4**, a joint member **400** is shown, according to an example embodiment. In various embodiments, each of the segments **102**, **104**, **106**, **108**, **110**, **112**, **114**, and **116** of the faucet body **100** described with respect to FIG. **1** include structures similar to the joint member **400** at ends thereof that are adjacent to other ones of the segments **102**, **104**, **106**, **108**, **110**, **112**, **114**,

and **116**. As such, two joint members may be disposed at each of the joints **122** described with respect to FIG. **1**. As shown, the joint member **400** includes an annular shaped portion **402**. The annular shaped portion **402** includes cavities having magnetic elements **406** disposed therein. The magnetic elements **406** are in some embodiments uniformly distributed throughout the annular shaped portion **402** in a circumferential direction.

(21) In one embodiment, the magnetic orientation of the magnetic elements **406** for a particular joint member **400** is chosen based on the positioning of the joint member **400**. For example, the magnetic elements **406** may be oriented such that like poles of the magnetic elements **406** of an adjacent joint member **400** (e.g., associated with another one of the segments **102**, **104**, **106**, **108**, **110**, **112**, **114**, and **116**) face one another. In such an arrangement, when adjacent segments **102**, **104**, **106**, **108**, **110**, **112**, **114**, and **116** are rotated such that the magnetic elements **406** disposed in adjacent joint members **400** are aligned or substantially overlapping each another, the magnetic elements repel or bias away from one another, thereby facilitating further rotation of the segments with respect to one another. However, upon the user rotating a particular segment such that the magnetic elements **406** in adjacent joint members **400** are not aligned, the magnetic elements **406** attract or bias toward one another, thereby securely holding the segments **104**, **106**, **108**, **110**, **112**, **114**, and **116** in a fixed rotational position.

(22) In some embodiments, the number of magnetic elements disposed in each joint member **400** decreases with proximity to the water outlet assembly **118**. For example, in one embodiment, the joint members **400** disposed at the joint **122** between the segments **116** and **114** include two magnetic elements **406** and the joint members **400** disposed in the joint between the segments **102** and **104** include six magnetic elements **406**. Such a difference is to account for the greater strain placed on the latter joint **122** due to the weight of the additional segments **104**, **106**, **108**, **110**, **112**, **114**, and **116** supported. Joints **122** between those previously described may have intermediate numbers of magnetic elements (e.g., the joint between the segments **112** and **110** may each include four magnetic elements **406**). As such, segments closer to the base **134** are more difficult to rotate, but provide stronger mechanical support to the remaining segments.

(23) The annular-shaped portion **402** also defines an inner cylindrical opening **404**. In various embodiments, the inner cylindrical opening **404** is of a diameter that is similar to the inner openings enclosed by each of the segments **102**, **104**, **106**, **108**, **110**, **112**, **114**, and **116**. As such, the inner cylindrical openings **404** may be configured to hold a waterway tube configured to direct water received from a water source to the outlet assembly **118**. In one embodiment, the diameter of the inner cylindrical openings **404** are chosen to house both a waterway tube and wiring for the water level sensor **132**.

(24) Referring now to FIG. **5**, a portion of a waterway tube **500** is shown, according to an example embodiment. The waterway tube **500** may extend from an intake valve of the faucet assembly including the faucet body **100** and extend through each of the segments **102**, **104**, **106**, **108**, **110**, **112**, **114**, and **116**. As shown, the waterway tube **500** includes an end portion **502** having an initial diameter greater than the remainder of the waterway tube **500**. The diameter of the end portion **502** gradually decreases with proximity to an end thereof. In one embodiment, the first and second sets of nozzles **126** and **128** are formed in the end portion **502**. In the example shown, water is being discharged from the waterway tube **500** via the second set of nozzles **128**, which extend substantially parallel to a contour defined by the outer surface of the end portion **502**. As such, individual streams of water emerging from the second set of nozzles **128** converge at a focal distance F from the end of the waterway tube **500**.

(25) Also as shown, the water level sensor **132** is disposed on the end portion **502** of the waterway tube **500**. For example, in some embodiments a structure (e.g., ledge) **504** is formed having a surface that extends substantially perpendicular to the central axis **130**. The water level sensor **132** may be affixed to the surface via any method (e.g., an adhesive may be applied to the surface). In such embodiments, since the water level sensor **132** is disposed on the structure **504** that is

displaced from an outer surface of the waterway tube **500**, clearance is provided for wiring **506** associated with the water level sensor **132**. For example, the wiring **506** may extend from the water level sensor **132** and be affixed to the outer surface of the waterway tube **500** prior to the insertion of the waterway tube **500** into the faucet body **100**.

(26) The wiring **506** is configured to provide sensor signals generated via the water level sensor **132** to a controller. Such sensor signals are indicative of the distance of a water level from the water level sensor **132**. In some embodiments, upon such a signal indicating that the water level is the focal distance F away from the water level sensor **132**, the controller is configured to close an intake valve so as to prevent further flow from the faucet. As such, the discharged stream of water provides the user with a visual indication as to level to which the faucet will fill a container.

(27) Referring now to FIG. **6**, a schematic side view of a faucet system **600** is shown, according to an example embodiment. The faucet system **600** includes a faucet assembly **602**, a controller **606**, and a user interface device **622**. The faucet assembly **602** includes a faucet body **604** in fluid communication with a water source via a base. In various embodiments, the faucet body **604** includes a structure similar to the faucet body **100** described with respect to FIGS. **1-5**.

Accordingly, like reference numerals may be used to aid in the description of the faucet body **604**. (28) The faucet body includes the outlet assembly **118** and the water level sensor **132**. As described herein the outlet assembly **118** includes a valve including a flow diverter configured to direct water received via an intake to either a first chamber or a second chamber. The first and second chambers are in fluid communication with separate sets of nozzles of the outlet assembly **118**. Thus, through controlling the configuration of the valve, the form of the water output from the faucet body **604** may be adjusted.

(29) The controller **606** is configured to receive various inputs and provide control signals to various components of the faucet system **600** based on the inputs. The controller **606** includes faucet interfaces **608**, a processor **610**, and a memory **612**. The faucet interfaces **608** include various physical connections with various components of the faucet system **600**. For example, via the faucet interfaces **608**, the controller **606** may be communicably coupled to electrical control valves (e.g., a main intake valve, the valve of the outlet assembly **118**) and the water level sensor **132** via various wires or cables associated with such elements. As such, the faucet interfaces **608** may include a plurality of jacks or soldered joints whereby such components are connected to the controller **606**. Additionally, the faucet interfaces **608** may include a plurality of additional components such as analogue-to-digital converters configured to render signals received and provided by the controller **606** into an accessible form.

(30) The controller **606** includes a processor **610** and a memory **612**. Processor **610** may be a general purpose or specific purpose processor, an application specific integrated circuit (ASIC), one or more field programmable gate arrays (FPGAs), a group of processing components, or other suitable processing components. Processor **610** may be configured to execute computer code or instructions stored in memory **612** or received from other computer readable media (e.g., CD ROM, network storage, a remote server, etc.) to perform one or more of the processes described herein. Memory **612** may include one or more data storage devices (e.g., memory units, memory devices, computer-readable storage media, etc.) configured to store data, computer code, executable instructions, or other forms of computer-readable information. Memory **612** may include random access memory (RAM), read-only memory (ROM), hard drive storage, temporary storage, non-volatile memory, flash memory, optical memory, or any other suitable memory for storing software objects and/or computer instructions.

(31) The user interface device **622** is configured to receive inputs from a user of the faucet system **600** to perform various operations described herein. The user interface device **622** may take a number of different forms in accordance with the present disclosure. While only a single user interface device is shown in FIG. **6**, it should be understood that the faucet system **600** may include multiple user interface devices **622** in multiple forms. For example, in one embodiment, one user

interface device comprises a button disposed proximate to the outlet assembly **118**. The button may be mechanically coupled to the valve disposed therein, enabling the user to manually manipulate the flow output from the outlet assembly. Another user interface device **622** may include an electrical input device. Such a user interface may include a touch display or panel enabling the user to provide inputs to the faucet system to cause water to be discharged from the outlet assembly (e.g., similar to the outlet assembly **118** described with respect to FIG. 1). Yet another user interface device **622** may include a speaker including command recognition modules enabling the user to provide inputs to the faucet system **600** via various audible commands.

(32) In some embodiments, the user interface device **622** (e.g., a button) enables the user to place the faucet into a filling mode. When placed into the filling mode, the controller **606** is configured to control the flow discharged by the faucet system **600** based on a water level sensed by the water level sensor **132**.

(33) In this regard, the memory **612** is shown to include a flow control module **614**. The flow control module **614** is structured to cause the processor **610** to provide control signals to various components of the faucet system **600**. For example, in one embodiment, in response to the user providing an input to place the faucet system **600** into a water filling mode, the controller **606** is configured to provide a first control signal to the outlet assembly **118** to cause a converging water flow to be discharged from the faucet body **604** (e.g., place the diverter into a second configuration to cause water to be discharged via the second set of nozzles **128**). As shown, the converging water flow converges to a point a focal distance F from an emission face of the faucet body **604**.

(34) In some embodiments, at a time after receiving the user input to place the faucet system **600** into the water filling mode, the flow control module **614** causes the controller to change the flow output of the faucet. For example, upon the user depressing a filling mode button (or a predetermined time period thereafter), the flow control module **614** causes the valve of the outlet assembly **118** to change such that a uniform flow is discharged from the faucet. The uniform flow may have a higher rate than the converging flow, so as to more quickly fill a container **618** placed beneath the faucet body **604** in, for example, a faucet basin **616**.

(35) Additionally, the flow control module **614** may cause the processor **610** to monitor signals generated by the water level sensor **132** received via the faucet interfaces **608**. For example, the processor **610** may receive signals indicative of a delay between the transmittal of an ultrasonic beam **620** discharged by the water level sensor **132** and the receipt of a reflected component of the ultrasonic beam **620**. The delay may be compared with a threshold value (e.g., corresponding to a water level being the focal distance F from the water level sensor **132** or other component of the faucet body **604**). In response to receiving an indication that the water level has reached the predetermined level, the flow control module **614** may cause the processor **610** to prevent further water flow by closing an electrical intake valve associated with the faucet system **600**.

(36) Referring now to FIG. 7, the faucet system **600** described with respect to FIG. 6 is shown, but has been placed into a different configuration. For example, the user may have rotated various segments of the faucet body **604** with respect to one another, so as to change the height of the water level sensor **132** with respect to the faucet basin **616**. As a result, the focal distance F is also displaced by the amount the faucet body **604** was adjusted. Due to this adjustment, the user may fill a container **700** that is larger than the container **618** described with respect to FIG. 6 to the same level. As such, the adjustable nature of the faucet body **604** facilitates multiple volumes of containers being filled to different levels.

(37) Referring now to FIG. 8, the configuration of the faucet system **600** is shown at a later time, according to an example embodiment. As shown, the controller **606** has placed the outlet assembly **118** into a configuration such that an evenly distributed spray (e.g., through the first set of nozzles **126**) is discharged. A volume of water has been received in the container **700** such that a top water level **800** is beneath the focal distance F . As such, upon the controller receiving an indication of the water level **800** from the water level sensor **132**, the depicted flow state of the discharged water

will be maintained until the water level **800** reaches the focal distance F. At this point, the controller **606** will automatically prevent further flow from the faucet. As such, the user does not need to actively monitor the status of the water level **800**.

(38) Referring now to FIG. **9**, a faucet body **900** is shown, according to an example embodiment. The faucet body **900** may serve as an alternative to the faucet body **100**. In various embodiments, the faucet body **900** may include any of structures and features described in U.S. Pat. No. 9,568,132 entitled “Clutched Joint for Articulating Faucet,” incorporated by reference herein in its entirety. In summary, instead of including a plurality of segments that are each rotatable with respect to one another as in the faucet body **100**, the faucet body **900** includes a first segment **902**, a second segment **904**, a third segment **906**, and a spray head **908** that are adjustable with respect to one another. The spray head **908** may be configured to produce an adjustable flow output as well as include a water level sensor similar to the outlet assembly **118** described with respect to FIG. **1**.

(39) The segments **902**, **904**, **906**, and **908** are coupled to one another via joints **910**, **912**, and **914**. Each of the joints **910**, **912**, and **914** includes two housings: one attached to each of the respective segments **902**, **904**, **906**, and **908** that are coupled at the associated joint **910**, **912**, and **914**. Such housings are rotatably coupled to one another via a clutch assembly, such that the segments **902**, **904**, **906**, and **908** may be moved in a plane extending through the center of the faucet body **900**. As such, the spray head **908** may be changed in height, enabling the user to fill up various containers to a desired level in accordance with the systems and methods described herein.

(40) Referring now to FIG. **10**, a flow diagram of a method **1000** for operating a faucet is shown, according to an example embodiment. Method **1000** may be executed by, for example the controller **606** of the faucet system **600** described with respect to FIGS. **6-8**. For example, method **1000** may be executed to automatically fill a container to a desired level.

(41) In an operation **1002**, a first input to discharge water until a relative distance between a water level in a container reaches a filling distance from a water outlet of a faucet is received. For example, a user of the faucet system **600** may provide such an input via the user interface device **622**. In an illustrative example, a user may press a filling mode button to place the faucet system **600** into a filling mode. When in the filling mode, the controller **606** operates the faucet in a manner to facilitate the user filling a container beneath the outlet assembly **118** to a desired level. To this end, the controller **606** is configured to place the outlet assembly **118** into a configuration in which a converging water flow is discharged upon receipt of a flow emission input from the user (e.g., by providing a control signal to an electrical diverter valve placed in the outlet assembly **118**). Such a flow emission input may be provided in a number of ways. For example, such an input may be provided simultaneously with the first input (i.e., the first input may cause the faucet to discharge water). Alternatively, the user may provide such an input via the user interface device **622**, which may include a multifunctional display or panel configured to receive any of the user inputs described herein. Additionally, such a water emission input may be provided via a proximity sensor or handle assembly associated with the faucet assembly **602**.

(42) In various embodiments, the converging water flow converges to a point that is a predetermined distance (e.g., the focal distance F) from the outlet assembly **118**. In some embodiments, the predetermined distance is fixed (e.g., five inches from the outlet assembly **118**) based on the angular disposition of the second set of nozzles **128** of the outlet assembly **118** and not adjustable by the user.

(43) Also when placed in filling mode via the first input, the controller **606** is configured to monitor a water level sensed via the water level sensor **132**. As described herein, the controller **606** is configured to control the flow discharged by the faucet assembly **602** based on a sensed water level in a container beneath the faucet assembly **602**. For example, in one implementation, the controller **606** is configured to prevent water flow upon the sensed water level reaching a filling distance. In some embodiments, the filling distance corresponds to the focal distance F and is not adjustable. That way, the converging water flow provides the user with an exact visual representation of the

height where further water flow is prevented. In such embodiments, to adjust the filling level, the user adjusts the relative height of the outlet assembly through adjustments of portions of the faucet assembly **602**. In alternative embodiments, the filling distance is offset from the focal distance. In such embodiments, the filling distance may be adjustable by the user (e.g., the user interface device **622** may include a portion enabling the user to adjust the offset). This way, the user may adjust the filling distance without adjusting the relative height of the outlet assembly **118**.

(44) In an operation **1004**, control signals are provided to a valve and outlet assembly to cause the faucet to discharge a converging water flow. For example, the controller **606** may generate control signal to an electrical valve placed in the outlet assembly **118** so as to cause water received via an inlet to be directed to the second set of nozzles **128**. As such, upon receipt of the water emission input from the user, water is discharged in a plurality of individual streams that converge at the filling distance. At this point, while the converging water flow is discharged, the user may adjust the relative height of the outlet assembly **118** such that the focal distance F is at a desired fill level in the container.

(45) In an operation **1006**, a second input to place the faucet into an automatic filling mode is received. The user may provide such an input in a similar manner as the first input was provided in operation **1002**. For example, in one embodiment, the user may de-press the filling mode button so as to indicate that the faucet has been placed in a configuration (e.g., a desired height) such that the point at which the discharged water converges corresponds to a desired filling level in the container. In an operation **1008**, in response to receiving the second input, control signals are provided to the outlet assembly to cause the faucet to discharge non-converging water. For example, a control signal may be provided to the diverter in the outlet assembly **118** to cause water from the inlet to be discharged through the first set of nozzles **126**.

(46) In an operation **1010**, an indication is received from a water level sensor that the relative distance between the outlet and the water level in the container corresponds to the filling distance. For example, the controller **606** may monitor the level of water in the container by measuring the delay between the transmittal and receipt of an ultrasonic signal and, based on the delay, determine that the relative distance corresponds to the filling distance. In an operation **1012**, control signals are provided to a valve to prevent further emission of water from the faucet. As such, the faucet automatically fills the container to a desired level without the user needing to attend to the amount of water dispensed.

(47) The terms “coupled,” “connected,” and the like, as used herein, mean the joining of two members directly or indirectly to one another. Such joining may be stationary (e.g., permanent) or moveable (e.g., removable or releasable). Such joining may be achieved with the two members or the two members and any additional intermediate members being integrally formed as a single unitary body with one another or with the two members or the two members and any additional intermediate members being attached to one another.

(48) References herein to the positions of elements (e.g., “top,” “bottom,” “above,” “below,” etc.) are merely used to describe the orientation of various elements in the FIGURES. It should be noted that the orientation of various elements may differ according to other exemplary embodiments, and that such variations are intended to be encompassed by the present disclosure.

(49) The construction and arrangement of the elements of the faucet as shown in the exemplary embodiments are illustrative only. Although only a few embodiments of the present disclosure have been described in detail, those skilled in the art who review this disclosure will readily appreciate that many modifications are possible (e.g., variations in sizes, dimensions, structures, shapes and proportions of the various elements, values of parameters, mounting arrangements, use of materials, colors, orientations, etc.) without materially departing from the novel teachings and advantages of the subject matter recited. For example, elements shown as integrally formed may be constructed of multiple parts or elements, the position of elements may be reversed or otherwise varied, and the nature or number of discrete elements or positions may be altered or varied.

(50) Additionally, the word “exemplary” is used to mean serving as an example, instance, or illustration. Any embodiment or design described herein as “exemplary” is not necessarily to be construed as preferred or advantageous over other embodiments or designs (and such term is not intended to connote that such embodiments are necessarily extraordinary or superlative examples). Rather, use of the word “exemplary” is intended to present concepts in a concrete manner. Accordingly, all such modifications are intended to be included within the scope of the present disclosure. Other substitutions, modifications, changes, and omissions may be made in the design, operating conditions, and arrangement of the preferred and other exemplary embodiments without departing from the scope of the appended claims.

(51) Other substitutions, modifications, changes and omissions may also be made in the design, operating conditions and arrangement of the various exemplary embodiments without departing from the scope of the present invention. For example, any element disclosed in one embodiment may be incorporated or utilized with any other embodiment disclosed herein. Also, for example, the order or sequence of any process or method steps may be varied or resequenced according to alternative embodiments. Any means-plus-function clause is intended to cover the structures described herein as performing the recited function and not only structural equivalents but also equivalent structures. Other substitutions, modifications, changes and omissions may be made in the design, operating configuration, and arrangement of the preferred and other exemplary embodiments without departing from the scope of the appended claims.

Claims

1. A fluid delivery device, comprising: an outlet having a first set of nozzles configured to discharge fluid therefrom; a sensor configured to detect a distance between the outlet and a level of fluid in a container disposed below the outlet; and a controller configured to stop the discharge of fluid from the outlet when the detected distance falls below a predetermined distance value, the controller further configured to: receive a first input to discharge fluid from the outlet until a relative distance between the level of fluid in the container and the outlet of the fluid delivery device corresponds to the predetermined distance; and provide, in response to the first input, a control signal to a valve to discharge fluid from the first set of nozzles.
2. The fluid delivery device of claim 1, further comprising a base and a spout coupled to the base, wherein the spout includes a first portion proximate to the base, and a second portion adjustable relative to the first portion, and wherein the second portion includes the outlet.
3. The fluid delivery device of claim 1, wherein the first set of nozzles is oriented either at an angle with respect to a central axis defined by the outlet or parallel to the central axis.
4. The fluid delivery device of claim 1, wherein the outlet includes a second set of nozzles oriented at the other of an angle with respect to the central axis or parallel to the central axis.
5. The fluid delivery device of claim 1, wherein the outlet includes a second set of nozzles oriented at an angle different than the first set of nozzles, and wherein the controller is further configured to: receive a second input that the container has been placed below the outlet; and provide, in response to the second input, a control signal to the valve to discharge fluid from the second set of nozzles.
6. The fluid delivery device of claim 1, wherein stopping the flow of fluid through the outlet includes closing the valve in response to the detected distance reaching the predetermined distance.
7. A fluid delivery device, comprising: an outlet, wherein the outlet includes a first set of nozzles wherein fluid discharged from the first set of nozzles converges at a focal distance from the outlet; a sensor configured to detect a distance between the outlet and a level of fluid in a container disposed below the outlet; and a controller configured to control the flow of fluid through the outlet based on a comparison between the detected distance and the focal distance.
8. The fluid delivery device of claim 7, wherein the controller is further configured to: receive a first input to discharge fluid from the outlet until a relative distance between the level of fluid in the

container and the outlet corresponds to the focal distance; and provide, in response to the first input, a control signal to a valve to discharge fluid from the first set of nozzles.

9. The fluid delivery device of claim 8, further comprising: a second set of nozzles oriented parallel to a central axis such that fluid discharged from the second set of nozzles parallel to the central axis, and wherein the controller is further configured to: receive a second input that the container has been placed below the outlet; and provide, in response to the second input, a control signal to the valve to discharge fluid from the second set of nozzles.

10. The fluid delivery device of claim 9, wherein the controller is further configured to: receive, by the sensor, an indication that the relative distance corresponds to the focal distance; and provide, in response to the indication, a control signal to the valve to prevent fluid from being discharged from the outlet.

11. The fluid delivery device of claim 7, further comprising a base and a spout coupled to the base, wherein the spout includes a first portion proximate to the base and a second portion adjustable relative to the first portion.

12. The fluid delivery device of claim 7, wherein controlling the flow of fluid through the outlet includes closing a valve in response to the distance reaching a predetermined distance threshold.

13. A method of controlling a flow of fluid from a fluid delivery device, comprising: receiving, by a controller associated with the fluid delivery device, a first input to discharge fluid from an outlet of the fluid delivery device until the fluid reaches a predetermined distance from the outlet, wherein the outlet includes a first set of nozzles; providing, by the controller in response to the first input, a control signal to a valve to discharge fluid from the first set of nozzles; receiving, by the controller, a second input; and providing, by the controller in response to the second input, a control signal to a valve to discharge fluid from a second set of nozzles of the outlet, wherein the second set of nozzles are oriented parallel to a central axis.

14. The method of claim 13, further comprising: receiving, by a sensor, an indication that a fluid level in the container is at the predetermined distance from the outlet; and providing, in response to the indication, a control signal to the valve to prevent fluid from being discharged from the outlet.

15. The method of claim 14, wherein the first input and the second input are received from a user input device.

16. The method of claim 13, wherein the fluid delivery device includes a base and a spout coupled to the base, wherein the spout includes a first portion proximate to the base and a second portion adjustable relative to the first portion, and wherein the second portion includes the outlet.
