

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12406074
Kind Code	B1
Date of Patent	September 02, 2025
Inventor(s)	Bhatt; Pankil et al.

Request-scope security tokens

Abstract

Technologies are provided for preventing unauthorized requests using request identifiers associated with security tokens. A request can be received by a computing device that contains a request identifier and one or more security tokens. The computing device can determine whether the request identifier contained in the request is associated with all of the one or more security tokens contained in the request. If the request identifier is not associated with one or more of the security tokens, then the computing device can reject the request. If the request identifier is associated with the one or more security tokens, then the computing device can generate another request that includes one or more protected data items that are associated with the one or more security tokens. The computing device can then transmit the another request containing the one or more protected data items to another computing device for processing.

Inventors: Bhatt; Pankil (Seattle, WA), Gootman; David (Vancouver, CA), Maria Susai; Jose Pragash (Bothell, WA)

Applicant: Amazon Technologies, Inc. (Seattle, WA)

Family ID: 96882218

Assignee: Amazon Technologies, Inc. (Seattle, WA)

Appl. No.: 17/214246

Filed: March 26, 2021

Publication Classification

Int. Cl.: G06F21/00 (20130101); G06F21/44 (20130101); G06F21/60 (20130101); G06F21/62 (20130101)

U.S. Cl.:

CPC **G06F21/606** (20130101); **G06F21/44** (20130101); **G06F21/6227** (20130101);
G06F2221/2141 (20130101)

Field of Classification Search

CPC: G06F (21/44); G06F (21/606); G06F (21/6227); G06F (2221/2141)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
11270021	12/2021	Dunjic	N/A	G06F 21/6236
11388006	12/2021	Wang	N/A	H04L 9/12
2012/0079288	12/2011	Hars	713/193	H04L 63/083
2012/0324099	12/2011	Perez Martinez	709/224	H04W 4/18
2015/0281241	12/2014	Sharma	726/9	H04L 9/083
2021/0286883	12/2020	Prabhu	N/A	H04L 9/008

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
WO-2017014614	12/2016	WO	H04L 63/061

Primary Examiner: Mahmoudi; Rodman Alexander

Attorney, Agent or Firm: Klarquist Sparkman, LLP

Background/Summary

BACKGROUND

(1) In some scenarios, untrusted computers are used to perform operations or make requests that involve protected or sensitive data. Since the computer is not trusted, it may be desirable to have the computer perform these tasks in a way that does not involve sharing the protected or sensitive data with the untrusted computer. One possible approach is to encrypt the protected or sensitive data and to share the encrypted version of the data with the untrusted computer. However, there is a risk that the untrusted computer may be able to decrypt the encrypted data and gain access to the protected or sensitive data. Another approach that avoids this risk is to generate tokens that are associated with the protected or sensitive data, and to share the tokens with the untrusted computer instead of the protected or sensitive data.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a system diagram depicting an example system configured for processing requests comprising request-scope security tokens.
- (2) FIG. 2 is a flowchart of an example method for processing a request comprising a request-scope security token.
- (3) FIG. 3 is a diagram depicting an example computing device configured to process requests

comprising request-scope security tokens.

(4) FIG. 4 is flowchart of a method for processing a request comprising a request identifier and a security token.

(5) FIG. 5 is a diagram depicting an example request comprising a request identifier and a plurality of security tokens.

(6) FIG. 6 is a diagram depicting an example security token store and an example modified request.

(7) FIG. 7 is a diagram depicting an example transmission comprising a request identifier and a plurality of security tokens.

(8) FIG. 8 is an example system diagram depicting a plurality of virtual machine instances running in a multi-tenant environment comprising a server computer configured to process requests comprising request-scope security tokens.

(9) FIG. 9 is a diagram depicting a generalized example of a suitable computing environment in which the described innovations may be implemented.

DETAILED DESCRIPTION

(10) The following description is directed to technologies for processing requests comprising security tokens that are associated with protected data items.

(11) In at least some scenarios, security tokens can be provided to untrusted computers for processing instead of protected and/or sensitive data. For example, in a scenario where an untrusted computing device is configured to generate a request for processing by another computing device using protected data, a security token associated with the protected data can be provided to the untrusted computing device instead of the protected data. The untrusted computing device can then generate a request using the security token. The request can then be transmitted to a trusted intermediary computing device that can generate another request comprising the protected and/or sensitive data associated with the security token and transmit the another request to the another computing device for processing.

(12) However, in at least some cases, there may still be a risk that the untrusted computing device can commit malicious acts when it is provided with a security token instead of protected data. For example, the untrusted computing device may be able to submit unauthorized requests using the security token. Even when the untrusted computing device does not know the protected data associated with the security token, it may still be able to cause multiple operations to be performed using the protected data by submitting multiple requests with the security token. In another example, a malicious user may gain control of the untrusted computing device and may be able to substitute a security token associated with the malicious user's information (such as the malicious user's bank account information) for a security token that is supposed to be part of a request. The intermediary computing device that receives the manipulated request might then unwittingly process the request by generating a request comprising the malicious user's information instead of the information associated with the correct security token. In another example, if the same security tokens are associated with protected data items across multiple requests and are provided to the untrusted computing device, a malicious user that has gained control of the untrusted computing device may be able to reverse engineer the protected data items by making repeated requests with various values that cause security tokens to be sent to the untrusted computing device. By observing the generated security tokens, the malicious user can build a list of submitted values and their associated security tokens.

(13) At least some of the embodiments described herein can solve these problems by associating request identifiers with security tokens, and determining whether a request identifier contained in a received request is associated with every security token contained in the request. A request identifier and one or more security tokens can be provided to an untrusted computing device. The untrusted computing device can generate a request for processing using protected data that includes the one or more security tokens instead of the protected data. The request can also be required to include the provided request identifier. The request can be transmitted by the untrusted computing

device to a trusted intermediary computing device that has access to the protected data. The trusted computing device can verify that the request identifier in the request is associated with the one or more security tokens in the request. If the request identifier is not associated with each of the one or more security tokens, then the intermediary computing device can reject the request.

(14) In a different or further embodiment, a request identifier and one or more security tokens can be generated for each request. For example, a trusted computing device can receive a request for processing using one or more protected data items by another computing device. The trusted computing device can generate a request identifier and one or more security tokens that are associated with the one or more protected data items. The trusted computing device can transmit the request identifier and the one or more security tokens to an untrusted computing device in order to cause the untrusted computing device to generate a request for processing by the another computing device, wherein the generated request includes the request identifier and the one or more security tokens. The trusted computing device can receive the request from the untrusted computing device and verify that the request identifier included in the request is associated with the one or more security tokens in the request. If the request identifier is associated with the one or more security tokens, the trusted computing device can generate another request that includes the one or more protected data items associated with the one or more security tokens. The trusted computing device can then transmit the another request to the another other computing device for processing using the one or more protected data items. If the request identifier is not associated with the one or more security tokens, then the trusted computing device can reject the request. Thus, in at least some scenarios, the trusted computing device can ensure that the security tokens are only usable as part of a request that includes the associated request identifier, and that the security tokens cannot be used in any other requests.

(15) In at least some embodiments, generating the another request can comprise generating a modified version of the request received from the untrusted computing device. For example, the trusted computing device can create a version of the request received from the untrusted computing device in which the one or more security tokens are replaced with the one or more protected data items associated with the one or more security tokens.

(16) In a different or further embodiment, the request identifier and/or one or more security tokens can be deleted or marked as unusable after the trusted computing device transmits the another request comprising the one or more protected data items. For example, the request identifier, one or more security tokens, and one or more protected data items can be stored in a security record associated with the request identifier. After transmitting the another request comprising the one or more protected data items, the trusted computing device can delete the security record. In at least some embodiments, deleting the request identifier and/or one or more security tokens can help ensure that the request identifier and/or one or more security tokens are not used in any other requests.

(17) Additionally or alternatively, identifiers that limit the use of security tokens may be associated with other operational scopes besides requests. For example, security tokens can be associated with transaction identifiers. A transaction identifier may be associated with a transaction that comprises multiple requests. In such an embodiment, the associated security tokens may be usable in a plurality of authorized requests that are associated with a given transaction scope.

(18) FIG. 1 is a system diagram depicting an example system **100** configured for processing requests (e.g., **143**) comprising request identifiers (e.g., **111**) and one or more security tokens (e.g., **113**). The example system **100** comprises a server computer **110** that comprises one or more security tokens **113** that are associated with one or more protected data items **115**. For example, security token **113a** can be associated with protected data item **115a**, security token **113n** can be associated with protected data item **115n**, etc. The server computer **110** further comprises the request identifier **111** that is associated with the one or more security tokens **113**. Although it is not depicted, it is possible for the server computer **110** to comprise multiple request identifiers that are

associated with different security tokens. For example, the server computer **110** can comprise the request identifier **111** associated with the one or more security tokens **113** (which are in turn associated with the protected data items **115**), and one or more other request identifiers (not shown) that are associated with one or more other security tokens (not shown).

(19) The server computer **110** is configured to transmit a transmission **141** comprising the request identifier **111** and the one or more security tokens **113** to another server computer **120**. Although the request identifier **111** and the one or more security tokens **113** are depicted in IFG. **1** as being part of the same transmission **141**, in at least some embodiments the request identifier **111** and the one or more security tokens **113** are transmitted in multiple transmissions. The size and number of transmissions can be based on a transmission protocol (such as TCP/IP, UDP, HTTP, etc.) that is used by the server computer **110** to communicate with the server computer **120**. The server computer **110** can transmit the request identifier **111** and one or more security tokens **113** via one or more wired and/or wireless communication channels. In at least some embodiments, the request identifier **111** and the one or more security tokens **113** can be transmitted via a computer network to which the server computer **110** and the server computer **120** are connected.

(20) The server computer **120** is configured to receive the request identifier **111** and the one or more security tokens **113** from the server computer **110** and to generate a data payload **151** comprising the one or more security tokens **113**. The payload **151** can comprise one or more data structures that include the one or more security tokens **113**. In at least some embodiments, the data payload **151** can comprise a partial (e.g., incomplete) request to be transmitted to another server computer **130** for processing. In such an embodiment, the one or more security tokens **113** can be included in locations within the data payload **151** that should contain the one or more protected data items **115** when the request is transmitted to the other server computer **130**. Additionally or alternatively, the data payload **151** can comprise instructions that, when processed by the server computer **110**, cause the server computer **110** to generate a modified data payload **153**. The server computer **120** is further configured to transmit a request **143** comprising the request identifier **111** and the data payload **151** to the server computer **110**.

(21) The server computer **110** is configured to receive the request **143** from the server computer **120**. The server computer **110** is further configured to determine whether the request identifier **111** contained in the request **143** is associated with the one or more security tokens **113** contained in the data payload **151**. The server computer **110** can be configured to store request identifiers (e.g., **111**) in association with one or more security tokens (e.g., **113**) in one or more memories and/or one or more storage media (not shown). Upon receipt of the request **143**, the server computer **110** can inspect the request **143** to identify the request identifier **111** contained within the request **143**. The server computer **110** can search the one or more memories and/or one or more storage media for a request identifier that matches the request identifier **111**. If the request identifier **111** is found, the server computer **110** can identify any security tokens that are associated with the request identifier **111**. If the one or more security tokens associated with the request identifier **111** match the one or more security tokens **113** contained in the data payload **151**, then the server computer **110** can determine that the request identifier **111** contained in the request **143** is in fact associated with the one or more security tokens **113** contained within the data payload **151**.

(22) Based on the determination that the request identifier **111** is associated with the one or more security tokens **113**, the server computer **110** can generate a modified version of the data payload **153** that comprises the one or more protected data items **115** that are associated with the one or more security tokens **113**. In at least some embodiments, generating the modified version of the data payload **153** can comprise replacing the one or more security tokens **113** in the data payload **151** with the one or more protected data items **115** that are associated with the one or more security tokens **113**. For example, the server computer **110** can create the modified version of the data payload **153** by copying the data payload **151** and replacing the one or more security tokens **113** in the copy with the one or more protected data items **115** that are associated with the security tokens

113. The server computer **110** can then transmit a request **145** comprising the modified version of the data payload **153** to the other server computer **130** for processing.

(23) In at least some embodiments, generating the modified version of the payload **153** can comprise processing one or more instructions contained within the data payload **151**. For example, the data payload **151** can comprise a partial request to be transmitted to the other server computer **130**, along with instructions for completing the request using the one or more protected data items **115** that are associated with the one or more security tokens **113**. In such an embodiment, the completed request can be the request **145** that is transmitted to the other server computer **130**.

(24) The server computer **110** can be configured to reject a request where the request identifier is not associated with one or more security tokens contained in a data payload of the request. For example, after receiving the request **143**, the server computer **110** may receive another request (not shown), wherein the another request comprises another request identifier and another data payload comprising the one or more security tokens **113**. The server computer **110** can determine that the another request identifier is not associated with the one or more security tokens **113** and can reject the request. The request identifier (e.g., **111**) can be an identifier that is only good for use with a single request (e.g., **143**), and the one or more security tokens **113** can be associated with the request identifier **111** in order to ensure that they are only used as part of a request (e.g., **143**) containing the request identifier **111**.

(25) For example, the request **143** can be an idempotent request that, if processed more than once by the server computer **110**, would result in a regeneration of the request **145** and not a new request. Thus, in at least some scenarios, repeated transmissions of the request **143** by the server computer **120** would not result in the generation of multiple, different modified requests. Furthermore, since the security tokens **113** are associated with the request identifier **111**, the server computer **120** (or another server computer) is unable to issue a new request with a different request identifier that includes the one or more security tokens **113** since the server computer **110** would reject such a request as unauthorized.

(26) In another example, the request identifier **111** and/or the security tokens **113** can be deleted after the server computer **110** generates the request **145** and/or transmits the request **145** to the other computing device **130**. In at least some scenarios, deleting the request identifier **111** and/or the security tokens **113** can cause the server computer **110** to reject any other requests that contain the request identifier **111** and/or security tokens **113** since they will no longer be accessible by the server computer **110**.

(27) Optionally, the server computer **120** can comprise a service **123** that is configured to generate the data payload **151**. For example, the service **123** can be configured to generate data payloads that can be processed by the other server computer **130**, after protected data items associated with the security tokens in the data payloads have been added to the data payloads by the server computer **110**. In such an embodiment, the server computer **110** can be configured to reject any request comprising the request identifier **111** that is not received from the service **123**. For example, the server computer **110** can associate the request identifier **111** with the service **123**. After receiving the request **143**, the server computer **110** can determine that the request **143** is associated with the service **123**. For example, the server computer **110** can identify the request identifier **111** in the request **143**, determine that the request identifier **111** is associated with the service **123**, and determine that the request **143** and/or the data payload **151** was generated by the service **123**. For example, the server computer **110** can determine that the request **143** was received via a communication channel associated with the service **123**. Additionally or alternatively, the service **123** can be configured to digitally sign the request **143** and/or the data payload **151**, and the server computer **110** can be configured to verify the authenticity of the digital signature. Other techniques for determining that the request **143** is associated with, or received from, the service **123** are also possible. The server computer **110** can be configured to receive another request (not shown) comprising the request identifier **111**. The server computer **110** can determine that the another

request is not associated with the service **123**, and can reject the another request.

(28) The server computer **110** can be configured to generate the modified version of the data payload **153** based on the determination that the request identifier is associated with the service **123** and that the request identifier **111** is associated with the one or more security tokens **113**. The server computer **110** can be configured to reject a request if it determines that the request contains a request identifier associated with a service that is not associated with the request. For example, the server computer **110** can receive another request (not shown) that comprises the request identifier **111**. If the server computer **110** determines that the another request is not associated with the service **123**, then the server computer **110** can reject the another request. In at least some scenarios, this can allow the server computer **110** to ensure that, if a request identifier (e.g., **111**) and one or more security tokens (e.g., **113**) are transmitted to a computing device (e.g., server computer **120**) and/or service (e.g., **123**), only that computing device and/or service can transmit a request (e.g., **143**) that includes the request identifier and the one or more associated security tokens.

(29) In at least some embodiments, the service **123** can comprise a program that is developed by a third party and is hosted in a server environment with the server computer **110**. In such an embodiment, the server computer **110** can act as an intermediary device that allows the service **123** to trigger authorized requests to the server computer **130** without giving the service **123** access to any protected data items (e.g., **115**).

(30) In a different or further embodiment, one or more of the security tokens **113** can be associated with data item types of protected data items. Example data item types include field names associated with protected data items. The server computer **110** can be configured to transmit the request identifier **111**, the one or more security tokens **113**, and any data item type(s) of the one or more protected data items **115** associated with the one or more security tokens **113**. For example, the transmission **141** can indicate that the security token **113a** is associated with a data item type of the protected data item **115a**, that the security token **113n** is associated with a data item type of the protected data item **115n**, etc. In a particular example, the transmission **141** can indicate that the security token **113a** is associated with a user name (for which the protected data item **115a** holds a value) and that the security token **113n** is associated with a credit card number (for which the protected data item **115n** holds a value).

(31) The data item type(s) associated with the one or more security tokens **113** can be used by the server computer **120** and/or the service **123** to generate the data payload **151**. For example, the one or more security tokens **113** can be organized in the data payload **151** based on the associated data item types in order to ensure that, when the one or more protected data items **115** are added to the modified version of the payload **153** by the server computer **110**, the modified version of the data payload **153** is in a format that can be processed by the other server computer **130**. For example, in a scenario where the server computer **110** replaces the one or more security tokens **113** with one or more associated protected data items **115**, the security tokens **113** can be located in the positions in the data payload **151** that are associated with the data item types of the associated protected data items **115**. In such an embodiment, when the server computer **110** replaces the one or more security tokens **113** with the one or more protected data items **115**, the one or more protected data items **115** will be located in positions in the modified version of the data payload **153** that are associated with their respective data item types.

(32) Optionally, the server computer **110** can be configured to receive a request for processing **161**. The request **161** can be a request for processing by the other server computer **130** using the one or more protected data items **115**. In at least some embodiments, the request **161** can be received from a client computing device (not shown) that is associated with the one or more protected data items **115**. For example, the request **161** can be received from a computing device associated with an authenticated user session and the one or more protected data items **115** can be associated with the same authenticated user session.

(33) Responsive to receiving the request **161**, the server computer **110** can generate the request

identifier **111** and the one or more security tokens **113**, associate the one or more security tokens **113** with the request identifier **111**, and transmit the request identifier **111** and the one or more security tokens **113** to the server computer **120**. The server computer **110** can also be configured to associate the one or more security tokens **113** with the one or more protected data items **115**. After receiving the request **143** from the server computer **120**, the server computer **110** can generate the modified version of the data payload **153** and transmit the request **145** to the other server computer **130** for processing. In at least some embodiments, the server computer **110** can receive a response (not shown) from the server computer **130** and can transmit a response (not shown) to the request **161** base on the response received from the server computer **130**.

(34) In any of the embodiments described herein, a computer network can comprise a plurality of network devices configured to transmit network packets to one another. Network devices in a network can be connected by wired connections, wireless connections, or some combination thereof. Example types of computer networks include local area networks (such as a network local to a data center), remote networks (such as networks located external to a data center containing a server computer or other computing device which communicates with the network), virtual cloud networks (such as networks comprising servers and or virtual machines operating in a cloud computing environment), remote embedded networks (such as remote networks which are hosted by third parties), satellite networks, etc.

(35) In any of the embodiments described herein, a service can comprise one or more processes executing on one or more computing devices. In at least some embodiments, a service can be provided by a third party for the purposes of generating requests in a format that can be processed by another computing device. The service can be configured to receive a request identifier and one or more security tokens and to generate a request comprising the request identifier and the one or more security tokens that is in a format (or that contains a data payload that is in a format) that can be processed by the another computing device. In at least some embodiments, the service and the another computing device can be controlled by a same third party. Additionally or alternatively, the service and a computing device that transmits the request identifier and one or more security tokens to the service can be part of a same computer environment (such as a computer network, data center, subdomain, etc.)

(36) In any of the embodiments described herein, a security token can comprise an alphabetic, numeric, or alphanumeric value that is associated with a protected data item. Example security tokens include randomly generated number, globally unique identifiers (GUIDs), universally unique identifiers (UUIDs), or the like. In at least some scenarios, a security token can be generated using a cryptographic random number generator. A security token can be generated and associated with a protected data item. The security token can then be provided to untrusted computing devices instead of the protected data item. The security token can be associated with a request identifier. In at least some embodiments, a security token is only usable as part of a request that contains the associated request identifier.

(37) In any of the embodiments described herein, a protected data item can be a datum that cannot or should not be shared with an untrusted computing device. What sort of data qualify as protected data items can be context-specific and may be based on legal requirements, governing privacy regulations, and/or user preferences. Examples of data that may qualify as protected data items include account user names, passwords, email addresses, account billing information, credit card information, bank account information, medical history, etc.

(38) FIG. 2 is a flowchart of an example method **200** for processing a request comprising a request identifier and a security token. Any of the example systems described herein can be used to perform all or part of the example method **200**.

(39) For example, the example computing device **310** depicted in FIG. 3 can be used to perform all or part of the example method **200**. FIG. 3 is a diagram depicting the example computing device **310**. The computing device **310** comprises a processing unit **311** and a memory **313** storing

instructions that, when executed by the processing unit **311**, cause the computing device to perform operations related to requests comprising request identifiers and security tokens.

(40) Referring to FIG. 2, at **210** a first request is received from a first computing device, wherein the first request comprises a request identifier and a security token. For example, the computing device **310** can receive a request **341** comprising a request identifier **321** and one or more security tokens **333**. The request **341** can be received from a source computing device (not shown), via one or more wired and/or wireless communication channels. For example, the request **341** can be received via a computer network to which the computing device **310** and the source computing device are connected. In at least some embodiments, the request **341** can be a request for one or more operations to be performed by a destination computing device (not shown) using one or more protected data items **335** that are associated with the one or more security tokens **333**.

(41) At **220**, it is determined that the security token is associated with the request identifier. For example, the computing device **310** can determine that the one or more security tokens **333** is/are associated with the request identifier **321**. In at least some embodiments, the computing device **310** can retrieve a security record associated with the request identifier **321** and determine using the security record that the request identifier **321** is associated with the one or more security tokens **333**. For example, the computing device **310** can comprise a security record **350** comprising the request identifier **321** and the one or more security tokens **333**. By verifying that the security record **350** for the request identifier **321** contains the one or more security tokens **333** included in the request **341**, the computing device **310** can determine that the request identifier **321** is associated with the one or more security tokens **333**. Optionally, such a security record may also contain the one or more protected data items **335** associated with the one or more security tokens **333**. In at least some embodiments, the security record **350** can be stored in the memory **313** of the computing device **310**. Additionally or alternatively, all or part of the security record **350** can be stored in another storage medium (not shown) of the computing device **310** and/or one or more other computing devices (not shown). For example, the computing device **310** can retrieve the security record from a remote storage device (not shown) that is connected to the computing device **310** via one or more wired and/or wireless communication channels.

(42) At **230**, based on the determining, a second request is generated, wherein the second request comprises a protected data item associated with the security token. For example, based on the determining that the request identifier **321** is associated with the one or more security tokens **333**, the computing device **310** can generate a request **345** that comprises one or more protected data items **335** associated with the one or more security tokens **333**. In at least some embodiments, generating the request **345** can comprise replacing the one or more security tokens **333** in the request **341** with the one or more protected data items **335** associated with the one or more security tokens **333**. For example, the computing device **310** can copy the request **341** and, for each of the one or more security tokens **333**, the computing device **310** can look up one of the one or more protected data items **335** that is associated with the security token and replace the security token with the associated protected data item. Additionally or alternatively, the computing device **310** can be configured to generate a modified version of a data payload that contains the one or more security tokens **333** in the request **341**, wherein the modified version of the data payload contains the one or more protected data items **335** associated with the one or more security tokens **333** instead of the one or more security tokens **333**. Additionally or alternatively, the computing device **310** can be configured to generate the request **345** by using the one or more protected data items **335** to complete a partial data payload that is contained within the request **341**. In at least some such embodiments, the request **341** can comprise instructions for modifying the partial data payload using the one or more protected data items **335** that are associated with the one or more security tokens **333** contained in the request **341**. Optionally, the request **345** can include the request identifier **321**.

(43) At **240**, the second request is transmitted to a second computing device. For example, the

computing device **310** can transmit the request **345** to a destination computing device (not shown). The computing device **310** can transmit the request **345** via one or more wired and/or wireless communication channels. For example, the computing device **310** can transmit the request **345** via a computer network to which the computing device **310** and the destination computing device are connected.

(44) The example method **200** can further comprise generating the security token, associating the security token with the protected data item, generating the request identifier, associating the request identifier with the security token, and/or transmitting the security token and the request identifier to the first computing device. For example, the computing device and **310** can generate the one or more security tokens **333** and associate the one or more security tokens **333** with the one or more protected data items **335**. Associating the one or more security tokens **333** with the one or more protected data items **335** can comprise generating the security record **350** and storing the one or more security tokens **333** in association with the one or more protected data items **335** in the security record **350**. The computing device **310** can generate the request identifier **321** and associate the one or more security tokens **333** with the request identifier **321**. Associating the one or more security tokens **333** with the request identifier **321** can comprise using the security record **350**. For example, the computing device **310** can store the request identifier **321** in the security record **350** with the one or more security tokens **333**. Additionally or alternatively, the computing device **310** can store the security record **350** as part of an index or table for which the request identifier **321** is used as a key to look up the security record **350**.

(45) The computing device **310** can transmit the request identifier **321** and the one or more security tokens **333** to the source computing device (not shown). In at least some embodiments, the computing device **310** can transmit the request identifier **321** and the one or more security tokens **333** to the source computing device in order to cause the source computing device to generate the request **341** and to transmit the request **341** to the computing device **310**. For example, the request **341** can be generated by the source computing device in a format that can be processed by the destination computing device after the computing device **310** has added the one or more protected data items **335** associated with the one or more security tokens **333**.

(46) In at least some embodiments, transmitting the security token and the request identifier to the first computing device comprises transmitting a message in which the security token is associated with a data item type of the protected data item. For example, the computing device **310** can transmit a message (not shown) in which the one or more security tokens **333** are associated with data item types of the one or more protected data items **335**. For example, the message can associate the security token **333a** with a data item type of the protected data item **335a**, associate the security token **333n** with the protected data item **335n**, etc.

(47) The example method **200** can further comprise receiving another request from the first computing device or another computing device, wherein the another request comprises the security token and another request identifier; determining that the security token is not associated with the another request identifier; and rejecting the another request. For example, the computing device **310** can receive another request (not shown) from the source computing device, wherein the another request comprises the one or more security tokens **333** and another request identifier. The computing device **310** can determine that the another request identifier is not associated with the one or more security tokens **333**. For example, the computing device **310** can retrieve another security record associated with the another request identifier and determine, based on the another security record that the another request identifier is not associated with the one or more security tokens **333** contained in the another request. After determining that the another request identifier is not associated with that the one or more security tokens **333**, the computing device **310** can reject the another request. In this way, the computing device **310** can be used to ensure that a request will only be processed if it contains a valid request identifier and security tokens that are associated with that valid request identifier.

(48) In at least some embodiments, the example method **200** further comprises assigning the request identifier to a service. In such an embodiment, the example method **200** can comprise determining that the request received from the first computing device is associated with the service, and generating the modified version of the request based on the determining that the request identifier is associated with the security token and the determining that the request is associated with the service. For example, the example computing device **310** can transmit the request identifier **321** and the one or more security tokens **333** to a service running on the source computing device. The computing device **310** can assign the request identifier **321** to the service (not shown). For example, the computing device **310** can store an identifier associated with the service in the security record **350** in association with the request identifier **321**. After receiving the request **341** from the source computing device, the computing device **310** can determine that the request **341** is associated with the service. For example, the computing device **310** can determine that the request **341** is received via a communication channel associated with the service. Additionally or alternatively, the computing device **310** can determine that the requested **341** is signed with a digital signature using a digital certificate associated with the service. Other techniques for ascertaining the association between the service and the request **341** can also be used. The computing device **310** can generate the request **345** based on the determining that the request identifier **321** is associated with the one or more security tokens **333** and the determining that the request **341** is associated with the service.

(49) In a different or further embodiment, the request identifier and/or the security token can be deleted or marked as unusable after the second request is generated or after the second request is transmitted to the second computing device. For example, the computing device **310** can be configured to delete the security record **350** after generating the request **345** or transmitting the request **345** to the destination computing device. In such an embodiment, a subsequent request containing the request identifier **321** and/or the one or more security tokens **333** can be rejected since the security record **350** associating the request identifier **321** with the one or more security tokens **333** no longer exists.

(50) FIG. **4** is a flowchart of an example method **400** for processing a request comprising a request identifier and a security token. Any of the example systems described herein can be used to perform all or part of the example method **400**. For example, the example computing device **310** can be used to perform all or part of the example method **400**.

(51) At **410**, a first request is received from a first computing device, wherein the first request comprises a request identifier and a security token. For example, the computing device **310** can receive the request **341** comprising the request identifier **321** and the one or more security tokens **333**. Additionally or alternatively, the computing device **310** can receive another request (not shown) comprising another request identifier and the one or more security tokens **333** and/or one or more other security tokens.

(52) At **420**, it is determined whether the received request is valid. Determining whether the received request is valid can comprise determining whether the request identifier in the request is associated with the security token in the request. For example, the computing device **310** can determine whether the request identifier **321** is associated with the one or more security tokens **333** in the request **341**. If the request identifier **321** is associated with the one or more security tokens **333**, then the computing device **310** can determine that the requested **341** is valid. However, if the computing device **310** determines that the request identifier **321** is not associated with one or more of the one or more security tokens **333**, then the computing device **310** can determine that the request **341** is not valid.

(53) Additionally or alternatively, determining whether the received request is valid can comprise determining whether the request was received from a computing device and/or service associated with the request identifier. For example, the computing device **310** can determine whether the request **341** was received from a computing device and/or service associated with the request

identifier **321**. In an embodiment where the computing device **310** transmits the request identifier **321** and the one or more security tokens **333** to a source computing device or a service running on the source computing device, the computing device **310** can determine whether the request **341** is received from the source computing device or service running on the source computing device. If the computing device **310** determines that the request **341** is received from a computing device and/or service associated with the request identifier **321**, then the computing device can determine that the request is valid. However, if the computing device **310** determines that the request **341** is not received from a computing device and/or service associated with the request identifier **321**, then the computing device **310** can determine that the request is invalid.

(54) If it is determined at **420** that the request is valid, then at **430** a second request that comprises a protected data item associated with the security token is generated, as described herein, and, at **440**, the second of the request is transmitted to a second computing device.

(55) However, if it is determined at **420** that the request is invalid then, at **450**, the request is rejected. Rejecting the request can comprise transmitting a response indicating that the request is invalid. For example, the computing device **310** can transmit a response (not shown) indicating that the request **341** or another request is invalid.

(56) FIG. 5 is a diagram depicting an example request **500** comprising a request identifier **501** and a plurality of security tokens **533**, **543**, **553**, **563**, and **573**. The example request **500** can be received and processed by a computing device in any of the systems described herein. For example, the request **500** can be received and processed by the server computer **110** from the server computer **120** in the example system **100** depicted in FIG. 1. For example, the request **500** can be received and processed by the computing device **310** depicted in FIG. 3. In some embodiments, all or part of the contents of the example request **500** depicted in FIG. 5 can be part of a data payload included in the request.

(57) The example request **500** is formatted using a JavaScript Object Notation (JSON). However, this is not intended to be limiting. Other formats for requests comprising request identifiers and one or more security tokens are possible.

(58) In addition to the request identifier **501** and the plurality of security tokens **533**, **543**, **553**, **563**, and **573**, the example request **500** comprises a partial request **502** to be processed by another computing device (such as the server computer **130** depicted in FIG. 1). In the example depicted in FIG. 5, the partial request **502** comprises a partial HTTP request. However, other types of requests are possible. The partial request **502** comprises a field **503** that indicates that the request should be an HTTP GET request. The partial request **502** further comprises a field **505** that indicates a path for the request. The partial request **502** further comprises a field **507** that defines headers **509** and **511** to be included in the request. The partial request **502** further comprises a field **513** that defines a partial body for the request.

(59) The example request **500** further comprises a collection **520** of privileged operations **521-529**. The privileged operations **521-529** can be processed by a computing device to modify the contents of the partial request **502** by replacing a security token with a protected data item associated with the security token. For example, each of the privileged operations **521-529** contains a security token and a path within the partial request **500** to where a protected data item associated with the security token should be placed.

(60) The privileged operation **521** contains the security token **533** and a path **531**, indicating that a protected data item associated with the security token **533** should be placed in an “amount” field of the partial request body **513**. The privileged operation **523** contains the security token **543** and a path **541**, indicating that a protected data item associated with the security token **543** should be placed in a “cardInfo.cardNumber” field of the partial request body **513**. The privileged operation **525** contains the security token **553** and a path **551**, indicating that a protected data item associated with the security token **553** should be placed in a “cardInfo.expiryDate” field of the partial request body **513**. The privileged operation **527** contains the security token **563** and a path **561**, indicating

that a protected data item associated with the security token **563** should be placed in a “billingActor.name” field of the partial request body **513**. The privileged operation **529** contains the security token **573** and a path **571**, indicating that a protected data item associated with the security token **573** should be placed in a “billingActor.address” field of the partial request body **513**.

(61) FIG. **6** is a diagram depicting an example security token store **601** and an example request **605** that is based on a security record **607** contained in the security token store **601** and the request **500** depicted in FIG. **5**.

(62) The security token store **601** can comprise one or more security records (e.g., **607**) that associate request identifiers (e.g., **501**) with one or more security tokens (e.g., **533**, **543**, **553**, **563**, and **573**). A computing device that receives the request **500** can use the request identifier **501** to locate the security record **607** in the security token store **601**. The computing device can then verify that the request **500** is authorized by determining that the security record **607** associates the request identifier **501** contained in the request **500** with the plurality of security tokens **533**, **543**, **553**, **563**, and **573** contained in the request **500**. Optionally, the security record **607** can include a service identifier **603** of a service associated with the request identifier **501**. In such an embodiment, verifying that the request **500** is authorized can comprise determining that the request **500** is associated with the service identified by the service identifier **603**.

(63) The security record **607** comprises a token map, in which the security tokens **533**, **543**, **553**, **563**, and **573** that are associated with the request identifier **501** are mapped to associated protected data items **621-629**. For example, the security token **543** is associated with the protected data item **621**, the security token **553** is associated with the protected data item **623**, the security token **563** is associated with the protected data item **625**, the security token **573** is associated with the protected data item **627**, and the security token **533** is associated with the protected data item **629**.

(64) A computing device that receives the request **500** can use the partial request **502** and the privileged operations **521-529** included in the request **500**, along with the security record **607**, to generate the example request **605**. For example the request **605** includes the values of the command field **503**, the path field **505**, and the headers **509** and **511** specified in the partial request **502**. The request **605** further comprises a completed version **613** of the partial request body **513**, in which the protected data items **621-629** that are associated with the security tokens **533**, **543**, **553**, **563**, and **573** have been placed in the partial body **513** based on the privileged operations **521-529**. The security token was **533**, **543**, **553**, **563**, and **573** (and their associated privileged operations) have been replaced in the request **605** with their respective protected data items, and thus are no longer present in the request.

(65) FIG. **7** is a diagram depicting an example transmission **700** comprising the request identifier **501** and the plurality of security tokens **533**, **543**, **553**, **563**, and **573**. In any of the example systems described herein, the example transmission **700** can be transmitted to a computing device (or service running on a computing device) in order to cause the computing device (or service running on the computing device) to generate a request comprising the request identifier **501** and the plurality of security tokens **533**, **543**, **553**, **563**, and **573**. For example, the server computer **110** depicted in FIG. **1** can transmit the transmission **700** to the server computer **120** in order to cause the server computer **122** generate the example request **500**. For example, the computing device **310** depicted in FIG. **3** can transmit the term and submission **700** to a source computing device in order to cause the source computing device to generate the example request **500**.

(66) The transmission **700** comprises data item types **701-709** of the protected data items **621-629** that are associated with the security tokens **533**, **543**, **553**, **563**, and **573**. A computing device that receives the transmission **700** can use the data item types **701-709** when generating the request **500**. For instance, in the example depicted in FIG. **5**, the paths **531**, **541**, **551**, **561**, and **571** in the privileged operations **521-529** can be based on the data item types **701-709** that are associated with the security tokens **533**, **543**, **553**, **563**, and **573**.

(67) FIG. **8** is a computing system diagram of a network-based compute service provider **800** that

illustrates one environment in which embodiments described herein can be used. By way of background, the compute service provider **800** (i.e., the cloud provider) is capable of delivery of computing and storage capacity as a service to a community of end recipients. In an example embodiment, the compute service provider can be established for an organization by or on behalf of the organization. That is, the compute service provider **800** may offer a “private cloud environment.” In another embodiment, the compute service provider **800** supports a multi-tenant environment, wherein a plurality of customers operate independently (i.e., a public cloud environment). Generally speaking, the compute service provider **800** can provide the following models: Infrastructure as a Service (“IaaS”), Platform as a Service (“PaaS”), and/or Software as a Service (“SaaS”). Other models can be provided. For the IaaS model, the compute service provider **800** can offer computers as physical or virtual machines and other resources. The virtual machines can be run as guests by a hypervisor, as described further below. The PaaS model delivers a computing platform that can include an operating system, programming language execution environment, database, and web server. Application developers can develop and run their software solutions on the compute service provider platform without the cost of buying and managing the underlying hardware and software. The SaaS model allows installation and operation of application software in the compute service provider. In some embodiments, end users access the compute service provider **800** using networked client devices, such as desktop computers, laptops, tablets, smartphones, etc. running web browsers or other lightweight client applications. Those skilled in the art will recognize that the compute service provider **800** can be described as a “cloud” environment.

(68) The particular illustrated compute service provider **800** includes a plurality of server computers **802A-802D**. While only four server computers are shown, any number can be used, and large centers can include thousands of server computers. The server computers **802A-802D** can provide computing resources for executing software instances **806A-806D**. In one embodiment, the instances **806A-806D** are virtual machines. As known in the art, a virtual machine is an instance of a software implementation of a machine (i.e. a computer) that executes applications like a physical machine. In the example, each of the servers **802A-802D** can be configured to execute a hypervisor **808** or another type of program configured to enable the execution of multiple instances **806** on a single server. For example, each of the servers **802A-802D** can be configured (e.g., via the hypervisor **808**) to support one or more virtual machine slots, with each virtual machine slot capable of running a virtual machine instance (e.g., server computer **802A** could be configured to support three virtual machine slots each running a corresponding virtual machine instance). Additionally, each of the instances **806** can be configured to execute one or more applications.

(69) It should be appreciated that although the embodiments disclosed herein are described primarily in the context of virtual machines, other types of instances can be utilized with the concepts and technologies disclosed herein. For instance, the technologies disclosed herein can be utilized with storage resources, data communications resources, and with other types of computing resources. The embodiments disclosed herein might also execute all or a portion of an application directly on a computer system without utilizing virtual machine instances.

(70) One or more server computers **804** can be reserved for executing software components for managing the operation of the server computers **802** and the instances **806**. For example, the server computer **804** can execute a management component **810**. A customer can access the management component **810** to configure various aspects of the operation of the instances **806** purchased by the customer. For example, the customer can purchase, rent or lease instances and make changes to the configuration of the instances. The customer can also specify settings regarding how the purchased instances are to be scaled in response to demand. The management component can further include a policy document to implement customer policies. An auto scaling component **812** can scale the instances **806** based upon rules defined by the customer. In one embodiment, the auto scaling component **812** allows a customer to specify scale-up rules for use in determining when new

instances should be instantiated and scale-down rules for use in determining when existing instances should be terminated. The auto scaling component **812** can consist of a number of subcomponents executing on different server computers **802** or other computing devices. The auto scaling component **812** can monitor available computing resources over an internal management network and modify resources available based on need.

(71) A deployment component **814** can be used to assist customers in the deployment of new instances **806** of computing resources. The deployment component can have access to account information associated with the instances, such as who is the owner of the account, credit card information, country of the owner, etc. The deployment component **814** can receive a configuration from a customer that includes data describing how new instances **806** should be configured. For example, the configuration can specify one or more applications to be installed in new instances **806**, provide scripts and/or other types of code to be executed for configuring new instances **806**, provide cache logic specifying how an application cache should be prepared, and other types of information. The deployment component **814** can utilize the customer-provided configuration and cache logic to configure, prime, and launch new instances **806**. The configuration, cache logic, and other information may be specified by a customer using the management component **810** or by providing this information directly to the deployment component **814**. The instance manager can be considered part of the deployment component.

(72) Customer account information **815** can include any desired information associated with a customer of the multi-tenant environment. For example, the customer account information can include a unique identifier for a customer, a customer address, billing information, licensing information, customization parameters for launching instances, scheduling information, auto-scaling parameters, previous IP addresses used to access the account, etc.

(73) A network **830** can be utilized to interconnect the server computers **802A-802D** and the server computer **804**. The network **830** can comprise Clos networks or other types of multi-tiered network fabrics. The network **830** can be a local area network (LAN) and can be connected to a Wide Area Network (WAN) **840** so that end users can access the compute service provider **800**. It should be appreciated that the network topology illustrated in FIG. **8** has been simplified and that many more networks and network devices can be utilized to interconnect the various computing systems disclosed herein.

(74) A server computer **816** is configured to process requests comprising request identifiers and security tokens as described herein. For example, the server computer **816** can be configured to receive requests comprising request identifiers and security tokens via the network **830** from one or more of the instances **806**. The server computer **816** can validate such a request by determining whether a request identifier contained within the request is associated with all of the security tokens that are also contained within the request. For example, the server computer **816** can comprise a token data store **817** and can search the token data store **817** for a security record associated with the request identifier. If a record associated with the request identifier is found, the server computer **816** can determine whether or not the record contains all of the security tokens included in the request. If a record for the request identifier cannot be found, or if it does not contain all the security tokens included in the request, then the server computer **816** can reject the request. However, if the record is found and it contains all the security tokens, then the server computer **816** can generate another request (such as a modified version of the received request) that comprises protected data items that are associated with the security tokens. The server computer **816** can then transmit the another request to another computing device for processing. The another computing device can be one of the server computers **802**. Additionally or alternatively, the server computer **816** can transmit the another request via the wide area network **840** to a computing device that is external to the compute service provider **800**.

(75) In at least some embodiments, determining whether a request is valid can comprise determining that a request identifier contained within the request is associated with a service that is

running on one or more of the instances **806**, and then determining whether the request was generated by that service.

(76) FIG. **9** depicts a generalized example of a suitable computing environment **900** in which the described innovations may be implemented. The computing environment **900** is not intended to suggest any limitation as to scope of use or functionality, as the innovations may be implemented in diverse general-purpose or special-purpose computing systems. For example, the computing environment **900** can be any of a variety of computing devices (e.g., desktop computer, laptop computer, server computer, tablet computer, etc.).

(77) With reference to FIG. **9**, the computing environment **900** includes one or more processing units **910**, **915** and memory **920**, **925**. In FIG. **9**, this basic configuration **930** is included within a dashed line. The processing units **910**, **915** execute computer-executable instructions. A processing unit can be a general-purpose central processing unit (CPU), processor in an application-specific integrated circuit (ASIC) or any other type of processor. In a multi-processing system, multiple processing units execute computer-executable instructions to increase processing power. For example, FIG. **9** shows a central processing unit **910** as well as a graphics processing unit or co-processing unit **915**. The tangible memory **920**, **925** may be volatile memory (e.g., registers, cache, RAM), non-volatile memory (e.g., ROM, EEPROM, flash memory, etc.), or some combination of the two, accessible by the processing unit(s). The memory **920**, **925** can store software **980** implementing one or more innovations described herein, (for example, in the form of computer-executable instructions suitable for execution by the processing unit(s)). In at least some embodiments, the computing environment **900** can comprise a server computer or other computing device as described herein.

(78) A computing system may have additional features. For example, the computing environment **900** includes storage **940**, one or more input devices **950**, one or more output devices **960**, and one or more communication connections **970**. An interconnection mechanism (not shown) such as a bus, controller, or network interconnects the components of the computing environment **900**. Typically, operating system software (not shown) provides an operating environment for other software executing in the computing environment **900**, and coordinates activities of the components of the computing environment **900**.

(79) The tangible storage **940** may be removable or non-removable, and includes magnetic disks, magnetic tapes or cassettes, CD-ROMs, DVDs, or any other medium which can be used to store information in a non-transitory way and which can be accessed within the computing environment **900**. The storage **940** can store instructions for the software **980** implementing one or more innovations described herein (for example in a storage medium and/or firmware of the storage **940**).

(80) The input device(s) **950** may be a touch input device such as a keyboard, mouse, pen, or trackball, a voice input device, a scanning device, or another device that provides input to the computing environment **900**. The output device(s) **960** may be a display, printer, speaker, CD-writer, or another device that provides output from the computing environment **900**.

(81) The communication connection(s) **970** enable communication over a communication medium to another computing entity. The communication medium conveys information such as computer-executable instructions, audio or video input or output, or other data in a modulated data signal. A modulated data signal is a signal that has one or more of its characteristics set or changed in such a manner as to encode information in the signal. By way of example, and not limitation, communication media can use an electrical, optical, RF, or other carrier. In at least some embodiments, the communication connection(s) can connect the computing environment **900** to a computer network as described herein.

(82) Although the operations of some of the disclosed methods are described in a particular, sequential order for convenient presentation, it should be understood that this manner of description encompasses rearrangement, unless a particular ordering is required by specific language set forth

below. For example, operations described sequentially may in some cases be rearranged or performed concurrently. Moreover, for the sake of simplicity, the attached figures may not show the various ways in which the disclosed methods can be used in conjunction with other methods.

(83) Any of the disclosed methods can be implemented as computer-executable instructions stored on one or more computer-readable storage media (e.g., one or more optical media discs, volatile memory components (such as DRAM or SRAM), or non-volatile memory components (such as flash memory or hard drives)) and executed on a computer (e.g., any commercially available computer, including smart phones or other mobile devices that include computing hardware). The term computer-readable storage media does not include communication connections, such as signals and carrier waves. Any of the computer-executable instructions for implementing the disclosed techniques as well as any data created and used during implementation of the disclosed embodiments can be stored on one or more computer-readable storage media. The computer-executable instructions can be part of, for example, a dedicated software application or a software application that is accessed or downloaded via a web browser or other software application (such as a remote computing application). Such software can be executed, for example, on a single local computer (e.g., any suitable commercially available computer) or in a network environment (e.g., via the Internet, a wide-area network, a local-area network, a client-server network (such as a cloud computing network), or other such network) using one or more network computers.

(84) For clarity, only certain selected aspects of the software-based implementations are described. Other details that are well known in the art are omitted. For example, it should be understood that the disclosed technology is not limited to any specific computer language or program. For instance, the disclosed technology can be implemented by software written in C, C++, Java, assembly language, or any other suitable programming language. Likewise, the disclosed technology is not limited to any particular computer or type of hardware. Certain details of suitable computers and hardware are well known and need not be set forth in detail in this disclosure.

(85) It should also be well understood that any functionality described herein can be performed, at least in part, by one or more hardware logic components, instead of software. For example, and without limitation, illustrative types of hardware logic components that can be used include Field-programmable Gate Arrays (FPGAs), Application-Specific Integrated Circuits (ASICs), Program-Specific Standard Products (ASSPs), System-On-a-Chip systems (SOCs), Complex Programmable Logic Devices (CPLDs), etc.

(86) Furthermore, any of the software-based embodiments (comprising, for example, computer-executable instructions for causing a computer to perform any of the disclosed methods) can be uploaded, downloaded, or remotely accessed through a suitable communication means. Such suitable communication means include, for example, the Internet, the World Wide Web, an intranet, software applications, cable (including fiber optic cable), magnetic communications, electromagnetic communications (including RF, microwave, and infrared communications), electronic communications, or other such communication means.

(87) The disclosed methods, apparatus, and systems should not be construed as limiting in any way. Instead, the present disclosure is directed toward all novel and nonobvious features and aspects of the various disclosed embodiments, alone and in various combinations and subcombinations with one another. The disclosed methods, apparatus, and systems are not limited to any specific aspect or feature or combination thereof, nor do the disclosed embodiments require that any one or more specific advantages be present or problems be solved.

(88) In view of the many possible embodiments to which the principles of the disclosed invention may be applied, it should be recognized that the illustrated embodiments are only examples of the invention and should not be taken as limiting the scope of the invention. We therefore claim as our invention all that comes within the scope of these claims.

Claims

1. A system comprising: a first server computer comprising a security token associated with a protected data item and a request identifier associated with the security token, wherein the first server computer is configured to: transmit the request identifier and the security token to a second server computer; receive a request from the second server computer, wherein the request comprises the request identifier and a data payload comprising the security token, determine that the request identifier is associated with the security token, based on the determination that the request identifier is associated with the security token, generate a modified version of the data payload, wherein the modified version of the data payload comprises the protected data item associated with the security token, and transmit a request comprising the modified version of the data payload to a third server computer; and the second server computer, wherein the second server computer is configured to: receive the request identifier and the security token from the first server computer, generate the data payload comprising the security token, and transmit the request comprising the request identifier and the data payload to the first server computer.
2. The system of claim 1, wherein the first server computer is further configured to: receive another request, wherein the another request comprises another request identifier and another data payload comprising the security token; determine that the another request identifier is not associated with the security token; and reject the another request.
3. The system of claim 1, wherein: the second server computer comprises a service configured to generate the data payload; and the first server computer is further configured to: associate the request identifier with the service, determine that the request is associated with the service, and generate the modified version of the data payload based on the determination that the request identifier is associated with the service and the determination that the request identifier is associated with the security token.
4. The system of claim 3, wherein the first server computer is further configured to: receive another request comprising the request identifier; determine that the another request is not associated with the service; and reject the another request.
5. The system of claim 1, wherein the first server computer is further configured to transmit the request identifier, the security token, and a data item type of the protected data item associated with the security token to the second server computer.
6. The system of claim 1, wherein the generating the modified version of the data payload comprises replacing the security token in the data payload with the protected data item.
7. The system of claim 1, wherein: the first server computer is further configured to: receive a request for processing by the third server computer from a client computing device associated with the protected data item; and responsive to receiving the request from the client computing device: generate the request identifier and the security token, associate the security token with the protected data item and the request identifier, and transmit the request identifier and the security token to the second server computer.
8. A method, comprising: transmitting a request identifier and a security token from a first computing device to a second computing device; receiving, in the first computing device, a first request from the second computing device, wherein the first request comprises the request identifier and the security token within a payload; determining, in the first computing device, that the security token is associated with the request identifier; based on the determining, generating a second request, wherein the second request comprises a protected data item associated with the security token, wherein the generating of the second request includes modifying the payload of the first request by replacing the security token with the protected data item within the modified payload such that the protected data item is located in a position associated with its data item type; and transmitting the second request from the first computing device to a third computing device.

9. The method of claim 8, further comprising: receiving another request from the second computing device, wherein the another request comprises the security token and another request identifier; determining that the security token is not associated with the another request identifier; and rejecting the another request.
10. The method of claim 8, further comprising: generating the security token; associating the security token with the protected data item; generating the request identifier; and associating the request identifier with the security token.
11. The method of claim 8, wherein transmitting the security token and the request identifier to the second computing device comprises: transmitting a message in which the security token is associated with a data item type of the protected data item.
12. The method of claim 8, wherein: the first request comprises a plurality of security tokens, including the security token; and the method further comprises: determining that the request identifier is associated with the plurality of security tokens, and generating the second request based on the determining that the request identifier is associated with the plurality of security tokens, wherein the second request comprises a plurality of protected data items associated with the plurality of security tokens.
13. The method of claim 8, further comprising: associating the request identifier with a service; determining that the request received from the second computing device is associated with the service; and generating the second request based on the determining that the request identifier is associated with the security token and the determining that the first request is associated with the service.
14. A computing device, comprising: a processing unit; and a memory storing instructions that, when executed by the processing unit, cause the computing device to perform operations, the operations comprising: transmitting a security token and a request identifier from a first server computer to a source computing device, which is a second server computer, wherein the security token and the request identifier are used for generation of requests; receiving a request from the source computing device, wherein the request comprises the security token within a payload and the request identifier; retrieving a security record associated with the request identifier; determining, using the security record, that the request identifier is associated with the security token; based on the determining, generating a second request comprising a protected data item associated with the security token, wherein the generating includes modifying the payload by replacing the security token with the protected data item within the modified payload and locating the protected data item in a position that is associated with its respective data type; and transmitting the second request to a destination computing device, which is a third server computer.
15. The computing device of claim 14, wherein the operations further comprise: receiving another request from the source computing device, wherein the another request comprises the security token and another request identifier; retrieving another security record associated with the another request identifier; determining, based on the another security record, that the another request identifier is not associated with the security token; and rejecting the another request.
16. The computing device of claim 14, wherein the operations further comprise: generating the security token; associating the security token with the protected data item; generating the request identifier; and associating the security token with the request identifier using the security record.
17. The computing device of claim 16, wherein transmitting the security token and the request identifier to the source computing device comprises: transmitting a message in which the security token is associated with a data item type of the protected data item.
18. The computing device of claim 14, further comprising: associating the request identifier with a service; determining that the request received from the source computing device is associated with the service; and generating the second request based on the determining that the request identifier is associated with the security token and the determining that the request is associated with the service.

19. The computing device of claim 14, wherein: the operations further comprise: deleting the security record after transmitting the second request to the destination computing device.
20. The computing device of claim 14, wherein: the request comprises a request for an operation to be performed by the destination computing device using the protected data item.
-