

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent
Kind Code
Date of Patent
Inventor(s)

12407037
B1
September 02, 2025
Dawson; James et al.

Busbar cooling system for a vehicle battery pack

Abstract

A busbar cooling system includes an enclosure and a conductive assembly. The enclosure has a first non-conductive housing and a second non-conductive housing that are configured to permit fluid to flow through the busbar cooling system, the upper housing having an upper internal wall arrangement and the lower housing having a lower internal wall arrangement, wherein the upper and lower internal wall arrangements collectively define a plurality of distinct and concentrically arranged cavities. The conductive assembly is configured to permit electrical current to pass through the busbar cooling system, said conductive assembly includes an internal cooling core having a plurality individual conductors that are concentrically arranged in a spaced apart relationship to one another, and wherein each cavity is configured to receive a substantial extent of one of the conductors of the internal cooling core.

Inventors: Dawson; James (Carol Stream, IL), Degen; Jason (Carol Stream, IL), Houmard; Jamie (Carol Stream, IL)

Applicant: Eaton Intelligent Power Limited (Dublin, IE)

Family ID: 96882231

Assignee: Eaton Intelligent Power Limited (Dublin, IE)

Appl. No.: 17/693313

Filed: March 11, 2022

Related U.S. Application Data

us-provisional-application US 63159689 20210311

Publication Classification

Int. Cl.: H01M10/625 (20140101); H01M10/613 (20140101); H01M10/6556 (20140101);
H01M10/6568 (20140101); H01M50/502 (20210101)

U.S. Cl.:

CPC H01M10/625 (20150401); H01M10/613 (20150401); H01M10/6556 (20150401);
H01M10/6568 (20150401); H01M50/502 (20210101); H01M2220/20 (20130101)

Field of Classification Search

CPC: H01M (10/625); H01M (10/613); H01M (10/6556); H01M (10/6568); H01M (50/502);
H01M (2220/20)

USPC: 429/120

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2016/0190663	12/2015	Bahrami	429/120	H01M 10/613
2018/0069278	12/2017	Mastrandrea	N/A	H01M 50/213
2018/0261992	12/2017	Bower	N/A	H01M 50/512
2019/0067763	12/2018	Ing	N/A	H01M 10/04
2020/0313260	12/2019	Wang	N/A	H01M 10/625

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
3696877	12/2019	EP	H01M 10/613

Primary Examiner: Erwin; James M

Attorney, Agent or Firm: Meunier Carlin & Curfman LLC

Background/Summary

PRIORITY CLAIM (1) This application is claims the benefit of U.S. Provisional Patent Application Ser. No. 63/159,689, the disclosures of which is hereby incorporated by reference in their entirety for all purposes.

TECHNICAL FIELD

(1) This disclosure relates to a busbar cooling system to improve thermal management issues associated with rapidly charging and/or discharging a battery pack in a vehicle, such as a motor vehicle. In particular, the busbar cooling system has an enclosure with upper and lower housings, a current inlet casing, a current outlet casing, a male charging connector assembly, and a male discharging connector assembly. The cooling system also includes a conductive assembly with an internal cooling core that is bathed with a cooling fluid within the enclosure, a current inlet assembly, and a current outlet assembly.

BACKGROUND OF THE INVENTION

(2) Electrified vehicles, including hybrid electric vehicles (HEVs), plug-in hybrid electric vehicles (PHEVs), fuel cell vehicles (FCVs), and battery electric vehicles (BEVs), differ from conventional

motor vehicles because they are operated using one or more electric machines or motors powered by a battery pack. The battery pack includes a plurality of battery cell assemblies arranged in one or more battery arrays or modules. These battery arrays or modules are electrically and mechanically coupled to one another using busbars. In addition, the battery pack is electrically and mechanically coupled to an on-board charger for AC charging and an exterior charger for DC charging using busbars.

(3) There are two primary types of chargers used to charge the battery cells in the battery pack of a vehicle. The first type of charger is located within the vehicle and commonly referred to as an “on-board” charger. The on-board charger typically: (i) accepts AC from an external source (e.g., outlet), (ii) has limited power, typically less than about 22 kW, and (iii) needs a considerable period of time to fully charge the vehicle's battery pack. Charging times for the vehicle's battery pack using the on-board charger are typically between 8-12 hours and can reach up to about 24 hours depending on the power level of the charger and the battery characteristics.

(4) The second type of charger is external to the vehicle and commonly referred to as an “off-board” charger. This off-board charger typically: (i) accepts DC from an external source (e.g., fast-charging station or “super charger”), (ii) has nearly unlimited power, and (iii) needs only a short period of time to fully charge the vehicle's battery pack. Charging times for the vehicle's battery pack using the off-board charger are typically between 30 minutes and 1 hour depending on the power level of the charger and the battery characteristics. However, it is desirable to further reduce the charging time, for example under 15 minutes or even 10 minutes, to improve the utility of the vehicles, reduce the vehicle's downtime while charging and make them more appealing to the general public and consumers.

(5) Reducing the charging time of the vehicle's battery pack can generally be achieved in two ways: using higher charging voltages or using higher charging currents. Using a higher charging voltage is typically not feasible because it undesirably increases the size, weight, and cost of the charging system due to at least the insulation requirements and other concerns. While using a higher charging current does not involve the same concerns associated with increasing the charging voltage, using a higher charging current does create thermal management issues that must be addressed. These thermal management issues, namely the build-up of heat, result from the high current flow over electrical components that have resistances. These thermal management issues are further exacerbated because the vehicle is stationary and not moving when it is charging and as a result, there is no air flow passing through the vehicle to provide convective cooling of the various electric components and the battery pack.

(6) In addition to the significant thermal management issues that arise while charging the battery pack, other thermal management issues may arise while rapidly discharging the battery pack. For example, the rapid discharge of the battery pack may occur when a vehicle is quickly accelerated (e.g., launch control found in the Porsche Taycan or the Ludicrous Mode found in the Tesla Model P) or aggressively driven for even a relatively moderate period of time.

(7) Conventional methods attempting to manage these thermal management issues include active cooling of the battery cells, increasing the cross-sectional area of the busbars that are utilized to carry the current from the source (e.g., charger or battery) to the receiver (e.g., battery or motor), and/or replacing certain electrical components with other components that have a lower resistance. However, each of these solutions has significant limitations and concerns that reduce their effectiveness and/or practicality. For example, actively cooling the battery cells increases system weight, cost and complexity and does not solve thermal management issues associated with transferring current into or out of the battery cells. Additionally, the reduction in cooling that is achieved by increasing the busbar's cross-sectional area does not overcome the downside effects of increasing the weight and material costs of the enlarged busbar. Finally, using lower resistance materials undesirably increases the cost of the charging system, thereby reducing its practicality and appeal.

(8) Accordingly, there is an unmet need for a busbar cooling system that effectively manages the thermal management issues associated: (i) charging the battery pack or (ii) discharging the battery pack, including the usage of conventional busbars. A full discussion of the features and advantages of the present invention is deferred to the following detailed description, which proceeds with reference to the accompanying drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The accompanying drawings, which are included to provide further understanding and are incorporated in and constitute a part of this specification, illustrate disclosed embodiments and together with the description serve to explain the principles of the disclosed embodiments. In the drawings:
- (2) FIG. 1 is a perspective view of a first embodiment of a busbar cooling system having: (i) an enclosure with current inlet and outlet casings, (ii) a male charging connector assembly, and (iii) a male discharging connector assembly;
- (3) FIG. 2 is an exploded view of the busbar cooling system of FIG. 1, wherein the busbar cooling system includes: (i) the enclosure and (ii) a conductive assembly with an internal cooling core in an uncoupled state S.sub.U, a current inlet assembly, and a current outlet assembly;
- (4) FIG. 3 is a perspective view of internal cooling core of FIG. 2 in the uncoupled state S.sub.U;
- (5) FIG. 4 is a perspective view of internal cooling core of FIG. 2 in a coupled state S.sub.CU;
- (6) FIG. 5 is a top view of the internal cooling core of FIG. 2 in the coupled state S.sub.CU;
- (7) FIG. 6 is a perspective view of the busbar cooling system of FIG. 1, wherein the busbar cooling system includes: (i) the enclosure and (ii) the conductive assembly with the internal cooling core in the coupled state S.sub.C, the current inlet assembly, and the current outlet assembly;
- (8) FIG. 7 is a perspective view of the conductive assembly of FIG. 6 in a disconnected state SD;
- (9) FIG. 8 is a top view of the conductive assembly of FIG. 7;
- (10) FIG. 9 is a side view of the conductive assembly of FIG. 7;
- (11) FIG. 10 is a perspective view of the conductive assembly of FIG. 2 in a connected state S.sub.CN;
- (12) FIGS. 11 and 12 are top views of the conductive assembly of FIG. 10;
- (13) FIG. 13 is a cross-sectional view of the conductive assembly taken along line 13-13 of FIG. 12;
- (14) FIG. 14 is a perspective view of the busbar cooling system of FIG. 1 in a first partially assembled state S.sub.PA1, wherein: (i) the upper housing is separated from the conductive assembly, (ii) the lower housing is separated from the conductive assembly, (iii) the current inlet casing is coupled to the current inlet assembly, and (iv) the current outlet casing is coupled to the current outlet assembly;
- (15) FIG. 15 is a side view of the busbar cooling system of FIG. 14, wherein the upper and lower housings have been omitted to reveal the positional arrangement of the conductive assembly, and the current inlet and outlet casings;
- (16) FIG. 16 is a top view of the busbar cooling system of FIG. 15;
- (17) FIG. 17 is a lower perspective view of the upper housing of FIG. 14;
- (18) FIG. 18 is an elevated end view of the upper housing of FIG. 14;
- (19) FIG. 19 is a plan view of a housing of the enclosure of FIG. 14, showing the dimensions of the internal cavities;
- (20) FIG. 20 is a perspective view of the busbar cooling system of FIG. 1 in a second partially assembled state S.sub.PA2, showing the conductive assembly and the lower housing;
- (21) FIG. 21 is a perspective view of the busbar cooling system of FIG. 1 in the second partially

assembled state S.sub.PA2, wherein the upper housing and current inlet casing have been omitted to show a sealing assembly and an extent of the conductive assembly;

(22) FIG. 22 is a perspective view of the busbar cooling system of FIG. 1 in a fully assembled state S.sub.FA;

(23) FIG. 23 is a first side view of the busbar cooling system of FIG. 22;

(24) FIG. 24 is a second side view of the busbar cooling system of FIG. 22;

(25) FIG. 25 is a cross-sectional view of the busbar cooling system taken along line 25-25 of FIG. 24, showing the distinct cavities and an extent of the internal cooling core positioned therein;

(26) FIG. 26 is a second side view of the busbar cooling system of FIG. 22;

(27) FIG. 27 is a cross-sectional view of the busbar cooling system taken along line 27-27 of FIG. 26, showing the distinct cavities formed in the enclosure and an extent of the internal cooling core positioned therein;

(28) FIG. 28 is a top view of the busbar cooling system FIG. 22;

(29) FIG. 29 is a cross-sectional view of the busbar cooling system taken along line 29-29 of FIG. 28, showing an extent of the cooling core and the enclosure with inlet and outlet openings;

(30) FIG. 30 is a top view of the busbar cooling system of FIG. 22;

(31) FIG. 31 is a cross-sectional view of the busbar cooling system taken along line 31-31 of FIG. 30, showing a fluid distribution assembly formed in an extent of the upper housing;

(32) FIG. 32 is zoomed-in view of FIG. 31;

(33) FIG. 33 is a first end view of the busbar cooling system of FIG. 22;

(34) FIG. 34 is a cross-sectional view of the busbar cooling system taken along line 34-34 of FIG. 33, showing a fluid distribution assembly formed in an extent of the upper housing;

(35) FIG. 35 is zoomed-in view of FIG. 34;

(36) FIG. 36 is a first end view of the busbar cooling system of FIG. 22;

(37) FIG. 37 is a cross-sectional view of the busbar cooling system taken along line 37-37 of FIG. 36, showing a fluid distribution assembly formed in an extent of the upper housing with an extent of the internal cooling core positioned in said fluid distribution assembly;

(38) FIG. 38 is zoomed-in view of FIG. 37;

(39) FIG. 39 is a side view of the busbar cooling system of FIG. 22;

(40) FIG. 40 is a cross-sectional view of the busbar cooling system taken along line 40-40 of FIG. 39, showing a fluid distribution assembly formed in an extent of the upper housing;

(41) FIG. 41 is a side view of the busbar cooling system of FIG. 22;

(42) FIG. 42 is a cross-sectional view of the busbar cooling system taken along line 42-42 of FIG. 41, showing a fluid distribution assembly formed in an extent of the lower housing;

(43) FIG. 43 is a side view of the busbar cooling system of FIG. 22, wherein a portion of the busbar cooling system has been cutaway to reveal an inner extent of housing and the conductive assembly;

(44) FIG. 44 is a perspective view of the busbar cooling system of FIG. 43, wherein the Figure has been annotated to show current flow through the busbar cooling system;

(45) FIG. 45 is a side view of the busbar cooling system of FIG. 22, wherein an portion of the busbar cooling system has been cutaway to reveal an inner extent of housing and the conductive assembly;

(46) FIG. 46 is a perspective view of the busbar cooling system of FIG. 45, wherein the Figure has been annotated to show fluid flow through the busbar cooling system;

(47) FIG. 47 is a side view of the busbar cooling system of FIG. 22;

(48) FIG. 48 is a cross-sectional view of the busbar cooling system taken along line 48-48 of FIG. 47, showing an internal conductor of the cooling core and the enclosure with the inlet opening;

(49) FIG. 49 shows a second embodiment of the internal cooling core positioned within the lower housing of the busbar cooling system of FIG. 1;

(50) FIG. 50 is a cross-sectional view taken along the longitudinal axis of the second embodiment of the internal cooling core and the lower housing of FIG. 49;

(51) FIG. 51 is a diagram showing a vehicle, an AC charging system, and a DC charging system, and wherein the busbar cooling system is positioned between the battery management system (BMS) and battery units and the DC fast-charging station;

(52) FIG. 52 is a diagram showing a first installation environment of the inventive busbar cooling system;

(53) FIG. 53 is a diagram showing a second installation environment of the inventive busbar cooling system;

(54) FIG. 54 is a diagram showing a third installation environment of the inventive busbar cooling system;

(55) FIG. 55 is a diagram showing a fourth installation environment of the inventive busbar cooling system;

(56) FIG. 56 is a front perspective view of a fifth installation environment, showing three inventive busbar cooling systems installed in a skateboard of a vehicle;

(57) FIG. 57 is a rear perspective view of the fifth installation environment of FIG. 56, showing three inventive busbar cooling systems installed in the vehicle;

(58) FIG. 58 is an exploded view of a second embodiment of the busbar cooling system having (i) an enclosure with a front housing and a rear housing, (ii) a conductive assembly with an internal cooling core in an uncoupled state S.sub.U, and (iii) sealing assemblies;

(59) FIG. 59 is a perspective view of the internal cooling core of FIG. 58 in the uncoupled state S.sub.U;

(60) FIG. 60 is a perspective view of internal cooling core of FIG. 58 in a coupled state S.sub.CU;

(61) FIG. 61 is a side view of internal cooling core of FIG. 58 in the coupled state S.sub.CU;

(62) FIG. 62 is an exploded view of the busbar cooling system of FIG. 58, wherein the internal cooling core of the conductive assembly is in the coupled state S.sub.CU;

(63) FIG. 63 is a perspective view of a rear housing of the busbar cooling system of FIG. 58;

(64) FIG. 64 is a front view of the rear housing portion of FIG. 58;

(65) FIG. 65 is a side view of the rear housing portion of FIG. 58;

(66) FIG. 66 is a perspective view of the busbar cooling system of FIG. 58 in a partially assembled state SPA, wherein the front housing and sealing assemblies are separated from the conductive assembly, and an extent of the conductive assembly resides within the rear housing;

(67) FIG. 67 is a frontal view of the busbar cooling system of FIG. 58 in the partially assembled state SPA, wherein the front housing and sealing assemblies are omitted;

(68) FIG. 68 is a perspective view of the busbar cooling system of FIG. 58 in the partially assembled state SPA, wherein the front housing and sealing assemblies are omitted;

(69) FIG. 69 is a perspective view of the busbar cooling system of FIG. 58 in a second partially assembled state S.sub.PA2, where an extent of the conductive assembly resides within the rear housing and the front housing is separated from the conductive assembly and the sealing assembly;

(70) FIG. 70 is a perspective view of the busbar cooling system of FIG. 58 in a fully assembled state S.sub.FA;

(71) FIG. 71 is a top view of the busbar cooling system of FIG. 70;

(72) FIG. 72 is a side view of the busbar cooling system of FIG. 70;

(73) FIG. 73 is a side view of the busbar cooling system of FIG. 70;

(74) FIG. 74 is a cross-sectional view of the busbar cooling system taken along line 74-74 of FIG. 73 and showing the system in the fully assembled state S.sub.FA;

(75) FIG. 75 is a front view of the busbar cooling system of FIG. 70; and

(76) FIG. 76 is a cross-sectional view of the busbar cooling system taken along line 76-76 of FIG. 75 and showing the system in the fully assembled state S.sub.FA.

DETAILED DESCRIPTION

(77) The detailed description set forth below is intended as a description of various implementations and is not intended to represent the only implementations in which the subject

technology may be practiced. As those skilled in the art would realize, the described implementations may be modified in various ways, all without departing from the scope of the present disclosure. Accordingly, the drawings and description are to be regarded as illustrative and not restrictive.

(78) The busbar cooling system **10, 1010** is designed and configured to help effectively control thermal management issues, namely excessive temperatures and undesirable heat buildup, associated with rapidly charging and/or discharging a battery pack, in particular a vehicle battery pack **4**. In particular, the busbar cooling system **10, 1010** is designed to reduce the heat that is generated by current flowing across a busbar while current is flowing: (i) from outside of the vehicle and into the battery pack **4**, (ii) between the battery modules contained in the battery pack **4**, or (iii) between the battery pack **4** to a device or component within the vehicle (e.g., motors) that is external to the battery pack **4**. Managing and reducing heat that is generated during these conditions is beneficial because it allows: (a) the battery pack **4** to be charged using a higher current level, (b) the battery pack **4** to be discharged at a higher current level, and/or (c) for more efficient use of the electrical power that is being used to charge the battery pack **4** or is being used by the external device (e.g., motors). Additionally, if the current level is not increased, then the busbar cooling system **10** allows the vehicle to employ (i) materials that have higher resistivity and lower material costs, or (ii) busbars that have smaller cross-sectional areas which reduces material costs and are lighter in weight. Further, the busbar cooling system **10, 1010** makes it easier or possible to comply with or exceed the current and heat performance requirements outlined in various vehicle specifications, such as USCAR.

(79) As detailed in the following paragraphs, the busbar cooling system **10, 1010** reduces the heat generated by the current flow across the busbar and between vehicle components because it is positioned between the busbar's endpoints and preferably at or near mid-length of the busbar. In contrast to conventional devices that are designed to reduce the busbar's heat buildup, the busbar cooling system **10, 1010** is: (i) not simply positioned adjacent to the busbar, (ii) is not designed to merely envelop or surround the busbar with a fluid-filled jacket, and (iii) can be used in multiple different configurations. The system's **10, 1010** unique configuration, including its distinct enclosure with internal cavities are configured to receive a fluid that surrounds and bathes a significant extent of the electrical conductors in a spaced-apart relationship, is significantly more efficient at cooling the busbar in comparison to conventional devices. As such, the structures and/or features of conventional devices cannot be simply adopted or implemented into a busbar cooling system without careful analysis and verification of the complex realities of designing, testing, manufacturing, and certifying a busbar cooling system. Theoretical designs that are an attempt to implement such modifications from conventional devices are insufficient (and in some instances, woefully insufficient) because they amount to mere design exercises that are not tethered to the complex realities of successfully designing, manufacturing, validating and testing a busbar cooling system.

(80) The multiple different configurations of the busbar cooling system **10, 1010** have unique benefits and may be used independently of one another or in combination. In one configuration shown in FIG. 52, the busbar cooling system **10, 1010** may be completely separate from the vehicle's active cooling system. In this configuration, the busbar cooling system **10, 1010** includes a separate pump and a separate radiator. The separate pump that is associated with the system **10, 1010** may be: (i) only powered when the vehicle is connected to an external DC charging system (e.g., fast charging) and (ii) only powered by the external DC charging system (i.e., not powered by the vehicle's battery pack **4**). In other words, this configuration does not utilize power in any manner from the vehicle's battery pack **4** and as such there is no electrical drain on the vehicle's battery pack **4**. In a similar configuration shown in FIG. 53, the busbar cooling system **10, 1010** includes a separate pump and a separate radiator, wherein said pump is powered by the vehicle's battery pack **4**. As such, the separate pump can be powered when the vehicle is not connected to an

external DC charging system.

(81) In another configuration shown in FIG. 54, the busbar cooling system **10, 1010** is fully integrated into the vehicle's active cooling system and does not require a separate pump or radiator. This configuration eliminates the weight, cost, and space considerations associated with the first configuration's pump and radiator requirements. This configuration requires sufficient plumbing to connect the fluid ports to the vehicle's active cooling. As such, it is difficult to retrofit a previously designed active cooling system to include said system **10, 1010** without significant modifications. In yet another configuration shown in FIG. 55, the busbar cooling system **10, 1010** may receive cooling fluid from a device (e.g., external DC charging system) exterior to the vehicle. This configuration is beneficial because it does not require the pump and radiator requirements of the first configuration and does not require integration into the vehicle's current active cooling system of the third configuration; however, this configuration requires either multiple connections between the external DC charging system and the vehicle, or it requires the passing of fluid adjacent a high power connector.

(82) The busbar cooling system **10, 1010** effectively controls and minimizes thermal management issues associated with rapidly charging and/or discharging a battery pack **4**, where the battery pack **4** can be installed in a "vehicle" **2** that includes an airplane, motor vehicle (e.g., car, van, pick-up truck, SUV), a military vehicle (e.g., tank, personnel carrier, heavy-duty truck, and troop transporter), a bus, a locomotive, a tractor, marine applications (e.g., cargo ship, tanker, pleasure boat, submarine and sailing yacht), telecommunications hardware (e.g., server), a power storage system (e.g., backup power storage), renewable energy hardware (e.g., wind turbines and solar cell arrays), a 24-48 volt system, for a high-power application, for a high-current application, for a high-voltage application.

I. System

(83) To facilitate the flow of current flow from the charger **5010** into the system **10** and out of the system **10** into other devices (e.g., battery management system (BMS), battery pack **4**, or the combination thereof **4a**), the vehicle **2** utilizes a busbar **5**. The busbar **5** may be: (i) a flexible busbar, which is comprised of a plurality of conductors, (ii) a rigid busbar, which is formed from a single conductor, (iii) a RigiFlex busbar, which is disclosed in PCT/US20/50016 and/or U.S. provisional application 63/234,320, or (iv) a combination thereof. On one side of the system **10**, the busbar **5** is coupled to a male charging connector assembly **6**. Likewise, a busbar **5** is coupled to a male discharging connector assembly **8** on the other side of the system **10**. As such, the busbar **5** is coupled to both sides of the system **10** via the male charging/discharging connector assemblies **6, 8**. Said male charging/discharging connector assemblies **6, 8** include male terminal assemblies having male terminal bodies that are received by the female receiver **332** of the female terminals **324a, 324b**, when the male charging/discharging connector assemblies **6, 8** are coupled to the system **10**. For sake of brevity, specific disclosure of the male charging/discharging connector assemblies **6, 8** is omitted from this application because it is disclosed in detail in the following applications PCT/US19/36010, PCT/US19/36070, PCT/US21/43788, PCT/US21/47180, PCT/US20/13757, PCT/US21/43686, PCT/US20/49870, and U.S. patent Ser. No. 17/570,740, all of which are fully incorporated herein by reference.

(84) The system **10** is mechanically and electrically coupled between the male charging/discharging connector assemblies **6, 8**. The busbar cooling system **10** is comprised of: (i) a conductive assembly **100** and (ii) an enclosure **400** that surrounds at least an extent of the conductive assembly **100**. The conductive assembly **100** is configured to allow current to pass through the busbar cooling system **10**, while the enclosure **400** is configured to allow a non-conductive fluid to pass through the busbar cooling system **10**. The configuration of the conductive assembly **100** and the enclosure **400** enable a substantial extent of the conductive assembly **100** to come into direct contact and bathed with the non-conductive fluid which is supplied into the enclosure **400**. Direct contact between the conductive assembly **100** and the non-conductive fluid is beneficial because it

allows the system **10** extract more heat from the busbars **5** in comparison with systems that separate the conductive assembly **100** from the non-conductive fluid.

II. Conductive Assembly

(85) The conductive assembly **100** is comprised of: (i) an internal cooling core **150**, (ii) a current inlet assembly **300a**, and (iii) a current outlet assembly **300b**. The conductive assembly **100** is made from a conductive material and is configured to allow current to pass through the busbar cooling system **10**. In particular, the current inlet assembly **300a** is designed to receive current from: (i) the charging system (e.g., external DC charger), (ii) a first battery module, or (iii) the battery pack **4**. The current that is received by the current inlet assembly **300a** is then transferred through the internal cooling core **150** to the current outlet assembly **300b**. The current outlet assembly **300b** then transfers the current that is received from the internal cooling core **150** to from: (i) the battery pack **4**, (ii) a second battery module, or (iii) a device or system (e.g., motor) contained within the vehicle. Additional details about the structure and function of the conductive assembly **100** will be discussed below in greater detail.

(86) The internal cooling core **150** is comprised of at least one conductor **154** and preferably a plurality of individual conductors **156**. As best shown in FIGS. 2-5, the internal cooling core **150** includes eight individual conductors **154a-154h**; nevertheless, any number of conductors may be utilized (e.g., **1** to **1000**, and preferable between 5 and 20). Each of the individual conductor **154a-154h** is designed to: (i) receive current from the current inlet assembly **300a**, (ii) fit within a distinct cavity that is formed within the enclosure **400**, (iii) enable a majority of one of the conductor **154a-154h** to be spaced away from other conductors **154a-154h** contained within the internal cooling core **150**, (iv) minimize the resistance that is generated by the conductor **154a-154h**, (v) maximize the amount of heat that can be removed from the busbar **5**, and (vi) transfer the received current to current outlet assembly **300b**.

(87) To achieve these design objections, each conductor **154a-154h** has a complex configuration that can be broken down into three primary segments, which include: (i) first segment or the current receiving segment **158**, (ii) second segment or the cooling segment **164**, and (iii) third segment or the current providing segment **168**. It should be understood that more (e.g., between 3 and 100) or less (e.g., between 1 and 2) segments may be included or identified for each conductor **154a-154h** in the internal cooling core **150**. The current receiving segment **158** includes a combination of complex bends **160** that enable the plurality of conductors **156** to be: (i) coupled to one another, and (ii) coupled to the current inlet assembly **300a**. Coupling said conductor **154a-154h** to one another is beneficial as it facilitates even or uniform distribution of current into the internal cooling core **150** from male charging connector. However, in other embodiments, the conductors **154a-154h** may not be coupled to one another and instead may be individually coupled to the current inlet assembly **300a**. As shown in FIG. 5, the length of the current receiving segment **158** L.sub.CR is between 6 mm and 20 mm and preferably 13 mm. It should be understood that length of the current receiving segment **158** L.sub.CR may be greater or smaller in other embodiments of the system **10**.

(88) The cooling segment **164** includes an amalgamation of bends **166**, which are configured to provide a plurality of spaces **172** between each of the conductors **154a-154h**. In other words, the cooling segment **164** and likewise the conductors **154a-154h** in the internal cooling core **150** are in a spaced apart in relationship to one another. These spaces **172** enable system **10** to efficiently and effectively cool the busbar **5** and increase the surface area that can be cooled by the non-conductive fluid. In fact, the surface area of the internal cooling core **150** has a surface area that is approximately 10.4 times greater than the surface area of a conventional rectangular busbar CRB that would extend between the current inlet assembly **300a** and a current outlet assembly **300b**. As described below, the conventional rectangular busbar CRB has a rectangular configuration defined by a stack of rectangular conductors that are not separated by intervening structures or gaps/spaces. Said 10.4 time greater or about 1,044% is determined by dividing the surface area of internal

cooling core **150** (86,806.95 mm.sup.2) by surface area of the conventional rectangular busbar (8,314 mm.sup.2). The surface area of internal and external sides of the internal cooling core **150** is calculated from: (a) a total conductor length of 855.8 mm, as each conductors **154a-154h** is spaced apart from other conductors **154a-154h**, (b) width of each conductor is 50 mm, and (c) a thickness of each conductor is 0.5 mm, and (d) there are 8 conductors **154a-154h** contained in the internal cooling core **150**. And the surface area of the internal and external sides of the conventional rectangular busbar CRB is calculated from: (a) a length of 83.16 mm, which extends between the current inlet assembly **300a** and a current outlet assembly **300b**, (b) width of each conductor is 50 mm, and (c) an overall thickness of the busbar is 4 mm, which is formed by 8 conductors that each have a thickness of 0.5 mm. As disclosed above, these surface area calculations only take into account the surface areas of the sides and do not take into account the surface area of the top, bottom, front, and rear extents of the conductors.

(89) Each space **174a-174g** contained in the plurality of spaces **172** are balanced such that: (i) a significant amount of fluid can flow around each individual conductor **154a-154h** to enable effective cooling of each conductor **154a-154h**, and (ii) too much fluid is not required, which would increase the size, weight, and space requirements of the system **10**. It should be understood that the each space **174a-174g** is sized based upon: (i) the anticipated current flow through the internal cooling core **150**, (ii) size of each conductor **154a-154h** (e.g., length, width, height, and thickness), (iii) conductor material (e.g., aluminum, brass, graphene, silver, pure copper, gold, zinc, nickel, bronze, iron, platinum, steel, lead, stainless steel, or any combination thereof), (iv) type of fluid (e.g., chemical composition, density, and etc.), and/or (i) volumetric flow rate of the system **10**. In the first embodiment (see FIG. 5), the width of the space W.sub.S is between 1 mm and 10 mm and is preferably 5.5 mm and the length of the cooling segment **164** L.sub.C is between 30 mm and 120 mm and is preferably 60 mm. It should be understood that width of the space W.sub.S between the conductors **154a-154h** and the length of the cooling segment L.sub.C may be greater or smaller in other embodiments of the system **10**.

(90) The current providing segment **168** includes a combination of complex bends **170** that enable the plurality of conductors **156** to be: (i) coupled to one another, and (ii) coupled to the current outlet assembly **300b**. Coupling said conductor **154a-154h** to one another is beneficial as it facilitates even or uniform distribution out of the internal cooling core **150** and into the male discharging connector. However, in other embodiments, the conductors **154a-154h** may not be coupled to one another and instead may be individually coupled to the current outlet assembly **300b**. As shown in FIG. 5, the length of the current providing segment **168** L.sub.CP is between 6 mm and 20 mm and preferably 13 mm. It should be understood that length of the current providing segment **168** L.sub.CP may be greater or smaller in other embodiments of the system **10**.

(91) As shown in FIGS. 2-5, the bends **160**, **170** in the individual conductors **154** formed within the first and third segments **158**, **168** substantially mirror each other. While the mirroring of these bends **160**, **170** is unnecessary to enable the system **10** to function, it is desirable because it enables the current inlet assembly **300a** and current outlet assembly **300b** to mirror one another. As such, non-symmetrical designs may be utilized and are contemplated by this disclosure. Nevertheless, mirroring of these components **300a**, **300b** increases efficiencies, simplifies assembly, reduces installation cost, and reduces additional parts. In particular, the first and third segments **158**, **168** include a flared out design that is comprised of: (i) a flat mounting extent **200a**, **200b**, (ii) a curved receiving extent **202a**, **202b**, and (iii) longitudinal extent **204a**, **204b**. The flat mounting extent **200a**, **200b** is designed to be directly coupled to an adapter **304a**, **304b** that is included within the current inlet and outlet assembly **300a**, **300b**, while the curved receiving extent **202a**, **202b** is designed to receive the touch proof post **314a**, **314b** that is also included within the current inlet and outlet assembly **300a**, **300b**. This flared out arrangement is not only beneficial for the placement of the touch proof post **314a**, **314b**, but it also ensures that the adapters **304a**, **304b** are not simply coupled to a plurality of end surfaces of the plurality of conductors **154a-154h**. This not

only helps ensure proper current flow path into and through the system **10**, but it also increase durability and removes failure modes.

(92) The longitudinal extent **204a**, **204b** of the first and third segments **158**, **168** is designed to ensure that the conductors **154a-154h** are properly jointed together prior to being bent in the curved receiving extent **202a**, **202b**. In other words, reducing the length of the longitudinal extent **204a**, **204b** may introduce failure modes into the system **10** because the conductors **154a-154h** may not be sufficiently coupled to one another prior to being bent in the curved receiving extent **202a**, **202b**. Other designs or configurations are contemplated by this disclosure and apparent to those skilled in the art. For example, the flared out design may be omitted, such that the conductors **154a-154h** will only include a longitudinal extent (e.g., omitting the flat mounting extent **200a**, **200b** and curved receiving extent **202a**, **202b**). While feasible, this design may not be preferred because the adaptor **304a**, **304b** will only be coupled to a plurality of end surfaces of the conductors **154a-154h** (i.e., not to a side of the conductors **154a-155h**). Nevertheless, this design may have some benefits because it would allow the width of the adaptors **304a**, **304b** to be reduced from approximately 14 mm to 4 mm for a cooling core **150** that includes 8 conductors with widths of 0.5 mm each.

(93) Still referring to FIGS. 2-5, the amalgamation of bends **166** contained in the cooling segment **164** of each conductor **154a-154h** are not uniform for all conductors **154a-154h** contained in the cooling core **150**. In other words, each conductor **154a-154h** is different from at least one other conductor **154a-154h**. And in fact, the four conductors **154a-154d** on one side **177a** of the **0** each have configurations that are different from one another. Similarly, the four conductors **154e-154h** on the opposed side **177b** of the central longitudinal axis **176** each have configurations that are different from one another. Stated another way, any adjacent conductors—namely, **154a** and **154b**, **154b** and **154c**, **154c** and **154d**, **154e** and **154f**, **154f** and **154g**, **154g** and **154h**—that are not included in the center pair of conductors **154d** and **154e** have a different configuration. The differences in the amalgamation of bends **166** allows for the creation of the spaces **174a-174h** between the conductors **154a-154h** in order to form the core's **150** spaced-apart design. In particular, this spaced-apart design provides a concentric arrangement for the plurality of conductors **156**. This concentric configuration of conductors **154a-154h** allow system **10** to efficiently and effectively cool the internal cooling core **150**.

(94) While almost all of the adjacent conductors **154a-154h** may have a different configuration, the configuration of the outer most conductors match **154a**, **154h**, the configuration of the inner most conductors match **154d**, **154e**, and the configuration of the pairs of conductors **154b**, **154g**; **154c**, **154f** that are positioned between the inner and outer conductors **154d**, **154e**, **154a**, and **154f** match. Stated another way, the configuration of the second segment **164** and in turn the configuration of the internal cooling core **150** are mirrored about the central longitudinal axis **176**. Additionally, the configuration of the second segment **164** and in turn the configuration of the internal cooling core **150** is also mirrored about the central vertical axis **178**. While the mirroring of these bends **166** about the axis **176**, **178** is unnecessary to enable the system **10** to function, it is desirable because it enables extents of the enclosure **400** to mirror one another, reduces the number of parts in half, increases efficiencies, simplifies assembly, and reduces installation cost. As such, non-symmetrical designs may be utilized and are contemplated by this disclosure.

(95) Based on this concentric arrangement of conductors **154a-154h**, the outermost conductors **154a** **154h** are the longest conductors (i.e., a length between 60 mm and 240 mm, preferably 120 mm), while the innermost conductor **154d**, **154e** is the shortest conductor (i.e., a length between 45 mm and 180 mm, preferably 93 mm). In other words, the length of the outermost conductor **154a**, **154h** is approximately 29% longer than the length of the innermost conductors **154d**, **154e**. The difference in the lengths between the outermost and innermost conductors **154a**, **154h**, **154d**, **154e** is different than the length of the conductors that comprise the conventional rectangular busbar CRB. In other words, the lengths of each conductor in the conventional rectangular busbar CRB are equal, but the lengths of all conductors **154a-154h** contained in the internal cooling core **150** are

not equal. In fact, the total or combined length of all conductors **154a-154h** contained in the system **10** is approximately 855.8 mm, while the total or combined length of all conductors contained in the conventional rectangular busbar CRB that would extend between the current inlet assembly **300a** and a current outlet assembly **300b** is approximately 665.28 mm. As such, the total length of the concentric arrangement of conductors **154a-154h** is approximately 28% more than the total length of all conductors contained in the conventional rectangular busbar CRB. This increase in length also increase the resistance of the internal cooling core **150** as compared to the resistance of the conventional rectangular busbar CRB. In particular, the total resistance of the concentric arrangement of conductors **154a-154h** is approximately 71.8 $\mu\Omega$, while the total resistance of the conventional rectangular busbar CRB is approximately 55 $\mu\Omega$. As such, the total resistance of the internal cooling core **150** is about 30.5% larger than the total resistance of the conventional rectangular busbar CRB. Increasing the total resistance of the internal cooling core **150** by about 30.5% and increasing the total length of the concentric arrangement of conductors **154a-154h** by approximately 28% is unconventional because they contradict the goals of decreasing: (i) weight, (ii) cost, (iii) resistance, (iv) size, and (v) complexity of manufacturing, of the system **10**.

(96) A majority of the bends contained within the cooling segment **164** are formed at 90 degree angles or substantially at 90 degrees to maximize the spaces **172** formed between the conductors **154a-154h** and to help ensure that the fluid properly flows through the enclosure **400** and around the conductors **154a-154h**. Nevertheless, other configurations are contemplated by this disclosure. For example, the conductors **154a-154h** that are contained within this cooling segment **164** may have a different configurations, which include alterations of: (i) type of bend contained in conductor (e.g., arc, curvilinear, parabolic, etc.), (ii) number of bends (e.g., 0-200), and (iii) angle of the bends angles between 1 degree-179 degrees. While the length of each conductor **154a-154d** contained on one side **177a** of the central longitudinal axis **176** is different from one another, the thickness and height of said conductors **154a-154d** do not change. This simplifies manufacturing because the same stock material can be used to form each conductor **154a-154d** and the bends that are formed in the stock material do not need to be specifically centered around differences in the stock material. Nevertheless, the thicknesses and the heights of the conductors **154a-154d** may change over the length or height of the conductors **154a-154d**. For example, the outermost conductor **154a** may have a greater thickness the one of the inner conductors **154d** to aid in current transfer due to the increase in length. Alternatively, the height of the innermost conductor **154d** may be less than the height of the other conductors **154a-154c** because the innermost conductor **154d** has a shorter length in comparison to the outermost conductor **154a**. Finally, other configurations of the height and thickness are contemplated by this disclosure.

(97) As shown in FIG. 3, each conductor **154a-154h** is bent according to its position within the core **150**. These bends may be formed using any number of machines and known techniques. In addition to bending the individual conductors using a bending machine or press, the conductors may be cast or printed (3D printing) in the desired configuration. Once the individual conductors **154a-154h** are formed in the desired configuration, the conductors **154a-154h** are typically coupled to one another via a weldment process. In other embodiments, the conductors **154a-154h** may be coupled to each other using other known techniques. Instead of forming the individual conductors **154a-154h** and then coupling them to one another, as shown in FIGS. 3-5, it should be understood that core **150** could be formed as a single piece via a casting, printing (3D printing), or any other known method of forming the depicted and/or described internal cooling core **150**.

(98) As best shown in FIGS. 2, 6-13, 20, 25, and 29, the current inlet and outlet assemblies **300a**, **300b** include: (i) an adaptor **304a**, **304b**, (ii) an optional touch proof post **314a**, **314b**, and (iii) a female terminal **324a**, **324b**. As discussed above, the current inlet and outlet assemblies **300a**, **300b** are designed to facilitate current flowing into and out of the internal cooling core **150**. To facilitate said current flow, the adaptor **304a**, **304b** is designed to: (i) extent the entire length along the front and back surfaces of the conductors **154a-154h**, (ii) couple the female terminal **324a**, **324b** to the

inner core **150**. As such, the adaptor **304a**, **304b** includes three portions, wherein: (i) a first portion **306a**, **306b** is a flat extent that is designed to be coupled to an upper extent **230** of the core **150**, (ii) a second extent **308a**, **308b** is a raised extent that provides additional space for the touch proof post **314a**, **314b** and extends across a middle extent **234** of the core **150**, and (iii) a third extent **310a**, **310b** that is a flat extent that is designed to be coupled to a lower extent **238** of the core **150**.

(99) To ensure that the adaptor **304a**, **304b** can be coupled to the flared out design of each conductor **154a-154h** (described above), the width of the adaptor **304a**, **304b** is between 7 mm and 28 mm and preferably 14 mm. As shown in at least FIG. **11**, the width $W_{sub.A}$ of the adaptors **304a**, **304b** is: (i) approximately equal to the width of the rear wall of the terminal **324a**, **324b** $W_{sub.TRW}$, and (ii) less than the width $W_{sub.T}$ of the terminal. As such, the current flow path is defined from (i) from the male connector assembly **6**, (ii) into the sidewalls **328a-328d** of the female terminal **324a**, (ii) into the rear wall **330** of the female terminal **324a**, and (iv) into the adaptor **304a** is not restricted by the width of said adaptor **304a**. Likewise, the current flow path is further defined: (i) from the internal cooling core **150**, (ii) into the adaptor **304b**, (iii) into the rear wall of the female terminal **324b** is not restricted by the width of said adaptor **304b**. In other words, the width $W_{sub.A}$ of the adaptors **304a**, **304b** do not form a current choke point in the system **10**. Additionally, unlike the thickness of 0.5 mm for each individual conductor **154a-154h**, the adaptor **304a**, **304b** has a significant thickness $T_{sub.A}$ that is between 4 mm and 1 mm and preferably equal to or larger than 2 mm. The significant thickness $T_{sub.A}$ of the adaptors **304a**, **304b** is desirable to ensure that said thickness $T_{sub.A}$ is equal to or greater than the thickness $T_{sub.ME}$ of the flat mounting extent **200**. As such, the thicknesses $T_{sub.A}$ of the adaptors **304a**, **304b** also do not create a choke point for current flow into and out of the internal cooling core **150**.

(100) It should be understood that other designs and configurations of the adaptor **304a**, **304b** are contemplated within this disclosure. For example, the second extent **308a**, **308b** and the touch proof post **314a**, **314b** may be omitted. As such, the adaptor **304a**, **304b** in this alternative embodiment would be a linear piece of metal coupled between the core **150** and the female terminals **324a**, **324b**. In a further alternative embodiment, the adaptor **304a**, **304b** may be omitted in its entirety and the female terminals **324a**, **324b** may be directly coupled to the core **150**. In particular, this alternative design may be particularly useful when the core **150** is integrally formed from a single piece of metal (e.g., cast or printed). Additionally, this alternative design is beneficial because it either: (i) reduces parts, weight, and cost or (ii) allows for an increase in the internal cooling core **150**.

(101) The touch proof post **314a**, **314b** is made from a non-conductive material, is designed to protect from foreign objects contacting the conductive extent of the female terminals **324a**, **324b**. Additionally, said touch proof post **314a**, **314b** is received by an extent of the male connector assembly when the male terminal is inserted into the female receptacle **326a**, **326b**, which aids in positing of the male terminal, and reduces vibrations between the male the female terminals. Additional information about the touch proof post **314a**, **314b** is described in connection with PCT/US19/36070, PCT/US20/13757, PCT/US20/49870, PCT/US21/33446, and U.S. Provisional Application No. 63/222,859, each of which is incorporated herein by reference. As discussed within these references, the touch proof post **314a**, **314b** is optional and may be omitted from system **10**. Moreover, the touch proof post **314a**, **314b** may be replaced with the internal interlock system described in detail in PCT/US21/43686, which is incorporated herein by reference.

(102) The female terminal **324a**, **324b** is made from a conductive material and is designed to be mechanically and electrically connected to the male terminal bodies (not shown), which are contained in the male charging connector assembly **6** and the male discharging connector assembly **8**. The female terminal **324a**, **324b** includes a female terminal body **326a**, **326b**, wherein said body **326a**, **326b** is comprised of: (i) a rear wall **330** and (ii) an arrangement of female terminal sidewalls **328a-328d** that are coupled to one another via a rear wall **330** to form a substantially rectangular shape. The rear wall **330** coupled to the adaptor **304a**, **304b** and includes an opening **330a** formed

that is designed to receive an extent of the touch proof post **314a**, **314b**.

(103) In the arrangement of female terminal side walls **328a-328d**, one female terminal side wall **328a** of the arrangement of female terminal side walls **328a-328d** is: (i) substantially parallel with another one female terminal side wall **328c** of the arrangement of female terminal side walls **328a-328d** and (ii) substantially perpendicular to two female terminal side wall **328b**, **328d** of the arrangement of female terminal side walls **328a-328d**. Also, all female terminal side walls **328a-328d** are perpendicular to the rear wall **330**. As such, the combination of walls **328a-328d**, **330** of the female terminal body **326a**, **326b** defines a female terminal receiver **332**. The female terminal receiver **332** is designed and configured to be coupled, both electrically and mechanically, to an extent of the male terminal body when the male terminal body is inserted into the female terminal receiver **332**. Additional information about the female terminal **324a**, **324b** is described in connection with PCT/US19/36010, PCT/US19/36070, PCT/US20/13757, PCT/US20/49870, PCT/US21/43686, and U.S. Provisional Application No. 63/222,859, each of which is incorporated herein by reference.

(104) The female terminal **324a**, **324b** is typically formed for a single piece of material (e.g., metal). Therefore, the female terminal **324a**, **324b** is a one-piece female terminal **324a**, **324b** and has integrally formed features. To integrally form these features, the female terminal **324a**, **324b** is typically formed using a die cutting process. However, it should be understood that other types of forming the female terminal **324a**, **324b** may be utilized, such as casting or using an additive manufacturing process (e.g., 3D printing). In other embodiments, the features of the female terminal **324a**, **324b** may not be formed from one-piece or be integrally formed, but instead formed from separate pieces that are welded together. In alternative embodiments, the current inlet and outlet assemblies **300a**, **300b** may include multiple female terminals **324a**, **324b** on each side of the internal cooling core **150**. For example, there may be three female terminals in the current inlet assembly **300a**, and there may be three female terminals in the current outlet assembly **300b**. Alternatively, there may be six female terminals in the current inlet assembly **300a** and only one female terminal in the current outlet assembly **300b**. In fact, there could be any number (e.g., 1 to 100) of female terminals in the current inlet assembly **300a** and any number (e.g., 1 to 100) of female terminals in the current outlet assembly **300b**. In further embodiments, the female terminals may be replaced with one or more male terminals or any combination thereof.

III. Enclosure

(105) As best shown in FIGS. **2**, **6**, **14**, **17-19**, **25**, **27**, **34-35**, **37-38**, **40**, **42**, and **44-48**, the enclosure **400** is comprised of: (i) a current inlet casing **450a**, (ii) a current outlet casing **450b**, (iii) a current inlet sealing assembly **600a**, (iv) a current outlet sealing assembly **600b**, (v) a housing assembly **700**. The enclosure **400** is configured to allow a non-conductive fluid to pass through the busbar cooling system **10**. In particular, the non-conductive fluid is designed to flow into system **10** from an inlet **706** formed within a upper housing **704** of the housing assembly **700**, around the conductors **154a-154h** contained in the internal cooling core **150**, and out of system **10** through an outlet **714** that is formed within a lower housing **712** of the housing assembly **700**. Said non-conductive fluid may be in the form of: (i) a gas (e.g., air), (ii) a liquid (e.g., 3M Novec Engineered Fluid, MIVOLT, AmpCool 100 series (i.e., single-phase fluid), hydrocarbon based liquids (e.g., mineral-oils, synthetic-oils or bio-oils), fluorocarbon based liquids, and/or fully engineered liquids), (iii) a phase change material (i.e., dual-phase fluid), or (iv) any other chemical or substance that may be used in connection with the cooling of a material. It should be understood that the above described fluids may: (i) weigh 80% of the weight of water, (ii) may have a dielectric constant between 2 and 2.2, and (iii) a heat capacity between 1.2 and 1.5 kJ/kg K. In addition to the non-conductive fluids that are disclosed above, other non-conductive fluids that are designed to be place in contact with and cool electrical components may be utilized.

(106) As best shown in FIGS. **2**, **6**, **14-16**, **21**, **25**, **29**, and **44-48**, the current inlet/outlet casings **450a**, **450b** are designed to: (i) receive an extent of the female terminals **324a**, **324b**, (ii) facilitate

the coupling of the male charging/discharging connector assemblies **6, 8** with the system **10**, (iii) help ensure that fluid does not improperly leak out of the apertures **703a, 705a** formed in the front and rear of the housing assembly **700**. To achieve these design goals, the casings **450a, 450b** include: (i) a main portion **460a, 460b** and (ii) a terminal portion **480a, 480b**. The main portion **460a, 460b** has a plurality of side walls **462a, 462b** that are designed to: (i) fill the apertures **703a, 705a** that are formed in the housing **700**, and (ii) form a receiver **464a, 464b**. Said receiver **464a, 464b** is designed to receive an extent of the conductive assembly **100** and more specifically a majority of the current receiving/providing segment **158, 168** of the core **150**. As such and as shown in FIGS. **25**, the current receiving/providing segment **158, 168** of the core **150** extend past the outermost surface of the sidewalls **722a-722d, 732a-732d** of the housing assembly **700**. This design helps maximizes the cooling capacity of the system **10** and facilitates the coupling of the connector assemblies **6, 8**, to the female terminals **324a, 324b**.

(107) As discussed above, one function of the main portion **460a, 460b** of the casings **450a, 450b** is to fill the apertures **703a, 705a** that are formed in the housing **700**. To ensure that the apertures **703a, 705a** are filled and that the main portion **460a, 460b** of the casings **450a, 450b** make a proper seal with the sidewalls **722a-722d, 732a-732d** of the housing assembly **700**, the main portion **460a, 460b** includes a tongue or flange **468a, 468b** that is configured to be received by an extent (e.g., groove) of the sidewalls **722a-722d, 732a-732d**. This tongue and groove configuration helps ensure that the main portion **460a, 460b** is properly coupled to the housing, whereby ensuring that fluid does not accidentally escape the housing assembly **700**. It should be understood that other structures may be utilized to ensure that these structures are properly aligned and joined with one another. For example, a dovetail joint or any other similar arrangement may be utilized.

(108) Like the main portion **460a, 460b**, the terminal portion **480a, 480b** includes a plurality of side walls **482a, 482b** that form a receiver **484a, 484b** that is designed to receive an extent of the conductive assembly **100** and more specifically a majority of the female terminal **324a, 324b**. The terminal portion **480a, 480b** also includes a ramped or sloped inner surface **482a, 482b** that aids in the coupling of the male terminal assemblies of the male charging/discharging connector assemblies **6, 8** with the female terminal **324a, 324b**. This ramped or sloped inner surface **482a, 482b** is described in greater detail within PCT/US19/36070 and PCT/US21/57959, which both incorporated herein by reference. Further, the terminal portion **480a, 480b** includes an outward projection **484a, 484b** that interacts with the connector position assurance (CPA) coupled to the male charging/discharging connector assemblies **6, 8**. Additional details about the CPA projections **484a, 484b** and the male CPA structures that interacts with the CPA projection **484a, 484b** are described within PCT/US19/36070, PCT/US20/49870, PCT/US21/33446, PCT/US21/57959.

(109) In addition to keeping the fluid from leaking out of the housing assembly **700**, the current inlet/outlet casings **450a, 450b** are made from a non-conductive material (e.g., plastic) and are designed to protect the female terminals **324a, 324b** for contact with foreign objects. It should be understood that other shapes, configurations, or designs of the inlet/outlet casings **450a, 450b** are contemplated by this disclosure. For example, the inlet/outlet casings **450a, 450b** may include terminal portions of the conductive assembly **100** includes multiple terminals on one or both sides of the internal cooling core **150**. Alternatively, the shape of the terminal portions **480a, 480b** may be circular or any other shape that is configured to receive the shape of the female terminals **324a, 324b**. Further, the shape of the main portion **460a, 460b** may be altered if the shape of the adaptor **304a, 304b** or the current receiving/providing segment **158, 168** of the individual conductors **154** is altered.

(110) As best shown in FIGS. **2, 6, 20, 25**, and **29**, the sealing assemblies **600a, 600b** are designed to ensure that fluid does not improperly leak out of the enclosure **400**. The sealing assemblies **600a, 600b** are preferable formed from a liquid that is injected into the gaps or openings between the adaptor **304a, 304b**, female terminal **324a, 324b** and the inlet/outlet casings **450a, 450b** during assembly and then the liquid cures and forms a solid seal between these components. For example,

the liquid may be a Loctite manufactured by Henkel AG & Company, KGaA. Alternatively, the seal may be formed from a solid silicon material or any other type of liquid or solid sealing agent. (111) As best shown in FIGS. 1-2, 6, 14, 17-48, the housing assembly 700 includes an upper housing 704 and a lower housing 712 that may be coupled together using a welded processes. Both the upper and lower housings 704, 712 include a wall arrangement 720, 730, which are comprised of: (i) a plurality of exterior side walls 722a-722d, 732a-732d, (ii) a top or a bottom wall 724, 734, and (iii) a plurality of interior walls 748a-748g. The combination of exterior walls 722a-722d, 724 of the upper housing 704 from an upper receptacle 704a, while the combination of walls 732a-732d, 734 of the lower housing 712 from a lower receptacle 712a. The combination of the upper receptacle 704a and lower receptacle 712a form the non-conductive fluid receiver 707. As discussed in greater detail below, the interior walls 748a-748g and the cooling segment 164 of the internal cooling core are positioned in the non-conductive fluid receiver 707, while the non-conductive fluid receiver 707 is designed and configured to receive the non-conductive fluid, when said fluid passes from the inlet 706 to the outlet 714. It should be understood that the housing assembly 700 is made from a non-conductive material (e.g., plastic) and the components of the housing 700 (i.e., upper and lower housings 704, 712) may be welded together once the conductive assembly 100 is installed therein. Additionally, other methods of joining the components of the housing 700 are contemplated by this disclosure.

(112) As shown in the Figures including FIG. 19, a plurality of structures may be formed in the wall arrangement 720, 730, wherein said structures may include: (i) a frontal aperture 703 and a rear aperture 705, wherein said frontal aperture 703a is formed in the front wall 722a, 732a and said rear aperture 705 is formed in the rear wall 722c, 732c, and (ii) an inlet opening 706 and an outlet opening 714, wherein said inlet opening 706 is formed in the top wall 724 and said outlet opening 714 is formed in the bottom wall 734. Said housing apertures 703, 705 allow the terminal 324a, 324b to be coupled to the core 150 and male connector assemblies 6, 8 and have an aperture width $W_{sub.HA}$ that is greater than both the opening 706, 714 width $W_{sub.O}$ and fluid distribution assembly 800a, 800b width $W_{sub.FDA}$. It should be understood that in other embodiments, the aperture width $W_{sub.HA}$ may be smaller or larger.

(113) The inlet and outlet openings 706, 714 are configured to allow fluid to enter and exit the non-conductive fluid receiver 707. As shown in the Figures, the inlet and outlet openings 706, 714 have substantially the same size and are positioned above and below portions of the cooling core 150 at a location where the conductors 154a-154h are coupled to one another. To facilitate the fluid flow into and out of the system 10, the inlet and outlet openings 706, 714 may be configured to receive a threaded barbed hose fitting 708, wherein said threaded barbed hose fitting 708 is designed to be couple a hose or other liquid carrying member to the housings 704, 712. In other embodiments, the inlet and outlet openings 706, 714 may have other: (i) locations, (ii) differing sizes, and/or (iii) configurations that interact with other components to receive and return the non-conductive fluid.

(114) As best shown in FIGS. 25, 32, 35, 38, 40, and 42, the housings 704, 712 include a fluid distribution assembly 800a, 800b that extends radially from the inlet/outlet openings 706, 714 and into the housings 704, 712. The fluid distribution assembly 800a is comprised of a collection of a plurality 802a, 802b of channels 804a-804g, 806a-806g. In particular, the channels 804a-804g, 806a-806g are recesses or grooves that are formed in a wall of the housing 704, 714, such as the top/bottom wall 724, 734 of the housings 704, 712. While the shape of each channel 804a-804g, 806a-806g are mirrored across the central longitudinal axis 176, the shape of channels on one side of the axis 176 are substantially different from one another. In particular, channels 804a, 804g, 806a, 806g are the deepest and widest channels, while channels 804d, 806d are the narrowest and thinnest channels. For example, the width of channels 804a, 804g, 806a, 806g is nearly 4.5 times greater than the width of channels 804d, 806d. Also, extending from channels 804d, 806d is a fan shaped recess that further aids in the distribution of fluid in the cavities that receive the center most conductors 154d, 154e. It should be understood that other configurations are contemplated by this

disclosure.

(115) As best shown in FIGS. 38, 40, and 42, an extent of each one of the conductors **154a-154h** is positioned substantially in the center of each one of said channels **804a-804g**, **806a-806g**. In other words, each channel **804a-804g**, **806a-806g** is substantially centered over an extent of each conductor **154a-154h**. This design is beneficial because it ensures that non-conductive fluid that is transferred into or out of the system **10** flows evenly over the interior and exterior surfaces of the conductors **154a-154h**. Without the formation of the fluid distribution assembly **800a**, **800b**, the non-conductive fluid could not flow into certain individual cavities **710a-710h** and said flow over the conductors **154a-154h** would not be substantially even. Nevertheless, alterations to the housing assembly **700** are contemplated by this disclosure to ensure that the fluid distribution assembly **800a**, **800b** could be omitted and the non-conductive fluid could flow into all cavities **710a-710h** and said flow over the conductors **154a-154h** would be substantially even. For example, the space between the upper and lower edges of the conductors **154a-154h** and the inner surfaces of the top/bottom wall **724**, **734** could be increased and/or openings could be formed between the cavities **710a-710h** to allow fluid to flow therebetween.

(116) The fluid distribution assembly **800a**, **800b** has a width W.sub.FDA that is: (i) greater than the width W.sub.LC of the longitudinal extent **204a**, **204b** of the current receiving/providing segment **168** of the cooling core **150**, (ii) greater than the opening **706**, **714** width W.sub.O, and (iii) less than the width WTC inlet/outlet casings **450a**, **450b**. This configuration ensures that an extent of each conductor **154a-154h** is positioned within an extent of the fluid distribution assembly **800a**, **800b**, while not extending too far into the distinct cavities **710a-710h** of the housing assembly **700**. The fluid distribution assembly **800a**, **800b** also includes a height H.sub.FDA that extends between an extent of the assembly **800a**, **800b** and the top/bottom of the conductors **154a-154h**. Said height H.sub.FDA is non-uniform across the fluid distribution assembly **800a**, **800b** and in fact tapers to zero or disappears as it moves radially outward from the edge of the inlet/outlet openings **706**, **714**. As such, each of the fluid distribution assembly **800a**, **800b** has a length L.sub.FDA1, L.sub.FDA2 that extends from the outermost extent of the channels **804a-804g**, **806a-806g** to an inner most extent of the channels **804a-804g**, **806a-806g**. The length of L.sub.FDA1, L.sub.FDA2 the fluid distribution assembly **800a**, **800b** does not extend over half the length of the housing **700** and as such, there is a housing length L.sub.H is positioned between the fluid distribution assembly lengths L.sub.FDA1, L.sub.FDA2.

(117) As described above, the housing **700** includes a plurality of interior walls **748a-748g**. In particular, the plurality of interior walls **748a-748g** includes: (i) a plurality of upper housing an interior wall arrangement with a plurality of interior walls **750a-750g** that extend downward from the top wall **724** and (ii) a plurality of lower housing having a interior wall arrangement with a plurality of interior walls **752a-752g** that extend upward from the bottom wall **734**. In other words, said plurality of interior walls **748a-748g** are positioned in the non-conductive fluid receiver **707** of the housing **700** are formed from walls **750a-750g**, **752a-752g**. Specifically, interior wall **750a** of the upper housing **704** is placed in contact with interior wall **752a** of the lower housing **712**, when the upper housing **704** is coupled to the lower housing **712**, to form wall **748a**. Additionally, the other interior walls **750b-750g** of the upper housing **704** have a similar positional relationship with the other interior walls **752a-752g** of the lower housing **712**, when the upper housing **704** is coupled to the lower housing **712**, to form walls **748b-748g**. It should be understood that the disclosure contemplates interior walls **748a-748g** with other configurations. For example, openings other than **756a-756c** may be formed in said walls **748a-748g**.

(118) The interior walls **748a-748g** have gaps or openings **756a-756c** formed between extents of said walls **748a-748g**, wherein said gaps or openings **756a-756c** are aligned with: (i) each other, (ii) the front and rear apertures **705a**, **705b**, and (iii) the center wall **748d**. In particular, the first gap or opening **756a** is formed between an outermost pair of walls **748a**, **748g** and has a first opening width W.sub.FO, the second gap or opening **756b** is formed between a second outermost pair of

walls **748b**, **748f** and has a second opening width $W_{sub.SO}$, and the third gap or opening **756c** is formed between an innermost pair of walls **748c**, **748d** and has a third opening width $W_{sub.TO}$. As shown in FIG. **19**, the first opening width $W_{sub.FO}$ is larger than the second opening width $W_{sub.SO}$, and the second opening width $W_{sub.SO}$ is larger than the third opening width $W_{sub.TO}$. Other than openings **756a-756c**, no openings are formed between the walls **748a-748g**, which therefor forms distinct cavities **710a-710h** in the non-conductive fluid receiver **707**. Due to this configuration and the configuration of the fluid distribution assembly **800a**, **800b**, no fluid can flow between the cavities **710a-710h** within the area of the system **10** that extends between the inner most points of the fluid distribution assembly **800a**, **800b** and is shown as the housing length $L_{sub.H}$ in a combination of FIGS. **40** and **42**.

(119) Each distinct cavity **710a-710h** is configured to receive a major extent of one of the individual conductors **154a-154h**. In other words, the outermost cavity **710a** receives a substantial extent of the outermost individual conductor **154a**. Likewise, one of the innermost cavities **710d** receives a substantial extent of one of the innermost individual conductor **154d**. The arrangement of these conductors **154a-154h** within these cavities **710a-710h** is best shown in FIGS. **21**, **25**, **27**, **37**, and **44**. By forming these distinct cavities **710a-710h** that surround each of the conductors **154a-154h**, turbulent flow across the surface of each conductor **154** is increased, which increases the cooling capabilities of the system **10**. The conductors **154a-154h** extend across the entire height of the cavity **710a-710h** in order to maximize the cooling capacity in a defined space. In alternative embodiments, the internal walls **708**, **7016** may be omitted and the volume contained within the housing **700** may be substantially unobscured except for the conductors **154**. This design may not perform as well as the design that includes the internal walls **708**, **716**, but maybe sufficient in some applications.

(120) Do to the concentric configuration, the outer cavities **710a**, **710h** have a longer length than the inner cavities **710d**, **710e** and as such outer cavities **710a**, **710h** will hold more fluid than the inner cavities **710d**, **710e**. The width $W_{sub.D}$ of each distinct cavity **710a-710h** may be between 1 mm and 20 mm, preferably between 4 mm and 5 mm. The width of each distinct cavity **710a-710h** may remain constant or substantially constant across the housing **700**, or said widths may vary laterally or horizontally across the housing **700**. Additionally, the outer cavities **710a**, **710h** may have a larger width than the inner cavities **710d**, **710e**. This is beneficial because the length of the conductors **154a**, **154h** are longer in these cavities and increasing fluid flow across these conductors **154a**, **154h** will help reduce the effects of the increases of resistance. Other configurations of the width, length, depth, and configuration of these cavities **710a-710h** is contemplated by this disclosure.

IV. Operation and Functionality of the System

(121) FIGS. **44** and **46** have been included herein to illustrate the operation of system **10**, wherein FIG. **44** has been annotated to show an electrical flow path through the system **10** and FIG. **46** has been annotated to show a fluid flow path through the system **10**. To show the electrical current flow path, the conductive elements of system **10** are shown with orange highlighting in FIG. **44**. In particular, the electrical flow path through the system **10** includes: (i) the upstream busbar **5a**, (ii) the male charging connector assembly **6**, which includes electrical flow through the male terminal assembly (e.g., contact arm), (iii) the female terminal **324a**, which includes electrical flow through the sidewall sidewalls **328a-328d** and into the rear wall **330**, (iv) the adaptor assembly **304a**, (v) the internal cooling core **150**, including electrical flow through the current receiving segment **158**, the cooling segment **164**, and the current providing segment **168**, (vi) the adaptor assembly **304b**, (vii) the female terminal **324b**, which includes electrical flow through the sidewalls **328a-328d** and into the rear wall **330**, (viii) the male charging connector assembly **6**, which includes electrical flow through the male terminal assembly (e.g., contact arm), and (ix) the downstream busbar **5b**. To note, the housing **700** is not highlighted in this orange color because it is made from a non-conductive material.

(122) Similar to FIG. 44, the cavities **710a-710h** have been annotated with blue highlighting to show how the fluid enters and moves through the system **10**. In particular, the fluid flow path through the system **10** includes: (i) hose fitting **708**, (ii) inlet opening **706**, (iii) fluid distribution assembly **800a**, which includes channels **804a-804g**, (iv) cavities **710a-710h**, and (v) outlet opening **714**. To note, the housing **700** and the conductors **154** are not highlighted in this blue color because the fluid enters into housing **700** and flows around the conductors **154** and is not absorbed by either one of these structures.

(123) As described above, the length of the concentric arrangement of conductors **154a-154h** is approximately 28% greater than the total length of all conductors contained in the conventional rectangular busbar CRB. This increase in length also increase the resistance of the internal cooling core **150** as compared to the resistance of the conventional rectangular busbar CRB, wherein the total resistance of the internal cooling core **150** is about 30.5% larger than the total resistance of the conventional rectangular busbar CRB. While the concentric arrangement of conductors **154a-154h** increased both the length and resistance over the conventional rectangular busbar CRB, it also increased the surface area by approximately 1,044% or about 10.4 times. This substantial increase in surface area leads to an even greater increase in thermal conductivity, as the thermal conductivity is calculated by multiplying the surface area by the thermal conductivity constant of the material and dividing that result by the thickness of the material. As such, the thermal conductivity of the internal cooling core **150** is approximately 83 times greater than the thermal conductivity of the conventional rectangular busbar CRB that is configured to extend between the current inlet assembly **300a** and the current outlet assembly **300b**. Said 83× increase amounts to approximately an 8,300% increase, which is determined by dividing the thermal conductivity of internal cooling core **150** (67,709,421 J/s.Math.m.Math.° C.) by the thermal conductivity of the conventional rectangular busbar (810,615 J/s.Math.m.Math.° C.). Because the percent increase in the thermal conductivity of the internal cooling core **150** is several hundred times greater than the percent increase in the resistance of the internal cooling core **150**, the system **10** enjoys at least the following significant benefits over a conventional cooling system: (i) the size of the busbar **5** to be substantially reduced, (ii) the current carrying capacity, which complying with the standard 55 degrees C. rise over ambient, to be substantially increased, and/or (iii) the ability to use other non-traditional materials (e.g., aluminum, brass, graphene, zinc, nickel, bronze, iron, steel, lead, stainless steel, and/or any combination thereof) in the power distribution system **10**. In light of the above calculations, preliminary testing by the owner of the present Application has shown that the system **10** allows for: (i) increasing, and potentially doubling, the current carrying capacity of the upstream and downstream busbars **5a, 5b**, and/or (ii) significantly reducing the dimensions of the upstream and downstream busbars **5a, 5b**, which reduces the material and fabrications costs of these components.

(124) As described above, system **10** may be installed in multiple different configurations, wherein each configuration has a unique benefit. In a first configuration shown in FIG. 52-53, the busbar cooling system **10** may be completely separate from the vehicle's active cooling system. In this configuration, the busbar cooling system **10** includes a separate pump **5000** and a separate radiator **5004**. The separate pump **5000** that is associated with the system **10** may be either powered by: (i) only the external DC charging system **5010**, as shown in FIG. 52, and is not powered by the vehicle's battery pack **4** (i.e., does not drain the vehicle's battery pack **4** in any manner), or (ii) vehicle's battery pack **4** when the external DC charging system **5010** is coupled to the vehicle, as shown in FIG. 53. The configuration shown in FIG. 52 is beneficial because there is no drain on the vehicle's battery in any state (e.g., while charging or not charging).

(125) FIG. 54 show another configuration, wherein the busbar cooling system **10** is fully integrated into the vehicle's active cooling system and does not require a separate pump or radiator. While this configuration eliminates the weight, cost, and space considerations associated with the pump and radiator requirements of the first configuration, this configuration requires proper plumbing to

connect the fluid ports to the vehicle's active cooling. As such, this configuration cannot be retrofitted within a previously designed active cooling system without significant modifications. (126) FIG. 55 shows a final configuration, wherein the busbar cooling system **10** may receive fluid from a device (e.g., external DC charging system) that is exterior to the vehicle. This configuration is beneficial because it does not require the pump and radiator requirements of the first configuration and does not require integration into the vehicle's current active cooling system of the second configuration; however, this configuration requires either multiple connections between the external DC charging system and the vehicle or it requires the passing of fluid adjacent a high power connector.

(127) As shown in FIGS. 49 and 50, another beneficial factor of system **10** is the fact that different internal cooling cores **150** may be utilized without changing the other components contained within system **10**. Utilizing different internal cooling cores **150** is desirable because they can be appropriately sized to the busbar **5** that they are coupled to and the current applied to said busbar **5**. Specifically, FIGS. 49 and 50 show how a lower current application may replace the inner core **150** (i.e., shown in FIGS. 1-48) that has eight individual conductors **154** and a height of 50 mm with an inner core **150a** (i.e., shown in FIGS. 49-50) that has four individual conductors **154a-154d** and a height of 11 mm. This reduces the system's **10** weight and cost, without requiring a redesign of the system **10** or a comprehensive change of components. It should be understood that while the internal cooling core **150** can be changed to be appropriately sized for the current application, the design may choose to oversize the internal cooling core **150** or may choose to utilize the same size internal cooling core **150** for all of the systems **10** that are contained within a specific application to minimize the change that the wrong system **10** was installed in the wrong location. Nevertheless, the ability to change the internal cooling core **150** to match the desired application provides a significant benefit over conventional systems.

V. Second Embodiment of the System

(128) Similar to system **10** as described above, FIGS. 58-76 show another embodiment of system **1010**. For the sake of brevity, the above disclosure regarding system **10** will not be repeated below, but it should be understood that across both embodiments of the system **10**, **1010** like numbers represent like structures. For example, the foregoing disclosure relating to the internal cooling core **150** applies in equal force to the internal cooling core **1150** of this second embodiment **1010**. Further, it should be understood that the design of both internal cooling cores **150**, **1150** are substantially similar.

(129) A primary difference between these two embodiments **10**, **1010** is the fact that the second cooling system **1010** does not include separate connectors **6**, **8** located in the current inlet/outlet assemblies **300a**, **300b**; instead, the busbar **1100** extends directly and continuously through the housing **1700**. In other words, the internal cooling core **1150** is comprised of the individual conductors **1154** that comprise the busbar **1100**. The configuration of the housing **1400** helps reduce the number of components that are required for the system **1010**.

(130) Due to the design and configuration of the system **1010**, the busbar **5** has a configuration where the individual conductors **1152** that comprise the busbar **5** can be separated from one another into distinct items within the housing **1700**. Conventional flexible busbars may be employed with the system **1010**, but additional design considerations should be undertaken to ensure that fluid cannot escape the housing **1700** between the conductors **1152**. For example, this potential issue may be solved by coupling the conductors **152** to one another where the conductors enter and exit through the apertures formed in the housing **1700**. Alternatively, the busbar that is described with PCT Application Nos. PCT/US2020/50018 may be utilized because segments of that busbar are rigid (e.g., conductors **1152** are coupled to one another) and other segments of that busbar are flexible (i.e., conductors **1152** are not coupled to one another or are partially coupled to one another).

(131) Due to the omission of the connectors and the requirement that the internal cooling core **1150**

is an integral aspect of the busbar 5, this second embodiment of the system 1010 is not as modular and requires upfront design considerations to incorporate it into the system 10. However, if these consideration are addressed and managed, then this the system 1010 can effectively cool the busbar 5 because it does not require additional components (e.g., connectors) that increase the resistance of the overall system and in turn increases the heat that needs to be cooled during operation of the system 1010. Additionally, the reduction in the number of parts increases the systems 1010 durability while reducing both the manufacturing cost of the system 1010 and potential failure points of the system 1010.

MATERIALS AND DISCLOSURE THAT ARE INCORPORATED BY REFERENCE

(132) PCT Application Nos. PCT/US21/57959, PCT/US21/33446, PCT/US21/43686, PCT/US21/47180, PCT/US21/43788, PCT/US2020/50018, PCT/US2020/50016, PCT/US2020/49870, PCT/US2020/14484, PCT/US2020/13757, PCT/US2019/36127, PCT/US2019/36070, PCT/US2019/36010, and PCT/US2018/019787, U.S. patent application Ser. No. 16/194,891, U.S. Provisional Applications 63/159,689, 63/234,320, 63/222,859, and U.S. Design patent application Ser. Nos. 29/749,813, and 29/749,790, each of which is fully incorporated herein by reference and made a part hereof.

(133) SAE Specifications, including: J1742_201003 entitled, “Connections for High Voltage On-Board Vehicle Electrical Wiring Harnesses—Test Methods and General Performance Requirements,” last revised in March 2010, each of which is fully incorporated herein by reference and made a part hereof.

(134) ASTM Specifications, including: (i) D4935-18, entitled “Standard Test Method for Measuring the Electromagnetic Shielding Effectiveness of Planar Materials,” and (ii) ASTM D257, entitled “Standard Test Methods for DC Resistance or Conductance of Insulating Materials,” each of which are fully incorporated herein by reference and made a part hereof.

(135) American National Standards Institute and/or EOS/ESD Association, Inc. Specifications, including: ANSI/ESD STM11.11 Surface Resistance Measurements of Static Dissipative Planar Materials, each of which is fully incorporated herein by reference and made a part hereof.

(136) DIN Specification, including Connectors for electronic equipment—Tests and measurements—Part 5-2: Current-carrying capacity tests; Test 5b: Current-temperature de-rating (IEC 60512-5-2:2002), each of which are fully incorporated herein by reference and made a part hereof.

(137) USCAR Specifications, including: (i) SAE/USCAR-2, Revision 6, which was last revised in February 2013 and has ISBN: 978-0-7680-7998-2, (ii) SAE/USCAR-12, Revision 5, which was last revised in August 2017 and has ISBN: 978-0-7680-8446-7, (iii) SAE/USCAR-21, Revision 3, which was last revised in December 2014, (iv) SAE/USCAR-25, Revision 3, which was revised on March 2016 and has ISBN: 978-0-7680-8319-4, (v) SAE/USCAR-37, which was revised on August 2008 and has ISBN: 978-0-7680-2098-4, (vi) SAE/USCAR-38, Revision 1, which was revised on May 2016 and has ISBN: 978-0-7680-8350-7, each of which are fully incorporated herein by reference and made a part hereof.

(138) Other standards, including Federal Test Standard 101C and 4046, each of which is fully incorporated herein by reference and made a part hereof.

INDUSTRIAL APPLICABILITY

(139) While some implementations have been illustrated and described, numerous modifications come to mind without significantly departing from the spirit of the disclosure; and the scope of protection is only limited by the scope of the accompanying claims. For example, the overall shape of the of the components described above may be changed to: a triangular prism, a pentagonal prism, a hexagonal prism, octagonal prism, sphere, a cone, a tetrahedron, a cuboid, a dodecahedron, an icosahedron, an octahedron, an ellipsoid, or any other similar shape.

(140) It should be understood that the following terms used herein shall generally mean the following: a. “High power” shall mean (i) voltage between 20 volts to 600 volts regardless of current or (ii) at any current greater than or equal to 80 amps regardless of voltage. b. “High

current” shall mean current greater than or equal to 80 amps regardless of voltage. c. “High voltage” shall mean a voltage between 20 volts to 600 volts regardless of current. d. “Vehicle” shall mean an airplane, motor vehicle (e.g., car, van, pick-up truck, SUV), a military vehicle (e.g., tank, personnel carrier, heavy-duty truck, and troop transporter), a bus, a locomotive, a tractor, marine applications (e.g., cargo ship, tanker, pleasure boat, submarine and sailing yacht), telecommunications hardware (e.g., server), a power storage system (e.g., backup power storage), renewable energy hardware (e.g., wind turbines and solar cell arrays), a 24-48 volt system, for a high-power application, for a high-current application, for a high-voltage application.

(141) Headings and subheadings, if any, are used for convenience only and are not limiting. The word exemplary is used to mean serving as an example or illustration. To the extent that the term includes, have, or the like is used, such term is intended to be inclusive in a manner similar to the term comprise as comprise is interpreted when employed as a transitional word in a claim.

Relational terms such as first and second and the like may be used to distinguish one entity or action from another without necessarily requiring or implying any actual such relationship or order between such entities or actions.

(142) Phrases such as an aspect, the aspect, another aspect, some aspects, one or more aspects, an implementation, the implementation, another implementation, some implementations, one or more implementations, an embodiment, the embodiment, another embodiment, some embodiments, one or more embodiments, a configuration, the configuration, another configuration, some configurations, one or more configurations, the subject technology, the disclosure, the present disclosure, other variations thereof and alike are for convenience and do not imply that a disclosure relating to such phrase(s) is essential to the subject technology or that such disclosure applies to all configurations of the subject technology. A disclosure relating to such phrase(s) may apply to all configurations, or one or more configurations. A disclosure relating to such phrase(s) may provide one or more examples. A phrase such as an aspect or some aspects may refer to one or more aspects and vice versa, and this applies similarly to other foregoing phrases.

(143) Numerous modifications to the present disclosure will be apparent to those skilled in the art in view of the foregoing description. Preferred embodiments of this disclosure are described herein, including the best mode known to the inventors for carrying out the disclosure. It should be understood that the illustrated embodiments are exemplary only, and should not be taken as limiting the scope of the disclosure.

Claims

1. A busbar cooling system for a motor vehicle, the busbar cooling system comprising: an enclosure with a non-conductive upper housing and a non-conductive lower housing that are configured to permit fluid to flow through the busbar cooling system, the upper housing having an upper internal wall arrangement and the lower housing having a lower internal wall arrangement, wherein the upper and lower internal wall arrangements collectively define a plurality of distinct and concentrically arranged cavities; a conductive assembly that is configured to permit electrical current to pass through the busbar cooling system, said conductive assembly includes an internal cooling core having a plurality individual conductors that are concentrically arranged in a spaced apart relationship to one another; and wherein each cavity is configured to receive a substantial extent of one of the conductors of the internal cooling core.

2. The busbar cooling system of claim 1, wherein each pair of concentrically arranged conductors has a unique configuration based upon the positional arrangement within the internal cooling core.

3. The busbar cooling system of claim 1, further comprising: a charging connector assembly located between a first busbar and a current inlet casing affixed to an inlet end of the enclosure; and, a discharging connector assembly located between a second busbar and a current outlet casing affixed to an outlet end of the enclosure.

4. The busbar cooling system of claim 3, wherein a current inlet assembly resides within the current inlet casing, the current inlet assembly being electrically connected to an inlet portion of the internal cooling core.
5. The busbar cooling system of claim 3, wherein a current outlet assembly resides within the current outlet casing, the current outlet assembly being electrically connected to an outlet portion of the internal cooling core.
6. The busbar cooling system of claim 1, wherein the conductive assembly includes a current inlet assembly and a current outlet assembly.
7. The busbar cooling system of claim 6, wherein during operation of the busbar cooling system, a current flow path is provided from a supply busbar to the current inlet assembly, through the internal cooling core and then through the current outlet assembly to an exit busbar.
8. The busbar cooling system of claim 1, wherein the conductive assembly includes a current receiving segment that resides within a first aperture formed in both the upper and lower housings of the enclosure.
9. The busbar cooling system of claim 8, wherein the conductive assembly includes a current providing segment that resides within a second aperture formed in both the upper and lower housings of the enclosure.
10. The busbar cooling system of claim 1, wherein the upper and lower internal wall arrangements each includes a centermost wall and at least one pair of internal walls that are located external to the centermost wall.
11. The busbar cooling system of claim 10, wherein the at least one pair of internal walls comprises a first pair of internal walls that are outwardly spaced from the centermost wall to define a first pair of cavities.
12. The busbar cooling system of claim 11, wherein the at least one pair of internal walls comprises (i) a first pair of internal walls that are separated by a first gap and (ii) a second pair of internal walls that are separated by a second gap, and wherein the first and second gaps are aligned with the centermost wall.
13. The busbar cooling system of claim 12, wherein the first and second gaps and the centermost wall are aligned with a first aperture formed in both the upper and lower housings of the enclosure.
14. The busbar cooling system of claim 13, wherein the first and second gaps and the centermost wall are aligned with a second aperture formed in both the upper and lower housings of the enclosure.
15. The busbar cooling system of claim 1, wherein the internal cooling core is bathed with a cooling fluid within the enclosure during operation of the busbar cooling system.
16. The busbar cooling system of claim 15, wherein the upper housing has an inlet port that supplies cooling fluid to the internal cooling core and the lower housing has a discharge port that drains cooling fluid from the internal cooling core and the enclosure to define a cooling fluid flow path.
17. The busbar cooling system of claim 16, wherein the upper housing has a fluid distribution assembly that extends from the inlet port to supply cooling fluid into the cavities and to the internal cooling core to further define a cooling fluid flow path.
18. The busbar cooling system of claim 17, wherein the fluid distribution assembly comprises a plurality of channels formed in a wall of the upper housing, and wherein the channels extend from the inlet port to supply cooling fluid into the cavities and to the internal cooling core to further define the cooling fluid flow path.
19. The busbar cooling system of claim 1, wherein a first pair of conductors of the internal cooling core reside in a first set of cavities that are adjacent to a centermost wall of the upper and lower housings, wherein a second pair of conductors of the internal cooling core reside in a second set of cavities that are located outward of the first set of cavities, wherein a third pair of conductors of the internal cooling core reside in a third set of cavities that are located outward of the second set of

cavities, and wherein a fourth pair of conductors of the internal cooling core reside in a fourth set of cavities that are located outward of the third set of cavities and inward of external walls of the upper and lower housings.
