

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250280174

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

Wannerberg; Petter

GAZE-BASED AUDIO SWITCHING AND 3D SIGHT LINE TRIANGULATION MAP

Abstract

Systems and methods of gaze-based switching of audio components of content streams are disclosed. A first audio/video stream is provided to a first device of a first user. A second audio/video stream is provided to a second device of a second user. Based on determining that the gaze of the second user is directed to a display of the first device, the system pauses the second audio/video stream at the second device and causes an audio portion of the first audio/video stream to be played at the second device. The gaze can be determined by maintaining and modifying a 3D gaze map of an environment indicating the real-time 3D locations of the user and target object of the user's gaze. The 3D gaze map is updated based on cross-referencing video feeds of position data of the user and the target object and of gaze data of the user captured by a plurality of camera devices.

Inventors: Wannerberg; Petter (Lidingö, SE)

Applicant: Adeia Guides Inc. (San Jose, CA)

Family ID: 96880654

Appl. No.: 18/592213

Filed: February 29, 2024

Publication Classification

Int. Cl.: H04N21/442 (20110101); G06T7/70 (20170101); H04N21/43 (20110101);
H04N21/4363 (20110101); H04N21/4415 (20110101)

U.S. Cl.:

CPC H04N21/44218 (20130101); G06T7/70 (20170101); H04N21/43076 (20200801);
H04N21/43637 (20130101); H04N21/4415 (20130101); G06T2207/10016 (20130101);

Background/Summary

BACKGROUND

[0001] This disclosure relates to providing multiple media streams to multiple devices and gaze detection.

SUMMARY

[0002] Modern media delivery systems commonly provide multiple media streams to multiple devices in the same environment. For example, such multi-delivery may occur because multiple user devices (e.g., operated by different users) have requested multiple media streams for consumption. In such an environment, the system can, for example, output audio of at least some media via headphones while video is being provided to respective displays of personal devices, e.g., to mitigate sound interference that would otherwise result from multiple devices simultaneously playing audio via speakers. Sometimes, in such a scenario, a first user wants to peek into a device of another user. As a result, the first user could see the video on the screen of the second user's device but not receive the accompanying audio which is being output to headphones connected to the second user's device. The system can output the accompanying audio via a speaker such that the first user can hear it, but this results in sound interference with audio of other media that is already playing on other personal devices in the environment.

[0003] In one approach, while the audio/video stream is sent to the second user's device, a copy of the audio/video stream is also sent to the first user. For instance, the copy may be transmitted by way of sending a hyperlink or audio/video file to the first user's device. However, creating and transmitting duplicate copies of the same content stream results in wasted resources, including consuming bandwidth. A server may expend resources to replicate the audio/video file, which may be large in size. The server would then need to combine, mix, and encode the same audio/video file multiple times. Transmission of these duplicated streams over the wireless network to multiple computing devices consumes bandwidth on the network, which can also compromise resolution of each stream. Sending the copies to multiple computing devices consumes storage in each of those devices and requires each device to decode the stream, thereby consuming bandwidth and processing power of each device.

[0004] In one approach, the first user can borrow the second user's headphones or temporarily connect the first user's own headphones with the second user's smartphone. However, switching and connecting back and forth between devices is cumbersome, delays playback of the media, and may also require the second user to manually pause the video before and after switching devices and to manually synchronize playback when the devices are temporarily switched. Constantly switching and connecting between devices can also increase the risk of errors with toggling between the multiple headphones to the same smartphone (e.g., audio output to one user's headphones fails, or the audio output is directed to the wrong headphones) and retransmission errors, which can cause the multiple connected headphones to underperform. Moreover, it deprives the second user the ability to hear the audio when both users are watching the video together on the second user's smartphone screen.

[0005] To solve these problems, systems and methods described are provided herein for modifying delivery of audio portions of media streams based on detected user gaze. In some approaches, a media application is provided for modifying the delivery of the audio portions. The media application may be executed at least in part at one or more remote or local servers (e.g., a content provider server which combines, encodes, and distributes the audio portions, or a cloud application), computing devices (e.g., mobile devices or headphones which receive the media

streams and/or audio portion of the media streams), a central audio media source device connected to the same Wi-Fi network as the computing devices (e.g., a smart TV or home theater PC through which all audio media flows and which distributes audio to the computing devices), and/or at or distributed across any one or more other suitable computing devices, in communication over any suitable type of network (e.g., the Internet, local wireless network, cloud-based service).

[0006] In some embodiments, the media application determines that a first audio/video stream is provided to a first device of a first user and that a second audio/video stream is provided to a second device of a second user. In some approaches, the media application determines that the gaze of the second user is directed to the display of the first device. Based on this determination, the media application pauses the second audio/video stream at the second device and causes an audio portion of the first audio/video stream to be played by the second device.

[0007] In some embodiments, the first device and second device may be connected to the same wireless network. In some embodiments, the media application pauses the second audio/video stream at the second device by: identifying the second audio/video stream provided to the second device via the wireless network based on the metadata of the stream, and temporarily preventing delivery of the stream to the second device via the wireless network.

[0008] In some embodiments, the media application causes the audio portion of the first audio/video stream to be played by the second device by: receiving the first audio/video stream over the wireless network; identifying the stream being provided to the first device via the wireless network based on the metadata of the stream; decoding the audio portion of the stream; combining and encoding the audio portion of the stream; and distributing, over the wireless network, the audio portion of the stream to the second device.

[0009] In some embodiments, when the media application (e.g., by way of a camera) no longer detects the gaze of the second user on the first device, the media application terminates the audio portion of the first audio/video stream to the second device over the wireless network. The media application then resumes delivery of the second audio/video stream to the second device over the wireless network.

[0010] In some embodiments, the media application determines the gaze of the second user by maintaining a 3D map of the environment. The 3D map may indicate respective 3D locations of multiple camera devices in the environment. The media application may analyze first video data from the multiple camera devices to identify a 3D location of the second user in the environment and a 3D location of the first device in the environment. The media application updates the 3D map of the environment indicating the 3D location of the second user and the 3D location of the first device. The media application may analyze second video data from the multiple devices in combination with cross-referencing the updated 3D map to determine that the gaze of the second user is directed at the first device.

[0011] A benefit of the described systems and methods includes saved resources and lowered costs by avoiding replication of the video stream and distribution of multiple copies across a network to multiple computing devices. By modifying delivery of audio portions of the media streams, a server would not need to expend resources to duplicate the video stream or combine, mix, and encode such copies. Avoiding replication of the video stream eliminates transmission of duplicate video streams which results in less data being distributed across the wireless network, thereby freeing up bandwidth on the network. The saved bandwidth also allows the server to provide a single video stream in higher resolution. Eliminating transmission of duplicate video streams to multiple computing devices saves storage on the computing devices, and further removes the need for the computing devices to expend bandwidth and processing power to decode the video streams.

[0012] Gaze detection systems are commonly used to identify the object of the user's gaze, such as to determine that the user is looking at a display of a computing device. Such gaze detection systems may employ, for example, eye tracking techniques to determine the gaze of the user. However, accuracy in gaze detection systems can be compromised due to various factors. For

example, the accuracy of gaze estimation decreases when the focal point of the user's gaze is out of range of a gaze tracking device (e.g., the user's eyes are looking away from, or beyond a certain distance of the camera of a tracking device). When the user's gaze is out of range of the gaze tracking device, the gaze tracking device can lose track of the user's eye movements and is unable to determine where the user's gaze is landing. Gaze detection accuracy can also be compromised when the position of the target of the user's gaze is dynamic and/or when the position of the device capturing the user's eye movement data is itself dynamic. For instance, it is difficult to determine where the user's gaze is landing when the user is looking at a moving target or if the gaze tracking device itself is moving. Moreover, it is important to get accurate location data of the user and the target of the gaze in order to triangulate the user's gaze.

[0013] In one approach, multiple cameras can be installed in every room and from numerous positions in an environment to track the user's gaze when the user is in various locations. However, installing numerous camera equipment and their maintenance is expensive. The excessive video streams consume storage on the server and/or computing devices. Each computing device must also expend processing power to decode, analyze, and select which video stream includes relevant data for tracking the user's gaze.

[0014] In one approach, every tracking device may be configured with a multitude of sensors, such as inertial sensors, optical sensors, lidar, sonar, or positioning systems, for collecting accurate location data of the user and the tracking device for triangulating the user's gaze. However, installation of extra sensor equipment is costly. Moreover, more processing power is needed to support the multiple tracking devices to perform positioning calculations, such as Simultaneous Localization and Mapping (SLAM) calculations.

[0015] To solve these problems, systems and methods are provided herein for modifying a 3D map of an environment with user gaze data. In some approaches, a gaze mapping application is provided for modifying the 3D map of the environment with user gaze data. The gaze mapping application may be executed at least in part at one or more remote or local servers, computing devices or camera devices (e.g., an eye tracking device or a mobile or smart device connected to a camera), and/or at or distributed across any one or more other suitable computing devices, in communication over any suitable type of network (e.g., the Internet or local wireless network). In some embodiments, the media application comprises the gaze mapping application. In some embodiments, the gaze mapping application is executed together with the media application (e.g., at a central audio media source device connected to the same Wi-Fi network as the computing devices, such as a smart TV or home theater PC).

[0016] In some embodiments, the 3D map indicates 3D locations of a plurality of camera devices in the environment. Each camera device can capture video data of the environment. The gaze mapping application can analyze first video data captured from the camera devices to identify (a) a 3D location of the user in the environment and (b) a 3D location of a mobile device in the environment. The gaze mapping application may update the 3D map to include the 3D locations of the user and of the mobile device. The gaze mapping application may analyze second video data captured from the camera devices in combination with cross-referencing the updated 3D map, to determine that the user's gaze is directed to a display of the mobile device. Based on determining the gaze, the gaze mapping application may cause the mobile device to perform an action. In some embodiments, such action can include playing media content, sharing media content, causing a second device to play media content which is already playing on the mobile device, playing media content on the mobile device which is already playing on the second device, or activating a household appliance.

[0017] In some embodiments, the mobile device is capable of capturing video data of the environment. In some embodiments, the gaze mapping application analyzes the second video data in combination with cross-referencing the updated 3D map by: receiving, from each camera device and the mobile device, eye movement data and/or head position data of the user; projecting a line

of sight of the user based on cross-referencing such data from each device and using the updated 3D map; and triangulating the gaze of the user based on the cross-referenced line of sight in the updated 3D map.

[0018] In some embodiments, the 3D map of the environment comprises a plurality of reference meshes, wherein at least one of the reference meshes corresponds to the mobile device. The gaze mapping application can determine that the gaze of the user is on the mobile device based on determining a focal point of the triangulated gaze of the user, and determining a collision of the focal point with the reference mesh corresponding to the mobile device.

[0019] In some embodiments, the 3D location of the user in the environment may be a blind spot, wherein no camera devices are present. The gaze mapping application can determine a blind spot based on determining a previous 3D location of the user based on a most recent trigger of a collision volume corresponding to a particular 3D location of a reference mesh in the environment and a second 3D location which the user is not located in based on non-triggering of a second collision volume corresponding to the second 3D location. The gaze mapping application may estimate a trajectory of the user based on a first duration that the user was at the previous 3D location and a second duration that the user was not located in the second 3D location. The gaze mapping application may triangulate the gaze of the user located in the blind spot based on: calculating a geometry of the blind spot with respect to the 3D map of the environment; projecting a line of sight from the user in the blind spot based on the calculated geometry of the blind spot and the estimated trajectory of the user; and determining a collision between the projected line of sight with a reference mesh corresponding to the mobile device.

[0020] A benefit of the described systems and methods includes eliminating the need to install additional eye tracking equipment by utilizing existing camera devices already in the environment for collecting accurate user location data and device location data. This results in conserving energy otherwise needed to operate such equipment. This also conserves network resources, such as storage and bandwidth, otherwise needed to store, process, and transfer data (e.g., video streams) from each equipment and to analyze which data from the multitude of camera devices includes relevant data for gaze calculation.

[0021] Another benefit includes eliminating the need to reposition tracking devices to capture a user's dynamic gaze (e.g., where the user changes position or the gaze target changes position) by cross-referencing position data of the user and of the gaze target captured by multiple existing devices in the environment. This allows for real-time detection of a user's dynamic gaze, thereby avoiding gaze calculation delays due to continuously reconfiguring the tracking devices each time they are repositioned. This also increases accuracy of the gaze calculation when the user's position and/or the position of the gaze target is dynamic.

[0022] Yet another benefit includes accurately triangulating the user's gaze when the user is in a blind spot by cross-referencing user position data and gaze target position data between existing camera devices in a nearby environment. This also eliminates the need to install additional tracking equipment or reposition and reconfiguring them, thereby conserving energy for operating and processing data of such additional equipment and reducing delays in real-time dynamic gaze calculations.

Description

BRIEF DESCRIPTION OF THE FIGURES

[0023] The present disclosure, in accordance with one or more various embodiments, is described in detail with reference to the following Figures. The drawings are provided for purposes of illustration only and merely depict typical or example embodiments. These drawings are provided to facilitate an understanding of the concepts disclosed herein and should not be considered

limiting of the breadth, scope, or applicability of these concepts. It should be noted that for clarity and ease of illustration, these drawings are not necessarily made to scale.

[0024] FIGS. **1A** and **1B** show an example scenario of a using a system for gaze-based audio switching, in accordance with various embodiments of this disclosure;

[0025] FIG. **2** shows an example network architecture for providing a system for gaze-based audio switching, in accordance with various embodiments of this disclosure;

[0026] FIG. **2** shows an example system of providing an immersive virtual experience in autonomous vehicles in self-driving mode, in accordance with various embodiments of this disclosure;

[0027] FIGS. **3A-3E** show an example scenario of maintaining and modifying a 3D map of an environment for triangulating a gaze of a user, in accordance with various embodiments of the disclosure;

[0028] FIG. **4** shows an example of maintaining and modifying a 3D map of an environment for triangulating a plurality of gazes of a plurality of users, in accordance with various embodiments of the disclosure;

[0029] FIGS. **5A** and **5B** show example techniques for cross-referencing video data from a plurality of camera devices to determine a position of a user and/or position of a target object and/or line of sight of the user, in accordance with various embodiments of the disclosure;

[0030] FIGS. **6A** and **6B** show an example scenario of estimating a gaze of a user when position of the user is in a blind spot, in accordance with various embodiments of the disclosure;

[0031] FIG. **7** shows an illustrative user equipment device, in accordance with some embodiments of this disclosure;

[0032] FIG. **8** shows an illustrative system, in accordance with some embodiments of this disclosure;

[0033] FIG. **9** is a flowchart of a detailed illustrative process for switching audio based on gaze, in accordance with various embodiments of the disclosure;

[0034] FIG. **10** is a flowchart of a detailed illustrative process using face recognition to determine audio switching, in accordance with various embodiments of the disclosure;

[0035] FIG. **11** is flowchart of another detailed illustrative process using face recognition to determine audio switching, in accordance with various embodiments of the disclosure;

[0036] FIG. **12** is a flowchart of a detailed illustrative process for triangulating dynamic gaze of a user, in accordance with various embodiments of the disclosure; and

[0037] FIG. **13** is a flowchart of another detailed illustrative process for triangulating dynamic gaze of a user, in accordance with various embodiments of the disclosure.

DETAILED DESCRIPTION

[0038] FIGS. **1A** and **1B** show an example scenario **100** of a using a system for gaze-based audio switching, in accordance with various embodiments of this disclosure. In some embodiments, a media content server provides content streams (also referred to as media streams) to various client devices that are in the same environment. In some alternative embodiments, each of a plurality of media content servers provides content streams to the various client devices that are within the same environment. For example, client devices, such as user devices **113**, **114**, may each include any one of smartphones, tablets, laptops or notebooks, smart televisions, gaming consoles, smart speakers, wearable devices, digital cameras, extended reality (XR) devices (e.g., virtual reality (VR) headsets or augmented reality (AR) glasses), or other computing devices suitable for consuming media content. In some embodiments, the first user device **113** and second user device **114** are located within the same environment when they are in the same physical space. For example, the positions of each user device **113**, **114** may be within a particular distance of each other. For example, users **101** and **102** and their respective devices are within a common boundary of an environment, such as sitting together in the living room or riding in the same vehicle. In some embodiments, the various client devices within an environment are connected to the same network.

For instance, user devices **113** and **114** may be connected to the same local Wi-Fi network (e.g., by way of networking device **150**) or other suitable local area network (e.g., LAN).

[0039] In some embodiments, content server **160** (e.g., “WeTube”) provides a first media stream **121** (e.g., an audio/video (AV) stream of “What Does the Fox Say,” by Ylvis) by way of networking device **150** to the first user device **113** associated with a first user **101** (e.g., Max's tablet). Meanwhile, content server **161** (e.g., “Placify”) provides a second media stream **122** (e.g., an AV stream of “Let It Be,” by the Beatles) by way of networking device **150** to second user device **114** associated with a second user **102** (e.g., Amy's tablet). As referred to herein, the terms “media,” “media asset,” and “content” may be understood to mean electronically consumable user assets, such as audio/visual content, television programming, as well as pay-per-view programs, on-demand programs (as in video-on-demand (VOD) systems), live content, Internet content (e.g., streaming content, downloadable content, Webcasts, etc.), video clips, audio, content information, pictures, GIFs, rotating images, documents, playlists, websites, articles, books, electronic books, blogs, advertisements, chat sessions, social media, applications, games, XR content, 3D content and/or any other media or multimedia and/or combination of the same. As referred to herein, the term “multimedia” should be understood to mean content that utilizes at least two different content forms described above, for example, text, audio, images, video, or interactivity content forms. Content may be recorded, played, transmitted to, processed, displayed and/or accessed by a computing device, and/or can be part of a live performance or live event. In some embodiments, the media asset is generated for display from a broadcast or stream received at a computing device, or from a recording stored in a memory of the computing device and/or a remote server.

[0040] In some embodiments, the first user device **113** is communicatively connected to a first audio device **111** associated with the first user **101**, and the first user device **113** routes the audio portion of the first media stream **121** to the first audio device **111**. For instance, Max (e.g. first user **101**) may watch the video stream of “What Does the Fox Say” on his tablet (e.g., first user device **121**) while listening to the audio portion of the video stream by way of his headphones (e.g., first audio device **111**). In addition to, or alternatively, in some embodiments, the second user device **114** is communicatively connected to a second audio device **112** of the second user **102**, and the second user device **122** routes the audio portion of the second media stream **122** to the second audio device **112**. For instance, Amy (e.g., second user **102**) watches the video stream of “Let It Be” on her tablet (e.g., second user device **114**) while listening to the audio portion of the video by way of her headphones (e.g., second audio device **112**).

[0041] In some approaches, a media application is provided for modifying delivery of the audio portions of the media streams to the user devices and/or associated devices. In some embodiments, the media application is executed at least in part at one or more remote or local servers (e.g., a content provider server which combines, encodes, and distributes the audio portions, such as media content source **802** or server **804** of FIG. **8**), and/or at database **805** of FIG. **8**, and/or computing devices (e.g., mobile devices or headphones which receive the media streams and/or audio portion of the media streams, such as user devices **113**, **114**, audio devices **111**, **112**, or computing device **700**, **701** of FIG. **7**, or user equipment **807**, **808**, **810** of FIG. **8**), and/or a central audio media source device connected to the same Wi-Fi network as the computing devices (e.g., a smart TV or home theater PC through which all audio media flows and which distributes audio to the computing devices, such as smart TV **222** of FIG. **2**), and/or at or distributed across any one or more other suitable computing devices, in communication over any suitable type of network (e.g., the Internet or local wireless network such as a LAN associated with networking device **150** or communication network **809** of FIG. **8**). For instance, networking device **150** may comprise a router, modem-router or gateway, wireless access point, or any other suitable network device.

[0042] In some embodiments, at step **1** of FIG. **1A**, the media application detects that the first media stream **121** (e.g., video of “What Does the Fox Say,” by Ylvis) is being provided on the local wireless network (e.g., by way of networking device **150**) to the first user device **113** (e.g., Max's

tablet). At step 2 of FIG. 1A, the media application also detects that the second media stream **122** (e.g., video of “Let it Be,” by The Beatles) is being provided on the same local wireless network (e.g., by way of networking device **150**) to the second user device **114** (e.g., Amy's tablet). The media application determines the source and destination of each media stream **121**, **122** based on metadata associated with the respective media streams. Additionally, or alternatively, the media application determines the source and destination of each media stream **121**, **122** by communicating directly with each content server **160**, **161**. Additionally, or alternatively, the media application identifies or monitors the media streams **121**, **122** received or playing at each user device **113**, **114**, respectively.

[0043] In some embodiments, the media application monitors the gaze of each user and identifies the target object, such as computing device (or a target portion thereof) of each respective gaze at a given time. At step 3 of FIG. 1A, the media application identifies the second user **102** and determines that the gaze **130** of the second user **102** is directed at the display of the first user device **113**. For example, Amy (e.g., second user **102**) may be watching “Let It Be” (e.g., the second media stream **122**) on the display of her tablet (e.g., second user device **114**), and then shift her gaze **130** to peek at the display of Max's tablet (e.g., first user device **113**) and temporarily watch “What Does the Fox Say?” (e.g., the first media stream **121**). The media application may identify the second user **102** and her associated devices **114**, **112**, based on, for instance, user profile data, metadata associated with media stream **122**, face recognition (discussed in further detail in FIGS. **10** and **11**), or using a modified 3D map of the environment based on cross-referenced video data of the user from a plurality of camera devices (discussed in further detail in FIGS. 3A-3E). The media application determines gaze **130** of the identified second user **102** based on eye tracking data of the second user **102**, received by way of various camera devices in the environment. Such various camera devices may include, for instance, user devices **113**, **114** and networking device **150** which are communicatively connected with and/or integrated with cameras **141**, **140**, **142**, respectively, and/or other suitable devices with image or video capturing capabilities. Capturing eye tracking data may include measuring and recording the movements and positions of the eyes of the user. Eye tracking data may comprise the direction, velocity, and duration of eye movements, as well as the position of the pupil and the corneal reflection. Cameras **140**, **141**, **142** may also include specialized sensors which track the eye movements of users. Camera devices **140**, **141**, **142** may also be integrated with IR (infrared) illuminators, which allow the camera devices **140**, **141**, **142** to capture eye tracking data of a user under any lighting condition.

[0044] In some embodiments, the media application analyzes the eye tracking data (e.g., captured eye movements) to precisely determine the gaze of a user and other information relating to how a user's eyes move (e.g., user's eye movement patterns). Gaze refers to the specific direction or point in space at which a user is looking. The media application estimates gaze **130** of the second user **102** utilizing gaze estimation algorithms and/or eye tracking machine learning models to interpret the eye tracking data and calculate the estimated gaze vector and/or estimated gaze point. The gaze vector is also referred to as the line of sight or sight line of the user. The gaze point comprises a 3D point in space indicated by the gaze vector (e.g., terminal point of the gaze vector).

[0045] Additionally, or alternatively, in some embodiments, the media application determines gaze **130** based on glint tracking data. For example, camera devices **140**, **141**, **142** may track, in addition to the iris and/or the whites of the eye, the lighting glints on the eyeball from the ambient light in the environment. The media application cross-references glint tracking data with eye movement data to increase the accuracy of gaze estimation, such as when many parts of the user's eyes are obscured, if the user's eyes are turned away from or are far away from (e.g., beyond a particular distance of) the view of the camera device, or if the eyes are not illuminated by IR.

[0046] Additionally, or alternatively, in some embodiments, the media application determines gaze **130** based on head gaze data. Head gaze data includes head position in relation to the camera. Additionally, or alternatively, in some approaches, media application estimates the user's gaze by

combining head gaze data and eye tracking data. The media application further uses the combined head gaze and eye tracking data to determine the possible gaze point candidates that can be eliminated. For example, a user's head may be directed toward one direction while the user's eyes are focused in another direction or focused on a different target object than head gaze data would otherwise indicate on its own. The media application further uses the head gaze data to distinguish between possible target objects of the user's gaze. For example, multipole objects may be possible target objects of the user's gaze because they are close to each other within a degree of angle that is below a certain value.

[0047] Additionally, or alternatively, the media application determines the gaze of each user using a modified 3D gaze map of the environment indicating the gaze of each user in real-time, discussed in further detail in FIGS. 3A-3E.

[0048] In some approaches, at step 4 of FIG. 1B, the media application modifies delivery of the audio portions associated with the media streams 121, 122 such that the audio portion transmitted to the device(s) associated with each user matches the visual content displayed on the target object of the user's gaze. The media application determines which audio portion to deliver to which device based on determining the current gaze of each user and identifying the respective device(s) associated with each user. Additionally, or alternatively, the media application determines which audio portion to deliver to which device based on the respective real-time gaze of each user as indicated by way of the modified 3D gaze map of the environment based on cross-referencing positioning data and gaze data from multiple camera devices (discussed in further detail in FIGS. 3A-3E). For example, when the media application detects that the second user 102 peeks at the first user device 113 to watch the first media stream 121, media application may identify the content playing at the device of the second user's 102 gaze 130 (e.g., the first media stream 121). The media application may modify delivery of the audio and/or video streams such that the second user 102 can also hear the accompanying audio of the first media stream 121 on her audio device 112. For example, when media application detects that the second user 102 returns her gaze to her own second device 114 to resume watching the second media stream 122, media application may identify the content playing at the device of the second user's 102 current or updated gaze (e.g., the second media stream 122). The media application may redistribute audio and/or streams such that the second user 102 can hear the accompanying audio of the second media stream 122.

[0049] In some embodiments, at step 5 of FIG. 1B, the media application determines that the first user 101 continues to direct his gaze at his own first user device 113. The media application identifies that the current content playing on the first user device 113 is media stream 121 (e.g., "What Does the Fox Say?") based on various data, such as metadata associated with the media stream 121 and/or by monitoring activity of first user device 113. Based on these determinations, media application (or content server 160) continues to facilitate delivery of the first media stream 121 (e.g., "What Does the Fox Say?") to the first user device 113 of first user 101 over the wireless network. The media application also continues delivering accompanying audio (e.g., music associated with "What Does the Fox Say?") to the first audio device 111.

[0050] In some approaches, at step 6 of FIG. 1B, the media application pauses delivery of the second media stream 122 (e.g., "Let It Be" video) at the second user device 114. Additionally, the media application pauses delivery of the audio portion of the second media stream 122 (e.g., music associated with "Let It Be") at the second audio device 112. In some alternative approaches, the media application continues to deliver the second media stream 122 at the second user device 114 but dampens (e.g., lowers or mutes) the volume of the audio component of the second media stream 122 at the second audio device 112.

[0051] In some embodiments, at step 7 of FIG. 1B, the media application delivers the audio portion of the first media stream 121 (e.g., music associated with "What Does the Fox Say?") to the second audio device 112. In some alternative embodiments, the media application sends a request to the content server 160 for a replicate of the audio portion of the first media stream 121. Media

application then distributes one copy of the audio portion of the first media stream **121** to the first user **101** at the first audio device **111** and another copy of the audio portion of the first media stream **121** but distributes a single video stream of the first media stream to the first user device **113**.

[0052] In some embodiments, the media application determines that the gaze of the first user **101** is not directed to a display of any device. Based on the determining, the media application continues delivery of the audio portion of the first media stream **121** to the first user device **113** over the wireless network. For example, the first user **101** may temporarily angle the first user device **113** toward the second user **102**, such that the second user **102** can peek at the first media stream **121** and momentarily watch “What Does the Fox Say?” The media application may continue to route the audio portion of “What Does the Fox Say?” to the first user **101** at the first audio device **111** while simultaneously delivering a copy of that audio portion to the second user **102** at the second audio device **112**, despite the first user **101** not currently gazing at the display of his own first user device **113**. In some embodiments, the media application synchronizes the distribution of the audio portion of the first media stream **121** to each user device **113**, **114**. This allows both users **101**, **102** to watch and listen to the same content at the same time with each other.

[0053] In some approaches, the media application detects that the gaze **130** of the second user **102** is no longer directed to the first user device **113** and/or the gaze **130** is redirected to the second user device **114**. Based on the detection, the media application terminates delivery of the audio portion of the first media stream **121** at the second audio device **112**. The media application resumes delivering the second media stream **122** to the second user device **114** and resumes delivering the audio portion of the second media stream **122** to the second audio device **112** over the wireless network.

[0054] FIG. 2 shows an example network architecture for providing a system for gaze-based audio switching, in accordance with various embodiments of this disclosure. In some embodiments, user devices **113**, **114** are connected to the same local wireless network by way of networking device **150**. Additionally, or alternatively, in some embodiments, user devices **113**, **114** are connected with a common cloud application, such as the media application by way of a common cloud service. Additionally, or alternatively, in some embodiments, user devices **113**, **114** are connected with a common multimedia device such as smart TV **222**, on which the media application is executed.

[0055] In some embodiments, the media application, for example, by way of smart TV **222**, facilitates all audio media flows and distributes content streams and associated audio portions between content servers and each user device **113**, **114** and common multimedia devices (e.g., smart TV **222** and speaker **220** which is communicatively connected with smart TV **222**).

[0056] In some implementations, the media application receives content stream information that is played at each user device **113**, **114**. For example, each user device **113**, **114** may provide to media application metadata associated with the content stream currently playing on each user device. For example, each user device **113**, **114** may forward the entire stream package or the decoded audio portion thereof to the media application. For example, media application may communicate directly with content servers which are transmitting the streams to the user devices **113**, **114** over the local wireless network or collect the stream information when it arrives at the local wireless network.

[0057] In some implementations, the media application receives various data **230** from each camera device in the environment to determine the gaze of each user. For example, the various data **230** may comprise at least one of approximate 3D position of each user **101**, **102** in the environment, head direction of each user, or gaze data (e.g., eye tracking data, glint data). For example, the media application may receive eye tracking data of each user in the environment from various devices which capture video feed of the users. For example, each user device **113**, **114** may be integrated with camera functionality and/or sensors to capture head position and/or eye tracking data of users **101**, **102**, respectively. For example, smart TV **222** may also be integrated with camera functionality and capture head position and/or eye tracking data of user **101**, **102**.

Additionally, or alternatively, in some implementations, the media application receives face recognition data of each user.

[0058] In some implementations, the media application merges the eye tracking data of the plurality of video feeds received from user devices **113**, **114**, and smart TV **222**. For example, the media application may cross-reference the user position data and eye tracking data from the various video feeds to estimate the gaze of each user. For example, the media application may separately estimate the gaze of each user from the user position data and eye tracking data from each of the various video feeds and cross-reference the gaze estimations to project an accurate line of sight (e.g., gaze vector) and/or gaze point of each user **101**, **102**. Memory **234** stores the estimated gaze data **232**. Additionally, memory **234** stores any user rulesets or user profiles (e.g., indicating user preferences) for management of audio portions of content streams based on the respective user's gaze. For example, a ruleset may define that the audio portion delivered to a user should match the video portion of the content stream that is displayed at the gaze point (e.g., target) of the user's gaze.

[0059] In some implementations, the media application determines a modified audio distribution **236** based on the gaze data and using user device data to identify and locate the appropriate destinations for the modified audio distribution. A decoder **238** decodes the audio portions of the appropriate streams. A mixer **240** mixes and combines the audio portions of the streams. Media application, by way of an audio distributor **242**, modifies the metadata of each of the audio portions streams such that one of the audio portion streams is directed to user device **113** and the other is directed to user device **114**. For example, the media application may request a second copy of the audio portion of the first media stream **121** from content server **160**, decode, mix, and combine the audio portion copies, and distribute the audio portion (e.g., the audio of “What Does the Fox Say?”) to each user **101**, **102**. For example, the first user device **113** may decode and send the audio portion of the first media stream **121** directly to the media application, and the media application may mix, combine, and deliver the audio portion to the second user device **114**.

[0060] In some embodiments, the media application modifies the audio delivered to the various devices based on gaze, by adjusting the sound levels of the audio sources. For example, the media application may tag (e.g., with a “music” tag) each audio source (e.g., speaker **220**, first audio device **111** associated with first user **101**, second audio device **112** associated with second user **102**) when it is playing audio. If second user **102**, while listening to a first music stream on her headphones (e.g., second audio device **112**), directs her gaze toward smart TV **222** (and/or associated speakers **220**) which is playing a second music stream, media application may determine based on her gaze and the current content on her headphones that the “music” tag associated with her headphones conflict with the “music” tag of the speakers **220**. Based on a user ruleset associated with the user **102**, media application may dampen (e.g., lower or mute) the volume of the music playing through the second audio device **112** while increasing the volume of the music playing through speakers **220** for as long as the second user's **102** gaze remains on the smart TV **222** and/or speakers **220**. Additionally, media application may display on second user device **114** information associated with the music playing from the speakers **220** for a period of time after the second user **102** returns her gaze to the second user device **114**. Example systems and methods that may be implemented to control and modify audio sources in a room are described in greater detail in connection with Phillips, “Field Of Vision Audio Control For Physical Or Mix Of Physical And Extended Reality Media Displays In A Spatially Mapped Space,” patent application Ser. No. 17/949,842, filed Sep. 21, 2022, which is hereby incorporated by reference herein in its entirety.

[0061] FIGS. 3A-3E show an example scenario **300** of maintaining and modifying a 3D map **350** of an environment (e.g., living room **301**) for triangulating a gaze of a user, in accordance with various embodiments of the disclosure. In some approaches, a gaze mapping application is provided for maintaining and modifying the 3D map **350** of the environment with real-time user gaze data. The gaze mapping application may be executed at least in part at one or more remote or

local servers (e.g., server **805** of FIG. **8**) and/or at database **805** of FIG. **8**, and/or computing devices or any suitable camera devices (e.g., an eye tracking device or a mobile or smart device connected to a camera, such as virtual assistant **316** integrated with camera **318**, smart TV **312** integrated with camera **314**, mobile device **320** integrated with camera **322**, user devices **113**, **114** of FIG. **1**, smart TV **222** of FIG. **2**, computing device **700**, **701** of FIG. **7**, or user equipment **807**, **808**, **810** of FIG. **8**), and/or at or distributed across any one or more other suitable computing devices, in communication over any suitable type of network (e.g., the Internet or local wireless network such as a LAN associated with networking device **150** or communication network **809** of FIG. **8**). In some embodiments, the media application comprises the gaze mapping application. In some embodiments, the gaze mapping application is executed together with the media application (e.g., at a central audio media source device connected to the same Wi-Fi network as the computing devices, such as smart TV **312** or a home theater PC).

[0062] In some embodiments, at step **1** of FIG. **3A**, the gaze mapping application maintains an original 3D map **350** of the living room **301**. The original 3D map **350** comprises a static 3D map of polygons (also referred to as reference mesh or 3D mesh) representing objects within the environment (e.g., a digital copy of the living room **301**) and which indicates the 3D location of such objects. The original 3D map **350** includes digital representations of camera devices (e.g., home assistant **316** integrated with camera **318**, smart TV **312** integrated with camera **314**) and static points of interest or static objects (e.g., sofa **310**). For example, gaze mapping application may generate and provide the original 3D map **350** by way of various techniques, such as using LIDAR enabled devices, creating a CAD (Computer Aided Design) scan of the home, extrapolating 3D images from autonomous devices (e.g., robotic vacuum cleaners, home alarm systems with scanning capabilities). The objects and/or various points of interest (e.g., including 3D points in space) are represented as collision geometries (also referred to as collision volumes or collision boxes). Database **805** of FIG. **8**, or other suitable memory or storage, stores and/or records updates to the 3D map **350**.

[0063] In some embodiments, the gaze mapping application determines the real-time 3D position of dynamic objects and subjects in the living room **301** by cross-referencing position data of such objects and subjects from a plurality of sources (e.g., a first set of video feeds from a plurality of camera devices). For example, the positions of user **330** (e.g., which corresponds to second user **102** of FIGS. **1A** and **1B**) and mobile device **320** (e.g., which corresponds to first user device **113** of FIGS. **1A** and **1B**) within the living room **301** change over time. For example, home assistant **316** (e.g., communicatively connected with or integrated with camera **318**) and smart TV (e.g., communicatively connected with or integrated with camera **314**) may capture video feeds of various objects or subjects in the environment. Cameras **314**, **318** may also be equipped with various sensors, such as those with face recognition capabilities, IR illumination, eye tracking, or face and head gaze tracking capabilities, to capture other positional or image data of the objects or subjects. At step **2** of FIG. **3B**, home assistant **316** (e.g., by way of camera **318**) collects video data on the 3D locations of user **330** and mobile device **320**. Additionally, at step **3** of FIG. **3B**, smart TV **312** (e.g., by way of camera **314**) collects video data on the 3D location of user **330** and mobile device **320**. The gaze mapping application cross-references the user **330** position data from the video feed captured by home assistant **316** with the user **330** position data from the video feed captured by smart TV **312** to determine an accurate, current 3D position of the user **330**. The gaze mapping application also cross-references the mobile device **320** position data from the video feed captured by home assistant **316** with the mobile device **320** position data from the video feed captured by smart TV **312** to determine an accurate, current 3D position of the mobile device **320**. By cross-referencing an increasing number of sources of positional data of the same object or subject, gaze mapping application can calculate the real-time 3D position of the object or subject with increased accuracy. Further, sharing and cross-referencing such data results in off-device processing of heavy computational tasks of calculating real-time positions of multiple objects or

subjects in an environment.

[0064] In some additional embodiments, the gaze mapping application tracks and tags the dynamic objects and subjects by applying computer vision algorithms and using neural network models trained on captured image data from the camera devices.

[0065] In some approaches, mobile device **320** also collects position data of itself, which the gaze mapping application cross-references with the position data of the mobile device **320** from the video feeds captured by home assistant **316** and by smart TV **312**. For example, mobile device **320** may be equipped with camera capabilities, inertial systems (e.g., which can track gimbal rotation in X, Y, Z coordinates as well as translation movement X, Y, Z by way of accelerometers), LIDAR, or other equipment suitable for capturing self-positioning data.

[0066] In some approaches, mobile device **320** also collects position data of user **330** by capturing video feed of the user **330** by way of camera **322**. The gaze mapping application then cross-references the position data of the user **330** from three sources (e.g., home assistant **316**, smart TV **312**, and mobile device **320**) to calculate the 3D position of the user with increased accuracy.

[0067] In some embodiments, at step **4** of FIG. **3C**, the gaze mapping application updates the 3D map **350** (e.g., resulting in updated 3D map **351**) to include the calculated 3D positions of user **330** and mobile device **320**.

[0068] In some embodiments, the gaze mapping application determines the line of sight **340** (also referred to as the gaze or gaze vector) of the user **330** and triangulates the line of sight **340** to identify the target object (e.g., the mobile device **320** located at the gaze point, also referred to as focal point of the gaze) at which the user **330** is looking.

[0069] In some example approaches, to determine the line of sight **340**, the gaze mapping application projects a line of sight of the user based on cross-referencing gaze data of the user **330** received from a second set of video feeds from multiple sources (e.g., plurality of camera devices). For example, the plurality of camera devices may include home assistant **316** (integrated with camera **318**) and smart TV **312** (integrated with camera **314**). Additionally, the plurality of camera devices may also include the target object of the gaze itself, such as mobile device (integrated with camera **322**). At steps **5-7** of FIG. **3D**, the home assistant **316**, smart TV **312**, and mobile device **320**, respectively, collect video data comprising gaze data (e.g., eye tracking data such as eye movement and/or head position) of the user **330**. At step **8** of FIG. **3D**, the gaze mapping application combines and cross-references the eye tracking data from each camera device with each other to project the user's **330** line of sight. Additionally, in some embodiments, the gaze mapping application projects the line of sight by cross-referencing the combined eye tracking data of the user **330** with the position data cross-referenced from the first set of video feeds captured by the camera device (e.g., position data of the user **330**, position data of the target object such as the mobile device **320**, and/or position data of the camera devices such as home assistant **316**, smart TV **312**, and/or mobile device **320**),

[0070] In some example approaches, to triangulate the line of sight **340** (e.g., to identify the target object of the user's **330** gaze), the gaze mapping application cross-references the projected line of sight **340** with the updated 3D map **351**. The gaze mapping application maintains a database of locations and sizes for objects and subjects, represented as collision volumes, in the updated 3D map **351**. The gaze mapping application determines any collision between the projected line of sight **340** with a collision volume (e.g., corresponding to a reference mesh representation of an object such as mobile device **320**) positioned in the updated 3D map **351**. When the gaze mapping application detects that the collision volume corresponding to the target object (e.g., mobile device **320**) has been triggered, the gaze mapping application identifies the mobile device **320**, at its 3D location in the 3D map **351**, as the object where the user's **330** line of sight **340** lands. The gaze mapping application updates the 3D map **351** to include the current line of sight **340** and/or gaze point of the user **330** from their current 3D position in the 3D map **351**.

[0071] In some implementations, gaze mapping application processes the gaze **340** as user input to

cause a device to perform an action. For example, the device performing the action may include the target object of the gaze (e.g., mobile device **320**), another device associated with the user **330** and/or target object (e.g., headphones **332**), or other suitable computing device, appliance, or smart or IoT device. Gaze mapping application identifies the device for performing the action and the action to perform based on various factors, such as inferring user intent based on user profile information or user activity history with the target object, whether the gaze is directed toward a particular portion of the target object (e.g., a graphical icon on the screen of mobile device **320**), or a ruleset associated with the target device when the gaze **340** is directed at it. At step **9** of FIG. **3D**, based on determining that the gaze **340** of user **330** is directed at the screen of mobile device **320**, gaze mapping application causes the headphones **332** (e.g., which corresponds to second audio device **112** of FIGS. **1A** and **1B**) to play the audio component associated with the content currently playing on mobile device **320**. In some additional embodiments, gaze mapping application causes headphones to play such audio component further based on inferring the user's **330** intent based on contextual rules (e.g., an action is assigned to when the user's **330** current circumstances satisfy a particular set of criteria). For example, because user **330** is currently wearing headphones **332** while gazing at content displayed on mobile device **320**, gaze mapping application may infer that user **330** intends to hear to the audio component of such content.

[0072] Additionally, or alternatively, in some embodiments, gaze mapping application processes other user actions directed at the target object to infer the user's intent for a device to perform an action. For example, gaze mapping application may capture (e.g., by way of sensors and/or cameras **318**, **316**, **322**) the user's **330** gestures, lip reading, or head movements directed toward the mobile device **320**. For example, user **330** may gaze at smart TV **312** and point toward a third user who is wearing headphones in the living room **301**. Gaze mapping application may determine, based on the combination of the user's **330** gaze directed at the smart TV **312** and the user's **330** gesture directed at the third user, that the user **330** intends for the audio component of content playing on the smart TV **312** to be distributed to the third user's headphones. For example, if user **330** directs her gaze at home assistant **316** for over at least a certain period of time while speaking, the gaze mapping application may determine that the user **330** intends to utter a command or query to the home assistant **316**, and may instruct the home assistant to execute such command or query.

[0073] FIG. **4** shows an example **400** of maintaining and modifying a 3D map **401** of an environment for triangulating a plurality of gazes of a plurality of users, in accordance with various embodiments of the disclosure. In some embodiments, gaze mapping application determines the line of sight **431** of user (A) **411** (e.g., directed at speaker **442**) by cross-references a collaboration of video data of user (A) **411** that is captured by multiple camera devices (e.g., smart TV **440**, tablet **421**, phone **422**). Additionally, in some embodiments, gaze mapping application cross-references such video data of user (A)'s **411** presence at a first location (e.g., within the living room) with video data which captures user (A)'s **411** absence from a second location (e.g., within the closet). For example, another processing device **444** located in the closet may capture video feed of the closet area, indicating user (A)'s absence from the closet.

[0074] In some embodiments, the same camera devices (e.g., smart TV **440**, tablet **421**, phone **422**, other processing device **444**) also capture video feed of the user (A)'s eye movements or fail to capture such eye movements within the respective camera device's field of view. Gaze mapping application cross-references such video data of the eye movements to determine what the user (A) **411** is looking at as well as what he is not looking at.

[0075] In some embodiments, the same camera devices (e.g., smart TV **440**, tablet **421**, phone **422**, other processing device **444**) also capture video feed of any object or subject within their field of view, and gaze mapping application cross-references such video feeds to determine the position and line of sight **432** of user (B) **412**, as well as for any other additional user in the environment.

[0076] In some approaches, collision volumes corresponding to certain points of interest are configured in the 3D map **401**. For example, doorway **450** may be configured as a collision

volume. If user (A) **411** triggers the collision volume of doorway **450**, gaze mapping application cross-references such collision data with the time of collision and video feeds from the camera devices indicating where the user (A) **411** is present and where user (A) **411** is not present to determine whether the user (A) **411** has exited the room. In some embodiments, gaze mapping application switches the camera devices of the room to standby mode when it determines that no users are longer in the room or that the users have exited the room.

[0077] FIGS. **5A** and **5B** show examples **500**, **550** techniques, respectively, for cross-referencing video data from a plurality of camera devices to determine a position of a user and/or position of a target object and/or line of sight of the user, in accordance with various embodiments of the disclosure. In some embodiments, in FIG. **5A**, a user **502** is located in environment (e.g., room **501**), represented as a 3D map **520** comprising a static mesh of the room **501** and a plurality of reference meshes representing objects therein (e.g., devices **510**, **512**, **514**). The smart TV **514** (e.g., equipped with camera capabilities) captures first video data of the position of the user **502** and position of mobile phone **510**, as well as second video data of eye movements of the user **502**. Mobile phone **510** captures first video data of the user **502** and inertial sensor data (such as SLAM-based data) of its own position, as well as second video data of eye movements of the user **502**. Virtual assistant **512** captures first video data of the position of the user **502** and position of mobile phone **510**, as well as second video data of eye movements of the user **502**. The gaze mapping application cross-references the position data from these multiple sources to determine the real-time 3D position of the user **502** and 3D position of the mobile device **510** with a certain degree of accuracy. The gaze mapping application also cross-references the eye movement data of the user **502** from the multiple sources as well as the 3D positions of the user **502** and mobile device **510** to estimate, with a certain degree of accuracy, a line of sight **530** of the user **502** and determine that the user **502** is gazing at the mobile device **510**.

[0078] In some embodiments, gaze mapping application assigns collision volumes to various points of interest within the static mesh of 3D map **520**. Gaze mapping application determines the gaze point of the user **502**, based on determining that the line of sight **530** triggered (e.g., collided with) such collision volume.

[0079] In some embodiments, in FIG. **5B**, gaze mapping application culls data from certain camera devices, or deactivates such camera devices, which are unable to capture sufficient data (e.g., due to the field of view, angle, or position of the camera device). For example, gaze mapping application may utilize data from mobile device **510** if the mobile device **510** is able to perform at least one of: (1) capture video feed of anchor object (e.g., known static object) **542** within its view; (2) capture sufficient video data to determine its own 3D position based on the view of the ceiling or walls **540** and/or its data from its internal spatial mapping, LIDAR, or image recognition in combination with cross-referencing the 3D map of room **551**; or (3) user's **502** face is within view of the frustum **530** of the camera of mobile device **510**.

[0080] FIGS. **6A** and **6B** show an example scenario **600** of estimating a gaze of a user when position of the user is in a blind spot, in accordance with various embodiments of the disclosure. For example, a blind spot may comprise a portion or area of an environment which does not have tracking devices (e.g., camera devices) to capture position data or gaze data of a user and/or target object of the user's gaze. In some embodiments, at step **1** of FIG. **6A**, the gaze mapping application determines a previous location of user **330**. For example, position data of the user **330** cross-referenced from home assistant **316**, smart TV **312**, and mobile device **320** may indicate that user **330** was most recently located at sofa **310** in the living room **301**. For example, gaze mapping application may monitor a user's location over time and maintain a ledger of user position history.

[0081] In some embodiments, gaze mapping application sets trigger points within the static mesh of the 3D map of the environment, by setting and activating collision volumes at various points of interest, such as doorway **604**. At step **2** of FIG. **6B**, the gaze mapping application detects that the user **330** triggered the collision volume corresponding to doorway **604**. Based on this detection and

based on the user's **330** previous location in the living room **301**, gaze mapping application determines that the user **330** has exited the living room **301** and entered the corridor **601** (e.g., which may be a blind spot).

[0082] In some embodiments, at step **3** of FIG. **6B**, gaze mapping application determines that the user **330** is not currently located in kitchen **602**, based on cross-referenced video data from a plurality of camera devices **610**, **612** indicating that user **330** is not currently present in kitchen **602**. At step **4** of FIG. **6B**, gaze mapping application estimates a trajectory of the user **330** (and/or a current position of the user **330** based on the estimated trajectory) based at least on the duration the user **330** was located at the previous 3D location (e.g., living room **301**) and the duration that the user **330** was not located at a second 3D location (e.g., kitchen **602**). Additionally, in some embodiments, gaze mapping application estimates the trajectory based on detecting that the user **330** triggered (or did not trigger) a collision volume and the time of the triggering. For example, gaze mapping application may detect that user **330** moved through doorway **604** at a certain time after being present in the living room **301**. For example, gaze mapping application may also calculate that the user **330** did not enter kitchen **602** for a period of time after exiting living room **301** and triggering collision volume at doorway **604**. In some embodiments, gaze mapping application monitors the user's history of trigger and not triggering certain collision volumes, to estimate the user's trajectory and current position. For example, gaze mapping application may project the user's **330** trajectory based on a sequence of triggered and/or untriggered collision volumes over a period of time. Further in some embodiments, the gaze mapping application makes such determination of the user's current position in a blind spot (e.g., corridor **601**) based on eliminating locations where the user is not located (e.g., kitchen **602**), determined based on the user position history and failure to trigger certain collision volumes.

[0083] In some embodiments, at step **5** of FIG. **6B**, gaze mapping application triangulates the gaze **340** of user **330** based on determining the geometry of the blind spot (e.g., corridor **601**) with respect to the 3D map of living room **301**, projecting the line of sight **340** from the user **330** in the blind spot, and determining a collision between the projected line of sight with a reference mesh corresponding to the target object (e.g., mobile device **320**). For example, gaze mapping application may determine, based on determining that the user **330** is currently in the corridor **601** and based on the size, shape, and position of the blind spot in relation to the size, shape, and position of the living room **301**, an estimated position within the corridor **601** where the user **330** is likely to be. In some approaches, gaze mapping application maintains a light of sight heat map, comprising points of interest on the 3D map which are reachable (e.g., viewable by a user) from various positions on the 3D map. For example, if a user is located in a particular space where a given point of interest cannot be seen by the user and/or cannot be captured from a camera device, gaze mapping application removes the point of interest from the list of candidate points of interest in the heat map (e.g., deactivates the collision volume corresponding to that point of interest, thereby saving computing resources and increasing computing efficiency of devices). Based on the user's **330** estimated position within the corridor **601** and the line of sight heat map, gaze mapping application projects a possible line of sight **340** of the user **330** from such position in the corridor **601**. Gaze mapping application then identifies the target object (e.g., mobile device **320**) corresponding to the collision volume in the 3D map with which the projected line of sight **340** collides.

[0084] FIGS. **7-8** depict illustrative devices, systems, servers, and related hardware for switching audio based on gaze and triangulating dynamic gaze of a user, in accordance with some embodiments of this disclosure. FIG. **7** shows generalized embodiments of illustrative user equipment devices **700** and **701**, which may correspond to the above-described user devices (e.g., device **113**, **114**, **316**, **222**, **312**, **320**, **440**, **421**, **422**, **440**, **444**, **510**, **512**, **514**, **610**, **612**). In some embodiments, user equipment device **700**, **701** is a smartphone device, a tablet, smart TV, or any other suitable device capable of processing audio and/or video data, smart assistant device or home

assistant device, a camera device or any other suitable computing device with camera functionality and/or sensors for tracking positions or movements of a subject or object, a network-based server hosting a user-accessible client device, a non-user-owned device, any other suitable device, or any combination thereof. Each of user equipment device **700**, **701** is communicatively connected to at least one of microphone **716**, audio input equipment (e.g., speaker or headphones **714**, which may correspond to audio device **111**, **112**, **220**, **332**, **442**), camera **718** (e.g. which may correspond to camera **140**, **141**, **142**, **314**, **318**, **322**), display circuitry **712**, user input interface circuitry **710**, and sensors **720**. For example, sensors **720** may include eye tracking sensors, IR sensors, IR illuminators, accelerometers, and gyroscopes. For example, display **712** may be a television display or a computer display, a 3D display (such as, for example, a tensor display, a light field display, a volumetric display, a multi-layer display, an LCD display or any other suitable type of display, or any combination thereof). For example, user input interface **710** may be a remote-control device. [0085] In some embodiments, each one of user equipment device **700**, **701** receives content and data via input/output (I/O) path (e.g., circuitry) **702**. I/O path **702** provides content (e.g., broadcast programming, on-demand programming, Internet content, content available over a local area network (LAN) or wide area network (WAN), and/or other content) and data to control circuitry **704**, which comprises processing circuitry **706** and storage **708**. Control circuitry **704** is used to send and receive commands, requests, and other suitable data using I/O path **702**, which comprises I/O circuitry. I/O path **702** connects control circuitry **704** (and specifically processing circuitry **706**) to one or more communications paths (described below). I/O functions may be provided by one or more of these communications paths, but are shown as a single path in FIG. 7 to avoid overcomplicating the drawing.

[0086] Control circuitry **704** may be based on any suitable control circuitry such as processing circuitry **706**. As referred to herein, control circuitry should be understood to mean circuitry based on one or more microprocessors, microcontrollers, digital signal processors, programmable logic devices, field-programmable gate arrays (FPGAs), application-specific integrated circuits (ASICs), etc., and may include a multi-core processor (e.g., dual-core, quad-core, hexa-core, or any suitable number of cores) or supercomputer. In some embodiments, control circuitry may be distributed across multiple separate processors or processing units, for example, multiple of the same type of processing units (e.g., two Intel Core i7 processors) or multiple different processors (e.g., an Intel Core i5 processor and an Intel Core i7 processor). In some embodiments, control circuitry **704** executes instructions for the media application and/or gaze mapping application stored in memory (e.g., storage **708**). Specifically, control circuitry **704** may be instructed by the media application and/or gaze mapping application to perform the functions discussed above and below. In some implementations, processing or actions performed by control circuitry **704** may be based on instructions received from the media application and/or gaze mapping application.

[0087] In some client/server-based embodiments, control circuitry **704** may include communications circuitry suitable for communicating with a server or other networks or servers. The media application and/or gaze mapping application is a stand-alone application implemented on a device or a server. The media application and/or gaze mapping application may be implemented as software or a set of executable instructions. The instructions for performing any of the embodiments discussed herein of the media application and/or gaze mapping application may be encoded on non-transitory computer-readable media (e.g., a hard drive, random-access memory on a DRAM integrated circuit, read-only memory on a BLU-RAY disk, etc.). For example, in FIG. 7, the instructions may be stored in storage **708**, and executed by control circuitry **704** of a device **700**, **701**.

[0088] In some embodiments, the media application and/or gaze mapping application is a client/server application where only the client application resides on device **700** (e.g., device **113**, **114**, **316**, **222**, **312**, **320**, **440**, **421**, **422**, **440**, **444**, **510**, **512**, **514**, **610**, **612**), and a server application resides on an external server (e.g., server **804**, server **160**, server **161**). For example, the media

application and/or gaze mapping application may be implemented partially as a client application on control circuitry **704** of device **700**, **701** and partially on server **804** as a server application running on control circuitry **811**. Server **804** may be a part of a local area network with one or more of devices **700**, **701** or may be part of a cloud computing environment accessed via the internet. In a cloud computing environment, various types of computing services for performing searches on the internet or informational databases, providing encoding/decoding capabilities, providing storage (e.g., for a database) or parsing data (e.g., using machine learning algorithms described above and below) are provided by a collection of network-accessible computing and storage resources (e.g., server **804**), referred to as “the cloud.” Device **700**, **701** may be a cloud client that relies on the cloud computing capabilities from server **804** to receive and process encoded data for 3D media content. When executed by control circuitry of server **804**, the media application and/or gaze mapping application instructs control circuitry **811** to perform processing tasks for the client device and facilitate the gaze-based audio switching and/or dynamic triangulation of the user's gaze.

[0089] Control circuitry **704** may include communications circuitry suitable for communicating with a server, edge computing systems and devices, a table or database server, or other networks or servers. The instructions for carrying out the above-mentioned functionality may be stored on a server (which is described in more detail in connection with FIG. **8**). Communications circuitry may include a cable modem, an integrated services digital network (ISDN) modem, a digital subscriber line (DSL) modem, a telephone modem, Ethernet card, or a wireless modem for communications with other equipment, or any other suitable communications circuitry. Such communications may involve the Internet or any other suitable communication networks or paths (which is described in more detail in connection with FIG. **8**). In addition, communications circuitry may include circuitry that enables peer-to-peer communication of user equipment devices, or communication of user equipment devices in locations remote from each other (described in more detail below).

[0090] Memory may be an electronic storage device provided as storage **708** that is part of control circuitry **704**. As referred to herein, the phrase “electronic storage device” or “storage device” should be understood to mean any device for storing electronic data, computer software, or firmware, such as random-access memory, read-only memory, hard drives, optical drives, digital video disc (DVD) recorders, compact disc (CD) recorders, BLU-RAY disc (BD) recorders, BLU-RAY 3D disc recorders, digital video recorders (DVR, sometimes called a personal video recorder, or PVR), solid state devices, quantum storage devices, gaming consoles, gaming media, or any other suitable fixed or removable storage devices, and/or any combination of the same. Storage **708** may be used to store various types of content described herein as well as media application and/or gaze mapping application data described above. Nonvolatile memory may also be used (e.g., to launch a boot-up routine and other instructions). Cloud-based storage, described in relation to FIG. **7**, may be used to supplement storage **708** or instead of storage **708**.

[0091] Control circuitry **704** may include video generating circuitry and tuning circuitry, such as one or more analog tuners, one or more H.265 decoders or any other suitable digital decoding circuitry, high-definition tuners, or any other suitable tuning or video circuits or combinations of such circuits. Encoding circuitry (e.g., for converting over-the-air, analog, or digital signals to MPEG signals for storage) may also be provided. Control circuitry **704** may also include scaler circuitry for upconverting and downconverting content into the preferred output format of user equipment **700**, **701**. Control circuitry **704** may also include digital-to-analog converter circuitry and analog-to-digital converter circuitry for converting between digital and analog signals. The tuning and encoding circuitry may be used by user equipment device **700**, **701** to receive and to display, to play, or to record content. The tuning and encoding circuitry may also be used to receive video encoding/decoding data. The circuitry described herein, including for example, the tuning, video generating, encoding, decoding, encrypting, decrypting, scaler, and analog/digital circuitry,

may be implemented using software running on one or more general purpose or specialized processors. Multiple tuners may be provided to handle simultaneous tuning functions (e.g., watch and record functions, picture-in-picture (PIP) functions, multiple-tuner recording, etc.). If storage **708** is provided as a separate device from user equipment device **700**, the tuning and encoding circuitry (including multiple tuners) may be associated with storage **708**.

[0092] Control circuitry **704** may receive instruction from a user by way of user input interface circuitry **710**. User input circuitry **710** may be any suitable user interface circuitry, such as a remote control, mouse, trackball, keypad, keyboard, touch screen, touchpad, stylus input, joystick, voice recognition interface, or other user input interfaces. Display **712** circuitry may be provided as a stand-alone device or integrated with other elements of each one of user equipment device **700**, **701**. For example, display circuitry **712** may be a touchscreen or touch-sensitive display. In such circumstances, user input interface circuitry **710** may be integrated with or combined with display circuitry **712**. In some embodiments, user input interface circuitry **710** includes a remote-control device having one or more microphones, buttons, keypads, any other components configured to receive user input or combinations thereof. For example, user input interface circuitry **710** may include a handheld remote-control device having an alphanumeric keypad and option buttons.

[0093] Audio output equipment **714** may be integrated with or combined with display circuitry **712**. Display circuitry **712** may be one or more of a monitor, a television, a liquid crystal display (LCD) for a mobile device, amorphous silicon display, low-temperature polysilicon display, electronic ink display, electrophoretic display, active matrix display, electro-wetting display, electro-fluidic display, cathode ray tube display, light-emitting diode display, electroluminescent display, plasma display panel, high-performance addressing display, thin-film transistor display, organic light-emitting diode display, surface-conduction electron-emitter display (SED), laser television, carbon nanotubes, quantum dot display, interferometric modulator display, or any other suitable equipment for displaying visual images. A video card or graphics card may generate the output to the display circuitry **712**. Audio output equipment **714** may be provided as integrated with other elements of each one of device **700** and equipment **701** or may be stand-alone units. An audio component of videos and other content displayed on display circuitry **712** may be played through speakers (or headphones) of audio output equipment **714**. In some embodiments, audio may be distributed to a receiver (not shown), which processes and outputs the audio via speakers of audio output equipment **714**. In some embodiments, for example, control circuitry **704** is configured to provide audio cues to a user, or other audio feedback to a user, using speakers of audio output equipment **714**. There may be a separate microphone **716** or audio output equipment **714** may include a microphone configured to receive audio input such as voice commands or speech. For example, a user may speak letters or words that are received by the microphone and converted to text by control circuitry **704**. In a further example, a user may voice commands that are received by a microphone and recognized by control circuitry **704**. Camera **718** may be any suitable video camera integrated with the equipment or externally connected. Camera **718** may be a digital camera comprising a charge-coupled device (CCD) and/or a complementary metal-oxide semiconductor (CMOS) image sensor. Camera **718** may be an analog camera that converts to digital images via a video card.

[0094] The media application and/or gaze mapping application may be implemented using any suitable architecture. For example, it may be a stand-alone application wholly-implemented on each one of user equipment device **700** and user equipment device **701**. In such an approach, instructions of the application may be stored locally (e.g., in storage **708**), and data for use by the application is downloaded on a periodic basis (e.g., from an out-of-band feed, from an Internet resource, or using another suitable approach). Control circuitry **704** may retrieve instructions of the application from storage **708** and process the instructions to provide encoding/decoding functionality and preform any of the actions discussed herein. Based on the processed instructions, control circuitry **704** may determine what action to perform when input is received from user input

interface circuitry **710**. For example, movement of a cursor on a display up/down may be indicated by the processed instructions when user input interface circuitry **710** indicates that an up/down button was selected. An application and/or any instructions for performing any of the embodiments discussed herein may be encoded on computer-readable media. Computer-readable media includes any media capable of storing data. The computer-readable media may be non-transitory including, but not limited to, volatile and non-volatile computer memory or storage devices such as a hard disk, floppy disk, USB drive, DVD, CD, media card, register memory, processor cache, Random Access Memory (RAM), etc.

[0095] In some embodiments, the media application and/or gaze mapping application is a client/server-based application. Data for use by a thick or thin client implemented on each one of user equipment device **700** and user equipment device **701** may be retrieved on-demand by issuing requests to a server remote to each one of user equipment device **700** and user equipment device **701**. For example, the remote server may store the instructions for the application in a storage device. The remote server may process the stored instructions using circuitry (e.g., control circuitry **604**) and generate the displays discussed above and below. The client device may receive the displays generated by the remote server and may display the content of the displays locally on device **700**, **701**. This way, the processing of the instructions is performed remotely by the server while the resulting displays (e.g., that may include text, a keyboard, or other visuals) are provided locally on device **700**, **701**. Device **700**, **701** may receive inputs from the user via input interface circuitry **710** and transmit those inputs to the remote server for processing and generating the corresponding displays. For example, device **700**, **701** may transmit a communication to the remote server indicating that an up/down button was selected via input interface circuitry **710**. The remote server may process instructions in accordance with that input and generate a display of the application corresponding to the input (e.g., a display that moves a cursor up/down). The generated display is then transmitted to device **700**, **701** for presentation to the user.

[0096] In some embodiments, the media application and/or gaze mapping application may be downloaded and interpreted or otherwise run by an interpreter or virtual machine (run by control circuitry **704**). In some embodiments, the media application and/or gaze mapping application may be encoded in the ETV Binary Interchange Format (EBIF), received by control circuitry **704** as part of a suitable feed, and interpreted by a user agent running on control circuitry **704**. For example, the media application and/or gaze mapping application may be an EBIF application. In some embodiments, the media application and/or gaze mapping application may be defined by a series of JAVA-based files that are received and run by a local virtual machine or other suitable middleware executed by control circuitry **704**. In some of such embodiments (e.g., those employing MPEG-2 or other digital media encoding schemes), media application and/or gaze mapping application may be, for example, encoded and transmitted in an MPEG-2 object carousel with the MPEG audio and video packets of a program.

[0097] FIG. **8** is a diagram of an illustrative system **800** for encoding and/or decoding of 3D media content, in accordance with some embodiments of this disclosure. System **800** may comprise user equipment devices **807**, **808**, and/or **810** and/or any other suitable number and types of user equipment, capable of transmitting data by way of communication network **809**. Communication network **809** may be one or more networks including the Internet, a mobile phone network, mobile voice or data network (e.g., a 5G, 4G, or LTE network), cable network, public switched telephone network, or other types of communication network or combinations of communication networks. Paths (e.g., depicted as arrows connecting the respective devices to the communication network **809**) may separately or together include one or more communications paths, such as a satellite path, a fiber-optic path, a cable path, a path that supports Internet communications (e.g., IPTV), free-space connections (e.g., for broadcast or other wireless signals), or any other suitable wired or wireless communications path or combination of such paths. Communications with the client devices may be provided by one or more of these communications paths but are shown as a single

path in FIG. 8 to avoid overcomplicating the drawing.

[0098] Although communications paths are not drawn between user equipment devices, these devices may communicate directly with each other via communications paths as well as other short-range, point-to-point communications paths, such as USB cables, IEEE 1394 cables, wireless paths (e.g., Bluetooth, infrared, IEEE 702-11x, etc.), or other short-range communication via wired or wireless paths. The user equipment devices may also communicate with each other directly through an indirect path via communication network **809**.

[0099] System **800** may comprise media content source **802** (e.g., corresponding to servers **160**, **161**) and/or one or more servers **804**. In some embodiments, the media application and/or gaze mapping application may be executed at one or more of control circuitry **811** of server **804** (and/or control circuitry of user equipment devices **807**, **808**, **810**).

[0100] In some embodiments, server **804** includes control circuitry **811** and storage **814** (e.g., RAM, ROM, Hard Disk, Removable Disk, etc.). Storage **814** may store one or more databases. Server **804** may also include an input/output path **812**. I/O path **812** may provide encoding/decoding data, device information, or other data, over a local area network (LAN) or wide area network (WAN), and/or other content and data to control circuitry **811**, which may include processing circuitry, and storage **814**. Control circuitry **811** may be used to send and receive commands, requests, and other suitable data using I/O path **812**, which may comprise I/O circuitry. I/O path **812** may connect control circuitry **811** (and specifically control circuitry) to one or more communications paths.

[0101] Control circuitry **811** may be based on any suitable control circuitry such as one or more microprocessors, microcontrollers, digital signal processors, programmable logic devices, field-programmable gate arrays (FPGAs), application-specific integrated circuits (ASICs), etc., and may include a multi-core processor (e.g., dual-core, quad-core, hexa-core, or any suitable number of cores) or supercomputer. In some embodiments, control circuitry **811** may be distributed across multiple separate processors or processing units, for example, multiple of the same type of processing units (e.g., two Intel Core i7 processors) or multiple different processors (e.g., an Intel Core i5 processor and an Intel Core i7 processor). In some embodiments, control circuitry **811** executes instructions for an emulation system application stored in memory (e.g., the storage **814**). Memory may be an electronic storage device provided as storage **814** that is part of control circuitry **811**.

[0102] Media content source **802**, server **804**, or any combination thereof, may include an encoder. Such encoder may comprise any suitable combination of hardware and/or software configured to process data to reduce storage space required to store the data and/or bandwidth required to transmit the image data, while minimizing the impact of the encoding on the quality of the media content being encoded. In some embodiments, the data to be compressed may comprise a raw, uncompressed 3D media content, or 3D media content in any other suitable format. In some embodiments, each of user equipment devices **807**, **808** and/or **810** may receive encoded or encoded data locally or over a communication network (e.g., communication network **809** of FIG. 8) and may comprise one or more decoders. Such decoder may comprise any suitable combination of hardware and/or software configured to convert data in a coded form to a form that is usable as video signals and/or audio signals or any other suitable type of data signal, or any combination thereof. User equipment devices **807**, **808** and/or **810** may be provided with encoded data, and may be configured to implement one or more machine learning models to modify delivery of audio portion of media streams based on detected gaze and/or triangulate a dynamic gaze of a user. In some embodiments, at least a portion of decoding may be performed remote from user equipment devices **807**, **808** and/or **810**.

[0103] FIGS. 9-12 are flowcharts of various processes **900-1200**, respectively. In various embodiments, the individual steps of each process **900-1200** may be implemented by one or more components of the devices and systems of FIGS. 7-8. Although the present disclosure may describe

certain steps of each process **900-1200** (and of other processes described herein) as being implemented by certain components of the devices and systems of FIGS. **7-8**, this is for purposes of illustration only, and it should be understood that other components of the devices and systems of FIGS. **7-8** may implement those steps instead. For example, the steps of each process **900-1200** may be executed by server **804** and/or by user equipment device **807, 808**, and/or **810** and/or by control circuitry **704** of a device **700, 701** to switch audio based on user's gaze and/or dynamically triangulate the user's gaze.

[0104] FIG. **9** is a flowchart **900** of a detailed illustrative process for switching audio based on gaze, in accordance with various embodiments of the disclosure. In various embodiments, the individual steps of process **900** may be implemented by one or more components of the devices and systems of FIGS. **7-8**. Although the present disclosure may describe certain steps of process **900** (and of other processes described herein) as being implemented by certain components of the devices and systems of FIGS. **7-8**, this is for purposes of illustration only, and it should be understood that other components of the devices and systems of FIGS. **7-8** may implement those steps instead. For example, the steps of process **900** may be executed by server **804** and/or by user equipment device **807, 808**, and/or **810** and/or by control circuitry **704** of a device **700, 701** to detect a user's gaze and modify delivery of the audio portion of a media stream to a user's device based on the detected user's gaze.

[0105] In some embodiments, at step **902**, the control circuitry (e.g., control circuitry **811** and/or control circuitry **704**) determines that a first audio/video stream is being provided to a first device associated with a first user. At step **904**, the control circuitry determines that a second audio/video stream is being provided to a second device associated with a second user. In some embodiments, the first and second devices are connected to the same network (e.g., same local wireless network) and are within a certain distance of each other. For example, the first user and second user may be viewing their respective devices while sitting next to each other in the same vehicle or same room. In some embodiments, the first and second audio/video streams are provided the same content provider. Alternatively, the first and second audio/video streams are provided by different content providers.

[0106] In some embodiments, at step **806**, the control circuitry detects the gaze of the second user. For example, the control circuitry may monitor the gaze of each user using eye tracking data of each user captured by the user's associated device or other camera device in the environment. For example, the control circuitry may determine the real-time gaze of each user using a modified 3D gaze map of the environment.

[0107] In some embodiments, at step **908**, if the control circuitry detects that the gaze of the second user is directed to her own device (e.g., the second device), then the control circuitry continues to distribute the second audio/video stream to the second device, such that the second device continues playback of the second audio/video stream.

[0108] In some embodiments, at step **910**, if the control circuitry detects that the gaze of the second user is directed to the device of the first user (e.g., the first device), then the control circuitry causes the second audio/video stream to become paused at the second device at step **914** and causes the audio portion of the first audio/video stream to be played by the second device. For example, the control circuitry may request from the appropriate content provider a replicate of the audio portion of the first audio/video stream. The control circuitry may decode, mix, combine, and encode the audio portion and distribute it to the second audio device until the second user ceases gazing at the first device, at which point, the control circuitry causes the second audio/video stream to resume playback at the second device.

[0109] FIG. **10** is a flowchart **100** of a detailed illustrative process using face recognition to determine audio switching, in accordance with various embodiments of the disclosure. In some embodiments, at step **1002**, users in a shared environment consume content on their respective computing devices. For instance, two users may be sitting next to each other in the living room,

each consuming content on their own respective smartphones. In some embodiments, at step **1004**, the control circuitry (e.g., control circuitry **811** and/or control circuitry **704**) determines whether a 3D gaze map is available for detecting the gaze of each user, wherein the 3D gaze map indicates the real-time gaze of a user in an environment. At step **1006**, if such 3D gaze map is available, then at least a camera device in the environment captures gaze data (e.g., eye tracking data) of the users and the control circuitry infers each user's intent with respect to devices based on gaze data of the user. For instance, if the control circuitry detects a second user's gaze is directed to a first user's device, the control circuitry infers that the user intends to listen to the accompany audio of the content playing on the first user's device and processes the second user's gaze as input requesting such audio. At step **1010**, the control circuitry distributes content to various devices of each user (or common devices, such as smart TV). At step **1012**, an audio stream mixer decodes, mixes, combines, and encodes the audio portion associated with the content displayed on the device at which a user directs their gaze. At step **1014**, when the control circuitry determines that the second user's gaze is directed to the first user's device (e.g., as indicated by the 3D gaze map), the control circuitry distributes to the second user the audio portion of the content playing at the first user's device.

[0110] In some embodiments, at step **1020**, if no such 3D gaze map is available, the control circuitry determines user's intent and validates whether the user is authorized to view content (and/or authorized to access the device playing such content) based on face recognition. For example, various camera devices in the environment may capture image data of each user. At step **1024**, control circuitry distributes content to various devices of each user (or common devices, such as smart TV). At step **1026**, an audio stream mixer decodes, mixes, combines, and encodes the audio portion associated with the content displayed on the device at which a user is authorized to view. At step **1028**, the control circuitry determines, based on image recognition of the second user's face looking at the first user's device, that the second user is authorized to view the content on the first user's device, the control circuitry distributes to the second user the audio portion of the content playing at the first user's device.

[0111] FIG. **11** is flowchart **1100** of another detailed illustrative process using face recognition to determine audio switching, in accordance with various embodiments of the disclosure. In some embodiments, at steps **1102** and **1104**, the control circuitry (e.g., control circuitry **811** and/or control circuitry **704**) begins a media session, providing media content to users who connect to the same network. At steps **1106** and **1108**, the control circuitry identifies the users, their associated devices, and their access status (e.g., whether a user is authorized to view certain content and/or access the displays of certain content consuming devices). At step **1110**, the control circuitry collects face recognition data for identifying the users. At step **1114**, the control circuitry distributes content streams to each user device.

[0112] In some embodiments, for user (1) device (e.g., associated with user (1)), at step **1118**, the control circuitry maintains and stores face recognition data of users who are authorized to access content on the user (1) device. At step **1122**, if user (2) looks at the display of user (1)'s device to view a first content stream, and at step **1116** if the control circuitry recognizes the user (2) as being authorized to view the user (1) device, then at step **1120** the user (1) device sends the decoded audio portion of the first content stream to the mixer, which routes the decoded audio portion to the user (2) device.

[0113] In some embodiments, for user (2) device (e.g., associated with user (2)), at step **1124**, the control circuitry maintains and stores face recognition data of users who are authorized to access content on the user (2) device. At step **1128**, if user (1) looks at the display of user (2)'s device to view a second content stream, and at step **1116** if the control circuitry recognizes the user (1) as being authorized to view the user (2) device, then at step **1126** the user (2) device sends the decoded audio portion of the second content stream to the mixer, which routes the decoded audio portion to the user (1) device.

[0114] FIG. **12** is a flowchart **1200** of a detailed illustrative process for triangulating dynamic gaze of a user, in accordance with various embodiments of the disclosure. In some embodiments, at step **1202**, the control circuitry (e.g., control circuitry **811** and/or control circuitry **704**) maintains a 3D map of an environment. The 3D map comprises a static mesh representation of the environment and reference mesh representation of objects and subjects therein. The 3D map indicates 3D locations of a plurality of camera devices in the environment.

[0115] In some embodiments, at step **1204**, the control circuitry collects first video data of position data of dynamic subjects and/or objects (e.g., a user and/or the target object of the user's gaze, respectively) in the environment. The first video data comprises a plurality of video feeds captured by each of the plurality of camera devices.

[0116] In some embodiments, at step **1206**, the control circuitry determines whether the 3D location of the user and/or target object (e.g., mobile device at which the user is viewing) is determined from the first video data. For example, the control circuitry cross-references the position data from the multiple video feeds of the plurality of camera devices to determine the real-time position of the user and/or mobile device with increased accuracy. If the 3D location of the user and/or mobile device have been determined from the first video feed, then at step **1208** the control circuitry updates the 3D map to indicate the 3D location of the user and/or mobile device.

[0117] In some embodiments, at step **1210**, the control circuitry analyzes second video data from the camera devices in combination with cross-referencing the updated 3D map of the environment. The second video data comprises gaze data (e.g., eye tracking data, such as eye movement data, head gaze and/or head position data) of the user. For example, the plurality of camera devices may capture multiple video feeds of the user and use sensors to track the user's eye movements. The control circuitry combines the gaze data from the multiple video feeds and cross-references the combined gaze data with the positions of the user and/or mobile device as indicated in the updated 3D map. At step **1212**, based on the cross-referencing, the control circuitry determines the gaze of the user by estimating a projected line of sight of the user.

[0118] In some embodiments, at step **1214**, the control circuitry determines whether the gaze of the user is directed to the display of the mobile device. For example, the control circuitry may determine that the projected line of sight of the user collides (e.g., intersects) with a collision volume corresponding to a reference mesh representing the mobile device in the updated 3D map. The triggering of such collision volume by the projected line of sight indicates that the mobile device is located at the focal point of the user's gaze.

[0119] In some embodiments, at step **1216**, in response to determining that the user's gaze is directed to the mobile device, the control circuitry causes the mobile device to perform an action. For example, the mobile device may direct an audio stream (e.g., which is associated with the content stream currently playing on the mobile device) to an audio device (e.g., headphones) of the user. For example, if the user's gaze is directed to a specific portion of the mobile device (e.g., a particular graphical icon on the screen of the mobile device which corresponds to a mobile application), the control circuitry may cause the mobile device to execute the mobile application.

[0120] FIG. **13** is an example system **1300** for triangulating dynamic gaze of a user, in accordance with various embodiments of the disclosure. In some embodiments, central processing device **1301** merges the data (e.g., video feeds of position of the user **1319** and/or target mobile device **1313**, or eye tracking data of the user **1319**) captured by a plurality of camera devices in the environment into one cohesive 3D gaze map. For example, central processing device **1301** may comprise a smart TV, gaming consoles, a laptop, mobile devices, or other suitable computing device.

[0121] In some embodiments, camera **1302** is communicatively connected to the central processing device **1301**. For example, camera **1302** may comprise cameras integrated with a mobile device or other computing device, CCV camera or other surveillance equipment, or any other suitable device capable of capturing and transmitting video streams.

[0122] In some embodiments, the control circuitry, by way of position cross-reference component

1303, cross-references position data captured by multiple devices (e.g., using inertial sensors and/or cameras).

[0123] In some embodiments, the control circuitry, by way of dataset culling component **1304**, culls out irrelevant data, such as data which cannot be determined in 3D space or is not likely to contribute to accurate tracking of a subject which is already being tracked by another camera device in the environment. For example, if the control circuitry determines that lighting conditions for a camera device are under a particular quality or the distance between the camera device and the subject are beyond a certain distance, then the control circuitry may cull video data from such camera device. For example, the control circuitry may score such video data from such camera device with a low score. Camera devices with a score below a threshold are excluded from data capture and calculations. The score may increase if the conditions of the camera device for capturing relevant data changes (e.g., lighting conditions around the camera device improve, or the camera device is positioned at an optimal angle or distance to the subject).

[0124] In some embodiments, the control circuitry, by way of position assumption component **1305**, configures 3D meshes in the 3D map that act as triggers (e.g., collision volumes) to determine if users move between rooms. For example, if user **1319** collides with the kitchen door collider, or if the user **1319** is at the same time not detected in the room, the control circuitry may assume that the user **1319** has exited the living room and entered into the kitchen.

[0125] In some embodiments, the control circuitry, by way of gaze calculation component **1306**, receives eye tracking data from each camera device in a room and outputs a dataset indicating where each user is looking compared to the device camera. The control circuitry determines the identity of a user from several streams of video and assigns a tag to the user and their associated device(s) to streamline compilation of the data (e.g., avoid collecting and processing further additional streams for the same task of identifying the user). The control circuitry cross-references the position data and eye tracking data from multiple video streams of multiple camera devices. The control circuitry additionally rates the accuracy of such data. The control circuitry determines whether the combined data reaches a certain level of accuracy and selects data points having such level accuracy to draw a line of sight. The line of sight is weighted to a median between the different data points in the hierarchy of confidence. Thus, the rendered line of sight will be associated with the compiled confidence level from all of the device inputs (e.g., data sources such as camera devices) which were identified as relevant or having high confidence by dataset culling component **1304**. The control circuitry extends the line of sight from the user's eye until it makes contact with any collision mesh (e.g., point of interest) or the static mesh of the environment. The collision indicates the identity of the target object (e.g., focal point of the gaze) and the 3D location of such target option.

[0126] In some embodiments, points of interests **1307** are represented in the 3D map as collision volumes. Static 3D map **1308** of the environment comprises polygonal collision and reference meshes representing objects within the environment.

[0127] In some embodiments, mobile device **1313** is equipped with camera **1314** and/or sensors which can capture and process eye tracking data **1315** of the user. Mobile device **1313** can also save face recognition data **1316** of authorized users who are allowed to access the mobile device **1313**.

[0128] The processes discussed above are intended to be illustrative and not limiting. One skilled in the art would appreciate that the steps of the processes discussed herein may be omitted, modified, combined and/or rearranged, and any additional steps may be performed without departing from the scope of the invention. More generally, the above disclosure is meant to be illustrative and not limiting. Only the claims that follow are meant to set bounds as to what the present invention includes. Furthermore, it should be noted that the features and limitations described in any one embodiment may be applied to any other embodiment herein, and flowcharts or examples relating to one embodiment may be combined with any other embodiment in a suitable manner, done in

different orders, or done in parallel. In addition, the systems and methods described herein may be performed in real time. It should also be noted that the systems and/or methods described above may be applied to, or used in accordance with, other systems and/or methods.

Claims

1. A method comprising: determining that a first audio/video stream is being provided to a first device associated with a first user; determining that a second audio/video stream is being provided to a second device associated with a second user; determining that a gaze of a second user is directed to a display of the first device; and in response to the determining that the gaze of the second user is directed to the display of the first device; causing the second audio/video stream to become paused at the second device; and causing an audio portion of the first audio/video stream to be played by the second device.
2. The method of claim 1, wherein the first device and the second device are connected to same wireless network.
3. The method of claim 2, wherein the causing the second audio/video stream to become paused at the second device further comprises: identifying the second audio/video stream being provided to the second device via the wireless network based on metadata associated with the second audio/video stream; and temporarily preventing delivery of the second audio/video stream to the second device via the wireless network.
4. The method of claim 2, wherein the causing the audio portion of the first audio/video stream to be played by the second device further comprises: receiving over a wireless network the first audio/video stream; identifying the first audio/video stream being provided to the first device via the wireless network based on metadata associated with the first audio/video stream; decoding the audio portion of first audio/video stream; combining and encoding the audio portion of the first audio/video stream; and distributing, over the wireless network, the audio portion of the first audio/video stream to the second device.
5. The method of claim 4, further comprising: distributing the audio portion of the first audio/video stream to the first device simultaneously with distributing the audio portion of the first audio/video stream to the second device; and synchronizing the audio portion of the first audio/video stream distributed to the first device with the audio portion the first audio/video stream distributed to the second device.
6. The method of claim 3, further comprising: detecting that the gaze of the second user is no longer on the first device; terminating the audio portion of the first audio/video stream via the wireless network to the second device; and resuming delivery of the second audio/video stream to the second device via the wireless network.
7. The method of claim 2, further comprising: determining that a gaze of the first user is not directed to a display of any device; continuing delivery of the audio portion of the first audio/video stream to the first device via the wireless network.
8. The method of claim 1, wherein the determining that the gaze of the second user is directed to the display of the first device further comprises: receiving an image captured from the first device; and recognizing the image as a face of the second user.
9. The method of claim 8, further comprising: determining, based on the recognized face of the second user, that the second user is authorized to view the first audio/video stream or view content displayed on the first device.
10. The method of claim 1, wherein the causing the audio portion of the first audio/video stream to be played by the second device is further in response to: detecting a gesture of the second user directed at the first user.
11. The method of claim 1, wherein the gaze of the second user is determined based on: maintaining a 3D map of an environment indicating respective 3D locations of each of a plurality

of camera devices in the environment; analyzing first video data from the plurality of camera devices to identify: (a) a 3D location of the second user in the environment; and (b) a 3D location of the first device in the environment; updating the 3D map of the environment indicating the 3D location of the second user and the 3D location of the first device; analyzing second video data from the plurality of camera devices in combination with cross-referencing the updated 3D map of the environment to determine that the gaze of the second user is directed at the first device.

12. A system comprising: control circuitry configured to: determine that a first audio/video stream is being provided to a first device associated with a first user; determine that a second audio/video stream is being provided to a second device associated with a second user; determine that a gaze of a second user is directed to a display of the first device; and input/output circuitry configured to: in response to the determining that the gaze of the second user is directed to the display of the first device; cause the second audio/video stream to become paused at the second device; and cause an audio portion of the first audio/video stream to be played by the second device.

13. The system of claim 12, wherein the first device and the second device are connected to same wireless network.

14. The system of claim 13, wherein further to causing the second audio/video stream to become paused at the second device, the control circuitry is further configured to: identify the second audio/video stream being provided to the second device via the wireless network based on metadata associated with the second audio/video stream; and temporarily prevent delivery of the second audio/video stream to the second device via the wireless network.

15. The system of claim 13, wherein further to causing the audio portion of the first audio/video stream to be played by the second device, the control circuitry is further configured to: receive over a wireless network the first audio/video stream; identify the first audio/video stream being provided to the first device via the wireless network based on metadata associated with the first audio/video stream; decode the audio portion of first audio/video stream; combine and encoding the audio portion of the first audio/video stream; and distribute, over the wireless network, the audio portion of the first audio/video stream to the second device.

16. The system of claim 15, wherein the control circuitry is further configured to: distribute the audio portion of the first audio/video stream to the first device simultaneously with distributing the audio portion of the first audio/video stream to the second device; and synchronize the audio portion of the first audio/video stream distributed to the first device with the audio portion the first audio/video stream distributed to the second device.

17. The system of claim 14, wherein the control circuitry is further configured to: detect that the gaze of the second user is no longer on the first device; terminate the audio portion of the first audio/video stream via the wireless network to the second device; and resume delivery of the second audio/video stream to the second device via the wireless network.

18. The system of claim 13, wherein the control circuitry is further configured to: determine that a gaze of the first user is not directed to a display of any device; continue delivery of the audio portion of the first audio/video stream to the first device via the wireless network.

19. The system of claim 12, wherein the control circuitry configured to determine that the gaze of the second user is directed to the display of the first device is further configured to: receive an image captured from the first device; and recognize the image as a face of the second user.

20. The system of claim 19, wherein the control circuitry is further configured to: determine, based on the recognized face of the second user, that the second user is authorized to view the first audio/video stream or view content displayed on the first device.

21.-75. (canceled)
