

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12414891
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Davis; David T. et al.

Inflatable support

Abstract

An inflatable patient support includes a top panel defining a first perimeter and a bottom panel defining a second perimeter. The second perimeter of the bottom panel is coupled to the first perimeter of the top panel. An internal wall is coupled between the top panel and the bottom panel to define a first chamber and a second chamber. The internal wall defines at least one passage therethrough that allows fluid communication between the first chamber and the second chamber. The first chamber and the second chamber are inflatable.

Inventors: Davis; David T. (Bethlehem, PA), Werkheiser; Jason K. (Fogelsville, PA), Englebert, III; John F. (Bethlehem, PA)

Applicant: D.T. Davis Enterprises, Ltd. (Allentown, PA)

Family ID: 1000008821276

Assignee: D.T. Davis Enterprises, Ltd. (Allentown, PA)

Appl. No.: 17/717217

Filed: April 11, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20220233386 A1	Jul. 28, 2022

Related U.S. Application Data

continuation parent-doc US 16061956 US 11298282 20220412 WO PCT/US2017/015609
20170130 child-doc US 17717217
us-provisional-application US 62288161 20160128

Publication Classification

Int. Cl.: **A61G13/12** (20060101); **A61B5/00** (20060101); **A61B5/055** (20060101); **A61B6/04** (20060101); **A61G7/10** (20060101)

U.S. Cl.:

CPC **A61G13/1265** (20130101); **A61B5/055** (20130101); **A61B5/70** (20130101); **A61B5/702** (20130101); **A61B6/0485** (20130101); **A61G7/1021** (20130101); **A61G13/12** (20130101); A61G2200/30 (20130101); A61G2200/54 (20130101)

Field of Classification Search

CPC: A61G (13/1265); A61G (13/12); A61G (7/1021); A61G (7/1013); A61G (2200/54); A61G (2200/30); A61B (5/702); A61B (5/70); A61B (5/0555); A61B (6/0485); A47C (27/081); A47C (27/087); A47C (27/10); A47C (27/08)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1726939	12/1928	Anderson	267/117	A47C 27/081
2612645	12/1951	Boland	297/DIG.3	A47C 20/048
5249318	12/1992	Loadsmen	N/A	N/A
5287577	12/1993	Bremer	5/81.1 R	A61G 13/1225
2002/0125758	12/2001	Duncan	N/A	N/A
2002/0166168	12/2001	Weedling et al.	N/A	N/A
2004/0143906	12/2003	Kasatshko et al.	N/A	N/A
2005/0044634	12/2004	Wang	5/709	A47C 27/084
2005/0081299	12/2004	Torres	N/A	N/A
2005/0193496	12/2004	Weedling et al.	N/A	N/A
2006/0021133	12/2005	Davis	N/A	N/A
2006/0080781	12/2005	Zheng	5/655.5	A47C 27/085
2007/0006385	12/2006	Davis	N/A	N/A
2007/0028380	12/2006	Russo	5/81.1 R	A61G 7/1021
2008/0244830	12/2007	Davis	N/A	N/A
2009/0144904	12/2008	Moye	N/A	N/A
2011/0056502	12/2010	Davis et al.	N/A	N/A
2011/0200177	12/2010	Patton et al.	N/A	N/A
2012/0011658	12/2011	Weedling	5/710	A61G 7/065
2012/0210511	12/2011	Davis	5/81.1 R	A61G 7/1051
2013/0025054	12/2012	Graw et al.	N/A	N/A
2013/0055504	12/2012	Peash	5/654	A61G 5/14
2014/0230154	12/2013	Palumbo	5/706	A63B 6/02
2015/0272771	12/2014	O'Brien	N/A	N/A
2016/0186874	12/2015	Lin	N/A	N/A
2017/0332802	12/2016	Stern	N/A	A61G 7/05769

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2663508	12/2011	CA	N/A
1611165	12/2004	CN	N/A
2905019	12/2006	CN	N/A
101180024	12/2007	CN	N/A
201691445	12/2010	CN	N/A
102316765	12/2011	CN	N/A
202703870	12/2012	CN	N/A
204319143	12/2014	CN	N/A
0569056	12/1992	EP	N/A
0828472	12/1998	EP	N/A
2002035052	12/2001	JP	N/A
2003086152	12/2002	WO	N/A

OTHER PUBLICATIONS

First Office Action issued corresponding in Chinese Patent Application No. 202210753278.0 dated Dec. 6, 2023, 16 pages. cited by applicant

Primary Examiner: Mikowski; Justin C

Assistant Examiner: Labarge; Alison N

Attorney, Agent or Firm: Duane Morris LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION (1) This application is a continuation of U.S. patent application Ser. No. 16/061,956, filed on Jun. 13, 2018, entitled “Inflatable Support” (now U.S. Pat. No. 11,298,282), which is a national stage entry of International Application Serial No. PCT/US2017/015609, filed on Jan. 30, 2017, entitled “Inflatable Support,” which claimed benefit to U.S. Provisional Appl. Ser. No. 62/288,161, filed Jan. 28, 2016, entitled “Hovertech Two Chamber Inflatable Support,” each of which is incorporated herein in their respective entirety.

BACKGROUND

(1) Positioning patients for medical imaging and other procedures presents risks to both the patient and caregivers. Patients must be placed in a seated position and a device inserted to maintain the patient in the seated position. Often, this requires a caregiver to lift a patient, which can result in injury to the caregiver or require multiple caregivers. Moving and/or readjusting a patient who has certain injuries can also exacerbate such injuries.

(2) The use of devices or supports to maintain a patient in a seated position can cause issues during imaging. Internal stringers, supports, or other structures can limit imaging and/or generate artifacts in images of patients. Such limitations and artifacts can result in false positive/negative results during medical imaging resulting in misdiagnosis and/or improper treatment.

SUMMARY

(3) In various embodiments, an inflatable patient support is disclosed. The inflatable patient support includes a top panel defining a first perimeter and a bottom panel defining a second perimeter. The second perimeter of the bottom panel is coupled to the first perimeter of the top panel. An internal wall is coupled between the top panel and the bottom panel to define a first chamber and a second chamber. The internal wall defines at least one passage therethrough that

allows fluid communication between the first chamber and the second chamber. The first chamber and the second chamber are inflatable

(4) In various embodiments, a method of positioning a patient is disclosed. The method includes positioning a patient on an inflatable patient support. The inflatable patient support comprises a top panel defining a first perimeter, a bottom panel defining a second perimeter, and an internal wall. The second perimeter of the bottom panel is coupled to the first perimeter of the top panel and the internal wall is coupled between the top panel and the bottom panel to define a first chamber and a second chamber. The internal wall defines at least one passage therethrough that allows fluid communication between the first chamber and the second chamber. The first chamber and the second chamber are inflatable. An inflation device is coupled to the first chamber of the inflatable patient support and the first chamber of the inflatable patient support is inflated. The first chamber is inflated at a first rate by air flow from the inflation device. The second chamber is inflated at a second rate by air flow from the first chamber through the at least one passage defined in the internal wall.

(5) In various embodiments, an inflatable support is disclosed. The inflatable support includes a body having a top panel defining a first perimeter and a bottom panel defining a second perimeter. The second perimeter of the bottom panel is coupled to the first perimeter of the top panel. The body is configured to be inflated. The body defines a flat profile in a deflated configuration and a patient seating area in an inflated position. An internal wall is coupled between the top panel and the bottom panel. The internal wall, the top panel, and the bottom panel define a first chamber and a second chamber. The internal wall defines at least one passage therethrough configured to provide air flow between the first chamber and the second chamber. An inflation valve is coupled to the body and configured to be coupled to an inflation device. The inflation valve is configured to provide air flow from the inflation device to the first chamber such that a portion of the body defining the first chamber inflates at a first rate by air flow from the inflation device and a portion of the body defining the second chamber inflates at a second rate by air flow through the at least one passage.

Description

BRIEF DESCRIPTION OF THE FIGURES

- (1) The features and advantages of the present invention will be more fully disclosed in, or rendered obvious by the following detailed description of the preferred embodiments, which are to be considered together with the accompanying drawings wherein like numbers refer to like parts and further wherein:
- (2) FIG. 1 illustrates a side view of an inflatable seat support in an inflated state, in accordance with some embodiments.
- (3) FIG. 2 illustrates a perspective view the inflatable seat support of FIG. 1 in a deflated state, in accordance with some embodiments.
- (4) FIG. 3 illustrates a perspective view of the inflatable seat support of FIG. 1 in a partially inflated state, in accordance with some embodiments.
- (5) FIG. 4 illustrates a perspective view of the inflatable seat support of FIG. 1 in a fully inflated state, in accordance with some embodiments.
- (6) FIG. 5 illustrates a top down view of the inflatable seat support of FIG. 4, in accordance with some embodiments.
- (7) FIG. 6 illustrates a top down view of the inflatable support of FIG. 1 having a patient positioned in a patient seating area, in accordance with some embodiments.
- (8) FIG. 7 illustrates a top-down view of an inflatable support having an inflation valve located on a bottom panel, in accordance with some embodiments.

(9) FIG. 8 illustrates a system including an inflatable support and an inflation device, in accordance with some embodiments.

(10) FIG. 9 illustrates a method of positioning a patient using an inflatable support, in accordance with some embodiments.

DETAILED DESCRIPTION

(11) The description of the preferred embodiments is intended to be read in connection with the accompanying drawings, which are to be considered part of the entire written description of this invention. The drawing figures are not necessarily to scale and certain features of the invention may be shown exaggerated in scale or in somewhat schematic form in the interest of clarity and conciseness. In this description, relative terms such as “horizontal,” “vertical,” “up,” “down,” “top,” “bottom,” as well as derivatives thereof (e.g., “horizontally,” “downwardly,” “upwardly,” etc.) should be construed to refer to the orientation as then described or as shown in the drawing figure under discussion. These relative terms are for convenience of description and normally are not intended to require a particular orientation. Terms including “inwardly” versus “outwardly,” “longitudinal” versus “lateral” and the like are to be interpreted relative to one another or relative to an axis of elongation, or an axis or center of rotation, as appropriate. Terms concerning attachments, coupling and the like, such as “connected” and “interconnected,” refer to a relationship wherein structures are secured or attached to one another either directly or indirectly through intervening structures, as well as both moveable or rigid attachments or relationships, unless expressly described otherwise. The term “operatively coupled” is such an attachment, coupling, or connection that allows the pertinent structures to operate as intended by virtue of that relationship.

(12) In various embodiments, an inflatable support is disclosed. The inflatable support includes a body having an upper panel and a lower panel. The upper panel and the lower panel have similar shapes and are coupled about a perimeter of each of the upper panel and the lower panel. At least one inner wall extends from an inner surface of the upper panel to an inner surface of the lower panel. The upper panel, the lower panel, and the inner wall define a first inflation chamber and a second inflation chamber. In some embodiments, a channel extends through the inner wall to couple the first and second inflation chambers. An inlet valve is coupled to a portion of the body and is configured to direct air flow into one of the first inflation chamber or the second inflation chamber.

(13) FIGS. 1-5 illustrate an inflatable support 2, in accordance with some embodiments. The inflatable support 2 includes a body 4 defined by an upper panel 6 and a lower panel 8. A perimeter 10a of the upper panel 6 is coupled to a perimeter 10b of the lower panel 8 to define a perimeter 10 of the body 4. In some embodiments, the upper panel 6 and the lower panel 8 have a similar size and/or shape, although it will be appreciated that the upper panel 6 and the lower panel 8 can have a disparate size and/or shape in some embodiments. The upper panel 6 and/or the lower panel 8 can be a single panel or sheet of material and/or can include multiple sheets or material coupled together.

(14) An internal wall 22 extends between and is coupled to an inner surface of the upper panel 6 and an inner surface of the lower panel 8. The internal wall 22 divides an inner volume of the body 4 into a first inflatable chamber 24 and a second inflatable chamber 26. The first and second inflatable chambers 24, 26 correspond to first and second inflatable portions 28, 30 of the body 4. For example, in the illustrated embodiment, the internal wall 22 defines a first, or rear, inflatable chamber 24 corresponding to a first, or rear, inflatable section 28 and the a second, or front, inflatable chamber 26 corresponding to a second, or front, inflatable section 30. Although a single internal wall 22 is illustrated, it will be appreciated that the inflatable support 2 can include a plurality of internal walls 22 defining two or more inflatable chambers corresponding to two or more inflatable portions of the body 4.

(15) The inflatable support 2 includes one or more air inlets 14 formed in at least one of the upper

panel **6** and/or the bottom panel **8**. An inflation device, such as a blower (see FIG. **8**) is coupled to one or more of the air inlets **14**. Air is pumped from the inflation device into the internal volume of the body **4** to inflate the first inflatable section **28** and/or the second inflatable section **30**. In some embodiments, the inflatable seat support **2** is configured for hands-free inflation. For example, in some embodiments, the air inlets **14** are configured to securely couple to a hose of the inflation device. Although embodiments are illustrated herein showing two air inlets **14**, it will be appreciated that the inflatable support **2** can include a lesser and/or greater number of air inlets **14**. (16) The air inlets **14** can include any suitable valve and/or port configured to allow air movement from the inflation device to at least one of the internal chambers **24**, **26**. For example, in some embodiments, the air inlets **14** include one-way valves configured to allow air movement from the inflation device to the internal chambers **24**, **26** but prevent air movement out of the internal chambers **24**, **26**. In other embodiments, the air inlets **14** can include two-way valves/ports and a cap or other device configured to seal the air inlets **14** after inflation.

(17) In some embodiments, the internal wall **22** defines one or more internal air passages **32** that allow fluid communication (e.g., air flow) between the first internal chamber **24** and the second internal chamber **26**. During inflation of the body **4**, the inflation device is coupled to one of the inlet ports **14** and an inflation gas, such as air, is pumped into one of the internal chambers **24**, **26**. For example, in the illustrated embodiment, the air inlets **14** provide fluid communication between an inflation device and the first internal chamber **24**. The inflation gas flows through the air passage **32** from the first internal chamber **24** to the second internal chamber **26** and inflates the second inflatable portion **30**. Although embodiments are illustrated having the inlet port **14** coupled to the first inflatable section **28**, it will be appreciated that one or more inlet ports can be coupled to the second inflatable section **30** and/or any additional inflatable sections.

(18) In some embodiments, the first inflatable portion **28** is configured to inflate at a first rate and the second inflatable portion **30** is configured to inflate at a second rate. For example, in the illustrated embodiment, the inlet port **14** is coupled to the first internal chamber **24**. Air flow from the inflation device into the first internal chamber **24** inflates the first inflatable portion **28** at a first inflation rate. Simultaneously, air flows from the first internal chamber **24** to the second internal chamber **26** through the air passage(s) **32** defined in the internal wall **22**. Air flow through the air passage(s) **32** into the second internal chamber **26** inflates the second inflatable portion **30** at a second inflation rate. In some embodiments, air flow through the air passage(s) **32** occurs after the first internal chamber **24** has been inflated to a predetermined pressure.

(19) In some embodiments, the size ratio of the inlet ports **14** and/or the internal passage(s) **32** are configured to define an inflation ratio between the first inflation rate and the second inflation rate. The ratio between the first inflation rate and the second inflation ratio is selected to provide advantageous inflation of the inflatable support **2**. For example, in some embodiments, the ratio between the first inflation rate and the second inflation rate is selected such that the first inflatable portion **28** inflates at a higher rate than the second inflatable portion **30**. The ratio between the first inflation rate and the second inflation rate can be, for example, a 2:1 ratio, a 4:1 ratio, and/or any other suitable ratio. Although example inflation rates are given herein, it will be appreciated that the inflation ratio can be selected to provide any suitable ratio of inflation.

(20) In some embodiments, the size of the inlet port(s) **14** and/or the internal air passage(s) **32** are configured to provide a predetermined inflation ratio. For example, in some embodiments, the inflation ratio between the first inflatable portion and the second inflatable portion is equal to X:1, where X is the area ratio between the inlet port(s) **14** and the internal air passage(s) **32**. The area ratio can be calculated as:

$$(21) \text{Area ratio} = \frac{A_L}{A_s * n}$$

where A.sub.L is equal to the area of the inlet port **14**, A.sub.s is equal to the area of the internal passage(s) **32**, and n is equal to the number of internal passage(s) **32** defined in the internal wall **22**. As one example, the inflatable support can include a single inlet port **14** having a diameter of

0.7625" and two internal passage(s) **32** each heaving a diameter of about 0.375". In this example, the area ratio can be calculated as:

$$(22) A_s = \left(\frac{0.375}{2}\right)^2 = 0.1104466 \text{ in}^2 \quad A_L = \left(\frac{0.7625}{2}\right)^2 = 0.4566354 \text{ in}^2$$

$$\text{Area ratio} = \frac{A_L}{A_s} = 2.0672222 \approx 2$$

In the example embodiments, the inflation ratio is equal to about 2:1 (e.g., the first inflatable portion **28** inflates at about twice the rate of the second inflatable portion **30**). Although specific values are provided in this example, it will be recognized that the size of the inlet port(s) **14**, the size of the internal passage(s) **32**, and/or the number of inlet port(s) **14** and/or internal passage(s) **32** may be varied based on one or more parameters of the inflatable support **2**.

(23) In some embodiments, the inflation ratio between the first inflation rate and the second inflation rate is selected such that the first inflatable portion **28** substantially inflates prior to inflation of the second inflatable portion **30**. For example, as discussed in more detail below, the first inflatable portion **28** may be substantially inflated prior to the second inflatable portion **30** to position a patient prior to inflation of the second inflatable portion **30**. Inflation of the second inflatable portion **30** raises the patient into a seated position. Substantially inflating the first inflatable portion **28** prior to substantially inflating the second inflatable portion **30** causes a patient that is slightly off-center to be repositioned prior to raising the patient to a seated position, providing additional stability and preventing the patient from sliding off of the inflatable support **2** during inflation.

(24) In some embodiments, one or more exhaust ports **16** are formed in at least one of the first inflatable portion **28** and/or the second inflatable portion **30** to allow deflation of the inflatable support **2**. In the illustrated embodiment, the exhaust ports **16** are formed in the upper panel **6**, although it will be appreciated that the exhaust ports **16** can additionally or alternatively be formed in the lower panel **8**. The exhaust ports **16** can be sized and configured to provide deflation of the inflatable support **2** at a predetermined rate. In some embodiments, the exhaust port(s) **16** can have different sizes configured to provide different rates of deflation for each of the inflatable portions **28**, **30** of the body **4**.

(25) In some embodiments, the inflatable seat support **2** comprises a bellows design sized and configured to support a patient during one or more procedures, such as, for example, a radiological imaging procedure. The shape of the upper panel **6** and the lower panel **8** are selected to provide a specific shape when inflated. For example, in some embodiments, the upper panel **6** and the lower panel **8** are selected such that a patient seating area **34** is defined by the inflatable support **2** in an inflated position (see FIG. **4**). In some embodiments, the upper panel **6** and/or the lower panel **8** have a rounded profile in an inflated state configured to provide lateral stability to the inflatable support **2**. Although embodiments are illustrated having a rounded profile, it will be appreciated that the upper panel **6** and/or the lower panel **8** can have any suitable profile shape, including but not limited to a squared profile, a rounded profile, an oblong profile, etc.

(26) In some embodiments, the patient seating area **34** is defined by the geometry of the second inflatable portion **30** when inflated and is not present (e.g., not defined) prior to inflation of the inflatable support **30** (see FIG. **2**). The patient seating area **34** can be defined by the shape and perimeter **10** of a portion of the first and/or second inflatable portion **28**, **30** when inflated. The first inflatable portion **28** is configured to position a patient within the patient seating area **34** prior to inflation of the second inflatable portion **30**.

(27) In some embodiments, a seating tongue **36** extends from body **4**. The seating tongue **36** is positioned within the seating area **34** defined by the body **4**. The seating tongue **36** is configured to be positioned beneath a patient to maintain **2** in a fixed position with respect to a patient during inflation, use, and deflation. In some embodiments, the seating tongue **36** includes a non-inflatable fabric strip that extends from the perimeter **10**. When a patient is positioned on the seating tongue **36**, the weight of the patient prevents the inflatable support **2** from moving with respect to the patient and/or a surface (such as a table). In some embodiments, the inflatable support **2** can be

coupled to the surface by one or more additional means, such as straps, hook and loop connections, ties, and/or any other suitable attachment mechanism. The surface can be any suitable surface, including, but not limited to, a hospital bed or a radiological imaging table.

(28) In some embodiments, the inflatable support **2** includes arm sections **38a**, **38b** extending from the body **4** and further defining the patient seating area **34**. The arm sections **38a**, **38b** are configured to position a patient within the patient seating area **34** during inflation of the first inflatable portion **28**. The arm sections **38a**, **38b** are defined by a portion of the first inflatable portion **28** and inflate at the first rate. As the arm sections **38a**, **38b** inflate, the patient is positioned in the center of the patient seating area **34**. In some embodiments, the arm sections **38a**, **38b** provide stability to the patient and prevent the patient from sliding out of the patient seating area **34** during inflation of the inflatable support **2**. Although embodiments are illustrated herein including two arm sections **38a**, **38b**, it will be appreciated that the inflatable support **2** can include a lesser or greater number of arm sections configured to position a patient within the patient seating area **34** during inflation.

(29) In some embodiments, the body **4**, the internal wall **22**, and/or the tongue **36** include a radiolucent material. The radiolucent material allows x-rays and other radioscopic procedures to be performed on a patient supported by the inflatable support **2** without interfering with the imaging. The radiolucent material can be a flexible radiolucent plastic or other material, such as TPU, EVA, Nylon, PCV, and/or any other suitable material.

(30) The internal wall **22** may be heat bonded, glued, ultrasonically bonded, and/or otherwise attached to the upper and lower panels **6**, **8**. In some embodiments, the location of the internal wall **22** determines the size and shape of the patient seating area **34**, the support arms **38a**, **38b**, and/or one or more features of the inflatable support **2**. In some embodiments, the inflatable support **2** is constructed without internal stringers or supports. Each of the internal chambers **24**, **26** are defined by the inner surface of the body **4** and one or more internal chamber walls **22** that are coupled directly to the upper panel **6** and the lower panel **8** of the inflatable support **2**. The internal chamber wall(s) **22** includes a radiolucent material. For example, in some embodiments, the internal chamber wall(s) **22** include the same radiolucent material as the body **4** of the inflatable support **2**, although it will be appreciated that alternative and/or additional radiolucent materials can be used. By excluding internal supports, the inflatable support **2** advantageously allows imaging of a patient without interference due to stringers and/or other internal support members. The absence of internal stringers further allows the inflatable support **2** to lay flat in a deflated state. Although embodiments are illustrated herein without internal stringers/supports, it will be appreciated that the inflatable support **2** can include one or more internal stringers/supports in some embodiments.

(31) In some embodiments, a strap **40** is coupled to the body **4** and/or the tongue **36**. The strap **40** is configured to couple the inflatable support **2** to a patient. For example, in some embodiments, the strap **40** is coupled to the tongue **36**. In other embodiments, the strap **40** is coupled to one or more portions of the body **4**, such as, for example, protrusions **42a** and **42b**. The protrusions **42a**, **42b** comprise a non-inflatable section of the body **4**. The strap **40** may be placed over a patient and buckled when the inflatable seat support **2** is in a deflated state. For example, the strap **40** may be placed over a patient's chest and/or abdomen. The strap **40** maintains the inflatable seat support **2** in contact with the patient in a deflated state and maintains the inflatable seat support **2** out of contact with imaging machinery, positioning machinery, and/or other medical machinery during positioning or movement of a patient. Although a single strap **40** is disclosed, those skilled in the art will recognize that the inflatable support **2** may comprise any suitable number of straps **40**.

(32) In operation, the inflatable support **2** is used to transition a patient from a first position, such as a laying position, to a second position, such as a seated position. The inflatable support **2** can be further configured to move the patient from the second position back to the first position. For example, in some embodiments, a patient is positioned on the inflatable support **2** when the inflatable support **2** is in a deflated state, such as shown in FIG. 2. An inflation device is coupled to

one of the inlet ports **14**. The inflatable support **2** is inflated to raise the patient from a laying position to a seated position for one or more procedures, such as, for example, radiological imaging. After the procedures are performed, one or more of the outlet ports **16** are unsealed to allow the first internal chamber **24** and the second internal chamber **26** to deflate, transitioning the patient from the second position back to the first position. In some embodiments, the inflatable support **2** may be inflated prior to the patient being seated on the inflatable support **2**.

(33) FIG. 2 illustrates one embodiment of the inflatable seat support **2** in a deflated state. As shown in FIG. 2, the inflatable seat support **2** defines a substantially rectangular shape in a deflated state. The upper panel **6** and the lower panel **8** lay flat in the deflated state. The patient seating area **36** (see, for example, FIGS. 3-4) is not visible in FIG. 2, as the patient seating area **36** is defined by the inflated geometry of the inflatable support **2**. Similarly, the arm sections **40a**, **40b** are not shown and are only defined by the inflatable support **2** in an inflated state. By providing a rectangular, flat shape, the inflatable support **2** can be easily stored and/or positioned in the deflated state.

(34) FIG. 3 illustrates the inflatable support **2** in a partially inflated state. The first inflatable portion **28** is partially inflated by, for example, an inflation device (not shown) coupled to one or more of the air inlet(s) **14**. The first inflatable portion **28** is partially inflated. As the first inflatable portion **28** inflates, the air flow rate into the second inflatable portion **30** increases and the second inflatable portion **30** begins to inflate. The curved perimeter of the first inflatable portion **28** defines a patient seating area **34**. The second inflatable portion **30** raises a patient from a flat, laying position (when the inflatable support **2** is deflated) into a sitting or partially-reclined position when the second inflatable portion **30** is at least partially inflated.

(35) FIG. 6 illustrates a top down view of one embodiment of the inflatable support **2** having a patient **50** positioned thereon. The patient **50** is positioned with an abdomen section located on the seating tongue **36** and the upper body extending onto the body **4** of the inflatable support **2**. After the patient **50** is positioned, an inflation device is coupled to the air inlet **14** to inflate the first inflatable portion **28**. The weight of the patient **50** on the seating tongue **36** maintains the position of the inflatable support **2** during inflation. As the first inflatable portion **28** inflates, the patient **50** is centered on the body **4** of the inflatable support **2**. The second inflatable portion **30** is sequentially and/or simultaneously inflated to raise the patient **50** from a laying position to a seated position.

(36) Although embodiments of the inflatable support **2** discussed herein include a first inflatable portion **28** and a second inflatable portion **30**, it will be recognized that the inflatable support **2** may include any number of independent and/or interdependent inflatable sections defining one or more internal chambers. For example, in some embodiments, a second internal wall can define a third internal chamber corresponding to a third inflatable portion of an inflatable support **2**. The third inflatable portion can be inflated at one of the first or second rates and/or can be inflated at a third rate, different from the first and second inflation rates. In some embodiments, one or more internal passages may be defined in the second internal wall to allow air to flow from the first and/or second internal chambers **24**, **26** to the third internal chamber at a predetermined flow rate. In other embodiments, the second internal wall can define a third internal chamber separate and independently inflatable from the first and second internal chambers **24**, **26** of the inflatable support **2**.

(37) FIG. 7 illustrates a top-down view of an inflatable support **2a** having an air inlet located on a bottom panel, in accordance with some embodiments. The inflatable support **2a** is similar to the inflatable support **2** discussed in conjunction with FIGS. 1-6, and similar description is not repeated herein. The inflatable support **2a** includes at least one air inlet **14a** (shown in phantom) formed through a bottom panel **8** of the inflatable support **2**. The air inlet **14a** allows an inflation device coupled to the air inlet **14a** to be positioned away from a patient and/or connected to the inflatable support **2a** while the patient is being positioned thereon without interfering with positioning the patient. The inflatable support **2a** includes at least two deflation valves **16** coupled to an upper

panel 6 of the body 4. In the illustrated embodiment, the deflation valves 16 are in fluid communication with the second internal chamber 26 such that opening the deflation valves 16 results in rapid deflation of the second inflatable portion 30 and slower deflation of the first inflatable portion 28, as air must travel from the first inflatable portion 28, through the internal passage(s) 32, and into the second inflatable portion 30 before being expelled through the deflation valves 16. In some embodiments, a patient's weight on the inflatable support 2a helps to force air from the first inflatable portion 28, into the second inflatable portion 30, and out of the deflation valves 16.

(38) FIG. 8 illustrates a system 100 including an inflatable support 2b coupled to an inflation device 60, in accordance with some embodiments. The inflatable support 2b is similar to the inflatable support 2 discussed above in conjunction with FIGS. 1-6, and similar description is not repeated herein. The inflation device 60 includes a pump 62 and a hose 64 coupling the pump 62 to one or more of the air inlet(s) 14 of the inflatable support 2b. The pump 62 is configured to provide positive air flow into the first internal chamber 24 of the inflatable support 2b. In some embodiments, the pump 62 is configured to provide a predetermined air flow rate. The predetermined air flow rate is selected to inflate the first inflatable portion 28 at a first inflation rate. In some embodiments, the hose 64 includes a coupling mechanism 66 configured to couple the hose 64 to the air inlet(s) 14. The coupling mechanism 66 can include any suitable coupling mechanism, such as a clamp, clip, thread, and/or any other suitable coupling mechanism.

(39) FIG. 9 is a flowchart illustrating a method 200 of positioning a patient for medical imaging using an inflatable support, in accordance with some embodiments. At step 202, an inflatable support, such as the inflatable support 2 discussed above, is positioned on a surface. The surface can include any suitable patient-receiving surface, such as an imaging table (e.g., radiological imaging table), a hospital bed, and/or any other suitable surface. At step 204, a patient is positioned over the inflatable support 2. The patient can be positioned such that the patient is seated on and/or otherwise applying weight to a tongue 36 extending from a body 4 of the inflatable support 2. At step 206, one or more imaging and/or other medical procedures are performed.

(40) At step 208, an inflation device, such as inflation device 60, is coupled to at least one of the air inlets 14 on the body 4. The inflation device 60 can include a hose 64 coupled to the air inlets 14 by one or more coupling mechanisms 66 and/or can be manually coupled by a user.

(41) At step 210, the inflation device begins inflating the inflatable support 2 through the air inlet(s) 14. The inflation device provides a positive air flow into the first internal chamber 24 of the inflatable support 2. At step 212, the first inflatable portion 28 is partially inflated by the positive air flow and positions the patient within a seating area 34. The first inflatable portion 28 is inflated at a first rate by the positive air flow from the inflation device. As the first inflatable portion 28 inflates, the patient is centered with respect to the inflatable support 2 and positioned within the seating area 34.

(42) At step 214, the second inflatable portion 30 begins to inflate. The second inflatable portion 30 is inflated by a positive air flow from the first internal chamber 24 into the second internal chamber 26 through one or more internal passages 32 defined in an internal wall 22. The second inflatable portion 30 is inflated at a second flow rate. In some embodiments, the second flow rate is determined by the ratio between the air inlet(s) 14 and the internal passage(s) 32 as discussed above. The second inflation rate is less than the first inflation rate.

(43) At step 216, the first inflatable portion 28 and the second inflatable portion 30 fully inflate and position the patient in a seated position. In some embodiments, the first inflatable portion 28 includes one or more arm sections 38a, 38b configured to maintain the patient in the center of the patient seating area 34 during inflation of the second inflatable portion 30.

(44) At step 218, at least one deflation valve 16 is opened to allow air to flow out of the first and second internal chambers 24, 26. In some embodiments, the one or more deflation valves are sized and configured to provide deflation of the first and second inflatable portions 28, 30 at a

predetermined rate of deflation. For example, in some embodiments, one or more deflation valves **16** are coupled to the second inflatable portion **30** and provide deflation of the second inflatable portion **30** at a first rate. The one or more deflation valves **16** also provide deflation of the first inflatable portion **28** at a second deflation rate which is less than the first deflation rate. In other embodiments, at least one deflation valve **16** is coupled to the first inflatable portion **28** and at least one deflation valve **16** is coupled to the second inflatable portion **30**.

(45) At step **220**, the inflatable support **2** is fully deflated and the patient is returned to a laying position. The patient can be subsequently removed from the inflatable support **2** and/or remain on the inflatable support **2** to allow the patient to be transitioned back to the seated position for subsequent and/or additional procedures.

(46) Although the subject matter has been described in terms of exemplary embodiments, it is not limited thereto. Rather, the appended claims should be construed broadly, to include other variants and embodiments, which may be made by those skilled in the art.

Claims

1. An inflatable patient support, comprising: a top panel defining a first perimeter; a bottom panel defining a second perimeter, wherein the second perimeter of the bottom panel is coupled to the first perimeter of the top panel to define at least one inflatable internal chamber therebetween, wherein the top panel and the bottom panel define a substantially flat profile in a deflated state, wherein the top panel and the bottom panel define a rounded profile configured to provide lateral stability in an inflated state, and wherein a patient seating area is defined by a shape and perimeter of a portion of the top panel and the bottom panel only in the inflated state; arm sections defining the patient seating area and being thicker than the patient seating area in the inflated state and configured to provide stability to a patient and maintain the patient in a center of the patient seating area while the patient is raised from a laying position to a seated position during inflation; an inflation valve coupled to the top panel at a first location, wherein the inflation valve is configured to couple the at least one inflatable internal chamber to an air inflow; and a deflation valve coupled to the top panel at a second location.
2. The inflatable patient support of claim 1, comprising an internal wall positioned within the internal chamber and coupled between the top panel and the bottom panel, wherein the internal wall divides the internal chamber to define a first chamber and a second chamber.
3. The inflatable patient support of claim 2, wherein the internal wall comprises at least one passage allowing fluid communication between the first chamber and the second chamber.
4. The inflatable patient support of claim 2, wherein the first chamber is configured to be inflated at a first inflation rate and the second chamber is configured to be inflated at a second inflation rate different than the first inflation rate.
5. The inflatable patient support of claim 4, wherein the first chamber is inflated at the first inflation rate by air flow from the inflation valve.
6. The inflatable patient support of claim 1, wherein the top panel and the bottom panel each comprise a radiolucent material.
7. The inflatable patient support of claim 1, comprising a seating tongue extending from at least one of the first perimeter or the second perimeter, wherein the seating tongue is sized and configured to receive a user.
8. The inflatable patient support of claim 1, comprising at least one strap coupled to one of the first perimeter or the second perimeter, wherein the at least one strap is configured to couple a user to the inflatable patient support.
9. The inflatable patient support of claim 8, wherein the strap is configured to be coupled to a protrusion comprising a non-inflatable section of the inflatable patient support.
10. A method of positioning a patient, comprising: positioning a patient on an inflatable patient

support, wherein the inflatable patient support comprises a top panel defining a first perimeter, a bottom panel defining a second perimeter, an inflation valve coupled to the top panel at a first location, and a deflation valve coupled to the top panel at a second location, wherein the second perimeter of the bottom panel is coupled to the first perimeter of the top panel to define at least one inflatable internal chamber therebetween, wherein the top panel and the bottom panel define a substantially flat profile in a deflated state, wherein the top panel and the bottom panel define a rounded profile configured to provide lateral stability in an inflated state, wherein a patient seating area is defined by a shape and perimeter of arm sections of the top panel and the bottom panel only in the inflated state and that are thicker than the patient seating area in the inflated state, and wherein the inflation valve is configured to couple the at least one inflatable internal chamber to an air inflow; coupling an inflation device to the inflation valve; and providing an air flow from the inflation device to the at least one inflatable internal chamber of the inflatable patient support to inflate the inflatable patient support while providing stability to the patient and maintaining the patient in a center of the patient seating area while the patient is raised from a laying position to a seated position during inflation.

11. The method of claim 10, wherein the inflatable patient support comprises an internal wall positioned within the internal chamber and coupled between the top panel and the bottom panel, wherein the internal wall divides the internal chamber to define a first chamber and a second chamber.

12. The method of claim 11, wherein the air flow is provided to the first chamber, and wherein the second chamber is inflated by air flow between the first chamber and the second chamber.

13. The method of claim 12, wherein the first chamber is configured to be inflated at a first inflation rate and the second chamber is configured to be inflated at a second inflation rate different than the first inflation rate.

14. The method of claim 13, wherein the first chamber is inflated at the first inflation rate by air flow from the inflation valve.

15. The method of claim 10, wherein positioning the patient on the inflatable patient support comprises positioning the patient on a tongue extending from one of the first perimeter or the second perimeter.

16. The method of claim 10, wherein prior to positioning the patient on the inflatable patient support, the method comprises positioning the inflatable patient support on an imaging table.

17. The method of claim 16, comprising performing one or more imaging operations on the patient prior to inflation or after inflation of the inflatable patient support.

18. The method of claim 10, wherein prior to coupling an inflation device to the inflation valve, the method comprises attaching the patient to the inflatable patient support using at least one strap coupled to one of the first perimeter or the second perimeter.

19. The method of claim 10, comprising maintaining the patient in a predetermined location with respect to the inflatable patient support, wherein the patient is maintained in the predetermined location by the arm sections when the inflatable patient support is inflated.

20. An inflatable patient support, comprising: a top panel defining a first perimeter; a bottom panel defining a second perimeter, wherein the second perimeter of the bottom panel is at least partially coupled to the first perimeter of the top panel to define at least one inflatable internal chamber therebetween, wherein the top panel and the bottom panel define a substantially flat profile in a deflated state, wherein the top panel and the bottom panel define a rounded profile configured to provide lateral stability in an inflated state, wherein a patient seating area is defined by a shape and perimeter of arm sections of the top panel and the bottom panel only in the inflated state and that are thicker than the patient seating area in the inflated state, and wherein the patient seating area is adjacent to a tongue extending from the top panel; and an inflation valve coupled to the top panel at a first location, wherein the inflation valve is configured to couple the at least one inflatable internal chamber to an air inflow.

