

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12416806
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Shin; Bongsu et al.

Image display device capable of expressing multiple depth

Abstract

An image display apparatus includes a display device configured to modulate light to form an image; a driver configured to drive the display device such that a position of the display device varies; a light transmitter configured to transmit the image formed by the display device to an observers eye and comprising a focusing member; and a processor configured to generate a light modulation signal and a driving signal according to image information and control the display device and the driver according to the light modulation signal and the driving signal, respectively.

Inventors:	Shin; Bongsu (Suwon-si, KR), Kim; Yuntae (Suwon-si, KR), Sung; Geeyoung (Suwon-si, KR), Lee; Changkun (Suwon-si, KR)
Applicant:	SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)
Family ID:	1000008821260
Assignee:	SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)
Appl. No.:	17/628111
Filed (or PCT Filed):	July 16, 2020
PCT No.:	PCT/KR2020/009388
PCT Pub. No.:	WO2021/010772
PCT Pub. Date:	January 21, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20220326522 A1	Oct. 13, 2022

Foreign Application Priority Data

KR	10-2019-0087098	Jul. 18, 2019
----	-----------------	---------------

Publication Classification

Int. Cl.: G02B27/01 (20060101); G06F3/01 (20060101)

U.S. Cl.:

CPC G02B27/0172 (20130101); G06F3/013 (20130101); G02B2027/0127 (20130101); G02B2027/014 (20130101)

Field of Classification Search

CPC: G02B (27/01-0189); G02B (2027/0105-0198); G06F (3/00-167)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5737012	12/1997	Tabata et al.	N/A	N/A
9304319	12/2015	Bar-Zeev et al.	N/A	N/A
10088673	12/2017	Xu	N/A	N/A
10379612	12/2018	Bonnier et al.	N/A	N/A
11030926	12/2020	Shin et al.	N/A	N/A
2003/0020879	12/2002	Sonehara	N/A	N/A
2006/0232665	12/2005	Schowengerdt et al.	N/A	N/A
2011/0205633	12/2010	Suzuki	359/872	G02B 27/0101
2015/0153572	12/2014	Miao	359/630	G02B 27/017
2016/0260258	12/2015	Lo et al.	N/A	N/A
2016/0282626	12/2015	Border et al.	N/A	N/A
2016/0286177	12/2015	Border et al.	N/A	N/A
2016/0313558	12/2015	Gutierrez	N/A	N/A
2017/0148215	12/2016	Aksoy	N/A	G02B 27/017
2017/0160798	12/2016	Lanman et al.	N/A	N/A
2017/0255021	12/2016	Oto	N/A	N/A
2017/0269353	12/2016	Xu	N/A	N/A
2017/0330376	12/2016	Haseltine et al.	N/A	N/A
2017/0336637	12/2016	Van Heugten	N/A	N/A
2017/0357088	12/2016	Matsuzaki et al.	N/A	N/A
2018/0015876	12/2017	Yamagata et al.	N/A	N/A
2018/0053284	12/2017	Rodriguez et al.	N/A	N/A
2018/0120567	12/2017	Cobb	N/A	N/A
2018/0275367	12/2017	Lim	N/A	N/A
2018/0275410	12/2017	Yeoh et al.	N/A	N/A

2019/0018236	12/2018	Perreault	N/A	G02B 27/0172
2019/0212546	12/2018	Sohn et al.	N/A	N/A
2019/0302479	12/2018	Smyth et al.	N/A	N/A
2019/0353894	12/2018	Zhou	N/A	N/A
2020/0125227	12/2019	Shin et al.	N/A	N/A
2020/0285310	12/2019	Sazuka et al.	N/A	N/A
2020/0371360	12/2019	Dalrymple et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
107077002	12/2016	CN	N/A
107376349	12/2016	CN	N/A
109863533	12/2018	CN	N/A
109923461	12/2018	CN	N/A
8-234141	12/1995	JP	N/A
2008-020813	12/2007	JP	N/A
100703930	12/2001	KR	N/A
1020140077398	12/2013	KR	N/A
101592087	12/2014	KR	N/A
101626679	12/2015	KR	N/A
101670970	12/2015	KR	N/A
1020180107433	12/2017	KR	N/A
101917762	12/2018	KR	N/A
1020190010345	12/2018	KR	N/A
10-2019-0033405	12/2018	KR	N/A
1020190033414	12/2018	KR	N/A
2012175939	12/2011	WO	N/A
2016/048546	12/2015	WO	N/A
2016/178152	12/2015	WO	N/A
2018/058155	12/2017	WO	N/A
2018/196968	12/2017	WO	N/A
2019/110617	12/2018	WO	N/A

OTHER PUBLICATIONS

Communication dated Jan. 29, 2024, issued by the China Intellectual Property Administration in Chinese Application No. 202010079696.7. cited by applicant

Communication dated Feb. 1, 2024, issued by the China Intellectual Property Administration in Chinese Application No. 202080062250.1. cited by applicant

Communication issued Aug. 7, 2024 by the China National Intellectual Property Administration in Chinese Patent Application No. 202080062250.1. cited by applicant

Communication dated Oct. 30, 2023, issued by the European Patent Office in counterpart European Patent Application No. 20840549.8. cited by applicant

Communication dated Jan. 27, 2021 issued by the European Patent Office in European Application No. 20172099.2. cited by applicant

Communication dated Oct. 27, 2020, issued by the European Patent Office in European Application No. 20172099.2. cited by applicant

International Search Report (PCT/ISA/210) dated Oct. 15, 2020 issued by International Searching Authority for International Application No. PCT/KR2020/009388. cited by applicant

Kim et al., "Foveated AR: Dynamically-Foveated Augmented Reality Display", ACM Trans. Graph, Jul. 2019, 15 total pages, vol. 38. cited by applicant
Communication dated Jul. 14, 2023 issued by the European Patent Office in counterpart European Application No. 20840549.8. cited by applicant
Communication dated Jul. 24, 2023 issued by the European Patent Office in counterpart European Application No. 20172099.2. cited by applicant

Primary Examiner: Lamb, II; Christopher A

Attorney, Agent or Firm: Sughrue Mion, PLLC

Background/Summary

TECHNICAL FIELD

(1) The present disclosure relates to image display device capable of expressing multi-depth.

BACKGROUND ART

(2) 3-dimensional (3D) image display technology has been applied to various fields, and recently, has been applied to an image display apparatus related to a virtual reality (VR) display and an augmented reality (AR) display.

(3) A head-mounted display that provides VR tends to now be widely applied to the entertainment industry as it becomes commercially available. In addition, the head-mounted display is developed into a form that may be applied in the medical, education, and industrial fields.

(4) The AR display, which is an advanced form of the VR display, is an image apparatus that combines the real world and VR and has the feature of deriving the interaction between reality and VR. The interaction between reality and VR is based on a function of providing information about a real situation in real time, and may further increase an effect of reality by superimposing virtual objects or information on an environment of the real world.

(5) In such apparatuses, stereoscopy technology is commonly used for a 3D image display, which may be accompanied by visual fatigue due to a vergence-accommodation mismatch. Accordingly, a 3D image display method capable of reducing visual fatigue has been sought.

DISCLOSURE

Technical Problem

(6) Provided are image display apparatuses capable of multi-depth expression.

Technical Solution

(7) According to an aspect of an embodiment, an image display apparatus includes a display device configured to modulate light to form an image; a driver configured to drive the display device such that a position of the display device varies; a light transmitter configured to transmit the image formed by the display device to an observer's eye and comprising a focusing member; and a processor configured to generate a light modulation signal and a driving signal according to image information and control the display device and the driver according to the light modulation signal and the driving signal, respectively.

(8) Additional aspects will be set forth in part in the description which follows and, in part, will be apparent from the description, or may be learned by practice of the presented embodiments of the disclosure.

(9) The driver may be further configured to move the display device in parallel such that a distance between the display device and the focusing member varies.

(10) The driver may include a shape variable portion which is deformable according to an applied signal to provide a driving force to the display device.

- (11) The shape variable portion may include a material of which a shape varies by heat.
- (12) The shape variable portion may include a shape memory alloy or an electro active polymer.
- (13) The light transmitter may be further configured to transmit the image formed by the display device to the observer's eye as an enlarged image on a virtual image plane at a predetermined position.
- (14) The image information may include depth information related to the position of the virtual image plane with respect to each of images of a plurality of frames, and the processor may be further configured to generate the driving signal according to the depth information.
- (15) The depth information may be information previously set from a saliency map with respect to each of the images of the plurality of frames.
- (16) The processor may be further configured to generate a scale factor to be applied to any one of images of two successive frames with different depth information and generate the light modulation signal by reflecting the scale factor to the image information.
- (17) The processor may be further configured to compute a magnification at which each of the images of the two frames is imaged and set the scale factor to 1 when a change value between two magnifications is equal to or less than a predetermined reference value.
- (18) The processor may be further configured to compute a magnification at which each of the images of the two frames is imaged and determine a similarity of the images of the two frames when the change value between two magnifications is larger than the predetermined reference value.
- (19) The processor may be further configured to set the scale factor to 1 when the similarity of the images of the two frames is equal to or less than a predetermined reference value and generate a scale factor that offsets the change value when the similarity of the images of the two frames is larger than the predetermined reference value.
- (20) The processor may be further configured to, with respect to an image of the same frame, transmit the driving signal to be delayed by a predetermined time compared to the light modulation signal and control the display device and the driver.
- (21) The predetermined time may be set to be equal to or greater than a convergence-accommodation time of an observers eye.
- (22) The light transmitter may be further configured to combine first light including an image from the display device with second light including an image of a real environment in front of an observer and transmit the combined light to the observer's eye.
- (23) The light transmitter may include a beam splitter disposed obliquely with respect to a traveling path of the first light and a traveling path of the second light and the focusing member.
- (24) The beam splitter may be a half mirror.
- (25) The display device may include a first display device and a second display device, the driver may include a first driver and a second driver respectively configured to drive the first display device and the second display device such that positions of the first display device and the second display device vary, and the light transmitter may include a first light transmitter and a second light transmitter configured to transmit images formed by the first display device and the second display device to a left eye and a right eye of an observer, respectively.
- (26) The image information may include information about a pair of left eye image and right eye image to be perceived as a three-dimensional (3D) image of one frame, and the processor may be further configured to control the first display device and the second display device such that the left eye image is formed by the first display device and the right eye image is formed by the second display device.
- (27) The image information may further include depth information related to positions of a virtual image plane on which the left eye image and the right eye image are to be imaged, and the processor may be further configured to control the first driver and the second driver according to the depth information.

- (28) The image display apparatus may be a wearable apparatus.
- (29) The driver may drive the display device to a position corresponding to one of two depth values respectively representing a near and a far.
- (30) The image display apparatus may further include an eye tracking sensor configured to sense a depth position that the observers eye views.
- (31) The processor may generate the driving signal with reference to a measurement value sensed by the eye tracking sensor.
- (32) The processor may determine whether the measurement value is within a near range or a far range, and generate the driving signal so that the display device is driven to a position corresponding to one of two representative values representing the near range and the far range.
- (33) The processor may generate the driving signal based on a depth value set by using a saliency map with respect to each image of a plurality of frames.
- (34) The processor may correct the driving signal by reflecting a measurement value sensed by the eye tracking sensor.
- (35) The processor may correct the driving signal only when a depth value set by using the saliency map and the measurement value sensed by the eye tracking sensor belong to different ranges among previously set near range and far range.

Advantageous Effects

- (36) The image display apparatuses described above may be capable of a wide range of depth expression in a compact structure.
 - (37) The image display apparatuses described above may provide a 3D image combining a binocular disparity method and a depth expression.
 - (38) The image display apparatuses described above may be easily applied to a wearable device, and may be applied to, for example, a glasses-type AR display apparatus, etc.
-

Description

DESCRIPTION OF DRAWINGS

- (1) FIG. 1 is a diagram illustrating a configuration and an optical arrangement of an image display apparatus according to an embodiment;
- (2) FIG. 2 is a block diagram illustrating an example of a configuration of a processor that may be employed in the image display apparatus of FIG. 1;
- (3) FIG. 3 is a block diagram illustrating another example of a configuration of a processor that may be employed in the image display apparatus of FIG. 1;
- (4) FIG. 4 is a block diagram illustrating another example of a configuration of a processor that may be employed in the image display apparatus of FIG. 1;
- (5) FIG. 5 is a flowchart illustrating an example of an operation of a scale factor generator included in the processor of FIG. 4;
- (6) FIGS. 6 and 7 illustrate an example that a display device and image plane positions change according to deformation of a driver together with an example of a structure of the driver in the image display apparatus of FIG. 1;
- (7) FIG. 8 is a perspective view illustrating a detailed shape of the driver of FIGS. 6 and 7;
- (8) FIG. 9 illustrates an example of a configuration of a driver that may be employed in the image display apparatus of FIG. 1;
- (9) FIG. 10 illustrates another example of a configuration of a driver that may be employed in the image display apparatus of FIG. 1;
- (10) FIG. 11 illustrates another example of a configuration of a driver that may be employed in the image display apparatus of FIG. 1;
- (11) FIG. 12 illustrates a configuration and an optical arrangement of an image display apparatus

according to another embodiment;

(12) FIG. 13 is a block diagram illustrating an example of a configuration of a processor included in the image display apparatus of FIG. 12; FIG. 14 is a diagram illustrating a configuration and an optical arrangement of an image display apparatus according to another embodiment;

(13) FIG. 15 is a block diagram illustrating an example of a configuration of a processor that may be employed in the image display apparatus of FIG. 14;

(14) FIG. 16 is a flowchart illustrating an example of a process, performed by the processor of FIG. 15, of generating driving signal;

(15) FIG. 17 is a flowchart illustrating another example of a process, performed by the processor of FIG. 15, of generating driving signal;

(16) FIG. 18 is a block diagram illustrating another example of a configuration of a processor that may be employed in the image display apparatus of FIG. 14; and

(17) FIG. 19 is a flowchart illustrating an example of a process, performed by the processor of FIG. 18, of generating driving signal.

MODE FOR INVENTION

(18) Reference will now be made in detail to embodiments, examples of which are illustrated in the accompanying drawings, wherein like reference numerals refer to like elements throughout. In this regard, the present embodiments may have different forms and should not be construed as being limited to the descriptions set forth herein. Accordingly, the embodiments are merely described below, by referring to the figures, to explain aspects. As used herein, the term “and/or” includes any and all combinations of one or more of the associated listed items. Expressions such as “at least one of,” when preceding a list of elements, modify the entire list of elements and do not modify the individual elements of the list.

(19) Hereinafter, when a constituent element is disposed “above” or “on” to another constituent element, the constituent element may be only directly on the other constituent element or above the other constituent elements in a non-contact manner.

(20) The expression of singularity in the present specification includes the expression of plurality unless clearly specified otherwise in context. Also, terms such as “comprise” and/or “comprising” may be construed to denote a constituent element, but may not be construed to exclude the existence of or a possibility of addition of another constituent element.

(21) The use of the terms “a” and “an” and “the” and similar referents in the context of describing the disclosure (especially in the context of the following claims) are to be construed to cover both the singular and the plural.

(22) Also, operations of all methods described herein may be performed in any suitable order unless otherwise indicated herein or otherwise clearly contradicted by context. The present disclosure is not limited to the described order of the operations. The use of any and all examples, or language (e.g., “such as”) provided herein, is intended merely to better illuminate the disclosure and does not pose a limitation on the scope of the disclosure unless otherwise claimed.

(23) FIG. 1 is a diagram illustrating a configuration and an optical arrangement of an image display apparatus 1000 according to an embodiment, and FIG. 2 is a block diagram illustrating an example of a configuration of a processor 400 that may be employed in the image display apparatus 1000 of FIG. 1.

(24) The image display apparatus 1000 includes a display device 100 that modulates light to form an image, a driver 200 that drives the display device 100 such that a position of the display device 100 varies, a light transmitter 300 that transmits an image formed by the display device 100 to the observer's eyes, and the processor 400 that controls the display device 100 and the driver 200 according to image information.

(25) The display device 100 modulates the light according to the image information of the image to be provided to an observer to form the image. The image formed by the display device 100 may be provided to both eyes of the observer, and for convenience, only an optical system toward one eye

is shown in the drawing. The image formed by the display device **100** may be, for example, a stereo image provided to each of the left and right eyes of the observer, a hologram image, a light field image, an integral photography (IP) image, etc., and may include a multi-view or super multi-view image. In addition, the image is not limited thereto and may be a general two-dimensional (2D) image.

(26) The display device **100** may include, for example, a liquid crystal on silicon (LCoS) device, a liquid crystal display (LCD) device, an organic light emitting diode (OLED) display device, and a digital micromirror device (DMD), and also may include next-generation display devices such as a micro LED, a quantum dot LED, etc.

(27) Although not illustrated in the image display apparatus **1000**, a light source that provides the light for forming the image may be provided in the display device **100**, and a configuration such as a beam splitter for adjusting an optical path, a relay lens for enlarging or reducing the image, a spatial filter for noise removal, etc. may be further provided.

(28) The light transmitter **300** changes a path of the image formed by the display device **100**, forms the image of a size suitable for the observer's field of vision, and transmits the image to the observer's eye. The light transmitter **300** may include a focusing member **310** and may also include a beam splitter **330** as a member for diverting the light to change the path.

(29) The focusing member **310** may include an image forming member having refractive power and may enlarge or reduce the image formed by the display device **100**. The focusing member **310** is shown as a concave mirror, but is not limited thereto. The focusing member **310** may have a combination shape of a concave mirror, a convex lens, a concave lens, etc.

(30) The beam splitter **330** may include a half mirror that transmits half of an incidence light and reflects the other half thereof. However, the beam splitter **330** is not limited thereto and may include a polarizing beam splitter that transmits or reflects the incidence light according to polarization. When the beam splitter **330** may include a polarizing beam splitter, additional optical elements for polarization conversion may be further provided in the light transmitter **300**.

(31) As shown, the focusing member **310** and the beam splitter **330** are fixed through a transparent light guide member **350** such that the light transmitter **300** may have an integral structure. However, this is an example and is not limited thereto.

(32) The light transmitter **300** not only may transmit the light including the image formed by the display device **100** to the observer's eye, but also may transmit the light including a real environment image of the front of the observer. Accordingly, the image display apparatus **1000** may function as a see-through type display.

(33) The light transmitter **300** is not limited to the illustrated shape and configuration. An additional optical element may be further provided so as to transmit the image formed by the display device **100** to an observer's pupil along with the real environment image of the front of the observer, and optical windows having various shapes and structures may be employed.

(34) The light of the image formed by the display device **100** reaches the observer's eye along a path such that the light passes through the beam splitter **330** and is reflected by the focusing member **310** and then reflected by the beam splitter **330**. In this path, the observer recognizes a virtual image formed on a virtual image plane VP at a predetermined position of the rear of the beam splitter **330**, and a sense of depth sensed by the observer varies depending on the position of the virtual image plane VP.

(35) The image display apparatus **1000** according to an embodiment may not fix the position of the virtual image plane VP to one value but may change the position of the virtual image plane VP by reflecting the sense of depth of the image to be displayed. To this end, the image display apparatus **1000** includes the driver **200** for driving the position of the display device **100**. The driver **200** may move the display device **100** in parallel such that a distance between the driver **200** and the focusing member **310** varies. When the position of the display device **100** varies in an A1 direction, the position of the virtual image plane VP varies in an A2 direction.

(36) The driver **200** employed in the image display apparatus **1000** employs a shape variable material in order to widen the position driving range of the display device **100** in a volume as small as possible. That is, the driver **200** may be deformed according to an applied signal and provide driving force to the display device **100**. For such shape variation, a material of which a shape varies by heat may be employed in the driver **200**. The driver **200** may include a shape memory alloy (SMA) or an electro active polymer (EAP). An example of a detailed configuration of varying the position of the display device **100** by driving the driver **200** will be described later with reference to FIGS. **6** to **11**.

(37) The processor **400** may generate a light modulation signal SG**1** to be transmitted to the display device **100** and a driving signal SG**2** to be transmitted to the driver **200** according to image information related to an image to be perceived by the observer. The display device **100** and the driver **200** are controlled by the generated light modulation signal SG**1** and the driving signal SG**2**, respectively. That is, the image is formed on the display device **100** by the light modulation signal SG**1**, and the position of the display device **100** is driven such that the virtual image plane VP set appropriately in accordance with the image is located.

(38) The image display apparatus **1000** may also include a memory **500** and may store various data and codes of programs necessary for driving the image display apparatus **1000** in the memory **500** including the image information.

(39) The processor **400** may include a light modulation signal generator **410** and a driving signal generator **480**. The light modulation signal SG**1** and the driving signal SG**2** are generated by the light modulation signal generator **410** and the driving signal generator **480**, respectively, with reference to the image information.

(40) The image information may include data for each pixel related to color values of a plurality of pixels with respect to each of images of a plurality of frames to be provided to the observer, and include depth information related to the position of the virtual image plane VP on which each image is imaged.

(41) The depth information included in the image information may be a previously determined representative depth value with respect to each of the images of the plurality of frames. This depth value may be set to one or more values.

(42) The representative depth may be previously set from a saliency map. A saliency map analysis may be performed to select a region that is highly likely to be viewed by the observer, that is, a region having a high visual concentration. Brightness, color, outline, object size, etc. may be considered to select the region having high visual concentration. For example, a region having a great difference in brightness or color, a region having a strong outline feature, and a region having a large size of an object compared to the surroundings may be areas of high visual concentration. A depth value corresponding to this region may be selected as the representative depth. Alternatively, a position with high visual concentration may be selected according to contents included in the image.

(43) In addition, the representative depth may be set according to, for example, a frequency of each depth by analyzing a depth map and a color map of the image. Alternatively, the representative depth may be set through a zone of comfort (ZOC) analysis considering human visual perception characteristics.

(44) The representative depth set as described above may be a successive value or may be a plurality of discrete values. That is, not all of values necessary for depth representation are used, but the representative depth may be set among discrete values obtained by quantizing these values at predetermined intervals. In the case of quantizing the depth value, when the representative depth value is selected for every frame for moving image representation, a variation of the representative depth value selected in successive frames may be reduced. Accordingly, the position variation of the display device **100** by the driver **200** may be reduced, and when the position of the virtual image plane VP changes in correspondence to the representative depth, the driving signal SG**2**

applied to the driver **200** may also be quantized and may be easily driven. When the same representative depth value is selected in the successive frames, the position driving of the display device **100** is not necessary, and thus, driving of the image display apparatus **1000** may be further simplified. The quantized depth value may be set to, for example, two depth values respectively representing near and far.

(45) The light modulation signal generator **410** may generate an electric signal implementing the color value determined with reference to the data for each pixel included in the image information as the light modulation signal SG1.

(46) The driving signal generator **480** may generate the driving signal SG2 for moving the position of the display device **100** such that the virtual image plane VP is formed on a position corresponding to the representative depth value set with reference to the depth information. The driving signal SG2 may be, for example, an electrical signal that generates heat suitable for deformation of the variable material of the driver **200**.

(47) The light modulation signal SG1 and the driving signal SG2 may be transmitted to the display device **100** and the driver **200**, respectively, such that the corresponding image may be perceived by the observer from a changed position of the virtual image plane VP.

(48) The driving signal SG2 for driving the driver **200** may be transmitted to be delayed by a predetermined time compared to the light modulation signal SG1. The predetermined time may be set to be equal to or greater than a convergence-accommodation time of the observers eye. This takes into account the time it takes for the human eye to perceive an image of a changed depth position.

(49) FIG. 3 is a block diagram illustrating another example of a configuration of a processor **401** that may be employed in the image display apparatus **1000** of FIG. 1.

(50) The processor **401** may further include a representative depth extractor **430** together with the light modulation signal generator **410** and the driving signal generator **480**.

(51) In the description of FIG. 2, the image information is described as including previously set depth information, but is not limited thereto. The processor **401** may include the representative depth extractor **430**. That is, the processor **401** extracts a representative depth for each image with reference to data for each pixel included in the image information and reflects the representative depth to the image information again. Referring to this, the driving signal generator **480** may generate the driving signal SG2.

(52) FIG. 4 is a block diagram illustrating another example of a configuration of a processor **402** that may be employed in the image display apparatus **1000** of FIG. 1, and FIG. 5 is a flowchart illustrating an example of an operation of a scale factor generator **450** included in the processor **402** of FIG. 4.

(53) The processor **402** may further include the scale factor generator **450** in addition to the light modulation signal generator **410**, the driving signal generator **480**, and the representative depth extractor **430**.

(54) The scale factor generator **450** generates a scale factor to be applied to any one of images of two consecutive frames having different depth information.

(55) This is considered that when the images of the two consecutive frames have different virtual image planes VPs, the images of the two consecutive frames may exhibit different magnifications.

(56) A magnification m is defined as follows.

$$(57) \frac{d_i}{d_o} = \frac{\text{imagedistance}}{\text{objectdistance}} = m(\text{magnification})$$

(58) wherein, $d_{\text{sub.o}}$ denotes a distance from an image display surface of the display device **100** to the focusing member **310**, and $d_{\text{sub.i}}$ denotes a distance from the focusing member **310** to the virtual image plane VP. $d_{\text{sub.i}}$ denotes a distance along an virtual light path, and the indicated distances $d_{\text{sub.i}}$ and $d_{\text{sub.i}'}$ include a distance from the center of the focusing member **310** to the center of the beam splitter **330** and a distance from the center of the beam splitter **330** to the virtual image plane VP.

(59) When $d_{sub.o}$ and $d_{sub.i}$ are determined according to a position of the display device **100** and a position of the virtual image plane VP and the magnification at this time is m , a magnification m' corresponding to a changed position of the virtual image plane VP is $d_{sub.i}'/d_{sub.o}'$, which is different from m . This change in the magnification in the successive frame images may be felt to be awkward to an observer. In order to form a more natural sense of depth, the processor **402** may form an image on the display device **100** by reflecting the scale factor that may offset the change in the magnification to the image information.

(60) The scale factor does not have to be applied to all successive frame images having different magnifications, and may be applied when a magnification change value is larger than a predetermined reference value. In addition, even when the magnification change value is large, the application of the scale factor may not be required for images of other scenes which are not related to each other. Considering this situation, the scale factor may be set and applied.

(61) Referring to FIG. 5, in order to generate the scale factor, the scale factor generator **450** determines the change in the magnification of the images of the two consecutive frames (S451). That is, the scale factor generator **450** computes magnifications m_1 and m_2 of each of the images of the two consecutive frames and calculates a change value. The change value may be defined, for example, as a ratio m_2/m_1 or a difference m_2-m_1 .

(62) Next, the scale factor generator **450** compares the calculated change value between the two magnifications m_1 and m_2 with a predetermined reference value (S452).

(63) If the change value between the two magnifications m_1 and m_2 is less than or equal to the predetermined reference value, the scale factor generator **450** sets the scale factor to 1 (S456).

(64) Otherwise, when the change value between the two magnifications m_1 and m_2 is larger than the predetermined reference value, the scale factor generator **450** determines a similarity of the images of the two frames (S453). In order to determine the similarity of the images, a numerical value defined according to a predetermined determination reference may be compared. The numerical value is referred to as the similarity. The similarity may be defined based on a pixel value, or may be defined by other reference suitable for image comparison.

(65) Even when the change in the magnification is large, the scale factor may not be applied with respect to an unrelated scene. This is because an observer may feel the change in the magnification naturally as part of a scene change. When the similarity of the compared images of the two frames is equal to or less than a predetermined reference value, the scale factor generator **450** may set the scale factor to 1 (S456).

(66) When the similarity of the compared images of the two frames is larger than the predetermined reference value, the scale factor generator **450** may generate the scale factor that offsets the magnification change value (S455). For example, when the change value is set as a ratio, the scale factor may be set to a value inversely proportional to the magnification change value.

(67) As such, the scale factor set by the scale factor generator **450** is reflected to the image information again, and the light modulation signal generator **410** generates a light modulation signal with reference thereto.

(68) As described with reference to FIG. 3, the representative depth extractor **430** may set the representative depth from the image information and reflect the representative depth to the image information as depth information. Referring to the representative depth, the driving signal generator **480** may generate the driving signal SG2.

(69) The processor **402** illustrated in FIG. 4 includes the representative depth extractor **430** together with the scale factor generator **450** but this is an example. The processor **402** does not have to include the representative depth extractor **430** and the scale factor generator **450** together. For example, a representative depth set by another processor or the like may be previously included in the image information as the depth information. In addition, the scale factor may be set by another processor or the like and previously included in the image information.

(70) FIGS. 6 and 7 illustrate an example that the display device **100** and the image plane positions

change according to deformation of the driver **200** together with an example of a structure of the driver **200** in the image display apparatus **1000** of FIG. **1**. FIG. **8** is a perspective view illustrating a detailed shape of the driver **200** of FIGS. **6** and **7**.

(71) Referring to FIGS. **6** and **7**, the driver **200** may include a deformation portion **210**, a bridge portion **220**, and a driving controller **230**. The deformation portion **210** may have a wire shape. The length of the deformation portion **210** may vary depending on the temperature of the deformation portion **210** or an electric field formed in the deformation portion **210**. For example, the deformation portion **210** may include an SMA, an EAP, and a combination thereof. When the deformation portion **210** includes an SMA, the deformation portion **210** may have a short length at a high temperature and may have a long length at a low temperature. When the deformation portion **210** includes an EAP and when the electric field is applied to the deformation portion **210**, the length of the deformation portion **210** may increase in a direction perpendicular to the applied electric field. Hereinafter, an example that the deformation portion **210** is deformed by the temperature will be described.

(72) As shown in FIG. **8**, the bridge portion **220** includes a plate shape member extending in one direction and provided with recess regions facing each other at both ends. The bridge portion **220** may have elasticity and may be bent by the deformation portion **210** to have an arch shape. The deformation portion **210** may be fitted into the recess regions of the bridge portion **220** and may have a shape surrounding an end of the bridge portion **220**. When the deformation portion **210** winds both ends of the bridge portion **220**, the recess regions of the bridge portion **220** fix the deformation portion **210**, and thus, positions of the deformation portion **210** and the bridge portion **220** may be aligned.

(73) The temperature of the deformation portion **210** may be adjusted by an electrical signal applied to the deformation portion **210**. The electrical signal may be applied by the driving controller **230**. The driving controller **230** may apply the electrical signal to the deformation portion **210** according to the driving signal SG2 transmitted from the processor **400**. The electrical signal may be a current signal or a voltage signal. For example, a current is applied to the deformation portion **210** by the driving controller **230** to increase the temperature of the deformation portion **210**. When no current is applied to the deformation portion **210**, the temperature of the deformation portion **210** may be lowered.

(74) A degree of bending of the bridge portion **220** may vary according to a change in the length of the deformation portion **210**. When the length of the deformation portion **210** decreases, the degree of bending of the bridge portion **220** may increase. Accordingly, a distance between the display device **100** and the focusing member **310** may decrease. When the length of the deformation portion **210** increases, the degree of bending of the bridge portion **220** may be reduced. Accordingly, the distance between the display device **100** and the focusing member **310** may increase.

(75) Referring to FIG. **6**, the driving controller **230** may not apply a current to the deformation portion **210**. In this state, the display device **100** may be spaced apart from the focusing member **310** by the distance $d_{\text{sub.o'}}$, and a distance on an optical path from the focusing member **310** to the virtual image plane VP may be $d_{\text{sub.i'}}$.

(76) Referring to FIG. **7**, the current may be applied to the deformation portion **210** to increase the temperature of the deformation portion **210**. The current may be applied by the driving controller **230**. Accordingly, the length of the deformation portion **210** may decrease. The temperature of the deformation portion **210** may be controlled such that a degree of change in the length of the deformation portion **210** may be adjusted.

(77) When the length of the deformation portion **210** decreases, the degree of bending of the bridge portion **220** may increase. In this deformation process, the bridge portion **220** may push the display device **100** to place the display device **100** close to the light transmitter **300**. The distance between the display device **100** and the focusing member **310** may decrease to $d_{\text{sub.o}}$, and the distance

between the virtual image plane VP and the focusing member **310** may decrease to d.sub.i.

(78) Referring back to FIG. **6**, when the driving controller **230** does not apply current to the deformation portion **210** again, the temperature of the deformation portion **210** may be lowered and the length thereof may increase again. The degree of bending of the bridge portion **220** may be reduced. The distance between the display device **100** and the focusing member **310** may increase again to d.sub.o, and the distance between the virtual image plane VP and the focusing member **310** may decrease again to d.sub.i'.

(79) FIGS. **9** to **11** illustrate examples of configurations of drivers **201**, **202**, and **203** that may be employed in the image display apparatus **1000** of FIG. **1**.

(80) Referring to FIG. **9**, the driver **201** may include deformation portions **212**, a support portion **240**, and the driving controller **230**. Each of the deformation portions **212** may be substantially the same as the deformation portion **210** described with reference to FIG. **8** except for a position and a shape thereof.

(81) The deformation portions **212** may be disposed between the support portion **240** and the display device **100**. Both ends of each of the deformation portions **212** may be in contact with the support portion **240** and the display device **100**, respectively. A pair of deformation portions **212** is shown, but this is an example. In other embodiments, one deformation portion **212** or three or more deformation portions **212** may be provided.

(82) The driving controller **230** may be electrically connected to the deformation portions **212** to apply an electrical signal to each of the deformation portions **212**. For example, the driving controller **230** may apply a current to the deformation portions **212**.

(83) When the electrical signal is applied to the deformation portions **212** and the temperature of each of the deformation portions **212** increases, the length of each of the deformation portions **212** may decrease. In this case, the display device **100** is closer to the support portion **240**, that is, a distance from the display device **100** to the focusing member **310** increases.

(84) By controlling the temperature of each of the deformation portions **212**, a degree of change in the length of each of the deformation portions **212** may be adjusted and the distance between the display device **100** and the focusing member **310** may be controlled.

(85) Referring to FIG. **10**, the driver **202** may include the deformation portions **212**, the support portion **240**, restoration portions **252**, and the driving controller **230**. The deformation portions **212**, the support portion **240**, and the driving controller **230** may be substantially the same as those described with reference to FIG. **9**.

(86) The restoration portions **252** may be provided between the support portion **240** and the display device **100**. The restoration portions **252** may extend from the support portion **240** to the display device **100**. The restoration portions **252** may extend to cross each other. Both ends of each of the restoration portions **252** may be in contact with the support portion **240** and the display device **100**, respectively. The restoration portions **252** may have elasticity. For example, each of the restoration portions **252** may include a rod including carbon. When the restoration portions **252** are bent, the restoration portions **252** may have a restoring force to be restored to a state before bent again.

(87) When an electrical signal is applied to the deformation portions **212**, the temperature of each of the deformation portions **212** increases, the length of each of the deformation portions **212** decreases, and the restoration portions **252** are bent. Accordingly, the display device **100** receives a driving force moving toward the support portion **240**, and the distance between the display device **100** and the focusing member **310** increases. The temperature of the deformation portions **212** may be controlled such that the degree of change in the length of each of the deformation portions **212** may be adjusted, and the distance between the display device **100** and the focusing member **310** may be controlled.

(88) The restoration portions **252** have the restoring force, and thus, when the applied electrical signal disappears, the restoration portions **252** may be restored to the original state according to an increase in the length of each of the deformation portions **212**. The restoring force may act in a

direction in which a distance between the display device **100** and the support portion **240** increases, and accordingly, the distance between the display device **100** and the focusing member **310** may decrease.

(89) Referring to FIG. **11**, the driver **203** may include deformation portions **212**, the support portion **240**, restoration portions **254**, and the driving controller **230**. The deformation portions **212**, the support portion **240**, and the driving controller **230** may be substantially the same as those described with reference to FIG. **9**.

(90) The restoration portions **254** may be provided between the support portion **240** and the display device **100**. The restoration portions **254** may include a torsion spring. When the restoration portions **254** are twisted, the restoration portions **254** may have a restoring force to be restored to a state before twisted. Both ends of each of the restoration portions **254** may be in contact with the support portion **240** and the display device **100**, respectively.

(91) When the electrical signal is applied to the deformation portions **212**, the temperature of each of the deformation portions **212** may increase, the length of each of the deformation portions **212** may decrease, and the display device **100** and the support portion **240** may be close to each other. As the display device **100** and the support portion **240** are close to each other, the restoration portions **254** may be twisted. Accordingly, the display device **100** is far away from the focusing member **310**. By controlling the temperature of each of the deformation portions **212**, the degree of change in the length of each of the deformation portions **212** may be adjusted and the distance between the display device **100** and the focusing member **310** may be controlled.

(92) The restoration portions **254** have a restoring force to return to an initial state, and thus, when the applied electric signal disappears, the restoration portions **254** may be restored to the original state according to an increase in the length of the deformation portions **212**. The restoring force may act in a direction in which the distance between the display device **100** and the support portion **240** increases. Accordingly, the distance between the display device **100** and the focusing member **310** may decrease.

(93) As described above, the drivers **200**, **201**, **202**, and **203** that may be provided in the image display apparatus **1000** according to the embodiment may employ a shape variable material to have a small volume and increase a position driving range of the display device **100**. The driving range of the display device **100** may be within about 1 mm. When the driving range is implemented by, for example, a voice coil motor, a piezo actuator, or the like, a volume increase is very large, whereas in the embodiment, the driving range may be implemented with a volume smaller than these.

(94) FIG. **12** illustrates a configuration and an optical arrangement of an image display apparatus **2000** according to another embodiment. FIG. **13** is a block diagram illustrating an example of a configuration of a processor **800** included in the image display apparatus **2000** of FIG. **12**.

(95) The image display apparatus **2000** may include a first display device **160**, a first driver **260**, a first light transmitter **360**, a second display device **170**, a second driver **270**, and a second light transmitter **370**.

(96) The first driver **260** and the second driver **270** drive positions of the first display device **160** and the second display device **170**, respectively, and the first light transmitter **360** and the second light transmitter **370** transmit images formed by the first display device **160** and the second display device **170** to the left and right eyes of an observer, respectively.

(97) The image display apparatus **2000** further includes the processor **800** and a memory **700**. The processor **800** controls the first display device **160**, the second display device **170**, the first driver **260**, and the second driver **270** according to image information stored in the memory **700**. The processor **800** may include a light modulation signal generator **810** and a driving signal generator **880**. Program codes for executing the light modulation signal generator **810** and the driving signal generator **880** may be stored in the memory **700**.

(98) The image information stored in the memory **700** may include information about a pair of a

left eye image and a right eye image that may be perceived as 3D images of one frame. The left eye image and the right eye image have a predetermined disparity. The processor **800** generates light modulation signals SG1_L and SG1_R such that the left eye image is formed on the first display device **160** and the right eye image is formed on the second display device **170** and accordingly, controls the first display device **160** and the second display device **170**.

(99) The image information may further include depth information related to positions of the virtual image plane VP on which the left eye image and the right eye image are to be imaged, and the processor **800** generates driving signals SG2_L and SG2_R such that the virtual image plane VP is formed according to the depth information, that is, on a set depth position and controls the first driver **160** and the second driver **270**.

(100) The depth information may be previously set with respect to an image of each frame and stored in the memory **700**, or the set depth information may be reflected to the image information according to execution of a representative depth extractor **830** included in the processor **800**.

(101) The processor **800** may also include a scale factor generator **850** in addition to the light modulation signal generator **810** and the representative depth extractor **830**, and the driving signal generator **880**.

(102) The scale factor generator **850** differs only in generating a scale factor according to a change in the magnification between successive frame images with respect to left eye image information and right eye image information respectively provided for both eyes and is substantially the same as the scale factor generator **450** described with reference to FIGS. **4** and **5**.

(103) The image display apparatus **2000** according to the embodiment may express a 3D image by combining a binocular disparity method and a depth expression. For an image including an object of a predetermined depth position, a vergence accommodation conflict (VAC) may be reduced by adjusting a position of the virtual image plane VP on which the image is imaged. In addition, an image in which objects are present at various depth positions may be formed on the virtual image plane VP, for example, using a depth position of a main object determined according to the salience map as the representative depth position, and the remaining sense of depth may be expressed in binocular parallax such that a 3D image may be perceived. In addition, as the representative depth position, only two values identified as near and far in an image of a plurality of frames may be used. Since the image display apparatus **2000** according to the embodiment utilizes both the binocular parallax and the scale factor, a natural depth expression with less eye fatigue of the observer is possible even by using only two types of depth values. In the above-described image display apparatuses **1000** and **2000**, an eye tracking module tracking an observer's gaze may be further applied, and information measured by the eye tracking module may be used to generate a driving signal driving a position of a display device.

(104) FIG. **14** is a diagram illustrating a configuration and an optical arrangement of an image display apparatus **3000** according to another embodiment. FIG. **15** is a block diagram illustrating an example of a configuration of a processor that may be employed in the image display apparatus **3000** of FIG. **14**.

(105) The image display apparatus **3000** of the present embodiment is different from the image display apparatus **2000** of FIG. **12** in that the image display apparatus **3000** further includes an eye tracking sensor ES, and a processor **801** processes a signal S_ES sensed by the eye tracking sensor ES and generates driving signals SG2_R and SG2_L. Hereinafter, the differences will be mainly described.

(106) The image display apparatus **3000** may include a first display device **160**, a first driver **170**, a first light transmitter **360**, a second display device **260**, and a second driver **270**, and a second light transmitter **370**. As described above, the first driver **260** and the second driver **270** may have a structure of any one of the drivers **200**, **201**, **202**, and **203** employing a shape variable material, or combined or modified therefrom. The first driver **260** and the second driver **270** may drive positions of the first display device **160** and the second display device **170**, respectively, and the

first light transmitter **360** and the second light transmitter **370** may transmit images formed by the first display device **160** and the second display device **170**, respectively, to observer's left eye and right eye.

(107) The image display apparatus **3000** may also include the eye tracking sensor ES that tracks an observer's gaze. The eye tracking sensor ES may sense an actual position and a rotation angle of the pupil, and may sense a vergence position of both eyes. The signal S_ES sensed by the eye tracking sensor ES may be transmitted to the processor **801**, and an eye tracking module included in the processor **801** may calculate a depth position that an observer views.

(108) FIGS. **14** and **15** illustrate that the two eye tracking sensors ES are disposed in the first light transmitter **360** and the second light transmitter **370**, respectively, but the present disclosure is not limited thereto. The eye tracking sensors ES may be disposed in other suitable positions at which the pupil positions of both eyes may be sensed, and the number thereof may be changed.

(109) Referring to FIG. **15**, the processor **801** may include a light modulation signal generator **810**, a driving signal generator **880**, and a representative depth determiner **831**, and may further include a scale factor generator **850**. The representative depth determiner **831** may include the eye tracking module that processes the signal S_ES sensed by the eye tracking sensor ES and determines the depth position that the observer views, and a program code for execution of the eye tracking module may be stored in the memory **700**.

(110) FIG. **16** is a flowchart illustrating an example of a process, performed by the processor **801** of FIG. **15**, of generating the driving signals SG2_R and SG2_L.

(111) The representative depth determiner **831** processes a signal sensed by the eye tracking sensor ES and determines a depth value dm corresponding to depth position that an observer views (S810), and then, based on the determined depth value dm, generates the driving signals SG2_R and SG2_L (S815). That is, the driving signals SG2_R and SG2_L used to change positions of the display devices **160** and **170** are generated so that a virtual image plane VP is formed on a position corresponding to the determined depth value dm, and are transmitted to the first driver **260** and the second driver **270**.

(112) FIG. **17** is a flowchart illustrating another example of a process, performed by the processor **801** of FIG. **15**, of generating the driving signals SG2_R and SG2_L.

(113) The representative depth determiner **831** processes a signal sensed by the eye tracking sensor ES and determines the depth value dm corresponding to the depth position that an observer views (S820), and then, sets a representative depth value dr to be reflected in the generation of the driving signals SG2_R and SG2_L from the determined depth value dm (S823). The representative depth value dr may be determined as one of two values dn and df respectively representing previously set near range and far range. In such setting, the two representative values dn and df, and a depth value dc serving as a criterion identifying the near range and the far range may be determined in advance. When the depth value dm determined by the eye tracking sensor ES is smaller than dc ($0 < dm < dc$), dn may be determined as the representative depth value dr. When the depth value dm determined by the eye tracking sensor ES is greater than dc ($dc < dm < \infty$), df may be determined as the representative depth value dr. When the depth value dm determined by the eye tracking sensor ES is equal to dc, dn or df may be determined as the representative depth value dr.

(114) Next, based on the determined representative depth value dr, the driving signals SG2_R and SG2_L are generated (S825). That is, the driving signals SG2_R and SG2_L used to change positions of the display devices **160** and **170** are generated so that the virtual image plane VP is formed on a position corresponding to the determined depth value dm, and are transmitted to the first driver **260** and the second driver **270**.

(115) Even the sense of depth is expressed by using only two depth values representing two ranges identified as near and far as described above, the image display apparatus **3000** according to the embodiment utilizes a binocular parallax and a scale factor together, thereby reducing fatigue of observers eyes, and enabling a natural depth expression.

(116) FIG. **18** is a block diagram illustrating another example of a configuration of a processor **802** that may be employed in the image display apparatus **3000** of FIG. **14**. FIG. **19** is a flowchart illustrating an example of a process, performed by the processor **802** of FIG. **18**, of generating the driving signals SG2_R and SG2_L.

(117) The processor **802** may include the light modulation signal generator **810**, the driving signal generator **880**, and a representative depth determiner **832**, and may further include the scale factor generator **850**. The representative depth determiner **832** may include a saliency map module and an eye tracking module, that is, which may be utilized to generate the driving signals SG2_R and SG2_L.

(118) Referring to FIG. **18**, first, the depth value ds may be determined by using the saliency map module (**S830**). As described above, the saliency map analysis is to select a region with a high probability of an observer's attention, that is, a region with a high visual concentration. The depth value ds of the selected region may be determined as a representative depth value of the corresponding frame image. In order to select the region with high visual concentration, for example, brightness, color, outline, object size, etc. may be considered.

(119) The driving signals SG2_R and SG2_L are generated according to the determined depth value ds (**S832**).

(120) In addition, the depth value dm is determined from a sensing result of the eye tracking sensor ES (**S834**). Next, the driving signals SG2_R and SG2_L are corrected with reference to the determined depth value dm .

(121) Such a process is to reflect the case that unlike the result of the saliency map analysis, the observer intentionally focuses his or her gaze on another region, to driving of a position of a display device. For example, although the position of the display device is driven so that an image is displayed on a position of a virtual position suitable for a viewing region expected by the saliency map analysis, when the observer views another region, visual fatigue may be accompanied due to the vergence-accommodation mismatch. In addition, as a depth difference between the expected viewing position and an actual viewing position increases, fatigue may increase. Therefore, while a representative depth is set for each of a plurality of frame images by utilizing the saliency map analysis, a more natural depth expression is possible by correcting the driving signals SG2_R and SG2_L by referring to the sensing result of the eye tracking sensor ES.

(122) When the depth value ds is determined by utilizing the saliency map, the depth value may be determined as one of two representative values representing a near range and a far range, rather than a successive value. In this case, the driving signals SG2_R and SG2_L are corrected only when the depth value ds determined by the saliency map analysis and the depth value dm determined by the eye tracking sensor ES belong to different ranges. That is, the driving signals SG2_R and SG2_L are corrected only when the observer views a far region with respect to an image that is expected to view the near region, or vice versa. In other words, even when there is a slight difference between the expected viewing region set in the saliency map and the actual viewing region, the driving signals SG2_R and SG2_L are not corrected when the two regions are within the same range. As described above, the natural depth expression is possible while driving a driver as simple as possible by combining the saliency map and gaze tracking of the observer.

(123) The image display apparatuses **1000**, **2000** and **3000** described above may be configured in a wearable form. All or some of components of the image display apparatuses **1000** and **2000** may be configured in a wearable form.

(124) For example, the image display apparatuses **1000**, **2000** and **3000** may be applied in the form of a head mounted display (HMD). In addition, the image display apparatuses **1000** and **2000** are not limited thereto, and may be applied to a glasses-type display or a goggle-type display.

(125) The image display apparatuses **1000**, **2000** and **3000** described above may be applied to implement augmented reality (AR) in that both an image formed on a display device and an image of the real world may be shown to an observer.

(126) The AR may further increase an effect of reality by showing a virtual object or information combined on an environment of the real world. For example, at a position of the observer, an image forming unit may form additional information about the environment provided by the real world and provide the additional information to the observer. An AR display may be applied to a ubiquitous environment or an internet of things (IoT) environment.

(127) The image of the real world is not limited to a real environment, and may be, for example, an image formed by another image device. Accordingly, the image display apparatuses described above may be applied to multi image display apparatuses that display two images together.

(128) The image display apparatuses **1000**, **2000** and **3000** described above may operate in synchronization with or in connection to other electronic devices such as a smart phone. For example, a processor for driving the image display apparatuses **1000**, **2000** and **3000** may be provided in the smart phone. In addition, the image display apparatuses **1000**, **2000** and **3000** described above may be provided in a smart phone.

(129) It should be understood that embodiments described herein should be considered in a descriptive sense only and not for purposes of limitation. Descriptions of features or aspects within each embodiment should typically be considered as available for other similar features or aspects in other embodiments. While one or more embodiments have been described with reference to the figures, it will be understood by those of ordinary skill in the art that various changes in form and details may be made therein without departing from the spirit and scope as defined by the following claims.

Claims

1. An image display apparatus comprising: a display device configured to modulate light to form an image; a driver configured to drive the display device such that a position of the display device varies; a light transmitter configured to transmit the image formed by the display device to an observer's eye and comprising a focusing member; and a processor configured to: generate driving signal based on image information, wherein the image information comprises depth information related to the position of a virtual image plane with respect to each of a plurality of images, generate a scale factor to be applied to any one of two successive images with different depth information from among the plurality of images, generate a light modulation signal based on the image information and the scale factor, and control the display device and the driver according to the light modulation signal and the driving signal, respectively.
2. The image display apparatus of claim 1, wherein the driver is further configured to move the display device in parallel such that a distance between the display device and the focusing member varies.
3. The image display apparatus of claim 1, wherein the driver comprises a shape variable portion which is deformable according to an applied signal to provide a driving force to the display device.
4. The image display apparatus of claim 3, wherein the shape variable portion comprises a material of which a shape varies by heat.
5. The image display apparatus of claim 3, wherein the shape variable portion comprises a shape memory alloy or an electro active polymer.
6. The image display apparatus of claim 1, wherein the light transmitter is further configured to transmit the image formed by the display device to the observer's eye as an enlarged image on the virtual image plane at a predetermined position.
7. The image display apparatus of claim 1, wherein the depth information comprises information previously set from a saliency map with respect to each of the images of the plurality of frames.
8. The image display apparatus of claim 1, wherein the processor is further configured to: compute a magnification at which each of the two successive images is imaged, and based on a change value between the magnifications at which each of the two successive images is imaged being equal to or

less than a predetermined reference value, set the scale factor to 1.

9. The image display apparatus of claim 1, wherein the processor is further configured to: compute a magnification at which each of the two successive images is imaged, and based on the change value between the magnifications at which each of the two successive images is imaged being larger than a predetermined reference value, determine a similarity of the two successive images.

10. The image display apparatus of claim 9, wherein the processor is further configured to: based on the similarity of the two successive images being equal to or less than a the predetermined reference value, set the scale value to 1, and based on the similarity of the two successive images being larger than the predetermined reference value, generate a scale factor that offsets the change value.

11. The image display apparatus of claim 1, wherein the processor is further configured to transmit the driving signal based on a predetermined time delay compared to transmission of the light modulation signal.

12. The image display apparatus of claim 11, wherein the predetermined time delay is equal to or greater than a convergence-accommodation time of the observer's eye.

13. The image display apparatus of claim 1, wherein the light transmitter is further configured to combine first light comprising an image from the display device with second light comprising an image of a real environment in front of an observer and to transmit the combined light to the observer's eye.

14. The image display apparatus of claim 13, wherein the light transmitter further comprises: a beam splitter disposed obliquely with respect to a traveling path of the first light and a traveling path of the second light.

15. The image display apparatus of claim 14, wherein the beam splitter comprises a half mirror.

16. The image display apparatus of claim 1, wherein the display device comprises a first display device and a second display device, wherein the driver comprises a first driver and a second driver respectively configured to drive the first display device and the second display device such that positions of the first display device and the second display device vary, and wherein the light transmitter comprises a first light transmitter and a second light transmitter configured to transmit images formed by the first display device and the second display device to a left eye and a right eye of the observer, respectively.

17. The image display apparatus of claim 16, wherein the image information comprises information about a pair of a left eye image and a right eye image to be perceived as a three-dimensional (3D) image, and wherein the processor is further configured to control the first display device and the second display device such that the left eye image is formed by the first display device and the right eye image is formed by the second display device.

18. The image display apparatus of claim 17, wherein the image information further comprises: depth information related to positions of a virtual image plane on which the left eye image and the right eye image are to be imaged, and wherein the processor is further configured to control the first driver and the second driver according to the depth information.

19. The image display apparatus of claim 16, wherein the image display apparatus is a wearable apparatus.

20. An image display apparatus comprising: a display device configured to modulate light to form an image; a driver configured to drive the display device such that a position of the display device varies; a light transmitter configured to transmit the image formed by the display device to an observer's eye and comprising a focusing member; a processor configured to generate a light modulation signal and a driving signal according to image information and to control the display device and the driver according to the light modulation signal and the driving signal, respectively; and an eye tracking sensor configured to sense a depth position that the observer's eye views, wherein the processor is further configured to: generate the driving signal based on a depth value set by using a saliency map with respect to each image of a plurality of frames, and based on the

depth value set by using the saliency map and a measurement value sensed by the eye tracking sensor belonging to different ranges among a previously set near range and a previously set far range, correct the driving signal.

21. The image display apparatus of claim 20, wherein the processor is further configured to generate the driving signal based on the measurement value sensed by the eye tracking sensor.

22. The image display apparatus of claim 20, wherein the processor is configured to determine whether the measurement value is within a near range or a far range, and generate the driving signal so that the display device is driven to a position corresponding to one of two representative values representing the near range and the far range.

23. The image display apparatus of claim 20, wherein the processor is configured to correct the driving signal based on the measurement value sensed by the eye tracking sensor.
