

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12417243
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Lim; Jinho et al.

Method and electronic device for generating content based on capacity of external device

Abstract

An electronic device is provided. The electronic device includes a communication module, a camera module, a memory configured to store capability-related information about an external electronic device and information related to content, and a processor configured to be operatively connected to the communication module, the camera module, and the memory. The processor may generate at least one first content corresponding to a user using the camera module, may convert the at least one first content into at least one second content, based on the capability-related information about the external electronic device and the information related to the content, and may transmit the converted at least one second content to the external electronic device through the communication module.

Inventors: Lim; Jinho (Suwon-si, KR), Moon; Jongbo (Suwon-si, KR), Lee; Joohong (Suwon-si, KR), Chae; Sangwon (Suwon-si, KR), Park; Chanmin (Suwon-si, KR)

Applicant: Samsung Electronics Co., Ltd. (Suwon-si, KR)

Family ID: 1000008821305

Assignee: Samsung Electronics Co., Ltd. (Suwon-si, KR)

Appl. No.: 17/864820

Filed: July 14, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230026123 A1	Jan. 26, 2023

Foreign Application Priority Data

KR	10-2021-0092452	Jul. 14, 2021
----	-----------------	---------------

Related U.S. Application Data

continuation parent-doc WO PCT/KR2022/007480 20220526 PENDING child-doc US 17864820

Publication Classification

Int. Cl.: **G06T13/40** (20110101); **G06F16/11** (20190101); **G06F16/583** (20190101); **G06T9/00** (20060101); **G06T11/60** (20060101)

U.S. Cl.:

CPC **G06F16/5862** (20190101); **G06F16/116** (20190101); **G06T9/00** (20130101); **G06T11/60** (20130101);

Field of Classification Search

CPC: G06T (5/50)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7590310	12/2008	Retterath	382/190	G06F 16/5838
10891367	12/2020	Fram	N/A	N/A
11043190	12/2020	Broderick	N/A	G06F 3/1423
2013/0038601	12/2012	Han et al.	N/A	N/A
2014/0168216	12/2013	Kim et al.	N/A	N/A
2018/0270448	12/2017	Onuma	N/A	H04N 7/18
2019/0180489	12/2018	Antonyan	N/A	G06T 11/001
2019/0255439	12/2018	Nakagawa et al.	N/A	N/A
2020/0391114	12/2019	Sefcik et al.	N/A	N/A
2021/0005003	12/2020	Chong et al.	N/A	N/A
2021/0027513	12/2020	Choi et al.	N/A	N/A
2021/0089706	12/2020	Kellum et al.	N/A	N/A
2021/0304452	12/2020	Lee	N/A	G06T 7/50

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
104284131	12/2014	CN	N/A
112750176	12/2020	CN	N/A
2688295	12/2013	EP	G06F 3/041
2018-057981	12/2017	JP	N/A
10-2014-0022670	12/2013	KR	N/A

10-1671900	12/2015	KR	N/A
10-1699930	12/2016	KR	N/A
10-1711684	12/2016	KR	N/A
10-2018-0012166	12/2017	KR	N/A
10-2020-0053232	12/2019	KR	N/A
10-2241153	12/2020	KR	N/A
WO-2021252343	12/2020	WO	N/A
WO-2022175717	12/2021	WO	N/A

OTHER PUBLICATIONS

International Search Report dated Aug. 23, 2022, issued in International Patent Application No. PCT/KR2022/007480. cited by applicant

Primary Examiner: Xiao; Di

Attorney, Agent or Firm: Jefferson IP Law, LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION(S) (1) This application is a continuation application, claiming priority under § 365(c), of an International application No. PCT/KR2022/007480, filed on May 26, 2022, which is based on and claims the benefit of a Korean patent application number 10-2021-0092452, filed on Jul. 14, 2021, in the Korean Intellectual Property Office, the disclosure of which is incorporated by reference herein in its entirety.

TECHNICAL FIELD

(1) The disclosure relates to a method and an electronic device for generating content based on a capability of an external device.

BACKGROUND ART

(2) An electronic device may generate an avatar to replace a user using a user image or may receive various characters (e.g., a character resembling a celebrity) to be used as avatars from the outside through a network. The electronic device may use an emoticon, a sticker, and/or an avatar, instead of text, as an auxiliary method of communication in a cyberspace. The electronic device may easily convey a user's emotion, feeling, or thought using an avatar. The electronic device may provide various services using an avatar, for example, avatar filming, a social networking service/site (SNS), or a messenger service, to the user.

(3) According to an embodiment, the electronic device may generate an avatar (e.g., a three-dimensional (3D) model avatar and/or an augmented reality (AR) emoji) while achieving an optimized quality, based on specifications and capabilities of the electronic device, and may provide the avatar of an optimized quality to the user. Technological development improves the capability of a graphics processing unit (GPU) forming the electronic device, and the electronic device may generate a high-resolution avatar. For example, the mesh of an avatar may include about 20,000 or more vertices, and the texture of an avatar may have a resolution of 1K*1K (i.e., 1024*1024) or more.

(4) The above information is presented as background information only to assist with an understanding of the disclosure. No determination has been made, and no assertion is made, as to whether any of the above might be applicable as prior art with regard to the disclosure.

DISCLOSURE

Technical Problem

(5) Since an electronic device generates an avatar corresponding to a specification and a capability of the electronic device, a large data size, a high-level rendering processing capability, and a high-level memory capacity are required. An external electronic device (e.g., a wearable device, a watch, and/or AR glasses) linked with the electronic device may have a specification and a capability relatively lower than those of the electronic device. Accordingly, when the electronic device transmits the avatar to the external electronic device and displays the avatar through the external electronic device, it may take a long time to transmit an avatar file, to load data, and to process rendering.

(6) Aspects of the disclosure are to address at least the above-mentioned problems and/or disadvantages and to provide at least the advantages described below. Accordingly, an aspect of the disclosure is to provide a method and an electronic device for identifying an external electronic device (e.g., a wearable device, a watch, and/or AR glasses), generating an avatar optimized for the identified external electronic device, and transmitting the optimized avatar to the external electronic device when generating the avatar.

(7) Additional aspects will be set forth in part in the description which follows and, in part, will be apparent from the description, or may be learned by practice of the presented embodiments.

Technical Solution

(8) In accordance with an aspect of the disclosure, an electronic device is provided. The electronic device includes a communication module, a camera module, a memory configured to store capability-related information about an external electronic device and information related to content, and a processor configured to be operatively connected to the communication module, the camera module, and the memory. The processor may generate at least one first content corresponding to a user using the camera module, may convert the at least one first content into at least one second content, based on the capability-related information about the external electronic device and the information related to the content, and may transmit the at least one second content to the external electronic device through the communication module.

(9) In accordance with another aspect of the disclosure, a method is provided. The method includes generating at least one first content corresponding to a user using a camera module, converting the at least one first content into at least one second content, based on capability-related information about an external electronic device and information related to content, and transmitting the at least one second content to the external electronic device.

Advantageous Effects

(10) According to various embodiments of the disclosure, when generating an avatar, an electronic device may identify a specification and a capability of an external electronic device (e.g., a wearable device, a watch, and/or AR glasses) and may generate an avatar optimized for the external electronic device, based on the specification and the capability. According to an embodiment, in displaying an avatar through an external device, the electronic device may generate an avatar optimized for the external device while maintaining a high quality according to actual feeling of a user and may transmit the avatar to the external device.

(11) According to various embodiments, an electronic device may generate an avatar having an optimized size, capability, and quality, based on at least one external device and may share the generated avatar with the external device. In addition, various effects directly or indirectly identified through this document may be provided.

(12) Other aspects, advantages, and salient features of the disclosure will become apparent to those skilled in the art from the following detailed description, which, taken in conjunction with the annexed drawings, discloses various embodiments of the disclosure.

Description

DESCRIPTION OF DRAWINGS

(1) The above and other aspects, features, and advantages of certain embodiments of the disclosure will be more apparent from the following description taken in conjunction with the accompanying drawings, in which:

(2) FIG. 1 is a block diagram of an electronic device in a network environment according to an embodiment of the disclosure;

(3) FIG. 2 illustrates an operation of generating an avatar and transmitting the avatar to an external device according to an embodiment of the disclosure;

(4) FIG. 3 is a block diagram of an electronic device according to an embodiment of the disclosure;

(5) FIG. 4 is a flowchart illustrating a method for generating content, based on a capability of an external device according to an embodiment of the disclosure;

(6) FIG. 5 illustrates an operation of an electronic device generating content, based on a capability of an external device, and transmitting the content to the external device according to an embodiment of the disclosure;

(7) FIG. 6 illustrates an operation of adjusting the resolution of an avatar, based on the texture type of the avatar according to an embodiment of the disclosure;

(8) FIG. 7A illustrates an operation of generating an avatar, based on a capability of an external electronic device according to an embodiment of the disclosure;

(9) FIG. 7B illustrates an operation of generating an avatar, based on a head part of the avatar according to an embodiment of the disclosure;

(10) FIG. 7C illustrates an operation of generating an avatar, based on a body part of the avatar according to an embodiment of the disclosure;

(11) FIG. 7D illustrates an operation of generating an avatar in which a head part is greater than a different part according to an embodiment of the disclosure;

(12) FIG. 7E illustrates an operation of generating an avatar in which a body part is greater than a different part according to an embodiment of the disclosure;

(13) FIG. 7F illustrates an operation of generating an avatar, based on a portion of a head part and a body part of the avatar according to an embodiment of the disclosure; and

(14) FIG. 8 is a flowchart illustrating a method for generating an avatar in response to a request from an external electronic device according to an embodiment of the disclosure.

(15) Throughout the drawings, it should be noted that like reference numbers are used to depict the same or similar elements, features, and structures.

MODE FOR INVENTION

(16) The following description with reference to the accompanying drawings is provided to assist in a comprehensive understanding of various embodiments of the disclosure as defined by the claims and their equivalents. It includes various specific details to assist in that understanding but these are to be regarded as merely exemplary. Accordingly, those of ordinary skill in the art will recognize that various changes and modifications of the various embodiments described herein can be made without departing from the scope and spirit of the disclosure. In addition, descriptions of well-known functions and constructions may be omitted for clarity and conciseness.

(17) The terms and words used in the following description and claims are not limited to the bibliographical meanings, but, are merely used by the inventor to enable a clear and consistent understanding of the disclosure. Accordingly, it should be apparent to those skilled in the art that the following description of various embodiments of the disclosure is provided for illustration purpose only and not for the purpose of limiting the disclosure as defined by the appended claims and their equivalents.

(18) It is to be understood that the singular forms “a,” “an,” and “the” include plural referents unless the context clearly dictates otherwise. Thus, for example, reference to “a component surface” includes reference to one or more of such surfaces.

(19) FIG. 1 illustrates an electronic device in a network environment according to an embodiment of the disclosure.

(20) Referring to FIG. 1, an electronic device **101** in a network environment **100** may communicate with an electronic device **102** via a first network **198** (e.g., a short-range wireless communication network), or at least one of electronic device **104** or a server **108** via a second network **199** (e.g., a long-range wireless communication network). The electronic device **101** may communicate with the electronic device **104** via the server **108**. The electronic device **101** includes a processor **120**, memory **130**, an input module **150**, an audio output module **155**, a display module **160**, an audio module **170**, a sensor module **176**, an interface **177**, a connecting terminal **178**, a haptic module **179**, a camera module **180**, a power management module **188**, a battery **189**, a communication module **190**, a subscriber identity module (SIM) **196**, or an antenna module **197**. In some embodiments, at least one of the components (e.g., the connecting terminal **178**) may be omitted from the electronic device **101**, or one or more other components may be added in the electronic device **101**. In some embodiments, some of the components (e.g., the sensor module **176**, the camera module **180**, or the antenna module **197**) may be implemented as a single component (e.g., the display module **160**).

(21) The processor **120** may execute, for example, software (e.g., a program **140**) to control at least one other component (e.g., a hardware or software component) of the electronic device **101** coupled with the processor **120**, and may perform various data processing or computation. As at least part of the data processing or computation, the processor **120** may store a command or data received from another component (e.g., the sensor module **176** or the communication module **190**) in volatile memory **132**, process the command or the data stored in the volatile memory **132**, and store resulting data in non-volatile memory **134**. The processor **120** may include a main processor **121** (e.g., a central processing unit (CPU) or an application processor (AP)), or an auxiliary processor **123** (e.g., a graphics processing unit (GPU), a neural processing unit (NPU), an image signal processor (ISP), a sensor hub processor, or a communication processor (CP)) that is operable independently from, or in conjunction with, the main processor **121**. For example, when the electronic device **101** includes the main processor **121** and the auxiliary processor **123**, the auxiliary processor **123** may be adapted to consume less power than the main processor **121**, or to be specific to a specified function. The auxiliary processor **123** may be implemented as separate from, or as part of the main processor **121**.

(22) The auxiliary processor **123** may control at least some of functions or states related to at least one component (e.g., the display module **160**, the sensor module **176**, or the communication module **190**) among the components of the electronic device **101**, instead of the main processor **121** while the main processor **121** is in an inactive (e.g., sleep) state, or together with the main processor **121** while the main processor **121** is in an active state (e.g., executing an application). The auxiliary processor **123** (e.g., an ISP or a CP) may be implemented as part of another component (e.g., the camera module **180** or the communication module **190**) functionally related to the auxiliary processor **123**. According to an embodiment, the auxiliary processor **123** (e.g., the neural processing unit) may include a hardware structure specified for artificial intelligence model processing. An artificial intelligence model may be generated by machine learning. Such learning may be performed, e.g., by the electronic device **101** where the artificial intelligence is performed or via a separate server (e.g., the server **108**). Learning algorithms may include, but are not limited to, e.g., supervised learning, unsupervised learning, semi-supervised learning, or reinforcement learning. The artificial intelligence model may include a plurality of artificial neural network layers. The artificial neural network may be a deep neural network (DNN), a convolutional neural network (CNN), a recurrent neural network (RNN), a restricted boltzmann machine (RBM), a deep belief network (DBN), a bidirectional recurrent deep neural network (BRDNN), deep Q-network or a combination of two or more thereof but is not limited thereto. The artificial intelligence model may, additionally or alternatively, include a software structure other than the hardware structure.

(23) The memory **130** may store various data used by at least one component (e.g., the processor **120** or the sensor module **176**) of the electronic device **101**. The various data may include, for example, software (e.g., the program **140**) and input data or output data for a command related thereto. The memory **130** may include the volatile memory **132** or the non-volatile memory **134**. The non-volatile memory **134** may include an internal memory **136** or external memory **138**.

(24) The program **140** may be stored in the memory **130** as software, and may include, for example, an operating system (OS) **142**, middleware **144**, or an application **146**.

(25) The input module **150** may receive a command or data to be used by another component (e.g., the processor **120**) of the electronic device **101**, from the outside (e.g., a user) of the electronic device **101**. The input module **150** may include, for example, a microphone, a mouse, a keyboard, a key (e.g., a button), or a digital pen (e.g., a stylus pen).

(26) The audio output module **155** may output sound signals to the outside of the electronic device **101**. The audio output module **155** may include, for example, a speaker or a receiver. The speaker may be used for general purposes, such as playing multimedia or playing record. The receiver may be used for receiving incoming calls. The receiver may be implemented as separate from, or as part of the speaker.

(27) The display module **160** may visually provide information to the outside (e.g., a user) of the electronic device **101**. The display module **160** may include, for example, a display, a hologram device, or a projector and control circuitry to control a corresponding one of the display, hologram device, and projector. The display module **160** may include a touch sensor adapted to detect a touch, or a pressure sensor adapted to measure the intensity of force incurred by the touch.

(28) The audio module **170** may convert a sound into an electrical signal and vice versa. The audio module **170** may obtain the sound via the input module **150**, or output the sound via the audio output module **155** or a headphone of an external electronic device (e.g., an electronic device **102**) directly (e.g., wiredly) or wirelessly coupled with the electronic device **101**.

(29) The sensor module **176** may detect an operational state (e.g., power or temperature) of the electronic device **101** or an environmental state (e.g., a state of a user) external to the electronic device **101**, and then generate an electrical signal or data value corresponding to the detected state. The sensor module **176** may include, for example, a gesture sensor, a gyro sensor, an atmospheric pressure sensor, a magnetic sensor, an acceleration sensor, a grip sensor, a proximity sensor, a color sensor, an infrared (IR) sensor, a biometric sensor, a temperature sensor, a humidity sensor, or an illuminance sensor.

(30) The interface **177** may support one or more specified protocols to be used for the electronic device **101** to be coupled with the external electronic device (e.g., the electronic device **102**) directly (e.g., wiredly) or wirelessly. The interface **177** may include, for example, a high definition multimedia interface (HDMI), a universal serial bus (USB) interface, a secure digital (SD) card interface, or an audio interface.

(31) A connection terminal **178** may include a connector via which the electronic device **101** may be physically connected with the external electronic device (e.g., the electronic device **102**). The connection terminal **178** may include, for example, an HDMI connector, a USB connector, an SD card connector, or an audio connector (e.g., a headphone connector).

(32) The haptic module **179** may convert an electrical signal into a mechanical stimulus (e.g., a vibration or a movement) or electrical stimulus which may be recognized by a user via his tactile sensation or kinesthetic sensation. The haptic module **179** may include, for example, a motor, a piezoelectric element, or an electric stimulator.

(33) The camera module **180** may capture a still image or moving images. The camera module **180** may include one or more lenses, image sensors, image signal processors, or flashes.

(34) The power management module **188** may manage power supplied to the electronic device **101**. The power management module **188** may be implemented as at least part of, for example, a power management integrated circuit (PMIC).

(35) The battery **189** may supply power to at least one component of the electronic device **101**. The battery **189** may include, for example, a primary cell which is not rechargeable, a secondary cell which is rechargeable, or a fuel cell.

(36) The communication module **190** may support establishing a direct (e.g., wired) communication channel or a wireless communication channel between the electronic device **101** and the external electronic device (e.g., the electronic device **102**, the electronic device **104**, or the server **108**) and performing communication via the established communication channel. The communication module **190** may include one or more communication processors that are operable independently from the processor **120** (e.g., the AP) and supports a direct (e.g., wired) communication or a wireless communication. The communication module **190** may include a wireless communication module **192** (e.g., a cellular communication module, a short-range wireless communication module, or a global navigation satellite system (GNSS) communication module) or a wired communication module **194** (e.g., a local area network (LAN) communication module or a power line communication (PLC) module). A corresponding one of these communication modules may communicate with the external electronic device via the first network **198** (e.g., a short-range communication network, such as Bluetooth™, wireless-fidelity (Wi-Fi) direct, or a standard of the Infrared Data Association (IrDA)) or the second network **199** (e.g., a long-range communication network, such as a legacy cellular network, a fifth generation (5G) network, a next-generation communication network, the Internet, or a computer network (e.g., LAN or wide area network (WAN))). These various types of communication modules may be implemented as a single component (e.g., a single chip), or may be implemented as multi components (e.g., multi chips) separate from each other. The wireless communication module **192** may identify and authenticate the electronic device **101** in a communication network, such as the first network **198** or the second network **199**, using subscriber information (e.g., international mobile subscriber identity (IMSI)) stored in the SIM **196**.

(37) The wireless communication module **192** may support a 5G network, after a fourth generation (4G) network, and next-generation communication technology, e.g., new radio (NR) access technology. The NR access technology may support enhanced mobile broadband (eMBB), massive machine type communications (mMTC), or ultra-reliable and low-latency communications (URLLC). The wireless communication module **192** may support a high-frequency band (e.g., the mmWave band) to achieve, e.g., a high data transmission rate. The wireless communication module **192** may support various technologies for securing performance on a high-frequency band, such as, e.g., beamforming, massive multiple-input multiple-output (massive MIMO), full dimensional MIMO (FD-MIMO), array antenna, analog beam-forming, or large scale antenna. The wireless communication module **192** may support various requirements specified in the electronic device **101**, an external electronic device (e.g., the electronic device **104**), or a network system (e.g., the second network **199**). According to an embodiment, the wireless communication module **192** may support a peak data rate (e.g., 20 Gbps or more) for implementing eMBB, loss coverage (e.g., 164 dB or less) for implementing mMTC, or U-plane latency (e.g., 0.5 ms or less for each of downlink (DL) and uplink (UL), or a round trip of 1 ms or less) for implementing URLLC.

(38) The antenna module **197** may transmit or receive a signal or power to or from the outside (e.g., the external electronic device) of the electronic device **101**. The antenna module **197** may include an antenna including a radiating element composed of a conductive material or a conductive pattern formed in or on a substrate (e.g., a printed circuit board (PCB)). According to an embodiment, the antenna module **197** may include a plurality of antennas (e.g., array antennas). In such a case, at least one antenna appropriate for a communication scheme used in the communication network, such as the first network **198** or the second network **199**, may be selected, for example, by the communication module **190** (e.g., the wireless communication module **192**) from the plurality of antennas. The signal or the power may then be transmitted or received between the communication module **190** and the external electronic device via the selected at least one antenna. Another

component (e.g., a radio frequency integrated circuit (RFIC)) other than the radiating element may be additionally formed as part of the antenna module **197**.

(39) At least some of the above-described components may be coupled mutually and communicate signals (e.g., commands or data) therebetween via an inter-peripheral communication scheme (e.g., a bus, general purpose input and output (GPIO), serial peripheral interface (SPI), or mobile industry processor interface (MIPI)).

(40) Commands or data may be transmitted or received between the electronic device **101** and the external electronic device **104** via the server **108** coupled with the second network **199**. Each of the electronic devices **102** or **104** may be a device of a same type as, or a different type, from the electronic device **101**. All or some of operations to be executed at the electronic device **101** may be executed at one or more of the external electronic devices **102**, **104**, or **108**. For example, if the electronic device **101** should perform a function or a service automatically, or in response to a request from a user or another device, the electronic device **101**, instead of, or in addition to, executing the function or the service, may request the one or more external electronic devices to perform at least part of the function or the service. The one or more external electronic devices receiving the request may perform the at least part of the function or the service requested, or an additional function or an additional service related to the request, and transfer an outcome of the performing to the electronic device **101**. The electronic device **101** may provide the outcome, with or without further processing of the outcome, as at least part of a reply to the request. To that end, a cloud computing, distributed computing, mobile edge computing (MEC), or client-server computing technology may be used, for example. The electronic device **101** may provide ultra low-latency services using, e.g., distributed computing or mobile edge computing. In another embodiment, the external electronic device **104** may include an internet-of-things (IoT) device. The server **108** may be an intelligent server using machine learning and/or a neural network. According to an embodiment, the external electronic device **104** or the server **108** may be included in the second network **199**. The electronic device **101** may be applied to intelligent services (e.g., smart home, smart city, smart car, or healthcare) based on 5G communication technology or IoT-related technology.

(41) FIG. 2 illustrates an operation of generating an avatar and transmitting the avatar to an external device (e.g., a wearable device) according to an embodiment of the disclosure.

(42) According to various embodiments, an electronic device **200** (e.g., the electronic device **101** of FIG. 1) may store at least one program (e.g., the program **140** of FIG. 1) as software in a memory (e.g., the memory **130** of FIG. 1). For example, the at least one program **140** may include at least one application (e.g., the application **146** of FIG. 1). The application **146** may be defined as application software developed to perform a designated task, and may provide various functions to a user so that the user may efficiently perform the designated task. For example, the avatar application **201** is an application for generating an avatar of a user that uses the electronic device **200**, and may generate a virtual character corresponding to the user. For example, the avatar may have an appearance similar to that of the user, and may include virtual content capable of expressing an emotion of the user. According to an embodiment, the electronic device **200** may generate an avatar with an optimized quality, based on a specifications and a capability of the electronic device **200**, using the avatar application **201**. For example, as the capability of the electronic device **200** improves, a higher-quality avatar may be configured. A high-quality avatar may be configured relatively more precisely than a low-quality avatar. A high-quality avatar may require a large data size, a high-level rendering processing capability (e.g., GPU specification), and a large memory capacity (e.g., memory size).

(43) According to an embodiment, the quality of the avatar may be determined based on the specification and capability of the electronic device **200**, and processing time may be determined according to the specification and capability of the electronic device **200**. For example, an electronic device having a low specification and a low capability may take a relatively long time to

process an avatar.

(44) Referring to FIG. 2, an electronic device **200** may execute an avatar application **201** to generate an avatar, and may transmit the generated avatar to an external electronic device **210** (e.g., a wearable device, a watch **211**, and/or AR glasses **212**) so that the external electronic device **210** may utilize the avatar.

(45) According to an embodiment, when transmitting the avatar to the external electronic device **210**, the electronic device **200** may be affected by a state of communication with the external electronic device **210** and a specification and/or a capability of the external electronic device **210**. For example, the specification and/or the capability of the external electronic device **210** may be relatively lower than the specification and/or the capability of the electronic device **200**. For example, compared to the electronic device **200**, the external electronic device **210** may be designed to include a relatively small internal space for disposing various components and to have a low resolution of a display. In the external electronic device **210**, compared to the electronic device **200**, components having a relatively low specification may be disposed to support the low resolution of the display.

(46) According to an embodiment, the avatar generated by the electronic device **200** may be configured with a high capacity, and it may take a considerable time to transmit the avatar to the external electronic device **210**. For example, the external electronic device **210** may take a considerable time for an operation of loading the avatar received from the electronic device **200** and displaying the avatar on the display. The external electronic device **210** configured with a relatively low specification than the electronic device **200** may take a considerable time to load the avatar.

(47) According to an embodiment, the electronic device **200** may determine the quality of the avatar, based on preset configuration information, configuration information in the avatar application (e.g., a platform), and the specification and/or the capability of the electronic device **200**.

(48) FIG. 3 is a block diagram of an electronic device according to an embodiment of the disclosure.

(49) Referring to FIG. 3 depicting block diagram **300**, an electronic device **200** (e.g., an electronic device **101** of FIG. 1) may include a processor (e.g., a processor **120** of FIG. 1), a memory (e.g., a memory **130** of FIG. 1), a camera module (e.g., a camera module **180** of FIG. 1), a communication module (e.g., a communication module **190** of FIG. 1), and/or an avatar application **310**. The electronic device **200** may be operatively connected to an external electronic device **210** and a server (e.g., the server **108** of FIG. 1) through the communication module **190**, and may transmit and receive data thereto and therefrom. The avatar application **310** may include various components (e.g., an avatar generator **311**, an avatar request receiver **312**, an analysis/determination unit **313**, an avatar optimizer **314**, and/or an avatar storage unit **315**) for generating an avatar.

(50) According to an embodiment, the processor **120** of the electronic device **200** may generate an avatar associated with a user, based on the avatar application **310**. For example, the avatar may be virtual content to replace the user, and may be configured based on an appearance of the user. The avatar may be configured as a human-shaped icon reflecting a characteristic of the user, based on the user. The avatar may express an emotion of the user on behalf of the user. The electronic device **200** may capture an image associated with the user using the camera module (e.g., the camera module **180** of FIG. 1) in response to execution of the avatar application **310**, and may configure at least one avatar, based on the captured image.

(51) According to an embodiment, the processor **120** may execute the avatar application **310** in response to an instruction to request an avatar. The processor **120** may transmit the instruction to the avatar request receiver **312**. The processor **120** may analyze and determine at least one information (e.g., specification and capability-related information about the external electronic

device **210**) for generating an avatar in the analysis/determination unit **313** of the avatar application **310**. For example, when the electronic device **200** autonomously requests an avatar, the processor **120** may analyze a specification and a capability of the electronic device **200** to determine information to be reflected in the avatar. In another example, to use an avatar in the external electronic device **210**, the electronic device **200** may request to generate the avatar, may analyze a specification and a capability of the external electronic device **210**, and may determine information to be reflected in the avatar. The processor **120** may determine the optimized quality of the avatar, based on the information to be reflected in the avatar, in the avatar optimizer **314**. For example, when the avatar is loaded and displayed in the external electronic device **210**, the processor **120** may perform a process for optimizing the avatar through the avatar optimizer **314** to optimize the avatar to be displayed on the external electronic device **210**. According to an embodiment, the processor **120** may generate a first avatar (e.g., an avatar optimized for the electronic device **200**), based on the specification and the capability of the electronic device **200**, through the avatar generator **311**, and may store the first avatar in the avatar storage unit **315**. According to an embodiment, the processor **120** may generate a second avatar (e.g., an avatar optimized for the external electronic device **210**), based on the specification and the capability of the external electronic device **210**, and may store the second avatar in the avatar storage unit **315**. The avatar storage unit **315** may be at least partially included in the memory **130** of the electronic device **200**. Referring to FIG. 3, the memory **130** and the avatar storage unit **315** are illustrated separately, but the disclosure is not limited thereto. The electronic device **200** may store the first avatar and the second avatar in a storage space of the server **108**.

(52) According to an embodiment, the processor **120** of the electronic device **200** may utilize the first avatar when displaying the avatar in the electronic device **200**, and may transmit the second avatar to the external electronic device **210** when displaying the avatar in the external electronic device **210**.

(53) According to an embodiment, the electronic device **200** may be operatively connected to the external electronic device **210** through the communication module **190**, and may obtain the specification and capability-related information about the external electronic device **210** from the external electronic device **210**. According to an embodiment, when connected with the external electronic device **210**, the electronic device **200** may obtain plug-in information about the external electronic device **210**, and may store the obtained plug-in information in the memory **130**. For example, the processor **120** of the electronic device **200** may predict or analyze the specification and capability-related information about the external electronic device **210**, based on the plug-in information stored in the memory **130**. When generating an avatar to be transmitted to the external electronic device **210**, the processor **120** may identify whether the plug-in information about the external electronic device **210** is stored in the memory **130**, and may generate an optimized avatar corresponding to the external electronic device **210**, based on the plug-in information.

(54) According to an embodiment, when generating the optimized avatar for the external electronic device **210**, the processor **120** may generate the avatar, based on the specification and the capability of the external electronic device **210**. For example, the processor **120** may determine a texture size for the optimized avatar for the external electronic device **210** and/or a texture format for the optimized avatar for the external electronic device **210**. For example, the texture size for the avatar may be differently determined depending on each texture type (e.g., a physically based rendering (PBR) material type) or may be differently determined depending on each part (e.g., a head or a body) of the avatar.

(55) According to various embodiments, an electronic device **101** or **200** may include a communication module **190**, a camera module **180**, a memory **130** configured to store capability-related information about an external electronic device **210** and information related to content, and a processor **120** configured to be operatively connected to the communication module **190**, the camera module **180**, and the memory **130**. The processor **120** may generate at least one first content

corresponding to a user using the camera module **180**, may convert the at least one first content into at least one second content, based on the capability-related information about the external electronic device **210** and the information related to the content, and may transmit the at least one second content to the external electronic device **210** through the communication module **190**.

(56) According to an embodiment, the first content and the second content may include at least one of an avatar replacing the user, virtual content, a virtual character, and a virtual icon, which are generated based on an image captured using the camera module **180**.

(57) According to an embodiment, the capability-related information about the external electronic device **210** may include specification information and capability information about at least one component forming the external electronic device **210**.

(58) According to an embodiment, the information related to the content may include texture information about the content, texture size information, texture format information, and/or information about a part forming the content.

(59) According to an embodiment, the texture information about the content may include at least one of albedo, normal, metallic, and/or roughness, which represent a texture of the content, and optimized texture size information may be determined according to the texture information.

(60) According to an embodiment, the texture format information about the content may include a compression method for minimizing quality deterioration and/or a lossy compression method in which quality deterioration occurs, in an operation of compressing the content to be converted into a file format.

(61) According to an embodiment, the information about the part forming the content may include at least one of a head part, a body part, and/or a bottom part.

(62) According to an embodiment, the processor **120** may individually convert the first content in response to each body part forming the first content, based on the capability-related information about the external electronic device **210** and the information related to the content, and may generate the second content by integrating each of the converted body part.

(63) According to an embodiment, the processor **120** may generate third content corresponding to the external electronic device **210**, based on the capability-related information about the external electronic device **210** and the information related to the content included in a request signal, in response to the request signal from the external electronic device **210**, and may transmit the third content to the external electronic device **210** through the communication module **190**.

(64) According to an embodiment, the processor **120** may identify whether the third content is stored in the memory **130** in response to the request signal from the external electronic device **210**, and may transmit the third content stored in the memory **130** to the external electronic device **210** when the third content is stored in the memory **130**.

(65) According to an embodiment, the external electronic device **210** may include at least one of a wearable watch, AR glasses, a smartphone, a virtual reality (VR) device, and a personal computer (PC).

(66) FIG. 4 is a flowchart illustrating a method for generating content, based on a capability of an external device according to an embodiment of the disclosure.

(67) According to various embodiments, an electronic device (e.g., the electronic device **101** of FIG. 1 or the electronic device **200** of FIG. 2) may generate first content (e.g., an avatar) associated with a user, based on an avatar application (e.g., the avatar application **310** of FIG. 3). For example, a processor (e.g., the processor **120** of FIG. 1) of the electronic device **101** may capture an image corresponding to the user using a camera module (e.g., the camera module **180** of FIG. 1), and may generate the first content, based on the image. The processor **120** may determine the quality of the first content, based on a specification and a capability of the electronic device **101**. For example, the avatar (e.g., the first content) may be virtual content (e.g., a virtual character) to replace the user, and may be configured based on an appearance of the user. The avatar may express an emotion of the user on behalf of the user. The electronic device **101** may use the avatar for

communication with an external electronic device (e.g., the electronic devices **102** or **104** of FIG. **1** or the external electronic device **210** of FIG. **2**), and may convey exact intention to a counterpart (or user) using the external electronic device **210**. According to an embodiment, the electronic device **101** may identify a specification and a capability of the external electronic device **210** to which the avatar is transmitted, and may generate second content, based on the specification and the capability of the external electronic device **210**. For example, the processor **120** may at least partially convert the first content, thereby generating the second content. According to an embodiment, the electronic device **101** may convert the first content (e.g., the avatar) into the second content, based on the specification and the capability of the external electronic device **210**, so that the first content may be quickly received and displayed on the external electronic device **210**. For example, the second content may include an optimized avatar corresponding to the specification and the capability of the external electronic device **210**.

(68) In operation **401**, the processor **120** may generate at least one first content associated with the user. For example, the first content may include virtual content (e.g., a virtual character or an avatar) to replace the user. The processor **120** may activate the camera module **180** to capture an image including the user, and may generate the first content corresponding to the user, based on the image. According to an embodiment, the processor **120** may generate the first content optimized for the electronic device **101**, based on the specification and the capability of the electronic device **101**. For example, the quality of the first content may be determined based on the specification and the capability of the electronic device **101**. According to an embodiment, the processor **120** may determine a texture size for the first content (e.g., the avatar) and/or a texture format for the first content (e.g., the avatar), based on the specification and the capability of the electronic device **101**. According to an embodiment, the processor **120** may provide the user with the first content optimized for the electronic device **101**.

(69) In operation **403**, the processor **120** may identify the external electronic device **210** for using the first content. For example, when transmitting a message to the external electronic device **210**, the processor **120** may include the first content in the message. The electronic device **101** may more accurately convey the user's emotion and intention using the first content. The processor **120** may identify the specification and the capability of the external electronic device **210** that is currently being operatively connected and/or the external electronic device **210** that has been previously connected. According to an embodiment, the processor **120** may configure optimized content (e.g., an avatar) corresponding to the external electronic device **210** by identifying the specification and the capability of the external electronic device **210**. According to an embodiment, the processor **120** may determine a texture size for the second content (e.g., the avatar) and/or a texture format for the second content (e.g., the avatar), based on the specification and the capability of the external electronic device **210**.

(70) In operation **405**, the processor **120** may convert the first content into the second content, based on capability information (e.g., capability-related information or specification-related information) about the external electronic device **210** and attribute information about the first content. For example, the processor **120** may convert the first content generated to be optimized according to the capability of the electronic device **101** into the second content optimized according to the capability of the external electronic device **210**. For example, when the electronic device **101** has a more remarkable capability than the external electronic device **210** (e.g., a wearable device), the processor **120** may perform an operation of downscaling the first content may convert the first content into the second content.

(71) In operation **407**, the processor **120** may transmit the second content to the external electronic device **210**. According to an embodiment, since the second content is optimized based on the capability information about the external electronic device **210**, the external electronic device **210** may provide the second content to the user optimized for the external electronic device **210**.

(72) According to an embodiment, the electronic device **101** may configure the avatar

corresponding to the capability of the external electronic device **210** so that the avatar configured with an optimal quality may be provided even in a situation where the avatar is provided to the user through the external electronic device **210**. According to an embodiment, when the avatar is displayed on the electronic device **101**, the electronic device **101** may display the first content (e.g., a first avatar) optimized based on the electronic device **101**. When the avatar is displayed on the external electronic device **210**, the electronic device **101** may transmit the second content (e.g., a second avatar) optimized based on the external electronic device **210** to the external electronic device **210**, and may display the second content through the external electronic device **210**.

(73) FIG. 5 illustrates an operation of an electronic device generating content, based on a capability of an external device, and transmitting the content to the external device according to an embodiment of the disclosure.

(74) According to various embodiments, in a state of being operatively connected to an external electronic device (e.g., the electronic device **102** or **104** of FIG. 1 or the external electronic device **210** of FIG. 2), the electronic device (e.g., the electronic device **101** of FIG. 1 or the electronic device **200** of FIG. 2) may share data with the external electronic device **210**. The electronic device **101** may execute an avatar application (e.g., the avatar application **310** of FIG. 3) to generate first content **510** (e.g., an avatar) associated with a user. For example, the first content **510** may include a first avatar optimized based on a specification and a capability of the electronic device **101**. The electronic device **101** may convert the first content **510** into second content **520**, and may transmit the second content **520** to the external electronic device **210**. For example, the second content **520** may include a second avatar optimized based on a specification and a capability of the external electronic device **210**.

(75) According to an embodiment, the electronic device **101** may identify the specification and/or the capability of the external electronic device **210**, may generate an avatar optimized based on the external electronic device **210**, and may transmit the avatar to the external electronic device **210**. According to an embodiment, when the electronic device **101** is used, the first avatar (e.g., first content **510**) optimized corresponding to the electronic device **101** may be displayed on a display (e.g., the display module **160** of FIG. 1) of the electronic device **101**. When the external electronic device **210** is used, the second avatar (e.g., second content **520**) optimized corresponding to the external electronic device **210** may be displayed on a display **221** of the external electronic device **210**.

(76) Referring to FIG. 5, a first content **510** may be configured based on first avatar-related information **511** (e.g., capability information about the electronic device **101**, texture information about the first content **510**, and/or texture format information about the first content **510**).

(77) For example, the capability information about the electronic device **101** may include a specification of the processor **120**, a capacity of the memory **130**, and/or a resolution supportable by a display module (e.g., the display module of FIG. 1). The capability information about the electronic device **101** may include detailed specification information about at least one component forming the electronic device **101** and/or capability information about a processing ability to configure the avatar (e.g., the first content **510**).

(78) For example, the texture information about the first content **510** may include feel information and/or size information about the first avatar. The texture information may include a physically based rendering (PBR) material type (e.g., albedo, normal, metallic, or roughness). For example, when rendering the first content **510** (e.g., the first avatar), the processor **120** may perform the rendering using a Phong shading method or a physically based shading (PBS) method. When performing the rendering based on the PBS method, the processor **120** may determine a size for texture forming the first content **510** according to a texture type (e.g., albedo, normal, metallic, or roughness). According to an embodiment, the processor **120** may configure a different texture type or a different texture size according to a part (e.g., a head, a body, or a bottom) of the first content **510**. For example, the first content **510** may be configured as the entire part (e.g., the head, the

body, and the bottom) forming the avatar.

(79) For example, the texture format information about the first content **510** may include information about the format of the first content **510** in an operation in which the processor **120** compresses the first content **510** to be converted into a file format. The texture format information may be configured such that each part of the first content **510** has a different format.

(80) According to an embodiment, the electronic device **101** may configure the first content **510**, based on the first avatar-related information **511** (e.g., the capability information about the electronic device **101**, the texture information about the first content **510**, and/or the texture format information about the first content **510**).

(81) Referring to FIG. 5, a second content **520** may be configured based on second avatar-related information **521** (e.g., capability information about the external electronic device **210**, texture information about the second content **520**, and/or texture format information about the second content **520**).

(82) For example, the capability information about the external electronic device **210** may include a specification of a processor, a capacity of a memory, and/or a resolution supportable by a display module corresponding to the external electronic device **210**. The capability information about the external electronic device **210** may include detailed specification information about at least one component forming the external electronic device **210** and/or capability information about a processing ability to configure the avatar (e.g., the second content **520**). According to an embodiment, when operatively connected to the external electronic device **210**, the electronic device **200** may obtain the capability information about the external electronic device **210** and may store the capability information in the memory **130**.

(83) For example, the texture information about the second content **520** may include feel information and/or size information about the second avatar. When rendering the second content **520** (e.g., the second avatar), the processor **120** may perform the rendering using the Phong shading method or the physically based shading (PBS) method. When performing the rendering based on the PBS method, the processor **120** may determine a size for texture forming the second content **520** according to a texture type (e.g., albedo, normal, metallic, or roughness). According to an embodiment, the processor **120** may configure a different texture type or a different texture size according to a part (e.g., a head, a body, or a bottom) of the second content **520**. For example, the second content **520** may be configured as the entire part (e.g., the head, the body, and the bottom) forming the avatar. The second content **520** of FIG. 5 is configured as the head of the avatar, but is not limited thereto.

(84) For example, the texture format information about the second content **520** may include information about the format (e.g., a portable network graphic (PNG) format that minimizes quality deterioration or a JPG format as a lossy compression technique in which quality deterioration at least partially occurs) of the second content **520** in an operation in which the processor **120** compresses the second content **520** to be converted into a file format. The texture format information may be configured such that each part of the second content **520** has a different format.

(85) According to an embodiment, the electronic device **200** may configure the second content **520**, based on the second avatar-related information **521** (e.g., the capability information about the external electronic device **210**, the texture information about the second content **520**, and/or the texture format information about the second content **520**). According to an embodiment, the electronic device **200** may first generate the first content **510** and may then convert the first content **510** to the second content **520**, based on the second avatar-related information **521**.

(86) According to an embodiment, the first content **510** may be displayed with an optimized quality through the display module **160** of the electronic device **200**. For example, the first content **510** may include an avatar optimized according to the resolution supported by the display module **160**. The second content **520** may be displayed with an optimized quality through the display **221** of the external electronic device **210** (e.g., a watch **211**). For example, the second content **520** may

include an avatar optimized according to the resolution supported by the display **221** of the watch **211**.

(87) FIG. **6** illustrates an operation of adjusting the resolution of an avatar, based on the texture type of the avatar according to an embodiment of the disclosure.

(88) According to an embodiment, in generating an avatar, an electronic device (e.g., the electronic device **101** of FIG. **1** or the electronic device **200** of FIG. **2**) may determine a texture for the avatar. For example, the texture for the avatar may include a physically based rendering (PBR) material type (e.g., albedo, normal, metallic, or roughness).

(89) For example, since the electronic device **101** and an external electronic device (e.g., the external electronic device **210** of FIG. **2**) have different specifications and capabilities, a different size of an optimized avatar may be configured depending on a texture type. For example, the better a capability and a specification of the electronic device **101** are, the larger the size of an avatar optimized according to a texture type may be configured.

(90) Table 1 is a table showing avatar sizes configured for the electronic device **101** and the external electronic device **210** according to texture types.

(91) TABLE-US-00001
TABLE 1 For external electronic device Texture type For electronic device (e.g., watch)
Albedo 1024*1024 512*512 Normal 1024*1024 256*256 Roughness 1024*1024 256*256 Metallic 1024*1024 256*256

(92) Textures for the avatar may be divided into four types: albedo, normal, metallic, and roughness. Albedo may be a texture corresponding to a raw color level, and normal may be a texture corresponding to a normal map level of a 3d mesh surface. Metallic and roughness may be textures corresponding to a metal level and a roughness level of a surface, respectively.

(93) Referring to Table 1, the electronic device **101** may configure a first avatar in a size of 1024*1024 in response to all four textures. The first avatar may be an avatar configured with an optimized quality in the electronic device **101**. The electronic device **101** may convert (e.g., upscale or downscale) the first avatar into a second avatar in order to transmit the avatar to the external electronic device **210** (e.g., a wearable watch). For example, when the external electronic device **210** has a specification and a capability lower than those of the electronic device **101**, the electronic device **101** may downscale the first avatar to be converted into the second avatar.

(94) Referring to FIG. **6**, when a first avatar is converted into a second avatar, based on an albedo texture, an electronic device **101** may downscale the first avatar **611** configured in a 1024*1024 size into the second avatar **612** with a 512*512 size. In another example, when the first avatar is converted into the second avatar, based on a normal texture, the electronic device **101** may downscale the first avatar **621** configured in a 1024*1024 size into the second avatar **622** with a 256*256 size.

(95) According to an embodiment, the electronic device **101** may identify a texture type (e.g., albedo, normal, metallic, or roughness) for the avatar, and may convert (e.g., upscale or downscale) the avatar to have a different size for each texture type.

(96) According to an embodiment, the electronic device **101** may apply a different texture type to each part (e.g., a head, a body, or a bottom) forming the avatar. Parts forming the avatar are not limited to the head, the body, and the bottom, and may be classified variously according to a configuration. According to an embodiment, when configuring the avatar, the electronic device **101** may configure the avatar such that each part forming the avatar has a different quality.

(97) Table 2 is a table showing different ratios for individual parts.

(98) TABLE-US-00002
TABLE 2 External Avatar part Texture type Electronic device electronic device
Head/hair/ Albedo 1024*1024 512*512 (Glasses or Normal 1024*1024 256*256 earring)
Metallic top/headwear Roughness Body Albedo 1024*1024 256*256 Normal 1024*1024 128*128
Metallic Roughness Bottom/shoes Albedo 1024*1024 256*256 Normal 1024*1024 128*128
Metallic Roughness

(99) Referring to Table 2, the electronic device **101** may optimize the entire part (e.g., the head, the

body, and the bottom) of the first avatar, based on a 1024*1024 ratio. The first avatar may be an avatar optimized for the electronic device **101** regardless of a part and a texture type. The electronic device **101** may convert the first avatar into the second avatar so that an avatar optimized for the external electronic device **210** is displayed through the external electronic device **210**.

(100) Referring to Table 2, in a texture type of albedo, the electronic device **101** may downscale the head of the first avatar with a 1024*1024 ratio into a head of the second avatar with a 512*512 ratio. In a texture type of normal, the electronic device **101** may downscale the body of the first avatar with a 1024*1024 ratio into a body of the second avatar with a 128*128 ratio. For example, the external electronic device **210** corresponds to a wearable watch and has a relatively small size (e.g., resolution) of a display, thus being utilized focusing on the head of the second avatar. When converting the second avatar for the external electronic device **210**, the electronic device **101** may convert the second avatar, focusing on the head. According to an embodiment, the electronic device **101** may apply different types of textures or may apply different resolutions for the respective parts (e.g., the head, the body, and the bottom) forming the avatar.

(101) According to an embodiment, after configuring the avatar, the electronic device **101** may apply a different format by each part of the avatar or at least partially in an operation of compressing the avatar to be converted into a file format. For example, when generating the first avatar optimized for the electronic device **101**, the electronic device **101** may use a texture in a PNG format. When generating and/or converting the second avatar optimized for the external electronic device **210**, the electronic device **101** may use a texture in a lossy compression format, such as JPG. The external electronic device **210** may include a wearable watch, and may display the avatar in a relatively small size. According to an embodiment, even though the texture in the lossy compression format is used due to the small size of the avatar, it may be difficult for a user to visually recognize quality deterioration.

(102) According to an embodiment, the electronic device **101** may identify a texture type (e.g., albedo, normal, metallic, or roughness) and may apply a different format for each texture type. Table 3 is a table showing different formats applied by each part of the avatar or according to the texture type.

(103) TABLE-US-00003

TABLE 3	Electronic device	External device	Texture device	electronic device	Part
requiring alpha	All textures:	Albedo/normal:	PNG blending (glasses, eyelash, PNG format format socks, and see-through	Metallic/roughness: JPG clothes)	format
Part not requiring alpha	All textures:	Textures other than blending	PNG format	Normal: JPG format	Normal: PNG format
Normal texture	All textures:	All textures:	PNG PNG format format	Total capacity	8.14 MB 6.85 MB

(104) Referring to Table 3, the electronic device **101** may optimize the entire part (e.g., the head, the body, and the bottom) of the first avatar, based on the PNG format. The first avatar may be an avatar optimized for the electronic device **101** regardless of a part and a texture type. The electronic device **101** may convert the first avatar into the second avatar so that the avatar optimized for the external electronic device **210** is displayed through the external electronic device **210**.

(105) Referring to Table 3, in an operation of converting the first avatar into the second avatar, when a part requiring alpha blending (e.g., a part requiring precise rendering) is an albedo/normal texture, the electronic device **101** may perform compression in the PNG format, and when the part requiring alpha blending is a metallic/roughness texture, the electronic device **101** may perform lossy compression in the JPG format. The electronic device **101** may perform compression in the PNG format only when a part not requiring alpha blending is a normal texture. In albedo/metallic/roughness textures other than the normal texture, the electronic device **101** may perform lossy compression in the JPG format. Referring to Table 3, since a rendering error is visually identified when lossy compression is performed on the normal texture, the electronic device **101** may perform compression in the PNG format on the normal texture.

(106) Referring to Table 3, the electronic device **101** may configured the first avatar with a capacity

of about 8.14 MB, and may configure the second avatar with a capacity of about 6.85 MB. According to an embodiment, the electronic device **101** may apply a different method for configuring an optimized avatar, based on the specification and the capability of the electronic device **101**.

(107) FIG. 7A illustrates an operation of generating an avatar, based on a capability of an external electronic device according to an embodiment of the disclosure.

(108) Referring to FIG. 7A, an electronic device (e.g., an electronic device **101** of FIG. 1 or an electronic device **200** of FIG. 2) may execute an avatar application (e.g., an avatar application **310** of FIG. 3), and may generate first content **710** (e.g., a first avatar) associated with a user, based on an avatar application **310**. For example, a processor (e.g., the processor **120** of FIG. 1) of the electronic device **101** may capture an image corresponding to the user using a camera module (e.g., the camera module **180** of FIG. 1), and may generate the first content **710**, based on the image. The processor **120** may determine a quality for the first content **710**, based on a specification and a capability of the electronic device **101**.

(109) Referring to FIG. 7A, a processor **120** may classify a first content **710** by at least one part (e.g., a head **711**, a body **712**, and a bottom **713**). According to an embodiment, the processor **120** may configure a different texture type (e.g., albedo, normal, metallic, or roughness) for each part. According to another embodiment, the processor **120** may configure a different resolution for each part. According to another embodiment, the processor **120** may apply a different texture format (e.g., a PNG format or a JPG format) to each part.

(110) FIG. 7B illustrates an operation of generating an avatar, based on a head part of an avatar according to an embodiment of the disclosure. FIG. 7C illustrates an operation of generating an avatar, based on a body part of the avatar according to an embodiment of the disclosure.

(111) Referring to FIG. 7B, a processor **120** of an electronic device **101** may configure an avatar **720** (e.g., a head avatar) including only a head. For example, when providing the avatar to the external electronic device **210**, the electronic device **101** may configure the avatar, based on a specification and a capability of an external electronic device **210**. For example, when the external electronic device **210** is a wearable watch, since the size of a screen on which the avatar is displayed is small, the electronic device **101** may configure the avatar **720** including only the head. Referring to FIG. 7C, a processor **120** of an electronic device **101** may configure an avatar **730** (e.g., a body avatar) including only a body. For example, when providing the avatar to the external electronic device **210**, the electronic device **101** may configure the avatar, based on the specification and the capability of the external electronic device **210**.

(112) According to an embodiment, the electronic device **101** may determine a texture type, a resolution, and/or a texture format for each body part (e.g., the head avatar **720** and the body avatar **730**), based on the specification and the capability of the external electronic device **210**, and may configure an avatar according to the determination.

(113) FIG. 7D illustrates an operation of generating an avatar **740** in which a head part **741** is greater than a different part according to an embodiment of the disclosure. FIG. 7E illustrates an operation of generating an avatar **750** in which a body part **751** is greater than a different part according to an embodiment of the disclosure.

(114) According to an embodiment, the processor **120** of the electronic device **101** may configure a part (e.g., a head and a body) among body parts to be larger than a different part. The processor **120** may configure a texture type, a texture size, and/or texture format information for an enlarged body part to be different from those for a different body part.

(115) FIG. 7F illustrates an operation of generating an avatar, based on a portion of a head part and a body part of the avatar according to an embodiment of the disclosure.

(116) According to an embodiment, the processor **120** of the electronic device **101** may generate an avatar **760** configured only with a head part **761** and a portion **762** of a body among body parts, based on avatar-related information (e.g., specification and capability information about an

electronic device to use the avatar, texture information about the avatar, and/or texture format information about the avatar). According to an embodiment, the processor **120** may individually determine a texture type, a texture size, and/or texture format information in response to at least one of the body parts of the avatar.

(117) FIG. **8** is a flowchart illustrating a method of generating an avatar in response to a request from an external electronic device according to various embodiments of the disclosure.

(118) According to various embodiments, an electronic device (e.g., the electronic device **101** of FIG. **1** or the electronic device **200** of FIG. **2**) may generate first content (e.g., an avatar) associated with a user, based on an avatar application (e.g., the avatar application **310** of FIG. **3**). For example, a processor (e.g., the processor **120** of FIG. **1**) of the electronic device **101** may capture an image corresponding to the user using a camera module (e.g., the camera module **180** of FIG. **1**), and may generate the first content, based on the image. The processor **120** may determine a quality for the first content, based on a specification and a capability of the electronic device **101**. The processor **120** may store the generated first content in a memory (e.g., the memory **130** of FIG. **1**).

(119) According to an embodiment, the electronic device **101** may receive an avatar generation request from an external electronic device (e.g., the electronic device **102** or **104** of FIG. **1**, or the external electronic device **210** of FIG. **2**), and may generate second content (e.g., an avatar) in response to the request. For example, an avatar generation request signal may include at least one of the type of the external electronic device **210**, a specification of the external electronic device **210**, capability information about the external electronic device **210**, and/or avatar-related information (e.g., a texture type for an avatar, a texture size (resolution) for the avatar, and/or a body part of the avatar). The external electronic device **210** may request whether to generate an avatar by giving priority to capability or to generate an avatar by giving priority to quality. The electronic device **101** may generate a new avatar, based on the signal received from the external electronic device **210**, or may generate the second content by converting the first content stored in the memory **130**. According to an embodiment, the electronic device **101** may generate an avatar in response to the avatar generation request signal received from the external electronic device **210**, and may transmit the avatar to the external electronic device **210**.

(120) In operation **801**, the processor **120** may receive a request to generate an avatar from the external electronic device **210**. For example, the electronic device **101** is in a state of being operatively connected to the external electronic device **210** and may share data with the external electronic device **210**. The external electronic device **210** may transmit a request signal for generating an avatar including avatar-related information to the electronic device **101**. Table 4 is a table showing the avatar-related information included in the request signal.

(121) TABLE-US-00004 TABLE 4 Avatar-related information

Content Package name (essential)	1.
Package name of application generating request signal	Type of external electronic device (optional)
1. Wearable watch device (optional)	2. AR glass
3. Phone	4. VR
5. PC	Display size (optional)
X*Y (e.g., 1024*1024, 512*512, 128*128)	Upscale/downscale (optional)
1. Downscale	2. Upscale
Blend shape (optional)	Include/exclude Body part (optional)
1. Head + body	2. Head only
3. Body only	4. Big head + body
5. Head + big body	Quality (optional)
1. Automatic,	2. Capability first,
3. Quality first	

(122) Referring to Table 4, the request signal for generating the avatar may necessarily include a package name of an application generating the request signal, and may optionally include various pieces of information necessary to generate the avatar. For example, the request signal may include the type of the external electronic device **210** (e.g., a wearable watch, AR glasses, a phone, a VR, or a PC). When the type of the external electronic device **210** is identified, the processor **120** may determine specification and capability information about the external electronic device **210**. For example, the processor **120** may infer specification and capability information corresponding to the type of the external electronic device **210**. The request signal may include information about the size (e.g., 1024*1024, 512*512, or 128*128) of a display (e.g., the size of an actual physical

display). When converting the first content (e.g., the first avatar) stored in the memory **130** into the second content, the processor **120** may perform a downscale operation when overall quality is reduced, and may perform an upscale operation when the overall quality is increased. The request signal may include information about whether to include a blend shape effect. The request signal may request conversion of only a designated part of body parts of the avatar. Referring to FIGS. 7A to 7F, the processor **120** may individually configure the avatar by each body part. The request signal may include quality information (e.g., automatic, capability first, or quality first) when generating the avatar.

(123) In operation **803**, the processor **120** may identify whether an avatar corresponding to the request signal exists in the memory **130**. For example, when the electronic device **101** is previously linked with a different electronic device and executes an avatar-related application, the electronic device **101** may have generated an avatar for the different electronic device and may have stored the avatar in the memory **130**.

(124) When the avatar corresponding to the request signal matches an avatar stored in the memory **130** in operation **803**, the processor **120** may transmit the matched avatar stored in the memory **130** to the external electronic device **210** in operation **805**.

(125) When the avatar corresponding to the request signal does not match the avatar stored in the memory **130** in operation **803**, the processor **120** may identify the avatar-related information according to the request signal in operation **807**. Table 4 illustrated above shows the avatar-related information. According to an embodiment, the request signal may include at least one of the type of the external electronic device **210**, a display size of the external electronic device **210**, a desired body part of the avatar, and quality information about the avatar.

(126) In operation **809**, the processor **120** may generate an avatar, based on the avatar-related information. For example, when the external electronic device **210** is a wearable watch, the generated avatar may be configured with an optimized quality in the wearable watch. The processor **120** may map the generated avatar to the external electronic device **210**, and may store the avatar in the memory **130**. According to another embodiment, when the electronic device **101** receives an avatar request signal from a different electronic device that is a wearable watch, the electronic device **101** may compare and analyze the avatar stored in the memory **130**, and may transmit the avatar stored in the memory **130** to the different electronic device when the avatar matches the avatar request signal.

(127) In operation **811**, the processor **120** may transmit the avatar generated in response to the external electronic device **210** to the external electronic device **210**. When the generated avatar is displayed through a display of the external electronic device **210**, the avatar may be configured with an optimal quality.

(128) According to an embodiment, the electronic device **101** may receive a signal for requesting generation of an avatar from the external electronic device **210**, and may generate an optimized avatar corresponding to the external electronic device **210** in response to the received signal. The electronic device **101** may transmit the generated avatar to the external electronic device **210** so that the avatar is configured with an optimal quality when displayed through the display of the external electronic device **210**.

(129) A method according to various embodiments may include generating at least one first content corresponding to a user using a camera module **180**, converting the at least one first content into at least one second content, based on capability-related information about an external electronic device **210** and information related to content, and transmitting the at least one second content to the external electronic device **210**.

(130) According to an embodiment, the first content and the second content may include at least one of an avatar replacing the user, virtual content, a virtual character, and a virtual icon, which are generated based on an image captured using the camera module **180**.

(131) According to an embodiment, the capability-related information about the external electronic

device **210** may include specification information and capability information about at least one component forming the external electronic device **210**.

(132) According to an embodiment, the information related to the content may include texture information about the content, texture size information, texture format information, and/or information about a part forming the content.

(133) According to an embodiment, the texture information about the content may include at least one of albedo, normal, metallic, and/or roughness, which represent a texture of the content, and the method may further include determining optimized texture size information according to the texture information.

(134) According to an embodiment, the texture format information about the content may include a compression method for minimizing quality deterioration and/or a lossy compression method in which quality deterioration occurs, in an operation of compressing the content to be converted into a file format, and the information about the part forming the content may include at least one of a head part, a body part, and/or a bottom part.

(135) According to an embodiment, the method may further include individually converting the first content in response to each body part forming the first content, based on the capability-related information about the external electronic device **210** and the information related to the content, and generating the second content by integrating each of the converted body part.

(136) According to an embodiment, the method may further include generating third content corresponding to the external electronic device **210**, based on the capability-related information about the external electronic device **210** and the information related to the content included in a request signal, in response to the request signal from the external electronic device **210**, and transmitting the third content to the external electronic device **210** through the communication module **190**.

(137) According to an embodiment, the method may further include identifying whether the third content is stored in the memory **130** in response to the request signal from the external electronic device **210**, and transmitting the third content stored in the memory **130** to the external electronic device **210** when the third content is stored in the memory **130**.

(138) The electronic device according to various embodiments may be one of various types of electronic devices. The electronic devices may include, for example, a portable communication device (e.g., a smartphone), a computer device, a portable multimedia device, a portable medical device, a camera, a wearable device, or a home appliance. According to an embodiment of the disclosure, the electronic devices are not limited to those described above.

(139) It should be appreciated that various embodiments of the disclosure and the terms used therein are not intended to limit the technological features set forth herein to particular embodiments and include various changes, equivalents, or replacements for a corresponding embodiment. With regard to the description of the drawings, similar reference numerals may be used to refer to similar or related elements. It is to be understood that a singular form of a noun corresponding to an item may include one or more of the things, unless the relevant context clearly indicates otherwise. As used herein, each of such phrases as “A or B,” “at least one of A and B,” “at least one of A or B,” “A, B, or C,” “at least one of A, B, and C,” and “at least one of A, B, or C,” may include any one of, or all possible combinations of the items enumerated together in a corresponding one of the phrases. As used herein, such terms as “1st” and “2nd,” or “first” and “second” may be used to simply distinguish a corresponding component from another, and does not limit the components in other aspect (e.g., importance or order). It is to be understood that if an element (e.g., a first element) is referred to, with or without the term “operatively” or “communicatively,” as “coupled with,” “coupled to,” “connected with,” or “connected to” another element (e.g., a second element), it means that the element may be coupled with the other element directly (e.g., wiredly), wirelessly, or via a third element.

(140) As used in connection with various embodiments of the disclosure, the term “module” may

include a unit implemented in hardware, software, or firmware, and may interchangeably be used with other terms, for example, “logic,” “logic block,” “part,” or “circuitry.” A module may be a single integral component, or a minimum unit or part thereof, adapted to perform one or more functions. For example, according to an embodiment, the module may be implemented in a form of an application-specific integrated circuit (ASIC).

(141) Various embodiments as set forth herein may be implemented as software (e.g., the program **140**) including one or more instructions that are stored in a storage medium (e.g., internal memory **136** or external memory **138**) that is readable by a machine (e.g., the electronic device **101**). For example, a processor (e.g., the processor **120**) of the machine (e.g., the electronic device **101**) may invoke at least one of the one or more instructions stored in the storage medium, and execute it, with or without using one or more other components under the control of the processor. This allows the machine to be operated to perform at least one function according to the at least one instruction invoked. The one or more instructions may include a code generated by a compiler or a code executable by an interpreter. The machine-readable storage medium may be provided in the form of a non-transitory storage medium. Wherein, the term “non-transitory” simply means that the storage medium is a tangible device, and does not include a signal (e.g., an electromagnetic wave), but this term does not differentiate between where data is semi-permanently stored in the storage medium and where the data is temporarily stored in the storage medium.

(142) According to an embodiment, a method according to various embodiments of the disclosure may be included and provided in a computer program product. The computer program product may be traded as a product between a seller and a buyer. The computer program product may be distributed in the form of a machine-readable storage medium (e.g., compact disc read only memory (CD-ROM)), or be distributed (e.g., downloaded or uploaded) online via an application store (e.g., PlayStore™), or between two user devices (e.g., smart phones) directly. If distributed online, at least part of the computer program product may be temporarily generated or at least temporarily stored in the machine-readable storage medium, such as memory of the manufacturer's server, a server of the application store, or a relay server.

(143) According to various embodiments, each component (e.g., a module or a program) of the above-described components may include a single entity or multiple entities, and some of the multiple entities may be separately disposed in different components. According to various embodiments, one or more of the above-described components may be omitted, or one or more other components may be added. Alternatively or additionally, a plurality of components (e.g., modules or programs) may be integrated into a single component. In such a case, according to various embodiments, the integrated component may still perform one or more functions of each of the plurality of components in the same or similar manner as they are performed by a corresponding one of the plurality of components before the integration. According to various embodiments, operations performed by the module, the program, or another component may be carried out sequentially, in parallel, repeatedly, or heuristically, or one or more of the operations may be executed in a different order or omitted, or one or more other operations may be added.

(144) While the disclosure has been shown and described with reference to various embodiments thereof, it will be understood by those skilled in the art that various changes in form and details may be made therein without departing from the spirit and scope of the disclosure as defined by the appended claims and their equivalents.

Claims

1. An electronic device comprising: a communication circuitry; a camera; memory configured to store capability-related information of an external electronic device; and a processor operatively connected to the communication circuitry, the camera, and the memory, wherein the memory is further configured to store instructions that, when executed by the processor, cause the electronic

device to: generate a first avatar corresponding to a user using the camera, identify first configuration information corresponding to each of a plurality of body parts based on the first avatar, change the first configuration information into at least one piece of second configuration information determined based on the capability-related information of the external electronic device, wherein the at least one piece of second configuration information comprises texture information about each of the plurality of body parts, texture size information determined based on the texture information, or texture format information determined based on the texture information, and is determined separately for each of the plurality of body parts, generate a second avatar different from the first avatar based on the at least one piece of second configuration information corresponding to each of the plurality of body parts, and transmit the second avatar to the external electronic device through the communication circuitry.

2. The electronic device of claim 1, wherein the first avatar and the second avatar comprise at least one of an avatar replacing the user, virtual content, a virtual character, or a virtual icon, which are generated based on an image captured using the camera.

3. The electronic device of claim 1, wherein the capability-related information of the external electronic device comprises specification information and capability information about at least one component forming the external electronic device.

4. The electronic device of claim 1, wherein the texture information about the first avatar comprises at least one of albedo, normal, metallic, or roughness, which represents a visual texture.

5. The electronic device of claim 1, wherein the texture format information about the first avatar comprises a compression method for minimizing quality deterioration and a lossy compression method in which quality deterioration occurs, in an operation of compressing an avatar to be converted into a file format.

6. The electronic device of claim 1, wherein the first configuration information related to the first avatar further comprises information about a part forming the first avatar, and wherein the information about the part forming the first avatar comprises at least one of a head part, a body part, or a bottom part.

7. The electronic device of claim 1, wherein the processor is further configured to: generate third avatar corresponding to the external electronic device, based on the capability-related information of the external electronic device, in response to a request signal of the external electronic device; and transmit the third avatar to the external electronic device through the communication circuitry.

8. The electronic device of claim 7, wherein the processor is further configured to: identify whether the third avatar is stored in the memory in response to the request signal of the external electronic device; and transmit the third avatar stored in the memory to the external electronic device in response to the third avatar being stored in the memory.

9. The electronic device of claim 1, wherein the external electronic device comprises at least one of a wearable watch, augmented reality (AR) glasses, a smartphone, a virtual reality (VR) device, or a personal computer (PC).

10. The electronic device of claim 1, wherein the at least one piece of second configuration information comprises information about each of the plurality of body parts indicating which of the plurality of body parts to include or exclude based on the capability-related information of the external electronic device.

11. A method comprising: generating a first avatar corresponding to a user using a camera; identifying first configuration information corresponding to each of a plurality of body parts based on the first avatar; changing the first configuration information into at least one piece of second configuration information determined based on capability-related information of an external electronic device, wherein the at least one piece of second configuration information comprises texture information about each of the plurality of body parts, texture size information determined based on the texture information, or texture format information determined based on the texture information, and is determined separately for each of the plurality of body parts; generating a

second avatar different from the first avatar based on the at least one piece of second configuration information corresponding to each of the plurality of body parts; and transmitting the second avatar to the external electronic device.

12. The method of claim 11, wherein the first avatar and the second avatar comprise at least one of an avatar replacing the user, virtual content, a virtual character, or a virtual icon, which are generated based on an image captured using the camera.

13. The method of claim 11, wherein the capability-related information of the external electronic device comprises specification information and capability information about at least one component forming the external electronic device.

14. The method of claim 11, wherein the texture information about the first avatar comprises at least one of albedo, normal, metallic, or roughness, which represent a visual texture.

15. The method of claim 11, wherein the texture format information about the first avatar comprises a compression method for minimizing quality deterioration and a lossy compression method in which quality deterioration occurs, in an operation of compressing an avatar to be converted into a file format, wherein the first configuration information related to the first avatar further comprises information about a part forming the first avatar, and wherein the information about the part forming the first avatar comprises at least one of a head part, a body part, or a bottom part.

16. The method of claim 11, further comprising: generating third avatar corresponding to the external electronic device, based on the capability-related information of the external electronic device, in response to a request signal of the external electronic device; and transmitting the third avatar to the external electronic device through a communication circuitry.

17. The method of claim 16, further comprising: identifying whether the third avatar is stored in a memory in response to the request signal of the external electronic device; and transmitting the third avatar stored in the memory to the external electronic device in response to the third avatar being stored in the memory.

18. The method of claim 11, wherein the at least one piece of second configuration information comprises information about each of the plurality of body parts indicating which of the plurality of body parts to include or exclude based on the capability-related information of the external electronic device.
