

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent
Kind Code
Date of Patent
Inventor(s)

12417606
B2
September 16, 2025
Belligundu; Suhas et al.

Method and system for anomaly detection using multimodal knowledge graph

Abstract

A method and system for detecting anomalies associated with a plurality of data objects of a technical installation is provided. The method includes receiving a request to detect anomaly associated with the plurality of data objects in an image data. The image data can be a static image data or a dynamic image data. The method includes classifying the plurality of data objects using a multimodal knowledge graph. The multimodal knowledge graph includes a plurality of pre-classified data objects, each of pre-classified data object is connected using one or more paths. Further, the method includes detecting whether anomaly exists in the plurality of classified data objects. The anomaly is detected by evaluating the plurality of classified data objects with reference data corresponding to the plurality of classified data objects obtained from the multimodal knowledge graph. Furthermore, the method includes generating a notification indicating the detected anomaly based on the evaluation.

Inventors:	Belligundu; Suhas (Karnataka, IN), Sudhakaran; Vinay (Karnataka, IN)
Applicant:	Siemens Aktiengesellschaft (Munich, DE)
Family ID:	1000008821249
Assignee:	SIEMENS AKTIENGESELLSCHAFT (Munich, DE)
Appl. No.:	17/773165
Filed (or PCT Filed):	November 02, 2020
PCT No.:	PCT/EP2020/080686
PCT Pub. No.:	WO2021/084125
PCT Pub. Date:	May 06, 2021

Prior Publication Data

Foreign Application Priority Data

EP19206513Oct. 31, 2019

Publication Classification

Int. Cl.: G06V10/20 (20220101); G06T7/00 (20170101); G06V10/70 (20220101); G06V10/764 (20220101)

U.S. Cl.:

CPCG06V10/20 (20220101); G06T7/0004 (20130101); G06V10/70 (20220101); G06V10/764 (20220101);

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6035305	12/1999	Strevey	N/A	G06Q 10/06
2011/0052068	12/2010	Cobb	382/190	G06V 10/7715
2016/0034784	12/2015	Ohmura	382/103	G06T 7/254
2016/0055409	12/2015	Majumdar	706/20	G06N 7/01
2016/0139977	12/2015	Ashani	714/26	G06F 11/0706
2017/0293611	12/2016	Tu	N/A	G06F 16/48
2018/0150701	12/2017	Kang	N/A	G06F 18/2413
2018/0350053	12/2017	Sugaya	N/A	G06T 7/001
2019/0197396	12/2018	Rajkumar	N/A	B25J 9/1671
2021/0081698	12/2020	Lindeman	N/A	G06Q 30/0283

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
110378381	12/2018	CN	G06K 9/62
2003297888	12/2002	JP	G01B 11/30

OTHER PUBLICATIONS

Y. Wang, L. Gao, Y. Gao, X. Li and L. Gao, “Knowledge Graph-guided Convolutional Neural Network for Surface Defect Recognition,” 2020 IEEE 16th International Conference on Automation Science and Engineering (CASE), Hong Kong, China, 2020, pp. 594-599, doi: 10.1109/CASE48305.2020.9216752. (Year: 2020). cited by examiner

F. Schroff et al: "Object Class Segmentation using Random Forests", Proceedings of the British Machine Vision Conference 2008, Jan. 1, 2008 (Jan. 1, 2008), pp. 54.1-54.10, XP055264531, DOI: 10.5244/C.22.54 ISBN: 978-1-901725-36-0 the whole document. cited by applicant

Boykov Y et al: "Fast approximate energy minimization via graph cuts", IEEE Transactions on Pattern Analysis and Machine Intelligence, IEEE Computer Society, USA, vol. 23, No. 11, Nov. 1, 2001 (Nov. 1, 2001), pp. 1222-1239, XP011093916, ISSN: 0162-8828, DOI: 10.1109/34.969114 the whole document. cited by applicant

Faliu Yi et al: "Image segmentation: A survey of graph-cut methods", Systems and Informatics (ICSAI), 2012 International Conference on, IEEE, May 19, 2012 (May 19, 2012), pp. 1936-1941, XP032192906, DOI: 10.1109/ICSAI.2012.6223428 ISBN: 978-1-4673-0198-5 the whole document. cited by applicant

International Search Report & Written Opinion for PCT/EP2020/080686 mailed Jan. 27, 2021. cited by applicant

Wu Ming-Ju et al: "Wafer Map Failure Pattern Recognition and Similarity Ranking for Large-Scale Data Sets", Feb. 1, 2015, pp. 1-12, XP011571748. cited by applicant

Marino Kenneth et al; "The More You Know: Using Knowledge Graphs for Image Classification"; Carnegie Mellon University; 5000 Forbes Ave, Pittsburgh, PA 15213. cited by applicant

Primary Examiner: Menberu; Beniyam

Attorney, Agent or Firm: Schmeiser, Olsen & Watts LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) This application claims priority to PCT Application No. PCT/EP2020/080686, having a filing date of Nov. 2, 2020, which claims priority to EP Application No. 19 206 513.4, having a filing date of Oct. 31, 2019, the entire contents both of which are hereby incorporated by reference.

FIELD OF TECHNOLOGY

(2) The following generally relates to computer vision and more particularly relates to a method and system for anomaly detection using multimodal knowledge graph.

BACKGROUND

(3) In general, object detection model incorporates a machine-learning mechanism that utilizes human knowledge in form of labeled data as an input. Since it is difficult to provide enough labeled data, considering from human levels to the machine-learning mechanism, the performance of the machine-learning mechanism is limited. Without sufficiently large datasets including labels, the machine-learning mechanism fails to detect the objects, which it is not trained on.

(4) Zero-Shot Learning (ZSL) refers to a method for determining objects of new classes (unseen classes). For example, conventional object recognition methods need to predefine some classes (annotated labels, as described above), and then need to train the object detection model to recognize the objects in these classes. However, if there is an object in an unseen class, the model will fail to recognize it. ZSL is proposed to solve this problem.

(5) According to the ZSL, the knowledge from seen classes is transferred to unseen classes. That is, a semantic space including the seen and unseen classes along with visual representation of the images/pictures that are projected and analysed. However, the ZSL, predominantly, is limited to classification of classes, instead of detecting the location of the objects in the image(s).

(6) Thus, for constructing object detectors, the ZSL still requires annotated training images to train source classification models. For this purpose, the ZSL model is extended to object detection and

focus on a Zero-Short Detection (ZSD) that requires zero examples for the unseen classes. However, the ZSD is not accurate without any prior information.

(7) From the aforementioned reasoning, it is evident that one of the main shortcomings in existing object detection models is their requirements of high amount of training data to achieve good accuracy. In addition, a practical problem in extending machine-learning models to domain specific data is that the quality and quantity of annotated data is poor and can be expensive to obtain. Another problem is with the availability of sufficient training data in certain domains. It can also be noted that a lot of information/knowledge is available in the form of knowledge graphs such as manuals, standard operating procedures, expert blogs, prior knowledge or the like, but the existing object detection models are not able to use this valuable information to aid them in classification and detection of the objects.

SUMMARY

(8) An aspect relates to a method and a system for anomaly detection using multimodal knowledge graph.

(9) According to a first aspect, the object of the disclosure is achieved by a method for detecting anomalies associated with a plurality of data objects of a technical installation. The technical installation can include industrial plants, sites, monitoring and control areas, and the like. The plurality of data objects of the technical installation can include, for example industrial equipment(s), machinery, tools, components, devices, and the like. Without limiting to the technical installation, the plurality of data objects may also include data objects such as for example, a car, a tree, a cart, a road, and the like. The method comprises receiving a request to detect anomaly associated with the plurality of data objects in an image data. The image data can be a static image data and/or a dynamic image data. The static image data includes still image and the dynamic image data includes a sequence of image data, for example a video data, a multimedia data, a graphics interchange format (GIF), and the like. The method further comprises classifying the plurality of data objects using a multimodal knowledge graph. The multimodal knowledge graph comprises a plurality of pre-classified data objects, each of pre-classified data object is connected using one or more paths. The multimodal knowledge graph also comprises reference data along with the pre-classified data objects. The method additionally comprises detecting whether the anomaly exists in the plurality of classified data objects. The anomaly is detected by evaluating the plurality of classified data objects with the reference data corresponding to the plurality of classified data objects obtained from the multimodal knowledge graph. The anomaly can also be detected by evaluating the plurality of classified data objects with the pre-classified data objects and the reference data. The reference data includes a set of pre-defined rules, a standard operating procedure, a pre-defined activity or a process, and the like. The pre-classified data objects are the data objects which are already classified and information regarding these pre-classified data objects is available in the multimodal knowledge graph. The method additionally comprises generating a notification indicating the detected anomaly based on the evaluation. For example, a notification can be in a text or a graphical form indicating the detected anomaly.

(10) In an embodiment, the method for classifying the plurality of data objects using the multimodal knowledge graph comprises receiving a first data corresponding to seen data classes (i.e., known classes/trained classes) of each data object from the plurality of data objects. Further, the method comprises identifying a second data corresponding to unseen data classes (i.e., unknown classes/untrained classes) associated of each data object from the plurality of data objects using the received first data. The method additionally comprises classifying the plurality of data objects using the first data and the second data.

(11) In an embodiment, the method further comprises determining that the anomaly in the plurality of classified data objects fails to exist in the multimodal knowledge graph. Furthermore, the method comprises outputting the plurality of classified data objects on a display screen of an electronic device.

(12) In an embodiment, the method comprises receiving an update request to update the one or more paths of the multimodal knowledge graph. The method additionally comprises classifying the plurality of data objects using the multimodal knowledge graph comprising the updated path. The method additionally comprises detecting whether the anomaly exists in the plurality of classified data objects using the multimodal knowledge graph comprising the updated path, wherein the anomaly is detected by evaluating the plurality of classified data objects with the reference data corresponding to the plurality of classified data objects obtained from the multimodal knowledge graph comprising the updated path. The method additionally comprises generating a notification indicating the detected anomaly based on the evaluation and outputting the plurality of classified data objects on the display screen of the electronic device.

(13) In an embodiment, the one or more paths of the multimodal knowledge graph is updated by adding a sequence of nodes and edges, wherein each node indicates a visual concept of the data object, and each edge indicates a relationship between the visual concepts among the plurality of data objects.

(14) In an embodiment, the method further comprises generating one or more recommendations to rectify the detected anomaly. The one or more recommendations is generated by analysing similar detected anomaly in relation to the plurality of data objects obtained from the multimodal knowledge graph.

(15) According to a second aspect, the object of the disclosure is achieved by a method for detecting anomalies associated with a plurality of data objects of a technical installation. The method comprising receiving a request to detect anomaly associated with the plurality of data objects obtained from an image data and sensor data. The sensor data is related to operating parameters of the data objects. For example, the sensor data includes operating pressure, operating temperature of a data object such as a pump. The sensor data may be analysed over time periods to determine anomaly. The image data comprises at least one of a static image data and a dynamic image data. The method comprises classifying the plurality of data objects using a multimodal knowledge graph, wherein the multimodal knowledge graph comprises a plurality of pre-classified data objects, each of pre-classified data object is connected using one or more paths. The method additionally comprises detecting whether the anomaly exists in the plurality of classified data objects, wherein the anomaly is detected by evaluating the plurality of classified data objects with reference data corresponding to the plurality of classified data objects obtained from the multimodal knowledge graph. The reference data includes a set of pre-defined rules, a standard operating procedure, a pre-defined activity or a process, and the like. Further, the method additionally comprises generating a notification indicating the detected anomaly based on the evaluation.

(16) According to a third aspect, the object of the disclosure is achieved by a system for detecting anomalies associated with a plurality of data objects of a technical installation. The system comprising one or more processing units, a memory operatively coupled to the one or more processing units. The memory comprising an anomaly detection module configured to perform the embodiments of the method steps as described above.

(17) According to a fourth aspect, the object of the disclosure is achieved by a computer program product (non-transitory computer readable storage medium having instructions, which when executed by a processor, perform actions) for detecting anomalies associated with a plurality of data objects of a technical installation. The computer program product includes a non-transitory storage medium readable by a processing circuit, the storage medium storing instructions executable by the processing circuit and configured to cause for execution of the method steps as described above.

Description

BRIEF DESCRIPTION

- (1) Some of the embodiments will be described in detail, with reference to the following figures, wherein like designations denote like members, wherein:
- (2) FIG. 1 illustrates a block diagram of a system, according to an embodiment of present invention;
- (3) FIG. 2 illustrates a block diagram of an illustrative computing system for implementing one or more embodiments of the present invention;
- (4) FIG. 3 illustrates various components of an anomaly detection module as shown in FIG. 2, according to an embodiment of the present invention;
- (5) FIG. 4 is a flow diagram illustrating an exemplary detecting anomaly associated with a plurality of data objects of a technical installation, according to an embodiment of the present invention;
- (6) FIG. 5 is a flow diagram illustrating a process for updating the multimodal knowledge graph, according to an embodiment of the present invention; and
- (7) FIG. 6 illustrates an example scenario of the reinforcement learning using the multimodal knowledge graph, according to an embodiment of the present invention.

DETAILED DESCRIPTION

- (8) Various embodiments of the present disclosure will now be described in detail with reference to the accompanying drawings. In the following description, specific details such as detailed configuration and components are merely provided to assist the overall understanding of these embodiments of the present disclosure. Therefore, it should be apparent to those skilled in the art that various changes and modifications of the embodiments described herein can be made without departing from the scope and spirit of the present disclosure. In addition, descriptions of well-known functions and constructions are omitted for clarity and conciseness.
- (9) Also, the various embodiments described herein are not necessarily mutually exclusive, as some embodiments can be combined with one or more other embodiments to form new embodiments.
- (10) FIG. 1 is a block diagram of a system **100**, according to an embodiment of present invention.
- (11) The system **100** may include a server **101**, a network(s) **105**, and devices **106.1-106.n** (hereinafter alternatively referred as electronic device **106**). Further, the server **101** includes a database **102**, an anomaly detection module **103**, and a network interface(s) **104**.
- (12) The server **101** communicates with the electronic device **106** using the network **105**. The server **101** may include hardware, software, or firmware components. The database **102** includes a collection of image data comprising a plurality of data objects of a technical installation. The data objects can include, for example industrial equipment(s), machinery, tools, components, devices, and the like.
- (13) In an embodiment, the anomaly detection module **103** communicates with the database **102** to obtain the image data comprising the plurality of data objects. Alternatively, the anomaly detection module **103** may obtain the image data from a remote server or a cloud by communicating through the network interface **104**.
- (14) Although not shown in FIG. 1, the server **101** includes a processor, a memory and a storage unit. The memory includes the anomaly detection module **103** stored in the form of machine-readable instructions executable by the processor. When executed by the processor, the anomaly detection module **103** causes the processor to detect whether the anomaly exists in the plurality of classified data objects by evaluating the plurality of classified data objects with the reference data corresponding to the plurality of classified data objects obtained from the multimodal knowledge graph. Method steps performed by the processor to achieve the above functionality are described in greater detail in FIGS. 3 and 4.
- (15) The electronic device **106** may be a device having a screen and capable of performing human-machine interaction, such as a mobile phone, notebook computer, tablet, desktop computer, virtual reality (VR) device, Augmented reality (AR) device, server, or the like. The electronic devices **106**

are provided with input units and display units, respectively. Users of the electronic devices **106** can access the server **101** via a graphical user interface displayed on the respective display units. The graphical user interfaces may be specifically designed for accessing the anomaly detection module **103** in the server **101**.

(16) The network interface **104** via which the anomaly detection module **103** may communicate with one or more other devices or systems via the network **105**. The network **105** may include, but are not limited to, any one or more different types of communications networks such as, for example, cable networks, public networks (e.g., the Internet), private networks (e.g., frame-relay networks), wireless networks, cellular networks, telephone networks (e.g., a public switched telephone network), cloud-based networks, or any other suitable private or public packet switched or circuit switched networks. Such network(s) may have any suitable communication range associated therewith and may include, for example, global networks (e.g., the Internet), metropolitan area networks (MANs), wide area networks (WANs), local area networks (LANs), or personal area networks (PANs).

(17) In addition, the network interface **104** may include communication links and associated networking devices (e.g., link-layer switches, routers, etc.) for transmitting network traffic over any suitable type of medium including, but not limited to, coaxial cable, twisted-pair wire (e.g., twisted-pair copper wire), optical fiber, a hybrid fiber-coaxial (HFC) medium, a microwave medium, a radio frequency communication medium, a satellite communication medium, or any combination thereof.

(18) In an exemplary operation, the electronic device **106** may send the request to the server **101** to detect anomaly associated with the plurality of data objects in the image data. The processor in the server **101** receives the request from the electronic device **106**. The processor obtains the image data comprising the plurality of data objects from the database **102**. Further, the processor classifies the plurality of data objects using the multimodal knowledge graph which includes a plurality of pre-classified objects or known classification of the plurality of data objects. Thus, the processor in the server classifies the plurality of data objects obtained from the database **102**, using the pre-classified objects in the multimodal knowledge graph. Accordingly, the processor in the server **101** detects whether the anomaly exists in the plurality of classified data objects, by evaluating the plurality of classified data objects with reference data corresponding to the plurality of classified data objects obtained from the multimodal knowledge graph. For example, the reference data includes a set of pre-defined rules, a standard operating procedure, a pre-defined activity or a process, and the like. The notification can be a text or in a graphical form indicating the detected anomaly. Additionally, the processor outputs the detected anomaly on the display unit of the electronic device **106**. For example, the graphical user interface on the electronic device **106** may display the generated notification indicating the anomaly.

(19) However, it should be noted that, in case if the anomaly detection fails to meet a threshold (i.e., threshold such as detection of the anomaly in predefined sequence of objects in the image data or persistence of anomaly for the sequence of the data objects in the image data) the processor fails to output or trigger the anomaly. Thereby, increasing the reliability of the detected anomaly, and avoiding the false triggering of the anomaly. In the system **100**, a plurality of users can simultaneously validate whether the detected anomaly is a real anomaly or not by accessing the server **101** from the electronic device **106**.

(20) In case, if the processor determines that the anomaly in the plurality of classified objects fails to meet the threshold, the processor outputs only the plurality of classified data objects on the display screen of the electronic device **106**.

(21) In accordance with the foregoing description, the anomaly detection module **103** may be implemented in a cloud computing environment, wherein the anomaly detection module **103** is hosted on a cloud server. The various embodiments pertaining to the anomaly detection module **103** are described in later parts of description.

(22) In an exemplary embodiment, the proposed method and system can be used for detection of the anomaly with respect to a manufacturing process in an industrial environment. The industrial environment may include various equipment, various sensors and controller(s) for monitoring the manufacturing process. For example, the industry may include food & beverage industries, equipment (i.e., electrical, mechanical, or the like) manufacturing industries and any such process automation industries. Consider a scenario in which the manufacturing process of the biscuits is examined to detect anomaly. For example, anomaly in terms of shape and quality of the biscuits. The anomaly detection module **103** obtains the image data from a camera source installed in the industrial environment, sensor data from various sensors monitoring the process and data from the controller (i.e., Programmable Logic Controller PLC), or the like. The data from the camera, sensors, and the controller can also be obtained from the database **102**. Further, the obtained image data, the sensor data, and the data from the controller can be evaluated with reference data (i.e., reference shape or reference quality) stored in the multimodal knowledge graph. For example, a sample of ten biscuits may be compared with the reference shape to detect anomaly with respect to the shape of the biscuits being processed. Further, the sensor data can be processed to determine the anomaly associated with the quality of biscuits. In case of the anomaly detection, the anomaly detection module **103** can provide the notification to the user (i.e., plant engineer) and may also generate and indicate the one or more recommendations (available from the multimodal knowledge graph) to rectify the detected anomaly. The recommendations may include reduction or addition of some ingredients to achieve the desired quality of the biscuits.

(23) FIG. 2 illustrates a block diagram of the illustrative computing system **200** for implementing one or more embodiments of the present invention.

(24) The computing system **200** may include processing unit **201**, one or more memory devices **202** (referred to herein as memory **202**/memory unit **202**), storage unit **203**, an input unit **204**, and an output unit **205**. The system **200** may further include one or more buses **206** that functionally couple various components of the computing system **200**.

(25) The memory **202** may include volatile memory (memory that maintains its state when supplied with power) such as random-access memory (RAM) and/or non-volatile memory (memory that maintains its state even when not supplied with power) such as read-only memory (ROM), flash memory, ferroelectric RAM (FRAM), and so forth. Persistent data storage, as that term is used herein, may include non-volatile memory. In certain example embodiments, volatile memory may enable faster read/write access than non-volatile memory. However, in certain other example embodiments, certain types of non-volatile memory (e.g., FRAM) may enable faster read/write access than certain types of volatile memory. In certain example, the storage unit **203** may be equivalent to the memory **202**. In various implementations, the memory **202** may include multiple different types of memory such as various types of static random-access memory (SRAM), various types of dynamic random-access memory (DRAM), various types of unalterable ROM, and/or writable variants of ROM such as electrically erasable programmable read-only memory (EEPROM), flash memory, and so forth. The memory **202** may include main memory as well as various forms of cache memory such as instruction cache(s), data cache(s), translation lookaside buffer(s) (TLBs), and so forth. Further, cache memory such as a data cache may be a multi-level cache organized as a hierarchy of one or more cache levels (L1, L2, etc.).

(26) The storage unit **203** may include removable storage and/or non-removable storage including, but not limited to, magnetic storage, optical disk storage, and/or tape storage. The storage unit **203** may provide non-volatile storage of computer-executable instructions and other data. The storage unit **203** and the memory **202**, removable and/or non-removable, are examples of computer-readable storage media (CRSM).

(27) The storage unit **203** may store computer-executable code, instructions, or the like that may be loadable into the memory **202** and executable by the processing unit **201** to cause the processing unit **201** to perform or initiate various operations such as the operations required for detecting the

anomaly associated with the plurality of data objects of the technical installation. The storage unit **203** may additionally store data (such as the image data, the sensor data, the controller data, and the like) that may be copied to memory **202** for use by the processing unit **201** during the execution of the computer-executable instructions. Moreover, output data generated as a result of execution of the computer-executable instructions by the processing unit **201** may be stored initially in memory **202** and may ultimately be copied to storage unit **203** for non-volatile storage.

(28) More specifically, the storage unit **203** may store an operating systems (O/S); the database **102** configured to access the memory **202**; and one or more program module, applications, engines, managers, computer-executable code, scripts, or the like such as, for example, the various modules of the anomaly detection module **103**. Any of the components depicted as being stored in storage unit **203** may include any combination of software, firmware, and/or hardware. The software and/or firmware may include computer-executable instructions (e.g., computer-executable program code) that may be loaded into the memory **202** for execution by one or more of the processing unit **201** to perform any of the corresponding operations described earlier.

(29) The processing unit **201** may be configured to access the memory **202** and execute computer-executable instructions loaded therein. For example, the processing unit **201** may be configured to execute computer-executable instructions of the various program module, applications, engines, managers, or the like of the anomaly detection module **103** to cause or facilitate various operations to be performed in accordance with one or more embodiments of the disclosure. The processing unit **201** may include any suitable processing unit capable of accepting data as input, processing the input data in accordance with stored computer-executable instructions, and generating output data. The processing unit **201** may include any type of suitable processing unit including, but not limited to, a central processing unit, a microprocessor, a Reduced Instruction Set Computer (RISC) microprocessor, a Complex Instruction Set Computer (CISC) microprocessor, a microcontroller, an Application Specific Integrated Circuit (ASIC), a Field-Programmable Gate Array (FPGA), a System-on-a-Chip (SoC), a digital signal processor (DSP), and so forth. Further, the processing unit **201** may have any suitable microarchitecture design that includes any number of constituent components such as, for example, registers, multiplexers, arithmetic logic units, cache controllers for controlling read/write operations to cache memory, branch predictors, or the like. The microarchitecture design of the processing unit **201** may be capable of supporting any of a variety of instruction sets.

(30) The input unit **204** and the output unit **205** may facilitate the receipt of input information by the anomaly detection module **103** from one or more I/O devices as well as the output of information from the anomaly detection module **103** to the one or more I/O devices. The I/O devices may include any of a variety of components such as a display or a display screen having a touch surface or a touchscreen; an audio output device for producing sound, such as a speaker; an audio capture device, such as a microphone; an image and/or video capture device, such as a camera; a haptic unit; and so forth. Any of these components may be integrated into the components of the computing system **200** or only into the anomaly detection module **103** or may be separate. The I/O devices may further include, for example, any number of peripheral devices such as data storage devices, printing devices, and so forth. The input unit **204** and the output unit **205** may also include an I/O interface for an external peripheral device connection such as universal serial bus (USB), FireWire, Thunderbolt, Ethernet port or other connection protocol that may connect to one or more networks.

(31) The I/O interface(s) may also include a connection to one or more antennas to connect to one or more networks via a wireless local area network (WLAN) (such as WiFi) radio, Bluetooth, and/or a wireless network radio, such as a radio capable of communication with a wireless communication network such as a Long-Term Evolution (LTE) network, WiMAX network, 3G network, etc.

(32) The bus(es) **206** may include at least one of a system bus, a memory bus, an address bus, or a

message bus, and may permit the exchange of information (e.g., data (including computer-executable code), signaling, etc.) between various components of the anomaly detection module **103**. The bus(es) **206** may include, without limitation, a memory bus or a memory controller, a peripheral bus, an accelerated graphics port, and so forth.

(33) FIG. 3 illustrates various components of the anomaly detection module **103**, according to an embodiment of the present invention.

(34) As depicted in FIG. 3, the anomaly detection module **103** comprises a classification module(s) **302**, a multimodal knowledge base module(s) **304**, an object detection module(s) **308**, an evaluation module(s) **310**, a recommendation engine **312**, a reinforcement-learning module(s) **314**, and the storage unit **203**. The multimodal knowledge base module(s) **304** incorporates a multimodal knowledge graph **306**. For example, the multimodal knowledge graph **306** can be either locally stored in the memory **202** or can be retrieved from the storage unit **203**. The classification module **302**, the multimodal knowledge base module **304**, the object detection module **308**, the multimodal knowledge graph **306**, the evaluation module(s) **310**, the recommendation engine **312**, and the reinforcement-learning module **314**, may take a form of hardware such as the processing unit **201** with embedded software, or a computer program in the form machine-readable instructions stored on a computer program product (e.g., the memory unit **202**) and executable by the processing unit **201**.

(35) The anomaly detection module **103** can be configured to receive the request from the electronic device **106** to detect anomaly associated with the plurality of data objects in the image data which includes the static image data and the dynamic image data. The request may be received by the anomaly detection module **103** through a suitable communication protocol. For example, the image data can be obtained from the storage unit **203** or can be directly obtained from any runtime applications (e.g., camera) without being stored in the storage unit **203**. For example, the image data may be a graphical representation of the media files (e.g., videos) or images associated with media files (e.g., album), multimedia files, or the like.

(36) The objects in the image data may be of same or different classes and the objects may be structured objects such as car or unstructured objects such as sky. Partially occluded objects may also be present in the image data.

(37) In an embodiment, the classification module **302** can be configured to detect the number of data objects in the image data, for example, data object-1, data object-2, data object 3 and so on to data object “N”. Further, the classification module **302** can be configured to classify the data objects of known classes (i.e., seen classes from the identified objects) from the image data. The classification module **302** can be configured to classify the data objects of unknown classes (i.e., unseen classes from the identified objects) using the multimodal knowledge graph **306**.

(38) In an embodiment, the classification module **302** can be configured to classify the plurality of data objects in the image data using the pre-classified objects available in the multimodal knowledge graph **306**. In an exemplary embodiment, the multimodal knowledge graph **306** includes numerical features in the form of graph structure, visual data/concepts in the form of graph structure, knowledge about the data objects, classification of objects belonging to both seen classes and unseen classes, system design, manuals, state-of the art procedures, or the like, in form of graph structure. The path in multimodal knowledge graph **306** indicates relations between nodes and edges of the multimodal knowledge graph **306**. In certain example embodiments, the visual concepts in the multimodal knowledge graph **306** are represented as nodes and the relationships between them as edges.

(39) Further, the multimodal knowledge base module **304** communicates with the object detection module **308** in that the output from the object detection module **308** is received as input to the multimodal knowledge base module **304** comprising the multimodal knowledge graph **306**.

(40) In certain example embodiments, the object detection module **308** may be configured to detect the data objects using two steps, a training step and a detection step. In the training step, the object

detection module **308** can be trained using training samples to adjust parameters of the object detection module **308**. The training samples may include images of data objects belonging to certain class (such as humans, buildings or cars), pixel of the images, and pattern of objects such as edges, horizontal edges, round shapes or the like, present in the image data. The classes of data objects used during the training step are known as seen classes and the classes of objects which are not used during the training step are known as unseen classes. Subsequent to the training step, the object detection module **308** can be configured to detect the data objects i.e., corresponding to both seen and unseen classes in the detection step. Thus, the object detection module **308** detects the data objects in the image data.

(41) Further, the evaluation module **310** can be configured to evaluate (or compare) the plurality of classified data objects with the reference data corresponding to the plurality of classified data objects obtained from the multimodal knowledge graph **306**. The reference data includes a set of pre-defined rules, a standard operating procedure, a pre-defined activity or a process, and the like. For example, the evaluation module **310** can be configured to evaluate whether the detected anomaly in the plurality of classified data objects (i.e., when the classified data objects are compared/evaluated with the reference data) meets the threshold value. For example, the threshold value can be a pre-determined value (for example, 0.8). In case, if it is determined that the detected anomaly in the plurality of classified data objects meets the threshold value, then the evaluation module **310** can be configured to detect the anomaly in the plurality of classified data objects.

(42) In an embodiment, the evaluation module **310** can be configured to generate the notification, such as for example a text or in a graphical form, indicating the detected anomaly.

(43) In another embodiment, if the evaluation module **310** determines that there is no anomaly in the plurality of classified data objects, then the evaluation module **310** can be configured to trigger a display unit of the electronic device to output the plurality of classified data objects on the display screen of the electronic device **106**.

(44) The recommendation engine **312** can be configured to generate one or more recommendations to rectify the detected anomaly. For example, the one or more recommendations may be generated by analysing similar detected anomaly in relation to the plurality of data objects and determining the solutions/recommendation used to rectify the detected anomaly from the multimodal knowledge graph **306**.

(45) In an embodiment, the reinforcement-learning module **314** can be configured to receive an update request from the electronic device **106** to update path(s) of the multimodal knowledge graph **306**. Upon receiving the update request from the electronic device **106**, the one or more paths of the multimodal knowledge graph **306** are updated. Thus, the one or more paths of the multimodal knowledge graph **306** are updated by adding a sequence of nodes and edges, wherein each node indicates a visual concept of the plurality of objects and each edge indicates a relationship between the visual concepts of the plurality of objects.

(46) With the updated paths in the multimodal knowledge graph **306**, the anomaly detection module **103** detects whether the anomaly exists in the classified data objects using the multimodal knowledge graph **306** with the updated path. Further, the evaluation module **310** can be configured to generate a notification as a text or in a graphical form indicating the detected anomaly.

(47) Example embodiments of the disclosure incorporate the knowledge obtained from the multimodal knowledge graph **306** to determine the anomaly within the industrial environment. Since the training data set in the industrial environment is limited, the present disclosure describes the use of the multimodal knowledge graph **306** to determine the industrial objects and to detect the anomalies associated with the industrial objects. Further, the present disclosure describes a reasoning-based model to forecast the unforeseen actions using the multimodal knowledge graph **306**.

(48) FIG. 4 is a flow diagram **400** illustrating a process for detecting anomalies associated with the plurality of data objects using the technical installation, according to an embodiment of the present

invention.

(49) At step **402**, the request to detect anomaly associated with the plurality of data objects in the image data is received.

(50) At step **404**, the plurality of data objects are classified using the multimodal knowledge graph **306**. The multimodal knowledge graph **306** includes the plurality of pre-classified data objects, where each of the pre-classified object is connected using the one or more paths. For example, the data objects (i.e., the first objects/the second objects) from the image data are detected. The data objects can be classified using the classification (i.e., the seen classes) of the data objects. The untrained classifications (i.e., the unseen classes) of the objects can be derived using the multimodal knowledge graph **306**.

(51) At step **406**, it is detected whether the anomaly exists in the plurality of classified data objects. In an embodiment, the anomaly is detected by evaluating the plurality of classified data objects with the reference data corresponding to the plurality of classified data objects obtained from the multimodal knowledge graph **306**. If it is determined that the anomaly exists, then at step **408**, the notification indicating the detected anomaly is generated.

(52) If it is determined that the anomaly fails to exist in the plurality of data objects, then at step **410**, the plurality of classified data objects are displayed on the screen of the electronic device **106**.

(53) FIG. 5 is a flow diagram **500** illustrating the process for updating the multimodal knowledge graph **306**, according to the embodiment of the present invention.

(54) At step **502**, the update request to update the one or more paths of the multimodal knowledge graph **306** is received.

(55) At step **504**, the plurality of data objects are classified using the multimodal knowledge graph **306** comprising the one or more updated paths.

(56) At step **506**, it is detected whether the anomaly exists in the plurality of classified data objects. In an embodiment, the anomaly is detected by evaluating the plurality of classified data objects with the reference data corresponding to the plurality of classified data objects obtained from the multimodal knowledge graph **306** comprising the one or more updated paths. If it is determined that the anomaly exists, then at step **508**, the notification indicating the detected anomaly is generated.

(57) If it is determined that the anomaly fails to exist in the plurality of data objects, then at step **510**, the plurality of classified data objects are displayed on the screen of the electronic device **106**.

(58) FIG. 6 illustrates an example scenario of the reinforcement learning module **314** using the multimodal knowledge graph **306** according to an embodiment of the present invention.

(59) For example, consider the image data “X” comprising multiple objects such as object “A”, object “B” and object “C” and that the objects “A” & “B” exist in the image data “X” but are not connected in the multimodal knowledge graph **306** (or the walk length between them is high). Initially, say “A” and “C” were classified (path-1), and “B” was suppressed. This is because, the multimodal knowledge graph **306** estimates that these two objects “A” & “B” cannot occur together. In case of the conventional learning-based model, the object “B” will never be detected, as there is no way a system would know the classification is wrong. Unlike the conventional learning-based model, the feedback can be provided using the reinforcement learning module **314**, indicating to predict the one or more paths in the multimodal knowledge graph **306** using the association/classification (i.e., contextual based association) between objects “A” and “C”. Thus, a new path (path-2) is created in the multimodal knowledge graph **306** using the association/classification between objects “A” and “B”. The information regarding path-2 is provided to the object detection module **308**, which then recomputes the classifications and detects the objects (“A”, “B” and “C”) as shown in image data “Y”.

(60) Although the present invention has been disclosed in the form of preferred embodiments and variations thereon, it will be understood that numerous additional modifications and variations could be made thereto without departing from the scope of the invention.

(61) For the sake of clarity, it is to be understood that the use of “a” or “an” throughout this application does not exclude a plurality, and “comprising” does not exclude other steps or elements.

Claims

1. A method for detecting anomalies associated with a plurality of data objects of a technical installation, the method comprising: receiving a request to detect an anomaly associated with the plurality of data objects in an image data, wherein the image data comprises at least one of a static image data and a dynamic image data; classifying the plurality of data objects using a multimodal knowledge graph, wherein the multimodal knowledge graph comprises a plurality of pre-classified data objects, each pre-classified data object being connected to at least one further pre-classified data object of the multimodal knowledge graph using one or more paths according to relations between pre-classified data objects; detecting whether the anomaly exists in the plurality of classified data objects, wherein the anomaly is detected by evaluating the plurality of classified data objects with regard to reference data corresponding to the plurality of classified data objects obtained from the multimodal knowledge graph; generating a notification on a display screen of an electronic device in a text or graphical form indicating the anomaly based on the evaluating; determining that the anomaly in the plurality of classified data objects fails to exist; outputting the plurality of classified data objects on the display screen of the electronic device; receiving an update request to update the one or more paths of the multimodal knowledge graph; classifying the plurality of data objects using the multimodal knowledge graph comprising the updated path; detecting whether the anomaly exists in the plurality of classified data objects using the multimodal knowledge graph comprising the updated path, wherein the anomaly is detected by evaluating the plurality of classified data objects with the reference data corresponding to the plurality of classified data objects obtained from the multimodal knowledge graph comprising the updated path; and generating a notification on the display screen of the electronic device in a text or graphical form indicating the detected anomaly based on the evaluating the plurality of classified data objects with the reference data corresponding to the plurality of classified data objects obtained from the multimodal knowledge graph comprising the updated path.
2. The method of claim 1, wherein classifying the plurality of data objects using the multimodal knowledge graph comprises: receiving first data corresponding to seen data classes of each data object from the plurality of data objects; identifying second data corresponding to unseen data classes associated of each data object from the plurality of data objects using the first data; and classifying the plurality of data objects using the first data and the second data.
3. The method of claim 1, further comprising: outputting the plurality of classified data objects on the display screen of the electronic device.
4. The method of claim 1, wherein the one or more paths of the multimodal knowledge graph is updated by adding a sequence of nodes and edges, further wherein each node indicates a visual concept of the plurality of objects and each edge indicates a relationship between the visual concepts of the plurality of objects.
5. The method of claim 1, wherein the method further comprising: generating one or more recommendations to rectify the detected anomaly, wherein the one or more recommendations is generated by analysing similar detected anomaly in relation to the plurality of data objects obtained from the multimodal knowledge graph.
6. A system for detection of anomalies associated with a plurality of data objects of a technical installation, the system comprising one or more processing units, a memory operatively coupled to the one or more processing units, the memory comprising an anomaly detection module configured to perform at least one of the steps as claimed in claim 1.
7. A computer program product, comprising a computer readable hardware storage device having computer readable program code stored therein, said program code executable by a processor of a

computer system to implement a method according to claim 1.

8. A method for detecting anomalies associated with a plurality of data objects of a technical installation, the method comprising: receiving a request to detect an anomaly associated with the plurality of data objects obtained from an image data and a sensor data, wherein the image data comprises at least one of a static image data and a dynamic image data; classifying the plurality of data objects using a multimodal knowledge graph, wherein the multimodal knowledge graph comprises a plurality of pre-classified data objects, each of pre-classified data object being connected to at least one further pre-classified data object of the multimodal knowledge graph using one or more paths according to relations between pre-classified data objects; detecting whether the anomaly exists in the plurality of classified data objects, wherein the anomaly is detected by evaluating the plurality of classified data objects with reference data corresponding to the plurality of classified data objects obtained from the multimodal knowledge graph; generating a notification on a graphical user interface in a text or graphical form indicating the detected anomaly based on the evaluating; determining that the anomaly in the plurality of classified data objects fails to exist; outputting the plurality of classified data objects on a display screen of an electronic device; receiving an update request to update the one or more paths of the multimodal knowledge graph; classifying the plurality of data objects using the multimodal knowledge graph comprising the updated path; detecting whether the anomaly exists in the plurality of classified data objects using the multimodal knowledge graph comprising the updated path, wherein the anomaly is detected by evaluating the plurality of classified data objects with the reference data corresponding to the plurality of classified data objects obtained from the multimodal knowledge graph comprising the updated path; and generating a notification on the display screen of the electronic device in a text or graphical form indicating the detected anomaly based on the evaluating the plurality of classified data objects with the reference data corresponding to the plurality of classified data objects obtained from the multimodal knowledge graph comprising the updated path.

9. The method of claim 8, wherein the sensor data is obtained from a plurality of sensors and controller attached to the technical installation.
