

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12418124
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Masaki; Shingo

Electrical connector for flat-type conductors

Abstract

The locking members have an upper arm portion, a mountable portion, and a strut portion; the upper arm portion has a pressure-receiving arm portion and a locking arm portion; the mountable portion has an upper clamping portion and a lower clamping portion that extend in the forward-backward direction, and a coupling portion that couples the upper clamping portion and the lower clamping portion, with the upper clamping portion being resiliently displaceable in the up-down direction, and the mounting portion of the housing being clamped by the upper clamping portion and lower clamping portion in the up-down direction; the strut portion extends upwardly from the upper clamping portion and is coupled to the upper arm portion; the movable member has cam portions located above the pressure-receiving arm portions; and the cam portions depress the pressure-receiving arm portions downward when the movable member moves from the closed position to the open position.

Inventors:	Masaki; Shingo (Kanagawa, JP)
Applicant:	Hirose Electric Co., Ltd. (Kanagawa, JP)
Family ID:	1000008821309
Assignee:	HIROSE ELECTRIC CO., LTD. (Kanagawa, JP)
Appl. No.:	17/875292
Filed:	July 27, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230032779 A1	Feb. 02, 2023

Foreign Application Priority Data

JP	2021-125764	Jul. 30, 2021
----	-------------	---------------

Publication Classification

Int. Cl.: H01R12/88 (20110101); H01R12/79 (20110101)

U.S. Cl.:

CPC H01R12/88 (20130101); H01R12/79 (20130101)

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7137838	12/2005	Koga	439/492	H01R 12/79
7766680	12/2009	Suzuki	439/495	H01R 12/79

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
101345361	12/2010	CN	N/A
2002190360	12/2001	JP	N/A
2009021157	12/2008	JP	N/A
2009064577	12/2008	JP	N/A
2012212658	12/2011	JP	N/A
2013187056	12/2012	JP	N/A
1688170	12/2019	TW	N/A

Primary Examiner: Gushi; Ross N

Attorney, Agent or Firm: Procopio, Cory, Hargreaves & Savitch LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

Background

(1) This application claims priority to Japanese Patent Application No. 20021-1.25764, filed Jul. 30, 2021, the contents of which are incorporated herein by reference in its entirety for all purposes.

Technical Field

(2) The present invention relates to an electrical connector for flat-type conductors, to which a flat-type conductor is connected.

Background Art

(3) A connector, into which a strip-shaped flat-type conductor extending in the forward-backward direction and dimensionally thick in the up-down direction is inserted and connected toward the front, has been disclosed in Patent Document 1. Although the description of Patent Document 1 assumes the direction of insertion of the flat-type conductor (signal transmission medium) to be toward the rear and the direction of extraction to be toward the front, the description herein

assumes the direction of insertion of the flat-type conductor to be toward the front and the direction of extraction to be toward the rear. The connector of Patent Document 1 is mounted to a mounting face on a circuit board, and multiple terminals, which are arranged such that the terminal array direction is the strip width direction of the flat-type conductor, are retained in a housing. In addition, locking members used to prevent the decoupling of the flat-type conductor are positioned in the terminal array direction on opposite external sides of the terminal array range and are retained in the housing.

(4) The locking members have a movable beam portion that extends in the forward-backward direction along the top wall of the housing and can be resiliently displaced in the up-down direction, a fixed beam portion that extends in the forward-backward direction along the bottom wall of the housing and is mounted to said bottom wall, and a coupling strut portion that couples the intermediate portions of the movable beam portion and the fixed beam portion in the forward-backward direction. Engaging locking portions that can engage the flat-type conductor are provided in a downwardly protruding fashion in the rear end portions of the movable beam portions. The engaging locking portions enter cut-out portions (engagement position-setting portions) formed in both edges of the front end portion of the flat-type conductor from above and are positioned so as to permit engagement from the rear with engageable portions located in front of said cut-out portions, thereby preventing rearward decoupling of the flat-type conductor. The front end portions of the movable beam portions are provided with actuating unlocking portions used for disengaging the engaging locking portions. In addition, at a location directly above the actuating unlocking portions, the housing has an actuating locking cover portion that can be resiliently displaced in the up-down direction.

(5) According to Patent Document 1, when the flat-type conductor is inserted, the front end portion of the flat-type conductor abuts the engaging locking portions of the locking members and lifts said engaging locking portions up. At such time, as a result of rocking motion about the coupling strut portion or the vicinity thereof as a pivotal center, the movable beam portion is resiliently displaced and further insertion of the flat-type conductor is allowed. Furthermore, when the flat-type conductor is inserted to yield the front and the cut-out portions of the flat-type conductor reach the locations of the engaging locking portions, under the action of the resilient restoring force of the movable beam portions, the engaging locking portions enter the cut-out portions from above and are positioned so as to permit engagement with the engageable portions.

(6) In addition, when the flat-type conductor is extracted, as a result of performing an unlocking operation during which the actuating locking cover portion of the housing is downwardly depressed, said actuating locking cover portion depresses the actuating unlocking portions of the locking members, and the movable beam portions effect rocking motion in the same manner as during the above-described flat-type conductor insertion process. As a result, the engaging locking portions move upward and said engaging locking portions are disengaged from the engageable portions of the flat-type conductor, thereby allowing rearward extraction of the flat-type conductor.

RELATED ART DOCUMENTS

Patent Documents

(7) [Patent Documents 1]

(8) Japanese Published Patent Application No. 2012-212658

SUMMARY

Problems to be Solved

(9) It is an object of the present disclosure to ensure a long spring length for the locking members or terminals without increasing the size of the connector.

(10) If the insertion and extraction of the flat-type conductor is allowed by the resilient displacement of the movable beam portions of the locking members, as in Patent Document 1, ensuring that the movable beam portions and coupling strut portions have a long resiliently deformable length, that is, the spring length, makes it possible for the movable beam portions to be

resiliently displaced by a small force, thereby facilitating the operation of insertion and the operation of unlocking of the flat-type conductor. However, while said spring length can be increased if movable beam portions and coupling strut portions of greater length are, formed, this leads to an increase in the size of the locking members and, by extension, the connector, which is undesirable.

(11) In addition, in some electrical connectors for flat-type conductors, a shape including a movable beam portion, a fixed beam portion, and a coupling strut portion may be employed for the terminals, in a manner similar to the locking members of Patent Document 1 described above. In such a case, contact portions formed on the rear end side of the movable beam portions are brought into contact with the circuits of the flat-type conductor inserted into the connector under contact pressure from above. In addition, when the flat-type conductor is extracted, pressure-receiving portions formed on the front end side of the movable beam portions are depressed from above, as a result of which the movable beams effect a rearing motion and the contact portions move upward, such that contact between said contact portions and the circuits of the flat-type conductor is interrupted and rearward extraction of the flat-type conductor is allowed. While increasing the spring length is desirable even if the terminals are shaped in such a manner, attempts at increasing the spring length by forming movable beam portions and coupling strut portions of greater length bring about an increase in the size of the terminals and, by extension, the connector.

(12) In view of such circumstances, it is an object of the present invention to provide an electrical connector for flat-type conductors in which it is possible to ensure that the locking members or terminals have a long spring length without increasing the size of the connector.

Technical Solution

(13) In accordance with the present invention, the above-described problem is solved by the electrical connectors for flat-type conductors according to the following first invention and second invention.

(14) First Invention

(15) The electrical connector for flat-type conductors according to the first invention is an electrical connector for flat-type conductors to which a flat-type conductor extending in the forward-backward direction and dimensionally thick in the up-down direction is connected, wherein said connector comprises a housing that has formed therein a receiving space open toward the rear for forward insertion of the flat-type conductor, multiple terminals that are arranged and retained in the housing such that the terminal array direction is a direction perpendicular to both the forward-backward direction and the up-down direction, locking members that are disposed outside the array range of the terminals in the terminal array direction and retained in the housing, and a movable member that is provided forwardly of the receiving space and is capable of moving between a closed position and an open position while pivoting about a pivoting axis extending in the terminal array direction, extraction of the flat-type conductor is prevented when the movable member is in the closed position, and extraction of the flat-type conductor is permitted when the movable member is in the open position.

(16) In such an electrical connector for flat-type conductors, in the first invention, the locking members have an upper arm portion that extends in the forward-backward direction upwardly of the receiving space, a mountable portion that is mounted to the housing at a location downward of the upper arm portion and forward of the receiving space, a strut portion that extends upwardly from the mountable portion and is coupled to the upper arm portion; the upper arm portion has a pressure-receiving arm portion that extends forwardly from the top end of the strut portion, and a locking arm portion that extends rearwardly from the top end of the strut portion; the locking arm portion has an engaging portion positioned so as to permit engagement from the rear with an engageable portion in the flat-type conductor when the movable member is in the closed position; the mountable portion has an upper clamping portion and a lower clamping portion that are spaced apart from each other in the up-down direction and extend in the forward-backward direction, and a

coupling portion that couples the front end portions of the upper clamping portion and lower clamping portion; the upper clamping portion is resiliently displaceable in the up-down direction and the mounting portion formed as part of the housing, is clamped by the upper clamping portion and lower clamping portion in the up-down direction; the strut portion extends upward from the upper clamping portion; the movable member has a cam portion located above the pressure-receiving arm portion; and, the cam portion depresses the pressure-receiving arm portion downward when the movable member moves from the closed position to the open position.

(17) In the first invention, the locking arm portion, strut portion, and upper clamping portion of the locking member are resiliently displaceable, and the spring length is the length of the range comprising these sections. During insertion of the flat-type conductor, when the front end portion of the flat-type conductor abuts the engaging portions of the locking members and lifts said engaging portions up, the locking arm portions, strut portions, and upper clamping portions are resiliently displaced upward, with the coupling portions serving as a fulcrum, and, as a result, further insertion of the flat-type conductor is allowed. In addition, during extraction of the flat-type conductor, as the movable member moves to the open position, the cam portion of the movable member depresses the pressure-receiving portions, and, as a result, in the same manner as during insertion of the flat-type conductor, the locking arm portions, strut portions, and upper clamping portions are resiliently displaced upward. As a result, the engaging portions of the locking arm portions are disengaged from the flat-type conductor, thereby allowing extraction of the flat-type conductor.

(18) In the first invention, resilient displacement is made possible not only in the locking arm portion and the strut portion, but also in the upper clamping portion of the mountable portion, which ensures a correspondingly longer spring length. Further, since the upper clamping portion, which forms part of the mountable portion used for mounting the locking members to the housing, is employed as a resiliently displaceable section, there is no need to provide new sections in the locking members, or make the locking arm portions or strut portions longer in order to increase the spring length, and there is no increase in connector size.

(19) In the first invention, the electrical connector for flat-type conductors is mountable to a mounting face of a circuit board using solder connections, and the locking members may have an anchor portion that extends toward the front from the mountable portion and is anchored to the mounting face of the circuit board using solder connections.

(20) In the first invention, in the process of insertion and extraction of the flat-type conductor, the upper clamping portion of the locking member, which forms part of the mountable portion, is resiliently displaced upward along with the locking arm portion and the strut portion. If, at such time, the lower clamping portion is displaced upward along with the upper clamping portion, the clamping force with which the mounting portion of the housing is clamped by the upper clamping portion and lower clamping portion, in other words, the strength of attachment of the mountable portion to the housing, is unlikely to decrease. However, should the upper clamping portion and lower clamping portion become spaced apart if, for instance, the lower clamping portion is not displaced upward and only the upper clamping portion is displaced upward, then the above-mentioned clamping force, that is, the strength of attachment of the mountable portion, may be slightly decreased.

(21) However, if in the first invention the electrical connector for flat-type conductors is mountable to a mounting face on a circuit board, the operations of insertion and extraction of the flat-type conductor are performed after mounting to the mounting face of the circuit board, that is, after securing the anchor portions of the locking members to the mounting face of the circuit board using solder connections. Therefore, even if the upper clamping portion and lower clamping portion of the mountable portion become spaced apart and the above-mentioned clamping force, that is, the strength of attachment to the housing, is slightly decreased, the locking members will not become decoupled from the housing because the position of the locking members relative to the circuit

board will have already been fixed at that point in time.

(22) <Second Invention>

(23) The electrical connector for flat-type conductors according to the second invention is an electrical connector for flat-type conductors to which a flat-type conductor extending in the forward-backward direction and dimensionally thick in the up-down direction is connected, wherein said connector comprises a housing that has formed therein a receiving space open toward the rear for forward insertion of a flat-type conductor, multiple terminals that are arranged and retained in the housing such that the terminal array direction is a direction perpendicular to both the forward-backward direction and the up-down direction, and a movable member that is provided forwardly of the receiving space and is capable of moving between a closed position and an open position while pivoting about a pivoting axis extending in the terminal array direction.

(24) In such an electrical connector for flat-type conductors, in the second invention, the terminals have an upper arm portion that extends in the forward-backward direction upwardly of the receiving space, a mountable portion that is mounted to the housing at a location downward of the upper arm portion and forward of the receiving space, and a strut portion that extends upwardly from the mountable portion and is coupled to the upper arm portion; the upper arm portion has a pressure-receiving arm portion that extends forwardly from the top end of the strut portion, and a contact arm portion that extends rearwardly from the top end of the strut portion; the contact arm portion has a contact portion that comes into contact with the circuits of the flat-type conductor from above when the movable member is in the closed position; the mountable portion has an upper clamping portion and a lower clamping portion that are spaced apart from each other in the up-down direction and extend in the forward-backward direction, and a coupling portion that couples the front end portions of the upper clamping portion and lower clamping portion; the upper clamping portion is resiliently displaceable in the up-down direction, and the mounting portion, formed as part of the housing, is clamped by the upper clamping portion and lower clamping portion in the up-down direction, the strut portion extends upward from the upper clamping portion; the movable member has a cam portion located above the pressure-receiving arm portion; and the cam portion depresses the pressure-receiving arm portions downward when the movable member moves from the closed position to the open position.

(25) In the second invention, the contact arm portion, strut portion, and upper clamping portion of the terminals are resiliently displaceable, and the spring length is the length of the range comprising these sections. During insertion of the t-type conductor, when the front end portion of the flat-type conductor abuts the contact portions of the contact arm portions and lifts said contact portions up, the contact arm portions, strut portions, and upper clamping portions are resiliently displaced upward, with the coupling portions serving as a fulcrum, and, as a result, further insertion of the flat-type conductor is allowed. In addition, during extraction of the flat-type conductor, as the movable member moves to the open position, the cam portion of the movable member depresses the pressure-receiving portions, as a result of which, in the same manner as during insertion of the flat-type conductor, the contact arm portion, strut portion, and upper clamping portion are resiliently displaced upward. As a result, contact between the contact portions of the contact arm portions and the circuits of the flat-type conductor is interrupted.

(26) In the second invention, resilient displacement is made possible not only in the contact arm portion and the strut portion, but also in the upper clamping portion of the mountable portion, which ensures a correspondingly longer spring length. Further, since the upper clamping portion, which forms part of the mountable portion used for mounting the terminal to the housing, is employed as a resiliently displaceable section, there is no need to provide new sections in the terminals, or make the contact arm portions or strut portions longer in order to increase the spring length, and there is no increase in connector size.

(27) In the second invention, the electrical connector for flat-type conductors is mountable to a mounting face on a circuit board using solder connections, and the terminals may have an anchor

portion that extends toward the front from the mountable portion and is anchored to the mounting face of the circuit board using solder connections.

(28) In the second invention, in the process of insertion and extraction of the flat-type conductor, the upper clamping portion of the terminals, which forms part of the mountable portion, is resiliently displaced upward along with the contact arm portion and the strut portion. If, at such time, the lower clamping portion is displaced upward along with the upper clamping portion, the clamping force with which the mounting portion of the housing is clamped by the upper clamping portion and lower clamping portion, in other words, the strength of attachment of the mountable portion to the housing, is unlikely to decrease. However, should the upper clamping portion and lower clamping portion become spaced apart if, for instance, the lower clamping portion is not displaced upward and only the upper clamping portion is displaced upward, then the above-mentioned clamping force, that is, the strength of attachment of the mountable portion, may be slightly decreased.

(29) However, if in the second invention the electrical connector for flat-type conductors is mountable to a mounting face on a circuit board, the operations of insertion and extraction of the flat-type conductor are performed after mounting to the mounting face of the circuit board, that is, after securing the anchor portions of the terminals to the mounting face of the circuit board using solder connections. Therefore, even if the upper clamping portion and lower clamping portion of the mountable portion become spaced apart and the above-mentioned clamping force, that is, the strength of attachment to the housing is slightly decreased, the terminals will not become decoupled from the housing because the position of the terminals relative to the circuit board will have already been fixed at that point in time.

Technical Effect

(30) In the present invention, as described above, in the locking members or terminals, resilient displacement is made possible not only in the arm portions (locking arm portion or contact arm portion) and the strut portion, but also in the upper clamping portion of the mountable portion, which ensures a correspondingly longer spring length. As a result, the operations of insertion and extraction of the flat-type conductor can be accomplished with ease. Further, since in the present invention the upper clamping portion, which forms part of the mountable portion used for mounting the locking members or terminals to the housing, is employed as a resiliently displaceable section, there is no need to provide new sections in the locking members or terminals, or make the arm portions or strut portions longer in order to increase the spring length, and there is **110** increase in connector size.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) FIG. 1 illustrates a perspective view illustrating an electrical connector for flat-type conductors according to an embodiment of the present invention, shown along with a flat-type conductor.

(2) FIG. 2 illustrates a perspective view illustrating the electrical connector for flat-type conductors, with one first terminal, one second terminal, a locking member, and a movable member shown in an exploded condition.

(3) FIGS. 3(A) to 3(C) illustrate a longitudinal cross-sectional view of the electrical connector for flat-type conductors, wherein 3(A) illustrates a cross-section at the location of a first terminal, FIG. 3(B) a cross-section at the location of a second terminal, and FIG. 3(C) a cross-section at the location of a locking member.

(4) FIGS. 4(A) to 4(C) illustrate a longitudinal cross-sectional view of the electrical connector for flat-type conductors upon completion of insertion of the flat-type conductor, wherein FIG. 4(A) illustrates a cross-section at the location of a first terminal, FIG. 4(B) a cross-section at the location

of a second terminal, and FIG. 4(C) a cross-section at the location of a locking member, (5) FIGS. 5(A) to 5(C) illustrate a longitudinal cross-sectional view of the electrical connector for flat-type conductors immediately prior to removal of the flat-type conductor, wherein FIG. 5 (A) illustrates a cross-section at the location of a first terminal, FIG. 5(B) a cross-section at the location of a second terminal, and FIG. 5(C) a cross-section at the location of a locking member.

DETAILED DESCRIPTION

(6) Embodiments of the present invention will be discussed hereinbelow with reference to the accompanying drawings.

(7) FIG. 1 is a perspective view of the electrical connector for flat-type conductors **1** (hereinafter referred to as “connector **1**”) according to the present embodiment. FIG. 2 is a perspective view illustrating the connector **1**, with one first terminal **20**, one second terminal **30**, a locking member **40**, and a movable member **50** shown in an exploded condition FIG. 3(A) to 3 (C) show longitudinal cross-sectional views of the connector **1** wherein FIG. 3(A) illustrates cross-section at the location of a first terminal **20**, FIG. 3(B) a cross-section at the location of a second terminal **30**, FIG. 3(C) a cross-section at the location of a locking member **40**.

(8) The connector **1** is mounted to a mounting face on a circuit board (not shown), and a flat-type conductor C (e.g, FPC) serving as a counterpart connect body, is adapted to be connected thereto so as to permit insertion and extraction such that the direction of insertion and extraction is a forward-backward direction (X-axis direction) parallel to said mounting face. The connector **1** puts the circuit board and the flat-type conductor C in electrical communication when the flat-type conductor C is connected. In the present embodiment, the X-axis direction (forward-backward direction), direction X1 is toward the front and direction X2 is toward the rear. In addition, the connector width direction is the Y-axis direction, which is perpendicular to the forward-backward direction (X-axis direction) in a plane (XY plane) parallel to the mounting face of the circuit board, and the connector thickness direction is the Z-axis direction (up-down direction), which is perpendicular to the mounting face of the circuit board.

(9) The flat-type conductor C, which extends in the forward-backward direction (X-axis direction) in the form of a flexible strip whose width direction is the connector width direction (Y-axis direction), has multiple circuits extending in the forward-backward direction formed in an array in the connector width direction. Said circuits are embedded within an insulating layer in the flat-type conductor C and extend in the forward-backward direction all the way to the front end of the flat-type conductor C. In addition, the above-mentioned circuits include connecting circuits C1 whose top face of the flat-type conductor C in its front end section is exposed, and can be brought into contact with first terminals **20** and second terminals **30** in the connector **1**, to be described below. The connecting circuits C1 include first circuits C1A, which are in contact with the first terminals **20**, and second circuits C1B, which are in contact with the second terminals **30**, with the two types of circuits positioned alternately in the connector width direction while being offset in the forward-backward direction.

(10) Further, the flat-type conductor C has cut-out portions C2 formed in the opposite side edges of the above-mentioned front end section, and the rear end edges of ears C3, which are located forwardly of said cut-out portions C2, operate as engageable portions C3A engaging the engaging portions **43A**, to be described below, of the connector **1** (see FIG. 4(C)).

(11) The connector **1** comprises a housing **10** made of plastic or another electrically insulating material, multiple first terminals **20** and second terminals **30** of sheet metal arranged such that the terminal array direction is the connector width direction and retained in the housing **10**, locking members **40** of sheet metal arranged on opposite external sides of the terminal array range in the connector width direction, and a movable member **50** made of plastic or another electrically insulating material that can pivot between a closed position and an open position, to be described below, and the flat-type conductor C is adapted to be inserted and connected thereto from the rear.

(12) The housing **10**, as shown in FIGS. 1, 2, has a substantially rectangular parallelepiped-like

exterior configuration whose longitudinal direction is the connector width direction, and a receiving space **11** used to receive the flat-type conductor C is formed therein as a rearwardly open space. As shown in FIG. 2, the housing **10** has a top wall **12** and a bottom wall **13** that extend parallel to the mounting face of the circuit board, two side walls **14** that extend in the up-down direction and couple the opposite end portions of the top wall **12** and the bottom wall **13** in the connector width direction, and a front wall **15** that couples the front ends of the top wall **12** and the bottom wall **13** (see FIGS. 3(A) to 3(C)). A movable member accommodating space **16** for accommodating the movable member **50** is formed forwardly of the front wall **15** between the two side walls **14** in the connector width direction.

(13) The receiving space **11**, which has a rear end opening **11A** that is enclosed by the top wall **12**, the bottom wall **13**, and the two side walls **14** and forms an insertion aperture for the flat-type conductor C (see FIGS. 3(A) to 3(C)) in the rear end face of the housing **10**, is adapted to receive the front end section of the flat-type conductor C within a space extending from the rear end opening **11A** to the rear face of the front wall **15** in the forward-backward direction (see FIGS. 4(A) to 4(C)).

(14) Along with being in a face-to-face relationship with the mounting face of the circuit board at a location below the top wall **12**, the bottom wall **13** has its rear end within the terminal array range in the connector width direction (Y-axis direction) positioned slightly forwardly of the rear end of the top wall **12** (see FIG. 1 and FIG. 2). In addition, within the terminal array range in the connector width direction, the bottom wall **13** has its front end portion projecting into the movable member accommodating space **16** (see FIGS. 3(A) and 3(B)). On the other hand, at locations corresponding to the locking members **40** outside the terminal array range in the connector width direction, the front end portion of the bottom wall **13** is positioned rearwardly of the front face of the front wall **15** (see FIG. 3(C)). In addition, at a location corresponding to the locking member **40**, the front end portion of the bottom wall **13** has its bottom face recessed, thereby making it thinner than other portions, and is formed as a mounting portion **13A** used for mounting the locking member **40** (see FIG. 3(C)).

(15) In addition, as shown in FIGS. 3(A) and 3(B), a first terminal accommodating portion **17** for accommodating and retaining the first terminals **20** and a second terminal accommodating portion **18** for accommodating and retaining the second terminals **30** are formed in the housing **10**. The first terminal accommodating portion **17** and second terminal accommodating portion **18** are arranged alternately at predetermined intervals in the connector width direction. In addition, as shown in FIG. 3(C), locking member accommodating portions **19** for accommodating and retaining the locking members **40** are formed in the housing **10** at the opposite ends of the receiving space **11** in the connector width direction, in other words, on opposite external sides of the terminal array range.

(16) As seen in FIG. 3(A), the first terminal accommodating portion **17** has a front groove portion **17A** serving as a front space that has a slit-shaped configuration extending at right angles to the connector width direction and is used for accommodating and retaining by press-fitting the front end section of the first contact arm portion **24** and the base portion **21**, to be described below, of the first terminals **20**, and an upper groove portion **17B** that accommodates the rear end section of the first contact arm portion **24**, to be described below, of the first terminals **20**. The front groove portion **17A** is formed to extend in the forward-backward direction within a range extending from the top wall **12** to the bottom wall **13** in the up-down direction. Recessed from the bottom face of the top wall **12**, the upper groove portion **17B** extends from the front groove portion **17A** toward the rear. In addition, as seen in FIG. 3(A), while being open toward the rear and downward, the upper groove portion **17B** passes through the top wall **12** in the up-down direction at a location corresponding to the rear end portion of the first contact arm portion **24** in the forward-backward direction.

(17) As seen in FIG. 3(B), the second terminal accommodating portion **18** has a front groove

portion **18A** that has a slit-shaped configuration extending at right angles to the connector width direction and is used for accommodating and retaining by press-fitting the front end section of the lower arm portion **34**, the front end section of the upper arm portion **31**, and the strut portion **37**, to be described below, of the second terminals **30**, an upper groove portion **18B** accommodating the rear end section of the upper arm portion **31**, to be described below, of the second terminals **30**, and a lower groove portion **18C** accommodating the rear end section of the lower arm portion **34**, to be described below, of the second terminals **30**.

(18) The front groove portion **18A** is formed to pass in the forward-backward direction within a range extending from the top wall **12** to the bottom wall **13** in the up-down direction. As seen in FIG. 3(B), within the front groove portion **18A**, a second terminal retaining portion **18A-1** used for retaining the second terminal **30** by press-listing is formed so as to couple the opposed interior groove surfaces (two surfaces facing each other in the connector width direction) of the front groove portion **18A** at a vertically intermediate position in the front half of the front groove **18A**. A press-fitting groove **18A-2** used for retaining the retained arm portion **35** by press-fitting is formed in the forward-backward director between the second terminal retaining portion **18A-1** and the bottom wall **13**. Recessed from the bottom face of the top wall **12**, the upper groove portion **18B** extends from the front groove portion **18A** toward the rear. In addition, as seen in FIG. 3(B), while being open toward the rear and downward, the upper groove portion **18B** extends through the top wall **12** in the up-down direction at a location corresponding to the rear end portion of the upper arm portion **31** in the forward-backward direction. As seen in FIG. 3(B), at a location proximate to the rear end, the lower groove portion **18C** extends through the bottom wall **13** in the up-down direction at a location corresponding to the hereinafter-described reinforcing portion **36B** of the lower arm portion **34**.

(19) As shown in FIG. 3(C), the locking member accommodating portion **19** has a front groove portion **19A** that has a slit-shaped configuration extending at right angles to the connector width direction and is used to accommodate by press-fitting the mountable portion **44**, the front end section of the upper arm portion **41**, and the strut portion **45**, to be described below, of the locking member **40**, and an upper groove portion **19B** that accommodates the rear end section of the upper arm portion **41** of the locking member **40**. The front groove portion **19A** is formed so as to extend in the forward-backward direction throughout the full extent of the housing **10** in the up-down direction. As show in FIG. 3(C), a mounting portion. **13A**, which constitutes the front end portion of the bottom wall **13**, enters from the rear and extends at the bottom of the front groove **19A**. The mounting portion **13A** is formed so as to couple the opposed interior groove surfaces (surfaces facing each other in the connector width direction) of the front groove portion **19A**. As shown in FIG. 3(C), the upper groove portion **19B**, which extends in the forward-backward direction to a location proximate to the rear end of the top wall **12**, extends through the top wall **12** in the up-down direction throughout the full extent in the forward-backward direction.

(20) The first terminals **20**, which are fabricated by punching from metal plate members while keeping their major faces (rolled surface) flat, are accommodated within the first terminal accommodating portions **17** of the housing **10**, as illustrated in FIG. 3(A), as a result of which the major faces of all the first terminals **20** are arranged and retained in the housing **10** at right angles to the connector width direction (Y-axis direction).

(21) The first terminals **20** are press-fitting mounted to the housing **10** from the front. As illustrated in FIG. 3(A), the first terminals **20** have a base portion **21** that is press-fittingly retained in the front groove portion **17A** of the housing **10**, a first contact arm portion **24** that extends toward the rear from the rear edge of the base portion **21** through the front groove portion **17A** and the upper groove portion **17B**, and a projecting arm portion **25** that extends toward front from the front edge of the bottom portion of the base portion **21** and projects into the movable member accommodating space **16**.

(22) The first contact arm portion **24**, which extends slopingly downward as one moves rearward,

is resiliently displaceable in the up-down direction. A first contact portion **24A**, which can be brought into contact with the first circuit **C1A** on the flat-type conductor **C** from above, is provided in a downwardly protruding configuration in the rear end portion of the first contact arm portion **24**. The first contact portion **24A**, which is located within the receiving space **11**, faces the interior surface of the receiving space **11**, in other words, the top face of the bottom wall **13** across a gap $\delta 1$ in the up-down direction (Z-axis direction), which is the connector thickness direction. The rear end face of the first contact portion **24A**, which slopes downward as one moves forward, forms a first guide face **24A-1** used for forwardly guiding the flat-type conductor **C**. The bottom portion of the first guide face **24A-1** constitutes the rear end face of the first contact portion **24A**.

(23) At the top and bottom edges of the base portion **21**, the base portion **21**, which has two press-fit protrusions **21A** formed at the bottom edge, is press-fittingly retained by the upper interior wall surface and lower interior wall surface of the front groove portion **17A**. The base portion **21** has a retained portion **22** that is formed and retained with dimensions encompassing the full extent of the front groove portion **17A** in the up-down direction, and an extension portion **23** that extends toward the rear along the first contact arm portion **24** from the rear edge of the bottom portion of the retained portion **22**.

(24) The extension portion **23**, which is made shorter than the first contact arm portion **24** in the forward-backward direction, is accommodated within the front groove portion **17A** in its entirety and has a reflective portion **23A** in its rear end portion. In the present embodiment, light emitted forwardly in the receiving space **11** during post-production inspection of the connector can be reflected back by the reflective portions **23A**. The reflective portions **23A** are formed as reflecting surfaces **23A-1**, whose rear end faces (through-thickness faces) are flat surfaces perpendicular to the forward-backward direction.

(25) In the present embodiment, the reflecting surface **23A-1** is formed having the same dimensions as the gap **61** in the connector width direction while having dimensions exceeding the gap **61** in the up-down direction. Specifically, in the up-down direction, the reflecting surface **23A-1** is positioned so as to include the protruding end (bottom end) of the first contact portion **24A** because the top end of the said reflecting surface **23A-1** is located above said protruding end, and is also positioned so as to include the location of the top face of the bottom wall **13** (interior surface of the receiving space **11**) because the bottom end of the said reflecting surface **23A-1** is located below the top face of said bottom wall **13**. In other words, when viewed from the rear, the reflecting surface **23A-1** is positioned within a range that includes the entire gap $\delta 1$.

(26) Substantially the rear half of the projecting arm portion **25** forms a supported arm portion **25A** that extends along the bottom wall **13** and is supported from below by the bottom wall **13**.

Substantially the front half of the projecting arm portion **25** extends forwardly and downwardly of the front end of the bottom wall **13** and forms a first connecting portion **25B** that serves as an anchor portion solder-connected to the circuits (not show the mounting face of the circuit board with its bottom edge portion. In addition, a protruding portion **25C**, which protrudes from the top edge of the projecting arm portion **25**, is formed at an intermediate location of the projecting arm portion **25** in the forward-backward direction. In the present embodiment, sections made up of the front edge portion of the retained portion **22**, the supported arm portion **25A**, and the protruding portion **25C** are positioned so as to enclose the hereinafter-described first shaft body portions **54** of the movable member **50** from the rear, from below, and from the front, thereby forming first restricting portions **20A** that restrict the rearward, downward, and forward movement of the first shaft body portions **54**.

(27) The second terminals **30**, which are fabricated by punching from metal plate members while keeping their major faces (rolled surface) flat, are accommodated within the second terminal accommodating portions **18** of the housing **10**, as illustrated in FIG. 3(B), as a result of which the major faces of all the second terminals **30** are arranged and retained in the housing **10** at right angles to the connector width direction (Y-axis direction).

(28) The second terminals **30** are press-fittingly mounted to the housing **10** from the rear. As illustrated in FIG. 3(B), the second terminals **30** have an upper arm portion **31** that extends in the forward-backward direction along the top wall **12**, a lower arm portion **34** that is positioned downwardly of the upper arm portion **31** and extends in the forward-backward direction along the bottom wall **13**, and a strut portion **37** that extends in the up-down direction and couples the intermediate portions of the upper arm portion **31** and the lower arm portion **34** in the forward-backward direction.

(29) The upper arm portion **31** has a restricting arm portion **32** that extends toward the front from the top end of the strut portion **37**, and a second contact arm portion **33** that extends toward the rear from the top end of the strut portion **37**. The restricting arm portions **32**, which have their front end portions projecting into the movable member accommodating space **16**, form second shaft restricting portions **32A** located above the hereinafter-described second shaft body portions **55** of the movable member **50**. The second shaft restricting portions **32A**, which are positioned at a slight gap from the second shaft body portions **55** in the up-down direction, restrict the upward movement of the second shaft body portions **55**. In the present embodiment, the previously discussed first shaft restricting portions **20A** of the first terminals **20** restrict the movement of the first shaft body portions **54** and the second shaft restricting portions of the second terminals **30** restrict the movement of the second shaft body portions **55**, thereby restricting the movement of the first shaft body portions **54**, the second shaft body portions **55** (which are referred to collectively hereinbelow as “shaft body portions **54, 55**” whenever necessary), and, by extension, the movable member **50** in a plane perpendicular to the connector width direction, which, as a result, makes it possible to prevent the detachment of the movable member **50**.

(30) The second contact arm portion **33**, as illustrated in FIG. 3(B), extends slopingly downward as one moves rearward through the upper groove portion **18B**, and is resiliently displaceable in the up-down direction. A second contact portion **33A**, which can be brought into contact with the second circuit **C1A** of the flat-type conductor **C** from above, is provided in a downwardly protruding configuration in the rear end portion of the second contact arm portion **33**. The second contact portion **33A** is positioned rearwardly of the first contact portion **24A** of the first contact arm portion **24** of the first ten **20**. The rear end face of the second terminals **30**, which slopes downward as one moves forward, is formed as a second guide face **33A-1** used for forwardly guiding the flat-type conductor **C**. The bottom portion of the second guide face **33A-1** constitutes the rear end face of the second contact portion **33A**.

(31) The lower arm portion **34** has a retained arm portion **35** that extends toward the front from the bottom end of the strut portion **37**, and a projecting arm portion **36** that extends toward the rear from the bottom end of the strut portion **37**. As illustrated in FIG. 3(B), the retained arm portion **35**, which is made shorter than the restricting arm portion **32** of the upper arm portion **31**, is press-fitted from the rear into the press-fit groove portion **18A-2** of the second terminal accommodating portion **18** of the housing **10**. An upwardly protruding press-fit protrusion **35A** is formed in the front end portion of the retained arm portion **35**, and the second terminals **30** are retained within the second terminal accommodating portions **18** due to the fact that said press-fit protrusions **35A** bite into the bottom face of the second terminal retaining portions **18A-1**.

(32) Substantially the front half of the projecting arm portion **36** forms a rectilinear portion **36A** that extends in a rectilinear manner in the forward-backward direction along the top face of the bottom wall **13**. Substantially the rear half of the projecting arm portion **36** has a reinforcing portion **36B** that is located rearwardly of the rear end of the bottom wall **13** and extends toward the rear and downward from the rectilinear portion **36A**, and a second connecting portion **36C** that extends rearwardly from the reinforcing portion **36B**. The second connecting portion **36C** is solder-connected to the circuits (not shown) on the mounting face of the circuit board with its bottom edge portion.

(33) As illustrated in FIG. 3(B), a recess portion **36B-1** is formed in the top edge of the reinforcing

portion **36B**, within a range that includes the second contact portion **33A** of the second contact arise portion **33** in the forward-backward direction. In the present embodiment, the gap between the second contact portion **33A** and the reinforcing portion **36B** in the up-down direction is increased by forming the recess portion **36B-1** in the reinforcing portion **36B**, and, for this reason, in a punching die (not shown) used to form the second terminals **30** by punching from metal plate members, the section of the die used to form the above-mentioned gap can be made sufficiently large and adequate strength can be ensured in said section of the die.

(34) The reinforcing portion **36B** is made larger than the rectilinear portion **36A** in the up-down direction, thereby avoiding a decrease in the strength of the reinforcing portion **36B** itself due to the presence of the recess portion **36B-1**. In addition, a front protrusion **36B-2** and a rear protrusion **36B-3**, which protrude upwardly toward the receiving space **11** at the respective locations of the front and rear ends of the recess portion **36B-1**, are formed at the top edge of the reinforcing portion **36B**. The front protrusion **36B-2** is located forwardly of the second contact portion **33A**, and the rear protrusion **36B-3** is located rearwardly of the second contact portion **33A**. Therefore, once the flat-type conductor **C** has been inserted into the receiving space **11** and the second contact portion **33A** has been brought into contact with the flat-type conductor **C** under contact pressure from above, the front protrusion **36B-2** and the rear protrusion **36B-3** support the flat-type conductor **C** from below. As a result, once pressure has been applied in the up-down direction at three points, i.e., the second contact portion **33A**, the front protrusion **36B-2**, and the rear protrusion **36B-3**, the flat-type conductor **C** becomes securely clamped in the up-down direction, and inadvertent decoupling of the flat-type conductor **C** is prevented.

(35) The bottom edge of the reinforcing portion **36B**, which is positioned slightly above the bottom edge of the second connecting portion **36C**, is adapted to avoid abutment against the mounting face of the circuit board when the connector **1** is disposed on said mounting face. Therefore, the second connecting portion **36C** can be reliably connected to the circuits of the circuit board because a state in which the bottom edge of the reinforcing portion **36B** would be located below the bottom edge of the second connecting portion **36C** is unlikely to occur even if the bottom edge of the reinforcing portion **36B** is located slightly downwardly of the normal design position because of fabrication errors.

(36) The locking members **40**, which are fabricated by punching from metal plate members while keeping their major faces (rolled surface) flat, are accommodated within the locking member accommodating portions **19** of the housing **10**, as illustrated in FIG. 3(C), as a result of which the locking members **40** are retained in the housing **10** with their major faces at right angles to the connector width direction (Y-axis direction).

(37) The locking members **40** are press-fittingly mounted to the housing **10** from the front. As illustrated in FIG. 3(C), the locking members **40** have an upper arm portion **41** that extends in the forward-backward direction along the top wall **12** upwardly of the receiving space **11**, a mountable portion **44** that is mounted to the housing **10** downwardly of the upper arm portion **41**, a strut portion **45** that extends upwardly from the mountable portion **44** and is coupled to the upper arm portion **41**, and a projecting arm portion **46** that extends toward the front from the mountable portion **44**.

(38) The upper arm portion **41** has a pressure-receiving arm portion **42** that extends toward the front from the top end of the strut portion **45** and a kicking arm portion **43** that extends toward the rear from the top end of the strut portion **45**. As illustrated in FIG. 3(C), the pressure receiving arm portion **42** has a curved shape extending in a crank-like configuration when viewed in the connector width direction, with its front end portion positioned downwardly of other parts to form pressure-receiving portion **42A**. The pressure-receiving portions **42A**, which are positioned with their top edges in contact with the pressure-applying portions **56A** of the hereinafter-described cam portions **56** provided in the movable member **50**, are adapted to be downwardly displaced under pressure applied from above by said pressure-applying portions **56A** when the movable member **50**

is brought to the open position (see FIG. 5(C)). In addition, in the present embodiment, the pressure-receiving portions **42A** are located within the hounds of the shaft body portions **54** and **55** of the movable member **50** in the forward-backward and up-down directions.

(39) The locking arm portion **43**, which extends slopingly downward as one moves rearward through the upper groove portion **19B**, is resiliently displaceable in the up-down direction. An engaging portion **43A** is provided in a downwardly protruding configuration in the rear end portions of the locking arm portions **43**. The engaging portions **43A** are positioned so as to permit entry into the notched portions **C2** of the flat-type conductor **C** from above and engagement with engageable portions **C3A** from the rear when the movable member **50** is in the closed position (see FIG. 4(C)). The rear end face of the engaging portions **43A**, which slopes downward as one moves forward, is formed as an inclined face **43A-1** used for forwardly guiding the flat-type conductor **C**.

(40) The mountable portion **44**, which has a rearwardly open recumbent U-shaped configuration, is accommodated within the front groove portion **19A** located forwardly of the receiving space **11**. The mountable portion **44** has an upper clamping portion **44A** and a lower clamping portion **44B**, which are spaced apart from each other in the up-down direction and extend in the forward-backward direction, and a coupling portion **44C** that couples the (front end portions of the upper clamping portion **44A** and the lower clamping portion **44B**. The upper clamping portion **44A** is resiliently displaceable in the up-down direction and, as illustrated in FIG. 3(C), the upper clamping portion **44A** and lower clamping portion **44B** clamp the mounting portion **13A** of the housing **10** in the up-down direction.

(41) The strut portion **45** extends upward from the upper clamping portion **44A** at a location proximal of the rear end of the upper clamping portion **44A**, and is coupled to the upper arm portion **41**. The projecting arm portion **46**, which is positioned at the same height in the up-down direction as the lower clamping portion **44B**, extends forwardly from the front end of said lower clamping portion **44B** and projects into the movable member accommodating space **16**. The front end portion of the projecting arm portion **46**, which is formed as an anchor portion **46A** used for anchoring to the mounting face of the circuit board, is adapted to be anchored to the mounting face with the bottom edge portion of said anchor portion **46A** using solder connections.

(42) As illustrated in FIG. 1, the movable member **50** extends across the full width of the movable member accommodating space **16** in the connector width direction, with the entire movable member **50** accommodated within the movable member accommodating space **16** in the closed position. In FIG. 2, the movable member **50**, which is in a closed-position orientation, is shown separated from the housing **10**. As illustrated in FIG. 2, the movable member **50** has an actuating portion **51**, end walls **52**, partition walls **53**, first shaft body portions **54**, second shaft body portions **55**, and cam portions **56**.

(43) As shown in FIG. 2, the actuating portion **51**, which is formed on the front end side of the movable member **50** while extending, in the connector width direction, is adapted to receive actuating input for moving (pivoting) the movable member **50** between the closed position and the open position. The end walls **52** are provided in a rearwardly extending configuration from the opposite ends of the actuating portion **51** in the connector width direction. Multiple partition walls **53**, which extend from the actuating portion **51** toward the rear between the two end walls **52** in the connector width direction, are formed in a side-by-side arrangement at spaced intervals in the connector width direction.

(44) As shown in FIG. 2, the first shaft body portions **54**, which are provided in the same positions as the first terminals **20** in the connector width direction, couple the opposed faces (faces perpendicular to the connector width direction) of the rear end portions (end portions on the X2 side) of two mutually adjacent partition walls **53**. As shown in FIG. 3(A), the cross-sectional shape of the first shaft body portions **54** perpendicular to the connector width direction is a substantially square shape with rounded corners. In addition, as shown in FIG. 3(A), the first shaft body portions

54 are positioned in front of the retained portions **22** of the first terminals **20**, above the supported arm portions **25A**, and behind the protruding portions **25C** with a slight gap from, respectively, the retained portions **22**, the supported arm portions **25A**, and the protruding portions **25C**.

(45) The second shaft body portions **55** are provided in the same positions as the second terminals **30** in the connector width direction and, as shown in FIG. 2, couple the opposed faces (faces perpendicular to the connector width direction) of the rear end portions (end portions on the X2 side) of two mutually adjacent partition walls **53**. As shown in FIG. 3(B), the cross-sectional shape of the second shaft body portions **55** perpendicular to the connector width direction has a substantially rectangular configuration with rounded corners, whose longitudinal direction is the up-down direction. In addition, as shown in FIG. 3(13), along with having their bottom faces supported by the bottom wall **13** of the housing **10**, the second shaft body portions **55** are positioned below the second shaft restricting portions **32A** of the second terminals **30** with a slight gap from said second shaft restricting portions **32A**.

(46) The cam portions **56** are provided in the same positions in the connector width direction as the locking members **40** and, as shown in FIG. 2, couple the opposed faces (faces perpendicular to the connector width direction) of the most outward partition walls **53** in the connector width direction and the end walls **52** adjacent to said partition walls **53**. As shown in FIG. 3(C), the cam portions **56** extend in the forward-backward direction, and, along with having their front end portions coupled to the bottom portion of the actuating portion **51**, have a rear edge of a circular actuate shape. The cam portions **56** are positioned upwardly of the pressure-receiving portions **42A** of the pressure-receiving arm portions **42** of the locking members **40** and downwardly of the rear half of the pressure-receiving arm portions **42** (sections extending in the forward-backward direction). The rear end portions of the cam portions **56** are formed as pressure-applying portions **56A** capable of applying pressure to the pressure-receiving portions **42A** from above, and the bottom faces of the pressure-applying portions **56A** are brought into contact with the pressure-receiving portions **42A**. In the present embodiment, the pressure-applying portions **56A** are located within the bounds of the first shaft body portions **54** and second shaft body portions **55** in the up-down and forward-backward directions.

(47) The pivotal center O, through which the pivotal axis of the movable member **50** passes, is shown in each view of FIGS. 3(A) to 3(C). As shown in FIG. 3(A), at the location of the first shaft body portions **54** in the connector width direction, the pivotal center O is positioned slightly forwardly of the substantially central portion of the first shaft body portions **54** when viewed in the connector width direction. As shown in FIG. 3(B), at the location of the second shaft body portions **55** in the connector width direction, the pivotal center O is positioned slightly to the front in the top portion of the second shaft body portions **55** when viewed in the connector width direction. As shown in FIG. 3(C), at the location of the cam portions **56** in the connector width direction, the pivotal center O is positioned at the point of contact between the pressure-applying portions **56A** of the cam portions **56** and the pressure-receiving portion **42A**.

(48) In the present embodiment, positioning the pressure-receiving portions **42A** formed in the front end portions of the pressure-receiving arm portions **42** of the locking members **40** downwardly of the other parts of the pressure-receiving arm portions **42** makes it possible to provide the cam portions **56** of the movable member **50** in a lower position in comparison with forming the entire pressure-receiving arm portion **42** in a rectilinear manner even though the cam portions **56** of the movable member **50** are located above the pressure-receiving portions **42A**, and, as a result, makes it possible to achieve a reduction in the profile, i.e., miniaturization in the up-down direction, of the connector **1**.

(49) In addition, in the present embodiment, positioning the pressure-applying portions **56A** of the cam portions **56** in the movable member **50** within the bounds of the shaft body portions **54** and **55** in the tip-down direction achieves a reduction in the profile of the movable member **50** and, by extension, the connector **1** in comparison with positioning the pressure-applying portions **56A**

outside the range of the shaft body portions **54** and **55** in the up-down direction. Further, since the pressure-applying portions **56A** of the cam portions **56** are located within the bounds of the shaft body portions **54** and **55** in the up-down direction, the pressure-applying portions **56A** are located in the vicinity of the pivotal axis, in other words, pivotal center O of the movable member **50**.

Therefore, it becomes easy to apply pressure to the pressure-receiving portions **42A** with the pressure-applying portions **56A** from above without maximizing the size of the cam portions **56**.

(50) At such time, the closer the pressure-applying portions **56A** are to the pivotal axis, the greater the force (pressure force) required to depress the pressure-receiving portions **42A** with the pressure-applying portions **56A** when moving the movable member **50** from the closed position to the open position during the unlocking operation. However, in the present embodiment, the locking members **40** are disposed only on opposite external sides of the terminal array range and the number of the provided locking members **40** is small. Furthermore, in the process of pivoting of the movable member, the first shaft restricting portions **20A** of the first terminals **20** do not come into contact with the first shaft body portions **54** of the movable member **50** and no contact pressure is generated therebetween. In addition, in the process of pivoting of the movable member **50**, the second shaft restricting portions **32A** of the second terminals **30** are only temporarily lifted up by the corner portions **55A** of the second shaft body portions **55**, and the duration of the contact pressure therebetween is therefore short. As a result, the actuating force unlocking actuating force) required to move the movable member **50** from the closed position to the open position is decreased, which makes it possible to easily perform the unlocking operation even if the above-mentioned pressure force increases during the unlocking operation.

(51) Although in the present embodiment the movable member **50** is adapted to move between the closed position and the open position simply by pivoting about a pivotal axis extending in the connector width direction, the way of movement of the movable member **50** is not limited thereto, and it may, for example, be adapted to pivot in combination with sliding movement.

(52) The connector **1** is assembled in accordance with the following procedure. First, the first terminals **20** and the locking members **40** are mounted to the housing **10** from the front. Specifically, the base portions **21** of the first terminals **20** are press fitted into the front groove portions **17A** of the housing **10** (see FIG. 3(A)), and the mounting portions **13A** of the housing **10** are clamped by the mountable portions **44** of the locking members **40** (see FIG. 3(C)). The first terminals **20** and the locking members **40** may be mounted either one after the other, or at the same time.

(53) Next, the movable member **50** is disposed in the movable member accommodating space **16** of the housing **10**. Specifically, the first shaft body portions **54** are disposed in the spaces surrounded by the first shaft restricting portions **20A** formed by the front end portions of the retained portions **22** of the first terminals **20**, the supported arm portions **25A** and the protruding portions **25C** (see FIG. 3(A)), the second shaft body portions **55** are disposed the top face of the front end portion of the bottom wall **13** (see FIG. 3(B)), and the pressure-applying portions **56A** of the cam portions **56** are disposed on the pressure-receiving portions **42A** of the locking members **40** (see FIG. 3(C)). Next, the second terminals **30** are mounted to the housing **10** from the rear. Specifically, the retained arm portions **35** of the second terminals **30** are press-fitted into the press-fit groove portions **18A-2** of the housing **10** from the rear (see FIG. 3(B)). As a result, the second shaft restricting portions **32A** of the second terminals **30** are positioned immediately above the second shaft body portions **55** of the movable member **50**. Therefore, the movement of the shaft body portions **54**, **55** in a plane perpendicular to the connector width direction is restricted by the first shaft restricting portions **20A** of the first terminals **20** and the second shaft restricting portions **32A** of the second terminals **30** and, as a result, detachment of the movable member **50** from the housing **10** is adequately prevented. The mounting of the first terminals **20**, the second terminals **30**, the locking members **40**, and the movable member **50** to the housing **10** in this manner completes the assembly of the connector **1**.

(54) In the present embodiment, an inspection to confirm whether the vertical dimensions of the gap through which the flat-type conductor C enters at the location of the first contact portions **24A** of the first terminals **20** are properly ensured or not is carried out upon completion of assembly of the connector **1**. With respect to the first terminals **20**, the term gap, as used herein, refers to the vertical dimensions of the space between the first contact portions **24A** and the top face of the bottom wall **13** of the housing **10** facing the same, which is designated as $\delta 1$ in FIG. 3(A).

(55) The inspection device (not shown) used for inspection, which is provided behind the connector **1**, has an emitting portion (not shown) that emits light forwardly toward the receiving space **11** of the housing **10**, an imaging portion (not shown) that captures images (inspection images) of the connector **1** as seen from the rear, and a measuring portion (not shown) that analyzes the captured inspection images and measures the vertical dimensions of the gap $\delta 1$.

(56) At the time of inspection, when light is emitted forwardly from the emitting portion toward the receiving space **1**, the light that reaches the reflecting surfaces **23A-1** of the first terminals **20** is reflected back, i.e., toward the rear end opening **11A**, by said reflecting surfaces **23A-1**. In the present embodiment, the first guide faces **24A-1**, which constitute the rear end faces of the first terminals **20**, are inclined faces sloping downward as one moves forward, and the light that reaches the first guide faces **24A-1** is unlikely to be reflected toward the rear end opening **11A**.

(57) Therefore, in the inspection images captured by the imaging portion, the first contact portions **24A** become darker, and the reflecting surfaces **23A-1** become lighter. In other words, clear inspection images with high contrast between the first contact portions **24A** and the reflecting surfaces **23A-1** are obtained. As a result, the location of the protruding ends (bottom ends) of the first contact portions **24A** in the inspection images can be easily determined, which makes it possible for the measuring portion to precisely measure the vertical dimensions of the gap $\delta 1$.

(58) In the present embodiment, positioning the reflecting surfaces **23A-1** within a range that includes the entire gap $\delta 1$ as previously discussed makes it possible for light emitted forwardly toward the receiving space **11** to be adequately reflected back by the reflecting surface **23A-1**. In addition, since the reflecting surfaces **23A-1** are formed as surfaces perpendicular to the forward-backward direction in the forward-backward direction, light can be reflected back by the reflecting surfaces **23A-1** in a more adequate manner.

(59) In addition, in the present embodiment, the reflective portions **23A** are formed in the rear end portions of the extension portions **21** extending toward the rear from the retained portions **22**, which makes it possible to dispose the reflecting surfaces **23A-1** closer to the first contact portions **24A** in the forward-backward direction. In other words, given the constraint that the reflecting surfaces **23A-1** are disposed forwardly of the first contact portions **24A**, the reflecting surfaces **23A-1** can be disposed as rearwardly as possible, in other words, at locations close to the rear end opening **11A** of the receiving space **11**. Therefore, even though the rear end opening **11A** of the receiving space **11** is small, light emitted forwardly toward the receiving space **11** is likely to reach the reflecting surfaces **23A-1** and a sufficient quantity of light can be reflected back by the reflecting surfaces **23A-1**. As a result, it becomes easy to capture clear inspection images with high contrast between the first contact portions **24A** and the reflecting surfaces **23A-1** and determine the location of the first contact portions **24A**, which makes it possible to accurately measure the dimensions of the gap $\delta 1$.

(60) Although in the present embodiment the extension portions **23** provided with the reflective portions **23A** are arm-shaped sections that extend toward the rear from the rear ends of the retained portions **22**, the form of the extension portions is not limited thereto. For example, the extension portions may be arm-shaped sections of a substantially L-shaped configuration that extend downward from the bottom edge of the front end sections of the contact arm portions **24** and then extend further rearward. In such a case, the reflective portions are formed in the rear end portions of the rearwardly extending sections, and the reflecting surfaces are formed on the rear end faces of said rear end portions. In addition, the extension portions may be arm-shaped sections or

protrusion-shaped sections that extend downward from the bottom edges of the front end sections of the contact arm portions **24**. In such a case, the reflective portions are formed in the bottom end portions of the extension portions, and the reflecting surfaces are formed on the rear end faces of said bottom end portions.

(61) In addition, although in the present embodiment the reflecting surfaces **23A-1** are located within a range that includes the entire gap **δ1**, it is not essential for the reflecting surfaces **23A-1** to be located within a range that includes the entire gap **61** as long as sufficient reflected light can be obtained to determine the location of the first contact portions **24A**. For example, the reflecting surfaces **23A-1** may be provided within a range that overlaps with a portion of the gap **61** while including the protruding ends of the contact portions, in addition, although in the present embodiment the reflecting surfaces **23A-1** are flat surfaces perpendicular to the forward-backward direction, it is not essential for the reflecting surfaces **23A-1** to be surfaces perpendicular to the forward-backward direction as long as sufficient reflected light can be obtained to determine the location of the first contact portions **24A**, and these surfaces may be, for example, somewhat curved or somewhat inclined.

(62) The operations of insertion and extraction of the flat-type conductor C into and from the connector **1** will be described below.

(63) First, the first connecting portions **25B** of the first terminals **20** and the second connecting portions **36C** of the second terminals **30** of the connector **1** are solder-connected to the corresponding circuits of the circuit board (not shown) and the anchor portions **46A** of the locking members **40** are solder-connected to the corresponding portions of the circuit board. The connector **1** is mounted to the circuit board using the solder connections of these first connecting portions **25B**, second connecting portions **36C**, and anchor portions **46A**.

(64) Next, as shown in FIG. **1**, the flat-type conductor C is positioned so as to extend parallel to the mounting face of the circuit board (not shown) in the forward-backward direction (X-axis direction) behind the connector **1**, in which the movable member **50** has been brought to the closed position. Next, the flat-type conductor C is inserted into the receiving space **11** of the connector **1** in the forward direction (X1 direction).

(65) In the process of insertion of the flat-type conductor C into the receiving space **11**, the front end of the flat-type conductor C, first, resiliently displaces the second contact arm portions **33** upward by abutting the second guide faces **33A-1** of the second contact portions **33A** of the second terminals **30** and pushing the second contact portions **33A** upward under the action of the upward component of the abutment force. As the flat-type conductor C is inserted further forward while being guided by the second guide faces **33A-1**, the front end of said flat-type conductor C resiliently displaces the first contact arm portions **24** upward by abutting the first guide faces **24A-1** of the first contact portions **24A** of the first terminals **20** and pushing said first contact portions **24A** up. The flat-type conductor C is inserted further forward while being, guided by the first stride faces **24A-1**.

(66) As illustrated in FIGS. **4(A)** and **4(B)**, even upon complete insertion of the flat-type conductor C, the first contact arm portions **24** of the first terminals **20** and the second contact arm portions **33** of the second terminals **30** remain resiliently displaced. As a result, a state is maintained in which the first contact portions **24A** and the second contact portions **33A** have been brought into contact with, respectively, the first circuit C1A and the second circuit C1B (see FIG. **1**) of the flat-type conductor C under contact pressure.

(67) In addition, in the process of insertion of the flat-type conductor C into the receiving space **11**, specifically, when the front end of the flat-type conductor C passes the location of the second contact portions **33A** and before it reaches the location of the first contact portions **24A**, the ear portions C3 located proximal of the opposite ends of the flat-type conductor C in the width direction abut the inclined laces **43A-1** of the engaging portions **43A** formed in the locking arm portions **43** of the locking members **40**. Then, as the flat-type conductor C is inserted further

forward while being guided by the inclined faces **43A-1**, the engaging portions **43A** are lifted up under the action of the vertical component of the force of abutment against the inclined faces **43A-1**.

(68) In the present embodiment, the locking arm portions **43**, strut portions **45**, and upper clamping portions **44A** of the locking members **40** are resiliently displaceable, and the spring length is the length of the range encompassing these sections. Therefore, when the ear portions **C3** of the flat-type conductor **C** lift the engaging portions **43A**, the locking arm portions **43**, strut portions **45**, and upper clamping portions **44A** effect rocking motion about the coupling portions **44C** of the mountable portions **44** as fulcras and are resiliently displaced upward (**Z1** direction), and, as a result, further insertion of the flat-type conductor **C** is permitted.

(69) When the flat-type conductor **C** is inserted further forward and the ear portions **C3** pass the location of the engaging portions **43A**, the locking arm portions **43** are displaced downward (**Z2** direction) such that the amount of resilient displacement is reduced and they return to a free state, thus push-fitting into the notched portions **C2** of the flat-type conductor **C**. As a result, the engageable portions **C3A** of the flat-type conductor **C** are positioned so as to permit engagement with the engaging portions **43A** forwardly of said engaging portions **43A**, and rearward extraction of the flat-type conductor **C** is prevented (see FIG. 4(C)). It should be noted that it is not essential for the locking arm portions **43** to go back to a completely free state. For example, it is possible to use a configuration in which the engaging portions **43A** are positioned so as to permit engagement with the engageable portions **C3A** by push-fitting into the notched portions **C2** of the flat conductor **C** while a certain amount of residual resilient displacement remains in the locking arm portions **43**.

(70) The operation of insertion of the flat-type conductor **C** is complete when, as shown in FIG. 4(A-C), the front end of the flat-type conductor **C** abuts the front wall **15** of the housing **10**.

(71) When the flat-type conductor **C** in the condition illustrated in FIGS. 4(A to 4(C)), that is, connected to the connector **1**, is intentionally extracted from the connector **1**, the movable member **50** in the closed position is pivoted, which brings it to the open position illustrated in FIGS. 5(A) to 5(C). Due to the fact that the pressure-applying portions **56A** of the cam portions **56** of the movable member **50** push the pressure-receiving portions **42A** of the locking members **40** down as the movable member **50** moves to the open position, the locking arm portions **43**, strut portions **45**, and upper clamping portions **44A** are resiliently displaced upward as previously discussed in connection with the operation of insertion of the flat-type conductor **C**. As a result, the engaging portions **43A** of the locking arm portions **43** of the locking members **40** are upwardly detached from the notched portions **C2** of the flat-type conductor **C**. The state of detachment of the engaging portions **43A** from the notched portions **C2** is maintained even after bringing the movable member **50** to the open position, as a result of which the engaging portions **43A** are disengaged from the engageable portions **C3A** of the flat-type conductor **C** and extraction of the flat-type conductor **C** is permitted. The flat-type conductor **C** is then easily extracted from the connector **1** by pulling said flat-type conductor **C** toward the rear (**X2** direction), and the extraction operation is complete.

(72) As the movable member **50** is pivoted from the closed position to the open position, the first shaft body portions **54** of the movable member **50** do not come into contact with the first shaft restricting portions **20A** made up of the front end portions of the retained portions **22** of the first terminals **20**, the supported arm portions **25A**, and the protruding portions **25C**. On the other hand, in the second shaft body portions **55** of the movable member **50**, immediately after the movable member **50** starts pivoting toward the open position, the corner portions **55A** of the second shaft body portions **55** abut the second shaft restricting portions **32A** from below and bring said second shaft restricting portions **32A** to a state of resilient displacement by slightly lifting them up. Then, as the movable member **50** pivots further and reaches the open position, as illustrated in FIG. 5 (B), the second shaft restricting portions **32A** are brought out of the state of resilient displacement, supporting and contacting the corner portions **55A** of the second shaft body portions **55** from

above.

(73) In addition, since in the present embodiment, as previously discussed, resilient displacement is made possible not only in the locking arm portions **43** and strut portions **45**, but also in the upper clamping portions **44A** of the mountable portions **44**, a longer spring length is correspondingly ensured in addition, since the upper clamping portions **44A**, which form part of the mountable portions **44** used for mounting the locking members **40** to the housing **10**, are used as resiliently displaceable sections, there is no need to provide new sections in the locking members **40** or make the locking arm portions **43** and strut portions **45** longer in order to increase the spring length, and no increase in the size of the connector **1** occurs.

(74) Although in the present embodiment, the upper clamping portions **44A** of the mountable portions **44** of the locking members **40** are resiliently displaced upward along with the locking arm portions **43** and the strut portions **45** in the process of insertion and extraction of the flat-type conductor C, the lower clamping portion **44B** is not resiliently displaced upward. Therefore, since the upper clamping portion **44A** and the lower clamping portion **44B** in the mountable portion **44** are spaced apart because only the upper clamping portion **44A** is displaced upward, the clamping force applied by the mountable portion **44** to the mounting portion **13A** of the housing **10**, i.e., the strength of attachment of the mountable portion **44**, may be somewhat decreased.

(75) However, the operations of insertion and extraction of the flat-type conductor C are performed after mounting the connector **1** to the mounting face of the circuit board, i.e., after anchoring the anchor portions **46A** of the locking members **40** to the mounting face of the circuit board using solder connections. Therefore, even though the upper clamping portions **44A** and the lower clamping portions **44B** of the mountable portions **44** are spaced apart and the clamping force is somewhat decreased, the locking members **40** do not become detached from the housing **10** because the locking members **40** are already anchored to the circuit board at this point in time.

(76) In addition, although in the present embodiment the lower clamping portion **44B** is not resiliently displaced upward when the upper clamping portion **44A** of the mountable portion **44** is resiliently displaced upward, as an alternative, both the upper clamping portion **44A** and the lower clamping portion **44B** may be resiliently displaced upward. By doing so, the condition is which the mounting portion **13A** of the housing **10** is clamped by the upper clamping portion **44A** and the lower clamping portion **44B** is maintained even in the state of resilient displacement. As a result, the decrease in the strength of attachment of the mountable portion **44** to the housing **10** can be minimized.

(77) Although in the present embodiment the locking members **40** are provided with mountable portions **44** having upper clamping portions **44A**, lower clamping portions **44B**, and coupling portions **44C**, and the upper clamping portions **44A** are resiliently displaceable along with the locking arm portions **43** and the strut portions **45**, as long as the magnitude of the unlocking actuating force is kept to an acceptable level, the spring length of the terminals can be increased by adopting a configuration similar to that of the locking members **40** for at least one type of terminal from it among the first terminals and second terminals.

(78) If a configuration similar to that of the locking members **40** is applied to the terminals, said terminals are provided with upper arm portions, mountable portions, strut portions, and connecting portions (anchor portions). In addition, the upper arm portions are provided with a pressure-receiving arm portion that extends forwardly from the top end of the strut portion and has a pressure-receiving portion formed in the front end portion, and a contact arm portion that extends rearwardly from the top end of the strut portion and has a contact portion formed in the rear end portion. Furthermore, above the pressure-receiving portions of the pressure-receiving arm portions, the movable member is provided with cam portions similar to the cam portions **56** and the movable member **50** of the present embodiment.

(79) If the terminals are configured in this manner, as the movable member moves to the open position when the flat-type conductor is extracted, the cam portions of the movable member

depress the pressure-receiving portions, and the contact arm portions, strut portions, and upper clamping portions of the mountable portions are resiliently displaced upward. As a result, contact between the contact portions of the contact arm portions and the circuits of the flat-type conductor is broken.

(80) Even though the spring length is increased with the terminals configure in this manner, no increase in the size of the connector occurs and, in addition, even though the strength of attachment of the mountable portion to the housing is somewhat reduced, the terminals do not become detached from the housing in the same manner as described above for the locking members **40**.

DESCRIPTION OF THE REFERENCE NUMERALS

(81) **1** Connector **10** Housing **11** Receiving space **11A** Rear end opening **13A** Mounting portion **20** First terminal **20A** First shaft restricting portion **21** Base portion **22** Returned portion **23** Extension portion **23A** Reflective portion **23A-1** Reflecting surface **24** First contact arm portion **24A** First contact portion **25B** First connecting portion (anchor portion) **30** Second terminal **31** Upper arm portion **32A** Second shaft restricting portion) **33** Second contact arm portion **33A** Second contact portion **34** Lower arm portion **36** Projecting arm portion **36B-1** Recess portion **36B-2** Front protrusion **36B-3** Rear protrusion **36C** Second connecting portion (anchor portion) **37** Strut portion **40** Locking, member **41** Upper arm portion **42** Pressure-receiving arm portion **42A** Pressure-receiving portion **43** Locking arm portion **43A** Engaging portion **44** Mountable portion **44A** Upper clamping portion **44B** Lower clamping portion **44C** Coupling portion **45** Strut portion **46A** Anchor portion **50** Movable member **54** First shaft body portion **55** Second shaft body portion **56** Cam portion **56A** Pressure-applying portion **C** Flat-type conductor **C1** Connecting circuit **C1A** First circuit **C1B** Second circuit **C3A** Engageable portion **O** Pivotal center **δ1** Gap

Claims

1. An electrical connector for flat-type conductors to which a flat-type conductor extending in a forward-backward direction and dimensionally thick in an up-down direction is connected, said connector comprising; a housing that has formed therein a receiving space open toward a rear for forward insertion of the flat-type conductor, multiple terminals that are arranged and retained in the housing such that a terminal array direction is a direction perpendicular to both the forward-backward direction and the up-down direction, locking members that are disposed outside an array range of the terminals in the terminal array direction and retained in the housing, and a movable member that is provided forwardly of the receiving space and is capable of moving between a closed position and an open position while pivoting about a pivotal axis extending in the terminal array direction, with extraction of the flat-type conductor being prevented when the movable member is in the closed position and extraction of the flat-type conductor being permitted when the movable member is in the open position, wherein the locking members have an upper arm portion that extends in the forward-backward direction upwardly of the receiving space, a mountable portion that is mounted to the housing at a location downward of the upper arm portion and forward of the receiving space, and a strut portion that extends upwardly from the mountable portion and is coupled to the upper arm portion; the upper arm portion has a pressure-receiving arm portion that extends forwardly from a top end of the strut portion, and a locking arm portion that extends rearwardly from the top end of the strut portion; the locking arm portion has an engaging portion positioned so as to permit engagement from the rear with an engageable portion in the flat-type conductor when the movable member is in the closed position; the mountable portion has an upper clamping portion and a lower clamping portion that are spaced apart from each other in the up-down direction and extend in the forward-backward direction, and a coupling portion that couples front end portions of the upper clamping portion and lower clamping portion, with the upper clamping portion, which is positioned forward of the receiving space, being resiliently displaceable in the up-down direction by effecting rocking motion about the coupling portion of the

mountable portion as a fulcrum, and a mounting portion, formed as part of the housing, being clamped by the upper clamping portion and lower clamping portion in the up-down direction; the strut portion extends upward from the upper clamping portion, the movable member has cam portions located above the pressure-receiving arm portions, and the cam portions depress the pressure-receiving arm portions downward when the movable member moves from the closed position to the open position.

2. The electrical connector for flat-type conductors according to claim 1, wherein the electrical connector for flat-type conductors is mountable to a mounting face of a circuit board using solder connections, and the locking members have an anchor portion that extends toward the front from the mountable portion and is anchored to the mounting face of the circuit board using solder connections.

3. The electrical connector according to claim 1, wherein the coupling portion is configured as a living hinge that enables the upper clamping portion to rock about the coupling portion while maintaining the clamping relationship with the mounting portion of the housing.

4. The electrical connector according to claim 1, wherein the coupling portion has a reduced thickness compared to the upper and lower clamping portions to facilitate elastic deformation during the rocking motion of the upper clamping portion.

5. The electrical connector according to claim 1, wherein the upper clamping portion, strut portion, and upper arm portion are configured to move together as a single unit when effecting the rocking motion about the coupling portion as the fulcrum.

6. An electrical connector for flat-type conductors to which a flat-type conductor extending in a forward-backward direction and dimensionally thick in a up-down direction is connected, said connector comprising: a housing that has formed therein a receiving space open toward a rear for forward insertion of the flat-type conductor, multiple terminals that are arranged and retained in the housing such that a terminal array direction is a direction perpendicular to both the forward-backward direction and the up-down direction, and a movable member that is provided forwardly of the receiving space and is capable of moving between a closed position and an open position while pivoting about a pivotal axis extending in the terminal array direction, wherein the terminals have an upper arm portion that extends in the forward-backward direction upwardly of the receiving space, a mountable portion that is mounted to the housing at a location downward of the upper arm portion and forward of the receiving space, and a strut portion that extends upwardly from the mountable portion and is coupled to the upper arm portion; the upper arm portion has a pressure-receiving arm portion that extends forwardly from a top end of the strut portion, and a contact arm portion that extends rearwardly from the top end of the strut portion: the contact arm portion has a contact portion that comes into contact with circuits of the flat-type conductor from above when the movable member is in the closed position; the mountable portion has an upper clamping portion and a lower clamping portion that are spaced apart from each other in the up-down direction and extend in the forward-backward direction, and a coupling portion that couples front end portions of the upper clamping portion and lower clamping portion, with the upper clamping portion, which is positioned forward of the receiving space, being resiliently displaceable in the up-down direction by effecting rocking motion about the coupling portion of the mountable portion as a fulcrum, and a mounting portion, formed as part of the housing, being clamped by the upper clamping portion and lower clamping portion in the up-down direction; the strut portion extends upward from the upper clamping portion; the movable member has cam portions located above the pressure-receiving arm portions; and the cam portions depress the pressure-receiving arm portions downward when the movable member moves from the closed position to the open position.

7. The electrical connector for flat-type conductors according to claim 6, wherein the electrical connector for flat-type conductors is mountable to a mounting face of a circuit board using solder connections, and the terminals have an anchor portion that extends toward the front from the

mountable portion and is anchored to the mounting face of the circuit board using solder connections.
