

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent

12409519

Kind Code

B1

Date of Patent

September 09, 2025

Inventor(s)

Wen; Jiangtao et al.

Intelligent machining line for pipe sections and method for machining same

Abstract

Disclosed are an intelligent machining line for pipe sections and a method for machining same. The intelligent machining line for pipe sections includes: a cutting station, an assembly station, a finished product station, and a derusting station. The cutting station includes a first material conveying module, a clamping module and a cutting module. The assembly station includes a support module, a welding module, a first fitting storage module and a first transfer module. The finished product station includes a second transfer module and a finished product storage module. The first transfer module includes a driving structure and a grabbing assembly. The grabbing assembly is configured to grab a pipe section to be machined, a fitting or an assembled pipe section, and the driving structure is configured to drive the grabbing assembly to move among the assembly station, the cutting station and the finished product station.

Inventors: Wen; Jiangtao (Hubei, CN), He; Yong (Hubei, CN), Wei; Min (Hubei, CN), Liu; Bo (Hubei, CN), Dang; Pengfei (Hubei, CN), Zhang; Zhiheng (Hubei, CN), Li; Hongbin (Hubei, CN), Huang; Jinyou (Hubei, CN), Zhang; Yicai (Hubei, CN)

Applicant: CHINA CONSTRUCTION THIRD ENGINEERING BUREAU GROUP CO., LTD (Hubei, CN); CHINA CONSTRUCTION THIRD BUREAU FIRST ENGINEERING CO., LTD. (Hubei, CN); CHINA CONSTRUCTION THIRD BUREAU FIRST ENGINEERING & MEP CO., LTD. (Guangdong, CN)

Family ID: 91347888

Assignee: CHINA CONSTRUCTION THIRD ENGINEERING BUREAU GROUP CO., LTD (Wuhan, CN); CHINA CONSTRUCTION THIRD BUREAU FIRST ENGINEERING CO., LTD. (Wuhan, CN); CHINA CONSTRUCTION THIRD BUREAU FIRST ENGINEERING & MEP CO., LTD. (Shenzhen, CN)

Appl. No.: 19/030934

Filed: January 17, 2025

Foreign Application Priority Data

CN202410265778.9Mar. 08, 2024

Publication Classification

Int. Cl.: B23P21/00 (20060101); B23P23/06 (20060101); F16L13/02 (20060101)

U.S. Cl.:

CPC B23P21/004 (20130101); B23P23/06 (20130101); F16L13/02 (20130101)

Field of Classification Search

CPC: Y10T (29/5185); Y10T (29/5199); Y10T (29/5367); Y10T (29/49829); Y10T (29/5124); Y10T (29/5145); Y10T (29/5191); Y10T (29/5196); B23P (19/04); B23P (21/004); B23P (23/06); B21D (45/00); B21D (13/02)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6237204	12/2000	Hoglund et al.	N/A	N/A
2023/0405743	12/2022	Kang	N/A	B23P 23/06

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
202015947	12/2010	CN	N/A
104384935	12/2014	CN	N/A
109290808	12/2018	CN	B23P 15/00
211564673	12/2019	CN	N/A
215356796	12/2020	CN	N/A
217513071	12/2021	CN	N/A
116060540	12/2022	CN	N/A
4020924	12/1990	DE	N/A
4212316	12/2022	EP	N/A

OTHER PUBLICATIONS

Notification to Grant Patent Right for Invention, Chinese Application No. 202410265778.9, mailed Jul. 23, 2024 (3 pages). cited by applicant

Weimin Long; “China Strategic Emerging Industries Research and Development: Welding Materials and Equipment”, Mechanical Industry Press, pp. 317-320, date of issue Dec. 31, 2020. cited by applicant

Hairen Liu et al.; Marine Electric & Electronic Engineering, “Study on Intelligent Length Measurement and Fixed Length CuttingUnit for Ship Pipe Processing”, pp. 1-4 and 10, vol. 40, No. 08, date of issue Aug. 15, 2020. cited by applicant

Bowen Sun; Ship Standardization Engineer, “Research on Pipeline Prefabrication Production Line”, pp. 51-65, date of issue Mar. 15, 2020. cited by applicant

Background/Summary

FIELD

(1) The disclosure relates to the technical field of machining apparatuses, in particular to an intelligent machining line for pipe sections and a method for machining same.

BACKGROUND OF THE INVENTION

(2) Pipe sections used in architecture and engineering are formed by welding various portions. In a process of machining the pipe sections, long pipes are cut and derusted (in random order), cut portions serve as main pipe sections, then fittings such as flanges, branch pipes and elbow pipes are welded to the main pipe sections, and the pipe sections used in the architecture and engineering are formed accordingly.

(3) In a process of machining existing pipe sections, cutting, welding and derusting (in random order) are separate procedures, and are most performed manually on construction sites or engineering sites. But manual operation of cutting, derusting and welding is inefficient, especially when fittings including large flanges and branch pipes are attached and welded to the main pipe sections. In consequence, the output falls far short of the actual demand, and labor-intensive work is needed, resulting in waste.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) To describe technical solutions in examples of the disclosure or in the prior art more clearly, accompanying drawings required in description of the examples or in the prior art will be briefly introduced below. Apparently, the accompanying drawings in the following description merely show some examples of the disclosure, and a person of ordinary skill in the art can still derive other accompanying drawings from structures shown in these accompanying drawings without creative efforts.

(2) FIG. 1 is a schematic structural diagram of an intelligent machining line for pipe sections according to an example of the disclosure;

(3) FIG. 2 is a schematic diagram of a partial structure in FIG. 1;

(4) FIG. 3 is a schematic structural diagram of a driving structure and a second grabbing assembly in FIG. 1 according to an example;

(5) FIG. 4 is a partial enlarged view at portion A in FIG. 2;

(6) FIG. 5 is a partial enlarged view of portion B in FIG. 2;

(7) FIG. 6 is a partial enlarged view of portion C in FIG. 2;

(8) FIG. 7 is a partial enlarged view at portion D in FIG. 2;

(9) FIG. 8 is a partial enlarged view of portion E in FIG. 2;

(10) FIG. 9 is a schematic structural diagram of a material placement assembly in FIG. 1 according to an example;

(11) FIG. 10 is a schematic structural diagram of a power module and a second fitting storage module in FIG. 2 according to an example;

(12) FIG. 11 is a schematic structural diagram of a first material conveying module, a third material conveying module and a fourth material conveying module in FIG. 1 according to the example;

- (13) FIG. 12 is a schematic structural diagram of a second transfer module and a finished product storage module in FIG. 2 according to an example;
- (14) FIG. 13 is a schematic structural diagram of a derusting module in FIG. 1 from one perspective;
- (15) FIG. 14 is a schematic partial structural diagram of the derusting module in FIG. 1 from another perspective;
- (16) FIG. 15 is a schematic structural diagram of a protective assembly in an intelligent machining line for pipe sections according to example of the disclosure;
- (17) FIG. 16 is a schematic structural diagram of a first grabbing assembly in an intelligent machining line for pipe sections according to an example of the disclosure;
- (18) FIG. 17 is a schematic structural diagram of a clamping assembly in FIG. 2 according to an example;
- (19) FIG. 18 is a schematic structural diagram of a positioning plate, a first support leg or a third support leg in 2 according to an example; and
- (20) FIG. 19 is a schematic structural diagram of a placement frame in FIG. 9 according to an example.

(21) The implementation of objectives, functional features and advantages of the disclosure will be further described in conjunction with examples and with reference to accompanying drawings.

DETAILED DESCRIPTION OF THE INVENTION

(22) The technical solutions in the examples of the disclosure will be described clearly and comprehensively below in conjunction with the accompanying drawings in the examples of the disclosure. Obviously, the described examples are only part of the examples of the present disclosure, not all of the examples. Based on the examples of the present disclosure, all other disclosure obtained by a person skilled in the art without creative effort fall within the protection scope of the present disclosure.

(23) It should be noted that all directional indications (such as up, down, left, right, front, rear, etc.) in the examples of the disclosure are only used to explain the relative position relationship, motion situation, etc. between the components in a certain posture (as shown in the attached drawings). If the certain posture changes, the directional indication changes accordingly.

(24) In the disclosure, unless otherwise explicitly specified and limited, the terms “connected”, “fixed” and the like are to be interpreted broadly, for example, “fixed” may be a fixed connection, a detachable connection, or an integral connection; may be a mechanical connection, or an electrical connection; may be a direct connection, or may be indirectly connected through an intermediary; may be a communication between two elements or an interaction relationship between two elements, unless otherwise explicitly limited. For those skilled in the art, the specific meanings of the above terms in the disclosure can be understood according to specific circumstances.

(25) In addition, if there are descriptions involving “first”, “second”, etc. in the examples of the disclosure, the descriptions of “first”, “second”, etc. are only used for descriptive purposes, and cannot be understood as indicating or implying their relative importance or implicitly indicating the number of indicated technical features. Thus, a feature defined by “first” and “second” may explicitly or implicitly include at least one of the features. In addition, the meaning of “and/or” appearing in the whole text includes three parallel schemes, taking “A and/or B” as an example, including scheme A, or scheme B, or scheme A and B simultaneously satisfied. In addition, technical solutions of various examples may be combined with each other, but it must be based on what can be achieved by a person skilled in the art. When the combination of technical solutions is contradictory or cannot be achieved, it should be deemed that such combination of technical solutions does not exist, and is not within the scope of protection required by the disclosure.

(26) The intelligent machining line for pipe sections described herein includes at least one control unit designed to control some or all of the steps described and claimed herein for the pipe machining process. The control unit may be only one or formed by a plurality of different control

units, e.g. at least one control unit associated with the equipment A, at least one control unit associated with the device B, and at least one control unit managing the controller for the production line C. Of course, depending on design choices and operational needs, different configurations can be envisaged. The term “control unit” means an electronic component that may include at least one of a digital processor (e.g., including at least one selected from the group consisting of CPU, GPU, GPGPU), a memory (or memories), analog circuitry, or a combination of one or more digital processing units and one or more analog circuitry. The control unit can be “configured” or “programmed” to perform certain steps: This can be done by virtually any means that allows the control unit to be configured or programmed. For example, where the control unit includes one or more CPUs and one or more memories, one or more programs may be stored in an appropriate group of memories connected to the one or more CPUs. The one or more programs containing instructions that, when executed by the one or more CPUs, program or configure the control unit to perform the operations described in relation to the control unit. Alternatively, if the control unit is or includes analog circuitry, the control unit circuitry may be designed to include circuitry configured for, in use, processing electrical signals in order to perform steps associated with the control unit. The control unit may include one or more digital units (e.g. of microprocessor type), or one or more analog units, or a suitable combination of digital and analog units; the control unit may be configured to coordinate all actions necessary to execute the instructions and instruction sets.

(27) The disclosure provides an intelligent machining line for pipe sections used to perform derusting, cutting and welding on the pipe sections.

(28) In an example of the disclosure, with reference to FIGS. 1 and 2, the intelligent machining line for pipe sections includes a cutting station, an assembly station and a finished product station.

(29) With reference to FIGS. 1 and 2, the cutting station includes a first material conveying module **10**, a clamping module **20**, and a cutting module **30**. The first material conveying module **10** is configured to convey and support a pipe section to be cut. The pipe section to be cut may be rusted or not.

(30) In this example, with reference to FIGS. 1 and 2, the first material conveying module **10** may adopt a structure described below, as shown in FIG. 5. The first material conveying module **10** includes a first machine frame **11**. A first conveying roller **12** is mounted on the first machine frame **11**. The first conveying roller **12** is configured to convey the pipe section to move in the direction **st1**. A plurality of first conveying rollers **12** are provided. The plurality of first conveying rollers **12** are distributed at intervals in the direction **st1**. The first conveying rollers **12** are connected to the first machine frame **11** through first mounting frames **13**. The first conveying rollers **12** are mounted at the first mounting frames **13**. The plurality of first conveying rollers **12** are connected in one-to-one correspondence, through a plurality of first mounting frames **13**, to the first machine frame **11**. One ends of the plurality of first mounting frames **13** are all hinged to the first machine frame **11**, and the other ends of the plurality of first mounting frames **13** are integrally arranged. The other ends of the plurality of first mounting frames **13** may be integrally arranged by a method as follows: the other ends of the plurality of first mounting frames **13** are all fixedly arranged at the connection plate **15**. A first driving member **14** configured to drive the plurality of first conveying rollers **12** to rotate is mounted on the connection plate **15**. The first driving member **14** includes a plurality of sprocket wheels and a chain. The chain is connected to the plurality of sprocket wheels. The plurality of sprocket wheels are connected to the plurality of first conveying rollers **12** in one-to-one correspondence. The first conveying roller **12** includes a first roller body and a fifth rotary shaft. The first roller body is keyed to the fifth rotary shaft, such that the first roller body rotates synchronously along with the fifth rotary shaft. The first roller body is configured to consist of two symmetrical cone frustum-shaped structures, and small ends of the two cone frustum-shaped structures are connected (see FIG. 15). One end of the fifth rotary shaft is rotatably connected to the first mounting frame **13**, and the other end of the fifth rotary shaft penetrates the connection

plate **15**. The sprocket wheel is keyed to one end, penetrates to the outside of the connection plate **15**, of the fifth rotary shaft. The first driving member **14** further includes a first driving motor. The first driving motor is mounted at the connection plate **15**. The first driving motor is configured to drive the chain to work. The chain works to rotate the plurality of sprocket wheels. The plurality of sprocket wheels may drive the fifth rotary shafts and the first roller bodies to rotate while rotating. When the first roller body rotates, the pipe section located on the first roller body may move in the direction st1 and rotate forwards and backwards along with the first driving motor, such that the pipe can move back and forth on the first material conveying module **10**. A second driving member configured to turn over the plurality of first mounting frames **13** around a hinged joint is mounted on the first machine frame **11**. The second driving member may adopt a driving cylinder. A stretchable end of the driving cylinder is hinged to the connection plate **15**. A base of the driving cylinder is mounted at the first machine frame **11**. When stretching or retracting, the driving cylinder may jack or drop the connection plate **15** respectively, and also turn over the plurality of first mounting frames **13** around the hinged joint. Two groups of driven disks **16** are further arranged on the first machine frame **11**. A plurality of driven disks are included in each group of driven disks **16**. The plurality of driven disks **16** in each group are uniformly distributed in the direction st1. The driven disk **16** is rotatably mounted at the first machine frame **11**.

(31) With reference to FIG. **4**, the clamping module **20** is configured to clamp the pipe section to be cut and drive the pipe section to be cut to rotate on the first material conveying module **10**. The cutting module **30** is configured to cut the pipe section to be cut. The clamping module **20** is arranged at an end of the first material conveying module **10**. When the pipe section rotates on the first material conveying module **10**, the first driving member **14** drop the plurality of first mounting frames **13**. In this case, the pipe section is in contact with the two groups of driven disks **16**, the pipe section rotates on the first material conveying module **10**, and the driven disks **16** rotate around axes of the driven disks under the action of rotation of the pipe section. Thus, friction force between the pipe section and the first material conveying module **10** can be reduced, and the pipe section can be machined advantageously.

(32) In this example, with reference to FIG. **4**, the clamping module **20** includes a second machine frame **21**, a first chuck **22**, a third driving member and a fourth driving member. The first chuck **22** is configured as a scroll chuck. The scroll chuck may be an electric scroll chuck or a pneumatic scroll chuck, which is not limited herein. The scroll chuck is configured to clamp a pipe section to be machined. The first chuck **22** is slidably mounted to the second machine frame **21**. A first guide rail is fixedly arranged on the second machine frame **21**. A first slide table is mounted on the first guide rail. The first slide table moves in a direction st2. The direction st2 is arranged perpendicular to the ground. The third driving member is mounted at one end of the first slide table. The first chuck **22** is mounted at the other end of the first slide table. The third driving member is configured as a driving motor. An output end of the third driving member is connected to the first chuck **22**. The third driving member is configured to drive the first chuck **22** to rotate. When the first chuck **22** clamps the pipe section to be machined, the first chuck **22** may also drive the pipe section to be machined to rotate while rotating. The fourth driving member is mounted at the second machine frame **21**. The fourth driving member is configured as a driving cylinder member or a hydraulic member. A stretchable end of the fourth driving member is connected to the first slide table. The fourth driving member stretches or retracts to drive the first slide table to ascend or descend. The first slide table may drive the first chuck **22** and the third driving member to ascend or descend while ascending or descending. Under the action of the fourth driving member, the first slide table may be driven to ascend or descend, and then the first chuck **22** may be driven to ascend or descend. By adjusting an axis of the first chuck **22** and an axis of the pipe section through ascending or descending of the first chuck **22**, the axis of the first chuck **22** coincides with the axis of the pipe section. Thus, the clamping module **20** in this structure can clamp pipe sections with different diameters. In this example, the pipe section to be machined is transferred through the first

conveying roller **12** in the first material conveying module **10**. The pipe section moves to the clamping module **20** in the direction st1 in the first material conveying module **10**. When the pipe section to be machined abuts against the first chuck **22**, the first driving member **14** drops the plurality of first mounting frames **13**, the driven disk **16** abuts against a surface to be machined and is not in contact with the first conveying roller **12**. In this case, the axis of the pipe section to be machined is fixed, and a user operates the first chuck **22** to align a center of the first chuck **22** with the axis of the pipe section to be machined, and clamp the pipe section to be machined. When the pipe section is machined and needs to be turned over after the first chuck **22** clamps the pipe section to be machined, the third driving member may drive the first chuck **22** to rotate, so as to cause the first chuck **22** to rotate the pipe section. The driven disk **16** may rotate around the axis of the driven disk during rotation of the pipe section, such that the friction force of the pipe section when rotating on the first material conveying module **10** can be reduced in this structure.

(33) With reference to FIG. 5, the cutting module **30** is slidably arranged at a side of the first material conveying module **10**, and moves in a direction of the axis of the pipe section.

(34) In this example, with reference to FIG. 5, the cutting module **30** includes a second guide rail **31**, a second slide table **32**, a third machine frame **33** and a cutting member **34**. The second guide rail **31** is arranged at a side of the first machine frame **11**. The second slide table **32** is mounted at the second guide rail **31**. The second slide table **32** slides in the direction st1. The third machine frame **33** is fixedly arranged at the second slide table **32**. The cutting member **34** is mounted at the third machine frame **33**. In such an arrangement, when the second slide table **32** slides in the direction st1, the third machine frame **33** and the cutting member **34** may be driven to slide together in the direction st1. Thus, the third machine frame **33** and the cutting member **34** can slide along the axis of the pipe section to be cut, and the cutting member **34** cuts the pipe section advantageously. When cutting the pipe section, the cutting member **34** starts cutting from an end, far away from the clamping module **20**, of the pipe section.

(35) In this example, with reference to FIG. 5, the cutting member **34** is slidably mounted at the third machine frame **33**. In this case, the cutting member **34** moves in the direction st2. A third guide rail is fixedly arranged on the third machine frame **33**. A third slide table for mounting the cutting member **34** is mounted on the third guide rail. The cutting member **34** includes a first mounting seat **341**, a multi-link structure and a cutting gun **342**. The multi-link structure is hinged to the first mounting seat **341**. The cutting gun **342** is hinged to the multi-link structure. The multi-link structure may rotate the cutting gun **342**. The multi-link structure includes a first overturning frame **343**, a second overturning frame **344**, a third overturning frame **345** and a fourth overturning frame **346**. The first overturning frame **343** and the second overturning frame **344** are abreast arranged. In addition, a bottom of the first overturning frame **343** and a bottom of the second overturning frame **344** are both hinged to the first mounting seat **341**. The third overturning frame **345** and the fourth overturning frame **346** are stacked. An end of the third overturning frame **345** is hinged to a top of the first overturning frame **343**. The third overturning frame **345** is further hinged to the second overturning frame **344**. An end of the fourth overturning frame **346** is hinged to a top of the second overturning frame **344**. In addition, the fourth overturning frame **346** is located above the third overturning frame **345**. The cutting gun **342** is hinged to the third overturning frame **345** and the fourth overturning frame **346**. When the multi-link structure is deformed in a direction st3, the cutting gun **342** may be driven to rotate around a direction M. A thirteenth driving member configured to drive the multi-link structure to move in the direction st3 is further arranged on the first mounting seat **341**. The thirteenth driving member may be configured as a driving cylinder. When the thirteenth driving member is configured as the driving cylinder, a stretchable end of the thirteenth driving member is hinged to the first overturning frame **343** or the second overturning frame **344**. The stretchable end of the thirteenth driving member stretches or retracts to swing the first overturning frame **343** and the second overturning frame **344** around hinged joints of the first overturning frame and the second overturning frame with the first mounting seat **341**. Then, the

third overturning frame **345** and the fourth overturning frame **346** move in the direction **st3**, and the multi-link structure moves in the direction **st3** and drives the cutting member **342** to rotate around the direction **M**. A fifth driving member is further mounted at the third slide table, and the fifth driving member is configured to rotate the first mounting seat **341** on the third slide table. The fifth driving member is configured as a second driving motor. An output end of the second driving motor is connected to the first mounting seat **341**. The second driving motor works to rotate the first mounting seat **341**. The first mounting seat **341** rotates to rotate the multi-link structure and the cutting gun **342**. In this structure, a degree of freedom of the cutting gun **342** can be increased, and the cutting gun **342** can perform all-round machining outside the pipe section. For example, the cutting gun cut gaps with different specifications outside the pipe section.

(36) Further, in this example, with reference to FIG. 5, the cutting module **30** further includes an operation table **36**. The operation table **36** is fixedly arranged at the second slide table **32**. The operation table **36** is configured to control the cutting gun **342** to perform cutting work. The operation table **36** drives, through a control unit, the cutting gun **342** to perform the cutting work.

(37) Further, in this example, with reference to FIG. 15, the cutting station further includes a protective assembly **37**. The protective assembly **37** is detachably mounted in the first material conveying module **10**. When the intelligent machining line for pipe sections machines a pipe section with a larger diameter, the protective assembly **37** may be mounted in the first material conveying module **10**, in order to avoid the situation that the pipe section with the larger diameter falls from the first material conveying module **10** after cutting. The protective assembly **37** includes two groups of symmetrically arranged guardrails **371** and a plurality of mounting clamps **372**. The two groups of guardrails **371** are symmetrically arranged with respect to the first material conveying module **10**. The plurality of mounting clamps **372** are divided into two groups and fixed to the first mounting frame **13**. The two groups of mounting clamps **372** are arranged far away from the first conveying roller **12**. Thus, influence of the mounting clamp **372** on the first conveying roller when the first conveying roller **12** drives the pipe section to move in the direction **st1** is avoided. The guardrail **371** is inserted into the mounting clamp **372**. The mounting clamp **372** is configured in a U-shaped structure. When in use, the guardrail **371** is inserted into an opening in the mounting clamp **372**, such that the protective assembly **37** may be mounted in the first material conveying module **10**. In this example, the user may choose not to mount the protective assembly **37** for the pipe section with a smaller diameter during machining.

(38) In this example, the user may place the pipe section to be cut on the first material conveying module **10** through a crane, then transfer the pipe section through the first material conveying module **10**, and move the pipe section to be cut to the clamping module **20**. Then, the user operates the clamping module **20** to clamp an end of the pipe section to be cut. In this case, the clamping module **20** may rotate the pipe section to be cut around an axis of the pipe section to be cut on the first material conveying module **10**. After the pipe section to be cut is clamped by the clamping module **20**, the cutting module **30** moves in the direction of the axis of the pipe section to be cut, to the end, far away from the clamping module **20**, of the pipe section to be cut, and starts cutting work from this end. In this example, the first material conveying module **10**, the clamping module **20** and the cutting module **30** are not limited.

(39) With reference to FIGS. 1, 2, 7 and 8, the assembly station is located downstream of the cutting station, and a pipe section machined by the cutting station enters the assembly station for being assembled. The assembly station includes a support module **40**, a welding module **50**, a first fitting storage module **60** and a first transfer module **80**. A plurality of support modules **40**, a plurality of welding modules **50** and a plurality of first fitting storage modules **60**, may be arranged.

(40) With reference to FIG. 8, the support module **40** is configured to support the pipe section to be machined, and may clamp and rotate the pipe section to be machined. The pipe section to be machined may be a pipe section cut by the cutting station or a pipe section not cut by the cutting

station.

(41) In this example, with reference to FIGS. 8 and 17, the support module **40** includes a fourth guide rail **41**, a support assembly **43** and a clamping assembly **44**. The fourth guide rail **41** is arranged downstream of the cutting station. The fourth guide rail **41** is fixedly arranged at a preset position on the ground. A fourth slide table **42** is mounted at the fourth guide rail **41**. The support assembly **43** is fixedly arranged at the fourth slide table **42**. The support assembly **43** may slide along the fourth guide rail **41** under the action of the fourth slide table **42**. In this example, the support assembly **43** includes a slide seat **431**, a mounting plate **432**, a sixth driving member **433** and a support member **434**. The slide seat **431** is fixedly arranged at the fourth slide table **42**. The fourth slide table **42** is connected to the slide seat **431** through bolt locking. The mounting plate **432** is mounted at the slide seat **431** through the sixth driving member **433**. The sixth driving member **433** is configured to drive the mounting plate **432** to ascend and descend. The sixth driving member **433** may be configured as a cylinder driving member, a hydraulic driving member or a motor driving member. The support member **434** is mounted at the mounting plate **432**. Thus, the mounting plate **432** ascends or descends to drive the support member **434** to ascend or descend. The support member **434** is configured to support the pipe section. In this example, the support member **434** ascends or descends in order to enable the support assembly **43** to support pipe sections with different diameters with a desirable support effect. The support member **434** includes a first mounting frame **4341** and a bearing **4342**. The first mounting frame **4341** is slidably mounted at the mounting plate **432** through a linear driving module. The bearing **4342** is mounted at the first mounting frame **4341**, and abuts against the outside of the pipe section. At least two bearings **4342** are arranged. When the pipe section rotates on the support member **434**, the bearing **4342** may rotate around an axis of the bearing. Thus, the friction force generated during the rotation of the pipe section can be reduced, a position of the bearing **4342** can be adjusted under the action of the linear driving module, and two bearings **4342** can abut against the outside of the pipe section.

(42) In an example, with reference to FIG. 17, the clamping assembly **44** includes a fourth machine frame **441**, a clamping member **443** and a seventh driving member **442**. The clamping member **443** and the seventh driving member **442** are both mounted at the fourth machine frame **441**. The clamping member **443** is configured to clamp the pipe section to be machined, and rotate the pipe section to be machined on the support assembly **43**. The seventh driving member **442** is configured to turn the clamping member **443** over. In this example, an overturning direction of the clamping member **443** is perpendicular to a moving direction of the support member **434**. In this example, specific structures of the clamping member **443** and the seventh driving member **442** are not limited.

(43) In this example, with reference to FIG. 17, the clamping member **443** includes a second chuck **4431**, a mounting seat and an eighth driving member **4434**. The second chuck **4431** is configured as a scroll chuck, and the scroll chuck adopts an electric chuck member, a pneumatic chuck member or a manually driven chuck member. The mounting seat is connected to the fourth machine frame **441** through a first rotary shaft **4433**. A number of the first rotary shafts **4433** is two. The two first rotary shafts **4433** are symmetrically fixed outside the mounting seat. Axes of the two first rotary shafts **4433** are coaxially arranged. The first rotary shaft **4433** is rotatably engaged with the fourth machine frame **441**. That is, the first rotary shaft **4433** may rotate on the fourth machine frame **441**. The second chuck **4431** and the eighth driving member **4434** are both mounted at the mounting seat. The second chuck **4431** is configured to clamp the pipe section to be machined. The eighth driving member **4434** is configured to rotate the second chuck **4431**, so as to cause the second chuck **4431** to rotate the pipe section to be machined. The eighth driving member **4434** drives the second chuck **4431** to rotate, so as to rotate the pipe section to be machined. The eighth driving member **4434** is configured as a third driving motor, and an output end of the eighth driving member **4434** is connected to the second chuck **4431**. The eighth driving member **4434** works to

rotate the second chuck **4431**, so as to cause the second chuck **4431** to rotate the pipe section.

(44) In this example, with reference to FIG. 17, the seventh driving member **442** may adopt the following structure. The seventh driving member **442** includes a first meshing tooth **4421**, a second meshing tooth **4422** and a fourth driving motor **4423**. The first meshing tooth **4421** is fixedly arranged at one rotary shaft of the two first rotary shafts **4433**. The second meshing tooth **4422** is mounted at an output end of the fourth driving motor **4423**. The second meshing tooth **4422** meshes with the first meshing tooth **4421**. The fourth driving motor **4423** works to rotate the second meshing tooth **4422**. The second meshing tooth **4422** rotates the first meshing tooth **4421**. The first meshing tooth **4421** rotates to rotate the first rotary shaft **4433**, so as turn over the mounting seat. The first meshing tooth **4421** has a sector tooth structure. The second meshing tooth **4422** has a circular tooth structure. The sector tooth is a half circular tooth.

(45) In this example, an overturning angle of the mounting seat is 80 degrees to 100 degrees. When the mounting seat is turned over to 90 degrees, the second chuck **4431** faces upwards. In this case, the user may mount, at the second chuck **4431**, a flange of the pipe section to be machined required for welding, and then clamp the flange by the second chuck **4431**. Then, the mounting seat drives the flange to turn over, so as to cause the flange to align with and abut against one end of the pipe section to be machined. Then, the flange is welded by the welding module **50** (see FIG. 7) to the pipe section to be machined. Through such an operation, the flange having a large structure can be connected to the pipe section to be machined advantageously, and the pipe section to be machined can be machined by the user advantageously. This operation is more stable than a method of welding the flange with the flange lifted by a crane. Especially after the flange is aligned with a welding position of the pipe section to be machined, the flange is more stable in a welding process through restriction by the second chuck **4431**. In this example, the user may place the flange on the second chuck **4431** through a power device **750** (see FIG. 10).

(46) In this example, with reference to FIG. 7, the welding module **50** includes a fifth guide rail **51**, a multi-axis mechanical arm **52**, a welding gun **53**, a locating camera **56** and a monitoring camera **57**. A fifth slide table **54** is connected to the fifth guide rail **51**. The fifth slide table **54** slides along the fifth guide rail **51**. The multi-axis mechanical arm **52** is fixedly arranged at the fifth slide table **54**. The fifth slide table **54** is fixedly provided with a mechanical arm mounting seat **55** through bolt locking. The multi-axis mechanical arm **52** is fixedly arranged at the mechanical arm mounting seat **55** through bolt locking. Under the action of the mechanical arm mounting seat **55**, a height of a tail end of the multi-axis mechanical arm **52** can be further increased, and the multi-axis mechanical arm **52** can be used advantageously. The welding gun **53**, the locating camera **56** and the monitoring camera **57** are both mounted at the tail end of the multi-axis mechanical arm **52**. The locating camera **56** is configured as a laser locating camera. The laser locating camera is configured to locate a welding position. The monitoring camera **57** is configured as a molten pool monitoring camera. The molten pool monitoring camera is configured to detect a welding trajectory of the welding gun **53** during a welding operation. In this example, the laser locating camera is configured to locate the welding position and feed back image information of the welding position to the control unit. The control unit controls the multi-axis mechanical arm **52** to operate the welding gun **53** according to the image information, so as to cause the welding gun **53** to perform the welding operation along the welding position. The molten pool monitoring camera is configured to detect the welding trajectory of the welding gun **53** during the welding operation, and feed the welding trajectory back to the control unit. The control unit feeds back the welding trajectory to the user through a display, and the user determines whether the welding is qualified according to the welding trajectory fed back. The user can also compute accuracy of the welding module **50** according to repeated welding trajectories, and maintain the welding module **50** according to the accuracy.

(47) With reference to FIG. 8, the first fitting storage module **60** is configured to store fittings. The fittings include a branch pipe section, an elbow pipe, the flange, etc.

(48) In this example, with reference to FIG. 8, the first fitting storage module **60** is configured as a storage rack. The storage rack is erected at a side of the support module **40**. The storage rack is configured to store the branch pipe, the elbow pipe, the flange, etc.

(49) In this example, with reference to FIG. 9, the assembly station further includes a material placement assembly **70**. The material placement assembly **70** is used for the fittings such as the branch pipe, the elbow pipe and the flange to be placed. The material placement assembly **70** is slidably mounted at the fourth guide rail **41**.

(50) In this example, with reference to FIG. 9, the material placement assembly **70** may adopt the following structure. The material placement assembly **70** includes a first movable seat **71**, a ninth driving member **72**, a pedestal **73** and a placement table **74**. The first movable seat **71** is slidably mounted at the fourth guide rail **41**. The pedestal **73** is mounted at the first movable seat **71** through the ninth driving member **72**. The ninth driving member **72** is configured to drive the pedestal **73** to ascend and descend. The ninth driving member **72** may drive the pedestal **73** to ascend and descend through the cylinder driving member, the hydraulic driving member or the motor driving member. The placement table **74** is mounted at the pedestal **73**. A sixth rotary shaft is arranged between the placement table **74** and the pedestal **73**. When the user pushes the placement table **74**, the placement table **74** may rotate around the sixth rotary shaft. A second rotary shaft is fixed to one of the pedestal **73** and the placement table **74** and rotates with respect to the other of the pedestal and the placement table. Thus, when the user pushes the placement table **74**, the placement table **74** may rotate around the sixth rotary shaft on the pedestal **73**. A positioning structure **75** is also arranged between the placement table **74** and the pedestal **73**. The positioning structure **75** is configured to position the placement table **74** at a preset position. The positioning structure **75** includes a plurality of positioning holes and positioning pins. The plurality of positioning holes are provided in a surface, close to the placement table **74**, of the pedestal **73** and are distributed in a circumferential manner. A through hole for the positioning pin to penetrate therethrough is provided in the placement table **74**. The positioning pin penetrates the through hole to be inserted into one of the positioning holes. The placement table **74** may be positioned at the preset position through matching of the positioning pin with the through hole and the positioning hole. The material placement assembly **70** further includes a placement frame **76**. The placement frame **76** is fixedly arranged at the placement table **74**. The placement table **74** is used for the fittings such as the elbow pipe, the flange or the branch pipe to be placed. The placement frame **76** is used for the flange to be placed. When the flange is placed on the placement table **74**, the flange is in a horizontal state, and when it is placed on the placement frame **76**, it is in an upright state. In this example, the pedestal **73** drives the placement table **74** to ascend or descend, and may simultaneously drive the placement frame **76** to ascend or descend. Thus, the fitting can be pre-aligned with the pipe section to be machined.

(51) In this example, with reference to FIG. 9, a limiting member **77** for restricting the elbow pipe is inserted into a top surface of the placement table **74**. Thus, during machining, one end of the elbow pipe is restricted, and the other end of the elbow pipe can correspond to an end of the pipe section to be machined, at which welding by the welding module **50** is performed advantageously. The limiting member **77** is configured as a limiting plate. The limiting plate is inserted into the placement table **74**. The top surface of the placement table **74** is provided with a plurality of adjustment recesses for the limiting plate to be inserted. An angle of the limiting plate on the top surface of the placement table **74** may be adjusted through the plurality of adjustment recesses, such that the limiting plate is applied to limitation on elbow pipes with different structures advantageously.

(52) In this example, with reference to FIGS. 9 and 19, the placement frame **76** may adopt the following structure. The placement frame **76** includes a fifth machine frame **761**. A bidirectional screw **762** is mounted in the fifth machine frame **761**. Two mounting rods **764** are connected to the bidirectional screw **762**. Two connection blocks **763** are in threaded connection to the bidirectional

screw **762**. A guide structure is arranged on the fifth machine frame **761**. When the bidirectional screw **762** rotates, the guide structure causes the two connection blocks **763** to get close to each other or far away from each other. The guide structure is configured as a guide hole. The two mounting rods **764** are inserted into the two connection blocks **763** respectively. The mounting rod **764** is used for the flange to be placed. Thus, when the mounting rod **764** needs to be used, the mounting rod **764** merely needs to be inserted into the connection block **763**. When the placement frame **76** is used, the placement table **74** needs to be rotated, and the placement frame **76** is arranged towards one end of the pipe section to be machined, so as to cause the flange to correspond to the pipe section to be machined. Specifically, in this example, by rotating the bidirectional screw, a space between the two mounting rods can be adjusted. Thus, the placement frame **76** can be used for flanges with different specifications to be placed, and a use effect of the disclosure is further improved.

(53) With reference to FIGS. **1**, **2** and **7**, the first transfer module **80** is configured to transfer the pipe section to be machined to the support module **40**, and then the first transfer module **80** transfers the fitting and attach the fitting to the pipe section to be machined. The welding module **50** is configured to weld fitting to the pipe section to be machined.

(54) In this example, with reference to FIG. **3**, the first transfer module **80** may adopt the following structure. The first transfer module **80** includes a driving structure **81** and a grabbing assembly. The grabbing assembly is configured to grab the pipe section to be machined, the fitting or the assembled pipe section. The driving structure **81** is configured to drive the grabbing assembly to move among the assembly station, the cutting station and the finished product station. In this example, the first transfer module **80** transfers the pipe section to be machined and the fitting, and attach the fitting to the pipe section to be machined. The operation can reduce difficulty of manual transfer of large flanges and branch pipes, improve production efficiency of the pipe section, and solve the technical problems in the prior art. In this example, the first transfer module **80** may be further configured as a transfer robot. A cut pipe section is transferred by the transfer robot from a feeding area in the first material conveying module **10** to the assembly station, or the fitting is attached by the transfer robot to the pipe section to be machined.

(55) In this example, the cut pipe section is transferred by the first transfer module **80** from the first material conveying module **10** to the support module **40**. The support module **40** supports and clamps the pipe section to be machined, and then the first transfer module **80** attaches the fitting required by a production process of the pipe section to the pipe section to be machined. After the fitting is attached to the pipe section to be machined, the welding module **50** welds the fittings to the pipe section to be machined. After one fitting is welded to the pipe section to be machined, the first transfer module **80** may transfer a next fitting and attach the fitting to the pipe section being machined, and then the welding module **50** welds the fitting and the pipe section together. In this example, the support module **40**, the welding module **50**, the first fitting storage module **60** and the first transfer module **80** are not limited.

(56) With reference to FIG. **2**, the finished product station is arranged downstream of the assembly station, and the finished product station includes a second transfer module **90** and a finished product storage module **100**.

(57) The finished product storage module **100** is configured to store the assembled pipe section.

(58) In this example, with reference to FIG. **12**, the finished product storage module **100** may adopt the following structure. The finished product storage module **100** includes a material frame body **110** and a material holder **120**. The material frame body **110** is configured as a rectangular frame structure and is provided with an opening at a top. Further, four side surfaces and a bottom surface of the material frame body **110** may be configured to have hollowed structures. The material holder **120** is fixedly arranged at the top of the material frame body **110**. The top of the material holder **120** is configured as a serrated structure. An interior of the material frame body **110** is used for a pipe section with a smaller structure to be placed. The top of the material holder **120** is used for a

larger pipe section to be placed. The outside of the material frame body **110** is provided with a transfer area. A transfer apparatus may transfer the material frame body **110** through the transfer area.

(59) In this example, with reference to FIG. **12**, a bottom of the material frame body **110** is provided with a plurality of first support legs **130**. The plurality of first support legs **130** are fixedly arranged at the bottom of the material frame body **110** to suspend the bottom of the material frame body **110**.

(60) In this example, with reference to FIG. **12**, the transfer area is arranged at the bottom of the material frame body **110**. In this example, the transfer area is located at the bottom of the material frame body **110**, such that the material frame body **110** can be applied to a common transfer tool such as a forklift or an automated guided vehicle (AGV). In addition, the forklift and the AGV are more flexible to use and occupy a small area. A plurality of limiting blocks **140** are fixedly arranged at the bottom of the material frame body **110**. The plurality of the limiting blocks **140** define the transfer area. The limiting block **140** is fixedly arranged on the material frame body **110**. Since the material frame body **110** adopts the hollowed structure, the limiting block **140** may be fixedly arranged on the material frame body **110** through welding.

(61) The second transfer module **90** is configured to transfer the finished product storage module **100**, so as to move the finished product storage module **100** to the preset position.

(62) In this example, with reference to FIG. **12**, the second transfer module **90** may adopt the following structure, and the second transfer module **90** is configured as the AGV or the forklift or the intelligent transfer robot.

(63) In this example, the first transfer module **80** places the assembled pipe section into the finished product storage module **100**. After a particular number of assembled pipe sections are placed in the finished product storage module **100**, the finished product storage module **100** is transferred to the preset position by the second transfer module **90**. The preset position is a painted place, a storage place, etc. In this example, the second transfer module **90** and the finished product storage module **100** are not specifically limited.

(64) According to the technical solution of the disclosure, the first transfer module **80** is adopted to transfer the pipe section to be machined and the fitting, and attach the fitting to the pipe section to be machined. After the fitting is attached to the pipe section to be machined, the fitting and the pipe section to be machined are welded together by the welding module **50**. Under the action of the first transfer module **80**, manual transfer of fittings with the large structures such as flanges and elbow pipes is avoided, and manual attachment of the fitting to the pipe section to be machined is avoided. Difficulty of manual transfer is further reduced, the production efficiency of the pipe section is improved, and the technical problems in the prior art is solved.

(65) In an example, with reference to FIG. **1**, the intelligent machining line for pipe sections further includes a derusting station. The derusting station is arranged upstream of the cutting station. The derusting station includes a derusting module **200**, a second material conveying module **300** and a third material conveying module **400**.

(66) The second material conveying module **300** is configured to convey a pipe section to be derusted to the derusting module **200**.

(67) In this example, the second material conveying module **300** is configured as a steel pipe translation assembly.

(68) The derusting module **200** is configured to derust the pipe section to be derusted.

(69) In this example, with reference to FIGS. **13** and **14**, the derusting module **200** may adopt the following structure. The derusting module **200** includes a sixth machine frame **210**, a laser emitter **220** and a controller. The sixth machine frame **210** is provided with a feeding opening **211** and a discharging opening **212**. The sixth machine frame **210** is provided with a derusting position between the feeding opening **211** and the discharging opening **212**. The feeding opening **211** and the discharging opening **212** are used for the pipe section to get in and out of the derusting position

respectively. The laser emitter **220** is arranged at the sixth machine frame **210**. An emitting end of the laser emitter **220** is arranged towards the derusting position. The controller is arranged at the sixth machine frame **210**. The controller is electrically connected to the laser emitter **220**. The controller is configured to control an output power of the laser emitter **220**. In this example, the laser emitter **220** is arranged, and the laser emitter **220** emits laser towards the derusting position. When the pipe section needs to be derusted, the pipe section is sent into the sixth machine frame **210** from the feeding opening **211** at first, and the pipe section is controlled to pass through the derusting position. In this case, the laser emitted by the laser emitter **220** can quickly heat a rusting substance on the pipe section to a vaporized or molten state, such that the rusting substance is peeled off from a surface of the pipe section, and an efficient and thorough derusting effect is achieved. In this case, the pipe section continuously moves from the feeding opening **211** to the discharging opening **212**, and continuously passes through the derusting position. The laser emitter **220** maintains the emitting end opposite the derusting position, and then the pipe section leaves the sixth machine frame **210** from the discharging opening **212**. Thus, the surface of the pipe section is derusted. The output power of the laser emitter **220** is controlled by the controller for pipe sections with different specifications, such that energy carried by the laser can better adapt to a current rusting degree of pipe section, and a derusting effect is guaranteed. The sixth machine frame **210** includes a housing and a frame. The feeding opening **211** and the discharging opening **212** are provided in the housing. In addition, flexible baffles are arranged at positions of the feeding opening **211** and the discharging opening **212**, so as to prevent the rusting substance at the derusting position from spilling into the surrounding environment.

(70) In this example, the derusting module **200** further includes a tenth driving member. The tenth driving member is arranged at the sixth machine frame **210** and is electrically connected to the controller. The tenth driving member is in driving connection to the laser emitter **220**, and is configured to adjust a space from the laser emitter **220** to the derusting position. The tenth driving member is configured as a motor linear driving module.

(71) In this example, the derusting module **200** further includes a ranging sensor arranged at the laser emitter **220**. The ranging sensor is electrically connected to the controller, and is configured to measure a distance from the laser emitter **220** to the derusting position. In this way, the user can accurately and timely adjust a position of the laser emitter **220** according to the space from the laser emitter **220** to the derusting position fed back by the ranging sensor, and guarantee that a length of the laser in an axial direction of the pipe section conforms to a diameter of a current pipe section. Thus, accuracy and reliability of laser derusting are improved, adjusting can be implemented to a most suitable position for derusting with minimum energy consumption, cost is reduced, and the derusting effect is further guaranteed.

(72) In this example, the derusting module **200** further includes a cooling device. The cooling device is arranged at the sixth machine frame **210** and is configured to cool the laser emitter **220**. It should be noted that the laser emitter **220** is likely to generate a large amount of heat when emitting the laser. In a process of derusting, the cooling device is started to cool the laser emitter **220**. Thus, the laser emitter **220** is guaranteed at an appropriate temperature and influence of overheating on the derusting effect is avoided. Specifically, the cooling device may be configured as a water cooling device or an air cooling device.

(73) In this example, the derusting module **200** further includes a dust collector, a dust suction pipe section of the dust collector is arranged opposite the derusting position, and the dust collector is electrically connected to the controller. It should be noted that in the process of derusting, the laser vaporizes the rusting substance with heat, which inevitably produces dusty gas. In this way, the dust collector can suck this part of the gas away, and thus prevent the condition that the gas diffuses to the derusting environment, pollutes the derusted pipe section or endangers health of technicians.

(74) In this example, with reference to FIG. 13, the derusting module **200** further includes a filter **230**. The filter **230** is in communication with the dust collector. The filter **230** is electrically

connected to the controller, and is configured to filter the air in a derusting apparatus. Thus, the filter **230** filters the vaporized rusting substance, so as to guarantee that the rusting substance satisfies emission standards before being emitted, satisfies requirements for environmental protection, and avoids endangering the health of the technicians. Specifically, when the laser emitter **220** is in a running state, the controller synchronously controls the dust collector and the filter **230** to run, so as to minimize a content of the vaporized rusting substance in the environment. The filter **230** includes an exhaust system and a filtering structure. The exhaust system is configured to promote a gas flow, so as to cause the gas in the environment to inevitably flow through a filtering structure. Thus, a purification effect is guaranteed.

(75) In this example, with reference to FIG. **14**, the derusting module **200** further includes a waste hopper **240**. An inlet of the waste hopper **240** is provided upwards and located below the derusting position. The waste hopper **240** is in communication with the filter **230**. It should be noted that besides the vaporized part, the rusting substance on the pipe section also peels off partially. The waste hopper **240** is arranged to collect the peeled rusting substance, cleanliness of the derusting environment is guaranteed, the technicians clean the derusting apparatus advantageously after the derusting operation is completed, and user experience is improved.

(76) The third material conveying module **400** is configured to convey or store the derusted pipe section.

(77) In this example, the third material conveying module **400** is configured as a steel pipe translation assembly.

(78) In this example, the pipe section to be cut can be derusted before being cut through the derusting station. Thus, pollution of the pipe section to be cut in a cutting process can be reduced, rust flying can be avoided, and the working environment can be improved. In this example, the second material conveying module **300**, the third material conveying module **400** and the derusting module **200** are not limited. A derusting method of the derusting module **200** may be laser derusting, physical derusting, chemical derusting, etc.

(79) In an example, with reference to FIGS. **6** and **11**, the intelligent machining line for pipe sections further includes a temporary storage station. The temporary storage station is arranged between the derusting station and the cutting station. The temporary storage station includes a third transfer module **500** and a fourth material conveying module **600**.

(80) In this example, the third transfer module **500** is configured as a steel pipe transfer assembly.

(81) The third transfer module **500** is mounted at the fourth material conveying module **600**. The fourth material conveying module **600** is arranged corresponding to the first material conveying module **10**, and is located at a side of the third material conveying module **400**. The third transfer module **500** is configured to convey the pipe section on the third material conveying module **400** to the fourth material conveying module **600**. The fourth material conveying module **600** is configured to convey the pipe section to the first material conveying module **10**.

(82) In this example, the fourth material conveying module **600** is configured as a steel pipe translation assembly. The fourth material conveying module **600** is arranged close to the third material conveying module **400**, and is arranged parallel to the third material conveying module **400**.

(83) In this example, the pipe section derusted by the derusting module **200** enters the third material conveying module **400**, and is conveyed on the third material conveying module **400**. When conveyed to a position by the third material conveying module **400**, the third transfer module **500** transfers the pipe section on the third material conveying module **400** to the fourth material conveying module **600**, and then the fourth material conveying module **600** conveys the pipe section towards the first material conveying module **10**, and conveys the pipe section into the cutting station.

(84) Further, in an example, with reference to FIG. **11**, one end of the third material conveying module **400** is provided with a first sensor **910**, and the other end of the third material conveying

module is provided with a second sensor **920**. The first sensor **910** is arranged close to the derusting module **200**. In this example, the first sensor **910** is configured to obtain incoming material information. When the pipe section derusted by the derusting module **200** enters the third material conveying module **400**, the first sensor **910** may sense entry of the pipe section into the third material conveying module **400**. In this case, the third material conveying module **400** starts to convey the pipe section. When one end of the pipe section corresponds to the second sensor **920** on the third material conveying module **400**, the second sensor **920** feeds back to the third material conveying module **400**, the third material conveying module **400** stops conveying the pipe section, and the pipe section is stored on the third material conveying module **400**. In addition, when the pipe section is stored on the third material conveying module **400**, the third material conveying module **400** also feeds back to the second material conveying module **300** and the derusting module **200**, the second material conveying module **300** stops conveying the pipe section to the derusting module **200**, and the derusting module **200** stops derusting. Alternatively, the second material conveying module **300** decreases a conveying speed and the derusting module **200** decreases a derusting speed. On the contrary, when the second sensor **920** does not sense existence of the pipe section on the third material conveying module **400** for a long time, and feeds back information to the second material conveying module **300** and the derusting module **200**, the second material conveying module **300** increases the conveying speed and the derusting module **200** increases the derusting speed. A third sensor **930**, a fourth sensor **940** and a fifth sensor **950** are uniformly arranged on the fourth material conveying module **600**. In this example, the third sensor **930**, the fourth sensor **940** and the fifth sensor **950** are arranged at two ends and a middle position of the fourth material conveying module **600** respectively. Thus, a state of the material left on the fourth conveying module **600** can be fully sensed, such that the third transfer module **500** transfers the pipe section on the third material conveying module **400** to the fourth material conveying module **600** advantageously.

(85) Further, in this example, with reference to FIG. 11, a sixth sensor **960** is arranged at an end, close to the fourth material conveying module **600**, of the first material conveying module **10**. Thus, the fourth material conveying module **600** conveys the pipe section to be cut to the first material conveying module **10** in the cutting station. In this case, the sixth sensor **960** obtains first incoming material information and feeds such information back to the first material conveying module **10**. In this case, the first material conveying module **10** drives the pipe section to move towards the clamping module **20** until the pipe section to be cut come into contact with the clamping module **20**, then the pipe section to be cut is clamped by the clamping module **20**, and then the pipe section to be cut is cut by the cutting module **30**.

(86) The feeding area is arranged on the first material conveying module **10**. The first material conveying module **10** is configured to convey the cut pipe section to the feeding area. The sixth sensor **960** is located in the feeding area. The sixth sensor **960** is electrically connected to the first transfer module **80**. That is to say, the feeding area is close to the fourth material conveying module **600**. When the pipe section to be cut is divided into a plurality of pipe sections to be machined, the user may operate the first material conveying module **10** to convey the divided pipe sections to be machined to the feeding area one by one. Whenever one pipe section to be machined is conveyed to the feeding area, the sixth sensor **960** obtains second incoming material information and feeds the second incoming material information back to the first transfer module **80** in the assembly station. In this case, the first transfer module **80** arrives at the feeding area in the first material conveying module **10**, and transfers the pipe section to be machined to the support module **40** in the assembly station.

(87) In an example, the first transfer module **80** may also adopt the following structure. The first transfer module **80** further includes a truss platform **83**.

(88) In this example, with reference to FIG. 3, the driving structure is mounted at the truss platform **83**. The grabbing assembly is mounted at the driving structure. The driving structure is configured

to drive the grabbing assembly to move, so as to transfer the pipe section to be machined or the first fitting to the support module **40**.

(89) In this example, with reference to FIG. 3, the truss platform **83** may adopt the following structure. The truss platform **83** includes a seventh machine frame **831** having a rectangular ring structure and a plurality of second support legs **832**. The plurality of second support legs **832** are fixedly arranged at preset positions. The preset position may be selected according to actual demand from the user. The seventh machine frame **831** is fixedly arranged on the plurality of second support legs **832**. The seventh machine frame **831** and the plurality of second support legs **832** may be connected through welding or bolt locking.

(90) In this example, with reference to FIG. 3, the driving structure may adopt the following structure. The driving structure includes a first driving assembly **811**, a second driving assembly **812** and a third driving assembly **813**.

(91) In this example, with reference to FIG. 3, the first driving assembly **811** includes a movable beam **8111** and a first motor linear module **8112**. The movable beam **8111** is slidably mounted at the seventh machine frame **831** through the first motor linear module **8112**. In this example, the movable beam **8111** moves in the direction st3.

(92) In this example, with reference to FIG. 3, the second driving assembly **812** includes a second movable seat **8121** and a second motor linear module **8122**. In this example, the movable beam **8111** is configured as a rectangular beam, and the second movable seat **8121** is movably mounted at the movable beam **8111** through the second motor linear module **8122**. In this example, the second movable seat **8121** moves in the direction st1.

(93) In this example, with reference to FIG. 3, the third driving assembly **813** includes a second mounting frame **8131**, a movable rod **8132**, a quick release plate **8133**, a guide member **8134** and a third motor linear module **8135**. The second mounting frame **8131** is fixedly arranged at the second movable seat **8121** in the second driving assembly **812**. The second mounting frame **8131** is fixedly arranged at the second movable seat **8121** through bolt locking. The movable rod **8132** is arranged at the second mounting frame **8131**. The movable rod **8132** is configured as a rigid rod. The quick release plate **8133** is fixedly arranged at an end of the movable rod **8132**, and is used for the grabbing assembly to be mounted. The guide member **8134** connects the second mounting frame **8131** to the movable rod **8132**, such that the movable rod **8132** moves on the second mounting frame **8131**. The second mounting frame **8131** may be configured as a cylindrical frame. The cylindrical frame may be a cylinder or a prism. The movable rod **8132** is movably mounted in the second mounting frame **8131** through the third motor linear module **8135**, and the movable rod **8132** also moves in the direction st2. In this example, the quick release plate **8133** is fixedly arranged at an end, close to the ground, of the movable rod **8132** through bolt locking. The grabbing assembly is connected to the quick release plate **8133** through bolt locking. When the disclosure needs to replace different grabbing assemblies according to actual demand, the grabbing assembly may be separated from the quick release plate **8133**.

(94) In this example, with reference to FIG. 1, at least two driving structures are arranged, and each driving structure is connected to the grabbing assembly.

(95) In this example, with reference to FIG. 16, the grabbing assembly may adopt the first grabbing assembly **82**. The first grabbing assembly **82** has the following structure. The first grabbing assembly **82** includes a second mounting frame **821**, a third rotary shaft **822**, a fourth rotary shaft **823** and an adsorption portion **824**.

(96) In this example, the fourth rotary shaft **823** is rotatably connected to a connector **827**, and is connected to the third rotary shaft **822** at an included angle through the connector **827**. The third rotary shaft **822** is rotatably connected to the second mounting frame **821**. The adsorption portion **824** is connected to the fourth rotary shaft **823**. The adsorption portion **824** may rotate around rotation axes of the third rotary shaft **822** and the fourth rotary shaft **823**. Specifically, the adsorption portion **824** rotates around the rotation axis of the fourth rotary shaft **823** and swings

around the rotation axis of the third rotary shaft **822**.

(97) In this example, the first grabbing assembly **82** further includes a fifth driving motor **825** arranged on the second mounting frame **821** and a sixth driving motor **826** arranged on the connector **827**. The fifth driving motor **825** is in driving connection to the third rotary shaft **822**. The third rotary shaft **822** extends horizontally. The connector **827** is fixed to the third rotary shaft **822**. The sixth driving motor **826** is in driving connection to the fourth rotary shaft **823**. The fourth rotary shaft **823** extends vertically, and is rotatably connected to the connector **827**.

(98) In this example, the adsorption portion **824** is configured as an electromagnet. The adsorption portion **824** includes a plurality of support arms distributed in a circumferential direction. At a junction of the support arms, the adsorption portion **824** is connected to a rotary mechanism. A lower surface of the support arm is provided with a scale **828**. The scale **828** extends in parallel to a corresponding support arm. Spaces between the same scale value of scales **828** and the junction of the plurality of support arms are equal. A lower end of the adsorption portion **824** is provided with a hook.

(99) In an example, with reference to FIG. 3, the grabbing assembly may also adopt a second grabbing assembly **84**. The second grabbing assembly **84** has the following structure. The second grabbing assembly **84** includes an eighth machine frame **841**, two first clamping jaws **842** and a fourth driving assembly. In this example, the two oppositely arranged first clamping jaws **842** are slidably arranged on the eighth machine frame **841**. The fourth driving assembly is fixedly arranged on the eighth machine frame **841**. The fourth driving assembly is configured to make the two first clamping jaws **842** move close to or away from each other, such that the two first clamping jaws **842** clamp the pipe section.

(100) In this example, with reference to FIGS. 2 and 3, two driving structures are arranged. The two driving structures are connected to the grabbing assembly. Thus, a use effect of the first transfer module **80** can be improved, the first transfer module **80** can transfer the pipe section and the fitting, use flexibility can be greatly improved, and difficulty of manual transfer can be effectively solved.

(101) In an example, with reference to FIGS. 2 and 10, the assembly station further includes a power module **700** and a second fitting storage module **800**. The power module **700** and the second fitting storage module **800** are both located outside the truss platform **83**. The second fitting storage module **800** is configured to store a second fitting. The power module **700** is configured to transfer the second fitting to the support module **40**. The welding module **50** is configured to weld the second fitting to the pipe section to be machined.

(102) In this example, with reference to FIG. 10, the power module **700** includes a mechanical arm **710** and a power device **750**.

(103) In this example, with reference to FIG. 10, the mechanical arm **710** may adopt the following structure. The mechanical arm **710** includes a third mounting frame **720**, a third grabbing assembly **730** and a fourth grabbing assembly **740**. The third mounting frame **720** is configured as a frame. A connection seat is fixedly arranged at the third mounting frame **720**. The connection seat is connected to the power device **750**. The third grabbing assembly **730** includes two second clamping jaws **731** and an eleventh driving member **732**. The two second clamping jaws **731** are movably mounted at the third mounting frame **720**. The eleventh driving member **732** is fixedly arranged at the third mounting frame **720**. The eleventh driving member **732** is configured to drive the two second clamping jaws **731** to move close to or away from each other, such that the third grabbing assembly **730** clamps or unclamps materials. The fourth grabbing assembly **740** includes a magnetic attraction member **741**. The magnetic attraction member **741** is mounted at the third mounting frame **720**. The magnetic attraction member **741** is configured to make the fourth grabbing assembly **740** magnetically attract materials. A mounting pipe is fixedly arranged on the third mounting frame **720**. The magnetic attraction member **741** is mounted at the mounting pipe.

(104) In this example, with reference to FIG. 10, the power device **750** includes a power arm **760**,

and the power arm **760** includes a connection rod **761**, an operation rod **762** and a twelfth driving member **763**. The connection rod **761** is hinged to the connection seat in the mechanical arm **710**. The twelfth driving member **763** is configured as a driving cylinder. The twelfth driving member **763** is mounted at an operation rod **762**. A stretchable end of the twelfth driving member **763** is hinged to the connection seat. Thus, when the twelfth driving member **763** stretches, the mechanical arm **710** may be turned over through an angle around a hinged joint with the connection rod **761**, and the mechanical arm **710** may be turned over by 90 degrees.

(105) In an example, with reference to FIG. **10**, the second fitting storage module **800** includes a storage table **810** and a third support leg **820**. The third support leg **820** is fixedly arranged at a bottom of the storage table **810**. The third support leg **820** is fixed to the storage table **810** through welding. The storage table **810** is used for the fittings such as the branch pipe, the elbow pipes and the flange to be placed.

(106) In an example, with reference to FIGS. **10** and **18**, the intelligent machining line for pipe sections further includes a positioning plate **101** matching the plurality of first support legs **130** and the plurality of third support legs **820**. In order to place the material frame body **110** and the storage table **810** at the preset position advantageously, the user may fix the positioning plate **101** to the preset position. Thus, in a subsequent use process, the storage table **810** and the material frame body **110** may be placed at the preset positions directly according to the positioning plate **101**. Thus, the first transfer module **80** and the power module **700** can work advantageously.

(107) In this example, with reference to FIG. **18**, a top of the positioning plate **101** is provided with a recess **102**. Balls **201** are embedded in bottoms of the first support leg **130** and the third support leg **820**. When the ball **201** falls into the recess **102**, the first support leg **130** or the third support leg **820** may be limited in the positioning plate **101** under the self-weight of the material frame body **110** or the storage table **810**. Thus, the material frame body **110** and the storage table **810** may be positioned at the preset positions.

(108) In this example, with reference to FIG. **10**, a bottom of the storage table **810** is further provided with a transfer area. In the intelligent machining line for pipe sections, according to the preset positions of the material frame body **110** and the storage table **810**, a route for the transfer apparatus may be planned, and the transfer apparatus transfers the material frame body **110** and the storage table **810** advantageously. In addition, when no fitting exists on the storage table **810**, the storage table **810** may be replaced by the transfer apparatus, so as to supplement the fitting.

(109) In an example, with reference to FIG. **1**, two finished product stations are configured, one of the finished product stations is located inside the truss platform **83**, and the other one of the finished product stations is located outside the truss platform **83**. In this example, the two finished product stations are arranged in order that the production line transfers the pipe section advantageously, such that flow efficiency of the production line is improved. The finished product station outside the truss platform **83** may be used as a waiting station to replace the station inside the truss platform **83**, so as to improve the flow efficiency of the production line.

(110) In this example, with reference to FIGS. **1** and **2**, for a first finished product station arranged inside the truss platform **83**, in actual use, the material frame body **110** carrying the fittings may be transferred to the first finished product station by the transfer apparatus. Then the fittings in the material frame body **110** are taken out by the first transfer module **80** and placed in the plurality of first fitting storage modules **60** respectively, so as to supplement the fitting.

(111) In an example, the intelligent machining line for pipe sections further includes a visual assembly (not shown). The visual assembly includes a plurality of cameras, the plurality of cameras are mounted on the truss platform **83**, and the plurality of cameras are configured to acquire image information of the intelligent machining line for pipe sections.

(112) In this example, the intelligent machining line for pipe sections is provided with a master control unit, and the visual assembly is connected to the master control unit. The image information acquired by the plurality of cameras is fed back to the master control unit, and working efficiency

of modules in the intelligent machining line for pipe sections is controlled by the master control unit.

(113) For example, after the camera acquires the situation that the pipe section to be machined on the support module **40** is finished, the master control unit may drive the first transfer module **80** to transfer the pipe section to be machined from the feeding area to the support module **40**. When no fittings exist on the first fitting storage module **60**, the fitting may be supplemented through the transfer apparatus.

(114) The disclosure further provides a method for machining pipe sections. The method for machining pipe sections is applied to the intelligent machining line for pipe sections. Reference is made to the example for a specific structure of the intelligent machining line for pipe sections. Since the intelligent machining line for pipe sections adopts all technical solutions of all the examples described above, the intelligent machining line for pipe sections has at least all the beneficial effects brought by the technical solutions of the examples described above, and will not be repeated herein. The method for machining pipe sections includes: **S10**, the pipe section is cut by the cutting module **30**. **S20**, the cut pipe section is transferred by the first transfer module **80** to the support module **40**, and the cut pipe section is taken as a pipe section to be machined. **S30**, the fitting required for finished product pipe section production is moved by the first transfer module **80** to a position outside the pipe section to be machined, and the fitting is made by the first transfer module to attach to and abut against the pipe section to be machined. **S40**, the fitting is welded by the welding module **50** to the pipe section to be machined. **S50**, welding of one fitting is completed, then, a second fitting required for the pipe section production is continuously transferred by the first transfer module **80**, the second fitting is made by the first transfer module to attach to and abut against the pipe section to be machined, and the second fitting is welded by the welding module **50** to the pipe section to be machined until the pipe section is assembled. **S60**, an assembled pipe section is moved by the first transfer module **80** to the finished product storage module **100**. **S70**, a particular number of assembled pipe sections are stored in the finished product storage module **100**, and then the finished product storage module **100** is transferred by the second transfer module **90** to a preset position.

(115) According to the technical solution of the disclosure, the fittings (an elbow pipe, a branch pipe and a flange, etc.) are transferred by the first transfer module **80**, manual transfer is replaced by the first transfer module **80**, and the fittings are attached to the pipe section to be machined. Thus, difficulty of a manual operation can be reduced, machining efficiency of the pipe section can be improved, and the technical problems in the prior art can be solved.

(116) In an example, the method for machining pipe sections further includes **S80**. **S80** is before **S50**, and **S80** includes:

(117) When one end of the pipe section to be machined is in contact with the clamping module **20**, and the fitting needs to be fitted to the other end of the pipe section to be machined, the fittings on the second fitting storage module **800** may be transferred by the power module **700** to the placement table **74** or the placement frame **76** in the material placement assembly **70**. In this case, a height of the placement table **74** and a height of the placement frame **76** are adjusted by the ninth driving member **72**, so as to pre-align the fitting with the pipe section to be machined. Then, the first movable seat **71** is moved so as to cause the first movable seat **71** to get close to the end of the pipe section to be machined, and the fitting to abut against the end of the pipe section to be machined, and the welding module **50** welds the fitting to the pipe section to be machined in this case.

(118) Under the action of **S80**, the production efficiency of the pipe section machining can be further improved, and manual work can be reduced.

(119) In an example, the method for machining pipe sections further includes **S90**. **S90** is before **S10**, and **S90** includes:

(120) The pipe section to be cut is derusted by a derusting module **200**.

(121) In this example, the derusting module **200** performs laser derusting, and the derusting module **200** may also perform grinding derusting, derusting agent derusting, etc. besides the laser derusting. The pipe section to be cut is derusted before being cut, rust on the surface can be removed, pollution in subsequent cutting and conveying can be reduced, the working environment can be improved, and a lot of rust in a subsequent operation area can be avoided.

Claims

1. An intelligent machining line for pipe sections, comprising: a cutting station, an assembly station, a finished product station, a derusting station, a temporary storage station, and sensors, wherein the cutting station comprises a first conveyor, a clamping module, and a cutting module, wherein the first conveyor comprises a machine frame and a roller mounted on the machine frame, the first conveyor is configured to convey and support a pipe section to be cut, the clamping module is configured to clamp the pipe section to be cut and drive the pipe section to be cut to rotate on the first conveyor, and the cutting module is configured to cut the pipe section to be cut, and the cutting module is slidably arranged at a side of the first conveyor and moves along an axial direction of the pipe section; the assembly station is arranged downstream of the cutting station and comprises a support module, a welding module, a first fitting storage module, and a first transfer module, wherein the support module is configured to support a pipe section to be machined, and is capable of clamping and driving the pipe section to be machined to rotate, the first fitting storage module is configured to store a first fitting, the first transfer module is configured to transfer the pipe section to be machined to the support module and attach the first fitting to the pipe section to be machined, the welding module is configured to weld the first fitting to the pipe section to be machined to obtain an assembled pipe section, and the first transfer module comprises a driving structure and a grabbing assembly, wherein the grabbing assembly is configured to grab the pipe section to be machined, the first fitting or the assembled pipe section, and the driving structure is configured to drive the grabbing assembly to move among the assembly station, the cutting station and the finished product station; the finished product station is arranged downstream of the assembly station and comprises a second transfer module and a finished product storage module, wherein the finished product storage module is configured to store the assembled pipe section, and the second transfer module is configured to transfer the finished product storage module, so as to move the finished product storage module to a preset position; the derusting station is arranged upstream of the cutting station and comprises a derusting module, a second conveyor, and a third conveyor, wherein the derusting module is configured to derust the pipe section to be derusted; and the temporary storage station is arranged between the derusting station and the cutting station and comprises a fourth conveyor, wherein the fourth conveyor is arranged corresponding to the first conveyor, and is located at a side of the third conveyor; wherein the third conveyor is provided with a first sensor and a second sensor, and a third sensor, a fourth sensor and a fifth sensor are arranged on the fourth conveyor; wherein an end of the first conveyor is provided with a sixth sensor; wherein a feeding area is provided on the first conveyor, the first conveyor is configured to convey a cut pipe section to the feeding area, the sixth sensor is located in the feeding area, and the sixth sensor is electrically connected to the first transfer module; wherein the first transfer module further comprises a truss platform, the driving structure is mounted at the truss platform, the grabbing assembly is mounted at the driving structure, and the driving structure is configured to drive the grabbing assembly to transfer the pipe section to be machined or the first fitting to the support module; and wherein the assembly station further comprises a power module and a second fitting storage module, wherein the power module and the second fitting storage module are both located outside the truss platform, the second fitting storage module is configured to store a second fitting, the power module is configured to transfer the second fitting to the support module, and the welding module is configured to weld the second fitting to the pipe section to be machined.

2. The intelligent machining line for pipe sections according to claim 1, wherein the finished product station comprises a first and a second finished product stations, one of the first and second finished product stations is located inside the truss platform, and the other one of the first and second finished product stations is located outside the truss platform.
3. The intelligent machining line for pipe sections according to claim 2, further comprising a visual assembly, wherein the visual assembly comprises a plurality of cameras, the plurality of cameras are mounted on the truss platform, and the plurality of cameras are configured to acquire image information of the intelligent machining line for pipe sections.
4. A method for machining pipe sections using the intelligent machining line for pipe sections according to claim 1, comprising: cutting the pipe section by the cutting module to obtain a cut pipe section; transferring the cut pipe section by the first transfer module, to the support module, with the cut pipe section serving as the pipe section to be machined; moving the first fitting to a position outside the pipe section to be machined by the first transfer module, and making the fitting attach to and abut against the pipe section to be machined; welding the first fitting to the pipe section to be machined by the welding module; transferring the second fitting by the first transfer module, and making the second fitting attach to and abut against the pipe section to be machined, and welding the second fitting to the pipe section to be machined by the welding module to obtain an assembled pipe section; moving the assembled pipe section to the finished product storage module by the first transfer module; and storing the assembled pipe section in the finished product storage module, and then transferring the finished product storage module to the preset position by the second transfer module.
5. An intelligent machining line for pipe sections, comprising: a cutting station, wherein the cutting station comprises a first material conveying module, a clamping module, and a cutting module, wherein the first material conveying module is configured to convey and support a pipe section to be cut, the clamping module is configured to clamp the pipe section to be cut and drive the pipe section to be cut to rotate on the first material conveying module, and the cutting module is configured to cut the pipe section to be cut, and the cutting module is slidably arranged at a side of the first material conveying module, and moves along an axial direction of the pipe section; an assembly station, wherein the assembly station is arranged downstream of the cutting station, and the assembly station comprises a support module, a welding module, a first fitting storage module, and a first transfer module, wherein the support module is configured to support a pipe section to be machined, and is capable of clamping and driving the pipe section to be machined to rotate, the first fitting storage module is configured to store a first fitting, the first transfer module is configured to transfer the pipe section to be machined to the support module and attach the first fitting to the pipe section to be machined, and the welding module is configured to weld the first fitting to the pipe section to be machined; and a finished product station, wherein the finished product station is arranged downstream of the assembly station, and the finished product station comprises a second transfer module and a finished product storage module, wherein the finished product storage module is configured to store an assembled pipe section, and the second transfer module is configured to transfer the finished product storage module, so as to move the finished product storage module to a preset position, wherein the first transfer module comprises a driving structure and a grabbing assembly, wherein the grabbing assembly is configured to grab the pipe section to be machined, the first fitting or the assembled pipe section, and the driving structure is configured to drive the grabbing assembly to move among the assembly station, the cutting station and the finished product station; the intelligent machining line for pipe sections further comprises a derusting station, wherein the derusting station is arranged upstream of the cutting station, and the derusting station comprises a derusting module, wherein the derusting module is configured to derust the pipe section to be derusted; the intelligent machining line for pipe sections further comprises a temporary storage station, wherein the temporary storage station is arranged between the derusting station and the cutting station; an end of the first material conveying module is

provided with a sensor; a feeding area is provided on the first material conveying module, the first material conveying module is configured to convey a cut pipe section to the feeding area, the sensor is located in the feeding area, and the sensor is electrically connected to the first transfer module; the first transfer module further comprises a truss platform, the driving structure is mounted at the truss platform, the grabbing assembly is mounted at the driving structure, and the driving structure is configured to drive the grabbing assembly to move, so as to transfer the pipe section to be machined or the first fitting to the support module; and the assembly station further comprises a power module and a second fitting storage module, wherein the power module and the second fitting storage module are both located outside the truss platform, the second fitting storage module is configured to store a second fitting, and the power module is configured to transfer the second fitting to the support module, and the welding module is configured to weld the second fitting to the pipe section to be machined.
