

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12410021
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Alexander; Paul W. et al.

Deployable truck ramp with bladders

Abstract

A deployable ramp is provided for a cargo loading system of a vehicle. The ramp includes one or more rigid element having a surface for supporting a load. The ramp further includes one or more bladders defining a chamber that is fluidly connected to an outlet of a compressor. The chamber is adapted to receive a fluid from the compressor. The bladder is attached to rigid element, and the at bladder is movable to a collapsed state where the chamber has a first volume. The bladder is further movable to an expanded state where the chamber has a second volume and contains a pressurized fluid for supporting the rigid element, in response to the bladder receiving the fluid from the compressor. The second volume is higher than the first volume.

Inventors: Alexander; Paul W. (Ypsilanti, MI), Kim; Wonhee Michael (Royal Oak, MI), Kollar; Craig A. (Sterling Heights, MI), Polewarczyk; Joseph M. (Lake Orion, MI), Shah; Bhavesh (Troy, MI), Casalduc; Rafael Gabriel (Detroit, MI)

Applicant: GM Global Technology Operations LLC (Detroit, MI)

Family ID: 91951233

Assignee: GM GLOBAL TECHNOLOGY OPERATIONS LLC (Detroit, MI)

Appl. No.: 18/165474

Filed: February 07, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240262641 A1	Aug. 08, 2024

Publication Classification

Int. Cl.: B65G69/28 (20060101); B60P1/43 (20060101); B62D33/027 (20060101)

U.S. Cl.:

CPC **B65G69/28** (20130101); **B60P1/43** (20130101); **B62D33/0273** (20130101);

Field of Classification Search

CPC: B65G (69/28); B65G (69/30); B62D (33/0273); B60P (1/43)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5184366	12/1992	Rawdon	414/535	B64C 1/22
6192541	12/2000	Castelli	405/218	E01D 15/24
10687634	12/2019	Kim	N/A	B60N 2/914
11572949	12/2022	Kim	N/A	F16J 3/041
2003/0082036	12/2002	Carawan	414/527	B60P 1/00
2019/0106916	12/2018	Sutherland	N/A	E05B 51/02
2021/0086597	12/2020	Yen	N/A	B60J 7/064
2021/0114507	12/2020	Alexander	N/A	B60P 7/04
2022/0212858	12/2021	Krajewski	N/A	B62D 25/06
2024/0227653	12/2023	Minjeur	N/A	B60P 1/43

Primary Examiner: Joerger; Kaitlin S

Attorney, Agent or Firm: Vivacqua Crane, PLLC

Background/Summary

INTRODUCTION

(1) The present disclosure relates to systems and methods for loading and unloading vehicles, and more particularly to a deployable ramp with bladders.

(2) Automotive manufacturers are continuously investigating accessories for improving the usability and versatility of cargo beds, such as truck beds. The truck beds can have a substantial amount of cargo capacity for transporting various types of cargo (e.g., motorcycles, all-terrain vehicles, utility-terrain vehicles, outdoor power equipment, such as riding lawn mowers, lawn aerators, and tractors, large furniture, appliances, all construction materials, such as gravel, topsoil, sand, stones, mulch, and the like). Occupants may use hand carts, dollies, and wheelbarrows, and ramps to load and unload the cargo that do not already have their own wheels. Certain loading ramps may have slip-resistant surfaces and arched configurations for loading convenience. Transporting these ramps from a loading site to an unloading site can occupy storage space in the vehicle that may otherwise be used to transport additional cargo.

(3) Thus, while the current loading ramps achieve their intended purpose, there is a need for a new and improved loading ramp that addresses these issues.

SUMMARY

(4) According to several aspects, a cargo loading system (“system”) is provided for a vehicle. The system includes a compressor for pressurizing a fluid, and the compressor has an inlet and an

outlet. The system further includes a deployable ramp (“ramp”) having one or more rigid elements with a surface for supporting a load. The ramp further includes one or more bladders that define a chamber fluidly connected to the outlet of the compressor, with the bladder being adapted to receive the fluid from the compressor. The bladder is attached to the rigid element, and the bladder is movable to a collapsed state where the chamber has a first volume. The bladder is further movable to an expanded state where the chamber has a second volume, with the second volume being higher than the first volume. The bladder contains a pressurized fluid for supporting the rigid element, in response to the bladder receiving the fluid from the compressor.

(5) In one aspect, the inlet of the compressor is adapted to fluidly connect to the chamber of the bladder and configured to draw fluid from the bladder.

(6) In another aspect, the bladder includes a first wall portion, a second wall portion facing the first wall portion, and a plurality of tethers attaching the first and second wall portions to one another.

(7) In another aspect, the rigid element is attached to the first and/or second wall portions.

(8) According to several aspects, a deployable ramp (“ramp”) is provided for a cargo loading system (“system”) of a vehicle. The ramp includes one or more rigid elements having a surface for supporting a load. The ramp further includes one or more bladders defining a chamber, which is fluidly connected to an outlet of a compressor and adapted to receive a fluid from the compressor. The bladder is attached to the rigid element and movable to a collapsed state where the chamber has a first volume. The bladder is further movable to an expanded state where the chamber has a second volume, with the second volume being higher than the first volume. The bladder contains a pressurized fluid for supporting the rigid element, in response to the bladder receiving the fluid from the compressor.

(9) In one aspect, the bladder includes a first wall portion, a second wall portion facing the first wall portion, and a plurality of tethers attaching the first and second wall portions to one another.

(10) In another aspect, the rigid element is attached to the first and/or second wall portions.

(11) In another aspect, the tethers have a common length, with the first and second wall portions being planar and positioned parallel relative to one another, in response to the bladder being moved to the expanded state. The first and second wall portions are spaced from one another by the common length of the tethers.

(12) In another aspect, the rigid element includes one or more plates attached to the first and/or second wall portions.

(13) In another aspect, the plate is a single upper plate attached to the first wall portion.

(14) In another aspect, the plates include a single upper plate attached to the first wall portion and a single lower plate attached to the second wall portion.

(15) In another aspect, the plates include multiple upper plates, with each of the upper plates having a peripheral edge portion surrounding a center portion, with the peripheral edge portion being attached to the first wall portion.

(16) In another aspect, the first wall portion includes multiple attachment surface areas that are attached to an associated one of the peripheral edge portions of the plates. The first wall portion further includes adjoining surface areas between the attachment surface areas. The adjoining surface areas are free of the plates to permit the bladder to fold along the adjoining surface areas of the first wall, in response to the bladder moving to the collapsed state.

(17) In another aspect, the bladder further includes a pair of non-perpendicular tethers, with each non-perpendicular tether attaching a pair of predetermined anchor points of an associated one of the first and second wall portions. The anchor points are disposed on opposite sides of an adjoining surface, and each non-perpendicular tether is configured to be positioned non-perpendicular to the first and second wall portions when the bladder is moved to the expanded state. The length of one of the non-perpendicular tethers is different from the length of the other of the non-perpendicular tethers, such that the non-perpendicular tethers pull the first and second wall portions toward one another and increase resistance to folding when the bladder is moved to the expanded state.

(18) In another aspect, the plates include multiple upper plates attached to the first wall portion of the bladder, with each upper plate having a first peripheral edge portion. The plates further include one or more lower plates attached to the second wall portion of the bladder, with each lower plate having a second peripheral edge portion. The bladder has a bisecting axis, with the upper and lower wall portions being disposed on an associated one of two opposing sides of the bisecting axis. The first peripheral edge portion of the upper plate is spaced from the second peripheral edge portion of the lower plate by an offset distance in a direction along the bisecting axis. The first and second wall portions are spaced from one another by a bladder thickness, and the bladder thickness is greater than the offset distance.

(19) In another aspect, the rigid element is a frame with a grating that has the surface for supporting the load, and the bladders includes multiple closed air tubes with each closed air tube having a length that is less than a predetermined maximum threshold.

(20) In another aspect, the frame includes two or more sub-panels attached to one another at a coupling, such that the bladder moves to the expanded state in response to the sub-panels being coplanar with one another and the at least one bladder is moved to the collapsed state in response to the sub-panels being folded on top of one another.

(21) In another aspect, the rigid element includes a pair of side rails attached to an associated one of opposing sides of the bladder, with each of the side rails having first and second ends. The rigid elements further include a first linkage assembly for attaching the first ends of the associated side rails to one another. The rigid elements further include a second linkage assembly for attaching the second ends of the associated side rails to one another. Each of the first and second linkage assemblies are configured to move the side rails toward one another such that the bladder is disposed in the collapsed state and away from one another such that the bladder is disposed in the expanded state.

(22) According to several aspects, a method of operating a deployable ramp (“ramp”) for a cargo loading system (“system”) of a vehicle. The method includes fluidly connecting a chamber, defined by a bladder, to an outlet of a compressor. The method further includes receiving, using the chamber, a fluid from the compressor, with the bladder being attached to the rigid element in response to fluidly connecting the chamber to the outlet of the compressor. The method further includes moving the bladder to a collapsed state where the chamber has a first volume. The method further includes moving the bladder to an expanded state where the chamber has a second volume, with the second volume being higher than the first volume. The chamber contains a pressurized fluid, in response to the chamber receiving the fluid from the compressor. The method further includes supporting, using the bladder, the rigid element in response to the bladder receiving the fluid from the compressor. The method further includes supporting, using the rigid element, a load.

(23) In one aspect, the method further includes fluidly connecting an inlet of the compressor to the chamber to draw fluid from the chamber and move the bladder from the expanded state to the collapsed state.

(24) Further areas of applicability will become apparent from the description provided herein. It should be understood that the description and specific examples are intended for purposes of illustration only and are not intended to limit the scope of the present disclosure.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1A is a perspective view of one non-limiting example of a vehicle having a cargo system including a deployable ramp and a compressor.

(2) FIG. 1B is a bottom plan view of the panel assembly of FIG. 1A, illustrating the bladder having an exemplary predetermined shape for reinforcing the load-bearing plate.

- (3) FIG. 1C is a cross-sectional view of the ramp of FIG. 1B, illustrating the ramp having a plate and a bladder with drop stitch knitting for supporting the plate.
- (4) FIG. 1D is an enlarged view of the panel assembly of FIG. 1A, illustrating the bladder and the load-bearing plate supporting a load.
- (5) FIG. 2 is a cross-sectional view of another example of the panel assembly of FIG. 1C, illustrating the panel assembly having an upper plate, a bladder supporting the upper plate, and a lower plate supporting the bladder.
- (6) FIG. 3A is a cross-sectional view of yet another example of the panel assembly of FIG. 1C, illustrating the panel assembly having first and second upper plates and a bladder supporting the first and second upper plates.
- (7) FIG. 3B is a cross-sectional view of the panel assembly of FIG. 3A, illustrating the bladder being deflated.
- (8) FIG. 3C is a cross-sectional view of the panel assembly of FIG. 3B, illustrating the panel assembly being folded for storage.
- (9) FIG. 4A is a cross-sectional view of still another example of the panel assembly of FIG. 1C, illustrating the panel assembly being deployed from a collapsed state.
- (10) FIG. 4B is a cross-sectional view of the panel assembly of FIG. 4A, illustrating the bladder inflating to overlap end portions of the first and second upper plates.
- (11) FIG. 4C is a cross-sectional view of the panel assembly of FIG. 4B, illustrating the bladder fully inflated for supporting the first and second upper plates.
- (12) FIG. 5 is a cross-sectional view of yet another example of the panel assembly of FIG. 1C, illustrating the panel assembly having multiple upper plates and bladders supporting adjacent ends of the upper plates.
- (13) FIG. 6A is a cross-sectional view of another example of the panel assembly of FIG. 1C, illustrating the panel assembly further having a lower plate supporting a portion of the bladder that is positioned under adjacent ends of the upper plates.
- (14) FIG. 6B is an enlarged cross-sectional view of the panel assembly of FIG. 6A, illustrating the bladder attached to the upper and lower plates and configured to fold.
- (15) FIG. 7A is a cross-sectional view of another example of the panel assembly of FIG. 1C, illustrating the bladder further having a tether attaching upper and lower sheets to one another.
- (16) FIG. 7B is an enlarged view of the bladder of FIG. 7A, illustrating the tether for bending the bladder along a crease that increases pressure of the bladder and increases an associated force that opposes folding of the bladder and supports the upper plates.
- (17) FIG. 8A is a perspective view of still another example of the panel assembly of FIG. 1C, illustrating the panel assembly having multiple bladders enclosed within by a frame to provide a ramp for a truck bed.
- (18) FIG. 8B is a cross-sectional view of the panel assembly of FIG. 8A, as taken along line 8B-8B, illustrating a lateral cross-section of multiple bladders.
- (19) FIG. 8C is a cross-sectional view of the panel assembly of FIG. 8A, as taken along line 8C-8C, illustrating a longitudinal cross-section of multiple bladders.
- (20) FIG. 9A is perspective view of another example of the panel assembly of FIG. 1C, illustrating the panel assembly having multiple bladders attached to a collapsible frame.
- (21) FIG. 9B is an enlarged perspective view of the panel assembly of FIG. 9A, illustrating of the frame for moving the bladder between collapsed and expanded states.

DETAILED DESCRIPTION

- (22) The following description is merely exemplary in nature and is not intended to limit the present disclosure, application, or uses.
- (23) Referring to FIGS. 1A-1D, there is generally illustrated one non-limiting example of a vehicle **100** having a cargo system **102** (“system”) including a deployable ramp **104** (“ramp”). In this non-limiting example, the vehicle **100** is a truck having a truck bed for storing cargo that can be

accessed by the system **102** and the ramp **104**. In other non-limiting examples, the vehicle may include a box van, a sports utility vehicle, a wagon, a bus, a train, other land vehicles, an aircraft, a watercraft, and the like, which have a cargo bed, storage space, luggage compartment, or other suitable space for storing cargo. As described in detail below, the ramp **104** includes one or more rigid elements **106** and one or more bladders **108**. The combination of the rigid element **106** and the inflated bladder **108** is configured to support a total load above a predetermined threshold, in response to the bladder **108** receiving fluid from an outlet **110** of the compressor **112**. In addition, the combination of the rigid element **106** and the inflated bladder **108** provides the ramp **104** with a mass below a predetermined mass threshold, such that the ramp may provide versatility. The movement of the ramp **104** to a collapsed state (i.e., via deflating the bladder and folding of the ramp **104**) may provide the ramp **104** with a size below a predetermined size threshold for convenient storage on a vehicle and providing more available space for loading cargo onto the vehicle **100**. In this non-limiting example, the system **102** includes a compressor **112** having an inlet **114** and an outlet **110**. The compressor **112** is configured to increase the pressure of a fluid. In other examples, the system may not include the compressor.

(24) Each one of the bladders **108** defines a chamber **116** fluidly connected to an outlet **110** of the compressor **112** to receive the fluid from the compressor **112** and move the ramp **104** from a collapsed state to an expanded state, in response to the bladder **108** receiving the fluid from the compressor **112**. In the expanded state, the bladder **108** supports the rigid element **106** and any load on the rigid element **106**.

(25) Referring to FIG. **1B**, the bladder **108** has an X-shaped configuration to reinforce predetermined sections of the rigid element **106** (e.g., surface area portions of a single upper plate **118** that are empirically determined to deform or dimple under a load without the bladder **108**). In other examples, the ramp can include any number of bladders and have any suitable shape attached to any portion of the rigid element.

(26) Referring to FIGS. **1C** and **1D**, the bladder **108** includes a first wall portion **120**, a second wall portion **122** facing the first wall portion **120** to define a cavity, and a plurality of tethers **124** (e.g., drop stitch tethers, etc.) attaching the first and second wall portions **120**, **122** to one another and disposed within the cavity. The tethers **124** hold the first and second wall portions **120**, **122** in predetermined positions relative to another, such that the bladder **108** has a predetermined thickness and shape. In this non-limiting example, the tethers **124** have a common length, such that the first and second wall portions **120**, **122** are planar and positioned parallel relative to one another and spaced from one another by the common length of the tethers **124**, in response to the bladder **108** being moved to the expanded state.

(27) The rigid elements may include one or more plates **126** (e.g., metal panels with or without perforations, non-slip surfaces, etc.) attached to the first and/or second wall portions **120**, **122**. In this non-limiting example, the rigid element **106** is a single upper plate **118** attached to the first wall portion **120**. Each rigid element **106** is attached to one or more associated bladders **108**. The rigid element **106** has a surface **128** for supporting a load **130** (FIG. **1D**), such that the ramp **104** provides a rigid stable surface for supporting rolling wheels and blocks the load **130** from deforming the bladder **108** (i.e., dimpling of the bladder, etc.).

(28) Referring now to FIG. **2**, another non-limiting example of a ramp **204** is similar to the ramp **104** of FIG. **1C** and includes the same components identified by the same numbers increased by 100. However, while the ramp **104** of FIG. **1C** includes a single upper plate **118** attached to the first wall portion **120**, the ramp **204** includes a single upper plate **218** attached to the first wall portion **120** and a single lower plate **219** attached to the second wall portion **222**.

(29) Referring to FIGS. **3A-3C**, yet another non-limiting example of a ramp **304** is similar to the ramp **104** of FIG. **1C** and has the same components identified by the same numbers increased by 200. However, while the ramp **104** of FIG. **1C** has a single upper plate **118** attached to the first wall portion **120**, the ramp **304** includes two upper plates **318a**, **318b** attached to the first wall portion

320 of the bladder **308**. More specifically, the first wall portion **320** includes multiple attachment surface areas (e.g., two attachment surface areas **332a**, **332b**) attached to an associated one of the two upper plates **318a**, **318b** and the first wall portion **320** further includes an adjoining surface area **334** (e.g., a strip surface area) that is disposed between the attachment surface areas **332a**, **332b**. As best shown in FIG. 3C, the adjoining surface area **334** is free of the plates to permit the bladder **308** to fold along the adjoining surface areas **334** of the first wall portion **320** in response to the bladder **308** moving to the collapsed state.

(30) The inlet **314** of the compressor **312** is adapted to fluidly connect to the chamber **316** of the bladder **308** and configured to draw fluid from the bladder **308** and move the ramp **304** from the expanded state (FIG. 3A) toward the collapsed state (FIG. 3C). In particular, the bladder **308** is movable to the collapsed state (FIG. 3C) where the chamber has a first volume, and the bladder **308** is further movable to the expanded state (FIG. 3A) where the chamber **316** has a second volume, with the second volume being higher than the first volume.

(31) Referring to FIGS. 4A-4C, still another non-limiting example of a ramp **404** is similar to the ramp **104** of FIG. 1C and has the same components identified by the same numbers increased by 300. However, while the ramp **104** of FIG. 1C has a single upper plate **118** attached to the first wall portion **120**, the ramp **404** includes two upper plates **418a**, **418b** attached to the first wall portion **420** of the bladder **408**, and the upper plates **418a**, **418b** include edge portions **436** that overlap and support one another.

(32) Referring to FIG. 5, another non-limiting example of a ramp **504** is similar to the ramp **104** of FIG. 1C and has the same components identified by the same numbers increased by 400. However, while the ramp **104** of FIG. 1C includes the single upper plate **118** attached to and supported by the first wall portion **120** of the bladder **108**, the ramp **504** includes multiple upper plates (e.g., three upper plates **518a**, **518b**, **518c** etc.), with each upper plate having a peripheral edge portion **538** surrounding a center portion **540**, and the peripheral edge portion **538** being attached to the first wall portion **520** and the center portion **540** being free of the bladders **508**. More specifically, the first wall portion **520** of each bladder **508** includes multiple attachment surface areas **534** attached to an associated one of peripheral edge portions **538** of the upper plates. The first wall portion **520** further includes multiple adjoining surface areas (e.g., strip surface areas) between the attachment surface areas **532**. As best shown in FIG. 3C, the adjoining surface areas **534** are free of the plates to permit the bladder **508** to fold along the adjoining surface areas **534** of the first wall portion **520** in response to the bladder **508** moving to the collapsed state.

(33) Referring to FIGS. 6A and 6B, yet another non-limiting example of a ramp **604** is similar to the ramp **104** of FIG. 1C and has the same components identified by the same numbers increased by 500. However, while the ramp **104** of FIG. 1C has a single upper plate **118** attached to the first wall portion **120**, the ramp **604** has multiple upper plates (e.g., three upper plates **618a**, **618b**, **618c** attached to the first wall portion **620** and a lower plate **619** attached to the second wall portion **622**. Each of the upper plates has a first peripheral edge portion **638**, and the lower plate **619** has a second peripheral edge portion **638**. The bladder **608** has a bisecting axis **642**, and the upper and lower wall portions **620**, **622** are disposed on an associated one of two opposing sides of the bisecting axis **642**. The first peripheral edge portion **638** of the upper plate is spaced from the second peripheral edge portion **638** of the lower plate **619** by an offset distance $L_{sub.OS}$ in a direction along the bisecting axis **642**. The first and second wall portions **620**, **622** are spaced from one another by a bladder thickness $L_{sub.side}$. The bladder **608** is sized such that the bladder thickness $L_{sub.side}$ is greater than the offset distance $L_{sub.OS}$, allowing for full, 180 degree folding without stressing or damaging the constituent elements.

(34) Referring to FIGS. 7A and 7B, still another non-limiting example of a ramp **704** is similar to the ramp **104** of FIG. 1C and has the same components identified by the same numbers increased by 600. However, while the ramp **104** of FIG. 1C has a single upper plate **118** attached to the first wall portion **120**, the ramp **704** has multiple upper plates (e.g., two upper plates **718a**, **718b**, etc.)

attached to the first wall portion **720** of the bladder **708**. In addition, the bladder **708** further includes one or more non-perpendicular tethers (e.g., non-perpendicular tethers **744**, **745**), with each one of the non-perpendicular tethers **744**, **745** attaching a pair of predetermined anchor points **746**, **748** of an associated one of the first and second wall portions **720**, **722**. The anchor points **746**, **748** are disposed on opposite sides of an adjoining surface **734** (e.g., a bending location associated with a strip surface area in a gap between the plates **718a**, **718b**). The non-perpendicular tethers **744**, **745** are configured to be positioned non-perpendicular to the first and second wall portions **720**, **722** when the bladder **708** is moved to the expanded state. The length of the non-perpendicular tether **744** is different from the length of the non-perpendicular tether **745**, such that the non-perpendicular tethers **744**, **745** pull the first and second wall portions **720**, **722** toward one another and increase resistance to folding along the plate boundaries (e.g., the adjoining surface **734**) when the bladder **708** is moved to the expanded state.

(35) Referring to FIGS. **8A-8C**, still another non-limiting example of a ramp **804** is similar to the ramp **104** of FIG. **1C** and has the same components identified by the same numbers increased by 600. However, while the ramp **104** of FIG. **1C** has one rigid element **106** in the form of a single upper plate **118** attached to the first wall portion **120** of a single bladder **108**, the ramp **804** includes two rigid elements in the form of a frame **850** with a grating **852** having the surface **828** for supporting the load. Also, in this non-limiting example, the bladder **808** includes a plurality of closed air tubes **809**, and each of these closed air tubes **809** may have a length that is less than a predetermined maximum threshold to decrease deflection of the associated closed air tube **809** in a direction that is transverse to a longitudinal axis of the closed air tube **809** when the closed air tube **809** receives a load in the same direction.

(36) Referring to FIGS. **9A** and **9B**, yet another non-limiting example of a ramp **904** is similar to the ramp **104** of FIG. **1C** and has the same components identified by the same numbers increased by 600. However, while the ramp **104** of FIG. **1C** has one rigid element **106** in the form of a single upper plate **118** attached to the first wall portion **120** of a single bladder **108**, the ramp **904** has a rigid element **906** in the form of a frame **954** having two or more sub-panels **956a**, **956b** attached to one another at a coupling (e.g., a piano hinge, a hook fastener, etc.), such that the bladder **908** moves to the expanded state in response to the sub-panels **956a**, **956b** being co-planar with one another and the at least one bladder is moved to the collapsed state, in response to the sub-panels **956a**, **956b** being folded on top of one another.

(37) More specifically, the frame **954** includes a pair of side rails **958**, **960** attached to an associated one of opposing sides **962**, **964** of the bladder **908**, with each of the side rails having first and second ends **966**, **968**. The frame **954** further includes a first linkage assembly **970** attaching the first ends **966** of the associated side rails **958**, **960** to one another. The frame **954** further includes a second linkage assembly **972** attaching the second ends **968** of the associated side rails **958**, **960** to one another. Each of the first and second linkage assemblies **970**, **972** are configured to move the side rails **958**, **960** toward one another, such that the bladder **908** is disposed in the collapsed state and away from one another such that the bladder **908** is disposed in the expanded state.

(38) A method is provided for operating the ramp **104** of FIG. **1** for the system **102**. The method includes fluidly connecting the chamber **116**, defined by the bladder **108**, to the outlet of the compressor **112**. The method further includes receiving, using the chamber **116** of the bladder **108**, the fluid from the compressor **112**, with the bladder **108** attached to the rigid element **106**. The method further includes moving the bladder **108** to the collapsed state where the chamber **116** has a first volume. The method further includes moving the bladder **108** to the expanded state where the chamber **116** contains a pressurized fluid and has a second volume, with the second volume being higher than the first volume. The method further includes supporting, using the bladder **108**, the rigid element, in response to the bladder **108** receiving the fluid from the compressor **112**. The method further includes supporting, using the rigid element **106**, a load.

(39) In some examples, system elements may be implemented as computer readable instructions

(e.g., software) on one or more computing devices (e.g., servers, personal computers, etc.), stored on computer readable media associated therewith (e.g., disks, memories, etc.). A computer program product may comprise such instructions stored on computer readable media for carrying out the functions described herein.

(40) Accordingly, it is to be understood that the above description is intended to be illustrative and not restrictive. Many embodiments and applications other than the examples provided would be apparent to those of skill in the art upon reading the above description. The scope of the invention should be determined, not with reference to the above description, but should instead be determined with reference to the appended claims, along with the full scope of equivalents to which such claims are entitled. It is anticipated and intended that future developments will occur in the arts discussed herein, and that the disclosed systems and methods will be incorporated into such future embodiments. In sum, it should be understood that the invention is capable of modification and variation and is limited only by the following claims.

(41) All terms used in the claims are intended to be given their plain and ordinary meanings as understood by those skilled in the art unless an explicit indication to the contrary is made herein. In particular, use of the singular articles such as “a,” “the,” “said,” etc. should be read to recite one or more of the indicated elements unless a claim recites an explicit limitation to the contrary.

(42) The description of the present disclosure is merely exemplary in nature and variations that do not depart from the gist of the present disclosure are intended to be within the scope of the present disclosure. Such variations are not to be regarded as a departure from the spirit and scope of the present disclosure.

Claims

1. A cargo loading system for a vehicle, the cargo loading system comprising: a compressor having an inlet and an outlet, the compressor for pressurizing a fluid; and a deployable ramp comprising: at least one rigid element having a surface for supporting a load; and at least one bladder defining a chamber fluidly connected to the outlet of the compressor and adapted to receive the fluid from the compressor, the at least one bladder attached to the at least one rigid element, the at least one bladder is movable to a collapsed state where the chamber has a first volume, the at least one bladder is further movable to an expanded state where the chamber has a second volume and contains a pressurized fluid for supporting the at least one rigid element in response to the at least one bladder receiving the fluid from the compressor, with the second volume being higher than the first volume, wherein the inlet of the compressor is adapted to fluidly connect to the chamber of the at least one bladder and configured to draw fluid from the at least one bladder, and wherein the at least one bladder comprises: a first wall portion; a second wall portion facing the first wall portion; and a plurality of tethers attaching the first and second wall portions to one another.

2. The cargo loading system of claim 1 wherein the at least one rigid element is attached to at least one of the first and second wall portions.

3. A deployable ramp for a cargo loading system of a vehicle, the deployable ramp comprising: at least one rigid element having a surface for supporting a load; and at least one bladder defining a chamber fluidly connected to an outlet of a compressor and adapted to receive a fluid from the compressor, the at least one bladder attached to the at least one rigid element, the at least one bladder is movable to a collapsed state where the chamber has a first volume, the at least one bladder is further movable to an expanded state where the chamber has a second volume and contains a pressurized fluid for supporting the at least one rigid element in response to the at least one bladder receiving the fluid from the compressor, with the second volume being higher than the first volume, wherein the at least one bladder comprises: a first wall portion; a second wall portion facing the first wall portion; and a plurality of tethers attaching the first and second wall portions to one another.

4. The deployable ramp of claim 3 wherein the at least one rigid element is attached to at least one of the first and second wall portions.
5. The deployable ramp of claim 3 wherein the plurality of tethers have a common length, with the first and second wall portions being planar and positioned parallel relative to one another in response to the at least one bladder being moved to the expanded state, with the first and second wall portions being spaced from one another by the common length of the tethers.
6. The deployable ramp of claim 5 wherein the at least one rigid element comprises at least one plate attached to at least one of the first and second wall portions.
7. The deployable ramp of claim 5 wherein the at least one plate comprises a single upper plate attached to the first wall portion.
8. The deployable ramp of claim 5 wherein the at least one plate comprises a single upper plate attached to the first wall portion and a single lower plate attached to the second wall portion.
9. The deployable ramp of claim 5 wherein the at least one plate comprises a plurality of upper plates, with each of the upper plates having a peripheral edge portion surrounding a center portion, and the peripheral edge portion being attached to the first wall portion.
10. The deployable ramp of claim 9 wherein the first wall portion includes a plurality of attachment surface areas attached to an associated one of the peripheral edge portions of the plates, and the first wall portion further includes a plurality of adjoining surface areas between the attachment surface areas, with the adjoining surface areas being free of the plates to permit the at least one bladder to fold along the adjoining surface areas of the first wall in response to the at least one bladder moving to the collapsed state.
11. The deployable ramp of claim 10 wherein the at least one bladder further includes a pair of non-perpendicular tethers, with each non-perpendicular tether attaching a pair of predetermined anchor points of an associated one of the first and second wall portions, the anchor points being disposed on opposite sides of an adjoining surface, each of the non-perpendicular tethers is configured to be positioned non-perpendicular to the first and second wall portions when the bladder is moved to the expanded state, the length of one of the non-perpendicular tethers is different from the length of the other of the non-perpendicular tethers, such that the non-perpendicular tethers pull the first and second wall portions toward one another and increase resistance to folding when the bladder is moved to the expanded state.
12. The deployable ramp of claim 5 wherein the at least one plate includes: a plurality of upper plates attached to the first wall portion of the at least one bladder, with each of the upper plates having a first peripheral edge portion; and at least one lower plate is attached to the second wall portion of the at least one bladder, with the at least one lower plate having a second peripheral edge portion; where the at least one bladder has a bisecting axis, and the upper and lower wall portions are disposed on an associated one of two opposing sides of the bisecting axis; and where the first peripheral edge portion of the upper plate is spaced from the second peripheral edge portion of the lower plate by an offset distance in a direction along the bisecting axis; where the first and second wall portions are spaced from one another by a bladder thickness; and where the bladder thickness is greater than the offset distance.
13. The deployable ramp of claim 5 wherein the at least one rigid element comprises a frame with a grating having the surface for supporting the load, and the at least one bladder comprises a plurality of closed air tubes, with each of the closed air tubes having a length that is less than a predetermined maximum threshold.
14. The deployable ramp of claim 13 wherein the frame includes at least two sub-panels attached to one another at a coupling, such that the at least one bladder moves to the expanded state in response to the sub-panels being co-planar with one another and the at least one bladder is moved to the collapsed state in response to the sub-panels being folded on top of one another.
15. The deployable ramp of claim 5 wherein the at least one rigid element comprises a frame comprising: a pair of side rails attached to an associated one of opposing sides of the at least one

bladder, with each of the side rails having first and second ends; and a first linkage assembly attaching the first ends of the associated side rails to one another; and a second linkage assembly attaching the second ends of the associated side rails to one another; and where each of the first and second linkage assemblies are configured to move the side rails toward one another such that the at least one bladder is disposed in the collapsed state and away from one another such that the at least one bladder is disposed in the expanded state.

16. A method of operating a deployable ramp for a cargo loading system of a vehicle, the method comprising: fluidly connecting a chamber defined by at least one bladder to an outlet of a compressor, wherein the at least one bladder comprises a first wall portion, a second wall portion facing the first wall portion, and a plurality of tethers attaching the first and second wall portions to one another; receiving, using the chamber of the at least one bladder, a fluid from the compressor, with the at least one bladder attached to the at least one rigid element in response to fluidly connecting the chamber to the outlet of the compressor; moving the at least one bladder to a collapsed state where the chamber has a first volume; moving the at least one bladder to an expanded state where the chamber has a second volume and contains a pressurized fluid, with the second volume being higher than the first volume in response to the chamber receiving the fluid from the compressor; supporting, using the at least one bladder, the at least one rigid element in response to the at least one bladder receiving the fluid from the compressor, and supporting, using at least one rigid element, a load.

17. The method of claim 16 further comprising fluidly connecting an inlet of the compressor to the chamber to draw fluid from the chamber and move the at least one bladder from the expanded state to the collapsed state.
