

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12411518
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Koorapati; Sagar et al.

Throttle control circuits for throttling activity in processing segment circuits in an integrated circuit (IC) chip and related methods

Abstract

A throttle control circuit receives a throttle control signal for controlling power consumption in a plurality of processing segment circuits. The throttle control signal has a throttle control value based on throttle requests from monitoring circuits that have detected power-related events or conditions and correspond to a requested change in activity in the plurality of processing segment circuits. The throttle control circuit receives the throttle control signal in a plurality of throttle administration circuits that each generates a throttle select signal to select an activity control signal for a corresponding processing segment circuit. In each of a first number (N) of consecutive cycles of a clock signal, the activity control signal disables state changes in the corresponding processing segment circuit for a second number (M) of cycles among the first number (N) of consecutive cycles to reduce power consumption in the processing segment circuits.

Inventors:	Koorapati; Sagar (Austin, TX), Naveh; Alon (Corte Madera, CA)
Applicant:	QUALCOMM Incorporated (San Diego, CA)
Family ID:	91302349
Assignee:	QUALCOMM Incorporated (San Diego, CA)
Appl. No.:	18/339478
Filed:	June 22, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240427368 A1	Dec. 26, 2024

Publication Classification

Int. Cl.: G06F1/08 (20060101); G06F1/3228 (20190101); G06F1/324 (20190101)

U.S. Cl.:

CPC **G06F1/08** (20130101); **G06F1/3228** (20130101); **G06F1/324** (20130101);

Field of Classification Search

CPC: G06F (1/08); G06F (1/324); G06F (1/3228)

USPC: 713/320; 713/324

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7966511	12/2010	Naveh	713/100	G06F 1/324
11048323	12/2020	Ho	N/A	G06F 1/329
11733757	12/2022	Naveh	713/300	G06F 1/3243
12228988	12/2024	Koorapati	N/A	G06F 1/3203
2015/0309551	12/2014	Yeager	N/A	N/A
2021/0096635	12/2020	Kalyanam et al.	N/A	N/A
2021/0405729	12/2020	Abou-Alfotouh	N/A	G06F 1/3206

OTHER PUBLICATIONS

“Static and Dynamic Frequency Scaling on Multicore CPUs”—by Wenlei Bao, Changwan Hong, Sudheer Chunduri, Sriram Krishnamoorthy, Louis-Noel Pouchet, Fabrice Rastello, and P. Sadayappan; 26 Pages, dated Dec. 2016 (Year: 2016). cited by examiner

“Low Power Design for a Multi-core Multi-thread Microprocessor”—by Wang Yong-Wen, Zheng Qian-Bing, Dou Qiang, and Zhang Min-Xuan; 6 Pages, Dated 2010 (Year: 2010). cited by examiner

International Search Report and Written Opinion for International Patent Application No. PCT/US2024/028309, mailed Sep. 2, 2024, 14 pages. cited by applicant

Primary Examiner: Misiura; Brian T

Attorney, Agent or Firm: W&T

Background/Summary

BACKGROUND

I. Field of the Disclosure

(1) The field of the disclosure relates to processor-based systems (e.g., central processing unit (CPU)-based systems, graphic processing unit (GPU)-based systems), or neural network processing unit (NPU)-based systems, and more particularly, to power distribution management of circuits in the processor-based systems.

II. Background

(2) Microprocessors, also known as processing units (PUs), perform computational tasks in a wide variety of applications. One type of conventional microprocessor or PU is a central processing unit (CPU). Another type of microprocessor or PU is a dedicated processing unit known as a graphics

processing unit (GPU). A GPU is designed with specialized hardware to accelerate the rendering of graphics and video data for display. A GPU may be implemented as an integrated element of a general-purpose CPU or as a discrete hardware element that is separate from the CPU. Other examples of PUs may include neural network processing units or neural processing units (NPU). CPUs are configured to execute software instructions that cause a processor to fetch data from a location in a memory and to perform one or more processor operations using the fetched data.

(3) PUs are included in a computer system that includes other supporting processing devices (circuits) involved with or accessed as part of performing computing operations in the computer system. Examples of these other supporting processing devices include memory, input/output (I/O) devices, secondary storage, modems, video processors, and related interface circuits. The PUs and supporting processing devices in a computer system are referred to collectively as processing devices. Processing devices of a processor-based system can be provided in separate integrated circuits (ICs) in separate IC chips or may be aggregated in a larger IC, like a system-on-a-chip (SoC) IC, wherein some or all of these processing devices are integrated into the same IC chip. For example, an SoC IC chip may include a PU that includes a plurality of processor cores and supporting processing devices, such as a memory system that includes cache memory and memory controllers for controlling access to external memory, I/O interfaces, power management systems, etc. An SoC may be particularly advantageous for applications in which a limited area is available for the computer system (e.g., a mobile computing device such as a cellular device). To manage power distributed to the processing devices, the SoC may also include a power management system that includes one or more power rails in the SoC that supply power to its components. A separate power management integrated circuit (PMIC) that can be off-chip or on-chip with the SoC can independently control power supplied to the power rails. The SoC may be designed with a plurality of different power rails that are distributed within the SoC to provide power to various clusters of the processing devices for their operation. For example, all the processor cores in the SoC may be coupled to a common power rail for power, whereas supporting processing devices may be powered from separate power rails in the SoC, depending on the design of the SoC.

SUMMARY OF THE DISCLOSURE

(4) Aspects disclosed herein include throttle control circuits for throttling activity of processing segment circuits in an integrated circuit (IC) chip. Related methods of throttle control in an IC chip are also disclosed. The IC chip includes a processor as well as integrated supporting processing devices (e.g., network nodes, memory controllers, internal memory, input/output (I/O) interface circuits, etc.) for the processor. For example, the processor may be a central processing unit (CPU), a graphics processing unit (GPU), or a neural network processing unit (NPU), wherein the processor includes multiple processing units (PUs) and/or processor cores. The processor-based system may be provided as a system-on-a-chip (SoC) that includes a processor and the integrated supporting processing devices for the PU. As examples, the SoC may be employed in smaller mobile devices (e.g., a cellular phone, a laptop computer), as well as enterprise systems such as server chips in computer servers. The IC chip may also include a hierarchical power management system that is configured to control power consumption by the processor-based system at both local and centralized levels to achieve a desired performance within an overall power budget for the IC chip. The hierarchical power management system can be configured to control power consumption by controlling the power level (e.g., by controlling the voltage level) distributed at one or more power rails in the IC chip that provide power to the PUs and the integrated supporting processing devices. For example, the hierarchical power management system can be configured to provide additional power to certain power rails to supply power to higher current-demanding devices to achieve higher performance while providing less power to other power rails to keep the overall power within power and/or thermal limits for the IC chip. The hierarchical power management system can also be configured to control power consumption by throttling performance (e.g., frequency) of the processing devices in the processor-based system, which in turn throttles (i.e.,

reduces, maintains, or increases) their current demand and thus their power consumption. Note, as used herein, throttle can mean to take an action that will decrease or increase a parameter that affects power and thus results in a respective decrease or increase in power consumption.

(5) The hierarchical power management system is configured to throttle performance of the processing devices in the processor-based system because the level of processing activity in the processing devices in a SoC can vary based on workload conditions. Some power rails in the SoC may experience heightened current demand. It is desired that this current demand does not exceed the maximum current limitations of its respective power rail. Even if a higher current demand on a power rail is within its maximum current limits, a heightened activity of a processing device in the SoC can generate a sudden increase in current demand from its power rail, referred to as a “di/dt” event. This di/dt event can cause a voltage droop in the power rail, thus negatively affecting performance of processing devices powered by such power rail. Also, even if a higher current demand on a power rail is within its maximum current limits, a higher current demand can increase the overall power consumption of the SoC. Processing devices may have a maximum power rating to operate properly and/or to not impact performance in an undesired manner. Higher current demand from processing devices can also generate excess heat. Thus, the maximum power rating of the SoC may be based in part on the ability of the SoC to dissipate heat generated by the processing devices during their operation.

(6) In exemplary aspects, the hierarchical power management system may include local area management (LAM) circuits distributed in the IC chip that are each associated with and provided to monitor one or more processing circuits (also referred to as “processing devices”) in the IC chip. The LAM circuits may be configured to generate power events associated with monitored processing circuits in the IC chip that represent power consumption associated with the monitored processing devices in the IC chip. The power events can be reported from local areas in the IC chip, where power estimations for particular monitored processing devices are performed, to a centralized power estimation and limit (PEL) circuit in the hierarchical power management system. The PEL circuit may be configured to estimate and control (i.e., throttle) power in the processor-based system in the IC chip to achieve a desired performance within an overall power budget for the IC chip. The PEL circuit may determine how to throttle power based on the received power events. For example, the power events may be associated with estimations of power consumption that can be thought of as power throttle recommendations to throttle power in the IC chip if the estimated power consumption exceeds the power limits of the IC chip or negatively affects performance.

(7) The activity of the processing devices in the IC chip may affect its steady state current demand (I) and current transients (di/dt), and thus its power consumption. Because the IC chip may be larger in terms of die area due to the integration of the PUs and integrated supporting processing devices, there can be a significant delay between when the PEL circuit receives a power event regarding power consumption of a monitored processing device and the PEL circuit throttling power in the IC chip to throttle power consumption in response. This delay can, for example, cause devices in the IC chip to temporarily continue to consume excess power that can cause thermal and/or power issues (e.g., di/dt issues, voltage droop, heat generation) or permanent damage before the power management circuit has time to react. Thus, in response to the power events, current demand and transients, and other monitoring and control circuits associated with each LAM circuit, localized control may also be asserted on the processing circuits to improve response time and avoid performance issues.

(8) In this regard, the processor-based system includes, additionally or alternatively, a throttle control circuit that may be associated with a LAM circuit and receive a throttle control signal for controlling power consumption in a plurality of processing segment circuits which may be associated with the LAM circuit. The throttle control signal has a throttle control value that may be based on throttle requests provided from monitoring circuits that have detected power-related

events or conditions associated with the LAM circuit and correspond to a requested change in activity in the plurality of processing segment circuits. In an exemplary aspect, the throttle control circuit receives the throttle control signal in a plurality of throttle administration circuits. Each throttle administration circuit generates a throttle select signal to select an activity control signal for a corresponding processing segment circuit. A throttle sequence selection circuit receives the respective throttle select signals and provides, to the plurality of processing segment circuits, a selected activity control signal to reduce state changes in the processing segment circuit according to the throttle control value. In this regard, in each of a first number (N) of consecutive cycles of a clock signal, the activity control signal disables state changes in the corresponding processing segment circuit for a second number (M) of cycles among the first number (N) of consecutive cycles to reduce power consumption in the processing segment circuits.

(9) In this regard, in one exemplary aspect, an integrated circuit (IC) chip comprising a processor-based system. The processor-based system comprises a plurality of processing segment circuits, each configured to operate in response to a clock signal; and a throttle control circuit. The throttle control circuit comprises a plurality of throttle administration circuits, each configured to receive a throttle control signal and generate a throttle select signal based on the throttle control signal, corresponding one of the first plurality of processing segment circuits; and a throttle sequence selection circuit configured to provide, to each of the first plurality of processing segment circuits, an activity control signal configured to throttle activity in the processing segment circuit in a first number (M) of cycles among a second number (N) of consecutive cycles of the clock signal based on a corresponding throttle select signal.

(10) In another exemplary aspect, a method of controlling activity in an integrated circuit (IC) chip comprising a processor-based system is disclosed. The method comprises operating each of a plurality of processing segment circuits in response to a clock signal; receiving, in each of a plurality of throttle administration circuits, a throttle control signal; and generating a throttle select signal corresponding one of the first plurality of processing segment circuits. The method further comprises providing an activity control signal, based on the corresponding throttle select signal, to each of the first plurality of processing segment circuits in each cycle of a first number (N) of consecutive cycles of the clock signal, the activity control signal configured to disable operation in the processing segment circuit in a second number (M) of cycles among the first number (N) of consecutive cycles.

(11) In another exemplary aspect, a throttle control circuit is disclosed. The throttle control circuit comprises a plurality of throttle administration circuits, each configured to receive a throttle control signal and generate a throttle select signal based on the throttle control signal, corresponding one of a first plurality of processing segment circuits. The throttle control circuit also comprises a throttle sequence selection circuit configured to provide, to each of the first plurality of processing segment circuits in each cycle of a first number (N) of consecutive cycles of the clock signal, an activity control signal configured to disable state changes in the processing segment circuit in a second number (M) of cycles among the first number of consecutive cycles based on the corresponding throttle select signal.

Description

BRIEF DESCRIPTION OF THE FIGURES

(1) FIG. 1 is a schematic diagram of an exemplary processor-based system in the form of an exemplary system-on-a-chip (SoC) in an integrated circuit (IC) chip;

(2) FIG. 2 is a logic diagram of the exemplary processor-based system in FIG. 1, illustrating processing circuits and other support devices communicatively coupled to an internal communication network and an optional hierarchical power management system that is configured

to perform power estimation and throttling of power consumption;

(3) FIG. 3 is a top view of an exemplary physical layout of the semiconductor die (“die”) that is an SoC in an IC chip of the processor-based system in FIG. 1 illustrating the physical layout of different tile regions and the devices physically present in such different tile regions, and coded with indicia indicating the separate power rails from which devices are supplied with power from the hierarchical power management system;

(4) FIG. 4 is a table illustrating an exemplary assignment of power rails driven by respective power management ICs (PMIC), in the processor-based system in FIG. 1, to devices in the processor-based system for supplying power to such devices;

(5) FIG. 5 is another top view of the processor-based system in the IC chip in FIG. 1, illustrating local area management (LAM) circuits, regional activity management (RAM) circuits, and a power estimation and limiting (PEL) circuit as part of a hierarchical power management system, wherein the hierarchical power management system is configured to locally monitor the activity of devices in the processor-based system to estimate and throttle its power consumption and report activity power events regarding estimated power consumption to the PEL circuit, wherein the PEL circuit is configured to collect activity power events regarding power consumption of the monitored processing devices and throttle power in the IC chip in response;

(6) FIG. 6 is a schematic diagram of an exemplary three (3) level hierarchical power management system that can be provided in the processor-based system in the IC chip in FIG. 1, wherein the three (3) level hierarchical power management system may include: a first, local level of LAM circuits configured to perform local device monitoring and power consumption throttling, and report activity power events regarding monitored processing device power consumption, a second, intermediate level of RAM circuits configured to receive and aggregate local activity power events, and a third, centralized level of a PEL circuit configured to collect aggregated activity power events regarding power consumption of the monitored processing devices and throttle power in the IC chip in response;

(7) FIG. 7 is a schematic diagram of an exemplary two (2) level hierarchical power management system that can be provided in the processor-based system in the IC chip in FIG. 1, wherein two (2) level hierarchical power management systems may include: a first local level of LAM circuits configured to perform local device monitoring and power consumption throttling, and a second, centralized level of a PEL circuit configured to collect aggregated activity power events regarding power consumption of the monitored processing devices and throttle power in the IC chip in response;

(8) FIG. 8 is a flowchart illustrating an exemplary process of a hierarchical power management system of the processor-based system in FIG. 6, locally monitoring and throttling power consumption of monitored processing devices and hierarchically reporting activity power events related to the monitored power consumption to a PEL circuit configured to throttle power consumption in the processor-based system in response to the received power events;

(9) FIG. 9A is a schematic diagram illustrating an exemplary di/dt circuit that can be provided in a LAM circuit in the hierarchical power management system in FIG. 6, wherein the di/dt circuit is configured to collect activity samples of a device monitored by the LAM circuit and correlate the activity samples to estimate current and generate estimated current samples in a designated time window which can then be used to determine the slope of a rate of change in current (di/dt) consumed by the monitored processing device to determine whether the power consumption of the monitored processing device should be throttled by the LAM circuit;

(10) FIG. 9B is a graph illustrating exemplary estimated current samples collected by the di/dt circuit in FIG. 9A plotted as a function of time to determine the rate of change in current (di/dt) consumed by the monitored processing device;

(11) FIG. 10 is a logic diagram of an exemplary PEL circuit that can be provided in a hierarchical power management system of the processor-based system and that illustrates exemplary

components for receiving power events, decoding the received power events in tracking circuits, and merging the tracked power events to generate a power limiting management responses to throttle power consumption in the processor-based system in response to the received power events;

(12) FIG. 11 is a block diagram of an exemplary throttle control circuit in a processor-based system configured to receive a throttle control signal and provide, to a plurality of processing segment circuits, selected activity control signals to control activity in a clock window of N consecutive clock cycles, including throttling activity in a number M of the N consecutive cycles based on the throttle control signal;

(13) FIG. 12 is a block diagram of a throttle control circuit including a plurality of throttle administration circuits, each configured to receive the throttle control signal and generate a throttle select signal corresponding to one of the plurality of processing segment circuits;

(14) FIG. 13 is a block diagram showing details of a throttle sequence selection circuit configured to receive throttle select signals corresponding to each of the plurality of processing segment circuits and provide a selected activity control signal to the processing segment circuit;

(15) FIG. 14 is a timing diagram illustrating sequence signals that are generated by throttle sequence generators and provided as activity control signals to throttle activity in processing segment circuits in different numbers of cycles of the cycle window of N consecutive cycles;

(16) FIG. 15 is a state diagram illustrating the states of finite state machines (FSMs) in the throttle administration circuits and provided to illustrate state transitions in the FSMs in response to increases and decreases of the throttle control value;

(17) FIG. 16 is a flowchart illustrating an exemplary process for receiving throttle request(s) and generating selected activity control signals to throttle activity in processing segment circuits, including but not limited to the throttle control circuit in FIGS. 11-13 and 15;

(18) FIG. 17 is a block diagram of another exemplary processor-based system that includes the throttle control circuit configured to receive a throttle control signal for controlling power in a plurality of processing segment circuits in an IC chip and providing, to each of the plurality of processing segment circuits, a selected activity control signal configured to disable state change activity in the processing segment circuit in one number (M) of cycles among another number (N) of consecutive cycles of a clock signal CLK, including but not limited to the throttle control circuit in FIGS. 11-13 and 15; and

(19) FIG. 18 is a block diagram of an exemplary wireless communication device that includes radio-frequency (RF) components that can include the throttle control circuit configured to receive a throttle control signal for controlling power in a plurality of processing segment circuits in an IC chip and providing, to each of the plurality of processing segment circuits, a selected activity control signal configured to disable state change activity in the processing segment circuit in one number (M) of cycles among another number (N) of consecutive cycles of a clock signal CLK, including but not limited to the throttle management circuit in FIGS. 11-13 and 15.

DETAILED DESCRIPTION

(20) With reference now to the drawing figures, several exemplary aspects of the present disclosure are described. The word “exemplary” is used herein to mean “serving as an example, instance, or illustration.” Any aspect described herein as “exemplary” is not necessarily to be construed as preferred or advantageous over other aspects.

(21) Aspects disclosed herein may optionally include a hierarchical power estimation and throttling in a processor-based system in an integrated circuit (IC) chip. Related power management and power throttling methods are also disclosed. The IC chip includes a processor as well as integrated supporting processing devices (e.g., network nodes, memory controllers, internal memory, input/output (I/O) interface circuits, etc.) for the processor. For example, the processor may be a central processing unit (CPU), graphics processing unit (GPU), or neural network processing unit (NPU), wherein the processor includes multiple processing units (PUs) and/or processor cores. The

processor-based system may be provided as a system-on-a-chip (SoC) that includes a processor and the integrated supporting processing devices for the PU. As examples, the SoC may be employed in smaller mobile devices (e.g., a cellular phone, a laptop computer), as well as enterprise systems such as server chips in computer servers. The IC chip may also include a hierarchical power management system that is configured to control power consumption by the processor-based system at both local and centralized levels to achieve a desired performance within an overall power budget for the IC chip. The hierarchical power management system can be configured to control power consumption by controlling the power level (e.g., voltage level) distributed at one or more power rails in the IC chip that provide power to the PUs and the integrated supporting processing devices. For example, the hierarchical power management system can be configured to provide additional power to certain power rails supplying power to higher current-demanding devices to achieve higher performance while providing less power to other power rails to keep the overall power within power and/or thermal limits for the IC chip. The hierarchical power management system can also be configured to control power consumption by throttling performance (e.g., frequency) of the processing devices in the processor-based system, which in turn throttles (i.e., reduces, maintains, or increases) their current demand and thus their power consumption. Note, as used herein, throttle can mean to take an action that will decrease or increase a parameter that affects power and thus results in a respective decrease or increase in power consumption.

(22) In exemplary aspects, the hierarchical power management system may include local area management (LAM) circuits distributed in the IC chip that are each associated with one or more processing devices in the IC chip. The LAM circuits may be configured to generate power events associated with its monitored processing devices in the IC chip that represent power consumption associated with the monitored processing devices in the IC chip. The power events can be reported from local areas in the IC chip, where power estimations for particular monitored processing devices are performed, to a centralized power estimation and limit (PEL) circuit in the hierarchical power management system. The PEL circuit is configured to estimate and control (i.e., throttle) power in the processor-based system in the IC chip to achieve a desired performance within an overall power budget for the IC chip. The PEL circuit may determine how to throttle power based on the received power events. For example, the power events may be associated with estimations of power consumption that can be thought of as power throttle recommendations to throttle power in the IC chip if the estimated power consumption exceeds the power limits of the IC chip or negatively affects performance.

(23) The activity of the processing devices in the IC chip may affect its steady state current demand and transient current demands (e.g., changes in current flow rate referred to as “ di/dt ”) and thus affect power consumption. Because the IC chip may be larger in terms of die area due to the integration of the processing units and integrated supporting processing devices, there can be a significant delay between when PEL circuit receives a power event regarding the consumption of a monitored processing device and the PEL circuit throttling power in the IC chip to throttle power consumption in response. This delay can, for example, cause devices in the IC chip to temporarily continue to consume excess power that can cause performance issues (e.g., di/dt issues, voltage droop, heat generation) before the power management circuit has time to react.

(24) In this regard, the processor-based system includes, additionally or alternatively, a throttle control circuit that may be associated with a LAM circuit and receive a throttle control signal for controlling power consumption in a plurality of processing segment circuits which may be associated with the LAM circuit. The throttle control signal has a throttle control value that may be based on throttle requests provided from monitoring circuits that have detected power-related events or conditions associated with the LAM circuit and correspond to a requested change in activity in the plurality of processing segment circuits. In an exemplary aspect, the throttle control circuit receives the throttle control signal in a plurality of throttle administration circuits. Each

throttle administration circuit generates a throttle select signal to select an activity control signal for a corresponding processing segment circuit. A throttle sequence selection circuit receives the respective throttle select signals and provides, to the plurality of processing segment circuits, a selected activity control signal to reduce state changes in the processing segment circuit according to the throttle control value. In this regard, in each of a first number (N) of consecutive cycles of a clock signal CLK, the activity control signal disables state changes in the corresponding processing segment circuit for a second number (M) of cycles among the first number (N) of consecutive cycles to reduce power consumption in the processing segment circuits.

(25) In this regard, FIG. 1 is a schematic diagram of an exemplary processor-based system **100** in the form of an exemplary system-on-a-chip (SoC) **102** in an integrated circuit (IC) chip **104**. Optionally, a hierarchical power management system can be provided. The SoC **102** may be employed in smaller mobile devices (e.g., a cellular phone, a laptop computer), as well as enterprise systems such as server chips in computer servers. The processor-based system **100** is first described with regard to FIG. 1 before exemplary hierarchical power management systems that can be provided in the processor-based system **100** to estimate and throttle power consumption in the IC chip **104** are described starting at FIG. 2 below.

(26) With reference to FIG. 1, the processor-based system **100** is provided in a single semiconductor die **106** and integrated into a single IC chip **104**. The processor-based system **100** includes a plurality of processing unit (PU) clusters **108(0)-108(N)** that are examples of processing devices **110** in the processor-based system **100**. Each of the PU clusters **108(0)-108(N)** can include one or more processor cores **112(0)-112(N)**, which are each configured to execute instructions (e.g., software, firmware) to carry out tasks as is known for processors. For example, the PU clusters **108(0)-108(N)** may be central processing unit (CPU) clusters wherein one or more of the processor cores **112(0)-112(N)** includes CPUs and/or graphics processing unit (GPU) clusters, wherein one or more of the processor cores **112(0)-112(N)** includes GPUs. The processor-based system **100** includes an internal communication network **114** that facilitates providing communication paths between the PU clusters **108(0)-108(N)** and other supporting processing devices that are also considered to be processing devices to carry out desired processing requests and related processing tasks. The PU clusters **108(0)-108(N)** are communicatively coupled to the internal communication network **114**. The internal communication network **114** can be a coherent communication bus that provides a fabric in the processor-based system **100**. The internal communication network **114** can be a network fabric that typically consists of network nodes and their communication lines, a network of wires, and/or communication channels that provide communication paths that provide reliable communication between different PU clusters **108(0)-108(N)** and the supporting processing devices **110**. Network nodes are the circuits, such as interconnected switches and routers, that provide a reliable network fabric that provides and receives data on the communication paths between different PU clusters **108(0)-108(N)** and the supporting processing devices **110**. The fabric provided by the internal communication network **114** also includes a network of wires or communication channels that allow different processing devices in the processor-based system **100** to communicate and exchange data with each other at high speeds.

(27) For example, as shown in FIG. 1, the processor-based system **100** also includes internal cache memory **116** and memory controllers (MCs) **118(0)-118(M)** as other types of processing devices **110** that provide access to memory. The cache memory **116** shown in FIG. 1 is a shared cache memory that is communicatively coupled to the internal communication network **114** and can be accessed by the PU clusters **108(0)-108(N)** through the internal communication network **114**. The processor-based system **100** may also include private cache memory and/or private shared cache memory that is integrated or privately accessible by one or more of the respective PU clusters **108(0)-108(N)** without having to access such through the internal communications network **114**. The memory controllers **118(0)-118(M)** are communicatively coupled to the internal communication network **114** in the IC chip **104**. The memory controllers **118(0)-118(M)** provide

the PU clusters **108(0)-108(N)** access to memory for storing and retrieving data to carry out processing tasks. For example, the memory controllers **118(0)-118(M)** may be coupled to external memory from the IC chip **104** or internal memory integrated into the IC chip **104**.

(28) Also, as shown in FIG. **1**, the processor-based system **100** in this example also includes I/O interface circuits **120(0)-120(X)** as other examples of processing devices **110** that are also communicatively coupled to the internal communication network **114**. The I/O interface circuits **120(0)-120(X)** provide access to I/O devices, which may be internal and integrated into the IC chip **104** or external to the IC chip **104**. For example, the I/O interface circuits **120(0)-120(X)** may be a peripheral component interconnect (PCI) interface circuits that are used for connecting I/O hardware devices to a processor-based system, like the processor-based system **100** in FIG. **1**, to allow high-speed data to be transferred between devices and the PU clusters **108(0)-108(N)** in the processor-based system **100**.

(29) Also, as shown in FIG. **1**, the processor-based system **100** in this example also includes socket-to-socket (S2S) interface circuits **122(0)-122(Y)** as other examples of processing devices **110** that are also communicatively coupled to the internal communication network **114**. The S2S interface circuits **122(0)-122(Y)** allow the processor-based system **100** to be coupled to another separate processor-based system (which may be like the processor-based system **100** in FIG. **1**) in a socket-to-socket connection. For example, the processor-based system **100** shown in FIG. **1** may be a first CPU motherboard system that can be communicatively coupled to another processor-based system for communication through the internal communication network **114** and a coupled S2S interface circuit **122(0)-122(Y)**.

(30) Also, as shown in FIG. **1**, the processor-based system **100** in this example also includes other interface (I/F) circuits **127(0)-127(Z)** as other examples of processing devices **110** that are also communicatively coupled to the internal communication network **114**. The interface circuits **127(0)-127(Z)** can provide an additional external communications interface to the SoC **102** and can be configured to provide a communication interface according to the desired standard or protocol. For example, the interface circuits **127(0)-127(Z)** could be PCIe interface circuits that are configured to support PCIe communications with the SoC **102**.

(31) Thus, in the processor-based system **100** in FIG. **1**, the internal communication network **114** enables different processing devices such as PU clusters **108(0)-108(N)** and their processor cores **112(0)-112(N)**, caches, the memory controllers **118(0)-118(M)**, the I/O interface circuits **120(0)-120(X)**, and/or the S2S interface circuits **122(0)-122(Y)** to work together efficiently. The fabric provided by the internal communication network **114** is designed to provide high bandwidth, low latency, and efficient routing of data between different processing devices of the processor-based system **100**.

(32) Also, as shown in FIG. **1** and as described in more detail below, the processor-based system **100** may also include a hierarchical power management system **124**. In this example, the hierarchical power management system **124** is integrated into the same IC chip **104** and in the same die **106** that includes the PU clusters **108(0)-108(N)** and the internal communication network **114**. The hierarchical power management system **124** may be configured to control the power consumption of the processor-based system **100** by controlling the power consumption of some or all of the processing devices **110** in the IC chip **104**. The hierarchical power management system **124** may be configured to manage power consumption to achieve a desired performance within an overall power budget for the IC chip **104**. For example, the processor-based system **100** may have an overall power budget that is based on the ability of the IC chip **104** to dissipate heat generated by the operation of the processor-based system **100**. The processor-based system **100** may also have an overall power budget that is based on a current limit of power rails in the IC chip **104**. The power budget of the processor-based system **100** may also be based on the power supply limits of a power supply that is powering the processor-based system **100**. Thus, the hierarchical power management system **124** can be configured to control power consumption by controlling the power

level (e.g., voltage level) distributed at one or more of the power rails in the IC chip **104** that provide power to the processing devices **110** or by controlling operating frequency. For example, the hierarchical power management system **124** can be configured to cause additional power to be supplied to certain power rails, thus supplying power to higher current demanding devices to achieve higher performance while providing less power to other power rails to keep the overall power within power and/or thermal limits for the IC chip **104**. For example, the hierarchical power management system **124** can be configured to communicate with or include a power management integrated circuit (PMIC) chip **125** (that can either be on-chip or off-chip to the SoC **120**) to actually cause the power supplied to certain power rails to be adjusted.

(33) Also, as discussed in more detail below, a hierarchical power management system **124** can also be configured to control power consumption in the processor-based system **100** by throttling performance, which may include controlling clock frequency and/or supply voltage on the power rails provided to the processing devices **110** in the processor-based system **100**. Throttling performance may also include controlling activity that causes the consumption of power. These methods, in turn, throttle (i.e., reduce, maintain, or increase) the current demand of such processing devices **110** and, thus, their power consumption in the IC chip **104**. Throttling may generally refer to any measure (for example, modifying activity, a clock frequency, and/or a supply voltage) to effect (i.e., reduce, maintain, or increase) power consumption. Performance of clocked circuits in the processing devices **110** in the processor-based system **100** in terms of frequency (f) is related to power (P) according to the power equation $P = c f V_{sup}^2$, where ' c ' is capacitance and ' V ' is voltage. Thus, reducing the frequency of a clocked circuit in a processing device **110** in the processor-based system **100** also reduces its power consumption.

(34) FIG. 2 is a logic diagram of the exemplary processor-based system **100** in FIG. 1 illustrating processing devices **110** communicatively coupled to the internal communication network **114**. A hierarchical power management system **124** to control power consumption in the IC chip **104** may be provided in accordance with aspects of the present disclosure. Common elements in the processor-based system **100** in FIGS. 1 and 2 are shown with common element numbers and thus are not re-described. The IC chip **104** can also include target devices **200**, whose control also affects power, which can include the processing devices **110** and other circuits that are described below. As will be discussed in more detail below, the hierarchical power management system **124** may be configured to throttle power to target devices **200** as well as processing devices **110** to throttle power consumption in the IC chip **104**.

(35) As also shown in FIG. 2, the hierarchical power management system **124** may include a centralized power estimation and limiting (PEL) circuit **126** that is configured to estimate power consumption in the IC chip **104** and take actions to limit or throttle power consumption in the IC chip **104**. In this example, the PEL circuit **126** can be provided as part of a power management integrated circuit (PMIC) **125** that is integrated into the IC chip **104**. The PEL circuit **126** may communicate such power throttling requests to a power management controller (PMC) **128**, which is configured to control power provided by voltage rails in the IC chip **104**. Throttling power consumption can include both increasing power (e.g., increasing voltage to power rails) to increase power consumption for increased performance and decreasing power (e.g., decreasing voltage to power rails) to decrease power consumption. The hierarchical power management system **124** may be configured to estimate power consumption in the IC chip **104** through receipt of power events **130** reported to it from devices at lower hierarchical levels in the IC chip **104** that provide information that provides an indirect indication of power consumption. For example, the IC chip **104** may have one or more temperature sensor(s) **132** that are configured to report thermal power events **130(1)** to the PEL circuit **126** to provide an indication of the temperature in the IC chip **104**, which can then be correlated to power consumption by the processor-based system **100** in the IC chip **104**. As another example, the IC chip **104** may have one or more telemetry sensor(s) **134** (e.g., current sensors) that are configured to detect and report telemetry power events **130(2)** to the PEL

circuit **126** to provide an indication of the telematics information in the IC chip **104** which can then also be correlated to power consumption by the processor-based system **100** in the IC chip **104**.

(36) The power consumption of the processing devices **110** in the processor-based system **100** may contribute to the power consumption in the IC chip **104**. Thus, it may be desired to also have a way for the PEL circuit **126** in the hierarchical power management system **124** to receive a direct indication of power consumption for the processing devices **110**. The PEL circuit **126** can then use this information to estimate power consumption in the IC chip **104** and use such information to appropriately throttle the power consumption in the IC chip **104**. In this regard, as shown in FIG. 2, hierarchical power management system **124** may also include local area management (LAM) circuits **136** that are each associated with one or more processing devices **110** in the IC chip **104**. The LAM circuits **136** could be placed in various places in the IC chip **104**, including at corners of the IC chip **104**, where power estimation and power limiting may need to be performed. For example, LAM circuits **136(1)(0)-136(1)(N)** may be associated with one or more of the PU clusters **108(0)-108(N)**, as shown in FIG. 2. As another example, LAM circuits **136(2)-136(5)**, **136(6)(0)-136(6)(X)** may also be associated with respective one or more of the memory controllers **118**, the internal communication network **114**, e.g., the fabric, one or more of the I/O interface circuits **120**, the one or more of the S2S interface circuits **122**, and/or one or more interface circuits **127(0)-127(Z)**. Each LAM circuit **136(2)-136(5)**, **136(6)(0)-136(6)(X)** is configured to monitor the activity related to its associated processing device **110** as a monitored processing device **110** to then generate respective activity power events **138(1)(0)-138(1)(N)**, **138(2)-138(5)**, **138(6)(0)-138(6)(Z)** (referred to herein individually, partially, or collectively as “activity power events **138**”) that are communicated directly or indirectly to the PEL circuit **126**. The activity power events **138(1)(0)-138(1)(N)**, **138(2)-138(5)**, **138(6)(0)-138(6)(Z)** contain information that relates to the power consumption of the respective monitored processing device **110**. For example, the activity power events **138(1)(0)-138(1)(N)**, **138(2)-138(5)**, **138(6)(0)-138(6)(Z)** could contain processing activity information, or power consumption information that is generated by the respective LAM circuits **136(1)(0)-136(1)(N)**, **136(2)-136(5)**, **136(6)(0)-136(6)(X)** estimating power consumption of its monitored processing device **110** based on processing activity of its monitored processing device **110**.

(37) In either case, in this manner, the activity power events **138** can be reported from local areas in the IC chip **104**, where power estimations for particular monitored processing devices **110** are performed, to the centralized PEL circuit **126**. The PEL circuit **126** can then be configured to use the received activity power events **138** and/or the other power events **130** to estimate and control (i.e., throttle) power in the processor-based system **100** in the IC chip **104** to achieve a desired performance within an overall power budget for the IC chip **104**. For example, the activity power events **138** that are associated with estimations of power consumption of processing devices **110** that can be thought of in essence as power throttle recommendations to the PEL circuit **126** for the PEL circuit **126** to throttle power in the IC chip **104** if the estimated power consumption exceeds the power limits of the IC chip **104** or negatively affects performance in an undesired manner.

(38) The PEL circuit **126** being configured to receive activity power events **138** relating to activity for individual processing devices **110** in the processor-based system **100** allows the PEL circuit **126** to throttle power consumption to certain local processing devices **110** that are responsible for increased power consumption. This allows the PEL circuit **126** to throttle power with discrimination as opposed to throttling power to the power rails or, in other ways, in the IC chip **104** that affects the power delivered to a larger set of processing devices **110** as a whole. For example, as discussed in more detail below, the PEL circuit **126** can be configured to use the received activity power events **138** to perform performance throttling of processing devices **110** in the processor-based system **100** to throttle its power consumption. The PEL circuit **126** can be configured to generate power limiting management responses **140** to be communicated to certain LAM circuits **136** in the processor-based system **100** to cause such LAM circuits **136** to limit the

performance of its monitored processing device **110**.

(39) Performance throttling of a processing device **110** in the processor-based system **100** to throttle its power consumption can be accomplished in different manners. For example, as discussed in more detail below, performance throttling can be achieved by the PEL circuit **126** by generating a throughput throttling power limiting management response **140**, which is destined for the LAM circuit **136(3)** associated with the internal communication network **114**. The LAM circuit **136(3)** can be configured to throttle the throughput of communication traffic in the internal communication network **114**, such as at a particular network node in the internal communication network **114**, to throttle current demand in the internal communication network **114** and thus its power consumption. Throughput throttling can be isolated to only certain areas or network nodes in the internal communication network **114**. In another example, as discussed in more detail below, performance throttling in the processor-based system **100** can be achieved by the PEL circuit **126** by generating a clock throttling power limiting management response **140** to cause a clock circuit (which may be clocking one or more of the processing devices **110**) to throttle the speed (i.e., clock frequency) of certain clocked processing devices **110**. Clock throttling of a processing device **110** throttles its current demand, which throttles its power consumption. In another example, as discussed in more detail below, performance throttling in the processor-based system **100** can be achieved by throttling or changing the power states of a monitored processing device **110** to throttle its performance and thus its power consumption.

(40) FIG. **3** is a top view of an exemplary physical layout of the semiconductor die (“die”) **106** of the IC chip **104** in FIG. **1** that includes the processor-based system **100** to illustrate further exemplary details of the physical layout of a hierarchical power management system **124** and an exemplary organization of power rails provided in the processor-based system **100**.

(41) As shown in FIG. **3**, the IC chip **104** has a physical layout that includes a center tile CTILE, a west tile WTILE, an east tile ETILE, a south tile STILE, a north tile NTILE, and an A-tile ATILE. A tile is a smaller section of a semiconductor die that has been processed in a wafer process and contains a set of IC components. The center tile CTILE in this example includes the PU clusters **108(0)-108(N)**, shown as NCC0-NCC19. Different numbers of processor cores can be provided in different PU clusters **108(0)-108(N)**, NCC0-NCC19. In this example, the PU clusters **108(0)-108(N)**, NCC0-NCC19 are all powered by a same power rail **300(1)**. The center tile CTILE in this example also includes the internal communication network **114**, which is shown by a plurality of center network nodes FABC00-FABC65. The network nodes FABC00-FABC65 are circuits that create a network fabric (“fabric”) of communication paths between the different PU clusters **108(0)-108(N)** and the supporting processing devices **110**. In this example, the network nodes FABC00-FABC65 are powered by a second power rail **300(2)**. The network nodes FABC00-FABC65 are circuits that can include interconnected switches and/or routers that provide a reliable network fabric that provides and receives data on the internal communications network **114** between different PU clusters **108(0)-108(N)** and the supporting processing devices **110**. The center tile CTILE in this example also includes the system level cache memory **116(0)-116(7)** powered by a third power rail **300(3)** to provide shared cache memory **116** for the PU clusters **108(0)-108(N)**, NCC0-NCC19. The system level cache memory **116(0)-116(7)** that is organized into different quadrants adjacent to and coupled to respective memory circuits DDR0-DDR7 that include respective memory controllers **118(0)-118(7)** and memory **304(0)-304(7)** (e.g., dynamic data random access memory (DDR) circuits) in the west tile WTILE to provide interlacing memory schemes for example. The memory circuits DDR0-DDR7 may be powered by yet a separate, fourth power rail **300(4)**. The memory circuits DDR0-DDR7 are also communicatively coupled to the internal communication network **114** through the respective network nodes FABC00-FABC05.

(42) With continuing reference to FIG. **3**, the center tile CTILE in this example also includes the system level cache memory **116(8)-116(15)**, also powered by the third power rail **300(3)**, to provide additional shared cache memory **116** for the PU clusters **108(0)-108(N)**, NCC0-NCC19. The

system level cache memory **116(8)-116(15)** may be organized into different quadrants adjacent to respective memory circuits **DDR8-DDR15** that include respective memory controllers **118(8)-118(15)** and coupled memory **304(8)-304(15)** (e.g., DDR circuits) in the east tile **ETILE** to provide interlacing memory schemes for example. The memory circuits **DDR8-DDR15** are also shown as being powered by the same fourth power rail **300(4)** as is powering the memory circuits **DDR0-DDR7** in the west tile **WTILE**. The memory circuits **DDR8-DDR15** are also communicatively coupled to the internal communication network **114** through the respective network nodes **FABC60-FABC65**.

(43) With continuing reference to FIG. 3, the center tile **CTILE** of the IC chip **104** in this example includes request node circuits **FABS00, FABS40, FABN57, FABN47** that are coupled to the internal communication network **114** to provide network interfaces between the I/O interface circuits **120(0)-120(3), 120(4)-120(7)** and the internal communication network **114** in the respective south tile **STILE** and north tile **NTILE**. The request node circuits **FABS00, FABS40, FABN57, FABN47** manage the traffic requests from the I/O interface circuits **120(0)-120(3), 120(4)-120(7)** to the internal communication network **114** and vice versa. The request node circuits **FABS00, FABS40, FABN57, FABN47** and the I/O interface circuits **120(0)-120(3), 120(4)-120(7)** in this example are powered by a fifth power rail **300(5)**.

(44) With continuing reference to FIG. 3, the A-tile **ATILE** in the IC chip **104** includes the PEL circuit **126** and the PMC **128** of the hierarchical power management system **124** in this example.

(45) Thus, as shown in FIG. 3, the processing devices **110** in the processor-based system **100** in the IC chip **104** are powered by a series of different power rails **300(1)-300(5)**. Thus, the PEL circuit **126** in the hierarchical power management system **124** has the resolution of each of these different power rails **300(1)-300(5)** in which to vary the voltage on such power rails **300(1)-300(5)** to throttle power consumption in the IC chip **104** based on the activity power events **130, 138**. Note that each power rail **300(1)-300(5)** can actually be included as a single or multiple power rails.

(46) FIG. 4 is a table **400** illustrating an exemplary assignment of power management circuits **AK0-AK5** in the PMIC **125** in the processor-based system **100** to devices in the processor-based system **100** for supplying power to such devices. Power management circuits **AK0-AK5** can be responsible for controlling one or more different power rails **300(1)-300(5)**, as shown in FIG. 3, to supply power to various components. Multiple devices in the processor-based system **100** can be coupled to the same power rail **300(1)-300(5)** to receive power. For example, as shown in FIG. 4, in this example, PU clusters **NCC19, 18, 15, 14** are powered from power rails controlled by power management circuit **AK0**, PU clusters **NCC 11-10** are powered from power rails controlled by power management circuit **AK1**, PU clusters **NCC2, 3, 6, 7** are powered from power rails controlled by power management circuit **AK2**, PU clusters **NCC0, 1, 4, 5** are powered from power rails controlled by power management circuit **AK3**, PU clusters **NCC9-8** are powered from power rails controlled by power management circuit **AK4**, and PU clusters **NCC12, 13, 16, 17** are powered from power rails controlled by power management circuit **AK5**. Also, as shown in FIG. 4, a single device in the processor-based system **100** can be coupled to more than one power rail to receive power. For example, power supplied to the logic circuits (**SoC_Logic**) can be controlled by the multiple power management circuits **AK1-AK4**. The cache memory **116** can be supplied power from power rails controlled by the power management circuits **AK0-AK5**. Different memory controllers **118** are shown as being powered by power rails controlled by the power management circuits **AK0-AK5**. The I/O interface circuits **120(0)-120(3)** are shown as being powered by power rails controlled by separate respective power management circuits **AK3, AK2, AK5, AK0**.

(47) FIG. 5 is another top view of the processor-based system **100** in the IC chip **104** in FIG. 1, illustrating local area management (LAM) circuits **136** and the PEL circuit **126** as part of the hierarchical power management system **124**. As discussed above with regard to FIG. 2, the LAM circuits **136** can be configured to locally monitor activity of processing devices **110**, such as the PU clusters **108(0)-108(N)** in the processor-based system **100** to estimate and throttle its power

consumption and report activity power events **138** regarding estimated power consumption to the PEL circuit **126**. The processor-based system **100** in this example includes a clock circuit **506** that generates a clock signal **508** to clock the PU clusters **108(0)-108(N)** to control the speed of the PU clusters **108(0)-108(N)**. The PEL circuit **126** is configured to collect activity power events **138** regarding power consumption of the monitored processing devices **110** and issue power limiting management responses **140** in response to throttle power consumption in the IC chip **104**.

(48) As shown in FIG. 5, a plurality of LAM circuits **136(3)** are distributed in the center tile CTILE and associated with respective network node **500** (as processing devices **110**) of the internal communication network **114**. For example, the internal communication network **114** can be a mesh network, as shown in FIG. 5. The internal communication network **114** is capable of routing communication traffic from the PU clusters **108(0)-108(N)** through different network nodes **500** based on performance and traffic characteristics of the internal communication network **114**. In this manner, the throughput of the internal communication network **114** is not limited by any single network node **500**. The processor-based system **100** in this example includes a clock circuit **510** that generates a clock signal **512** to clock the network nodes **500** to control the speed of the internal communication network **114**. The clock circuit **510** is another example of a target device **200** in the IC chip **104**. As will be discussed in more detail below, the LAM circuits **136(3)** associated with the network nodes **500** in the internal communication network **114** are configured to sample the processing activity of respectively assigned network nodes **500** to generate a plurality of activity samples. The LAM circuits **136(3)** are then configured to estimate the power consumption of the assigned network node **500** based on the activity samples regarding its assigned network node **500** to generate an activity power event **138** based on the such estimated power consumption of the respective network node **500**.

(49) Also, as shown in FIG. 5, in this example, the hierarchical power management system **124** may also include regional activity management (RAM) circuits **502(3)** configured to monitor activity of the internal communication network **114**. The RAM circuits **502(3)** can be located in a particular region of the internal communication network **114**, with each being assigned and coupled to a subset of the LAM circuits **136(3)**. The RAM circuits **502(3)** can be intermediate power management circuits in the hierarchical power management system **124**. The RAM circuits **502(3)** may be coupled to the PEL circuit **126** through a second communication network **504**. The RAM circuits **502(3)** can be communicatively and hierarchically located between the LAM circuits **136(3)** and the centralized PEL circuit **126**. In some examples, the RAM circuits **502(3)** are configured to receive and aggregate activity power events **138** reported by assigned LAM circuits **136(3)** regarding activity of their monitored network node **500**. The RAM circuits **502(3)** can then aggregate these activity power events **138** and report an aggregated activity power event to the PEL circuit **126** so that the PEL circuit **126** can determine how the power consumption of network nodes **500** should be throttled to achieve a desired overall performance of the internal communication network **114** while also maintaining power consumption within desired limits. The PEL circuit **126** can communicate a power limiting management response **140** back to a given RAM circuit **502(3)** to perform throughput throttling of a given network node(s) **500** in response to the power consumption of a network node(s) **500** being determined to exceed desired limits. For example, as discussed in more detail below, the RAM circuit **502(3)** can be configured to throttle throughput of a given network node(s) **500** by selectively enabling and disabling communication traffic through the network node(s) **500**.

(50) Also, as shown in FIG. 5, in this example, a plurality of LAM circuits **136(2)** are distributed in the west tile WTILE and the east tile ETILE and associated with respective memory circuits **DDR0-DDR7, DDR8-DDR15** (as processing devices **110**). As will also be discussed in more detail below, the LAM circuits **136(2)** associated with the memory circuits **DDR0-DDR7, DDR8-DDR15** are configured to sample processing activity of respectively assigned memory circuits **DDR0-DDR7, DDR8-DDR15** to generate a plurality of activity samples. The LAM circuits **136(2)** are

then configured to estimate the power consumption of the assigned memory circuit **DDR0-DDR7**, **DDR8-DDR15** based on the activity samples regarding their assigned network node **500** to generate an activity power event **138** based on the such estimated power consumption of the respective memory circuits **DDR0-DDR7**, **DDR8-DDR15**.

(51) Also, as shown in FIG. 5, in this example, the hierarchical power management system **124** also includes regional RAM circuits **502(2)** configured to monitor activity of the memory circuits **DDR0-DDR7**, **DDR8-DDR15**. The RAM circuits **502(2)** are located in a particular region of the memory circuits **DDR0-DDR7**, **DDR8-DDR15**, with each being assigned and coupled to a subset of the LAM circuits **136(2)**. The RAM circuits **502(2)** are communicatively and hierarchically located between the LAM circuits **136(2)** and the centralized PEL circuit **126**. The RAM circuits **502(2)** are coupled to the PEL circuit **126** through the second communication network **504**. The RAM circuits **502(2)** are configured to receive and aggregate activity power events **138** reported by assigned LAM circuits **136(2)** regarding activity of their monitored memory circuits **DDR0-DDR7**, **DDR8-DDR15**. The RAM circuits **502(2)** can then aggregate these activity power events **138** and report an aggregated activity power event to the PEL circuit **126** so that the PEL circuit **126** can determine how power consumption of the memory circuits **DDR0-DDR7**, **DDR8-DDR15** should be throttled to achieve a desired overall performance of the memory circuits **DDR0-DDR7**, **DDR8-DDR15** while also maintaining power consumption within desired limits. The PEL circuit **126** can communicate a power limiting management response **140** back to a given RAM circuit **502(2)** to perform throughput and/or performance throttling of a given memory circuit(s) **DDR0-DDR7**, **DDR8-DDR15** in response to the power consumption of a memory circuit **DDR0-DDR7**, **DDR8-DDR15** being determined to exceed desired limits. For example, as discussed in more detail below, the RAM circuit **502(2)** can be configured to throttle throughput and/or performance of a given memory circuit(s) **DDR0-DDR7**, **DDR8-DDR15** by selectively enabling and disabling memory access requests/responses to the memory circuits **DDR0-DDR7**, **DDR8-DDR15**.

(52) Also, as shown in FIG. 5, in this example, the hierarchical power management system **124** also includes regional RAM circuits **502(4)** configured to monitor activity of the I/O interface circuits **120(0)-120(7)**. The RAM circuits **502(4)** are located in a particular region of the I/O interface circuits **120(0)-120(7)**, with each being assigned and coupled to a subset of the LAM circuits **136(4)** as shown. The RAM circuits **502(4)** are communicatively and hierarchically located between the LAM circuits **136(4)** and the centralized PEL circuit **126**. The RAM circuits **502(4)** are coupled to the PEL circuit **126** through the second communication network **504**. The RAM circuits **502(4)** are configured to receive and aggregate activity power events **138** reported by assigned LAM circuits **136(4)** regarding activity of their monitored I/O interface circuits **120(0)-120(7)**. The RAM circuits **502(4)** can then aggregate these activity power events **138** and report an aggregated activity power event to the PEL circuit **126** so that the PEL circuit **126** can determine how power consumption of the I/O interface circuits **120(0)-120(7)** should be throttled to achieve a desired overall performance of the I/O interface circuits **120(0)-120(7)** while also maintaining power consumption within desired limits. The PEL circuit **126** can communicate a power limiting management response **140** back to a given RAM circuit **502(4)** to perform throughput and/or performance throttling of a given I/O interface circuit(s) **120(0)-120(7)** in response to the power consumption of an I/O interface circuit(s) **120(0)-120(7)** being determined to exceed desired limits. For example, as discussed in more detail below, the RAM circuit **502(4)** can be configured to throttle throughput and/or performance of a given I/O interface circuit(s) **120(0)-120(7)** by selectively enabling and disabling access requests/responses to the I/O interface circuit(s) **120(0)-120(7)**.

(53) As shown back in FIG. 2, LAM circuits **136(1)(0)-136(1)(N)** can also be associated with each PU cluster **108(0)-108(N)** in the processor-based system **100** to sample activity therein to estimate power consumption in a respective PU cluster **108(0)-108(N)**. The LAM circuits **136(1)(0)-136(1)(N)** can be configured to generate activity power events **138**, including the estimated power

consumptions in response to a RAM circuit **502**, which in turn aggregates such activity power events **138** to the PEL circuit **126**. The RAM circuits **502** assigned to the subset of LAM circuits **136(1)(0)-136(1)(N)** are coupled to the PEL circuit **126** through the second communication network **504**. The PEL circuit **126** can generate power-limiting management responses **140** in response to throttle the performance of the PU clusters **108(0)-108(N)**.

(54) As also shown in FIG. 2, LAM circuits **136(5)** can also be associated with each S2S interface circuit **122(0)-122(Y)** in the processor-based system **100** to sample activity therein to estimate power consumption in a respective S2S interface circuit **122(0)-122(Y)**. The LAM circuits **136(5)** can be configured to generate activity power events **138**, including the estimated power consumptions in response to a RAM circuit **502**, which in turn aggregates such activity power events **138** to the PEL circuit **126**. The RAM circuits **502** assigned to the subset of LAM circuits **136(5)** are coupled to the PEL circuit **126** through the second communication network **504**. In response, the PEL circuit **126** can generate power-limiting management responses **140** to throttle the performance of the S2S interface circuits **122(0)-122(Y)**.

(55) As shown back in FIG. 2, LAM circuits **136(6)(0)-136(6)(X)** can also be associated with each interface circuit **127(0)-127(Z)** in the processor-based system **100** to sample activity therein to estimate power consumption in a respective interface circuit **127(0)-127(Z)**. The LAM circuits **136(6)(0)-136(6)(X)** can be configured to generate activity power events **138** that include the estimated power consumptions in response to a RAM circuit **502**, which in turn aggregates such activity power events **138** to the PEL circuit **126**. The RAM circuits **502** assigned to a subset of LAM circuits **136(6)(0)-136(6)(X)**, is coupled to the PEL circuit **126** through the second communication network **504**. The PEL circuit **126** can generate power limiting management responses **140** in response to throttle the performance of the interface circuits **127(0)-127(Z)**.

(56) In this example, any of the RAM circuits **502**, **502(2)-502(4)** discussed above can also include circuitry to behave functionally as a LAM circuit for an assigned processing device **110**. In this regard, any of the RAM circuits **502**, **502(2)-502(4)** can also be configured to sample the processing activity of its respective assigned processing device **110** to generate a plurality of activity samples for such processing device **110**. Such RAM circuits **502**, **502(2)-502(4)** can be configured to estimate the power consumption of its assigned processing device **110** based on the activity samples regarding its assigned processing device **110** to generate an aggregated activity power event based on the such estimated power consumption of the respective processing device **110** and the other received activity power events **138** from its coupled LAM circuits **136(1)(0)-(1)(N)**, **136(2)-136(5)**, **136(6)(0)-136(6)(X)**.

(57) Note that in any of the above-referenced examples, the RAM circuits **502** are optional for any of the monitored processing devices **110**, and their respective LAM circuits **136(1)-136(6)** can be configured to communicate activity power events **138** directly to the PEL circuit **126**.

(58) FIG. 6 is a schematic diagram illustrating additional exemplary detail of a three (3) level hierarchical power management system **624** that can be provided as the hierarchical power management system **124** in the processor-based system **100** in the IC chip **104** in FIGS. 1-3 and 5. Common elements between the hierarchical power management system **624** in FIG. 6 and the hierarchical power management system **124** in FIGS. 1-3 and 5 are shown with common element numbers. In this regard, FIG. 6 illustrates a single LAM circuit **136** communicatively coupled to a single RAM circuit **502** which is coupled to the PEL circuit **126**. Note, however, that this is to simplify the illustration in FIG. 6. In the hierarchical power management system **624** in FIG. 6, there can be a plurality of RAM circuits **502** that are communicatively coupled to the PEL circuit **126**. There can also be a plurality of LAM circuits **136** that are communicatively coupled to each RAM circuit **502** of the plurality of RAM circuits **502**. The discussion below regarding the exemplary operation of the LAM circuit **136** and RAM circuit **502** are equally applicable to any number of LAM circuits **136** and RAM circuits **502** included in the processor-based system, including the LAM circuits **136(1)(0)-(1)(N)**, **136(2)-136(5)**, **136(6)(1)-136(6)(X)** and the RAM

circuits **502**, **502(2)**-**502(4)**.

(59) With reference to FIG. **6**, the LAM circuit **136** in this example is configured to sample the processing activity as a received activity sample **600** of an assigned, monitored processing device **110** in each cycle of a given local time window. The LAM circuit **136** periodically samples activity of its monitored processing device **110** in a local time window representing the activity of the assigned, monitored processing device **110** in that local time window. In this example, the LAM circuit **136** is configured to correlate received activity samples **600** into a power consumption during a given local time window for the activity of the processing device **110** for that given local time window. The LAM circuit **136** includes an accumulate circuit **602** that is configured to accumulate the estimated power consumptions based on the received activity samples **600** sampled in a given local time window to generate an estimated current demand **604** for the monitored processing device **110** for the local time window. The estimated current demand **604** is an estimate of the accumulated current measurement reported by the assigned processing device **110** (i.e., power consumption) over the local time window. The accumulate circuit **602** may then provide the estimated current demand **604** (current demand over time) for each local time window in a generated activity power event **606** on the second communication network **504**, representing the estimated power consumption of the monitored processing device **110** that is communicated to the RAM circuit **502** assigned to the LAM circuit **136**. The accumulate circuit **602** may repeat the same process for subsequent local time windows to accumulate the estimated power consumptions for received activity samples **600** during the local time window to generate a next estimated current demand **604** for the monitored processing device **110**.

(60) With continuing reference to FIG. **6**, the RAM circuit **502** may include an aggregation circuit **608** that is configured to aggregate the received activity power events **606** from its coupled LAM circuits **136** into a generated aggregated activity power event **138**. The RAM circuit **502** may then be configured to communicate the aggregated activity power event **138** on the second communication network **504** to the PEL circuit **126**. Note that in this example, the RAM circuit **502** also includes its own LAM circuit **136R** that may be configured like the LAM circuit **136** in FIG. **6**. In this regard, the LAM circuit **136R** may be configured to sample the processing activity **600R** of an assigned processing device **110** into a plurality of activity samples **600R**. The processing activity **600R** of the assigned processing device **110** may be sampled periodically by the LAM circuit **136R** to generate a plurality of activity samples over a given local time window representing the activity of the assigned, monitored processing device **110**. The LAM circuit **136R** is configured to determine a current flow rate and/or a change in the current flow rate (i.e., di/dt) of current provided to the assigned processing device **110** and represented by the received plurality of activity samples **600**. The LAM circuit **136R** can be programmed to correlate processing activity to power consumption to estimate the power consumption of the monitored processing device **110** over the local time window. The LAM circuit **136R** can then be configured to generate an activity power event **606** representing the estimated power consumption of the monitored processing device **110** that is communicated to the aggregation circuit **608** of the RAM circuit **502** to be aggregated into the aggregated activity power event **138**.

(61) With continuing reference to FIG. **6**, the PEL circuit **126** may be configured to receive the aggregated activity power events **138** from the one or more RAM circuits **502** included in the hierarchical power management system **624**. In this example, the PEL circuit **126** includes a decode circuit **610** that is configured to decode the received aggregated activity power events **138** into decoded activity power events **611** to be routed to a corresponding activity tracker circuit **612(1)**-**612(T)** that are each associated with a monitored processing device **110** in the processor-based system **100**. The PEL circuit **126** can also include other energy tracker circuits (not shown) that are associated with other power events (e.g., temperature, droop detection) that can also affect how the PEL circuit **126** decides to throttle power. The activity tracker circuits **612(1)**-**612(T)** may be configured to aggregate associated activity power events **138** for an assigned monitored

processing device **110** to determine whether power consumption for a monitored processing device **110** exceeds a defined threshold current flow rate/change in current flow rate (di/dt). The activity tracker circuits **612(1)-612(T)** can also each include a power limit management policy that can be configured to generate respective power throttle recommendations **614(1)-614(T)** for the PEL circuit **126** to use to determine how to throttle the distributed power and/or performance of the monitored processing devices **110** to throttle power consumption.

(62) With continuing reference to FIG. 6, the PEL circuit **126** also includes a merge circuit **616** that merges the power throttle recommendations **614(1)-614(T)** for the individual monitored processing devices **110** into merged power throttle recommendations **618(1)-618(Q)**. The merged power throttle recommendations **618(1)-618(Q)** are provided to respective assigned target circuits **620(1)-620(Q)**. Each target circuit **620(1)-620(Q)** is associated with a different target device **200** in the processor-based system **100** in which the PEL circuit **126** can issue power limiting management responses **140(1)-140(Q)** to limit the power consumption of such target device **200**. The target devices **200** are devices in the IC chip **104** whose operational control (e.g., operating voltage, frequency, workload) can affect power consumption in the IC chip **104**. The target devices in the IC chip **104** can include more than just the processing devices **110** in the processor-based system **100**. For example, the target devices **200** can include the power rails **300(1)-300(5)**, as shown in FIG. 3 and/or any of the processing devices **110** in the processor-based system **100**. The PEL circuit **126** can be programmed to map (e.g., through firmware, electronic fuses, etc.) the merged power throttle recommendations **618(1)-618(Q)** to a particular target device **200**, and thus a target circuit **620(1)-620(Q)**, that may not directly correlate to each other. For example, it may be desired for the PEL circuit **126** to throttle power consumption of the I/O interface circuits **120(0)-120(X)** by not only throttling power consumption for the I/O interface circuits **120(0)-120(X)** but also by throttling power of the PU clusters **108(0)-108(N)** that may be contributing to the power consumption by the I/O interface circuits **120(0)-120(X)**. In this manner, the merged power throttle recommendations **618(1)-618(Q)** and/or other power events related to power issues and power consumption in the IC chip **104** can be mapped in the PEL circuit **126** to correlate to different target devices **200** for throttling power consumption. The merge circuit **616** can be programmed in a “many-to-many mapping” to correlate to different power-limiting management responses within the IC chip **104** in the desired manner for more flexibility in managing power consumption in the IC chip **104** while still achieving the desired performance. In this manner, the power throttling management behavior of the PEL circuit **126** can be configured and changed even after the IC chip **104** is deployed in an application.

(63) With continuing reference to FIG. 6, the target circuits **620(1)-620(Q)** may each be configured to determine if the power consumption of an associated target device **200** in the processor-based system **100** should be throttled based on the merged power throttle recommendations **618(1)-618(Q)** provided to the target circuits **620(1)-620(Q)**. The target circuits **620(1)-620(Q)** can each include finite state machine (FSM) circuits **622(1)-622(Q)** that are configured to analyze the respective received merged power throttle recommendation **618(1)-618(Q)** to determine if the power consumption of an associated target device **200** should be throttled. If an FSM circuit **622(1)-622(Q)** determines that the power consumption of an associated target device **200** in the processor-based system **100** should be throttled, the FSM circuit **622(1)-622(Q)** causes an associated power limiting command generation circuit **625(1)-625(Q)** to generate a power limiting management response **140(1)-140(Q)** to cause the power consumption of a target device **200** associated with the power limiting management response **140(1)-140(Q)** to limit power consumption.

(64) For example, if the target circuit **620(1)-620(Q)** is assigned to a target device **200** of a power rail **300(1)-300(5)**, the target circuit **620(1)-620(Q)** can be configured to determine how to throttle the voltage to the associated power rail **300(1)-300(5)** to control power consumption of processing devices **110** powered by such power rail **300(1)-300(5)**. The respective power limiting command

generation circuit **625(1)-625(Q)** can be configured to generate a performance throttling power limiting management response **140(1)-140(Q)** to cause the voltage provided to the associated power rail **300(1)-300(5)** to be throttled to control power consumption of processing devices **110** powered by such associated power rail **300(1)-300(5)**.

(65) In another example, if the target circuit **620(1)-620(Q)** is assigned to a target device **200**, such as the internal communication network **114**, the target circuit **620(1)-620(Q)** can be configured to determine how to throttle performance of the internal communication network **114** to control power consumption of the internal communication network **114**. For example, to throttle the throughput performance of the internal communication network **114**, the target device **200** may be the clock circuit **506** (FIG. 5) that is configured to clock the internal communication network **114**. The clock circuit **506** is another example of a target device **200** in the IC chip **104**. The target circuit **620(1)-620(Q)** can determine a throttle frequency of the clock signal **508** generated by the clock circuit **506** (FIG. 5) for generating a clock throttling power limiting management response **140(1)-140(Q)**. The clock throttling power limiting management response **140(1)-140(Q)** may cause the clock signal **508** to be throttled, which will, in turn, throttle the speed and the throughput performance of the internal communication network **114** and thus its power consumption and/or other circuits clocked by the clock signal **508**.

(66) In another example, if the target circuit **620(1)-620(Q)** is assigned to a target device **200** as a PU cluster **108(0)-108(N)** or any other processing device **110**, the target circuit **620(1)-620(Q)** can be configured to determine how to throttle performance of the internal communication network **114** to control power consumption of the internal communication network **114**. For example, to throttle performance of the PU cluster **108(0)-108(N)** or other processing device **110**, the target device **200** may be the clock circuit **506** (FIG. 5) that is configured to clock the PU clusters **108(0)-108(N)**. The target circuit **620(1)-620(Q)** can determine a throttle frequency of the clock signal **508** generated by the clock circuit **506** for generating a performance power limiting management response **140(1)-140(Q)**. The clock throttling power limiting management response **140(1)-140(Q)** will cause the clock signal **508** to be throttled, which will, in turn, throttle the performance of the PU clusters **108(0)-108(N)** or other processing devices **110**.

(67) As shown in FIG. 6, in this example, to communicate the power limiting management responses **140(1)-140(Q)** generated by the PEL circuit **126** to affect a power throttling of a target device **200** in the processor-based system **100**, the power limiting management responses **140(1)-140(Q)** are communicated to a target device **200** in the processor-based system **100**. For target devices **200** that are monitored processing devices **110** monitored by a LAM circuit **136** or RAM circuit **502**, the PEL circuit **126** can be configured to communicate an associated power limiting management response **140(1)-140(Q)** to the RAM circuit **502**. The RAM circuit **502** in this example includes a command processor **626** that is configured to receive a power limiting management response **140(1)-140(Q)** to process the power limiting management response **140(1)-140(Q)** to identify the LAM circuit **136** to communicate with to effectuate the power throttling requested in the received power limiting management response **140(1)-140(Q)**. In this example, the RAM circuit **502** includes a limiting command engine circuit **628** that is configured to generate a local power limiting management response **630** directed to the LAM circuit **136** that can effectuate the power throttling requested in the received power limiting management response **140(1)-140(Q)**. Note that if the local power limiting management response **630** is to throttle power consumption of multiple processing devices **110** monitored by multiple LAM circuits **136** associated with the RAM circuit **502**, the limiting command engine circuit **628** can address the local power limiting management response **630** to multiple LAM circuits **136**. Also note that in this example, if the RAM circuit **502** includes the LAM circuit **136R**, and the RAM circuit **502** is monitoring a processing device **110** that is the target device **200** to be throttled, the limiting command engine circuit **628** generates the local power limiting management response **630** directed to the LAM circuit **136R**.

(68) With continuing reference to FIG. 6, in response to a LAM circuit **136** receiving a local power limiting management response **630**, a power limiting management decode and sequencer circuit **632** may process the received local power limiting management response **630**. The power limiting management decode and sequencer circuit **632** may be configured to determine a power throttling response to be effectuated to a monitored processing device **110** based on the local power limiting management response **630**. In this regard, the power limiting management decode and sequencer circuit **632** may be configured to generate local throttle signals **634** to cause the power consumption in the processing device **110** to be throttled. For example, power limiting management decode and sequencer circuit **632** can be configured to generate a sequence of local throttle signals **634** to continually throttle up or down the power consumption of the monitored processing device **110** associated with its LAM circuit **136**.

(69) Note that in the sequence of operations and communications described above with regard to the LAM circuits **136** communicating activity power events **606** to the RAM circuits **502**, and the RAM circuits **502** communicating aggregated activity power events **138** to the PEL circuit **126**, communication delays are incurred. There is a delay between generating the activity samples **600** of sampling of power consumptions in a processing device **110** in a LAM circuit **136** and the reporting and receipt of an associated aggregated activity power event **138** in the PEL circuit **126**. This delay can be particularly large for an IC chip **104** that has a larger area, such as one that includes a number of PU clusters **108(0)-108(N)** and other processing devices **110** as in the processor-based system **100**. By the time the PEL circuit **126** receives the associated aggregated activity power event **138** and processes such to a generation of an associated power limiting management response **140(1)-140(Q)**, the power consumed by the monitored processing device **110** may have already exceeded desired power limits in an undesired manner and/or for an undesired amount of time, possibly causing the power consumption in the IC chip **104** to exceed designed power limits. Further, instantaneous current demand by a monitored processing device **110** can cause di/dt events or voltage droop events that can cause performance issues and/or failures that may not be able to be timely addressed by the PEL circuit **126**.

(70) To mitigate the delay in the PEL circuit **126** receiving aggregated activity power events **138** associated with monitored processing devices **110** in the processor-based system **100** that may affect throttling of power consumption within the processor-based system **100**, each of the LAM circuits **136**, **136R** can also be configured to directly throttle performance of an associated monitored processing device **110** to throttle its current demand and thus throttle its power consumption. This gives the PEL circuit **126** more reaction time to receive and process aggregated activity power events **138** to determine how power consumption in the processor-based system **100** should be throttled to achieve a desired overall performance while also maintaining power consumption within desired limits. In this manner, the LAM circuits **136**, **136R** may be able to more timely mitigate a power issue by locally throttling power consumption of its specific monitored processing device **110** on a device granularity (without having to throttle performance in other processing devices **110**). The LAM circuits **136**, **136R** can be configured to continuously monitor and throttle power consumption locally in its monitored processing device **110**, co-existent with the PEL circuit **126** generating power limiting management responses **140** to limit power consumption by target devices **200** in the processor-based system **100**.

(71) In this regard, as shown in FIG. 6, the LAM circuit **136** in this example includes a di/dt circuit **636** to track the rate of change of power consumption by the processing device **110** for local power consumption throttling of its monitored processing device **110**. In this regard, the di/dt circuit **636** may be configured to receive the estimated current demand **604** for the activity of the processing device **110** sampled by the LAM circuit **136** from the accumulate circuit **602** in each local time window. For each incoming estimated current demand **604** received (e.g., received for a given local time window), the di/dt circuit **636** may be configured to generate a next summed current demand **638** of such incoming estimated current demand **604** in the next local time window from the

accumulate circuit **602** with one or more previously received estimated current demands **604** received for a previous estimated current demand **604** in a previous local time window. In this manner, the next summed current demand **638** is a running sum of the estimated current demands **604** for the processing device **110** over consecutive local time windows. The di/dt circuit **636** may provide the next summed current demand **638** to an application processor **640** that provides a determined next current flow rate **642** based on the next summed current demand **638** to a throttle FSM circuit **644**. The throttle FSM circuit **644** may be configured to determine on an ongoing basis whether the next current flow rate **642** of the assigned processing device **110** exceeds a threshold current flow rate or indicates an excessive change in current flow rate beyond those configured for the monitored processing device **110** in the LAM circuit **136**. In response to determining that the next current flow rate **642** of the assigned processing device **110** exceeds the threshold current flow rate or indicates an excessive change in current flow rate, the throttle FSM circuit **644** is configured to generate the local throttle signals **634** to throttle the power consumption of the monitored processing device **110**.

(72) In this manner, the LAM circuit **136** may be configured to continually monitor the ongoing current flow rate of its monitored processing device **110** to be able to locally throttle the power consumption of the monitored processing device **110**. In this manner, the LAM circuit **136** may be configured to respond more quickly to power consumption issues caused by the current demand of the monitored processing device **110**, such as di/dt events and voltage droops, before the PEL circuit **126** may be able to respond.

(73) As an example, if the monitored processing device **110** by the LAM circuit **136** is a network node **500** of the internal communication network **114**, the local throttle signals **634** generated by the LAM circuit **136** may be a throughput throttle to selectively enable and disable communication flow in the network node **500** to throttle its throughput thus throttling its power consumption. As another example, if the monitored processing device **110** by the LAM circuit **136** is a PU cluster **108(0)-108(N)** or other processing device **110**, the local throttle signals **634** generated by the LAM circuit **136** may be a performance throttle to selectively throttle performance or workload of the monitored PU cluster **108(0)-108(N)** or other processing device **110** to throttle its performance thus throttling its power consumption.

(74) Note that sampling of processing activity discussed herein may be accomplished by determining or sampling a quantity that is associated with an instantaneous activity of the monitored processing device **110**. For example, the workload performed by a monitored processing device **100** may be determined or discoverable as an indirect method to determine instantaneous activity that can be correlated to an estimated current or power consumption. As another example, activity of a monitored processing device **110** may be determined by sensing a temperature at a temperature sensor associated with the processing device **110**. As another example, a voltage droop may be sensed at the processing device **110** to determine an activity sample. Also, other quantities may be used to sample activity. As an example, an incoming interrupt at the processing device, a status register, a state of an interrupt queue, or a signal indicating whether the processing device is busy or idle may be used for sampling of processing activity.

(75) Note that the components to perform local throttling by the LAM circuit **136** can also be provided in the LAM circuit **136R** in the RAM circuit **502** so that the LAM circuit **136R** may also be configured to locally throttle a monitored processing device **110**.

(76) Note that the hierarchical power management system **124** provided in the IC chip **104** for the processor-based system **100** in FIG. **1** is not limited to the three (3) level hierarchical power management system **624** in FIG. **6**. For example, FIG. **7** is a schematic diagram of an alternative two (2) level hierarchical power management system **724** that can be provided as the hierarchical power management system **124** in the processor-based system **100** in the IC chip **104** in FIGS. **1-3** and **5**. The hierarchical power management system **724** in FIG. **7** is similar to the hierarchical power management system **624** in FIG. **6**, except that the intermediate RAM circuits **502** are not

included in the hierarchical power management system **724** in FIG. 7. The LAM circuits **136** can be configured to provide activity power events **606** directly to the PEL circuit **126** to be processed. Common elements between the hierarchical power management system **724** in FIG. 7 and the hierarchical power management system **124** in FIGS. 1-3 and 5 are shown with common element numbers and are not re-described.

(77) Also, as discussed herein, it is stated that the PEL circuit **126** receives activity power events **606** from a LAM circuit **136**, this receipt of activity power events **606** can be directly from the LAM circuit **136** to the PEL circuit **126** or indirectly from one or more intermediate circuits, including the RAM circuits **502**. For example, as discussed above, the activity power events **606** generated by the LAM circuits **136** can be indirectly reported to the PEL circuit **126** the as part of being included in aggregated activity power events **138** generated and reported by a RAM circuit **502** to the PEL circuit **126** as part of received activity power events **606**.

(78) FIG. 8 is a flowchart illustrating an exemplary process **800** of the LAM circuits **136** and/or the RAM circuits **502** in hierarchical power management systems **124**, **624**, **724** in FIGS. 1-3 and 5-7 locally monitoring and throttling power consumption of monitored processing devices **110**. The process **800** also includes the hierarchically reporting activity power events **606**, **138** related to the monitored power consumption by LAM circuits **136** and/or the RAM circuits **502** to throttle power consumption in the processor-based system **100** in response to the received activity power events **606**, **138**. The process **800** in FIG. 8 is discussed with regard to the hierarchical power management systems **624**, **724** as examples.

(79) In this regard, as shown in FIG. 8, a first step of the process **800** can be sampling processing activity of an assigned processing device **110** of a plurality of processing devices **110** coupled to at least one power rails **300(1)-300(5)** of a plurality of power rails **300(1)-300(5)** to generate a plurality of activity samples **600** (block **802** in FIG. 8). A next step in the process **800** can be determining a current flow rate **642** of the assigned processing device **110** based on the plurality of activity samples **600** (block **804** in FIG. 8). A next step in the process **800** can be determining whether the current flow rate **642** of the assigned processing device **110** exceeds a defined threshold current flow rate (block **806** in FIG. 8). A next step in the process **800** can be throttling the processing activity of the assigned processing device **110** to throttle its power consumption in response to determining the current flow rate **642** of the assigned processing device **110** exceeds the threshold current flow rate (block **808** in FIG. 8). Also, in addition to and/or in parallel to steps **804-808**, another step in the process **800** can be estimating power consumption of the assigned processing device **110** based on the plurality of activity samples **600** (block **810** in FIG. 8). A next step in the process **800** can be generating an activity power event **606**, **138** based on the estimated power consumption of the assigned processing device **110** (block **812** in FIG. 8). A next step in the process **800** can be receiving a plurality of power events based on the activity power events **606**, **138** (block **814** in FIG. 8). A next step in the process **800** can be generating a power limiting management response **140** to cause power consumption to be throttled in the IC chip **104** based on the received plurality of activity power events **606**, **138** (block **816** in FIG. 8).

(80) FIG. 9A is a schematic diagram illustrating exemplary detail of the di/dt circuit **636** and throttle FSM circuit **644** in the LAM circuit **136** shown in FIG. 6 to collect received estimated current demands **604** for processing activity of a monitored processing device **110** over local time windows and determine if a current flow rate and/or change in current flow rate of the monitored processing device **110** exceeds a threshold. This information is used by the LAM circuit **136** to determine if its monitored processing device **110** should be locally throttled by its assigned LAM circuit **136**, as previously discussed in FIG. 6.

(81) In this regard, as shown in FIG. 9A, the di/dt circuit **636** is configured to receive next estimated current demands **604** that are generated for each local time window of the LAM circuit **136**, as discussed in FIG. 6. The di/dt circuit **636** includes a plurality of latch circuits **900(1)-900(4)** that are clocked circuits (e.g., flip-flops) and are configured to store the incoming next estimated

current demands **604** and previously received estimated current demands **604P(1)-604P(3)**. Latch circuit **900(1)** stores the next incoming estimated current demand **604**. The next incoming estimated current demand **604** stored in the latch circuit **900(1)** and the previous estimated current demands **604P(1)-604P(3)** stored in the latch circuits **900(1)-900(3)** are then shifted to the next respective latch circuit **900(2)-900(4)** for each newly received incoming estimated current demand **604** representing a local time window. For each incoming estimated current demand **604** received representing a local time window, the incoming estimated current demand **604** and previous estimated current demands **604P(1)-604P(3)** are provided to respective summing circuits **902(1)-902(4)**. The summing circuits **902(1)-902(3)** subtract the incoming estimated current demand **604** with a respective previous estimated current demand **604P(1)-604P(3)** to generate respective changes to current flow rates over local time windows (i.e., change in current flow rates) di_dt_1 , di_dt_2 , di_dt_3 , as discussed below, of the incoming estimated current demand **604** and the respective estimated current demands **604P(1)-604P(3)**. Thus, the determined change in current flow rates di_dt_1 , di_dt_2 , di_dt_3 represent a rate in change in current flow rate or current demand and thus rate of change in power consumption of the monitored processing device **110** between the local time windows when the incoming estimated current demand **604** was received and a previous local time window of the respective previous estimated current demands **604P(1)-604P(3)**. di_dt_1 is the change in current or current flow rate between respective estimated current demand **604** and **604P(1)**. di_dt_2 is the change in current or current flow rate between respective estimated current demand **604** and **604P(2)**. di_dt_3 is the change in current or current flow rate between respective estimated current demand **604** and **604P(3)**.

(82) With continuing reference to FIG. 9A, these changes in current flow rates di_dt_1 , di_dt_2 , di_dt_3 may then be provided to a multiplexing circuit **904** that can selectively provide one of the changes in current flow rates di_dt_1 , di_dt_2 , di_dt_3 as the next current flow rate **642** to a comparator circuit **906** in the throttle FSM circuit **644**, discussed below. The selected change in current flow rate di_dt_1 , di_dt_2 , di_dt_3 provided as the next current flow rate **642** to the multiplexing circuit **904** may be based on a local time window selection signal $sel_di_dt_window$ to select the local time windows to be compared to each current flow rate. This allows the flexibility of the di/dt circuit **636** to be programmed to select the local time windows of estimated current demands **604P(1)**, **604P(2)** to be compared to the incoming estimated current demand **604**. For example, FIG. 9B is a graph **920** illustrating exemplary incoming and estimated current demands **604**, **604P(1)-604P(3)** collected by the di/dt circuit **636** in FIG. 9A plotted as a function of a local time window to show how the incoming and estimated current demands **604**, **604P(1)-604P(3)** can be subtracted to generate respective change in current flow rates di_dt_1 , di_dt_2 , di_dt_3 between the incoming estimated current demand **604** and the estimated current demands **604P(1)-604P(3)** over their respective local time windows twN , $twN-1$, $twN-2$, $twN-3$. The duration of the local time windows is known. Thus, the change in current flow rates di_dt_1 , di_dt_2 , di_dt_3 represent a change in current demand between the incoming estimated current demand **604** in a current local time window and a respective previous estimated current demand **604P(1)-604P(3)** over the difference in their local time windows. The current flow rate curve **922** represents the current flow rate of a processing device **110** over a period of local time windows $twN-3$, $twN-2$, $twN-1$, and twN . As shown in FIG. 9B, the slope of the current flow rate curve **922** changes at each of the local time windows $twN-3$, $twN-2$, $twN-1$, and twN based on the change in current demand or change in current flow rate demanded of the processing device **110** between local time windows $twN-3$, $twN-2$, $twN-1$, and twN . FIG. 9B shows the basis on which the di/dt circuit **636** in FIG. 9A can generate the change in current flow rates di_dt_1 , di_dt_2 , di_dt_3 representing a change in current demand between the incoming estimated current demand **604** in a current local time window and a respective previous estimated current demand **604P(1)-604P(3)** over the difference in their local time windows $twN-3$, $twN-2$, $twN-1$, and twN . This can be used to provide the current flow rate **642** of the processing device **110** to use to determine local power

consumption throttling.

(83) The selected next current flow rate **642** is provided by the di/dt circuit **636** to the comparator circuit **906** in the throttle FSM circuit **644**. The throttle FSM circuit **644** may be configured to generate the local throttle signals **634** to throttle power consumption of the monitored processing device **110** based on whether the selected next current flow rate **642** (from selection of change in current flow rate di_dt_1, di_dt_2, di_dt_3) exceeds a threshold current flow rate (which can include a threshold change in current flow rate) for the monitored processing device **110**. The threshold current flow rate for the monitored processing device **110** can be obtained from a current flow rate register **908**. The current flow rate register **908** can be programmed with a threshold current flow rate for the monitored processing device **110**. For example, the current flow rate register **908** can be programmed with different threshold current flow rates (e.g., lowest, level 1, level 2, highest) so that the comparator circuit **906** can generate local throttle signals **634** for different levels of power consumption throttling based on the comparison of selected next current flow rate **642** (from selection of change in current flow rate di_dt_1, di_dt_2, di_dt_3) with the selected threshold current flow rate obtained from the current flow rate register **908**.

(84) Note that when current flow rate is discussed herein, such also means current flow and represents current (I) (e.g., charge (q) over time (t) (q/t)) or a change in the current flow rate (e.g., a change in current over time (di/dt)). A determined change in the current flow rate (di/dt) is determined from a determined current flow rate (t/T).

(85) The components of the hierarchical power management systems **124**, **624**, **724** in FIGS. 1-3 and 5-7 described above can be provided in different implementations. For example, FIG. 10 is a logic diagram of another exemplary PEL circuit **1026** that can be any of PEL circuits **126** provided in the hierarchical power management system **124**, **624**, **724** in FIGS. 1-3 and 5-7. Common elements between the PEL circuit **1026** in FIG. 10 and the PEL circuit **126** in the hierarchical power management system **124**, **624**, **724** in FIGS. 1-3 and 5-7 are shown with common element numbers.

(86) In another example of the components of the hierarchical power management systems **124**, **624**, **724** in FIGS. 1-3 and 5-7 described above, FIG. 10 shows the PEL circuit **1026** configured to receive the aggregated activity power events **138(1)-138(5)** from the one or more RAM circuits **502**. The PEL circuit **1026** can be the PEL circuit **126** provided in the hierarchical power management system **124**, **624**, **724** in FIGS. 1-3 and 5-7. In this example, the PEL circuit **1026** includes the decode circuit **610** that is configured to decode the received aggregated activity power events **138(1)-138(5)** into the corresponding activity tracker circuit **612(1)-612(T)** as previously described. The PEL circuit **1026** in this example also includes energy tracker circuits **1000(1)-1000(E)** that are associated with energy power events **1002**, such as PMIC telemetry power events **1002(1)**, temperature events **1002(2)**, and voltage droop detection events **1002(3)** (all of which are examples of non-activity power events), that can also affect how the PEL circuit **1026** decides to throttle power. The PEL circuit **1026** in this example also includes maximum average power (MAP) tracker circuits **1004(1)-1004(B)**, which are circuit trackers that track the total power consumed in the SoC **120** according to a defined maximum power consumption limit. Similar to the activity tracker circuits **612(1)-612(T)**, the energy tracker circuits **1000(1)-1000(E)** and the MAP tracker circuits **1004(1)-1004(B)** are configured to respective energy power events **1002(1)-1002(3)** and/or aggregated activity power events **138(1)-138(5)** to determine whether a factor exists that is dependent on power consumption that exceeds a defined power (e.g., current) threshold/limit.

(87) The energy tracker circuits **1000(1)-1000(E)** may each include respective data aggregator circuits **1016(1)-1016(E)** that are configured to aggregate the received energy power events **1002** into respective aggregated energy power events **1018(1)-1018(E)**. The activity tracker circuits **612(1)-612(T)** may also each include respective data aggregator circuits **1020(1)-1020(T)** that are configured to aggregate received energy power events into respective aggregated energy power

events **1022(1)-1022(T)**. The MAP tracker circuits **1004(1)-1004(B)** may also each include respective data aggregator circuits **1024(1)-1024(T)** that are configured to aggregate received energy power events into respective aggregated MAP power events **1027(1)-1027(B)**. The energy tracker circuits **1000(1)-1000(E)**, the activity tracker circuits **612(1)-612(T)**, and the MAP tracker circuits **1004(1)-1004(B)** in this example, each include a respective energy power limit management policy circuits **1006**, activity power limit management policy circuits **1008**, and MAP power limit management policy circuits **1010** that are configured to generate respective energy power throttle recommendations **1012**, activity power throttle recommendations **614**, and MAP power throttle recommendations **1014**. These generated respective energy power throttle recommendations **1012**, activity power throttle recommendations **614**, and MAP power throttle recommendations **1014** may be based on the respective received aggregated energy power events **1018(1)-1018(E)**, aggregated activity power events, **1022(1)-1022(T)**, aggregated MAP power events **1027(1)-1027(B)** for the PEL circuit **1026** to process to determine how to throttle power consumption in the IC chip **104**.

(88) With continuing reference to FIG. **10**, the energy tracker circuits **1000(1)-1000(E)**, the activity tracker circuits **612(1)-612(T)**, and the MAP tracker circuits **1004(1)-1004(B)** are configured to compare a power consumption indicated by the respective aggregated energy power events **1018(1)-1018(E)**, aggregated activity power events **1022(1)-1022(T)**, and aggregated MAP power events **1027(1)-1027(B)**, to the respective energy power limit management policy circuits **1006**, activity power limit management policy circuits **1008**, and MAP power limit management policy circuits **1010** energy tracker circuits **1000(1)-1000(E)**, the activity tracker circuits **612(1)-612(T)**, and the MAP tracker circuits **1004(1)-1004(B)**. The energy tracker circuits **1000(1)-1000(E)**, the activity tracker circuits **612(1)-612(T)**, and the MAP tracker circuits **1004(1)-1004(B)** may then be configured to generate the respective energy power throttle recommendations **1012**, activity power throttle recommendations **614**, and MAP power throttle recommendations **1014** based on the comparison of the power consumptions indicated by the respective aggregated power events **1018(1)-1018(E)**, **1022(1)-1022(T)**, **1027(1)-1027(B)** to the respective power limit management policy circuits **1006**, **1008**, **1010**. For example, the energy power limit management policy circuits **1006**, the activity power limit management policy circuits **1008**, and the MAP limiting management policy circuits **1010** may each have respective a threshold power consumption that is compared to the respective aggregated power events **1018(1)-1018(E)**, **1022(1)-1022(T)**, **1027(1)-1027(B)** to determine the respective power throttle recommendations **1012**, **614**, **1014**.

(89) With continuing reference to FIG. **10**, the PEL circuit **1026** also includes the merge circuit **616** that merges the energy power throttle recommendations **1012**, generates respective activity power throttle recommendations **614**, and MAP power throttle recommendations **1014** into merged power throttle recommendations **618(1)-618(6)**. The merged power throttle recommendations **618(1)-618(6)** are provided to respective assigned target circuits **620(1)-620(6)**. Note that each merged power throttle recommendation **618(1)-618(6)** can be influenced by power throttle recommendations from each of the energy power throttle recommendations **1012**, generate respective activity power throttle recommendations **614**, and MAP power throttle recommendations **1014**. Each target circuit **620(1)-620(6)** is associated with a different target device **200** in the processor-based system **100** in which the PEL circuit **1026** can issue power limiting management responses **140(1)-140(6)** to limit the power consumption of such target device **200**.

(90) The target devices **200** can include the interface circuits **127(1)-127(Z)** that can be throttled by power limiting management responses **140(1)** communicated to a RAM circuit **502(6)** and/or LAM circuit **136(6)** configured to throttle power consumption in such interface circuits **127(1)-127(Z)**. The target devices **200** can include the PU clusters **108(0)-108(N)** that can be throttled by power limiting management responses **140(2)** communicated to a RAM circuit **502(1)** and/or LAM circuit **136(1)** configured to throttle power consumption in such PU clusters **108(0)-108(N)**. The target devices **200** can include the internal communication network **114** that can be throttled by power

limiting management responses **140(3)** communicated to a RAM circuit **502(3)** and/or LAM circuit **136(3)** configured to throttle power consumption in such internal communication network **114**. The target devices **200** can include the memory controllers **118(0)-118(M)** that can be throttled by power limiting management responses **140(4)** communicated to a RAM circuit **502(2)** and/or LAM circuit **136(2)** configured to throttle power consumption in such memory controllers **118(0)-118(M)**. The target devices **200** can include the I/O interface circuits **120(0)-120(X)** that can be throttled by power limiting management responses **140(5)** communicated to a RAM circuit **502(4)** and/or LAM circuit **136(4)** configured to throttle power consumption in such I/O interface circuits **120(0)-120(X)**. The target devices **200** can include the S2S interface circuits **122(0)-122(Y)** that can be throttled by power limiting management responses **140(6)** communicated to a RAM circuit **502(5)** and/or LAM circuit **136(5)** configured to throttle power consumption in such S2S interface circuits **122(0)-122(Y)**.

(91) The merge circuit **616** in the PEL circuit **1026** can be programmed to map (e.g., through firmware, electronic fuses, etc.) merged power throttle recommendations **618(1)-618(6)** to a particular target device **200**, and thus a target circuit **620(1)-620(6)**, that may not directly correlate to each other. In this manner, the merged power throttle recommendations **618(1)-618(6)** related to power issues and power consumption in the IC chip **104** can be mapped in the PEL circuit **1026** to correlate to different target devices **200** for throttling power consumption. The merge circuit **616** can be programmed in a “many-to-many mapping” to correlate to different power-limiting management responses within the IC chip **104** in the desired manner for more flexibility in managing power consumption in the IC chip **104** while still achieving the desired performance. In this manner, the power throttling management behavior of the PEL circuit **1026** can be configured and changed even after the IC chip **104** is deployed in an application.

(92) With continuing reference to FIG. **10**, the target circuits **620(1)-620(6)** may each be configured to determine if the power consumption of an associated target device **200** in the processor-based system **100** should be throttled based on the merged power throttle recommendations **618(1)-618(6)** provided to the target circuits **620(1)-620(6)**. The target circuits **620(1)-620(6)** may each be configured to analyze the respectively received merged power throttle recommendation **618(1)-618(6)** to determine if the power consumption of an associated target device **200** should be throttled. If a target circuit **620(1)-620(Q)** determines that the power consumption of an associated target device **200** in the processor-based system **100** should be throttled, the target circuit **620(1)-620(Q)** causes an associated power limiting management response **140(1)-140(6)** to be generated to be communicated to a respective RAM circuit **502(1)-502(6)** and/or LAM circuit **136(1)-136(6)** cause the power consumption of a target device **200** associated with the power limiting management response **140(1)-140(Q)** to limit power consumption.

(93) The components of a power management system, such as hierarchical power management systems **124**, **624**, **724** in FIGS. **1-3** and **5-7** described above, can be provided in different implementations, including circuits that implement throttling locally. As an example, FIG. **11** is a block diagram of an exemplary throttle control circuit **1100** configured to receive a throttle control signal **1102** for controlling power in processing segment circuits **1104(1)-1104(X)** in an IC chip **1106**. The throttle control circuit **1100** provides, to the processing segment circuits **1104(1)-1104(X)** in a number (N) of consecutive cycles of a clock signal CLK, selected activity control signals **1108(1)-1108(X)** configured to throttle activity in a number (M) of the cycles in the window, where the number M may vary among the processing segment circuits **1104(1)-1104(X)**. Each processing segment circuit **1104(1)-1104(X)** is a segment of the processing circuits associated with a LAM circuit **1110** that may be separately throttled by the throttle control circuit **1100**. Each of the processing segment circuits **1104(1)-1104(X)** operates in response to the clock signal CLK, which is a periodic clock employed to synchronize state changes in the IC chip **1106**. Herein, “operation” of the processing segment circuits **1104(1)-1104(X)** refers to state change activity and/or switch activity in sequential circuits in response to the clock signal CLK.

(94) The throttle control circuit **1100** may be included in the LAM circuit **1110**, which may be any of the LAM circuits **136** in FIG. 1, 2, or 5. The throttle control signal **1102** may be generated in a throttle request accumulate circuit **1112** based on throttle requests **1114(1)-1114(R)** generated circuits for monitoring power-related events and conditions. For example, the throttle requests **1114(1)-1114(R)** may be generated in a di/dt circuit **1116** in the LAM circuit **1110**, a temperature sensor **1118** that is located near the LAM circuit **1110**, and/or in one or more additional monitoring circuits **1120** that monitor an indication of power consumption. For example, the monitoring circuits **1120** may provide a throttle request based on any of firmware instructions, current events or conditions, power events or conditions, and activity events or conditions. The di/dt circuit **1116** and the temperature sensor **1118** may be the di/dt circuit **636** in FIG. 6 and the temperature sensor **132** in FIG. 2. The throttle control signal **1102** based on the throttle requests **1114(1)-1114(R)** indicates a throttle control value **1122** that may be any of N values based on the throttle requests **1114(1)-1114(R)**. The throttle requests **1114(1)-1114(R)** may vary according to any of rate of change of current, temperature, level of detected activity, etc.

(95) Each processing segment circuit **1104(1)-1104(X)** includes at least one transistor circuit configured to change an output voltage state in response to the clock signal CLK. The processing segment circuits **1104(1)-1104(X)** associated with the LAM circuit **1110** may each be located adjacent to another one of the processing segment circuits **1104(1)-1104(X)** and may each be coupled to a same power rail to receive a power supply voltage.

(96) The purpose of the throttle control circuit **1100** in this example is to provide local control or throttling of activity in the processing segment circuits **1104(1)-1104(X)** associated with the LAM circuit **1110**. Activity in the processing segment circuits **1104(1)-1104(X)** refers to state changes or changes in a voltage state on the outputs of sequential circuits that occur in response to the clock signal CLK. For example, the voltage level on outputs of storage circuits, including memory circuits, latch circuits, and/or flip-flop circuits among the processing segment circuits **1104(1)-1104(X)**, may change state (e.g., switch) in response to a voltage or a change in voltage (e.g., a level, transition or edge) of the clock signal CLK. Such state changes cause a surge in current in the power rail(s), providing a power supply voltage to the processing segment circuits **1104(1)-1104(X)**. The number of circuits that switch in response to the clock signal CLK at a given moment varies depending on circumstances, such as a type of instructions being executed, a frequency of executing instructions, the data being processed, and other factors. As a result, the current and power requirements vary. Circuits can be provided to monitor current and power in an area local to the LAM circuit **1110** by detecting electrical characteristics such as current level, rate of change of current (di/dt), power level, rate of change of power consumption, or temperature. Current and power can also be measured indirectly by monitoring processing activity, such as by firmware. When these monitoring circuits determine, based on the particular aspect of current or power states or events that they measure, that the amount of activity in the processing segment circuits **1104(1)-1104(X)** should be reduced, they can generate one of the threshold requests **1114(1)-1114(R)**, which are the throttle requests **1114(1)-1114(R)** from FIG. 11. The throttle request accumulate circuit **1112** receives the throttle requests **1114(1)-1114(R)** and generates the throttle control signal **1102** based on a predetermined algorithm or voting method.

(97) Stopping all activity in the processing segment circuits **1104(1)-1104(X)** would be an extreme and unnecessary response to a minor di/dt event, for example. For a more appropriate response, the throttle requests **1114(1)-1114(R)** each provide one of several values in a range to indicate, based on the severity of the problem detected (e.g., event or condition), an appropriate request for a reduction in activity. Consequently, the throttle control signal **1102** is a value based on the respective throttle requests. A reduction of activity in the processing segment circuits **1104(1)-1104(X)** can be achieved by reducing the number of cycles within a window of consecutive cycles (clock window) of the clock signal CLK, in which switching or state changes are allowed (enabled) to occur. Maximum power is consumed when switching is enabled in all (100

percent) of the cycles of the clock signal CLK. In a clock window including a number (N) of consecutive cycles of the clock signal CLK, activity can be reduced in the processing segment circuits **1104(1)-1104(X)** incrementally by reducing the number of cycles in which activity is enabled from N to 1. Thus, the number of possible values of the throttle control signal **1102** may equal to the number N of consecutive cycles in a clock cycle window of the clock cycle.

(98) However, not all of the processing segment circuits **1104(1)-1104(X)** may be identical in power consumption characteristics, as individual ones may perform different functions and therefore consume different amounts of power or may cause different rates of increase and/or decrease in current drawn on the power rail(s). In this regard, equally reducing the number of cycles of activity in all of the processing segment circuits **1104(1)-1104(X)** may not be necessary or desirable to achieve the desired change in the power distribution. In addition, performance can be optimized for each incremental level of requested throttle reduction by varying the extent to which activity is reduced among the processing segment circuits **1104(1)-1104(X)** in a configurable manner. Such configuration may be based on testing and programming of the IC chip **1106**.

(99) FIG. **12** is a block diagram of a throttle control circuit **1200**, including a plurality of throttle administration circuits **1202(1)-1202(X)**, each configured to receive a throttle control signal **1204** from a throttle request accumulate circuit **1206**. The throttle administration circuits **1202(1)-1202(X)** each generate one of throttle select signals **1208(1)-1208(X)** corresponding to one of the plurality of processing segment circuits **1104(1)-1104(X)** in FIG. **11**. The throttle select signals **1208(1)-1208(X)** have corresponding throttle select values **1207(1)-1207(X)** that may each be set to one of N possible values based on the throttle control values **1209** of the throttle control signal **1204** and also based on a corresponding one of throttle configuration signals **1210(1)-1210(X)**. In this example, the throttle configuration signals **1210(1)-1210(X)** are generated from configuration information **1212** stored in a configuration register **1214**.

(100) Implementation of an optimized incremental approach to activity reduction in the processing segment circuits **1104(1)-1104(X)** includes storing individualized configuration information **1212** for each of the processing segment circuits **1104(1)-1104(X)** in the configuration register **1214** for each incremental change in the throttle control value **1209** designated by the throttle control signal **1204**. Receiving both the throttle control value **1209** and the configuration information **1212**, the throttle administration circuits **1202(1)-1202(X)** generate selections of appropriate levels of activity for each one of the processing segment circuits **1104(1)-1104(X)**. The throttle administration circuit **1202(1)-1202(X)** is configured to, for a given throttle control value **1209**, determine the number of cycles, among the first number (N) of cycles, that activity in a corresponding one of the processing segment circuits **1104(1)-1104(X)** is disabled based on the configuration information **1212**.

(101) In a further aspect, while some of the throttle requests **1114(1)-1114(R)** are based on measures (e.g., of events or conditions) that change slowly, others may be based on measures that can change significantly from cycle to cycle. In addition, one of the benefits of locally applied throttle control is the ability to respond to detected problems quickly. Therefore, the throttle control circuit **1200** is configured to respond in a next cycle of the clock signal CLK to request a significant reduction in activity in the processing segment circuits **1104(1)-1104(X)**. On the other hand, sudden increases in activity in the processing segment circuits **1104(1)-1104(X)** can cause sudden increases in current that may result in a voltage droop, for example. Consequently, even if the throttle control signal **1204** indicates that a significant increase in activity is allowed, the throttle administration circuits **1202(1)-1202(X)** may not allow a significant increase to occur during one or a few cycles. Rather, to avoid sudden increases in current and power, the throttle administration circuits **1202(1)-1202(X)** may be implemented as finite state machines, referred to collectively as FSMs **1202**. The FMSs **1202** can gradually increase activity in the corresponding processing segment circuits **1104(1)-1104(X)** at a configurable rate. In view of the above considerations, the throttle administration circuits **1202(1)-1202(X)** generate the throttle select signals **1208(1)-1208(X)** that are each directed to one of the processing segment circuits

1104(1)-1104(X). The throttle select values **1207(1)-1207(N)** of the throttle select signals **1208(1)-1208(X)** are based on the most recent throttle control value **1209**, the configuration information **1212** indicating the appropriate activity level for the corresponding one of the processing segment circuits **1104(1)-1104(X)** at that throttle control value **1209**, and a transition limitation imposed by the FSM limiting the number of states by which the FSM **1202** can change in one direction. The throttle select signals **1208(1)-1208(X)** are provided to a throttle sequence selection circuit shown in FIG. **13**. Detailed operations of the throttle administration circuits **1202(1)-1202(X)** is described in more detail with reference to FIG. **15** below.

(102) FIG. **13** is a block diagram showing details of a throttle sequence selection circuit **1300** configured to receive the throttle select signals **1208(1)-1208(X)** in FIG. **12** corresponding to each of the plurality of processing segment circuits **1104(1)-1104(X)** in FIG. **11**. As noted above, the level of activity in a cycle window of N consecutive cycles can be in the range from N active cycles with no inactive cycles to one (1) active cycle (with $N-1$ inactive cycles). The throttle sequence selection circuit **1300** includes throttle sequence generators **1302(1)-1302(N)** that each generate sequence signals **1304(1)-1304(N)** that repeat every N cycles, where each of the sequence signals **1304(1)-1304(N)** is in a first state for M cycles and in a second state for $N-M$ cycles, where M ranges from zero (0) to $N-1$.

(103) In an example in which the clock window is eight (8) consecutive cycles (i.e., $N=8$), the value of M ranges from zero (0) to seven (7). In such an example, the throttle sequence generator **1302(1)** may generate a sequence in which the sequence signal **1304(1)** is in a first state (e.g., "0" or "1") for $M=1$ cycle and a second state (e.g., "1" or "0") for $N-M$ or $8-1=7$ cycles. Here, the first state is provided to enable (allow) activity in the processing segment circuits **1104(1)-1104(X)**, and the second state is provided to disable activity. In additional examples, the throttle sequence generator **1302(3)** may generate a sequence signal **1304(3)** that is in a first state for 3 cycles and a second state for 5 cycles, and the throttle sequence generator **1302(8)** may generate a sequence signal **1304(8)** that is in the first state for 8 cycles and the second state for 0 cycles. As should be apparent, the sequence signal **1304(8)** is provided to any of the processing segment circuits **1104(1)-1104(X)** in which no throttling or reduction in activity is requested, and the sequence signal **1304(1)** is provided for the most restrictive throttling response, allowing only one active cycle per cycle window.

(104) The throttle sequence selection circuit **1300** includes multiplexors **1306(1)-1306(X)**, each corresponding to one of the processing segment circuits **1104(1)-1104(X)**. Each of the sequence signals **1304(1)-1304(N)** is provided to each of the multiplexors **1306(1)-1306(N)**. The throttle select signals **1208(1)-1208(X)** generated in the throttle administration circuits **1202(1)-1202(X)** in FIG. **12** are employed by the multiplexors **1306(1)-1306(N)** to select, for each of the processing segment circuits **1104(1)-1104(X)**, a corresponding one of sequence signals **1304(1)-1304(N)** to throttle activity. Selected ones of the sequence signals **1304(1)-1304(N)** are provided on outputs **1308(1)-1308(X)** as activity control signals **1310(1)-1310(X)**, which are provided to the corresponding processing segment circuit **1104(1)-1104(X)**.

(105) It can easily be recognized that the number N of throttle sequence generators **1302(1)-1302(N)** in this example is determined by the number of different sequences that can be provided, which, in this case, corresponds to the number N of cycles in the clock window in the examples above. In another non-limiting example, rather than providing sequence signals **1304(1)-1304(N)** having each increment from 1 to N active cycles, throttle sequence generator **1302(1)-1302(N/2)** generating sequence signals **1304(1)-1304(N/2)** having only even numbers of active cycles (e.g., 2, 4, 6, and 8) may be employed. In such a case, for a cycle window having 8 cycles, only four (4) throttle sequence generators may be needed. Other cases, including odd numbers of active cycles or any combination of active and inactive signals are also possible.

(106) The number X of throttle administration circuits **1202(1)-1202(X)** in FIG. **12** is determined by a maximum number of the processing segment circuits **1104(1)-1104(X)** that can be controlled

by the throttle control circuit **1100**. Although the number X of throttle administration circuits **1202(1)-1202(X)** in the throttle control circuit **1100** may be greater than or less than the actual number of separately controlled processing segment circuits **1104(1)-1104(X)**, it is the same number in this example. The number X of multiplexors **1306(1)-1306(X)** corresponds to the number of the throttle administration circuits **1202(1)-1202(X)**, where each multiplexor is controlled by a corresponding one of the throttle administration circuits **1202(1)-1202(X)**. In the example in FIG. 13, although the number N of throttle sequence generators **1302(1)-1302(N)** and the number X of multiplexors **1306(1)-1306(X)** are equal (i.e., 8), it should be recognized that this is merely coincidental as the number N of throttle control values **1209** and the number X of separately controlled processing segment circuits **1104(1)-1104(X)** are independent of each other. The plurality of throttle sequence generators **1302(1)-1302(N)** generate the select signals **1304(1)-1304(N)** to disable every number, from 0 to N-1, of the cycles of the N consecutive cycles in a clock window. Thus, in response to a highest possible throttle control value **1209**, the FSMs **1202** are configured to provide activity control signals **1306(1)-1304(X)** to (depending on configuration information **1212**) disable activity in the processing segment circuits **1104(1)-1104(X)** in all but one of the cycles of the consecutive cycles of the clock window. In response to a lowest throttle control value **1209**, the FSMs **1202** are configured to provide an activity control signal **1306(1)-1306(X)** that does not disable activity in any of the cycles of the consecutive cycles of the clock window.

(107) FIG. 14 is a timing diagram **1400** illustrating the sequence signals **1304(1)-1304(N)** that are generated by the throttle sequence generators **1302(1)-1302(N)** and provided to disable activity (e.g., state changes) in a processing segment circuits **1104(1)-1104(X)** in different numbers of cycles of the cycle window of N consecutive cycles. Time proceeds from left to right in timing diagram **1400**.

(108) The sequence signals **1304(1)-1304(N)** are labeled in FIG. 14 based on their respective numbers of cycles in which activity is disabled. Referring to the description above, sequence signal **1304(1)** (e.g., M=1) is designated "7/8" because this signal causes activity to be disabled in 7 cycles of the 8-cycle clock window. The sequence signal **1304(3)** (e.g., M=3) is designated "5/8" because this signal causes activity to be disabled in 5 cycles of the 8-cycle clock window, and the sequence signal **1304(8)** (e.g., M=8), is designated "0/8" because this signal does not disable activity in any of the 8 cycles in the clock window.

(109) In the cycle window **W0**, in response to the enable signal **EN** being activated in cycle 1 of the clock signal **CLK**, the sequence signals indicated by 1/8 through 7/8 change from an enable state to a disable state (indicated by a transition from "0" to "1") to disable activity in the processing segment circuits **1104(1)-1104(X)** while the sequence signal 0/8 remains in the enable state. In each subsequent cycle, one of the sequence signals 1/8 through 7/8 transitions back to the enable state before the cycle window **W0** ends. Since the enable signal **EN** continues to be active in cycle window **W1**, the sequence signals 0/8 through 7/8 are repeated until the enable signal **EN** is deactivated in cycle window **W2**.

(110) FIG. 15 is a state diagram **1500** including states **1502(0)-1502(7)** of the throttle administration circuits **1202(1)-1202(X)** and is provided to illustrate examples of state transitions of the throttle administration circuits **1202(1)-1202(X)**, which occur in response to changes of the throttle control signal **1204** in FIG. 12 and also depend on the configuration information **1212** described above. Each FSM **1202** may have a number of states **1502(0)-1502(7)** equal to the number N of consecutive cycles in a clock window of the clock signal **CLK**.

(111) Any of the throttle administration circuits **1202(1)-1202(X)** being in the states **1502(0)** to **1502(7)** cause the corresponding sequence signals 0/8 to 7/8, respectively, to be selected by the multiplexors **1306(1)-1306(X)**. Generally, increases in the control value **1209** will result in upward transitions to more restrictive throttling of the processing segment circuits **1104(1)-1104(X)**. In this example, an upward transition refers to transitioning to a higher-numbered state, where state

1502(7) is the highest-numbered state and state **1502(0)** is the lowest. Since it is preferable to respond quickly to increases in throttling to avoid or reduce power-related problems, upward transitions may occur from any one of the states **1502(1)-1502(6)** to any higher numbered state (e.g., states **1502(2)-1502(7)**). For example, FIG. 15 illustrates any of upward transitions **1504(1)-1504(7)** may occur directly from the least restrictive state **1502(0)** to any of the more restrictive states **1502(1)-1502(7)**, depending on the throttle control signal **1204** and the configuration information **1212** in FIG. 12. In other words, the FSM **1202** can transition directly from no throttling (0/8 in FIG. 14) to any of the throttling states **1502(1)-1502(7)** that select sequence signals 1/8 to 7/8. Here, the term “transition directly” indicates that a transition may occur in a next clock cycle. Although not shown in FIG. 15, to reduce drawing congestion, upward direct transitions may also occur in the FSM **1202** from any one of the states **1502(1)-1502(6)** to any higher numbered state (e.g., states **1502(2)-1502(7)**).

(112) The FSM **1202** may remain in the least restrictive state **1502(0)**, for any number of cycles until the throttle control signal **1204** increases, causing a transition to one of the more restrictive states **1502(1)-1502(7)**. Since the throttling function is implemented by the sequence signals 0/8 to 7/8, the FSM **1202** remains in any of the states **1502(1)-1502(7)** for at least a full clock window (e.g., 8 cycles corresponding to clock windows **W0** and **W1** in FIG. 14) if the throttle control signal **1204** remains the same or reduces. If there is an increase in the throttle control signal **1204**, the clock window may be interrupted at any cycle by a transition to a more restrictive state.

(113) The state diagram **1500** also includes downward transitions **1506(2)-1506(7)** and downward transitions **1508(1)-1508(7)**, which are examples of transitions that may occur in response to decreases in the throttle control value **1209**. Downward transitions **1506(2)-1506(7)** and downward transitions **1508(1)-1508(7)** are transitions to lower states in the FSM **1202**, which correspond to less restriction on activity in the processing segment circuits **1104(1)-1104(X)**, and thus higher power consumption. For this reason, sudden significant increases in activity are avoided. In this regard, at the end of a clock window, if the throttle control signal **1204** has decreased (and assuming the configuration information **1212** is not conflicting with a reduction in throttling), the FSM **1202** will transition to a lower state where more activity is allowed in the processing segment circuits **1104(1)-1104(X)**. However, to avoid sudden surges in current due to the increased activity, the FSM **1202** may limit the downward transition to a state that is, for example, only one state or two states lower than a current state.

(114) Referring back to FIG. 15, it can be seen that the downward transitions **1506(2)-1506(7)** are transitions of two (2) states, such as from state **1502(2)** to state **1502(0)** or from state **1502(7)** to state **1502(5)**, which are allowed if the throttle control signal **1204** drops two levels or more. Alternatively, the FSMs **1202** may implement downward transitions **1508(1)-1508(7)**, which indicate a transition from any state to a next lower state. In this example, a downward transition **1508(1)** is a transition from state **1502(1)** to state **1502(0)** and downward transition **1508(7)** is from state **1502(7)** to state **1502(6)**. In other words, in response to an increase of the throttle control signal **1204** from a first throttle control value **1209** in a first cycle to a second throttle control value **1209** in a next cycle, each of the plurality of throttle administration circuits **1202(1)-1202(X)** is configured to transition (upward) from a first one of the states **1502(0)-1502(6)** corresponding to the first throttle control value **1209** to one of the states **1502(1)-1502(7)** corresponding to the second throttle control value **1209**, independent of a difference between the first one of the throttle control values **1209** and the second one of the throttle control values **1209**.

(115) The FSM **1202** may be configured to implement either downward transitions **1506(2)-1506(7)** or downward transitions **1508(1)-1508(7)** but is not limited to only these options. The FSMs **1202** may be able to select a transition limit indicating that the FSM **1202** can transition in the downward direction by a limited number of states in one transition. The transition limit may be regarded as a maximum number of states changed in a transition from one cycle to a next cycle or a maximum decrease in a corresponding one of the throttle select values **1207(1)-1207(X)** from

one cycle to a next cycle. The transition limit may be a configurable value stored in the configuration register **1214**. For example, the FSM **1202** may be configured to transition three (3) states downward (e.g., from state **1502(7)** to **1502(4)**) if the throttle control signal **1204** decreases by three levels or more (e.g., from a 7/8 value to a 4/8 value or lower). As noted above, the FSM **1202** stays in each state for at least 8 cycles as the throttle control value **1209** decreases (during which the corresponding processing segment circuit **1104(1)-1104(X)** receives the sequence signal, but may increase to a higher state in any cycle in response to an increase in the throttle control value **1209**).

(116) With further regard to the transition limit in the FSMs **1202**, a transition from a state **1502(0)-1502(6)** having a lower number to one of the states **1502(2)-1502(7)** having a higher number is referred to herein as an upward transition and corresponds to an increase in the throttle control values **1209** generated by each of the FSMs **1202**. Whereas a transition from a state **1502(1)-1502(7)** having a higher number to one of the states **1502(0)-1502(6)** having a lower number is referred to herein as a downward transition and corresponds to a decrease in the throttle control value **1209** generated by each of the FSMs **1202**. In this regard, each of the plurality of FSMs **1202** is configured to increase, from one cycle to a next cycle, a first corresponding one of the throttle select values **1207(1)-1207(X)** of the throttle select signal **1208(1)-1208(X)** to any second corresponding second throttle select value **1207(1)-1207(X)** in response to a corresponding increase in the throttle control value **1209**. Each of the FSMs **1202** is configured to decrease, from one cycle to a next cycle, the throttle select signal **1204** from a first corresponding one of the throttle select values **1207(1)-1207(X)** to a second corresponding one of the throttle select values **1207(1)-1207(X)** by no more than the transition limit. In response to the throttle control value **1209** staying the same or decreasing, the FSMs **1202** are configured to provide a same throttle select value for the first number N of consecutive clock cycles in the clock window.

(117) FIG. **16** is a flowchart illustrating an exemplary process **1600** for controlling activity in an integrated circuit (IC) chip comprising a processor-based system. The method comprises operating each of a plurality of processing segment circuits **1104(1)-1104(X)** in response to a clock signal CLK (block **1602**) and receiving, in each of a plurality of throttle administration circuits **1202(1)-1202(X)**, a throttle control signal **1204** (block **1604**). The method further includes generating a throttle select signal **1208(1)-1208(X)** corresponding to one of the first plurality of processing segment circuits **1104(1)-1104(X)** (block **1606**) and providing an activity control signal **1310(1)-1310(X)**, based on the corresponding throttle select signal **1208(1)-1208(X)**, to each of the first plurality of processing segment circuits **1104(1)-1104(X)** in each cycle of a first number (N) of consecutive cycles of the clock signal CLK, the activity control signals **1310(1)-1310(X)** configured to disable operation in the corresponding processing segment circuits **1104(1)-1104(X)** in a second number (M) of cycles among the first number (N) of consecutive cycles (block **1608**).

(118) A throttle control circuit configured to receive a throttle control signal and provide, to a plurality of processing segment circuits, selected activity control signals to control activity in a clock window of N consecutive clock cycles, including throttling activity in a number M of the N consecutive cycles based on the throttle control signal and components thereof illustrated in FIGS. **11-13** and **15**, and according to any aspects disclosed herein, may be provided in or integrated into any processor-based device. Examples, without limitation, include a set-top box, an entertainment unit, a navigation device, a communications device, a fixed location data unit, a mobile location data unit, a global positioning system (GPS) device, a mobile phone, a cellular phone, a smartphone, a session initiation protocol (SIP) phone, a tablet, a phablet, a server, a computer, a portable computer, a mobile computing device, laptop computer, a wearable computing device (e.g., a smartwatch, a health or fitness tracker, eyewear, etc.), a desktop computer, a personal digital assistant (PDA), a monitor, a computer monitor, a television, a tuner, a radio, a satellite radio, a music player, a digital music player, a portable music player, a digital video player, a video player, a digital video disc (DVD) player, a portable digital video player, an automobile, a vehicle

component, an avionics system, a drone, and a multicopter.

(119) FIG. 17 is a block diagram of another exemplary processor-based system that includes a throttle control circuit in a processor-based system on an IC chip configured to receive a throttle control signal and provide, to a plurality of processing segment circuits, selected activity control signals to control activity in a clock window of N consecutive clock cycles, including disabling activity in a number M of the N consecutive cycles based on the throttle control signal.

(120) In this example, the processor-based system 1700 may be formed in an IC chip 1702 and as a system-on-a-chip (SoC) 1704. The processor-based system 1700 includes a central processing unit (CPU)(s) 1706 that includes one or more processors 1708, which may also be referred to as CPU cores or processor cores. The CPU 1706 may have cache memory 1710 coupled to the CPU 1706 for rapid access to temporarily stored data. The CPU 1706 is coupled to a system bus 1712 and can intercouple master and slave devices included in the processor-based system 1700. As is well known, the CPU 1706 communicates with these other devices by exchanging address, control, and data information over the system bus 1712. For example, the CPU 1706 can communicate bus transaction requests to a memory controller 1714, as an example of a slave device. Although not illustrated in FIG. 17, multiple system buses 1712 could be provided, wherein each system bus 1712 constitutes a different fabric.

(121) Other master and slave devices can be connected to the system bus 1712. As illustrated in FIG. 17, these devices can include a memory system 1716 that includes the memory controller 1714 and a memory array(s) 1718, one or more input devices 1720, one or more output devices 1722, one or more network interface devices 1724, and one or more display controllers 1726, as examples. The input device(s) 1720 can include any type of input device, including, but not limited to, input keys, switches, voice processors, etc. The output device(s) 1722 can include any type of output device, including, but not limited to, audio, video, other visual indicators, etc. The network interface device(s) 1724 can be any device configured to allow an exchange of data to and from a network 1728. The network 1728 can be any type of network, including, but not limited to, a wired or wireless network, a private or public network, a local area network (LAN), a wireless local area network (WLAN), a wide area network (WAN), a BLUETOOTH™ network, and the Internet. The network interface device(s) 1724 can be configured to support any type of communications protocol desired.

(122) The CPU 1706 may also be configured to access the display controller(s) 1726 over the system bus 1712 to control information sent to one or more displays 1730. The display controller(s) 1726 sends information to the display(s) 1730 to be displayed via one or more video processor(s) 1732, which processes the information to be displayed into a format suitable for the display(s) 1730. The display(s) 1730 can include any type of display, including, but not limited to, a cathode ray tube (CRT), a liquid crystal display (LCD), a plasma display, a light emitting diode (LED) display, etc.

(123) The IC chip 1702 also includes a throttle control circuit in a processor-based system on an IC chip configured to receive a throttle control signal and provide, to a plurality of processing segment circuits, selected activity control signals to control activity in a clock window of N consecutive clock cycles, including disabling activity in a number M of the N consecutive cycles based on the throttle control signal, including but not limited to the throttle control circuit and components thereof illustrated in FIGS. 11-13 and 15. The processor-based system may include a PMIC 1734 corresponding to the PMIC chip 125 in FIG. 1. The processor-based system may include a temperature sensor 1742 corresponding to the temperature sensor 132 in FIG. 1. The processor-based system 1700 can include one or more LAM circuits 1740(1)-1740(6) that are associated with one or more of the processors 1708, the cache memory 1710, the memory controller 1714, the network interface device(s) 1724, the display controller 1726, and/or the system bus 1712 that are configured to monitor activity associated with these processing devices and reporting activity power events regarding activity of these devices within the hierarchical power management system

1700. The LAM circuits **1740(1)**-**1740(6)** may be the LAM circuits **136**, **136R** in the hierarchical power management systems **124**, **624**, **724** in FIGS. **1-3**, **5-7**, and **10A** as examples.

(124) FIG. **18** illustrates an exemplary wireless communications device **1800** that can include a throttle control circuit in a processor-based system on an IC chip configured to receive a throttle control signal and provide, to a plurality of processing segment circuits, selected activity control signals to control activity in a clock window of N consecutive clock cycles, including disabling activity in a number M of the N consecutive cycles based on the throttle control signal, including but not limited to the throttle control circuit and components thereof illustrated in FIGS. **11-13** and **15**.

(125) As shown in FIG. **18**, the wireless communications device **1800** includes an RF transceiver **1804** and a data processor **1806**. The RF transceiver **1804** and/or the data processor **1806** can include respective hierarchical power management systems **1802(1)**, **1802(2)** configured to locally monitor activity of devices in the processor-based system to locally estimate and throttle its power consumption and report activity power events regarding estimated power consumption to a centralized PEL circuit configured to collect activity power events regarding power consumption of the monitored processing devices and throttle power in the IC chip in response, including but not limited to the hierarchical power management systems **184**, **624**, **724** and their exemplary components in FIGS. **1-3**, **5-7**, and **9A-10**.

(126) The components of the RF transceiver **1804** and/or data processor **1806** can be split among multiple different die **1803(1)**, **1803(2)**. The data processor **1806** may include a memory to store data and program codes. The RF transceiver **1804** includes a transmitter **1808** and a receiver **1810** that support bi-directional communications. In general, the wireless communications device **1800** may include any number of transmitters **1808** and/or receivers **1810** for any number of communication systems and frequency bands. All or a portion of the RF transceiver **1804** may be implemented on one or more analog ICs, RF ICs, mixed-signal ICs, etc.

(127) The transmitter **1808** or the receiver **1810** may be implemented with a super-heterodyne architecture or a direct-conversion architecture. In the super-heterodyne architecture, a signal is frequency-converted between RF and baseband in multiple stages, e.g., from RF to an intermediate frequency (IF) in one stage and then from IF to baseband in another stage for the receiver **1810**. In the direct-conversion architecture, a signal is frequency-converted between RF and baseband in one stage. The super-heterodyne and direct-conversion architectures may use different circuit blocks and/or have different requirements. In the wireless communications device **1800** in FIG. **18**, the transmitter **1808** and the receiver **1810** are implemented with the direct-conversion architecture.

(128) In the transmit path, the data processor **1806** processes data to be transmitted and provides I and Q analog output signals to the transmitter **1808**. In the exemplary wireless communications device **1800**, the data processor **1806** includes digital-to-analog converters (DACs) **1812(1)**, **1812(2)** for converting digital signals generated by the data processor **1806** into the I and Q analog output signals, e.g., I and Q output currents, for further processing.

(129) Within the transmitter **1808**, lowpass filters **1814(1)**, **1814(2)** filter the I and Q analog output signals, respectively, to remove undesired signals caused by the prior digital-to-analog conversion. Amplifiers (AMPs) **1816(1)**, **1816(2)** amplify the signals from the lowpass filters **1814(1)**, **1814(2)**, respectively, and provide I and Q baseband signals. An upconverter **1818** upconverts the I and Q baseband signals with I and Q transmit (TX) local oscillator (LO) signals through mixers **1820(1)**, **1820(2)** from a TX LO signal generator **1822** to provide an upconverted signal **1824**. A filter **1826** filters the upconverted signal **1824** to remove undesired signals caused by the frequency upconversion as well as noise in a receive frequency band. A power amplifier (PA) **1828** amplifies the upconverted signal **1824** from the filter **1826** to obtain the desired output power level and provides a transmit RF signal. The transmit RF signal is routed through a duplexer or switch **1830** and transmitted via an antenna **1832**.

(130) In the receive path, the antenna **1832** receives signals transmitted by base stations and

provides a received RF signal, which is routed through the duplexer or switch **1830** and provided to a low noise amplifier (LNA) **1834**. The duplexer or switch **1830** is designed to operate with a specific receive (RX)-to-TX duplexer frequency separation, such that RX signals are isolated from TX signals. The received RF signal is amplified by the LNA **1834** and filtered by a filter **1836** to obtain a desired RF input signal. Downconversion mixers **1838(1)**, **1838(2)** mix the output of the filter **1836** with I and Q RX LO signals (i.e., LO_I and LO_Q) from an RX LO signal generator **1840** to generate I and Q baseband signals. The I and Q baseband signals are amplified by AMPs **1842(1)**, **1842(2)** and further filtered by lowpass filters **1844(1)**, **1844(2)** to obtain I and Q analog input signals, which are provided to the data processor **1806**. In this example, the data processor **1806** includes analog-to-digital converters (ADCs) **1846(1)**, **1846(2)** for converting the analog input signals into digital signals to be further processed by the data processor **1806**.

(131) In the wireless communications device **1800** of FIG. **18**, the TX LO signal generator **1822** generates the I and Q TX LO signals used for frequency upconversion, while the RX LO signal generator **1840** generates the I and Q RX LO signals used for frequency downconversion. Each LO signal is a periodic signal with a particular fundamental frequency. A TX phase-locked loop (PLL) circuit **1848** receives timing information from the data processor **1806** and generates a control signal used to adjust the frequency and/or phase of the TX LO signals from the TX LO signal generator **1822**. Similarly, an RX PLL circuit **1850** receives timing information from the data processor **1806** and generates a control signal used to adjust the frequency and/or phase of the RX LO signals from the RX LO signal generator **1840**.

(132) Those of skill in the art will further appreciate that the various illustrative logical blocks, modules, circuits, and algorithms described in connection with the aspects disclosed herein may be implemented as electronic hardware, instructions stored in memory or in another computer-readable medium wherein any such instructions are executed by a processor or other processing device, or combinations of both. As examples, the devices and components described herein may be employed in any circuit, hardware component, integrated circuit (IC), or IC chip. Memory disclosed herein may be any type and size of memory and may be configured to store any type of information desired. To clearly illustrate this interchangeability, various illustrative components, blocks, modules, circuits, and steps have been described above generally in terms of their functionality. How such functionality is implemented depends upon the particular application, design choices, and/or design constraints imposed on the overall system. Skilled artisans may implement the described functionality in varying ways for each particular application, but such implementation decisions should not be interpreted as causing a departure from the scope of the present disclosure.

(133) The various illustrative logical blocks, modules, and circuits described in connection with the aspects disclosed herein may be implemented or performed with a processor, a Digital Signal Processor (DSP), an Application Specific Integrated Circuit (ASIC), a Field Programmable Gate Array (FPGA) or other programmable logic device, discrete gate or transistor logic, discrete hardware components, or any combination thereof designed to perform the functions described herein. A processor may be a microprocessor, but in the alternative, the processor may be any conventional processor, controller, microcontroller, or state machine. A processor may also be implemented as a combination of computing devices (e.g., a combination of a DSP and a microprocessor, a plurality of microprocessors, one or more microprocessors in conjunction with a DSP core, or any other such configuration).

(134) The aspects disclosed herein may be embodied in hardware and in instructions that are stored in hardware and may reside, for example, in Random Access Memory (RAM), flash memory, Read Only Memory (ROM), Electrically Programmable ROM (EPROM), Electrically Erasable Programmable ROM (EEPROM), registers, a hard disk, a removable disk, a CD-ROM, or any other form of computer-readable medium known in the art. An exemplary storage medium is coupled to the processor such that the processor can read information from, and write information

to, the storage medium. In the alternative, the storage medium may be integral to the processor. The processor and the storage medium may reside in an ASIC. The ASIC may reside in a remote station. Alternatively, the processor and the storage medium may reside as discrete components in a remote station, base station, or server.

(135) It is also noted that the operational steps described in any of the exemplary aspects herein are described to provide examples and discussion. The operations described may be performed in numerous different sequences other than the illustrated sequences. Furthermore, operations described in a single operational step may actually be performed in a number of different steps. Additionally, one or more operational steps discussed in the exemplary aspects may be combined. It is to be understood that the operational steps illustrated in the flowchart diagrams may be subject to numerous different modifications, as will be readily apparent to one of skill in the art. Those of skill in the art will also understand that information and signals may be represented using any of a variety of different technologies and techniques. For example, data, instructions, commands, information, signals, bits, symbols, and chips that may be referenced throughout the above description may be represented by voltages, currents, electromagnetic waves, magnetic fields or particles, optical fields or particles, or any combination thereof.

(136) It is also noted that the operational steps described in any of the exemplary aspects herein are described to provide examples and discussion. The operations described may be performed in numerous different sequences other than the illustrated sequences. Furthermore, operations described in a single operational step may actually be performed in a number of different steps. Additionally, one or more operational steps discussed in the exemplary aspects may be combined. It is to be understood that the operational steps illustrated in the flowchart diagrams may be subject to numerous different modifications, as will be readily apparent to one of skill in the art. Those of skill in the art will also understand that information and signals may be represented using any of a variety of different technologies and techniques. For example, data, instructions, commands, information, signals, bits, symbols, and chips that may be referenced throughout the above description may be represented by voltages, currents, electromagnetic waves, magnetic fields or particles, optical fields or particles, or any combination thereof.

(137) The previous description of the disclosure is provided to enable any person skilled in the art to make or use the disclosure. Various modifications to the disclosure will be readily apparent to those skilled in the art, and the generic principles defined herein may be applied to other variations. Thus, the disclosure is not intended to be limited to the examples and designs described herein but is to be accorded the widest scope consistent with the principles and novel features disclosed herein.

(138) Implementation examples are described in the following numbered clauses:

(139) 1. An integrated circuit (IC) chip comprising a processor-based system, the processor-based system comprising:

(140) a plurality of processing segment circuits, each configured to operate in response to a clock signal; and a throttle control circuit comprising: a plurality of throttle administration circuits, each configured to receive a throttle control signal and generate a throttle select signal based on the throttle control signal, corresponding one of the first plurality of processing segment circuits; and a throttle sequence selection circuit configured to provide, to each of the first plurality of processing segment circuits, an activity control signal configured to throttle activity in the processing segment circuit in a first number (M) of cycles among a second number (N) of consecutive cycles of the clock signal based on a corresponding throttle select signal.

2. The IC chip of clause 1, each of the first plurality of processing segment circuits comprising at least one transistor circuit configured to change an output voltage state in response to the clock signal.

3. The IC chip of clause 1 or 2, each of the first plurality of processing segment circuits coupled to a same power rail to receive a power supply voltage.

4. The IC chip of any of clauses 1-3, each of the first plurality of processing segment circuits located adjacent to another one of the first plurality of processing segment circuits.
5. The IC chip of any of clauses 1-4, wherein: the throttle control signal indicates one of a third number (L) of throttle control values; and the third number (L) of throttle control values is equal to the first number (N) of consecutive clock cycles of the clock signal.
6. The IC chip of any of clauses 1-5, wherein the throttle select signal corresponding to one of the plurality of processing segment circuits is generated in one of the plurality of throttle administration circuits based on the throttle control signal and on configuration information corresponding to the processing segment circuit.
7. The IC chip of any of clauses 1-6, further comprising a configuration register configured to store, for each one of the plurality of processing segment circuits, configuration information corresponding to each of the throttle control values, wherein the throttle administration circuit is configured to, for a given throttle control value, determine the number M of cycles among the first number N of cycles, that activity in a corresponding one of the processing segment circuits is disabled based on the configuration information.
8. The IC chip of any of clauses 1-7, wherein each of the plurality of throttle administration circuits comprises a finite state machine having a fourth number (K) of states equal to the first number (N) of consecutive cycles of the clock signal.
9. The IC chip of clause 8, wherein: each of the plurality of throttle administration circuits is configured to generate the throttle select signal having a throttle select value for each of the fourth number (K) of states; and an increase of the throttle select value corresponds to an increase of the second number (M) of cycles in which activity in the processing segment circuit is disabled among the first number (N) of consecutive cycles.
10. The IC chip of clause 9, wherein each of the plurality of throttle administration circuits is configured to increase, from one cycle to a next cycle, the throttle select value of the throttle select signal from a first throttle select value to any second throttle select value higher than the first throttle select value in response to a corresponding increase in the throttle control value.
11. The IC chip of clause 9 or 10, wherein each of the plurality of throttle administration circuits is configured to decrease, from one cycle to a next cycle, the throttle select signal from a first throttle select value to a second throttle select value that is lower than the first throttle select value by no more than a transition limit.
12. The IC chip of any of clauses 9-11 wherein, in response to the throttle control value staying the same or decreasing, each of the plurality of throttle administration circuits is configured to provide the second throttle select value for the first number (N) of consecutive cycles of the clock signal.
13. The IC chip of clause 11 or 12, wherein the transition limit is a configurable value stored in a configuration register.
14. The IC chip of any of clauses 1-13, further comprising a plurality of throttle sequence generators configured to generate sequence signals that are selected by the throttle select signals to be provided as the activity control signal, wherein plurality of throttle sequence generators are configured to generate the select signals to disable every number, from 0 to N-1, of the cycles of the number N of consecutive cycles.
15. The IC chip of any of clauses 1-14, wherein in response to the throttle control signal having a highest throttle control value, the throttle sequence selection circuit is configured to provide the activity control signal to disable activity in all but one cycle of the first number (N) of consecutive cycles.
16. The IC chip of any of clauses 1-15, wherein in response to the throttle control signal having a lowest throttle select value, the throttle sequence selection circuit is configured to provide the activity control signal to disable activity in none of the first number (N) of consecutive cycles.
17. The IC chip of any of clauses 1-16, the throttle sequence selection circuit comprising a plurality of multiplexors, each controlled by one of the throttle select signals generated by the plurality of

throttle administration circuits, wherein each of the plurality of multiplexors comprises an output coupled to one of the plurality of processing segment circuits.

18. The IC chip of any of clauses 1-17, each of the plurality of processing segment circuits comprising an activity control circuit configured to receive the activity control signal and disable activity in a plurality of transistor circuits in the processing segment circuit, wherein disabling activity comprises gating the clock signal.

19. The IC chip of any of clauses 1-18, further comprising: at least a second plurality of processing segment circuits; and at least a second throttle control circuit configured to control state changes in the at least a second plurality of processing segment circuits to manage power in response to detected power events.

20. The IC chip of any of clauses 1-19 integrated into a device selected from the group consisting of: a set-top box; an entertainment unit; a navigation device; a communications device; a fixed location data unit; a mobile location data unit; a global positioning system (GPS) device; a mobile phone; a cellular phone; a smartphone; a session initiation protocol (SIP) phone; a tablet; a phablet; a server; a computer; a portable computer; a mobile computing device; a wearable computing device; a desktop computer; a personal digital assistant (PDA); a monitor; a computer monitor; a television; a tuner; a radio; a satellite radio; a music player; a digital music player; a portable music player; a digital video player; a video player; a digital video disc (DVD) player; a portable digital video player; an automobile; a vehicle component; avionics systems; a drone; and a multicopter.

21. A method of controlling activity in an integrated circuit (IC) chip comprising a processor-based system, the method comprising: operating each of a plurality of processing segment circuits in response to a clock signal; receiving, in each of a plurality of throttle administration circuits, a throttle control signal; generating a throttle select signal corresponding one of the first plurality of processing segment circuits; and providing an activity control signal, based on the corresponding throttle select signal, to each of the first plurality of processing segment circuits in each cycle of a first number (N) of consecutive cycles of the clock signal, the activity control signal configured to disable operation in the processing segment circuit in a second number (M) of cycles among the first number (N) of consecutive cycles.

22. The method of clause 21, further comprising generating the throttle select signals in each one of the plurality of throttle administration circuits based on the throttle control signal and on a configuration setting corresponding to the processing segment circuit.

23. The method of clause 21 or 22, further comprising disabling, based on configuration settings in a configuration register, a different second number (M) of state changes among the first number (N) of consecutive cycles in a first one of the plurality of processing segment circuits than in the first number (N) of consecutive cycles in a second one of the plurality of processing segment circuits.

24. The method of any of clauses 21-23, wherein an increase of the throttle select value corresponds to an increase of the second number M of cycles in which state changes in the processing segment circuit are disabled among the first number N of consecutive cycles.

25. The method of any of clauses 21-24, further comprising increasing, from a first cycle to a second cycle, the throttle select value of the throttle select signal from a first throttle select value to a second throttle select value that is higher than the first throttle control value in response to a corresponding increase in the throttle control value.

26. The method of any of clauses 21-25, further comprising reducing, from a first cycle to a second cycle, the throttle select value of the throttle select signal from a first throttle select value to a second throttle select value that is less than the first throttle select value by no more than a transition limit in response to a corresponding decrease in the throttle control value.

27. The method of clause 26, further comprising, in response to the throttle control value staying the same or decreasing, providing, in each of the plurality of throttle administration circuits, the second throttle select value for the first number (N) of consecutive cycles of the clock signal before further reducing the throttle select signal to a third throttle select value that is less than the second

throttle select value by not more than the transition limit.

28. A throttle control circuit comprising: a plurality of throttle administration circuits, each configured to receive a throttle control signal and generate a throttle select signal based on the throttle control signal, corresponding one of a first plurality of processing segment circuits; and a throttle sequence selection circuit configured to provide, to each of the first plurality of processing segment circuits in each cycle of a first number (N) of consecutive cycles of the clock signal, an activity control signal configured to disable state changes in the processing segment circuit in a second number (M) of cycles among the first number of consecutive cycles based on the corresponding throttle select signal.

Claims

1. An integrated circuit (IC) chip comprising a processor-based system, the processor-based system comprising: a first plurality of processing segment circuits, each configured to operate in response to a clock signal; and a throttle control circuit comprising: a plurality of throttle administration circuits, each configured to receive a throttle control signal and generate a throttle select signal, based on the throttle control signal, to a corresponding one of the first plurality of processing segment circuits; and a throttle sequence selection circuit configured to provide, to each of the first plurality of processing segment circuits, an activity control signal configured to throttle activity in the processing segment circuit in a first number (M) of cycles among a second number (N) of consecutive cycles of the clock signal based on a corresponding throttle select signal.
2. The IC chip of claim 1, each of the first plurality of processing segment circuits comprising at least one transistor circuit configured to change an output voltage state in response to the clock signal.
3. The IC chip of claim 1, each of the first plurality of processing segment circuits coupled to a same power rail to receive a power supply voltage.
4. The IC chip of claim 1, each of the first plurality of processing segment circuits located adjacent to another one of the first plurality of processing segment circuits.
5. The IC chip of claim 1, wherein: the throttle control signal indicates one of a third number (L) of throttle control values; and the third number (L) of throttle control values is equal to the first second number (N) of consecutive clock cycles of the clock signal.
6. The IC chip of claim 1, wherein the throttle select signal corresponding to one of the first plurality of processing segment circuits is generated in one of the plurality of throttle administration circuits based on the throttle control signal and on configuration information corresponding to the processing segment circuit.
7. The IC chip of claim 5, further comprising a configuration register configured to store, for each one of the first plurality of processing segment circuits, configuration information corresponding to each of the third number (L) of throttle control values, wherein each throttle administration circuit of the plurality of throttle administration circuits is configured to, for a given throttle control value of the third number (L) of throttle control values, determine the first number (M) of cycles, among the second number (N) of consecutive cycles, in which activity in a corresponding one of the processing segment circuits is disabled based on the configuration information.
8. The IC chip of claim 5, wherein each of the plurality of throttle administration circuits comprises a finite state machine having a fourth number (K) of states equal to the second number (N) of consecutive cycles of the clock signal.
9. The IC chip of claim 8, wherein: each of the plurality of throttle administration circuits is configured to generate the throttle select signal having a throttle select value for each of the fourth number (K) of states; and an increase of the throttle select value corresponds to an increase of the first number (M) of cycles in which activity in the processing segment circuit is disabled among the second number (N) of consecutive cycles.

10. The IC chip of claim 9, wherein each of the plurality of throttle administration circuits is configured to increase, from one cycle to a next cycle, the throttle select value of the throttle select signal from a first throttle select value to a second throttle select value higher than the first throttle select value in response to a corresponding increase in the one throttle control value.
11. The IC chip of claim 9, wherein each of the plurality of throttle administration circuits is configured to decrease, from one cycle to a next cycle, the throttle select signal from a first throttle select value to a second throttle select value that is lower than the first throttle select value by no more than a transition limit.
12. The IC chip of claim 10 wherein, in response to the one throttle control value staying the same or decreasing, each of the plurality of throttle administration circuits is configured to provide the second throttle select value for the first second number (N) of consecutive cycles of the clock signal.
13. The IC chip of claim 11, wherein the transition limit is a configurable value stored in a configuration register.
14. The IC chip of claim 1, further comprising a plurality of throttle sequence generators configured to generate sequence signals that are selected by the throttle select signals to be provided as the activity control signal, wherein the plurality of throttle sequence generators is configured to generate the sequence signals having a first state for the first number (M) of cycles and having a second state for N-M cycles and the every number M ranges from 0 to N-1 among the sequence signals.
15. The IC chip of claim 5, wherein in response to the throttle control signal having a highest throttle control value of the third number (L) of throttle control values, the throttle sequence selection circuit is configured to provide the activity control signal to disable activity in all but one cycle of the second number (N) of consecutive cycles.
16. The IC chip of claim 9, wherein in response to the throttle control signal having a lowest throttle select value, the throttle sequence selection circuit is configured to provide the activity control signal to disable activity in none of the second number (N) of consecutive cycles.
17. The IC chip of claim 1, the throttle sequence selection circuit comprising a plurality of multiplexors, each controlled by one of the throttle select signals generated by the plurality of throttle administration circuits, wherein each of the plurality of multiplexors comprises an output coupled to one of the first plurality of processing segment circuits.
18. The IC chip of claim 1, each of the first plurality of processing segment circuits comprising an activity control circuit configured to receive the activity control signal and disable activity in a plurality of transistor circuits in the processing segment circuit, wherein disabling activity comprises gating the clock signal.
19. The IC chip of claim 1, further comprising: at least a second plurality of processing segment circuits; and at least a second throttle control circuit configured to control state changes in the at least a second plurality of processing segment circuits to manage power in response to detected power events.
20. The IC chip of claim 1 integrated into a device selected from the group consisting of: a set-top box; an entertainment unit; a navigation device; a communications device; a fixed location data unit; a mobile location data unit; a global positioning system (GPS) device; a mobile phone; a cellular phone; a smartphone; a session initiation protocol (SIP) phone; a tablet; a phablet; a server; a computer; a portable computer; a mobile computing device; a wearable computing device; a desktop computer; a personal digital assistant (PDA); a monitor; a computer monitor; a television; a tuner; a radio; a satellite radio; a music player; a digital music player; a portable music player; a digital video player; a video player; a digital video disc (DVD) player; a portable digital video player; an automobile; a vehicle component; avionics systems; a drone; and a multicopter.
21. A method of controlling activity in an integrated circuit (IC) chip comprising a processor-based system, the method comprising: operating each of a first plurality of processing segment circuits in

response to a clock signal; receiving, in each of a plurality of throttle administration circuits, a throttle control signal; generating a throttle select signal to a corresponding one of the first plurality of processing segment circuits; and providing an activity control signal, based on the corresponding throttle select signal, to each of the first plurality of processing segment circuits in each cycle of a first second number (N) of consecutive cycles of the clock signal, the activity control signal configured to disable operation in the processing segment circuit in a first number (M) of cycles among the second number (N) of consecutive cycles.

22. The method of claim 21, further comprising generating the throttle select signals in each one of the plurality of throttle administration circuits based on the throttle control signal and on a configuration setting corresponding to the processing segment circuit.

23. The method of claim 21, further comprising disabling, based on configuration settings in a configuration register, a different first number (M) of state changes among the second number (N) of consecutive cycles in a first one of the first plurality of processing segment circuits than in a second one of the first plurality of processing segment circuits.

24. The method of claim 21, wherein an increase of a throttle select value of the throttle select signal corresponds to an increase of the first number (M) of cycles in which state changes in the processing segment circuit are disabled among the second number (N) of consecutive cycles.

25. The method of claim 24, further comprising increasing, from a first cycle to a second cycle, the throttle select value of the throttle select signal from a first throttle select value to a second throttle select value that is higher than the first throttle select value in response to a corresponding increase in a throttle control value of the throttle control signal.

26. The method of claim 24, further comprising reducing, from a first cycle to a second cycle, the throttle select value of the throttle select signal from a first throttle select value to a second throttle select value that is less than the first throttle select value by no more than a transition limit in response to a corresponding decrease in a throttle control value of the throttle control signal.

27. The method of claim 26, further comprising, in response to the throttle control value of the throttle control signal staying the same or decreasing, providing, in each of the plurality of throttle administration circuits, the second throttle select value for the first number (N) of consecutive cycles of the clock signal before further reducing the throttle select signal to a third throttle select value that is less than the second throttle select value by not more than the transition limit.

28. A throttle control circuit comprising: a plurality of throttle administration circuits, each configured to receive a throttle control signal and generate a throttle select signal, based on the throttle control signal, to a corresponding one of a first plurality of processing segment circuits; and a throttle sequence selection circuit configured to provide, to each of the first plurality of processing segment circuits in each cycle of a second number (N) of consecutive cycles of the clock signal, an activity control signal configured to disable state changes in the processing segment circuit in a first number (M) of cycles among the second number (N) of consecutive cycles based on the corresponding throttle select signal.
