

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12411992
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Royer; Burk

Updating annotated software objects

Abstract

In one example, a computer program product is disclosed. The computer program product includes instructions, executed by a processor, to parse an original annotated software object for at least one annotation construct. Each annotation construct is to define which attributes of the original annotated software object can be modified and a user role parameter. The instructions include parsing an updated annotated software object of the original annotated software object to use the annotation construct to determine: attribute changes to the original annotated software object and the user role parameter associated with the attribute changes. In the user role parameter is authorized to make the attribute changes, the attribute changes are accepted to store the attribute changes in the updated annotated software object. If the user role parameter is not authorized, the attribute changes are rejected to disallow storage of the attribute changes by the updated annotated software object.

Inventors:	Royer; Burk (Conroe, TX)
Applicant:	JPMorgan Chase Bank, N.A. (New York, NY)
Family ID:	91963243
Assignee:	JPMORGAN CHASE BANK, N.A. (New York, NY)
Appl. No.:	18/102929
Filed:	January 30, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240256713 A1	Aug. 01, 2024

Publication Classification

Int. Cl.: G06F21/62 (20130101); G06F8/30 (20180101)

U.S. Cl.:

CPC **G06F21/629** (20130101); **G06F8/30** (20130101);

Field of Classification Search

CPC: G06F (21/629); G06F (8/30); G06F (8/65)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2007/0234335	12/2006	Takahashi	717/168	G06F 8/71
2010/0100970	12/2009	Roy-Chowdhury	726/1	H04L 67/55
2011/0307712	12/2010	Sakthikumar	713/189	G06F 21/572
2013/0326330	12/2012	Harris	715/234	G06F 40/197
2015/0370769	12/2014	Pereira Filho	726/28	G06F 40/166
2022/0138161	12/2021	Anjum	715/272	G06F 40/197

Primary Examiner: Nguyen; Trong H

Attorney, Agent or Firm: Greenblum & Bernstein, P.L.C.

Background/Summary

BACKGROUND

(1) Software developers often use object-oriented programming to build software applications. This object-oriented approach can model real-world objects and their characteristics. As an example, a real-world object such as a bicycle with a state (e.g., color, two wheels, number of gears, etc.) and a behavior (accelerating, changing gears, etc.) can be modeled via object-oriented programming. A software object maintains this state in variables and implements the behavior with methods.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) Examples of the disclosure will be rendered by reference to specific examples which are illustrated in the appended drawings. The drawings illustrate only particular examples of the disclosure and therefore are not to be considered to be limiting of their scope. The principles here are described and explained with additional specificity and detail through the use of the accompanying drawings.

(2) FIG. 1 illustrates a software object update platform according to examples of the present disclosure.

(3) FIG. 2 illustrates components of the software object update system of FIG. 1 according to examples of the present disclosure.

(4) FIG. 3 illustrates a software object data structure with annotation constructs according to examples of the present disclosure.

(5) FIG. 4 illustrates the data structure of an update object utility to call the originalOrder object

and the updatedOrder object of FIG. 3 for parsing and comparison according to examples of the present disclosure.

(6) FIG. 5 illustrates a data structure for the parse/compare object utility of FIG. 4 according to an example of the present disclosure.

(7) FIG. 6 illustrates a method of updating annotated software objects according to an example of the present disclosure.

(8) FIG. 7A illustrates example instructions stored on a non-transitory computer-readable storage medium according to one example of the present disclosure.

(9) FIG. 7B illustrates an example computing device according to an example of the present disclosure.

(10) FIG. 8 illustrates a software object update platform according to an example of the present invention.

DETAILED DESCRIPTION

(11) Many software objects maintain their state in variables or attributes. Code changes to attributes that update the software object may be needed from time to time. As an example, code changes that modify the attributes of a Plain Old Java® Object (POJO) may be needed to improve the software object. However, such code changes can quickly become unmanageable and unwieldy, sometimes resulting in very large-sized software objects.

(12) If the software object is the main object in an application, and changes are constantly being made, software developers need to assess the preceding code changes whenever attributes are modified or added. One technique for assessing changes is to write compare methods. However, compare methods would require maintaining an even larger codebase particularly for large classes. Moreover, a compare method would only report that a mis-comparison exists and can return only a Boolean or a true/false value. Changes made by different individuals representing different groups and roles can further complicate this situation as this would require writing multiple compare methods.

(13) The present disclosure addresses the foregoing by providing an object-oriented framework (e.g., Java®) with annotation constructs defining inclusive and/or exclusive attributes within the POJO to compare, with the option of returning verbose results. As used herein, a “verbose” result is a returned String result (or List result) that includes a list of attributes that have “mis-compared” with old and new values.

(14) The present disclosure discloses a system, method and computer product to update annotated software objects. The method may include parsing an original annotated software object for an annotation construct. As will be further discussed below, an annotation construct defines a user role and attributes of a software object that can be modified. Conversely, the annotation construct may define attributes that cannot be modified.

(15) The method of the present disclosure may then parse an updated annotated software object to use the annotation construct to determine attribute changes to the original annotated software object and a corresponding user role parameter. If the user role parameter is authorized to make the attribute changes, the method accepts the attribute changes to store the attribute changes in the updated annotated software object.

(16) And, if the user role parameter is not authorized to make the attribute changes, the method rejects the attribute changes to the original annotated software object to disallow storage of the attribute changes by the updated annotated software object. Further, if the user role parameter is not authorized to make the attribute changes, the method may return a list of attribute changes in string format and/or a map format.

(17) In this manner, attribute code changes don't become unwieldy and unmanageable as such code changes can be authorized/rejected and tracked. Moreover, software developers can avoid larger codebases and need not write compare methods to assess such attribute code changes. The present disclosure goes beyond returning a mis-compare and Boolean true/false values but can return the

differences between the mis-compared software objects both in string and map formats. The present disclosure further assigns user roles to different individuals that can make attribute changes thus avoiding the need to write multiple compare methods.

(18) FIG. 1 illustrates a software object update platform **100** according to examples of the present disclosure.

(19) In FIG. 1, software object update platform **100** illustrates three platform users **102**, **108**, **112**, two of the users **102**, **108** can update original software objects based on their SALES roles (and annotated attributes), while the third user **112** cannot update software objects based on the user's SYND (syndicate) role.

(20) As used herein, a “role” is a position, function or responsibility assigned to an attribute to either authorize or disallow the modification of the attribute. However, use of a “role” or “user role” is a specific example of a “namespace” or “compare type” for an annotation.

(21) Referring to FIG. 1, software object update platform **100** includes the first user **102** communicably coupled to an annotated software object repository **106** that stores annotated software objects **104**, **104A**, **106a** . . . *n*. As used herein, an annotated software object includes one or more lines of software instructions and annotations, comments and the like. The annotated software object may be based on any object-oriented programming language including Java®, C++, PHP, JavaScript®, etc.

(22) As shown, first user **102** stores (via a network interface) an original annotated software object **104** developed by first user **102** in annotated software object repository **106**. Here, annotated software object repository **106** can be a single or multiple geographically-dispersed databases. First user **102** may represent a developer or software engineer utilizing a computing device having a processor and corresponding memory. As shown, first user **102** may be part of a SALES team, for example, within a large enterprise.

(23) The second user **108** can retrieve, from annotated software object repository **106**, the original annotated software object **104** and other annotated software objects that are stored by first user **102**. Second user **108** may represent another developer or software engineer also with a SALES role in the same sales group as first user **102**. The second user **108** can retrieve (via a network interface) original annotated software objects to change, update or improve the original annotated software objects.

(24) Both the first user **102** and the second user **108** may further communicate with a software object update system **110**. As implied by its name, the software object update system **110** facilitates the updating of original annotated software objects by determining whether such updates are permitted before the updated software object can be stored.

(25) In operation, first user **102** has developed original annotated software object **104** to perform a sales functionality (for example). As will be further discussed, first user **102** includes annotation constructs that designate attributes that can be modified. After building the original annotated software object **104**, first user **102** stores the software object in annotated software repository **106**. Annotated software repository **106** is generally available to all users of the system.

(26) Second user **108** wishes to update original annotated software object **104** begins by retrieving this original annotated software object **104** from annotated software object repository **106**. Upon retrieval, second user **108** makes the desired attribute updates to the original annotated software object **104**. The updates may be via a GUI (Graphical User Interface) not shown. In FIG. 1, the updated annotated software object is shown as **104A**.

(27) However, updated software objects cannot be stored in annotated software object repository **106** and are not generally available for other users without validation by the software object update system **110** in accordance with the principles and precepts of the present disclosure. Accordingly, as shown by path **1** in FIG. 1, second user **108** forwards updated annotated software object **104A** to software object update system **110** for validation. Although illustrated as being external to the user devices, software object update system **110** be local and integrated with the user devices or may be

provisioned.

(28) As noted, software object update system **110** receives updated annotated software object **104A**. Contemporaneously, as shown via path **2**, software object update system **110** retrieves, from the annotated software object repository **106**, the original annotated software object **104** previously stored by first user **102**. Original annotated software object **104** may include one or more annotation constructs to define which attributes of the original annotated software object **104** can be updated. Software object update system **110** then parses the original annotated software object for the annotation construct(s) which attributes of the original annotated software objects can be modified, and at least one user role parameter.

(29) Software object update system **110** also parses annotated updated annotated software object **104A** which includes attribute modifications to original annotated software object **104**. Software object update system **110** validates whether the attribute changes in updated annotated software object **104A** are permissible based on the annotation constructs of the original annotated software object **104**.

(30) In this case, the attribute changes are permissible because both first user **102** and second user **108** both have SALES roles (in this example) and because only attribute changes designated by annotation construct(s) of original annotated software object **104** are made. Accordingly, as shown by path **3** of FIG. **1**, the updated annotated software object **104A** is stored in annotated software object repository **106** for general use by all users of the update platform **100**.

(31) In FIG. **1**, in contrast, the third user **112** with a syndicate role (SYND) may not make changes to original annotated software object **104**. Users in the syndicate group have not been assigned a role as permissible change makers. Thus, although third user **112** has made attribute changes to original annotated software object **104** shown as original annotated software object **104B**, those attribute changes and the updated annotated software object are not stored by annotated software object repository **106**. In this manner, software object attribute changes are less complicated because only designated user roles can implement attribute changes to software objects, thus avoiding the need to write multiple or large compare methods that can substantially increase the codebase.

(32) FIG. **2** illustrates components of the software object update system **110** of FIG. **1** according to examples of the present disclosure.

(33) Here, software object update system **110** may include an object parsing engine **202** and an object update engine **206**. Object parsing engine **202** may be a program, a routine or instruction that may or may not be part of a compiler to breakup received inputs into constituent parts such as objects, methods and their attributes or options. Object parsing engine **202** may also parse to identify specific code. Object parsing engine **202** may include a compare engine **204** that works in conjunction with object parsing engine **202** to receive original and updated software objects.

(34) Here, object parsing engine **202** and/or compare engine **204** may parse original annotated software object to identify the annotation constructs that designate changeable attributes of the original annotated software object **104** and the user role parameter that can make such changes. Contemporaneously or shortly thereafter, object parsing engine **202** and/or compare engine **204** parses annotated software object **104A** to use the annotation constructs to extract attribute changes as well as the user role(s) corresponding to the attribute changes.

(35) The object update engine **206** (like object parsing engine **203**) may also be a program, a routine or instruction. Object update engine **206** analyzes the modified attributes and user role(s). If the user role is authorized for attribute changes, object update engine **206** accepts such changes but if unauthorized, the attribute changes are rejected. The attribute changes, if authorized, can then be saved to annotated software object repository **106**.

(36) FIG. **3** illustrates an example of the data structure of original annotated software object **104** (FIG. **1**) with annotation constructs according to the present disclosure. In this example, although the original annotated software object **104** has been illustrated with a JAVA® object, the present

disclosure is applicable to other object-oriented programming languages.

(37) Specifically, in FIG. 3, original annotated software object **104** is an InvestorOrder object **301** that includes various annotation constructs **302**, **306**, **310**. Each annotation construct **302**, **306**, **310** is to provide supplemental information about the software object. Here, the supplement information may indicate the modifiable attributes of the software object and the user role that can make such attribute modifications. As shown, each one of the annotation constructs **302**, **306**, **310** begins with **@** and do not change the action of a compiled program.

(38) The InvestorOrder object **301** is passed to a parse/compare utility **400** (FIG. 4) that reads the annotation constructs **302**, **306**, **310** to obtain the modifiable attributes and the designated user role(s) for comparison with changed attributes of an updated software object. In another example, the user role may be passed as a variable.

(39) As shown in FIG. 3, annotation construct **302** is: **@DiffCompare** (MARS_SYND_UPDATEABLE_WITHOUT_OVERRIDE) which has attributes **304**: private Long allocatedAmount; private Long internalAllocatedAmount.

(40) The user role or enumeration that can make subsequent changes is MARS_SYND_UPDATEABLE_WITHOUT_OVERRIDE **303**, and this user role can only change attributes **304**, i.e., allocatedAmount and internalAllocatedAmount stored by annotation construct **302**. If user role MARS_SYND_UPDATEABLE_WITHOUT_OVERRIDE **303** makes changes other than to attributes **304**, the changes would be rejected by software object update system **110**, and object update engine **204** (FIG. 2).

(41) The reverse is also true. If a different user role other than user role MARS_SYND_UPDATEABLE_WITHOUT_OVERRIDE **303** makes changes to attributes **304**, such changes are rejected by software object update system **110**.

(42) In FIG. 3, annotation construct **306** is also shown as: **@DiffCompare**({MARS_SYND_UPDATEABLE_WITHOUT_OVERRIDE, MARS_SALES_UPDATEABLE}) which lists a single attribute **308**: private Region salesDesk.

(43) The user roles that can make changes to attribute salesDesk **308** are MARS_SYND_UPDATEABLE_WITHOUT_OVERRIDE **303** and MARS_SALES_UPDATEABLE **305**. These two users can only change the listed attribute salesDesk **308**. If user roles MARS_SYND_UPDATEABLE_WITHOUT_OVERRIDE **303** and MARS_SALES_UPDATEABLE **305** make changes to attributes other than salesDesk **308**, the changes would be rejected by software object update system **110**.

(44) As a further example, annotation construct **310** is **@DiffCompare**({MARS_SYND_UPDATEABLE_WITHOUT_OVERRIDE, MARS_SALES_UPDATEABLE}) having a single attribute **312**: private String salesUserName.

(45) The user roles that can make changes to attribute salesUserName **312** are MARS_SYND_UPDATEABLE_WITHOUT_OVERRIDE **303** and MARS_SALES_UPDATEABLE **305**. These two user roles can only change the listed attribute salesUserName **312**. If the user roles MARS_SYND_UPDATEABLE_WITHOUT_OVERRIDE **303** and MARS_SALES_UPDATEABLE **305** make changes to attributes other than salesUserName **312**, the changes would be rejected by software object update system **110**.

(46) As can be seen in FIG. 3, user roles are defined in the annotation constructs for each attribute data type. For example, the attribute salesUserName **312** corresponds to a string data type. For this string type, the roles are MARS_SYND_UPDATEABLE_WITHOUT_OVERRIDE **303** and MARS_SALES_UPDATEABLE **305**, while for the attribute salesDesk **308** with a region data type, the same roles (MARS_SYND_UPDATEABLE_WITHOUT_OVERRIDE **303** and MARS_SALES_UPDATEABLE **305**) are defined.

(47) In operation, a user wishing to authorize or prevent unauthorized changes, inserts annotation constructs **302**, **306**, **310** into original annotated software object **104**, along with the applicable user role(s) e.g., MARS_SYND_UPDATEABLE_WITHOUT_OVERRIDE **303**. A user then passes the

original annotated software object and updated annotated software object for parsing/comparison, to determine whether the attribute updates are authorized.

(48) FIG. 4 illustrates the data structure of an update object utility **400** to call originalOrder object **301** and the updatedOrder **402** of the InvestorOrder for parsing and comparison according to examples of the present disclosure.

(49) Specifically, as an example, the statement **406** in FIG. 4:

diffString=DiffUtil.getDiffs(originalOrder, updatedOrder, MARS_SALES_UPDATEABLE, true)
passes originalOrder object **301** and updatedOrder **402** via a parse/compare object utility **404** or method DiffUtil.getDiffs further described with reference to FIG. 5. In this specific use case, when the sales role attempts to make an update, “isNonSyndicateUpdate” **401** is passed to the method “throwIfMarsOrderChangesNotAllowed” **403** as true; for the syndicate role, it's passed as false. Thus, parse/compare object utility **404** (method DiffUtil.getDiffs) uses MARS_SALES_UPDATEABLE DiffCompare annotated attributes for comparison when it's true, and the MARS_SYND_UPDATEABLE_WITHOUT_OVERRIDE DiffCompare annotated attributed when it's false. DiffUtil.getDiffs then parses the objects, and returns differences based on the role MARS_SALES_UPDATEABLE **305**.

(50) FIG. 5 illustrates an abbreviated data structure for parse/compare object utility **404** of FIG. 4 according to an example of the present disclosure.

(51) In FIG. 5, parse/compare object utility **404** (DiffUtil) is called by update object utility **400** of FIG. 4. Parse/compare object utility **404** parses originalOrder object **301** (see FIG. 4) and updatedOrder **402** (FIG. 4) and the returns the attribute changes between them. In FIG. 5, as shown, DiffResult **512** returns oldValue **514** of the original attribute defined by the annotated construct and a newValue **516** of the attribute as modified in the updated annotated software object. In one example implementation, parse/compare object utility **404** may use a software language introspector that can examine itself and/or manipulate internal properties of a program. A more detailed version of the parse/compare object utility is shown in the Appendix below.

(52) FIG. 6 illustrates a method **600** of updating annotated software objects according to an example of the present disclosure.

(53) At block **602**, method **600** involves parsing original annotated software object **104** for at least one annotation construct (e.g. **302**, FIG. 3). For some examples, each annotation construct **302** may define which attributes (e.g. **304**, FIG. 3) of original annotated software object **104** can be modified, and at least one user role parameter (e.g., **305**, FIG. 3).

(54) At block **604**, method **600** involves parsing updated annotated software object **104A**. Here, updated annotated software object **104A** is parsed to use the annotation construct **302** to determine: a) attribute changes to original annotated software object **104**; and b) the user role parameter **305** associated with the attribute changes.

(55) At block **606**, method **600** involves, if the user role parameter **305** is authorized to make the attribute changes, accepting the attribute changes to the original annotated software object **104** to store the attribute changes in the updated annotated software object **104A**.

(56) At block **608**, if the user role parameter **305** is not authorized to make the attribute changes, rejecting the attribute changes to the original annotated software object **104** to disallow storage of the attribute changes by the updated annotated software object **104A**.

(57) Although not shown, method **600** may involve returning a list of attribute changes in a string format and a list of attribute changes in map format if the user role parameter **305** is not authorized to make the attribute changes.

(58) FIG. 7A illustrates example instructions stored on a non-transitory computer-readable storage medium **700** for updating annotated software objects according to one example of the present disclosure, and FIG. 7B illustrates an example computing device **750** according to the present disclosure.

(59) As shown in FIG. 7A, the non-transitory computer-readable storage medium **700** includes

instruction **702**, instruction **704**, instruction **706** and instruction **708**.

(60) Instruction **702** may cause a processor **752** to parse an original annotated software object **104** for at least one annotation construct, each annotation construct is to define which attributes of the original annotated software object can be modified and a user role parameter.

(61) Instruction **704** may cause a processor **752** to parse an updated annotated software object **104A** that is an update of the original annotated software object **104** to use the annotation construct to determine: a) attribute changes to the original annotated software object; and b) a user role parameter associated with the attribute changes.

(62) Instruction **706** may cause a processor **752** to, if the user role parameter is authorized to make the attribute changes, accept the attribute changes to the original annotated software object **104** to store the attribute changes in the updated annotated software object **104B**.

(63) Instruction **708** may cause a processor **752** to, if the user role parameter is not authorized to make the attribute changes, reject the attribute changes to the original annotated software **104** object to disallow storage of the attribute changes by the updated annotated software object **104B**.

(64) The non-transitory computer-readable storage medium **700** may be any electronic, magnetic, optical, or other physical storage device that stores executable instructions. For example, the non-transitory computer-readable storage medium **700** may be random access memory (RAM), an electrically-erasable programmable read-only memory (EEPROM), a storage drive, an optical disc, or the like. The non-transitory computer-readable storage medium **700** can be encoded to store executable instructions that cause the processor **752** to perform operations according to examples of the disclosure.

(65) FIG. **8** illustrates a software object update platform **800** according to an example of the present invention. FIG. **8** includes the same components and operates as described with reference to software object update platform **100** of FIG. **1** except that software object update platform **800** includes a network **806**, and the software object update system **110** includes a server **802**, a processor **804** and a network communication interface **805**. Software object update system **110** communicates with the remainder of software object update platform **800** via network communication interface **805** and network **806**. Server **802**, for example, may cause processor **804** to parse, over network **806** via the network communication interface **805**, the original annotated software object **104**.

(66) The present disclosure may employ a software stack to enlist the underlying tools, frameworks, and libraries used to build and run example applications of the present disclosure. Such a software stack may include PHP, React, Cassandra™, Hadoop®, Swift®, etc. The software stack may include both frontend and backend technologies including programming languages, web frameworks servers, and operating systems. The frontend may include JavaScript®, HTML, CSS, and UI frameworks and libraries. In one example, a MEAN (MongoDB®, Express.js, AngularJS, and Node.js) stack may be employed. In another example, a LAMP (Linux®, Apache®, MySQL®, and PHP) stack may be utilized.

(67) While particular examples have been described, various modifications, changes and substitutions are intended in the foregoing disclosures, and it will be appreciated that in some instances some features of particular examples will be employed without a corresponding use of other features without departing from the scope and spirit as set forth. Therefore, many modifications may be made to adapt a particular situation or material to the essential scope and spirit.

(68) For example, a third role with different attributes that can be changed by the third role may be added. As another example, additional attributes and the DiffCompare annotations for the attributes can be added to the object for parsing. DiffUtil can use the attributes and associated annotations in the code. Further, other implementations of the present disclosure are possible. For example, the present disclosure may compare numerous objects across two different batch runs; using annotations to exclude any attributes (such as an update time stamp) that are expected to change.

(69) Any suitable programming language can be used to implement the routines of particular examples including Python®, C, C++, Java®, JavaScript®, assembly language, etc. Different programming techniques can be employed such as procedural or object oriented. The routines may execute on specialized processors.

(70) The specialized processor may include memory to store a set of instructions. The instructions may be either permanently or temporarily stored in the memory or memories of the processing machine. The processor executes the instructions that are stored in the memory or memories in order to process data. The set of instructions may include various instructions that perform a particular task or tasks, such as those tasks described above. Such a set of instructions for performing a particular task may be characterized as a software program.

(71) As used in the description herein and throughout the claims that follow, “a”, “an”, and “the” includes plural references unless the context clearly dictates otherwise. Also, as used in the description herein and throughout the claims that follow, the meaning of “in” includes “in” and “on” unless the context clearly dictates otherwise.

(72) While the above is a complete description of specific examples of the disclosure, additional examples are also possible. Thus, the above description should not be taken as limiting the scope of the disclosure, which is defined by the appended claims along with their full scope of equivalents.

(73) TABLE-US-00001 APPENDIX package com.XXXXXXXX.syndicate.util; import com.XXXXXXXX.syndicate.domain.interfaces.DiffCompare; import java.lang.reflect.Field; import java.util.*; import java.util.stream.Stream; import static com.XXXXXXXX.syndicate.domain.interfaces.DiffCompare.DEFAULT; public class DiffUtil {
 public static <T> String getDiffs(T t1, T t2) { return getDiffs(t1, t2, DEFAULT, false); }
 public static <T> String getDiffs(T t1, T t2, String compareType) { return getDiffs(t1, t2, compareType, false); }
 public static <T> String getDiffs(T t1, T t2, String compareType, boolean isReverse) {
 if(t1 == null && t2 == null) return “”; if(t1 == null && t2 != null)
return “null/non-null”; if(t1 != null && t2 == null) return “non-null/null”; String
miscompares = “”; for (Field field : t1.getClass().getDeclaredFields()) {
field.setAccessible(true); boolean doCompare = isReverse; if
(field.isAnnotationPresent(DiffCompare.class)) { DiffCompare diffCompare =
field.getAnnotation(DiffCompare.class); doCompare = Stream.of(diffCompare.value(
)).anyMatch(a -> a.equals(compareType)) != isReverse; } if(doCompare) {
try { Object o1 = field.get(t1); Object o2 = field.get(t2);
if (!o1.equals(o2)) { if (!miscompares.isEmpty()) {
miscompares += “,”; } miscompares +=
field.getName() + “[“ + o1 + ”]/[“ + o2 + ”]”; } } catch (Exception e)
{ } } } return miscompares; }
 public static class DiffResult
{ private final String attribute; private final Object oldValue; private final Object
newValue; public DiffResult(String attribute, Object oldValue, Object newValue) {
this.attribute = attribute; this.oldValue = oldValue; this.newValue = newValue;
} public String getAttribute() { return attribute; } public Object
getOldValue() { return oldValue; } public Object getNewValue() { return
newValue; } }
 public static <T> Collection<DiffResult> getDiffsCollction(T t1, T t2) {
return getDiffsCollection(t1, t2, DEFAULT, false); }
 public static <T>
Collection<DiffResult> getDiffsCollection(T t1, T t2, String compareType) { return
getDiffsCollection(t1, t2, compareType, false); }
 public static <T> Collection<DiffResult>
getDiffsCollection(T t1, T t2, String compareType, boolean isReverse) { if(t1 == null && t2
== null) return Collections.EMPTY_LIST; if(t1 == null && t2 != null) return
Collections.singleton(new DiffResult(t1.getClass().getSimpleName(), “null”, “non-null”));
if(t1 != null && t2 == null) return Collections.singleton(new DiffResult(t1.getClass(
).getSimpleName(), “non-null”, “null”)); ArrayList<DiffResult> miscompares = new

```

ArrayList<>( );      for (Field field : t1.getDeclaredFields( )) {
field.setAccessible(true);      boolean doCompare = isReverse;      if
(field.isAnnotationPresent(DiffCompare.class)) {      DiffCompare diffCompare =
field.getAnnotation(DiffCompare.class);      doCompare = Stream.of(diffCompare.value(
)).anyMatch(a -> a.equals(compareType)) != isReverse;      }      if(doCompare) {
try {      Object o1 = field.get(t1);      Object o2 = field.get(t2);
if (!o1.equals(o2)) {      mismatches.add(new DiffResult(field.getName( ),
o1, o2));      }      } catch (Exception e) {      }      }      }      return
mismatches;      } } DiffCompare Annotation Interface class
com.XXXXXXXXXXX.syndicate.domain.interfaces; import java.lang.annotation.ElementType;
import java.lang.annotation.Retention; import java.lang.annotation.RetentionPolicy; import
java.lang.annotation.Target; @Retention(RetentionPolicy.RUNTIME)
@Target(ElementType.FIELD) public @interface DiffCompare {      String DEFAULT =
"DEFAULT";      String[ ] value( ) default {DEFAULT}; }

```

Claims

1. A computer program stored on a non-transitory, computer-readable storage medium having instructions, which when executed by a processor is to perform the following operations: constructing electronically an original annotated software object within a software object update system comprising an object parsing program engine and an object updating program engine; executing the object parsing program engine that electronically parses for a specific software code in the original annotated software object associated with at least one annotation construct, wherein each of the at least one annotation construct is to define which attributes of the original annotated software object can be modified and at least one user role parameter comprising a no override parameter designation authorized to implement modifications of the original annotated software object; executing the object updating program engine that electronically parses an updated annotated software object, which is an update of the original annotated software object, based on the at least one annotation construct involving: a) attribute changes to the original annotated software object; and b) the at least one user role parameter associated with the attribute changes; responsive to the at least one user role parameter being authorized to make the attribute changes, accepting the attribute changes to the original annotated software object to store the attribute changes in the updated annotated software object, and responsive to the at least one user role parameter not being authorized to make the attribute changes, rejecting the attribute changes to the original annotated software object to disallow storage of the attribute changes by the updated annotated software object; and executing a software language introspection program as part of the object parsing program engine that self-examines and manipulates internal program properties of the object parsing program engine.
2. The computer program of claim 1, when the at least one user role parameter is not authorized to make the attribute changes, returning a list of attribute changes in a string format.
3. The computer program of claim 1 when the at least one user role parameter is not authorized to make the attribute changes, returning a list of attribute changes in a map format.
4. The computer program of claim 1, wherein the attribute changes are to a subset of attributes of the original annotated software component defined by the at least one annotation construct.
5. The computer program of claim 1, wherein the at least one annotation construct defines attributes that cannot be modified.
6. A server system comprising: a network communication interface; a non-transitory storage medium with instructions; and a processor to execute the instructions to: construct electronically an original annotated software object within a software object update system comprising an object parsing program engine and an object updating program engine; execute the object parsing

program engine, over a network via the network communication interface, that electronically parses for a specific software code in the original annotated software object for at least one annotation construct, wherein each of the at least one annotation construct is to define which attributes of the original annotated software object can be modified and at least one user role parameter comprising a no override parameter designation authorized to implement modifications of the original annotated software object; executing the object updating program engine that electronically parses an updated annotated software object, which is an update of the original annotated software object based on the at least one annotation construct involving: a) attribute changes to the original annotated software object; and b) the at least one user role parameter associated with the attribute changes; responsive to the at least one user role parameter being authorized to make the attribute changes, accept the attribute changes to the original annotated software object to store the attribute changes in the updated annotated software object; and responsive to the at least one user role parameter not being authorized to make the attribute changes, reject the attribute changes to the original annotated software object to disallow storage of the attribute changes by the updated annotated software object; and execute a software language introspection program as part of the object parsing program engine that self-examines and manipulates internal program properties of the object parsing program engine.

7. The server system of claim 6, when the at least one user role parameter is not authorized to make the attribute changes, the instructions are to return a list of attribute changes in a string format.

8. The server system of claim 6, when the at least one user role parameter is not authorized to make the attribute changes, the instructions are to return a list of attribute changes in a map format.

9. The server system of claim 6, wherein the attribute changes are to a subset of attributes of the original annotated software component defined by the at least one annotation construct.

10. The server system of claim 6, wherein the at least one annotation construct defines attributes that cannot be modified.

11. The server system of claim 6, wherein the instructions reject the attribute changes of the original annotated software when the at least one annotation construct does not list the attributes.

12. The server system of claim 6, wherein the instructions pass the at least one user role parameter as a user-defined variable within the software object update system.

13. A computer implemented method of updating annotated software objects, the method comprising: constructing electronically an original annotated software object within a software object update system comprising an object parsing program engine and an object updating program engine; executing the object parsing program engine that electronically parses for a specific software code in the original annotated software object associated with at least one annotation construct, wherein each of the at least one annotation construct is to define which attributes of the original annotated software object can be modified and at least one user role parameter comprising a no override parameter designation authorized to implement modifications of the original annotated software object; executing the object updating program engine that electronically parses an updated annotated software object, which is an update of the original annotated software object, based on the at least one annotation construct involving: a) attribute changes to the original annotated software object; and b) the at least one user role parameter associated with the attribute changes; responsive to the at least one user role parameter being authorized to make the attribute changes, accepting the attribute changes to the original annotated software object to store the attribute changes in the updated annotated software object; and responsive to the at least one user role parameter not being authorized to make the attribute changes, rejecting the attribute changes to the original annotated software object to disallow storage of the attribute changes by the updated annotated software object; and executing a software language introspection program as part of the object parsing program engine that self-examines and manipulates internal program properties of the object parsing program engine.

14. The computer implemented method of claim 13, when the at least one user role parameter is not

authorized to make the attribute changes, returning a list of attribute changes in a string format and a list of attribute changes in map format.

15. The computer implemented method of claim 13, wherein the attribute changes are to attributes that are not designated by the at least one annotation construct.
