

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12413747
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Lim; Youngkwon et al.

Submesh coding for dynamic mesh coding

Abstract

An apparatus comprises a communication interface and a processor operably coupled to the communication interface. The communication interface is configured to receive a compressed bitstream including association information between scene objects and submeshes. The processor is configured to determine an index of a scene object, decode the association information between scene objects and submeshes, determine an identifier of a submesh based on the association information and the index of the scene object, and reconstruct the submesh based on the identifier.

Inventors: Lim; Youngkwon (Mckinney, TX), Joshi; Rajan Laxman (San Diego, CA), Budagavi; Madhukar (Plano, TX)

Applicant: SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)

Family ID: 91854118

Assignee: SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)

Appl. No.: 18/391526

Filed: December 20, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240244232 A1	Jul. 18, 2024

Related U.S. Application Data

us-provisional-application US 63438732 20230112
us-provisional-application US 63439459 20230117
us-provisional-application US 63440009 20230119
us-provisional-application US 63442347 20230131

Publication Classification

Int. Cl.: H04N19/17 (20140101)

U.S. Cl.:

CPC H04N19/17 (20141101);

Field of Classification Search

CPC: H04N (19/17)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6563500	12/2002	Kim et al.	N/A	N/A
6850638	12/2004	Lounsbery	382/154	G06T 17/20
8712737	12/2013	Hickman	703/2	G06T 17/00
10121279	12/2017	Sundaram et al.	N/A	N/A
10395419	12/2018	Godzaridis	N/A	G06T 15/30
10891758	12/2020	Hemmer	N/A	N/A
11120623	12/2020	Jiang et al.	N/A	N/A
11354861	12/2021	Mason	N/A	G06T 17/205
2007/0239036	12/2006	Herve	600/476	G06T 11/006
2009/0005676	12/2008	Koenig	600/425	A61B 5/0073
2018/0232849	12/2017	Fuller	N/A	G06T 1/60
2021/0074058	12/2020	Venshtain	N/A	G06T 19/003
2021/0174551	12/2020	Graziosi	N/A	G06T 15/08
2022/0385721	12/2021	Kamaraju	N/A	G06T 19/006
2023/0156177	12/2022	Sato	345/419	G06T 7/70
2023/0386133	12/2022	Grossman	N/A	G06T 15/005

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2533202	12/2011	EP	N/A
10-2313555	12/2020	KR	N/A
10-2022-0137548	12/2021	KR	N/A
WO-2020040979	12/2018	WO	N/A

OTHER PUBLICATIONS

“V-DMC Test Model v2 (TMM v2)” ISO/IEC JTC 1/SC 29/WG 7. MPEG 3D Graphics and Haptics Coding. Dec. 1, 2022. cited by applicant

“WD 1.0 of V-DMC” ISO/IEC JTC 1/SC 29/WG 07. MPEG 3DGH. Nov. 16, 2022. cited by applicant

“Information technology—Coded Representation of Immersive Media—Part 5: Visual Volumetric Video-based Coding (V3C) and Video-based Point Cloud Compression (V-PCC)” ISO/IEC JTC

Primary Examiner: Jiang; Zaihan

Attorney, Agent or Firm: BROADVIEW IP LAW, PC

Background/Summary

CROSS REFERENCE TO RELATED APPLICATION (1) This application claims benefit of U.S. Provisional Application No. 63/438,732 filed on Jan. 12, 2023, U.S. Provisional Application No. 63/439,459 filed on Jan. 17, 2023, U.S. Provisional Application No. 63/440,009 filed on Jan. 19, 2023, U.S. Provisional Application No. 63/442,347 filed on Jan. 31, 2023, U.S. Provisional Application No. 63/459,873 filed on Apr. 17, 2023, and U.S. Provisional Application No. 63/542,897 filed on Oct. 6, 2023, in the United States Patent and Trademark Office, the entire contents of which are hereby incorporated by reference.

TECHNICAL FIELD

(1) The disclosure relates to dynamic mesh coding, and more particularly to, for example, but not limited to, submesh coding for dynamic mesh coding.

BACKGROUND

(2) Typically mesh encoding and decoding operations may be highly sequential. For base meshes with large number of vertices and high frame rates, a mesh codec such as Draco may have difficulty achieving real-time encoding and decoding. To alleviate this problem, the working draft (WD) 1.0 of the Video-based Dynamic Mesh Coding (V-DMC) has introduced the concept of submeshes. The basic idea is that a base mesh may be divided into multiple submeshes. Since the submeshes may not be mutually exclusive, some vertices and triangles may be common to different submeshes. The submeshes can be encoded and decoded independently without using any information from other submeshes. This can allow multiple instances of a mesh codec to operate in parallel on different submeshes. Furthermore, it enables functionality to perform partial decoding of the mesh by decoding only some of the submeshes present in a V-DMC bitstream. Each decoded submesh may undergo subdivision and then the decoded displacement field may be used to refine the positions of the subdivided points belonging to that submesh.

(3) The creation of submeshes, however, may not be sufficient to ensure the functionality of partial delivery, decoding and reconstruction of the full resolution mesh. As rendering engine decides which part of mesh needs to be decoded and reconstructed according to the context of rendering such as view point of the user and field of view of rendering devices and so on, a mesh may have to be subdivided into submeshes in a way that the appropriate portion of the mesh can be easily identified, delivered, decoded and reconstructed. For example, if a front side of an object needs to be rendered but the mesh is subdivided into a first submesh for a top part of the object, a second submesh for a middle part of the object, and a third submesh for a bottom part of the object according to semantical difference of the portions, then all three submeshes need to be delivered, decoded and reconstructed. So, subdivision of mesh to submeshes does not support partial access of a mesh.

(4) The description set forth in the background section should not be assumed to be prior art merely because it is set forth in the background section. The background section may describe aspects or embodiments of the present disclosure.

SUMMARY

- (5) Embodiments propose some methods to subdivide mesh into submeshes so that the portions of mesh according to the area to be rendered can be efficiently identified, delivered, decoded and reconstructed. Embodiments relates to improvements in the ability to perform partial decoding of the V-DMC bitstreams when multiple submeshes are being used.
- (6) One embodiment of the present disclosure may provide an apparatus comprising: a communication interface configured to receive a compressed bitstream including association information between scene objects and submeshes, wherein each of the submeshes is independently decodable from other submeshes; and a processor operably coupled to the communication interface. The processor may be configured to determine an index of a scene object, decode the association information between scene objects and submeshes, determine an identifier of a submesh based on the index of the scene object and the association information, and reconstruct the submesh based on the identifier.
- (7) In some embodiments, the association information includes a plurality of indices of the scene objects and a plurality of identifiers of the plurality of submeshes each being associated with a respective one index of the plurality of indices of the scene objects.
- (8) In some embodiments, the association information further includes first number information indicating a number of scene objects specified in the association information.
- (9) In some embodiments, the association information further includes second number information indicating a number of the plurality of identifiers of the plurality of submeshes. In some embodiments, the association information further includes information indicating whether a respective one submesh of the plurality of the submesh is completely included in a scene object associated with the respective one submesh.
- (10) In some embodiments, the compressed bitstream further includes 3D bounding box information specifying association between 3D bounding boxes and submeshes, and the index of the scene object is determined based on the 3D bounding box information.
- (11) In some embodiments, the compressed bitstream further includes visibility cones information specifying association between visibility cones and submeshes, and the index of the scene object is determined based on the visibility cones information.
- (12) In some embodiments, the association information further includes persistence information indicating whether a relationship between the scene objects and submeshes specified by the association information is persistent.
- (13) One embodiment of the present disclosure may provide a method comprising receiving a compressed bitstream including association information between scene objects and submeshes; determining an index of a scene object; decoding the association information between scene objects and submeshes; determining an identifier of a submesh based on the index of the scene object and the association information; and reconstructing the submesh based on the identifier.
- (14) In some embodiments, the association information includes a plurality of indices of the scene objects and a plurality of identifiers of the plurality of submeshes each being associated with a respective one index of the plurality of indices of the scene objects.
- (15) In some embodiments, the association information further includes first number information indicating a number of scene objects specified in the association information.
- (16) In some embodiments, the association information further includes second number information indicating a number of the plurality of identifiers of the plurality of submeshes.
- (17) In some embodiments, the association information further includes information indicating whether a respective one submesh of the plurality of the submesh is completely included in a scene object associated with the respective one submesh.
- (18) In some embodiments, the compressed bitstream further includes 3D bounding box information specifying association between 3D bounding boxes and submeshes, and the index of the scene object is determined based on the 3D bounding box information.
- (19) In some embodiments, the compressed bitstream further includes visibility cones information

specifying association between visibility cones and submeshes, and the index of the scene object is determined based on the visibility cones information.

(20) In some embodiments, the association information further includes persistence information indicating whether a relationship between the scene objects and submeshes specified by the association information is persistent.

(21) One embodiment of the present disclosure may provide an apparatus comprising a communication interface; and a processor operably coupled to the communication interface. The processor may be configured to divide a base mesh into a plurality of submeshes, encode a submesh of the plurality of submeshes independently from other submeshes, encode association information between scene objects and submeshes, and combine the encoded submesh and the encoded association information into a compressed bitstream.

(22) In some embodiments, the association information includes a plurality of indices of the scene objects and a plurality of identifiers of the plurality of submeshes each being associated with a respective one index of the plurality of indices of the scene objects.

(23) In some embodiments, the compressed bitstream further includes 3D bounding box information specifying association between 3D bounding boxes and submeshes.

(24) In some embodiments, the compressed bitstream further includes visibility cones information specifying association between visibility cones and submeshes.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 illustrates an example communication system **100** in accordance with an embodiment of this disclosure.

(2) FIGS. 2 and 3 illustrate example electronic devices in accordance with an embodiment of this disclosure.

(3) FIG. 4 illustrates a block diagram for an encoder encoding intra frames in accordance with an embodiment.

(4) FIG. 5 illustrates a block diagram for a decoder in accordance with an embodiment.

(5) FIG. 6 illustrates a flowchart for an encoder in accordance with an embodiment.

(6) FIG. 7 illustrates a flowchart for a decoder in accordance with an embodiment.

(7) FIG. 8 illustrates a 3D grid in accordance with an embodiment.

(8) FIG. 9 illustrates a flowchart for an encoder in accordance with an embodiment.

(9) FIG. 10 illustrates a flowchart for a decoder in accordance with an embodiment.

(10) FIG. 11 illustrates a flowchart for an encoder in accordance with an embodiment.

(11) FIG. 12 illustrates a flowchart for a decoder in accordance with an embodiment.

(12) In one or more implementations, not all of the depicted components in each figure may be required, and one or more implementations may include additional components not shown in a figure. Variations in the arrangement and type of the components may be made without departing from the scope of the subject disclosure. Additional components, different components, or fewer components may be utilized within the scope of the subject disclosure.

DETAILED DESCRIPTION

(13) The detailed description set forth below, in connection with the appended drawings, is intended as a description of various implementations and is not intended to represent the only implementations in which the subject technology may be practiced. Rather, the detailed description includes specific details for the purpose of providing a thorough understanding of the inventive subject matter. As those skilled in the art would realize, the described implementations may be modified in various ways, all without departing from the scope of the present disclosure. Accordingly, the drawings and description are to be regarded as illustrative in nature and not

restrictive. Like reference numerals designate like elements.

(14) Three hundred sixty degree (360°) video and 3D volumetric video are emerging as new ways of experiencing immersive content due to the ready availability of powerful handheld devices such as smartphones. While 360° video enables immersive “real life,” “being there” experience for consumers by capturing the 360° outside-in view of the world, 3D volumetric video can provide complete 6DoF experience of being and moving within the content. Users can interactively change their viewpoint and dynamically view any part of the captured scene or object they desire. Display and navigation sensors can track head movement of the user in real-time to determine the region of the 360° video or volumetric content that the user wants to view or interact with. Multimedia data that is three-dimensional (3D) in nature, such as point clouds or 3D polygonal meshes, can be used in the immersive environment.

(15) A point cloud is a set of 3D points along with attributes such as color, normal, reflectivity, point-size, etc. that represent an object's surface or volume. Point clouds are common in a variety of applications such as gaming, 3D maps, visualizations, medical applications, augmented reality, virtual reality, autonomous driving, multi-view replay, 6DoF immersive media, to name a few. Point clouds, if uncompressed, generally require a large amount of bandwidth for transmission. Due to the large bitrate requirement, point clouds are often compressed prior to transmission. To compress a 3D object such as a point cloud, often requires specialized hardware. To avoid specialized hardware to compress a 3D point cloud, a 3D point cloud can be transformed into traditional two-dimensional (2D) frames and that can be compressed and later be reconstructed and viewable to a user.

(16) Polygonal 3D meshes, especially triangular meshes, are another popular format for representing 3D objects. Meshes typically consist of a set of vertices, edges and faces that are used for representing the surface of 3D objects. Triangular meshes are simple polygonal meshes in which the faces are simple triangles covering the surface of the 3D object. Typically, there may be one or more attributes associated with the mesh. In one scenario, one or more attributes may be associated with each vertex in the mesh. For example, a texture attribute (RGB) may be associated with each vertex. In another scenario, each vertex may be associated with a pair of coordinates, (u, v). The (u, v) coordinates may point to a position in a texture map associated with the mesh. For example, the (u, v) coordinates may refer to row and column indices in the texture map, respectively. A mesh can be thought of as a point cloud with additional connectivity information.

(17) The point cloud or meshes may be dynamic, i.e., they may vary with time. In these cases, the point cloud or mesh at a particular time instant may be referred to as a point cloud frame or a mesh frame, respectively.

(18) Since point clouds and meshes contain a large amount of data, they require compression for efficient storage and transmission. This is particularly true for dynamic point clouds and meshes, which may contain 60 frames or higher per second.

(19) Figures discussed below, and the various embodiments used to describe the principles of the present disclosure in this patent document are by way of illustration only and should not be construed in any way to limit the scope of the disclosure. Those skilled in the art will understand that the principles of the present disclosure may be implemented in any suitably-arranged system or device.

(20) FIG. 1 illustrates an example communication system **100** in accordance with an embodiment of this disclosure. The embodiment of the communication system **100** shown in FIG. 1 is for illustration only. Other embodiments of the communication system **100** can be used without departing from the scope of this disclosure.

(21) The communication system **100** includes a network **102** that facilitates communication between various components in the communication system **100**. For example, the network **102** can communicate IP packets, frame relay frames, Asynchronous Transfer Mode (ATM) cells, or other information between network addresses. The network **102** includes one or more local area networks

(LANs), metropolitan area networks (MANs), wide area networks (WANs), all or a portion of a global network such as the Internet, or any other communication system or systems at one or more locations.

(22) In this example, the network **102** facilitates communications between a server **104** and various client devices **106-116**. The client devices **106-116** may be, for example, a smartphone, a tablet computer, a laptop, a personal computer, a TV, an interactive display, a wearable device, a HMD, or the like. The server **104** can represent one or more servers. Each server **104** includes any suitable computing or processing device that can provide computing services for one or more client devices, such as the client devices **106-116**. Each server **104** could, for example, include one or more processing devices, one or more memories storing instructions and data, and one or more network interfaces facilitating communication over the network **102**. As described in more detail below, the server **104** can transmit a compressed bitstream, representing a point cloud or mesh, to one or more display devices, such as a client device **106-116**. In certain embodiments, each server **104** can include an encoder.

(23) Each client device **106-116** represents any suitable computing or processing device that interacts with at least one server (such as the server **104**) or other computing device(s) over the network **102**. The client devices **106-116** include a desktop computer **106**, a mobile telephone or mobile device **108** (such as a smartphone), a PDA **110**, a laptop computer **112**, a tablet computer **114**, and a HMD **116**. However, any other or additional client devices could be used in the communication system **100**. Smartphones represent a class of mobile devices **108** that are handheld devices with mobile operating systems and integrated mobile broadband cellular network connections for voice, short message service (SMS), and Internet data communications. The HMD **116** can display 360° scenes including one or more dynamic or static 3D point clouds. In certain embodiments, any of the client devices **106-116** can include an encoder, decoder, or both. For example, the mobile device **108** can record a 3D volumetric video and then encode the video enabling the video to be transmitted to one of the client devices **106-116**. In another example, the laptop computer **112** can be used to generate a 3D point cloud or mesh, which is then encoded and transmitted to one of the client devices **106-116**.

(24) In this example, some client devices **108-116** communicate indirectly with the network **102**. For example, the mobile device **108** and PDA **110** communicate via one or more base stations **118**, such as cellular base stations or eNodeBs (eNBs). Also, the laptop computer **112**, the tablet computer **114**, and the HMD **116** communicate via one or more wireless access points **120**, such as IEEE 802.11 wireless access points. Note that these are for illustration only and that each client device **106-116** could communicate directly with the network **102** or indirectly with the network **102** via any suitable intermediate device(s) or network(s). In certain embodiments, the server **104** or any client device **106-116** can be used to compress a point cloud or mesh, generate a bitstream that represents the point cloud or mesh, and transmit the bitstream to another client device such as any client device **106-116**.

(25) In certain embodiments, any of the client devices **106-114** transmit information securely and efficiently to another device, such as, for example, the server **104**. Also, any of the client devices **106-116** can trigger the information transmission between itself and the server **104**. Any of the client devices **106-114** can function as a VR display when attached to a headset via brackets, and function similar to HMD **116**. For example, the mobile device **108** when attached to a bracket system and worn over the eyes of a user can function similarly as the HMD **116**. The mobile device **108** (or any other client device **106-116**) can trigger the information transmission between itself and the server **104**.

(26) In certain embodiments, any of the client devices **106-116** or the server **104** can create a 3D point cloud or mesh, compress a 3D point cloud or mesh, transmit a 3D point cloud or mesh, receive a 3D point cloud or mesh, decode a 3D point cloud or mesh, render a 3D point cloud or mesh, or a combination thereof. For example, the server **104** can then compress 3D point cloud or

mesh to generate a bitstream and then transmit the bitstream to one or more of the client devices **106-116**. For another example, one of the client devices **106-116** can compress a 3D point cloud or mesh to generate a bitstream and then transmit the bitstream to another one of the client devices **106-116** or to the server **104**.

(27) Although FIG. **1** illustrates one example of a communication system **100**, various changes can be made to FIG. **1**. For example, the communication system **100** could include any number of each component in any suitable arrangement. In general, computing and communication systems come in a wide variety of configurations, and FIG. **1** does not limit the scope of this disclosure to any particular configuration. While FIG. **1** illustrates one operational environment in which various features disclosed in this patent document can be used, these features could be used in any other suitable system.

(28) FIGS. **2** and **3** illustrate example electronic devices in accordance with an embodiment of this disclosure. In particular, FIG. **2** illustrates an example server **200**, and the server **200** could represent the server **104** in FIG. **1**. The server **200** can represent one or more encoders, decoders, local servers, remote servers, clustered computers, and components that act as a single pool of seamless resources, a cloud-based server, and the like. The server **200** can be accessed by one or more of the client devices **106-116** of FIG. **1** or another server.

(29) The server **200** can represent one or more local servers, one or more compression servers, or one or more encoding servers, such as an encoder. In certain embodiments, the encoder can perform decoding. As shown in FIG. **2**, the server **200** includes a bus system **205** that supports communication between at least one processing device (such as a processor **210**), at least one storage device **215**, at least one communications interface **220**, and at least one input/output (I/O) unit **225**.

(30) The processor **210** executes instructions that can be stored in a memory **230**. The processor **210** can include any suitable number(s) and type(s) of processors or other devices in any suitable arrangement. Example types of processors **210** include microprocessors, microcontrollers, digital signal processors, field programmable gate arrays, application specific integrated circuits, and discrete circuitry.

(31) In certain embodiments, the processor **210** can encode a 3D point cloud or mesh stored within the storage devices **215**. In certain embodiments, encoding a 3D point cloud also decodes the 3D point cloud or mesh to ensure that when the point cloud or mesh is reconstructed, the reconstructed 3D point cloud or mesh matches the 3D point cloud or mesh prior to the encoding.

(32) The memory **230** and a persistent storage **235** are examples of storage devices **215** that represent any structure(s) capable of storing and facilitating retrieval of information (such as data, program code, or other suitable information on a temporary or permanent basis). The memory **230** can represent a random access memory or any other suitable volatile or non-volatile storage device(s). For example, the instructions stored in the memory **230** can include instructions for decomposing a point cloud into patches, instructions for packing the patches on 2D frames, instructions for compressing the 2D frames, as well as instructions for encoding 2D frames in a certain order in order to generate a bitstream. The instructions stored in the memory **230** can also include instructions for rendering the point cloud on an omnidirectional 360° scene, as viewed through a VR headset, such as HMD **116** of FIG. **1**. The persistent storage **235** can contain one or more components or devices supporting longer-term storage of data, such as a read only memory, hard drive, Flash memory, or optical disc.

(33) The communications interface **220** supports communications with other systems or devices. For example, the communications interface **220** could include a network interface card or a wireless transceiver facilitating communications over the network **102** of FIG. **1**. The communications interface **220** can support communications through any suitable physical or wireless communication link(s). For example, the communications interface **220** can transmit a bitstream containing a 3D point cloud to another device such as one of the client devices **106-116**.

(34) The I/O unit **225** allows for input and output of data. For example, the I/O unit **225** can provide a connection for user input through a keyboard, mouse, keypad, touchscreen, or other suitable input device. The I/O unit **225** can also send output to a display, printer, or other suitable output device. Note, however, that the I/O unit **225** can be omitted, such as when I/O interactions with the server **200** occur via a network connection.

(35) Note that while FIG. **2** is described as representing the server **104** of FIG. **1**, the same or similar structure could be used in one or more of the various client devices **106-116**. For example, a desktop computer **106** or a laptop computer **112** could have the same or similar structure as that shown in FIG. **2**.

(36) FIG. **3** illustrates an example electronic device **300**, and the electronic device **300** could represent one or more of the client devices **106-116** in FIG. **1**. The electronic device **300** can be a mobile communication device, such as, for example, a mobile station, a subscriber station, a wireless terminal, a desktop computer (similar to the desktop computer **106** of FIG. **1**), a portable electronic device (similar to the mobile device **108**, the PDA **110**, the laptop computer **112**, the tablet computer **114**, or the HMD **116** of FIG. **1**), and the like. In certain embodiments, one or more of the client devices **106-116** of FIG. **1** can include the same or similar configuration as the electronic device **300**. In certain embodiments, the electronic device **300** is an encoder, a decoder, or both. For example, the electronic device **300** is usable with data transfer, image or video compression, image or video decompression, encoding, decoding, and media rendering applications.

(37) As shown in FIG. **3**, the electronic device **300** includes an antenna **305**, a radio-frequency (RF) transceiver **310**, transmit (TX) processing circuitry **315**, a microphone **320**, and receive (RX) processing circuitry **325**. The RF transceiver **310** can include, for example, a RF transceiver, a BLUETOOTH transceiver, a WI-FI transceiver, a ZIGBEE transceiver, an infrared transceiver, and various other wireless communication signals. The electronic device **300** also includes a speaker **330**, a processor **340**, an input/output (I/O) interface (IF) **345**, an input **350**, a display **355**, a memory **360**, and a sensor(s) **365**. The memory **360** includes an operating system (OS) **361**, and one or more applications **362**.

(38) The RF transceiver **310** receives, from the antenna **305**, an incoming RF signal transmitted from an access point (such as a base station, WI-FI router, or BLUETOOTH device) or other device of the network **102** (such as a WI-FI, BLUETOOTH, cellular, 5G, LTE, LTE-A, WiMAX, or any other type of wireless network). The RF transceiver **310** down-converts the incoming RF signal to generate an intermediate frequency or baseband signal. The intermediate frequency or baseband signal is sent to the RX processing circuitry **325** that generates a processed baseband signal by filtering, decoding, and/or digitizing the baseband or intermediate frequency signal. The RX processing circuitry **325** transmits the processed baseband signal to the speaker **330** (such as for voice data) or to the processor **340** for further processing (such as for web browsing data).

(39) The TX processing circuitry **315** receives analog or digital voice data from the microphone **320** or other outgoing baseband data from the processor **340**. The outgoing baseband data can include web data, e-mail, or interactive video game data. The TX processing circuitry **315** encodes, multiplexes, and/or digitizes the outgoing baseband data to generate a processed baseband or intermediate frequency signal. The RF transceiver **310** receives the outgoing processed baseband or intermediate frequency signal from the TX processing circuitry **315** and up-converts the baseband or intermediate frequency signal to an RF signal that is transmitted via the antenna **305**.

(40) The processor **340** can include one or more processors or other processing devices. The processor **340** can execute instructions that are stored in the memory **360**, such as the OS **361** in order to control the overall operation of the electronic device **300**. For example, the processor **340** could control the reception of forward channel signals and the transmission of reverse channel signals by the RF transceiver **310**, the RX processing circuitry **325**, and the TX processing circuitry **315** in accordance with well-known principles. The processor **340** can include any suitable

number(s) and type(s) of processors or other devices in any suitable arrangement. For example, in certain embodiments, the processor **340** includes at least one microprocessor or microcontroller. Example types of processor **340** include microprocessors, microcontrollers, digital signal processors, field programmable gate arrays, application specific integrated circuits, and discrete circuitry.

(41) The processor **340** is also capable of executing other processes and programs resident in the memory **360**, such as operations that receive and store data. The processor **340** can move data into or out of the memory **360** as required by an executing process. In certain embodiments, the processor **340** is configured to execute the one or more applications **362** based on the OS **361** or in response to signals received from external source(s) or an operator. Example, applications **362** can include an encoder, a decoder, a VR or AR application, a camera application (for still images and videos), a video phone call application, an email client, a social media client, a SMS messaging client, a virtual assistant, and the like. In certain embodiments, the processor **340** is configured to receive and transmit media content.

(42) The processor **340** is also coupled to the I/O interface **345** that provides the electronic device **300** with the ability to connect to other devices, such as client devices **106-114**. The I/O interface **345** is the communication path between these accessories and the processor **340**.

(43) The processor **340** is also coupled to the input **350** and the display **355**. The operator of the electronic device **300** can use the input **350** to enter data or inputs into the electronic device **300**. The input **350** can be a keyboard, touchscreen, mouse, track ball, voice input, or other device capable of acting as a user interface to allow a user in interact with the electronic device **300**. For example, the input **350** can include voice recognition processing, thereby allowing a user to input a voice command. In another example, the input **350** can include a touch panel, a (digital) pen sensor, a key, or an ultrasonic input device. The touch panel can recognize, for example, a touch input in at least one scheme, such as a capacitive scheme, a pressure sensitive scheme, an infrared scheme, or an ultrasonic scheme. The input **350** can be associated with the sensor(s) **365** and/or a camera by providing additional input to the processor **340**. In certain embodiments, the sensor **365** includes one or more inertial measurement units (IMUs) (such as accelerometers, gyroscope, and magnetometer), motion sensors, optical sensors, cameras, pressure sensors, heart rate sensors, altimeter, and the like. The input **350** can also include a control circuit. In the capacitive scheme, the input **350** can recognize touch or proximity.

(44) The display **355** can be a liquid crystal display (LCD), light-emitting diode (LED) display, organic LED (OLED), active matrix OLED (AMOLED), or other display capable of rendering text and/or graphics, such as from websites, videos, games, images, and the like. The display **355** can be sized to fit within a HMD. The display **355** can be a singular display screen or multiple display screens capable of creating a stereoscopic display. In certain embodiments, the display **355** is a heads-up display (HUD). The display **355** can display 3D objects, such as a 3D point cloud or mesh.

(45) The memory **360** is coupled to the processor **340**. Part of the memory **360** could include a RAM, and another part of the memory **360** could include a Flash memory or other ROM. The memory **360** can include persistent storage (not shown) that represents any structure(s) capable of storing and facilitating retrieval of information (such as data, program code, and/or other suitable information). The memory **360** can contain one or more components or devices supporting longer-term storage of data, such as a read only memory, hard drive, Flash memory, or optical disc. The memory **360** also can contain media content. The media content can include various types of media such as images, videos, three-dimensional content, VR content, AR content, 3D point clouds, meshes, and the like.

(46) The electronic device **300** further includes one or more sensors **365** that can meter a physical quantity or detect an activation state of the electronic device **300** and convert metered or detected information into an electrical signal. For example, the sensor **365** can include one or more buttons

for touch input, a camera, a gesture sensor, an IMU sensors (such as a gyroscope or gyro sensor and an accelerometer), an eye tracking sensor, an air pressure sensor, a magnetic sensor or magnetometer, a grip sensor, a proximity sensor, a color sensor, a bio-physical sensor, a temperature/humidity sensor, an illumination sensor, an Ultraviolet (UV) sensor, an Electromyography (EMG) sensor, an Electroencephalogram (EEG) sensor, an Electrocardiogram (ECG) sensor, an IR sensor, an ultrasound sensor, an iris sensor, a fingerprint sensor, a color sensor (such as a Red Green Blue (RGB) sensor), and the like. The sensor **365** can further include control circuits for controlling any of the sensors included therein.

(47) As discussed in greater detail below, one or more of these sensor(s) **365** may be used to control a user interface (UI), detect UI inputs, determine the orientation and facing the direction of the user for three-dimensional content display identification, and the like. Any of these sensor(s) **365** may be located within the electronic device **300**, within a secondary device operably connected to the electronic device **300**, within a headset configured to hold the electronic device **300**, or in a singular device where the electronic device **300** includes a headset.

(48) The electronic device **300** can create media content such as generate a virtual object or capture (or record) content through a camera. The electronic device **300** can encode the media content to generate a bitstream, such that the bitstream can be transmitted directly to another electronic device or indirectly such as through the network **102** of FIG. **1**. The electronic device **300** can receive a bitstream directly from another electronic device or indirectly such as through the network **102** of FIG. **1**.

(49) Although FIGS. **2** and **3** illustrate examples of electronic devices, various changes can be made to FIGS. **2** and **3**. For example, various components in FIGS. **2** and **3** could be combined, further subdivided, or omitted and additional components could be added according to particular needs. As a particular example, the processor **340** could be divided into multiple processors, such as one or more central processing units (CPUs) and one or more graphics processing units (GPUs). In addition, as with computing and communication, electronic devices and servers can come in a wide variety of configurations, and FIGS. **2** and **3** do not limit this disclosure to any particular electronic device or server.

(50) FIG. **4** illustrates a block diagram for an encoder encoding intra frames in accordance with an embodiment.

(51) As shown in FIG. **4**, the encoder **400** encoding intra frames in accordance with an embodiment may comprise a quantizer **401**, a static mesh encoder **403**, a static mesh decoder **405**, a displacements updater **407**, a wavelet transformer **409**, a quantizer **411**, an image packer **413**, a video encoder **415**, an image unpacker **417**, an inverse quantizer **419**, an inverse wavelet transformer **421**, an inverse quantizer **423**, a deformed mesh reconstructor **425**, an attribute transfer module **427**, a padding module **429**, a color space converter **431**, a video encoder **433**, a multiplexer **435**, and a controller **437**.

(52) The quantizer **401** may quantize a base mesh $m(i)$ to generate a quantized base mesh. In some embodiments, the base mesh may have fewer vertices compared to an original mesh.

(53) The static mesh encoder **403** may encode and compress the quantized base mesh to generate a compressed base mesh bitstream. In some embodiments, the base mesh may be compressed in a lossy or lossless manner. In some embodiments, an already existing mesh codec such as Draco may be used to compress the base mesh.

(54) The static mesh decoder **405** may decode the compressed base mesh bitstream to generate a reconstructed quantized base mesh $m'(i)$.

(55) The displacements updater **407** may update displacements $d(i)$ based on the base mesh $m(i)$ and the reconstructed quantized base mesh $m'(i)$ to generate updated displacements $d'(i)$. The reconstructed base mesh may undergo subdivision and then a displacement field between the original mesh and the subdivided reconstructed base mesh may be calculated. In inter coding of mesh frame, the base mesh may be coded by sending vertex motions instead of compressing the

base mesh directly. In either case, a displacement field may be created. The displacement field as well as the modified attribute map may be coded using a video codec and also included as a part of the V-DMC bitstream.

(56) The wavelet transformer **409** may perform a wavelet transform with the updated displacements $d'(i)$ to generate wavelet coefficients $e(i)$.

(57) The quantizer **411** may quantize the wavelet coefficients $e(i)$ to generate quantized wavelet coefficients $e'(i)$.

(58) The image packer **413** may pack the quantized wavelet coefficients $e'(i)$ into a 2D image to generate packed quantized wavelet coefficients.

(59) The video encoder **415** may encode the packed quantized wavelet coefficients to generate a compressed displacements bitstream.

(60) The image unpacker **417** may unpack the packed quantized wavelet coefficients to generate unpacked quantized wavelet coefficients.

(61) The inverse quantizer **419** may inversely quantize the quantized wavelet coefficients to generate wavelet coefficients.

(62) The inverse wavelet transformer **421** may perform an inverse wavelet transform with the wavelet coefficients to generate reconstructed displacements $d''(i)$.

(63) The inverse quantizer **423** may inversely quantize the reconstructed quantized base mesh $m'(i)$ to generate a reconstructed base mesh $m''(i)$.

(64) The deformed mesh reconstructor **425** may generate a reconstruct deformed mesh $DM(i)$ based on the reconstructed displacements $D''(i)$ and a reconstructed base mesh $m''(i)$.

(65) The attribute transfer module **427** may update an attribute map $A(i)$ based on a static/dynamic mesh $m(i)$ and a reconstructed deformed mesh $DM(i)$ to generate an updated attribute map $A'(i)$. The attribute map may be a texture map but other attributes may be sent as well.

(66) The padding module **429** may perform padding to fill empty areas in the updated attribute map $A'(i)$ so as to remove high frequency components.

(67) The color space converter **431** may perform a color space conversion of the padded updated attribute map $A'(i)$.

(68) The video encoder **433** may encode the output of the color space converter **431** to generate the compressed attribute bitstream.

(69) The multiplexer **435** may multiplex the compressed base mesh bitstream, the compressed displacements bitstream, and the compressed attribute bitstream to generate a compressed bitstream $b(i)$.

(70) The controller **437** may control modules of the encoder **400**.

(71) FIG. 5 illustrates a block diagram for a decoder in accordance with an embodiment.

(72) As shown in FIG. 5, the decoder **500** may comprise a demultiplexer **501**, a switch **503**, a static mesh decoder **505**, a mesh buffer **507**, a motion decoder **509**, a base mesh reconstructor **511**, a switch **513**, an inverse quantizer **515**, a video decoder **521**, an image unpacker **523**, an inverse quantizer **525**, an inverse wavelet transformer **527**, a deformed mesh reconstructor **529**, a video decoder **531**, and a color space converter **533**.

(73) The demultiplexer **501** may receive the compressed bitstream $b(i)$ from the encoder **400** to extract the compressed base mesh bitstream, the compressed displacements bitstream, and the compressed attribute bitstream from the compressed bitstream $b(i)$.

(74) The switch **503** may determine whether the compressed base mesh bitstream has an inter-coded mesh frame data or an intra-coded mesh frame data. If the compressed base mesh bitstream has the inter-coded mesh frame data, the switch **503** may transfer the inter-coded mesh frame data to the motion decoder **509**. If the compressed base mesh bitstream has the intra-coded mesh frame data, the switch **503** may transfer the intra-coded mesh frame data to the static mesh decoder **507**.

(75) The static mesh decoder **505** may decode the intra-coded mesh frame data to generate a reconstructed quantized base mesh frame.

- (76) The mesh buffer **507** may store the reconstructed quantized base mesh frames and the inter-coded mesh frame data for future use of decoding subsequent inter-coded mesh frames. The reconstructed quantized base mesh frames may be used as reference mesh frames.
- (77) The motion decoder **509** may obtain motion vectors for a current inter-coded mesh frame based on data stored in the mesh buffer **507** and syntax elements in the bitstream for the current inter-coded mesh frame. In some embodiments, the syntax elements in the bitstream for the current inter-coded mesh frame may be a motion vector difference.
- (78) The base mesh reconstructor **511** may generate a reconstructed quantized base mesh frame by using syntax elements in the bitstream for the current inter-coded mesh frame based on the motion vectors for the current inter-coded mesh frame.
- (79) The switch **513** may transmit the reconstructed quantized base mesh frame from the static mesh decoder **505** to the inverse quantizer **515**, if the compressed base mesh bitstream has the intra-coded mesh frame data. The switch **513** may transmit the reconstructed quantized base mesh frame from the static mesh decoder **511** to the inverse quantizer **515**, if the compressed base mesh bitstream has the inter-coded mesh frame data.
- (80) The inverse quantizer **515** may perform an inverse quantization with the reconstructed quantized base mesh frame to generate a reconstructed base mesh frame $m''(i)$.
- (81) The video decoder **521** may decode a displacements bitstream to generate packed quantized wavelet coefficients.
- (82) The image unpacker **523** may unpack the packed quantized wavelet coefficients to generate quantized wavelet coefficients.
- (83) The inverse quantizer **525** may perform the inverse quantization with quantized wavelet coefficients to generate wavelet coefficients.
- (84) The inverse wavelet transformer **527** may perform the inverse wavelet transform with wavelet coefficients to generate displacements.
- (85) The deformed mesh reconstructor **529** may reconstruct a deformed mesh based on the displacements and the reconstructed base mesh frame $m''(i)$.
- (86) The video decoder **531** may decode the attribute bitstream to generate an attribute map before a color space conversion.
- (87) The color space converter **533** may perform a color space conversion of the attribute map from the video decoder **531** to reconstruct the attribute map.
- (88) FIG. 6 illustrates a flowchart for an encoder in accordance with an embodiment.
- (89) At **601**, the encoder may divide a base mesh into a plurality of submeshes based on a linear 3D grid specifying a plurality of cuboids. In some embodiments, each of the plurality of submeshes may be associated with a respective one of the plurality of cuboids.
- (90) At **603**, the encoder may independently encode the plurality of submeshes to allow the decoder's partial access of the mesh by identifying, delivering, decoding and reconstructing only some of the submeshes present in a V-DMC bitstream. In some embodiments, each of the submeshes may be independently decodable from other submeshes.
- (91) At **605**, the encoder may encode 3D grid information for the linear 3D grid.
- (92) At **607**, the encoder may combine the plurality of encoded submeshes and the 3D grid information into a compressed bitstream. In some embodiments, the 3D grid information may be provided in a supplemental enhancement information (SEI) message or a volumetric usability information (VUI) message.
- (93) FIG. 7 illustrates a flowchart for a decoder in accordance with an embodiment.
- (94) At **701**, the decoder may receive a compressed bitstream including a plurality of encoded submeshes and 3D grid information.
- (95) At **703**, the decoder may determine a 3D region of a volumetric scene to be rendered. In some embodiments, the 3D region of the volumetric scene to be rendered may be determined according to a context of rendering such as view point of the user and a field of view of a rendering device

including the decoder.

(96) At **705**, the decoder may parse the bitstream and decode 3D grid information for the linear 3D grid specifying a plurality of cuboids.

(97) At **707**, the decoder may determine, among the plurality of cuboids specified by the linear 3D grid, one or more cuboids which overlap with the determined 3D region of the volumetric scene based on the decoded 3D grid information.

(98) At **709**, the decoder may identify identifiers of one or more submeshes belonging to the determined one or more cuboids. In some embodiments, an identifier of a submesh belonging to a cuboid may be calculated based on the 3D grid information.

(99) At **711**, the decoder may extract, from the bitstream, the one or more encoded submeshes based on the identifiers of one or more submeshes.

(100) At **713**, the decoder may decode the one or more encoded submeshes to reconstruct the one or more submeshes belonging to the 3D region of the volumetric scene.

(101) Hereinafter, the 3D grid information for the linear 3D grid in accordance with various embodiments will be described with reference to FIG. **8**.

(102) FIG. **8** illustrates a 3D grid in accordance with an embodiment.

(103) As shown in FIG. **8**, the 3D grid **800** may be defined in the local 3D patch coordinate system (u, v, d). The local 3D patch coordinate system (u, v, d) may be defined by the projection plane with origin O', tangent (u), bi-tangent (v), and normal (d) axes.

(104) In some embodiments, a mesh may be subdivided into submeshes based on a linear 3D grid **800**. In some embodiments, the origin position **801** of the 3D grid **800** to be applied to a mesh for subdivision may not be same with the origin position of the mesh. In some embodiments, the origin position **801** of the 3D grid **800** may be decided by a bitstream sender including an encoder which subdivides the mesh and the information about the difference between the origin position of the mesh and the origin position **801** of the 3D grid **800** may be signaled to a bitstream receiver including a decoder which decodes and reconstructs the submeshes.

(105) The structure of the 3D grid **800** on each axis may be decided by the bitstream sender. In some embodiments, the structure of the 3D grid **800** may be uniform. In some embodiments, when the structure of the 3D grid **800** is uniform, the sizes of all grids for all axes may be the same to create a uniform 3D grid and then the single value for the sizes of all grids for all axes may be signaled to the receiver. In some embodiments, the sizes of all grids for each axis may be the same, but the size of grids for one axis may be different from the size of grids for another axis to create a uniform 3D grid, and the size of grid of each axis may be separately signaled to the receiver. In some embodiments, the size of a grid for an axis may be different from the size of another grid for such axis to create a non-uniform 3D grid and the size of each grid of each axis may be individually signaled to the receiver. In some embodiments, information indicating whether the structure of the 3D grid **800** is uniform may be signaled to the receiver. When the structure of the 3D grid **800** is uniform, information indicating whether the size of grids for one axis may be different from the size of grids for another axis may be signaled to the receiver. In some embodiments, when the structure of the 3D grid **800** is uniform, spacing between adjacent grid planes vertical to an axis may be referred to as the size of grids for the axis. In some embodiments, when the structure of the 3D grid **800** is non-uniform, spacing between i-th grid plane and (i+1)-th grid plane vertical to an axis may be referred to as the size of the i-th grid for the axis.

(106) In some embodiments, the location and size of each submesh may be calculated by the receiver according to the origin position of the 3D grid **800** and size information of a grid associated with the submesh.

(107) When each submesh is delivered to the receiver, the location of each submesh may be signaled. For efficient and easy indication of such information, an identifier (ID or id) of submesh can be formulated to indicate its location. In some embodiments, if the total number of grids for x, y, and z axes are l, m, and n respectively, then the id of submeshes located in a.sup.th, b.sup.th and

c.sup.th grid location on x, y and z axes respectively can be formulated as $c+(b-1)*n+(a-1)*m*n$.

(108) In some embodiments, when a triangle has at least one vertex inside a cuboid defined by the 3D grid **800**, all vertices and sides of the triangle may be included in the submesh associated with the cuboid, even though some vertices of the triangle may lie outside the cuboid.

(109) In some embodiment, the shape of grids of all the axes may not be the same and the shape of a grid for one or more axes can be circular or triangular. In this scenario, the basic shape may be something different than a cuboid.

(110) In some embodiments, the subdivision information may be signaled with the syntax as shown in Table 1 by the sender and the receiver may process the syntax elements and recover the subdivision information about the 3D grid **800** applied to subdivision of a mesh into the submeshes.

(111) TABLE-US-00001 TABLE 1 submesh_division_by_grid_flag if(submesh_division_by_grid_flag == true){ submesh_division_grid_type submesh_division_grid_origin_offset_u submesh_division_grid_origin_offset_v submesh_division_grid_origin_offset_d if(submesh_division_grid_type == uniform){ submesh_division_with_same_grid_size if(submesh_division_with_same_grid_size == true) submesh_division_grid_size_single else(submesh_division_with_same_grid_size == false){ submesh_division_grid_size_u submesh_division_grid_size_v submesh_division_grid_size_d } } else if (submesh_division_grid_type == non_uniform){ submesh_division_grid_count_u for(l = 0; l < submesh_division_grid_count_u; l++) submesh_division_grid_size_u[l] submesh_division_grid_count_v for(m = 0; m < submesh_division_grid_count_v; m++) submesh_division_grid_size_v[m] submesh_division_grid_count_d for(n = 0; n < submesh_division_grid_count_d; n++) submesh_division_grid_size_d[n] } } }

(112) The syntax element submesh_division_by_grid_flag may indicate whether the structured 3D grid has been applied to subdivide a mesh into the submeshes. The syntax element submesh_division_by_grid_flag equal to 1 may indicate that the 3D grid has been applied to subdivide a mesh into the submeshes. The syntax element submesh_division_by_grid_flag equal to 0 may indicate that the 3D grid has not been applied to subdivide a mesh into the submeshes.

(113) The syntax element submesh_division_grid_type may indicate whether a structure of the 3D grid is uniform or non-uniform.

(114) The syntax element submesh_division_grid_origin_u may indicate the u coordinate value of the origin position of the 3D grid against to the origin position of the mesh. The syntax element submesh_division_grid_origin_v may indicate the v coordinate value of the origin position of the 3D grid against to the origin position of the mesh. The syntax element submesh_division_grid_origin_d may indicate the d coordinate value of the origin position of the 3D grid against to the origin position of the mesh.

(115) The syntax element submesh_division_with_same_grid_size may indicate that the size of all grids of all axes are same or not.

(116) The syntax element submesh_division_grid_size_single may indicate that the single value of grids to be applied to all axes when the sizes of all grids of all axes are the same.

(117) The syntax element submesh_division_grid_size_u[l] may indicate the size of the l-th grid on the u axis. The syntax element submesh_division_grid_size_v[m] may indicate the size of the m-th grid on the v axis. The syntax element submesh_division_grid_size_d[n] may indicate the size of the n-th grid on the d axis.

(118) The syntax element submesh_division_grid_count_u may indicate the total number of grids for the u axis. The syntax element submesh_division_grid_count_v may indicate the number total of grids for the v axis. The syntax element submesh_division_grid_count_d may indicate the total number of grids for the d axis. In some embodiments, the total number of defined grid planes

vertical to an axis minus 1 may be referred to as the total number of grids for the axis.

(119) FIG. 9 illustrates a flowchart for an encoder in accordance with an embodiment.

(120) At **901**, the encoder may divide a base mesh into a plurality of submeshes.

(121) At **903**, the encoder may independently encode the plurality of submeshes to allow the decoder's partial access of the mesh by identifying, delivering, decoding and reconstructing only some of the submeshes present in a V-DMC bitstream. In some embodiments, each of the submeshes may be independently decodable from other submeshes.

(122) At **905**, the encoder may identify scene objects within a plurality of 3D geometric shapes to generate 3D geometric shape information specifying association between a plurality of 3D geometric shapes and a plurality of scene objects. In some embodiments, the 3D geometric shape may be a visibility cone or a 3D bounding box.

(123) At **907**, the encoder may encode the 3D geometric shape information specifying association between a plurality of 3D geometric shape and a plurality of scene objects.

(124) At **909**, the encoder may encode association information between the plurality of scene objects and the plurality of submeshes.

(125) At **911**, the encoder may combine the plurality of encoded submeshes, the encoded 3D geometric shape information, and encoded association information into a compressed bitstream. In some embodiments, at least one of the encoded 3D geometric shape information or the encoded association information may be provided in a supplemental enhancement information (SEI) message or a volumetric usability information (VUI) message.

(126) FIG. 10 illustrates a flowchart for a decoder in accordance with an embodiment.

(127) At **1001**, the decoder may receive a compressed bitstream including a plurality of encoded submeshes, encoded 3D geometric shape information, and encoded association information.

(128) At **1003**, the decoder may determine a 3D region of a volumetric scene to be rendered. In some embodiments, the 3D region of the volumetric scene to be rendered may be determined according to a context of rendering such as view point of the user and a field of view of a rendering device including the decoder.

(129) At **1005**, the decoder may parse the bitstream and decode 3D geometric shape information.

(130) At **1007**, the decoder may determine one or more indices of one or more scene objects associated with one or more 3D geometric shapes which overlap with the determined 3D region of the volumetric scene based on the 3D geometric shape information.

(131) At **1009**, the decoder may parse the bitstream and decode association information between scene objects and submeshes. In some embodiments, by defining scene objects and associating them with submeshes, bounding boxes of submeshes in the 3D coordinate system can be known indirectly and such information can be utilized for partial access of mesh.

(132) At **1011**, the decoder may identify identifiers of one or more submeshes belonging to the determined scene objects based on the association information and the determined one or more indices of one or more scene objects.

(133) At **1013**, the decoder may extract, from the bitstream, one or more encoded submeshes belonging to the determined scene objects based on the identifiers.

(134) At **1015**, the decoder may decode the one or more encoded submeshes to reconstruct the one or more submeshes belonging to the 3D region of the volumetric scene.

(135) Hereinafter, the 3D geometric shape information in accordance with various embodiments will be described.

(136) In some embodiments, the 3D geometric shape information may comprise the 3D bounding box information, visibility cones information, or both. One or more 3D geometric shapes specified by the 3D geometric shape information may comprise at least one of one or more 3D bounding boxes or one or more visibility cones. In some embodiments, a volume defined as a cuboid solid having six rectangular faces placed at right angles may be referred to as the 3D bounding box.

(137) In some embodiments, the 3D geometric shape information may comprise information for a

plurality of 3D geometric shapes. Each of the plurality of 3D geometric shapes may be associated with a respective one of a plurality of scene objects. In some embodiments, a respective one of scene objects may have one or more complete submeshes. In some embodiments, a respective one of scene objects may contain subset of one or more submeshes. Information for a respective one 3D geometric shape of the plurality of 3D geometric shapes may comprise index information indicating an index of a scene object associated with the respective one 3D geometric shape. Information for a respective one 3D geometric shape of the plurality of 3D geometric shapes may further comprise information indicating a 3D region of the respective one 3D geometric shape. Information indicating the region of the respective one 3D geometric shape may comprise an origin and a size of the respective one 3D geometric shape. Thus, in some embodiments, the 3D geometric shape information may comprise region information of the plurality of 3D geometric shapes and association information between the plurality of 3D geometric shapes and the plurality of scene objects.

(138) In some embodiments, the 3D geometric shape information may be provided in a supplemental enhancement information (SEI) message or a volumetric usability information (VUI) message. The scene object information SEI message comprising the 3D bounding box information and the visibility cones information is shown in Table 2.

(139) TABLE-US-00002 TABLE 2 Descriptor scene_object_information(payloadSize) {
 soi_num_object_updates ue(v) ... soi_visibility_cones_present_flag u(1)
 soi_3d_bounding_box_present_flag u(1) ... for(i = 0; i < soi_num_object_updates; i++) {
 soi_object_idx[i] u(v) if(soi_visibility_cones_present_flag) {
 soi_visibility_cones_update_flag[k] u(1) if(soi_visibility_cones_update_flag[k]) {
 soi_direction_x[k] i(16) soi_direction_y[k] i(16) soi_direction_z[k] i(16)
 soi_angle[k] u(16) } } if(soi_3d_bounding_box_present_flag)
 { soi_3d_bounding_box_update_flag[k] u(1) if(
 soi_3d_bounding_box_update_flag[k]) { soi_3d_bounding_box_x[k] ue(v)
 soi_3d_bounding_box_y[k] ue(v) soi_3d_bounding_box_z[k] ue(v)
 soi_3d_bounding_box_size_x[k] ue(v) soi_3d_bounding_box_size_y[k] ue(v)
 soi_3d_bounding_box_size_z[k] ue(v) } } } }

(140) The soi_num_object_updates may indicate the number of objects that are to be updated by the current SEI message.

(141) The syntax element soi_visibility_cones_present_flag may indicate that visibility cones information is present in the current scene object information SEI message. The syntax element soi_visibility_cones_present_flag equal to 1 may indicate that visibility cones information is present in the current scene object information SEI message. The syntax element soi_visibility_cones_present_flag equal to 0 may indicate that visibility cones information is not present.

(142) The syntax element soi_3d_bounding_box_present_flag may indicate whether the 3D bounding box information is present in the current scene object information SEI message. The syntax element soi_3d_bounding_box_present_flag equal to 1 may indicate that 3D bounding box information is present in the current scene object information SEI message. The syntax element soi_3d_bounding_box_present_flag equal to 0 may indicate that 3D bounding box information is not present.

(143) The syntax element soi_visibility_cones_update_flag[i] may indicate whether visibility cones update information is present for an object with object index i. The syntax element soi_visibility_cones_update_flag[i] equal to 1 may indicate that visibility cones update information is present for an object with object index i. The syntax element soi_visibility_cones_update_flag[i] equal to 0 indicates that visibility cones update information is not present.

(144) The syntax element soi_object_idx[i] may indicate the object index of the i-th object to be updated.

active scene objects defined for a mesh at the time of the SEI message is signaled. The syntax element `soi_object_idx` may indicate the index of the scene object to be associated with a plurality of submeshes. The syntax element `number_of_submesh_included` may indicate the number of a plurality of submeshes fully included in the current scene object with an index indicated by the syntax element `soi_object_idx`. The syntax element `submesh_id` may indicate the identifier of a submesh associated with the current scene object with an index indicated by the syntax element `soi_object_idx`. In this scenario, submeshes with identifiers indicated by syntax elements `submesh_id` associated with the syntax element `soi_object_idx` may be completely included in a scene object with an index indicated by the syntax element `soi_object_idx`.

(161) In some embodiments, the association information between scene objects and submeshes may be included in SEI messages and the syntax and semantics for such SEI messages is shown in Table 4.

(162) TABLE-US-00004 TABLE 4 persistence_association_flag number_of_active_scene_object
for(i=0 ; i<number_of_active_scene_object ; i++){ soi_object_idx
number_of_submesh_included for(j=0 ; j<number_of_submesh_included ; j++){
submesh_id completely_included } }

(163) In Table 4, the syntax element `persistence_association_flag` may indicate the relationship between the scene objects and submeshes is persistent. The syntax element `persistence_association_flag` equal to 0 may indicate that the relationship is only valid for the current frame. The syntax element `number_of_active_scene_object` may indicate the number of active scene objects defined for a mesh at the time of the SEI message is signaled. The syntax element `soi_object_idx` may indicate the index of the scene object to be associated with a plurality of submeshes. The syntax element `number_of_submesh_included` may indicate the number of a plurality of submeshes fully included in the current scene object with an index indicated by the syntax element `soi_object_idx`. The syntax element `submesh_id` may indicate the identifier of a submesh associated with the current scene object with an index indicated by the syntax element `soi_object_idx`. The syntax element `completely_included` may indicate whether the submesh in this loop is completely included in the current scene object with an index indicated by the syntax element `soi_object_idx`. In some embodiments, the syntax element `completely_included` flag may not be present.

(164) In some embodiments, the association information may be included in SEI messages and the syntax and semantics for such SEI messages is shown in Table 5.

(165) TABLE-US-00005 TABLE 5 Descriptor submesh_soi_relationship_indication (payloadSize) { persistence_association_flag u(1) number_of_active_scene_objects ue(v)
submesh_id_length_minus1 ue(v) for(i=0 ; i<number_of_active_scene_object ; i++) {
soi_object_idx u(v) number_of_submesh_included ue(v) for((j=0 ;
j<number_of_submesh_included ; j++) { submesh_id u(v) completely_included u(1)
} } }

(166) In Table 5, the syntax element `persistence_association_flag` may indicate the relationship between the scene objects and submeshes is persistent. The syntax element `persistence_association_flag` equal to 0 may indicate that the relationship is only valid for the current frame. The syntax element `number_of_active_scene_object` may indicate the number of active scene objects defined for a mesh at the time of the SEI message is signaled. The syntax element `submesh_id_length_minus1` plus 1 may specify the number of bits used to represent the syntax element `pdu_submesh_id` in a patch data unit. The syntax element `soi_object_idx` may indicate the index of the scene object to be associated with a plurality of submeshes. The syntax element `number_of_submesh_included` may indicate the number of a plurality of submeshes fully included in the current scene object with an index indicated by the syntax element `soi_object_idx`. The syntax element `submesh_id` may indicate the identifier of a submesh associated with the current scene object with an index indicated by the syntax element `soi_object_idx`. The syntax

element completely_included may indicate whether the submesh in this loop is completely included in the current scene object with an index indicated by the syntax element soi_object_idx. In some embodiments, the syntax element completely_included flag may not be present.

(167) Referring to embodiments in accordance with FIG. 9 and FIG. 10, instead of creating and signaling submeshes based on the 3D grid, such constraints may be imposed on the submeshes creation. The submeshes may be created based on semantic objects or based on locations in the 3D space. However, for each submesh, a 3D bounding box (or cuboid) that contains the submesh in the 3D coordinate space may be signalled. The origin position of the 3D bounding box may be signalled in terms of x, y, and z coordinates. Additionally, the size of the 3D bounding box in x, y, and z direction (size_x, size_y, and size_z, respectively) may be also signalled. In one embodiment, the origin position of the 3D bounding box and size_x, size_y, and size_z may be chosen so that the volume of the 3D bounding box is as minimum as possible while the 3D bounding box contains all the vertices corresponding to the submesh. At the decoder side, if a renderer is interested in rendering only a part of the 3D space, the decoder may check the 3D bounding box information for each submesh to figure out which submeshes need to be decoded.

(168) FIG. 11 illustrates a flowchart for an encoder in accordance with an embodiment.

(169) At **1101**, the encoder may divide a base mesh into a plurality of submeshes.

(170) At **1103**, the encoder may independently encode the plurality of submeshes to allow the decoder's partial access of the mesh by identifying, delivering, decoding and reconstructing only some of the submeshes present in a V-DMC bitstream. In some embodiments, each of the submeshes may be independently decodable from other submeshes.

(171) At **1105**, the encoder may encode volumetric rectangle information for a plurality of volumetric rectangles.

(172) At **1107**, the encoder may identify submeshes within the plurality of volumetric rectangles to generate association information between a plurality of volumetric rectangles and a plurality of submeshes.

(173) At **1109**, the encoder may encode the association information.

(174) At **1111**, the encoder may combine the plurality of encoded submeshes, the encoded volumetric rectangle information, and the encoded association information into a compressed bitstream. In some embodiments, at least one of the encoded volumetric rectangle information or the encoded association information may be provided in a supplemental enhancement information (SEI) message or a volumetric usability information (VUI) message.

(175) FIG. 12 illustrates a flowchart for a decoder in accordance with an embodiment.

(176) At **1201**, the decoder may receive a compressed bitstream including a plurality of encoded submeshes, encoded volumetric rectangle information, and encoded association information.

(177) At **1203**, the decoder may determine a 3D region of a volumetric scene to be rendered. In some embodiments, the 3D region of the volumetric scene to be rendered may be determined according to a context of rendering such as view point of the user and a field of view of a rendering device including the decoder.

(178) At **1205**, the decoder may parse the bitstream and decode volumetric rectangle information.

(179) At **1207**, the decoder may determine one or more volumetric rectangles which overlap with the determined 3D region of the volumetric scene based on the decoded volumetric rectangle information.

(180) At **1209**, the decoder may parse the bitstream and decode association information between a plurality of volumetric rectangles and a plurality of submeshes.

(181) At **1211**, the decoder may identify identifiers of one or more submeshes belonging to the determined one or more volumetric rectangles based on the association information.

(182) At **1213**, the decoder may extract, from the bitstream, one or more encoded submeshes based on the identifiers.

(183) At **1215**, the decoder may decode the one or more submeshes to reconstruct the one or more

submeshes belonging to the 3D region of the volumetric scene.

(184) Hereinafter, the association information between a plurality of volumetric rectangles and a plurality of submeshes in accordance with various embodiments will be described.

(185) In some embodiments, the association information between volumetric rectangles and submeshes may be included in SEI messages and the syntax and semantics for such SEI messages is shown in Table 6. In some embodiments, one or more submeshes may be completely included in a volumetric rectangle.

(186) TABLE-US-00006 TABLE 6 number_of_active_volumetric_rectangle for(i=0 ; i<number_of_active_volumetric_rectangle ; i++){ vri_rectangle_idx
number_of_submesh_included for(j=0 ; j<number_of_submesh_included ; j++){
submesh_id } }

(187) The syntax element number_of_active_volumetric_rectangle may indicate the number of active volumetric rectangles defined for a mesh at the time when SEI message is signaled. The syntax element vri_rectangle_idx may indicate the index of the volumetric rectangle to be associated with the submeshes. The syntax element number_of_submesh_included may indicate the number of submeshes fully included in the current volumetric rectangle. The syntax element submesh_id may indicate the identifier of a submesh.

(188) The various illustrative blocks, units, modules, components, methods, operations, instructions, items, and algorithms may be implemented or performed with a processing circuitry.

(189) A reference to an element in the singular is not intended to mean one and only one unless specifically so stated, but rather one or more. For example, “a” module may refer to one or more modules. An element preceded by “a,” “an,” “the,” or “said” does not, without further constraints, preclude the existence of additional same elements.

(190) Headings and subheadings, if any, are used for convenience only and do not limit the subject technology. The term “exemplary” is used to mean serving as an example or illustration. To the extent that the term “include,” “have,” “carry,” “contain,” or the like is used, such term is intended to be inclusive in a manner similar to the term “comprise” as “comprise” is interpreted when employed as a transitional word in a claim. Relational terms such as first and second and the like may be used to distinguish one entity or action from another without necessarily requiring or implying any actual such relationship or order between such entities or actions.

(191) Phrases such as an aspect, the aspect, another aspect, some aspects, one or more aspects, an implementation, the implementation, another implementation, some implementations, one or more implementations, an embodiment, the embodiment, another embodiment, some embodiments, one or more embodiments, a configuration, the configuration, another configuration, some configurations, one or more configurations, the subject technology, the disclosure, the present disclosure, other variations thereof and alike are for convenience and do not imply that a disclosure relating to such phrase(s) is essential to the subject technology or that such disclosure applies to all configurations of the subject technology. A disclosure relating to such phrase(s) may apply to all configurations, or one or more configurations. A disclosure relating to such phrase(s) may provide one or more examples. A phrase such as an aspect or some aspects may refer to one or more aspects and vice versa, and this applies similarly to other foregoing phrases.

(192) A phrase “at least one of” preceding a series of items, with the terms “and” or “or” to separate any of the items, modifies the list as a whole, rather than each member of the list. The phrase “at least one of” does not require selection of at least one item; rather, the phrase allows a meaning that includes at least one of any one of the items, and/or at least one of any combination of the items, and/or at least one of each of the items. By way of example, each of the phrases “at least one of A, B, and C” or “at least one of A, B, or C” refers to only A, only B, or only C; any combination of A, B, and C; and/or at least one of each of A, B, and C.

(193) It is understood that the specific order or hierarchy of steps, operations, or processes disclosed is an illustration of exemplary approaches. Unless explicitly stated otherwise, it is

understood that the specific order or hierarchy of steps, operations, or processes may be performed in different order. Some of the steps, operations, or processes may be performed simultaneously or may be performed as a part of one or more other steps, operations, or processes. The accompanying method claims, if any, present elements of the various steps, operations or processes in a sample order, and are not meant to be limited to the specific order or hierarchy presented. These may be performed in serial, linearly, in parallel or in different order. It should be understood that the described instructions, operations, and systems can generally be integrated together in a single software/hardware product or packaged into multiple software/hardware products.

(194) The disclosure is provided to enable any person skilled in the art to practice the various aspects described herein. In some instances, well-known structures and components are shown in block diagram form in order to avoid obscuring the concepts of the subject technology. The disclosure provides various examples of the subject technology, and the subject technology is not limited to these examples. Various modifications to these aspects will be readily apparent to those skilled in the art, and the principles described herein may be applied to other aspects.

(195) All structural and functional equivalents to the elements of the various aspects described throughout this disclosure that are known or later come to be known to those of ordinary skill in the art are expressly incorporated herein by reference and are intended to be encompassed by the claims. Moreover, nothing disclosed herein is intended to be dedicated to the public regardless of whether such disclosure is explicitly recited in the claims. No claim element is to be construed under the provisions of 35 U.S.C. § 112, sixth paragraph, unless the element is expressly recited using a phrase means for or, in the case of a method claim, the element is recited using the phrase step for.

(196) The title, background, brief description of the drawings, abstract, and drawings are hereby incorporated into the disclosure and are provided as illustrative examples of the disclosure, not as restrictive descriptions. It is submitted with the understanding that they will not be used to limit the scope or meaning of the claims. In addition, in the detailed description, it can be seen that the description provides illustrative examples and the various features are grouped together in various implementations for the purpose of streamlining the disclosure. This method of disclosure is not to be interpreted as reflecting an intention that the claimed subject matter requires more features than are expressly recited in each claim. Rather, as the following claims reflect, inventive subject matter lies in less than all features of a single disclosed configuration or operation. The following claims are hereby incorporated into the detailed description, with each claim standing on its own as a separately claimed subject matter.

(197) The embodiments are provided solely as examples for understanding the invention. They are not intended and are not to be construed as limiting the scope of this invention in any manner. Although certain embodiments and examples have been provided, it will be apparent to those skilled in the art based on the disclosures herein that changes in the embodiments and examples shown may be made without departing from the scope of this invention.

(198) The claims are not intended to be limited to the aspects described herein, but are to be accorded the full scope consistent with the language claims and to encompass all legal equivalents. Notwithstanding, none of the claims are intended to embrace subject matter that fails to satisfy the requirements of the applicable patent law, nor should they be interpreted in such a way.

Claims

1. An apparatus for reconstructing a three-dimensional (3D) sub-mesh of a 3D mesh comprising a processor configured to: receive a compressed bitstream including a supplemental enhancement information (SEI) message including association information between scene objects and submeshes, wherein the association information includes a plurality of indices of the scene objects and a plurality of identifiers of the plurality of submeshes each being associated with a respective

- one index of the plurality of indices of the scene objects and each of the submeshes is independently decodable from other submeshes; determine an index of the scene object; decode the SEI message to obtain the association information between scene objects and submeshes; determine an identifier of a submesh based on the index of the scene object and the association information; and reconstruct the submesh based on the identifier.
2. The apparatus of claim 1, wherein the association information further includes first number information indicating a number of scene objects specified in the association information.
 3. The apparatus of claim 2, wherein the association information further includes second number information indicating a number of the plurality of identifiers of the plurality of submeshes.
 4. The apparatus of claim 3, wherein the association information further includes information indicating whether a respective one submesh of the plurality of the submesh is completely included in a scene object associated with the respective one submesh.
 5. The apparatus of claim 1, wherein the compressed bitstream further includes 3D bounding box information specifying association between 3D bounding boxes and submeshes, and the index of the scene object is determined based on the 3D bounding box information.
 6. The apparatus of claim 1, wherein the compressed bitstream further includes visibility cones information specifying association between visibility cones and submeshes, and the index of the scene object is determined based on the visibility cones information.
 7. The apparatus of claim 1, wherein the association information further includes persistence information indicating whether a relationship between the scene objects and submeshes specified by the association information is persistent.
 8. A method for reconstructing a three-dimensional (3D) sub-mesh of a 3D mesh comprising: receiving a compressed bitstream including a supplemental enhancement information (SEI) message including association information between scene objects and submeshes, wherein the association information includes a plurality of indices of the scene objects and a plurality of identifiers of the plurality of submeshes each being associated with a respective one index of the plurality of indices of the scene objects; determining an index of the scene object; decoding the SEI message to obtain the association information between scene objects and submeshes; determining an identifier of a submesh based on the index of the scene object and the association information; and reconstructing the submesh based on the identifier.
 9. The method of claim 8, wherein the association information further includes first number information indicating a number of scene objects specified in the association information.
 10. The method of claim 9, wherein the association information further includes second number information indicating a number of the plurality of identifiers of the plurality of submeshes.
 11. The method of claim 10, wherein the association information further includes information indicating whether a respective one submesh of the plurality of the submesh is completely included in a scene object associated with the respective one submesh.
 12. The method of claim 8, wherein the compressed bitstream further includes 3D bounding box information specifying association between 3D bounding boxes and submeshes, and the index of the scene object is determined based on the 3D bounding box information.
 13. The method of claim 8, wherein the compressed bitstream further includes visibility cones information specifying association between visibility cones and submeshes, and the index of the scene object is determined based on the visibility cones information.
 14. The method of claim 8, wherein the association information further includes persistence information indicating whether a relationship between the scene objects and submeshes specified by the association information is persistent.
 15. An apparatus for encoding a three-dimensional (3D) sub-mesh of a 3D mesh comprising: a communication interface; and a processor operably coupled to the communication interface, the processor configured to: divide a base mesh into a plurality of submeshes, encode a submesh of the plurality of submeshes independently from other submeshes, encode a supplemental enhancement

information (SEI) message including association information between scene objects and submeshes, wherein the association information includes a plurality of indices of the scene objects and a plurality of identifiers of the plurality of submeshes each being associated with a respective one index of the plurality of indices of the scene objects, and combine the encoded submesh and the encoded SEI message into a compressed bitstream.

16. The apparatus of claim 15, wherein the compressed bitstream further includes 3D bounding box information specifying association between 3D bounding boxes and submeshes.

17. The apparatus of claim 15, wherein the compressed bitstream further includes visibility cones information specifying association between visibility cones and submeshes.
