

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250273903

Kind Code

A1

Publication Date

August 28, 2025

Inventor(s)

CHEN; TSUNG-CHI et al.

Female Connector

Abstract

A female connector, wherein the female connector is provided to allow insertion of a male connector in the inserting direction. The insulation core of the female connector comprises an inserting guiding structure, which provides interference when the male connector is inserted in an incorrect inserting direction to prevent incorrect insertion of the male connector into the female connector, thereby enabling the male connector to be inserted into the female connector for power or signal transmission.

Inventors: CHEN; TSUNG-CHI (New Taipei City, TW), HUANG; MU-JUNG (New Taipei City, TW)

Applicant: Dongguan Tarng Yu Electronics Co., Ltd. (Dongguan City, CN); Tarng Yu Enterprise Co., Ltd. (New Taipei City, TW)

Family ID: 1000008467028

Appl. No.: 19/062321

Filed: February 25, 2025

Foreign Application Priority Data

TW

113201959

Feb. 26, 2024

Publication Classification

Int. Cl.: H01R13/629 (20060101); H01R13/40 (20060101)

U.S. Cl.:

CPC H01R13/629 (20130101); H01R13/40 (20130101);

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application claims the priority of Republic of China Patent Application No. 113201959 filed on Feb. 26, 2024, in the State Intellectual Property Office of the R.O.C., the disclosure of which is incorporated herein by reference.

BACKGROUND OF THE INVENTION

Field of the Invention

[0002] This application relates to signal transmission technology, and more specifically, to a female connector that can prevent incorrect inserting direction of a male connector.

Descriptions of the Related Art

[0003] In electrical equipment, it is often necessary to transmit electrical signals through a connector assembly composed of a female connector and a male connector. During the implementation of the connector assembly, the male connector can be inserted into the female connector to provide electrical signal transmission for the electrical equipment.

[0004] However, the inserting of the male connector into the female connector is usually directional. If the inserting direction of the male connector is incorrect, the electrical signal transmission of the connector assembly may suffer from voltage mismatches and other issues, thereby causing the electrical equipment to malfunction.

[0005] Therefore, how to provide a female connector that prevents incorrect inserting direction of the male connector is indeed an urgent problem to be solved by those skilled in the relevant technical field.

SUMMARY OF THE INVENTION

[0006] In view of the drawbacks of the prior art mentioned above, the present application provides a female connector, wherein the female connector is provided to allow insertion of a male connector in an inserting direction, the female connector comprising: a female conductive terminal set, wherein the female conductive terminal set comprises a first female terminal, a second female terminal, a third female terminal, and a fourth female terminal; and a female insulation core, wherein the female insulation core comprises a first female core lateral outer wall, a second female core lateral outer wall, a first female core longitudinal outer wall, a second female core longitudinal outer wall, a first female core lateral inner wall, a second female core lateral inner wall, and a first female core longitudinal inner wall; wherein, the first female core lateral outer wall and the second female core lateral outer wall extend laterally, respectively, and the first female core longitudinal outer wall and the second female core longitudinal outer wall extend longitudinally, respectively; the first female core longitudinal outer wall is connected to the first female core lateral outer wall, and the second female core longitudinal outer wall is connected to the second female core lateral outer wall to form a female core major internal inserting space; the first female core lateral inner wall and the second female core lateral inner wall extend laterally, respectively, wherein the first female core lateral inner wall is connected to the first female core longitudinal outer wall to form a first female major inserting guiding structure, and the first female core longitudinal inner wall is connected to the first female core lateral outer wall, the second female core lateral outer wall, and the second female core lateral inner wall to form a second female major inserting guiding structure, wherein, the first female major inserting guiding structure and the second female major inserting guiding structure partition the female core major internal inserting space into a first female major internal inserting subspace, a second female major internal inserting subspace, a third female major internal inserting subspace, and a fourth female major internal inserting subspace; the female insulation core is respectively mated with the first female terminal, the second female terminal, the third female terminal, and the fourth female terminal, allowing the first female terminal, the second

female terminal, the third female terminal, and the fourth female terminal to respectively extend into the first female major internal inserting subspace, the second female major internal inserting subspace, the third female major internal inserting subspace, and the fourth female major internal inserting subspace; and the first female major internal inserting subspace is in continuity with the second female major internal inserting subspace, and the third female major internal inserting subspace is in continuity with the fourth female major internal inserting subspace to guide the inserting of the male connector in the inserting direction, enabling the male connector to respectively enter the first female major internal inserting subspace, the second female major internal inserting subspace, the third female major internal inserting subspace, and the fourth female major internal inserting subspace and be inserted into the first female terminal, the second female terminal, the third female terminal, and the fourth female terminal, respectively.

[0007] Preferably, the female connector said above, wherein the first female major inserting guiding structure comprises a T-shaped cross-section; and the second female major inserting guiding structure comprises a T-shaped cross-section.

[0008] Preferably, the female connector said above, wherein the first female core lateral inner wall and the first female core longitudinal outer wall are substantially perpendicularly intersected, and the second female core lateral inner wall and the first female core longitudinal inner wall are substantially perpendicularly intersected.

[0009] Preferably, the female connector said above, wherein the female insulation core comprises a lateral extension plane, the first female core lateral inner wall and the second female core lateral inner wall extend along the lateral extension plane, and the lateral extension plane is substantially perpendicularly intersected with the first female core longitudinal outer wall and the first female core longitudinal inner wall.

[0010] Preferably, the female connector said above, wherein the female conductive terminal set further comprises a fifth female terminal and a sixth female terminal, and the female insulation core further comprises a third female core longitudinal outer wall and a third female core lateral inner wall, wherein the third female core longitudinal outer wall extends longitudinally and is respectively connected to the first female core lateral outer wall and the second female core lateral outer wall, thereby forming a female core minor internal inserting space; the third female core lateral inner wall is connected to the second female core longitudinal outer wall or the third female core longitudinal outer wall to form a first female minor inserting guiding structure; wherein, the first female minor inserting guiding structure partitions the female core minor internal inserting space into a first female minor internal inserting subspace and a second female minor internal inserting subspace; the female insulation core is further mated with the fifth female terminal and the sixth female terminal, allowing the fifth female terminal and the sixth female terminal to respectively extend into the first female minor internal inserting subspace and the second female minor internal inserting subspace; and the first female minor internal inserting subspace is in continuity with the second female minor internal inserting subspace to guide the insertion of the male connector in the inserting direction, enabling the male connector to respectively enter the first female minor internal inserting subspace and the second female minor internal inserting subspace and be inserted into the fifth female terminal and the sixth female terminal, respectively.

[0011] Preferably, the female connector said above, wherein the first female minor inserting guiding structure comprises a T-shaped cross-section.

[0012] Preferably, the female connector said above, wherein the third female core lateral inner wall and the second female core longitudinal outer wall or the third female core longitudinal outer wall are substantially perpendicularly intersected.

[0013] Preferably, the female connector said above, wherein the female insulation core comprises a lateral extension plane, the first female core lateral inner wall, the second female core lateral inner wall, and the third female core lateral inner wall extend along the lateral extension plane, and the lateral extension plane is substantially perpendicularly intersected with the first female core

longitudinal outer wall, the first female core longitudinal inner wall, the second female core longitudinal outer wall, and the third female core longitudinal outer wall.

[0014] Preferably, the female connector said above, wherein the female conductive terminal set further comprises a fifth female terminal and a sixth female terminal, and the female insulation core further comprises a third female core longitudinal outer wall, wherein the third female core longitudinal outer wall extends longitudinally and is respectively connected to the first female core lateral outer wall and the second female core lateral outer wall, thereby forming a female core minor internal inserting space; wherein, the female insulation core is further mated with the fifth female terminal and the sixth female terminal, allowing the fifth female terminal and the sixth female terminal to respectively extend into the female core minor internal inserting space; and the female core minor internal inserting space guides the insertion of the male connector in the inserting direction, enabling the male connector to enter the female core minor internal inserting space and be inserted into the fifth female terminal and the sixth female terminal.

[0015] Compared to the prior art, the present application provides a female connector, which allows a male connector to be inserted in the inserting direction. The core of the female connector an inserting guiding structure, which provides interference when the male connector is inserted in the wrong inserting direction, thereby preventing the male connector from being inserted into the female connector in the wrong direction. This ensures that the male connector can be inserted into the female connector to facilitate power or signal transmission.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0016] The above and other aspects, features and other advantages of the present invention will be more clearly understood from the following detailed description taken in conjunction with the accompanying drawings, in which:

[0017] FIG. 1 is a three-dimensional schematic view of the female connector of the present application in an embodiment.

[0018] FIG. 2 is a front schematic view of the female connector of the present application in an embodiment.

[0019] FIG. 3 is a front schematic view of the female connector of the present application in an embodiment.

[0020] FIG. 4 is a front schematic view of the female connector of the present application in an embodiment.

[0021] FIG. 5 is a front schematic view of the female connector of the present application in an embodiment.

[0022] FIG. 6 is a sectional schematic view of a partial component of the female connector shown in FIG. 4, taken along line AA.

[0023] FIG. 7 is a sectional schematic view of a partial component of the female connector shown in FIG. 4, taken along line BB.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

[0024] Embodiments of the present invention will now be described in detail with reference to the accompanying drawings. The invention may, however, be embodied in many different forms and should not be construed as being limited to the embodiments set forth herein. Rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the invention to those skilled in the art.

[0025] For a detailed description of the embodiments disclosed in the present application, please refer to FIGS. 1 to 7.

[0026] The present application provides at least one connector assembly 1 that can be installed in

electrical equipment, wherein the connector assembly **1** comprises a male connector **11** and a female connector **12**. The male connector **11** can be inserted into the female connector **12** in an inserting direction D to provide power or signal transmission for the electrical equipment.

[0027] In the embodiments shown in FIGS. **1**, **2**, and **5**, the female connector **12** comprises a female conductive terminal set **121** and a female insulation core **122**. The female conductive terminal set **121** comprises a first female terminal **1211**, a second female terminal **1212**, a third female terminal **1213**, a fourth female terminal **1214**, a fifth female terminal **1215**, and a sixth female terminal **1216**, which provide power or signal transmission. The female insulation core **122** comprises a first female core lateral outer wall **1221**, a second female core lateral outer wall **1222**, a first female core longitudinal outer wall **1223**, a second female core longitudinal outer wall **1224**, a first female core lateral inner wall **1225**, a second female core lateral inner wall **1226**, a first female core longitudinal inner wall **1227**, a third female core longitudinal outer wall **1228**, and a third female core lateral inner wall **1229**.

[0028] In the above embodiment, the first female core lateral outer wall **1221** and the second female core lateral outer wall **1222** respectively extend laterally, while the first female core longitudinal outer wall **1223**, the second female core longitudinal outer wall **1224**, and the third female core longitudinal outer wall **1228** respectively extend longitudinally. The first female core lateral inner wall **1225**, the second female core lateral inner wall **1226**, and the third female core lateral inner wall **1229** respectively extend laterally.

[0029] Additionally, the first female core longitudinal outer wall **1223** is connected to the first female core lateral outer wall **1221**, and the second female core longitudinal outer wall **1224** is connected to the second female core lateral outer wall **1222**, enabling the first female core longitudinal outer wall **1223**, the second female core longitudinal outer wall **1224**, the first female core lateral outer wall **1221**, and the second female core lateral outer wall **1222** to form a female core major internal inserting space S1. The third female core longitudinal outer wall **1228** is respectively connected to the first female core lateral outer wall **1221** and the second female core lateral outer wall **1222**, enabling the second female core longitudinal outer wall **1224**, the third female core longitudinal outer wall **1228**, the first female core lateral outer wall **1221**, and the second female core lateral outer wall **1222** to form a female core minor internal inserting space S2.

[0030] It should be noted that the male connector **11** can be inserted into the female connector **12** in the female core major internal inserting space S1 and the female core minor internal inserting space S2.

[0031] Additionally, the first female core lateral inner wall **1225** is connected to the first female core longitudinal outer wall **1223**, enabling the first female core lateral inner wall **1225** and the first female core longitudinal outer wall **1223** to form a first female major inserting guiding structure G2111. The first female core longitudinal inner wall **1227** is respectively connected to the first female core lateral outer wall **1221**, the second female core lateral outer wall **1222**, and the second female core lateral inner wall **1226**, enabling the first female core longitudinal inner wall **1227** and the second female core lateral inner wall **1226** to form a second female major inserting guiding structure G2112. As shown in FIG. **3**, the third female core lateral inner wall **1229** is connected to the second female core longitudinal outer wall **1224**, enabling the third female core lateral inner wall **1229** and the second female core longitudinal outer wall **1224** to form a first female minor inserting guiding structure G2211. As shown in FIG. **4**, the third female core lateral inner wall **1229** is connected to the third female core longitudinal outer wall **1228**, enabling the third female core lateral inner wall **1229** and the third female core longitudinal outer wall **1228** to form a first female minor inserting guiding structure G2211.

[0032] In the above embodiment, the first female major inserting guiding structure G2111 and the second female major inserting guiding structure G2112 partition the female core major internal inserting space S1 into a first female major internal inserting subspace S11, a second female major internal inserting subspace S12, a third female major internal inserting subspace S13, and a fourth

female major internal inserting subspace **S14**. The first female major internal inserting subspace **S11** is in continuity with the second female major internal inserting subspace **S12**, providing guidance for the insertion of the male connector **11** in the inserting direction D. The third female major internal inserting subspace **S13** is in continuity with the fourth female major internal inserting subspace **S14**, also providing guidance for the insertion of the male connector **11** in the inserting direction D. This allows the male connector **11** to be inserted into the female connector **12**, enabling the male connector **11** respectively to enter the first female major internal inserting subspace **S11**, the second female major internal inserting subspace **S12**, the third female major internal inserting subspace **S13**, and the fourth female major internal inserting subspace **S14**, respectively being inserted with the first female terminal **1211**, the second female terminal **1212**, the third female terminal **1213**, and the fourth female terminal **1214** to provide power or signal transmission for the electrical equipment.

[0033] Additionally, the first female minor inserting guiding structure **G2211** partitions the female core minor internal inserting space **S2** into a first female minor internal inserting subspace **S21** and a second female minor internal inserting subspace **S22**. The first female minor internal inserting subspace **S21** is in continuity with the second female minor internal inserting subspace **S22**, providing guidance for the insertion of the male connector **11** in the inserting direction D. This allows the male connector **11** to be inserted into the female connector **12** and enter the first female minor internal inserting subspace **S21** and the second female minor internal inserting subspace **S22**, respectively being inserted with the fifth female terminal **1215** and the sixth female terminal **1216** to provide power or signal transmission for the electrical equipment.

[0034] The female insulation core **122** mates with and positions the first female terminal **1211**, the second female terminal **1212**, the third female terminal **1213**, the fourth female terminal **1214**, the fifth female terminal **1215**, and the sixth female terminal **1216**, ensuring that the first female terminal **1211**, the second female terminal **1212**, the third female terminal **1213**, the fourth female terminal **1214**, the fifth female terminal **1215** remain separated and extend into the first female major internal inserting subspace **S11**, the second female major internal inserting subspace **S12**, the third female major internal inserting subspace **S13**, the fourth female major internal inserting subspace **S14**, the first female minor internal inserting subspace **S21**, and the second female minor internal inserting subspace **S22**, respectively.

[0035] It should be noted that when the male connector **11** is inserted into the female connector **12** in the inserting direction D, the first female major inserting guiding structure **G2111**, the second female major inserting guiding structure **G2112**, and the first female minor inserting guiding structure **G2211** provide guidance for the insertion of the male connector **11** in the inserting direction D. This ensures that the male connector **11** respectively enters the first female major internal inserting subspace **S11**, the second female major internal inserting subspace **S12**, the third female major internal inserting subspace **S13**, the fourth female major internal inserting subspace **S14**, the first female minor internal inserting subspace **S21**, and the second female minor internal inserting subspace **S22**, respectively being inserted with the first female terminal **1211**, the second female terminal **1212**, the third female terminal **1213**, the fourth female terminal **1214**, the fifth female terminal **1215**, and the sixth female terminal **1216** to provide power or signal transmission for the electrical equipment.

[0036] In the embodiment shown in FIGS. 3 to 4, the first female major inserting guiding structure **G2111** comprises a T-shaped cross-section that can form a foolproof structure; the second female major inserting guiding structure **G2112** comprises a T-shaped cross-section that can form a foolproof structure and constitutes a foolproof structure; and the first female minor inserting guiding structure **G2211** comprises a T-shaped cross-section that can form a foolproof structure. In this way, through the foolproof structures mentioned above, interference is provided when the inserting direction D of the male connector **11** is incorrect, thereby preventing the male connector **11** from being inserted into the female connector **12** in the wrong direction.

[0037] Additionally, in the embodiment shown in FIGS. 3 to 4, the first female core lateral inner wall **1225** and the first female core longitudinal outer wall **1223** are substantially perpendicularly intersecting to form a foolproof structure; the second female core lateral inner wall **1226** and the first female core longitudinal inner wall **1227** are substantially perpendicularly intersecting to form a foolproof structure; and the third female core lateral inner wall **1229** and either the second female core longitudinal outer wall **1224** or the third female core longitudinal outer wall **1228** are substantially perpendicularly intersecting to form a foolproof structure. In this way, through the foolproof structures mentioned above, interference is provided when the inserting direction D of the male connector **11** is incorrect, thereby preventing the male connector **11** from being inserted into the female connector **12** in the wrong direction.

[0038] Furthermore, the female insulation core **122** comprises a lateral extension plane A, and the first female core lateral inner wall **1225**, the second female core lateral inner wall **1226**, and the second female core lateral inner wall **1226** extend respectively along the lateral extension plane A to form a foolproof structure. Additionally, the first female core longitudinal outer wall **1223**, the first female core longitudinal inner wall **1227**, the second female core longitudinal outer wall **1224**, and the third female core longitudinal outer wall **1228** are respectively and substantially perpendicularly intersecting with the lateral extension plane A to form a foolproof structure. In this way, through the foolproof structures mentioned above, interference is provided when the inserting direction D of the male connector **11** is incorrect, thereby preventing the male connector **11** from being inserted into the female connector **12** in the wrong direction.

[0039] In the embodiment shown in FIG. 5, the third female core lateral inner wall **1229** can be omitted, thereby allowing the second female core longitudinal outer wall **1224**, the third female core longitudinal outer wall **1228**, the first female core lateral outer wall **1221**, and the second female core lateral outer wall **1222** to form a female core minor internal inserting space S2. It should be noted that the female core minor internal inserting space S2 can provide guidance for the insertion of the male connector **11** in the inserting direction D, allowing the male connector **11** to enter the female core minor internal inserting space S2 and insert into the fifth female terminal **1215** and the sixth female terminal **1216**.

[0040] It should be noted that the above embodiments of the connector assembly and its female connector in this application can also omit some components. For example, the female connector may optionally comprise only the female conductive terminal set and the female insulation core. The female conductive terminal set comprises a first female terminal, a second female terminal, a third female terminal, and a fourth female terminal. The female insulation core comprises a first female core lateral outer wall, a second female core lateral outer wall, a first female core longitudinal outer wall, a second female core longitudinal outer wall, a first female core lateral inner wall, a second female core lateral inner wall, and a first female core longitudinal inner wall. The first female core lateral outer wall and the second female core lateral outer wall respectively extend laterally, while the first female core longitudinal outer wall and the second female core longitudinal outer wall respectively extend longitudinally. The first female core longitudinal outer wall and the second female core longitudinal outer wall are respectively connected with the first female core lateral outer wall and the second female core lateral outer wall to form a female core major internal inserting space. The first female core lateral inner wall and the second female core lateral inner wall extend laterally. The first female core lateral inner wall is in continuity with the first female core longitudinal outer wall to form the first female major inserting guiding structure, and the first female core longitudinal inner wall is in continuity with the first female core lateral outer wall, the second female core lateral outer wall, and the second female core lateral inner wall to form the second female major inserting guiding structure. The first female major inserting guiding structure and the second female major inserting guiding structure partition the female core major internal inserting space into a first female major internal inserting subspace, a second female major internal inserting subspace, a third female major internal inserting subspace, and a fourth

female major internal inserting subspace. The female insulation core is respectively mated with the first female terminal, the second female terminal, the third female terminal, and the fourth female terminal, such that the first female terminal, the second female terminal, the third female terminal, and the fourth female terminal respectively extend into the first female major internal inserting subspace, the second female major internal inserting subspace, the third female major internal inserting subspace, and the fourth female major internal inserting subspace. The first female major internal inserting subspace is in continuity with the second female major internal inserting subspace, and the third female major internal inserting subspace is in continuity with the fourth female major internal inserting subspace, thereby providing guidance for the insertion of the male connector in the inserting direction, allowing the male connector to respectively enter the first female major internal inserting subspace, the second female major internal inserting subspace, the third female major internal inserting subspace, and the fourth female major internal inserting subspace and respectively insert into the first female terminal, the second female terminal, the third female terminal, and the fourth female terminal.

[0041] In summary, this application provides a female connector that allows for the insertion of a male connector in the inserting direction. The insulation core of the female connector comprises an inserting guiding structure, which provides interference when the inserting direction of the male connector is incorrect, thereby preventing the male connector from being inserted into the female connector in the wrong direction. This allows the male connector to be inserted into the female connector to facilitate power or signal transmission.

[0042] The examples above are only illustrative to explain principles and effects of the invention, but not to limit the invention. It will be apparent to those skilled in the art that modifications and variations can be made without departing from the spirit and scope of the invention. Therefore, the protection range of the rights of the invention should be as defined by the appended claims.

Claims

1. A female connector, wherein the female connector is provided to allow insertion of a male connector in an inserting direction, the female connector comprising: a female conductive terminal set, wherein the female conductive terminal set comprises a first female terminal, a second female terminal, a third female terminal, and a fourth female terminal; and a female insulation core, wherein the female insulation core comprises a first female core lateral outer wall, a second female core lateral outer wall, a first female core longitudinal outer wall, a second female core longitudinal outer wall, a first female core lateral inner wall, a second female core lateral inner wall, and a first female core longitudinal inner wall; wherein, the first female core lateral outer wall and the second female core lateral outer wall extend laterally, respectively, and the first female core longitudinal outer wall and the second female core longitudinal outer wall extend longitudinally, respectively; the first female core longitudinal outer wall is connected to the first female core lateral outer wall, and the second female core longitudinal outer wall is connected to the second female core lateral outer wall to form a female core major internal inserting space; the first female core lateral inner wall and the second female core lateral inner wall extend laterally, respectively, wherein the first female core lateral inner wall is connected to the first female core longitudinal outer wall to form a first female major inserting guiding structure, and the first female core longitudinal inner wall is connected to the first female core lateral outer wall, the second female core lateral outer wall, and the second female core lateral inner wall to form a second female major inserting guiding structure, wherein, the first female major inserting guiding structure and the second female major inserting guiding structure partition the female core major internal inserting space into a first female major internal inserting subspace, a second female major internal inserting subspace, a third female major internal inserting subspace, and a fourth female major internal inserting subspace; the female insulation core is respectively mated with the first female terminal, the second female terminal, the

third female terminal, and the fourth female terminal, allowing the first female terminal, the second female terminal, the third female terminal, and the fourth female terminal to respectively extend into the first female major internal inserting subspace, the second female major internal inserting subspace, the third female major internal inserting subspace, and the fourth female major internal inserting subspace; and the first female major internal inserting subspace is in continuity with the second female major internal inserting subspace, and the third female major internal inserting subspace is in continuity with the fourth female major internal inserting subspace to guide the inserting of the male connector in the inserting direction, enabling the male connector to respectively enter the first female major internal inserting subspace, the second female major internal inserting subspace, the third female major internal inserting subspace, and the fourth female major internal inserting subspace and be inserted into the first female terminal, the second female terminal, the third female terminal, and the fourth female terminal, respectively.

2. The female connector of claim 1, wherein the first female major inserting guiding structure comprises a T-shaped cross-section; and the second female major inserting guiding structure comprises a T-shaped cross-section.

3. The female connector of claim 1, wherein the first female core lateral inner wall and the first female core longitudinal outer wall are substantially perpendicularly intersected, and the second female core lateral inner wall and the first female core longitudinal inner wall are substantially perpendicularly intersected.

4. The female connector of claim 1, wherein the female insulation core comprises a lateral extension plane, the first female core lateral inner wall and the second female core lateral inner wall extend along the lateral extension plane, and the lateral extension plane is substantially perpendicularly intersected with the first female core longitudinal outer wall and the first female core longitudinal inner wall.

5. The female connector of claim 1, wherein the female conductive terminal set further comprises a fifth female terminal and a sixth female terminal, and the female insulation core further comprises a third female core longitudinal outer wall and a third female core lateral inner wall, wherein the third female core longitudinal outer wall extends longitudinally and is respectively connected to the first female core lateral outer wall and the second female core lateral outer wall, thereby forming a female core minor internal inserting space; the third female core lateral inner wall is connected to the second female core longitudinal outer wall or the third female core longitudinal outer wall to form a first female minor inserting guiding structure; wherein, the first female minor inserting guiding structure partitions the female core minor internal inserting space into a first female minor internal inserting subspace and a second female minor internal inserting subspace; the female insulation core is further mated with the fifth female terminal and the sixth female terminal, allowing the fifth female terminal and the sixth female terminal to respectively extend into the first female minor internal inserting subspace and the second female minor internal inserting subspace; and the first female minor internal inserting subspace is in continuity with the second female minor internal inserting subspace to guide the insertion of the male connector in the inserting direction, enabling the male connector to respectively enter the first female minor internal inserting subspace and the second female minor internal inserting subspace and be inserted into the fifth female terminal and the sixth female terminal, respectively.

6. The female connector of claim 5, wherein the first female minor inserting guiding structure comprises a T-shaped cross-section.

7. The female connector of claim 5, wherein the third female core lateral inner wall and the second female core longitudinal outer wall or the third female core longitudinal outer wall are substantially perpendicularly intersected.

8. The female connector of claim 5, wherein the female insulation core comprises a lateral extension plane, the first female core lateral inner wall, the second female core lateral inner wall, and the third female core lateral inner wall extend along the lateral extension plane, and the lateral

extension plane is substantially perpendicularly intersected with the first female core longitudinal outer wall, the first female core longitudinal inner wall, the second female core longitudinal outer wall, and the third female core longitudinal outer wall.

9. The female connector of claim 1, wherein the female conductive terminal set further comprises a fifth female terminal and a sixth female terminal, and the female insulation core further comprises a third female core longitudinal outer wall, wherein the third female core longitudinal outer wall extends longitudinally and is respectively connected to the first female core lateral outer wall and the second female core lateral outer wall, thereby forming a female core minor internal inserting space; wherein, the female insulation core is further mated with the fifth female terminal and the sixth female terminal, allowing the fifth female terminal and the sixth female terminal to respectively extend into the female core minor internal inserting space; and the female core minor internal inserting space guides the insertion of the male connector in the inserting direction, enabling the male connector to enter the female core minor internal inserting space and be inserted into the fifth female terminal and the sixth female terminal.
