

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250286238

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

LIN; Denghua et al.

BATTERY CELL, BATTERY AND ELECTRIC DEVICE

Abstract

A battery cell comprises a casing assembly and a battery cell assembly, wherein the casing assembly comprises a casing and a first electrode post; the casing is provided with a mounting hole, through which the first electrode post passes; the battery cell assembly comprises an active-substance coated portion and an electrically conductive portion; the active-substance coated portion is provided in the casing, the electrically conductive portion is electrically connected to the active-substance coated portion and the first electrode post; the first electrode post comprises a first electrode-post portion and a second electrode-post portion, which are formed in a split manner; at least part of the first electrode-post portion is stopped outside the casing; and at least part of the second electrode-post portion is stopped inside the casing, and the second electrode-post portion is connected to the electrically conductive portion.

Inventors: LIN; Denghua (Ningde, CN), HUANG; Shoujun (Ningde, CN), WU; Yu (Ningde, CN), ZHENG; Yulian (Ningde, CN), WANG; Peng (Ningde, CN), JIN; Haizu (Ningde, CN)

Applicant: CONTEMPORARY AMPEREX TECHNOLOGY CO., LIMITED (Ningde, CN)

Family ID: 88824940

Assignee: CONTEMPORARY AMPEREX TECHNOLOGY CO., LIMITED (Ningde, CN)

Appl. No.: 19/216038

Filed: May 22, 2025

Foreign Application Priority Data

CN

202321132714.9

May. 11, 2023

Related U.S. Application Data

parent WO continuation PCT/CN2023/121164 20230925 PENDING child US 19216038

Publication Classification

Int. Cl.: **H01M50/531** (20210101); **H01M10/658** (20140101); **H01M50/172** (20210101);
H01M50/184 (20210101); **H01M50/188** (20210101); **H01M50/55** (20210101);
H01M50/552 (20210101); **H01M50/566** (20210101)

U.S. Cl.:

CPC **H01M50/531** (20210101); **H01M10/658** (20150401); **H01M50/172** (20210101);
H01M50/184 (20210101); **H01M50/188** (20210101); **H01M50/55** (20210101);
H01M50/552 (20210101); **H01M50/566** (20210101);

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION [0001] This application is a continuation of International application PCT/CN2023/121164 filed on Sep. 25, 2023 that claims priority to Chinese Patent Application No. 202321132714.9 filed on May 11, 2023. The content of the applications is incorporated herein by reference in its entirety.

TECHNICAL FIELD

[0002] The present application relates to the technical field of batteries, and in particular, to a battery cell, a battery, and an electric device.

BACKGROUND

[0003] In recent years, new energy vehicles have developed by leaps and bounds. In the field of electric vehicles, batteries, as the power source of electric vehicles, play an irreplaceable and important role. Generally, a battery includes a plurality of battery cells, and each of the battery cells includes a housing and a battery cell assembly received in the housing. A post terminal that is electrically connected to the battery cell assembly is riveted to the housing, and the post terminal is electrically connected to a busbar component outside the housing, so as to realize the electrical connection among the plurality of battery cells. However, the application of such a post terminal is limited.

SUMMARY

[0004] Embodiments of the present application provide a battery cell, a battery, and an electric device, which are conducive to improving the design diversity of a first post terminal and enriching the application scenarios of the first post terminal, thereby improving the design diversity of the battery cell.

[0005] In a first aspect, the embodiments of the present application provide a battery cell. The battery cell includes: a housing assembly and a battery cell assembly, where the housing assembly includes a housing and a first post terminal, the housing is provided with a mounting hole, and the first post terminal is provided in the mounting hole in a penetrating manner; the battery cell assembly includes an active substance-coated part and a conductive part, the active substance-coated part is disposed in the housing, the conductive part electrically connects the active substance-coated part and the first post terminal; the first post terminal includes a first post terminal part and a second post terminal part that are separately formed and connected to each other, at least a part of the first post terminal part is stopped outside the housing, at least a part of the second post terminal part is stopped inside the housing, and the second post terminal part is connected to the conductive part.

[0006] In the above technical solution, the first post terminal is arranged to include the first post terminal part and the second post terminal part that are separately formed, at least a part of the first

post terminal part is stopped outside the housing, at least a part of the second post terminal part is stopped inside the housing, and the second post terminal part is connected to the conductive part, such that the structural forms and materials of the first post terminal part and the second post terminal part can be separately designed and selected, which is conducive to improving the design diversity of the first post terminal and enriching the application scenarios of the first post terminal. Specifically, the structural form and the material of the second post terminal part can be provided to provide convenience for connection to the conductive part, and the structural form and the material of the first post terminal part can be provided to be suitable for direct or indirect connection to the busbar component, such that the first post terminal can well meet the requirements of good connection to both the conductive part and the busbar component, thereby achieving a flexible design and expanded application scenarios of the first post terminal, which is conducive to improving the design diversity of the battery cell.

[0007] In some embodiments, the second post terminal part includes a first connecting part, the first post terminal has a cavity formed on a side of the first connecting part distal to and/or facing the active substance-coated part, at least a part of the conductive part is received in the cavity and connected to the first connecting part, and at least the first connecting part in the second post terminal part has a hardness greater than that of the first post terminal part.

[0008] In the above technical solution, since the first connecting part and the cavity are liable to deformation due to the difficulty in obtaining reliable support from the housing, the hardness of at least the first connecting part in the second post terminal part is set to be greater than that of the first post terminal part in the present application, such that the deformation of the first connecting part can be reduced to a certain extent, the connection reliability between the first connecting part and the conductive part can be improved, and the conductive yield can be improved. Besides, the first post terminal part of relatively low hardness is conducive to improving the yield of the electrical connection between the first post terminal part and the busbar component. In addition, at least a part of the conductive part is arranged to be accommodated in the cavity, such that at least the part of the conductive part can occupy the space inside the first post terminal, the space occupied by the conductive part in the housing can be reduced, and some space can be saved in the housing for accommodating the active substance-coated part of a larger size, thereby improving the volumetric energy density of the battery cell.

[0009] In some embodiments, the second post terminal part further includes a second connecting part provided in the mounting hole in a penetrating manner, the second connecting part is formed in an annular structure disposed around an inner wall of the mounting hole, the first connecting part is disposed in an annular region of the second connecting part and connected to an inner end part of the second connecting part proximal to the active substance-coated part, the second connecting part and the first connecting part jointly define the cavity in an enclosing manner, the cavity is open in a direction away from the active substance-coated part, a perforation that is in communication with the cavity is formed on the first connecting part, and the conductive part partially passes through the perforation and is received in the cavity.

[0010] In the above technical solution, the second post terminal part includes the second connecting part provided in the mounting hole in a penetrating manner, which facilitates the assembly of the second post terminal part and the housing. Besides, the second connecting part of the annular structure and the first connecting part connected to the inner end part of the second connecting part jointly define the cavity, such that the structure of the second post terminal part can be simplified, and the receiving volume of the cavity can be increased. Moreover, since the cavity is open in the direction away from the active substance-coated part, the conductive part partially extends into the cavity through the perforation on the first connecting part, which is conducive to connecting the conductive part to the first connecting part from the outside of the housing, and facilitates the manufacture of the battery cell.

[0011] In some embodiments, the perforation is formed at an edge position of the first connecting

part that is connected to the second connecting part.

[0012] In the above technical solution, since the perforation is formed at a position of the first connecting part proximal to the second connecting part, when at least a part of the conductive part extending into the cavity is connected to the first connecting part, the first connecting part can have a larger area to be connected to the conductive part, which is conducive to increasing the connection area between the conductive part and the first connecting part, thereby increasing the connection reliability and the conductive area between the conductive part and the first connecting part.

[0013] In some embodiments, the active substance-coated part includes a current collector and an active substance layer disposed on the current collector, the conductive part includes a tab part electrically connected to the current collector, the tab part includes a plurality of tab plates, parts of the plurality of tab plates proximal to the current collector converge to form a first gathering part, parts of the plurality of tab plates distal to the current collector converge and are connected to form a second gathering part, and the first gathering part connects the second gathering part and the active substance-coated part; and the conductive part is formed by the tab part, at least a part of the second gathering part passes through the perforation and is received in the cavity; or the conductive part includes the tab part and an adapting piece, at least a part of the adapting piece passes through the perforation and is received in the cavity, and the adapting piece is connected between the second gathering part and the first connecting part.

[0014] In the above technical solution, when the conductive part is formed by the tab part, the tab part includes the second gathering part formed by converging and connecting the plurality of tab plates, such that at least a part of the second gathering part can pass through the perforation and be received in the cavity, and the conductive part can be simplified in construction and processing. When the conductive part includes the tab part and the adapting piece, the adapting piece passes through the perforation, such that the operation is convenient. Besides, by using the adapting piece to achieve an indirect electrical connection between the second gathering part and the first connecting part, the adapting piece can be connected to the first connecting part at a part avoiding the second gathering part, such that the welding between the adapting piece and the first connecting part is firm, welding cracks are unlikely to occur, and the reliability and stability of the battery cell can be further improved.

[0015] In some embodiments, the first post terminal part is located outside the housing and is an annular structure, the second post terminal part includes a second connecting part provided in the mounting hole in a penetrating manner, the second connecting part is formed in an annular structure disposed around the inner wall of the mounting hole, and an end of the second connecting part distal to the active substance-coated part extends to be connected to an inner peripheral part of the first post terminal part.

[0016] In the above technical solution, the first post terminal part is located outside the housing and is an annular structure, and the second connecting part is formed in an annular structure disposed around the inner wall of the mounting hole and an outer end part of the second connecting part can extend to the inner peripheral part of the first post terminal part, such that the construction of the first post terminal can be simplified, the number of parts can be reduced, and the processing and production efficiency can be improved. Besides, since both the first post terminal part and the second connecting part are annular structures, the first post terminal part and the second connecting part can be connected from the outside of the housing and at the inner periphery of the first post terminal part, thereby reducing the difficulty of processing.

[0017] In some embodiments, an end part of the second connecting part distal to the active substance-coated part is the outer end part, the outer end part extends to a side of the inner peripheral part proximal to a central axis of the mounting hole, and an inner side surface of the inner peripheral part facing the central axis of the mounting hole is welded to an outer side surface of the outer end part distal to the central axis of the mounting hole.

[0018] In the above technical solution, a weld seam between the inner side surface of the inner peripheral part and the outer side surface of the outer end part can be located at an outer surface of the first post terminal distal to the active substance-coated part, thereby facilitating welding from the outside of the housing, reducing the difficulty of welding, and improving the welding yield.

[0019] In some embodiments, the housing assembly further includes a post terminal cover plate located outside the housing and lidding the first post terminal part, a clearance groove is formed on the post terminal cover plate, and the clearance groove corresponds to a welding position of the outer end part and the inner peripheral part for accommodating a weld mark.

[0020] In the above technical solution, since the weld mark formed by welding the outer end part and the inner peripheral part can be at least partially accommodated in the clearance groove, the interference between the weld mark and the post terminal cover plate can be mitigated, such that the post terminal cover plate can be assembled smoothly with the first post terminal part after the outer end part is welded to the inner peripheral part, thereby improving the compactness and the reliability of the connection between the post terminal cover plate and the first post terminal part.

[0021] In some embodiments, the post terminal cover plate includes an embedded part extending to the annular region of the second connecting part, and an outer peripheral surface of the embedded part is spaced apart from an inner side surface of the outer end part to form a first gap.

[0022] In the above technical solution, by providing the first gap between the outer peripheral surface of the embedded part and the outer end part, the problem that the post terminal cover plate cannot be mounted to the first post terminal part due to the reduced annular size of the second connecting part due to the welding of the inner peripheral part of the first post terminal part and the outer end part of the second post terminal part can be mitigated, such that the post terminal cover plate can be mounted smoothly after the welding of the outer end part and the inner peripheral part.

[0023] In some embodiments, an end part of the second connecting part distal to the active substance-coated part is an outer end part, the inner peripheral part abuts against a side of the outer end part distal to the active substance-coated part, and an inner end surface of the inner peripheral part facing the active substance-coated part is welded to an outer end surface of the outer end part distal to the active substance-coated part.

[0024] In the above technical solution, the weld seam between the inner end surface of the inner peripheral part and the outer end surface of the outer end part can be located in the annular region of the first post terminal part and the annular region of the second connecting part. That is, the welding head can extend into the annular region of the first post terminal part and the annular region of the second connecting part for welding. The flatness of the outer surface of the first post terminal distal to the active substance-coated part is slightly affected by the weld mark formed after welding, which is conducive to the subsequent welding of the first post terminal and the post terminal cover plate or the busbar component.

[0025] In some embodiments, the housing assembly further includes a post terminal cover plate located outside the housing and lidding the first post terminal part, the post terminal cover plate is partially embedded in an annular region of the inner peripheral part, and the post terminal cover plate is spaced apart from the inner peripheral part to form a second gap.

[0026] In the above technical solution, by providing the second gap between the post terminal cover plate and the inner peripheral part, the post terminal cover plate can be mounted smoothly after the first post terminal part is welded to the second post terminal part, thereby improving the compactness and the reliability of the connection between the post terminal cover plate and the first post terminal part.

[0027] In some embodiments, the first post terminal part is connected to the second post terminal part by welding

[0028] In the above technical solution, by connecting the first post terminal part to the second post terminal part by welding, the construction of the first post terminal can be simplified, and the first post terminal can be easily mounted to the housing, which is conducive to reducing the production

cost and improving the assembly efficiency.

[0029] In some embodiments, the first post terminal is provided with a recess at a welding position of the first post terminal part and the second post terminal part, and the recess is configured to accommodate a weld mark formed by welding the first post terminal part and the second post terminal part.

[0030] In the above technical solution, the recess is disposed on the first post terminal corresponding to the welding position of the first post terminal part and the second post terminal part to accommodate the weld mark, such that the problem that the weld mark protrudes from the surface of the welding position, which may affect the subsequent assembly of other parts, such as the post terminal cover plate, with the first post terminal, can be mitigated.

[0031] In some embodiments, the housing assembly further includes an insulating seal assembly, the insulating seal assembly connects the housing and the first post terminal in an insulating manner, the insulating seal assembly includes an insulating member and an insulating sealing member with stronger heat resistance than the insulating member, and the insulating sealing member is located between the welding position of the first post terminal part and the second post terminal part and the housing.

[0032] In the above technical solution, the insulating seal assembly is arranged to include the insulating sealing member with sealing performance and relatively strong heat resistance, the insulating sealing member is disposed between the welding position of the first post terminal part and the second post terminal part and the housing, and the insulating member is disposed distal to the welding position of the first post terminal part and the second post terminal part relative to the insulating sealing member, such that the influence of the welding temperature on the insulating member can be reduced by utilizing the insulating sealing member. Besides, the cost of the insulating seal assembly is reduced while the insulating sealing effect is ensured by arranging the insulating seal assembly to include the insulating member with relatively weak heat resistance.

[0033] In some embodiments, the welding position of the first post terminal part and the second post terminal part is located at an outer side of the mounting hole, the insulating member includes an outer insulating member and an inner insulating member, the outer insulating member is sandwiched between the first post terminal part and an outer wall of the housing, the inner insulating member is sandwiched between the second post terminal part and an inner wall of the housing, the insulating sealing member includes an inner segment and an outer segment, the inner segment extends inside the mounting hole and abuts against the first post terminal part and the inner insulating member separately at two ends in an axial direction of the mounting hole, and the outer segment extends at the outer side of the mounting hole and is connected to the inner segment at a radial inner end and abuts against the outer insulating member at a radial outer end in a radial direction of the mounting hole.

[0034] In the above technical solution, the assembly of the insulating seal assembly is convenient, and due to the structural distribution position of the insulating sealing member, both the inner insulating member and the outer insulating member can well obtain heat insulation protection of the sealing insulating member.

[0035] In some embodiments, the housing is provided with a plurality of post terminals, and at least one of the plurality of post terminals is the first post terminal.

[0036] In the above technical solution, at least one of all the post terminals of the housing assembly is arranged to be the first post terminal, such that a part of all the post terminals in the battery cell may be the separately formed first post terminals, or all the post terminals may be the separately formed first post terminals, which allows to flexibly select and match the post terminals according to manufacturing requirements, cost requirements, and the like.

[0037] In a second aspect, the embodiments of the present application further provide a battery. The battery includes the above battery cell.

[0038] In the above technical solution, the design of the battery cell is diversified, such that the

diversity of battery design can be improved.

[0039] In a third aspect, the embodiments of the present application further provide an electric device. The electric device includes the above battery.

[0040] In the above technical solution, the battery can have diversified designs, such that different batteries can be flexibly designed according to the actual requirements of the electric device, and the power supply requirements for the electric device can be optimized.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0041] To more clearly illustrate the technical solutions in embodiments of the present application, the drawings required for use in the embodiments will be briefly described below. It should be understood that the following drawings only illustrate some embodiments of the present application and therefore should not be considered as limiting the scope of the present application, and other related drawings can be derived from these drawings by those of ordinary skill in the art without creative efforts.

[0042] FIG. 1 is a schematic structural diagram of a vehicle as an electric device according to some embodiments of the present application;

[0043] FIG. 2 is an exploded view of a battery cell used in a battery according to some embodiments of the present application;

[0044] FIG. 3 is a three-dimensional view of a battery cell according to some embodiments of the present application;

[0045] FIG. 4 is an exploded view of the battery cell shown in FIG. 3;

[0046] FIG. 5 is an orthographic projection view of the battery cell shown in FIG. 3;

[0047] FIG. 6 is a cross-sectional view along the line A-A in FIG. 5;

[0048] FIG. 7 is a partially enlarged view of the portion B shown in FIG. 6;

[0049] FIG. 8 is a partial cross-sectional view of a battery cell according to some embodiments of the present application;

[0050] FIG. 9 is a partial cross-sectional view of a battery cell according to some embodiments of the present application;

[0051] FIG. 10 is a partial cross-sectional view of a battery cell according to some embodiments of the present application;

[0052] FIG. 11 is a three-dimensional view of a first post terminal according to some embodiments of the present application;

[0053] FIG. 12 is an orthographic projection view of the battery cell shown in FIG. 11;

[0054] FIG. 13 is a cross-sectional view along the line C-C in FIG. 12;

[0055] FIG. 14 is a cross-sectional view along the line D-D in FIG. 12;

[0056] FIG. 15 is a partial cross-sectional view of a battery cell according to some embodiments of the present application; and

[0057] FIG. 16 is a partial cross-sectional view of a battery cell according to some embodiments of the present application.

[0058] Reference numerals are as follows: electric device **1000**; battery **100**; controller **200**; motor **300**; case **20**; first case **201**; second case **202**; battery cell **10**; housing assembly **1**; housing **11**; mounting hole **111**; housing body **112**; bottom cover **113**; first post terminal **12**; first post terminal part **121**; first stopper part **1211**; inner peripheral part **12111**; inner end surface of the inner peripheral part **S11**; inner side surface of the inner peripheral part **S12**; outer peripheral part **12112**; extending part **1212**; second post terminal part **122**; second stopper part **1221**; first connecting part **1222**; perforation **12221**; second connecting part **1224**; outer end part **12241**; outer end surface of the outer end part **S21**; outer side surface of the outer end part **S22**; inner side surface of the outer

end part **S23**; cavity **123**; recess **124**; groove **125**; post terminal cover plate **13**; clearance groove **131**; embedded part **132**; outer peripheral surface of the embedded part **1321**; first gap **14**; second gap **15**; insulating seal assembly **16**; insulating member **161**; outer insulating member **1611**; inner insulating member **1612**; insulating sealing member **162**; outer segment of the insulating sealing member **1621**; inner segment of the insulating sealing member **1622**; insulating film **17**; battery cell assembly **2**; active substance-coated part **21**; current collector **211**; active substance layer **212**; conductive part **22**; tab part **221**; tab plate **2210**; first gathering part **2211**; second gathering part **2212**; adapting piece **222**; first direction Z; second direction X; and third direction Y.

DETAILED DESCRIPTION

[0059] To make the objectives, technical solutions, and advantages of embodiments of the present application clearer, the technical solutions in the embodiments of the present application will be clearly described hereinafter with reference to the drawings in the embodiments of the present application. It is obvious that the described embodiments are some, but not all, embodiments of the present application. Based on the embodiments in the present application, all other embodiments obtained by those of ordinary skill in the art without creative work shall fall within the protection scope of the present application.

[0060] Unless otherwise defined, all technical and scientific terms used in the present application have the same meaning as commonly understood by those of ordinary skill in the art to which the present application belongs. The terms used in the specification of the present application are only used to describe specific embodiments and are not intended to limit the present application. The terms “include”, “comprise”, “have”, and any variants thereof in the specification and claims of the present application and the above description of the drawings are intended to cover non-exclusive inclusion. The terms “first”, “second”, and the like in the specification and claims of the present application and the above drawings are used to distinguish different objects and are not intended to describe a specific order or priority.

[0061] Reference in the present application to “embodiment” means that a particular feature, structure, or characteristic described in connection with the embodiment can be included in at least one embodiment of the present application. The references of the word in the context of the specification do not necessarily refer to the same embodiment, nor to separate or alternative embodiments exclusive of other embodiments.

[0062] In the present application, the term “and/or” is only an association relationship that describes the associated objects, and indicates that there may be three relationships. For example, A and/or B may indicate that: only A is present, both A and B are present, and only B is present. In addition, the character “/” herein generally indicates an “or” relationship between the associated objects before and after the “/”.

[0063] In the embodiments of the present application, the same reference numerals represent the same components, and for the sake of brevity, detailed descriptions of the same components are omitted in different embodiments. It should be understood that the thickness, length, width, and other dimensions of various components in the embodiments of the present application shown in the drawings, as well as the overall thickness, length, width, and other dimensions of the integrated device are only exemplary and should not impose any limitation on the present application.

[0064] The term “plurality of” used in the present application refers to more than two (including two).

[0065] In the present application, battery cells may include lithium-ion secondary batteries, lithium-ion primary batteries, lithium-sulfur batteries, sodium-lithium-ion batteries, sodium-ion batteries, magnesium-ion batteries, etc. This is not limited in the embodiments of the present application. The battery cell may be cylindrical, flat, rectangular parallelepiped-shaped, or in other shapes, which is also not limited in the embodiments of the present application. According to the packaging method, battery cells are typically divided into three types: cylindrical battery cells, square battery cells, and pouch battery cells, which are not limited in the embodiments of the

present application.

[0066] Illustratively, a battery cell may generally include a housing, a battery cell assembly, and an electrolytic solution. The housing is configured to accommodate the battery cell assembly and the electrolytic solution. The housing is provided with a plurality of post terminals, which generally include at least one positive electrode post terminal and at least one negative electrode post terminal. The battery cell assembly includes one or a plurality of electrode assemblies, and the electrode assembly is formed by stacking or winding a positive electrode plate, a negative electrode plate, and a separator.

[0067] The positive electrode plate may generally include a positive electrode current collector and a positive electrode active substance layer. The positive electrode current collector is directly or indirectly coated with the positive electrode active substance layer, the positive electrode current collector not coated with the positive electrode active substance layer protrudes from the positive electrode current collector coated with the positive electrode active substance layer, the positive electrode current collector not coated with the positive electrode active substance layer serves as a positive electrode tab plate, and a plurality of positive electrode tab plates are stacked together and electrically connected to the positive electrode post terminal. Illustratively, the plurality of positive electrode tab plates stacked together may be directly welded to the positive electrode post terminal to form an electrical connection. Alternatively, the battery cell assembly may further include a positive electrode adapting piece, the plurality of positive electrode tab plates stacked together are welded to one end of the positive electrode adapting piece, and the other end of the positive electrode adapting piece is welded to the positive electrode post terminal to form an electrical connection between the positive electrode tab plates and the positive electrode post terminal.

[0068] The negative electrode plate may generally include a negative electrode current collector and a negative electrode active substance layer. The negative electrode current collector is directly or indirectly coated with the negative electrode active substance layer, the negative electrode current collector not coated with the negative electrode active substance layer protrudes from the negative electrode current collector coated with the negative electrode active substance layer, the negative electrode current collector not coated with the negative electrode active substance layer serves as a negative electrode tab plate, and a plurality of negative electrode tab plates are stacked together and electrically connected to the negative electrode post terminal. Illustratively, the plurality of negative electrode tab plates stacked together may be directly welded to the negative electrode post terminal to form an electrical connection. Alternatively, the battery cell assembly may further include a negative electrode adapting piece, the plurality of negative electrode tab plates stacked together are welded to one end of the negative electrode adapting piece, and the other end of the negative electrode adapting piece is welded to the negative electrode post terminal to form an electrical connection between the negative electrode tab plates and the negative electrode post terminal.

[0069] The material of the separator is not limited, such as polypropylene or polyethylene.

[0070] Meanwhile, a battery cell primarily works by the movement of metal ions between the positive electrode plate and the negative electrode plate. Taking lithium-ion batteries as an example, the material of the positive electrode current collector may be aluminum, the material of the positive electrode active substance layer may be lithium cobaltate, lithium iron phosphate, ternary lithium, lithium manganate, etc., the material of the negative electrode current collector may be copper, and the material of the negative electrode active substance layer may be carbon, silicon, etc. During the charging and discharging processes, Li^+ is intercalated or deintercalated back and forth between the two electrodes: during charging, Li^+ is deintercalated from the positive electrode, and intercalated into the negative electrode through the electrolyte, and the negative electrode is in a lithium-rich state; during discharging, the process is reversed.

[0071] The battery mentioned in the embodiments of the present application refers to a single physical module including one or a plurality of battery cells to provide higher voltage and capacity.

For example, the battery mentioned in the present application may be a battery module, a battery pack, or the like. A battery module generally includes a plurality of battery cells. A battery pack generally includes a case used for encapsulating one or a plurality of battery cells or one or a plurality of battery modules. The case can mitigate liquid or other foreign matters from affecting the charging or discharging of the battery cells.

[0072] In the battery, a plurality of battery cells may be connected in series, in parallel, or in series-parallel. The series-parallel connection means that both series connection and parallel connection are present for the connection among the plurality of battery cells. The plurality of battery cells can be directly connected in series, in parallel, or in series-parallel, and then the whole formed by the plurality of battery cells is accommodated in the case. Alternatively, the battery may also be in a form where a plurality of battery cells are first connected in series, in parallel, or in series-parallel to give a battery module, and then a plurality of battery modules are connected in series, in parallel, or in series-parallel to form a whole and accommodated in the case.

[0073] The battery in the related art further includes a busbar component, and the busbar component is configured to achieve electrical connection among a plurality of battery cells. When the battery is manufactured, the busbar component is welded to the post terminal of the battery cell to achieve the electrical connection between the busbar component and the post terminal.

Meanwhile, the post terminal can be electrically connected to the battery cell assembly through welding to the conductive parts, such as the tab plates or the adapting piece. Generally, the post terminal is an integrally formed part and is mounted to the housing in a riveted manner, such that the form of the post terminal needs to conform to the riveting requirements, and the post terminal is made of the same material, which limits the structural form and the material of such a post terminal. The post terminal is difficult to be flexibly modified into other novel structures or formed by various materials, making it difficult to meet more scenario requirements.

[0074] Based on the above considerations, in order to improve the design diversity and multi-scenario adaptability of the post terminal, the present application designs a battery cell, where the post terminal is arranged to include at least two parts that are separately formed, such that the structural form and the material of each part can be separately designed, which is conducive to flexibly designing the post terminal in various novel forms. In addition, at least a part of one part of the post terminal can be disposed outside the housing, and the part can be arranged to be suitable for direct or indirect connection to a busbar component; and at least a part of the other part of the post terminal can be disposed inside the housing, and the part can be arranged to be suitable for connection to a conductive part of a battery cell assembly, such that the post terminal can well meet the requirements of good connection to both the conductive part and the busbar component, thereby improving the design diversity and multi-scenario adaptability of the post terminal.

[0075] The embodiments of the present application further provide an electric device using the battery of the present application as a power source. The electric device may be, but is not limited to, a mobile phone, a tablet, a laptop computer, an electric toy, an electric tool, an electric bicycle, an electric car, a ship, a spacecraft, and the like. The electric toy may include a stationary or mobile electric toy, such as a game console, an electric car toy, an electric ship toy, and an electric airplane toy, and the spacecraft may include an airplane, a rocket, a space shuttle, a spaceship, and the like.

[0076] For ease of explanation in the following embodiments, the structures of the electric device, the battery, and the battery cell of the present application are described by taking the electric device as a vehicle as an example.

[0077] Referring to FIG. 1, FIG. 1 is a schematic structural diagram of a vehicle as an electric device **1000** according to some embodiments of the present application. The vehicle may be a fuel vehicle, a gas vehicle, or a new energy vehicle. The new energy vehicle may be a pure electric vehicle, a hybrid vehicle, an extended-range vehicle, or the like. A battery **100** is arranged in the vehicle, and the battery **100** may be arranged at the bottom, head, or tail of the vehicle. The battery **100** may be configured to supply power to the vehicle. For example, the battery **100** may serve as

an operation power source of the vehicle. The vehicle may further include a controller **200** and a motor **300**. The controller **200** is configured to control the battery **100** to power the motor **300**, e.g., for operation power needed by the vehicle for start-up, navigation, and driving. In some embodiments of the present application, the battery **100** may not only serve as the operation power source for the vehicle, but also as a driving power source for the vehicle to, instead of or in part instead of fuel or natural gas, provide driving power for the vehicle.

[0078] Referring to FIG. 2, FIG. 2 is an exploded view of a battery cell **10** used in the battery **100** according to some embodiments of the present application. The battery **100** includes a case **20** and a plurality of battery cells **10**, and the battery cells **10** are accommodated in the case **20**. The case **20** is configured to provide an assembly space for the battery cell **10**, and the case **20** may be in various structures. In some embodiments, the case **20** may include a first case **201** and a second case **202**. The first case **201** and the second case **202** are lidded with each other. The first case **201** and the second case **202** jointly define an assembly space for accommodating the battery cell **10**. The second case **202** may be of a hollow structure with one end open, the first case **201** may be of a plate structure, and the first case **201** lids the open side of the second case **202**, such that the first case **201** and the second case **202** jointly define an assembly space; or both the first case **201** and the second case **202** may be of hollow structures with one side open (for example, as shown in FIG. 2), and the open side of the first case **201** lids the open side of the second case **202**. Certainly, the case **20** formed by the first case **201** and the second case **202** may be in various shapes, such as a cylinder or a rectangular parallelepiped.

[0079] Referring to FIG. 3, FIG. 3 is a schematic diagram of a battery cell **10** according to some embodiments of the present application. The battery cell **10** is in the shape of a rectangular parallelepiped, and the height direction of the battery cell **10** is the first direction Z, the length direction of the battery cell **10** is the second direction X, and the thickness direction of the battery cell **10** is the third direction Y. The first direction Z, the second direction X, and the third direction Y are perpendicular to each other, which is, however, not limiting. In other embodiments of the present application, the battery cell **10** may also be cylindrical, flat, multi-prismatic, or in other shapes.

[0080] Referring to FIG. 4, FIG. 4 is an exploded view of the battery cell shown in FIG. 3. In the embodiments of the present application, the battery cell **10** includes a housing assembly **1** and a battery cell assembly **2**. The housing assembly **1** includes a housing **11** and a first post terminal **12** disposed on the housing **11**. The shape of the housing **11** is adjusted according to the type of the battery cell **10**, and the type of the battery cell **10** in the embodiments of the present application is not limited. For example, when the battery cell **10** is a square battery, the housing **11** is square, and when the battery cell **10** is a cylindrical battery, the housing **11** is cylindrical. The embodiments of the present application are all described by taking the housing **11** as a square as an example.

[0081] The housing **11** is provided with post terminals for electrical connection to the battery cell assembly **2** to ensure normal charging and discharging operations of the battery cell **10**. Generally, the number of post terminals is at least two, specifically including at least one positive electrode post terminal and at least one negative electrode post terminal. For example, when the number of post terminals is two, one is a positive electrode post terminal and the other is a negative electrode post terminal, and the two are electrically connected to positive and negative output positions of the battery cell assembly **2**, separately. For another example, when the number of post terminals is four, two may be positive electrode post terminals and two may be negative electrode post terminals. In this case, the two positive electrode post terminals are both electrically connected to a positive output position of the battery cell assembly **2**, and the two negative electrode post terminals are both electrically connected to a negative output position of the battery cell assembly **2**.

[0082] In the embodiments of the present application, at least one of the plurality of post terminals on the housing **11** is the first post terminal **12**, the first post terminal **12** can be used as a positive electrode post terminal or a negative electrode post terminal, and the first post terminal **12** is a post

terminal that is separately formed in parts and then connected. That is, all the post terminals on the housing **11** may be the separately formed first post terminals **12**, or a part of the post terminals on the housing **11** may be the separately formed first post terminals **12**. When a part of the post terminals on the housing **11** are the separately formed first post terminals **12**, the remaining post terminals on the housing **11** are integrally formed second post terminals (not shown).

[0083] Regardless of whether the post terminal on the housing **11** is the first post terminal **12** or the second post terminal, the first post terminal **12** and the second post terminal can be both electrically connected to the battery cell assembly **2** to ensure the normal charging and discharging processes of the battery cell **10**. Certainly, in other embodiments of the present application, only one post terminal may be disposed on the housing assembly **1**, which is the first post terminal **12**. In this case, the first post terminal **12** may include one part that is connected in an insulating manner and used as a positive electrode post terminal and another part used as a negative electrode post terminal. In order to simplify the description, the following description is mainly made with the housing **11** being provided with a plurality of post terminals, and all the post terminals being the first post terminals **12** as an example.

[0084] Referring to FIGS. 5-7, FIG. 5 is an orthographic projection view of the battery cell shown in FIG. 3, FIG. 6 is a cross-sectional view along the line A-A in FIG. 5, and FIG. 7 is a partially enlarged view of the portion B shown in FIG. 6. In the embodiments of the present application, the battery cell assembly **2** includes an active substance-coated part **21** and a conductive part **22**. The active substance-coated part **21** is disposed in the housing **11**. The active substance-coated part **21** is a part of the battery cell assembly **2** coated with an active substance, and can assist in the deintercalation of metal ions during the charging and discharging processes of the battery cell **10**. The conductive part **22** is a metal structure that electrically connects the active substance-coated part **21** and the post terminal, and is not coated with the active substance. Both the first post terminal **12** and the second post terminal can be electrically connected to the active substance-coated part **21** through the conductive part **22** to enable the charging and discharging operations of the battery cell **10**. For example, the conductive part **22** may include only tab plates, and the tab plates are directly electrically connected to the post terminal. For another example, the conductive part may include tab plates and an adapting piece connected to the tab plates by welding, and the tab plates are indirectly electrically connected to the post terminal via the adapting piece.

[0085] It can be understood that the active substance-coated part **21** is divided into a positive electrode active substance-coated part and a negative electrode active substance-coated part. The positive electrode active substance-coated part includes a part in which the positive electrode current collector is coated with a positive electrode active substance layer, and the negative electrode active substance-coated part includes a part in which the negative electrode current collector is coated with a negative electrode active substance layer. The conductive part **22** is divided into a positive electrode conductive part and a negative electrode conductive part. The positive electrode conductive part electrically connects the positive electrode active substance-coated part and the positive electrode post terminal, and the negative electrode conductive part electrically connects the negative electrode active substance-coated part and the negative electrode post terminal.

[0086] Referring to FIGS. 4, 6 and 7 again, in the embodiments of the present application, the housing **11** is provided with a mounting hole **111**, and the first post terminal **12** is provided in the mounting hole **111** in a penetrating manner. The first post terminal **12** includes a first post terminal part **121** and a second post terminal part **122** that are separately formed and connected to each other. That is, the first post terminal part **121** is separately machined, the second post terminal part **122** is also separately machined, and the first post terminal part **121** and the second post terminal part **122** are not integrally formed parts, but are directly or indirectly connected together through welding, bonding, and other processes. Therefore, the structural form and the material of the first post terminal part **121** and the structural form and the material of the second post terminal part **122**

can be designed separately, which is conducive to flexibly designing the first post terminal **12** in various novel forms and improving the design diversity of the first post terminal **12**.

[0087] In the embodiments of the present application, at least a part of the first post terminal part **121** is stopped outside the housing **11**, at least a part of the second post terminal part **122** is stopped inside the housing **11**, and the second post terminal part **122** is connected to the conductive part **22**. Referring to FIG. 7 again, the first post terminal part **121** includes a first stopper part **1211**, and the first stopper part **1211** directly or indirectly abuts against the outer side of the housing **11** to prevent the first post terminal part **121** from entering the housing **11** through the mounting hole **111**. The second post terminal part **122** includes a second stopper part **1221**, and the second stopper part **1221** directly or indirectly abuts against the inner side of the housing **11** to prevent the second post terminal part **122** from moving out of the housing **11** through the mounting hole **111**.

[0088] The second post terminal part **122** and the conductive part **22** are connected by welding or other means to be electrically connected to each other. Since at least a part of the second post terminal part is stopped inside the housing **11** and the second post terminal part **122** is connected to the conductive part **22**, the structural form, the material, and the like of the second post terminal part **122** can be provided to be suitable for connection to the conductive part **22**. Meanwhile, since at least a part of the first post terminal part **121** is stopped outside the housing **11**, the first post terminal part **121** can be directly or indirectly connected to the busbar component, such that the structural form, the material, and the like of the first post terminal part **121** can be provided to be suitable for direct or indirect connection to the busbar component. Therefore, the first post terminal **12** can well meet the requirements of good connection to both the conductive part **22** and the busbar component, thereby improving the multi-scenario adaptability of the first post terminal **12**.

[0089] In the above technical solution, the first post terminal **12** is arranged to include the first post terminal part **121** and the second post terminal part **122** that are separately formed, at least a part of the first post terminal part **121** is stopped outside the housing **11**, at least a part of the second post terminal part **122** is stopped inside the housing **11**, and the second post terminal part **122** is connected to the conductive part **22**, such that the structural forms and materials of the first post terminal part **121** and the second post terminal part **122** can be separately designed and selected, which is conducive to flexibly designing the post terminal in various novel forms, and improving the design diversity of the first post terminal **12** and enriching the application scenarios of the first post terminal **12**. Specifically, the structural form and the material of the second post terminal part **122** can be provided to provide convenience for connection to the conductive part **22**, and the structural form and the material of the first post terminal part **121** can be provided to be suitable for direct or indirect connection to the busbar component, such that the first post terminal **12** can well meet the requirements of good connection to both the conductive part **22** and the busbar component, thereby achieving a flexible design and expanded application scenarios of the first post terminal **12**, which is conducive to improving the design diversity of the battery cell **10**.

[0090] Referring to FIG. 7 again, in some embodiments of the present application, the second post terminal part **122** includes a first connecting part **1222**, the first post terminal **12** has a cavity **123** formed on a side of the first connecting part **1222** distal to the active substance-coated part **21**, and at least a part of the conductive part **22** is received in the cavity **123** and connected to the first connecting part **1222**. Therefore, at least a part of the conductive part **22** is arranged to be accommodated in the cavity **123**, such that at least the part of the conductive part **22** can occupy the space inside the first post terminal **12**, the space occupied by the conductive part **22** in the housing **11** can be reduced, and some space can be saved in the housing **11** for accommodating the active substance-coated part **21** of a larger size, thereby improving the volumetric energy density of the battery cell **10**.

[0091] In the embodiments of the present application, at least the first connecting part **1222** in the second post terminal part **122** has a hardness greater than that of the first post terminal part **121**. That is, only the hardness of the first connecting part **1222** may be greater than that of the first post

terminal part **121**, or the hardness of the whole second post terminal part **122** may be greater than that of the first post terminal part **121**.

[0092] It should be noted that the materials of the first connecting part **1222** and the first post terminal part **121** are not limited and can be selected from various kinds of materials, such as two kinds of copper materials of different hardness, or two kinds of aluminum materials of different hardness. For example, any one of the aluminum materials Al3003-H14, Al3003-H18, Al3003-H112, Al1060-H14, Al1060-H18, and Al1060-H112 can be selected for the first post terminal part **121** and the first connecting part **1222** (it can be understood that the hardness of H14 is lower than that of H18, and the hardness of H18 is lower than that of H112), as long as the selected material meets the requirement that the hardness of the first connecting part **1222** is greater than that of the first post terminal part **121**. For example, when the first connecting part **1222** is made of Al1060-H112 or Al3003-H112, the first post terminal part **121** may be made of any one of Al3003-H14, Al3003-H18, Al1060-H14, and Al1060-H18. For another example, when the first connecting part **1222** is made of Al1060-H18 or Al3003-H18, the first post terminal part **121** may be made of Al3003-H14 or Al1060-H14.

[0093] Relevant contents about hardness measurement are briefly introduced below. The testing operation is performed as follows: 1) The power supply is turned on to check whether the test equipment (such as a Vickers hardness tester) is normal or not. 2) A cut test sample is placed under the lens of the Vickers hardness tester, the test line is adjusted to zero through the ocular lens, and the lifting lever is adjusted to ensure that the surface of the sample is clearly visible through the ocular lens. 3) After the lifting lever is adjusted, the start button is pressed to start loading onto the sample. 4) Once the loading is finished, the lengths of two diagonal lines of the indentation are measured through the ocular lens, and input into the equipment. The equipment will automatically display the Vickers hardness value and record the measurement result. Through the hardness measurement, the magnitude relationship of the hardness of the first connecting part **1222** and the first post terminal part **121** can be learned.

[0094] In the above technical solution, since the cavity **123** is formed on the side of the first connecting part **1222** distal to the active substance-coated part **21**, the first connecting part is liable to deformation due to the lack of support from the housing **11**. However, the hardness of at least the first connecting part **1222** in the second post terminal part **122** is set to be greater than that of the first post terminal part **121** in the present application, such that the deformation of the first connecting part **1222** can be reduced to a certain extent, the connection reliability between the first connecting part **1222** and the conductive part **22** can be improved, and the conductive yield can be improved.

[0095] Besides, the first post terminal part **121** of relatively low hardness is conducive to improving the yield of the electrical connection between the first post terminal part **121** and the busbar component. Referring to FIG. 7 again, when the first post terminal part **121** is of a hollow structure, the post terminal of the cover plate **13** may be welded on the first post terminal part **121**, and the busbar component is welded on the post terminal cover plate **13**, which, due to the relatively low hardness of the first post terminal part **121**, is conducive to improving the welding yield of the first post terminal part **121** and the post terminal cover plate **13**, and thus improving the yield of electrical connection between the first post terminal part **121** and the busbar component. Referring to FIG. 9, FIG. 9 is a partial cross-sectional view of the battery cell **10** according to some embodiments of the present application. When the first post terminal part **121** is of a solid structure, the busbar component may be directly welded on the first post terminal part **121**, which, due to the relatively low hardness of the first post terminal part **121**, is conducive to improving the welding yield of the first post terminal part **121** and the busbar component, and thus improving the yield of electrical connection between the first post terminal part **121** and the busbar component.

[0096] In the related art, the post terminal is an integrally formed part and is riveted to the housing. If the hardness of the post terminal is high, it is difficult to meet the ductility requirements of

riveting and flanging, and the process is difficult; and if the hardness of the post terminal is low, a part of the post terminal corresponding to the cavity and connected to the conductive part is liable to deformation, and the insufficient strength makes it difficult to reliably connect to the conductive part. However, in the present application, the first post terminal **12** is arranged to include the second post terminal part **122** and the first post terminal part **121** that are separately machined, the second post terminal part **122** and the first post terminal part **121** have different hardness, the second post terminal part **122** of a higher hardness is unlikely to deform and is conducive to reliable connection to the conductive part **22**, and the first post terminal part **121** of a lower hardness has a better welding yield and is conducive to direct or indirect electrical connection to the busbar component.

[0097] In addition, the first stopper part **1211** of the first post terminal part **121** may be directly formed when the first post terminal part **121** is processed, or may be subsequently formed by riveting the first post terminal part **121** to the housing **11**. Since the first post terminal part **121** has relatively low hardness and good ductility, the first post terminal part **121** facilitates riveting. In order to simplify the processing, the first stopper part **1211** may be directly formed when the first post terminal part **121** is processed, and the second post terminal part **12** can be fixed to the housing **11** by welding the first post terminal part **121** and the second post terminal part **122**. In this case, the first post terminal part **121** does not need to be connected to the housing **11** by riveting, thereby simplifying the assembly process and improving the assembly efficiency.

[0098] It is worth noting that the relative positions of the cavity **123** and the first connecting part **1222** are not limited to the above description. For example, referring to FIG. 9 again, the first post terminal **12** may also have a cavity **123** formed on a side of the first connecting part **1222** facing the active substance-coated part **21**, which is conducive to increasing the volume of the conductive part **22** accommodated in the cavity **123**, and the cavity **123** may be provided in a closed manner to mitigate the problem that the electrolytic solution and the like in the housing **11** flow out from the first post terminal **12**. Alternatively, for another example, referring to FIG. 10, FIG. 10 is a partial cross-sectional view of the battery cell **10** according to some embodiments of the present application. The first post terminal **12** may also have cavities **123** formed on a side of the first connecting part **1222** facing the active substance-coated part **21** and a side distal to the active substance-coated part **21**, separately. A perforation **12221** communicating the cavities **123** on two sides of the first connecting part **1222** is formed on the first connecting part **1222**, and the conductive part **22** may partially extend into the cavity **123** at the outer side of the first connecting part **1222** through the perforation **12221**, thereby facilitating the connection between the conductive part **22** and the first connecting part **1222** from the outer side. The “outer side” refers to a side distal to the active substance-coated part **21**.

[0099] In some embodiments, referring to FIG. 7 again, the perforation **12221** is formed at an edge position of the first connecting part **1222** that is connected to the second connecting part **1224**. In the above technical solution, since the perforation **12221** is formed at a position of the first connecting part **1222** proximal to the second connecting part **1224**, when at least a part of the conductive part **22** extending into the cavity **123** is connected to the first connecting part **1222**, the first connecting part **1222** can have a larger area to be connected to the conductive part **22**, which is conducive to increasing the connection area between the conductive part **22** and the first connecting part **1222**, thereby increasing the connection reliability and the conductive area between the conductive part **22** and the first connecting part **1222**.

[0100] In some embodiments, referring to FIG. 7 again, the active substance-coated part **21** includes a current collector **211** and an active substance layer **212** disposed on the current collector **211**. The conductive part **22** includes a tab part **221** electrically connected to the current collector **211**. The tab part **221** includes a plurality of tab plates **2210**. Parts of the plurality of tab plates **2210** proximal to the current collector **211** converge to form a first gathering part **2211**, and parts of the plurality of tab plates **2210** distal to the current collector **211** converge and are connected to form a

second gathering part **2212**. The first gathering part **2211** connects the second gathering part **2212** and the active substance-coated part **21**.

[0101] In the above technical solution, the plurality of tab plates **2210** only converge (that is, get together in a direction toward each other) and gather but are not connected when forming the first gathering part **2211**, while the plurality of tab plates **2210** not only converge and gather but are also connected into an integrated structure when forming the second gathering part **2212**. For example, the plurality of tab plates **2210** may be connected into an integrated plate structure by welding (such as ultrasonic welding) to form the second gathering part **2212**. For example, the plurality of tab plates **2210** may also converge and be connected to form the second gathering part **2212** by conductive adhesive bonding, etc., which will not be described in detail herein.

[0102] It should be noted that in the embodiments of the present application, the tab plates **2210** are divided into positive electrode tab plates and negative electrode tab plates. The positive electrode tab plates that need to gather together are stacked together and ultrasonically pre-welded to form a second gathering part of the positive electrode, which can reduce the gap between layers and enable the plurality of fluffy positive electrode tab plates to form a plate structure of a certain rigidity. Similarly, the negative electrode tab plates that need to gather together are stacked together and ultrasonically pre-welded to form a second gathering part of the negative electrode, which can reduce the gap between layers and enable the plurality of fluffy negative electrode tab plates to form a plate structure of a certain rigidity.

[0103] In the above technical solution, the “parts of the plurality of tab plates **2210** proximal to the current collector **211** converge to form a first gathering part **2211**, and parts of the plurality of tab plates **2210** distal to the current collector **211** converge and are connected to form a second gathering part **2212**” is intended to illustrate that: in the extension direction of the tab plates **2210**, the first gathering part **2211** and the second gathering part **2212** are sequentially arranged in a direction away from the current collector **211**, and the specific positions of the first gathering part **2211** and the second gathering part **2212** are not limited, that is, it is not required how close the first gathering part **2211** is to the current collector **211**, or how far the second gathering part **2212** is from the current collector **211**. In some optional examples, the current collector **211** and the tab plates **2210** may be an integrated member, such as an integrally formed aluminum foil for the positive electrode plates, and an integrally formed copper foil for the negative electrode plates.

[0104] In some optional examples, referring to FIG. 7 again, the conductive part **22** is formed by the tab part **221**, and at least a part of the second gathering part **2212** passes through the perforation **12221** and is received in the cavity **123**. In the above technical solution, since the tab part **221** includes the second gathering part **2212** formed by converging and connecting the plurality of tab plates **2210**, at least a part of the second gathering part **2212** can pass through the perforation **12221** and be received in the cavity **123**, and the conductive part **22** can be simplified in construction and processing.

[0105] In other optional examples, referring to FIG. 8, FIG. 8 is a partial cross-sectional view of a battery cell according to some embodiments of the present application. The conductive part **22** includes the tab part **221** and an adapting piece **222**, at least a part of the adapting piece **222** passes through the perforation **12221** and is received in the cavity **123**, and the adapting piece **222** is connected between the second gathering part **2212** and the first connecting part **1222**. In the above technical solution, since the conductive part **22** includes the tab part **221** and the adapting piece **222**, the adapting piece **222** can pass through the perforation **12221**, such that the operation is convenient. Besides, by using the adapting piece **222** to achieve an indirect electrical connection between the second gathering part **2212** and the first connecting part **1222**, the adapting piece **222** can be connected to the first connecting part **1222** at a part avoiding the second gathering part **2212**, such that the welding between the adapting piece **222** and the first connecting part **1222** is firm, welding cracks are unlikely to occur, and the reliability and stability of the battery cell **10** can be further improved.

[0106] Referring to FIGS. 7 and 11-14, FIG. 11 is a three-dimensional view of the first post terminal **12** according to some embodiments of the present application, FIG. 12 is an orthographic projection view of the battery cell **10** shown in FIG. 11, FIG. 13 is a cross-sectional view along the line C-C in FIG. 12, and FIG. 14 is a cross-sectional view along the line D-D in FIG. 12. In some embodiments of the present application, the second post terminal part **122** further includes a second connecting part **1224** provided in the mounting hole **111** in a penetrating manner, the second connecting part **1224** is formed in an annular structure disposed around an inner wall of the mounting hole **111**, the first connecting part **1222** is disposed in an annular region of the second connecting part **1224** and connected to an inner end part of the second connecting part **1224** proximal to the active substance-coated part **21**, the second connecting part **1224** and the first connecting part **1222** jointly define the cavity **123** in an enclosing manner, the cavity **123** is open in a direction away from the active substance-coated part **21**, a perforation **12221** that is in communication with the cavity **123** is formed on the first connecting part **1222**, and the conductive part **22** partially passes through the perforation **12221** and is received in the cavity **123**.

[0107] The shape of the second connecting part **1224** is configured in an annular structure matching the shape of the mounting hole **111**. Here, it should be noted that the annular structure described in the present application is not limited to a circular ring shape, but may also be, for example, a rectangular ring shape, a racetrack ring shape, or an elliptical ring shape.

[0108] In the above technical solution, the second post terminal part **122** includes the second connecting part **1224** provided in the mounting hole **111** in a penetrating manner, which facilitates the assembly of the second post terminal part **122** and the housing **11**. Besides, the second connecting part **1224** of the annular structure and the first connecting part **1222** connected to the inner end part of the second connecting part **1224** jointly define the cavity **123**, such that the structure of the second post terminal part **122** can be simplified, and the receiving volume of the cavity **123** can be increased. Moreover, since the cavity **123** is open in the direction away from the active substance-coated part **21**, the conductive part **22** partially extends into the cavity **123** through the perforation **12221** on the first connecting part **1222**, which is conducive to connecting the conductive part **22** to the first connecting part **1222** from the outside of the housing **11**, and facilitates the manufacture of the battery cell **10**.

[0109] It is worth noting that the number, position, shape, and the like of the perforation **12221** are not limited. For example, one or at least two perforations may be formed, the perforation may for example be located at the center or the edge of the first connecting part **1222**, and the perforation may for example be rectangular, oblong, or elliptical.

[0110] Referring to FIG. 7 again, in some embodiments of the present application, the first post terminal part **121** is located outside the housing **11** and is an annular structure, the second post terminal part **122** includes a second connecting part **1224** provided in the mounting hole **111** in a penetrating manner, the second connecting part **1224** is formed in an annular structure disposed around the inner wall of the mounting hole **111**, and an end of the second connecting part **1224** distal to the active substance-coated part **21** extends to be connected to an inner peripheral part **12111** of the first post terminal part **121**. It can be understood that when the first post terminal part **121** includes the annular first stopper part **1211**, an inner end of the first stopper part **1211** forms the inner peripheral part **12111** of the first post terminal part **121**.

[0111] In the above technical solution, the first post terminal part **121** is located outside the housing **11** and is an annular structure, and the second connecting part **1224** is formed in an annular structure disposed around the inner wall of the mounting hole **111** and an outer end part **12241** of the second connecting part can extend to the inner peripheral part **12111** of the first post terminal part **121**, such that the construction of the first post terminal **12** can be simplified, the number of parts can be reduced, and the processing and production efficiency can be improved. Besides, since both the first post terminal part **121** and the second connecting part **1224** are annular structures, operations, such as welding, can be performed on the first post terminal part **121** and the second

connecting part **1224** from the outside of the housing **11** and at the inner periphery of the first post terminal part **121**, thereby improving the welding reliability and reducing the difficulty of welding. [0112] It is worth noting that the connection mode of the first post terminal part **121** and the second post terminal part **122** is not limited, and may be, for example, welding, or bonding. In addition, in other embodiments of the present application, the first post terminal part **121** and the second post terminal part **122** may also be indirectly connected. For example, the first post terminal **12** may further include a separately machined third post terminal part (not shown), the third post terminal part is provided in the mounting hole **111** in a penetrating manner, an outer end of the third post terminal part is welded to the first post terminal part **121**, an inner end of the third post terminal part is welded to the second post terminal part **122**, and the like.

[0113] In addition, in other embodiments of the present application, the first post terminal part **121** may not be configured in an annular structure located outside the housing **11**. For example, referring to FIG. **9** again, the first post terminal part **121** may be a solid cover plate structure, and in this case, the first post terminal part **121** and the second post terminal part **122** may be laser welded from the outside or the inside of the housing **11**. Alternatively, for another example, the first post terminal part **121** may be arranged to include a third connecting part (not shown) provided in the mounting hole **111** in a penetrating manner, and in this case, the second post terminal part **122** may be located inside the housing **11**, and the third connecting part extends to the second post terminal part **122** in a direction close to the active substance-coated part **21** and is welded to the second post terminal part **122**.

[0114] When “an end of the second connecting part **1224** distal to the active substance-coated part **21** extends to and is connected to the inner peripheral part **12111** of the first post terminal part **121**”, referring to FIG. **10** again, in some optional embodiments, the end of the second connecting part **1224** distal to the active substance-coated part **21** is the outer end part **12241**, and the outer end part **12241** extends to a side of the inner peripheral part **12111** proximal to the central axis of the mounting hole **111**. That is, in the radial direction of the mounting hole **111**, the outer end part **12241** is disposed proximal to the central axis of the mounting hole **111** relative to the inner peripheral part **12111**. An inner side surface **S12** of the inner peripheral part **12111** is disposed face to face with and connected to an outer side surface **S22** of the outer end part **12241** by welding, where the inner side surface **S12** of the inner peripheral part **12111** is a side surface of the inner peripheral part **12111** facing the central axis of the mounting hole **111**, and the outer side surface **S22** of the outer end part **12241** is a side surface of the outer end part **12241** distal to the central axis of the mounting hole **111**. Therefore, a weld seam between the inner side surface **S12** of the inner peripheral part **12111** and the outer side surface **S22** of the outer end part **12241** can be located at an outer surface of the first post terminal **12** distal to the active substance-coated part **21**, thereby facilitating welding from the outside of the housing **11**, reducing the difficulty of welding, and improving the welding yield.

[0115] Referring to FIG. **10** again, in some embodiments of the present application, the housing assembly **1** further includes a post terminal cover plate **13** located outside the housing **11** and lidding the first post terminal part **121**, a clearance groove **131** is formed on the post terminal cover plate **13**, and the clearance groove **131** corresponds to a welding position of the outer end part **12241** and the inner peripheral part **12111** for accommodating a weld mark. That is, the weld mark formed by welding the outer end part **12241** and the inner peripheral part **12111** can be at least partially accommodated in the clearance groove **131**, such that the problem of interference between the weld mark and the post terminal cover plate **13** can be mitigated, such that the post terminal cover plate **13** can still be assembled smoothly with the first post terminal part **121** after the outer end part **12241** is welded to the inner peripheral part **12111**, thereby improving the compactness and the reliability of the connection between the post terminal cover plate **13** and the first post terminal part **121**.

[0116] Illustratively, the inner peripheral part **12111** and the outer end part **12241** may be laser

welded, and a welding mark may be formed at the welding position, which may protrude from the surface of the welding position. The clearance groove **131** disposed at a position of the post terminal cover plate **13** corresponding to the weld mark for accommodating the weld mark can mitigate the interference caused by the weld mark to the mounting of the post terminal cover plate **13**, improve the compactness of fit between the post terminal cover plate **13** and the first post terminal part **121**, and improve the reliability of the connection between the post terminal cover plate **13** and the first post terminal part **121**.

[0117] The connection mode of the first post terminal part **121** and the post terminal cover plate **13** is not limited, and may be, for example, welding, bonding, or flanging and buckling. The first post terminal part **121** is lidded with the post terminal cover plate **13**, which can mitigate the problem that the electrolytic solution and the like flow out from the annular region of the first post terminal part **121**, and achieve a sealing effect.

[0118] Illustratively, as shown in FIG. 7, the first post terminal part **121** further includes an extending part **1212**, the extending part **1212** may extend, in a direction away from the first stopper part **1211**, from an end surface of the outer peripheral part **12112** of the first stopper part **1211** on a side distal to the housing **11**, such that the first post terminal part **121** may have a groove **125** formed between the extending part **1212** and the first stopper part **1211**, and the post terminal cover plate **13** may be embedded in the groove **125**. Therefore, the assembly efficiency, connection reliability, and fit compactness of the post terminal cover plate **13** and the first post terminal part **121** can be improved.

[0119] In addition, the post terminal cover plate **13** may be made of a conductive material, such that the post terminal cover plate **13** is electrically connected to the first post terminal part **121**, and the busbar component can be welded to the post terminal cover plate **13**, which allows to electrically connect the first post terminal **12** to the busbar component through the post terminal cover plate **13**. When the first post terminal part **121** and the busbar component are made of the same material, the post terminal cover plate **13** may be provided as an integral cover plate and made of the same material as the busbar component. When the first post terminal part **121** and the busbar component are made of different materials, the post terminal cover plate **13** may be provided as a composite cover plate formed by combining two parts, one of which is made of the same material as the busbar component for welding and the other made of the same material as the first post terminal part **121** for welding.

[0120] Illustratively, referring to FIG. 10, the depth **Z1** of the clearance groove **131** may be greater than or equal to 0.2 mm, such that after the first post terminal part **121** is welded to the second post terminal part **122**, the post terminal cover plate **13** can effectively avoid the weld mark so as to be smoothly mounted to the first post terminal part **121**. In addition, the depth **Z1** of the clearance groove **131** may be further set to be less than or equal to 0.4 mm to avoid an excessively large depth of the clearance groove **131**, which is conducive to increasing the thickness of the post terminal cover plate **13** at the corresponding clearance groove **131**, thereby increasing the structural strength and current conveyance efficiency of the post terminal cover plate **13** at the local position.

[0121] Illustratively, referring to FIG. 10, the post terminal cover plate **13** includes an embedded part **132** extending to the annular region of the second connecting part **1224**, and an outer peripheral surface **1321** of the embedded part **132** is spaced apart from an inner side surface **S23** of the outer end part **12241** to form a first gap **14**. Specifically, since the inner peripheral part **12111** of the first post terminal part **121** is welded to the outer end part **12241** of the second post terminal part **122**, the annular size of the second connecting part **1224** may be reduced, such that the embedded part **132** cannot extend into the annular region of the second connecting part **1224**. However, in the present application, the first gap **14** is provided between the outer peripheral surface **1321** of the embedded part **132** and the inner side surface **S23** of the outer end part **12241**, such that after the first post terminal part **121** is welded to the second post terminal part **122**, the annular region of the second connecting part **1224** still has a space for the embedded part **132** to

extend to, thereby ensuring that the post terminal cover plate **13** can be smoothly mounted to the first post terminal part **121** subsequently.

[0122] Illustratively, referring to FIG. **10**, the size **Z2** of the first gap **14** may be greater than or equal to 0.2 mm, such that after the first post terminal part **121** is welded to the second post terminal part **122**, the annular region of the second connecting part **1224** may have a sufficient space for the embedded part **132** to extend to, thereby improving the smoothness of mounting the post terminal cover plate **13** to the first post terminal part **121**. In addition, the size **Z2** of the first gap **14** may be further set to be less than or equal to 0.4 mm to avoid an excessively large first gap **14**, which is conducive to increasing the volume of the embedded part **132** as much as possible, thereby reducing the resistance and improving the current conveyance efficiency.

[0123] The present application is not limited to this, and there may be other optional embodiments when “an end of the second connecting part **1224** distal to the active substance-coated part **21** extends to and is connected to the inner peripheral part **12111** of the first post terminal part **121**”. For example, referring to FIG. **15**, FIG. **15** is a partial cross-sectional view of the battery cell **10** according to some embodiments of the present application. The end of the second connecting part **1224** distal to the active substance-coated part **21** is the outer end part **12241**, the inner peripheral part **12111** of the first post terminal part **121** abuts against a side of the outer end part **12241** distal to the active substance-coated part **21**. That is, in the axial direction of the mounting hole **111**, the inner peripheral part **12111** is disposed distal to the active substance-coated part **21** relative to the outer end part **12241**, and the inner end surface **S11** of the inner peripheral part **12111** is disposed face to face with and connected to the outer end surface **S21** of the outer end part **12241** by welding, where the inner end surface **S11** of the inner peripheral part **12111** is an end surface of the inner peripheral part **12111** on a side facing the active substance-coated part **21**, and the outer end surface **S21** of the outer end part **12241** is an end surface of the outer end part **12241** on a side distal to the active substance-coated part **21**.

[0124] Therefore, the welding head can extend into the annular region of the first post terminal part **121** and the annular region of the second connecting part **1224** for welding. The flatness of the outer surface of the first post terminal **12** distal to the active substance-coated part **21** is slightly affected by the weld mark formed after welding, which is conducive to the subsequent welding of the first post terminal **12** and the post terminal cover plate **13** or the busbar component.

[0125] Illustratively, referring to FIG. **15** again, the housing assembly **1** further includes a post terminal cover plate **13** located outside the housing **11** and lidding the first post terminal part **121**, the post terminal cover plate **13** is partially embedded in an annular region of the inner peripheral part **12111**, and the post terminal cover plate **13** is spaced apart from the inner peripheral part **12111** to form a second gap **15**.

[0126] Specifically, after the inner peripheral part **12111** of the first post terminal part **121** is welded to the outer end part **12241** of the second post terminal part **122**, the weld seams formed at the annular region of the first post terminal part **121** and the annular region of the second connecting part **1224** may protrude in the radial direction, and the inner peripheral part **12111** is likely to protrude in a direction away from the active substance-coated part **21**. The second gaps **15** separately provided at these two positions can ensure that the post terminal cover plate **13** can be smoothly assembled with the first post terminal part **121** after the first post terminal part **121** is welded to the second post terminal part **122**. Therefore, in the above technical solution, by providing the second gap **15** between the post terminal cover plate **13** and the inner peripheral part **12111**, the post terminal cover plate **13** can be ensured to be smoothly mounted after the first post terminal part **121** is welded to the second post terminal part **122**, thereby improving the compactness and the reliability of the connection between the post terminal cover plate **13** and the first post terminal part **121**.

[0127] In some embodiments of the present application, the first post terminal part **121** is connected to the second post terminal part **122** by welding. Therefore, the first post terminal **12** is

simple in construction and can be easily mounted to the housing **11**, which is conducive to reducing the production cost and improving the assembly efficiency.

[0128] Referring to FIG. **16**, FIG. **16** is a partial cross-sectional view of the battery cell **10** according to some embodiments of the present application. Illustratively, when the first post terminal part **121** is connected to the second post terminal part **122** by welding, the first post terminal **12** is provided with a recess **124** at a welding position of the first post terminal part **121** and the second post terminal part **122**, and the recess **124** is configured to accommodate a weld mark formed by welding the first post terminal part **121** and the second post terminal part **122**. Therefore, the problem that the weld mark protrudes from the surface of the welding position, which may affect the subsequent assembly of other parts, such as the post terminal cover plate **13**, with the first post terminal **12**, can be mitigated.

[0129] Referring to FIGS. **4** and **7** again, in some embodiments of the present application, the housing assembly **1** further includes an insulating seal assembly **16**, the insulating seal assembly **16** connects the housing **11** and the first post terminal **12** in an insulating manner, the insulating seal assembly **16** includes an insulating member **161** and an insulating sealing member **162** with stronger heat resistance than the insulating member **161**, and the insulating sealing member **162** is located between the welding position of the first post terminal part **121** and the second post terminal part **122** and the housing **11**.

[0130] The insulating seal assembly **16** is fitted between the housing **11** and the first post terminal **12**, such that the housing **11** and the first post terminal **12** are insulated from each other. The insulating seal assembly **16** includes the insulating member **161** and the insulating sealing member **162**. The insulating sealing member **162** has a sealing function in addition to an insulating function as compared to the insulating member **161**, and the insulating sealing member **162** has stronger heat resistance than the insulating member **161**.

[0131] In the above technical solution, the insulating seal assembly **16** is arranged to include the insulating member **161** with relatively weak heat resistance and the insulating sealing member **162** with sealing performance and relatively strong heat resistance, the insulating sealing member **162** is disposed between the welding position of the first post terminal part **121** and the second post terminal part **122** and the housing **11**, and the insulating member **161** is disposed distal to the welding position of the first post terminal part **121** and the second post terminal part **122** relative to the insulating sealing member **162**, such that the influence of the welding temperature on the insulating member **161** can be reduced by utilizing the insulating sealing member **162**, and further, the cost of the insulating seal assembly **16** can be reduced while the insulating sealing effect is ensured.

[0132] Illustratively, the insulating member **161** may be made of plastic with a temperature tolerance of about 250° C., and the insulating sealing member **162** may be made of rubber with a temperature tolerance of about 400° C. Therefore, the cost can be lowered, good insulation and sealing effects can be ensured, and the insulating sealing member **162** can effectively reduce the influence of the welding temperature on the insulating member **161**.

[0133] Referring to FIG. **7** again, in some embodiments of the present application, the welding position of the first post terminal part **121** and the second post terminal part **122** is located at an outer side of the mounting hole **111**, the insulating member **161** includes an outer insulating member **1611** and an inner insulating member **1612**, the outer insulating member **1611** is sandwiched between the first post terminal part **121** and an outer wall of the housing **11**, the inner insulating member **1612** is sandwiched between the second post terminal part **122** and an inner wall of the housing **11**, the insulating sealing member **162** includes an inner segment **1622** and an outer segment **1621**, the inner segment **1622** extends inside the mounting hole **111**, and the inner segment **1622** abuts against the first post terminal part **121** and the inner insulating member **1612** separately at two ends in the axial direction of the mounting hole **111**, and the outer segment **1621** extends at the outer side of the mounting hole **111**, and the outer segment **1621** is connected to the inner

segment **1622** at a radial inner end and abuts against the outer insulating member **1611** at a radial outer end in the radial direction of the mounting hole **111**.

[0134] Therefore, the assembly of the insulating seal assembly **16** is convenient, and due to the structural distribution position of the insulating sealing member **162**, both the inner insulating member **1612** and the outer insulating member **1611** can well obtain heat insulation protection of the sealing insulating member **161**. Moreover, the arrangement of the insulating sealing member **162** achieves a good sealing effect while ensuring low volume costs.

[0135] Certainly, the present application is not limited to this. For example, in other optional embodiments of the present application, the volume of the insulating sealing member **162** may be increased, and the inner segment **1622** of the insulating sealing member **162** abuts against the first post terminal part **121** and the second post terminal part **122** separately at two ends in the axial direction of the mounting hole **111**, and the inner insulating member **1612** abuts against a side of the inner segment **1622** distal to the central axis of the mounting hole **111** (the embodiment is not shown in the drawings).

[0136] Referring to FIGS. **3-7** and **11-14** again, the battery cell **10** according to specific embodiments of the present application is described.

[0137] The battery cell **10** includes a housing assembly **1** and a battery cell assembly **2**. The housing assembly **1** includes a housing **11**, the housing **11** includes a housing body **112** and a bottom cover **113**, a positive electrode post terminal and a negative electrode post terminal are provided on a side of the housing body **112** distal to the bottom cover **113**, both the positive electrode post terminal and the negative electrode post terminal are first post terminals **12**, and the first post terminal **12** is provided in a mounting hole **111** on the housing body **112** in a penetrating manner. The battery cell assembly **2** includes an active substance-coated part **21** and a conductive part **22**, where the active substance-coated part **21** is wrapped with an insulating film **17** and is disposed in the housing **11**, and the conductive part **22** electrically connects the active substance-coated part **21** and the first post terminal **12**.

[0138] The first post terminal **12** includes a first post terminal part **121** and a second post terminal part **122** that are separately formed, the second post terminal part **122** has a hardness greater than that of the first post terminal part **121**, at least a part of the first post terminal part **121** is stopped outside the housing **11**, and at least a part of the second post terminal part **122** is stopped inside the housing **11**. The second post terminal part **122** includes a first connecting part **1222** and a second connecting part **1224**, the second connecting part **1224** is provided in the mounting hole **111** in a penetrating manner, and the second connecting part **1224** is formed in an annular structure disposed around an inner wall of the mounting hole **111**. The first connecting part **1222** is disposed in an annular region of the second connecting part **1224** and is connected to an inner end part of the second connecting part **1224** proximal to the active substance-coated part **21**, a cavity **123** open in a direction away from the active substance-coated part **21** is defined between the second connecting part **1224** and the first connecting part **1222**, a perforation **12221** is formed on the first connecting part **1222**, and the conductive part **22** partially passes through the perforation **12221** and is received in the cavity **123** and is connected to the first connecting part **1222**.

[0139] The first post terminal part **121** is located outside the housing **11** and is an annular structure, an end of the second connecting part **1224** distal to the active substance-coated part **21** is an outer end part **12241**, the outer end part **12241** extends to a side of the inner peripheral part **12111** proximal to the central axis of the mounting hole **111**, and an inner side surface **S12** of the inner peripheral part **12111** facing the central axis of the mounting hole **111** is welded to an outer side surface **S22** of the outer end part **12241** distal to the central axis of the mounting hole **111**.

[0140] The housing assembly **1** further includes a post terminal cover plate **13** lidding the first post terminal part **121** and an insulating seal assembly **16** connecting the housing **11** and the first post terminal **12** in an insulating manner, where a clearance groove **131** is formed on the post terminal cover plate **13**, the clearance groove **131** corresponds to a welding position of the outer end part

12241 and the inner peripheral part **12111** for accommodating a weld mark, the post terminal cover plate **13** includes an embedded part **132** extending to the annular region of the second connecting part **1224**, a first gap **14** is provided between an outer peripheral surface **1321** of the embedded part **132** and an inner side surface **S23** of the outer end part **12241**, the insulating seal assembly **16** includes an insulating member **161** and an insulating sealing member **162** with stronger heat resistance than the insulating member **161**, and the insulating sealing member **162** is located between a welding position of the first post terminal part **121** and the second post terminal part **122** and the housing **11**.

[0141] In the above technical solution, since the first connecting part **1222** and the cavity **123** are liable to deformation due to the difficulty in obtaining reliable support from the housing **11**, in the present application, the first post terminal **12** is arranged to include the first post terminal part **121** and the second post terminal part **122** that are separately formed, and the hardness of the second post terminal part **122** is set to be greater than that of the first post terminal part **121**, such that the deformation of the first connecting part **1222** can be reduced to a certain extent, the connection reliability between the first connecting part **1222** and the conductive part **22** can be improved, and the conductive yield can be improved. Besides, the first post terminal part **121** of relatively low hardness is conducive to improving the welding yield of the first post terminal part **121** and the post terminal cover plate **13**.

[0142] According to some embodiments of the present application, the present application further provides a battery **100**. The battery **100** includes the battery cell **10** according to any one of the above embodiments.

[0143] In the above technical solution, since the battery **100** is provided with the above battery cell **10**, and since the design of the battery cell **10** is diversified, the design diversity of the battery **100** can be improved.

[0144] According to some embodiments of the present application, the present application further provides an electric device **1000**. The electric device **1000** includes the battery **100** according to the above embodiments, and the battery **100** is configured to provide electric energy for the electric device **1000**.

[0145] In the above technical solution, since the electric device **1000** is provided with the above battery **100**, and since the battery **100** can have diversified designs, different batteries **100** can be flexibly designed according to the actual requirements of the electric device **1000**, and the power supply requirements for the electric device **1000** can be optimized.

[0146] It should be noted that the embodiments and features of the embodiments in the present application may be combined with each other without conflict.

[0147] The above are only preferred embodiments of the present application, and are not intended to limit the present application. For those skilled in the art, the present application can be modified and varied. Any modification, equivalent substitution, improvement, and the like made within the spirit and principle of the present application shall all fall within the protection scope of the present application.

Claims

1. A battery cell, comprising: a housing assembly comprising a housing and a first post terminal, wherein the housing is provided with a mounting hole, and the first post terminal is provided in the mounting hole in a penetrating manner; and a battery cell assembly comprising an active substance-coated part and a conductive part, wherein the active substance-coated part is disposed in the housing, and the conductive part electrically connects the active substance-coated part and the first post terminal, and wherein the first post terminal comprises a first post terminal part and a second post terminal part that are separately formed and connected to each other, at least a part of the first post terminal part is stopped outside the housing, at least a part of the second post terminal part is

stopped inside the housing, and the second post terminal part is connected to the conductive part.

2. The battery cell according to claim 1, wherein the second post terminal part comprises a first connecting part, the first post terminal has a cavity formed on a side of the first connecting part distal to and/or facing the active substance-coated part, at least a part of the conductive part is received in the cavity and connected to the first connecting part, and at least the first connecting part in the second post terminal part has a hardness greater than that of the first post terminal part.

3. The battery cell according to claim 2, wherein the second post terminal part further comprises a second connecting part provided in the mounting hole in a penetrating manner, the second connecting part is formed in an annular structure disposed around an inner wall of the mounting hole, the first connecting part is disposed in an annular region of the second connecting part and connected to an inner end part of the second connecting part proximal to the active substance-coated part, the second connecting part and the first connecting part jointly define the cavity in an enclosing manner, the cavity is open in a direction away from the active substance-coated part, a perforation that is in communication with the cavity is formed on the first connecting part, and the conductive part partially passes through the perforation and is received in the cavity.

4. The battery cell according to claim 3, wherein the perforation is formed at an edge position of the first connecting part that is connected to the second connecting part.

5. The battery cell according to claim 3, wherein the active substance-coated part comprises a current collector and an active substance layer disposed on the current collector, the conductive part comprises a tab part electrically connected to the current collector, the tab part comprises a plurality of tab plates, parts of the plurality of tab plates proximal to the current collector converge to form a first gathering part, parts of the plurality of tab plates distal to the current collector converge and are connected to form a second gathering part, and the first gathering part connects the second gathering part and the active substance-coated part, and wherein the conductive part is formed by the tab part, at least a part of the second gathering part passes through the perforation and is received in the cavity; or the conductive part comprises the tab part and an adapting piece, at least a part of the adapting piece passes through the perforation and is received in the cavity, and the adapting piece is connected between the second gathering part and the first connecting part.

6. The battery cell according to claim 1, wherein the first post terminal part is located outside the housing and is an annular structure, the second post terminal part comprises a second connecting part provided in the mounting hole in a penetrating manner, the second connecting part is formed in an annular structure disposed around the inner wall of the mounting hole, and an end of the second connecting part distal to the active substance-coated part extends to be connected to an inner peripheral part of the first post terminal part.

7. The battery cell according to claim 6, wherein an end part of the second connecting part distal to the active substance-coated part is an outer end part, the outer end part extends to a side of the inner peripheral part proximal to a central axis of the mounting hole, and an inner side surface of the inner peripheral part facing the central axis of the mounting hole is welded to an outer side surface of the outer end part distal to the central axis of the mounting hole.

8. The battery cell according to claim 7, wherein the housing assembly further comprises a post terminal cover plate located outside the housing and lidding the first post terminal part, a clearance groove is formed on the post terminal cover plate, and the clearance groove corresponds to a welding position of the outer end part and the inner peripheral part for accommodating a weld mark.

9. The battery cell according to claim 8, wherein the post terminal cover plate comprises an embedded part extending to the annular region of the second connecting part, and an outer peripheral surface of the embedded part is spaced apart from an inner side surface of the outer end part to form a first gap.

10. The battery cell according to claim 6, wherein an end part of the second connecting part distal to the active substance-coated part is an outer end part, the inner peripheral part abuts against a side

of the outer end part distal to the active substance-coated part, and an inner end surface of the inner peripheral part facing the active substance-coated part is welded to an outer end surface of the outer end part distal to the active substance-coated part.

11. The battery cell according to claim 10, wherein the housing assembly further comprises a post terminal cover plate located outside the housing and lidding the first post terminal part, the post terminal cover plate is partially embedded in an annular region of the inner peripheral part, and the post terminal cover plate is spaced apart from the inner peripheral part to form a second gap.

12. The battery cell according to claim 1, wherein the first post terminal part is connected to the second post terminal part by welding.

13. The battery cell according to claim 12, wherein the first post terminal is provided with a recess at a welding position of the first post terminal part and the second post terminal part, and the recess is configured to accommodate a weld mark formed by welding the first post terminal part and the second post terminal part.

14. The battery cell according to claim 12, wherein the housing assembly further comprises an insulating seal assembly, the insulating seal assembly connects the housing and the first post terminal in an insulating manner, the insulating seal assembly comprises an insulating member and an insulating sealing member with stronger heat resistance than the insulating member, and the insulating sealing member is located between the welding position of the first post terminal part and the second post terminal part and the housing.

15. The battery cell according to claim 14, wherein the welding position of the first post terminal part and the second post terminal part is located at an outer side of the mounting hole, the insulating member comprises an outer insulating member and an inner insulating member, the outer insulating member is sandwiched between the first post terminal part and an outer wall of the housing, the inner insulating member is sandwiched between the second post terminal part and an inner wall of the housing, the insulating sealing member comprises an inner segment and an outer segment, the inner segment extends inside the mounting hole and abuts against the first post terminal part and the inner insulating member separately at two ends in an axial direction of the mounting hole, and the outer segment extends at the outer side of the mounting hole and is connected to the inner segment at a radial inner end and abuts against the outer insulating member at a radial outer end in a radial direction of the mounting hole.

16. The battery cell according to claim 1, wherein the housing is provided with a plurality of post terminals, and at least one of the plurality of post terminals is the first post terminal.

17. A battery, comprising the battery cell according to claim 1.

18. An electric device, comprising the battery according to claim 17.
