

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12402714
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Lewis; Sarah et al.

Positionable carriable device strap

Abstract

A carriable device can include a body that includes a first side, a second, opposing side, a first strap mount on the first side, and a second strap mount socket on the second side; and a strap that includes an end attached to the body, an opposing end, and a coupling attached to the opposing end, where the coupling is connectable to the first strap mount and wherein the coupling is connectable to the second strap mount.

Inventors: Lewis; Sarah (Morrisville, NC), Young; Julia (Morrisville, NC), Ent; Ali (Morrisville, NC), Perelli; Thomas (Morrisville, NC)

Applicant: LENOVO (SINGAPORE) PTE. LTD. (Singapore, SG)

Family ID: 91029227

Assignee: Lenovo (Singapore) Pte. Ltd. (Singapore, SG)

Appl. No.: 17/987581

Filed: November 15, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20240156238 A1	May. 16, 2024

Publication Classification

Int. Cl.: A45F3/14 (20060101); A45F3/04 (20060101)

U.S. Cl.:

CPC A45F3/14 (20130101); A45F2003/142 (20130101)

Field of Classification Search

CPC: A45F (3/14); A45F (3/047); A45F (2003/142)

USPC: 224/153; 224/578; 224/579; 224/580; 224/183

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3254816	12/1965	Gray	224/630	A45F 3/04
4213549	12/1979	Hibbard	224/601	A45C 11/22
4273274	12/1980	Freistadt	150/108	A45F 3/04
4988216	12/1990	Lyman	383/110	A45C 11/20
5957354	12/1998	Mentken	224/601	A45F 3/04
6286461	12/2000	Martz	119/497	A01K 1/0254
6460746	12/2001	Amram	224/628	A45F 3/047
6622899	12/2002	Klindworth-Garron	224/625	A45F 3/02
7160028	12/2006	Linday	150/108	A45C 9/00
8092087	12/2011	Simhony	150/108	A45F 3/14
8590759	12/2012	Mooney	224/645	A45F 3/04
9303353	12/2015	Audet	N/A	D06F 95/002
10130161	12/2017	Kao	N/A	A45F 3/12
10230077	12/2018	Rief	N/A	H01M 50/247
10407216	12/2018	Glass	N/A	B65D 33/00
11470947	12/2021	Linday	N/A	A45C 9/00
2009/0101254	12/2008	Vaccarella	150/108	A45C 13/26
2009/0205759	12/2008	Vaccarella	150/108	A45C 13/02
2015/0129627	12/2014	Roberts	224/581	A45F 3/02
2021/0100340	12/2020	Chang	N/A	A45F 3/047
2021/0376658	12/2020	Marino	N/A	A45C 15/06

Primary Examiner: Newhouse; Nathan J

Assistant Examiner: Vanterpool; Lester L

Background/Summary

TECHNICAL FIELD

(1) Subject matter disclosed herein generally relates to carriable devices.

BACKGROUND

(2) Carriable devices can include one or more straps, for example, a bag may include a single strap and a backpack may include two straps.

SUMMARY

(3) A carriable device can include a body that includes a first side, a second, opposing side, a first strap mount on the first side, and a second strap mount socket on the second side; and a strap that includes an end attached to the body, an opposing end, and a coupling attached to the opposing end,

where the coupling is connectable to the first strap mount and wherein the coupling is connectable to the second strap mount. Various other apparatuses, systems, methods, etc., are also disclosed.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) Features and advantages of the described implementations can be more readily understood by reference to the following description taken in conjunction with examples of the accompanying drawings.

(2) FIG. 1 is a series of diagrams of an example of a carriable device;

(3) FIG. 2 is a diagram of an example of a carriable device;

(4) FIG. 3 is a diagram of an example of a carriable device;

(5) FIG. 4 is a diagram of an example of a carriable device and an example of a detachable bag;

(6) FIG. 5 is a diagram of an example of a carriable device;

(7) FIG. 6 is a diagram of an example of a carriable device;

(8) FIG. 7 is a diagram of an example of an assembly;

(9) FIG. 8 is a diagram of an example of an assembly;

(10) FIG. 9 is a diagram of an example of an assembly; and

(11) FIG. 10 is a diagram of an example of an assembly;

DETAILED DESCRIPTION

(12) The following description includes the best mode presently contemplated for practicing the described implementations. This description is not to be taken in a limiting sense, but rather is made merely for the purpose of describing general principles of various implementations. The scope of invention should be ascertained with reference to issued claims.

(13) As an example, a carriable device can include a body that includes a first side, a second, opposing side, a first strap mount on the first side, and a second strap mount on the second side; and a strap that includes an end attached to the body, an opposing end, and a coupling attached to the opposing end, where the coupling is connectable to the first strap mount and wherein the coupling is connectable to the second strap mount.

(14) As an example, a carriable device can include a body that includes a strap mount; and a strap that includes an end attached to the body, an opposing end, and a coupling attached to the opposing end, where the coupling is connectable to the strap mount, and where the opposing end of the strap is rotatable via the strap mount and the coupling.

(15) FIG. 1 shows an example of a carriable device **100** that includes a body **110** that includes a first side **102**, a second, opposing side **104**, a first strap mount **120** on the first side **102**, and a second strap mount **140** on the second side **104**; and a strap **210** that includes an end **213** attached to the body **110**, an opposing end **211**, and a coupling **310** attached to the opposing end **211**, where the coupling **310** is connectable to the first strap mount **120** and where the coupling **310** is connectable to the second strap mount **140**.

(16) As shown in FIG. 1, the carriable device **100** can include opposing sides **101** and **105** and opposing sides **103** and **107** where the sides **102** and **104** may be defined by the sides **101**, **103**, **105** and **107**. As shown, the body **110** can include an attachment point **130** where the end **213** of the strap **210** attaches to the body **110**. For example, the strap **210** may be stitched to the body **110**, glued to the body **110**, etc. As shown, the strap **210** can include two opposing sides **212** and **214** where the strap **210** may be relatively flat and pliable such that it can be twisted. The strap **210** may be shaped like a ribbon where a length of the strap **210** between the ends **211** and **213** may be longer than a side dimension or side dimensions of the body **110**. For example, the strap **210** can have a length that is longer than the side **101** and/or can have a length that is longer than the side **103**. As an example, the strap **210** may be made of a fabric material, a polymeric material and/or

one or more other suitable materials.

(17) As shown in FIG. 1, the strap **210** can be transitioned from the side **102** (see, e.g., upper left configuration) to the side **104** (see, e.g., lower right configuration). For example, the mount **310** can be disconnected from the strap mount **120** on the side **102** and then connected to the strap mount **140** on the side **104**. As shown, the attachment point **130** may be at a juncture between the sides **102** and **103** or, for example, may be on the side **102** close to the side **103** (e.g., closer to the side **103** than the side **107**) or, for example, may be on the side **103** and close to the side **102** (e.g., closer to the side **102** than the side **104**).

(18) As an example, the strap **210** may be of suitable width and/or length for ergonomic placement over a shoulder of a user. For example, the strap **210** may be a shoulder strap where the side **102** of the body **110** can be adjacent to a user's back or where the side **102** or **104** may be adjacent to a user's side (e.g., left side or right side). As an example, the strap **210** may be suitable as a hand carry strap such that the body **110** can hang from a user's hand adjacent to a user's right leg or left leg. As an example, the strap **210** may be made of a fabric material, a polymeric material and/or one or more other suitable materials. As an example, the strap **210** may include a cushion, which may be adjustable. For example, consider an adjustable cushion that can be positionable for cushioning against a user's front shoulder surface (see, e.g., upper left configuration) and positionable for cushioning against a user's top shoulder surface (see, e.g., lower right configuration).

(19) FIG. 1 also shows an example of a coupling **310**, which may be a single sided coupling or a double sided coupling. As shown, the coupling **310** can hold the strap **210** at or proximate to the end **211**, noting that the coupling **310** may be adjustable such as, for example, adjustable by being slidable along the strap **210**. In the example of FIG. 1, the coupling **310** includes a strap securing component **312** and one or more connector components **314** and **316** where, for example, the strap securing component **312** can secure the coupling **310** to the strap **210** and where the one or more connector components **314** and **316** can be connected to the body **110** via one of the strap mounts **120** and **140**.

(20) In the example of FIG. 1, a coordinate system is shown that includes an x-axis and a y-axis that may be defined along with a z-axis, which, for example, may be utilized to define a thickness of the body **110**. In the example of FIG. 1, the z-axis may define a position of the strap mounts **120** and **140**. For example, the strap mounts **120** and **140** may be symmetrically located. As an example, the strap mounts **120** and **140** may be not symmetrically located. In the example of FIG. 1, the body **110** includes a long dimension along the y-axis direction and a short dimension along the x-axis direction; noting that a body may be square (e.g., equal dimensions).

(21) In the example of FIG. 1, the strap **210** may be twistable such that it may be twisted, for example, by 180 degrees. For example, consider the coupling **310** as being a single sided coupling that can be oriented by twisting the strap **210** to fit either of the straps mounts **120** and **140**. As an example, the strap mounts **120** and **140** can be fixed to the body **110**.

(22) As an example, the body **110** and the strap **210** can be connected using a rotatable coupling and mount connection that allows for changing orientation of the body **110** and/or the strap **210**. For example, consider the two orientations shown in FIG. 1 where the strap **210** can be used to support the body **110** on a user's back and where the strap **210** can be used to support the body **110** along a user's side. The rotatable coupling and mount connection can provide for locking, unlocking and relocking such that the coupling **310** can be connected to the mount **120** or the mount **140**. Such an approach can provide the carriable device **100** with flexibility as to how a user may wish to orient and carry it.

(23) As an example, a body may be a bag, a backpack, a container, a case, an electronic device, etc. For example, as to a case, consider a tablet computing device case, a smartphone case, a notebook computing device case, etc. As an example, a case can include a strap that can be a carrying strap that may form a loop with respect to points on the case where one of the points can include a mount

for connection with a coupling of the strap where the mount and coupling allow for rotation such that the strap may be oriented in a desired direction, for example, to facilitate a particular type of carrying (e.g., by hand, over a shoulder, etc.). In such an example, through rotation of the strap at an attachment point via a mount and a coupling, the strap may be adjustable for carrying in one or more manners without disconnecting the coupling from the mount. For example, a carriable device may include a mount on a single side that provides for connection to a coupling of a strap for rotation of the strap. As an example, in FIG. 1, the body **110** may include a single mount on a single side where the mount and the coupling **310** allow for rotation of the strap **210** at the end **211**. (24) FIG. 2 shows an example of a carriable device **1000** that includes a body **1010** and two straps **1210** and **1250**. In the example of FIG. 2, the strap **1210** includes a coupling **1310** that can connect to a mount **1020** of the body **1010**. In such a configuration, the straps **1210** and **1250** can be backpack straps for carrying the body **1010**.

(25) As shown in FIG. 2, the body **1010** includes a back side **1002**, a front side **1004**, a top side **1001**, a bottom side **1005** and opposing lateral sides **1003** and **1007**. As shown, the coupling **1310** is on the back side **1002**, closer to the top side **1001** than the bottom side **1005** and closer to the side **1003** than the side **1007**. Using backpack terminology, the strap **1210** may be referred to as a left shoulder strap where the side **1003** is a left side and the strap **1250** may be referred to as a right shoulder strap where the side **1007** is a right side.

(26) In the example of FIG. 2, the strap **1210** includes ends **1211** and **1213** and sides **1212** and **1214** where an adjustment mechanism such as a buckle **1215** may be positioned along the strap **1210**, noting that the strap **1210** may be a multi-piece strap where the pieces join via the buckle **1215**. As shown, the body **1010** includes an attachment point **1030** for the end **1213** of the strap **1210**. As to the strap **1250**, in the example of FIG. 2, it includes opposing ends **1251** and **1253** and sides **1252** and **1254** where an adjustment mechanism such as a buckle **1255** may be positioned along the strap **1250**, noting that the strap **1250** may be a multi-piece strap where the pieces join via the buckle **1255**. As shown, the body **1010** includes an attachment point **1051** for the end **1251** of the strap **1250** and an attachment point **1053** for the end **1253** of the strap **1250**. In the example of FIG. 2, the attachment point **1030** is closer to the side **1003** than the side **1007** and closer to the bottom side **1005** than the top side **1001** and the attachment point **1053** is closer to the side **1007** than the side **1003** and closer to the bottom side **1005** than the top side **1001**; noting that the attachment point **1051** is closer to the side **1007** than the side **1003** and closer to the top side **1001** than the bottom side **1005**.

(27) In the example of FIG. 2, the carriable device **1000** can include a front side flap **1044** and, for example, a detachable bag **1400**, which may include a coupling **1483** that connects to a mount **1083** of the body **1010** (e.g., on the side **1003** of the body **1010**).

(28) FIG. 3 shows an example of the carriable device **1000** where the flap **1044** extends downwardly from the top side **1001** and may optionally include a zipper **1045** for an internal compartment. As shown, the flap **1044** may include a hook **1049** that can be utilized to keep the flap **1044** closed, for example, by connecting with a feature or features of the bag **1400**. As shown, the bag **1400** can include another coupling **1487** that connects to another mount **1087** of the body **1010** (e.g., on the side **1007** of the body **1010**).

(29) FIG. 4 shows an example of the carriable device **1000** where the bag **1400** is removed from the body **1010** and where the coupling **1310** is disconnected from the mount **1020** on the back side **1002** of the body **1010**.

(30) FIG. 5 shows an example of the carriable device **1000** where the body **1010** includes a mount **1040** on the front side **1004** of the body **1010**. As shown, the front side **1004** of the body **1010** may include one or more zippers **1014** and **1016** for closing and opening one or more compartments (e.g., pockets, etc.) and may include a connector **1019** for connecting the hook **1049** of the flap **1044** to secure the flap **1044** in a closed position on the front side **1004** of the body **1010**. As shown in the example of FIG. 5, the flap **1044** can be lifted to reveal the mount **1040** on the front side

1004 of the body **1010** such that the coupling **1310** can be connected to the mount **1040**. In such an example, the mount **1020** can be a first mount and the mount **1040** can be a second mount where the mounts **1020** and **1040** can be on opposite sides of the body **1010**.

(31) As an example, the flap **1044**, if present, may be lifted to reveal an opening to an interior space of the body **1010** or other access feature (e.g., a zipper, etc.) that provides access to an interior space of the body **1010**. The body **1010** can include an interior space that may be a single space or a compartmentalized space. As an example, the interior space may be sufficient to receive one or more of books, items of clothing, a notebook computer, a tablet computer, etc.

(32) FIG. 6 shows an example of the carriable device **1000** in an orientation that differs from the orientation of the carriable device **1000** of FIG. 2. As explained, a carriable device can include mounts and a strap with a coupling where the coupling can be selectably connected to one of the mounts to provide a first configuration of the carriable device and selectably connected to the other one of the mounts to provide a second configuration of the carriable device.

(33) In the example of FIG. 6, the strap **1210** can be a shoulder strap where the body **1010** can be carried along a side of a person (e.g., a left side or a right side), rather than on a person's back (e.g., a back side). In the example of FIG. 6, the flap **1044** is shown as being closed and secured by the hook **1049** and the connector **1019** on the front side **1004** of the body **1010**. In such an example, the flap **1044** may remain closed under the force of gravity. As an example, one or more types of mechanisms may be utilized to secure the flap **1044**, if present. For example, consider hook material and loop material (e.g., VELCRO material). As shown in the example of FIG. 6, the flap **1044**, if present, may help to maintain an orientation of the strap **1210**. For example, the flap **1044** may help to maintain the strap **1210** as being substantially flat and parallel to the side **1004**, which may help to reduce risk of undesirable twisting of the strap **1210** (e.g., when the body **1010** is being carried by the strap **1210**). In such an example, the body **1010** may be more stably carried.

(34) As an example, the carriable device **1000** can be a hybrid bag that can be configured as a backpack and as a side bag. As an example, the configurations may be made using at least two instances of a locking rotatable mount and coupling mechanism. As explained, a carriable device can be a backpack with or without an auxiliary bag and can be changed in orientation creating a messenger bag (e.g., a side bag). A locking rotatable mount and coupling mechanism can allow a strap to be properly oriented in a selected configuration, which may be, for example, a vertical orientation or a horizontal orientation of a carriable device. In a vertical orientation, a long dimension may be oriented substantially along the direction of gravity while, in a horizontal orientation, a long dimension may be oriented substantially orthogonal to the direction of gravity.

(35) As an example, a carriable device can include a backpack orientation mount and a side bag orientation mount where the mounts can be on opposite sides of the carriable device. In such an example, the mounts can both be on a common half of the carriable device, as may be defined by a mid-point of a long dimension of the carriable device. While various examples show such a common half as being a top half of a backpack orientation, as an example, a common half may be a bottom half of a backpack orientation.

(36) FIG. 7 shows an example of an assembly **3000** that includes examples of mount and coupling features. As an example, one or more of the mount **120**, the mount **140**, the coupling **310**, the mount **1020**, the mount **1040**, and the coupling **1310** may include one or more features of the assembly **3000**. FIG. 7 also shows an example of a cylindrical coordinate system with a z-axis and a radial, r-axis. One or more features of the assembly **3000** may be defined with respect to one or more coordinate systems.

(37) The assembly **3000** can be a locking rotatable assembly that can function to rotate and can function to lock and unlock. Such functions can provide for changing an orientation of a carriable device by changing an anchor point for a strap of the carriable device.

(38) In the example of FIG. 7, the assembly **3000** can include a body material **3001** of a body and a strap material **3002** of a strap. As shown, the body material **3001** can be clamped between plates

3040 and **3070**, which may be interlocking components such as rivet components. A rivet may be formed by pressing or hammering a washer or disk onto a stud that extends through a material. For example, the plate **3040** can act as a stud while the plate **3070** can act as a washer or disk. As shown, the plate **3040** can be hat shaped where a portion extends through an opening of the material **3001** where the plate **3070** can be pressed onto that portion to form a secure, mount at a fixed location on the material **3001**.

(39) As an example, the plate **3070** can include a raised cylindrical portion that may be a race or seat for one or more rotating mechanisms. For example, consider a bearing assembly **3030** that can include an outer race for rolling elements where the raised cylindrical portion of the plate **3070** is an inner race for the rolling elements (e.g., ball bearings). In such an example, a plate **3020** can be rotatable via the bearing assembly **3030**.

(40) As shown in the example of FIG. 7, the plate **3020** can be utilized in combination with a plate **3050** to secure the strap material **3002**. The plates **3020** and **3050** may be interlocking components such as rivet components. For example, the plate **3050** can act as a stud while the plate **3020** can act as a washer or disk. As shown, the plate **3050** can be hat shaped where a portion extends through an opening the material **3002** where that portion of the plate **3050** can be pressed onto the plate **3020**, which may include a recess such as a washer type of recess to form a secure, mount at a fixed location on the material **3002**.

(41) In the example of FIG. 7, the assembly **3000** may include a latch **3060**. For example, consider a tool-less latch that can be operated by a user by pressing two latch levers toward each other using two fingers (e.g., a thumb and a forefinger). In such an example, the latch **3060** can provide for release of the plate **3020** from the bearing assembly **3030** such that the plates **3020** and **3050** that secure the strap material **3002** can be detached from the bearing assembly **3030** and the plates **3040** and **3070** that secure the body material **3001**. As an example, a latch may operate utilizing one or more key and keyway features. For example, the latch **3060** may include keys that can be received in one or more keyways of the bearing assembly **3030** and/or one or more other components, which may include a number of keyways such as, for example, a continuous keyway (e.g., 360 degree) or discrete keyways disposed at various angles (e.g., 0 degrees and 180 degrees, 90 degrees and 270 degrees, etc.). As an example, a latch may provide for release of a bearing assembly. For example, consider a bearing assembly that is connected to the plate **3020**.

(42) As an example, a bearing assembly may utilize one or more types of components. For example, consider use of a low friction coefficient nylon ring as a continuous bearing rather than rolling element bearings. As an example, a latch may include one or more torsion spring clip components. As an example, a latch may include one or more magnetic materials (e.g., one or more smart programmable magnetic materials). As an example, a latch may include a twist to lock and twist to unlock mechanism (e.g., consider a bayonet type of latch).

(43) As an example, a bearing assembly such as, for example, the bearing assembly **3030** of FIG. 7 or FIG. 8, may be limited in rotation. For example, consider a bearing assembly that is limited in rotation to approximately 90 degrees. In such an example, a bearing assembly may be part of a strap mount that is fixed to a material of a body in a particular orientation with respect to the body (e.g., a side or sides, an edge, edges, etc.). In such an example, a strap may be connected to the bearing assembly via a coupling where the coupling and the strap may be rotatable in a range of angles that corresponds to the limited rotation of the bearing assembly. In such an example, an end of the strap may be rotated to a first orientation and rotated to a second orientation where the first and second orientations correspond to different carrying configurations (e.g., consider a backpack type of carrying configuration and a side bag type of carrying configuration).

(44) As explained, a rivet may be utilized to clamp a material or one or more other types of interference fit components may be utilized. As an example, a portion of a rivet may include an integral bearing assembly. For example, consider the plate **3070** and the bearing assembly **3030** as being a unitary component (e.g., a turntable) or, for example, consider the plate **3020** and the

bearing assembly **3030** as being a unitary component (e.g., a turntable).

(45) As an example, a locking feature may register with a rotation feature using one or more pins and/or one or more magnets (e.g., with a locking feature).

(46) As an example, an assembly may be relatively low profile to minimize a moment arm. For example, a taller profile of the assembly **3000** may act to increase the moment arm, for example, pulling on a strap can create a greater force on a body of a carriable device and cause it to pull out on one side and in on the other side.

(47) FIG. **8** shows an example of the assembly **3000** where one or more functions of the latch **3060** may be replaced by one or more other features. The rotating device can also be used without the locking feature. For example, the plates **3020** and **3050** may be different and utilize a bayonet type of connection, a magnetic type of connection, etc. As an example, such types of connections may provide for a thinner assembly such that a profile of the assembly **3000** is reduced, which, as explained, may reduce a moment arm and/or other force on the assembly **3000**.

(48) FIG. **9** shows an example of an assembly **3300** that includes a turntable assembly **3330** that is attached to a material **3301** of a body and a coupling **3350** that is attached to a material **3302** of a strap. FIG. **9** also shows an example of a cylindrical coordinate system with a z-axis and a radial, r-axis. One or more features of the assembly **3300** may be defined with respect to one or more coordinate systems.

(49) In the example of FIG. **9**, the turntable assembly **3330** can include a base **3332** attached to the material **3301**, a spinning component **3334** and a cap **3336** that can rotate about a z-axis via the spinning component **3334**, which may be a low friction coefficient material that may include one or more rolling elements (e.g., balls, etc.). As an example, the cap **3336** can include magnetic material such as one or more permanent magnets and the coupling **3350** can include magnetic material such as one or more permanent magnets. As an example, the base **3332** can couple to the cap **3336** via an axle that may be built into one or more of the base **3332** and the cap **3336** (e.g., consider a central axle, which may be a cylindrical axle that is solid and/or hollow. In FIG. **9**, examples of magnetic field lines are shown whereby the coupling **3350** can connect to the cap **3336** via a magnetic attraction force where the cap **3336** is rotatable to accommodate an appropriate orientation of the coupling **3350** about the z-axis, for example, to orient a strap (see, e.g., the material **3302**). In the example of FIG. **9**, a user may apply force to the coupling **3350** to disconnect it from the cap **3336** of the turntable assembly **3330**.

(50) FIG. **10** shows an example of an assembly **3400** that includes a base **3432** that is attached to a material **3401** of a body and magnetic material **3436** that can be fit to the base **3432** and, for example, oriented as appropriate (e.g., with respect to the body), where a coupling **3450** can be attached to a material **3402** of a strap. FIG. **10** also shows an example of a cylindrical coordinate system with a z-axis and a radial, r-axis. One or more features of the assembly **3400** may be defined with respect to one or more coordinate systems.

(51) In the example of FIG. **10**, the magnetic material **3436** can include multiple magnetic poles that are arranged to allow for connection to the coupling **3450** in one or more orientations. For example, consider the magnetic material **3436** as including north poles and south poles that can connect to a north pole and a south pole of the coupling **3450** in two different orientations (e.g., or more). For example, consider two orientations that are approximately 90 degrees apart. In such an example, the coupling **3450** can be utilized to connect to a single mount in two different orientations.

(52) As an example, where a body includes two mounts, each mount may be oriented differently. For example, consider an arrangement of magnets for one mount and another arrangement of magnets for another mount where a coupling is oriented depending on the arrangement of magnets of each of the mounts.

(53) A magnetic material can be a ferromagnetic material, which may be magnetized. A magnet can attract another ferromagnetic material, such as, for example, iron, steel, nickel, cobalt, etc.

(54) A permanent magnet may be made from a material that is magnetized and creates its own persistent magnetic field. Materials that can be magnetized (e.g., ferromagnetic or ferrimagnetic) can include one or more elements such as, for example, one or more of iron, nickel and cobalt and their alloys, some alloys of rare-earth metals, and some naturally occurring minerals such as lodestone. Ferromagnetic materials can be classified as magnetically soft materials like annealed iron, which can be magnetized but do not tend to stay magnetized, and magnetically hard materials, which do. Permanent magnets can be made from hard ferromagnetic materials such as, for example, alnico and ferrite, which may be subjected to special processing in a strong magnetic field during manufacture to align their internal microcrystalline structure.

(55) As explained, a strap can be a carrying strap for a device. For example, consider a shoulder strap that may be utilized in one or more manners (e.g., backpack carrying strap or side bag carrying strap).

(56) As an example, a carriable device can include a body that includes a first side, a second, opposing side, a first strap mount on the first side, and a second strap mount socket on the second side; and a strap that includes an end attached to the body, an opposing end, and a coupling attached to the opposing end, where the coupling is connectable to the first strap mount and where the coupling is connectable to the second strap mount. In such an example, the strap can be a first strap and the carriable device can include a second strap. For example, consider two straps for a body such as a backpack.

(57) As an example, a carriable device can include a body that includes a first side, a second, opposing side, a first strap mount on the first side, and a second strap mount socket on the second side; and a strap that includes an end attached to the body, an opposing end, and a coupling attached to the opposing end, where the coupling is connectable to the first strap mount and where the coupling is connectable to the second strap mount. In such an example, the first side can be a back side of the body and the second side can be a front side of the body. In such an example, an end of the strap that is attached to the body can be attached at the back side of the body and, for example, where the coupling of the strap is connected to the first strap mount, the strap can be a backpack strap and/or, for example, where the coupling of the strap is connected to the second strap mount, the strap can be a side bag strap.

(58) As an example, a carriable device can include a coupling that is rotatably connectable to a first strap mount where the coupling is also rotatably connectable to a second strap mount.

(59) As an example, a first strap mount and a second strap mount can be positioned on a common half of a body. For example, consider a body that includes a top half and a bottom half, where the common half is the top half.

(60) As an example, a body can include a long dimension, a short dimension, and a thickness. In such an example, a position of an end of a strap attached to the body and a position of a first strap mount can span at least 70 percent of the long dimension of the body and a position of the end of the strap attached to the body and a position of a second strap mount can span at least 70 percent of the long dimension of the body.

(61) As an example, a coupling can be a single sided coupling with a single side that is connectable to a first strap mount and, for example, that is connectable to a second strap mount.

(62) As an example, a coupling can be a double sided coupling with a first side that is connectable to a first strap mount and a second side that is connectable to a second strap mount; noting that the first side may be suitable for connecting to the second strap mount and the second side may be suitable for connecting to the first strap mount or, for example, the first side and the second side may differ such as being keyed to connect to a corresponding strap mount (e.g., without being connectable to one or more other strap mounts).

(63) As an example, a carriable device can include a flap, where a second strap mount is coverable by the flap when the flap is in a closed position, and where the second strap mount is exposable by the flap being in at least a partially open position.

(64) As an example, a carriable device can include a first mount that includes a bearing assembly and/or can include a coupling that includes a bearing assembly. As an example, a coupling can include a latch. As an example, a latch may be a hand actuatable latch that can be released by hand, for example, to disconnect a coupling from a strap mount and/or to re-orient a coupling with respect to a strap mount. As an example, a latch may secure a coupling to a strap mount, optionally where an orientation of the coupling with respect to the strap mount may be fixed. For example, consider a coupling and strap mount that may be oriented in a first orientation and oriented in a second orientation where the first and second orientations may be approximately 90 degrees different (e.g., rotated by approximately 90 degrees). In such an example, the first orientation may be an over the shoulder back side orientation (e.g., a backpack type of orientation) and the second orientation may be an over the shoulder lateral side orientation (e.g., a side bag type of orientation).

(65) As an example, a coupling and one or more strap mounts can include magnetic materials. For example, a coupling, a first strap mount and a second strap mount can include magnetic materials. As an example, magnetic materials may be oriented to allow for connecting a coupling to a strap mount in one or more orientations. As an example, different strap mounts may provide for different orientations of a coupling. As explained, a coupling and strap mount may connect in a keyed manner, where a key may be a physical key and/or a magnetic key.

(66) As an example, a carriable device can include a body that includes a strap mount; and a strap that includes an end attached to the body, an opposing end, and a coupling attached to the opposing end, where the coupling is connectable to the strap mount, and where the opposing end of the strap is rotatable via the strap mount and the coupling. In such an example, the strap mount and the coupling may be freely rotatable, for example, via one or more bearing or bearing-like mechanisms and/or may be rotatable in a particular manner, for example, to lock into one or more orientations of the strap mount and the coupling (e.g., 0 degrees, 90 degrees, etc.). As an example, a freely rotatable arrangement of a strap mount and a coupling may include a latch where the latch can lock into one or more orientations of the strap mount and the coupling.

(67) Although examples of methods, devices, systems, etc., have been described in language specific to structural features and/or methodological acts, it is to be understood that the subject matter defined in the appended claims is not necessarily limited to the specific features or acts described. Rather, the specific features and acts are disclosed as examples of forms of implementing the claimed methods, devices, systems, etc.

Claims

1. A carriable device comprising: a body that comprises a long dimension and a short dimension of a first side and a second, opposing side, wherein the body further comprises a first strap mount on the first side, and a second strap mount on the second side; a flap that covers an opening to a compartment of the body; and a strap that comprises an end attached to the body, an opposing end, and a coupling attached to the opposing end, wherein the coupling is connectable to the first strap mount and wherein the coupling is connectable to the second strap mount, wherein the first side is a back side of the body and wherein the second side is a front side of the body, wherein the end of the strap that is attached to the body is attached at the back side of the body, wherein the coupling of the strap is connected to the first strap mount, the strap is a backpack strap for carrying the body in a vertical orientation of the long dimension, wherein the coupling of the strap is connected to the second strap mount, the strap is a side bag strap for carrying the body in a horizontal orientation of the long dimension, wherein the second strap mount is coverable by the flap when the flap is in a closed position, wherein the second strap mount is exposable by the flap being in at least a partially open position, wherein, in the vertical orientation the opening is oriented horizontally, and wherein, in the horizontal orientation, the opening is oriented vertically.
2. The carriable device of claim 1, wherein the strap is a first strap and further comprising a second

strap.

3. The carriable device of claim 1, wherein the coupling is rotatably connectable to the first strap mount.
 4. The carriable device of claim 1, wherein the coupling is rotatably connectable to the second strap mount.
 5. The carriable device of claim 1, wherein the first strap mount and the second strap mount are positioned on a common half of the body.
 6. The carriable device of claim 5, wherein the body comprises a top half and a bottom half, wherein the common half is the top half.
 7. The carriable device of claim 1, wherein the body comprises a thickness defined between the front side and the back side.
 8. The carriable device of claim 7, wherein a position of the end of the strap attached to the body and a position of the first strap mount span at least 70 percent of the long dimension of the body and wherein the position of the end of the strap attached to the body and a position of the second strap mount span at least 70 percent of the long dimension of the body.
 9. The carriable device of claim 1, wherein the coupling is a single sided coupling with a single side that is connectable to the first strap mount and that is connectable to the second strap mount.
 10. The carriable device of claim 1, wherein the coupling is a double sided coupling with a first side that is connectable to the first strap mount and a second side that is connectable to the second strap mount.
 11. The carriable device of claim 1, wherein the first mount comprises a bearing assembly.
 12. The carriable device of claim 1, wherein the coupling comprises a bearing assembly.
 13. The carriable device of claim 1, wherein the coupling comprises a latch.
 14. The carriable device of claim 1, wherein the coupling, the first strap mount and the second strap mount comprise magnetic materials.
 15. The carriable device of claim 1, wherein the coupling is rotatably connectable to the first strap mount and wherein the coupling is rotatably connectable to the second strap mount.
 16. The carriable device of claim 15, wherein the end attached to the body is stitched to the body.
-