

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12406224
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Skaaksrud; Ole-Petter

Centrally managed apparatus, systems, and methods for tuning a plurality of enhanced node-based logistics receptacles

Abstract

A centrally managed system for tuning a plurality of enhanced node-based logistics receptacles includes a backend server, a first enhanced node-based logistics receptacles, and a second node-based logistics receptacles. The backend server transmits a first setup message to a first bridge node, transmits a second setup message to a second bridge node, receives retrieved first event information from the first bridge node and retrieved second event information from the second bridge node, compares the retrieved first event information with a management profile and compares the retrieved second event information with the management profile, revises the management profile based upon the comparison of the retrieved first event information with the management profile and the comparison of the retrieved second event information with the management profile, and transmits an adjustment message that is based upon the revised management profile to the first bridge node.

Inventors:	Skaaksrud; Ole-Petter (Germantown, TN)
Applicant:	FEDEX CORPORATE SERVICES, INC. (Collierville, TN)
Family ID:	91583038
Assignee:	Federal Express Corporation (Memphis, TN)
Appl. No.:	18/226239
Filed:	July 25, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240214452 A1	Jun. 27, 2024

Related U.S. Application Data

Publication Classification

Int. Cl.: G06Q10/0836 (20230101); A47G29/12 (20060101); A47G29/14 (20060101); A47G29/20 (20060101); G01P13/00 (20060101); G06F1/3296 (20190101); G06Q10/0631 (20230101); G06Q10/08 (20240101); G06Q10/0833 (20230101); G06Q10/0834 (20230101); G06Q10/087 (20230101); G06Q10/20 (20230101); G06Q20/38 (20120101); G06Q20/40 (20120101); G06Q30/0202 (20230101); G06Q30/0251 (20230101); G07C9/00 (20200101); G07C9/20 (20200101); G07C9/22 (20200101); G07C9/27 (20200101); G07C9/38 (20200101); G07F17/12 (20060101); H04L41/069 (20220101); H04L41/0816 (20220101); H04L41/082 (20220101); H04L67/12 (20220101); H04W4/029 (20180101); H04W4/38 (20180101); H04W12/06 (20210101); G05D105/28 (20240101); G06K19/07 (20060101); H04W4/80 (20180101)

U.S. Cl.:

CPC G06Q10/0836 (20130101); A47G29/12095 (20170801); A47G29/1214 (20130101); A47G29/141 (20130101); A47G29/20 (20130101); G01P13/00 (20130101); G06F1/3296 (20130101); G06Q10/06315 (20130101); G06Q10/08 (20130101); G06Q10/0833 (20130101); G06Q10/08345 (20130101); G06Q10/087 (20130101); G06Q10/20 (20130101); G06Q20/382 (20130101); G06Q20/389 (20130101); G06Q20/401 (20130101); G06Q30/0202 (20130101); G06Q30/0267 (20130101); G07C9/00309 (20130101); G07C9/00571 (20130101); G07C9/00896 (20130101); G07C9/215 (20200101); G07C9/22 (20200101); G07C9/27 (20200101); G07C9/38 (20200101); G07F17/13 (20200501); H04L41/069 (20130101); H04L41/0816 (20130101); H04L41/082 (20130101); H04L67/12 (20130101); H04W4/029 (20180201); H04W4/38 (20180201); H04W12/06 (20130101); A47G2029/12105 (20170801); A47G2029/143 (20130101); A47G2029/145 (20130101); A47G2029/149 (20130101); G05D2105/285 (20240101); G06K19/0723 (20130101); G07C2009/0092 (20130101); H04W4/80 (20180201)

Field of Classification Search

CPC: H04L (67/12); H04L (41/069); H04L (41/0816); H04L (41/082); G06Q (10/0833)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9609973	12/2016	Pleasant	N/A	N/A
12093884	12/2023	Skaaksrud	N/A	N/A
12093885	12/2023	Skaaksrud	N/A	N/A
12131285	12/2023	Skaaksrud	N/A	N/A
12260368	12/2024	Skaaksrud	N/A	N/A
12277528	12/2024	Skaaksrud	N/A	N/A
2005/0154602	12/2004	Hertz	705/339	A47G 29/30
2006/0235739	12/2005	Levis	705/1.1	G06Q 10/08

2008/0189161	12/2007	Daily et al.	N/A	N/A
2013/0325231	12/2012	Park	N/A	N/A
2015/0102903	12/2014	Wilkinson	N/A	N/A
2015/0339862	12/2014	Skaaksrud	N/A	N/A
2015/0349917	12/2014	Skaaksrud	N/A	N/A
2015/0363843	12/2014	Loppatto	705/330	G06Q 30/0283
2016/0051073	12/2015	Heinz et al.	N/A	N/A
2017/0278063	12/2016	Dixon	N/A	A47G 29/141
2018/0197140	12/2017	Goja	N/A	A47G 29/1225
2018/0365641	12/2017	Zhu	N/A	N/A
2024/0211874	12/2023	Skaaksrud	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2829139	12/2013	CA	N/A
2008113568	12/2007	WO	N/A

OTHER PUBLICATIONS

U.S. Appl. No. 18/226,241 Notice of Allowance mailed Jun. 10, 2024. cited by applicant
Plasilova et al., “RFID-based Multi-purpose Smart Post Boxes in Smart Cities”, 2022 6th International Conference on Smart Grid and Smart Cities (ICSGSC), Chengdu, China, 2022, pp. 184-189. cited by applicant

U.S. Appl. No. 18/240,146 Notice of Allowance mailed Apr. 22, 2024. cited by applicant

U.S. Appl. No. 18/240,173 Notice of Allowance mailed May 6, 2024. cited by applicant
Lee, “Optimization of Modular Drone Delivery System”, IEEE Xplore, 2004, 8 pages. cited by applicant

U.S. Appl. No. 18/226,243 Notice of Allowance mailed Nov. 15, 2024. cited by applicant
Faugere et al., “Hyperconnected City Logistics: Smart Lockers Terminals & Last Mile Delivery Networks”, IPIC 3rd International Physical Internet Conference Jun. 2016, pp. 1-14. cited by applicant

U.S. Appl. No. 18/212,751 Notice of Allowance mailed Dec. 13, 2024. cited by applicant
Perlmutter, “PUDO: What it is, and How it Can Make Your Delivery Process More Efficient”, Bringg, 3 pages, Mar. 24, 2022, bringg.com, Retrieved from <https://www.bringg.com/blog/in-store-pickup/pudo-pick-up-drop-off/>. cited by applicant

U.S. Appl. No. 18/212,738 Notice of Allowance mailed Jan. 21, 2025. cited by applicant

U.S. Appl. No. 18/479,045 Notice of Allowance mailed Mar. 10, 2025. cited by applicant

U.S. Appl. No. 18/497,787 Office Action mailed Mar. 26, 2025. cited by applicant

Primary Examiner: Moise; Emmanuel L

Assistant Examiner: Yu; Xiang

Attorney, Agent or Firm: WITHERS & KEYS, LLC

Background/Summary

RELATED APPLICATIONS (1) The present application claims priority to U.S. Provisional Application No. 63/434,492, filed on Dec. 22, 2022. (2) The present application is also related in subject matter to the following non-provisional patent applications where each also claims the benefit of priority to the same above-referenced provisional patent application: (1) Non-Provisional

patent application Ser. No. 18/212,738 entitled “Improved Systems, Apparatus and Methods Involving an Enhanced Connected Node-based Logistics Receptacle and Methods of Operating the Same”; (2) Non-Provisional patent application Ser. No. 18/212,745 entitled “Enhanced Apparatus, Systems, and Methods for Receiving and Temporarily Maintaining a Delivery Item and Responsively Initiating a Dispatched Logistics Operation for a Storage Receptacle”; (3) Non-Provisional patent application Ser. No. 18/212,751 entitled “Enhanced Multi-compartment Logistics Receptacle Apparatus, Systems, and Methods for Receiving and Temporarily Maintaining a Delivery Item and Causing a Backend Server to Initiate a Dispatched Logistics Operation”; (4) Non-Provisional patent application Ser. No. 18/212,756 entitled “Apparatus, Systems, and Methods for Dynamically Tuning Operation of a Node-based Logistics Receptacle”; (5) Non-Provisional patent application Ser. No. 18/226,241 entitled “Apparatus, Systems, and Methods for Multi-domain Management of a Node-based Logistics Receptacle in Response to a Dispatched Logistics Operation Involving the Node-based Logistics Receptacle and a Mobile Courier Node”; (6) Non-Provisional patent application Ser. No. 18/226,243 entitled “Apparatus, Systems, and Methods for Receiving and Temporarily Maintaining a Delivery Item and Dynamically Initiating a Dispatched Logistics Operation for a Storage Receptacle”; (7) Non-Provisional patent application Ser. No. 18/226,248 entitled “Improved Connected Logistics Receptacle Apparatus, Systems, and Methods with Proactive Unlocking Functionality Related to a Dispatched Logistics Operation by a Mobile Logistics Asset Having an Associated Mobile Transceiver”; (8) Non-Provisional patent application Ser. No. 18/479,037 entitled “Improved Apparatus, Systems, and Methods for Monitoring and Initiating a Logistics Response Related to a Node-enabled Logistics Receptacle to be Serviced by a Logistics Asset”; (9) Non-Provisional patent application Ser. No. 18/240,123 entitled “Connected Logistics Receptacle Apparatus, Systems, and Methods with Enhanced Customer Identification Related to a Delivery Item Being Deposited by a Parcel Customer”; (10) Non-Provisional patent application Ser. No. 18/240,146 entitled “Connected Logistics Receptacle Apparatus, Systems, and Methods having Enhanced Status Indication Functionality Related to a Logistics Operation for a Delivery Item Being Deposited by a Parcel Customer”; (11) Non-Provisional patent application Ser. No. 18/240,173 entitled “Apparatus, Systems, and Methods for Self-tuning Operation of a Node-based Logistics Receptacle Based Upon Contextual Awareness”; (12) Non-Provisional patent application Ser. No. 18/479,042 entitled “Node-enabled Logistics Receptacle Apparatus, Systems, and Methods with a Deployable Storage Element for Receiving and Temporarily Maintaining a Delivery Item”; (13) Non-Provisional patent application Ser. No. 18/479,045 entitled “Enhanced Connected Logistics Receptacle Apparatus, Systems, and Methods that Selectively Retrieve and Report Event Information to a Backend Server to Initiate a Dispatched Logistics Operation Related to a Delivery Item”; (14) Non-Provisional patent application Ser. No. 18/479,047 entitled “Proactively Monitored and Reporting Logistics Receptacle Apparatus, Systems, and Methods for Receiving and Temporarily Maintaining a Delivery Item”; (15) Non-Provisional patent application Ser. No. 18/479,049 entitled “Apparatus, Systems, and Methods Providing an On-demand Deployable Logistics Capacity Related to a Reporting Node-based Logistics Receptacle”; (16) Non-Provisional patent application Ser. No. 18/497,787 entitled “Dynamic Learning Server-based Logistics Apparatus, Systems, and Methods”; (17) Non-Provisional patent application Ser. No. 18/497,801 entitled “Apparatus, Systems, and Methods for Self-executing Enhanced Interaction with a Node-based Logistics Receptacle”; (18) Non-Provisional patent application Ser. No. 18/497,814 entitled “Apparatus, Systems, and Methods for Enhanced Interaction with a Node-based Logistics Receptacle During an External Drop Off of a Delivery Item by a Parcel Customer Operating a Mobile User Device”; (19) Non-Provisional patent application Ser. No. 18/497,819 entitled “Apparatus, Systems, and Methods for Enhanced Interaction with a Node-based Logistics Receptacle and a Parcel Customer Operating a Mobile User Device.”

FIELD OF THE DISCLOSURE

(1) The present disclosure generally relates to systems, apparatus and methods in the field of logistics and, more particularly, to various aspects involving systems, apparatus, and methods for improved monitoring a state of an enhanced logistics receptacle and improved techniques for reporting changes to the state of the enhanced logistics receptacle to cause a backend server to initiate and/or revise one or more dispatched logistics operations.

BACKGROUND

(2) For a logistics operation involving the receipt, shipment, and delivery of packages (e.g., parcels, and the like), it is common to deploy one or more receptacles or repositories that can securely accept such packages for shipment and/or pickup of such packages. For example, such a receptacle or repository (generally referred to as a logistics receptacle) may be a drop box that allows a customer to securely deposit a package to be shipped within it but not provide customer access to an interior holding area of the drop box. Another example may be a locker unit type of logistics receptacle, which provides the customer with secure access to one or more parts of an interior temporary holding or storage area of the logistics receptacle and where a service courier picking up any packages may have access to the same and other areas within the holding/storage area(s). As such, a logistics receptacle is often an entry point and/or pickup point for a package being shipped from one location to another.

(3) A logistics receptacle may be publicly deployed. For example, a logistics entity may operate as a company in the logistics field and deploy different logistics receptacles at distinct geographic locations so that the public may be able to more conveniently drop off packages to be shipped rather than travel to a central shipping office or shipping center. As such, it is common that many publicly deployed logistics receptacles are not actively manned by personnel. Thus, publicly deployed logistics receptacles are often used as secure remote repositories for packages and are only periodically serviced by agents of a logistics entity, such as a courier or other types of logistics assets.

(4) The use and management of such logistics receptacles may face a variety of different problems and inefficiencies depending on how the logistics receptacle is implemented and used. For example, in some situations, the logistics receptacle may fill up quickly to a point of an overloaded or overflowing state prior to pickup service by a courier. In other situations, the logistics receptacle may have a current pickup time that may be inappropriate based on ongoing use—e.g., where the pickup time is either too early where the logistics asset (e.g., courier) dispatched for servicing may be wasted resulting in costly inefficiencies or where the pickup time is too late where customers may be frustrated given an overloaded state and where an earlier pickup time would allow for more room within a particular logistics receptacle.

(5) Prior attempts to address such problems are known to use one or more sensors within a logistics receptacle where a central processing device gathers data related to a deposited package and wirelessly reports such data to staff or package collection personnel. Such prior solutions may still suffer inefficiencies in how such a sensor-based logistics receptacle operates, how it monitors itself, and how such reported data may be used in management of the logistics receptacle and related to any logistics asset dispatch.

(6) The management and use of such a logistics receptacle can be improved to provide for quicker, more robust, and more efficient monitoring and reporting of events reflecting a status of the logistics receptacle so that the appropriate type of logistics operation may be dispatched and management of this and other logistics receptacles are further enhanced. Thus, there remains a need for improved systems, apparatus, and methods that may enhance monitoring of a connected node-enabled logistics receptacle and improve how to respond to such monitoring with responsive initiation of logistics operations related to one or more such logistics receptacles in a manner that distributes the intelligent monitoring and reporting in a more advantageous manner than previously

thought possible.

SUMMARY

(7) In the following description, certain aspects and embodiments will become evident. It should be understood that the aspects and embodiments, in their broadest sense, could be practiced without having one or more features of these aspects and embodiments. It should be understood that these aspects and embodiments are merely exemplary.

(8) One aspect of the disclosure relates to a centrally managed system for tuning a plurality of enhanced node-based logistics receptacles. The system includes a backend server maintaining a management profile related to each of the enhanced node-based logistics receptacles. The system also includes a first of the enhanced node-based logistics receptacles operative to communicate with the backend server.

(9) The first of the enhanced node-based logistics receptacles includes a first plurality of monitored receptacle components. The first of the enhanced node-based logistics receptacles includes a first wireless accessory sensor node having a first plurality of sensors that collectively monitor one or more interactions with respective ones of the first plurality of monitored receptacle components over a first recording time period. The first of the enhanced node-based logistics receptacles also includes a first bridge node operative to retrieve first event information from the first wireless accessory sensor node. The first event information is related to sensor data generated by the first plurality of sensors, and the first bridge node is further operative to transmit the retrieved first event information at a first upload time to the backed server.

(10) The system also includes a second of the node-based logistics receptacles operative to communicate with the backend server. The second of the enhanced node-based logistics receptacles includes a second plurality of monitored receptacle components. The second of the enhanced node-based logistics receptacles includes a second wireless accessory sensor node having a second plurality of sensors that collectively monitor one or more interactions with respective ones of the second plurality of monitored receptacle components over a second recording time period. The second of the enhanced node-based logistics receptacles includes a second bridge node operative to retrieve second event information from the second wireless accessory sensor node. The second event information is related to sensor data generated by the second plurality of sensors, and the second bridge node is further operative to transmit the retrieved second event information at a second upload time to the backed server.

(11) The backend server is programmatically configured to be operative to transmit a first setup message to the first bridge node. The first setup message configures operation of the first bridge node related to at least the first recording time period for the first wireless accessory sensor node and the first upload time for the first bridge node to transmit the retrieved first event information to the backend server.

(12) The backend server is programmatically configured to be operative to transmit a second setup message to the second bridge node. The second setup message configures operation of the second bridge node related to at least the second recording time period for the second wireless accessory sensor node and the second upload time for the second bridge node to transmit the retrieved second event information to the backend server.

(13) The backend server is programmatically configured to be operative to receive the retrieved first event information from the first bridge node and the retrieved second event information from the second bridge node. The backend server is programmatically configured to be operative to compare the retrieved first event information with the management profile and compare the retrieved second event information with the management profile. The backend server is programmatically configured to be operative to revise the management profile based upon the comparison of the retrieved first event information with the management profile and the comparison of the retrieved second event information with the management profile. The backend server is also programmatically configured to be operative to transmit an adjustment message to the

first bridge node, the adjustment message being based upon the revised management profile, the adjustment message initiating a first timing change to operation of the first bridge node.

(14) As described below, other aspects of the disclosure explain further details of various improvements in the operation of and use/management of an improved and enhanced system as well as a part of an improved network of logistics devices. Each of these aspects respectively effect improvements to the technology of smart and intelligent logistics receptacles and systems that are more advanced in how they monitor, report, and functions as an improved element useful in the logistics field. Those skilled in the art will appreciate that additional advantages of the above-described aspect and other aspects of the disclosed embodiments and examples will be set forth in part in the description which follows, and in part will be obvious from the description, or may be learned by practice of the invention. It is to be understood that both the foregoing general description and the following detailed description are exemplary and explanatory only and are not restrictive of the invention, as claimed.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The accompanying drawings, which are incorporated in and constitute a part of this specification, illustrate several embodiments according to one or more principles of the invention and together with the description, serve to explain one or more principles of the invention. In the drawings,

(2) FIG. 1 is a diagram of an exemplary connected logistics receptacle operating within a network and in communication with an exemplary backend server in accordance with an embodiment of the invention;

(3) FIG. 2 is a more detailed diagram of an exemplary connected logistics receptacle operating within a network in accordance with an embodiment of the invention;

(4) FIG. 3 is a detailed diagram of an exemplary bridge node device used as part of an exemplary connected logistics receptacle in accordance with an embodiment of the invention;

(5) FIG. 4 is a detailed diagram of an exemplary wireless accessory sensor node device used as part of an exemplary connected logistics receptacle in accordance with an embodiment of the invention;

(6) FIGS. 5A-5E are a series of diagrams illustrating different exemplary embodiments of an entrance opening to an exemplary connected logistics receptacle in accordance with different embodiments of the invention;

(7) FIGS. 6A-6D are timing diagrams illustrating activity during exemplary reporting periods for an exemplary connected logistics receptacle in accordance with different embodiments of the invention;

(8) FIG. 7 is a diagram of multiple exemplary connected logistics receptacles operating within a network that connects with an exemplary backend server in accordance with an embodiment of the invention;

(9) FIG. 8 is a detailed diagram of an exemplary backend server device in accordance with an embodiment of the invention;

(10) FIGS. 9A-9E are a series of diagrams of an exemplary backend server responding to receipt of retrieved event information from a bridge node in an exemplary connected logistics receptacle where the backend server initiates enhanced responses relative to the reporting exemplary connected logistics receptacle and/or relative to additional exemplary connected logistics receptacles in accordance with an embodiment of the invention;

(11) FIG. 10A is a diagram of a first exemplary multi-compartment logistics receptacle having multiple monitored receptacle compartments and a common access compartment in accordance with an embodiment of the invention;

(12) FIG. 10B is a diagram of a second exemplary multi-compartment logistics receptacle having multiple monitored receptacle compartments and a common selectively accessible retrieval door providing access within the compartments in accordance with an embodiment of the invention;

(13) FIG. 10C is a diagram of a third exemplary multi-compartment logistics receptacle similar to that in FIG. 10B but using different wireless accessory sensor nodes in each monitored receptacle compartment in accordance with an embodiment of the invention;

(14) FIG. 10D is a diagram of a fourth exemplary multi-compartment logistics receptacle having multiple monitored receptacle compartments and separate selectively accessible retrieval doors providing limited access to within individual compartments in accordance with an embodiment of the invention;

(15) FIG. 10E is a diagram of a fifth exemplary multi-compartment logistics receptacle similar to that in FIG. 10D but using different wireless accessory sensor nodes in each monitored receptacle compartment in accordance with an embodiment of the invention;

(16) FIG. 11 is a diagram illustrating an exemplary multi-compartment logistics receptacle operating within a network and in communication with an exemplary backend server where the server initiates a dispatched logistics operation with a particular logistics entity in accordance with an embodiment of the invention;

(17) FIG. 12A is a diagram illustrating an exemplary multi-compartment logistics receptacle involved in an exemplary swap type of dispatched logistics operation involving one of the monitored receptacle compartments in accordance with an embodiment of the invention;

(18) FIG. 12B is a diagram illustrating an exemplary multi-compartment logistics receptacle involved in an exemplary swap type of dispatched logistics operation involving two or more of the monitored receptacle compartments in accordance with an embodiment of the invention;

(19) FIGS. 13A and 13B collectively are a flow diagram illustrating an exemplary method for multi-domain management of a node-based logistics receptacle in response to a dispatched logistics operation involving the node-based logistics receptacle and a mobile courier node in accordance with an embodiment of the invention;

(20) FIGS. 14A and 14B collectively are a flow diagram illustrating another exemplary method for multi-domain management of a node-based logistics receptacle in response to a dispatched logistics operation involving the node-based logistics receptacle and a mobile courier node in accordance with an embodiment of the invention;

(21) FIG. 15A is a diagram of an exemplary system for dynamically tuning operations where the system's bridge node in an exemplary node-based logistics receptacle is transmitting retrieved event information to the system's backend server in accordance with an embodiment of the invention;

(22) FIG. 15B is a diagram of an exemplary system for dynamically tuning operations where the system's backend server sends an exemplary tuned time parameter message to the system's bridge node in an exemplary node-based logistics receptacle to cause the bridge node to alter timing related operations in accordance with an embodiment of the invention;

(23) FIG. 16 is a detailed diagram of an exemplary bridge node device used as part of an exemplary system for dynamically tuning operations in accordance with an embodiment of the invention;

(24) FIG. 17A is a diagram illustrating an exemplary user access device that is operative to access an online portal hosted by a backend server in accordance with an embodiment of the invention;

(25) FIG. 17B is a diagram illustrating an exemplary user access device that is operative to access an online portal hosted by an alternative or secondary server in accordance with an embodiment of the invention;

(26) FIG. 18 is a diagram illustrating an exemplary connected logistics receptacle operating within a network and in communication with an exemplary backend server where the logistics receptacle includes a display capable of showing updated operational information related to adjusted or updated operational aspects of the logistics receptacle in accordance with an embodiment of the invention;

invention;

(27) FIGS. **19A** and **19B** collectively are a flow diagram illustrating an exemplary method dynamically tuning operation of a node-based logistics receptacle in accordance with an embodiment of the invention;

(28) FIGS. **20A-20H** are a series of diagrams of an exemplary centrally managed system for tuning multiple enhanced node-based logistics receptacles involving a backend server in accordance with an embodiment of the invention;

(29) FIG. **21** is a diagram illustrating an exemplary connected logistics receptacle operating within a network and in communication with an exemplary backend server dynamically initiating a dispatched logistics operation in accordance with an embodiment of the invention;

(30) FIG. **22** is a diagram illustrating the exemplary connected logistics receptacle and exemplary backend server of FIG. **21** dynamically initiating a dispatched logistics operation involving consideration of an exemplary currently scheduled route relative to a location of the exemplary connected logistics receptacle in accordance with an embodiment of the invention;

(31) FIG. **23** is a diagram illustrating the exemplary connected logistics receptacle and exemplary backend server of FIG. **21** dynamically initiating a dispatched logistics operation involving an exemplary redirect dispatch message in accordance with an embodiment of the invention;

(32) FIG. **24** is a diagram illustrating the exemplary connected logistics receptacle and exemplary backend server of FIG. **21** dynamically initiating a dispatched logistics operation involving an exemplary combination dispatch message that initiates servicing a reporting logistics receptacle and dispatches an exemplary sweep operation of at least one more non-reporting logistics receptacle in accordance with an embodiment of the invention;

(33) FIG. **25** is a detailed diagram of another embodiment of an exemplary backend server that uses an exemplary logistics asset usage profile as part of dynamically initiating a dispatched logistics operation in accordance with an embodiment of the invention;

(34) FIGS. **26A-26C** are diagrams illustrating an exemplary connected logistics receptacle operating as part of a system with proactive unlocking functionality related to a dispatched logistics operation by an exemplary mobile logistics asset having an associated mobile transceiver in accordance with an embodiment of the invention;

(35) FIG. **27** is a diagram illustrating the exemplary connected logistics receptacle, exemplary backend server, and exemplary mobile logistics asset of FIGS. **26A-26C** and further illustrating authentication of the approaching mobile logistics asset in accordance with an embodiment of the invention;

(36) FIG. **28** is a diagram illustrating the exemplary connected logistics receptacle, exemplary backend server, and exemplary mobile logistics asset of FIGS. **26A-26C** and further illustrating another example of authentication of the approaching mobile logistics asset in combination with proximity sensing in accordance with an embodiment of the invention;

(37) FIGS. **29A-29B** are diagrams illustrating the exemplary connected logistics receptacle, exemplary backend server, and exemplary mobile logistics asset of FIGS. **26A-26C** and further illustrating still another example of authentication of the approaching mobile logistics asset related to the location of the mobile logistics asset in accordance with an embodiment of the invention;

(38) FIG. **30** is a diagram illustrating the exemplary connected logistics receptacle, exemplary backend server, and exemplary mobile logistics asset of FIGS. **26A-26C** and further illustrating examples of different exemplary courier validation messages from different external devices in accordance with an embodiment of the invention;

(39) FIG. **31** is a diagram illustrating an exemplary improved monitoring and logistics response system involving movement of the system's exemplary logistics receptacle in accordance with an embodiment of the invention;

(40) FIG. **32** is a diagram illustrating the exemplary improved monitoring and logistics response system of FIG. **31** involving an updated location of the system's exemplary logistics receptacle in

accordance with an embodiment of the invention;

(41) FIG. 33 is a diagram illustrating the exemplary improved monitoring and logistics response system of FIG. 31 involving replacement movement and use of an exemplary replacement logistics receptacle relative to a predetermined location where a second logistics receptacle was previously located in accordance with an embodiment of the invention;

(42) FIG. 34 is a flow diagram illustrating an exemplary improved method for monitoring and initiating a logistics response related to a node-enabled logistics receptacle to be serviced by a logistics asset in accordance with an embodiment of the invention;

(43) FIG. 35 is a flow diagram illustrating another exemplary improved method for monitoring and initiating a logistics response related to a node-enabled logistics receptacle to be serviced by a logistics asset in accordance with an embodiment of the invention;

(44) FIG. 36 is a diagram illustrating an exemplary enhanced connected logistics receptacle system that selectively retrieves and reports event information to a backend server to initiate a dispatched logistics operation related to a delivery item in accordance with an embodiment of the invention;

(45) FIG. 37 is a flow diagram illustrating an exemplary method for selective uploading and transmitting of event information from a node-based logistics receptacle in accordance with an embodiment of the invention;

(46) FIGS. 38A-38C are diagrams illustrating an exemplary connected logistics receptacle system with enhanced customer identification related to a delivery item being deposited by a parcel customer in accordance with an embodiment of the invention;

(47) FIGS. 39A-39B collectively are a flow diagram illustrating an exemplary method enhanced customer identification related to a delivery item being deposited with a node-based logistics receptacle in accordance with an embodiment of the invention;

(48) FIG. 40 is a diagram illustrating an exemplary enhanced connected logistics receptacle having enhanced status indication functionality related to a logistics operation for a delivery item being deposited by a parcel customer in accordance with an embodiment of the invention;

(49) FIG. 41 is a detailed diagram of an exemplary bridge node used within the exemplary enhanced connected logistics receptacle having enhanced status indication functionality of FIG. 40 in accordance with an embodiment of the invention;

(50) FIGS. 42A-42D are diagrams illustrating different examples of how the exemplary enhanced connected logistics receptacle having enhanced status indication functionality of FIG. 40 may generate and transmit exemplary status update notification to different types of external devices in accordance with an embodiment of the invention;

(51) FIG. 43 is a diagram illustrating aspects of an exemplary system for self-tuning operation of an exemplary node-based logistics receptacle based upon contextual awareness in accordance with an embodiment of the invention;

(52) FIG. 44 is a detailed diagram of an exemplary bridge node used within the exemplary node-based logistics receptacle of FIG. 43 in accordance with an embodiment of the invention;

(53) FIGS. 45A-45D are diagrams illustrating different examples of how the exemplary node-based logistics receptacle of FIG. 43 using external sensors may enhance monitoring of a local environment proximate the exemplary enhanced connected logistics receptacle in accordance with an embodiment of the invention;

(54) FIGS. 46A-46C are further diagrams illustrating examples of how the exemplary node-based logistics receptacle of FIG. 43 may enhance monitoring of a local environment proximate the exemplary enhanced connected logistics receptacle in accordance with an embodiment of the invention;

(55) FIG. 47 is a diagram illustrating an example of how the exemplary node-based logistics receptacle of FIG. 43 may use one or more external sensing elements of an external sensing infrastructure in accordance with an embodiment of the invention;

(56) FIG. 48 is a diagram of an exemplary proactively monitored and reporting logistics receptacle

system operating within a network in accordance with an embodiment of the invention;

(57) FIGS. **49A-49B** are timing diagrams illustrating exemplary wireless accessory sensor node activity during an exemplary reporting period for exemplary proactively monitored and reporting logistics receptacle system of FIG. **48** involving the generation of event information or non-event information in accordance with different embodiments of the invention;

(58) FIG. **50** is a timing diagram illustrating exemplary bridge node activity during the exemplary reporting period for exemplary proactively monitored and reporting logistics receptacle system of FIG. **48** involving status updates that may include event information or non-event information retrieved from an exemplary wireless accessory sensor node in accordance with an embodiment of the invention;

(59) FIG. **51** is a diagram illustrating aspects of an exemplary system for providing an on-demand deployable logistics capacity related to and in response to an exemplary reporting node-based logistics receptacle in accordance with an embodiment of the invention;

(60) FIGS. **52A-52C** are diagrams of different exemplary embodiments of a deployable mobile logistics receptacle in accordance with various embodiments of the invention;

(61) FIG. **53** is a diagram illustrating an embodiment of the system of FIG. **51** where the backend server causes the reporting node-based logistics receptacle to show alternative deposit information related to the deployable mobile logistics receptacle in accordance with an embodiment of the invention;

(62) FIG. **54** is a diagram illustrating an embodiment of the system of FIG. **51** where the backend server recalls the deployable mobile logistics receptacle in accordance with an embodiment of the invention;

(63) FIG. **55** is a diagram illustrating an embodiment of the system of FIG. **51** where the backend server activates an exemplary replacement deployable mobile logistics receptacle in accordance with an embodiment of the invention;

(64) FIG. **56** is a diagram illustrating an exemplary dynamic learning server-based logistics system in accordance with an embodiment of the invention;

(65) FIG. **57** is a diagram illustrating an embodiment of the system of FIG. **56** where the backend server transmits an exemplary setup message in accordance with an embodiment of the invention;

(66) FIGS. **58A-58B** are diagrams illustrating aspects of an exemplary node-based logistics receptacle with a deployable storage element in accordance with an embodiment of the invention;

(67) FIG. **59** is a diagram illustrating an exemplary deployable storage element deployed to a position external to the node-based logistics receptacle and near an exemplary mobile logistics asset in accordance with an embodiment of the invention;

(68) FIG. **60** is a diagram illustrating an exemplary deployable storage element deployed to a position external to the node-based logistics receptacle and near an exemplary autonomous mobile logistics asset in accordance with an embodiment of the invention;

(69) FIG. **61** is a detailed diagram illustrating an exemplary deployable autonomous mobile container as a type of deployable storage element in accordance with an embodiment of the invention;

(70) FIGS. **62A-62C** are diagrams illustrating various examples of closable access panels that provide access within an exemplary deployable autonomous mobile container and may secure what has been deposited within the exemplary deployable autonomous mobile container in accordance with an embodiment of the invention;

(71) FIG. **63A** is a diagram illustrating an exemplary deployable autonomous mobile container navigating towards an exemplary mobile logistics asset in accordance with an embodiment of the invention;

(72) FIG. **63B** is a diagram illustrating an exemplary deployable autonomous mobile container interacting with an exemplary mobile logistics asset as part of authenticating the exemplary mobile logistics asset in accordance with an embodiment of the invention;

(73) FIG. 63C is a diagram illustrating an exemplary deployable autonomous mobile container interacting with an exemplary mobile logistics asset as part of a security handshake interface operation in accordance with an embodiment of the invention;

(74) FIG. 63D is a diagram illustrating an exemplary deployable autonomous mobile container interacting with personnel associated with an exemplary mobile logistics asset using a human engagement interface on the deployable autonomous mobile container in accordance with an embodiment of the invention;

(75) FIG. 63E is a diagram illustrating an exemplary deployable autonomous mobile container autonomously loading into an exemplary mobile logistics asset in accordance with an embodiment of the invention;

(76) FIG. 64 is a diagram illustrating an exemplary node-based logistics receptacle receiving an exemplary deployable autonomous mobile container and verifying the compatibility of the deployable autonomous mobile container with that node-based logistics receptacle in accordance with an embodiment of the invention;

(77) FIG. 65 is a diagram illustrating an exemplary node-based logistics receptacle requesting a replacement deployable autonomous mobile container in accordance with an embodiment of the invention;

(78) FIGS. 66A-66C are diagrams illustrating an exemplary node-based logistics receptacle having a first deployable autonomous mobile container and a reserve deployable autonomous mobile container in accordance with an embodiment of the invention;

(79) FIG. 67 is a diagram illustrating an exemplary deployable autonomous mobile container that is deployed and receiving a remote input signal used by the deployable autonomous mobile container as part of generating propulsion and steering control signals in accordance with an embodiment of the invention;

(80) FIG. 68 is a diagram illustrating an exemplary deployable autonomous mobile container that is deployed and autonomously operating within a predefined area in accordance with an embodiment of the invention;

(81) FIG. 69 is a diagram illustrating an exemplary node-based logistics receptacle having a temporary storage area separate from an exemplary deployable autonomous mobile container and an exemplary parcel manipulator that is capable of moving contents of the temporary storage into the deployable autonomous mobile container in accordance with an embodiment of the invention;

(82) FIG. 70 is a diagram illustrating an exemplary system for self-executing enhanced interaction with a node-based logistics receptacle in accordance with an embodiment of the invention;

(83) FIG. 71 is a diagram illustrating another exemplary system for self-executing enhanced interaction with a node-based logistics receptacle that interfaces with an exemplary source of data related to an interaction with the node-based logistics receptacle in accordance with an embodiment of the invention;

(84) FIG. 72 is a diagram illustrating another exemplary system for self-executing enhanced interaction with a node-based logistics receptacle that interfaces with an exemplary device providing a service related to an interaction with the node-based logistics receptacle in accordance with an embodiment of the invention;

(85) FIG. 73 is a diagram illustrating another exemplary system for self-executing enhanced interaction with a node-based logistics receptacle that interfaces with an exemplary device that may interface with the node-based logistics receptacle with trusted access to within the node-based logistics receptacle in accordance with an embodiment of the invention;

(86) FIGS. 74A-74C are diagrams illustrating an exemplary system for enhanced interaction with a node-based logistics receptacle during an external drop off of a delivery item by a parcel customer operating a mobile user device in accordance with embodiments of the invention;

(87) FIGS. 75A-75C are diagrams illustrating another exemplary system for enhanced interaction with a node-based logistics receptacle during an external drop off of a delivery item by a parcel

customer that involves detection of whether the parcel customer is carrying the delivery item upon approach to the node-based logistics receptacle using an onboard external sensor in accordance with embodiments of the invention;

(88) FIGS. 76A-76D are diagrams illustrating still another exemplary system for enhanced interaction with a node-based logistics receptacle during an external drop off of a delivery item by a parcel customer that involves detection of whether the parcel customer is carrying the delivery item upon approach to the node-based logistics receptacle using a separately disposed external sensor in accordance with embodiments of the invention; and

(89) FIGS. 77A-77D are diagrams illustrating yet another exemplary system for enhanced interaction with a node-based logistics receptacle and a detected parcel customer that involves proactively sending the parcel customer alternative drop off information upon approach to the node-based logistics receptacle in accordance with embodiments of the invention.

DESCRIPTION OF THE EMBODIMENTS

(90) Reference will now be made in detail to exemplary embodiments. Wherever possible, the same reference numbers are used in the drawings and the description to refer to the same or like parts.

(91) The following describes various embodiments of an enhanced connected logistics receptacle that may be operated and applied by principles as set forth herein as part of exemplary systems, apparatus, and methods. In general, exemplary embodiments of the enhanced connected logistics receptacle transforms the logistics receptacle to become like an improved element of a mailroom or smart building operation where a drop off is more efficiently detected, where the entity dropping off the item being shipped may be automatically recognized and prompted, where a pickup is more efficiently requested, where operations of the receptacle (e.g., drop-off/pickup) may be verified, and which better avoids non-productive courier pickup interactions with the logistics receptacle.

(92) Those skilled in the art will appreciate that each embodiment described herein effects improvements to particular technologies, such as enhancing and improving how to quickly, automatically, and intelligently to detect package drop-off events, package pickup events, gather event information related to such events, report the event information to a backend server, and cause the backend server to initiate enhanced responsive actions. Embodiments may also have the backend server learning from such reported event information and responsively tune or modify the operations of one or more connected logistics receptacles as a result. As such, each embodiment describes a specific technological application in the logistics field involving enhanced automated package drop-off/pickup activity involving one or more enhanced connected logistics receptacles and a backend server where the specific technological application improves or otherwise enhances such technical fields as explained and supported by the disclosure that follows related to the illustrations shown in FIGS. 1-77D.

(93) FIG. 1 is a diagram of an exemplary connected logistics receptacle operating within a network and in communication with an exemplary backend server in accordance with an embodiment of the invention. Those skilled in the art will understand and appreciate that a logistics receptacle is a general term for an apparatus used as a repository or container that temporarily maintains custody of one or more packages being shipped or moved from one location to another location. Such a logistics receptacle may, for example, be referred to as a drop box or a package locker. In some embodiments, an exemplary logistics receptacle may be implemented as a single storage type of structure having a common temporary storage area within which to hold one or more deposited packages. In other embodiments, the logistics receptacle may be implemented with multiple compartmented storage areas that may be used by particular customers or couriers with selective access to the different storage areas. In different embodiments, an exemplary logistics receptacle may be stationary and fixed at a given physical location, stationary but movable between different physical locations, or be an intentionally mobile type of logistics receptacle (e.g., a vehicle-based logistics receptacle).

(94) Referring now to FIG. 1, an exemplary connected logistics receptacle **150** (also generally referred to as an exemplary node-based logistics receptacle) is shown that may accept a package **170** (as part of shipping package **170**), where the exemplary connected logistics receptacle **150** uses one or more onboard sensor(s) to detect such a package deposit as a type of change in state of receptacle **150** and communicate event information related to the change in state with an exemplary backend server **100** via a network **105**. Backend server **100** may, in some embodiments, access and use information available in other servers or network storage (such as exemplary third-party database **180**).

(95) While package **170** is shown as being deposited within exemplary connected logistics receptacle **150**, other packages (such as package **175**) may also be considered deposited with receptacle **150** albeit external to receptacle **150** but in proximity to receptacle **150**. In such an embodiment, exemplary connected logistics receptacle **150** may use external sensor(s) (e.g., external motion sensors deployed as part of a wireless accessory sensor node) to detect package **175** as another type of reportable event reflecting a change in state of receptacle **150** and communicate event information related to the change in state with exemplary backend server **100** via network **105**.

(96) Exemplary backend server **100** may be implemented as a dispatch and/or operational planning backend server computer, through communication network **105**. While exemplary backend server **100** is shown in FIG. 1 connecting through network **105** to logistics receptacle **150**, those skilled in the art will appreciate that backend server **100** may have a more direct or dedicated connections to the connected logistics receptacle **150** depending upon implementation details and desired communication paths. Furthermore, those skilled in the art will appreciate that an exemplary server may contain a collection of information within an internal database or other memory storage (not shown in FIG. 1), while multiple databases maintained on one or more other server platforms or network storage servers (e.g., such as third-party network storage database **180**) may be used in other embodiments to maintain such a collection of information accessible to backend server **100** via network **105**. Additionally, while not shown in FIG. 1, those skilled in the art will appreciate that a database for information accessible to backend server **100** may be implemented with cloud technology that essentially provides networked storage of information collections that may be directly accessible to networked computing devices, such as backend server **100**. Further information on a more detailed implementation and embodiment of exemplary backend server **100** is explained below relative to FIG. 8.

(97) Referring back to FIG. 1, exemplary network **105** may be a general data communication network involving a variety of communication networks or paths. Those skilled in the art will appreciate that such exemplary networks or paths may be implemented with hard wired structures (e.g., LAN, WAN, telecommunication lines, telecommunication support structures and telecommunication processing equipment, etc.), wireless structures (e.g., antennas, receivers, modems, routers, repeaters, etc.) and/or a combination of both depending upon the desired implementation of a network **105** that interconnects backend server **100** and other components shown in an embodiment illustrated in FIG. 1 (e.g., exemplary connected logistics receptacle **150** and networked third-party database **180**) as well as other components not shown in FIG. 1 (e.g., other logistics asset servers, third party servers, mobile delivery assets (such as a dispatched courier asset), and the like).

(98) Exemplary connected logistics receptacle **150** may operate as a storage receptacle structure that temporarily maintains custody of packages (such as package **170**) being shipped. Exemplary connected logistics receptacle **150** has an entrance opening **155** (shown in FIG. 1 with an articulating door **156**) through which package **170** may pass as package **170** is deposited within a temporary storage or holding area of the receptacle **150**. Exemplary connected logistics receptacle **150** is also shown having an exemplary selectively accessible retrieval door **160** (and lock **165**) through which package **170** may be retrieved from within receptacle **150** during a pickup logistics

operation. As explained in more detail below, embodiments may advantageously deploy distinct types of distributed electronic node devices involving, for example, a bridge node device and one or more wireless accessory sensor node devices as part of an enhanced monitoring and reporting system in an enhanced connected logistics receptacle **150**. In a general embodiment (and as shown in more detail in at least FIG. **2**), an exemplary bridge node (also referred to generally as a bridging node) may be mounted to the connected logistics receptacle **150** and operative to communicate with the different wireless accessory sensor nodes in an advantageous manner. Such wireless accessory sensor nodes are programmatically adapted and configured to detect a change in state of the connected logistics receptacle **150** using one or more sensor(s), record timestamped information reflecting the detected change in receptacle state, and broadcast a status flag (e.g., a data available flag that has been set) as part of an updated advertising signal. The exemplary bridge node is programmatically adapted and configured to detect the status flag and, in response, retrieve event information available for upload from the wireless accessory sensor node and transmit the retrieved event information to the backend server, which then responsively causes the backend server to initiate a dispatched logistics operation related to the connected logistics receptacle **150**.

(99) FIG. **2** is a more detailed diagram of exemplary connected logistics receptacle **150** in accordance with an embodiment of the invention. Referring now to FIG. **2**, exemplary connected logistics receptacle **150** is shown as a drop-box type of logistics receptacle with entrance opening **155** (and entrance opening door **156**), selectively accessible retrieval door **160** (and its lock **165**), temporary storage area **205** located within receptacle **150**, as well as a variety of exemplary internal components including an exemplary bridge node **200** and a variety of different exemplary wireless accessory sensor nodes **210**, **215**, **220**, **225**, **230**, **235**, **240**, **245** and **250**.

(100) Exemplary bridge node **200**, in general (and as explained in more detail with respect to FIG. **3**), is a low-power programmatically configured processing and communication device adapted to provide particular functionality as a device that communicates with backend server **100** external to the exemplary connected node-based logistics receptacle and with wireless accessory sensor node(s) within the logistics receptacle. In some embodiments, exemplary bridge node **200** may also communicate with other external wireless communication devices, such as handheld wireless node devices used by couriers, other logistics personnel, as well as customers that may be picking up or dropping off packages with the logistics receptacle. Exemplary bridge node **200** generally includes a processor **201**, memory **202**, wireless communication interfaces **203** (implementing a long-range wireless communication interface **203a** and a short-range wireless communications interface **203b**), and interface circuitry to an externally disposed user interface **255** (e.g., having one or more display, keys, status lights, touchscreens, buttons, switches, and/or speaker for interacting with a shipping customer and/or logistics personnel). Exemplary bridge node **200** is mounted to exemplary connected logistics receptacle **150** and operative to communicate with the different wireless accessory sensor nodes disposed as part of the exemplary connected logistics receptacle **150** via short-range wireless communications interface **203b**. The bridge node **200** can separately communicate with backend server **100** via long-range wireless communication interface **203a**. Those skilled in the art will appreciate that an embodiment of exemplary bridge node **200** and exemplary wireless accessory sensor nodes **210**, **215**, **220**, **225**, **230**, **235**, **240**, **245** and **250** may be implemented as a system of field-upgradable components so as to retro-fit an existing logistics receptacle and enhanced the local operation and remote management of such a logistics receptacle via such add-on intelligent monitoring and communication devices (e.g., bridge node **200** and different wireless accessory sensor nodes).

(101) In FIG. **2**, the different exemplary wireless accessory sensor nodes **210**, **215**, **220**, **225**, **230**, **235**, **240**, **245** and **250** shown are generally operative to detect different types of interactions with particular parts of the connected logistics receptacle **150** (as well as areas relative to the receptacle) using a variety of types of sensors/sensor elements where timestamped detections are logged on the respective wireless accessory sensor node for later upload through the bridging bridge node **200**. In

other words, the different exemplary wireless accessory sensor nodes may log timestamped information related to such changes, and responsively generate updated broadcasting signals having a status flag set (e.g., a data available flag set indicating event information is available for the bridge node to upload). Exemplary bridge node **200** operates to efficiently monitor for flags set in low power signals generated and broadcast by such different wireless accessory sensor nodes and, depending on the data included in such flags, uploads relevant event information that includes timestamped information reflecting the particular changes in the state of exemplary connected logistics receptacle **150**.

(102) The exemplary wireless accessory sensor nodes shown in FIG. 2 may include similar types of sensors or different types of sensors (and/or multi-element type of sensors) depending on what is monitored on particular components of connected node-based logistics receptacle **150**. For example, exemplary entrance opening sensor node **210** has at least one sensor that monitors for a change in state of entrance opening **155** (and/or entrance door **156**). Such a sensor in entrance opening sensor node **210** may be implemented with a motion sensor, an orientation status sensor, an accelerometer, a multiple-axis accelerometer, and/or a magnetic sensor (such as a magnetic reed switch type of sensor). In more detail, an embodiment of exemplary entrance opening sensor node **210** may be mounted to a moving part related to entrance opening **155** (and/or entrance door **156**), such as a gear, axle, hinge, cam or other structural item that moves when entrance opening **155** or entrance door **156** articulates or otherwise changes position.

(103) Exemplary temporary storage area motion sensor node **215** has a motion sensor that is mounted and configured to detect motion within temporary storage area **205**. Exemplary temporary storage area image/vision sensor node **220** has a camera sensor that is mounted and configured to detect pictures and/or video images of what is within temporary storage area **205**. Exemplary temporary storage area light sensor node **225** has a light sensor that is mounted and configured to detect changes in light within temporary storage area **205**. Exemplary temporary storage area chemical sensor node **230** has a chemical sensor that is mounted and configured to detect the existence of and/or changes in what chemicals (e.g., explosive/hazardous chemicals in gaseous or vapor form, and the like) are within temporary storage area **205**. Exemplary temporary storage area force sensor node **235** has a sensor (e.g., a scale, load cell, impact sensor) that is mounted at the bottom of temporary storage area **205** to detect changes in what has been deposited within temporary storage area **205**. Relative to selectively accessible retrieval door **160**, an exemplary accessible retrieval door sensor node **240** has at least one sensor (e.g., motion sensor, orientation status sensor, accelerometer, magnetic sensor, and the like) that monitors for a change in the state of door **160**. Exemplary accessible retrieval door lock sensor node **245** has a sensor that is mounted relative to lock **165** to detect changes in the state of lock **165** used to open or secure door **160**. Exemplary external sensor node **250** has at least one sensor (e.g., motion sensor, proximity sensor, range sensor, and the like) that monitors for a change in the state of the near-by and proximate environment of exemplary connected logistics receptacle **150**.

(104) Those skilled in the art will appreciate that in some embodiments, an exemplary wireless accessory sensor node may focus on a particular component of the logistics receptacle **150** (e.g., entrance opening sensor node **210**) where the receptacle's bridge node may interact with multiple wireless accessory sensor nodes disposed on the receptacle **150**. However, in some embodiments, an exemplary wireless accessory sensor node may have different sensors that monitor different components of the logistics receptacle **150** such that the receptacle's bridge node may interact with a single wireless accessory sensor node disposed on the receptacle **150**.

(105) In light of what is shown in at least FIG. 2, an embodiment of enhanced connected logistics receptacle system for receiving and temporarily maintaining a delivery item (such as package **170**) and causing a backend server to initiate a dispatched logistics operation. Such an exemplary system as shown in FIG. 2 includes a storage receptacle (such as exemplary receptacle **150**), a bridge node (such as exemplary bridge node **200**), and at least one wireless accessory sensor node (such as

exemplary wireless accessory sensor node **210**). The storage receptacle (e.g., exemplary receptacle **150** in FIG. 2) includes an entrance opening (e.g., exemplary entrance opening **155** and/or entrance opening door **156** in FIG. 2) for receiving the delivery item, a temporary storage area (e.g., exemplary storage area **205** in FIG. 2) for temporarily maintaining the delivery item once the delivery item has been deposited within the storage receptacle through the entrance opening, and a selectively accessible retrieval door (e.g., exemplary door **160** in FIG. 2) providing access to the temporary storage area of the storage receptacle.

(106) The system's bridge node (e.g., exemplary bridge node **200** in FIG. 2) is mounted to the storage receptacle, and includes bridge node processor **201**, bridge node memory **202** coupled to the bridge node processor **201** (where the bridge node memory storage **202** maintains bridge node code for execution by the bridge node processor—such as CRL control & management code **305** shown in FIG. 3), long-range communication interface **203a** coupled to the bridge node processor **201** that can communicate with the backend server **100** over a first communication path, and short-range communication interface **203b** coupled to the bridge node processor **201** that can communicate over a second communication path.

(107) In operation of this embodiment, the exemplary system's wireless accessory sensor node (e.g., exemplary wireless accessory sensor node **210**) has at least one sensor that monitors for a change in state of the storage receptacle (e.g., a motion sensor that detects a change in motion related to the entrance opening **155** or motion through the entrance opening **155**). In such an exemplary system, the wireless accessory sensor node (e.g., wireless accessory sensor node **210** that monitors entrance opening **155**) is programmatically adapted and, thus, configured to detect the change in state of the storage receptacle based upon sensor data generated by the sensor (e.g., sensor data monitoring motion of or through the entrance opening **155**); record timestamped information reflecting the detected change in state of the storage receptacle (e.g., the detected motion related to the entrance opening **155**); and broadcast an updated advertising signal having a data available flag set within the updated advertising signal. Such a data available flag indicates the wireless accessory sensor node has event information available for upload by the bridge node. Such event information includes at least the timestamped information reflecting the detected change in state of the storage receptacle (e.g., event information with timestamped information logged by wireless accessory sensor node **210** on detected motion related to the entrance opening **155** as a change in state of receptacle **150**).

(108) In operation of this embodiment, the exemplary bridge node's processor (e.g., processing unit **201**), when executing the bridge node code maintained on the bridge node memory, is programmatically adapted and, thus, configured to be operative to detect the data available flag set within the updated advertising signal over the short-range communication interface; retrieve the event information available for upload from the wireless accessory sensor node using the short-range communication interface; and transmit the retrieved event information to the backend server using the long-range communication interface to cause the backend server to initiate the dispatched logistics operation related to the storage receptacle.

(109) FIG. 3 is a more detailed diagram of an exemplary bridge node **200** used as part of an exemplary connected logistics receptacle **150** in accordance with an embodiment of the invention. Referring now to FIG. 3, exemplary bridge node **200** is shown having processing unit **201** coupled to memory **202** (i.e., non-volatile memory storage **305**, volatile memory **310**), a wireless communication interface **203** (i.e., a long-range communication interface **203a** and a short-range communication interface **203b**), clock/timer **335**, battery/power interface **340**, and a GPS location circuitry **345**. In some embodiments where connected logistics receptacle **150** is implemented with a user interface **255**, exemplary bridge node **200** includes interface circuitry **300** that allows interactive communication with and control of elements implementing user interface **255** for interacting with a shipping customer and/or logistics personnel.

(110) Bridge node processing unit **201** is logic (such as a processor, microprocessor, controller,

microcontroller, or other programmable logic device), which generally performs computations on data and executes operational and application program code and other program modules within memory of the bridge node **200**. Those skilled in the art will appreciate that processing unit **201** may be implemented with a single processor or logic unit, a more powerful multi-core processor, or multiple processors depending upon the desired implementation. In one embodiment, processing unit **201** may be implemented with a low power microprocessor and associated peripheral circuitry. Less complex microcontrollers or discrete circuitry may be used to implement processing unit **201** as well as more complex and sophisticated general purpose or dedicated purpose processors.

(111) In yet another embodiment, exemplary processing unit **201** may be implemented by a low power ARM1176JZ-F application processor used as part of a single-board computer, such as the Raspberry Pi Computer Model B-Rev-2. The ARM application processor is embedded within a Broadcom BCM2835 system-on-chip (SoC) deployed in the Raspberry Pi Computer. In this embodiment, the Raspberry Pi Computer device operates as a core of exemplary bridge node **200** and includes a Secure Digital memory card slot and flash memory card operating as memory storage **305**, a 512 Mbyte RAM memory storage operating as volatile memory **310**, an operating system (such as Linux) stored on memory storage **305** and running in volatile memory **310**, and peripherals that implement interface circuitry **300**, clock/timer **335**, and a power supply operating as a power interface **340**.

(112) As shown in FIG. 3, exemplary bridge node **200** includes short-range communication interface **203b** as a programmable radio and an omni-directional antenna coupled to the processing unit **201**. In some embodiments, short-range communication interface **203b** may have variable RF power characteristics, such as receiver sensitivity and/or RF output signal power level. In some embodiments, interface **203b** may use an antenna with a different antenna profile when directionality may be desired. Those skilled in the art will appreciate that short-range communication interface **203b** may be implemented with hardware, implemented with a combination of hardware and software, as well as implemented as a software-defined radio (SDR). Examples of short-range communication interface **203b** may include other hardware (not shown) for operatively coupling the device to a specific short-range communication path (e.g., a Bluetooth® Low Energy (BLE) connection path communicating at 2.4 GHz). While BLE is used in one embodiment to enable a short-range communication protocol, variable power short-range interface **203b** may be implemented with other low power, short-range communication protocols, such as ultra-low power communication protocols used with ultra-wideband impulse radio communications, ZigBee protocols, IEEE 802.15.4 standard communication protocols, and the like.

(113) In one embodiment, various RF characteristics of the radio's transceiver, such as the RF output power and the RF receiver sensitivity may be dynamically and programmatically varied under control of processing unit **201**. In other embodiments, further RF characteristics of the radio's transceiver may be programmatically varied, such as frequency, duty cycle, timing, modulation schemes, spread spectrum frequency hopping aspects, etc., as needed to flexibly adjust the RF output signal as needed depending upon a desired implementation and anticipated use of exemplary bridge node **200**. In other words, embodiments of bridge node **200** (or any other bridge node) may have programmatically adjustable RF characteristics (such as an adjustable RF output signal power, an adjustable RF receiver sensitivity, the ability to switch to a different frequency or frequency band, etc.) in order to better communicate with different ones of the above-described types of wireless accessory sensor nodes that may be deployed on exemplary connected logistics receptacle **150**.

(114) As noted above with respect to FIG. 2, exemplary bridge node **200** also includes long-range communication interface **203a** to provide a communication path to backend server **100** via network **105**. Those skilled in the art will appreciate that reference to a communication interface may include an interface that collectively implements a plurality of different exemplary data

communication interfaces while still being generally referenced as “a communication interface” or “wireless communication interface.” Furthermore, those skilled in the art will appreciate that communication interface **203a** may be implemented with hardware, implemented with a combination of hardware and software, as well as implemented as a software-defined radio (SDR). In more detail, an exemplary embodiment of communication interface **203a** may be implemented with a radio in the form of an IEEE 802.11g compliant Wi-Fi transceiver or a cellular radio. In yet another embodiment, both a Wi-Fi transceiver and a cellular radio may be used when best available or according to a priority (e.g., first attempt to use the Wi-Fi transceiver if available due to possible lower costs; and if not, then rely on the cellular radio). In other words, an embodiment may rely upon diverse types of radios as part of interface **203a**, or when one radio is out of reach from a connecting infrastructure radio within network **105**. In a further embodiment, interface **203a** may be implemented as a module providing general purpose signal processing at its core as part of a software-defined radio, which provides flexibility in transmission techniques, software-defined antennas, and adaptive radio protocols that may be dynamically changed to implement interface **203a**. Thus, in these embodiments, long-range wireless communication interface **203a** is used to communicate retrieved event information about detected changes in the state or status of exemplary connected logistics receptacle **150** to backend server **100** as well as to receive adjustment messages (such as a tuned time parameter message) from backend server **100**.

(115) Those skilled in the art will appreciate that in the embodiments described herein, communication interfaces **203a** and **203b** may be implemented as a single wireless transceiver-based communication interface having both short-range and longer-range communication capabilities (i.e., may function as both a first and second communication interface as described in the various embodiments herein). This type of wider range communication interface may be implemented using LPWAN (Low Power Wide Area Network) connectivity, such as LTE 5G, LTE-M, and NB-IoT (NarrowBand IoT). LPWAN, also commonly referred to low-power wide-area (LPWA) network or just low-power network (LPN), is a type of wide-area network wireless communication format that allows for extended range, low-bandwidth communications for power sensitive application, such as with devices that are battery powered devices (e.g., ID nodes, mobile bridge nodes, container nodes, command nodes, and the like). Exemplary types of LPWAN may include ultra-narrowband (UNB) technology from Sigfox, random phase multiple access (RPMA) technology from Ingenu, and other long-range WAN protocol (LoRaWAN) technology as promoted by the LoRa Alliance of companies (e.g., IBM, MicroChip, Cisco, Semtech, Singtel, KPN, Bouygues Telecom). LTE-M is a communication technology that allows a node-based device (such as a sensor-based ID node or command node) to directly connect to a Long Term Evolution (4G) cellular network without a gateway and on batteries. NB-IoT is a low-power communication technology that applies a narrowband approach to cellular IoT (Internet of Things) communications allowing for usage of parts of the GSM spectrum bandwidth in unused 200 kHz bands.

(116) The clock/timer **335** for exemplary bridge node **200** generally provides one or more timing circuits used in, for example, keeping track of reporting periods and timing aspects for when bridge node **200** should attempt to detect set flags in advertising signals broadcast by wireless accessory sensor nodes, when to attempt to retrieve event information from wireless accessory sensor nodes, and when to transmit the retrieved event information to the backend server **100**. In an embodiment where bridge node **200** conserves power by entering a sleep or dormant state for a predetermined time period as part of overall power conservation techniques, clock/timer **335** may assist processing unit **201** in managing timing operations, such as when to have bridge node **200** wake from a low power state (e.g., at the beginning of a reporting period for the bridge node).

(117) The battery/power interface **340** for bridge node **200** generally powers the circuitry implementing exemplary bridge node **200**. In one embodiment, battery/power interface **340** may be a rechargeable power source. For example, a bridge node may have a rechargeable power source along with a solar panel (e.g., a solar panel externally mounted on top of receptacle **150** or on one

or more panels of receptacle **150**) that charges the onboard rechargeable power source in order to help facilitate deployment of the connected logistics receptacle **150** in a remote location. In another embodiment, battery/power interface **340** may be a non-rechargeable power source (e.g., battery) intended to be disposed of after use. In yet another embodiment, battery/power interface **340** may be a power interface connector (such as a power cord and internal power supply on bridge node **200** where such an internal power supply is powered externally to receptacle **150**). In other words, when an exemplary bridge node is in a fixed or stationary configuration, it may be powered by a power cord connected to an electrical outlet, which is coupled to an external power source. Such an external power source (not shown, and depending on the availability of such a source proximate the location of the receptacle **150**), or may be operated by an external battery (not shown) or be connected to an existing power grid from which power is drawn.

(118) Likewise, those skilled in the art will appreciate that each of the illustrated exemplary wireless accessory sensor nodes in FIG. 2 may also be powered via such an external power source or may be operated by their own respective battery. In battery-operated embodiments, such a battery may be implemented as a rechargeable power source or a non-rechargeable power source intended to be disposed of after use.

(119) Referring back to FIG. 3, the interface circuitry **300** on bridge node **200** couples processing unit **201** to user interface **255**. In one embodiment, user interface **255** may provide a visual or projected display, as well as interactive buttons or soft keys, switches, and a pointing device to facilitate interaction with the display. In a further embodiment, a data entry device (e.g., keyboard, button, switch, soft keys, touch-sensitive input device, and the like) may also be used as part of the user interface **255**. In some embodiments, an exemplary user interface **255** may be implemented with an on-demand request input (e.g., button, soft key, and the like) that retrieves input from a customer to responsively initiate retrieval of information by bridge node **200** from one or more exemplary wireless accessory sensor nodes and further cause transmission of the retrieved information to backend server **100**. In such an embodiment, authentication of the customer by bridge node **200** may be implemented.

(120) In other embodiments, user interface **255** may take the form of one or more lights (e.g., status lights), audible input and output devices (e.g., a microphone and speaker), or an interactive touchscreen.

(121) As previously noted, an exemplary bridge node, such as bridge node **200**, may be positioned in a known fixed location (where bridge node **200** may not have onboard location circuitry such as circuitry **345**) or, alternatively, may include dedicated onboard location positioning circuitry (e.g., GPS circuitry **345**) to allow the bridge node **200** to self-determine its current location, movement, speed, and the like. In other embodiments, alternative circuitry and techniques may be relied upon for location circuitry **345** (rather than GPS), such as location circuitry compatible with other satellite-based systems (e.g., the European Galileo system, the Russian GLONASS system, the Chinese Compass system), terrestrial radio-based positioning systems (e.g., cell phone tower-based or Wi-Fi-based systems), infrared positioning systems, visible light based positioning systems, and ultrasound-based positioning systems).

(122) Regarding memory storage **305** and volatile memory **310** shown in FIG. 3, both are operatively coupled to processing unit **201** in exemplary bridge node **200**. Both memory components provide program elements used by processing unit **201** and maintain and store data elements accessible to processing unit **201**. In the embodiment shown in FIG. 3, exemplary memory storage **305** maintains executable program code (e.g., connected logistics receptacle (CLR) control and management code **315**, an operating system (not shown), and the like) as well as other data used in the operation of bridge node **200** (e.g., event information **320**, status flag info **325**, historic use info **327**, location data **330** that is related to the location of bridge node **200** as deployed on an exemplary connected logistics receptacle **150** as well as threshold data and levels that may be used in operation of bridge node **200**). Those skilled in the art will appreciate that

memory storage **305** is a tangible, non-transient computer readable medium on which information (e.g., executable code/modules, operational data, sensor measurements, etc.) may be kept in a non-volatile and non-transitory manner. Volatile memory **310** is typically a random access memory (RAM) structure used by processing unit **201** during operation of the bridge node **200**. Upon power up of bridge node **200**, volatile memory **310** may be populated with an operational program (such as an operating system and then CRL control and management code **315**) or specific program modules that help facilitate particular operations of bridge node **200**. And during operation of bridge node **200**, volatile memory **310** may also include certain data generated as the bridge node **200** executes instructions as programmed or loaded from memory storage **305**.

(123) Generally, an embodiment of CLR control and management code **315** is a collection of executable software features implemented as programmatic functions or program modules that generally control the behavior of a bridge node, such as bridge node **200**, as it performs and functions as described in the various embodiments disclosed herein. In other words, CLR control and management code **315** may also include further program code specific for bridge node functionality described in the embodiments described in more detail below that use a bridge node. As such, the collective code executing on a bridge node, such as bridge node **200** (or any of the other implementations of a bridge node as described herein), acts to programmatically configure the bridge node **200** beyond that of a generic processing device in order to be specially adapted, via such program code, to be operative to function unconventionally—whether alone with the specific functionality described herein or as part of a system.

(124) Event information **320** is a data structure generated by bridge node **200** based upon data retrieved from one or more wireless accessory sensor node(s). Exemplary event information **320** maintains timestamped information reflecting a detected change in state of connected logistics receptacle **150** and an identifier indicating a type of detected change in state of the connected logistics receptacle **150**. The timestamped information, for example, may indicate a particular time (e.g., time of day, date) corresponding to the detected change. In other examples, the timestamped information may indicate a series of times and/or dates corresponding to a series of related changes to the receptacle, where such a series of related changes to the receptacle are detected by the wireless accessory sensor node as the detected change in state of the storage receptacle. The identifier (which may be also referred to as state information) in event information **320** may, for example, identify details on the type of change detected relative to the state of particular components of the receptacle (e.g., a detected change in motion of or motion through entrance opening **155**, a detected image of package **170** moving into temporary storage area **205**, a detected chemical within temporary storage area **205**, a detected change in weight in what is maintained within receptacle **150**, a detected change in position of the selectively accessible retrieval door **160**, a detected change in the state of lock **165** for door **160**, a detected change in what has been placed within a predetermined range of receptacle **150** as monitored and detected by an external motion sensor or a proximity-based range sensor, etc.).

(125) The status flag information **325** in memory **202** of bridge node **200** is a data structure reflecting information on any status flag (e.g., data available flag) received as part of an advertising signal broadcast from one or more of the wireless accessory sensor nodes. In some embodiments, status flag information **325** may reflect that bridge node **200** has detected a single signal from one of the wireless accessory sensor nodes where that signal has a data available flag set (indicating event information is available for upload). In other embodiments, status flag information **325** may reflect that bridge node **200** has detected multiple signals from different ones of the wireless accessory sensor nodes where each of those signals has a data available flag set (indicating different event information is available for upload from different wireless accessory sensor nodes). In still other embodiments, status flag information **325** may more generally reflect that bridge node **200** has detected a signal from one or more of the wireless accessory nodes where that signal has a status flag set indicating at least that the respective wireless accessor sensor node remains operative

(e.g., a heartbeat type of status that may not be indicative that new data is now available for upload by bridge node **200** but simply that the wireless accessory sensor node has not failed or run out of power). Those skilled in the art will appreciate the situation where a signal may have a heartbeat type of status flag set as well as a data available flag set, which indicates to bridge node **200** that the particular wireless accessory sensor node remains nominally operable and has event information available for upload by the bridge node **200**.

(126) Historic use information **327** in memory **202** of bridge node **200** is a data structure reflecting accumulated and updated information tracked by bridge node **200** on use of particular components of the connected logistics receptacle **150** associated with bridge node **200** based upon the event information **320** retrieved over time. Some embodiments may rely upon backend server **100** to process and track historic use information reported to server **100** as retrieved event information **830** (which then may be used to update information in management profile **825**) and where server **100** may then update bridge node **200** with historic use information **327** or updates to such information **327**. However, other embodiments may have the bridge node **200** itself track the retrieved event information **320** and, based on data in information **320**, generate and/or update historic use information **327** maintained locally on the bridge node **200**.

(127) Location data **330** in memory **202** of bridge node **200** is a data structure used to store and maintain location information related to the location of bridge node **200** as deployed on an exemplary connected logistics receptacle **150**. As noted above, some system embodiments may have exemplary connected logistics receptacle **150** as a mobile type of apparatus (e.g., one that is moved between locations, where the receptacle **150** is disposed on a mobile platform, such as a mobile delivery vehicle). In such an embodiment, bridge node **200** may be implemented as a mobile bridge node, where the mobile bridge node includes location circuitry (e.g., GPS circuitry **345**) operative to generate location data **330** reflecting a current location of the mobile bridge node mounted to the storage receptacle **150**. In some embodiments, the bridge node **200** may include the current location of bridge node **200** as indicated by location data **300** along with the retrieved event information transmitted to the backend server.

(128) While FIG. **3** described above provides further details regarding an exemplary bridge node (e.g., exemplary bridge node **200**), FIG. **4** is a detailed diagram of an exemplary wireless accessory sensor node device used as part of an exemplary connected logistics receptacle in accordance with an embodiment of the invention. As previously mentioned, different exemplary wireless accessory sensor nodes **210**, **215**, **220**, **225**, **230**, **235**, **240**, **245** and **250** as shown in FIG. **2** are operative to detect different types of changes in the state of exemplary connected logistics receptacle **150**, log timestamped information related to such changes, and responsively generate updated broadcasting signals having a status flag set (e.g., a data available flag set indicating event information is available for the bridge node to upload). While different exemplary wireless accessory sensor nodes **210**, **215**, **220**, **225**, **230**, **235**, **240**, **245** and **250** may use different types and configurations of sensors to detect different types of changes in the state of exemplary connected logistics receptacle **150**, exemplary wireless accessory sensor node **210** is shown in FIG. **4** in more detail to explain and describe exemplary internal components, hardware, and software deployed in embodiments of a wireless accessory sensor node and that are used to monitor different parts of and areas around exemplary connected logistics receptacle.

(129) Referring now to FIG. **4**, exemplary wireless accessory sensor node **210** is a low-power transceiver-based processing device having a sensor node processing unit **400** (also referred to as a sensor node processor), sensor node memory **405**, a short-range wireless communication interface **440**, a clock/timer **435**, battery/power interface **445**, interface circuitry **402**, and various exemplary sensors. The sensor node processing unit **400** is in operative communication with at least one sensor (e.g., with one of onboard sensors **450a-450c** through internal bus connections, with a separate sensor **450d** through a wired connection off the sensor node, via interface circuitry **402**, and/or with a separate sensor **450e** through a wireless connection via short-range communication

interface **440**). While FIG. 4 is showing details related to exemplary wireless accessory sensor node **210** that monitors entrance opening **155**, those skilled in the art will appreciate that the type of sensor(s) used with a particular wireless accessory sensor node will depend upon the particular component of receptacle **150** (or area within or near receptacle **150**) being monitored.

(130) Different types of sensors may be used for one or more of sensors **450a-450c**, such a sensor implemented with a motion sensor, an orientation status sensor, an accelerometer, a multiple-axis accelerometer, and/or a magnetic sensor to monitor entrance opening **155** by exemplary wireless accessory sensor node **210**. In some embodiments, exemplary wireless accessory sensor node **210** may use a combination of more than one type of sensor to do such monitoring—e.g., where sensor **450a** is a motion sensor that detects motion of entrance opening **155** or motion through entrance opening **155**, where sensor **450b** is an orientation status sensor that detects changes in the orientation of entrance opening **155**, and where sensor **450c** is an accelerometer type of sensor that detects the acceleration of entrance opening **155** when such a component is moved (e.g., when entrance opening articulates when receiving a package **170**). Those skilled in the art will appreciate that with further sensors (e.g., sensors **450d**, **450e**, and more), an embodiment of exemplary wireless accessory sensor node may deploy an increasing variety of types of sensors to monitor a particular component of receptacle **150** or area relative to receptacle **150** in an increasingly robust manner. Additionally, an embodiment may deploy a second wireless accessory sensor node to deploy such a different type of sensor when monitoring the same component of receptacle **150** or area relative to receptacle **150** in a manner that does not have multiple sensors per sensor node but opts for more dedicated sensor node processing power per sensor.

(131) For example, as shown in FIG. 2, sensor data may be generated by a sensor in a wireless accessory sensor node **210** that monitors for changes in entrance opening **155** where the sensor data generated by that sensor indicates a change in state of entrance opening **155** as the change in state of the storage receptacle (e.g., exemplary connected logistics receptacle **150**). In such an example, further embodiments may implement that sensor as a motion sensor detecting a change in motion of entrance opening **155** as the change in state of the storage receptacle; a motion sensor detecting a change in motion of entrance opening **155** and a failure to return to a prior state of entrance opening **155** as the change in state of the storage receptacle; or a status sensor detecting a change in orientation of entrance opening **155** (and/or a failure to return to a prior state of the entrance opening **155**) as the change in state of the storage receptacle. When the sensor in this example detects a failure to return to the prior state of entrance opening **155**, the type of change may indicate an overflow state of the storage receptacle and the retrieved event information transmitted to the backend server by bridge node **200** is indicative of such an overflow state of the storage receptacle.

(132) Other embodiments may implement the sensor that monitors entrance opening **155** (via wireless accessory sensor node **210**) as a motion sensor detecting movement of what is received through the entrance opening **155** as the change in state of the storage receptacle; an accelerometer detecting a change in motion of the entrance opening **155** as the change in state of the storage receptacle; a multiple-axis accelerometer detecting a change in multi-dimensional motion of the entrance opening **155** as the change in state of the storage receptacle; or a magnetic sensor detecting a change in position of the entrance opening **155** as the change in state of the storage receptacle.

(133) In another example, as shown in FIG. 2, sensor data may be generated by a sensor in a wireless accessory sensor node that monitors for changes in temporary storage area **205** where the sensor data generated by that sensor indicates a change in state of temporary storage area **205** as the change in state of the storage receptacle (e.g., exemplary connected logistics receptacle **150**). In such an example, further embodiments may implement that sensor as a motion sensor detecting motion within the temporary storage area **205** as the change in state of the storage receptacle; an image sensor detecting a change of what is stored within the temporary storage area **205** as the

change in state of the storage receptacle; a scale disposed at a bottom of the temporary storage area **205** where the scale detects a change in weight of what is stored within the temporary storage area **205** as the change in state of the storage receptacle; a force sensor disposed within the temporary storage area **205** where the force sensor detects a change in what has been deposited within the temporary storage area **205** as the change in state of the storage receptacle; a load cell operative to detect an impact force related to the change in what has been deposited within the temporary storage area **205** as the change in state of the storage receptacle; a light sensor detecting a change in light within the temporary storage area **205** as the change in state of the storage receptacle; and a chemical sensor detecting a chemical within the temporary storage area **205** as the change in state of the storage receptacle.

(134) In yet another example, as shown in FIG. 2, sensor data may be generated by a sensor in a wireless accessory sensor node **240** that monitors for changes in selectively accessible retrieval door **160** where the sensor data generated by that sensor indicates a change in state of selectively accessible retrieval door **160** as the change in state of the storage receptacle (e.g., exemplary connected logistics receptacle **150**). In such an example, further embodiments may implement that sensor as a motion sensor detecting a change in motion of the selectively accessible retrieval door **160** as the change in state of the storage receptacle; a magnetic sensor detecting a change in position of the selectively accessible retrieval door **160** as the change in state of the storage receptacle; a motion sensor detecting a change in motion of the selectively accessible retrieval door **160** and a failure to return to a prior state of the selectively accessible retrieval door **160** as the change in state of the storage receptacle; a status sensor detecting a change in orientation of the selectively accessible retrieval door **160** and a failure to return to a prior state of the selectively accessible retrieval door **160** as the change in state of the storage receptacle. When the sensor in this example detects a failure to return to the prior state of door **160**, the type of change may indicate an unsecured state of the storage receptacle and the retrieved event information transmitted to the backend server by bridge node **200** is indicative of such an unsecured state of the storage receptacle.

(135) In yet another example, as shown in FIG. 2, sensor data may be generated by a sensor in a wireless accessory sensor node **245** that monitors lock **165** for changes in the state of lock **165** as the change in state of the storage receptacle (e.g., exemplary connected logistics receptacle **150**).

(136) In still another example, as shown in FIG. 2, sensor data may be generated by a sensor in wireless accessory sensor node **250** that monitors an area outside of exemplary connected logistics receptacle **150**. Such a sensor, for example, may be implemented as an external motion sensor detecting a change in what has been placed within a predetermined range of the storage receptacle as the change in state of the storage receptacle; or a range sensor detecting a change in what has been placed within a predetermined range of the storage receptacle as the change in state of the storage receptacle. Such a range sensor may be, for example, a proximity sensor, a depth sensor, a LiDAR sensor, an infrared sensor, or a laser-based sensor that is operable to detect a distance from the sensor to nearby objects.

(137) Those skilled in the art will appreciate that in some embodiments, one or more of the sensors (**450a-450e**) coupled to processor **400** and used as part of an exemplary wireless accessory sensor node may be implemented using multiple sensor elements for monitoring different types of changes in the state of the storage receptacle. Such different types of sensor elements may, for example, be a sensor element used to monitor a change relative to light within the storage receptacle, to monitor a change relative to motion within the storage receptacle, to capture one or more images of what is disposed within the receptacle, and to monitor for and detect a chemical within the storage receptacle. For example, when using a chemical sensor or chemical sensing element as part of a wireless accessory sensor node, the chemical being monitored for and detected (e.g., a vaporous chemical) may be a chemical indicative of a hazardous environmental condition, a chemical indicative of an explosive, a chemical indicative of a fire, or a chemical indicative of a targeted

biological agent.

(138) In one embodiment, one sensing element of the sensor may be disposed on the storage receptacle (e.g., exemplary connected logistics receptacle **150**) and operative to monitor a state of the entrance opening **155**, where a second of the sensor elements also disposed on the storage receptacle is operative to monitor a state of the selectively accessible retrieval door **160** of the storage receptacle. Extending this example further, another embodiment may have such a sensor where a third of the sensor elements is also disposed on the storage receptacle and operative to monitor a state of the temporary storage area **205** of the storage receptacle.

(139) In other embodiments, an exemplary wireless accessory sensor node may use multiple wireless sensors (e.g., sensor **450e** and others like it wirelessly coupled to processor **400** via interface **440**) disposed on different parts of the storage receptacle, where each of the wireless sensors monitor for different types of changes in the state of the storage receptacle. For example, in such an embodiment a first of the wireless sensors monitors a state of the entrance opening **155**, a second of the wireless sensors monitors a state of the selectively accessible retrieval door **160**, while a third of the wireless sensors monitors a state of the temporary storage area **205** of the storage receptacle.

(140) Referring back to FIG. **4**, sensor node processing unit **400** may be implemented with a low power consumption microprocessor or microcontroller, having a core processing section, and associated peripheral circuitry as dictated by the needs of the particular application. Less complex microcontrollers or discrete circuitry may also be used to implement sensor node processing unit **400**, but those skilled in the art will understand that some embodiments may use more complex and sophisticated microprocessors or microcontrollers. Additionally, exemplary sensor node processing unit **400** may be integrated into a single chip transceiver used as a core of an exemplary wireless accessory sensor node (e.g., wireless accessory sensor node **210** that monitors entrance opening **155**). As such, exemplary sensor node processing unit **400** operates as a transceiver-based processing core of an exemplary wireless accessory sensor node (such as sensor node **210**).

(141) The short-range wireless communication interface **440** is generally a programmable radio and an omni-directional antenna coupled to the sensor node processing unit **400**. In other embodiments, interface **440** may use an antenna with a different antenna profile when directionality may be desired. Those skilled in the art will appreciate that short-range communication interface **440** may be implemented with hardware, implemented with a combination of hardware and software, as well as implemented as a software-defined radio (SDR). Examples of variable power short-range communication interface **440** may include other interfacing hardware or software elements (not shown) for operatively coupling the device to a specific short-range communication path (e.g., a Bluetooth® Low Energy (BLE) connection path communicating at 2.4 GHz, a NB-IoT connection path using a low-power communication technology that applies a narrowband approach to cellular IoT (Internet of Things) communications allowing for usage of parts of the GSM spectrum bandwidth in unused 200 kHz bands, and the like).

(142) A signal broadcast by wireless communication interface **440** is generally referred to as an advertising signal—a signal advertised or otherwise broadcast by the interface **440** on the particular wireless accessory sensor node. Such an exemplary advertising signal, in general, may include header information (with one or more flags or other information) as well as data. In more detail, an exemplary advertising signal may be formatted as a Bluetooth® Low Energy (BLE) signal formatted with header information and in an advertisement packet type of configuration with different types of metadata in different parts of the packet. Such header information may generally include a flag, such as a status flag. In one embodiment, a status flag being set as part of the signal indicates at least that the respective wireless accessor sensor node broadcasting the signal remains operative (e.g., a heartbeat type of status that may not be indicative that new data is now available for upload by bridge node **200** but simply that the wireless accessory sensor node is operating nominally, has not failed, and/or run out of power). In another embodiment, the status flag may be

in the form of a data available flag, which is set to indicate new event information is available for upload from the respective wireless accessor sensor node broadcasting the signal.

(143) The clock/timer **435** for exemplary wireless accessory sensor node **210** generally provides one or more timing circuits used in, for example, time delay, pulse generation, and oscillator applications. In an embodiment where exemplary wireless accessory sensor node conserves power by entering a sleep or dormant state for a predetermined time period as part of overall power conservation techniques, timer **435** assists processing unit **400** in managing timing operations.

(144) The battery/power interface **445** for exemplary wireless accessory sensor node **210** is a type of power source that generally powers the low power circuitry implementing exemplary wireless accessory sensor node **210**. In one embodiment, battery **445** may be a rechargeable power source. In other embodiments, battery **445** may be a non-rechargeable power source intended to be disposed of after use. In some embodiments, the power source may involve alternative energy generation, such as a solar cell. In other embodiments, the battery/power interface **445** may be coupled to a common power source used to power exemplary bridge node **200**.

(145) In additional embodiments, one skilled in the art will appreciate that similar functionality in an exemplary wireless accessory sensor node may be implemented in other types of hardware. For example, an exemplary wireless accessory sensor node may be implemented with specially optimized hardware (e.g., a particular application specific integrated circuit (ASIC) having the same operational control and functionality as sensor node control and management code, as described below, discrete logic, or a combination of hardware and firmware depending upon requirements of the exemplary wireless accessory sensor node, such as power, processing speed, level of adjustability for the RF characteristics, number and types of sensors coupled to the processor **400**, cost, space, etc.

(146) As noted above, exemplary wireless accessory sensor node includes memory **405** accessible by the sensor node processing unit **400**. Memory storage **410** and volatile memory **412** are each operatively coupled to sensor node processing unit **400**. Both memory components provide programming and data elements used by sensor node processing unit **400**. In the embodiment shown in FIG. **4**, memory storage **410** maintains a variety of program code (e.g., sensor node (SN) control and management code **415**) and other data elements (e.g., sensor data **420**, timestamped information **425**, state information **430** that identifies the type of detected changes in the receptacle **150**, and the like). Memory storage **410** is a tangible, non-transient computer readable medium on which information (e.g., executable code/modules, node data, sensor measurements, etc.) may be kept in a non-volatile and non-transitory manner. Examples of such memory storage **410** may include a solid state memory, ROM, flash memory, or other media structure that allows long term, non-volatile storage of information. In contrast, volatile memory **412** is typically a random access memory (RAM) structure used by sensor node processing unit **400** during operation of the exemplary wireless accessory sensor node. Upon power up of exemplary wireless accessory sensor node **210**, volatile memory **412** may be populated with an operational program (such as SN control and management code **415** or a simple operating system (not shown)) or specific program modules that help facilitate particular operations of exemplary wireless accessory sensor node **210**. And during operation of the exemplary wireless accessory sensor node, volatile memory **412** may also include certain data (e.g., sensor data **420**, timestamped information **425**, state information **430** that identifies the type of detected changes in the receptacle **150**, and the like) generated as the exemplary wireless accessory sensor node **210** executes instructions as programmed or loaded from memory storage **410**. However, those skilled in the art will appreciate that not all data elements illustrated in FIG. **4** must appear in memory storage **410** and volatile memory **412** at the same time.

(147) Generally, an exemplary embodiment of SN control and management code **415** is a collection of software features implemented as programmatic functions or program modules that control the behavior of an exemplary wireless accessory sensor node (e.g., wireless accessory sensor node **210**). In an embodiment, the functionality of code **415** may be generally similar as implemented in

different wireless accessory sensor nodes. However, those skilled in the art will appreciate that while some principles of operation are similar between such wireless accessory sensor nodes, other embodiments may implement the functionality with some degree of specialization or in a different manner depending on the desired application and use of the node, and the type of sensor, sensors, and/or different sensor elements deployed on a particular wireless accessory sensor node. In other words, SN control and management code **415** may also include further program code specific for functionality described in the embodiments described in more detail below that use an exemplary wireless accessory sensor node. As such, the collective code executing on an exemplary wireless accessory sensor node, such as exemplary wireless accessory sensor node **210** (or any of the other implementations of exemplary wireless accessory sensor nodes as described herein), acts to programmatically configure the wireless accessory sensor node beyond that of a generic processing device in order to be specially adapted, via such program code, to be operative to function unconventionally—whether alone with the specific functionality described herein or as part of a system involving an exemplary connected logistics receptacle **150**.

(148) Sensor data **420** in volatile memory **415** and/or memory storage **410** may exist in memory **405** as a type of data collected from an onboard sensor (e.g., one of onboard sensors **450a-450c** through internal bus connections, a separate sensor **450d** through a wired connection off sensor node **210** via interface circuitry **402**, and/or a separate sensor **450e** through a wireless connection via short-range communication interface **440**). Such sensor data may reflect or otherwise indicate a state or status of a particular component of the storage receptacle (e.g., exemplary connected logistics receptacle **150**)—more particularly, a change in the state or status of the particular component of the storage receptacle. For example, sensor data **420** may include data reflecting or indicating motion of entrance opening **155** (e.g., when an articulating entrance opening **155** moves as it receives package **170**, or when the door **156** to entrance opening **155** moves as a static version of entrance opening **155** receives package **170** being deposited within connected logistics receptacle **150**). In other examples involving other wireless accessory sensor nodes, those skilled in the art will appreciate that such sensor data **420** may include image data, video data, light data, force or weight data, data indicative of the presence of a particular chemical, motion data, proximity or range data, or other sensor information indicative of a change in status or orientation.

(149) Timestamped information **425** in memory **405** is generally a data structure with logged information on the timing of detected changes in the state or status of a particular component of or area relative to exemplary connected logistics receptacle **150** being monitored by that particular wireless accessory sensor node and based upon sensor data generated related to such detected changes. The timestamped information **425**, for example, may indicate a particular time (e.g., time of day, date) corresponding to the detected change. In other examples, the timestamped information **425** may indicate a series of times and/or dates corresponding to a series of related detected changes, where such a series of related changes to the particular component of or area relative to exemplary connected logistics receptacle **150** are detected by the wireless accessory sensor node as the detected change in state of the storage receptacle.

(150) State information **430** in memory **405** is generally a data structure with information that includes an identifier indicating a type of detected change in state in the particular component of or area relative to exemplary connected logistics receptacle **150** being monitored by that particular wireless accessory sensor node. For example, the identifier information in the state information **430** may, for example, identify that the detected change in state is related to a detected change in motion of or motion through entrance opening **155**, a detected image of package **170** moving into temporary storage area **205**, a detected chemical within temporary storage area **205**, a detected change in weight in what is maintained within receptacle **150**, a detected change in position of the selectively accessible retrieval door **160**, a detected change in the state of lock **165** for door **160**, a detected change in what has been placed within a predetermined range of receptacle **150** as monitored and detected by an external motion sensor or range sensor, etc.).

(151) In operation in an embodiment, exemplary sensor node processing unit **401** (e.g., a programmable processor or controller), when executing SN control and management code **415** maintained within memory storage **410** and loaded into volatile memory **415**, becomes programmatically adapted and specially configured to be operative to receive the sensor data generated by the at least one sensor (e.g., sensor data on movement of entrance opening **210** as detected by sensor **450a**); detect the change in state of the storage receptacle (e.g., a change in the state of entrance opening **210** of exemplary connected logistics receptacle **150**) based upon the sensor data now stored as sensor data **420**; record the timestamped information **425** reflecting the detected change in state of the storage receptacle (e.g., the detected change in the state of entrance opening **210** of exemplary connected logistics receptacle **150**); and then broadcast an updated advertising signal having a data available flag set within the updated advertising signal. As noted above, such a data available flag indicates the wireless accessory sensor node **210** has event information available for upload by bridge node **200** (e.g., exemplary event information **320** as uploaded and stored on bridge node **200**), where such event information includes at least timestamped information **425** reflecting the detected change in state of the storage receptacle and may include identifier information from state information **430**.

(152) FIGS. 5A-5E are a series of diagrams illustrating different exemplary embodiments of an entrance opening to an exemplary connected logistics receptacle in accordance with different embodiments of the invention. Referring now to FIG. 5A, exemplary connected logistics receptacle **150** is shown in part where the entrance opening is implemented an articulating entrance door **156** that, when open as shown in FIG. 5B, allows the delivery item (e.g., package **170**) to be received and transferred into the temporary storage area **205** of receptacle **150**. In such an embodiment where the structure **155** shown in FIG. 5A operates as a static chute, as articulating entrance door **156** (which may have a handle) is opened as shown in FIG. 5B, package **170** may be placed within entrance **155** so that package **170** can slide down and into receptacle **150**. Those skilled in the art will appreciate that in some embodiments, the entrance opening may be considered to be implemented by chute **155**, a combination of chute **155** and door **156** (generally referenced as **155/156**), a hole in receptacle **150** covered by door **160**, a hold in receptacle **150** secured by a lockable door (similar to door **160**), or simply a hole opening alone in receptacle **150** allowing access to within receptacle (i.e., a place through which to deposit a delivery item).

(153) FIG. 5C illustrates an embodiment where entrance opening **155'** is a static chute with no articulating door that allows the delivery item (e.g., package **170**) to be inserted through the static chute and into temporary storage area **205** of receptacle **150**. Without a door, the embodiment of entrance opening **155'** shown in FIG. 5C includes an overhang **500** as a type of weather protection that allows package access into opening **155'** but helps prevent rain from entering opening **155'**. FIGS. 5D and 5E illustrate an embodiment where the entrance opening comprises an articulating drop chute **155''** that allows the delivery item (e.g., package **170**) to be received in a first (mostly horizontal) position of the articulating drop chute **155b** as shown in FIG. 5D. In FIG. 5E, the articulating drop chute **155''** changes position/orientation and transfers the received delivery item (e.g., package **170**) to temporary storage area **205** in a second position of the articulating drop chute.

(154) As noted above, embodiments of an exemplary connected logistics receptacle **150** deploy bridge node **200** and various wireless accessory sensor nodes operating in a distributed manner so as to operate more efficiently and use such distinct types of monitoring and communication devices to better monitor, detect, and report different kinds of state changes with respect to the receptacle **150** as types of meaningful interactions and engagements with receptacle **150**. From the perspective of an exemplary bridge node used in an exemplary system involving exemplary connected logistics receptacle **150**, the bridge node (e.g., bridge node **200**) may operate within a programmatically determined reporting period during which the bridge node wakes, attempts to detect if any data is available from any of the wireless accessory sensor nodes, and during which retrieved event

information may be transmitted to the backend server **100**. FIGS. 6A-6D are exemplary timing diagrams illustrating activity during such exemplary reporting periods for an exemplary connected logistics receptacle in accordance with different embodiments of the invention.

(155) Referring now to FIG. 6A, an exemplary timeline **600** of activity is shown having a beginning time at RP.sub.B where an exemplary reporting period for bridge node **200** begins and an ending time at RP.sub.E where the exemplary reporting period for bridge node **200** ends. In general, a bridge node's reporting period is considered a period of time during which the bridge node has been programmed to be operational. In some embodiments, the reporting period may be a time period defined by backend server **100** and provided by backend server **100** to bridge node **200**. In more detail, the reporting period may be implemented as a dynamically adjusted time period stored in the bridge node memory **202**, where the dynamically adjusted time period is defined by a reporting period update message sent by the backend server **100** to the bridge node **200** as part of adjusting or tuning operations performed by backend server **100** on one or more of exemplary connected logistics receptacle.

(156) In one embodiment, bridge node **200** may check for and retrieve data during the reporting period at a predetermined time of day. In more detail, an embodiment may have bridge node processor **201**, when executing CLR control and management code **315** (i.e., a type of bridge node code), programmatically adapted and operative to detect a data available flag set within the updated advertising signal over short-range communication interface **203b** by being further operative to wake from a low power state at a predetermined time of day (e.g., at time RP.sub.B or sometime during the exemplary reporting period) and after that predetermined time of day, detect the data available flag set within the updated advertising signal over the short-range communication interface **203b**. For example, as shown in FIG. 6A, bridge node **200** wakes from a low power state at time RP.sub.B, detects a data available flag set within an updated advertising signal from a wireless accessory sensor node deployed on connected logistics receptacle **150** (e.g., wireless accessory sensor node **210**) at time t.sub.1 (e.g., sometime after time RP.sub.B), and retrieves event information available for upload from wireless accessory sensor node **210** at time t.sub.2. In some instances, the data available flag may be a status flag indicative of a count related to the event information available for upload (e.g., a count of how many changes in state of a particular component of receptacle **150** have been detected and logged by a particular wireless accessory sensor node). In this example of FIG. 6A, bridge node **200** is then able to transmit the retrieved event information to backend server at time t.sub.3 prior to or at RP.sub.E.

(157) In FIG. 6B, another exemplary timeline **605** of activity is shown having a beginning time at RP.sub.B where an exemplary reporting period for bridge node **200** begins and an ending time at RP.sub.E where the exemplary reporting period for bridge node **200** ends. However, the activity shown in timeline **605** illustrates how a bridge node may retrieve event information and transmit such event information to backend server more than once during an exemplary reporting period. Referring now to FIG. 6B, an embodiment of bridge node processor **201**, when executing CLR control and management code **315** (i.e., a type of bridge node code), is programmatically adapted and operative to detect a data available flag set within an updated advertising signal over short-range communication interface **203b** after a beginning of a reporting period for bridge node **200**, and then detect, before an end of the reporting period for the bridge node, a second data available flag set within a subsequent advertising signal broadcast by the wireless accessory sensor node, retrieve additional event information available for upload from the wireless accessory sensor node related to the detected second data available flag, and transmit, using the long-range communication interface **203a**, the retrieved additional event information to the backend server **100** for use by the backend server **100** in initiating the dispatched logistics operation. For example, as shown in FIG. 6B, bridge node **200** wakes from a low power state at time RP.sub.B, detects a first data available flag set within an updated advertising signal from a wireless accessory sensor node deployed on connected logistics receptacle **150** (e.g., wireless accessory sensor node **210**) at time

t.sub.4 (e.g., after time RP.sub.B), retrieves event information available (EIA) for upload from wireless accessory sensor node **210** at time t.sub.5, transmits the retrieved EIA at time to, detects a second data available flag set at time t.sub.7 (from the same or a different wireless accessory sensor node), retrieves the additional EIA at time to, and transmits the additional retrieved EIA at time to at or prior to RP.sub.E. In some instances, the data available flag may be a status flag indicative of a count related to the event information available for upload (e.g., a count of how many changes in state of a particular component of receptacle **150** have been detected and logged by a particular wireless accessory sensor node). In this example of FIG. **6A**, bridge node **200** is then able to transmit the retrieved event information to backend server at time t.sub.3 prior to or at RP.sub.E. In this example, event information may be retrieved more than once by bridge node **200** and transmitted to backend server **100** upon retrieving any such event information.

(158) However, as shown in FIG. **6C**, other embodiments may have bridge node **200** retrieving event information more than once during the reporting period and may have bridge node **200** initiating a single transmission of accumulated event information to backend server **100** at or near the end of the reporting period. In FIG. **6C**, yet another exemplary timeline **610** of activity is shown having a beginning time at RP.sub.B where an exemplary reporting period for bridge node **200** begins and an ending time at RP.sub.E where the exemplary reporting period for bridge node **200** ends.

(159) Referring now to FIG. **6C**, an embodiment of bridge node processor **201**, when executing CLR control and management code **315** (i.e., a type of bridge node code), is programmatically adapted and operative after detecting the data available flag set within the updated advertising signal at time t.sub.10 and retrieving the event information available for upload from the wireless accessory sensor node at time t.sub.11, is further operative to detect a second data available flag set at time t.sub.12, retrieve additional event information at time t.sub.13, and then transmit the accumulated event information at time t.sub.14. In more detail, bridge node processor **201**, when executing CLR control and management code **315** (i.e., a type of bridge node code), is programmatically adapted and operative to detect, at time t.sub.12 prior to RP.sub.E, a subsequent data available flag set within a subsequent updated advertising signal over the short-range communication interface **203b**; retrieve additional event information available for upload from the wireless accessory sensor node (or a different wireless accessory sensor node used in connected logistics receptacle **150**) using the short-range communication interface **203b** before the end of the reporting period RP.sub.E, where the additional event information includes at least additional timestamped information reflecting an additional change in state of the storage receptacle (e.g., a component or area related to connected logistics receptacle **150**); and to transmit accumulated event information to backend server **100** to cause backend server **100** to initiate a dispatched logistics operation related to the storage receptacle. In this example, the accumulated event information includes at least the timestamped information reflecting the detected change in state of the storage receptacle and the additional timestamped information reflecting an additional change in state of the storage receptacle.

(160) In another exemplary embodiment with reference to FIG. **6C**, an embodiment of bridge node processor **201**, when executing CLR control and management code **315** (i.e., a type of bridge node code), is programmatically adapted and operative after detecting the data available flag set within the updated advertising signal at time t.sub.10 and retrieving the event information available for upload from the wireless accessory sensor node at time t.sub.11, is further operative to detect, prior to an end of the reporting period at time RP.sub.E, a subsequent data available flag set within a subsequent updated advertising signal over the short-range communication interface **203b**; retrieve additional event information available for upload from the wireless accessory sensor node using the short-range communication interface at the end of the reporting period where the additional event information includes at least additional timestamped information reflecting an additional change in state of exemplary connected logistics receptacle **150**; and then transmit accumulated event

information to the backend server after retrieval of the additional event information to cause the backend server **100** to initiate the dispatched logistics operation related to receptacle **150**. In this example, the accumulated event information includes at least the timestamped information reflecting the detected change in state of the storage receptacle and the additional timestamped information reflecting an additional change in state of the storage receptacle.

(161) In still another exemplary embodiment with reference to FIG. 6C, an embodiment of bridge node processor **201**, when executing CLR control and management code **315** (i.e., a type of bridge node code), is programmatically adapted and operative after detecting the data available flag set within the updated advertising signal at time $t_{sub.11}$ and retrieving the event information available for upload from the wireless accessory sensor node at time $t_{sub.11}$, is further operative after a beginning of the reporting period $RP_{sub.B}$ and before the end of the reporting period $RP_{sub.E}$, to periodically monitor for the data available flag set within any of one or more updated advertising signals broadcast by any of the wireless accessory sensor nodes disposed as part of receptacle **150** and monitored by bridge node **200**; and retrieve the event information available for upload related to such updated advertising signals by being operative to incrementally retrieve the event information from such wireless accessory sensor node(s) upon detecting the data available flag set within any of those updated advertising signals broadcast by the wireless accessory sensor node(s) where the incrementally retrieved event information takes the form of a series of timestamped information reflecting a series of changes of the state of the storage receptacle (e.g., changes of the state of entrance opening **155**, changes of the state of temporary storage area **205**, changes of the state of door **160**, and/or changes of the state of the area proximate connected logistics receptacle **150**). Thereafter, the bridge node processor **201**, when executing CLR control and management code **315**, is operative to transmit the retrieved event information to the backend server by transmitting the incrementally retrieved event information at the end of the reporting period at or near time $RP_{sub.E}$ to backend server **100** to cause backend server **100** to initiate a dispatched logistics operation.

(162) In FIG. 6D, still another exemplary timeline **615** of activity is shown having a beginning time at $RP_{sub.B}$ where an exemplary reporting period for bridge node **200** begins and an ending time at $RP_{sub.E}$ where the exemplary reporting period for bridge node **200** ends. However, the activity shown in timeline **615** illustrates how a bridge node may be aware of multiple instances of data being available for upload (via detecting different data available flags set over time) but delaying retrieval of the different event information and transmission of such accumulated event information to backend server **100** until at or near the end of an exemplary reporting period. Referring now to FIG. 6D, an embodiment of bridge node processor **201**, when executing CLR control and management code **315** (i.e., a type of bridge node code), is programmatically adapted and further operative (after detecting the data available flag set at time $t_{sub.15}$) to detect, prior to $RP_{sub.E}$, a subsequent data available flag set within a subsequent updated advertising signal and retrieve additional event information available for upload from the wireless accessory sensor node(s) where the additional event information includes at least additional timestamped information reflecting an additional change in state of the storage receptacle; and then transmit the different retrieved event information to backend server **100** by being operative to transmit accumulated event information to backend server **100** at $RP_{sub.E}$ to cause backend server **100** to initiate a dispatched logistics operation related to the storage receptacle **150**. Such accumulated event information in this further example includes at least (a) the timestamped information reflecting the detected change in state of the storage receptacle and (b) the additional timestamped information reflecting the additional change in state of the storage receptacle. For example, as illustrated in FIG. 6D, bridge node **200** may detect a first data available flag set at time $t_{sub.15}$, a second data available flag set at time $t_{sub.16}$, and potentially a further data available flag set at time $t_{sub.n}$ (prior to $RP_{sub.E}$). Bridge node **200** may then retrieve the different event information from one or more respective wireless accessory sensor nodes at time $t_{sub.17}$ before transmitting the accumulated event information at

time t.sub.18.

(163) In some embodiments, the bridge node **200** deployed as part of an exemplary connected logistics receptacle **150** may determine the type of event based upon retrieved event information (such as a pickup event occurring with respect to receptacle **150** when package **170** is removed from receptacle **150** or a drop off event occurring with respect to receptacle **150** when package **170** is received by receptacle **150**). For example, an embodiment of bridge node processor **201**, when executing CLR control and management code **315** (i.e., a type of bridge node code) as part of operation within exemplary connected logistics receptacle **150**, may be programmatically adapted and operative to transmit the retrieved event information to the backend server by being operative to first determine the retrieved event information indicates the detected change in state of the storage receptacle is a pickup event. The bridge node processor **201** may then be operative to transmit the retrieved event information to the backend server **100** using the long-range communication interface **203a** and after the retrieved event information is determined to indicate the detected change in state of the storage receptacle is the pickup event. In such an example, backend server **100** may respond with altering existing or scheduling different dispatched logistics operations related to exemplary connected logistics receptacle **150** and/or operations related to other managed connected logistics receptacles.

(164) In more detail, such an example may have the bridge node processor **201** determine the retrieved event information indicates the detected change in state of the storage receptacle **150** is a pickup event when the recorded timestamped information reflecting the detected change in state of the storage receptacle indicates a change in state of the selectively accessible retrieval door **160** (e.g., where the change in state of the selectively accessible retrieval door **160** corresponds to a detected change in motion of the selectively accessible retrieval door based upon motion sensor data, status/orientation data, magnetic sensor data, and/or lock sensor data related to the state of lock **165** for door **160**).

(165) In another example, the bridge node processor **201** may determine the retrieved event information indicates the detected change in state of the storage receptacle **150** is a pickup event when the recorded timestamped information reflecting the detected change in state of the storage receptacle **150** indicates (a) a change in state of the selectively accessible retrieval door **160** (or lock **165**) and (b) a change in state of the temporary storage area **205** of receptacle **150**. Such a change in the state of the selectively accessible retrieval door **160** may, for example, be based on motion sensor data, status/orientation data, magnetic sensor data, and/or lock sensor data. And such a change in the state of the temporary storage area **205** may, for example, be based on motion sensor data, image sensor data, sensor data on a detected change in weight of what is stored within temporary storage area **205**, sensor data on a detected impact force within temporary storage area **205**, sensor data on a detected chemical within temporary storage area **205**, and/or detected light sensor data reflecting a change in light detected within temporary storage area **205**.

(166) Exemplary backend server **100**, in various embodiments described herein, receives the retrieved event information from exemplary bridge node **200** disposed within exemplary connected logistics receptacle **150** and, in response to such a transmission, may initiate one or more dispatched logistics operations related to that particular exemplary connected logistics receptacle or other connected logistics receptacles also in communication with backend server **100**. FIG. 7 is a diagram of multiple exemplary connected logistics receptacles **150a-150c** operating within a network that connects with an exemplary backend server **100** in accordance with an embodiment of the invention. Referring now to FIG. 7, those skilled in the art will appreciate that exemplary backend server **100** may receive information from different exemplary connected logistics receptacles **150a-150c** via messages and communications over network **105** and may initiate different types of dispatched logistics operations as a result of such messages and communications. In other words, exemplary logistics assets **700a-700c** that may be dispatched for a dispatched logistics operation (e.g., a pickup operation, a delivery operation) related to one or more of

exemplary connected logistics receptacles **150a-150c** based on the different messages and communications sent to backend server **100**. Additionally, as explained in more detail below, backend server **100** may alter or tune the operational parameters of exemplary connected logistics receptacles **150a-150c** based on the different messages and communications sent to backend server **100**. Furthermore, as explained in more detail below, backend server **100** may setup, centrally manage, and track patterns of use, engagement, interactions for exemplary connected logistics receptacles **150a-150c**.

(167) FIG. **8** is a detailed diagram of an exemplary backend server (e.g., backend server **100**) in accordance with an embodiment of the invention. Referring now to FIG. **8**, exemplary backend server **100** is shown as a networked computing platform capable of connecting to and interacting with one or more connected logistics receptacles (e.g., exemplary connected logistics receptacle **150**, exemplary connected logistics receptacles **150a-150c**) as well as other servers or network storage (e.g., exemplary third-party database **180**). Embodiments of exemplary backend server **100** are operative to communicate with other networked devices/nodes that may be used by a shipping customer (e.g., a handheld mobile cellular phone, laptop, tablet, or other communication device) or logistics personnel (e.g., a mobile device used by a logistics courier, an onboard transceiver deployed on a logistics vehicle and used by logistics personnel, and the like). Those skilled in the art will appreciate that exemplary backend server **100** is a hardware-based processing component that may be implemented in a wide variety of ways. For example, those skilled in the art will further appreciate that backend server **100** may be implemented as a single computing system, a distributed server (e.g., separate servers for separate server related tasks), a hierarchical server (e.g., a server implemented with multiple levels where information may be maintained at different levels and tasks performed at different levels depending on implementation), a server farm that logically allows multiple distinct components to function as one server computing platform device from the perspective of a client device, or a cloud-based server with distributed storage and processing capability. In some regional deployments, an exemplary backend server may include servers dedicated for specific geographic regions as information collected within different regions may include and be subject to different regulatory controls and requirements implemented on respective regional servers.

(168) At its core, exemplary backend server **100** shown in FIG. **8** comprises a processing or logic unit **800** (commonly referred to as a processor) coupled to a network interface **890**, which facilitates and enables operative connections and communications through network **105** with one or more other network devices (e.g., exemplary connected logistics receptacle **150**, exemplary connected logistics receptacles **150a-150c**) as well as the other networked devices noted above that may be used by a shipping customer or logistics personnel. Using a network communication path(s) as well as program code or program modules (such as server control and management code **825**), the backend server **100** generally operates to communicate with and manage exemplary connected logistics receptacles (e.g., **150**, **150a-150c**) as well as communicate with various logistics assets as part of initiating and/or changing dispatched logistics operations related to exemplary connected logistics receptacles.

(169) Processing unit **800** of exemplary backend server **100** is operatively coupled to memory storage **815** and volatile memory **820**, which collectively store and provide a variety of executable program code (e.g., server control and management code **825**), data received from various exemplary connected logistics receptacle(s) (e.g., event information **830**), and data used during logistics receptacle management and dispatching operations by backend server **100** (e.g., management profile **835**, dispatch schedule data **840**, and context data **855** related to the environment in which particular exemplary connected logistics receptacles are located and operate). Likewise, while the embodiment shown in FIG. **8** illustrates a simplified single memory storage **815** (and volatile memory **820**), exemplary backend server **100** may deploy more than one memory storage media. Memory storage media, such as memory storage **815**, may be in differing

non-transitory forms (e.g., conventional hard disk drives, solid state memory such as flash memory, optical drives, RAID systems, cloud storage configured memory, network storage appliances, etc.). (170) Like memory storage **305** on a bridge node and memory storage **410** on a wireless accessory sensor node, memory storage **815** on backend server **100** is a tangible, non-transient computer readable medium on which information (such as executable code/modules (e.g., server control and management code **825**), data received from other devices (e.g., event information **830**, etc.), data used in operation of measurement information (e.g., management profile **835**, etc.), and information on the contextual environment for the exemplary connected logistics receptacles managed by backend server (e.g., context data **855**)) may be kept in a non-volatile and non-transitory manner.

(171) Exemplary event information **830**, as maintained in memory of backend server **100**, is a data structure that generally maintains transmitted event information (e.g., retrieved event information **320**) received from bridge nodes in one or more different exemplary connected logistics receptacles. As noted above with respect to exemplary event information **320** retrieved by a bridge node from a wireless accessory sensor node, exemplary event information **830** as stored on backend server **100** reflects information on detected changes on particular components of one or more connected logistics receptacles. In more detail, event information **830** includes timestamped information reflecting a detected change in state of a connected logistics receptacle (such as receptacle **150**) and an identifier indicating a type of detected change in state of the particular connected logistics receptacle. The timestamped information, for example, may indicate a particular time (e.g., time of day, date) corresponding to the detected change. In other examples, the timestamped information may indicate a series of times and/or dates corresponding to a series of related changes to the receptacle, where such a series of related changes to the receptacle are detected by the wireless accessory sensor node as the detected change in state of the storage receptacle. The identifier (which may be also referred to as state information) in event information **830** may, for example, identify details on the type of change detected relative to the state of particular components of the receptacle (e.g., a detected change in motion of or motion through entrance opening **155**, a detected image of package **170** moving into temporary storage area **205**, a detected chemical within temporary storage area **205**, a detected change in weight in what is maintained within receptacle **150**, a detected change in position of the selectively accessible retrieval door **160**, a detected change in the state of lock **165** for door **160**, a detected change in what has been placed within a predetermined range of receptacle **150** as monitored and detected by an external motion sensor or range sensor, etc.). Event information **830** maintains such timestamped and identifier information as corresponding to a particular connected logistics receptacle and, in more detail, may maintain such information categorized and organized relative to particular components on particular connected logistics receptacles managed by backend server **100**.

(172) Exemplary management profile **835** is generally a data structure generated, maintained, and updated by backend server **100** with information on the history and use of particular connected logistics receptacles (e.g., exemplary connected logistics receptacle **150**, exemplary connected logistics receptacles **150a-150c**), their respective components, and logistics assets used to service the particular connected logistics receptacle. Management profile **835** may, in some embodiments, be implemented with a database or records for each connected logistics receptacle being managed by backend server **100** or may be implemented as separate sub-profiles for each connected logistics receptacle being managed by backend server **100**.

(173) In more detail, the information maintained in exemplary management profile **835** includes engagement or interaction history relative to particular components (e.g., an entrance opening/door/handle, a temporary storage area, a selectively accessible retrieval door/lock, and the like) for each of the different connected logistics receptacles **150** being managed by backend server **100**. Exemplary management profile **835** may also include patterns of historic engagement or

interaction relative to components of each of the different connected logistics receptacles **150** being managed by backend server **100**. Such patterns (also referred to as server-tracked historic use patterns for a storage receptacle) are managed as an information profile that identifies a pattern of use of a particular storage receptacle (e.g., exemplary connected logistics receptacle **150**). For example, such patterns may include a pattern of delivery events for the receptacle over time and/or a pattern of pickup events for the receptacle over time. Further examples of profiles of patterns in management profile **835** may include a threshold occupancy pattern profile identifying a frequency of reaching a threshold occupied level within a particular storage receptacle, and/or an overload pattern profile identifying a frequency of reaching an overload condition for a particular storage receptacle.

(174) Such engagement/interaction history information and use pattern information in management profile **835** may be updated (e.g., updated continuously as new event information **830** is received, updated periodically but not necessarily as each bit of new event information **830** is received, or in some further embodiments updated at dynamically adjusted times depending on changes in engagement and patterns and rates of change of such engagement and patterns as further event information **830** is received from various connected logistics receptacles **150** to further enhance operations of backend server **100**).

(175) Exemplary management profile **835** may also include profile information on what logistics assets are dispatched in relation to particular connected logistics receptacles. In this way, logistics asset profile information within management profile **835** identifies what different logistics assets are dispatched, deployed, redirected or otherwise that are used to service particular exemplary connected logistics receptacles managed by backend server **100** as well as identifies patterns of such logistics assets usage relative to different exemplary connected logistics receptacles.

(176) Exemplary management profile **835** may also include threshold data related to particular exemplary connected logistics receptacles that may be used in managing the different connected logistics receptacles. Such threshold data may be a threshold change in use and/or patterns of use/engagement relative to particular exemplary connected logistics receptacles (e.g., use of and/or patterns in such use of particular components on exemplary connected logistics receptacle **150**). For example, such threshold data maintained in exemplary management profile **835** may include a threshold occupied level for different exemplary connected logistics receptacles where meeting such a threshold occupied level in that connected logistics receptacle may trigger certain actions by backend server (e.g., a sweep of other connected logistics receptacles). Such a threshold occupied level may be implemented as information defining an overflow condition (or overflow threshold level/condition) which may take the form of, for example, an amount within temporary storage area **205** as detected in video and/or image sensor data; a threshold number of deposits detected within temporary storage area **205**; an amount of weight detected as having been deposited within temporary storage area **205**; and/or a number of proximate deposits detected proximate the particular connected logistics receptacle **150**.

(177) Exemplary dispatch schedule data **840** maintained by backend server **100** is information related to logistics assets and their respective operations (e.g., capacity, availability, and schedule information associated with particular logistics assets (such as a commercial courier, shipping company, or private entity involved with pickup and/or delivery of items to and from connected logistics receptacles)). already scheduled dispatch operations,

(178) In some embodiments, processing unit **800** of exemplary backend server **100** is operatively coupled to user interface **805**, which may be coupled to further input devices (not shown) (such as a keyboard, screen or display, and the like) so that personnel may interact with backend server **100** directly.

(179) As noted above, backend server **100** may access context data **855** as part of managing exemplary connected logistics receptacles in the wireless node network. Those skilled in the art will appreciate that information corresponding to exemplary context data **855** may be accessed

from different sources, such as onboard connected logistics receptacle (CLR) context database **850** and/or third-party network storage database **180** that may maintain different types of exemplary context data **855**. As illustrated in FIG. **8**, exemplary CLR context database **850** is represented as a single database accessible by processing unit **800** internal to backend server **100**. Those skilled in the art will readily understand that other configurations that provide an accessible collection of context data **855** are possible and contemplated within the scope and principles of embodiments of the invention. For example, CLR context database **850** may be implemented as an externally accessible database (or multiple databases), such as an accessible storage maintained outside the backend server **100** via a dedicated interface or a network storage device (or network attached storage (NAS) unit) such as that shown as third-party network storage database **180** in FIG. **1**. In yet another embodiment, those skilled in the art will appreciate that CLR context database **850** (or simply the information represented as database **850** in FIG. **8**) may be implemented with cloud technology that essentially provides a distributed networked storage of collections of information (such as context data **855**, dispatch schedule data **840**, etc.) accessible to backend server **100**.

(180) Within CLR context database **850**, an exemplary embodiment of the collection of context data **855** may be maintained that generally relates to an environment in which the exemplary connected logistics receptacles are operating or anticipated to be operating. In more detail, exemplary context data **855** as maintained in CLR context database **850** may provide geographic crime data **860** (e.g., on-going crime scenes, crime patterns, different types of crimes in particular areas, and the like), traffic data **865** (e.g., current traffic, traffic patterns, construction locations, and the like), weather data **870** (e.g., current weather happening in particular areas, weather forecasts, historic weather events for areas, and the like), logistics asset staffing data **875** (e.g., couriers deployed in delivery vehicles as mobile logistics assets, shift change information on logistics personnel, and the like), logistics asset cost data **880** (e.g., fuel costs, and the like), as well as other third-party generated data **885** that relates to the operating environment or operations of any of the connected logistics receptacles managed by backend server **100**.

(181) As shown in FIG. **8**, exemplary third-party network storage database **180** may be accessed by backend server **100** to gain access to relevant additional information (e.g., types of context data **855** or dispatch schedule data **840**) not normally maintained within memory onboard backend server **100**. Such additional information may be more frequently updated on external database **180** and, as a result, may be periodically or occasionally accessed by backend server **100** to update information on backend server **100** or to further supplement relevant information (e.g., context data, dispatch related information, and the like) used by backend server. For example, exemplary information made accessible on third-party network storage database **180** may include further crime data **180a**, additional traffic data **180b**, other weather data **180c**, supplemental logistics asset staffing data **180d**, supplemental logistics asset cost data **180e**, and other third-party generated data **180f** that relates to the operating environment or operations of any of the connected logistics receptacles managed by backend server **100**, as well as additional dispatch schedule data **180g** where any of such data on database **180** may not be locally stored and maintained on backend server **100** that that may supplement/complement what is maintained within memory of backend server **100** (e.g., memory storage **815** and CLR context database **850** onboard backend server **100**).

(182) Generally, an embodiment of server control and management code **825** is a collection of executable software features implemented as programmatic functions or program modules that generally control operations of exemplary backend server **100**. Those skilled in the art will appreciate that backend server **100** will typically have an operating system (not shown) in memory storage **815** and loaded into volatile memory **820** when backend server **100** is powered and operating, and that server control and management code **825** serves to further expand upon the programmatically configured functionality of backend server **100**. In other words, server control and management code **825** includes program code specific for backend server **825** unconventional functionality described in the embodiments described in more detail below that use a backend

server as part of embodiments of the invention. As such, the collective code executing on backend server **100** (or any of the other implementations of a backend server as described herein), acts to programmatically configure the backend server **100** beyond that of a generic processing device in order to be specially adapted, via such program code, to be operative to function unconventionally—whether alone or in combination with other processing devices with the specific functionality described herein or as part of a system.

(183) Those skilled in the art will appreciate that the above identification of particular program code and data are not exhaustive and that embodiments may include further executable program code or modules as well as other data relevant to operations of a processing-based device, such as a wireless accessory sensor node, a bridge node, and a backend server

(184) As noted above, embodiments of an enhanced connected logistics receptacle system for receiving and temporarily maintaining a delivery item, are operative to cause a backend server (e.g., exemplary backend server **100**) to initiate a dispatched logistics operation. In more detail, an embodiment with bridge node **200** on the connected logistics receptacle **150** may be operative to use long-range communication interface **203a** to transmit the retrieved event information (e.g., event information **320**) to backend server **100** to cause the backend server **100** to initiate the dispatched logistics operation related to the storage receptacle **150**. In one example, the retrieved event information transmitted to the backend server **100** causes the backend server to reactively dispatch a logistics asset to the storage receptacle **150** for pickup of at least the delivery item (e.g., package **170**) from within the storage receptacle as the dispatched logistics operation. This may be accomplished, for example, where backend server **100** is caused or otherwise triggered by receipt of the event information (and analysis of such event information) to transmit a pickup message to a mobile node operated by the logistics asset, where such a pickup message identifies the storage receptacle **150** for the dispatched logistics operation. In another example, the retrieved event information transmitted to the backend server **100** causes the server to alter a previously scheduled dispatch operation related to the storage receptacle **150** as the dispatched logistics operation initiated by the bridge node **200** in receptacle **150**. In more detail, the retrieved event information transmitted to the backend server **100** in this example causes the backend server **100** to transmit a pickup message to an alternative logistics asset as the dispatched logistics operation related to the storage receptacle **150**. Such an alternative logistics asset is different than an original logistics asset corresponding to a previously scheduled dispatch operation related to the storage receptacle. In this example and with reference to FIG. 7, the dispatch schedule data **840** maintained on backend server **100** may indicate that the original logistics asset to be used for a particular connected logistics receptacle **150b** may be a first logistics asset (e.g., courier and vehicle **700a**). However, in response to retrieved event information sent to backend server **100** (now stored as event information **830**), such received event information by backend server **100** may cause backend server to transmit a pickup message to a second logistics asset (e.g., courier and vehicle **700b**) as the dispatched logistics operation related to the connected logistics receptacle **150b** that sent such event information to backend server **100**.

(185) Further embodiments involving an enhanced connected logistics receptacle system may also implement validation of the detected changes on the connected logistics receptacle. For example, an embodiment of such a system may implement the wireless accessory sensor node as having a second sensor. Using such a second sensor, the wireless accessory sensor node may be operative to detect the change in state of the storage receptacle based upon sensor data by detecting a change in state of the entrance opening using one sensor, and then validating the change in state of the entrance opening by detecting light within the temporary storage area using the second sensor. In this particular example, the change in state of the storage receptacle corresponds to a delivery event where the delivery item is received by the storage receptacle.

(186) In another example where the system's wireless accessory sensor node has such a second sensor, the wireless accessory sensor node can detect the change in the state of the storage

receptacle based upon sensor data by detecting a change in state of the selectively accessible retrieval door using one sensor, and then validating the change in state of the selectively accessible retrieval door by detecting light within the temporary storage area using the second sensor. In this additional example, the change in state of the storage receptacle corresponds to a pickup event where the delivery item is removed from the storage receptacle.

(187) As described above, various embodiments of an enhanced connected logistics receptacle system may use a single storage receptacle, a bridge node, and a wireless accessory sensor node having at least one sensor. However, a more detailed embodiment of an enhanced connected logistics receptacle system may use a single storage receptacle (e.g., receptacle **150**), a bridge node (e.g., bridge node **200**), and different wireless accessory sensor nodes (an embodiment which is also shown in FIG. 2). For example, such an embodiment of an enhanced connected logistics receptacle system may include the storage receptacle for receiving the delivery item, the bridge node mounted to storage receptacle, and two different wireless accessory sensor nodes (e.g., wireless accessory sensor nodes **210**, **240**). In this example, the system's first wireless accessory sensor node (e.g., wireless accessory sensor node **210**) has a first sensor disposed on the storage receptacle that monitors for a change in state of the entrance opening **155**. As part of this exemplary system, the first wireless accessory sensor node **210** is further operative to detect the change in state of the entrance opening **155** based upon first sensor data generated by the first sensor; record first timestamped information reflecting the detected change in state of the entrance opening **155**; and broadcast a first updated advertising signal having a first data available flag set within the first updated advertising signal. Such a first data available flag indicates the first wireless accessory sensor node **210** has first event information available for upload by the bridge node **200**, where the first event information includes at least the first timestamped information reflecting the detected change in state of the entrance opening **155**. In this example, the second wireless accessory sensor node **240** has a second sensor disposed on the storage receptacle that monitors for a change in state of the selectively accessible retrieval door **160**. As part of this exemplary system, the second wireless accessory sensor node **240** is further operative to detect the change in state of the selectively accessible retrieval door **160** based upon second sensor data generated by the second sensor; record second timestamped information reflecting the detected change in state of the selectively accessible retrieval door **160**; and broadcast a second updated advertising signal having a second data available flag set within the second updated advertising signal. Such a second data available flag indicates the second wireless accessory sensor node **240** has second event information available for upload by the bridge node **200**, where the second event information includes at least the second timestamped information reflecting the detected change in state of the selectively accessible retrieval door **160**.

(188) In this same example, the bridge node processor **201** within bridge node **200**, when executing the CLR control & management code **315** (as a type of bridge node code maintained on the bridge node memory), is operative to detect, using the short-range communication interface **203b**, at least one of (a) the first data available flag set within the first updated advertising signal and (b) the second data available flag set within the second updated advertising signal. The bridge node processor **201** is then further operative to responsively download, using the short-range communication interface **203b**, retrieved event information from at least one of the first wireless accessory sensor node **210** and the second wireless accessory sensor node **240** based upon which of the first data available flag set and the second data available flag set is detected. The retrieved event information includes the first event information when the first data available flag set is detected, and includes the second event information when the second data available flag is detected. The bridge node processor **201** is then further operative to transmit, using the long-range communication interface **203a**, the retrieved event information to the backend server **100** to cause the backend server **100** to initiate the dispatched logistics operation related to the storage receptacle.

(189) A further embodiment of this multiple wireless accessory sensor node example may have the enhanced connected logistics receptacle system further including a third wireless accessory sensor node (e.g., one of wireless accessory sensor nodes **215**, **220**, **225**, **230**, **235** shown in FIG. 2). In this further embodiment, the third wireless accessory sensor node has a third sensor disposed on the storage receptacle that monitors for a change in state of the temporary storage area **205** (e.g., motion detected within temporary storage area **205**, an image/video detected showing a change within temporary storage area **205**, light detected within temporary storage area **205**, a particular chemical detected within temporary storage area **205**, a force or impact or change in weight detected relative to what is stored within temporary storage area **205**). Such a third wireless accessory sensor node in this further embodiment is operative to detect the change in state of the temporary storage area **205** based upon third sensor data generated by the third sensor; record third timestamped information reflecting the detected change in state of the temporary storage area **205**; and broadcast a third updated advertising signal having a third data available flag set within the third updated advertising signal. Such a third data available flag indicates the third wireless accessory sensor node has third event information available for upload by the bridge node **200** and where such third event information includes at least the third timestamped information reflecting the detected change in state of the temporary storage area **205**. In this further embodiment involving such a third wireless accessory sensor node, bridge node processor **201** is further operative to detect, using the short-range communication interface **203b**, at least one of (a) the first data available flag set within the first updated advertising signal, (b) the second data available flag set within the second updated advertising signal, and (c) the third data available flag set within the third updated advertising signal. The bridge node processor **201** is then operative to use interface **203b** to responsively download event information from at least one of the first, second, or third wireless accessory sensor nodes based upon which of the first data available flag set and the second data available flag set and the third data available flag set is detected. Such downloaded/retrieved event information includes the first event information when the first data available flag set is detected, includes the second event information when the second data available flag is detected, and includes the third event information when the third data available flag is detected. Thereafter, bridge node processor **201** is further operative to use interface **203a** to transmit the retrieved event information to backend server **100** to cause backend server **100** to initiate the dispatched logistics operation related to the storage receptacle based upon at least one of the first event information, the second event information, and the third event information.

(190) Similar to embodiments described above, the different wireless accessory sensor nodes may use different types of sensors as described above, and use such different types of sensors to validate any detected change in state of particular components of receptacle **150** (e.g., using detected light within temporary storage area **205** to validate a detected change in state of entrance opening **155**).

(191) Likewise, those skilled in the art will appreciate that this embodiment of a multiple wireless accessory sensor node implementation of an enhanced connected logistics receptacle may utilize the type of bridge node activity timing during a reporting period shown in FIGS. 6A-6D when the system's bridge node **200** may detect one or more different flags set from one or more of the system's different wireless accessory sensor nodes. For example, bridge node **200** may wake from a low power state at a predetermined time of day, and detect a data available flag set within at least one of the first updated advertising signal and the second updated advertising signal over the short-range communication interface. Such detections may, for example, occur at the beginning of bridge node **200**'s reporting period, more than once during the reporting periods where bridge node **200** then transmits retrieved event information to backend server **100** each time event information from any of the wireless accessory sensor nodes is retrieved, more than once during the reporting period where bridge node **100** may retrieve event information after each detection or towards the end of the reporting period and only transmit accumulated event information to backend server **100** (rather after each detection/retrieval).

(192) In more detailed embodiments of such a multiple wireless accessory sensor node implementation of an enhanced connected logistics receptacle, the sensor used on different wireless accessory sensor nodes may have multiple sensor elements (e.g., focusing on different areas, using different types of sensing elements, using different sensitivity of sensing elements, and the like). For example, the first sensor used on wireless accessory sensor node **210** may be implemented with multiple sensor elements for monitoring different types of changes in the state of the entrance opening **155**. In more detail, such sensor elements may, for example, include a light sensor element operative to monitor a change relative to light within the storage receptacle **150** as one of the different types of changes in the state of the entrance opening **155**; and a motion sensor element operative to monitor a change relative to motion within the storage receptacle **150** as one of the different types of changes in the state of the entrance opening **155**. In another example, the first sensor used on wireless accessory sensor node **210** may be implemented with multiple wireless sensor elements disposed on different parts of the storage receptacle **150**, where each of such wireless sensor elements monitor different types of changes in the state of the entrance opening **155** (e.g., a wireless light sensor element operative to monitor a change relative to light within the storage receptacle **150** as one of the different types of changes in the state of the entrance opening **155**; and a wireless motion sensor element operative to monitor a change relative to motion within the storage receptacle **150** as one of the different types of changes in the state of the entrance opening **155**).

(193) In still another example, the second sensor used on wireless accessory sensor node **240** may be implemented with multiple sensor elements for monitoring different types of changes in the state of the selectively accessible retrieval door **160** of the storage receptacle **150** (e.g., where such sensor elements include at least two of a magnetic sensor element operative to monitor a change relative to a location of the selectively accessible retrieval door **160**, a light sensor element operative to monitor a change relative to light within the storage receptacle **150** as one of the different types of changes in the state of the selectively accessible retrieval door **160** of the storage receptacle **150**, and a motion sensor element operative to monitor a change relative to motion of the selectively accessible retrieval door **160** as one of the different types of changes in the state of the selectively accessible retrieval door **160** of the storage receptacle **150**).

(194) In another example, the second sensor may be implemented as multiple wireless sensor elements (e.g., similar to sensor **450e**) disposed on different parts of the storage receptacle **150** where each of the wireless sensor elements monitor different types of changes in the state of the selectively accessible retrieval door **160**. Such wireless sensor elements used for the second sensor in this example may include at least two of a wireless magnetic sensor element operative to monitor a change relative to a location of the selectively accessible retrieval door **160**; a wireless light sensor element operative to monitor a change relative to light within the storage receptacle **150** as one of the different types of changes in the state of the selectively accessible retrieval door **160**; and a wireless motion sensor element operative to monitor a change relative to motion of the selectively accessible retrieval door **160** as one of the different types of changes in the state of the selectively accessible retrieval door **160** of the storage receptacle **150**.

(195) In yet another example, the third sensor used with one of the wireless accessory sensor nodes managing sensors that monitor temporary storage area **205** of receptacle **150** may be implemented with multiple sensor elements for monitoring different types of changes in the state of the temporary storage area **205** (e.g., a scale/force sensor element operative to monitor an impact force or change relative to a weight of contents maintained in temporary storage area **205**; a motion sensor element operative to monitor a change relative to motion detected within the temporary storage area **205**; a light sensor element operative to monitor a change relative to light within the storage receptacle **150** as one of the different types of changes in the state of the temporary storage area **205**; an image sensor element operative to monitor what is located within the temporary storage area **205**; a chemical sensor element operative to detect a chemical within the storage

receptacle as one of the different types of changes in the state of the temporary storage area of the storage receptacle). Such a third sensor may be implemented (similar to that described above) using wireless sensor elements disposed on different part of the storage receptacle **150** (e.g., a wireless scale sensor element operative to monitor a change relative to a weight of contents maintained in the temporary storage area **205**; a wireless motion sensor element operative to monitor a change relative to motion detected within the temporary storage area **205**; a wireless light sensor element operative to monitor a change relative to light within the storage receptacle **150** as one of the different types of changes in the state of the temporary storage area **205**; a wireless image sensor element operative to monitor what is located within the temporary storage area **205**; and a wireless chemical sensor element operative to detect a particular chemical (such as a gaseous vapor) within the storage receptacle **150** as one of the different types of changes in the state of the temporary storage area **205**).

(196) In yet another more detailed embodiment of a multiple wireless accessory sensor node implementation of an enhanced connected logistics receptacle, further advantageous system operations may occur when one of the wireless accessory sensor nodes detects a pickup event prior to a drop off time for the storage receptacle **150**. In such an embodiment, memory **202** of bridge node **200** maintains information on a drop-off threshold time value for receptacle **150** that may be referenced and used during operation of bridge node **200**. For example, an embodiment may have bridge node processor **201** being further operative to (a) determine the retrieved event information indicates a detected change in state of the selectively accessible retrieval door **160** is a pickup event occurring before a drop off threshold time for the receptacle **150**, (b) use the short-range communication interface **203b** to detect a subsequent first data available flag set within another first updated advertising signal, (c) responsively download additional first event information available for upload from a wireless accessory sensor node where the additional first event information includes additional first timestamped information reflecting an additional change in state of the entrance opening **155** before the drop off threshold time, and (d) use the long-range communication interface **203a** to transmit the retrieved event information to the backend server **100** to cause the backend server to initiate the dispatched logistics operation related to the storage receptacle.

(197) In some embodiments, such a system may include the backend server as part of the system—e.g., where the enhanced connected logistics receptacle system may include the storage receptacle, a bridge node disposed as part of the storage receptacle, one or more wireless accessory sensor nodes (each having at least one sensor), and the backend server as express elements of such a system. In such a system embodiment, the backend server (e.g., backend server **100**) more specifically initiates the dispatched logistics operation by being further operative to reactively dispatch a logistics asset to the storage receptacle for pickup of at least the delivery item (e.g., package **170**) from within the storage receptacle **150** as at least part of the dispatched logistics operation.

(198) In even more detail, an exemplary system may further include a mobile node operated by the logistics asset (e.g., a wireless-capable tablet, a handheld mobile cellular phone, or some other mobile communication device used by logistics personnel operating delivery vehicle **700a**). As such, an example may have the backend server being operative to dispatch the logistics asset to the storage receptacle for pickup of at least the delivery item by being further operative to transmit a pickup message to the mobile node where the pickup message identifies the storage receptacle for the dispatched logistics operation. In another example, the backend server is operative to responsively initiate the dispatched logistics operation by being further operative to transmit a pickup message to the mobile node operated by the logistics asset, but where the pickup message identifies the storage receptacle for the dispatched logistics operation and alters a previously scheduled dispatch operation related to that storage receptacle as the dispatched logistics operation.

(199) In yet another embodiment, backend server may initiate or otherwise assign a different

logistics asset for the operation (rather than dispatching an originally scheduled logistics asset). For example, an exemplary system having the backend server as an element may further include a first mobile node operated by a first logistics asset previously responsible for performing the dispatched logistics operation (e.g., a mobile handheld phone operated by a courier in delivery vehicle **700a**), and a second mobile node operated by a second logistics asset (e.g., another mobile handheld phone operated by a courier in a different delivery vehicle **700b**). With these two different mobile nodes involved, the backend server in this embodiment is operative to responsively initiate the dispatched logistics operation by being further operative to assess the retrieved event information to determine a change in the dispatched logistics operation, transmit a pickup message to the second logistics asset to initiate the dispatched logistics operation related to the storage receptacle, and then transmit a notification message to the first logistics asset regarding the change in the dispatched logistics operation.

(200) In a further embodiment, such an exemplary system may be more of a retro-fit or refit type of system that upgrades or otherwise enhances an existing logistics storage receptacle, which has at least an entrance opening (e.g., entrance opening **155**) for receiving a delivery item (e.g., package **170**), a temporary storage area (e.g., area **205**) for temporarily maintaining the delivery item once deposited with the storage receptacle, and a retrieval door (e.g., door **160**) providing selective access to the temporary storage area. In more detail, where such enhanced connected logistics receptacle system may be deployed on an existing storage receptacle, the exemplary system includes a bridge node (e.g., bridge node **200**) mounted to the storage receptacle and a wireless accessory sensor node that monitors for a change in state of the storage receptacle. In such a retrofit system embodiment, the wireless accessory sensor node may include multiple sensors, such as a first sensor disposed on the storage receptacle for monitoring the entrance opening, a second sensor disposed on the storage receptacle for monitoring the temporary storage area, and a third sensor disposed on the storage receptacle for monitoring the retrieval door. As such, the system's wireless accessory sensor node is operative to detect the change in state of the storage receptacle based upon sensor data generated by the at least one of the first of the sensors, the second of the sensors, and the third of the sensors; record timestamped information reflecting the detected change in state of the storage receptacle; and broadcast an updated advertising signal having a data available flag set within the updated advertising signal. Such a data available flag indicates the system's wireless accessory sensor node has event information available for upload by the bridge node, and where the event information includes at least the timestamped information reflecting the detected change in state of the storage receptacle. The bridge node, through its programmable processor when executing bridge node code maintained on the bridge node memory (e.g., CLR control and management code **315**) is operative to detect the data available flag set within the updated advertising signal over the short-range communication interface, retrieve the event information available for upload from the wireless accessory sensor node using the short-range communication interface, and transmit (using the long-range communication interface **203a**) the retrieved event information to the backend server to cause the backend server to initiate the dispatched logistics operation related to the storage receptacle.

(201) Such different sensors used with this embodiment's wireless accessory sensor node may be implemented as onboard, wired, or wirelessly connected types of sensors (similar to the exemplary types of sensors **450a-450e** shown in FIG. 4). For example and consistent with what is shown in FIG. 2, the first sensor monitoring the entrance opening of the storage receptacle may be implemented as one or more of a motion sensor detecting a change in motion of the entrance opening as the change in state of the storage receptacle; a motion sensor detecting movement of what is received through the entrance opening as the change in state of the storage receptacle; an accelerometer detecting a change in motion of the entrance opening as the change in state of the storage receptacle; or a magnetic sensor detecting a change in position of the entrance opening as the change in state of the storage receptacle. The second sensor monitoring the temporary storage

area may be implemented as one or more of a motion sensor detecting motion within the temporary storage area as the change in state of the storage receptacle; an image sensor detecting a change of what is stored within the temporary storage area as the change in state of the storage receptacle; a scale disposed at a bottom of the temporary storage area, the scale detecting a change in weight of what is stored within the temporary storage area as the change in state of the storage receptacle; a force sensor disposed within the temporary storage area, the force sensor detecting an impact force related to a change in what has been deposited within the temporary storage area as the change in state of the storage receptacle; and a light sensor detecting a change in light within the temporary storage area as the change in state of the storage receptacle. The third sensor monitoring the selectively accessible retrieval door may be implemented as one or more of a motion sensor detecting a change in motion of the selectively accessible retrieval door as the change in state of the storage receptacle; a magnetic sensor detecting a change in position of the selectively accessible retrieval door as the change in state of the storage receptacle; a lock sensor detecting a change in a locked status of the selectively accessible retrieval door as the change in state of the storage receptacle; a range sensor detecting a change in what has been placed within a predetermined range of the storage receptacle as the change in state of the storage receptacle; and an external motion sensor detecting a change in what has been placed within the predetermined range of the storage receptacle as the change in state of the storage receptacle.

(202) Enhanced Backend Server Response with Different Types of Initiated Logistics Ops

(203) Further embodiments with an exemplary connected logistics receptacle (e.g., receptacle **150**) involve an expanded or enhanced backend server response when receiving retrieved event information from a particular connected logistics receptacle. For example, when one connected logistics receptacle (e.g., storage receptacle **150a**) transmits retrieved event information to backend server **100**, backend server **100** may be programmatically configured to be operative so as to cause or otherwise initiate a further dispatched logistics operation related to one or more additional storage receptacles (e.g., storage receptacles **150b**, **150c**). Generally, initiating a further dispatched logistics operation related to an additional storage receptacle (not the reporting storage receptacle) may be referred to as a triggered sweep. In other words, what triggers such a further dispatched logistics operation for that additional connected logistics receptacle is not the additional receptacle involved in such a further dispatched logistics operation. As explained in more detail below, further embodiments may set out that the basis for such a triggered sweep may, for example, include exceeding a threshold occupied level for the reporting storage receptacle; detecting or identifying an overflow condition that is found to exist for the reporting storage receptacle; or detecting a change in a historic use pattern for the reporting storage receptacle

(204) FIGS. **9A-9E** are a series of diagrams of an exemplary backend server (e.g., server **100**) responding to receipt of retrieved event information from a bridge node in an exemplary connected logistics receptacle where the backend server initiates one or more enhanced responses relative to the reporting exemplary connected logistics receptacle and/or relative to additional exemplary connected logistics receptacles in accordance with an embodiment of the invention. Referring now to FIG. **9A**, backend server **100** is illustrated that may be in communication with different storage receptacles (e.g., exemplary connected logistics receptacles **150a-150c**) over network **105** as well as with different exemplary logistics assets **700a-700c**. As shown in FIG. **9A**, exemplary backend server **100** is shown as part of an exemplary system where backend server **100** receives a message **900** of transmitted information (e.g., retrieved event information) from a reporting exemplary connected logistics receptacle **150a** over network **105**. Exemplary backend server **100** in this embodiment may respond by initiating a dispatched logistics operation involving the reporting exemplary connected logistics receptacle **150a** and/or may respond by initiating a further dispatched logistics operation involving an additional exemplary connected logistics receptacle (e.g., one or more of receptacles **150b**, **150c**). For example, as shown in FIG. **9B**, backend server **100** may respond with a dispatch message **905** transmitted to logistics asset **700a** to initiate a

pickup operation for reporting receptacle **150a**. Then, as shown in FIG. 9C, logistics asset **700a** responds to this dispatch message **905** by moving to the vicinity of receptacle **150a** so that logistics personnel (e.g., a courier operating a delivery vehicle operating as logistics asset **700a**) can pick up a package or other parcel delivery item from receptacle **150a**.

(205) In this example, as shown in FIG. 9D, backend server **100** may respond with a triggered sweep dispatch message **910** transmitted to logistics asset **700b** to initiate a further dispatched logistics operation for one or more non-reporting receptacles (such as receptacle **150b**). As a result, and as shown in FIG. 9E, logistics asset **700b** responds to this dispatch message **910** by moving to the vicinity of receptacle **150b** so that logistics personnel (e.g., a courier operating a delivery vehicle operating as logistics asset **700b**) can conduct the triggered sweep operation to pick up what may be in receptacle **150b**. In some embodiments, the further dispatched logistics operation may be conducted by other logistics assets (e.g., asset **700b**), but in other embodiments the further dispatched logistics operation may be conducted by the logistics asset that serviced the reporting receptacle **150a**. Additionally, in some embodiments backend server **100** may simply initiate the triggered sweep dispatched logistics operation of one or more non-reporting connected logistics receptacles (e.g., receptacles **150b**, **150c**) in response to receiving the retrieved event information in message **900**.

(206) In more detail and with reference to the illustrations of FIGS. 9A-9E, an embodiment of an enhanced system for receiving and temporarily maintaining package **170** as a delivery item and responsively initiating one or more dispatched logistics operations has such a system including a backend server (e.g., server **100**), a bridge node mounted to a storage receptacle (e.g., bridge node **200** in exemplary storage receptacle **150** or receptacle **150a**), and a wireless accessory sensor node (e.g., wireless accessory sensor node **210**) using at least one sensor to monitor for a change in the state of the storage receptacle. The system's wireless accessory sensor node is programmatically adapted to be operative to detect the change in state of the storage receptacle based upon sensor data generated by the at least one sensor, record timestamped information reflecting the detected change in state of the storage receptacle, and broadcast an updated advertising signal having a data available flag set within the updated advertising signal. In this embodiment, the data available flag indicates the wireless accessory sensor node has event information available for upload by the bridge node and where such event information includes at least the timestamped information reflecting the detected change in state of the storage receptacle. Similar to embodiments described above, the bridge node processor in the system's bridge node, when executing the bridge node code maintained on the bridge node memory (e.g., CLR control and management code **315**), is programmatically adapted so to be operative to detect the data available flag set within the updated advertising signal over the short-range communication interface, retrieve the event information available for upload from the wireless accessory sensor node using the short-range communication interface, and transmit the retrieved event information to the backend server using the long-range communication interface.

(207) In this particular embodiment, the system's backend server, in response to receiving the retrieved event information from the bridge node, is operative to reactively dispatch a logistics asset to the reporting storage receptacle for pickup of at least the delivery item from within the storage receptacle as the dispatched logistics operation initiated by the bridge node. For example, as shown in FIGS. 9B and 9C, backend server **100** reactively dispatches logistics asset **700a** to reporting storage receptacle **150a** for pickup of a delivery item (e.g., package **170**) from within receptacle **150a**. However, as an enhancement in this particular embodiment, the system's backend server is also operative to initiate a further dispatched logistics operation related to one or more additional storage receptacles managed by the backend server. For example, as shown in FIGS. 9D and 9E, backend server **100** is operative to dispatch a logistics asset (such as logistics asset **700b**) to one or more additional storage receptacles (e.g., receptacle **150b**) managed by backend server **100**.

(208) In more detail, the basis for triggering such a sweep of other receptacles may involve reaching a threshold occupied level within the reporting storage receptacle. Such a threshold occupied level for a particular storage receptacle may be maintained as threshold data maintained in memory storage **305** of bridge node **200**. That data identifies a particular threshold occupied level for the particular storage receptacle (e.g., pre-defined for the particular storage receptacle or a value for the threshold occupied level that is dynamically set by either the bridge node or tuned by the backend server). Once identified/detected as being reached, the existence of such a threshold occupied level being reached allows for responsive actions (such as triggering sweeps of other storage receptacles), which may be taken in light of this condition of the reporting storage receptacle.

(209) For example, an embodiment may have backend server **100** being further operative to determine whether the retrieved event information received from the bridge node indicates a threshold occupied level exists within the reporting storage receptacle, which then allows backend server **100** to initiate the further dispatched logistics operation with the other additional storage receptacles when the retrieved event information received from the bridge node indicates or reflects that the threshold occupied level exists within the storage receptacle. In some embodiments, the bridge node may send an indicator that the threshold occupied level exists as part of the event information transmitted to the backend server. In other embodiments, backend server **100** may maintain threshold occupied level information within management profile **835** and use that information along with the received event information from the reporting storage receptacle to determine whether the retrieved event information received from the bridge node indicates that a threshold occupied level exists within the reporting storage receptacle.

(210) Sensor data generated by the sensor on the wireless accessory sensor node may be used from the retrieved event information as indicating the threshold occupied level within the reporting storage receptacle. Such sensor data may include, for example, sensor data generated by an image sensor within the temporary storage area **205** where the image sensor detects a change in what is stored within the temporary storage area **205** as the change in state of reporting receptacle **150**. In another example, the sensor data is generated by a scale as a sensor on the wireless accessory sensor node, where the scale is disposed at a bottom of the temporary storage area **205** and detects a change in weight of what is stored within the temporary storage area **205** as the change in state of reporting receptacle **150**. In another example, the sensor data is generated by a force sensor as the sensor on the wireless accessory sensor node, where the force sensor detecting an impact related to what has been deposited within the temporary storage area **205** as the change in state of reporting receptacle **150**. In still another example, the sensor data is generated by a motion sensor on the wireless accessory sensor node, where the motion sensor detects (a) a change in motion of the entrance opening **155** and (b) a failure to return to a prior state of the entrance opening **155** (where (a) and (b) reflect the change in state of the reporting storage receptacle **150**). In a further example, the sensor data is generated by a status sensor on the wireless accessory sensor node, where the status sensor detects (a) a change in orientation of the entrance opening **155** and (b) a failure to return to a prior state of the entrance opening **155** (where (a) and (b) reflect the change in state of the reporting storage receptacle **150**).

(211) In further embodiments involving a threshold occupied level, the retrieved event information received from the bridge node and transmitted to backend server **100** is related to multiple types of sensor data generated by the wireless accessory sensor node in the reporting storage receptacle **150**. For example, such types of sensor data may include at least two from a group consisting of motion data, image data, orientation data, weight data, and force data.

(212) While the above description focuses on using a threshold occupied level within the reporting storage receptacle as a possible basis for triggering such a sweep of other receptacles, additional embodiments may involve the detection of an overflow condition within the reporting storage receptacle. Such an overflow condition for a particular storage receptacle may be defined by and

maintained as another type of threshold data maintained in memory storage **305** of bridge node **200**. That data identifies a particular overflow condition for the particular storage receptacle (e.g., a pre-defined or predetermined condition or a value that is dynamically set by either the bridge node or selectively tuned by the backend server). Once the overflow condition exists, the existence of such an overflow condition for the reporting storage receptacle allows for responsive actions (such as triggering sweeps of other storage receptacles), which may be taken in light of this condition of the reporting storage receptacle.

(213) In such an additional embodiment, backend server **100** is further operative to determine whether the retrieved event information received from the bridge node indicates an overflow condition exists within the reporting storage receptacle **150**, which then allows backend server **100** to initiate the further dispatched logistics operation with the other additional storage receptacles when the retrieved event information received from the bridge node indicates or reflects that the overflow condition exists within the storage receptacle. In some embodiments, the bridge node may send an indicator that the overflow condition exists as part of the event information transmitted to the backend server. In other embodiments, backend server **100** may maintain overflow condition information within management profile **835** and use that information along with the received event information from the reporting storage receptacle (e.g., sensor data related to the change in state of the reporting storage receptacle) to determine whether the retrieved event information received from the bridge node indicates that an overflow condition exists within the reporting storage receptacle.

(214) Sensor data generated by the sensor on the wireless accessory sensor node may be used from the retrieved event information as indicating the overflow condition within the reporting storage receptacle. Such sensor data may include, for example, sensor data generated by an external motion sensor on the wireless accessory sensor node, where the external motion sensor detects a change in what has been placed within a predetermined range of the reporting storage receptacle **150** as the change in state of the storage receptacle; sensor data generated by a proximity sensor on the wireless accessory sensor node, where the proximity sensor detects a change in what has been placed within a predetermined range of the reporting storage receptacle **150** as the change in state of the reporting storage receptacle **150**; sensor data generated by an image sensor on the wireless accessory sensor node, where the image sensor detects a change of what is stored within the temporary storage area **205** as the change in state of the reporting storage receptacle **150**; sensor data generated by an image sensor on the wireless accessory sensor node, where the image sensor detects a change of what has been placed within a predetermined range of the reporting storage receptacle **150** as the change in state of the reporting storage receptacle **150**; sensor data generated by a scale as the sensor on the wireless accessory sensor node, where the scale is disposed at a bottom of the temporary storage area **205** and detects a change in weight of what is stored within the temporary storage area **205** as the change in state of the reporting storage receptacle **150**; and sensor data generated by a force sensor on the wireless accessory sensor node, where the force sensor detects an impact related to what has been deposited within the temporary storage area **205** as the change in state of the reporting storage receptacle **150**. In a further example, sensor data is generated by a motion sensor on the wireless accessory sensor node, where the motion sensor detects (a) a change in motion of the entrance opening **155** and (b) a failure to return to a prior state of the entrance opening **155** (where (a) and (b) reflect the change in state of the reporting storage receptacle **150**). In still another example, the sensor data is generated by a status sensor on the wireless accessory sensor node, where the status sensor detects (a) a change in orientation of the entrance opening **155** and (b) a failure to return to a prior state of the entrance opening **155** (where (a) and (b) reflect the change in state of the reporting storage receptacle **150**).

(215) In further embodiments involving an overflow condition, the retrieved event information received from the bridge node and transmitted to backend server **100** is related to multiple types of sensor data generated by the wireless accessory sensor node in the reporting storage receptacle **150**.

For example, such types of sensor data may include at least two from a group consisting of motion data, proximity data, image data, force data, and weight data.

(216) Aside from embodiments described above that use a threshold occupied level or overflow condition within the reporting storage receptacle as a possible basis for triggering such a sweep of other receptacles, additional embodiments may involve a change in historic use pattern for the reporting storage receptacle as a basis for triggering such a sweep of other storage receptacles. In more detail, an additional embodiment may have backend server **100** being further operative to detect a threshold change in a server-tracked historic use pattern for the reporting storage receptacle based at least upon the retrieved event information received from the bridge node. As such, when the backend server detects the threshold change in the server-tracked historic use pattern for the reporting storage receptacle, the backend server is also operative to initiate the further dispatched logistics operation related to the one or more additional storage receptacles. In this example, such a server-tracked historic use pattern for the reporting storage receptacle may be implemented as a profile identifying a pattern of use of the reporting storage receptacle as maintained on the backend server (e.g., part of management profile **835**). In more detail, the profile identifying the pattern of use of the reporting storage receptacle may, for example, be a pattern of delivery events for the reporting storage receptacle and/or a pattern of pickup events for the reporting storage receptacle. In a further example, the profile identifying the pattern of use of the reporting storage receptacle may be a threshold occupancy pattern profile identifying a frequency of reaching a threshold occupied level within the reporting storage receptacle; or an overload pattern profile identifying a frequency of reaching an overload condition for the reporting storage receptacle.

(217) Still further embodiments may use a historic use profile maintained by the bridge node **200** on the reporting storage receptacle, and information in that profile may be used as a basis for triggering such a sweep of other receptacles. In one example, the bridge node memory in a system's bridge node **200** may store and maintain a historic use profile (e.g., a historic use profile stored as part of historic use information **327** on bridge node **200**), which identifies a pattern of use of the reporting storage receptacle. In this example, the retrieved event information transmitted to the backend server **100** (that causes the backend server **100** to initiate the further dispatched logistics operation related to one or more additional storage receptacles) indicates a change in the historic use pattern for the reporting storage receptacle as tracked by the bridge node. In more detail in such an example, bridge node processor **201** may be further operative to compare the retrieved event information with the historic use pattern for the reporting storage receptacle as indicated in the history use profile, and detect the change in the historic use pattern for the reporting storage receptacle based upon the comparison of the retrieved event information with the historic use pattern for the reporting storage receptacle. In such an example, bridge node processor **201** may further update the historic use profile in bridge node memory **202** based upon the retrieved event information in response to detecting the change in the historic use pattern for the reporting storage receptacle.

(218) Such a historic use profile may be implemented, for example, with information on a pattern of delivery events for the reporting storage receptacle as logged by the bridge node **200** and based upon sensor data generated by at least one sensor of the wireless accessory sensor node in the reporting storage receptacle. In another embodiment, the historic use profile is implemented with information on a pattern of pickup events for the reporting storage receptacle as logged by the bridge node **200** and based upon sensor data generated by at least one sensor of the wireless accessory sensor node in the reporting storage receptacle. In still another embodiment, the historic use profile may be implemented with information on a threshold occupancy pattern profile identifying a frequency of reaching a threshold occupied level within the reporting storage receptacle as logged by the bridge node **200** and based upon sensor data generated by at least one sensor of the wireless accessory sensor node in the reporting storage receptacle. In yet another embodiment, the historic use profile may be implemented with information defining an overload

pattern profile identifying a frequency of reaching an overload condition for the reporting storage receptacle as logged by the bridge node **200** and based upon sensor data generated by at least one sensor of the wireless accessory sensor node in the reporting storage receptacle.

(219) In a further embodiment of such a system with enhanced dispatching related to other storage receptacles, backend server **100** may reactively dispatch a logistics asset to the reporting storage receptacle for pickup of an item from within the reporting storage receptacle as the dispatched logistics operation in a variety of ways. For example, backend server **100** may be programmatically adapted and operative to transmit a pickup message to a mobile node operated by the logistics asset (where the pickup message identifies the reporting storage receptacle for the dispatched logistics operation); alter a previously scheduled dispatch operation related to the reporting storage receptacle as the dispatched logistics operation; or by a combination of transmitting a schedule alteration message to a mobile node operated by the logistics asset and then transmitting a pickup message to an alternative logistics asset as the dispatched logistics operation related to the reporting storage receptacle (where the alternative logistics asset is different than the logistics asset originally scheduled for the dispatched logistics operation related to the reporting storage receptacle).

(220) As noted in embodiments described above, sensor data may be used to detect a change in motion/orientation of a component on the storage receptacle (such as entrance opening **155** or door **160**) and a failure for that component to return to a prior state of that component as a type of detected change in state of the storage receptacle. When retrieval door **160** fails to return to its prior state (e.g., a closed state where the storage receptacle is secure), a further embodiment may have backend server **100** operative to reactively dispatch the logistics asset to the reporting storage receptacle as the dispatched logistics operation by being operative to determine a fault condition exists on the storage receptacle based upon the retrieved event information received from the bridge node, and generate a fault condition alert message to the logistics asset identifying the fault condition. In more detail, the fault conditions exist on the reporting storage receptacle when the retrieved event information received from the bridge node **200** of that reporting storage receptacle indicates a change in motion and/or orientation of retrieval door **600** and a failure to return to a prior state of the retrieval door **600** on that reporting storage receptacle. Examples of such a fault condition alert message transmitted by backend server **100** to the logistics asset identifies the fault condition as an unsecured state of the retrieval door and may expressly prompt or otherwise request the logistics asset secure the retrieval door on that reporting storage receptacle.

(221) While some embodiments of an enhanced system for receiving and temporarily maintaining a delivery item relative to a reporting storage receptacle and responsively initiating one or more dispatched logistics operations may include responsive operations relative to both the reporting storage receptacle and one or more other non-reporting storage receptacle(s), a further embodiment may focus more with details on responding with a triggered sweep dispatched logistics operation for such non-reporting storage receptacles. In such a further embodiment, the system may involve a backend server (e.g., exemplary backend server **100**) and monitoring and reporting electronics involved with and disposed relative to a first storage receptacle (e.g., exemplary connected logistics receptacle **150a**). Such electronics in this exemplary system include a bridge node (e.g., exemplary bridge node **200**) mounted to that storage receptacle and a wireless accessory sensor node (e.g., any of exemplary wireless accessory sensor nodes **210**, **215**, **220**, **225**, **230**, **235**, **240**, **245**, and/or **250**) disposed relative to that first storage receptacle having at least one sensor that monitors for a change in the state of that first storage receptacle. The system's wireless accessory sensor node is programmatically adapted so as to be operative to detect the change in state of the first storage receptacle based upon sensor data generated by the sensor(s); record timestamped information (e.g., exemplary timestamped information **425**) reflecting the detected change in state of the storage receptacle; and broadcast an updated advertising signal having a data available flag set within the updated advertising signal. The data available flag in such an updated advertising signal indicates the wireless accessory sensor node has event information available for upload by bridge node **200**.

Such event information to be uploaded by bridge node **200** includes at least the timestamped information reflecting the detected change in state of the first storage receptacle and may also include sensor data (e.g., exemplary sensor data **420**) and/or state information on the detected change in state (e.g., exemplary state information **430**). In the system's bridge node **200**, exemplary bridge node processor **201**, when executing the bridge node code maintained on the bridge node memory (e.g., CLR control and management code **315**), is operative to detect the data available flag set within the updated advertising signal over the short-range communication interface **203b**, retrieve the event information available for upload from the wireless accessory sensor node using the short-range communication interface **203b**, and then use long-range communication interface **203a** to transmit the retrieved event information to the backend server **100**. In response to receiving the retrieved event information from the bridge node **200**, backend server **100** in this system embodiment is operative to initiate the triggered sweep dispatched logistics operation related to the one or more additional storage receptacles (e.g., non-reporting storage receptacles **150b**, **150c**). (222) In further embodiments of such a system that initiates such a triggered sweep of one or more non-reporting storages receptacles may have the basis for triggering such a sweep of the non-reporting receptacle or receptacles may involve reaching a threshold occupied level for the reporting storage receptacle, detecting an overflow condition for the reporting storage receptacle, detecting a threshold change in historic use or a pattern of historic use for the reporting storage receptacle as previously described.

(223) Still further embodiments of a system that initiates such a triggered sweep of one or more non-reporting storages receptacles may also have backend server **100** initiating a dispatch operation relative to the reporting storage receptacle (e.g., receptacle **150a**). In more detail, an example of backend server **100** in such a system is operative to reactively dispatch the logistics asset to the first storage receptacle (e.g., receptacle **150a**) for pickup of at least the delivery item from within that first storage receptacle (the reporting storage receptacle) as the first dispatched logistics operation by being further operative to transmit a pickup message to a mobile node operated by the logistics asset (e.g., a mobile node used on logistics asset **700a**, such as a handheld cell phone or table used by logistics personnel on logistics asset **700a** or an onboard mobile transceiver deployed as part of a logistics delivery vehicle operating as logistics asset **700a**). Such a pickup message may identify that first storage receptacle for the first dispatched logistics operation.

(224) In another example, backend server **100** may alter a prior scheduled dispatch operation related to the reporting storage receptacle. In more detail, backend server **100** in this embodiment is operative to reactively dispatch the logistics asset **700a** to reporting storage receptacle **150a** for pickup of at least the delivery item from within that first storage receptacle as the first dispatched logistics operation by being further operative to alter a previously scheduled dispatch operation related to the first storage receptacle as the first dispatched logistics operation.

(225) In still another example, backend server **100** may initiate the use of a different logistics asset for the dispatch operation related to the reporting storage receptacle. In more detail, backend server **100** in this embodiment is operative to reactively dispatch a logistics asset to the first storage receptacle (the reporting receptacle) for pickup of at least the delivery item from within the first storage receptacle as the first dispatched logistics operation by being further operative to transmit a schedule alteration message to a mobile node operated by the logistics asset **700a**, and transmit a pickup message to an alternative logistics asset (e.g., logistics asset **700b**) as the first dispatched logistics operation related to that reporting storage receptacle. The alternative logistics asset in this example is different than the logistics asset originally scheduled for the first dispatched logistics operation related to the first storage receptacle (the reporting storage receptacle).

(226) In still further embodiments of such a system that initiates such a triggered sweep of one or more non-reporting storages receptacles, sensor data may be used to detect a change in motion/orientation of a component on the storage receptacle (such as entrance opening **155** or door **160**) and a failure for that component to return to a prior state of that component as a type of

detected change in state of the storage receptacle. Similar to embodiments described above, when retrieval door **160** fails to return to its prior state (e.g., a closed state where the storage receptacle is secure), a further embodiment may have backend server **100** operative to reactively dispatch the logistics asset to the reporting storage receptacle as the dispatched logistics operation by being operative to determine a fault condition exists on the storage receptacle based upon the retrieved event information received from the bridge node, and generate a fault condition alert message to the logistics asset identifying the fault condition. In more detail, the fault conditions exist on the reporting storage receptacle when the retrieved event information received from the bridge node **200** of that reporting storage receptacle indicates a change in motion and/or orientation of retrieval door **600** and a failure to return to a prior state of the retrieval door **600** on that reporting storage receptacle. Examples of such a fault condition alert message transmitted by backend server **100** to the logistics asset identifies the fault condition as an unsecured state of the retrieval door and may expressly prompt or otherwise request the logistics asset secure the retrieval door on that reporting storage receptacle.

(227) Multi-Compartment Logistics Receptacle

(228) As mentioned above, the receptacle **150** in some embodiments may be implemented as a multi-compartment secure access receptacle or container (such as a locker type of logistics receptacle) where each of the receptacle compartments have temporary storage per compartment and are monitored (similar to that shown and explained with respect to FIG. 2). In such an embodiment, the multi-compartment logistics receptacle has more than one entrance opening where a particular entrance opening is accessible to a shipping customer for depositing the package (i.e., item to be shipped). Once within the multi-compartment logistics receptacle, the package is secure and only removed from a secure storage area within a compartment of the receptacle by a person or device that is authorized to do so.

(229) Some embodiments of an exemplary multi-compartment logistics receptacle may have retrieval doors per compartment, rather than a single retrieval door for all temporary storage compartments. Some embodiments may include a common access door with further selectively accessible access doors to individual compartments within the receptacle. Some embodiments may deploy a monitoring and reporting system that uses a bridge or bridging node along with different configurations of wireless accessory sensor nodes and sensors. For example, an embodiment may use a single wireless accessory sensor node for the receptacle with multiple sensors deployed in each of the compartments on a compartment-by-compartment basis. In another example, an embodiment may use a wireless accessory sensor node dedicated per compartment with multiple sensors per compartment for that respective sensor node.

(230) FIGS. **10A-10E** illustrate a variety of exemplary embodiments of a multi-compartment logistics receptacle in the form of structural elements and electronic monitoring and reporting elements. Those skilled in the art will appreciate that the detailed explanation regarding potential sensors that monitor components of a logistics receptacle and wireless accessory sensor nodes related to FIG. 2 may also be applicable to the exemplary embodiments of a multi-compartment logistics receptacle shown in each of FIGS. **10A-10E**. For example, while the embodiments shown in FIGS. **10A-10E** may show one wireless accessory sensor node or a dedicated wireless accessory sensor node on a per-compartment basis, further embodiments may use multiple wireless accessory sensor nodes per compartment. Likewise, those skilled in the art will appreciate that the different types of sensors discussed relative to FIG. 2 may also be used in any of the exemplary embodiments of a multi-compartment logistics receptacle, such as that shown in FIG. **10A-10E**.

(231) FIG. **10A** is a diagram of an exemplary multi-compartment logistics receptacle as a system having multiple monitored receptacle compartments and a common access compartment in accordance with an embodiment of the invention. Referring now to FIG. **10A**, exemplary storage receptacle **1000** is shown having compartment **1005a**, compartment **1005b**, as well as a common access compartment **1010** that is selectively accessible via external access door **160x** (i.e., a type of

selectively accessible retrieval door that provides a level of access to compartments **1005a**, **1005b**). Compartment **1005a** has its own entrance door **156a**, entrance opening **155a**, temporary storage compartment area **205a**, as well as its own selectively accessible retrieval door **160a** through which a logistics asset (such as a courier) that is authorized to retrieve items from compartment **1005a** may gain access to the temporary storage area defined within compartment **1005a**. In other embodiments, compartment **1005a** may use alternative types of entrance openings as discussed above.

(232) In like manner, compartment **1005b** in this embodiment also has its own entrance door **156b**, entrance opening **155b**, temporary storage compartment area **205b**, as well as its own selectively accessible retrieval door **160b** through which a logistics asset (such as a courier) that is authorized to retrieve items from compartment **1005b** may gain access to the temporary storage area defined within compartment **1005b**. In other embodiments, compartment **1005b** may also use alternative types of entrance openings as discussed above.

(233) In FIG. **10A**, the exemplary multi-compartment logistics receptacle system shown includes an exemplary bridge node **200**, an exemplary wireless accessory sensor node **1002**, and different subsets of sensors **1020a**, **1020b** respectively deployed in each of compartments **1005a**, **1005b** that may monitor different aspects in each of the compartments **1005a**, **1005b** (similar that described above regarding wireless sensor nodes explained relative to FIGS. **2** and **4**). The exemplary bridge node **200** shown in FIG. **10A** is mounted to exemplary storage receptacle **1000** and operative to communicate with the backend server **100** over a first communication path (e.g., Wi-Fi, cellular, and the like), and may be further operative to communicate over a second communication path (e.g., Bluetooth® Low Energy (BLE), NFC, and the like) different than the first communication path. The embodiment shown in FIG. **10A** deploys an exemplary wireless accessory sensor node **1002** (similar to that explained in FIG. **4** regarding exemplary wireless accessory sensor node **210**) mounted to the storage receptacle **1000** and coupled (wired or wireless) to sensors **1020a**, **1020b** where such sensors monitor for a change in state of storage receptacle **1000**. In more detail, a first subset of sensors **1020a** is disposed relative to monitored receptacle compartment **1005a**, while a second subset of sensors **1020b** is disposed relative to monitored receptacle compartment **1005b**. Exemplary sensors **1020a**, for example, may include different types of sensors (e.g., motion sensors, magnetic sensors, light sensors, accelerometers, scale sensors, image sensors, lock sensors, and the like) that monitor components and aspects (e.g., the temporary storage compartment, entrance opening, retrieval door, light within the compartment, gas within the compartment, movement within the compartment, weight of contents held within the compartment, and the like) relative to monitored receptacle compartment **1005a**. Exemplary sensors **1020b**, in like manner, may include different types of sensors that monitor similar components and aspects relative to monitored receptacle compartment **1005b**.

(234) During operation of the exemplary multi-compartment logistics receptacle system shown in FIG. **10A**, exemplary wireless accessory sensor node **1002** is further operative to detect the change in state of the storage receptacle **1000** based upon sensor data generated by at least one of the sensors in the first subset of sensors **1020a** and in the second subset of sensors **1020b**; record timestamped information reflecting the detected change in state of the storage receptacle **1000**; and broadcast an updated advertising signal having a data available flag set within the updated advertising signal. Similar to that explained above, such a data available flag indicates the wireless accessory sensor node **1002** has event information available for upload by the bridge node **200**, where such event information available for upload including at least the timestamped information reflecting the detected change in state of the storage receptacle **1000**. Bridge node **200**, as part of this embodiment, is further operative to detect the data available flag set within the updated advertising signal, retrieve the event information available for upload from the wireless accessory sensor node **1002**, and transmit the retrieved event information to the backend server **100** (e.g., via network **105**) to cause the backend server **100** to initiate the dispatched logistics operation related

to the storage receptacle **1000**.

(235) Similar to that described above in embodiments using a single compartment logistics receptacle, the timestamped information may reflect a time of the detected change in the storage receptacle **1000** and a source of such a detected change in state of the storage receptacle **1000** (e.g., the source being at least one of compartments **1005a**, **1005b** and door **160a/160b/160x**). In more detail, the source of the detected change in state of the storage receptacle **1000** may include at least one of the monitored components associated with compartment **1005a**, the monitored components associated with compartment **1005b** (e.g., an entrance opening, temporary storage area, and the like), and the selectively accessible retrieval door(s) **160x/160a/160b**, locks for securing any of the doors.

(236) Similar to that described above in embodiments using a single compartment logistics receptacle, the event information may include the timestamped information and an identifier indicating a type of detected change in state of the storage receptacle (e.g., a change in state of at least one of entrance opening **155a/156a** and entrance opening **155b/156b**; a change in state of at least one of temporary storage area **205a** and temporary storage area **205b**; a change in state of entrance opening **155a/156a** and temporary storage area **205a**; a change in state of entrance opening **155b/156b** and temporary storage area **205b**; and a change in state of the selectively accessible retrieval door(s) **160x/160a/160b**).

(237) In some embodiments, a lock may be deployed for securing the selectively accessible retrieval door and where a lock sensor may monitor the state of the lock for that door. In such an embodiment, the type of detected change in state of the storage receptacle **1000** may include a change in the state of the lock as indicated by the lock sensor.

(238) In some embodiments, at least one of the sensors **1020a/1020b** may include an external motion sensor that monitors outside the storage receptacle **1000** (or a particular compartment of the receptacle **1000**) for movement within a predetermined range of the storage receptacle **1000** (or that particular compartment **1005a/1005b**). In such an embodiment, the type of detected change in state of the storage receptacle **1000** may include a change in what has been placed within a predetermined range of the storage receptacle **1000** (or the particular compartment **1005a/1005b**) as indicated by the external motion sensor.

(239) The timestamped information may, in some embodiments, include data indicating a series of times corresponding to a series of related changes to the storage receptacle **1000** (or compartments **1005a/1005b**). Such a series of related changes to the storage receptacle correspond to the detected change in state of the storage receptacle associated with the retrieved event information transmitted to the backend server **100**. Such a series of related changes may, for example, correspond to a series of related changes to at least two of the entrance opening **155a/156a**, temporary storage area **205a**, entrance opening **155b/156b**, temporary storage area **205b**, and the selectively accessible retrieval door(s) **160x/160a/160b**.

(240) In a more detailed embodiment of the exemplary multi-compartment logistics receptacle system shown in FIG. **10A**, the first subset of sensors **1020a** may, for example, be implemented to include a motion sensor detecting a change in motion of the first entrance opening **155a/156a** as the change in state of the storage receptacle **1000**; a motion sensor detecting movement of what is received through the first entrance opening **155a/156a** as the change in state of the storage receptacle **1000**; an accelerometer detecting a change in motion of the first entrance opening **155a/156a** as the change in state of the storage receptacle **1000**; a magnetic sensor detecting a change in position of the first entrance opening **155a/156a** as the change in state of the storage receptacle **1000**. In another example, the first subset of the sensors **1020a** may be implemented with at least two or more from a group consisting of a motion sensor detecting a change in motion of the first entrance opening **155a/156a**; a motion sensor detecting movement of what is received through the first entrance opening **155a**; an accelerometer detecting a change in motion of the first entrance opening **155a/156a**; and a magnetic sensor detecting a change in position of the first

entrance opening **155a/156a** as the change in state of the storage receptacle **1000**. Those skilled in the art will understand that similar types of sensors may be deployed as the second subset of sensors **1020b** for detecting changes in the state of receptacle **1000** relative to entrance opening **155b/156b** for compartment **1005b**.

(241) Relative to the temporary storage area **205a**, the first subset of the sensors **1020a** may include one or more of, for example, a motion sensor detecting motion within the first temporary storage area **205a**; an image sensor detecting a change of what is stored within the first temporary storage area **205a**; a scale disposed at a bottom of the first temporary storage area **205a** (where the scale detects a change in weight of what is stored within the first temporary storage area **205a**); and a light sensor detecting a change in light within the first temporary storage area **205a**. Those skilled in the art will understand that similar types of sensors may be deployed as the second subset of sensors **1020b** for detecting changes in the state of receptacle **1000** relative to temporary storage area **205b** in compartment **1005b**.

(242) Relative to the retrieval door(s) used on receptacle **1000**, the first subset of the sensors **1020a** may include one or more of, for example, a motion sensor detecting a change in motion of the selectively accessible retrieval door **160a**; a magnetic sensor detecting a change in position of the selectively accessible retrieval door **160a**; a lock sensor detecting a change in a locked status of the selectively accessible retrieval door **160a**; and an external motion sensor detecting a change in what has been placed within a predetermined range of the storage receptacle **1000** (e.g., compartment **1005a**) as the change in state of the storage receptacle. Those skilled in the art will understand that similar types of sensors may be deployed as the second subset of sensors **1020b** for detecting changes in the state of receptacle **1000** relative to door **160b** in compartment **1005b**.

(243) While not shown in FIG. **10A**, an embodiment may include further sensors that are operatively coupled to exemplary wireless accessory sensor node **1002** that similarly monitors components that may not be dedicated with just one of the monitored receptacle compartments **1005a/1005b**, such as the external access door **160x** and/or the common access compartment **1010**. Thus, one skilled in the art will appreciate that in such an embodiment, a detected change in state of storage receptacle **1000** may also be based on sensors detecting, for example, a change in light within compartment **1010**, movement of or change in position/orientation of door **160x**, movement within compartment **1010**, and the like

(244) Similar to that described above in embodiments using a single compartment logistics receptacle, those skilled in the art will appreciate that an embodiment of the exemplary multi-compartment logistics receptacle system shown in FIG. **10A** may have bridge node **200** waking at a predetermined time of day to detect any data available flag, may do so relative to points within the bridge node's reporting period, may detect subsequent data available flags prior to the end of the reporting period, transmit accumulated event information to the server at points during or at the end of the reporting period, and likewise periodically monitor for detected changes and incrementally retrieve/transmit relevant event information to backend server **100**.

(245) FIG. **10B** is a diagram of another exemplary multi-compartment logistics receptacle having multiple monitored receptacle compartments. Referring now to FIG. **10B**, exemplary storage receptacle **1015** is generally configured similar to exemplary receptacle **1000** of FIG. **10A**, but without a common access compartment **1010** that is selectively accessible via external access door **160x**. In other words, exemplary storage receptacle **1015** is shown having compartment **1015a**, compartment **1015b**, as well as a common selectively accessible retrieval door **160c** providing access to within each of the compartments **1015a**, **1015b** in accordance with an embodiment of the invention. Operation of the deployed bridge node **200**, wireless accessory sensor node **1002** and the groups of sensors **1020a**, **1020b** are similar to that described above relative to receptacle **1000** (with the exception that the retrieval door being monitored is door **160c** rather than particular compartment retrieval doors **160a**, **160b**).

(246) FIG. **10C** is a diagram of yet another exemplary multi-compartment logistics receptacle

similar to that in FIG. 10B, which uses door **160c**. However, in the embodiment shown in FIG. **10C**, the system uses different wireless accessory sensor nodes **1002a**, **1002b** for each of the monitored receptacle compartments **1015a**, **1015b**, respectively, in accordance with an embodiment of the invention. Those skilled in the art will appreciate that in some embodiments, it may be desired to use more than one wireless accessory sensor node within the receptacle and, in some instances, dedicate a wireless accessory sensor node and its own set of sensors to particular compartments. Operation of the deployed bridge node **200** and the groups of sensors **1020a**, **1020b** are similar to that described above relative to receptacle **1015**, but with the bridge node **200** being operative to detect advertising signals from both of the wireless accessory sensor nodes **1002a**, **1002b**, which respectively are coupled to the different subsets of sensors **1020a**, **1020b** for each compartment **1015a**, **1015b**.

(247) FIG. **10D** is a diagram of a fourth exemplary multi-compartment logistics receptacle having multiple monitored receptacle compartments similar to that in FIG. **10A** and separate selectively accessible retrieval doors **106a**, **160b** providing limited access to within individual compartments **1015a**, **1015b** in accordance with an embodiment of the invention. Referring now to FIG. **10D**, receptacle **1015** is shown configured similar to that of receptacle **1000** in FIG. **10A**, but without a common access compartment **1010** that is selectively accessible via external access door **160x**. The embodiment shown in FIG. **10D** operates similar to that of FIG. **10A** but allows for a logistics asset to directly access the individual compartments without accessing a common access compartment or the need to be authorized to access further parts of receptacle **1015** other than the particular retrieval door **106a**, **106b** for the appropriate compartment being serviced. Operation of the deployed bridge node **200**, wireless accessory sensor node **1002** and the groups of sensors **1020a**, **1020b** are similar to that described above relative to receptacle **1000**.

(248) FIG. **10E** is a diagram of a fifth exemplary multi-compartment logistics receptacle similar to that in FIG. **10D** but using different wireless accessory sensor nodes in each monitored receptacle compartment in accordance with an embodiment of the invention. In other words, the embodiment shown in FIG. **10E** is largely similar to that shown in FIG. **10C** but with a difference in that it uses individual retrieval doors **160a**, **160b** to provide access within each of compartments **1015a**, **1015b**. Thus, the embodiment shown in FIG. **10E** is a system that uses different wireless accessory sensor nodes **1002a**, **1002b** for each of the monitored receptacle compartments **1015a**, **1015b**, respectively, in accordance with an embodiment of the invention. Operation of the deployed bridge node **200** and the groups of sensors **1020a**, **1020b** are similar to that described above relative to receptacle **1015** in FIG. **10D**, but with the bridge node **200** being operative to detect advertising signals from both of the wireless accessory sensor nodes **1002a**, **1002b**, which respectively are coupled to the different subsets of sensors **1020a**, **1020b** for each compartment **1015a**, **1015b**.

(249) In each of the above-described embodiments of an exemplary multi-compartment logistics receptacle system shown in FIGS. **10A-10E** (as well as other embodiments that may use multi-compartment logistics receptacles similar to those shown in FIGS. **10A-10E**), such a system may validate detected changes through use of additional sensors (such as a light sensor), which help confirm or otherwise indicate the change is related to a pickup/delivery. For example, an embodiment may have a wireless accessory sensor node (such as node **1002**) being operative to detect the change in state of the storage receptacle based upon sensor data generated by at least one of the sensors by being further operative to detect a change in state of a first entrance opening (such as entrance opening **155a/156a**) using a first sensor from sensors **1020a**, and validate the change in state of that entrance opening by detecting light within the temporary storage area **205a** using a light sensor from the first group of sensors **1020a**. In this way, the change in state of the storage receptacle corresponds to a delivery event where the delivery item is received in that temporary storage compartment **1015a** of particular storage receptacle.

(250) In another embodiment, the wireless accessory sensor node (such as node **1002**) may be operative to detect the change in state of the storage receptacle based upon sensor data generated by

at least one of the sensors by being further operative to detect a change in state of the second entrance opening (such as entrance opening **155b/156b**) using a sensor from sensors **1020b**, and validate the change in state of the second entrance opening by detecting light within the temporary storage area using a light sensor from that group of sensors **1020b**. In this way, the change in state of the storage receptacle corresponds to a delivery event where the delivery item is received in the second temporary storage compartment **1015b** of the storage receptacle.

(251) In still another embodiment, the wireless accessory sensor node (such as node **1002**) may be operative to detect the change in state of the storage receptacle based upon sensor data generated by the at least one of the sensors by being further operative to detect a change in state of the selectively accessible retrieval door (such as door **160a**) using a sensor from sensors **1020a** and validate the change in state of the selectively accessible retrieval door by detecting light within the temporary storage area using a light sensor from that group of sensors **1020a**. In this way, the change in state of the storage receptacle corresponds to a pickup event where the delivery item is removed from within the storage receptacle (e.g., from within compartment **1015a** of receptacle **1000**).

(252) When the detected change in state of the storage receptacle is a pickup event, embodiments of the system's bridge node may be operative to transmit the retrieved event information back to the backend server in a particular manner. For example, an embodiment of the bridge node processor, when executing the multi-compartment bridge node code, may be operative to transmit the retrieved event information to the backend server by being operative to determine the retrieved event information indicates the detected change in state of the storage receptacle is a pickup event; and transmit, using the long-range communication interface and after the retrieved event information is determined to indicate the detected change in state of the storage receptacle is the pickup event, the retrieved event information to the backend server to cause the backend server to initiate the dispatched logistics operation related to the delivery item. In more detail, the bridge node processor may, for example, determine that the retrieved event information indicates the detected change in state of the storage receptacle is the pickup event when the recorded timestamped information reflecting the detected change in state of the storage receptacle indicates a change in state of the selectively accessible retrieval door. In another example, the bridge node processor may determine the retrieved event information indicates the detected change in state of the storage receptacle is the pickup event when the recorded timestamped information reflecting the detected change in state of the storage receptacle indicates (a) a change in state of the selectively accessible retrieval door and (b) a change in state of at least one of the first temporary storage compartment (e.g., a detected change in motion within the first temporary storage compartment based upon first motion sensor data as part of the sensor data; a detected change of what is stored within the first temporary storage compartment based upon first image sensor data as part of the sensor data; a detected change in weight of what is stored within the first temporary storage compartment based upon first scale data as part of the sensor data; and a detected change in light within the first temporary storage compartment based upon first light sensor data as part of the sensor data) and the second temporary storage compartment (e.g., a detected change in motion within the second temporary storage compartment based upon second motion sensor data as part of the sensor data; and a detected change of what is stored within the second temporary storage compartment based upon second image sensor data as part of the sensor data; a detected change in weight of what is stored within the second temporary storage compartment based upon second scale data as part of the sensor data; and a detected change in light within the second temporary storage compartment based upon second light sensor data as part of the sensor data).

(253) FIG. **11** is a diagram illustrating an exemplary multi-compartment logistics receptacle operating within a network and in communication with an exemplary backend server where the server initiates a dispatched logistics operation with a particular logistics entity in accordance with an embodiment of the invention.

(254) As explained above relative to FIG. 7, those skilled in the art will appreciate that exemplary backend server **100** may receive information from different exemplary connected logistics receptacles **150a-150c** via messages and communications over network **105** and may initiate different types of dispatched logistics operations as a result of such messages and communications. As shown in FIG. **11**, one or more of those exemplary connected logistics receptacles may be implemented as an exemplary multi-compartment logistics receptacle **1015**. Referring now to FIG. **11**, exemplary logistics assets **700a-700c** may be dispatched for a dispatched logistics operation (e.g., a pickup operation, a delivery operation) related to one or more of exemplary logistics receptacles, including exemplary multi-compartment logistics receptacle **1015**, based on the different messages and communications sent to backend server **100**. And similar to that described herein, backend server **100** may alter or tune the operational parameters of exemplary connected logistics receptacles (including exemplary multi-compartment logistics receptacle **1015**) based on the different messages and communications sent to backend server **100**.

(255) In some embodiments involving an enhanced multi-compartment logistics receptacle (such as those shown in FIGS. **10A-10E**), retrieval of the delivery item (e.g., package, parcel, letter, and the like) may be dynamically initiated with a particular logistics asset depending on the particular compartment associated with the detected change in state. For example, an embodiment may include an exemplary enhanced multi-compartment logistics receptacle system for receiving and temporarily maintaining a delivery item (e.g., package **170**, **175**) and causing initiation of a dispatched logistics operation where such a system includes at least backend server **100**, a multi-compartment storage receptacle **1015**, a bridge node **200**, and a wireless accessory sensor node **1002** that has (e.g., is wired to or wirelessly coupled to) sensors **1020a**, **1020b** for each compartment of the receptacle **1015**. Sensors **1020a**, **1020b** operate to monitor for a change in state of the storage receptacle **1015** (e.g., sensors **1020a** monitoring for a change in the state of compartment **1015a** of receptacle **1015**, and sensors **1020b** monitoring for a change in the state of compartment **1015b** of receptacle **1015**).

(256) In such an embodiment, the system's wireless accessory sensor node **1002** is programmatically configured and adapted so as to become operative to detect the change in state of the storage receptacle **1015** based upon sensor data generated by at least one of the sensors in the first subset of sensors **1020a** and in the second subset of sensors **1020b**. The wireless accessory sensor node **1002** is further operative to record timestamped information reflecting the detected change in state of the storage receptacle, and broadcast an updated advertising signal having a data available flag set within the updated advertising signal. The data available flag indicates the wireless accessory sensor node **1002** has event information available for upload by the bridge node **200**. Such event information available for upload includes at least (a) the timestamped information reflecting the detected change in state of the storage receptacle, and (b) a detected change indicator identifying which of the receptacle's compartments is related to the detected change in state of the storage receptacle **1015**.

(257) In this embodiment, the system's bridge node **200** is programmatically configured and adapted so as to become operative to detect the data available flag set within the updated advertising signal, retrieve the event information available for upload from the wireless accessory sensor node **1002**, and transmit a state change notification to the backend server **100**. Such a state change notification is a message related to the retrieved event information reflecting the detected change in state of the storage receptacle **1015**.

(258) In this embodiment, the system's backend server **100** is operative to receive the notification from the bridge node and initiate the dispatched logistics operation with a first logistics entity and related to the first of the monitored receptacle compartments when the notification indicates the retrieved event information is related to the first of the monitored receptacle compartments. As such, the backend server initiates the dispatched logistics operation with more specificity based on the particular compartment **1015a**, **1015b** of receptacle **1015**. In more detail, backend server **100**

may be operative to initiate the dispatched logistics operation by being operative to identify the first logistics entity for the dispatched logistics operation based upon the detected change indicator included with the received event information and initiate the dispatched logistics operation related to the first of monitored receptacle compartments using the identified first logistics entity.

(259) In a further embodiment, the dispatched logistics operation involving receptacle **1015** may be implemented as a swap operation by the first logistics entity to retrieve the delivery item from the first of the monitored receptacle compartments and drop-off a second item into the first of the monitored receptacle compartments. For example, FIG. **12A** is a diagram illustrating exemplary multi-compartment logistics receptacle **1015** involved in an exemplary swap type of dispatched logistics operation being carried out by exemplary logistics asset **700a** involving monitored receptacle compartment **1015b** in accordance with an embodiment of the invention. Referring now to FIG. **12A**, receptacle **1015** is shown where exemplary logistics asset **700a** (as a type of logistics entity) has opened door **160b** as part of a swap operation to drop off package **175a** within compartment **1015b** (e.g., place package **175a** within temporary storage area **205b**) while also picking up package **175b** from within compartment **1015b**.

(260) Alternatively, such a dispatched logistics operation may be implemented as a swap operation by the first logistics entity to retrieve the delivery item from the first of the monitored receptacle compartments and drop-off a second item into the second of the monitored receptacle compartments. For example, FIG. **12B** is a diagram illustrating exemplary multi-compartment logistics receptacle **1015** involved in an exemplary swap type of dispatched logistics operation being carried out by exemplary logistics asset **700a** involving both of monitored receptacle compartments **1015a** and **1015b** in accordance with an embodiment of the invention. Referring now to FIG. **12B**, receptacle **1015** is shown where exemplary logistics asset **700a** (as a type of logistics entity) has opened door **160a** as part of a swap operation to drop off package **175a** within compartment **1015a**, and then opened door **160b** as part of the swap operation to pick up package **175b** from within compartment **1015b**.

(261) In some further embodiments, the backend server **100** identifies the particular logistics entity/asset for the dispatched logistics operation by considering the role of that logistics entity/asset. For example, a further embodiment may have the backend server being operative to identify the first logistics entity by being further operative to dynamically identify the first logistics entity based upon a role of the first logistics entity associated with the delivery item (e.g. where the role of the first logistics entity associated with the delivery item is a logistics courier role having the first logistics entity involved with the delivery item and at least one other additional delivery item as part of the dispatched logistics operation; where the role of the first logistics entity associated with the delivery item comprises a for-hire role (such as a gig worker) having the first logistics entity picking up only the delivery item and delivering the delivery item to a recipient as part of the dispatched logistics operation; where the role of the first logistics entity associated with the delivery item comprises a primary recipient role having the first logistics entity being an intended recipient of the delivery item; and where the role of the first logistics entity associated with the delivery item comprises a secondary recipient role having the first logistics entity being related to an intended recipient of the delivery item).

(262) In still further embodiments, a more explicit transfer of rights to access a particular compartment **1015a**, **1015b** of the multi-compartment storage receptacle **1015** may be implemented. For example, a further embodiment may have the backend server **100** operative to initiate the dispatched logistics operation with the first logistics entity by being operative to transfer a right to access the first of the monitored receptacle compartments (e.g., compartment **1015a**) to the first logistics entity for use in conducting the dispatched logistics operation with the first of the monitored receptacle compartments. More specifically, backend server **100** may be further operative to transmit a permissive notification to bridge node **200**, where the permissive notification identifies the transferred right to access the first of the monitored receptacle

compartments **1015a**. Such permissive notification may also identify the first logistics entity as being authorized to use the transferred right to access the first of the monitored receptacle compartment **1015a**. In another example, a further embodiment may have the backend server **100** being operative to initiate the dispatched logistics operation with the first logistics entity by further being operative to transfer a right to access each of the monitored receptacle compartments in the receptacle (or a subset of all compartments in the receptacle) to the first logistics entity for use in conducting the dispatched logistics operation with at least the first of the monitored receptacle compartments.

(263) In yet another further embodiment, the backend server may use a different logistics asset/entity for subsequent servicing of that multi-compartment logistics receptacle. For example, a further embodiment may have backend server **100** being further operative to receive a subsequent notification from bridge node **200** where the subsequent notification is related to additional event information reflecting a detected change in state of the storage receptacle for a different compartment (e.g., the second of the monitored receptacle compartments **1015b**). The backend server **100** is then operative to initiate a subsequent dispatched logistics operation with a second logistics entity (e.g., **700b**) and related to the second of the monitored receptacle compartments **1015b** when the subsequent notification indicates the additional event information is related to the second of the monitored receptacle compartments **1015b**. More particularly, the backend server may be further operative to initiate a subsequent dispatched logistics operation with a second logistics entity and related to the second of the monitored receptacle compartments when the notification indicates the retrieved event information is related to the second of the monitored receptacle components.

(264) Backend Server Tuning of a Node-Based Connected Logistics Receptacle

(265) As noted above, various embodiments may have the backend server learning from the reported event information and responsively tuning or modifying the operations of one or more node-based connected logistics receptacles (also referred to as node-based logistics receptacles herein) as a result. For example, an embodiment may implement adjusting or tuning operations by backend server **100** where the backend server **100** learns of engagement interactions and patterns of use/interaction with particular components of a node-based logistics receptacle and then updates the bridge node in that node-based logistics receptacle with revised operational parameters to tune, for example, the drop off time per location and alter the pickup resources needed. In more detail, such embodiments may have the server tuning when a particular bridge node deployed with a storage receptacle may retrieve or upload event information (which may be related to a revised drop off time for the receptacle) and/or tuning when such a bridge node transmits such retrieve event information to the backend server (e.g., at a revised end of a reporting period (related to a new drop-off time)). FIGS. **15A-19B** illustrate various aspects related to such server learning embodiments involving tuned timing related to the logistics receptacles.

(266) FIG. **15A** is a diagram of an exemplary system for dynamically tuning operations where the system's bridge node in an exemplary node-based logistics receptacle is transmitting retrieved event information to the system's backend server in accordance with an embodiment of the invention. Referring now to FIG. **15A**, exemplary backend server **100**, network **105**, exemplary node-based logistics receptacles **150a-150c**, and exemplary logistics asset **700a** are shown where exemplary node-based logistics receptacle **150a** has detected a change in state of receptacle **150a** and the bridge node within that exemplary node-based logistics receptacle **150a** transmits retrieved event information **1500** through network **105** to backend server **100**. In general, in such an exemplary system, backend server **100** responds to the transmitted retrieved event information **1500** with an exemplary tuned time parameter message **1505**, as shown in FIG. **15B**, sent by backend server **100** to the system's bridge node in exemplary node-based logistics receptacle **150a** to cause that bridge node to alter timing related operations in accordance with an embodiment of the invention.

(267) An exemplary embodiment of the bridge node device in such an embodiment is shown in FIG. 16. Referring now to FIG. 16, exemplary bridge node **16200** is illustrated with components (e.g., hardware and software elements) similar to that explained with respect to exemplary bridge node **200** (FIG. 3), but exemplary bridge node **16200** is expressly shown having timing data **1605** as additional data used in the operation of the bridge node. Exemplary timing data **1605** is generally a data structure that maintains information related to the timing of particular operations of the bridge node. As such, exemplary timing data **1605** may be implemented as a dynamic timing profile data structure on what is being altered in response to when the bridge node **16200** receives a tuned time parameter message. For example, exemplary timing data **1605** may be updated or revised in accordance with the tuned time parameter message to dynamically alter or update the predetermined time of day that bridge node **16200** retrieves or uploads available event information from a wireless accessory sensor node in the receptacle. In addition, or alternatively, exemplary timing data **1605** may be updated or revised in accordance with the tuned time parameter message to dynamically alter or update the predetermined time of day that bridge node **16200** transmits retrieved event information to backend server **100**. Those skilled in the art will appreciate that other bridge nodes, such as exemplary bridge node **200**, may also be implemented with exemplary timing data **1605** used for storing, maintaining, and updating information related to timing of operations for that particular bridge node—e.g., reporting periods, waking times, retrieval times for uploading event information from a wireless accessory sensor node, transmission times for sending retrieved event information to the backend server, and the like.

(268) In an embodiment that may make use of such exemplary revised timing data **1605** in response to a tuned time parameter message **1505**, an exemplary system for dynamically tuning operation of a node-based logistics receptacle is described. Such a node-based logistics receptacle **150a** (similar to receptacle **150**) used relative to such a system has multiple storage receptacle components including at least an entrance opening **155/156** for receiving a delivery item (e.g., package **170**), a temporary storage area **205** for temporarily maintaining the delivery item once received, and a retrieval door **160** providing selective access to the delivery item within the temporary storage area **205**. In general, the exemplary system for dynamically tuning operation of the node-based logistics receptacle includes backend server **100**, a wireless accessory sensor node (e.g., nodes **210**, **1002**, **1002a/1002b**), and a bridge node (e.g., bridge node **16200**). The system's wireless accessory sensor node is disposed on the node-based logistics receptacle and has sensors (e.g., sensors **450a-450e**, **1020a**, **1020b**) that collectively monitor the storage receptacle components of the node-based logistics receptacle. Each of the sensors is operative to generate sensor data reflecting one or more interactions with the storage receptacle components of that node-based logistics receptacle over a recording time period.

(269) The system's bridge node **16200** is disposed on the node-based logistics receptacle and programmatically operative to retrieve event information from the wireless accessory sensor node at a predetermined time of day. In more detail, an embodiment may have the system's bridge node **16200** being operative to retrieve the event information from the wireless accessory sensor node at the predetermined time of day by being further operative to wake from a low power state at the predetermined time of day, and once woken from the low power state, retrieve the event information from the wireless accessory sensor node.

(270) The system's bridge node **16200** then transmits the retrieved event information to the backend server **100**. The retrieved event information (such as exemplary retrieved event information **1500**) represents the sensor data generated over the recording time period. In response to receiving the retrieved event information from bridge node **16200**, backend server **100** is programmatically operative to transmit a tuned time parameter message (such as exemplary tuned time parameter message **1505**) to the bridge node. Such a tuned time parameter message causes bridge node **16200** to alter the predetermined time of day that the bridge node **16200** retrieves subsequent event information from the wireless accessory sensor node in the reporting node-based logistics

receptacle **150a**.

(271) In more detail, an example of such a system embodiment may have backend server **100** being operative to generate the tuned time parameter message **1505** based upon a customer-initiated interaction with the one or more of the storage receptacle components (e.g., entrance opening **155/156**, temporary storage area **205**) as indicated by the retrieved event information **1500** received from the bridge node. In another example, the embodiment may have backend server **100** being operative to generate the tuned time parameter message **1505** based upon a courier-initiated interaction with one or more of the storage receptacle components (e.g., the retrieval door **160**, temporary storage area **205**) as indicated by the retrieved event information **1500** received from the bridge node.

(272) In still further embodiments, an exemplary system embodiment may have backend server **100** being further operative to generate the tuned time parameter message **1505** based upon (a) timing information of the detected/sensed interactions with the storage receptacle component(s) as indicated by the retrieved event information **1500** received from the bridge node; and/or (b) a type of the interactions with the storage receptacle component(s) as indicated by the retrieved event information **1500** received from the bridge node. Examples of such a type of interaction may include, but is not limited to, a sensed movement of the entrance opening **155/156**; a sensed movement of an object moving through the entrance opening **155**; a change in position of the entrance opening **155/156**; a sensed movement within the temporary storage area **205**; a change in what is stored within the temporary storage area **205**; a change in weight of what is stored within the temporary storage area **205**; a change in light detected within the temporary storage area **205** (or more generally within the receptacle **150a**); a change in position of the retrieval door **160**; and a sensed movement of the retrieval door **160**.

(273) Further embodiments of such an exemplary system for dynamically tuning operations of a logistics receptacle may identify/detect interactions and compare event information related to such interactions to prior interaction history for that node-based logistics receptacle (e.g., for particular components of that receptacle) as the basis for generating the tuned time parameter message **1505**. For example, a further embodiment may have backend server **100** being further operative to generate the tuned time parameter message **1505** by being operative to receive the retrieved event information **1500** from the bridge node **16200** and identify a first engagement event (e.g., a drop-off event or pickup event) for a first of the storage receptacle components of that node-based logistics receptacle **150a** from the retrieved event information **1500**. The backend server **100** is also operative to then compare the identified first engagement event for the first storage receptacle component with a prior component engagement history for the first storage receptacle component (e.g., server-tracked historic use pattern and engagement history information in management profile **835**) and generate the tuned time parameter message **1501** based upon that comparison. In more detail, when such a prior component engagement history is implemented as a server-tracked historic use pattern for the first of the storage receptacle components, the backend server **100** may conduct such a comparison by detecting a threshold change in the server-tracked historic use pattern for the first storage receptacle component based upon the identified first engagement event. This server-tracked historic use pattern may, for example, be maintained on the backend server as part of a profile (e.g., as part of management profile **835**) identifying a pattern of use of the node-based logistics receptacle, such as a pattern of delivery events for the node-based logistics receptacle or a pattern of pickup events for the node-based logistics receptacle. The profile may, in some examples, include information representing a threshold occupancy pattern profile identifying a frequency of reaching a threshold occupied level within the node-based logistics receptacle. In still other examples, the profile may include information representing an overload pattern profile identifying a frequency of reaching an overload condition for the node-based logistics receptacle.

(274) In another example, a further embodiment may have backend server **100** being further operative to generate the tuned time parameter message **1505** by being operative to receive the

retrieved event information **1500** from the bridge node **16200**; identify multiple engagement events for the storage receptacle components of the node-based logistics receptacle **150a** from the retrieved event information **1500**; compare the identified engagement events for those storage receptacle components with a prior component engagement history for those storage receptacle components (e.g., information in management profile **835**); and generate the tuned time parameter message **1505** based upon the comparison.

(275) Such a prior component engagement history may be implemented as a server-tracked historic use pattern for the storage receptacle components. As such, the backend server **100** may be operative to compare the identified engagement events for the storage receptacle components with the prior component engagement history for those storage receptacle components by being further operative to detect a threshold change in the server-tracked historic use pattern for those storage receptacle components based upon the identified engagement events.

(276) In still other embodiments, the server may identify a pattern of engagements as part of generating the tuned time parameter message. In more detail, a further embodiment may have backend server **100** being operative to receive the retrieved event information **1500** from the bridge node **16200**; identify a pattern of engagement events for one or more of the storage receptacle components of the node-based logistics receptacle **150a** from the retrieved event information **1500**; compare the identified pattern of engagement events for the storage receptacle components with a prior component engagement history for those storage receptacle components; and generate the tuned time parameter message **1505** based upon the comparison. In this further embodiment, the prior component engagement history may be implemented as a server tracked profile (e.g., a management profile **835** that maintains a server-tracked historic use pattern for receptacle components) for the node-based logistics receptacle **150a** indicating a prior pattern related to use of the storage receptacle components; a prior pattern related to timing of interactions with the storage receptacle components; and a prior pattern related to types of the interactions with the storage receptacle components. In still a further example, the backend server **100** may conduct the comparison of identified pattern of engagement events for the storage receptacle components with the prior component engagement history for the storage receptacle components by detecting a threshold change in the server-tracked historic use pattern for the storage receptacle components based upon the identified pattern of engagement events.

(277) In addition to transmitting the tuned time parameter message, further embodiments may have the backend server **100** taking steps to initiate a logistics operation (pickup from, delivery to) this particular node-based logistics receptacle **150a**. For example, backend server **100** may be further programmatically operative, in response to receiving the retrieved event information **1500**, to initiate a dispatched logistics operation related to the node-based logistics receptacle **150a** with a first logistics asset (e.g., asset **700a**). In another example, backend server **100** may be programmatically operative, in response to receiving the retrieved event information **1500**, to initiate an alternative dispatched logistics operation related to the node-based logistics receptacle **150a** with an alternative logistics asset (such as asset **700b**). This alternative logistics asset may be different than an original logistics asset corresponding to a previously scheduled dispatch operation for that node-based logistics receptacle **150a**.

(278) Still further embodiments relating to dynamic tuning operations for a node-based logistics receptacle (such as receptacle **150a**) may involve sending a message to the backend server at predetermined time of day indicating no interactions detected. For example, a further system embodiment to that described above may have the system's bridge node **16200** being further programmatically operative to transmit a first confirmation status message to the backend server **100**, where the first confirmation status message represents a type of confirmation that the bridge node **16200** is at least operative to determine no further event information is available to upload from the system's wireless accessory sensor node during a subsequent reporting time period and where transmission of such a confirmation status message by bridge node **16200** may occur at a

designated or dynamically updated time of day.

(279) Likewise, the system's bridge node **16200** in another embodiment may be further programmatically operative to transmit a second confirmation status message to the backend server **100**, where the second confirmation status message represents another type of confirmation that the bridge node **16200** is at least operative to receive a signal from the wireless accessory sensor node during the subsequent reporting time period. In more detail, the signals from the wireless accessory sensor node may indicate no further interactions with the storage receptacle components of the node-based logistics receptacle **150a** over the subsequent reporting time period and where the bridge node may transmit the second confirmation status message to the backend server at a designated time of day.

(280) The system embodiments relating to dynamic tuning operations for a node-based logistics receptacle (such as receptacle **150a**) described above involve tuning or adjusting when the bridge node **16200** retrieves or uploads available event information from the wireless accessory sensor node, but a further embodiment may also tune the time for transmitting or uploading such retrieved event information to the backend server **100**. For example, an embodiment may implement the tuned time parameter message **1505** such that it also causes the bridge node **16200** to alter when the bridge node **16200** transmits future retrieved event information to the backend server **100**. In more detail, the tuned time parameter message generated by backend server **100** may cause the bridge node **16200** to alter a cutoff time of day when the node-based logistics receptacle **150a** is designated to no longer accept any further delivery item (e.g., packages, letters, parcels, objects, and the like) for the day and when the bridge node **16200** transmits future retrieved event information to the backend server. In even more detail in such an example, the backend server **100** may be programmatically operative to transmit the tuned time parameter message **1505** to the bridge node **16200** in receptacle **150a** by being further programmatically operative to (a) determine whether an adjustment of the cutoff time of day for the node-based logistics receptacle **150a** is warranted based upon the retrieved event information **1500** received by the backend server **100**; (b) generate the tuned time parameter message **1505** when the adjustment of the cutoff time of day for the node-based logistics receptacle **150a** is determined to be warranted based upon the retrieved event information **1500** received by the backend server **100**; and (c) transmit the tuned time parameter message **1505** to the bridge node **16200** causing the bridge node **16200** to at least alter when the bridge node **16200** transmits future retrieved event information to the backend server **100**.

(281) The system embodiments relating to dynamic tuning operations for a node-based logistics receptacle (such as receptacle **150a**) described above may also inform others about adjustments related to the node-based logistics receptacle in various ways, such as via an online portal or via an integral display on the receptacle itself. FIG. 17A is a diagram illustrating an exemplary user access device **1700** that is operative to access an online portal **1710** hosted by backend server **100** in accordance with an embodiment of the invention. Referring now to FIG. 17A, exemplary user access device **1700** is a processor based communication device (such as a smartphone, laptop, tablet, and the like) that is able to connect to network **105** and may communicate with other devices, such as mobile handheld bridge nodes used by logistics personnel and or connect with and communicate with a node-based logistics receptacle (e.g., once authorized and authenticated to do so). Generally, user access device **1700** via its screen **1705** (or field of view display when device **1700** is an augmented reality based device) allows a user, in the embodiment shown in FIG. 17A, to access and view operational information on a node-based logistics receptacle, such as updated operational information on times of use for receptacle **150a** (e.g., an adjusted cutoff time of day for the node-based logistics receptacle **150a** for accepting any further delivery item or after which deliver items will not be accepted/reported; an adjusted period of time during which the node-based logistics receptacle will accept any further delivery item and outside of which items will not be accepted/reported).

(282) In more detail, an embodiment may have exemplary user access device **1700** showing online

portal **1710** as a window on screen **1705** and where the information shown in online portal **1710** is provided by backend server **100** (as shown in FIG. **17A**) or, in other examples, by a secondary/cloud server **1720** (separate from backend server **100**, as shown in FIG. **17B**). Those skilled in the art will appreciate that secondary/cloud server **1720** may provide hosting services for such information presented in online portal **1710**, and may gain access such information via a third party database **1725** (which may be populated from backend server **100** with updated operational information on a particular node-based logistics receptacle—information that may be maintained by backend server **100** as part of management profile **835**, information that may be updated by backend server **100**, and information that may be separately uploaded to database **1725** and/or secondary/cloud server **1720**).

(283) In another embodiment, exemplary user access device **1700** may be implemented as an exemplary processor based augmented reality device. Those skilled in the art will appreciate that incorporation of augmented reality as part of the user operating device **1700** facilitates an enhanced interactive experience that combines real world content (e.g., a view of the surrounding area proximate device **1700**) and processor-generated content (e.g., virtual symbols, objects, information, prompted messages, directions, sensory information, and the like overlaid with the real world content) shown in an interwoven manner that advantageously allows the user to perceive both the real world content and the processor-generated content. In general, an exemplary augmented reality enhanced device implementation of user access device **1700** may include a processor, memory, a display (e.g., a heads up display that may be viewed on the device by the user or a look through display viewed through by the user with real world and processor-generated content appearing on the display overlaid on the real world content), sensors (e.g., GPS sensors, accelerometer, imaging sensors, camera, and the like), a wireless transceiver for communication with other devices, as well as input devices for user input and interactivity (e.g., button, cursor, touchscreen, microphone, and the like). Such an exemplary augmented reality enhanced device implementation of user access device **1700** may, for example, be implemented as augmented reality glasses that project a digital overlay directly in the user's field of vision. In general, an exemplary augmented reality enhanced device implementation of user access device **1700** presents the user with a combination of digital and physical worlds, facilitates interactions made in near real time with less distraction for the user, and an accurate 3D identification of virtual and real objects for use by the user when providing such interactions (e.g., receiving information displayed, recognizing objects (such as an exemplary node-based logistics receptacle), and providing responsive input/feedback based upon the information displayed). Further, such an exemplary processor based augmented reality device implementation of user access device **1700** may still provide the ability to connect to network **105** and communicate with other devices, such as mobile handheld bridge nodes used by logistics personnel (which may themselves have augmented reality features) and/or connect with and communicate with a node-based logistics receptacle (e.g., once authorized and authenticated to do so) via its wireless transceiver.

(284) Generally, those skilled in the art will appreciate that an exemplary augmented reality enhanced user access device **1700** via its screen **1705** (i.e., the field of view display for the AR device **1700**) allows, for example, a user to access and view operational information on a node-based logistics receptacle, such as updated operational information on times of use for receptacle **150a** (e.g., an adjusted cutoff time of day for the node-based logistics receptacle **150a** for accepting any further delivery item or after which deliver items will not be accepted/reported; an adjusted period of time during which the node-based logistics receptacle will accept any further delivery item and outside of which items will not be accepted/reported) in combination with a view of the real world. For example, an embodiment may have exemplary augmented reality enhanced user access device **1700** showing online portal **1710** on a portion of screen **1705** (e.g., as part of screen **1705**, as an overlay of information on screen **1705**) where the information shown in online portal **1710** is provided by backend server **100** (as shown in FIG. **17A**) or, in other examples, by a

secondary/cloud server **1720** (separate from backend server **100**, as shown in FIG. **17B**) while also allowing the user operating device **1700** a view on the remaining part of screen **1705** of the real world. Information shown on screen **1705** may be accompanied, for example, with additional notification enhancements (e.g., sound, colors, highlights, haptic feedback, and the like) that help draw attention to the information as perceived on screen **1705**.

(285) Those skilled in the art will appreciate that various embodiments of exemplary user access device **1700** may be implemented using a desktop computer, a laptop computer, a tablet (such as an Apple iPad® touchscreen tablet), a personal area network device (such as a Bluetooth® device), a smartphone (such as an Apple iPhone®), a smart wearable device (such as a Samsung Galaxy Gear™ smartwatch device, or a Google Glass™ wearable smart optics), an augmented reality (AR) headset, or other such devices capable of communicating over network **105** and its wired and/or wireless communication paths. Thus, an exemplary user access device may be a mobile type of device intended to be easily moved (such as a tablet or smartphone), and may be a non-mobile type of device intended to be operated from a fixed location (such as a desktop computer).

(286) FIG. **18** is a diagram illustrating an exemplary connected logistics receptacle **150** (similar to that in FIG. **1**) in communication with an exemplary backend server **100** where the logistics receptacle **150** includes an exemplary integral display **255** disposed to be viewable from outside of logistics receptacle **150** and capable of showing updated operational information related to adjusted or updated operational aspects of the logistics receptacle **150** in accordance with an embodiment of the invention. Referring now to FIG. **18**, exemplary display **255** is shown on the front of exemplary node-based logistics receptacle **150** so as to present displayed information on display **255** to a user of receptacle **150**. In such an example, the tuned time parameter message **1505** transmitted to the bridge node **16200** (disposed as part of receptacle **150**) may cause the bridge node **16200** to generate an updated operational information message shown on display **255**. In an example, this updated operational information message may reflect a changed cutoff time of day when the node-based logistics receptacle **150** is designated to no longer accept any further delivery item for the day; may reflect a new pickup time of day for the node-based logistics receptacle; may include a prompt to check online for a new pickup time of day for the node-based logistics receptacle (e.g., such as a visually scannable code generated on the display, where the visually scannable code (barcode, QR code, and the like) is related to online available information on the new pickup time).

(287) FIGS. **19A** and **19B** collectively are a flow diagram illustrating an exemplary method for dynamically tuning the operation of a node-based logistics receptacle similar to that discussed above in FIGS. **15A-18** and in accordance with an embodiment of the invention. Referring now to FIG. **19A**, exemplary method **1900** begins at step **1905** where the sensors of the wireless accessory sensor node on the node-based logistics receptacle are monitoring the receptacle's storage receptacle components for one or more interactions over a recording time period. At step **1910**, method **1900** determines if at least one of the sensors has generated sensor data reflecting interactions with one or more of the storage receptacle components of the node-based logistics receptacle over the recording time period. If not, then step **1910** returns to step **1905** for continued monitoring. However, if so, step **1910** proceeds to step **1915**.

(288) At step **1915**, method **1900** has the bridge node retrieving event information from the wireless accessory sensor node at a predetermined time of day, where such event information is related to the generated sensor data (e.g., event information may include information on a type of interaction, the component interacted with, timestamped information on the interaction, and the like). In some embodiments of step **1915**, method **1900** may implement this step by first having the bridge node waking from a low power state at the predetermined time of day, and then retrieving the event information from the wireless accessory sensor node by the bridge node once woken from the low power state. In a further embodiment, the retrieved event information in step **1915** may indicate a customer-initiated interaction with the one or more of the storage receptacle components (e.g., the entrance opening, the temporary storage area). In another example, the retrieved event

information may indicate a courier-initiated interaction with one or more of the storage receptacle components (e.g., the retrieval door, the temporary storage area). In still another embodiment of step **1915**, the retrieved event information may indicate timing information of the interactions with the one or more of the storage receptacle components. In yet another embodiment of step **1915**, the retrieved event information may indicate a type of the one or more interactions with the one or more of the storage receptacle components (e.g., a sensed movement of the entrance opening; a sensed movement of an object moving through the entrance opening; a change in position of the entrance opening; a sensed movement within the temporary storage area; a change in what is stored within the temporary storage area; a change in weight of what is stored within the temporary storage area; a change in light detected within the temporary storage area; a change in position of the retrieval door; and/or a sensed movement of the retrieval door).

(289) At step **1920**, method **1900** has the bridge node transmitting the retrieved event information to the backend server, where the retrieved event information represents the sensor data generated over the recording time period.

(290) At step **1925**, method **1900** has the backend server receiving the retrieved event information and comparing this retrieved event information to a prior component engagement history for the reporting node-based logistics receptacle (e.g., part of the information kept in exemplary management profile **835**). In a further embodiment of method **1900**, step **1925** may be implemented with the backend server identifying a first engagement event (e.g., a drop-off event, pickup event) for a first of the storage receptacle components of the reporting node-based logistics receptacle from the retrieved event information and comparing that identified first engagement event with a prior component engagement history for the first of the storage receptacle components (e.g., a server-tracked historic use pattern for that storage receptacle component). In this example, the backend server may generate the tuned time parameter message in step **1930** based upon the comparison of the identified first engagement event with the prior component engagement history (e.g., the server-tracked historic use pattern) for the first of the storage receptacle components. Using such a server-tracked historic use pattern, an embodiment of step **1925** may implement such a comparison by detecting a threshold change in the server-tracked historic use pattern for the first of the storage receptacle components based upon the identified first engagement event. The server-tracked historic use pattern in this embodiment of step **1925** may be maintained on the backend server as part of a profile (e.g., management profile **825**) identifying a pattern of use of the node-based logistics receptacle. Such a profile may, for example, be a pattern of delivery events for the node-based logistics receptacle; a pattern of pickup events for the node-based logistics receptacle; a threshold occupancy pattern profile identifying a frequency of reaching a threshold occupied level within the node-based logistics receptacle; or an overload pattern profile identifying a frequency of reaching an overload condition for the node-based logistics receptacle.

(291) In other embodiments of method **1900**, step **1925** may involve identifying multiple engagement events for the one or more of the storage receptacle components of the node-based logistics receptacle from the retrieved event information, and comparing the identified engagement events with a prior component engagement history (e.g., a server-tracked historic use pattern maintained as part of a profile, such as management profile **835**, which identifies patterns of use of the receptacle) for the one or more of the storage receptacle components. The tuned time parameter message may be generated based on this comparison and, in some embodiments of step **1925**, the comparison may involve detecting a threshold change in the server-tracked historic use pattern for the one or more of the storage receptacle components based upon the identified engagement events.

(292) In still other embodiments of method **1900**, step **1925** may perform such a comparison based upon identified patterns of engagements compared to server-tracked engagement history information. For example, the comparing step of step **1925** may be implemented with the backend server identifying a pattern of engagement events for the storage receptacle components of the node-based logistics receptacle from the retrieved event information and comparing the identified

pattern of engagement events with a prior component engagement history for the storage receptacle components. In this example, the backend server may generate the tuned time parameter message in step **1930** based upon the comparison of the identified pattern of engagement events for the storage receptacle components with the prior component engagement history for the storage receptacle components. As with the other examples above, the prior component engagement history for the storage receptacle components may be implemented with a server-tracked profile for the node-based logistics receptacle (e.g., management profile **835**) indicating a prior pattern related to use of the one or more of the storage receptacle components; a prior pattern related to timing of the one or more interactions with the one or more of the storage receptacle components; or a prior pattern related to types of the one or more interactions with the one or more of the storage receptacle components; or a server-tracked historic use pattern for the one or more of the storage receptacle components. When step **1925** is using such a server-tracked historic use pattern as the prior component engagement history, the comparing in step **1925** may be implemented by detecting a threshold change in the server-tracked historic use pattern for the one or more of the storage receptacle components based upon the identified pattern of engagement events.

(293) At step **1930**, the backend server proceeds with generating a tuned time parameter message (e.g., message **1505**) for the bridge node based upon the comparison of the retrieved event information to the prior component engagement history for the node-based logistics receptacle performed in step **1925**. Step **1930** proceeds through transition A to step **1935** on FIG. **19B**, where method **1900** has the backend server transmitting the tuned time parameter message to the bridge node. Thereafter, at step **1940**, method **1900** has the bridge node in the reporting node-based logistics receptacle altering the predetermined time of day that the bridge node retrieves subsequent event information from the wireless accessory sensor node based upon the tuned time parameter message.

(294) In a further embodiment of method **1900**, the backend server may also cause the initiation of a logistics operation for the reporting node-based logistics receptacle. For example, method **1900** may further include the step, in response to the backend server receiving the retrieved event information, of initiating a dispatched logistics operation by the backend server, where the dispatched logistics operation is related to the reporting node-based logistics receptacle and a first logistics asset (such as asset **700a**). In another example, method **1900** may further comprise the step of having the backend server initiating an alternative dispatched logistics operation in response to receiving the retrieved event information. Such an alternative dispatched logistics operating in this example is related to the reporting node-based logistics receptacle and an alternative logistics asset, which is different than an original logistics asset corresponding to a previously scheduled dispatch operation for the node-based logistics receptacle.

(295) An embodiment of method **1900** may also have the bridge node notifying the backend server with a message indicating that no interactions were detected. For example, method **1900** may further include a step of having the bridge node transmitting a first confirmation status message to the backend server, where the first confirmation status message represents a first confirmation that the bridge node is operative to determine no further event information is available to upload from the wireless accessory sensor node during a subsequent reporting time period, which may be done at a designated time of day (e.g., defined as part of information in exemplary timing data **1605**). In another example, method **1900** may further include a step of having the bridge node transmitting a second confirmation status message to the backend server, where the second confirmation status message represents a second confirmation that the bridge node is operative to receive a signal from the wireless accessory sensor node during the subsequent reporting time period (e.g., where the signal indicates no further interactions with the storage receptacle components of the node-based logistics receptacle over the subsequent reporting time period; and where such a second confirmation status message is sent at a designated time of day (which may be defined as part of information in exemplary timing data **1605**)).

(296) Embodiments of method **1900** relating to dynamic tuning operations for a node-based logistics receptacle (such as receptacle **150a**) described above involve tuning or adjusting when the bridge node **16200** retrieves or uploads available event information from the wireless accessory sensor node, but a further embodiment of method **1900** may also tune the time for transmitting or uploading such retrieved event information to the backend server. For example, method **1900** may further include a step where the bridge node is altering when the bridge node transmits future retrieved event information to the backend server based upon the tuned time parameter message. This may take the form of the bridge node altering a cutoff time of day when the node-based logistics receptacle is designated to no longer accept any further delivery item for the day and when the bridge node transmits future retrieved event information to the backend server based upon the tuned time parameter message (where such altered timing may be updated as part of exemplary timing data **1605**).

(297) In more detail, an embodiment of method **1900** may implement step **1940** where the tuned time parameter message is transmitted by (a) having the backend server determining whether an adjustment of the cutoff time of day for the node-based logistics receptacle is warranted based upon the retrieved event information received by the backend server; (b) having the backend server generating the tuned time parameter message once the adjustment of the cutoff time of day for the node-based logistics receptacle is determined to be warranted based upon the retrieved event information received by the backend server; and (c) having the backend server transmitting the tuned time parameter message to the bridge node causing the bridge node to at least alter when the bridge node transmits the retrieved subsequent event information to the backend server.

(298) Embodiments of method **1900** relating to dynamic tuning operations for a node-based logistics receptacle (such as receptacle **150a**) described above may also include steps that inform or notify others about adjustments related to the node-based logistics receptacle in various ways, such as via an online portal or via an integral display on the receptacle itself. For example, an embodiment of method **1900** may further include a step where the backend server is updating operational information on the node-based logistics receptacle, where such updated operational information (e.g., an altered time when the bridge node transmits future retrieved event information to the backend server based upon the tuned time parameter message; an adjusted cutoff time of day for the node-based logistics receptacle for accepting any further delivery item; an adjusted period of time during which the node-based logistics receptacle will accept any further delivery item) is accessible through an online portal and including information on an altered time when the bridge node transmits future retrieved event information to the backend server based upon the tuned time parameter message. As explained relative to FIGS. **17A** and **17B**, such an online portal may be hosted by the backend server or a second server (e.g., secondary/cloud server **1720**). In another example, a further embodiment of method **1900** has the bridge node generating an updated operational information message shown on a display coupled to the bridge node (e.g., integral display **255** shown in FIG. **18**) and disposed on the node-based logistics receptacle. In this example, the updated operational information message may reflect a changed cutoff time of day when the node-based logistics receptacle is designated to no longer accept any further delivery item for the day; a new pickup time of day for the node-based logistics receptacle; a prompt shown on the display advising to check online for a new pickup time of day for the node-based logistics receptacle (e.g., where such a prompt may include a visually scannable code generated on the display and related to online available information on the new pickup time or other changed operational timing related to that node-based logistics receptacle).

(299) In a further system embodiment, similar to system embodiments described above related to dynamic tuning operations for a node-based logistics receptacle (such as receptacle **150a**), an exemplary system may focus on changes to when the bridge node transfers event information to the server (as opposed to when the bridge node retrieves or uploads the event information from the wireless accessory sensor node or in combination with when the bridge node retrieves or uploads

the event information from the wireless accessory sensor node). For example, an embodiment of such a system for dynamically tuning operation of a node-based logistics receptacle (such as receptacle **150**, **150a** having storage receptacle components including at least an entrance opening **155/156** for receiving a delivery item, a temporary storage area **205** for temporarily maintaining the delivery item once received, and a retrieval door **160** providing selective access to the delivery item within the temporary storage area). The exemplary system includes at least a backend server **100**; a bridge node (e.g., bridge node **16200**), and a wireless accessory sensor node (e.g., sensor node **210**, **1002**, **1002a**, **1002b**). In this embodiment, the system's wireless accessory sensor node is disposed on the node-based logistics receptacle and has multiple sensors (e.g., sensors **1020a**, **1020b**, **440a-450e**) that collectively monitor the storage receptacle components of the node-based logistics receptacle, wherein each of the sensors is operative to generate sensor data reflecting one or more interactions with one or more of the storage receptacle components of the node-based logistics receptacle over a recording time period (e.g., as defined in exemplary timing data **1605**). The system's bridge node is disposed on the node-based logistics receptacle and programmatically operative to retrieve event information from the wireless accessory sensor node at a predetermined time of day (e.g., as defined in exemplary timing data **1605**) and transmit the retrieved event information to the backend server (where the retrieved event information represents at least the sensor data generated over the recording time period. The system's backend server is programmatically operative, in response to receiving the retrieved event information, to transmit a tuned time parameter message to the bridge node. Such a tuned time parameter message causes the system's bridge node to alter a predetermined time of day when the bridge node transmits future retrieved event information to the backend server. In more detail, the tuned time parameter message may cause the bridge node to alter a cutoff time of day when the node-based logistics receptacle is designated to no longer accept any further delivery item for the day as the predetermined time of day when the bridge node transmits the future retrieved event information to the backend server; and/or alter a cutoff time of day when the node-based logistics receptacle is designated to no longer accept any further delivery item for the day and when the bridge node transmits future retrieved event information to the backend server. Further still, the backend server may be operative to transmit the tuned time parameter message by being more specifically operative to (i) determine whether an adjustment of the cutoff time of day for the node-based logistics receptacle is warranted based upon the retrieved event information received by the backend server; (ii) generate the tuned time parameter message when the adjustment of the cutoff time of day for the node-based logistics receptacle is determined to be warranted based upon the retrieved event information received by the backend server; and (iii) transmit the tuned time parameter message to the bridge node causing the bridge node to at least alter when the bridge node transmits future retrieved event information to the backend server.

(300) Similar to the system embodiments described above, this system embodiment relating to dynamic tuning operations for a node-based logistics receptacle may also inform others about adjustments related to the node-based logistics receptacle in various ways, such as via an online portal or via an integral display on the receptacle itself as described above relative to FIGS. **17A**, **17B** and **18**.

(301) And also similar to the system embodiments described above, this system embodiment may also involve sending a message to the backend server at predetermined time of day indicating no interactions detected. For example, a further system embodiment to that described above may have the system's bridge node **16200** being further programmatically operative to transmit a first confirmation status message to the backend server **100**, where the first confirmation status message represents a type of confirmation that the bridge node **16200** is at least operative to determine no further event information is available to upload from the system's wireless accessory sensor node during a subsequent reporting time period and where transmission of such a confirmation status message by bridge node **16200** may occur at a designated or dynamically updated time of day.

(302) Likewise, the system's bridge node **16200** in another embodiment may be further programmatically operative to transmit a second confirmation status message to the backend server **100**, where the second confirmation status message represents another type of confirmation that the bridge node **16200** is at least operative to receive a signal from the wireless accessory sensor node during the subsequent reporting time period. In more detail, the signals from the wireless accessory sensor node may indicate no further interactions with the storage receptacle components of the node-based logistics receptacle **150a** over the subsequent reporting time period and where the bridge node may transmit the second confirmation status message to the backend server at a designated time of day.

(303) Server Setup, Management & Training of a Network of Node-Based Connected Logistics Receptacles

(304) While various embodiments described above focus on dynamic tuning operations for a particular node-based logistics receptacle based upon event information reported by that node-based logistics receptacle, additional embodiments may employ a different type of dynamic tuning operation. As explained in more detail below, such additional embodiments include a backend server that centrally manages multiple node-based logistics receptacles. In doing so, the backend server generally configures each one, and may dynamically tune the operation of each based upon a more robust set of information being reported by multiple different node-based logistics receptacles. Such information is used by the backend server to better learn and adapt to interactions and events occurring across a network of node-based logistics receptacles. In this way, these additional embodiments focus on a different type of centralized network setup, management, and dynamic tuning that may be applied to a fleet of connected node-based logistics receptacles beyond that addressed in embodiments described above.

(305) FIGS. **20A-20H** are a series of diagrams of an exemplary centrally managed system for tuning multiple enhanced node-based logistics receptacles involving a backend server in accordance with an embodiment of the invention. Referring now to FIG. **20A**, backend server **100** is shown as being operative to be in communication with various exemplary enhanced node-based logistics receptacles (e.g., receptacles **150a-150c**) via network **105** as well as exemplary logistics asset **700a**. As explained above, backend server maintains an exemplary management profile (e.g., management profile **835**) related to each of the enhanced node-based logistics receptacles.

(306) A first of the enhanced node-based logistics receptacles **150a** is operative to communicate with the backend server **100** and includes multiple monitored receptacle components, a first bridge node (e.g., similar to bridge node **200**, **16200**), and a first wireless accessory sensor node (e.g., similar to sensor node **210**, **1002**, **1002a**, **1002b**). The first wireless accessory sensor node is coupled to or otherwise equipped with a group of first sensors that collectively monitor one or more interactions with respective ones of the monitored receptacle components of first receptacle **150a** over a first recording time period. The first bridge node (as part of receptacle **150a**) is operative to retrieve first event information (information related to sensor data generated by the first sensors) from the first wireless accessory sensor node and transmit the retrieved first event information at a first upload time to the backed server **100**.

(307) A second of the node-based logistics receptacles **150b** is operative to communicate with the backend server **100** and includes multiple of its own monitored receptacle components, a second bridge node (e.g., similar to bridge node **200**, **16200**), and a second wireless accessory sensor node (e.g., similar to sensor node **210**, **1002**, **1002a**, **1002b**). The second wireless accessory sensor node is coupled to or otherwise equipped with a group of second sensors that collectively monitor one or more interactions with respective ones of the monitored receptacle components of receptacle **150b** over a second recording time period. The second bridge node (as part of receptacle **150b**) is operative to retrieve second event information from the second wireless accessory sensor node, where the second event information is related to sensor data generated by the second plurality of sensors. The second bridge node is then operative to transmit the retrieved second event

information at a second upload time to the backend server.

(308) As illustrated in FIG. 20A, backend server **100** is programmatically configured (e.g., via executable code, such as an embodiment of exemplary server control and management code **825**) to be operative to transmit a first setup message **2000a** to the first bridge node within receptacle **150a**. In general, the first setup message **2000a** presents a command or instructions that initiate or otherwise cause a configuring task related to operation of the first bridge node to be undertaken by the first bridge node. Such a configuring task, in this embodiment shown in FIG. 20A, relates to at least the first recording time period for the first wireless accessory sensor node and the first upload time for the first bridge node to transmit the retrieved first event information to the backend server.

(309) In FIG. 20B, backend server **100** is programmatically configured (e.g., via executable code, such as an embodiment of exemplary server control and management code **825**) to be operative to transmit a second setup message **2000b** to the second bridge node within receptacle **150b**. As with the first setup message **2000a**, the second setup message **2000b** presents a command or instructions that initiate or otherwise cause a configuring task related to operation of the second bridge node to be undertaken by the second bridge node. Such a configuring task, in this embodiment shown in FIG. 20B, relates to at least the second recording time period for the second wireless accessory sensor node and the second upload time for the second bridge node to transmit the retrieved second event information to the backend server.

(310) In further embodiments involving more specific implementations of such setup messages, the first setup message may, for example, configure operation of the first bridge node related to (a) the first recording time period for the first wireless accessory sensor node, (b) a first predetermined time for retrieving the first event information, and (c) the first upload time for transmitting the retrieved first event information to the backend server. Further still, another example may also have the second setup message configuring operation of the second bridge node related to (d) the second recording time period for the second wireless accessory sensor node, (e) a second predetermined time for retrieving the second event information, and (f) the second upload time for transmitting the retrieved second event information to the backend server.

(311) Similar to that described above, those skilled in the art will appreciate that the respective wireless accessory sensor node in a particular receptacle (e.g., the first receptacle **150a** and the second receptacle **150b**) may operate by monitoring interactions with its sensors. Such a first/second wireless accessory sensor node is then operative to (a) detect, within its recording time period and using one or more of its sensors, a change in relevant monitored receptacle components, where the detected change corresponds to interactions with the respective monitored receptacle components; (b) record sensor data generated by its sensors (including timestamped information reflecting the detected change); and (c) broadcast an updated advertising signal by that sensor node where the updated advertising signal has a data available flag set indicating that one of the wireless accessory sensor nodes has event information available for upload by the bridge node in that particular receptacle (where such event information includes at least the timestamped information).

(312) As shown in FIGS. 20C and 20D, backend server **100** is shown operative to receive the retrieved first event information **1500a** from the first bridge node and the retrieved second event information **1500b** from the second bridge node, respectively. Such retrieved event information from each of receptacles **150a** and **150b** represents changes in state (e.g., interactions with particular monitored components) of those receptacles **150a**, **150b**.

(313) Once the retrieved first event information **1500a** and the retrieved second event information **1500b** are received by backend server **100**, backend server **100** is further operative to compare the retrieved first event information **1500a** with information in the management profile (e.g., information in exemplary management profile **835** maintained on server **100** that relates to receptacle **150a**) and compare the retrieved second event information **1500b** with the management profile (e.g., other information in exemplary management profile **835** maintained on server **100** that relates to receptacle **150b**). Backend server **100** then revises, changes, or otherwise updated the

management profile in a type of learning task based upon the comparison of the retrieved first event information **1500a** with information in the management profile **835** and the comparison of the retrieved second event information **1500b** with information in the management profile **835**. (314) In such an embodiment, exemplary management profile **835** may maintain different types of information on each of the different managed node-based logistics receptacles and in different ways (e.g., as part of a single data structure as the profile, as part of a database as the profile with differing records for each of the different receptacles, as part of distinctly stored data structures collectively referred to as the profile, and the like). In one example, the management profile may be implemented with a prior component engagement history for each of the enhanced node-based logistics receptacles (e.g., where the prior component engagement history for each of the enhanced node-based logistics receptacles includes a separate prior history of interactions with the monitored receptacle components for each of the receptacles). In another example, the management profile may be implemented with a server-tracked historic use pattern for each of the enhanced node-based logistics receptacles (e.g., a pattern of engagement events (such as delivery or pickup events) related to each of the receptacles; a threshold occupancy pattern profile identifying a frequency of reaching a threshold occupied level within each of the receptacles (or a particular threshold occupied level for particular receptacles where they may be different for different receptacles); an overload pattern profile identifying a frequency of reaching an overload condition for each of the receptacles (or a particular overload pattern/condition for particular receptacles where they may be different for different receptacles). In yet another example, the management profile may be implemented with a logistics asset profile related to logistics assets assigned to service each of the particular receptacles. In more detail, the logistics asset profile may identify a first logistics asset assigned to service one receptacle and identify a second logistics asset assigned to service another of the receptacles. In some situations, the logistics asset profile may identify a first logistics asset commonly assigned to service some or all of the receptacles.

(315) FIGS. **20E** and **20F** illustrate how backend server **100** responds to such “learning” based upon information from multiple node-based logistics receptacle by generating and transmitting an adjustment message to at least one of the bridge nodes. For example, FIG. **20E** shows backend server **100** being operative to transmit an adjustment message **2005a** to the first bridge node in receptacle **150a**, where that adjustment message **2005a** is based upon the revised management profile **835**. Such an adjustment message **2005a** causes or otherwise initiates the first bridge node to undertake a first timing change to operation of the first bridge node. For example, in such an embodiment, the first timing change may cause the first bridge node to instruct the first wireless accessory sensor node to update the first recording time period over which the sensors generate the sensor data related to the first event information. In another example, the first timing change may involve an update to a first predetermined time on when the first bridge node retrieves the first event information upon implementing the update. In yet another example, the first timing change may involve an update to the first upload time on when the first bridge node is operative to transmit the retrieved first event information to the backend server upon implementing the update. Thus, a reporting receptacle may be tuned and managed in such a manner by backend server, as well as non-reporting receptacles, in such an embodiment.

(316) In some embodiments, further adjustments may be made to other receptacles being managed by backend server—e.g., via an additional adjustment message **2005b** transmitted by backend server **100** to another bridge node (such as the second bridge node disposed in and operating as part of node-based logistics receptacle **150b** or a bridge node disposed in and operating as part of node-based logistics receptacle **150c**). For example, an embodiment may have the additional adjustment message **2005b** generated based upon the revised management profile. Such an additional adjustment message **2005b** initiates a second timing change to operation of the second bridge node (e.g., causes the second bridge node to undertake a second timing change to operation of the second bridge node). Such a second timing change may, for example, cause the second bridge node to

instruct the second wireless accessory sensor node to update the second recording time period over which the second plurality of sensors generate the sensor data related to the second event information; update a second predetermined time on when the second bridge node is operative to retrieve the second event information upon implementing the update; and/or update the second upload time on when the second bridge node is operative to transmit the retrieved second event information to the backend server upon implementing the update.

(317) FIGS. **20G** and **20H** illustrate how backend server **100** may further respond by initiating a dispatched logistics operation. For example, FIG. **20G** shows backend server **100** being further programmatically operative, after revising the management profile **835** in this embodiment, to initiate a dispatched logistics operation related to at least one of the enhanced node-based logistics receptacles based upon the revised management profile. As shown in FIG. **20G**, backend server **100** generates and transmits an exemplary dispatch message **2010** and transmits it through network **105** to a logistics asset **700a** for the dispatched logistics operation. In some embodiments, such as that shown in FIG. **20H**, initiation of the dispatched logistics operation may, for example, be initiated by backend server **100** via dispatch message **2015** to an alternative logistics asset than previously assigned to the at least one of the enhanced node-based logistics receptacles (e.g., to logistics asset **700b**, rather than to previously assigned logistics asset **700a**). Further still, an embodiment may have such a dispatched logistics operation initiated by the backend server **100** at an alternative time than previously scheduled for a receptacle.

(318) In some embodiments, backend server **100** may implement an even more robust type of “learning” using the reported event information from different node-based logistics receptacles as well as environmental context data related to particular receptacle(s). Such embodiments may have backend server **100** revising the management profile with consideration of environmental context data (e.g., exemplary context data **855**, information maintained in exemplary CLR context database **850**, and the like) related to at least one of the node-based logistics receptacles being tuned by the backend server. For example, an embodiment may have backend server **100** being programmatically configured to be operative to revise management profile **835** based upon (a) a comparison of the retrieved first event information with the management profile; (b) a comparison of the retrieved second event information with the management profile; and (c) a relevant portion of the environmental context data (e.g., exemplary context data **855**, information maintained in exemplary CLR context database **850**, context data maintained in database **180** and accessible to server **100**) related to at least the first of the enhanced node-based logistics receptacles. In yet another example, another embodiment may have backend server **100** being programmatically configured to be operative to revise management profile **835** based upon (a) a comparison of the retrieved first event information with the management profile **835**; (b) the comparison of the retrieved second event information with the management profile; (c) a relevant portion of the environmental context data (e.g., exemplary context data **855**, information maintained in exemplary CLR context database **850**, context data maintained in database **180** and accessible to server **100**) related to the first node-based logistics receptacle (e.g., receptacle **150a**); and (d) another relevant portion of the environmental context data related to the second node-based logistics receptacle (e.g., receptacle **150b**). Those skilled in the art will appreciate that consideration of context data related to particular node-based logistics receptacles as the backend server **100** compares interactions with different node-based logistics receptacles to engagement histories, use patterns, and other profiled historic usage information on those receptacles provides an even more detailed way of backend server **100** learning and adjusting to how such node-based logistics receptacles may be managed and adjusted to better suit the usage environment and operating situation for the different node-based logistics receptacles.

(319) In another example, an embodiment of an exemplary centrally managed system for tuning a different enhanced node-based logistics receptacles that revises a management profile using reported event information from multiple receptacles as well as environmental context data about

the physical operating environment relative to such receptacles may include a backend server (such as backend server **100**) and multiple node-enabled logistics receptacles (such as exemplary receptacles **150a** and **150b**). The system's backend server maintains at least a management profile (e.g., exemplary management profile **835**) related to each of the enhanced node-based logistics receptacles and environmental context data about a physical operating environment of each of the enhanced node-based logistics receptacles (e.g., exemplary context data **855**, information maintained in exemplary CLR context database **850**, context data maintained in database **180** and accessible to server **100**).

(320) The system's first enhanced node-based logistics receptacle (e.g., receptacle **150a**) is operative to communicate with the backend server **100** and has at least multiple monitored receptacle components (e.g., entrance opening, temporary storage area, selectively accessible retrieval door), a first wireless accessory sensor node having multiple sensors that collectively monitor one or more interactions with respective ones of the monitored receptacle components of receptacle **150a** over a first recording time period, and a first bridge node operative to retrieve first event information from the first wireless accessory sensor node and transmit the retrieved first event information at a first upload time to the backed server. The first event information is related to sensor data generated by the sensors coupled to the first wireless accessory sensor node (e.g., light data, motion data, image data, status data, weight data, force data, and the like as exemplary sensor data).

(321) The system's second enhanced node-based logistics receptacles (e.g., receptacle **150b**) is also operative to communicate with the backend server **100** and has at least multiple monitored receptacle components (e.g., entrance opening, temporary storage area, selectively accessible retrieval door), a second wireless accessory sensor node having multiple sensors that collectively monitor one or more interactions with respective ones of the monitored receptacle components of receptacle **150b** over a second recording time period, and a second bridge node operative to retrieve second event information from the second wireless accessory sensor node and transmit the retrieved second event information at a second upload time to the backed server. The second event information is related to sensor data generated by the sensors coupled to the second wireless accessory sensor node (e.g., light data, motion data, image data, status data, weight data, force data, and the like as exemplary sensor data).

(322) The system's backend server in this particular embodiment is programmatically configured to be operative to transmit a first setup message to the first bridge node and a second setup message to the second bridge node. In this example, the first setup message functions to configure operation of the first bridge node related to at least (a) the first recording time period for the first wireless accessory sensor node and (b) the first upload time for transmitting the retrieved first event information to the backend server. Likewise, the second setup message functions to configure operation of the second bridge node related to at least (c) the second recording time period for the second wireless accessory sensor node and (d) the second upload time for transmitting the retrieved second event information to the backend server. The system's backend server is further operative to receive the retrieved first event information from the first bridge node and the retrieved second event information from the second bridge node; and then compare the retrieved first event information with the management profile and compare the retrieved second event information with the management profile.

(323) Notably, the system's backend server in this particular embodiment is also programmatically configured to revise the management profile (e.g., exemplary management profile **835**) based upon (1) the comparison of the retrieved first event information with the management profile, (2) the comparison of the retrieved second event information with the management profile, (3) a first portion of the environmental context data related to the first of the enhanced node-based logistics receptacles, and (4) a second portion of the environmental context data related to the second of the enhanced node-based logistics receptacles.

(324) The backend server in this embodiment then transmits at least an adjustment message to the first bridge node, where such an adjustment message is based upon the revised management profile and such an adjustment message initiates a first timing change to operation of at least the first bridge node (e.g., an update to the first upload time on when the first bridge node is operative to transmit the retrieved first event information to the backend server upon implementing the update). In other examples, the backend server may send an additional adjustment message to the second bridge node where such an additional adjustment message is based upon the revised management profile initiates a second timing change to operation of the second bridge node (e.g., an update to the second upload time on when the second bridge node is operative to transmit the retrieved second event information to the backend server upon implementing the update).

(325) The environmental context data (e.g., data **855**) used in this particular embodiment, may be implemented with for example, traffic data related to the location of each of the enhanced node-based logistics receptacles (e.g., exemplary traffic data **865**, **180b**); weather data related to the location of each of the enhanced node-based logistics receptacles (e.g., exemplary weather data **870**, **180c**); fuel cost data related to the location of each of the enhanced node-based logistics receptacles (e.g., kept as part of data **855**); crime data related to the location of each of the enhanced node-based logistics receptacles (e.g., exemplary crime data **860**, **180a**); logistics asset staffing data related to the location of each of the enhanced node-based logistics receptacles (e.g., exemplary logistics asset staffing data **875**, **180d**); logistics asset cost data; and other third party context data. As previously explained, such environmental context data may be kept on backend server **100** as exemplary context data **855** and maintained in CLR context database **850** or database **180**. Such environmental context data may provide geographic crime data **860** (e.g., on-going crime scenes, crime patterns, different types of crimes in particular areas, and the like), traffic data **865** (e.g., current traffic, traffic patterns, construction locations, and the like), weather data **870** (e.g., current weather happening in particular areas, weather forecasts, historic weather events for areas, and the like), logistics asset staffing data **875** (e.g., couriers deployed in delivery vehicles as mobile logistics assets, shift change information on logistics personnel, and the like), logistics asset cost data **880** (e.g., fuel costs, and the like), as well as other third-party generated data **885** that relates to the operating environment or operations of any of the connected logistics receptacles managed by backend server **100**. Further still, those skilled in the art will appreciate that the environmental context data about the physical operating environment of each of the enhanced node-based logistics receptacles may be implemented with information about an anticipated operating environment for at least one of the enhanced node-based logistics receptacles, where that receptacle is anticipated to be moved to a second location corresponding to the anticipated operating environment for at least one of the enhanced node-based logistics receptacles.

(326) Those skilled in the art will appreciate that further examples of such a system may implement the server-maintained management profile in a manner similar to that described above (e.g., as with exemplary management profile **835** that may include prior component engagement histories for the different managed receptacles, historic use patterns for the different managed receptacles, information on logistics resources assigned to the different managed receptacles, thresholds for different receptacles, and the like). Those skilled in the art will appreciate that further examples of such a system may have backend server being responsive to cause or otherwise initiate/alter logistics operations for the managed node-based logistics receptacles similar to that described in other embodiments above. Those skilled in the art will also appreciate that further examples of such a system may have backend server setting up each of the managed node-based logistics receptacles in similar ways to that described in other embodiments above.

(327) Enhanced Pickup Processing

(328) Various embodiments described above focus on ways for a backend server to “tune” or otherwise modify operations of an exemplary connected logistics receptacle. Further embodiments described below relate to enhanced methods for multi-domain management of such an exemplary

connected node-based logistics receptacle in response to a dispatched logistics operation involving the node-based logistics receptacle and a mobile courier node. In general, embodiments may have an initiated dispatched logistics operation beginning where a courier (e.g., a type of logistics asset) being deployed to service a particular logistics receptacle (e.g., exemplary receptacle **150**, **1000**, and the like). As part of such a logistics operation (e.g., a pickup operation), interactions with monitored components of the receptacle (such as opening of the retrieval door) may trigger a sensor coupled to the receptacle's wireless accessory sensor node. The receptacle's bridge node then reports a new event to the backend server if such an event is seen before the last drop-off time. Enhancing this further, the receptacle's bridge node may report chute interactions and/or interactions detected relative to the receptacle's temporary storage area. The courier's mobile or handheld node (a type of mobile bridge node with scanning capability) may record one or more barcode pickup scans on what is retrieved. Information on such interactions and pickup scans are each sent to the backend server by the receptacle's bridge node and the courier's node, respectively. The backend server in such an embodiment uses the chute/temporary storage interactions (knowing no further will be detected for what is being retrieved) and barcode pickup scans of each delivery item in the logistics receptacle (or compartment of the logistics receptacle) to adjust for pickup thresholds, reporting period, etc. for that particular logistics receptacle. Such an enhancement may extend and expand upon the backend server's ability to tuning for more specific conditions.

(329) FIGS. **13A-13B** collectively represent a flow diagram illustrating an exemplary method for multi-domain management of a node-based logistics receptacle (e.g., exemplary logistics receptacle **50**, **1000**, **1015**) in response to a dispatched logistics operation involving the node-based logistics receptacle and a mobile courier node in accordance with an embodiment of the invention. An embodiment of such an exemplary mobile courier node may be implemented similar to exemplary bridge node **200** as shown and explained relative to FIG. **3**, but programmatically configured via onboard program code (in place of CLR control and management code **315** and info/data **320-330**) to be operative to communicate with backend server **100** and include a sensor capable of capturing machine-readable references (such as scannable images of barcodes, QR codes, and the like visible on the outside of a delivery item) or textual information (such a textual information on a label on a delivery item).

(330) Referring now to FIG. **13A**, exemplary method **1300** is shown as a method for multi-domain management of a node-based logistics receptacle in response to a dispatched logistics operation involving the node-based logistics receptacle and a mobile courier node. As referenced in method **1300**, the node-based logistics receptacle (e.g., receptacle **150**) has a multiple storage receptacle components including at least an entrance opening (e.g., entrance opening **155**/entrance door **156**) for receiving one or more shipping items (e.g., package **170**), a temporary storage area (e.g., storage area **205**) for temporarily maintaining the shipping items once received, and a retrieval door (e.g., door **160**) providing selective access to the shipping items within the temporary storage area. The node-based logistics receptacle used in method **1300** further has a wireless accessory sensor node coupled to multiple sensors (e.g., exemplary wireless accessory sensor node **210**, **1002** operatively coupled to different sensors) disposed on the node-based logistics receptacle and a receptacle bridge node (e.g., exemplary bridge node **200**) disposed on the node-based logistics receptacle operative to communicate with a backend server (e.g., server **100**).

(331) At step **1305**, method **1300** begins by monitoring the retrieval door of the node-based logistics receptacle during the dispatched logistics operation for pickup retrieval door interactions using a first of the sensors coupled to the wireless accessory sensor node. At step **1310**, method **1300** proceeds to step **1315** when detecting a pickup retrieval door interaction with the retrieval door of the node-based logistics receptacle during the dispatched logistics operation. If no pickup retrieval door interaction is detected, method **1300** returns to step **1305** for continued monitoring.

(332) In more detail, an embodiment of method **1300** may implement step **1310** more specifically by detecting the retrieval door interaction using a sensor coupled to the wireless accessory sensor

node as a change in state of retrieval door **160** based upon sensor data generated by a sensor monitoring door **160** (e.g., where the wireless accessory sensor node is implemented by exemplary accessible retrieval door sensor node **240**, which has at least one sensor (such as a motion sensor, orientation status sensor, accelerometer, magnetic sensor, and the like) that monitors for a change in the state of door **160**). Step **1310** then has the wireless accessory sensor node recording timestamped information and broadcasting an updated advertising signal. The timing information recorded in this implementation of step **1310** reflects timing associated with or corresponding to the retrieval door interaction as the detected change in state of the retrieval door. The broadcasted updated advertising signal has a data available flag set within the updated advertising signal, where that data available flag indicating the wireless accessory sensor node has the initial pickup event information available for upload by the receptacle bridge node. Such initial pickup event information includes at least the timestamped information reflecting the detected change in state of the retrieval door.

(333) At step **1315**, method **1300** has the receptacle bridge node uploading initial pickup event information from the wireless accessory sensor node. Such initial pickup event information corresponds to at least timing associated with the pickup retrieval door interaction as detected by the first of the sensors in step **1310**.

(334) Next, at step **1320**, the receptacle bridge node determines whether the pickup retrieval door interaction occurred prior to a predetermined drop off time setting for the node-based logistics receptacle based upon the initial pickup event information. If so, method **1300** proceeds from step **1320** to step **1325**. Otherwise, method **1300** returns to step **1305**.

(335) At step **1325**, method **1300** proceeds with the receptacle bridge node transmitting the initial event information to the backend server. Then, at step **1330**, method **1300** proceeds with the receptacle bridge node uploading engagement event information from the wireless accessory sensor node. The engagement event information uploaded corresponding to one or more interactions with at least one of (a) the entrance opening as detected by a second of the sensors coupled to the wireless accessory sensor node, and (b) the temporary storage area as detected by a third of the sensors coupled to the wireless accessory sensor node.

(336) In more detail, an embodiment of method **1300** may implement step **1330** with more specificity to upload the engagement event information by (i) first detecting (using the second of the sensors coupled to the wireless accessory sensor node) the one or more interactions with the entrance opening; (ii) recording, by the wireless accessory sensor node, entrance opening timestamped information reflecting each of the detected interactions with the entrance opening; (iii) detecting (using the third of the sensors coupled to the wireless accessory sensor node) the one or more interactions with the temporary storage area; (iv) recording, by the wireless accessory sensor node, storage area timestamped information reflecting each of the detected one or more interactions with the temporary storage area; (v) broadcasting, by the wireless accessory sensor node, an updated advertising signal having a data available flag set within the updated advertising signal, the data available flag indicating the wireless accessory sensor node has the engagement event information available for upload by the receptacle bridge node; and (vi) uploading, by the receptacle bridge node, the engagement event information from the wireless accessory sensor node in response to the receptacle bridge node detecting the data available flag set within the updated advertising signal, the engagement event information including at least the entrance opening timestamped information and the storage area timestamped information. In such a further embodiment of step **1330**, the one or more interactions with the entrance opening/temporary storage area may be interactions that occur prior to the predetermined drop off time setting for the node-based logistics receptacle.

(337) At step **1335**, method **1300** proceeds with the receptacle bridge node transmitting the engagement event information to the backend server. After step **1335**, method **1300** proceeds through transition A to step **1340** on FIG. **13B**, where method **1300** continues with the mobile

courier node transmitting pickup scan information to the backend server. Such pickup scan information represents the one or more shipping items as retrieved from the temporary storage area as part of the dispatched logistics operation. For example, the mobile courier node may be used by logistics personnel (e.g., courier, gig worker, and the like) operating the exemplary logistics asset (e.g., asset **700a**) that has been dispatched for the dispatched logistics operation. A further embodiment of method **1300** may implement step **1340** with more specificity with the mobile courier node generating the pickup scan information as barcode information representing the one or more shipping items as retrieved from the temporary storage area as part of the dispatched logistics operation; and then transmitting the pickup scan information to the backend server. In yet another example, step **1340** may be implemented with the mobile courier node the pickup scan information as wirelessly broadcast information detected from the one or more shipping items as retrieved from the temporary storage area as part of the dispatched logistics operation; and transmitting, by the mobile courier node, the pickup scan information to the backend server.

(338) At step **1345**, method **1300** proceeds by having the backend server generating an adjustment message for the receptacle bridge node in the node-based logistics receptacle based upon an assessment of the engagement event information and the pickup scan information. Such an adjustment message acts as a type of remote command for the receptacle bridge node that initiates an operational change for the node-based logistics receptacle. In more detail, an embodiment of method **1300** may implement step **1345** with the backend server **100** updating a server-maintained profile identifying a pattern of use of the node-based logistics receptacle (e.g., information kept in exemplary management profile **835** in memory of backend server **100**) with the engagement event information and with the pickup scan information; determining the updated server-maintained profile indicates a threshold change in the pattern of use of the node-based logistics receptacle; and then generating the adjustment message for the receptacle bridge node in the node-based logistics receptacle based upon the updated server-maintained profile. In such a further embodiment of step **1345**, the threshold change in the pattern of use of the node-based logistics receptacle may, for example, be a threshold change in a frequency of reaching a pickup threshold level for the node-based logistics receptacle or a threshold change in a historic average content amount for the node-based logistics receptacle (where the historic average content amount may, for example, relate to prior pickup scan information as reported to the backend server and the pickup scan information transmitted to the backend server as part of the dispatched logistics operation).

(339) At step **1350**, method **1300** proceeds with the backend server transmitting the adjustment message to the receptacle bridge node in the node-based logistics receptacle, and then step **1355** has the receptacle bridge node responsively initiating the operational change related to the adjustment message in response to receipt of the adjustment message.

(340) In further embodiments of method **1300**, such an operational change may involve altering pickup threshold values and/or operational timing adjustments. For example, an embodiment of method **1300** may implement initiating the operational change for the node-based logistics receptacle in step **1355** with the receptacle bridge node altering a pickup threshold value for the node-based logistics receptacle stored by the receptacle bridge node. In more detail, this may also involve the further steps of detecting, using one or more of the sensors coupled to the wireless accessory sensor node, one or more changes in a subsequent state of the storage receptacle components; having the receptacle bridge node upload subsequent event information from the wireless accessory sensor node (where the subsequent event information is related to the detected changes in the subsequent state of the storage receptacle components); having the receptacle bridge node comparing the subsequent event information and the pickup threshold value to determine a pickup request condition exists; and transmitting, by the receptacle bridge node, a pickup request message to the backend server, the pickup request message reporting the subsequent event information to the backend server and indicating the pickup request condition exists.

(341) In another example, a further embodiment of method **1300** may implement initiating the

operational change for the node-based logistics receptacle in step **1355** with the receptacle bridge node altering an operational timing value for the node-based logistics receptacle stored by the receptacle bridge node. Such an operational timing value may be implemented, for example, as the predetermined drop off time setting for the node-based logistics receptacle; a predetermined time value for when the receptacle bridge node uploads the engagement event information; a predetermined time value for when the receptacle bridge node transmits the engagement event information to the backend server; a predetermined recording time period during which the wireless accessory sensor node is operative to monitor the entrance opening; and/or a predetermined recording time period during which the wireless accessory sensor node is operative to monitor the each of the entrance opening, the temporary storage, and the retrieval door of the node-based logistics receptacle.

(342) In some embodiments, the engagement event information uploaded as part of step **1325** may be more limited in that such information corresponds to what is referenced as chute event information. Such chute event information relates to interactions as detected by sensors coupled to the wireless accessory sensor node that monitor the entrance opening structure for the logistics receptacle (such as entrance door **156**, entrance opening **155**, the variations of such structure shown and described relative to FIG. 5, and the like) as opposed to interactions detected relative to what is then further received in the temporary storage area of the receptacle.

(343) Relative to such a further embodiment, FIGS. **14A** and **14B** collectively are a flow diagram illustrating another exemplary method **1400** for multi-domain management of a node-based logistics receptacle in response to a dispatched logistics operation involving the node-based logistics receptacle and a mobile courier node in accordance with an embodiment of the invention.

(344) Referring now to FIG. **14A**, exemplary method **1400** is shown as a method for multi-domain management of a node-based logistics receptacle in response to a dispatched logistics operation involving the node-based logistics receptacle and a mobile courier node. Similar to that with method **1300** and as referenced in method **1400**, the node-based logistics receptacle (e.g., receptacle **150**) has a multiple storage receptacle components including at least an entrance opening (e.g., entrance opening **155**/entrance door **156**) for receiving one or more shipping items (e.g., package **170**), a temporary storage area (e.g., storage area **205**) for temporarily maintaining the shipping items once received, and a retrieval door (e.g., door **160**) providing selective access to the shipping items within the temporary storage area. The node-based logistics receptacle used in method **1400** further has a wireless accessory sensor node coupled to multiple sensors (e.g., exemplary wireless accessory sensor node **210**, **1002** operatively coupled to different sensors) disposed on the node-based logistics receptacle and a receptacle bridge node (e.g., exemplary bridge node **200**) disposed on the node-based logistics receptacle operative to communicate with a backend server (e.g., server **100**).

(345) Exemplary method **1400** begins at step **1405** where it can be seen in FIG. **14A**, steps **1405-1425** of exemplary method **1400** are the same as steps **1305-1325** of method **1300**. At step **1430**, method **1400** proceeds with the receptacle bridge node uploading chute event information from the wireless accessory sensor node where such chute event information uploaded corresponds to one or more interactions with the entrance opening as detected by a second of the sensors coupled to the wireless accessory sensor node.

(346) In more detail, an embodiment of method **1400** may implement step **1430** with more specificity to upload the chute event information by (i) detecting (using the second of the sensors coupled to the wireless accessory sensor node) the one or more interactions with the entrance opening; (ii) having the wireless accessory sensor node recording timestamped information reflecting each of the detected interactions with the entrance opening (where such timestamped information reflects a detected change in state of the retrieval door as indicated by the detected one or more interactions with the entrance opening); (iii) having the wireless accessory sensor node broadcasting an updated advertising signal having a data available flag set within the updated

advertising signal (where the data available flag indicates the wireless accessory sensor node has the chute event information available for upload by the receptacle bridge node); and (iv) having the receptacle's bridge node uploading the chute event information from the wireless accessory sensor node in response to the receptacle bridge node detecting the data available flag set within the updated advertising signal (where the chute event information includes at least the timestamped information). In such a further embodiment of step **1430**, the one or more interactions with the entrance opening may be interactions that occur prior to the predetermined drop off time setting for the node-based logistics receptacle.

(347) At step **1435**, method **1400** proceeds with the receptacle bridge node transmitting the chute event information to the backend server. After step **1435**, method **1400** proceeds through transition A to step **1440** on FIG. **14B**, where method **1400** continues with the mobile courier node transmitting pickup scan information to the backend server (similar to that explained in step **1340** on FIG. **13B**). Such pickup scan information represents the one or more shipping items as retrieved from the temporary storage area as part of the dispatched logistics operation. For example, the mobile courier node may be used by logistics personnel (e.g., courier, gig worker, and the like) operating the exemplary logistics asset (e.g., asset **700a**) that has been dispatched for the dispatched logistics operation. A further embodiment of method **1400** may implement step **1440** with more specificity with the mobile courier node generating the pickup scan information as barcode information representing the one or more shipping items as retrieved from the temporary storage area as part of the dispatched logistics operation; and then transmitting the pickup scan information to the backend server. In yet another example, step **1440** may be implemented with the mobile courier node the pickup scan information as wirelessly broadcast information detected from the one or more shipping items as retrieved from the temporary storage area as part of the dispatched logistics operation; and transmitting, by the mobile courier node, the pickup scan information to the backend server.

(348) At step **1445**, method **1400** proceeds by having the backend server generating an adjustment message for the receptacle bridge node in the node-based logistics receptacle based upon an assessment of the chute event information and the pickup scan information. Such an adjustment message acts as a type of remote command for the receptacle bridge node that initiates an operational change for the node-based logistics receptacle. In more detail, an embodiment of method **1400** may implement step **1445** with the backend server **100** updating a server-maintained profile identifying a pattern of use of the node-based logistics receptacle (e.g., information kept in exemplary management profile **835** in memory of backend server **100**) with the chute event information and with the pickup scan information; determining the updated server-maintained profile indicates a threshold change in the pattern of use of the node-based logistics receptacle; and generating the adjustment message for the receptacle bridge node in the node-based logistics receptacle based upon the updated server-maintained profile. In such a further embodiment of step **1445**, the threshold change in the pattern of use of the node-based logistics receptacle may, for example, be implemented as a threshold change in a frequency of reaching a pickup threshold level for the node-based logistics receptacle or a threshold change in a historic average content amount for the node-based logistics receptacle (where such an historic average content amount relates to prior pickup scan information as reported to the backend server **100** and the pickup scan information transmitted to the backend server **100** as part of the dispatched logistics operation).

(349) At step **1450**, method **1400** has the backend server transmitting the adjustment message to the receptacle bridge node in the node-based logistics receptacle, and then step **1455** has the receptacle bridge node responsively initiating the operational change related to the adjustment message in response to receipt of the adjustment message.

(350) In further embodiments of method **1400**, such an operational change may involve altering pickup threshold values and/or operational timing adjustments. For example, an embodiment of method **1400** may implement initiating the operational change for the node-based logistics

receptacle in step **1455** with the receptacle bridge node altering a pickup threshold value for the node-based logistics receptacle stored by the receptacle bridge node. In more detail, this may also involve the further steps of detecting, using one or more of the sensors coupled to the wireless accessory sensor node, one or more changes in a subsequent state of the storage receptacle components; having the receptacle bridge node upload subsequent event information from the wireless accessory sensor node (where the subsequent event information is related to the detected changes in the subsequent state of the storage receptacle components); having the receptacle bridge node comparing the subsequent event information and the pickup threshold value to determine a pickup request condition exists; and transmitting, by the receptacle bridge node, a pickup request message to the backend server, the pickup request message reporting the subsequent event information to the backend server and indicating the pickup request condition exists.

(351) In another example, a further embodiment of method **1400** may implement initiating the operational change for the node-based logistics receptacle in step **1455** with the receptacle bridge node altering an operational timing value for the node-based logistics receptacle stored by the receptacle bridge node. Such an operational timing value may be implemented, for example, as the predetermined drop off time setting for the node-based logistics receptacle; a predetermined time value for when the receptacle bridge node uploads the engagement event information; a predetermined time value for when the receptacle bridge node transmits the engagement event information to the backend server; a predetermined recording time period during which the wireless accessory sensor node is operative to monitor the entrance opening; and/or a predetermined recording time period during which the wireless accessory sensor node is operative to monitor the each of the entrance opening, the temporary storage, and the retrieval door of the node-based logistics receptacle.

(352) Dynamically Scheduled On-Road Logistics Assets

(353) Further embodiments may enhance how logistics asset(s) are involved and dynamically involved when initiating dispatched logistics operations to various enhanced connected node-base logistics receptacles by the backend server. In some embodiments, dynamically initiating such a dispatched logistics operation may be implemented based upon the event information reported to the backend server and server tracked location of the logistics asset, while in other embodiments may have the backend server selecting the logistics asset to use based upon the reported event information and a logistics asset usage profile related to costs and/or environmental impact for using different logistics assets (e.g., types) as well as the location of such logistics assets. FIGS. **21-25** provide illustrations of various related embodiments of systems that have its backend server being dynamically initiate dispatched logistics operations with particular logistics assets under a variety of conditions as explained in more detail below.

(354) FIG. **21** is a diagram illustrating exemplary connected logistics receptacle **105a** operating within a network and in communication with exemplary backend server **100** that is operable to dynamically initiate a dispatched logistics operation in accordance with an embodiment of the invention. Referring now to FIG. **21**, such a system is shown with backend server **100** (which maintains management profile **835** related to various storage receptacles) and node-based logistics receptacle **150a** having a storage receptacle, a bridge node, and at least one wireless accessory sensor node and sensors that monitor for a change in state of the storage receptacle. As shown in FIG. **21**, exemplary node-based logistics receptacle **150a** is positioned at location **2100** where customers may deposit or pickup packages (e.g., package **170**, **175**) using receptacle **150a**. Location **2100** is shown relative to a roadway network **2105**, on which one or more logistics assets (e.g., logistics asset **700a**) may be traveling.

(355) Those skilled in the art will appreciate that logistics asset **700a** may be equipped with a location tracking device (not shown), such as a GPS receiver, and be able to provide its location via location message **2110** sent to backend server **100**. In this manner, backend server **100** is aware of or otherwise has visibility to the current location of this particular logistics asset **700a**. Those

skilled in that art will further appreciate that backend server **100** may be similarly aware of and have visibility to the location of other logistics assets (a group of which may be available for dispatched logistics operations). Those skilled in the art will also understand that determining a location using location/tracking devices may be implemented using a variety of methodologies/devices other than GPS (or in addition to GPS), such as with wireless location services or techniques that use characteristics of Wi-Fi, cellular, or other access points to discover a device's location, triangulate a location, and the like.

(356) In operation and consistent with at least one of the embodiments explained above, the bridge node device in receptacle **150a** is able to transmit event information **1505** relative to detected changes in the state of the storage receptacle part of receptacle **150a**. For example, the wireless accessory sensor node in exemplary node-based logistics receptacle **150a** detects the change in state of the storage receptacle based upon sensor data generated by its sensor(s); records timestamped information reflecting the detected change in state of the storage receptacle; and broadcasts an updated advertising signal having a data available flag set within the updated advertising signal, where the data available flag indicates the wireless accessory sensor node has event information available for upload by the bridge node. The receptacle's bridge node detects the data available flag set within the updated advertising signal during a reporting period for the bridge node; retrieves the event information available for upload during the reporting period from the wireless accessory sensor node (where the event information includes at least the timestamped information reflecting the detected change in state of the storage receptacle); and transmits the retrieved event information **1505** to the backend server **100** at a reporting time during the reporting period.

(357) The system's backend server **100**, in response to receiving the retrieved event information **1505** from the bridge node in receptacle **150a**, is enhanced so as to be operative to identify location information related to a first logistics asset (e.g., based upon the location message **2110** sent by that logistics asset **700a**); compare the retrieved event information **1505** received from the bridge node in receptacle **150a** to that location information for the first logistics asset; and then dynamically initiate the dispatched logistics operation as a result of comparing the retrieved event information **1505** to the location information related to the first logistics asset (e.g., a current position of the logistics asset **700a** as tracked by the backend server **100**).

(358) In more detail, the system's backend server **100** may compare the retrieved event information **1505** to the location information related to logistics asset **700a** by being further operative to determine whether the location information related to logistics asset **700a** indicates logistics asset **700a** is within a predetermined range of the storage receptacle (e.g., the storage receptacle that is part of node-based logistics receptacle **150a**). For example, the exemplary location message **2110** may indicate that the current position of logistics asset **700a** is less than 2 miles from location **2100** of receptacle **150a**. Backend server **100** may use such information to determine that being less than 2 miles from location **2100** of receptacle **150a** means that logistics asset is within a predetermined ranges of receptacle **150a** for purposes of dynamically initiating the dispatched logistics operation. Thereafter, in such an example, the backend server **100** dynamically initiates the dispatched logistics operation when (and given that) the first logistics asset is within such a predetermined range of the storage receptacle (where such a range may vary for different receptacles and/or for different logistics assets being considered). However, if the backend server **100** determines the first logistics asset is not within the predetermined range of that storage receptacle (e.g., the location **2100** of receptacle **150a**), the backend server **100** may respond by initiating the dispatched logistics operation using an alternative logistics asset (such as logistics asset **700b**).

(359) In even more detail, the system's backend server **100** may compare the retrieved event information **1505** to the location information related to logistics asset **700a** by being further operative to determine whether the location information related to logistics asset **700a** indicates that logistics asset **700a** will pass within a predetermined range of the storage receptacle in

exemplary logistics receptacle **150a** prior to a predetermined response time. More specifically, an example may have the system's backend server **100** use the location information to determine if logistics asset is on a currently scheduled router (e.g., exemplary route **2200** in FIG. 22) and predict whether logistics asset **700a** will pass within that predetermined range of receptacle **150a** prior to a particular response time. Thereafter, in such an example, the backend server **100** dynamically initiates the dispatched logistics operation when (a) the logistics asset **700a** is located within the predetermined range of the storage receptacle on the currently scheduled route and (b) when the backend server **100** predicts the first logistics asset will pass within the predetermined range of the storage receptacle prior to the predetermined response time. However, if (a) or (b) are conditions that are not met, the backend server **100** may respond by initiating the dispatched logistics operation using an alternative logistics asset (such as logistics asset **700b**).

(360) An embodiment involving such dynamic initiation of the dispatched logistics operation may also consider context information (e.g., exemplary context data **855**, context data from CLR context database **850**, and/or context data from database **180** accessible by backend server **100**) related to the storage receptacle of interest. For example, the system's backend server **100** may dynamically initiate the dispatched logistics operation based upon a comparison of the retrieved event information **1505** received from the bridge node in receptacle **150a** to context information related to an operating environment of the storage receptacle that is part of receptacle **150a**. In more detail, this may be implemented with the system's backend server **100** being operative to access context information related to the storage receptacle in node-based logistics receptacle **150a** and then dynamically initiate the dispatched logistics operation based upon (a) comparing the retrieved event information **1505** received to the location information related to logistics asset **700a**, and (b) comparing the retrieved event information **1505** to the context information related to the storage receptacle in exemplary logistics receptacle **150a**. Such context information, for example, may include information related to the current location of the storage receptacle (e.g., location **2100** for receptacle **150a**), such as crime data, traffic data, and/or weather data. In another example, such context information may include at least one of logistics asset staffing data regarding the logistics asset **700a** and logistics asset cost data regarding that logistics asset **700a**.

(361) While an embodiment noted above considers the route of logistics asset **700a** (e.g., exemplary route **2200** shown in FIG. 22) and a particular response time when dynamically initiating a dispatched logistics operation, another embodiment may have backend server **100** operative to compare the retrieved event information **1505** to the location information related to logistics asset **700a** by being further operative to determine whether that location information indicates the logistics asset **700a** is on a currently scheduled route **2200** that will pass within a predetermined range of the storage receptacle in node-based logistics receptacle **150a**. If so, backend server **100** will send a dispatch message to logistics asset **700a** (or an agent of asset **700a**) to initiate the dispatched logistics operation. If not, backend server **100** may send a different dispatch message to an alternative logistics asset (e.g., logistics asset **700b** shown in FIG. 22) when the currently schedule route of the first logistics asset will pass within the predetermined range of the storage receptacle.

(362) Further still, an embodiment involving the dynamic initiation of the dispatched logistics operation may also consider context information (e.g., exemplary context data **855**, context data from CLR context database **850**, and/or context data from database **180** accessible by backend server **100**) related to a particular route of a logistics asset. For example, the system's backend server **100** may dynamically initiate the dispatched logistics operation based upon based upon a comparison of the retrieved event information **1505** to context information related to locations on a route for the logistics asset **700a** (e.g., exemplary route **2200**). Such context information may, for example, include at least one of crime data, traffic data, and weather data regarding the locations on the route for logistics asset **700a**. In more detail, this may be implemented with the system's backend server **100** being operative to access context information related to locations on a

scheduled route for logistics asset **700a** and then dynamically initiate the dispatched logistics operation as a result of (a) comparing the retrieved event information **1505** to the location information related to logistics asset **700a**, and (b) comparing the retrieved event information **1505** to the context information related to the locations on the scheduled route for logistics asset **700a**. (363) FIG. **23** is a diagram illustrating the exemplary connected logistics receptacle and exemplary backend server of FIG. **21** dynamically initiating a dispatched logistics operation involving an exemplary redirect dispatch message in accordance with an embodiment of the invention. Referring now to FIG. **23**, exemplary logistics asset **700a** may be on a prior scheduled logistics operation related to a node-based logistics receptacle positioned at location **2305**. As such, logistics asset **700a** is shown traversing roadway network **2105** towards location **2305**. However, the system's backend server **100** is shown as operative to dynamically initiate the dispatched logistics operation by being further operative to transmit an exemplary redirect dispatch message **2300** to logistics asset **700a** to redirect logistics asset **700a** from such a prior scheduled logistics operation involving a receptacle (e.g., pickup and/or delivery) at location **2305**. In more detail, redirect dispatch message **2300** may redirect logistics asset **700a** to location **2100** of receptacle **150a** (or in some embodiments, to a predicted location of receptacle **150a** when such an exemplary node-based logistics receptacle **150a** is implemented as a mobile structure having a mobile storage receptacle). (364) FIG. **24** is a diagram illustrating the exemplary connected logistics receptacle and exemplary backend server of FIG. **21** dynamically initiating a dispatched logistics operation involving an exemplary combination dispatch message that initiates servicing a reporting node-based logistics receptacle and initiates the dispatch of an exemplary sweep operation of at least one more non-reporting node-based logistics receptacle in accordance with an embodiment of the invention. Referring now to FIG. **24**, exemplary reporting node-enabled logistics receptacle **150a** is shown positioned at location **2100a** while other exemplary logistics receptacles **150b** and **150c** are respectively shown as positioned at locations **2100b** and **2100c**. In one example, an embodiment may have backend server **100** being operative to dynamically initiate the dispatched logistics operation by being further operative to transmit an exemplary combination dispatch message **2400** to logistics asset **700a** to (a) initiate servicing of the storage receptacle in logistics receptacle **150a** as the dispatched logistics operation and to (b) further dispatch a sweep operation to service an additional storage receptacle (such as one of logistics receptacles **150b**, **150c**). Such a sweep operation to service the additional storage receptacle may be dispatched without the backend server **100** receiving additional event information from either of the additional storage receptacles **150b**, **150c**. In another example, an embodiment may have backend server **100** being operative to dynamically initiate the dispatched logistics operation by transmitting a combination dispatch message **2400** to the logistics asset **700a** to (a) continue with a sweep operation of an additional storage receptacle (such as logistics receptacle **150b**, **150c**) and then to (b) service the storage receptacle in logistics receptacle **150a** upon completion of the sweep operation (which may be dispatched without the backend server receiving additional event information from the additional storage receptacle).

(365) In some embodiments involving dynamically initiating the dispatched logistics operation, the backend server **100** may consider a historic use pattern for the reporting node-based logistics receptacle. For example, an embodiment may have backend server **100** being operative to dynamically initiate the dispatched logistics operation based upon a comparison of the retrieved event information **1505** to a server-tracked historic use pattern for the storage receptacle maintained as part of management profile **835** on the backend server **100**. Such a historic use pattern may be implemented with information on prior detected engagements with the storage receptacle in logistics receptacle **105a** as updated by backend server **100** based on prior event information on that storage receptacle as received by backend server **100**; implemented as a profile identifying a pattern of use of the storage receptacle as maintained on the backend server; and/or a pattern of delivery/pickup events for the storage receptacle.

(366) In another example, backend server **100** may be further operative to dynamically initiate the dispatched logistics operation when the comparison of the retrieved event information **1505** to the server-tracked historic use pattern for the storage receptacle in reporting logistics receptacle **150a** indicates a likelihood for an additional deposit of a further delivery item to receptacle **150a** to be less than a threshold dispatch initiation value. In such a situation, when the likelihood of the additional deposit is lower than this threshold value, backend server **100** proceeds to initiate the dispatched logistics operation rather than wait (i.e., with server **100** intelligently learning and responding to the retrieved event information **1505** in a dynamic way that further considers this historic use pattern and likelihood of an additional deposit within a relevant period of time).

(367) In a more detailed example, the backend server **100** may be operative to dynamically initiate the dispatched logistics operation by being further operative to access a server-tracked historic use pattern for the storage receptacle in logistics receptacle **150a** (e.g., as part of information in exemplary management profile **835**) and compare the retrieved event information **1505** to the server-tracked historic use pattern for the storage receptacle. Backend server **100** then is operative to dynamically initiate the dispatched logistics operation as a result of (a) comparing the retrieved event information **1505** to the location information related to logistics asset **700a** (e.g., data indicating the location of asset **700a** as provided in location message **2110**), and (b) comparing the retrieved event information **1505** to the server-tracked historic use pattern for the storage receptacle as part of node-based logistics receptacle **150a**.

(368) In still another detailed example, the backend server **100** may be operative to dynamically initiate the dispatched logistics operation by being further operative to similarly access a server-tracked historic use pattern for the storage receptacle in logistics receptacle **150a** (e.g., as part of information in exemplary management profile **835**) and compare the retrieved event information **1505** to the server-tracked historic use pattern for the storage receptacle. Backend server **100**, in this example, may also be operative to determine whether a likelihood for an additionally detected deposit of a further delivery item (e.g., package **170**, **175**) within the storage receptacle is less than a threshold dispatch initiation value based upon the comparison of retrieved event information **1505** to the server-tracked historic use pattern for the storage receptacle. Thereafter, backend server **100** may dynamically initiate the dispatched logistics operation as a result of (a) comparing the retrieved event information **1505** to the location of logistics asset **700a** (e.g., data indicating the location of asset **700a** as provided in location message **2110**) and (b) when the likelihood for an additional deposit of a further delivery item detected within the storage receptacle in node-based logistics receptacle **150a** is determined to be less than the threshold dispatch initiation value.

(369) In a further embodiment, a system may be deployed that dynamically initiates a dispatched logistics operation based on historic use patterns kept as part of the management profile maintained by backend server **100** (rather than based on the location of a particular logistics asset). For example, such a system embodiment may include backend server **100**, and a bridge node (e.g., exemplary bridge node **200**, **16200**) mounted to the storage receptacle in exemplary node-based logistics receptacle **150a** as well as a wireless accessory sensor node (e.g., exemplary wireless accessory sensor node **210**, **1002**, **1002a**, **1002b**) and one or more coupled sensor(s) within logistics receptacle **150a**. The system's backend server **100** in this example maintains a historic use pattern for the storage receptacle in receptacle **150a** as part of a management profile related to at least that storage receptacle (e.g., historic use pattern information maintained in memory of backend server **100** as part of exemplary management profile **835** and previously updated by backend server **100** based on prior detected engagements with the storage receptacle).

(370) Those skilled in the art will appreciate that this system embodiment similarly has the wireless accessory sensor node being operative to detect a change in state of the storage receptacle based upon sensor data generated by at least one of the sensors, record timestamped information reflecting the detected change, and broadcast an updated advertising signal having a data available flag set within the updated advertising signal, where the data available flag indicates the wireless

accessory sensor node has event information available for upload by the bridge node (i.e., event information including at least the timestamped information reflecting the detected change in state of the storage receptacle). And similarly as described before, the system's bridge node is programmatically operative to detect such a data available flag set within the updated advertising signal during a reporting period for the bridge node, retrieve the event information available for upload during that reporting period from the wireless accessory sensor node, and transmit the retrieved event information (e.g., exemplary retrieved event information **1505**) to the backend server at a reporting time during the reporting period.

(371) In this example, the backend server **100** responds to receiving the retrieved event information from the bridge node, by being operative to then access the historic use pattern for the storage receptacle as part of logistics receptacle **150a**; compare the retrieved event information **1505** to the historic use pattern for that storage receptacle; and then dynamically initiate the dispatched logistics operation as a result of comparing the retrieved event information **1505** to the historic use pattern for that storage receptacle. Such a historic use pattern may include information on the prior detected engagements with the storage receptacle as updated by the backend server **100** based on prior event information on the storage receptacle as received by the backend server **100**. Such a historic use pattern, in particular, may also be implemented as a server-tracked profile identifying a pattern of use of the storage receptacle as maintained on the backend server **100** where the profile may identify the pattern of use of that storage receptacle as a pattern of delivery events for the storage receptacle or as a pattern of component state change for the storage receptacle based upon prior event information on the storage receptacle as received by the backend server **100**. When using such a historic use pattern, the backend server **100**, in some embodiments, may dynamically initiate the dispatched logistics operation when the result of comparing the retrieved event information **1505** to the historic use pattern for the storage receptacle indicates a likelihood for an additional deposit of a further delivery item detected within the storage receptacle to be less than a threshold dispatch initiation value.

(372) Those skilled in the art will appreciate that further embodiments that dynamically initiate the dispatched logistics operation based on a historic use pattern may also have the backend server **100** considering the location of a particular logistics asset, that location relative to a predetermined ranges from the reporting receptacle, a route being used by a particular logistics asset, use of an alternative logistics asset, and consideration of a predetermined response time similar to that described above. Likewise, those skilled in the art will appreciate that still further embodiments that dynamically initiate the dispatched logistics operation based on a historic use pattern and may also have the backend server **100** considering (e.g., comparing to event information) context information related to the operating environment of the particular storage receptacle (such as crime data, traffic data, and weather data, logistics asset staffing data, and logistics asset cost data) as well as context information related to locations on a route for a particular logistics asset used to service that storage receptacle. Additionally, those skilled in the art will appreciate that further embodiments that dynamically initiate the dispatched logistics operation based on a historic use pattern may also have the backend server **100** initiating the dispatched logistics operation via a transmitted redirect dispatch message to a particular logistics asset to redirect the logistics asset from a prior scheduled logistics operation (e.g., or to redirect the logistics asset to a predicted location of the storage receptacle when implemented as a mobile storage receptacle). Further still, those skilled in the art will appreciate that yet further embodiments that dynamically initiate the dispatched logistics operation based on a historic use pattern may also have the backend server **100** initiating the dispatched logistics operation via transmission of a combination dispatch message to a particular logistics asset to (a) initiate servicing the storage receptacle as part of reporting node-based logistics receptacle **150a** as the dispatched logistics operation and to (b) further dispatch a sweep operation to service an additional storage receptacle (e.g., non-reporting node-enabled logistics receptacle **150b**). Alternatively, such a combination dispatch message may be transmitted

to the particular logistics asset to (a) prompt that logistics asset to continue with a sweep operation of an additional storage receptacle (e.g., receptacle **150b**) and then to (b) initiate servicing of the storage receptacle (e.g., receptacle **150a**) upon completion of the sweep operation of the additional non-reporting storage receptacle.

(373) In an even more detailed embodiment, a system may be deployed that dynamically initiates a dispatched logistics operation based on context information on the operating environment for a reporting logistics receptacle, a historic use pattern for that receptacle, and a logistics asset profile related to one or more logistics assets used to service that receptacle. For example, such a more detailed system embodiment may similarly include backend server **100**, and a bridge node (e.g., exemplary bridge node **200**, **16200**) mounted to the storage receptacle in exemplary node-based logistics receptacle **150a** as well as a wireless accessory sensor node (e.g., exemplary wireless accessory sensor node **210**, **1002**, **1002a**, **1002b**) and one or more coupled sensor(s) within logistics receptacle **150a**. The system's backend server **100** in this example maintains a management profile (e.g., exemplary management profile **835**) related to the storage receptacle (e.g., related to at least the storage receptacle as part of exemplary node-based logistics receptacle **150a**) and context information related to an operating environment of that storage receptacle. More specifically, the server-maintained management profile includes at least a historic use pattern for the storage receptacle and a logistics asset profile related to one or more logistics assets used to service the storage receptacle. Such a historic use pattern in this example is information maintained and updated by the backend server **100** on prior detected engagements with the storage receptacle part of logistics receptacle **150a**.

(374) Those skilled in the art will appreciate that this more detailed system embodiment similarly has the wireless accessory sensor node being operative to detect a change in state of the storage receptacle based upon sensor data generated by at least one of the sensors, record timestamped information reflecting the detected change, and broadcast an updated advertising signal having a data available flag set within the updated advertising signal, where the data available flag indicates the wireless accessory sensor node has event information available for upload by the bridge node (i.e., event information including at least the timestamped information reflecting the detected change in state of the storage receptacle). And similarly as described before, the system's bridge node is programmatically operative to detect such a data available flag set within the updated advertising signal during a reporting period for the bridge node, retrieve the event information available for upload during that reporting period from the wireless accessory sensor node, and transmit the retrieved event information (e.g., exemplary retrieved event information **1505**) to the backend server at a reporting time during the reporting period.

(375) In this more detailed example, the backend server **100** responds to receiving the retrieved event information from the bridge node, by being operative to generate a comparison of the retrieved event information **1505** (e.g., information on what monitored component of the storage receptacle detected a change in state indicative of an interaction or engagement with part of the storage receptacle) to the historic use pattern for that storage receptacle (e.g., a pattern of delivery events for that storage receptacle), the logistics asset profile on logistics receptacles used to service that storage receptacle, and the context information on the operating environment for that storage receptacle; and dynamically initiate the dispatched logistics operation as a result of the comparison. In some situations, the backend server **100** in this more detailed example may be further operative to dynamically initiate the dispatched logistics operation when the result of the comparison indicates a likelihood for an additional deposit of a further delivery item detected within this particular storage receptacle to be less than a threshold dispatch initiation value.

(376) Those skilled in the art will appreciate that further embodiments of such a more detailed example that dynamically initiate the dispatched logistics operation based on a historic use pattern, context data, and a logistics asset profile may also have the backend server **100** considering the location of a particular logistics asset as part of the logistics asset profile, that location relative to a

predetermined ranges from the reporting receptacle, a route being used by a particular logistics asset, use of an alternative logistics asset, and consideration of a predetermined response time similar to that described above. Likewise, those skilled in the art will appreciate that still further embodiments that dynamically initiate the dispatched logistics operation based on a historic use pattern, context data, and a logistics asset profile may also have the context information considered in the comparison being related to the operating environment of the particular storage receptacle (such as crime data, traffic data, and weather data, logistics asset staffing data, and logistics asset cost data) as well as context information related to locations on a route for a particular logistics asset used to service that storage receptacle. Additionally, those skilled in the art will appreciate that further embodiments that dynamically initiate the dispatched logistics operation based on a historic use pattern, context data, and a logistics asset profile may also have the backend server **100** initiating the dispatched logistics operation via a transmitted redirect dispatch message to a particular logistics asset to redirect the logistics asset from a prior scheduled logistics operation (e.g., or to redirect the logistics asset to a predicted location of the storage receptacle when implemented as a mobile storage receptacle). Further still, those skilled in the art will appreciate that yet further embodiments that dynamically initiate the dispatched logistics operation based on a historic use pattern, context data, and a logistics asset profile may also have the backend server **100** initiating the dispatched logistics operation via transmission of a combination dispatch message to a particular logistics asset to (a) initiate servicing the storage receptacle as part of reporting node-based logistics receptacle **150a** as the dispatched logistics operation and to (b) further dispatch a sweep operation to service an additional storage receptacle (e.g., non-reporting node-enabled logistics receptacle **150b**). Alternatively, such a combination dispatch message may be transmitted to the particular logistics asset to (a) prompt that logistics asset to continue with a sweep operation of an additional storage receptacle (e.g., receptacle **150b**) and then to (b) initiate servicing of the storage receptacle (e.g., receptacle **150a**) upon completion of the sweep operation of the additional non-reporting storage receptacle.

(377) A further system embodiment may have backend server **100** dynamically initiating the dispatched logistics operation based upon information maintained in a logistics asset usage profile. FIG. 25 is a detailed diagram of another embodiment of an exemplary backend server **25100** (similar to exemplary server **100**) that uses an exemplary logistics asset usage profile **2500** as part of dynamically initiating a dispatched logistics operation in accordance with an embodiment of the invention. Referring now to FIG. 25, exemplary backend server **25100** is shown with similar components than that of backend server **100**, and notably includes exemplary logistics asset usage profile **2500** as a data structure that maintains (and may be updated with) information related to costs incurred (e.g., monetary, environmental impact, and the like) associated with use of particular logistics assets that may be selectively and dynamically chosen by the backend server **100** for a particular dispatched logistics operation. Updates to exemplary logistics asset usage profile **2500** may be performed by backend server **100** based upon cost-related information provided to backend server **25100** and/or specific updates from third-party logistics entities on their respective cost information, fees, types of logistics assets available, configurability of such assets, and the like.

(378) For example, an exemplary system embodiment relying upon information in a logistics asset usage profile (such as profile **2500**) when dynamically initiating a dispatched logistics operation may similarly include backend server **25100**, a bridge node (e.g., exemplary bridge node **200**, **16200**) mounted to the storage receptacle in exemplary node-based logistics receptacle **150a**, and a wireless accessory sensor node (e.g., exemplary wireless accessory sensor node **210**, **1002**, **1002a**, **1002b**) and one or more coupled sensor(s) within logistics receptacle **150a**. The system's backend server **25100** in this embodiment maintains a logistics asset usage profile (e.g., exemplary profile **2500**) related to multiple logistics assets (e.g., exemplary logistics assets **700a-700c**). Such a logistics asset usage profile used by the system's backend server **25100** may include, for example, cost information related use of each of the logistics assets; environmental impact information

related to use of each of the logistics assets; and logistics asset class information for each of the logistics assets.

(379) Those skilled in the art will appreciate that this system embodiment has the system's wireless accessory sensor node being operative to detect a change in state of the storage receptacle based upon sensor data generated by at least one of the sensors, record timestamped information reflecting the detected change, and broadcast an updated advertising signal having a data available flag set within the updated advertising signal, where the data available flag indicates the wireless accessory sensor node has event information available for upload by the bridge node (i.e., event information including at least the timestamped information reflecting the detected change in state of the storage receptacle). And similarly as described before, the system's bridge node is programmatically operative to detect such a data available flag set within the updated advertising signal during a reporting period for the bridge node, retrieve the event information available for upload during that reporting period from the wireless accessory sensor node, and transmit the retrieved event information (e.g., exemplary retrieved event information **1505**) to the backend server **25100** at a reporting time during the reporting period. Thereafter, the backend server **25100** responds to receiving the retrieved event information **1505** by being operative to compare the retrieved event information **1505** to the logistics asset usage profile; select a first logistics asset (e.g., exemplary logistics asset **700a**) from the logistics assets covered in the logistics asset usage profile as a result of the comparison involving the logistics asset usage profile and the retrieved event information **1505** received; and dynamically initiate the dispatched logistics operation using the selected first logistics asset.

(380) As mentioned above, the exemplary logistics asset usage profile **2500** used in this embodiment may include cost information related to use of each of the different logistics assets. As such, backend server **2510** may compare the retrieved event information **1505** to the logistics asset usage profile **2500** and select the first logistics asset by being further operative to identify a location of the storage receptacle (i.e., the location of reporting receptacle **150a**) based upon the retrieved event information **1505**; compare the location of the storage receptacle to the cost information related to use of each of the different logistics assets; and select the first logistics asset as a result of comparing the location of the storage receptacle to the cost information related use of each of the logistics assets. In more detail, backend server **2510** may compare the retrieved event information **1505** to the logistics asset usage profile **2500** and select the first logistics asset based upon the result of comparing the location of the storage receptacle to the cost information related use of each of the logistics assets as a monetary cost optimized selection from the logistics assets. Such a monetary cost optimized selection generally is a selection that attempts to find one of the logistics assets where use of that particular logistics asset for this particular dispatched logistics operation presented a lower monetary cost to be incurred when compared to use of other logistics assets characterized in the logistics asset usage profile **2500**.

(381) Furthermore, the exemplary logistics asset usage profile **2500** used in this embodiment may be implemented to include environmental impact information related to use of each of the different logistics assets. Examples of such environment impact information may include but is not limited to environmentally released greenhouse gas/compounds related to use of particular logistics assets, noise related to logistics asset use, degradation of air quality related to logistics asset use, degradation of water resources due to logistics asset use, and the like. Those skilled in the art will appreciate that electric powered or solar powered logistics asset vehicles may have a lower environmental impact through use when compared to some fossil fuel powered delivery vehicles used by other logistics assets. Likewise, those skilled in the art will appreciate the autonomous electric delivery robots operating as a type of logistics asset may also have a lower environmental impact (and lower monetary cost incurred) related to their use when compared to human-controlled and deployed fossil fuel powered delivery vehicles as another type of logistics asset. As such, backend server **2510** may compare the retrieved event information **1505** to the logistics asset usage

profile **2500** and select the first logistics asset by being further operative to identify a location of the storage receptacle based upon the retrieved event information **1505**; compare the location of the storage receptacle to the environmental impact information related to use of each of the logistics assets; and select the first logistics asset as a result of this comparison involving environmental impact information. In more detail, the backend server may select the first logistics asset based upon the result of comparing the location of the storage receptacle (e.g., the location of position **2100** for node-enabled logistics receptacle **150a**) to the environmental impact information related use of each of the different logistics assets as an environmental cost optimized selection from the different logistics assets.

(382) Additionally, the exemplary logistics asset usage profile **2500** used in this embodiment may be implemented to include logistics asset class information for each of the different logistics assets. Such logistics asset class information is generally information that distinguishes each of the different logistics assets with a characteristic grouping or class assigned to each of the assets. Exemplary logistics asset class information may include an incurred time factor for use of a type of logistics asset in the dispatched logistics operation. In another example, exemplary logistics asset class information may be implemented as a type of logistics asset for use in the dispatched logistics operation (e.g., an autonomous type of logistics asset, a non-autonomous type of logistics asset, an inhouse fleet type of logistics asset, a third-party fleet type of logistics asset, and a third-party trusted class type of logistics asset (such as an on-demand type of single engagement logistics asset from a marketplace set of logistics resources like Uber®, Lyft®, or other gig-type on-demand couriers)). As such, backend server **25100** may compare the retrieved event information **1505** to the logistics asset usage profile **2500** and select the first logistics asset by being further operative to identify a location of the storage receptacle (e.g., position **2100** of receptacle **150a**) based upon the retrieved event information; compare the location of the storage receptacle to the logistics asset class information in profile **2500**; and select the first logistics asset as a result of comparing the location of the storage receptacle to the logistics asset class information related use of each of the different logistics assets.

(383) Comparison of the retrieved event information **1505** to information in the logistics asset usage profile **2500** may, in some embodiments, involve specific consideration of the location of the storage receptacle related to such event information. For example, the system embodiment may have backend server **25100** being operative to compare the retrieved event information to the logistics asset usage profile by being further operative to identify a location of the storage receptacle; and compare the retrieved event information to the logistics asset usage profile using the location of the storage receptacle. In some embodiments, backend server **25100** may identify the location of the storage receptacle based upon location information in the management profile maintained by the backend server (e.g., exemplary management profile **835** that may be updated with revised position information as different node-based logistics receptacles are moved or relocated).

(384) Exemplary logistics asset usage profile **2500**, as implemented in some embodiments, may include location information related to each of the different logistics assets. As such and in a particular example, backend server **25100** may be operative to compare the retrieved event information **1505** to the logistics asset usage profile **2500** and select the first logistics asset by being further operative to identify the location of the storage receptacle based upon the retrieved event information; compare the location of the storage receptacle to (a) the cost information related to use of each of the plurality of logistics assets and (b) the location information related to each of the plurality of logistics assets; and select the first logistics asset as a result of comparing the location of the storage receptacle to (a) and (b). In another example where the logistics asset usage profile includes location information on the logistics assets, backend server **25100** may be operative to compare the retrieved event information **1505** to the logistics asset usage profile **2500** and select the first logistics asset by being further operative to identify the location of the storage

receptacle based upon the retrieved event information; compare the location of the storage receptacle to (a) the environmental impact information related to use of each of the plurality of logistics assets and (b) the location information related to each of the plurality of logistics assets; and then select the first logistics asset as a result of comparing the location of the storage receptacle to (a) and (b). In still another example where the logistics asset usage profile includes location information on the logistics assets, backend server **25100** may be operative to compare the retrieved event information **1505** to the logistics asset usage profile **2500** and select the first logistics asset by being further operative to identify the location of the storage receptacle based upon the retrieved event information; compare the location of the storage receptacle to (a) the logistics asset class information related to each of the plurality of logistics assets and (b) the location information related to each of the plurality of logistics assets, and then select the first logistics asset as a result of comparing the location of the storage receptacle to (a) and (b).

(385) In a further embodiment that involves the backend server **25100** using logistics asset usage profile **2500**, server **25100** may also consider historic use pattern information as part of dynamically initiating the dispatched logistics operation. For example, an embodiment may have the system's backend server **25100** being further operative to dynamically initiate the dispatched logistics operation based upon a comparison of the retrieved event information **1505** to a server-tracked historic use pattern for the storage receptacle (e.g., identifying a pattern of use (such as delivery events) of that storage receptacle) maintained as part of management profile **835** on the backend server **25100**. The server-tracked historic use pattern in such an embodiment is information on prior detected engagements with the storage receptacle as updated by the backend server based on prior event information on the storage receptacle as received by the backend server. In this example, backend server **25100** may be further operative to dynamically initiate the dispatched logistics operation when the comparison of the retrieved event information **1505** to the server-tracked historic use pattern for the storage receptacle indicates a likelihood for an additional deposit of a further delivery item detected within the storage receptacle to be less than a threshold dispatch initiation value. In more detail, backend server **25100** may dynamically initiate the dispatched logistics operation using the first logistics asset by being further operative to (a) access a server-tracked historic use pattern for the storage receptacle from exemplary management profile **835**; (b) compare the retrieved event information **1505** to the server-tracked historic use pattern for that storage receptacle that is part of the logistics receptacle **150a** sending the event information **1505**; and (c) dynamically initiate the dispatched logistics operation using the first logistics asset when the likelihood for an additional deposit of a further delivery item detected within that storage receptacle is determined to be less than the threshold dispatch initiation value (where the likelihood for an additional deposit of a further delivery item is based upon comparing the retrieved event information **1505** to the server-tracked historic use pattern for that storage receptacle).

(386) Those skilled in the art will appreciate that still further embodiments that dynamically initiate the dispatched logistics operation based on information within a logistics asset usage profile may also have the backend server **25100** considering (e.g., comparing to event information) context information related to the operating environment of the particular storage receptacle (such as crime data, traffic data, and weather data, logistics asset staffing data, and logistics asset cost data) as well as context information related to locations on a route for a particular logistics asset used to service that storage receptacle. For example, an embodiment may have backend server **25100** be further operative to dynamically initiate the dispatched logistics operation using the first logistics asset based upon a further comparison of the retrieved event information received from the bridge node (e.g., exemplary retrieved event information **1505**) to context information related to an operating environment of the storage receptacle (e.g., information related to a current location of the storage receptacle, such as crime data, traffic data, and/or weather data). In another example, an embodiment may have backend server **25100** being further operative to dynamically initiate the dispatched logistics operation using the first logistics asset based upon a comparison of the

retrieved event information **1505** to context information related to multiple locations on a route for the first logistics asset (e.g., at least one of crime data, traffic data, and/or weather data regarding the different locations on the route for the first logistics asset). Such a route may, more specifically, be an existing scheduled route for the first logistics asset.

(387) Additionally, those skilled in the art will appreciate that further embodiments that dynamically initiate the dispatched logistics operation based on information in a logistics asset usage profile may also have the backend server **25100** initiating the dispatched logistics operation via a transmitted redirect dispatch message to a particular logistics asset to redirect the logistics asset from a prior scheduled logistics operation (e.g., or to redirect the logistics asset to a predicted location of the storage receptacle when implemented as a mobile storage receptacle). Further still, those skilled in the art will appreciate that yet further embodiments that dynamically initiate the dispatched logistics operation based on information in a logistics asset usage profile may also have the backend server **25100** initiating the dispatched logistics operation via transmission of a combination dispatch message to a particular logistics asset to (a) initiate servicing the storage receptacle as part of reporting node-based logistics receptacle **150a** as the dispatched logistics operation and to (b) further dispatch a sweep operation to service an additional storage receptacle (e.g., non-reporting node-enabled logistics receptacle **150b**). Alternatively, such a combination dispatch message may be transmitted to the particular logistics asset to (a) prompt that logistics asset to continue with a sweep operation of an additional storage receptacle (e.g., receptacle **150b**) and then to (b) initiate servicing of the storage receptacle (e.g., receptacle **150a**) upon completion of the sweep operation of the additional non-reporting storage receptacle.

(388) More generally, another embodiment of an exemplary system that dynamically initiates a dispatched logistics operation for a storage receptacle based upon information in a logistics asset usage profile may similarly include backend server **25100**, a bridge node (e.g., exemplary bridge node **200**, **16200**) mounted to the storage receptacle in exemplary node-based logistics receptacle **150a**, and a wireless accessory sensor node (e.g., exemplary wireless accessory sensor node **210**, **1002**, **1002a**, **1002b**) and one or more coupled sensor(s) within logistics receptacle **150a**. In this more general embodiment, the system's backend server **25100** maintains a logistics asset usage profile (e.g., exemplary profile **2500**) related to multiple logistics assets (e.g., exemplary logistics assets **700a-700c**). Such a logistics asset usage profile used by the system's backend server **25100** may include, for example, cost information related use of each of the logistics assets; environmental impact information related to use of each of the logistics assets; and logistics asset class information for each of the logistics assets. Those skilled in the art will appreciate that this system embodiment has the system's bridge node being operative to retrieve event information from the wireless accessory sensor node and transmit the retrieved event information (e.g., exemplary retrieved event information **1505**) to the backend server **25100**. Backend server **25100**, in response to receiving the retrieved event information **1505**, is operative to compare the retrieved event information received from the bridge node to the logistics asset usage profile related to the plurality of logistics assets, select a first logistics asset from the plurality of logistics assets as a result of comparing the retrieved event information received from the bridge node to the logistics asset usage profile, and dynamically initiate the dispatched logistics operation using the first logistics asset.

(389) Self Auto-Unlocking of a Node-Based Connected Logistics Receptacle

(390) In some embodiments, a further improvement may have an exemplary node-based connected logistics receptacle deployed as part of a system equipped to automatically unlock to provide enhanced access to within the logistics receptacle. For example, and as illustrated in FIGS. **26A-30**, an embodiment's system may have an exemplary bridge node become aware of the state or status of an approaching mobile logistics asset (e.g., a logistics delivery van with a vehicle deployed type of bridge node operating as an associated mobile transceiver or a courier riding in the van having a mobile handheld node (e.g., smartphone or mobile bridge node like device operated by that

courier)). As that mobile logistics asset approaches the exemplary connected logistics receptacle, the receptacle's bridge node becomes aware of status information on the mobile logistics asset (such as the ignition state of the mobile delivery van) and the receptacle's bridge node may automatically change the locked state of that exemplary node-based connected logistics receptacle upon approach depending on the status information, without interrogation of the receptacle's bridge node, and/or with authentication of the approaching logistics asset. Various embodiments may involve modes of interaction that include direct node-to-node authentication, contextual awareness (e.g., where the backend server knows why such a mobile logistics asset is approaching and initiates an automatic unlock to be carried out by the receptacle's bridge node), and/or where an approaching device may issue an unlock request to the backend server where the backend server responsively sends an unlock key to the approaching device (e.g., the mobile logistics asset's mobile handheld or to the vehicle's mobile transceiver) when in proximity to the appropriate node-based connected logistics receptacle.

(391) In more detail, FIGS. **26A-26C** present diagrams illustrating an exemplary connected logistics receptacle operating as part of a system with proactive unlocking functionality related to a dispatched logistics operation by an exemplary mobile logistics asset having an associated mobile transceiver in accordance with an embodiment of the invention. Referring now to FIG. **26A**, exemplary connected logistics receptacle **150a** is shown along with backend server **100** and exemplary mobile logistics asset **700a** (e.g., courier personnel **2615** and a delivery vehicle **2602**).

(392) Exemplary connected logistics receptacle **150a** shown in FIG. **26A** has a storage receptacle for receiving and maintaining a delivery item (as previously described having temporary storage area **205** and accessible retrieval door **160**). Exemplary connected logistics receptacle **150a** is illustrated having at least exemplary bridge node **200**, exemplary wireless accessory sensor nodes **210**, **245**, lock **165** for door **160** that provides access to within the storage receptacle, and sensors **450a-450e** that are coupled to at least one of the wireless accessory sensor nodes on receptacle **150a**. Consistent with exemplary lock **165** described above, those skilled in the art will appreciate that lock **165** shown in FIG. **26A** is disposed on the storage receptacle and relative to the selectively accessible retrieval door **160**, and is operative to change between two lock states in response to a lock control input (e.g., a secure state of lock **165** that prevents the selectively accessible retrieval door **160** from opening and providing access to within the temporary storage area, and an unlocked state of lock **165** that allows the selectively accessible retrieval door **160** to open relative to the temporary storage area for selective access to within the temporary storage area of exemplary connected logistics receptacle **150a**).

(393) Exemplary delivery vehicle **2602** is shown as having an exemplary mobile transceiver **2600**, location circuitry **2605** coupled to transceiver **2600**, and vehicle status monitoring circuitry **2610** coupled to transceiver **2600**. Exemplary mobile transceiver **2600** is a type of vehicle-based wireless transceiver associated with the mobile logistics asset **700a** and operative to wirelessly communicate (e.g., via communication over network **105** to backend server **100**, via communication to other handheld or mobile transceivers, via communication to exemplary bridge node **200** within receptacle **150a**). Exemplary location circuitry **2605** is disposed on or within vehicle **2602** and is operative to provide information on the current location of vehicle **2602** (e.g., location coordinates, relative position, and the like) and/or movement status of vehicle **2602** (e.g., moving, stationary, direction of movement, current speed, and the like). Exemplary vehicle status monitoring circuitry **2610** may be implemented with sensor-based hardware and/or software that receives and/or monitors information on the delivery vehicle **2602**, such as the operating status of the vehicle (e.g., an ignition status, a braking status, a transmission status (such as a park, reverse, drive indication), a status of doors on the vehicle, and the like).

(394) Exemplary courier personnel **2615** shown in FIG. **26A** is equipped with a wireless device **2630** and mobile node-enabled badge **2620**. Exemplary mobile handheld communication device **2630** is carried by courier personnel **2615** and may operate as a type of mobile wireless transceiver

associated with the mobile logistics asset **700a** (e.g., such as an augmented reality enabled implementation of device **2630** used by logistics personnel). Using exemplary mobile handheld communication device **2630**, courier personnel **2615** may send/receive information, which may be displayed as information **2635** on the device **2630** (e.g., exemplary information **2635** as processor-generated information overlaid on a view through device **2630**). Exemplary mobile node-enabled badge **2620** in this example is carried by courier personnel **2615** and aside from providing visual identification information related to courier personnel **2615** may also operate as a type of mobile wireless transceiver associated with the mobile logistics asset **700a** where information may be wirelessly transmitted by logic **2625** within badge **2620**. Exemplary mobile node-enabled badge **2620** identifies personnel **2615** via information presented on badge **2620** and/or via information maintained by logic **2625** (e.g., an RFID tag within information related to personnel **2615**, a BLE device capable of storing and sending information related to personnel **2615** to other devices, a battery-powered transceiver operative to maintain and wirelessly transmit such information, and the like).

(395) Those skilled in the art will appreciate that exemplary wireless device **2630** carried by logistics personnel **2615** (e.g., operating as a type of mobile wireless transceiver associated with the mobile logistics asset **700a**) may, like exemplary device **1700** previously noted, be implemented as an exemplary processor-based augmented reality device (e.g., AR headset or enhanced glasses) used by courier personnel **2615**. Those skilled in the art will appreciate that incorporation of augmented reality as part of the logistics personnel operating device **2630** (like exemplary device **1700**) facilitates an enhanced interactive experience that combines real world content (e.g., a view of the surrounding area proximate device **2630**) and processor-generated content (e.g., such as exemplary information **2635** corresponding to virtual symbols, objects, information, prompted messages, directions, sensory information, and the like overlaid on the real world content) shown in an interwoven manner that advantageously allows the logistics personnel to better perceive both the real world content and the processor-generated content. In general, an exemplary augmented reality enhanced device implementation of device **2630** may include a processor, memory, a display (e.g., a heads up display that may be viewed on the device by the user or a look through display viewed through by the user with real world and processor-generated content appearing on the display), sensors (e.g., GPS sensors, accelerometer, imaging sensors, camera, and the like), a wireless transceiver for communication with other devices, as well as input devices for user input and interactivity (e.g., button, cursor, touchscreen, microphone, and the like). Such an exemplary augmented reality enhanced device implementation of device **2630** may, for example, be implemented as augmented reality glasses that project a digital overlay directly in the logistics personnel's field of vision. In general, an exemplary augmented reality enhanced device implementation of device **2630** presents the logistics personnel (as the user) with a combination of digital and physical worlds, facilitates interactions made in near real time with less distraction for the logistics personnel, and an accurate 3D identification of virtual and real objects for use by the logistics personnel when engaging in such interactions (e.g., receiving information displayed, recognizing objects (such as an exemplary node-based logistics receptacle), and providing responsive input/feedback based upon the information displayed). Further, such an exemplary processor based augmented reality device implementation of device **2630** may still provide the ability to connect to network **105** and communicate with other devices, such as mobile handheld bridge nodes used by other logistics personnel (which may themselves have augmented reality features), wireless transceivers onboard a logistics vehicle, and/or connect with and communicate with a node-based logistics receptacle (e.g., once authorized and authenticated to do so) via its wireless transceiver. Information presented via exemplary augmented reality enhanced device **2630** may be accompanied, for example, with additional notification enhancements (e.g., sound, colors, highlights, haptic feedback, and the like) that help draw attention to the information as perceived by the logistics personnel operating the exemplary augmented reality enhanced device **2630**.

(396) In this exemplary embodiment of an improved connected logistics receptacle system with proactive unlocking functionality related to a dispatched logistics operation by a mobile logistics asset (e.g., exemplary mobile logistics asset **700a**), exemplary bridge node **200** is mounted to the storage receptacle of exemplary connected logistics receptacle **150a** and programmatically adapted and configured to be operative to perform particular tasks that have bridge node **200** advantageously interacting with backend server **100** as well as transceiver elements of the mobile logistics asset to initiate such unlocking functionality. For example, exemplary bridge node **200** is programmatically adapted and configured to transmit time-based event information to the backend server **100** to cause the backend server **100** to initiate the dispatched logistics operation for the storage receptacle, which may involve having server **100** initiating communications with mobile logistics asset **700a**. Such time-based event information reflects detection of receipt of the delivery item relative to the storage receptacle.

(397) Exemplary bridge node **200** in this embodiment is further programmatically adapted and configured to receive status information from the mobile transceiver associated with the mobile logistics asset **700a**, such as exemplary status information **2640** received from mobile transceiver **2600** on delivery vehicle **2602** as shown in FIG. **26B**. In other embodiments, such status information may be received from mobile node-enabled badge **2620** carried by courier personnel **2615** operating as the mobile transceiver associated with the mobile logistics asset **700a** or from mobile handheld communication device **2630** carried by courier personnel **2615** operating as the mobile transceiver associated with the mobile logistics asset **700a**.

(398) The status information received includes at least an operating status related to the mobile logistics asset **700** (e.g., an operating status of the delivery vehicle **2602** associated with the mobile logistics asset **700a**). In more detail, the operating status of the delivery vehicle **2602** associated with the mobile logistics asset **700a** may include an ignition status of the delivery vehicle **2602**, a braking status of delivery vehicle **2602**, a transmission status of delivery vehicle **2602**, a status of doors/access openings on delivery vehicle **2602**, a location status of the delivery vehicle **2602**, a movement status of delivery vehicle **2602**, a location status and movement status of delivery vehicle **2602**, or a combination of different types of operating status information on the delivery vehicle **2602**. The location status of vehicle **2602** may, in some examples, include a current location of the delivery vehicle **2602** relative to a location of the storage receptacle and/or relative to a geo-fence location associated with the storage receptacle.

(399) With the status information, exemplary bridge node **200** in this embodiment is further programmatically adapted and configured to generate a lock control input **2645** (e.g., a type of command or control signal) to automatically change the lock **165** from the secure state to the unlocked state based upon the status information received from the mobile transceiver. Further embodiments may have exemplary bridge node **200** being operative to generate a subsequent signal as the lock control input to automatically change the lock from the unlocked state to the secure state based upon updated status information received from the mobile transceiver.

(400) In more detailed embodiments, such an exemplary system may deploy authentication functionality on whether the mobile transceiver is authorized for accessing the storage receptacle as part of exemplary connected logistics receptacle **150a**. FIG. **27** is a diagram illustrating the exemplary connected logistics receptacle **150a**, exemplary backend server **100**, and exemplary mobile logistics asset **700a** of FIGS. **26A-26C** and further illustrating authentication of the approaching mobile logistics asset **700a** in accordance with an embodiment of the invention. Referring now to FIG. **27**, exemplary authentication data **2705** from backend server **100** may be received by exemplary bridge node **200** to use as part of authentication handshaking **2700** communications with the approaching mobile transceiver **2600**. Bridge node **200** may then be operative to authenticate whether the mobile transceiver **2600** associated with the mobile logistics asset **700a** is authorized to conduct the dispatched logistics operation for the storage receptacle based upon authentication data **2705** that identifies an authorized entity dispatched for the

dispatched logistics operation for the storage receptacle. Such exemplary authentication data **2705** may, for example, be implemented as a device identifier for an authorized communication device associated with the authorized entity dispatched for the dispatched logistics operation for the storage receptacle. As such, the bridge node **200** is further operative to authenticate whether the mobile transceiver associated with the mobile logistics asset **700a** (e.g., mobile transceiver **2600**, handheld **2630**, node-enabled badge **2620**, an AR headset implementing any of devices **2600**, **2630**) is authorized to conduct the dispatched logistics operation for the storage receptacle.

(401) In more detail, bridge node **200** may be operative to generate the lock control input by being further operative to generate the lock control input **2645** to automatically change the lock **165** from the secure state to the unlocked state when (a) the mobile transceiver **2600** has been authenticated by the bridge node **200** as being authorized to conduct the dispatched logistics operation for the storage receptacle and (b) based upon the status information received from the mobile transceiver **2600**. Such an authentication of whether the mobile transceiver **2600** associated with the mobile logistics asset **700a** is authorized to conduct the dispatched logistics operation for the storage receptacle may be accomplished when bridge node **200** successfully conducts an authentication handshake operation with authentication handshaking signals **2700** with the mobile transceiver **2600**. Such an authentication handshake operation may be implemented using an encrypted identify verification protocol as part of authentication handshaking signals **2700**. In a further example, the authentication handshake operation may be implemented as an identify verification operation where the bridge node **200** is operative to send a challenge message to the mobile transceiver **2600** to which the mobile transceiver **2600** responds with a correct response message to the challenge message as part of the authentication handshake operation (e.g., as part of the messaging making up authentication handshaking signals **2700**).

(402) FIG. **28** is a diagram illustrating the exemplary connected logistics receptacle **105a**, exemplary backend server **100**, and exemplary mobile logistics asset **700a** of FIGS. **26A-26C** and further illustrating another example of authentication of the approaching mobile logistics asset in combination with detecting the approaching logistics asset (e.g., via proximity sensing) in accordance with an embodiment of the invention. Referring now to FIG. **28**, exemplary mobile logistics asset **700a** is shown approaching the location of exemplary connected logistics receptacle **150a**. In such a situation, an exemplary embodiment may have bridge node **200** being further operative, prior to receiving the status information, to detect the mobile transceiver **2600** associated with the mobile logistics asset **700a** after transmission of the time-based event information to the backend server **100**. Such detection may, for example, be in the form of physical proximity detecting the approaching mobile logistics asset **700a** using external sensor node **250** that uses an external sensor monitoring for a change in the state of the near-by and proximate environment of exemplary connected logistics receptacle **150a**. In another example, such detection may be in the form of bridge node **200** detecting an identification message broadcast from the mobile transceiver **2600**.

(403) In another example, bridge node **200** may, prior to receiving the status information, be further operative to detect, after transmission of the retrieved event information to the backend server **100**, the mobile logistics asset **700a** to be within a threshold distance from the storage receptacle using an external proximity sensor coupled to the bridge node **200** (e.g., a proximity sensor coupled to bridge node **200** through exemplary external sensor node **250**); and then authenticate whether the mobile transceiver associated with the detected mobile logistics asset (e.g., transceiver **2600**, device **2630**, badge **2620**, an AR headset implementing any of devices **2600**, **2630**, and the like) is authorized to conduct the dispatched logistics operation for the storage receptacle. In another example, bridge node **200** may, prior to receiving the status information, be further operative to detect, prior to receiving the status information, the mobile transceiver associated with the mobile logistics asset after transmission of the retrieved event information to the backend server; and authenticate whether the mobile transceiver is authorized to conduct the dispatched logistics

operation for the storage receptacle.

(404) In yet another example, the bridge node **200** may be operative to receive the status information from the mobile transceiver by being further operative to receive an operating status message from the mobile transceiver having information on an operating status of a delivery vehicle associated with the mobile logistics asset. With that operating status message, the bridge node **200** is operative in this example to generate the lock control input to automatically change the lock **165** from the secure state to the unlocked state by being further operative to authenticate whether the mobile transceiver associated with the mobile logistics asset is authorized to conduct the dispatched logistics operation for the storage receptacle, and generate the lock control input to automatically change the lock from the secure state to the unlocked state when (a) the mobile transceiver has been authenticated by the bridge node as being authorized to conduct the dispatched logistics operation for the storage receptacle and (b) based upon the operating status of the delivery vehicle associated with the mobile logistics asset. In some embodiments, the bridge node **200** is also operative to generate a subsequent signal as the lock control input to automatically change the lock **165** from the unlocked state to the secure state based upon updated status information received from the mobile transceiver.

(405) FIGS. **29A-29B** are diagrams illustrating the exemplary connected logistics receptacle **150a**, exemplary backend server **100**, and exemplary mobile logistics asset **700a** of FIGS. **26A-26C** and further illustrating still another example of authentication of the approaching mobile logistics asset **700a** related to the location of the mobile logistics asset **700a** in accordance with an embodiment of the invention. Referring now to FIG. **29A**, exemplary bridge node **200** is programmatically adapted and configured to receive an unlock request **2905** from the backend server **100**. The unlock request **2905** in this example may be based upon a current location of the mobile logistics asset **700a** according to a location message **2900** received by the backend server **100** from the mobile transceiver **2600**.

(406) In a further example shown in FIG. **29B**, the mobile asset's location may be sent to the backend server **100**, which then requests that the bridge node **200** trigger authentication with mobile transceiver **2600** and then unlock upon successful authentication. In more detail, such an example may have bridge node **200** being operative to receive an authentication unlock request **2910** from the backend server **100**. In response to the authentication unlock request **2910**, the bridge node **200** authenticates whether the mobile transceiver **2600** associated with the mobile logistics asset **700a** is authorized to conduct the dispatched logistics operation for the storage receptacle. The bridge node **200** then generates the lock control input **2645** to automatically change the lock **165** from the secure state to the unlocked state when (a) the mobile transceiver **2600** (or device **2630** or badge **2620** or an AR headset implementing devices **2600** or **2630**) has been authenticated by the bridge node **200** as being authorized to conduct the dispatched logistics operation for the storage receptacle and (b) based upon the status information received from the mobile transceiver. Such authentication may be accomplished, for example, by successfully conducting an authentication handshake operation between bridge node **200** and the respective mobile transceiver (e.g., transceiver **2600**, badge **2620**, and/or handheld device **2630**, which may be implemented as an AR headset).

(407) In some embodiments, a courier validation message may also be provided by the respective mobile transceiver. FIG. **30** is a diagram illustrating the exemplary connected logistics receptacle **150a**, exemplary backend server **100**, and exemplary mobile logistics asset **700a** of FIGS. **26A-26C** and further illustrating examples of different exemplary courier validation messages from different external transceiver devices (e.g., transceiver **2600**, badge **2620**, and/or handheld device **2630**, which may be implemented with augmented reality (AR) functionality) in accordance with an embodiment of the invention. Referring now to FIG. **30**, bridge node **200** in this example is operative to generate the lock control input **2645** to automatically change the lock **165** from the secure state to the unlocked state by being further operative to receive a courier validation message

3000 from the mobile transceiver **2600** prior to generating the lock control input **2645**; and then generate the lock control input **2645** to automatically change the lock **165** from the secure state to the unlocked state based upon (a) the status information received from the mobile transceiver and (b) the courier validation message received from the mobile transceiver. In a more detailed example, the processor in bridge node **200** may be operative to generate the lock control input to automatically change the lock from the secure state to the unlocked state by being further operative to receive courier validation message **3000** from the mobile transceiver (e.g., transceiver **2600**, handheld transceiver **2630**, an AR enabled transceiver implementing devices **2600** or **2630**) prior to generating the lock control input **2645**; and generate the lock control input **2645** to automatically change the lock **165** from the secure state to the unlocked state (a) based upon the status information received from the mobile transceiver and (b) when the courier validation message **3000** indicates a validation approval input from an operator of the mobile transceiver (e.g., from courier personnel **2615**) to automatically change the lock **165** from the secure state to the unlocked state. (408) Those skilled in the art will appreciate that a further embodiment of such a system with proactive unlocking functionality related to a dispatched logistics operation may further include a wireless accessory sensor node having at least one sensor that monitors for a deposit of the delivery item relative to the storage receptacle, where the wireless accessory sensor node is operative to (a) detect receipt of the delivery item relative to the storage receptacle based upon sensor data generated by at least one sensor and (b) notify the bridge node **200** of time-based event information available for upload related to the detected receipt of the delivery item. In such a further embodiment, the bridge node **200** is also operative to retrieve the time-based event information from the wireless accessory sensor node in response to the notification from the wireless accessory sensor node and then (as described in embodiments above) transmit the time-based event information to the backend server **100**, which causes the backend server **100** to initiate the dispatched logistics operation for the storage receptacle.

(409) Those skilled in the art will also appreciate that a more detailed embodiment of such a system with proactive unlocking functionality related to a dispatched logistics operation may have the storage receptacle comprising an entrance opening **155** for receiving the delivery item, a temporary storage area **205** for temporarily maintaining the delivery item once the delivery item has been deposited within the storage receptacle through the entrance opening, a selectively accessible retrieval door **160** providing access to the delivery item within the temporary storage area **205** of the storage receptacle, and a lock **165** disposed on the storage receptacle and relative to the selectively accessible retrieval door **160**. Similar to that described above, the lock **165** can change between two lock states in response to a lock control input **2645**, where a first of the lock states comprises a secure state that prevents the selectively accessible retrieval door **160** from opening and providing access to within the temporary storage area **205**, and where a second of the lock states is an unlocked state that allows the selectively accessible retrieval door **160** to open relative to the temporary storage area **205** for selective access to within the temporary storage area **205**.

(410) The bridge node **200** in this more detailed embodiment includes a bridge node processor **201**, a bridge node memory **202** coupled to the bridge node processor and maintaining bridge node code for execution by the bridge node processor **201**, and a communication interface **203** coupled to the bridge node processor **201** where the communication interface is operative to communicate with backend server **100** and a mobile transceiver associated with the mobile logistics asset **700a** (e.g., transceiver **2600**, device **2630**, badge **2620**). Such a mobile transceiver may, for example, be implemented as an augmented reality device used by logistics personnel associated with logistics asset **700a**. This more detailed embodiment also includes a wireless accessory sensor node having at least one sensor that monitors for a change in the storage receptacle associated with a deposit of the delivery item relative to the storage receptacle. The wireless accessory sensor node in this more detailed embodiment is further operative to detect the receipt of the delivery item relative to the storage receptacle based upon sensor data generated by the at least one sensor; record timestamped

information reflecting the detected receipt of the delivery item; and broadcast a notification of event information available for upload related to the detected receipt of the delivery item, the event information including at least the timestamped information reflecting the detected receipt of the delivery item.

(411) In this more detailed embodiment, the bridge node processor **201**, when executing the bridge node code in memory of bridge node **200**, is also operative to receive the notification about the event information available for upload from the wireless accessory sensor node; retrieve the event information available for upload from the wireless accessory sensor node; transmit the retrieved event information to the backend server to cause the backend server to initiate the dispatched logistics operation for the storage receptacle; receive status information from the mobile transceiver associated with the mobile logistics asset (where the status information is related to an operating status of the mobile logistics asset); and generate the lock control input to automatically change the lock from the secure state to the unlocked state based upon the status information received from the mobile transceiver.

(412) Monitoring Movement of the Node-Enabled Logistics Receptacle

(413) In additional embodiments, a further improvement may involve an exemplary connected node-enabled logistics receptacle deployed as part of a system equipped to automatically monitor its own movement and/or location and adaptively cause the backend server **100** to respond by altering a dispatched logistics operation to be conducted by a logistics asset. In such an embodiment, the exemplary node-enabled logistics receptacle is deployed in the system as a location and/or motion aware logistics platform that may use location circuitry (e.g., exemplary GPS location circuitry **345**) and/or different onboard sensors that may detect movement of the node-enabled logistics receptacle. In general, when there has been movement of a logistics receptacle, a logistics asset (such as a courier) may be faced with difficulty finding the logistics receptacle. As such, an embodiment may have the node-enabled logistics receptacle generally detecting its movement, which may then be transmitted to the backend server. The backend server, having been advantageously updated with such movement and/or location related information, can alert the logistics asset (e.g., courier) of this movement and/or new location. In other words, such an embodiment has the practical application of updating the backend server of movement and/or a new location to proactively or reactively inform the logistics asset (and/or customers) in a self-healing type of system. Such detected movement/location, in some embodiments as explained in more detail below, may include motion, changes in location, and/or changes in position/orientation. Such movement may further include intentional movement where the move of the node-enabled logistics receptacle was planned and may include confirmation and/or operational mode changes for the node within the logistics receptacle (e.g., a bridge node and/or wireless accessory sensor node(s)) after the move is complete or at least upon reaching a particular location or within a threshold distance of that particular location. For example, the node-based logistics receptacle may change operational modes (e.g., from a low power or less than fully active mode to a normal mode of operation) once arriving at or close to a predetermined location (e.g., a new location, a location where another logistics receptacle used to be, and the like).

(414) FIGS. **31-35** provide illustrations related to such exemplary embodiments that involve self-monitoring of a node-enabled logistics receptacle's movement/location and responding accordingly. FIG. **31** is a diagram illustrating an exemplary improved monitoring and logistics response system involving movement of the system's exemplary logistics receptacle in accordance with an embodiment of the invention. Referring now to FIG. **31**, an example of an improved monitoring and logistics response system is shown including exemplary backend server **100**, exemplary connected node-enabled logistics receptacle **150a** and exemplary mobile logistics asset **700a**. As shown in FIG. **31**, exemplary logistics receptacle **150a** is operative to receive and temporarily maintain a delivery item being shipped. Consistent with descriptions above, exemplary logistics receptacle **150a** has an entrance opening through which the delivery is received and a temporary

storage area where the delivery item is temporarily and securely maintained until an authorized pickup to be conducted by a logistics asset (such as exemplary logistics asset **700a**).

(415) Those skilled in the art will appreciate that exemplary logistics receptacle **150a** is implemented with a sensor-based node (e.g., bridge node **200** that is coupled to a variety of different types of sensors **450a-450e**) disposed on the logistics receptacle **150a**. Such an exemplary sensor-based node is implemented with a processor, memory storage that maintains management code for execution by the processor, a communication interface coupled to the processor and that is operative to communicate with a backend server, and at least one sensor coupled to the processor that generates sensor data related to movement associated with the logistics receptacle **150a**. In such an exemplary system, the processor of the sensor-based node in logistics receptacle **150a** (when executing the management code maintained on the node memory storage), is operative to detect movement associated with the logistics receptacle **150a** based upon the sensor data, and transmit an alert notification **3100** through network **105** to backend server **100** over the node's communication interface (e.g., wireless communication interface **203** of exemplary bridge node **200**). Such an alert notification **3100** identifies the logistics receptacle **150a** and informs the backend server **100** of the detected movement. The system's backend server **100** in such an embodiment is then operative to alert the logistics asset **700a** with an alert message **3105** about the detected movement associated with the logistics receptacle **150a** causing the logistics asset **700a** to alter a dispatched logistics operation to be conducted by the logistics asset **700a** relative to the logistics receptacle **150a**.

(416) In such a system embodiment, detecting movement may be implemented in a variety of ways. More particularly, an embodiment may have the node processor of the sensor-based node in logistics receptacle **150a** be operative to detect the movement by being further operative to detect motion associated with the logistics receptacle using the sensor data generated by at least one sensor. Such motion detection may, for example, involve a tilt sensor where the detected motion is a tilt movement detected by the tilt sensor; an inertial sensor where the detected motion is an inertial movement detected by the inertial sensor; an accelerometer where the detected motion is an accelerated movement detected by the accelerometer; and/or an external motion sensor focused externally with respect to the logistics receptacle **150a** and where the detected motion is motion relative to an external environment of the logistics receptacle **150a** as detected by the external motion sensor.

(417) In another example, detecting movement may involve detecting a change in location. More particularly, an embodiment may have the node processor of the sensor-based node in logistics receptacle **150a** be operative to detect the movement by being further operative to detect a location change of the logistics receptacle **150a** using the sensor data generated by at least one sensor. Such location change detection may, for example, have the sensor being location circuitry **345** where the location change is a change in physical location of the logistics receptacle **150a** as detected by the location circuitry **345** (e.g., a change in location coordinates as detected by GPS location circuitry **345**). Alternatively (or in addition), such location change detection may have the sensor being a proximity sensor where the location change comprises a change in proximity of the logistics receptacle **150a** relative to at least one object disposed external to the logistics receptacle **150a** as detected by the proximity sensor. Thus, an embodiment may have sensor circuitry within logistics receptacle **150a** being able to detect a change in location via location circuitry (e.g., location circuitry compatible with satellite-based systems (e.g., GPS, the European Galileo system, the Russian GLONASS system, the Chinese Compass system), terrestrial radio-based positioning systems (e.g., cell phone tower-based or Wi-Fi-based systems), infrared positioning systems, visible light based positioning systems, and ultrasound-based positioning systems).

(418) Stated another way, further system examples may detect movement using the sensor-based node of logistics receptacle **150a** that involves detecting a positional change of the logistics receptacle **150a** (such as a change in position or even orientation) using wireless communication

circuitry as the sensor (e.g., exemplary wireless communication interface **203**). In more detail, the sensor used for detecting movement may be implemented with a millimeter wave sensor element operatively implemented in the communication interface **203** of exemplary bridge node **200** such that the position change is detected by the millimeter wave sensor element in communication interface **203**.

(419) In still further embodiments, exemplary systems may detect movement via the sensor-based node of logistics receptacle **150a** using a combination of motion, location and/or position. For example, such a system embodiment may have the node processor of the sensor-based node within logistics receptacle **150a** be operative to detect the movement by being further operative to detect the movement as (a) motion associated with the logistics receptacle **150a** using a first sensor (e.g., a motion sensor, a tilt sensor, an inertial sensor, an accelerometer, an external motion sensor) coupled to the sensor-based node and (b) a change in location of the logistics receptacle **150a** using a second sensor (e.g., location circuitry, proximity sensor, wireless communication circuitry) coupled to the sensor-based node. In another example, such a system embodiment may have the node processor of the sensor-based node within logistics receptacle **150a** be operative to detect the movement by being further operative to detect the movement as at least one of (a) motion associated with the logistics receptacle **150a** using a first sensor coupled to the sensor-based node; (b) a change in location of the logistics receptacle **150a** using a second sensor coupled to the sensor-based node; and (c) a change in position of the logistics receptacle **150a** using a third sensor coupled to the sensor-based node. Those skilled in the art will appreciate that embodiments may involve a combination of any of (a), (b), and (c) as detailed above as ways to implement self-detection of movement of exemplary logistics receptacle **150a**.

(420) While FIG. **31** illustrates such an exemplary system notifying backend server **100** of self-detected movement (e.g., change in motion, change in location, change in position, and combinations thereof), FIG. **32** is a diagram illustrating the exemplary improved monitoring and logistics response system of FIG. **31** involving an updated location of the system's exemplary logistics receptacle **150a** in accordance with an embodiment of the invention. Referring now to FIG. **32**, the system's sensor-based node may have its processor being further operative to detect an updated location **3205** (e.g., distinct from and/or relative to an original location **3200**) of the logistics receptacle **150a** after no longer detecting the movement associated with the logistics receptacle **150a**, and transmit a message **3210** with the updated location of the logistics receptacle **150a** to the backend server **100**. With this updated location information from message **3210**, backend server **100** is then operative to send a different message **3215** to alert the logistics asset **700a** about the updated location of the logistics receptacle **150a** causing the logistics asset **700a** to alter the dispatched logistics operation to be conducted by the logistics asset **700a** relative to the logistics receptacle **150a**. Such an alert message **3215** may, in some examples, alert the logistics asset **700a** about (a) the movement associated with the logistics receptacle **150a** and (b) the updated location **3205** of the logistics receptacle **150a**, where (a) and (b) causes the logistics asset **700a** to alter the dispatched logistics operation to be conducted by the logistics asset **700a** relative to the logistics receptacle **150a**.

(421) In more detail, the system's sensor-based node may have its processor, after transmitting the alert notification **3100**, being further operative to (a) detect the updated location **3205** of the logistics receptacle **150a** after transmitting the alert notification **3100** and no longer detecting the movement associated with the logistics receptacle **150a**, and (b) transmit the updated location **3205** of the logistics receptacle **150a** to the backend server **100** via message **3210**. In such a detailed example, those skilled in the art will appreciate that backend server **100** is operative to alert the logistics asset **700a** via message **3215** to alert the logistics asset **700a** about the updated location **3205** of the logistics receptacle **150a**, which causes the logistics asset **700a** to alter the dispatched logistics operation to be conducted by the logistics asset **700a** relative to the logistics receptacle **150a**. In some embodiment a message **3215** may alert the logistics asset **700a** about the movement

associated with the logistics receptacle **150a** and the updated location **3205** of the logistics receptacle **150a** causing the logistics asset **700a** to alter the dispatched logistics operation to be conducted by the logistics asset **700a** relative to the logistics receptacle **150a**. For example, in response to message **3215** (which may include information on self-detected movement of receptacle **150a** and/or a self-detected updated location of receptacle **150a** as reported in message **3210**), logistics asset **700a** alters the dispatched logistics operation relative to logistics receptacle **150a** by changing pre-arranged route details and travel to the updated location **3205** (rather than to location **3200**) as part of the dispatched logistics operation now altered in light of the self-detected and reported information from logistics receptacle **150a**.

(422) In yet a more detailed example, the node processor of the sensor-based node within logistics receptacle **150a**, after detecting the movement, may be further operative to detect updated location **3205** of the logistics receptacle **150a** after transmitting the alert notification **3100** and no longer detecting the movement associated with the logistics receptacle **150a**; and transmit alert notification **3210**, which includes (a) first notification data providing an identifier corresponding to the logistics receptacle **150a**, (b) second notification data informing the backend server **100** of the movement associated with the logistics receptacle **150a**, and (c) third notification data providing the updated location **3205** of the logistics receptacle **150a**. Thereafter in this example, backend server **100** is operative to alert the logistics asset via message **3215** about the movement associated with the logistics receptacle **150a** and the updated location **3205** of the logistics receptacle **150a** causing the logistics asset **700a** to alter the dispatched logistics operation to be conducted by the logistics asset **700a** relative to the logistics receptacle **150a**.

(423) Those skilled in the art will appreciate that examples of such detected movement associated with the node-enabled logistics receptacle **150a** relates to preplanned movement associated with the logistics receptacle **150a**. Such preplanned movement may, for example, be movement related to previously scheduled maintenance on the receptacle **150a** or simply a planned change in operative location for the logistics receptacle **150a** to make more efficient use of logistics receptacle **150a** and better serve customers seeking to deposit delivery items for shipping using a logistics receptacle and a logistics asset from one location to another location. In some embodiments, the node processor of the sensor-based node within logistics receptacle **150a**, after transmitting the alert notification **3210**, may be further operative to receive a confirmation from the backend server **100** that the detected movement associated with the logistics receptacle **150a** relates to preplanned movement associated with the logistics receptacle **150a** as identified in the alert notification. In this way, the sensor-based node within logistics receptacle **150a** may be made aware that the self-detected movement and/or change in location/position is intentional (rather than something nefarious or unauthorized).

(424) In some examples, the node processor of the sensor-based node within logistics receptacle **150a**, after transmitting the alert notification **3210** and after a threshold period of time without receiving such a confirmation, may be further operative to issue a priority alert message to the backend server **100** that the detected movement associated with the logistics receptacle **150a** has not been confirmed as authorized or otherwise preplanned movement, which causes the backend server **100** further request more frequent updates to the location of the logistics receptacle **150a** being moved in such an unauthorized manner and to deploy resources (e.g., police, logistics assets, and the like) to recover the logistics receptacle **150a** self-reporting such unauthorized movement. Embodiments may have such a moving logistics receptacle **150a** enter a restricted mode of operation that secures the logistics receptacle **150a** (e.g., changes the state of lock **165** to a locked state) until the moving logistics receptacle **150a** is recovered and confirmation of such a recovery with backend server **100** is established.

(425) Those skilled in the art will appreciate that operational modes of the logistics receptacle **150a** (e.g., components within the logistics receptacle) may change or be self-adaptively changed based on the self-detected changes in movement, location, and/or position for the particular node-enabled

logistics receptacle. For example, further embodiments may have the node processor of the sensor-based node within logistics receptacle **150a**, after detecting the movement, being further operative to cause a change from a current operational mode of the node-based logistics receptacle (e.g., the sensor-based node disposed within the logistics receptacle and/or other components of the logistics receptacle controlled by such a sensor-based node within that logistics receptacle) to a secondary operational mode. In more detail, such a change from the current operational mode to the secondary operational mode may occur after detecting a cessation of movement associated with the logistics receptacle **150a** corresponding to an end of the preplanned movement associated with the logistics receptacle **150a**.

(426) In an example embodiment, the secondary operational mode may be implemented as a normal operation of the sensor-based node disposed within the logistics receptacle **150a** at a new location (e.g., location **3205**). Such a new location may be a predetermined address associated with the preplanned movement, such as a new road intersection, new commercial address, new building or facility, and the like. The secondary operational mode may be a normal operation of the sensor-based node disposed within logistics receptacle **150a** at the new location as confirmed by the backend server **100** to the sensor-based node within logistics receptacle **150a** via a confirmation message sent by backend server **100** once logistics receptacle **150a** reports the updated location via message **3210**. In more detail regarding shifting from a current operational mode to the secondary operational mode, the node processor of the sensor-based node (e.g., bridge node **100**) within logistics receptacle **150a** may be programmatically adapted to be further operative to detect, based upon further sensor data, a cessation of movement associated with the logistics receptacle **150a** corresponding to an end of the preplanned movement associated with the logistics receptacle **150a**; report an updated location to the backend server **100**; and receive a confirmation message from the backend server **100** that the updated location of the logistics receptacle is a predetermined new location for the logistics receptacle **150a**. In this more detailed example, the secondary operational mode may be implemented as normal operation of the sensor-based node disposed within the logistics receptacle **150a** at the predetermined new location.

(427) In other embodiments, such a secondary operational mode may be implemented as a type of decommissioned mode of operation for at least the sensor-based node disposed within the logistics receptacle **150a**. In an example, the decommissioned mode of operation for at least the sensor-based node disposed within the logistics receptacle **150a** may be implemented once the sensor-based node has detected the movement associated with the logistics receptacle **150a**. Such a decommissioned mode of operation may be a low-power operational state of the sensor-based node within the logistics receptacle **150a** as the logistics receptacle **150a** is placed at an inventory location for temporary storage; a non-operational state of the sensor-based node within the logistics receptacle **150a** as the logistics receptacle **150a** is placed at an inventory location for temporary storage; or a non-operational state of the sensor-based node as the logistics receptacle **150a** is placed at a maintenance location for refurbishment.

(428) FIG. **33** is a diagram illustrating the exemplary improved monitoring and logistics response system of FIG. **31**, but involves replacement movement and use of an exemplary replacement logistics receptacle relative to a predetermined location where a second logistics receptacle was previously located in accordance with an embodiment of the invention. In other words, the system's node-enabled logistics receptacle may be a new unit being moved from an original location to replace another logistics receptacle at the new location. In such an example, the movement of the replacement logistics receptacle is a type of replacement movement—e.g., coming in to replace another logistics receptacle. Referring now to FIG. **33**, an example of an improved monitoring and logistics response system is shown including exemplary backend server **100**, exemplary connected node-enabled logistics receptacle **150a** and exemplary mobile logistics asset **700a** where logistics receptacle **150a** is being moved from location **3300** to a location **3305** where exemplary node-enabled logistics receptacle **150b** is being replaced. As shown in FIG. **31**, those skilled in the art

will appreciate that the node processor of the sensor-based node within exemplary logistics receptacle **150a** detects movement as a replacement movement associated with the logistics receptacle **150a**, which may be reported via message **3310** to backend server **100** (which then may initiate or cause an alert message **3315** to be sent to logistics asset **700a** so as to alter a dispatched logistics operation—e.g., updating logistics asset **700a** that logistics receptacle **150a** is moving to location **3305** to replace logistics receptacle **150b**). After detecting the replacement movement, the node processor of the sensor-based node within exemplary logistics receptacle **150a** is then operative to change its current operational mode (e.g., a decommissioned operational mode) to a secondary operational mode (e.g., a newly commissioned mode) for the sensor-based node disposed within the logistics receptacle **150a**. In an embodiment, such a decommissioned operational mode has the sensor-based node within exemplary logistics receptacle **150a** still able to detect movement, but with limited other operational capabilities (e.g., limited abilities to detect and report delivery items received, limited abilities to monitor components of the logistics receptacle, and the like) while the newly commissioned operational mode has the sensor-based node within exemplary logistics receptacle **150a** transitioning to a fully operational mode of operating to monitor for delivery items received, communicate with backend server **100** about such received delivery items, and provide other intelligent node-enabled services relative to operation of the logistics receptacle. In an embodiment, the node processor of the sensor-based node within exemplary logistics receptacle **150a** shown in FIG. **33** may be operative to detect the replacement movement prior to reaching a predetermined location (e.g., such as the prior location **3305** of second logistics receptacle **150b** before the second logistics receptacle **150b** was moved away from the prior location **3305**. More specifically, the node processor of the sensor-based node within exemplary logistics receptacle **150a** may be operative to change the current operational mode to the secondary operational mode by being further operative to change the current operational mode from the decommissioned mode of operation to the newly commissioned mode of operation upon arrival at the predetermined location (e.g., location **3305**). The predetermined location may be a geolocation associated with a previous location **3305** of a currently decommissioned sensor-based node within a second logistics receptacle **150b** being replaced by the sensor-based node and the logistics receptacle **150a**.

(429) In a further embodiment, the node processor of the sensor-based node within exemplary logistics receptacle **150a** may be operative to detect the replacement movement associated with the replacement logistics receptacle **150a** by detecting the replacement movement prior to reaching a geofence perimeter **3320** relative to the predetermined location **3305** that was previously associated with second logistics receptacle **150b** prior to when the second logistics receptacle **150a** was decommissioned. More specifically, the node processor of the sensor-based node within exemplary logistics receptacle **150a** may also be operative to change the current operational mode for the sensor-based node in logistics receptacle **150a** (i.e., the replacement unit in this embodiment) to the secondary operational mode by being further operative to change the current operational mode from a decommissioned mode of operation to a newly commissioned mode of operation upon detecting the logistics receptacle **150a** is within the geofence perimeter **3320** relative to the predetermined location **3305**.

(430) FIG. **34** is a flow diagram illustrating an exemplary improved method for monitoring and initiating a logistics response related to a node-enabled logistics receptacle (e.g., receptacle **150a**) to be serviced by a logistics asset (e.g., logistics asset **700a**) in accordance with an embodiment of the invention. Referring now to FIG. **34**, exemplary method **3400** for monitoring and initiating a logistics response related to a node-enabled logistics receptacle (e.g., exemplary node-enabled logistics receptacle **150a**) to be serviced by a logistics asset (e.g., exemplary logistics asset **700a**) is illustrated beginning with step **3405**. At step **3405**, method **3400** has a sensor-based node (e.g., exemplary bridge node) disposed within the node-enabled logistics receptacle detecting movement associated with the node-enabled logistics receptacle.

(431) In more detail, step **3405** may detect such movement using at least one sensor coupled to the sensor-based node for detecting motion associated with the node-enabled logistics receptacle. Such motion, for example, may be a tilt movement detected by a tilt sensor, an inertial movement detected by an inertial sensor, an acceleration detected by an accelerometer sensor as the at least one sensor coupled to the sensor-based node, and/or motion relative to an external environment of the node-enabled logistics receptacle as detected by an externally focused motion sensor.

(432) In a further embodiment, step **3405** may detect such movement using at least one sensor coupled to the sensor-based node for detecting a location change of the node-enabled logistics receptacle. Such a location change, for example, may be a change in physical location as detected by location circuitry coupled to the sensor-based node, a change in proximity to at least one object disposed external to the node-enabled logistics receptacle as detected by a proximity sensor coupled to the sensor-based node, and/or a change in location coordinates as detected by location circuitry coupled to the sensor-based node.

(433) In still another embodiment, step **3405** may detect such movement using at least one sensor coupled to the sensor-based node for detecting a position change of the node-enabled logistics receptacle. Such a position change, for example, may be a change in orientation of the node-enabled logistics receptacle. The position change may, for example, be detected by a wireless communication sensor coupled to the sensor-based node, a wireless communication interface of the sensor-based node, and/or at least one millimeter wave sensor coupled to the sensor-based node.

(434) In yet another embodiment, step **3405** may detect the movement as both (a) the motion associated with the node-enabled logistics receptacle using a first sensor coupled to the sensor-based node, and (b) a change in location of the node-enabled logistics receptacle using a second sensor coupled to the sensor-based node. In this embodiment, the motion may, for example, be a tilt movement detected by a tilt sensor as the first sensor, an inertial movement detected by an inertial sensor as the first sensor, an acceleration detected by an accelerometer sensor as the first sensor, and/or motion relative to an external environment of the node-enabled logistics receptacle as detected by an externally focused motion sensor as the first sensor coupled to the sensor-based node. In this embodiment, the location change may, for example, be a change in location as detected by location circuitry coupled to the sensor-based node, a change in proximity to at least one object disposed external to the node-enabled logistics receptacle by a proximity sensor coupled to the sensor-based node, and/or a change in location coordinates by location circuitry coupled to the sensor-based node as the second sensor coupled to the sensor-based node.

(435) In still another embodiment, the detecting in step **3405** may be implemented as detecting the movement as at least one of (a) motion associated with the node-enabled logistics receptacle using a first sensor coupled to the sensor-based node; (b) a change in location of the node-enabled logistics receptacle using a second sensor coupled to the sensor-based node; and (c) a change in position of the node-enabled logistics receptacle using a third sensor coupled to the sensor-based node.

(436) At step **3410**, method **3400** then proceeds with the sensor-based node transmitting an alert notification to a backend server. Such an alert notification (e.g., exemplary alert notification **3100**) identifying the node-enabled logistics receptacle and informing the backend server of the movement in response to detecting the movement.

(437) At step **3415**, method **3400** proceeds with the backend server alerting the logistics asset about the detected movement associated with the node-enabled logistics receptacle causing the logistics asset to alter a dispatched logistics operation to be conducted by the logistics asset relative to the node-enabled logistics receptacle.

(438) In further embodiments of method **3400**, the sensor-based node may detect location after movement is no longer detected. For example, method **3400** may include, after the detecting step, the steps of (a) detecting, by the sensor-based node, an updated location of the node-enabled logistics receptacle after no longer detecting the movement associated with the node-enabled

logistics receptacle and (b) transmitting, by the sensor-based node, the updated location of the node-enabled logistics receptacle to the backend server. In such an example, the backend server may then alert the logistics asset about the updated location of the node-enabled logistics receptacle causing the logistics asset to alter the dispatched logistics operation to be conducted by the logistics asset relative to the node-enabled logistics receptacle. More specifically, the alerting step may have the backend server alerting the logistics asset about the movement associated with the node-enabled logistics receptacle and the updated location of the node-enabled logistics receptacle, which then causes the logistics asset to alter the dispatched logistics operation to be conducted by the logistics asset relative to the node-enabled logistics receptacle.

(439) In another embodiment, method **3400** may, after transmitting in step **3410**, include the steps of (a) detecting, by the sensor-based node, an updated location of the node-enabled logistics receptacle after transmitting the alert notification and no longer detecting the movement associated with the node-enabled logistics receptacle; and (b) transmitting, by the sensor-based node, the updated location of the node-enabled logistics receptacle to the backend server. Here, the alerting step **3415** may be implemented with the backend server alerting the logistics asset about the updated location of the node-enabled logistics receptacle causing the logistics asset to alter the dispatched logistics operation to be conducted by the logistics asset relative to the node-enabled logistics receptacle. More specifically, the alerting step may be implemented with the backend server alerting the logistics asset about the movement associated with the node-enabled logistics receptacle and the updated location of the node-enabled logistics receptacle causing the logistics asset to alter the dispatched logistics operation to be conducted by the logistics asset relative to the node-enabled logistics receptacle.

(440) In still another embodiment, method **3400** may include the step of detecting, by the sensor-based node, an updated location of the node-enabled logistics receptacle after transmitting the alert notification in step **3410** and no longer detecting the movement associated with the node-enabled logistics receptacle. In such an embodiment, step **3410** of transmitting the alert notification comprises transmitting, by the sensor-based node, the alert notification to the backend server, where the alert notification comprises (a) first notification data providing an identifier corresponding to the node-enabled logistics receptacle, (b) second notification data informing the backend server of the movement associated with the node-enabled logistics receptacle, and (c) third notification data providing the updated location of the node-enabled logistics receptacle. In such an embodiment, step **3415** then may be implemented as alerting, by the backend server, the logistics asset about the movement associated with the node-enabled logistics receptacle and the updated location of the node-enabled logistics receptacle causing the logistics asset to alter the dispatched logistics operation to be conducted by the logistics asset relative to the node-enabled logistics receptacle.

(441) In some embodiments of method **3400**, the detected movement associated with the node-enabled logistics receptacle relates to preplanned movement associated with the node-enabled logistics receptacle. For example, after the step of transmitting the alert notification in step **3410**, method **3400** may further include a step of confirming, by the backend server, that the detected movement associated with the node-enabled logistics receptacle relates to the preplanned movement associated with the node-enabled logistics receptacle as identified in the alert notification. In another example, after step **3405** of detecting the movement, method **3400** may include the step of changing, by the sensor-based node, a current operational mode for the node-enabled logistics receptacle to a secondary operational mode for the node-enabled logistics receptacle. This may be implemented where such a changing step further comprises changing, by the sensor-based node, the current operational mode for the node-enabled logistics receptacle to the secondary operational mode for the node-enabled logistics receptacle once the sensor-based node disposed within the node-enabled logistics receptacle detects a cessation of movement associated with the node-enabled logistics receptacle corresponding to an end of the preplanned movement

associated with the node-enabled logistics receptacle.

(442) In additional embodiments of method **3400**, the secondary operational mode for the node-enabled logistics receptacle may be a normal operation of the node-enabled logistics receptacle at a new location, such as a predetermined address associated with the preplanned movement. More specifically, the secondary operational mode for the node-enabled logistics receptacle may be a normal operation of the node-enabled logistics receptacle at the new location as confirmed by the backend server to the sensor-based node. In even more detail, an embodiment of method **3400** may further include the steps of (a) detecting, by the sensor-based node, a cessation of movement associated with the node-enabled logistics receptacle corresponding to an end of the preplanned movement associated with the node-enabled logistics receptacle; (b) reporting, by the sensor-based node, an updated location to the backend server; and (c) receiving, by the sensor-based node, a confirmation message from the backend server that the updated location of the node-enabled logistics receptacle is a predetermined new location for the node-enabled logistics receptacle. In such an embodiment, the secondary operational mode for the node-enabled logistics receptacle is a normal operation of the node-enabled logistics receptacle at the predetermined new location.

(443) In a further embodiment of method **3400**, the secondary operational mode for the node-enabled logistics receptacle may be a decommissioned mode of operation for the node-enabled logistics receptacle. For example, the secondary operational mode for the node-enabled logistics receptacle may be a decommissioned mode of operation for the node-enabled logistics receptacle once the sensor-based node has detected the movement associated with the node-enabled logistics receptacle. More specifically, the decommissioned mode of operation for the node-enabled logistics receptacle may be implemented as a low-power operational state of the node-enabled logistics receptacle as the node-enabled logistics receptacle is placed at an inventory location for temporary storage; a non-operational state of the node-enabled logistics receptacle as the node-enabled logistics receptacle is placed at an inventory location for temporary storage; or a non-operational state of the node-enabled logistics receptacle as the node-enabled logistics receptacle is placed at a maintenance location for refurbishment.

(444) In still further embodiments of method **3400**, the step of detecting **3405** may have the sensor-based node disposed within the node-enabled logistics receptacle detecting a replacement movement associated with the node-enabled logistics receptacle as the movement as the node-enabled logistics receptacle is replacing another logistics receptacle. As such, method **3400** may also include, after the step of detecting the replacement movement, the step of changing, by the sensor-based node, a current operational mode for the node-enabled logistics receptacle to a secondary operational mode for the node-enabled logistics receptacle, where the current operational mode for the node-enabled logistics receptacle is a decommissioned mode of operation for the node-enabled logistics receptacle and the secondary operational mode for the node-enabled logistics receptacle comprises a newly commissioned mode of operation for the node-enabled logistics receptacle. In such an embodiment, detecting the replacement movement may be implemented as detecting, by the sensor-based node disposed within the node-enabled logistics receptacle, the replacement movement prior to reaching a predetermined location (e.g., where the predetermined location is a prior location of a second node-enabled logistics receptacle before the second node-enabled logistics receptacle was moved away from the prior location, or where the predetermined location is a geolocation associated with a previous location of a currently decommissioned node-enabled logistics receptacle being replaced by the node-enabled logistics receptacle).

(445) Further still, another embodiment of method **3400** may have the step of detecting the replacement movement implemented by the sensor-based node disposed within the node-enabled logistics receptacle detecting the replacement movement prior to reaching a geofence perimeter relative to a predetermined location (e.g., perimeter **3320** relative to location **3305**) that was previously associated with a second node-enabled logistics receptacle prior to when the second

node-enabled logistics receptacle was decommissioned. Here, the step of changing the current operational mode for the node-enabled logistics receptacle to the secondary operational mode may include changing the current operational mode for the node-enabled logistics receptacle from the decommissioned mode of operation to the newly commissioned mode of operation upon arrival at the predetermined location or upon detecting the node-enabled logistics receptacle is within the geofence perimeter relative to the predetermined location.

(446) FIG. 35 is a flow diagram illustrating another exemplary improved method for monitoring and initiating a logistics response related to a node-enabled logistics receptacle (e.g., receptacle 150a) to be serviced by a logistics asset (e.g., logistics asset 700a) in accordance with an embodiment of the invention. Referring now to FIG. 35, exemplary method 3500 for monitoring and initiating a logistics response related to a node-enabled logistics receptacle (e.g., exemplary node-enabled logistics receptacle 150a) to be serviced by a logistics asset (e.g., exemplary logistics asset 700a) is illustrated beginning with step 3505.

(447) At step 3505, method 3500 begins with a sensor-based node disposed within the node-enabled logistics receptacle detecting sensor data reflecting a condition of the node-enabled logistics receptacle. The sensor data is indicative of an inability of the node-enabled logistics receptacle to participate in a previously scheduled logistics operation to be conducted by the logistics asset relative to the node-enabled logistics receptacle. For example, an embodiment of step 3505 may be implemented with the sensor-based node disposed within the node-enabled logistics receptacle detecting movement associated with the node-enabled logistics receptacle based upon the sensor data reflecting the condition of the node-enabled logistics receptacle. Stated another way, an embodiment may have the condition of the node-enabled logistics receptacle in step 3505 be motion associated with the node-enabled logistics receptacle (e.g., a tilt movement detected by a tilt sensor, an inertial movement detected by an inertial sensor, an acceleration detected by an accelerometer sensor, and/or motion relative to an external environment of the node-enabled logistics receptacle as detected by an externally focused motion sensor).

(448) In another embodiment, the condition of the node-enabled logistics receptacle in step 3505 may be a location change of the node-enabled logistics receptacle (e.g., a change in physical location as detected by location circuitry coupled to the sensor-based node, a change in proximity to at least one object disposed external to the node-enabled logistics receptacle as detected by a proximity sensor coupled to the sensor-based node, and/or a change in location coordinates as detected by location circuitry coupled to the sensor-based node as the at least one sensor coupled to the sensor-based node).

(449) In still another embodiment, the condition of the node-enabled logistics receptacle in step 3505 may be a position change of the node-enabled logistics receptacle (e.g., a change in orientation of the node-enabled logistics receptacle, a position change detected by a wireless communication sensor coupled to the sensor-based node, a position change detected by a wireless communication interface of the sensor-based node, and/or a position change detected by at least one millimeter wave sensor coupled to the sensor-based node).

(450) In yet another embodiment, the condition of the node-enabled logistics receptacle in step 3505 may be at least one of (a) motion associated with the node-enabled logistics receptacle using a first sensor coupled to the sensor-based node and (b) a change in location of the node-enabled logistics receptacle using a second sensor coupled to the sensor-based node. For example, such motion may be a tilt movement detected by a tilt sensor as the first sensor coupled to the sensor-based node; an inertial movement detected by an inertial sensor as the first sensor coupled to the sensor-based node; an acceleration detected by an accelerometer sensor as the first sensor coupled to the sensor-based node; and/or motion relative to an external environment of the node-enabled logistics receptacle as detected by an externally focused motion sensor as the first sensor coupled to the sensor-based node. Furthermore, the change in location may be a change in location as detected by location circuitry coupled to the sensor-based node as the second sensor coupled to the sensor-

based node; a change in proximity to at least one object disposed external to the node-enabled logistics receptacle by a proximity sensor coupled to the sensor-based node as the second sensor coupled to the sensor-based node; a change in location coordinates by location circuitry coupled to the sensor-based node as the second sensor coupled to the sensor-based node.

(451) In even more detail, an embodiment of method **3500** may be implemented as having the condition of the node-enabled logistics receptacle being at least one of (a) motion associated with the node-enabled logistics receptacle using a first sensor coupled to the sensor-based node; (b) a change in location of the node-enabled logistics receptacle using a second sensor coupled to the sensor-based node; and (c) a change in position of the node-enabled logistics receptacle using a third sensor coupled to the sensor-based node.

(452) At step **3510**, method **3500** has the sensor-based node transmitting an alert notification to a backend server. Here, the alert notification identifies the node-enabled logistics receptacle and informs the backend server of the movement in response to detecting the sensor data indicative of the inability of the node-enabled logistics receptacle to participate in the previously scheduled logistics operation.

(453) At step **3515**, method **3500** proceeds with the backend server alerting the logistics asset about the detected movement associated with the node-enabled logistics receptacle causing the logistics asset to alter a dispatched logistics operation to be conducted by the logistics asset relative to the node-enabled logistics receptacle.

(454) A further embodiment of method **3500** may, for example and after detecting movement associated with the node-enabled logistics receptacle based upon the sensor data reflecting the condition of the node-enabled logistics receptacle, include the further steps of (a) detecting, by the sensor-based node, an updated location of the node-enabled logistics receptacle after no longer detecting the movement associated with the node-enabled logistics receptacle; and (b) transmitting, by the sensor-based node, the updated location of the node-enabled logistics receptacle to the backend server. In this embodiment, the alerting step **3515** may be implemented as alerting, by the backend server, the logistics asset about the updated location of the node-enabled logistics receptacle causing the logistics asset to alter the dispatched logistics operation to be conducted by the logistics asset relative to the node-enabled logistics receptacle. In more detail, step **3515** may be implemented with the backend server alerting the logistics asset about the movement associated with the node-enabled logistics receptacle and the updated location of the node-enabled logistics receptacle causing the logistics asset to alter the dispatched logistics operation to be conducted by the logistics asset relative to the node-enabled logistics receptacle.

(455) Another embodiment of method **3500** may, for example and after detecting movement associated with the node-enabled logistics receptacle based upon the sensor data reflecting the condition of the node-enabled logistics receptacle, include the following steps after step **3510** of (a) detecting, by the sensor-based node, an updated location of the node-enabled logistics receptacle after transmitting the alert notification and no longer detecting the movement associated with the node-enabled logistics receptacle; and (b) transmitting, by the sensor-based node, the updated location of the node-enabled logistics receptacle to the backend server. In this particular embodiment, step **3515** may be implemented as alerting, by the backend server, the logistics asset about the updated location of the node-enabled logistics receptacle causing the logistics asset to alter the dispatched logistics operation to be conducted by the logistics asset relative to the node-enabled logistics receptacle. More specifically, step **3515** may be implemented as with the backend server alerting the logistics asset about the movement associated with the node-enabled logistics receptacle and the updated location of the node-enabled logistics receptacle causing the logistics asset to alter the dispatched logistics operation to be conducted by the logistics asset relative to the node-enabled logistics receptacle.

(456) Still another embodiment of method **3500** may, for example and after detecting movement associated with the node-enabled logistics receptacle, include the step of detecting, by the sensor-

based on, an updated location of the node-enabled logistics receptacle after transmitting the alert notification in step **3510** and no longer detecting the movement associated with the node-enabled logistics receptacle. In such an embodiment, step **3510** may be implemented as transmitting, by the sensor-based node, the alert notification to the backend server, where the alert notification comprises (a) first notification data providing an identifier corresponding to the node-enabled logistics receptacle, (b) second notification data informing the backend server of the movement associated with the node-enabled logistics receptacle, and (c) third notification data providing the updated location of the node-enabled logistics receptacle. In such an embodiment, step **3515** may be implemented with the backend server alerting the logistics asset about the movement associated with the node-enabled logistics receptacle and the updated location of the node-enabled logistics receptacle causing the logistics asset to alter the dispatched logistics operation to be conducted by the logistics asset relative to the node-enabled logistics receptacle.

(457) In still another embodiment of method **3500**, as part of detecting movement associated with the node-enabled logistics receptacle based upon the sensor data reflecting the condition of the node-enabled logistics receptacle those skilled in the art will appreciate that such detected movement may be associated with intentional movement of the node-enabled logistics receptacle, such as preplanned movement associated with the node-enabled logistics receptacle. In such an embodiment, method **3500** may also include, after step **3510**, the step of confirming, by the backend server, that the detected movement detected movement associated with the node-enabled logistics receptacle relates to the preplanned movement associated with the node-enabled logistics receptacle as identified in the alert notification.

(458) After detecting movement in such a further embodiment of method **3500**, method **3500** may also have the operational mode for the node-enabled logistics change as a result of such preplanned movement. For example, such an embodiment may include, after detecting the preplanned movement, a step where the sensor-based node changes a current operational mode for the node-enabled logistics receptacle to a secondary operational mode for the node-enabled logistics receptacle. More specifically, such a changing step may be implemented with the sensor-based node changing the current operational mode for the node-enabled logistics receptacle to the secondary operational mode for the node-enabled logistics receptacle once the sensor-based node disposed within the node-enabled logistics receptacle detects a cessation of movement associated with the node-enabled logistics receptacle corresponding to an end of the preplanned movement associated with the node-enabled logistics receptacle. The secondary operational mode for the node-enabled logistics receptacle may, for example, be normal operation of the node-enabled logistics receptacle at a new location (e.g., a predetermined address associated with the preplanned movement) or be normal operation of the node-enabled logistics receptacle at a new location as confirmed by the backend server to the sensor-based node. In more detail, method **3500** may include the steps of (a) detecting, by the sensor-based node, a cessation of movement associated with the node-enabled logistics receptacle corresponding to an end of the preplanned movement associated with the node-enabled logistics receptacle; (b) reporting, by the sensor-based node, an updated location to the backend server; and (c) receiving, by the sensor-based node, a confirmation message from the backend server that the updated location of the node-enabled logistics receptacle is a predetermined new location for the node-enabled logistics receptacle. In such a situation, the secondary operational mode for the node-enabled logistics receptacle may be normal operation of the node-enabled logistics receptacle at the predetermined new location.

(459) In other embodiments of method **3500**, the secondary operational mode for the node-enabled logistics receptacle may be implemented as a decommissioned mode of operation for the node-enabled logistics receptacle (e.g., a decommissioned mode of operation for the node-enabled logistics receptacle once the sensor-based node has detected the movement associated with the node-enabled logistics receptacle). In more detail, the decommissioned mode of operation for the node-enabled logistics receptacle may, for example, be implemented as a low-power operational

state of the node-enabled logistics receptacle as the node-enabled logistics receptacle is placed at an inventory location for temporary storage; a non-operational state of the node-enabled logistics receptacle as the node-enabled logistics receptacle is placed at an inventory location for temporary storage; or a non-operational state of the node-enabled logistics receptacle as the node-enabled logistics receptacle is placed at a maintenance location for refurbishment.

(460) In some embodiments of method **3500**, the node-enabled logistics receptacle may be in use as replacement hardware where it shifts to a secondary operational mode from a currently decommissioned mode of operation. For example, an embodiment of method **3500** may detect movement in step **3505** with the sensor-based node disposed within the node-enabled logistics receptacle detecting a replacement movement associated with the node-enabled logistics receptacle as the movement; and then after such a detection, further include the step of changing, by the sensor-based node, a current operational mode for the node-enabled logistics receptacle to a secondary operational mode for the node-enabled logistics receptacle, where the current operational mode for the node-enabled logistics receptacle comprises a decommissioned mode of operation for the node-enabled logistics receptacle and the secondary operational mode for the node-enabled logistics receptacle comprises a newly commissioned mode of operation for the node-enabled logistics receptacle.

(461) In more detail, the step of detecting the replacement movement may be performed prior to reaching a predetermined location (e.g., a prior location of a second node-enabled logistics receptacle before the second node-enabled logistics receptacle was moved away from the prior location or a geolocation associated with a previous location of a currently decommissioned node-enabled logistics receptacle being replaced by the node-enabled logistics receptacle). The step of detecting the replacement movement may also be implemented with the sensor-based node disposed within the node-enabled logistics receptacle detecting the replacement movement prior to reaching a geofence perimeter relative to a predetermined location that was previously associated with a second node-enabled logistics receptacle prior to when the second node-enabled logistics receptacle was decommissioned.

(462) The step of changing the current operational mode for the node-enabled logistics receptacle to the secondary operational mode may be implemented as changing the current operational mode for the node-enabled logistics receptacle from the decommissioned mode of operation to the newly commissioned mode of operation upon arrival at the predetermined location or upon detecting the node-enabled logistics receptacle is within the geofence perimeter relative to the predetermined location.

(463) Another embodiment of method **3500** may implement step **3505** with the sensor-based node disposed within the node-enabled logistics receptacle detecting a sensed maintenance condition associated with the node-enabled logistics receptacle based upon the sensor data reflecting the condition of the node-enabled logistics receptacle. In such an embodiment, method **3500** may include, after step **3505**, the step of changing, by the sensor-based node, a current operational mode for the node-enabled logistics receptacle to a secondary operational mode for the node-enabled logistics receptacle, where the secondary operational mode for the node-enabled logistics receptacle is a decommissioned mode of operation for the node-enabled logistics receptacle at a current location of the node-enabled logistics receptacle. In more detail, changing the current operational mode for the node-enabled logistics receptacle to the decommissioned mode of operation may involve causing the sensor-based node to temporarily enter the decommissioned mode of operation while remaining at the current location of the node-enabled logistics receptacle awaiting a maintenance operation on the node-enabled logistics receptacle (e.g., a dispatched maintenance operation on the node-enabled logistics receptacle, such as a dispatched maintenance operation on the node-enabled logistics receptacle initiated by the backend server in response to the alert notification).

(464) In a further embodiment of method **3500**, the sensor-based node disposed within the node-

enabled logistics receptacle may, at step **3505**, detect an inoperative condition associated with the node-enabled logistics receptacle based upon the sensor data reflecting the condition of the node-enabled logistics receptacle. In more detail in such an embodiment, method **3500** may, after the step of detecting the inoperative condition, include changing, by the sensor-based node, a current operational mode for the node-enabled logistics receptacle to a secondary operational mode for the node-enabled logistics receptacle, where the secondary operational mode for the node-enabled logistics receptacle is a decommissioned mode of operation for the node-enabled logistics receptacle at a current location of the node-enabled logistics receptacle. Such a step of changing the current operational mode for the node-enabled logistics receptacle to the decommissioned mode of operation may be implemented as causing the sensor-based node to enter the decommissioned mode of operation while awaiting removal from the current location of the node-enabled logistics receptacle.

(465) On-Demand Deployable Logistics Capacity

(466) In additional embodiments, a further improvement may involve on-demand deployment of a deployable mobile logistics receptacle to help address surges in demand at, for example, the location of an existing exemplary node-based logistics receptacle. In general, an existing exemplary node-based logistics receptacle may be experiencing capacity or occupancy issues and report event information to the backend server, which may then respond by activating such a deployable mobile logistics receptacle to help address the capacity or occupancy issues relative to the reporting node-based logistics receptacle.

(467) FIGS. **51-55** provide illustrations related to such exemplary embodiments that involve systems providing on-demand deployment of a deployable mobile logistics receptacle. FIG. **51** is a diagram illustrating aspects of an exemplary system for providing an on-demand deployable logistics capacity related to and in response to an exemplary reporting node-based logistics receptacle in accordance with an embodiment of the invention. Referring now to FIG. **51**, exemplary connected node-based logistics receptacle **51150** is shown operative to communicate with backend server **100** with components similar to exemplary logistics receptacle **150** described relative to FIG. **2**. Those skilled in the art will appreciate that exemplary connected logistics receptacle **51150** shown in FIG. **51** is similarly structured to exemplary connected/node-based logistics receptacle **150** and **150a**, with the exception that exemplary receptacle **51150** is equipped with an exemplary bridge node **51200** that transmits a status update message **51005** including information related to event information indicating a demand surge condition existing relative to receptacle **51150**.

(468) As such, an exemplary system providing an on-demand deployable logistics capacity related to a reporting node-based logistics receptacle as shown in FIG. **48** includes exemplary backend server **100** and an exemplary deployable mobile logistics receptacle **51020**.

(469) In this embodiment, the system's deployable mobile logistics receptacle is configured (as explained in more detail below) and operative to receive parcel items at a deployed location (such as at or near the reporting node-based logistics receptacle **51150**). The system's backend server **100** in this embodiment is in communication with the reporting node-based logistics receptacle **51150**. As such, exemplary backend server **100** is programmatically configured to be operative to receive a message (such as status update message **51005**) that includes event information from the reporting node-based logistics receptacle **51150**. The event information indicates a demand surge condition exists relative to the reporting node-based logistics receptacle **51150**.

(470) In more detail, backend server **100** may receive the event information from the reporting node-based logistics receptacle **51150** by being further operative to receive status update message **51005** from the reporting node-based logistics receptacle **51150**, where the status update message **51005** includes at least the event information reflecting or otherwise indicating at least a change in state of the reporting node-based logistics receptacle (e.g., a deposit was made within the temporary storage area of receptacle **51150**, and the like). Backend server **100** may determine that

the demand surge condition exists relative to the reporting node-based logistics receptacle **51150** based upon the event information and information stored within management profile **835** maintained by the backend server **100** on the reporting node-based logistics receptacle **51150**. As previously noted, exemplary management profile **835** is generally a data structure generated, maintained, and updated by backend server **100** with information on operations (e.g., history and use) of particular connected logistics receptacles (e.g., exemplary connected logistics receptacle **51150**), their respective components, and logistics assets used to service the particular connected logistics receptacle. In particular, an exemplary management profile **835** used in system embodiments for on-demand deployment of a deployable mobile logistics receptacle may have the management profile including information relating to a pattern of use of the reporting node-based logistics receptacle **51150**; information relating to a pattern on detected threshold capacity conditions for the reporting node-based logistics receptacle **51150**; information relating to a pattern of overflow conditions for the reporting node-based logistics receptacle **51150**; and/or prior/historic use information on the reporting node-based logistics receptacle **51150** (generally and/or specific to particular receptacle components on receptacle **51150**, such as the entrance opening, the temporary storage area, the access door, and the area outside but proximate to the receptacle **51150**). Such historic use information may, for example, include a pattern of delivery events for the reporting node-based logistics receptacle **51150**; a pattern of pickup events for the reporting node-based logistics receptacle **51150**; and/or an overload pattern profile identifying a frequency of reaching an overload condition for the reporting node-based logistics receptacle **51150**.

(471) In one example, backend server **100** may determine that the demand surge condition exists relative to the reporting node-based logistics receptacle **51150** when the event information from message **51005** indicates at least a threshold number of parcels are currently maintained within the node-based logistics receptacle **51150**, when the event information from message **51005** indicates at least a threshold level of contents within the reporting node-based logistics receptacle **51150**, when the event information from message **51005** indicates at least a threshold weight of contents exists within the reporting node-based logistics receptacle **51150**, when the event information from message **51005** includes indicia of an overflow condition for the reporting node-based logistics receptacle **51150**, and/or when the event information from message **51005** includes indicia that the reporting node-based logistics receptacle **51150** is within a threshold range of an overflow condition for that reporting node-based logistics receptacle **51150**. Such threshold information relative to reporting node-based logistics receptacle **51150** may be available to backend server **100** as part of exemplary management profile **835**.

(472) In a further example, the system's backend server **100** may be programmatically configured to be operative to receive the event information from the reporting node-based logistics receptacle **51150** by being further operative to receive the status update message **51005** from the reporting node-based logistics receptacle **51150** (where the status update message **51005** includes at least event information indicating at least a change in state of the reporting node-based logistics receptacle **51150**); compare the event information with management profile **835**, which defines historic use information on the reporting node-based logistics receptacle **51150**; and determine that the demand surge condition exists relative to the reporting node-based logistics receptacle **51150** based upon the comparison.

(473) Once backend server **100** determines that the demand surge condition exists relative to the reporting node-based logistics receptacle **51150**, exemplary backend server **100** is programmatically configured to be further operative to send an exemplary activation message **51010** to the deployable mobile logistics receptacle **51020** to initiate deployment of the deployable mobile logistics receptacle **51020** to a location of the reporting node-based logistics receptacle **51150** as the deployed location of the deployable mobile logistics receptacle **51020**.

(474) The system's exemplary deployable mobile logistics receptacle **51020** is operative to receive the activation message from the backend server, move from a current position of the deployable

mobile logistics receptacle to a deployed location in response to the activation message, and provide, at the deployed location, the on-demand deployable logistics capacity related to a subsequent shipping deposit. Such a deployed location, for example, may be a location within a predetermined distance from the location of the reporting node-based logistics receptacle **51150**. In more detail, the deployment location may be a location within a predetermined distance from the location of the reporting node-based logistics receptacle **51150**, where such a predetermined distance is maintained as part of management profile **835** stored by the backend server **100** regarding the reporting node-based logistics receptacle **51150**. In the example shown in FIG. **51**, exemplary deployable mobile logistics receptacle **51020** receives activation message **51010** from backend server **100**. In response to the activation message **51010**, exemplary deployable mobile logistics receptacle **51020** begins at position A prior to deployment and moves that current position to the deployed location (e.g., position B at a deployed location at, near, or otherwise substantially close to the location of reporting node-based logistics receptacle **51150** so as to be within a particular predetermined distance from receptacle **51150**).

(475) Exemplary deployable mobile logistics receptacle **51020** may be implemented in various ways so that it is responsive to the activation message, be movable between different locations, and provide similar logistics services for accepting and providing access to delivery items (e.g., letters, packages, parcels, and other objects being shipped). FIGS. **52A-52C** are diagrams of different exemplary embodiments of deployable mobile logistics receptacle **51020a-c** in accordance with various embodiments of the invention.

(476) Referring now to FIG. **52A**, an example deployable mobile logistics receptacle **51020** is shown as exemplary deployable mobile logistics receptacle **51020a**. Exemplary deployable mobile logistics receptacle **51020a** is a wheel-based movable apparatus that can receive and temporarily maintain custody of delivery/parcel items as well as provide selective access to such delivery items. In one embodiment, exemplary deployable mobile logistics receptacle **51020a** may be moved via human control. In other embodiments, exemplary deployable mobile logistics receptacle **51020a** may be moved via other mechanisms, such as being towed or propelled under the control of an externally disposed human operator.

(477) As shown in FIG. **52A**, exemplary deployable mobile logistics receptacle **51020a** is implemented as having a movable container housing **52005a**, an entrance opening **52156a/52155a**, a temporary storage area **52205a**, a selectively accessible retrieval door **52160a**, a sensor-enabled node **52505a**, sensors **52510a**, **52515a**, **52520a**, and a wireless transceiver **52500a**. The exemplary movable container housing **52005a** is generally a housing within which the parcel items are received at the deployed location. The exemplary entrance opening **52156a/52155a** is disposed on the movable container housing **52005a** and provides an opening through which the parcel items are received at the deployed location. As shown in FIG. **52A**, exemplary entrance door **52156a** is disposed on the movable container housing **52005a** and can be articulated to expose an opening through housing **52005a** and entrance opening chute **52155a**. Exemplary temporary storage area **52205a** is disposed within the movable container housing **52005a** as a temporary holding area for maintaining the parcel items as they are received and deposited at the deployed location.

Exemplary selectively accessible retrieval door **52160a**, which may include a lock or other security measure to selectively open/close the door, provides selective access to the temporary storage area **52205a** within the mobile container housing **52005a**. Exemplary sensor-enabled node **52505a** is shown mounted to the housing **52005a** and coupled to each of holding area sensor **52510a**, entrance opening sensor **52515a**, and access door sensor **52520a**. Those skilled in the art will appreciate that exemplary deployable mobile logistics receptacle **51020a** may be equipped with further types of sensors (much like any of the sensors that are described herein as being used onboard an exemplary node-based logistics receptacle, such as receptacle **150**). Exemplary wireless transceiver **52500a** disposed on the movable container housing **52005a** is operatively coupled to the sensor-enabled node **52505a** and operative to receive the activation message **51010** from

backend server **100** and otherwise communicate with server **100** via network **105**.

(478) In more detail, exemplary sensor-enabled node **52505a** used in exemplary deployable mobile logistics receptacle **51020a** and disposed on the movable container housing **52005a** may be operative to change a mode of operation from a low power mode to an active mode of operation in response to the activation message **51010** as received by the wireless transceiver **52500a**. Once in the active mode of operation, exemplary sensor-enabled node **52505a** may then be operative to detect a change in state of the deployable mobile logistics receptacle **51150** based upon sensor data generated by the sensor-enabled node **52505a**, such as sensor data provided by one of sensors **52510a**, **52515a** relative to at least one of the entrance opening **52155a/52156a** and the temporary storage area **52205a**. In another example, exemplary sensor-enabled node **52505a** may be operative to detect the change in state of the deployable mobile logistics receptacle **51020a** based upon sensor data generated by the sensor-enabled node **52505a**, such as sensor data provided by one of sensors **52510a**, **52515a**, and **52520a** relative to at least one of the entrance opening **52155a/52156a**, the temporary storage area **52205a**, and the selectively accessible retrieval door **52160a**. In still another example, exemplary sensor-enabled node **52505a** may be programmatically configured to be further operative to transmit mobile event information to the backend server **100** in response to a detected change in state of the deployable mobile logistics receptacle **52020a**.

(479) Referring now to FIG. **52B**, another exemplary deployable mobile logistics receptacle **51020** is shown as a mobile delivery vehicle-based logistics receptacle **51020b**. Exemplary deployable mobile logistics receptacle **51020b** is a vehicle-based movable apparatus that, like receptacle **51020a**, can receive and temporarily maintain custody of delivery/parcel items as well as provide selective access to such delivery items. In one embodiment, those skilled in the art will appreciate that exemplary mobile delivery vehicle-based logistics receptacle **51020b** may be moved via human control of the mobile delivery vehicle (e.g., truck, van, car, or other vehicle). Such a mobile delivery vehicle may, for example, be engine-powered, solar-powered, electric-powered, human-powered/pedaled, or hybrid-powered with a combination of such propulsion techniques implemented on the mobile delivery vehicle.

(480) As shown in FIG. **52B**, mobile delivery vehicle-based logistics receptacle **51020b** is implemented as having a movable delivery vehicle **52005b**, a vehicle-based entrance opening **52156b/52155b**, a vehicle-based temporary storage area **52205b**, a selectively accessible retrieval door **52160b**, a sensor-enabled node **52505b**, sensors **52510b**, **52515b**, **52520b**, and a wireless transceiver **52500b**. The exemplary mobile delivery vehicle **52005b** has a portion that operates as type of housing within which the parcel items are received at the deployed location. This may, in some instances, be a housing structure on the mobile vehicle platform where the housing structure provides for storage of any accepted or to be picked up parcel items.

(481) The exemplary vehicle-based entrance opening **52156b/52155b** is disposed on the mobile delivery vehicle **52005b** (e.g., along a side of vehicle **52005b**) and provides an opening through which the parcel items are received at the deployed location. As shown in FIG. **52B**, exemplary entrance door **52156b** is disposed on the vehicle **52005b** and can be articulated to expose an opening through a wall/side of vehicle **52005b** and entrance opening chute **52155b**. Exemplary temporary storage area **52205b** is disposed within the mobile delivery vehicle **52005b** as a temporary holding area for maintaining the parcel items as they are received and deposited at the deployed location. Exemplary selectively accessible retrieval door **52160b**, which may include a lock or other security measure to selectively open/close the door, is shown disposed on an end of mobile delivery vehicle **52005b** and provides selective access to the temporary storage area **52205b** within the mobile delivery vehicle **52005b**.

(482) Exemplary sensor-enabled node **52505b** (much like that with exemplary node **52505a**) is shown mounted to the vehicle **52005b** and coupled to each of holding area sensor **52510b**, vehicle-based entrance opening sensor **52515b**, and access door sensor **52520b**. Those skilled in the art will appreciate that exemplary deployable mobile logistics receptacle **51020b** may be equipped with

further types of sensors (much like any of the sensors that are described herein as being used onboard an exemplary node-based logistics receptacle, such as receptacle **150**). Exemplary wireless transceiver **52500b** disposed on the mobile delivery vehicle **52005b** is operatively coupled to the sensor-enabled node **52505b** and operative to receive the activation message **51010** from backend server **100** and otherwise communicate with server **100** via network **105**.

(483) In more detail, exemplary sensor-enabled node **52505b** used in exemplary deployable mobile logistics receptacle **51020b** (i.e., mobile delivery vehicle-based logistics receptacle **51020b**) and disposed on the mobile delivery vehicle **52005b** may be operative to change a mode of operation from a low power mode to an active mode of operation in response to the activation message **51010** as received by the wireless transceiver **52500b**. Once in the active mode of operation, exemplary sensor-enabled node **52505b** may then be operative to detect a change in state of the mobile delivery vehicle-based logistics receptacle **51020b** based upon sensor data generated by the sensor-enabled node **52505b**, such as sensor data provided by one of sensors **52510b**, **52515b** relative to at least one of the vehicle-based entrance opening **52155b/52156b** and the vehicle-based temporary storage area **52205b**. In another example, exemplary sensor-enabled node **52505b** may be operative to detect the change in state of the mobile delivery vehicle-based logistics receptacle **51020b** based upon sensor data generated by the sensor-enabled node **52505b**, such as sensor data provided by one of sensors **52510b**, **52515b**, and **52520b** relative to at least one of the vehicle-based entrance opening **52155b/52156b**, the vehicle-based temporary storage area **52205b**, and the selectively accessible retrieval door **52160b** at the back of the vehicle **52005b**. In still another example, exemplary sensor-enabled node **52505b** may be programmatically configured to be further operative to transmit mobile event information to the backend server **100** in response to a detected change in state of the deployable mobile logistics receptacle **52020a**.

(484) Referring now to FIG. **52C**, another exemplary deployable mobile logistics receptacle **51020** is shown as a deployable mobile autonomous logistics receptacle (generally referred to as a type of deployable autonomous mobile container **51020c**). Exemplary deployable autonomous container **51020c** is a self-moving apparatus that, like receptacles **51020a** and **51020b**, can receive and temporarily maintain custody of delivery/parcel items as well as provide selective access to such delivery items. Those skilled in the art will appreciate that exemplary deployable autonomous container **51020c** generally accepts instructions (that may include a destination location) and is operative to navigate from its initial position to the desired destination based upon location circuitry and navigation sensors that help container **51020c** autonomously track where it is, where it is going, and avoid and navigate obstacles in its path towards its destination.

(485) As shown in FIG. **52C**, an embodiment of exemplary deployable autonomous container **51020c** is implemented as having a container housing **52005c**, an entrance opening **52156c/52155c**, a temporary storage area **52205c**, a selectively accessible retrieval door **52160c**, an autonomous controller **52600**, a propulsion and steering system **52610**, mobile container navigation sensors **52615**, container status sensors **52510b**, **52515b**, **52520b**, a wireless transceiver **52500c**, and location circuitry (GPS) **52605**. In more detail, exemplary container housing **52005c** generally provides structural walls, bottom and top that collectively define a type of container within which to temporarily maintain parcel items that are being dropped off or being maintained for pickup. The exemplary entrance opening **52156c/52155c** is disposed on the container housing **52005c** and provides an opening through which the parcel items are received at the deployed location. Exemplary temporary storage area **52205c**, which maintains the parcel items received at the deployed location, is disposed within the container housing **52005c**. Exemplary selectively accessible retrieval door **52160c**, which may include a lock or other security measure to selectively open/close the door, is shown disposed on container housing **52005c** and provides selective access to the temporary storage area **52205c**.

(486) As shown in FIG. **52C**, exemplary autonomous controller **52600** is generally disposed on the container housing **52005c** but interfaces with each of the propulsion and steering system **52610**,

mobile container navigation sensors **52615**, container status sensors **52510b**, **52515b**, **52520b**, wireless transceiver **52500c**, and location circuitry (GPS) **52605**. The exemplary autonomous controller **52600** may be implemented with at least one controller or processor that is operatively connected to sensors (e.g., mobile container navigation sensors **52615**, container status sensors **52510b**, **52515b**, **52520b**) through hardwired and/or wireless interfacing circuitry or dedicated sensor processing circuitry that may buffer sensor data and process the sensor data. Those skilled in the art will appreciate that exemplary autonomous controller **52600** has the power and self-governance in the performance of sensor processing and responsive control functions that allow the exemplary deployable autonomous container **51020c** to move, avoid collisions, navigate towards specified locations, and effect actuated and articulated interactions while moving or stationary as part of the logistics operations described herein.

(487) In more detail, such an exemplary autonomous controller **52600** may be implemented as an onboard processing module or system with one or more processors or controllers (such as CPUs/GPUs) and program code or software modules that execute on this platform to programmatically configure the autonomous controller **52600** to be operative to provide the autonomous capability to run the exemplary deployable autonomous container **51020c** as discussed herein. Further, such an exemplary autonomous controller **52600** may also have redundant, fault-tolerant features for safety control, as well as parallel sensing and parallel processing that allows for common and/or distributed management for operations of such an exemplary autonomous controller **52600**. For example, an embodiment of autonomous controller **52600** may deploy distributed management where tasks may be offloaded from a particular processor or system within autonomous controller **52600** and assigned (permanently or dynamically) to another processor or system (e.g., where a sensor may have processing of its sensor data built-in, which offloads the sensor data processing from another processor or system within an embodiment of autonomous controller **52600**).

(488) Those skilled in the art will appreciate that exemplary autonomous controller **52600** used in embodiments described herein may, for example, be implemented with an NVIDIA® Jetson™ Xavier AI embedded computing module for autonomous machines that features a 512-Core Volta GPU with Tensor Cores, 8-Core ARM 64-Bit CPU, dual NVDLA deep learning accelerators, video processor for up to 2× 4K 60 fps encode and decode, seven-way VLIW vision processor and 16 GB 256-Bit LPDDR4 memory. Another embodiment of an exemplary autonomous controller **52600** may be implemented with an NVIDIA® DRIVE platform level solution powered by two NVIDIA DRIVE Orin™ systems-on-a-chip (SoC) that feature ARM Cortex-A78AE CPU cores and an NVIDIA® DRIVE Hyperion sensor suite. Still another embodiment of such an exemplary autonomous controller **52600** may, for example, be implemented with an ARM Cortex-A76AE autonomous processor with superscalar, out-of-order processing and split-lock flexibility to allow for a split mode with highest multicore performance or split mode for advanced multicore fault-tolerance features for built-in safety and diagnostic functionality at a hardware level (e.g., fail-operational or fault-tolerant capability—where the control system detects a control system fault with memory, processing, data bus, or other control system sub-systems, reports the fault, and continues operation in a degraded mode as needed).

(489) As shown in FIG. 52C, exemplary propulsion and steering system **52610** is disposed on the container housing **52005c**. Exemplary propulsion and steering system **52610**, in general, is responsive to propulsion and steering control signals from the autonomous controller **52600** that cause changes to directional movement of the deployable autonomous mobile container **51020c**. Exemplary propulsion and steering system **52610** provides kinetic movement related power for deployable autonomous mobile container **51020c**. Those skilled in the art will appreciate that such power may be engine-powered, solar-powered, electric-powered, or hybrid-powered with a combination of such propulsion techniques implemented to move exemplary deployable autonomous mobile container **51020c**. Transferring such power from exemplary propulsion and

steering system **52610** to ground contact surfaces may, for example, take the form of wheels or other propulsion tracks selected for enhanced traction via tread/track materials and patterns so as to help maneuver through and navigate uneven streets, broken/buckled sidewalks, tree roots, standing water, grassy sloped terrain, and the like on its way to its deployed location. In some embodiments, exemplary propulsion and steering system **52610** may power less than all wheels on container **51020c** while all wheels may be powered in other embodiments. Likewise, exemplary propulsion and steering system **52610** may steer less than all wheels on container **51020c** in some embodiments, while all wheels may be steerable in other embodiments.

(490) Exemplary mobile container navigation sensors **52615** are coupled to the autonomous controller **52600** and disposed on housing **52005c** in different locations so as to monitor the environment proximate the deployable autonomous mobile container **51020c**—e.g., in front of container **51020c** relative to its direction of travel, as well as behind and on each side. This allows autonomous controller **52600** to receive robust external environmental sensory data from the mobile container navigation sensors **52615** to enable collision free travel and navigation when moving to and from different locations. Those skilled in the art will appreciate that exemplary mobile container navigation sensors **52615** may be of a variety of types of sensors (e.g., motion sensors, proximity sensors, image sensors, video sensors, LiDAR sensors, depth sensors, infrared sensors, ultrasonic sensors, thermal sensors, and the like) and are operative to autonomously detect an object in the path of the deployable autonomous mobile container **51020c** and provide navigation feedback sensor data to the autonomous controller **52600** on the detected object.

(491) Exemplary container status sensors **52510c**, **52515c**, **52520c** are each coupled to the autonomous controller **52600** and each operative to detect a change in state of the deployable autonomous mobile container **51020c** based upon sensor data generated by at least one of the container status sensors **52510c**, **52515c**, **52520c** relative to at least one of the entrance opening **52156c/52155c**, temporary storage area **52205c**, and selectively accessible retrieval door **52160c**. As such, those skilled in the art will appreciate that exemplary container status sensors **52510c**, **52515c**, **52520c** may be used to monitor for deposit/pickup interactions with the deployable autonomous mobile container **51020c**.

(492) Exemplary wireless transceiver **52500c** is disposed on the container housing **52005c** of deployable autonomous mobile container **51020c** and is operatively coupled to the coupled to the autonomous controller **52600**. As used onboard the deployable autonomous mobile container **51020c**, the wireless radio transceiver **52500c** is operative to communicate with the backend server **100** disposed external to the deployable autonomous mobile container **51020c** receive the activation message **51010** from the backend server **100**.

(493) Exemplary location circuitry **52605**, such as a Global Positioning System (GPS) receiver and antenna, is disposed on the container housing **52005c** and also operatively coupled to the autonomous controller **52600**. In general, the location circuitry **52605** generates location data on a location of the deployable autonomous mobile container **51020c** and provides the location data to the autonomous controller **52600**. As such, exemplary location circuitry **52605** allows autonomous controller **52600** to self-determine its location or to determine its location by itself. In other examples, alternative circuitry and techniques may be relied upon for location circuitry **52605** (rather than GPS), such as location circuitry compatible with other satellite-based systems (e.g., the European Galileo system, the Russian GLONASS system, the Chinese Compass system), terrestrial radio-based positioning systems (e.g., cell phone tower-based or Wi-Fi-based systems), infrared positioning systems, visible light based positioning systems, and ultrasound-based positioning systems).

(494) In operation, the autonomous controller **52600** of exemplary autonomous mobile container **51020c** may be programmatically configured to be operative to cause the deployable autonomous mobile container to move from a current position of the deployable autonomous mobile container **51020c** (e.g., Position A) to the deployed location (e.g., Position B) in response to the activation

message **51010** by sending the propulsion and steering control signals to the propulsion and steering system **52610**. In more detail, moving from the current position to the deployed position has the autonomous controller **52600** of exemplary autonomous mobile container **51020c** receiving navigation sensor feedback as it navigates towards the deployed location while avoiding collisions, as well as revising the propulsion and steering control signals sent to the propulsion and steering system **52610** to correct speed, direction, and avoid objects in its path. Once at the deployed location (e.g., Position B shown in FIG. 51), an embodiment may have the autonomous controller **52600** of exemplary autonomous mobile container **51020c** being programmatically configured to be further operative to transmit mobile event information to the backend server **100** in response to a detected change in state of the deployable autonomous mobile container **51020c** based upon the sensor data generated by at least one of the container status sensors **52510c**, **52515c**, **52520c**.

(495) In a further embodiment, the autonomous controller **52600** of exemplary autonomous mobile container **51020c** may be programmatically operative to receive, using the wireless radio transceiver, the activation message **51010** from the backend server **100**; move from a current position of the deployable autonomous mobile container **51020c** to the deployed location in response to the activation message **51010**; and provide, at the deployed location, the on-demand deployable logistics capacity related to a subsequent shipping deposit.

(496) FIG. 53 is a diagram illustrating an embodiment of the system of FIG. 51 where the backend server **100** causes the exemplary reporting node-based logistics receptacle **51150** to show alternative deposit information related to the exemplary deployable mobile logistics receptacle **51020** in accordance with an embodiment of the invention. Referring now to FIG. 53, exemplary deployable mobile logistics receptacle **51020** is shown at its deployed location (Position B). Once located at this deployed position, an embodiment has the backend server being programmatically configured to be further operative to transmit an update message **53005** to the reporting node-based logistics receptacle **51150**. Receipt of the update message **53005** causes the reporting node-based logistics receptacle **51150** to generate a visible display message indicating alternative deposit information related to the deployable mobile logistics receptacle **51020**. Such a visible display message may be shown using externally disposed user interface **255** on the reporting node-based logistics receptacle **51150**. As previously noted, externally disposed user interface **255** may have one or more display, keys, status lights, touchscreens, buttons, switches, and/or speaker for interacting with a shipping customer and/or logistics personnel. In more detail, receipt of the update message **53005** may cause the reporting node-based logistics **51150** to generate a change in status light (e.g., an externally exposed status light part of interface **255**) on the reporting node-based logistics receptacle **51150** as the visible display message indicating the alternative deposit information related to the deployable mobile logistics receptacle **51020**. Alternatively, or in combination, receipt of the update message **53005** may cause the reporting node-based logistics **51150** to generate a change in what is shown on an external display screen (e.g., an exemplary display-based user interface part of interface **255**) on the reporting node-based logistics receptacle **51150** as the visible display message indicating the alternative deposit information related to the deployable mobile logistics receptacle **51020**. Such alternative deposit information related to the deployable mobile logistics receptacle **51020** may be related to and include information on the deployed location of the deployable mobile logistics receptacle **51020** so as to assist customers in using the deployable mobile logistics receptacle **51020** for subsequent drop off actions.

(497) A further embodiment may have the system's backend server **100** being programmatically configured to be further operative to transmit an update message **53005** to the reporting node-based logistics receptacle **51150** where the update message **53005** causes the reporting node-based logistics receptacle **51150** to wirelessly broadcast a status update message indicating alternative deposit information related to the deployable mobile logistics receptacle **51020**. Such a wirelessly broadcast status update message may thus allow wirelessly enabled customers to receive alternative deposit information related to the deployable mobile logistics receptacle **51020**, such as the

deployed location of the deployable mobile logistics receptacle **51020**.

(498) FIG. **54** is a diagram illustrating an embodiment of the system of FIG. **51** where the backend server **100** recalls the deployable mobile logistics receptacle **51020** in accordance with an embodiment of the invention. Those skilled in the art will appreciate that at some point in time, the usefulness of having the deployable mobile logistics receptacle **51020** deployed at Position B (its deployed location at or near the location of reporting node-based logistics receptacle **51150**) may change. This may, for example, be because the reporting node-based logistics receptacle **51150** may have been serviced and no longer have a demand surge condition existing. In other examples, this may be because the deployable mobile logistics receptacle **51020** itself reaches a particular level of capacity. Thus, an embodiment may have the system's backend server **100** being programmatically configured to be further operative to send a recall message **54005** to the deployable mobile logistics receptacle **51020** to initiate a recall of the deployable mobile logistics receptacle **51020** from the deployed location of the deployable mobile logistics receptacle **51020**. In a further embodiment, the system's backend server **100** may be programmatically configured to be further operative to transmit a recall message **54005** to the deployable mobile logistics receptacle **51020** to initiate a recall of the deployable mobile logistics receptacle **51020** from the deployed location of the deployable mobile logistics receptacle **51020**, and then transmit a recall update message **54010** to the reporting node-based logistics receptacle **51150**, the receipt of which causes the reporting node-based logistics receptacle **51150** to generate a visible display message indicating a change in operational status related to the deployable mobile logistics receptacle **51020**, indicating a recall status related to the deployable mobile logistics receptacle **51020**, and/or indicating a return to normal operation for the reporting node-based logistics receptacle **51150**. The system's deployable mobile logistics receptacle **51020** may also be further operative, in response to the recall message **54005**, to move from the deployed location (e.g., Position B shown in FIG. **54**) to a recall location (e.g., Position C shown in FIG. **54**). In one example, the recall location may be a logistics facility location capable of unloading the deployable mobile logistics receptacle **51020** and temporarily storing the deployable mobile logistics receptacle **51020** awaiting a further deployment of the deployable mobile logistics receptacle **51020**. In another example, the recall location may be a location of a mobile logistics vehicle (not shown in FIG. **54**, but similar to a delivery van associated with a logistics asset **700a**) capable of receiving the deployable mobile logistics receptacle **51020**.

(499) FIG. **55** is a diagram illustrating an embodiment of the system of FIG. **51** where the system's backend server **100** activates an exemplary replacement deployable mobile logistics receptacle in accordance with an embodiment of the invention. Referring now to FIG. **55**, the system's backend server **100** and deployed mobile logistics receptacle **51020** are shown once the deployed mobile logistics receptacle **51020** has been recalled. Here, there still may be a need to have a deployed mobile logistics receptacle at or near the reporting node-based logistics receptacle **51150** as it may still be in conditions corresponding to a demand surge condition (e.g., at capacity, in an overflow condition, still awaiting pickup servicing, and the like). In such a situation, an embodiment may have the system's backend server **100** being programmatically configured to be further operative to transmit a supplemental activation message **55005** to an exemplary replacement deployable mobile logistics receptacle **51020r** to initiate deployment of the replacement deployable mobile logistics receptacle **51020r** to the deployed location of the deployable mobile logistics receptacle **51020** (e.g., at or near the reporting node-based logistics receptacle **51150**). In more detail, the system's backend server **100** may also be operative to transmit a recall message (e.g., message **54005** as explained above) to the deployable mobile logistics receptacle **51020** to initiate a recall of the deployable mobile logistics receptacle **51020** from the deployed location of the deployable mobile logistics receptacle (e.g., Position B) and causing deployable mobile logistics receptacle **51020** to move to the recall location (e.g., Position C). The system's backend server **100** may be operative to transmit the supplemental activation message **55005** to the replacement deployable mobile logistics

receptacle **51020r** to initiate deployment of the replacement deployable mobile logistics receptacle **51020r** to the deployed location of the deployable mobile logistics receptacle (e.g., Position B) after a predetermined time period after sending the activation message to the deployable mobile logistics receptacle and/or initiate deployment of the replacement deployable mobile logistics receptacle **51020r** to the deployed location of the deployable mobile logistics receptacle based upon feedback information received from the deployable mobile logistics receptacle **51020**. Such feedback information from the existing deployed mobile logistics receptacle **51020** to backend server allows the backend server **100** to learn of conditions related to the previously deployed mobile logistics receptacle **51020** (e.g., exemplary feedback information corresponding to a status of the deployable mobile logistics receptacle (such as operating status, capacity status, overflow status or condition, and the like), exemplary feedback information corresponding to mobile event information related to one or more detected changes in the deployable mobile logistics receptacle (such as any detected status changes reflecting interactions with components of the deployable mobile logistics receptacle representing a pickup or drop off).

(500) In some embodiments described below, those skilled in the art will appreciate that initiating deployment of an exemplary deployable mobile logistics receptacle **51020** may be allowed and implemented via machine-to-machine (M2M) micropayment using blockchain. In such embodiments, when exemplary backend server **100** generally desires to send the activation message **51010** to a deployable mobile logistics receptacle to initiate deployment of an exemplary deployable mobile logistics receptacle (e.g., deployable mobile logistics receptacles **51020**, **51020a**, **51020b**, or **51020c**), the exemplary backend server **100** in such a system embodiment may do so autonomously and securely using predefined terms and conditions defined in a self-executing smart contract between the devices (e.g., backend server **100** and the deployable mobile logistics receptacle **51020**). Those skilled in the art will appreciate that such an exemplary smart contract may be generally considered as a self-executing contract with the terms of the agreement between the devices being directly written into lines of code (e.g., computerized transaction protocols that execute contract conditions making a transaction traceable, transparent and irreversible). The devices may be commonly owned or may be devices associated with different entities (e.g., when the backend server **100** is owned and operated by one entity and the deployable mobile logistics receptacle **51020** is owned and operated by another entity). Such a smart contract may be implemented and considered a decentralized application on network **105** that executes business logic in response to events where execution can result in the exchange of money, delivery of services (such as initiating use of a third party device, such as an exemplary deployable mobile logistics receptacle), unlocking of content protected by digital rights management or other types of data manipulation (such as the exchange of sensor data gathered by the deployable mobile logistics receptacle). Smart contracts may also be used to enforce privacy protection by, for example, facilitating the selective release of privacy-protected data to meet a specific request or permitting access to a particular secured area (such as a temporary storage area within deployable mobile logistics receptacle **51020**) or initiating use of a third party device for a particular task (such as initiating use of the deployable mobile logistics receptacle **51020** that provides a type of on-demand deployable logistics capacity related to a reporting node-based logistics receptacle **51150**).

(501) Referring back to FIG. **51**, a further system embodiment may have the backend server **100** being programmatically configured to be operative to send the activation message **51010** to the deployable mobile logistics receptacle **51020** to initiate deployment of the deployable mobile logistics receptacle **51020** by being further programmatically configured to be operative to send the activation message **51010** to the deployable mobile logistics receptacle **51020** to initiate deployment of the deployable mobile logistics receptacle **51020** according to a smart contract based activation agreement related to the deployable mobile logistics receptacle **51020**. Those skilled in the art will appreciate that establishing such a smart contract based connection by one network device with another network device may be generally accomplished with the execution of

a smart contract application (a type of decentralized application on network **105**) that will create and allow such a connection and interaction with the two devices under terms of that smart contract. In more detail, an embodiment may have the backend server **100** being programmatically configured to be operative to send the activation message **51010** to the deployable mobile logistics receptacle **51020** to initiate deployment of the deployable mobile logistics receptacle **51020** by being further programmatically configured to be operative to establish a smart contract based activation agreement with the deployable mobile logistics receptacle **51020**, where the smart contract based activation agreement provides terms for paid for deployment of the deployable mobile logistics receptacle **51020**; and send the activation message **51010** to the deployable mobile logistics receptacle **51020** to initiate deployment of the deployable mobile logistics receptacle **51020** according to the terms for paid for deployment of the deployable mobile logistics receptacle **51020** according to the smart contract based activation agreement.

(502) Those skilled in the art will appreciate that in a further example, this may involve running an exemplary decentralized application residing on one of the devices or on a part of network **105** representing the smart contract in response to events (such as a request to establish a smart contract based connection used to initiate deployment of a deployable mobile logistics receptacle) by one device/entity (e.g., backend server **100**) with another device/entity (e.g., deployable mobile logistics receptacle **51020**). The smart contract facilitating (e.g., used in establishing) such a connection involves a transaction between the two devices/entities. Data representing payment for such a transaction (e.g., payment for establishing the smart contract based connection for the performance of a service by the deployable mobile logistics receptacle **51020** for backend server **100**) may be stored in an extendible chain in a distributed fashion on the network **105**, such a distributed blockchain based virtual permanent ledger.

(503) Here, the smart contract based connection provides paid-for use of exemplary deployable mobile logistics receptacle **51020**. As such, the system's deployable mobile logistics receptacle **51020** may deploy to provide on-demand logistics capacity near reporting node-based logistics receptacle **51150** under terms of the smart contract based connection with the backend server **100**. In more detail, such a smart contract based connection may, for example, be implemented by a protocol for an automated transaction stored on a blockchain and run in response to meeting at least a payment condition for deploying the deployable mobile logistics receptacle. In some embodiments, the smart contract based connection may provide for initiating deployment of the deployable mobile logistics receptacle **51020** under predetermined pricing terms as the payment condition. Such predetermined pricing terms may, for example, relate to a blockchain-based payment for payment for initiating deployment of the deployable mobile logistics receptacle (e.g., supplied by a logistics asset having one or more deployable mobile logistics receptacles, supplied by a logistics broker having access to one or more third-party for-hire deployable mobile logistics receptacles) in response to the activation message and/or a blockchain-based payment for access rights to the data generated by any of the sensing elements in deployable mobile logistics receptacle **51020**.

(504) Selective Retrieval and Reporting of Event Information

(505) Some of the embodiments described above involve the bridge node retrieving the available event information from the wireless accessory sensor node at particular times as described herein. However, in additional embodiments, the storage receptacle's bridge node may only selectively retrieve particular logged/captured sensor data and information (e.g., as event information) from the wireless accessory sensor node based upon information generally referred to as selective criteria where not all available event information is retrieved to be then transmitted to the backend server for use in causing the backend server to initiate a dispatched logistics operation related to the storage receptacle. The selective criteria may be implemented as one or more types of information, as described in more detail below. In this way, such additional embodiments involving this type of selective retrieval of event information report back only particular types, classes, subsets of event

information or event information that has been triaged at the level of the node-based logistics receptacle to be more refined and more useful to the backend server in managing and/or servicing the node-based logistics receptacle.

(506) FIG. **36** is a diagram illustrating an exemplary enhanced connected logistics receptacle system that selectively retrieves and reports particular event information to a backend server to initiate a dispatched logistics operation related to a delivery item in accordance with an embodiment of the invention. Referring now FIG. **36**, exemplary connected logistics receptacle **36150** is shown along with backend server **100** and exemplary mobile logistics asset **700a** (e.g., courier personnel **2615** (equipped with a mobile handheld communication device **2630** and mobile node-enabled badge **2620**) and a delivery vehicle **2602** (equipped with an exemplary mobile transceiver **2600**, location circuitry **2605** coupled to transceiver **2600**, and vehicle status monitoring circuitry **2610** coupled to transceiver **2600**).

(507) Those skilled in the art will appreciate that exemplary connected logistics receptacle **36150** shown in FIG. **36** is similarly structured to exemplary connected logistics receptacle **150a**, with the exception that exemplary receptacle **36150** includes selective monitoring and management code for execution by the processor in bridge node **200** (controlling functionality of bridge node **200** in such additional embodiments) and use of selectivity information **3605** maintained within memory **305/310** of bridge node **200** as part of selectively retrieving and reporting particular event information. In other words, and as explained in more detail below, data maintained as part of exemplary selectivity information **3605** generally reflects selective criteria used by the bridge node **200** to determine what is to be retrieved and uploaded from the wireless accessory sensor node regarding available event information generated on and maintained by the wireless accessory sensor node (e.g., exemplary wireless accessory sensor node **210**).

(508) As such, an exemplary system embodiment is shown in FIG. **36** that includes exemplary connected logistics receptacle **36150** having a storage receptacle for receiving and maintaining a delivery item (as previously described having an entrance opening, a temporary storage area **205** and selectively accessible retrieval door **160**). The system's exemplary connected logistics receptacle **36150** is also illustrated being equipped with at least exemplary bridge node **200**, exemplary wireless accessory sensor nodes **210**, **245**, lock **165** for door **160** that provides access to within the storage receptacle, and sensors **450a-450e** that are coupled to at least one of the wireless accessory sensor nodes on receptacle **150a**. The system's exemplary bridge node **200**, consistent with previously descriptions, is mounted to the storage receptacle and includes a bridge node processor **201**, a bridge node memory **202** (e.g., volatile memory **310** and non-volatile memory **305**), and a wireless communication interface **203**. As noted above, the bridge node memory is coupled to the bridge node processor and maintains selective monitoring and management code (e.g., a type of CLR control and management code **315**) for execution by the bridge node processor along with at least exemplary selectivity information **3605** that is used during execution of the selective monitoring and management code. The communication interface is coupled to the bridge node processor and is operative to communicate with at least the backend server **100** over a first communication path (e.g., exemplary network **105**).

(509) Consistent with the description above, the system uses at least one exemplary wireless accessory sensor node (e.g., node **210**) coupled to a plurality of sensors (e.g., sensors **450a-450e**) where each of the sensors respectively monitors for a change in state of the storage receptacle. The system's exemplary wireless accessory sensor node **210** is operative to detect the change in state of the storage receptacle based upon sensor data generated by the at least one sensor; record timestamped information reflecting the detected change in state of the storage receptacle; and broadcast an updated advertising signal having a data available flag set within the updated advertising signal. Here, the data available flag indicates the wireless accessory sensor node has at least some event information available for upload by the bridge node **200** (where such event information includes at least the timestamped information reflecting the detected change in state of

the storage receptacle).

(510) The bridge node processor within the system's exemplary bridge node **200**, when executing the selective monitoring and management code maintained on the bridge node memory, is operative to detect the data available flag set within the updated advertising signal over the communication interface; selectively retrieve the event information from the wireless accessory sensor node using the communication interface based upon a selective criteria for upload (e.g., data maintained within selectivity information **3605**); and transmit, using the bridge node's communication interface, the retrieved event information in a message **3610** to the backend server **100** to cause the backend server **100** to initiate the dispatched logistics operation via a dispatch message **3615** related to the storage receptacle.

(511) In a further embodiment of such an exemplary system, the selective criteria used by bridge node **200** may originate from the backend server. For example, the system's bridge node processor may be further operative to receive a selective criteria message from the backend server **100**. Such a selective criteria message updates the selectivity information **3605** used by the bridge node **200** as the selective criteria. In more detail, the selective criteria message may cause the bridge node **200** processor to store (or update) selectivity information **3605** in the bridge node memory where the selectivity information is identified in the selective criteria message and, thereafter, corresponds to the selective criteria used when selectively retrieving the event information available for upload.

(512) In another embodiment of such an exemplary system, the selective criteria used by bridge node **200** may come from what is broadcast by the system's wireless accessory sensor node. For example, the system's bridge node processor may be further operative to selectively retrieve the event information available for upload based upon the selective criteria by being further operative to detect a selection identifier based upon information within the updated advertising signal (e.g., information within the data available flag itself), and then selectively retrieve the event information available for upload from the wireless accessory sensor node using the communication interface based upon the detected selection identifier representing the selective criteria for upload.

(513) In still another embodiment, what is selectively retrieved is only a subset or portion of the available event information on the wireless accessory sensor node. For example, and in more detail, the exemplary system's bridge node processor may be operative to selectively retrieve the event information based upon the selective criteria for upload by being further operative to selectively retrieve, based upon the selective criteria for upload, at least a subset or portion of the event information available for upload and maintained on the wireless accessory sensor node. The particular subset or portion of the available event information maintained on the wireless accessory sensor node may be indicated by the selective criteria for upload.

(514) What is selectively retrieved, in other embodiments, may be based upon the type of component in the storage receptacle where a change was detected that warrants retrieval. For example, the selective criteria for upload may be a predetermined type of change in state of the storage receptacle related to one or a subset of the monitored storage receptacle components (e.g., the entrance opening, the temporary storage area, the access door, and the like). In more detail, the selectively retrieved event information may be a portion of the event information available for upload on the wireless accessory sensor node that corresponds to the identified type of change in state of the storage receptacle related to the one of the monitored storage receptacle components.

(515) In other embodiments, the selective criteria for upload may be a predetermined class of sensor related to the detected change in state of the storage receptacle. For example, such a predetermined class of sensor may be a prioritized class of sensor identifying a first subset of the sensors. In more detail, the predetermined class of sensor related to the detected change in state of the storage receptacle may be a motion class of sensor that includes a motion sensor capable of detecting at least a change in motion of one of the monitored receptacle structural components, a change in motion of an object moving in relation to one of the monitored receptacle structural components, a change in motion outside of the storage receptacle, and/or a change in motion of one

of the monitored receptacle structural components.

(516) In another embodiment, the predetermined class of sensor related to the detected change in state of the storage receptacle may be a status class of sensor. For example, when the monitored storage receptacle components include a lock, such as exemplary lock **165** for securing the selectively accessible retrieval door **160**, the status class of sensor may be a lock sensor capable of detecting a change in state of the lock **165** as the change in state of the storage receptacle. In another example, the status class of sensor may be a range sensor (e.g., a range sensor coupled to wireless accessory sensor node **250**) capable of detecting a change in what has been placed within a predetermined range of the storage receptacle as the change in state of the storage receptacle. In yet another example, the status class of sensor may be an orientation sensor capable of detecting a change in orientation of one of the monitored storage receptacle components as the change in state of the storage receptacle. In still another example, the status class of sensor may include a magnetic sensor capable of detecting a change in position of one of the monitored storage receptacle components as the change in state of the storage receptacle.

(517) In yet another embodiment, the predetermined class of sensor related to the detected change in state of the storage receptacle may be an imaging class of sensor. In other embodiments, the predetermined class of sensor related to the detected change in state of the storage receptacle may be a force class of sensor, such as a scale capable of detecting a change in weight of what is maintained within the storage receptacle as the change in state of the storage receptacle or an impact sensor capable of detecting a change in what has been deposited within the storage receptacle as the change in state of the storage receptacle. Further still, additional embodiments may have the predetermined class of sensor related to the detected change in state of the storage receptacle being a light class of sensor (e.g., light detection sensor, laser-based sensor, etc.) or a chemical class of sensor (e.g., an explosive sensor, a sensor that detects particular vaporous chemicals in gas form, or other chemical sensors).

(518) In further embodiments, the selective criteria for upload may be a threshold detection condition relative to the detected change in state of the storage receptacle. For example, the bridge node processor in the system's bridge node **200** may be operative to selectively retrieve the event information based upon the selective criteria for upload by being further operative to selectively retrieve, based upon the threshold detection condition as the selective criteria for upload, a portion of the event information available for upload associated with the threshold detection condition. Such a threshold detection condition may, for example, be detection of an external package as the detected change in state of the storage receptacle; detection of a package count excess condition as the detected change in state of the storage receptacle; and/or detection of a weight excess condition as the detected change in state of the storage receptacle.

(519) The selective criteria for upload, in still further embodiments, may be based upon the time of detection. For example, an embodiment may implement the selective criteria for upload as a temporal preference criteria identifying which in a series of detected changes in state of the storage receptacle warrant reporting to the backend server. In more detail, such a temporal preference criteria may identify a first in the series of detected changes in state of the storage receptacle, a last in the series of detected changes in state of the storage receptacle, or a predetermined one in the series of detected changes in state of the storage receptacle as the particular detected change that warrants having its related event information being retrieved by the bridge node **200** for reporting to the backend server **100**.

(520) Further still, the selective criteria for upload used in other embodiments may prioritize retrieval of particular event information for particular customers. For example, the selective criteria for upload used by the system's bridge node **200** may be implemented as a customer prioritization preference criteria, which defines a customer associated with the detected change in state of the storage receptacle. In more detail, an embodiment may have the system's bridge node processor being further operative to identify a customer associated with the detected change in state of the

storage receptacle based upon a broadcast signal received by the communication interface from a mobile user access device associated with the shipping customer (e.g., a smartphone or augmented reality communication device (e.g., AR glassware/headset) used by a shipping customer dropping off the delivery item or other parcels at the node-based logistics receptacle **36150**, a wireless transceiver based mobile tag used by the shipping customer, a wireless transceiver in a mobile vehicle used by the shipping customer, and the like). The broadcast signal from the mobile user access device associated with the customer may include an RF signature associated with the customer, which may be used in identifying the customer. The bridge node processor in such an embodiment is operative to selectively retrieve the event information from the wireless accessory sensor node based upon the selective criteria for upload by being further operative to selectively retrieve the event information from the wireless accessory sensor node when a customer prioritization criteria matches the identified customer associated with the detected change in state of the storage receptacle. Here, the customer prioritization criteria defines whether the identified customer warrants prioritized reporting to the backend server of interactions with the storage receptacle. In some examples, the customer prioritization criteria may define a first class of one or more customers that warrants non-delayed reporting of the interactions with the storage receptacle and/or an additional class of one or more customers where reporting of the interactions with the storage receptacle are delayed until a predetermined time (e.g., time from detection, time of day, the end of a reporting period associated with the bridge node, time on a particular day of the week, and the like).

(521) In similar embodiments, the selective criteria for upload used in other embodiments may prioritize retrieval of particular event information for particular entities. For example, the selective criteria for upload used by the system's bridge node **200** may be implemented as an entity prioritization preference criteria, which defines an entity associated with the detected change in state of the storage receptacle. In more detail, an embodiment may have the system's bridge node processor being further operative to identify the entity associated with the detected change in state of the storage receptacle based upon a broadcast signal received by the communication interface from a mobile user access device associated with the entity (e.g., a smartphone used by an entity employee, a wireless transceiver based mobile tag used by the entity employee, a wireless transceiver in a mobile vehicle used by the entity, and the like). The broadcast signal from the mobile user access device associated with the entity may include an RF signature associated with the entity, which may be used in identifying the particular entity. The bridge node processor in such an embodiment is operative to selectively retrieve the event information from the wireless accessory sensor node based upon the selective criteria for upload by being further operative to selectively retrieve the event information from the wireless accessory sensor node when the entity prioritization criteria matches the identified entity associated with the detected change in state of the storage receptacle, where the entity prioritization criteria defines whether the identified entity warrants prioritized reporting to the backend server of interactions with the storage receptacle. In some examples, the entity prioritization criteria may define a first class of one or more entities that warrants non-delayed reporting of the interactions with the storage receptacle and/or an additional class of one or more entities where reporting of the interactions with the storage receptacle are delayed until a predetermined time (e.g., time from detection, time of day, the end of a reporting period associated with the bridge node, time on a particular day of the week, and the like).

(522) In light of such a system embodiment illustrated in FIG. **36** and described above, those skilled in the art will appreciate that another related embodiment involves a method for uploading and transmitting of event information from a node-based logistics receptacle implemented by the above-described system components. FIG. **37** is a flow diagram illustrating an exemplary method **3700** for selective uploading and transmitting of event information from a node-based logistics receptacle in accordance with an embodiment of the invention. In such an exemplary method **3700**, the node-based logistics receptacle used may be implemented with exemplary node-based logistics

receptacle **36150**, which has multiple monitored storage receptacle components (including at least an entrance opening **155** for receiving one or more shipping items, a temporary storage area **205** for temporarily maintaining the one or more shipping items once received, and a retrieval door **160** providing selective access to the one or more shipping items within the temporary storage area). The node-based logistics receptacle used in implementing exemplary method **3700** further has a wireless accessory sensor node coupled to multiple sensors (e.g., exemplary wireless accessory sensor node **210**) disposed on the node-based logistics receptacle and a receptacle bridge node (e.g., exemplary bridge node **200**) disposed on the node-based logistics receptacle operative to communicate with a backend server (e.g., exemplary backend server **100**).

(523) Referring now to FIG. **37**, exemplary method **3700** begins at step **3705** with the wireless accessory sensor node monitoring for a change in state of the storage receptacle using the sensors. At step **3710**, method **3700** proceeds with the wireless accessory sensor node detecting the change in state of the storage receptacle based upon sensor data generated by at least one of the sensors. If a change is detected, step **3710** proceeds to step **3715**. If a change is not yet detected, then method **3700** proceeds back to step **3705** to continue monitoring for a sensor-based change in state of the storage receptacle.

(524) At step **3715**, method **3700** proceeds with the wireless accessory sensor node recording timestamped information reflecting the detected change in state of the storage receptacle. At step **3720**, method **3700** then has the wireless accessory sensor node broadcasting an updated advertising signal having a data available flag set within the updated advertising signal. The data available flag indicates the wireless accessory sensor node has event information available for upload by the bridge node. Such event information includes at least the timestamped information reflecting the detected change in state of the storage receptacle, but may include further information (e.g., the type of sensor detecting the change, the component monitored related to the change, and the like consistent with the description herein on types of event information).

(525) At step **3725**, method **3700** proceeds with the bridge node detecting the data available flag set within the updated advertising signal. At this point, the bridge node is made aware there is event information available but as described in more detail below, the bridge node only selectively retrieves the event information in step **3730** using the communication interface of the bridge node and based upon a selective criteria for upload. In this way, a selective amount of what event information available on the wireless accessory sensor node is then retrieved by the bridge node from the wireless accessory sensor node in step **3730**. In more detail, such selective criteria may be implemented using selectivity information maintained by the bridge node (e.g., data in selectivity information **3605**).

(526) Finally, at step **3735**, method **3700** proceeds with the bridge node transmitting the retrieved event information to the backend server to cause the backend server to initiate the dispatched logistics operation related to the storage receptacle.

(527) In further embodiments of method **3700**, the selective criteria used by the bridge node in step **3730** may originate from the backend server. For example, an embodiment of method **3700** may also include the step of receiving, by the bridge node, a selective criteria message from the backend server **100**. Such a selective criteria message updates the selectivity information **3605** used by the bridge node **200** as the selective criteria. In more detail, such an embodiment of method **3700** may have the bridge node receiving a selective criteria message from the backend server and then storing selectivity information in memory of the bridge node where such selectivity information is identified in the selective criteria message and corresponds to the selective criteria used when selectively retrieving the event information available for upload in step **3730**.

(528) In another embodiment of exemplary method **3700**, the selective criteria used by bridge node **200** in step **3730** may come from what is broadcast by the system's wireless accessory sensor node. For example, step **3730** may be implemented with the bridge node selectively retrieving the event information available for upload based upon the selective criteria with the bridge node detecting a

selection identifier based upon information within the updated advertising signal (e.g., information within the data available flag itself), and then selectively retrieving the event information available for upload from the wireless accessory sensor node using the communication interface based upon the detected selection identifier representing the selective criteria for upload.

(529) In still another embodiment of method **3700**, what is selectively retrieved in step **3730** is only a subset or portion of the available event information on the wireless accessory sensor node. For example, and in more detail, step **3730** may be implemented with the bridge node selectively retrieving, based upon the selective criteria for upload, at least a subset or portion of the event information available for upload and maintained on the wireless accessory sensor node. The particular subset or portion of the available event information maintained on the wireless accessory sensor node may be indicated by the selective criteria for upload.

(530) What is selectively retrieved, in other embodiments of step **3730**, may be based upon the type of component in the storage receptacle where a change was detected that warrants retrieval. For example, the selective criteria for upload may be a predetermined type of change in state of the storage receptacle related to one or a subset of the monitored storage receptacle components (e.g., the entrance opening, the temporary storage area, the access door, and the like). In more detail, the selectively retrieved event information may be a portion of the event information available for upload on the wireless accessory sensor node that corresponds to the identified type of change in state of the storage receptacle related to the one of the monitored storage receptacle components.

(531) In still other embodiments of step **3730** of method **3700**, the selective criteria for upload used in step **3730** may be a predetermined class of sensor related to the detected change in state of the storage receptacle. For example, such a predetermined class of sensor may be a prioritized class of sensor identifying a first subset of the sensors. In more detail, the predetermined class of sensor related to the detected change in state of the storage receptacle may be a motion class of sensor that includes a motion sensor capable of detecting at least a change in motion of one of the monitored receptacle structural components, a change in motion of an object moving in relation to one of the monitored receptacle structural components, a change in motion outside of the storage receptacle, and/or a change in motion of one of the monitored receptacle structural components.

(532) In another embodiment of step **3730** of method **3700**, the predetermined class of sensor related to the detected change in state of the storage receptacle may be a status class of sensor. For example, when the monitored storage receptacle components include a lock, such as exemplary lock **165** for securing the selectively accessible retrieval door **160**, the status class of sensor may be a lock sensor capable of detecting a change in state of the lock **165** as the change in state of the storage receptacle. In another example, the status class of sensor may be a range sensor (e.g., a range sensor coupled to wireless accessory sensor node **250**) capable of detecting a change in what has been placed within a predetermined range of the storage receptacle as the change in state of the storage receptacle. In yet another example, the status class of sensor may be an orientation sensor capable of detecting a change in orientation of one of the monitored storage receptacle components as the change in state of the storage receptacle. In still another example, the status class of sensor may include a magnetic sensor capable of detecting a change in position of one of the monitored storage receptacle components as the change in state of the storage receptacle.

(533) In yet another embodiment of step **3730**, the predetermined class of sensor related to the detected change in state of the storage receptacle may be an imaging class of sensor. In other embodiments of step **3730**, the predetermined class of sensor related to the detected change in state of the storage receptacle may be a force class of sensor, such as a scale capable of detecting a change in weight of what is maintained within the storage receptacle as the change in state of the storage receptacle or an impact sensor capable of detecting a change in what has been deposited within the storage receptacle as the change in state of the storage receptacle. Further still, additional embodiments of step **3730** may have the predetermined class of sensor related to the detected change in state of the storage receptacle being a light class of sensor (e.g., light detection sensor,

laser-based sensor, etc.) or a chemical class of sensor (e.g., an explosive sensor, a sensor that detects particular vaporous chemicals in gas form, or other chemical sensors).

(534) In further embodiments of method **3700**, the selective criteria for upload used in step **3730** may be a threshold detection condition relative to the detected change in state of the storage receptacle. For example, the step **3730** may have the bridge node selectively retrieving, based upon the threshold detection condition as the selective criteria for upload, a portion of the event information available for upload associated with the threshold detection condition. Such a threshold detection condition may, for example, be detection of an external package as the detected change in state of the storage receptacle; detection of a package count excess condition as the detected change in state of the storage receptacle; and/or detection of a weight excess condition as the detected change in state of the storage receptacle.

(535) The selective criteria for upload, in still further embodiments, may be based upon the time of detection. For example, an embodiment may implement the selective criteria for upload as a temporal preference criteria identifying which in a series of detected changes in state of the storage receptacle warrant reporting to the backend server. In more detail, such a temporal preference criteria may identify a first in the series of detected changes in state of the storage receptacle, a last in the series of detected changes in state of the storage receptacle, or a predetermined one in the series of detected changes in state of the storage receptacle as the particular detected change that warrants having its related event information being retrieved by the bridge node **200** for reporting to the backend server **100**.

(536) Further still, the selective criteria for upload used in other embodiments of step **3730** of method **3700** may prioritize retrieval of particular event information for particular customers. For example, the selective criteria for upload used by the system's bridge node **200** may be implemented as a customer prioritization preference criteria, which defines a customer associated with the detected change in state of the storage receptacle. In more detail, an embodiment may have step **3730** implemented with the bridge node identifying a customer associated with the detected change in state of the storage receptacle based upon a broadcast signal received by the communication interface from a mobile user access device associated with the shipping customer (e.g., a smartphone used by a shipping customer dropping off the delivery item or other parcels at the node-based logistics receptacle **36150**, a wireless transceiver based mobile tag used by the shipping customer, a wireless transceiver in a mobile vehicle used by the shipping customer, and the like). The broadcast signal from the mobile user access device associated with the customer may include an RF signature associated with the customer, which may be used in identifying the customer. In such an embodiment, step **3730** may be implemented with the bridge node selectively retrieving the event information from the wireless accessory sensor node based upon the selective criteria for upload by being further operative to selectively retrieve the event information from the wireless accessory sensor node when a customer prioritization criteria matches the identified customer associated with the detected change in state of the storage receptacle. Here, the customer prioritization criteria defines whether the identified customer warrants prioritized reporting to the backend server of interactions with the storage receptacle. In some examples, the customer prioritization criteria may define a first class of one or more customers that warrants non-delayed reporting of the interactions with the storage receptacle and/or an additional class of one or more customers where reporting of the interactions with the storage receptacle are delayed until a predetermined time (e.g., time from detection, time of day, the end of a reporting period associated with the bridge node, time on a particular day of the week, and the like).

(537) In similar more detailed embodiments of method **3700**, the selective criteria for upload used in other embodiments may prioritize retrieval of particular event information for particular entities. For example, the selective criteria for upload used by the system's bridge node **200** may be implemented as an entity prioritization preference criteria, which defines an entity associated with the detected change in state of the storage receptacle. In more detail, an embodiment may

implement step **3730** with the bridge node identifying the entity associated with the detected change in state of the storage receptacle based upon a broadcast signal received by the communication interface from a mobile user access device associated with the entity (e.g., a smartphone used by an entity employee, a wireless transceiver based mobile tag used by the entity employee, a wireless transceiver in a mobile vehicle used by the entity, and the like). The broadcast signal from the mobile user access device associated with the entity may include an RF signature associated with the entity, which may be used in identifying the particular entity. Step **3730** in such an embodiment has the bridge node selectively retrieving the event information from the wireless accessory sensor node based upon the selective criteria for upload by selectively retrieving the event information from the wireless accessory sensor node when the entity prioritization criteria matches the identified entity associated with the detected change in state of the storage receptacle, where the entity prioritization criteria defines whether the identified entity warrants prioritized reporting to the backend server of interactions with the storage receptacle. In some examples, the entity prioritization criteria may define a first class of one or more entities that warrants non-delayed reporting of the interactions with the storage receptacle and/or an additional class of one or more entities where reporting of the interactions with the storage receptacle are delayed until a predetermined time (e.g., time from detection, time of day, the end of a reporting period associated with the bridge node, time on a particular day of the week, and the like).

(538) Enhanced Customer Identification by a Node-Based Logistics Receptacle

(539) Some of the embodiments described herein involve detection of a change in state of the node-based logistics receptacle (e.g., changes in monitored components of the storage receptacle). Additional embodiments may also monitor for and identify the parcel customer dropping off the delivery item (e.g., exemplary package **170**, which may be a parcel, letter, boxed item, unboxed item, or other object being deposited with the storage receptacle for shipment). As explained in more detail below, embodiments that also involve customer identification may enhance and adapt an exemplary node-based logistics receptacle so as to detect wireless signals being broadcast by the parcel customer's mobile user device (e.g., smartphone or wireless-enabled tablet running an app related to the shipment of the delivery item) as the parcel customer approaches the node-based logistics receptacle when depositing/dropping off the delivery item. In this way, such additional embodiments deploy self-monitoring node-based logistics receptacles to detect not only a change in the state of the receptacle's components (e.g., entrance opening, temporary storage area, access door, surrounding area next to the receptacle, and the like), but also detect and interact with parcel customer to validate and verify those parcel customers are authorized to use the particular node-based logistics receptacle as it relates to the particular delivery item being dropped off. Such additional functionality implemented in an exemplary node-based logistics receptacle also facilitates tracking and updating of custodial control related to the delivery item with more specificity, and updating the server with such updated custodial control information. In some embodiments, this may also have the advantage of early awareness of an unauthorized deposit and the ability to take corrective action on the part of the server (i.e., initiating a corrective logistics operation where a logistics asset is dispatched with particularity to retrieve a specific delivery item deposited in that node-based logistics receptacle where such a deposit was proactively detected, determined to be unauthorized, and notification of such an unauthorized deposit was reported to the server by the bridge node in the node-based logistics receptacle).

(540) FIGS. **38A-38C** are diagrams illustrating an exemplary connected logistics receptacle system with enhanced customer identification related to a delivery item being deposited by a parcel customer in accordance with an embodiment of the invention. Referring now FIG. **38A**, exemplary connected logistics receptacle **38150** is shown operative to communicate with backend server **100** and an exemplary parcel customer **3800**. Exemplary parcel customer **3800** is shown transporting exemplary package **180** (a type of delivery item) to be deposited within the exemplary connected logistics receptacle **38150**. Exemplary parcel customer **3800** is also shown equipped with a mobile

handheld communication device **3805** (more generally referred to as a mobile user device). Those skilled in the art will appreciate that as shown in FIG. **38A**, exemplary mobile user device **3805** is running an exemplary app that allows mobile user device **3805** to broadcast a wireless communication signal **3820** related to the delivery item (e.g., exemplary package **170**) being deposited with exemplary connected logistics receptacle **38150**.

(541) Those skilled in the art will appreciate that exemplary device **3805** carried by parcel customer **3800** may, like exemplary devices **1700** and **2630**, be implemented as an exemplary processor-based augmented reality device (e.g., an AR headset type of device with communication capabilities) used by parcel customer **3800**. Those skilled in the art will appreciate that incorporation of augmented reality as part of device **3805** (like exemplary devices **1700** and **2630** that are implemented with augmented reality functionality) facilitates an enhanced interactive experience that combines real world content (e.g., a view of the surrounding area proximate device **3805**) and processor-generated content (e.g., information corresponding to virtual symbols, objects, information, prompted messages, directions, sensory information, and the like overlaid on the real world content) shown in an interwoven manner that advantageously allows the parcel customer **3800** to better perceive both the real world content and the processor-generated content. In general, an exemplary augmented reality enhanced device implementation of device **3805** may include a processor, memory, a display (e.g., a heads up display that may be viewed on the device by the user or a look through display viewed through by the user with real world and processor-generated content appearing on the display), sensors (e.g., GPS sensors, accelerometer, imaging sensors, camera, and the like), a wireless transceiver for communication with other devices, as well as input devices for user input and interactivity (e.g., button, cursor, touchscreen, microphone, and the like). Such an exemplary augmented reality enhanced device implementation of device **3805** may, for example, be implemented as augmented reality glasses that project a digital overlay directly in the parcel customer's field of vision. In general, an exemplary augmented reality enhanced device implementation of device **3805** presents the parcel customer **3800** (as the user) with a combination of digital and physical worlds, facilitates interactions made in near real time with less distraction for the parcel customer **3800**, and an accurate 3D identification of virtual and real objects for use by the parcel customer **3800** when engaging in such interactions (e.g., receiving information displayed, recognizing objects (such as an exemplary node-based logistics receptacle), and providing responsive input/feedback based upon the information displayed). Further, such an exemplary processor based augmented reality device implementation of device **3805** may still provide the ability to connect to network **105** and communicate with other devices (which may themselves have augmented reality features), other wireless transceivers associated with logistics assets, and/or connect with and communicate with one or more node-based logistics receptacles via its wireless transceiver. Information presented via exemplary augmented reality enhanced device **3805** may be accompanied, for example, with additional notification enhancements (e.g., sound, colors, highlights, haptic feedback, and the like) that help draw attention to the information as perceived by the parcel customer **3800** operating the exemplary augmented reality enhanced device **3805**.

(542) Those skilled in the art will appreciate that exemplary connected logistics receptacle **38150** shown in FIGS. **38A-38C** is similarly structured to exemplary connected/node-based logistics receptacle **150a**, with the exception that exemplary receptacle **38150** includes an embodiment of monitoring and management code for execution by the processor in bridge node **200** (controlling functionality of bridge node **200** in such additional embodiments) and use of exemplary custodial control information **3825** and exemplary pre-authorized identification information **3830** maintained within memory **305/310** of bridge node **200** as part of enhanced customer identification functionality implemented in exemplary connected logistics receptacle **38150**. Those skilled in the art will appreciate that backend server **100** may, in some embodiments, transmit updates to the pre-authorized identification information **3830** for use by the exemplary connected logistics receptacle

38150. Those skilled in the art will also appreciate, as explained in more detail below, that bridge node **200** may update the custodial control information **3825** and provide such updated custodial control information to backend server **100**.

(543) As such, an exemplary connected logistics receptacle system embodiment with enhanced customer identification is shown in FIGS. **38A-38C** that includes exemplary connected logistics receptacle **38150** having a storage receptacle for receiving and maintaining a delivery item (as previously described having monitored storage receptacle components, such as an entrance opening, a temporary storage area **205** and selectively accessible retrieval door **160**). The system's exemplary connected logistics receptacle **38150** is also illustrated being equipped with at least exemplary bridge node **200**, exemplary wireless accessory sensor nodes **210**, **245**, lock **165** for door **160** that provides access to within the storage receptacle, and sensors **450a-450e** that are coupled to at least one of the wireless accessory sensor nodes on receptacle **38150**. The system's exemplary bridge node **200**, consistent with previously descriptions, is mounted to the storage receptacle and includes a bridge node processor **201**, a bridge node memory **202** (e.g., volatile memory **310** and non-volatile memory **305**), and a wireless communication interface **203**. As noted above, the bridge node memory is coupled to the bridge node processor and maintains an embodiment of monitoring and management code capable of enhanced customer identification (e.g., a type of CLR control and management code **315**) for execution by the bridge node processor along with at least exemplary custodial control information **3825** and exemplary pre-authorized identification information **3830** that may be used during execution of the monitoring and management code as explained below. The communication interface is coupled to the bridge node processor and is operative to communicate with at least the backend server **100** over a first communication path (e.g., exemplary network **105**).

(544) Consistent with the description above, the system embodiment uses at least one exemplary wireless accessory sensor node (e.g., node **210**) coupled to a plurality of sensors (e.g., sensors **450a-450e**) where each of the sensors respectively monitors for a change in state of the storage receptacle. Such sensors, as described above, may generate sensor data related to motion of the entrance opening, motion of objects moving through the entrance opening, motion of an object within the temporary storage area, image sensor data related a change of contents maintained within the temporary storage area, weight sensor data related a change in weight of what is stored within the temporary storage area, and the like. The system's exemplary wireless accessory sensor node **210** is operative to detect the change in state of the storage receptacle related to at least one of the monitored storage receptacle components based upon sensor data generated by at least one sensor and broadcast an updated advertising signal in response to the detected change in state of the storage receptacle.

(545) The bridge node processor within the system's exemplary bridge node **200**, when executing the monitoring and management code maintained on the bridge node memory, is operative to detect the updated advertising signal from the wireless accessory sensor node over the communication interface and then detect a wireless communication signal broadcast from a mobile user device associated with the parcel customer (e.g., detecting exemplary wireless signal **3820** being broadcast by device **3805** running app **3810** and used by parcel customer **3800**). Those skilled in the art will appreciate that device **3805** may be implemented, for example, as an AR headset type of device used by parcel customer **3800** where information shown via app **810** appears in the field of view of the AR headset as part of processor-generated content overlaid on real world content viewed through the AR headset version of device **3805**.

(546) Referring now to FIG. **38B**, the bridge node processor within the system's exemplary bridge node **200**, when executing the monitoring and management code maintained on the bridge node memory, is shown operative to transmit a validation message **3835** over the bridge node's communication interface to the mobile user device **3805** associated with the parcel customer **3800** in response to the detected wireless communication signal **3820** and the detected updated

advertising signal from the wireless accessory sensor node (e.g., node **210**). The mobile user device **3805** used by parcel customer **3800** receives the validation message **3835** and, through the app **3810** running on the device **3805**, is able to respond with a validation confirmation message **3840** transmitted back to the system's exemplary bridge node **200**, which receives the validation confirmation message **3840** over the bridge node's communication interface. Referring now to FIG. **38C**, the bridge node processor within the system's exemplary bridge node **200**, when executing the monitoring and management code maintained on the bridge node memory, is then operative to transmit, using the communication interface, event information **3845** to the backend server **100** when the validation confirmation message **3840** authenticates the parcel customer **3800** (where the transmitted event information includes at least information reflecting the detected change in state of the storage receptacle).

(547) More specifically, a further system embodiment may use exemplary authorization data provided as part of the broadcast wireless communication signal **3820** to help the system recognize the parcel customer as being an authorized customer (e.g., via the customer's mobile user device **3805** being an authorized device associated with an authorized customer). For example, the system's bridge node processor may be operative to detect the wireless communication signal broadcast by being operative to receive the wireless communication signal **3820** broadcast from the mobile user device **3805** associated with the parcel customer **3800** over the communication interface of the system's bridge node **200**; and recognize the mobile user device **3805** as an authorized mobile user device based upon authorization data within the wireless communication signal **3820**. In a more detailed example embodiment, the system's bridge node processor may be operative to recognize the mobile user device as the authorized mobile user device by being operative to identify the authorization data within the wireless communication signal **3820**, compare the authorization data to information on a plurality of pre-authorized mobile user devices (e.g., information maintained in exemplary pre-authorized identification information **3830**); and recognize the mobile user device **3805** as being an authorized mobile user device based upon the results of comparing that authorization data to the information on the pre-authorized mobile user devices.

(548) In a further embodiment, the exemplary validation message **3835** may request different kinds of information from the parcel customer **3800**. For example, the validation message **3835** may request confirmation that the parcel customer **3800** has deposited the delivery item in the storage receptacle and/or request authentication information from the parcel customer **3800** related to the delivery item. In more detail, such requested authentication information may, for example, include shipping information related to the delivery item (e.g., a tracking number for the delivery item, address information related to the delivery item, recipient information related to the delivery item, and the like) and/or information identifies the delivery item (e.g., contents description, weight information, and the like) and/or information identifies the parcel customer **3800** (e.g., name of the parcel customer, contact information for the parcel customer, entity associated with the parcel customer, and the like).

(549) Likewise, further embodiments may have the exemplary validation confirmation message **3840** including different information. For example, the validation confirmation message **3840** may include authentication information from the parcel customer **3800** related to the delivery item. Examples of such authentication information (similar to that noted above as being requested) may include shipping information related to the delivery item, information identifies the delivery item, and/or information identifies the parcel customer.

(550) In some system embodiments, custodial control information may be used (e.g., exemplary custodial control information **3825**) and updated as part of operations of the system. For example, the system's bridge node processor, when executing the monitoring and management code maintained on the bridge node memory, may be further operative to update custodial control information **3825** maintained within the bridge node memory related to custody of the delivery

item when the validation confirmation message **3840** authenticates the parcel customer **3800** (e.g., when the parcel customer's mobile user device **3805** is determined to be pre-authorized or associated with an authorized customer of the node-based connected logistics receptacle **38150**). In such an example, the event information transmitted to the backend server **100** may also include the updated custodial control information related to the delivery item as a way of updating the server **100** so that the server **100** may track custodial control and responsibility for a given delivery item. (551) In a further system embodiment, the event information sent back to server **100** may initiate a dispatched logistics operation (e.g., pickup) related to the storage receptacle (e.g., receptacle **38150**). In more detail, the bridge node processor, when executing the monitoring and management code maintained on the bridge node memory, may be operative to transmit the event information to the backend server **100** by being operative to transmit, using the communication interface of the system's bridge node **200**, the event information to the backend server **100** when the validation confirmation message **3840** authenticates the parcel customer **3800**, which then causes the backend server **100** to initiate a dispatched logistics operation related to the storage receptacle. Such event information may also, for example, include at least timing information related to the detected change in state of the storage receptacle and/or an identification of the delivery item and/or updated custodial control information related to the delivery item.

(552) And in yet another system embodiment, the system's wireless accessory sensor node may more specifically be operative to detect the change in state of the storage receptacle based upon the sensor data generated by at least one of the sensors; record timestamped information reflecting the detected change in state of the storage receptacle; and then broadcast the updated advertising signal having a data available flag set within the updated advertising signal. Such a data available flag indicates the system's wireless accessory sensor node has the event information available for upload by the bridge node and the event information includes at least the timestamped information reflecting the detected change in state of the storage receptacle.

(553) In light of such a system embodiment illustrated in FIGS. **38A-38C** and described above, those skilled in the art will appreciate that another related embodiment involves a method for enhanced customer identification related to a delivery item being deposited with a node-based logistics receptacle implemented by the above-described system components. FIGS. **39A-39B** collectively are a flow diagram illustrating an exemplary method **3900** for enhanced customer identification related to a delivery item being deposited with a node-based logistics receptacle in accordance with an embodiment of the invention. In such an exemplary method **3900**, the node-based logistics receptacle used may be implemented with exemplary node-based logistics receptacle **38150**, which has multiple monitored storage receptacle components (including at least an entrance opening **155** for receiving one or more shipping items, a temporary storage area **205** for temporarily maintaining the one or more shipping items once received, and a retrieval door **160** providing selective access to the one or more shipping items within the temporary storage area). The node-based logistics receptacle used in implementing exemplary method **3900** further has a wireless accessory sensor node coupled to multiple sensors (e.g., exemplary wireless accessory sensor node **210**) disposed on the node-based logistics receptacle and a receptacle bridge node (e.g., exemplary bridge node **200**) disposed on the node-based logistics receptacle operative to communicate with a backend server (e.g., exemplary backend server **100**).

(554) Referring now to FIG. **39A**, exemplary method **3900** begins at step **3905** with the wireless accessory sensor node monitoring for a change in state of the storage receptacle using the sensors. At step **3910**, method **3900** proceeds with the wireless accessory sensor node detecting the change in state of the storage receptacle based upon sensor data generated by at least one of the sensors. If a change is detected, step **3910** proceeds to step **3915**. If a change is not yet detected, then method **3900** proceeds back to step **3905** for continued monitoring for a sensor-based change in state of the storage receptacle. In more detail, an embodiment of method **3900** may implement step **3910** based upon sensor data generated by one of the sensors monitoring the entrance opening (e.g., a sensor

generating motion sensor data related to motion of the entrance opening, motion sensor data related to motion of an object through the entrance opening, and the like). Another embodiment of step **3910** may have the step of detecting the change in state of the storage receptacle being based upon sensor data generated by another of the sensors monitoring the temporary storage area (e.g., a sensor generating sensor data such as motion sensor data related to motion of an object within the temporary storage area, image sensor data related a change of contents maintained within the temporary storage area, weight sensor data related a change in weight of what is stored within the temporary storage area, and the like). Those skilled in the art will further appreciate that such sensor data used to detect the sensor-based change in step **3910** may also be from a combination of sensors monitoring the same or different monitored storage receptacle components.

(555) At step **3915**, method **3900** proceeds with the wireless accessory sensor node broadcasting an updated advertising signal in response to the detected change in state of the storage receptacle. At step **3920**, method **3900** proceeds with detecting, by the bridge node, the updated advertising signal from the wireless accessory sensor node.

(556) At step **3925**, method **3900** proceeds with the bridge node detecting a wireless communication signal broadcast from a mobile user device associated with the parcel customer (e.g., exemplary signal **3820** being transmitted from mobile device **3805** used by parcel customer **3800**). If such a wireless communication signal is detected, step **3925** proceeds to step **3930**.

However, if such a wireless communication signal is not yet detected, then method **3900** remains in step **3925** to continue trying to detect such a wireless communication signal broadcast from a mobile user device associated with the parcel customer. A further embodiment of method **3900** may implement step **3925** with the bridge node receiving the wireless communication signal broadcast from the mobile user device associated with the parcel customer and recognizing the mobile user device as an authorized mobile user device based upon authorization data within the wireless communication signal. In more detail, recognizing the mobile user device as the authorized mobile user device may, for example, have the bridge node first identifying the authorization data within the wireless communication signal, comparing the authorization data to information on pre-authorized mobile user devices that are authorized to interact with logistics receptacle **38150** (e.g., information stored in exemplary pre-authorized identification information **3830**, which may be updated by backend server **100**), and then recognizing the mobile user device as the authorized mobile user device based upon the results of comparing the authorization data to the information on the pre-authorized mobile user devices.

(557) At step **3930**, method **3900** proceeds with the bridge node transmitting a validation message (e.g., exemplary validation message **3835**) to the mobile user device associated with the parcel customer in response to the detected wireless communication signal and the detected updated advertising signal. For example, an exemplary validation message may request confirmation that the parcel customer has deposited the delivery item in the storage receptacle. In another example, an exemplary validation message may request authentication information from the parcel customer related to the delivery item (e.g., authentication information that includes shipping information related to the delivery item, authentication information that identifies the delivery item, and/or authentication information that identifies the parcel customer).

(558) At step **3935**, method **3900** proceeds with the bridge node receiving a validation confirmation message (e.g., exemplary validation confirmation message **3840**) from the mobile user device associated with the parcel customer. For example, an exemplary validation confirmation message may provide requested authentication information from the parcel customer related to the delivery item (such as shipping information related to the delivery item, information that identifies the delivery item, and/or information that identifies the parcel customer).

(559) After step **3935**, method **3900** proceeds through Transition A (shown at the bottom of FIG. **39A**) to step **3940** on FIG. **39B**, where method **3900** continues with the bridge node determining whether the validation confirmation message authenticates the parcel customer. If the validation

confirmation message authenticates the parcel customer, step **3940** proceeds to step **3945**. However, if the validation confirmation message does not authenticate the parcel customer (e.g., indicating the mobile user device **3805** or parcel customer **3800** is not authorized to use or otherwise interact with exemplary logistics receptacle **38150**), then method **3900** proceeds to step **3950**.

(560) At step **3945**, method **3900** proceeds with the bridge node transmitting event information to the backend server when the validation confirmation message authenticates the parcel customer. Such event information includes at least information reflecting the detected change in state of the storage receptacle.

(561) At step **3950** where the validation confirmation message did not authenticate the customer (e.g., the parcel customer **3800** or the mobile user device **3805** associated with the parcel customer **3800**), an embodiment of method **3900** may have the bridge node notifying the backend server about the non-authentication related to the delivery item and parcel customer. The backend server **100** may track such non-authenticated attempts to use the particular logistics receptacle **38150** and may take further action based upon the notification (e.g., update the pre-authorized identification information **3830**, contact the parcel customer **3800** via messaging to relay alternative logistics receptacle information where the parcel customer **3800** may be authenticated & authorized to use, and the like). This also may have the advantage of early awareness of an unauthorized deposit in exemplary logistics receptacle **38150** and the ability to take corrective action (as a type of further action based on the notification) on the part of the server. Such corrective action, for example, may have the backend server responsively initiating a corrective logistics operation where a logistics asset is dispatched with particularity to retrieve a specific delivery item deposited in that node-based logistics receptacle **38150** where such a deposit was proactively detected, determined to be unauthorized (e.g., performed by a non-authenticated customer), and notification of such an unauthorized deposit was reported to the server **100** by the bridge node **100** in the node-based logistics receptacle **38150**.

(562) At step **3955**, an embodiment of method **3900** may have the bridge node transmitting a re-authentication request message to the mobile user device and returning, through Transition B, to step **3935** on FIG. **39A** where the bridge node can receive another validation confirmation message (e.g., an attempt to correct information previously provided by the mobile user device **8305** and another attempt to authenticate the mobile user device and/or the parcel customer).

(563) Further embodiments of method **3900** may also have the bridge node accessing and updating custodial control information (e.g., exemplary custodial control information **3825**). For example, an embodiment of method **3900** may include a further step of updating, by the bridge node, custodial control information maintained within the bridge node related to custody of the delivery item when the validation confirmation message authenticates the parcel customer. In such an example, the event information transmitted to the backend server in step **3945** may also include updated custodial control information related to the delivery item.

(564) Those skilled in the art will also appreciate that event information transmitted to the backend server as part of step **3945** when the validation confirmation message authenticates the parcel customer may cause the backend server to initiate a dispatched logistics operation related to the storage receptacle (e.g., a pickup operation where the server dispatches a logistics asset to the location of exemplary node-based logistics receptacle **38150**). Such event information may include timing information related to the detected change in state of the storage receptacle, an identification of the delivery item, and/or an updated custodial control information related to the delivery item.

(565) Enhanced Status Indication Functionality for a Node-Based Logistics Receptacle

(566) Further embodiments of an exemplary connected node-based logistics receptacle have enhanced status indication functionality. Such embodiments deploy different types of exemplary status update notifications to reflect a status of the particular exemplary connected node-based logistics receptacle (e.g., its operational status and ability to effectively accept a delivery item that

may be efficiently serviced during a logistics operation).

(567) FIG. **40** is a diagram illustrating an exemplary enhanced connected logistics receptacle having enhanced status indication functionality related to a logistics operation for a delivery item being deposited by a parcel customer in accordance with an embodiment of the invention.

Referring now to FIG. **40**, exemplary connected logistics receptacle **40150** is shown operative to communicate with backend server **100** with components similar to exemplary logistics receptacle **150** described relative to FIG. **2**. Those skilled in the art will appreciate that exemplary connected logistics receptacle **40150** shown in FIGS. **40** and **42A-42D** is similarly structured to exemplary connected/node-based logistics receptacle **150** and **150a**, with the exception that exemplary receptacle **40150** is equipped with an exemplary bridge node **40200** (shown in more detail in FIG. **41**) that uses further types of data (e.g., a status indicator setting profile **4115**, customer registry file **4120**, and a history of prior event information **4125**) and equipped with different types of status indicators. As such, exemplary receptacle **40150** includes an embodiment of monitoring and management code for execution by the processor in bridge node **40200** (controlling functionality of bridge node **40200** in such additional embodiments) and use of such data (e.g., status indicator setting profile **4115**, customer registry file **4120**, and a history of prior event information **4125**) maintained within memory **305/310** of bridge node **40200** as part of enhanced status indication functionality implemented in exemplary connected logistics receptacle **40150**. Those skilled in the art will appreciate that backend server **100** may, in some embodiments, transmit updates to the status indicator setting profile **4115** and/or customer registry file **4120** (and prior event information **4125** in some cases) for use by the exemplary connected logistics receptacle **40150**. Those skilled in the art will also appreciate, as explained in more detail below, that bridge node **40200** may update the prior event information **4125** based upon its own detection and retrieval of event information.

(568) As shown in FIG. **2**, exemplary logistics receptacle **150** includes externally disposed user interface **255**, which may have one or more display, keys, status lights, touchscreens, buttons, switches, and/or speaker for interacting with a shipping customer and/or logistics personnel. Consistent with this and as shown in FIG. **40**, exemplary connected logistics receptacle **40150** is shown including exemplary display-based user interface **255a** and exemplary externally exposed status light **255a** as examples of types of a status indicator disposed on the logistics receptacle **40150**. Exemplary connected logistics receptacle **40150** is also shown including an exemplary electronically actuated physical indicator **4000** as a type of status indicator. Those skilled in the art will appreciate that exemplary electronically actuated physical indicator **4000** is disposed on the storage receptacle and operable to be actuated between a first position (corresponding to a first condition for receptacle **40150**) to a second position (corresponding to the second condition for receptacle **40150**). For example, the electronically actuated physical indicator **4000** may be implemented with an actuator **4005** that changes the position of a deployable indicator **4010** from a recessed position to an elevated or deployed position **4010'**. Such a deployable indicator **4010** may, for example, be implemented with a flag, board, colored object, or other physical symbol that is representative of a particular operational state of the receptacle **40150** (e.g., accepting or no longer accepting any more parcels) and actuatable to different positions. In another example, the electronically actuated physical indicator **4000** may be implemented with an electronically illuminated message visibly shown on another display-based user interface disposed on the storage device (e.g., on a display such as display **255a** that may be actuated to a different and more visible position so as to attract the attention of a parcel customer attempting to use receptacle **40150**).

(569) In more detail, FIG. **41** is a detailed diagram of exemplary bridge node **40200** used within the exemplary enhanced connected logistics receptacle **40150** having enhanced status indication functionality (via exemplary status indicators **4130**) in accordance with an embodiment of the invention. Referring now to FIG. **41**, exemplary bridge node **40200** is illustrated with components (e.g., hardware and software elements) similar to that explained with respect to exemplary bridge

node **200** (FIG. 3), but exemplary bridge node **40200** is expressly shown having status indicator setting profile **4115**, customer registry file **4120**, and prior event information **4125** as additional data used in the operation of the bridge node **40200** as explained in more detail below. Exemplary status indicators **4130** (e.g., actuated physical indicator **4000**, user interface display **255a**, light(s) **255b**) are coupled to the bridge node processor **201** of bridge node **40200** through interface circuitry **300**.

(570) As such, an exemplary connected logistics receptacle system embodiment with enhanced status indication as shown in FIGS. **40** and **42A-42D** includes exemplary connected logistics receptacle **40150** having a storage receptacle for receiving and maintaining a delivery item (as previously described having monitored storage receptacle components, such as an entrance opening, a temporary storage area **205** and selectively accessible retrieval door **160**). The system's exemplary connected logistics receptacle **40150** is equipped with at least exemplary bridge node **40200**, exemplary wireless accessory sensor nodes (such as node **210**), and sensors **450a-450e** that are coupled to at least one of the wireless accessory sensor nodes on receptacle **40150**. The system's exemplary bridge node **40200**, consistent with previously descriptions, is mounted to the storage receptacle and includes a bridge node processor **201**, a bridge node memory **202** (e.g., volatile memory **310** and non-volatile memory **305**), and a wireless communication interface **203**. As noted above and shown in FIG. **41**, the bridge node memory is coupled to the bridge node processor and maintains an embodiment of monitoring and management code capable of enhanced status indication (e.g., a type of CLR control and management code **315**) for execution by the bridge node processor along with at least exemplary status indicator setting profile **4115**, customer registry file **4120**, and prior event information **4125** that may be used during execution of the monitoring and management code as explained below. The communication interface is coupled to the bridge node processor and is operative to communicate with at least the backend server **100** over a first communication path (e.g., exemplary network **105**).

(571) Consistent with the description above, the system embodiment uses at least one exemplary wireless accessory sensor node (e.g., node **210**) coupled to a plurality of sensors (e.g., sensors **450a-450e**) where each of the sensors respectively monitors for a change in state of the storage receptacle. Such sensors, as described above, may generate sensor data related to motion of the entrance opening, motion of objects moving through the entrance opening, motion of an object within the temporary storage area, image sensor data related a change of contents maintained within the temporary storage area, weight sensor data related a change in weight of what is stored within the temporary storage area, and the like. The system's exemplary wireless accessory sensor node **210** is operative to detect the change in state of the storage receptacle related to at least one of the monitored storage receptacle components based upon sensor data generated by at least one sensor and broadcast an updated advertising signal in response to the detected change in state of the storage receptacle. The updated advertising signal indicates event information is available for upload by bridge node **40200**, where the event information is related to the detected change in state of the storage receptacle.

(572) The bridge node processor within the system's exemplary bridge node **40200**, when executing the monitoring and management code maintained on the bridge node memory, is operative to detect the updated advertising signal broadcast by the wireless accessory sensor node, retrieve the event information from the wireless accessory sensor node in response to detecting the updated advertising signal, and toggle the status indicator from the first condition (e.g., a condition related to a first operational state of the storage receptacle indicating the storage receptacle remains operative to accept an additional delivery item) to the second condition (e.g., another condition related to a second operational state of the storage receptacle indicating the storage receptacle is at least temporarily unable to accept an additional delivery item) based upon a comparison of the event information to the status indicator setting profile (e.g., data within profile **4115**).

(573) In more detail, the event information in such a system embodiment may reflect or otherwise

indicate a pickup event. For example, the event information may be or include timing information on the detected change in state of the storage receptacle and a type of the detected change in state of the storage receptacle (e.g., a state of a selectively accessible retrieval door providing access to within the storage receptacle) where the event information corresponds to a pickup event for the storage receptacle.

(574) Additional detailed system embodiments may compare the event information and data within the status indicator setting profile with more specificity. For example, the system's bridge node processor, when executing the monitoring and management code maintained on the bridge node memory, may be operative to toggle the status indicator by being further operative to toggle the status indicator from the first condition to the second condition may be implemented programmatically to occur when the comparison reflects timing information on the detected change in state of the storage receptacle as indicated in the event information is within a time threshold as defined by the status indicator setting profile. In another example, toggling the status indicator from the first condition to the second condition may be implemented programmatically to occur when the comparison reflects (a) a contents threshold has been detected as the detected change in state of the storage receptacle indicated in the event information and (b) a time threshold defined by the status indicator setting profile has been reached. In still another example, toggling the status indicator from the first condition to the second condition may be implemented programmatically to occur when the comparison reflects a contents threshold defined by the status indicator setting profile has been reached as the detected change in state of the storage receptacle indicated in the event information. In yet another example, toggling the status indicator from the first condition to the second condition may be implemented programmatically to occur when the comparison reflects (a) a pickup event corresponds to the detected change in state of the storage receptacle as indicated in the event information and (b) a time threshold defined by the status indicator setting profile has been reached. And in still another example, toggling the status indicator from the first condition to the second condition may be implemented programmatically to occur when the comparison reflects a time threshold defined by the status indicator setting profile has been reached.

(575) Further embodiments may adjust the status indicator setting profile **4115** as maintained within the system's bridge node **40200**. In other words, the bridge node processor, when executing the monitoring and management code maintained on the bridge node memory, may be further operative to adjust the status indicator setting profile **4115**. For example, the bridge node processor, when executing the monitoring and management code maintained on the bridge node memory, may be operative to adjust the status indicator setting profile **4115** by being operative to receive a remote adjustment message from the backend server **100** (where the remote adjustment message indicates an alteration to the contents of the status indicator setting profile **4115**) and adjust the status indicator setting profile **4115** according to the remote adjustment message.

(576) In another example, the bridge node processor, when executing the monitoring and management code maintained on the bridge node memory, may be further operative to transmit the event information to the backend server **100** to update the backend server **100** related to the storage receptacle. Thereafter, the bridge node processor may adjust the status indicator profile **4115** by being operative to receive a remote adjustment message from the backend server **100** in response to the transmitted event information (where the remote adjustment message indicates an alteration to the contents of the status indicator setting profile **4115**), and adjust the status indicator setting profile **4115** according to the remote adjustment message.

(577) In still another example, the bridge node processor, when executing the monitoring and management code maintained on the bridge node memory, may be operative to adjust the status indicator setting profile by being operative to generate an update of the status indicator setting profile based at least upon the event information; and adjust the status indicator setting profile according to the update of the status indicator setting profile. In a similar example, the bridge node processor may be operative to generate the update of the status indicator setting profile based at

least upon the event information and a history of prior event information maintained on the bridge node memory (e.g., data stored in exemplary prior event information **4125**).

(578) FIGS. **42A-42D** are diagrams illustrating different examples of how the exemplary enhanced connected logistics receptacle **40150** having enhanced status indication functionality of FIG. **40** may generate and transmit an exemplary status update notification to different types of external devices in accordance with an embodiment of the invention. In FIGS. **42A-42D**, exemplary external devices are shown that may receive such status update notifications and include, for example, a laptop **4200**, a desktop computer or terminal **4205**, a mobile handheld communication device **3805a** (e.g., smartphone, tablet, augmented reality (AR) headset type of interactive communication device, or the like) operated by a parcel customer **3800a**, mobile handheld communication device **2630** (e.g., smartphone, tablet, augmented reality headset device, or the like) that is used by courier personnel **2615** operated as a type of mobile wireless transceiver associated with mobile logistics asset **700a** (e.g., using delivery vehicle **2602**), and exemplary mobile transceiver **2600** as a type of vehicle-based wireless transceiver associated with the mobile logistics asset **700a** associated with delivery vehicle **2602**. Those skilled in the art will appreciate that such devices **3805a** (similar to exemplary device **3805**) and **2630** may be implemented with augmented reality enhanced functionality similar to that described above. Those skilled in the art will also appreciate that such examples of an external device that may, according to embodiments, receive status update notifications to report a change of the status indicator and/or take the place of the physical implementation of a status indicator change on the receptacle **40150** as a mechanism for enhanced status indication.

(579) How such a status update notification is provided to such external devices may be accomplished in a variety of ways. As shown in FIG. **42A**, an example shows an exemplary status update notification **4210a** may be provided (e.g., broadcast) to one or more of the different exemplary external devices in a manner that avoids the need to make use of network **105** (e.g., via Bluetooth or other short range communication paths). In FIG. **42B**, an example shows how exemplary receptacle **40150** (e.g., bridge node **40200** within receptacle **40150**) may transmit an exemplary status update notification **4210b** to one or more of the different exemplary external devices in a manner that uses network **105** as part of the communication path from the bridge node **40200** to the particular external device. Accordingly, further system embodiments may have the bridge node processor of bridge node **40200** being operative to generate a status update notification (such as notification **4210a**, **4210b**) based upon the comparison of the event information to the status indicator setting profile **4115** and then transmit, using the communication interface **203** of bridge node **40200**, the status update notification to at least one external user device.

(580) In other embodiments, information (such as status update notification information or simply the event information retrieved) may be sent to the server **100**, which then generates its own status update notification to external user devices (and may include logistics assets with logistics personnel). As shown in FIG. **42C**, an example shows how exemplary receptacle **40150** (e.g., bridge node **40200** within receptacle **40150**) may transmit information **4215** (e.g., event information) to backend server **100**, which then generates and transmits an exemplary status update notification **4210c** via network **105** to one or more of the different exemplary external devices. In more detail, a further system embodiment may have the bridge node processor **201** of bridge node **40200**, when executing the monitoring and management code maintained on the bridge node memory, being further operative to generate a status update notification based upon the comparison of the event information to the status indicator setting profile **4115**; and transmit, using the communication interface **203** of bridge node **40200**, the status update notification **4210c** to one or more external user devices identified in customer registry file **4120** maintained on the bridge node memory. Bridge node **40200** may, in such an example embodiment, receive the customer registry file **4120** from backend server **100** (as well as updates to the customer registry file **4120** from backend server **100**).

(581) A further system embodiment may, instead of toggling a physical status indicator on the node-based logistics receptacle, rely on transmitting the relevant status notification to others related to the updated operation status of the node-based logistics receptacle. In more detail, for example, a logistics receptacle similar to that of receptacle **150** may be used with exemplary bridge node **40200** where the bridge node's processor **201** is operative to detect the updated advertising signal broadcast by the wireless accessory sensor node and retrieve the event information from the wireless accessory sensor node in response to detecting the updated advertising signal. Thereafter, the bridge node's processor **201** may then generate a status update notification based upon the comparison of the event information to the status indicator setting profile (where the status update notification indicates a change from a first operational state of the storage receptacle to a second operational state of the storage receptacle based upon the comparison of the event information to the status indicator setting profile **4115**), and transmit the generated status update notification to at least one external user device operated by another parcel customer that warns the other parcel customer of the existence of the second operational state of the storage receptacle (e.g., that the logistics receptacle is at least temporarily unable to accept an additional delivery item).

(582) In still further embodiments, an exemplary system may use a physical status indicator, but be operative to toggle the status indicator based on remote input from the backend server **100** after the server **100** receives the reported event information. As shown in FIG. **42D**, an example shows how exemplary receptacle **40150** (e.g., bridge node **40200** within receptacle **40150**) may transmit information **4220** (e.g., event information) to backend server **100**, which then generates and transmits an exemplary status change command, causing the bridge node **40200** to generate and broadcast exemplary status notification update **4210d** to one or more of the different exemplary external devices (which may be done using network **105** or without using network **105**). In more detail, a further system embodiment may have the bridge node processor **201** of bridge node **40200**, when executing the monitoring and management code maintained on the bridge node memory, being further operative detect the updated advertising signal broadcast by the wireless accessory sensor node and retrieve the event information from the wireless accessory sensor node in response to detecting the updated advertising signal. The bridge node's processor is then operative to transmit (via the communication interface **203**) the event information to the backend server **100** to update the backend server **100** related to the storage receptacle. The bridge node's processor is further operative to receive, from the backend server **100**, a status change command generated by the backend server **100** based upon the event information and a status indicator setting profile maintained on the backend server **100**, and toggle the status indicator on receptacle **40150** from the first condition to the second condition based upon the received status change command.

(583) Further still, a system embodiment (with or without physical status indicators) may have the bridge node processor, when executing the monitoring and management code maintained on the bridge node memory, being operative to detect the updated advertising signal broadcast by the wireless accessory sensor node and retrieve the event information from the wireless accessory sensor node in response to detecting the updated advertising signal. The bridge node processor is also operative to cause the communication interface to transmit the event information to the backend server **100** to update the backend server **100** related to the storage receptacle. The bridge node processor, via the communication interface, is also operative to receive, from the backend server, a status change command generated by the backend server **100** based upon the event information and a status indicator setting profile maintained on the backend server **100**; generate a status update notification based upon the status change command (where the status update notification indicates a change from a first operational state of the storage receptacle to a second operational state of the storage receptacle based upon status change command received from the backend server **100**); and transmit, via the communication interface, the status update notification to at least one external user device operated by another parcel customer that warns the another parcel customer of the existence of the second operational state of the storage receptacle.

(584) Advanced Self-Tuning with a Contextually Aware Node-Based Logistics Receptacle
(585) Additional embodiments of an exemplary node-based logistics receptacle may be deployed with more contextual awareness related to the receptacle's physical environment and around the receptacle's operation as well as self-learning and training. Such embodiments may take advantage of environmental context information—such as traffic patterns, time of year, holidays, sales events, mortgage closing rates, weather, and the like to predict changes in future interactions with the exemplary node-based logistics receptacle. As explained in more detail below via the embodiments and description, strategic use of a variety of types of external sensing (e.g., motion sensors, machine vision, and the like) help monitor the environment where the exemplary node-based logistics receptacle is installed.

(586) FIG. 43 is a diagram illustrating aspects of an exemplary system for self-tuning operation of an exemplary node-based logistics receptacle based upon contextual awareness in accordance with an embodiment of the invention. Referring now to FIG. 43, exemplary connected logistics receptacle 43150 is shown operative to communicate with backend server 100 with components similar to exemplary logistics receptacle 150 described relative to FIG. 2. Those skilled in the art will appreciate that exemplary connected logistics receptacle 43150 shown in FIGS. 43 and 45A-47 is similarly structured to exemplary connected/node-based logistics receptacle 150 and 150a, with the exception that exemplary receptacle 43150 is equipped with an exemplary bridge node 43200 (shown in more detail in FIG. 44) that uses further types of data maintained on the bridge node 43200 (e.g., an exemplary management profile 4400 and environmental context data 4405) and operative to use different types of external sensors (e.g., an external sensor used with external sensor node 250 as part of receptacle 43150, exemplary external sensor 4300 disposed external to and separate from receptacle 43150). As such, exemplary receptacle 43150 includes an embodiment of monitoring and management code for execution by the processor in bridge node 43200 (controlling functionality of bridge node 43200 in such additional embodiments) and use of such data (e.g., exemplary management profile 4400 and environmental context data 4405) maintained within memory 305/310 of bridge node 43200 as part of enhanced self-tuning functionality based upon contextual awareness implemented in exemplary connected logistics receptacle 43150. Those skilled in the art will appreciate that backend server 100 may, in some embodiments, transmit updates to the exemplary management profile 4400 and/or environmental context data 4405 for use by the exemplary connected logistics receptacle 43150. Those skilled in the art will also appreciate, as explained in more detail below, that bridge node 43200 may update the exemplary management profile 4400 and/or environmental context data 4405 based on operations of receptacle 43150 without an update command or data from backend server 100.

(587) As shown in FIG. 2, exemplary logistics receptacle 150 includes exemplary external sensor node 250 having at least one sensor (e.g., motion sensor, proximity sensor, range sensor, and the like) that monitors the near-by or local environment proximate to exemplary connected logistics receptacle 150. Consistent with this and as shown in FIG. 43, exemplary connected logistics receptacle 43150 is shown including exemplary external sensor node 250 having at least one sensor that is disposed on receptacle 43150. Those skilled in the art will appreciate that the externally focused sensor coupled to external sensor node 250 may be disposed relative to logistics receptacle 43150 so as to have a sensing orientation to monitor particular locations proximate receptacle 43150 and/or particular externally viewable parts of receptacle 43150 (such as the entrance opening).

(588) As shown in FIG. 43, exemplary bridge node 43200 is shown as operable to communicate with (e.g., in communication with) another external sensor 4300 that is disposed external to and separate from the node-based logistics receptacle. As such, those skilled in the art will appreciate that an exemplary external sensor used in the embodiments that follow may be part of receptacle 43150 and coupled to bridge node 43200 (e.g., with or without using external sensor node 250 as an intermediary device that couples the external sensor to the bridge node) and/or may be separate

from receptacle **43150** but operative to generate and provide external sensor data to bridge node **43200**. Exemplary external sensors may be implemented with, for example, a motion sensor that generates motion sensor data as the external sensor data, an imaging sensor that generates image sensor data (e.g., via a security camera from a network of security cameras) as the external sensor data, or a machine vision sensor that generates video sensor data as the image sensor data). (589) In more detail, FIG. **44** is a detailed diagram of an exemplary bridge node **43200** used within the exemplary connected logistics receptacle **43150** of FIG. **43** in accordance with an embodiment of the invention. Referring now to FIG. **44**, exemplary bridge node **43200** is illustrated with components (e.g., hardware and software elements) similar to that explained with respect to exemplary bridge node **200** (FIG. **3**), but exemplary bridge node **43200** is expressly shown having exemplary management profile **4400** and environmental context data **4405** as additional data used in the operation of the bridge node **43200** as explained in more detail below. Exemplary external sensor **4300** is also shown coupled to the bridge node processor **201** of bridge node **43200** through interface circuitry **300**.

(590) As such, an exemplary system for self-tuning operation of exemplary node-based logistics receptacle **43150** based upon contextual awareness as shown in FIGS. **43** and **45A-47** includes exemplary connected logistics receptacle **43150** having a storage receptacle for receiving and maintaining a delivery item (as previously described having monitored storage receptacle components, such as an entrance opening, a temporary storage area **205** and selectively accessible retrieval door **160**). The system's exemplary connected logistics receptacle **43150** is equipped with at least exemplary bridge node **43200**, exemplary wireless accessory sensor nodes (such as node **210**, **250**, etc.), and sensors **450a-450e** that are coupled to at least one of the wireless accessory sensor nodes on receptacle **43150**. The system's exemplary bridge node **43200**, consistent with previously descriptions, is mounted to the storage receptacle and includes a bridge node processor **201**, a bridge node memory **202** (e.g., volatile memory **310** and non-volatile memory **305**), and a wireless communication interface **203**. As noted above and shown in FIG. **44**, the bridge node memory is coupled to the bridge node processor and maintains an embodiment of monitoring and management code capable of enhanced status indication (e.g., a type of CLR control and management code **315**) for execution by the bridge node processor along with at least exemplary management profile **4400** and environmental context data **4405** that may be used during execution of the monitoring and management code as explained below. The communication interface is coupled to the bridge node processor and is operative to communicate with at least the backend server **100** over a first communication path (e.g., exemplary network **105**).

(591) Consistent with the description above, the system embodiment uses an exemplary wireless accessory sensor node (e.g., node **210**) coupled to a plurality of sensors (e.g., sensors **450a-450e**) that collectively monitor the storage receptacle components of the node-based logistics receptacle **43150** and generate sensor data reflecting one or more interactions with one or more of the storage receptacle components of the node-based logistics receptacle **43150** over a recording time period. Such sensors, as described above, may generate sensor data related to motion of the entrance opening, motion of objects moving through the entrance opening, motion of an object within the temporary storage area, image sensor data related a change of contents maintained within the temporary storage area, weight sensor data related a change in weight of what is stored within the temporary storage area, and the like.

(592) The bridge node processor within the system's exemplary bridge node **43200**, when executing the monitoring and management code maintained on the bridge node memory, is programmatically operative to receive external sensor data generated by the external sensor (e.g., the external sensor used with external sensor node **250** and/or the external sensor **4300** disposed separate from receptacle **43150**) related to the local environment proximate the node-logistics receptacle **43150**. The system's bridge node processor is then operative to predict a change in future interactions with one or more of storage receptacle components of the node-based logistics receptacle **43150** based

upon the external sensor data received by the bridge node **43200**. The processor of bridge node **43200** is then programmatically operative to update the management profile **4400** stored within the bridge node memory **202** based upon the predicted change in future interactions with the storage receptacle components of the node-based logistics receptacle **43150** and alter, using the updated management profile **4400**, an operational task related to monitoring for and reporting a change in state of one or more of storage receptacle components of the node-based logistics receptacle **43150**. (593) In more detail, exemplary management profile **4400** as used within such a system embodiment, for example, may define the recording time period (e.g., a range of time during a day when the sensors monitor the storage receptacle components for one or more interactions with one or more of the storage receptacle components). Exemplary management profile **400** may, in some embodiments, define a predetermined time of day when the bridge node **43200** retrieves event information from the wireless accessory sensor node in response to detecting an updated advertising signal from the wireless accessory sensor node, where the event information includes at least information reflecting interaction(s) with one or more of the storage receptacle components of node-based logistics receptacle **43150** during the recording time period. Exemplary management profile **4400** may also define a transmission time when the bridge node **43200** sends retrieved event information to the backend server **100**.

(594) In some system embodiments, the memory of the system's bridge node **43200** (as shown in FIG. **44**) includes environmental context data **4405** as a type of contextual information locally stored that may be used as part of predicting the change in future interactions with the system's logistics receptacle **43150**. In more detail, an embodiment may have the bridge node memory maintaining environmental context data **4405** about the local operating environment of the node-based logistics receptacle **43150**. As such, the bridge node may then be programmatically operative to predict the change in the future interactions with one or more of storage receptacle components of the node-based logistics receptacle **43150** based upon the external sensor data received by the bridge node **43200** and at least a portion of the environmental context data. Exemplary environmental context data **4305** may, for example, be implemented with traffic data related to the location of the node-based logistics receptacle **43150**, weather data related to the location of the node-based logistics receptacle **43150**, crime data related to the location of the node-based logistics receptacle **43150**, holiday data related to the location of the node-based logistics receptacle **43150**, financial data associated with a financial transaction related to the location of the node-based logistics receptacle **43150** (e.g., mortgage rates, savings rates, lending fees, and the like related to that locality), seasonal activity data related to the location of the node-based logistics receptacle **43150**, and/or sales event data related to the location of the node-based logistics receptacle **43150**. (595) Further embodiments may have the bridge node being further programmatically operative to receive an update of the environmental context data **4405** about the local operating environment of the node-based logistics receptacle **43150**. For example, the system's bridge node may receive a first update of the environmental context data **4405** from the backend server **100** and receive a second update of the environmental context data **4405** from another network source of such locally relevant contextual data (e.g., a network memory storage device operative to communicate with bridge node **43200** via network **105**). In another example, the system's bridge node may be programmatically operative to generate a request for a context data update from the backend server **100** and transmit the request for the context data update to the backend server **100** using the communication interface **203**. The system's bridge node, in response to this request, is then operative to receive an update of the environmental context data **4405** about the local operating environment of the node-based logistics receptacle **43150** from the backend server **100** and update the environmental context data **4405** with the update of the environmental context data received from the backend server **100**.

(596) In some embodiments, the exemplary environmental context data may be locally stored by the system's bridge node **43200** in a database. For example, a system embodiment may also include

a contextual database (which may be part of memory **202** or separate from memory **202** depending on a desired implementation and amount of information to be stored, searched, and accessed). This contextual database is coupled to the system's bridge node **43200**, where the contextual database maintains the environmental context data **4405** about the local operating environment of the node-based logistics receptacle **43150**. Those skilled in the art will appreciate that the bridge node may also be programmatically operative to receive a database update for such a contextual database in a further example. Such a database update may include an update of some/all of the environmental context data **4405** about the local operating environment of the node-based logistics receptacle **43150**.

(597) As noted above, an exemplary system embodiment has the bridge node **43200** being operative to alter an operational task related to monitoring for and reporting a change in state of the one or more of storage receptacle components of the node-based logistics receptacle **43150**. In more detail, this may be implemented in more detailed embodiments, for example, by changing the recording time period, by changing the recording time period starting on a particular day, by temporarily changing the recording time period for a particular range of days, by changing the predetermined time of day when the bridge node **43200** retrieves event information from the wireless accessory sensor node, by changing the transmission time when the bridge node **43200** sends retrieved event information to the backend server **100**, and/or by changing when to request, from the backend server **100**, a dispatched logistics operation for the node-based logistics receptacle **43150**.

(598) FIGS. **45A-45D** are diagrams illustrating various examples of how exemplary node-based logistics receptacle **43150** of FIG. **43** using external sensors may enhance monitoring of a local environment proximate the exemplary enhanced connected logistics receptacle in accordance with an embodiment of the invention. Referring now to FIG. **45A**, exemplary node-based logistics receptacle **43150** is shown with graphic representations of how each of the external sensor associated with external sensing node **250** and the externally disposed external sensor **4300** monitor the local environment proximate the node-based logistics receptacle **43150**. Depending on the local environment, those skilled in the art will appreciate that different types of external sensors (as mentioned above) may be used and oriented so as to capture motion, movement, objects, and approaching people relative to receptacle **43150**.

(599) Referring now to FIG. **45B**, the external sensor data received by bridge node **43200** may identify an overflow condition for the exemplary node-based logistics receptacle **43150**. In an embodiment shown in FIG. **45B**, the bridge node **43200** may be programmatically operative to identify an overflow condition based upon at least a portion of the external sensor data. For example, a portion of the sensor data related to monitoring the entrance opening of receptacle **43150** may be used by bridge node **43200** to identify whether one or more packages **4500** have been left but are unable to be fully accepted within the receptacle **43150**. This may be the result of packages, letters, parcels and other object being deposited with receptacle **43150** but at a collectively level beyond an internal package holding capacity of receptacle **43150** as identified by separate external sensor **4300** or as identified by the sensor coupled to external sensor node **250**. The bridge node **43200** is then programmatically operative to predict the change in future interactions with one or more of the storage receptacle components of the node-based logistics receptacle based upon the external sensor data received by the bridge node **43200** and the identified overflow condition. The overflow condition may, in more detail and for example, be a condition of exemplary node-based logistics receptacle **43150** having exceeded an internal package holding capacity, a condition of exemplary node-based logistics receptacle **43150** identified using at least the portion of the external sensor data to have one or more parcels located outside and proximate to exemplary node-based logistics receptacle **43150**, or a condition of exemplary node-based logistics receptacle **43150** identified using at least the portion of the external sensor data to have one or more parcels visible in the entrance opening (e.g., where other parcels may be preventing the

visible parcels from passing through the entrance opening and no longer be visible).

(600) Referring now to FIG. **45C**, the external sensor data received by bridge node **43200** may identify a parcel customer for the exemplary node-based logistics receptacle **43150**. In an embodiment shown in FIG. **45C**, the bridge node may be programmatically operative to identify an approaching parcel customer (i.e., parcel customer **3800** carrying parcel **4505**) of the node-based logistics receptacle **43150** based upon at least a portion of the external sensor data. For example, and as shown in FIG. **45C**, external sensor data from each of the sensor coupled to external sensor node **250** and the external sensor **4300** may generate external sensor data used by bridge node **43200** to identify parcel customer **3800** as they approach logistics receptacle **43150**. Such external sensor data (or at least the portion used for identifying the parcel customer) may be image sensor data or video sensor data. In a further embodiment, such external sensor data may be an identified wireless signal broadcast by a mobile user device (e.g., smartphone, table, or other mobile electronic communication device) operated by the approaching customer. The bridge node **43200** may also be programmatically operative, in such an embodiment, to predict the change in future interactions with the one or more of the storage receptacle components of the node-based logistics receptacle based upon the external sensor data received by the bridge node and the identified approaching customer.

(601) Referring now to FIG. **45D**, the external sensor data received by bridge node **43200** may be used as part of confirming the drop off of an item with the exemplary node-based logistics receptacle **43150**. In an embodiment shown in FIG. **45D**, the bridge node is programmatically operative to receive the external sensor data by being further operative to confirm drop off of the delivery item (e.g., parcel **4505**) based upon at least a portion of the external sensor data prior to predicting the change in the future interactions with the one or more of the storage receptacle components of the node-based logistics receptacle. Thus, a more detailed example may have the bridge node being programmatically operative to receive the external sensor data by being further operative to identify the approaching customer of the node-based logistics receptacle **43150** based upon at least a first generated portion of the external sensor data; and confirm drop off of the delivery item by the approaching customer based upon a subsequently generated portion of the external sensor data prior to predicting the change in the future interactions with the one or more of the storage receptacle components of the node-based logistics receptacle **43150**.

(602) In such an example and in more detail, those skilled in the art will appreciate that the wireless accessory sensor node may be further operative to broadcast an updated advertising signal in response to the generated sensor data reflecting at least one interaction with the one or more of the storage receptacle components (e.g., the entrance opening) of the node-based logistics receptacle **43150** during the recording time period. The bridge node **43200**, in such an example, may be programmatically operative to receive the external sensor data and confirm drop off of the delivery item by being further operative to identify the delivery item with the approaching customer using a first part of the subsequently generated portion of the external sensor data, detect the updated advertising signal over the communication interface **203**, retrieve event information from the wireless accessory sensor node in response to detecting the updated advertising signal (where such event information includes at least information reflecting at least one interaction with the storage receptacle components of the node-based logistics receptacle **43150** during the recording time period), and then confirm drop off of the delivery item based upon the retrieved event information.

(603) In even more detail relative to such an example, those skilled in the art will appreciate that the wireless accessory sensor node may be further operative to broadcast an updated advertising signal in response to the generated sensor data reflecting at least one interaction with the one or more of the storage receptacle components (e.g., the entrance opening) of the node-based logistics receptacle **43150** during the recording time period. The bridge node **43200**, in this more detailed example, is programmatically operative to receive the external sensor data and confirm drop off of the delivery item by being further operative to identify the delivery item with the approaching

customer (e.g., parcel **4505** with customer **3800**) using a first part of the subsequently generated portion of the external sensor data, detect the updated advertising signal over the communication interface **203**, retrieve event information from the wireless accessory sensor node in response to detecting the updated advertising signal (where the event information includes at least information reflecting the interaction(s) with the one or more of the storage receptacle components of the node-based logistics receptacle **43150** during the recording time period, determine the approaching customer is moving away from the node-based logistics receptacle **43150** using a second part of the subsequently generated portion of the external sensor data, and confirm drop off of the delivery item (e.g., parcel **4505**) based upon the retrieved event information.

(604) FIGS. **46A-46C** are diagrams illustrating further examples of how the exemplary node-based logistics receptacle **43150** of FIG. **43** may enhance monitoring of a local environment proximate the exemplary enhanced connected logistics receptacle **43150** in accordance with an embodiment of the invention. In particular, FIGS. **46A-46C** provide examples of how exemplary bridge node **43200** may use the updated management profile **4400** to alter an exemplary operational task related to monitoring for and reporting a change in state of one or more of storage receptacle components of exemplary node-based logistics receptacle **43150**. Referring now to FIG. **46A**, exemplary node-based logistics receptacle **43150** is shown with exemplary bridge node **43200** being programmatically operative to alter, using the updated management profile **4400**, operation of the bridge node **43200** by initiating a new detection task related to a mobile user device **3805** operated by parcel customer **3800**. In more detail, bridge node **43200** may be operative to initiate the new detection task by being further operative to detect a signal **3820** from the mobile user device **3805** operated by the parcel customer **3800** (e.g., when device **3805** is executing an exemplary app **3810**) as the mobile user device **3805** approaches the node-based logistics receptacle **43150**.

(605) In another example illustrated in FIG. **46B**, exemplary bridge node **43200** is programmatically operative to alter, using the updated management profile **4400**, operation of the bridge node **43200** and initiate the new detection task by being further operative to identify a distance, D , from the approaching parcel customer **3800** to the node-based logistics receptacle **43150** based upon at least a first generated portion of the external sensor data. Those skilled in the art will appreciate that such a portion of the external sensor data may be generated using proximity sensor data, for example, relative to the external sensor(s).

(606) In yet another example illustrated in FIG. **46C**, exemplary bridge node **43200** is programmatically operative to alter, using the updated management profile **4400**, operation of the bridge node **43200** and initiate the new detection task by being further operative to determine how long the parcel customer **3800** is within a predetermined range, R , of exemplary node-based logistics receptacle **43150**. As shown in FIG. **46C**, parcel customer **3800** may be initially detected at a beginning time as crossing a threshold into the predetermined range R of receptacle **43150** (e.g., a physical distance). Exemplary bridge node **43200** may continue to monitor parcel customer **3800** while within such a range R and track the time parcel customer remains within such a range R . Alternatively (or in conjunction), bridge node **43200** may determine how long the parcel customer **3800** is within a predetermined range, R , of exemplary node-based logistics receptacle **43150** based upon how long bridge node **43200** detects a signal from mobile user device **3805** used by parcel customer **3800**. Further still, bridge node **43200** may determine how long a mobile user device **3805** operated by the parcel customer **3800** is within a predetermined range, R , of exemplary node-based logistics receptacle **43150** as a proxy for the parcel customer itself.

(607) Those skilled in the art will appreciate that the above-described system embodiments that involve self-tuning the operation of exemplary node-based logistics receptacle **43150** based upon contextual awareness may also include retrieval of event information. In more detail, a further embodiment may have the system's bridge node **43200** being programmatically operative to retrieve event information from the wireless accessory sensor node in response to receiving an updated advertising signal from the wireless accessory sensor node. Such an updated advertising

signal is related to at least one interaction with one or more of the storage receptacle components of exemplary node-based logistics receptacle **43150** during the recording time period.

(608) Those skilled in the art will appreciate that the above-described system embodiments that involve self-tuning the operation of exemplary node-based logistics receptacle **43150** based upon contextual awareness may also involve generating and transmitting a server notification related to external sensor data. In more detail, a further embodiment may have the system's bridge node **43200** being programmatically operative to generate a server notification related to at least a portion of the external sensor data; and transmit, over the communication interface **203**, the server notification to the backend server **100** to cause the backend server **100** to update a server-managed profile for the node-based logistics receptacle (e.g., information stored within exemplary management profile **835**). Likewise, an embodiment may have the system's bridge node **43200** being programmatically operative to generate a server management update related to the updated management profile; and transmit, over the communication interface, the server management update to the backend server to cause the backend server to update such a server-managed profile for the node-based logistics receptacle (e.g., exemplary management profile **835**).

(609) Those skilled in the art will appreciate that the above-described system embodiments that involve self-tuning the operation of exemplary node-based logistics receptacle **43150** based upon contextual awareness may also involve causing backend server **100** to change a particular dispatched logistics operation previously planned or scheduled for exemplary node-based logistics receptacle **43150**. In more detail, a further embodiment may have the system's bridge node **43200** being programmatically operative to retrieve event information from the wireless accessory sensor node in response to receiving an updated advertising signal from the wireless accessory sensor node (where the updated advertising signal is related to at least one interaction with the one or more of the storage receptacle components of exemplary node-based logistics receptacle **43150** during the recording time period. In this further embodiment, the system's bridge node **43200** may also be programmatically operative to transmit, using the communication interface **203**, a status update message to the backend server **100**. Such a status update message, for example, may reflect the retrieved event information and update the backend server **100** with at least a portion of the updated management profile **4400** (as updated by bridge node **43200**). This status update message causes the backend server **100** to alter a dispatched logistics operation for the node-based logistics receptacle **43150** based upon at least one of the retrieved event information and the portion of the updated management profile. In some embodiments, the status update message may cause the backend server **100** to alter a dispatched logistics operation for the node-based logistics receptacle **43150** based upon both of the retrieved event information and the portion of the updated management profile.

(610) FIG. **47** is a diagram illustrating an example of how the exemplary node-based logistics receptacle **43150** of FIG. **43** may use one or more external sensing elements of an external sensing infrastructure in accordance with an embodiment of the invention. In general, exemplary external sensing infrastructure may be available to an exemplary system embodiment as the external sensor (e.g., in place of or in addition to an external sensor disposed on receptacle **43150** or otherwise disposed separately from receptacle **43150**, such as exemplary external sensor **4300**). Referring now to FIG. **47**, the exemplary system embodiment illustrated using exemplary node-based logistics receptacle **43150** is shown having exemplary external sensing infrastructure **4700**, which may include multiple sensing elements **4705a-4705c** and a control node **4710** (e.g., a processor-based device interfacing with each of sensing elements **4705a-4705c** and operative to provide a remotely accessible interface for external sensing data generated by elements of external sensing infrastructure **4700**). Exemplary control node **4710** may provide a degree of control for each of the different sensing elements **4705a-4705c** (e.g., turning on/off particular sensing elements, gathering external sensor data generated by the different sensing elements **4705a-4705c**, and controlling access to such external sensor data).

(611) In some embodiments described below, those skilled in the art will appreciate that selective access to such external sensor data generated by one or more sensing elements **4705a-4705c** may be allowed and implemented via machine-to-machine (M2M) micropayment using blockchain techniques. In general, when exemplary node-based logistics receptacle **43150** desires access to an external source of sensor information (e.g., to confirm a sensed condition, such as when a door for its entrance opening is internally sensed to be stuck open), the exemplary node-based logistics receptacle **43150** in such a system embodiment may do so autonomously and securely using predefined pricing and access conditions defined in a self-executing smart contract between a seller (e.g., the owner of the external sensing infrastructure) and a purchaser (e.g., the owner of receptacle **43150**). For example, exemplary bridge node **43200** may selectively access a camera (e.g., an external sensing element having object detection capabilities) from a security system (a type of external sensing infrastructure) watching the street where the exemplary node-based logistics receptacle **43150** is located to validate or dismiss a potential overflow.

(612) Those skilled in the art will appreciate that such an exemplary smart contract may be generally considered as a self-executing agreed upon set of conditional rules with the terms of the agreement between the entities (e.g., between devices associated with such different entities) being directly written into lines of code (e.g., computerized transaction protocols that execute contract conditions making a transaction between devices/entities traceable, transparent and irreversible). Those skilled in the art appreciate that an exemplary smart contract is readily understood to, be tangibly implemented and considered a decentralized application on network **105** that executes logic (e.g., the programmatically coded conditional rules) in response to events where execution can result in the exchange of money, delivery of services (such as initiating use of a third party device), unlocking of content protected by digital rights management or other types of data manipulation (such as the exchange of sensor data gathered by the seller). Smart contracts may also be used to enforce privacy protection by, for example, facilitating the selective release of privacy-protected data to meet a specific request or permitting access to a particular secured area (such as the temporary storage area within receptacle **43150**) or initiating use of a third party device for a particular task.

(613) Referring back to FIG. **47**, a further system embodiment may have exemplary bridge node **43200** being operative to receive the external sensor data generated by the external sensor related to the local environment proximate the node-logistics receptacle **43150** by being further operative to communicate with the external sensing infrastructure **4700** over the communication interface **203** to establish a smart contract based connection with the external sensing infrastructure **4700**. In more detail, those skilled in the art will appreciate that establishing such a smart contract based connection by one network device with another network device may be generally accomplished with the execution of a smart contract application that will create and allow such a connection and interaction with the two network devices under terms of the smart contract.

(614) For example, this may involve running an exemplary decentralized application residing on one of the devices or on a part of network **105** representing the smart contract in response to events (such as a request to establish a smart contract based connection) by one device/entity with another device/entity. The smart contract facilitating (e.g., used in establishing) such a connection involves a transaction between the two devices/entities. Data representing payment for such a transaction (e.g., payment for establishing the smart contract based connection for use of data, for engagement between the devices/entities, for the performance of a service by one device/entity for the other device/entity, and the like) may be stored in an extendible chain in a distributed fashion on the network, such a distributed blockchain based virtual permanent ledger.

(615) Here, the smart contract based connection provides paid-for use of data generated by one (or more) of the sensing elements **4705a-4705c** of the external sensing infrastructure **4700**. As such, the system's exemplary bridge node **43200** may then receive the external sensor data as the data generated by the one (or more) sensing element(s) of the external sensing infrastructure **4700** under

terms of the smart contract based connection with the external sensing infrastructure **4700**. In more detail, such a smart contract based connection may, for example, be implemented by a protocol for an automated transaction stored on a blockchain and run in response to meeting at least a payment condition for receiving the data generated by the one (or more) sensing element(s) of the external sensing infrastructure **4700**. The smart contract based connection may, in some implementations, provide a cryptographically secure source of the data generated by the one (or more) sensing element(s) of the external sensing infrastructure **4700**. In some embodiments, the smart contract based connection may provide for receiving the data generated by the one (or more) sensing element(s) of the external sensing infrastructure **4700** under predetermined pricing terms as the payment condition. Such predetermined pricing terms may, for example, relate to a blockchain-based payment for access rights to the data generated by the one (or more) sensing element(s) of the external sensing infrastructure **4700** and/or a blockchain-based payment for access rights to the data generated by any of the sensing elements of the external sensing infrastructure. In another example, such predetermined pricing terms may relate to a blockchain-based payment on a per-access basis for access rights to the data generated by at least the one (or more) sensing element(s) of the external sensing infrastructure **4700**. Additionally, an example embodiment may have the smart contract based connection providing for receiving the data generated by the one (or more) sensing element(s) of the external sensing infrastructure **4700** under predetermined access conditions.

(616) Referring back to FIG. **47**, a further system embodiment may have exemplary bridge node **43200** being operative to detect when the receptacle **43150** needs to confirm a sensed condition with external sensor data. In more detail and for example, the system's exemplary bridge node **43200** may be further programmatically operative to receive the external sensor data generated by the external sensor related to the local environment proximate the node-logistics receptacle by being further operative to first identify a sensed state of at least one of the storage receptacle components of receptacle **43150** based upon internal sensor data generated by the wireless accessory sensor node when monitoring of the storage receptacle components, and then determine that the identified sensed state of the at least one of the storage receptacle components is a type of sensed state that warrants confirmation via external sensor verification. The exemplary bridge node **43200** is further operative to then communicate with the external sensing infrastructure **4700** over the communication interface **203** to establish a smart contract based connection with the external sensing infrastructure **4700** when the identified sensed state of the at least one of the storage receptacle components is the type of sensed state that warrants confirmation via external sensor verification. Here, the smart contract based connection provides at least paid-for use of data generated by the one (or more) sensing element(s) of the external sensing infrastructure **4700** under predetermined terms. The exemplary bridge node **43200** is then further operative to receive the external sensor data as the data generated by the one (or more) sensing element(s) of the external sensing infrastructure **4700** under the predetermined terms of the smart contract based connection with the external sensing infrastructure **4700**.

(617) In some embodiments, for example, the external sensing infrastructure **4700** may be a security system (e.g., exterior security system, interior security system, and the like) having sensing elements in form security cameras from a set of security cameras used by the security system (or at least a security camera in a set of sensors used by the security system that may have other non-camera sensors, such as door sensors, and the like). In other words, the external sensing infrastructure **4700** may be a camera-based monitoring system or at least have a visual-based sensor as part of the monitoring system.

(618) As shown in FIG. **47**, at least one of the exemplary external sensing elements **4705a-4705c** may be implemented as a security camera operably coupled to exemplary bridge node **43200** through a remotely accessible interface **4710** of the security system **4700** (e.g., camera-based monitoring system). As such, the exemplary bridge node **43200** may be further programmatically

operative to receive the external sensor data generated by the external sensor related to the local environment proximate the node-logistics receptacle **43150** by being further operative to establish a smart contract based connection with the security system **4700** (e.g., camera-based monitoring system) through the remotely accessible interface **4710** of the security system **4700** (e.g., camera-based monitoring system), and receive the external sensor data generated by the security camera over the remotely accessible interface **4710** of the security system **4700** (e.g., camera-based monitoring system) and the communication interface **203** of the bridge node **43200**.

(619) A further system embodiment, in event more detail, may have the bridge node **43200** being further programmatically operative to receive the external sensor data generated by the external sensor related to the local environment proximate the node-logistics receptacle **43150** by being further operative to (a) identify a sensed state of at least one of the storage receptacle components of receptacle **43150** based upon internal sensor data generated by the wireless accessory sensor node when monitoring of the storage receptacle components and (b) determine that the identified sensed state of the at least one of the storage receptacle components is a type of sensed state that warrants confirmation via external sensor verification. Exemplary bridge node **43200**, in this embodiment, is then further operative to (c) autonomously, in response to the determination in (b), establish a smart contract based connection with the external sensing infrastructure when the identified sensed state of the at least one of the storage receptacle components is the type of sensed state that warrants confirmation via external sensor verification (where the smart contract based connection provides at least paid-for use of data generated by one or more of the sensing elements **4705a-4705c** of the external sensing infrastructure **4700** under predetermined pricing and access conditions, and (d) receive the external sensor data as the data generated by the one of the sensing elements of the external sensing infrastructure under the predetermined pricing and access conditions of the smart contract based connection with the external sensing infrastructure. In this further system embodiment, exemplary bridge node **43200** may also be programmatically operative to (e) validate that the sensed state of the at least one of the storage receptacle components exceeds a threshold condition based upon the external sensor data as part of receiving the external sensor data.

(620) As such, exemplary bridge node **43200** in this embodiment may be programmatically operative to predict the change in future interactions by being operative to predict the change in future interactions based upon the external sensor data with consideration of the sensed state of at least one of the storage receptacle components based upon external sensor data. The bridge node **43200**, using such a prediction, may then transmit a confirmed condition message to the backend server **100** to cause the backend server **100** to responsively initiate a dispatched logistics operation to address the sensed state of at least one of the storage receptacle components based upon external sensor data.

(621) In yet a further embodiment, exemplary bridge node **43200** may be programmatically operative to predict the change in future interactions based upon the external sensor data while considering whether the sensed state of at least one of the storage receptacle components exceeds a threshold condition.

(622) Smart Contract Interactions Involving a Node-Based Logistics Receptacle

(623) In some embodiments set forth above, the embodiment's backend server and/or exemplary node-based logistics receptacle may interact with external third-party devices (such as external sensor networks operated by third parties or deployable mobile logistics assets operated by third parties) using exemplary smart contract agreements codified in tangible code that executes to govern the relative interactions. Those skilled in the art will appreciate that smart contracts are generally programmatic code stored on a blockchain that run automatically when predetermined rules are met. In more detail, an exemplary smart contract may be generally considered as a self-executing set of conditional rules with the terms of the agreed upon rules between the entities (e.g., between devices associated with such different entities) being directly written into lines of code

(e.g., computerized transaction protocols that execute contract conditions making a transaction between devices/entities traceable, transparent and irreversible). Those skilled in the art appreciate that an exemplary smart contract is not an abstract concept and, instead, is readily understood to be tangibly implemented and considered a decentralized application on network **105** that executes logic (e.g., the programmatically coded conditional rules) in response to events where execution can result in the exchange of money, delivery of services (such as initiating use of a third party device), unlocking of content protected by digital rights management or other types of data manipulation (such as the exchange of sensor data gathered by the seller). Smart contracts may also be used to enforce privacy protection by, for example, facilitating the selective release of privacy-protected data to meet a specific request or permitting access to a particular secured area (such as the temporary storage area within receptacle **43150**) or initiating use of a third party device for a particular task.

(624) Further embodiments described below and illustrated in FIGS. **70-73** provide details regarding an enhanced node-based logistics receptacle that may advantageously interact with different types of external devices where such interactions are facilitated and governed under conditions and/or terms of an exemplary smart contract embodied in code on a blockchain.

(625) FIG. **70** is a diagram illustrating an exemplary system for self-executing enhanced interaction with a node-based logistics receptacle in accordance with an embodiment of the invention.

Referring now to FIG. **70**, an embodiment is shown with exemplary node-based logistics receptacle **70150**, exemplary backend server **100**, and an exemplary external device capable of communication over network **105**, each of which are coupled to exemplary network **105**.

Exemplary connected node-based logistics receptacle **70150** is shown operative to communicate with backend server **100** with components similar to exemplary logistics receptacle **150** described relative to FIG. **2**. Those skilled in the art will appreciate that exemplary connected logistics receptacle **70150** shown in FIG. **70** is similarly structured to exemplary connected/node-based logistics receptacle **150** and **150a**, with the exception that exemplary receptacle **70150** is equipped with an exemplary bridge node **70200** and exemplary wireless accessory sensor node **210**, which may be coupled to exemplary sensors (such as sensors **450a-450e**). As such, exemplary receptacle **70150** includes an embodiment of monitoring and management code for execution by the processor in bridge node **70200** (controlling functionality of bridge node **70200**).

(626) As shown in FIG. **70**, exemplary network **105** is shown as having at least a portion being implemented with an exemplary peer-to-peer blockchain infrastructure **7005**. Those skilled in the art appreciate that exemplary peer-to-peer blockchain infrastructure **7005** may be implemented with blockchain protocol, which rides on top of Internet protocol (IP), and allows blockchain functions to be readily integrated into network-based applications. FIG. **70** further illustrates exemplary blockchain nodes **70150a-70150e** disposed within this exemplary peer-to-peer blockchain infrastructure **7005** part of network **105** that may be used with exemplary smart contract protocol code **7010**. In more detail, those skilled in the art will appreciate that the exemplary peer-to-peer blockchain infrastructure **7005** part of network **105**, as a blockchain network, includes a distributed database accessible by each of exemplary blockchain nodes **70150a-70150e**. Such a blockchain distributed database is a type of immutable ledger that is shared, distributed, fault-tolerant and an append-only database that maintains the records in “blocks” that facilitates transactions. In blockchain, data elements depicting an action or a transaction are stored in blocks combined in an on-going and growing chain, such as a block in a chain or sequence of transactions. Although the blocks are accessible by all the blockchain network users, they cannot be deleted or altered by them. The blocks are connected to each other in a chain as each block has a hash value of its predecessor. Each block contains several verified transactions. Also, each block includes a timestamp indicating the creation time of that block, and a random number (nonce) for cryptographic operations. As such, exemplary blockchain network **7005** consists of blockchain nodes **70150a-70150e** that maintain the blockchain in a peer-to-peer, distributed fashion where

blockchain nodes **70150a-70150e** have access to the blocks, but they cannot completely control them. The blockchain technology allows the communicating entities/devices coupled to network **105** (and exemplary blockchain network **7005**) to interact in the absence of a trusted third-party. The interactions are recorded in the distributed blockchain database available to each node. When such an entity/device (e.g., a blockchain user/device/entity) needs to communicate with or interact with another user/device/entity, it broadcasts its “transaction” to the blockchain network **7005**. Those skilled in the art will appreciate that nodes **70150a-70150e** in the network **7005** check if the communication/connection/interaction is valid and construct a new block of valid transactions (i.e., combining several valid transactions). If the new block is found valid, it is attached to the blockchain database and cannot be deleted or altered later. Otherwise, the block is dropped. Such blocks added, for example, may reflect a payment (e.g., machine-to-machine (M2M) micropayment) under predetermined pricing terms as explained in more detail below.

(627) As noted above, FIG. **70** further illustrates the exemplary blockchain nodes **70150a-70150e** disposed within this exemplary peer-to-peer blockchain infrastructure **7005** part of network **105** with exemplary smart contract protocol code **7010**. And as previously explained above, those skilled in the art will appreciate that such an exemplary smart contract protocol code **7010** is generally considered as a self-executing agreed upon set of conditional rules with the terms of the agreement between the entities (e.g., between devices associated with such different entities) being directly written into lines of code (e.g., computerized transaction protocols that execute contract conditions making a transaction between devices/entities traceable, transparent and irreversible). Those skilled in the art appreciate that exemplary smart contract protocol code **7010** is readily understood to be tangibly implemented via blockchain nodes **70150a-70150e** and considered a decentralized application on network **105** that executes the lines of code (e.g., the programmatically coded conditional rules) in response to events where execution can result in the exchange of money, delivery of services and/or data (such as initiating use of an external device **7000** or access to data generated by an external device **7000**), unlocking of a trusted access privilege (such as an access privilege granted to external device **7000** or those operating device **7000**). In other words, exemplary smart contract protocol code **7010** may facilitate the selective release of data from external device **7000** to meet a specific request, facilitate or initiate a service to be provided by external device **7000**, or permit trusted access by external device **7000** (or its operators) to a particular secured area (such as the temporary storage area within receptacle **70150**).

(628) As shown in FIG. **70**, an embodiment of a system for self-executing enhanced interaction with exemplary node-based logistics receptacle **70150** is illustrated. Exemplary E node-based logistics receptacle **70150**, similar to that described for receptacle **150**, has different storage receptacle components including at least an entrance opening **155/156** for receiving a delivery item, a temporary storage area **205** for temporarily maintaining the delivery item once received, and a retrieval door **160** providing selective access to the delivery item within the temporary storage area **205**. The system embodiment includes a wireless accessory sensor node (e.g., node **210** disposed on exemplary node-based logistics receptacle **70150**) and a bridge node (e.g., exemplary bridge node **70200** disposed on exemplary node-based logistics receptacle **70150**). In some embodiments, those skilled in the art will appreciate that such a system may include the node-based logistics receptacle while other embodiments may more generally include just the receptacle's bridge node and a wireless accessory sensor node as elements. In other words, the storage receptacle components (e.g., an entrance opening for receiving the delivery item, a temporary storage area for temporarily maintaining the delivery item once received, and a retrieval door providing selective access to the delivery item within the temporary storage area) may be elements of a system embodiment along with the receptacle's bridge node and a wireless accessory sensor node as elements.

(629) The wireless accessory sensor node **210** has or is coupled to sensors (e.g., sensors **450a-450e**) that collectively monitor the storage receptacle components of the node-based logistics receptacle

70150, where each of the sensors being operative to generate sensor data reflecting one or more interactions with one or more of the storage receptacle components of the node-based logistics receptacle **70150**. Such interactions may, for example, be passing of the delivery item through the entrance opening, movement of the entrance opening, deposit of the delivery item within the temporary storage area **205**, and a change in status of the retrieval door **160**.

(630) Exemplary bridge node **70200** (similar to that in exemplary bridge node **200**) has a bridge node processor **201**, a bridge node memory **202** coupled to the bridge node processor **201**, and a communication interface **203** coupled to the bridge node processor **201**. The bridge node memory **202** of exemplary bridge node **70200** maintains an embodiment of monitoring and management code for execution by the bridge node processor **201**. During execution of such code, bridge node processor **201** of exemplary bridge node **70200** becomes programmatically operative to upload information related the sensor data from the wireless accessory sensor node **210** in response to a signal broadcast by the wireless accessory sensor node **210** and detect an external device **7000** separate from the node-based logistics receptacle **70150** over the communication interface **203**.

(631) During execution of such code, bridge node processor **201** of exemplary bridge node **70200** is further programmatically operative to communicate with the external device **7000** over the communication interface to establish a smart contract based connection with the external device **7000** (where the smart contract based connection provides an interaction privilege associated with the external device **7000**), interface with the external device **7000** according to the interaction privilege, and transmit an update message to the backend server using the communication interface, the update message corresponding to at least a portion of the uploaded information related to the sensor data and information related to interfacing with the external device.

(632) In such a system embodiment, those skilled in the art will appreciate that establishing such a smart contract based connection by one network device (e.g., exemplary bridge node **70200**) with another network device (e.g., external device **7000**) may be generally accomplished with the execution of exemplary smart contract application **7010** (a type of decentralized application on the exemplary peer-to-peer blockchain infrastructure **7005** part of network **105**) that will create and allow such a connection and interaction with the two devices under terms of that smart contract application **7010**. In other words, an embodiment may involve running an exemplary decentralized application residing on one of the devices or on a part of network **105** representing the smart contract **7010** in response to detecting external device **7000**.

(633) FIGS. **71-73** provide more detailed examples with different types of external devices **7000** and what may be done in different embodiments when interfacing with exemplary external devices (e.g., exemplary external devices **7000a-7000c**) according to the smart contract based connection and the interaction privilege associated with that external device.

(634) In a more detailed example, FIG. **71** is a diagram illustrating another exemplary system for self-executing enhanced interaction with exemplary node-based logistics receptacle **70150** that interfaces with an exemplary source of data (e.g., external device **7000a**) related to an interaction with the node-based logistics receptacle **70150** in accordance with an embodiment of the invention. Those skilled in the art will appreciate that exemplary receptacle **70150** in this embodiment may operate similar to that of exemplary receptacle **43150** (which may use exemplary management profile **4400** and exemplary environmental context data **4405**) with respect to its ability to take advantage of exemplary smart contract application **7110** in establishing the connection with exemplary external device **7000a**.

(635) As shown in FIG. **71** (and similar to that shown in FIG. **70**), at least a portion of network **105** is similarly implemented with an exemplary peer-to-peer blockchain infrastructure **7105**. Those skilled in the art appreciate that exemplary peer-to-peer blockchain infrastructure **7105** may be implemented with blockchain protocol, which rides on top of Internet protocol (IP), and allows blockchain functions to be readily integrated into network-based applications. FIG. **71** further illustrates exemplary blockchain nodes **71150a-71150e** disposed within this exemplary peer-to-peer

blockchain infrastructure **7105** part of network **105** that may be used with exemplary smart contract application code **7110**.

(636) The system embodiment illustrated in FIG. **71** has exemplary external device **7000a** as an external source of data related to an interaction with the node-based logistics receptacle **70150**. As such, exemplary external device **7000a**, as an external data source (e.g., source of external sensor data), is operative to provide the bridge node **70200** with the data related to the interaction with the node-based logistics receptacle **70150** according to the interaction privilege provided by smart contract application **7110**. The exemplary bridge node **70200** on receptacle **70150** (similar to bridge node **43200** on receptacle **43150**) is programmatically operative to interface with the external device **7000a** according to the interaction privilege by being further operative to receive data related to the interaction (e.g., external sensor data) with the node-based logistics receptacle **70150** under terms defined by the interaction privilege from exemplary smart contract application **7110**.

(637) In FIG. **71** (similar to that shown in FIG. **47**), the smart contract based connection (based upon code in exemplary smart contract application **7110**) provides paid-for use of data generated by one (or more) of the sensing elements **4705a-4705c** of the external sensing infrastructure **4700** (as exemplary external device **7000a**) as data related to the interaction with the node-based logistics receptacle **70150**. As such, the system's exemplary bridge node **70200** may then receive the external sensor data as the data generated by the one (or more) sensing element(s) of the external sensing infrastructure **4700** (as a type of external device **7000a**) and related to the interaction with node-based logistics receptacle **70150** under terms of the smart contract based connection with the external sensing infrastructure **4700** governed by exemplary smart contract application **7110**. In more detail, such a smart contract based connection based upon code in exemplary smart contract application **7110** may, for example, be implemented by a protocol for an automated transaction stored on a blockchain and run in response to meeting at least a payment condition for receiving the data generated by the one (or more) sensing element(s) of the external sensing infrastructure **4700** and related to the interaction with node-based logistics receptacle **70150**. The smart contract based connection based upon code in exemplary smart contract application **7110** may, in some implementations, provide a cryptographically secure source of the data generated by the one (or more) sensing element(s) of the external sensing infrastructure **4700** and related to the interaction with node-based logistics receptacle **70150**. In some embodiments, the smart contract based connection based upon code in exemplary smart contract application **7110** may provide for receiving the data generated by the one (or more) sensing element(s) of the external sensing infrastructure **4700** related to the interaction with node-based logistics receptacle **70150** under predetermined pricing terms as the payment condition. Such predetermined pricing terms may, for example, relate to a blockchain-based payment for access rights to the data generated by the one (or more) sensing element(s) of the external sensing infrastructure **4700** (related to the interaction with node-based logistics receptacle **70150**) and/or a blockchain-based payment for access rights to the data generated by any of the sensing elements of the external sensing infrastructure (related to the interaction with node-based logistics receptacle **70150**). In another example, such predetermined pricing terms may relate to a blockchain-based payment on a per-access basis for access rights to the data generated by at least the one (or more) sensing element(s) of the external sensing infrastructure **4700** and related to the interaction with node-based logistics receptacle **70150**.

(638) Those skilled in the art will appreciate that in the system embodiment illustrated in FIG. **71**, exemplary external device **7000a** may be implemented as an external sensor operative to monitor the interaction with the node-based logistics receptacle **70150**, an external sensor operative to monitor a local environment proximate the node-based logistics receptacle **70150** for the interaction with the node-based logistics receptacle **70150**, an external sensing infrastructure having at least one sensing element (such as sensing element **4705a**) operative to monitor the interaction with the node-based logistics receptacle **70150**, and an external sensing infrastructure having at least one sensing element (such as an image sensor, video sensor, or a machine vision

sensor operative to identify an object (e.g., parcel approaching the receptacle **70150**) in the local environment proximate the node-based logistics receptacle **70150**) as part of monitoring the interaction operative to monitor a local environment proximate the node-based logistics receptacle **70150** for the interaction with the node-based logistics receptacle **70150**.

(639) In more detail, the smart contract based connection established via exemplary smart contract application **7110** may provide an interaction privilege associated with the external device **7000a** where the interaction privilege defines a time-based privilege restricting when the bridge node **70200** is allowed to interface with the external device **7000a** and receive the interaction related data/information. In another example, such an interaction privilege defines a cost-based privilege associated with when the bridge node **70200** interfaces with the external device **7000a** to receive the information to receive the interaction related data/information. In still another example, the interaction privilege defines an identity-based privilege associated whether the bridge node **70200** is authorized to interface with the external device **7000a** to receive the related data/information.

(640) In another detailed example, FIG. 72 illustrates another exemplary system for self-executing enhanced interaction with exemplary node-based logistics receptacle **70150** that interfaces with an exemplary external device **7000b** where external device **7000b** provides a service related to an interaction with exemplary node-based logistics receptacle **70150** in accordance with an embodiment of the invention. As shown in FIG. 72 (and similar to that shown in FIG. 70), at least a portion of network **105** is similarly implemented with an exemplary peer-to-peer blockchain infrastructure **7205** (similar to that of exemplary peer-to-peer blockchain infrastructure **7105** and **7005**). Those skilled in the art appreciate that exemplary peer-to-peer blockchain infrastructure **7205** may be implemented with blockchain protocol, which rides on top of Internet protocol (IP), and allows blockchain functions to be readily integrated into network-based applications. FIG. 72 further illustrates exemplary blockchain nodes **72150a-72150e** disposed within this exemplary peer-to-peer blockchain infrastructure **7205** part of network **105** that may be used with exemplary smart contract application code **7210**.

(641) The system embodiment illustrated in FIG. 72 has exemplary external device **7000b** as an external logistics asset related to an interaction with the node-based logistics receptacle **70150**. As such, exemplary external device **7000b** is an exemplary external logistics asset (such as exemplary replacement deployable mobile logistics receptacle **51020r**) operative to provide a dispatched logistics operation relative to the node-based logistics receptacle **70150** under terms defined by the interaction privilege from exemplary smart contract application **7210**.

(642) The exemplary bridge node **70200** on receptacle **70150** in the embodiment shown in FIG. 72 is programmatically operative to interface with the external device **7000b** according to the interaction privilege by being further operative to permissively interface with the external device **7000b** (e.g., exemplary replacement deployable mobile logistics receptacle **51020r**) as part of a dispatched logistics operation relative to the node-based logistics receptacle **70150** under self-executing terms of the smart contract based connection and the interaction privilege based upon code in exemplary smart contract application **7210**. In more detail, such a smart contract based connection based upon code in exemplary smart contract application **7210** may, for example, be implemented by a protocol for an automated transaction stored on a blockchain and run in response to meeting at least a payment condition as the interaction privilege for providing the dispatched logistics operation relative to the node-based logistics receptacle **70150**. Such a payment condition may, for example, relate to a blockchain-based payment for authorized interaction with the node-based logistics receptacle **70150** or a blockchain-based payment on a per-logistics operation basis for the authorized interaction with the node-based logistics receptacle **70150**.

(643) In one embodiment, exemplary external device **7000b** may be implemented as an external wireless transceiver operated by a logistics asset (mobile logistics receptacle **51020r**) providing the dispatched logistics operation relative to the node-based logistics receptacle **70150** under the smart contract based connection and the interaction privilege based upon code in exemplary smart

contract application **7210**. Such an external wireless transceiver may, for example, be implemented as a vehicle-based transceiver or a mobile transceiver operated by personnel associated with the logistics asset.

(644) In the system embodiment illustrated in FIG. **72**, the interaction privilege based upon code in exemplary smart contract application **7210** may, for example, define a time-based privilege restricting when the bridge node **70200** is allowed to interface with the external logistics asset **7000b**, a cost-based privilege associated with when the bridge node **70200** interfaces with the external logistics asset **7000b**, and/or an identity-based privilege associated whether the bridge node **70200** is authorized to interface with the external logistics asset **7000b**.

(645) In yet another detailed example, FIG. **73** illustrates another exemplary system for self-executing enhanced interaction with exemplary node-based logistics receptacle **70150** that interfaces with an exemplary external device **7000c** where external device **7000c** may be entrusted with access (also referred to as provided with a trusted access privilege) to within exemplary node-based logistics receptacle **70150** as another type of interaction with exemplary node-based logistics receptacle **70150** in accordance with an embodiment of the invention. As shown in FIG. **73** (and similar to that shown in FIG. **70**), at least a portion of network **105** is similarly implemented with an exemplary peer-to-peer blockchain infrastructure **7305** (similar to that of exemplary peer-to-peer blockchain infrastructure **7205**, **7105** and **7005**). Those skilled in the art appreciate that exemplary peer-to-peer blockchain infrastructure **7305** may be implemented with blockchain protocol, which rides on top of Internet protocol (IP), and allows blockchain functions to be readily integrated into network-based applications. FIG. **73** further illustrates exemplary blockchain nodes **73150a-73150e** disposed within this exemplary peer-to-peer blockchain infrastructure **7305** part of network **105** that may be used with exemplary smart contract application code **7310**.

(646) The system embodiment illustrated in FIG. **73** has exemplary external device **7000c** as an external mobile logistics asset **700a** that may interact with node-based logistics receptacle **70150** by depositing items within receptacle **70105** or retrieving items from within receptacle **70150** via a type of trusted access provided via exemplary smart contract application code **731**. In more detail, the interaction privilege based upon code in exemplary smart contract application **7310** may be a trusted access privilege relative to exemplary node-based logistics receptacle **70150**, such as a trusted access privilege for authorized access to within the node-based logistics receptacle **70150**. Thus, in the system embodiment illustrated in FIG. **73**, an example may have bridge node **70200**, when executing the monitoring and management code, being programmatically operative to interface with the external device **7000c** according to the trusted access privilege by being further operative to transmit a privilege inquiry through the communication interface **203** to the external device **7000c** (e.g., to one of transceivers **2600**, **2630**, which may be augmented reality devices); receive a privilege response in response to the privilege inquiry through the communication interface **203** from the external device **7000c**; and provide access to within the node-based logistics receptacle **70150** when the privilege response corresponds to an access right granted by the trusted access privilege based upon code in exemplary smart contract application **7310**. Providing such access to within node-based logistics receptacle **70150** may, for example, have bridge node **70200** being operative to actuate the retrieval door **160** from a secured position to an unsecured position. Exemplary bridge node **70200** may, in some embodiments, also be operative to record (or cause to be recorded) a blockchain-based payment for providing the access to within the node-based logistics receptacle **70150** in accordance with the trusted access privilege and the privilege response. Furthermore, exemplary bridge node **70200** may be operative to record (or cause to be recorded) the blockchain-based payment by being further operative to update a blockchain-based ledger on infrastructure **7305** to reflect the blockchain-based payment.

(647) In some embodiments, an exemplary trusted access privilege based upon code in exemplary smart contract application **7310** may, for example, define a time-based access privilege restricting when the bridge node **70200** is allowed to provide access to within the node-based logistics

receptacle **70150** (e.g., a time of day access privilege restricting when the bridge node **70200** is allowed to provide access to within the node-based logistics receptacle **70150** and/or a day of week access privilege restricting when the bridge node **70200** is allowed to provide access to within the node-based logistics receptacle **70150**). In another example, an exemplary trusted access privilege based upon code in exemplary smart contract application **7310** may, for example, define a cost-based privilege associated with a payment associated with when the bridge node **70200** provides access to within the node-based logistics receptacle **70150**. In still another example, an exemplary trusted access privilege based upon code in exemplary smart contract application **7310** may, for example, define an identity-based privilege associated whether the bridge node **70200** is authorized to provide access to within the node-based logistics receptacle **70150** for a logistics entity associated with the external device **7000c** (e.g., mobile logistics entity **700a**, which has vehicle-based transceiver **2600** on vehicle **2602** and mobile transceiver **2630** operated by personnel **2615** associated with mobile logistics asset **700a**).

(648) In some embodiments involving such a trusted access privilege defined by code in exemplary smart contract application **7310**, exemplary bridge node **70200** may validate the interaction (e.g., monitor what or how much is taken out or placed within receptacle **70150**) during such trusted access. For example, exemplary bridge node **70200** may be operative to interface with the external device **7000c** according to the trusted access privilege by being further operative to transmit a privilege inquiry through the communication interface **203** to the external device **7000c** (e.g., one or more of transceivers **2600**, **2630**); receive a privilege response in response to the privilege inquiry through the communication interface from the external device **7000c**; provide access to within the node-based logistics receptacle **70150** when the privilege response corresponds to an access right granted by the trusted access privilege; and validate what is taken out of the node-based logistics receptacle **70150** after providing access to within the node-based logistics receptacle **70150**. Validating, for example, may have bridge node **70200** being operative to detect what is taken out of the node-based logistics receptacle **70150** and whether what is detected as taken out is greater than a threshold occupancy level within the node-based logistics receptacle **70150**. In more detail, this may have bridge node **70200** being operative to detect what is taken out of the node-based logistics receptacle **70150** is greater than the threshold occupancy level within the node-based logistics receptacle **70150** based upon subsequent capacity information uploaded from an onboard wireless accessory sensor node (e.g., sensor data gathered by node **210**) as a result of interfacing with the external device **7000c** under terms of the trusted access privilege. A further example may have exemplary bridge node **70200** being operative to transmit a capacity update message to the backend server **100** using the communication interface **203** based upon the subsequent capacity information uploaded from the wireless accessory sensor node **210**. Still another example may have bridge node **70200** being operative to transmit such a capacity update message to the backend server **100** using the communication interface **203** when what is taken out of the node-based logistics receptacle **70150** is greater than the threshold occupancy level within the node-based logistics receptacle **70150** based upon the subsequent capacity information uploaded from the wireless accessory sensor node **210**.

(649) Enhanced Interaction with a Mobile Equipped Parcel Customer

(650) In further embodiments, an exemplary node-based logistics receptacle may sense an approaching parcel customer and interact with the parcel customer with knowledge of an anticipated drop off of a delivery item. Based upon the detection of such a potential parcel customer, the exemplary node-based logistics receptacle may interact with the approaching parcel customer through the customer's mobile device to, for example, verify if a deposit was or is to be made outside of the exemplary node-based logistics receptacle and coordinate with the backend server to initiate a dispatched logistics operation (e.g., pickup operation) with a higher level of urgency. The parcel customer's mobile device, in some examples, may be an augmented reality type of device (e.g., an AR headset having sensory, user input, and communication capabilities) that

helps free the parcel customer's hands from device operation and focus on carrying the delivery item itself. In some examples, the node-based logistics receptacle may use external sensor data (e.g., from an onboard externally focused sensor or a separately disposed external sensor) to generate carrying confirmation data on whether the parcel customer is carrying a delivery item as part of such enhanced interaction where a drop off verification confirmation message and detected placement of the delivery item may be used to trigger communications with the backend server on initiating an appropriate dispatched logistics operation to service the node-based logistics receptacle.

(651) FIGS. **74A-74C** are diagrams illustrating an exemplary system for enhanced interaction with a node-based logistics receptacle during an external drop off of a delivery item by a parcel customer operating a mobile user device in accordance with embodiments of the invention. Referring now to FIG. **74A**, exemplary node-based logistics receptacle **74150** is shown operative to communicate with backend server **100** with components similar to exemplary logistics receptacle **150** described relative to FIG. **2**. Those skilled in the art will appreciate that exemplary connected logistics receptacle **74150** shown in FIGS. **74A-76C** is similarly structured to exemplary connected/node-based logistics receptacle **150** and **150a**, with the exception that exemplary receptacle **74150** is equipped with an exemplary bridge node **74200** that uses further types of data maintained on the bridge node **74200** (e.g., exemplary anticipated entity data **e** shown and exemplary carrying confirmation data **7500**) and operative to use different types of external sensors that monitor interactions with receptacle **74150** and areas proximate to receptacle **74150** (e.g., an external sensor used with external sensor node **250** as part of receptacle **74150**, exemplary external sensor **4300** disposed external to and separate from receptacle **74150**). As such, exemplary receptacle **74150** includes an embodiment of monitoring and management code for execution by the processor in bridge node **74200** (controlling functionality of bridge node **74200** in such additional embodiments) and use of such data (e.g., exemplary anticipated entity data **7400** shown and exemplary carrying confirmation data **7500**) maintained within memory **305/310** of bridge node **74200** as part of enhanced interaction between exemplary node-based logistics receptacle **74150** and a mobile user device **3805** equipped parcel customer **3800** as implemented in exemplary node-based logistics receptacle **74150**. Those skilled in the art will appreciate that backend server **100** may, in some embodiments, transmit updates to the exemplary anticipated entity data **7400** for use by the exemplary connected logistics receptacle **74150**.

(652) As shown in FIG. **2**, exemplary logistics receptacle **150** includes exemplary external sensor node **250** having at least one sensor (e.g., motion sensor, proximity sensor, range sensor, and the like) that monitors the near-by or local environment proximate to exemplary connected logistics receptacle **150**. Consistent with this and as shown in FIGS. **74A-76C**, exemplary connected logistics receptacle **74150** is shown including exemplary external sensor node **250** having at least one sensor that is disposed on receptacle **74150**. Those skilled in the art will appreciate that the externally focused sensor coupled to external sensor node **250** may be disposed relative to logistics receptacle **74150** so as to have a sensing orientation to monitor particular locations proximate receptacle **74150** for any externally deposited parcel or delivery item.

(653) Referring back to FIG. **74A**, an exemplary system for enhanced interaction with node-based logistics receptacle **74150** during an external drop off of a delivery item **170** by a parcel customer **3800** operating mobile user device **3805** is illustrated. In general, an embodiment of such an exemplary system includes a wireless accessory sensor node (such as exemplary wireless accessory sensor node **210**) and a bridge node (such as exemplary bridge node **74200**), each of which are disposed on the node-based logistics receptacle **74150**.

(654) In this system embodiment, the wireless accessory sensor node includes at least one internal sensor that collectively monitors one or more of the storage receptacle components (e.g., entrance opening, temporary storage area, selectively accessible retrieval door) of the node-based logistics receptacle **74150** and generates internal sensor data reflecting an interaction with one or more of

the storage receptacle components of the node-based logistics receptacle **74150**. For example, such an internal sensor monitoring an entrance opening to the node-based logistics receptacle **74150** may be implemented with a variety of different types of internal sensors, such as a motion sensor detecting a change in motion of the entrance opening, a motion sensor detecting the change in motion of the entrance opening and a failure to return to a prior state of the one or more of the entrance opening, a motion sensor detecting movement of what passes through the entrance opening, an inertial sensor detecting a change in motion of the entrance opening, a status sensor detecting a change in orientation of the entrance opening, an accelerometer detecting a change in motion of the entrance opening, and/or a magnetic sensor detecting a change in position of the entrance opening. In another example, such an internal sensor monitoring the temporary storage area within the node-based logistics receptacle **74150** may be implemented with different types of sensors, such as an image sensor detecting a change in what is within the temporary storage area, a scale detecting a change in what is within the temporary storage area, a force sensor detecting a change in what has been deposited within the temporary storage area, a light sensor detecting a change in light within the node-enabled logistics receptacle, and/or a chemical sensor detecting presence of a chemical within the temporary storage area. In yet another example, the internal sensor monitoring the selectively accessible retrieval door on the node-based logistics receptacle **74150** may be implemented with different types of sensors, such as a motion sensor detecting a change in state of the selectively accessible retrieval door, a motion sensor detecting a change in state of the selectively accessible retrieval door and a failure to return to a prior state of the selectively accessible retrieval door, an inertial sensor detecting a change in inertial motion of the selectively accessible retrieval door, a gyroscopic sensor detecting a change in movement of the selectively accessible retrieval door, a status sensor detecting a change in orientation of the selectively accessible retrieval door, a magnetic sensor detecting a change in position of the selectively accessible retrieval door, and/or a lock sensor detecting a change in secured state of the selectively accessible retrieval door.

(655) In this system embodiment, the wireless accessory sensor node also includes (e.g., is coupled to) an external sensor that monitors a local environment proximate the node-based logistics receptacle **74150**. Such an external sensor (e.g., the external sensor used with and coupled to exemplary wireless accessory sensor node **250**) is operative to generate external sensor data relative to the local environment proximate the node-based logistics receptacle **74150** where such external sensor data is then used, for example, to detect and confirm if a delivery item has been placed near the receptacle **74150** as part of customer **3800** externally depositing such a delivery item. For example, and in more detail, such an external sensor may be implemented with an external motion, image or video sensor detecting a change in what has been placed within a predetermined range of the node-based logistics receptacle **74150** representative of the local environment proximate the node-based logistics receptacle **74150**. In another example, such an external sensor may be a machine vision sensor operative to identify an object in the local environment proximate the node-based logistics receptacle **74150** and detect a change in what has been placed within a predetermined range of the node-based logistics receptacle **74150** representative of that local environment based upon the identified object (e.g., package **170**). In still another example, the external sensor may be a range sensor (e.g., a proximity sensor, a depth sensor, a LiDAR sensor, an infrared sensor, and a laser-based sensor) detecting the change in what has been placed within the predetermined range of the node-based logistics receptacle **74150** representative of the local environment proximate the node-based logistics receptacle **74150**. Further still, an exemplary external sensor may be implemented with at least one of multiple sensing elements of an external sensing infrastructure disposed within a viewable range that includes the node-based logistics receptacle **74150**, where at least one of the sensing elements is operative to provide sensing element sensor data to the wireless accessory sensor node as the external sensor data. Those skilled in the art will appreciate that an exemplary wireless accessory

sensor node in such an embodiment may be coupled to different sensors (e.g., one or more internal sensors as well as one or more external sensors) consistent with the present disclosure.

(656) In this system embodiment, those skilled in the art will appreciate that the bridge node **74200** includes a bridge node processor, a bridge node memory coupled to the bridge node processor and maintaining monitoring and management code for execution by the bridge node processor, and a wireless transceiver-based communication interface coupled to the bridge node processor that is operative to communicate with at least backend server **100**.

(657) In operation when executing the monitoring and management code as part of this system embodiment, the bridge node processor of bridge node **74200** is programmatically configured so as to be operative to detect, using the communication interface, a wireless communication signal **3820** broadcast from the mobile user device **3805** operated by the parcel customer **3800**. In more detail, the bridge node processor of bridge node **74200** may be programmatically operative to detect the wireless communication signal **3820** broadcast by being further operative to detect an RF signature associated with the parcel customer **3800** (e.g., where such an RF signature is associated with at least one of the parcel customer **3800** and the mobile user device **3805** operated by the parcel customer **3800**). More specifically, another example of such detection may have the bridge node processor of bridge node **74200** being operative to detect the wireless communication signal **3820** by being further operative to detect an RF signature related to the wireless communication signal **3820** and identify the RF signature as corresponding to an anticipated drop off.

(658) In even more detail, yet another example of such detection may have the bridge node memory of bridge node **74200** maintaining anticipated entity data **7400** including entity information on one or more entity anticipated to make a deposit at the node-based logistics receptacle **74150**. In this example, the bridge node processor of bridge node **74200** may be programmatically operative to detect the wireless communication signal **3820** by being further operative to detect an RF signature related to the wireless communication signal **3820**, compare the RF signature with the entity information in the anticipated entity data **7400** maintained in the bridge node memory, and identify the RF signature as corresponding to an anticipated drop off entity based upon the results of that comparison. In some embodiments, the bridge node processor of bridge node **74200** may be receive, using the communication interface, an update to the anticipated entity data **7400**. Such an update to the anticipated entity data **7400** may, for example, have updated entity information on at least one additional entity anticipated to make a deposit at the node-based logistics receptacle **74150**.

(659) In further embodiments, the bridge node processor of bridge node **74200** may be programmatically operative to detect the wireless communication signal **3820** by being further operative to detect information associated with the parcel customer **3800** as part of a wireless message associated with or related to signal **3820** or another signal subsequently broadcast by mobile user device **3805**. Such information associated with the parcel customer **3800** and part of the wireless message may, for example, be associated with the mobile user device **3805** operated by the parcel customer **3800**. In more detail, the bridge node processor of bridge node **74200** may be programmatically operative to detect the wireless communication signal **3820** by being further operative to detect information associated with the parcel customer **3800** as part of a wireless message related to the wireless communication signal **3820**, and identify the information associated with the parcel customer **3800** as corresponding to an anticipated drop off entity. In even more detail, an example may have the bridge node processor of bridge node **74200** may be programmatically operative to detect the wireless communication signal **3820** by being further operative to detect information associated with the parcel customer **3800** as part of a wireless message related to the wireless communication signal **3820**, compare the information associated with the parcel customer **3800** with entity information in the anticipated entity data **7400** maintained in the bridge node memory, and identify the information associated with the parcel customer **3800** as corresponding to an anticipated drop off entity based upon that comparison.

(660) Referring now to FIG. 74B, the bridge node processor of bridge node **74200** in such a system embodiment is programmatically operative to detect placement of the delivery item **170** proximate the node-based logistics receptacle **74150** based upon the external sensor data generated by the external sensor and without information reflecting the interaction with the one or more of the storage receptacle components using the internal sensor data. In more detail, those skilled in the art will appreciate that the bridge node processor of bridge node **74200** in such a system embodiment is programmatically operative to detect the placement of the delivery item **170** proximate the node-based logistics receptacle **74150** (such as that shown in FIG. 74B) by being further operative to receive, from the system's wireless accessory sensor node, information corresponding to the external sensor data without receiving information corresponding to the internal sensor data. In even more detail, an example embodiment may have the bridge node processor of bridge node **74200** being programmatically operative to detect the placement of the delivery item **170** proximate the node-based logistics receptacle **74150** by being further operative to receive, from the system's wireless accessory sensor node, event information corresponding to the external sensor data; and receive, from the wireless accessory sensor node, non-event information generated by the wireless accessory sensor node representing a lack of physical interaction with the storage receptacle components. A further example with yet more detail may have the bridge node processor of bridge node **74200** being programmatically operative to detect the placement of the delivery item **170** proximate the node-based logistics receptacle **74150** by being further operative to detect, using the communication interface, an updated advertising signal generated by the system's wireless accessory sensor node; identify a flag set within the detected updated advertising signal; retrieve, using the communication interface, a status update from the system's wireless accessory sensor node in response to identifying the flag set; access event information corresponding to the external sensor data as part of the status update; confirm the status update does not include information representing a physical interaction with the storage receptacle components corresponding to the internal sensor data; and identify the placement of the delivery item **170** proximate the node-based logistics receptacle **74150** based upon the event information corresponding to the external sensor data.

(661) Once delivery item **170** is detected as being placed proximate the node-based logistics receptacle **74150**, the system's bridge node processor of bridge node **74200** in such a system embodiment is programmatically operative to responsively transmit, using the communication interface of bridge node **74200**, a verification message to the mobile user device **3805** operated by the parcel customer **3800**. In more detail, such a verification message may, for example, include a prompt for the parcel customer **3800** to verify that the delivery item **170** was placed outside of the node-based logistics receptacle **74150**. In another example, the verification message may include, for example, information provided to the mobile user device **3805** related to a request for the parcel customer **3800** to verify that the delivery item **170** was placed outside of the node-based logistics receptacle **74150**.

(662) The bridge node processor of bridge node **74200** in such a system embodiment is also programmatically operative to receive, using the communication interface, a verification confirmation message from the mobile user device **3805** operated by the parcel customer **3800**. Such a verification confirmation message, for example, may include a response from the mobile user device **3805** verifying that the delivery item **170** was placed outside of the node-based logistics receptacle **74150**. In more detail, the verification confirmation message may, for example, be a response from the mobile user device **3805** verifying that the delivery item **170** was placed outside of the node-based logistics receptacle **74150** for a future pickup logistics operation related to the node-based logistics receptacle **74150**.

(663) Those skilled in the art will appreciate that in some system embodiments, detecting placement of delivery item **170** and receipt of an exemplary verification confirmation message may automatically involve a smart contract based payment for use of the exemplary node-based

logistics receptacle **74150** related to the placed delivery item **170**. For example, an embodiment may have the bridge node processor of bridge node **74200** being further programmatically operative to communicate with the mobile user device **3805** over the communication interface, in response to receiving the verification confirmation message, to establish a smart contract based connection with the mobile user device **3805**, where such a smart contract based connection (e.g., via exemplary smart contract application code) provides terms for paid use of the node-based logistics receptacle **74150**. In more detail, such a smart contract based connection may include a protocol for an automated transaction via executable code stored on a blockchain and run in response to meeting at least a payment condition (e.g., predetermined pricing terms as reflected in the smart contract application code) for use of the node-based logistics receptacle **74150** in shipping the delivery item **170**. In particular, the predetermined pricing terms may, for example, relate to a blockchain-based payment for external deposit of the delivery item **170** proximate the node-based logistics receptacle **74150**. In some examples, the predetermined pricing terms relate to a blockchain-based payment for external deposit of the delivery item **170** proximate the node-based logistics receptacle **74150** during a predetermined time period (e.g., terms for particular hours during the day, terms for particular days of the week). Such predetermined pricing terms may also, for example, relate to a blockchain-based payment on a per-deposit basis for externally depositing one or more parcel items external to the node-based logistics receptacle **74150**.

(664) Referring now to FIG. **74C**, the bridge node processor of bridge node **74200** in such a system embodiment is programmatically operative to transmit, using the communication interface of bridge node **74200**, exemplary external deposit information **7405** to the backend server **100** related to the detected placement of the delivery item **170** based upon the verification confirmation message to cause the backend server **100** to initiate a dispatched logistics operation related to the node-based logistics receptacle **74150**. As shown in FIG. **74C**, backend server **100** receives exemplary deposit information **7405** reflecting the detected and customer confirmed placement of the delivery item **170**. In response, backend server **100** (with awareness of such an external placement of delivery item **170**) initiates the dispatched logistics operation by transmitting exemplary dispatch message **7410** to a particular logistics asset (such as exemplary logistics asset **700a**).

(665) In more detail and still with reference to FIG. **74C**, the external deposit information **7405** transmitted to the backend server **100** related to the detected placement of the delivery item **170** may, for example, include a priority level indicator to cause the backend server **100** to initiate the dispatched logistics operation related to the node-based logistics receptacle **74150** with a heightened level of urgency. Such a priority level indicator reflects, for example, that the delivery item **170** is deposited with the node-based logistics receptacle **74150** outside of a secured temporary storage area **205** within the node-based logistics receptacle **74150**.

(666) The initiated dispatch logistics operation by backend server **100** may, in more detail, be with a logistics asset capable of completing the dispatched logistics operation under a predetermined condition (e.g., a timing criteria related to pickup of the delivery item **170** deposited external to the node-enabled logistics receptacle **74150**). In another example, the initiated dispatch logistics operation by backend server **100** may, in more detail, be with a selected one of a multiple different logistics assets (e.g., similar logistics assets or a mix of different types of logistics assets), where the selected logistics asset being capable of completing the dispatched logistics operation under a predetermined time window for pickup of the delivery item **170**.

(667) This may, for example, have backend server **100** considering one or more for-hire logistics assets for the selected logistics asset to service node-based logistics receptacle **74150**. For example, the bridge node processor of bridge node **74200**, when executing the monitoring and management code, may be further programmatically operative to communicate with the for-hire logistics asset over the bridge node's communication interface to establish a smart contract based connection with the for-hire logistics asset when the for-hire logistics asset is the selected one of the logistics

dispatched by the backend server **100** for completing the dispatched logistics operation. Such a smart contract based connection provides terms for paid pickup of the delivery item **170** disposed external to the node-based logistics receptacle **74150**. As such, the for-hire logistics asset may be under payment terms defined by the smart contract based connection with the backend server when the for-hire logistics asset is selected.

(668) FIGS. **75A-75C** are diagrams illustrating another exemplary system for enhanced interaction with an embodiment of node-based logistics receptacle **74150** during an external drop off of a delivery item **170** by a parcel customer **3800** that involves detection of whether the parcel customer **3800** is carrying the delivery item **170** upon approach to the node-based logistics receptacle **74150** using an onboard external sensor in accordance with embodiments of the invention. Those skilled in the art will appreciate that the embodiment of exemplary node-based logistics receptacle **74150** (including exemplary internal and external sensors) shown in FIGS. **75A-75C** is similar to that of the example illustrated in FIGS. **74A-74C** and further includes exemplary carrying confirmation data **7500** maintained as part of the memory of bridge node **74200** and includes exemplary monitoring and management code that configures the bridge node processor of bridge node **74200** to be programmatically operative in a way that allows bridge node **74200** to detect whether customer **3800** is carrying a package or parcel or object that may be shipped (e.g., package **170**). In general, such a system embodiment may use the external sensor that is part of node-based logistics receptacle **74150** to detect an approaching parcel customer, detect whether the parcel customer is carrying a package or delivery item, send the customer a drop off verification message if detected to be carrying a package that prompts the customer to verify he/she is carrying such a package or delivery item, receive a customer response on whether the customer intends to place that package/delivery item outside of the node-based logistics receptacle, detect placement (with no detection of internal deposit), and respond to such placement with external deposit information being sent to the backend server to initiate a dispatched pickup.

(669) In more detail, such an additional system embodiment for enhanced interaction with a node-based logistics receptacle and a parcel entity (e.g., customer, logistics personnel, and the like) operating a mobile user device includes exemplary node-based logistics receptacle **74150** as shown in FIGS. **75A-75C** having a wireless accessory sensor node and a bridge node. The system's wireless accessory sensor node includes at least one internal sensor that collectively monitors one or more of the storage receptacle components of the node-based logistics receptacle **74150** and generates internal sensor data reflecting an interaction with one or more of the storage receptacle components of the node-based logistics receptacle. The system's wireless accessory sensor node also includes an external sensor for monitoring a local environment proximate the node-based logistics receptacle **74150**, the external sensor being operative to generate external sensor data relative to the local environment proximate the node-based logistics receptacle. The system's bridge node (e.g., bridge node **74200**) has a bridge node processor, a bridge node memory, and a communication interface. The bridge node memory is coupled to the bridge node processor and maintains an embodiment of monitoring and management code for execution by the bridge node processor as well as exemplary anticipated entity data **7400**. The bridge node's communication interface is coupled to the bridge node processor and is operative to communicate with at least backend server **100**.

(670) In this additional system embodiment, the bridge node processor of exemplary bridge node **74200** shown in FIGS. **75A-75C**, when executing the monitoring and management code, is programmatically operative to detect, using the communication interface, a wireless communication signal **3820** broadcast from the mobile user device **3805** operated by the parcel customer **3800** and identify the wireless communication signal **3820** as corresponding to an anticipated drop off entity. More specifically, the bridge node processor of bridge node **74200** may identify the wireless communication signal **3820** as corresponding to the anticipated drop off entity by being further operative to identify an RF signature from the wireless communication signal

3820 where the RF signature corresponds to the anticipated drop off entity. Such an RF signature may, for example, be associated with at least one of the parcel customer **3800** and the mobile user device **3805** operated by the parcel customer **3800**. In a more detailed example, the bridge node memory may maintain exemplary anticipated entity data **7400**, which includes entity information on one or more entities anticipated to make a deposit at the node-based logistics receptacle. As such, the bridge node processor of bridge node **74200**, when executing the monitoring and management code, may be programmatically operative to identify the wireless communication signal **3820** as corresponding to the anticipated drop off entity based upon comparing the RF signature with the entity information in the anticipated entity data **7400** maintained in the bridge node memory. In this system embodiment, bridge node **74200** may be further programmatically operative to receive, using the communication interface, an update to the anticipated entity data **7400** from backend server **100** where the update to the anticipated entity data **7400** has updated entity information on at least one additional entity anticipated to make a deposit at the node-based logistics receptacle **74150**.

(671) In another example, the bridge node processor of bridge node **74200** may identify the wireless communication signal **3820** as corresponding to the anticipated drop off entity by being further operative to identify information associated with the parcel customer **3800** as part of a wireless message in the wireless communication signal **3820**. Such information associated with the parcel customer **3800** as part of the wireless message may, in some instances, be associated with the mobile user device **3805** operated by the parcel customer **3800**. In more detail, the bridge node processor of bridge node **74200** may identify the wireless communication signal **3820** as corresponding to the anticipated drop off entity by being further operative to detect the information associated with the parcel customer **3800** as part of a wireless message related to the wireless communication signal **3820**, compare the information associated with the parcel customer **3820** with the entity information in the anticipated entity data **7400**, and identify the information associated with the parcel customer **3800** as corresponding to the anticipated drop off entity based upon such a comparison.

(672) In this additional system embodiment shown in FIGS. 75A-75C, the bridge node processor of exemplary bridge node **74200**, when executing the monitoring and management code, is programmatically operative to generate carrying confirmation data **7500** related to whether the parcel customer **3800** is carrying a delivery item (such as exemplary package **170**) based upon the external sensor data generated by the external sensor. For example, the external sensor data may be generated by a machine vision sensor capable of identifying such a delivery item being carried by parcel customer **3800** and discriminating it from other images in its field of view. Based upon such machine vision sensor data, bridge node **74200** may then generate information (i.e., carrying confirmation data **7500**) reflecting whether parcel customer has a delivery item in their position that may potentially be deposited with node-based logistics receptacle **74150**.

(673) In this additional system embodiment, the bridge node processor of exemplary bridge node **74200**, when executing the monitoring and management code, is programmatically operative to transmit, using the communication interface, a drop off verification message **7505** to the mobile user device **3805** operated by the parcel customer **3800** when the carrying confirmation data indicates the parcel customer **3800** is carrying the delivery item as shown in FIG. 75B. The drop off verification message **7505** includes a prompt for the parcel customer **3800** to verify that the parcel customer **3800** intends to place the delivery item **170** outside of the node-based logistics receptacle **74150**. The bridge node processor of exemplary bridge node **74200** is further operative to receive, using the communication interface, a drop off verification confirmation message **7510** from the mobile user device **3805** operated by the parcel customer **3805** as shown in FIG. 75B. The drop off verification confirmation message **7510** includes a response indicating whether the parcel customer **3800** intends to place the delivery item **1700** outside of the node-based logistics receptacle **74150**.

(674) The bridge node processor of exemplary bridge node **74200** is also operative to detect

placement of the delivery item **170** proximate the node-based logistics receptacle **74150** based upon subsequent external sensor data generated by the external sensor and without information reflecting the interaction with the one or more of the storage receptacle components using the internal sensor data. For example, and in more detail, the bridge node processor, when executing the monitoring and management code, may be programmatically operative to detect the placement of the delivery item **170** proximate the node-based logistics receptacle **74150** by being further operative to receive, from the wireless accessory sensor node, information corresponding to the subsequent external sensor data without receiving information corresponding to the internal sensor data. In a further example, the bridge node processor may be programmatically operative to detect the placement of the delivery item **170** proximate the node-based logistics receptacle **74150** by being further operative to receive, from the wireless accessory sensor node, event information corresponding to the external sensor data; and receive, from the wireless accessory sensor node, non-event information generated by the wireless accessory sensor node representing a lack of physical interaction with the storage receptacle components of node-based logistics receptacle **74150**. In still a more detailed example, the bridge node processor, when executing the monitoring and management code, may be programmatically operative to detect the placement of the delivery item **170** proximate the node-based logistics receptacle **74150** by being further operative to detect an updated advertising signal generated by the wireless accessory sensor node; identify a flag set within the detected updated advertising signal; retrieve, using the communication interface, a status update from the wireless accessory sensor node in response to identifying the flag set; access event information corresponding to the subsequent external sensor data as part of the status update; confirm the status update does not include information representing a physical interaction with the storage receptacle components corresponding to the internal sensor data; and then identify the placement of the delivery item **170** proximate the node-based logistics receptacle **74150** based upon the identified event information corresponding to the subsequent external sensor data.

(675) A further system embodiment may implement a smart contract based payment upon confirmation that parcel customer intends to use this node-based logistics receptacle **74150**. For example, the bridge node processor of bridge node **74200**, when executing the monitoring and management code, may be further programmatically operative to communicate with the mobile user device **3805** over the communication interface, in response to receiving the drop off verification confirmation message **7510** and when the response indicates the parcel customer intends to place the delivery item **170** outside of the node-based logistics receptacle **74150**, to establish a smart contract based connection with the mobile user device **3805** that provides terms for paid use of the node-based logistics receptacle **74150**. Those skilled in the art will appreciate that such a smart contract based connection may, for example, be implemented via a protocol for an automated transaction stored on a blockchain and run in response to meeting at least a payment condition for use of the node-based logistics receptacle **74150** in shipping the delivery item **170**. In more detail, the smart contract based connection may provide for paid use of the node-based logistics receptacle **74150** under predetermined pricing terms as the payment condition. Such predetermined pricing terms may, for example, relate to a blockchain-based payment for external deposit of the delivery item **170** proximate the node-based logistics receptacle, relate to a blockchain-based payment for external deposit of the delivery item **170** proximate the node-based logistics receptacle **74150** during a predetermined time period (such as specific time periods during the day, specific days of the week, and the like), or relate to a blockchain-based payment on a per-deposit basis for externally depositing one or more parcel items external to the node-based logistics receptacle **74150**.

(676) In another embodiment, the system may implement a smart contract based payment upon detecting that parcel customer **3800** has deposited delivery item **170** with node-based logistics receptacle **74150** (rather than based upon a confirmed intent to use receptacle **74150**). For example, the bridge node processor of bridge node **74200**, when executing the monitoring and management

code, may be further programmatically operative to communicate with the mobile user device **3805** over the communication interface, in response to detecting placement of the delivery item **170** proximate the node-based logistics receptacle **74150**, to establish a smart contract based connection with the mobile user device **3805** that provides terms for paid use of the node-based logistics receptacle **74150**. Those skilled in the art will appreciate that such a smart contract based connection may, for example, be implemented via a protocol for an automated transaction stored on a blockchain and run in response to meeting at least a payment condition for use of the node-based logistics receptacle **74150** in shipping the delivery item **170**. In more detail, the smart contract based connection may provide for paid use of the node-based logistics receptacle **74150** under predetermined pricing terms as the payment condition. Such predetermined pricing terms may, for example, relate to a blockchain-based payment for external deposit of the delivery item **170** proximate the node-based logistics receptacle **74150**, relate to a blockchain-based payment for external deposit of the delivery item **170** proximate the node-based logistics receptacle **74150** during a predetermined time period, or relate to a blockchain-based payment on a per-deposit basis for externally depositing one or more parcel items external to the node-based logistics receptacle **74150**.

(677) Referring now to FIG. 75C, the bridge node processor of exemplary bridge node **74200** is also operative to transmit, using the communication interface, exemplary external deposit information **7515** to the backend server **100** in response to the detected placement of the delivery item **170**. The exemplary external deposit information **7515** is related to the detected placement of the delivery item **170** and causes the backend server **100** to initiate a dispatched logistics operation related to the node-based logistics receptacle **74150**. In more detail, an embodiment of the external deposit information **7515** transmitted to the backend server **100** may include a priority level indicator to cause the backend server **100** to initiate the dispatched logistics operation related to the node-based logistics receptacle **74150** with a heightened level of urgency. Such a priority level indicator, for example, may reflect that the delivery item **170** is deposited with the node-based logistics receptacle **74150** outside of a secured temporary storage area **205** within the node-based logistics receptacle **74150**.

(678) In more detail, the external deposit information **7515** transmitted to the backend server **100** may cause the backend server **100** to initiate the dispatched logistics operation with a logistics asset capable of completing the dispatched logistics operation under a predetermined condition (e.g., a timing criteria related to pickup of the delivery item deposited external to the node-enabled logistics receptacle **74150**). For example, backend server **100** (with awareness of such an external placement of delivery item **170**) may initiate the dispatched logistics operation by transmitting exemplary dispatch message **7520** to a particular logistics asset (such as exemplary logistics asset **700a** shown in FIG. 75C). In a more detailed embodiment, the external deposit information **7515** transmitted to the backend server **100** may cause the backend server **100** to send dispatch message **7520** that initiates the dispatched logistics operation with a selected one of a multiple different logistics assets (e.g., similar logistics assets or a mix of different types of logistics assets), where the selected logistics asset is capable of completing the dispatched logistics operation under a predetermined time window for pickup of the delivery item **170**.

(679) As noted with the earlier system embodiment, this additional system embodiment may have the backend server **100** being caused to initiate the dispatched logistics operation where at least one of the logistics assets considered is a for-hire logistics asset. For example, the bridge node processor of bridge node **74200** in such an additional system embodiment, when executing the monitoring and management code, may be further programmatically operative to communicate with the for-hire logistics asset over the bridge node's communication interface to establish a smart contract based connection with the for-hire logistics asset when the for-hire logistics asset is the selected one of the logistics dispatched by the backend server **100** for completing the dispatched logistics operation. Such a smart contract based connection provides terms for paid pickup of the

delivery item **170** disposed external to the node-based logistics receptacle **74150**. As such, the for-hire logistics asset may be under payment terms defined by the smart contract based connection with the backend server when the for-hire logistics asset is selected.

(680) FIGS. **76A-76D** are diagrams illustrating a further embodiment of an exemplary system for enhanced interaction with a node-based logistics receptacle **74150** during an external drop off of a delivery item **170** by a parcel customer **3800**. In general, this further embodiment involves detection of whether the parcel customer **3800** is carrying the delivery item **170** upon approach to the node-based logistics receptacle **74150** using a separately disposed external sensor (such as sensor **4300** or a sensing element of external sensing infrastructure **4700**) in accordance with embodiments of the invention. In more detail, such a further system embodiment may use an external sensor that is not an integrated part of node-based logistics receptacle **74150** itself, such as sensor **4300** or external sensing infrastructure **4700**. Such a separate external sensor is disposed outside of the node-based logistics receptacle **74150** and is coupled to or otherwise may be in communication with the bridge node **74200** of receptacle **74150** as shown in FIGS. **76A-76D**.

(681) Those skilled in the art will appreciate that the embodiment of exemplary node-based logistics receptacle **74150** (including exemplary internal sensors) as shown in FIGS. **76A-76D** is similar to that of the example illustrated in FIGS. **74A-75C** while further involving the generation of exemplary carrying confirmation data **7500** as well as execution of an embodiment of exemplary monitoring and management code that configures the bridge node processor of bridge node **74200** to be programmatically operative in a way described below relative to such a further system embodiment.

(682) In more detail, a further system embodiment for enhanced interaction with a node-based logistics receptacle and a parcel entity (e.g., customer, logistics personnel, and the like) operating a mobile user device includes exemplary node-based logistics receptacle **74150** as shown in FIGS. **76A-76D** having a wireless accessory sensor node and a bridge node. The system's wireless accessory sensor node includes at least one internal sensor that collectively monitors one or more of the storage receptacle components of the node-based logistics receptacle **74150** and generates internal sensor data reflecting an interaction with one or more of the storage receptacle components of the node-based logistics receptacle. The system's bridge node (e.g., bridge node **74200**) has a bridge node processor, a bridge node memory, and a communication interface. The bridge node memory is coupled to the bridge node processor and maintains an embodiment of monitoring and management code for execution by the bridge node processor, exemplary anticipated entity data **7400**, and exemplary carrying confirmation data **7500** as generated by the system's bridge node. The bridge node's communication interface is coupled to the bridge node processor and is operative to communicate with at least backend server **100**.

(683) In this further system embodiment, the system includes an external sensor (such as exemplary external sensor **4300** shown in FIG. **76A**) in communication with the bridge node **74200**. The external sensor **4300** is disposed external to and separate from the node-based logistics receptacle **74150**, and is operative to monitor a local environment proximate the node-based logistics receptacle **74150** and generate external sensor data relative to the local environment proximate the node-based logistics receptacle **74150**. Examples of external sensor **4300** may be implemented as an image sensor that generates image sensor data as the external sensor data, a video sensor that generates video sensor data as the external sensor data, LiDAR sensor that generates multi-dimensional information on the local environment proximate node-based logistics receptacle **74150** as the external sensor data, as well as a machine vision sensor that generates video sensor data used to identify objects within its field of view. In more detail, those skilled in the art will appreciate that such a machine vision sensor can identify an object in the local environment proximate the node-based logistics receptacle **74150** based upon video sensor data and is further operative to detect a change in what has been placed within a predetermined range of the node-based logistics receptacle **74150** representative of the local environment proximate the node-based

logistics receptacle **74150** based upon the identified object.

(684) While external sensor **4300** is shown in FIG. **76A** as a type of separately disposed external sensor used in such a further system embodiment, FIG. **76B** illustrates exemplary node-based logistics receptacle **74150** being operative to communicate and receive external sensor data from one or more sensing elements **4705a-4705c** of exemplary external sensing infrastructure **4700** as another type of separately disposed external sensor used in such a further system embodiment. Referring now to FIG. **76B**, the system's external sensor may be implemented using at least one of a plurality of sensing elements **4705a-4705c** of an external sensing infrastructure **4700** disposed within a viewable range that includes the node-based logistics receptacle **74150** where at least one of the sensing elements **4705a-4705c** is operative to provide sensing element sensor data to the system's wireless accessory sensor node as the external sensor data.

(685) Those skilled in the art will further appreciate that the system's use of such an exemplary external sensor (e.g., external sensor **4300** or one of sensing elements **4705a-4705c** of external sensing infrastructure **4700**) may be facilitated through a smart contract based connection where receipt of the external sensor data may be a paid-for service provided under terms of the smart contract application code representing such a connection. For example, the ability of the bridge node **74200** to receive the external sensor data generated by the external sensor related to the local environment proximate the node-logistics receptacle **74150** may be possible with the bridge node processor of bridge node **74200** being further operative to communicate with the external sensing infrastructure **4700** (e.g., through its control node **4710**) over the communication interface to establish a smart contract based connection with the external sensing infrastructure **4700** where the smart contract based connection (via execution of the smart contract application code) provides paid-for use of data generated by the one of the sensing elements of the external sensing infrastructure **4700**, and then receive the external sensor data under terms of the smart contract based connection with the external sensing infrastructure **4700**. Those skilled in the art will appreciate that such a smart contract based connection may be implemented with code defining a protocol for an automated transaction stored on a blockchain and run in response to meeting at least a payment condition for receiving the data generated by the one of the sensing elements **4705a-4705c** of the external sensing infrastructure **4700**. In more detail, such a smart contract based connection may provide a cryptographically secure source of the data generated by the one of the sensing elements **4705a-4705c** of the external sensing infrastructure **4700**. Stated another way, an example may have the smart contract based connection running the smart contract application code to provide for the bridge node **74200** to receive the data generated by the one of the sensing elements **4705a-4705c** of the external sensing infrastructure **4700** under predetermined pricing terms as the payment condition and/or predetermined access conditions (such as time of day conditions, day of the week conditions, and the like). Such predetermined pricing terms, for example, may relate to a blockchain-based payment for access rights to the data generated by the one of the elements **4705a-4705c** of the external sensing infrastructure **4700**, relate to a blockchain-based payment for access rights to the data generated by any of the sensing elements **4705a-4705c** of the external sensing infrastructure **4700**, relate to a blockchain-based payment on a per-access basis for access rights to the data generated by at least the one of the sensing elements **4705a-4705c** of the external sensing infrastructure **4700**.

(686) Those skilled in the art will further appreciate that in some system embodiments, the external sensing infrastructure **4700** may be a security system with sensing elements being different security cameras used by the security system. In other embodiments, the external sensing infrastructure **4700** may be more generally a camera-based monitoring system where the sensing elements may be a set of cameras used by the camera-based monitoring system. In more detail, an example may have the external sensor of a system embodiment being a particular security camera operably coupled to the bridge node **74150** through a remotely accessible interface of the security system (e.g., control node **4710** of system **4700**). In such an example, the bridge node **74200** may be

further programmatically operative to receive the external sensor data generated by the external sensor related to the local environment proximate the node-logistics receptacle **74150** by being further operative to establish the smart contract based connection with the security system **4700** through the remotely accessible interface **4710** of the security system **4700**, and receive the external sensor data generated by the security camera over the remotely accessible interface **4710** of the security system and the communication interface **203** of the bridge node. This is equally applicable to an example where infrastructure **4700** is a camera-based monitoring system.

(687) In this further system embodiment, the bridge node processor of bridge node **74200**, when executing the monitoring and management code, is programmatically operative to detect a wireless communication signal **3820** broadcast from the mobile user device **3820** operated by the parcel customer **3800** and identify the wireless communication signal as corresponding to an anticipated drop off entity. Consistent with the related system embodiments described above, detecting such a signal and identifying it to correspond to an anticipated drop off entity may involve detecting an RF signature. For example, and in more detail, the bridge node processor of bridge node **74200**, when executing the monitoring and management code, may identify the wireless communication signal as corresponding to the anticipated drop off entity by being further operative to identify an RF signature from the wireless communication signal where the RF signature corresponds to the anticipated drop off entity. In particular, such an RF signature may be associated with at least one of the parcel customer **3800** and the mobile user device **3805** operated by the parcel customer **3800**. In another example, the bridge node's processor may be programmatically operative to identify the wireless communication signal as corresponding to the anticipated drop off entity based upon comparing the RF signature with the entity information in the anticipated entity data **7400** maintained in the bridge node memory (which may be updated by backend server **100** with updated entity information on at least one additional entity anticipated to make a deposit at the node-based logistics receptacle **74150**).

(688) Consistent with the related system embodiments describe above, detecting such a signal and identifying it to correspond to an anticipated drop off entity may involve detecting information in a wireless message portion of the wireless communication signal **3820**. For example, and in more detail, the bridge node processor of bridge node **74200** may identify the wireless communication signal **3820** as corresponding to the anticipated drop off entity by being further operative to identify information associated with the parcel customer **3800** as part of a wireless message in the wireless communication signal **3820**. Such information associated with the parcel customer **3800** as part of the wireless message may, in some instances, be associated with the mobile user device **3805** operated by the parcel customer **3800**. In even more detail, the bridge node processor may identify the wireless communication signal **3820** as corresponding to the anticipated drop off entity by being further operative to detect the information associated with the parcel customer **3800** as part of a wireless message related to the wireless communication signal **3820**; compare the information associated with the parcel customer **3800** with entity information in the anticipated entity data **7400** maintained in the bridge node memory; and identify the information associated with the parcel customer **3800** as corresponding to the anticipated drop off entity based upon the comparison.

(689) In a further system embodiment and with reference to FIG. **76C**, the bridge node processor of bridge node **74200**, when executing the monitoring and management code, is also programmatically operative to receive the external sensor data generated by the external sensor related to the local environment proximate the node-logistics receptacle **74150**, generate carrying confirmation data **7500** related to whether the parcel customer **3800** is carrying a delivery item **170** based upon the external sensor data generated by the external sensor, and responsively transmit a drop off verification message e to the mobile user device **3805** operated by the parcel customer **3800** when the carrying confirmation data **7500** indicates the parcel customer **3800** is carrying the delivery item **170**. Such a drop off verification message includes a prompt for the parcel customer **3800** to verify that the parcel customer **3800** intends to place the delivery item **170** outside of the

node-based logistics receptacle **74150**. The bridge node processor of bridge node **74200**, when executing the monitoring and management code, is further programmatically operative to receive a drop off verification confirmation message **7605** from the mobile user device **3805** that has a response indicating whether the parcel customer **3800** intends to place the delivery item **170** outside of the node-based logistics receptacle **74150**.

(690) In some embodiments, the system's bridge node processor may establish a smart contract based connection with mobile user device **3805** in response to receiving the drop off verification confirmation message **7605** and when the response indicates the parcel customer **3800** intends to place the delivery item **170** outside of the node-based logistics receptacle **74150**. Such a smart contract based connection may be implemented via a protocol for an automated transaction stored on a blockchain and run in response to meeting at least a payment condition for use of the node-based logistics receptacle **74150** in shipping the delivery item **170** where the payment condition may, for example, be under predetermined pricing terms. In more detail, such predetermined pricing terms may, for example, relate to a blockchain-based payment for external deposit of the delivery item **170** proximate the node-based logistics receptacle **74150**, relate to a blockchain-based payment for external deposit of the delivery item **170** proximate the node-based logistics receptacle **74150** during a predetermined time period, or relate to a blockchain-based payment on a per-deposit basis for externally depositing one or more parcel items external to the node-based logistics receptacle **74150**.

(691) Still referring to FIG. **76C**, the bridge node processor of bridge node **74200**, when executing the monitoring and management code, is programmatically operative to detect placement of the delivery item **170** proximate the node-based logistics receptacle **74150** based upon subsequent external sensor data generated by the external sensor (e.g., sensor **4300** or a sensing element of sensing infrastructure **470**) and without information reflecting the interaction with the one or more of the storage receptacle components using the internal sensor data. In more detail, detecting the placement of the delivery item **170** proximate the node-based logistics receptacle **74150** may be accomplished in an exemplary embodiment with the bridge node being further operative to receive, from the system's wireless accessory sensor node, information corresponding to the subsequent external sensor data without receiving information corresponding to the internal sensor data.

(692) Those skilled in the art will appreciate that in some embodiments, the system's bridge node processor may establish a smart contract based connection with mobile user device **3805** in response to detecting placement of the delivery item **170** proximate the node-based logistics receptacle **74150** (rather than information on the parcel customer's intent to deposit such an item **170**). Such a smart contract based connection provides terms for paid use of the node-based logistics receptacle **74150** by the parcel customer. Such a smart contract based connection may be implemented via a protocol for an automated transaction stored on a blockchain and run in response to meeting at least a payment condition for use of the node-based logistics receptacle **74150** in shipping the delivery item, where the payment condition may, for example be defined as predetermined pricing terms. In more detail, such predetermined pricing terms may, for example, relate to a blockchain-based payment for external deposit of the delivery item **170** proximate the node-based logistics receptacle **74150**, relate to a blockchain-based payment for external deposit of the delivery item **170** proximate the node-based logistics receptacle **74150** during a predetermined time period, or relate to a blockchain-based payment on a per-deposit basis for externally depositing one or more parcel items external to the node-based logistics receptacle **74150**.

(693) Now referring to FIG. **76D**, the bridge node processor of bridge node **74200**, when executing the monitoring and management code, is programmatically operative to transmit, using the communication interface, external deposit information **7610** to the backend server **100** in response to the detected placement of the delivery item **170**. The external deposit information **7610** is related to the detected placement of the delivery item **170** and causes the backend server **100** to initiate a dispatched logistics operation related to the node-based logistics receptacle **74150** via exemplary

dispatch message **7615**. In more detail, exemplary external deposit information **7610** transmitted to the backend server **100** may, for example, include a priority level indicator to cause the backend server **100** to initiate the dispatched logistics operation related to the node-based logistics receptacle **74150** with a heightened level of urgency. Such a priority level indicator may reflect that the delivery item **170** is deposited with the node-based logistics receptacle **74150** outside of a secured temporary storage area **205** within the node-based logistics receptacle. The external deposit information **7610** may, for example, cause the backend server **100** to initiate the dispatched logistics operation with a logistics asset (such as exemplary logistics asset **700a** shown in FIG. **76D**) capable of completing the dispatched logistics operation under a predetermined condition (e.g., a timing criteria related to pickup of the delivery item **170** deposited external to the node-enabled logistics receptacle **74150**). In another example embodiment, the external deposit information **7610** transmitted to the backend server **100** may cause the backend server **100** to initiate the dispatched logistics operation with a selected one of multiple different logistics assets (e.g., similar logistics assets or a mix of different types of logistics assets), where the selected logistics asset is capable of completing the dispatched logistics operation under a predetermined time window for pickup of the delivery item **170**.

(694) Similar to some of the previously described system embodiments, this may, for example, have backend server **100** considering one or more for-hire logistics assets for the selected logistics asset to service node-based logistics receptacle **74150**. For example, the bridge node processor of bridge node **74200**, when executing the monitoring and management code, may be further programmatically operative to communicate with the for-hire logistics asset over the bridge node's communication interface to establish a smart contract based connection with the for-hire logistics asset when the for-hire logistics asset is the selected one of the logistics dispatched by the backend server **100** for completing the dispatched logistics operation. Such a smart contract based connection provides terms for paid pickup of the delivery item **170** disposed external to the node-based logistics receptacle **74150**. As such, the for-hire logistics asset may be under payment terms defined by the smart contract based connection with the backend server when the for-hire logistics asset is selected.

(695) Enhanced and Proactive Interaction with Informed Option for Drop Off

(696) In still additional embodiments, an exemplary node-based logistics receptacle may sense an approaching parcel customer and interact with the parcel customer with knowledge of an anticipated drop off of a delivery item in an additional manner that proactively informs the parcel customer with alternative drop off information (e.g., via presentation of alternative drop off information on the parcel customer's mobile device, which may be an AR equipped headset). This, for example, may be the case when the parcel customer responds to a message from the node-based logistics receptacle that the parcel customer does not intend to use that particular node-based logistics receptacle. By providing such alternative drop off information to the approaching parcel customer, the parcel customer may elect to use another nearby node-based logistics receptacle or, for example, may rethink their intention not to use that particular node-based logistics receptacle and proceed with depositing their delivery item (e.g., package **170**) with that particular node-based logistics receptacle.

(697) FIGS. **77A-77D** are diagrams illustrating yet another exemplary system for enhanced interaction with a node-based logistics receptacle and a detected parcel customer that involves proactively sending the parcel customer alternative drop off information upon approach to the node-based logistics receptacle in accordance with embodiments of the invention. Referring now to FIG. **77A**, exemplary node-based logistics receptacle **77150** is shown operative to communicate with backend server **100** with components similar to exemplary logistics receptacle **150** described relative to FIG. **2**. Those skilled in the art will appreciate that exemplary node-based connected logistics receptacle **77150** shown in FIGS. **77A-77D** is generally similar to exemplary connected/node-based logistics receptacle **150** and **150a** and, more specifically, is similar to

exemplary node-based logistics receptacle **74150** (that includes exemplary anticipated entity data **7400** and exemplary carrying confirmation data **7500**), with the exception that exemplary receptacle **77150** is equipped with an exemplary bridge node **77200** that is programmatically configured differently so that it uses further types of data maintained on the bridge node **77200** (such as exemplary alternative drop off data **7700**) and is operative to use different types of external sensors that monitor interactions with receptacle **77150** and areas proximate to receptacle **77150** (e.g., an external sensor used with external sensor node **250** as part of receptacle **74150**, exemplary external sensor **4300** disposed external to and separate from receptacle **74150**). As such, exemplary receptacle **77150** includes an embodiment of monitoring and management code for execution by the processor in bridge node **77200** (controlling functionality of bridge node **77200** in such additional embodiments) and use of such data (e.g., exemplary anticipated entity data **7400**, exemplary carrying confirmation data **7500**, and exemplary alternative drop off data **7700**) maintained within memory **305/310** of bridge node **77200** as part of enhanced interaction between exemplary node-based logistics receptacle **77150** and a mobile user device **3805** equipped parcel customer **3800** as implemented in exemplary node-based logistics receptacle **77150**. Those skilled in the art will appreciate that backend server **100** may, in some embodiments, transmit updates to the exemplary anticipated entity data **7400** and/or exemplary alternative drop off data **7700** for use by the exemplary node-based logistics receptacle **77150**.

(698) In general, those skilled in the art will appreciate that exemplary alternative drop off data **7700** is stored in a data structure or file and locally maintains alternative drop off information on one or more alternative drop off points (e.g., other shipment facilities, other node-based logistics receptacles, other mobile logistics assets capable of operating as a drop off point) for a parcel shipment or delivery item (such as package **170**). For example, such alternative drop off information may include location information or address information for alternative drop off points. In another example, the alternative drop off information may include a respective distance from the particular node-based logistics receptacle **77150** to different alternative drop off points so that information may be provided on closer ones of the alternative drop off points relative to the location or address of the node-based logistics receptacle **77150**. Thus, when the bridge node **77200** of node-based logistics receptacle **77150** provides information on a particular alternative drop off point, such information may be a closest one of the possible alternative other drop off points. The alternative drop off information may also, for example, include directions to such an alternative drop off point.

(699) In some embodiments, the information in exemplary alternative drop off data **7700** may include other types of contextual information related to the different alternative drop off points. For example, the alternative drop off information may include traffic data relative to the alternative drop off point, weather data relative to the alternative drop off point, crime data relative to the alternative drop off point, seasonal activity data relative to the alternative drop off point, wait time data relative to a particular alternative drop off point (e.g., historic wait time at a shipping facility), operational timing data relative to the (e.g., opening and closing business hours for a shipping facility, last pickup times for a particular alternative node-based logistics receptacle, data identifying when items are accepted relative to that drop off point).

(700) Exemplary alternative drop off information in data **7700** may include different types of information on different types of drop off points. For example, the alternative drop off information may include information related to a staffed facility as an alternative drop off point and an unstaffed logistics receptacle as another alternative drop off point (e.g., location, closing time, wait time of the staffed facility; and location and last pickup time of the alternative node-based logistics receptacle).

(701) Exemplary alternative drop off information in data **7700** may, for example, include alternative drop off information related to one or more alternative drop off points for a parcel that may be detected as approaching node-based logistics receptacle **77150**. Those skilled in the art will

appreciate that bridge node **77200** may, be programmatically operative to receive, using the communication interface **203**, an update for the alternative drop off information **7700** or an updated portion of such information **7700** from the backend server **100** or a network storage data source (e.g., network database **180** and the like).

(702) Consistent with what is shown in FIG. 2 and as shown in FIGS. 77A-77D, exemplary connected logistics receptacle **77150** is shown including exemplary external sensor node **250** having at least one sensor that is disposed on receptacle **77150**. Those skilled in the art will appreciate that the externally focused sensor coupled to external sensor node **250** may be disposed relative to logistics receptacle **77150** so as to have a sensing orientation to monitor particular locations proximate receptacle **77150** for any externally deposited parcel or delivery item. Similarly, those skilled in the art will appreciate that exemplary external sensor **4300** shown in FIGS. 77A-77D may also have a sensing orientation to monitor particular locations proximate receptacle **77150** for any externally deposited parcel or delivery item.

(703) Referring back to FIG. 77A, an embodiment of an exemplary system for enhanced interaction with node-based logistics receptacle **77150** and a parcel customer **3800** operating mobile user device **3805** is illustrated. In general, an embodiment of such an exemplary system includes a wireless accessory sensor node (such as exemplary wireless accessory sensor node **210**) and a bridge node (such as exemplary bridge node **77200**), each of which are disposed on the node-based logistics receptacle **77150**. Exemplary node-based logistics receptacle **77150** (as explained relative to receptacle **150** above) has multiple storage receptacle components, such as an external housing, an entrance opening **155/156** disposed on the receptacle housing through which a delivery item may be inserted, a temporary storage area **205** within the receptacle housing for temporarily maintaining custody of the delivery item when inserted through the entrance opening, and a selectively accessible retrieval door **160** providing access to within the temporary storage area.

(704) In this system embodiment, the wireless accessory sensor node includes at least one internal sensor that collectively monitors one or more of the storage receptacle components (e.g., entrance opening, temporary storage area, selectively accessible retrieval door) of the node-based logistics receptacle **77150** and generates internal sensor data reflecting an interaction with one or more of the storage receptacle components of the node-based logistics receptacle **77150**. For example, such an internal sensor monitoring an entrance opening to the node-based logistics receptacle **77150** may be implemented with a variety of different types of internal sensors, such as a motion sensor detecting a change in motion of the entrance opening, a motion sensor detecting the change in motion of the entrance opening and a failure to return to a prior state of the one or more of the entrance opening, a motion sensor detecting movement of what passes through the entrance opening, an inertial sensor detecting a change in motion of the entrance opening, a status sensor detecting a change in orientation of the entrance opening, an accelerometer detecting a change in motion of the entrance opening, and/or a magnetic sensor detecting a change in position of the entrance opening. In another example, such an internal sensor monitoring the temporary storage area within the node-based logistics receptacle **77150** may be implemented with different types of sensors, such as an image sensor detecting a change in what is within the temporary storage area, a scale detecting a change in what is within the temporary storage area, a force sensor detecting a change in what has been deposited within the temporary storage area, a light sensor detecting a change in light within the node-enabled logistics receptacle, and/or a chemical sensor detecting presence of a chemical within the temporary storage area. In yet another example, the internal sensor monitoring the selectively accessible retrieval door on the node-based logistics receptacle **77150** may be implemented with different types of sensors, such as a motion sensor detecting a change in state of the selectively accessible retrieval door, a motion sensor detecting a change in state of the selectively accessible retrieval door and a failure to return to a prior state of the selectively accessible retrieval door, an inertial sensor detecting a change in inertial motion of the selectively accessible retrieval door, a gyroscopic sensor detecting a change in movement of the

selectively accessible retrieval door, a status sensor detecting a change in orientation of the selectively accessible retrieval door, a magnetic sensor detecting a change in position of the selectively accessible retrieval door, and/or a lock sensor detecting a change in secured state of the selectively accessible retrieval door.

(705) In this system embodiment, those skilled in the art will appreciate that the bridge node **77200** includes a bridge node processor, a bridge node memory coupled to the bridge node processor and maintaining monitoring and management code for execution by the bridge node processor, and a wireless transceiver-based communication interface coupled to the bridge node processor that is operative to communicate with at least backend server **100**.

(706) In this system embodiment, the bridge node **77200** is in communication (e.g., directly or indirectly) with an external sensor that operates to monitor a local environment proximate the node-based logistics receptacle **77150** and generate external sensor data relative to the local environment proximate the node-based logistics receptacle **77150**. Such an external sensor, in one example, may be disposed on receptacle **77150** (e.g., the external sensor coupled to external sensor node **250** as shown in FIG. **77A**). In another example, the external sensor may be disposed external to and separate from the node-based logistics receptacle **77150** (e.g., external sensor **4300** shown in FIG. **77A**). In this system embodiment, an exemplary external sensor may be implemented as an image sensor that generates image sensor data as the external sensor data or a machine vision sensor that generates video sensor data as the image sensor data. In more detail, such a machine vision sensor (a type of image sensor) may be operative to identify an object in the local environment proximate the node-based logistics receptacle **77150** based upon video sensor data and may be further operative to detect a change in what has been placed within a predetermined range of the node-based logistics receptacle **77150** representative of the local environment proximate the node-based logistics receptacle **77150** based upon the identified object.

(707) In still another example, the system's external sensor may be disposed externally to and separate from the node-based logistics receptacle **77150** (e.g., one of the sensing elements (such as a camera) of exemplary external sensing infrastructure **4700** (such as a security system) as shown in FIG. **76B**). More specifically, such an external sensing element of infrastructure **4700** may be disposed within a viewable range that includes the node-based logistics receptacle **77150** and is operative to provide sensing element sensor data to the wireless accessory sensor node as the external sensor data or to provide sensing element sensor data directly to the bridge node **77200** in node-based logistics receptacle **77150**. For example, bridge node **77200** may be programmatically operative to receive the external sensor data generated by the external sensor related to the local environment proximate the node-logistics receptacle **77150** by being further operative to communicate with the external sensing infrastructure **4700** over the communication interface to establish a smart contract based connection with the external sensing infrastructure **4700**. Those skilled in the art will appreciate that such a smart contract based connection through execution of the smart contract's application code provides paid for use of data generated by the one of the sensing elements of the external sensing infrastructure **4700**. As a result, the bridge node **77200** is operative to receive the external sensor data and the as the data generated by the one of the sensing elements of the external sensing infrastructure **4700** under terms of the smart contract based connection with the external sensing infrastructure **4700**. Here, the smart contract based connection may, for example, be implemented as a protocol for an automated transaction stored on a blockchain and run in response to meeting at least a payment condition for receiving the data generated by the one of the sensing elements of the external sensing infrastructure **4700**. Stated another way, the smart contract based connection may, for example, provide a cryptographically secure source of the data generated by the one of the sensing elements of the external sensing infrastructure **4700**. Such a smart contract based connection that provides for receiving the data generated by the one of the sensing elements of the external sensing infrastructure **4700** may do so under predetermined pricing terms as the payment condition or under predetermined access

conditions. Such predetermined pricing terms may, for example, relate to a blockchain-based payment for access rights to the data generated by the one of the sensing elements of the external sensing infrastructure **4700**; relate to a blockchain-based payment for access rights to the data generated by any of the sensing elements of the external sensing infrastructure **4700**; and relate to a blockchain-based payment on a per-access basis for access rights to the data generated by at least the one of the sensing elements of the external sensing infrastructure **4700**.

(708) In operation when executing the monitoring and management code as part of this system embodiment shown in FIGS. **77A-77D**, the bridge node processor of bridge node **77200** is programmatically configured so as to be operative to detect, using the communication interface **203**, a wireless communication signal **3820** broadcast from the mobile user device **3805** (e.g., a smartphone, tablet, mobile AR headset, and the like) operated by the parcel customer **3800**. In some examples, this may involve detecting an RF signature associated with the parcel customer **3800** (e.g., where such an RF signature is associated with at least one of the parcel customer **3800** and the mobile user device **3805** operated by the parcel customer **3800**) or an RF signature related to the wireless communication signal **3820**. The bridge node **77200** is then operative to identify the signal **3820** (e.g., the RF signature with that signal) as corresponding to one of multiple anticipated drop off entities maintained in anticipated entity data **7400**.

(709) The bridge node processor of bridge node **77200** is further programmatically configured so as to be operative to receive the external sensor data generated by the external sensor related to the local environment proximate the node-based logistics receptacle (e.g., data from the sensor associated with external sensor node **250** and/or data from external sensor **4300**) and to generate carrying confirmation data **7500** related to whether the parcel customer **3800** is carrying a delivery item (such as package **170**) based upon the external sensor data received from the external sensor.

(710) Referring now to FIG. **77B**, the bridge node processor of bridge node **74200** in such a system embodiment is programmatically operative to transmit, using the communication interface **203**, an exemplary drop off verification message **7600** to the mobile user device **3805** operated by the parcel customer **3800** when the carrying confirmation data **7600** indicates the parcel customer **3800** is carrying the delivery item. Such an exemplary drop off verification message **7600** presents a request (e.g., via information **7715** that can be displayed on mobile user device **3805**) that the parcel customer **3800** verify that the parcel customer **3800** intends to place the delivery item **170** with the node-based logistics receptacle **77150**.

(711) The bridge node processor of bridge node **74200** in such a system embodiment is also programmatically operative to receive, using the communication interface **203**, an exemplary drop off verification response message **7705** from the mobile user device **3805**, which indicates the parcel customer **3800** does not intend to place the delivery item **170** with the node-based logistics receptacle **77150** (e.g., deposited inside the receptacle **77150** or placed externally and proximate to the receptacle **77150**). Based upon this response message **7705**, the bridge node processor of bridge node **77200** in such a system embodiment is programmatically operative to transmit, using the communication interface **203**, an exemplary alternative drop off information message **7710** to the mobile user device **3805**, which provides exemplary alternative drop off information related to at least one alternative drop off point for the delivery item **170**. For example, the information **7715** displayed on mobile user device **3805** may be updated with the alternative drop off information received. As noted above, the content of such alternative drop off information is generated by bridge node **77200** using exemplary alternative drop off data **7700**, and proactively informs parcel customer **3800** of one or more alternative drop off points where delivery item **170** may be deposited.

(712) In further system embodiments, bridge node **77200** may generate such an alternative drop off information message **7710** with a type of contextual awareness of whether the parcel customer **3800** may be estimated to reach a particular alternative drop off point before pickup occurs for that alternative drop off point, which may involve determining an estimated reachable alternative drop

off point. This may, for example, involve a further request from bridge node **77200** to mobile user device **3800** on a transport mode for parcel customer **3800** (e.g., walking, biking, riding in a vehicle, and the like). In another example, the alternative drop off information provided in the alternative drop off information message **7710** may include multiple estimated reachable alternative drop off points assuming different types of transport modes (e.g., parcel customer movement by walking, biking, or driving) and based on contextual data related to areas between any such related alternative drop off points and node-based logistics receptacle **77150** (e.g., weather, traffic, and the like). As such, those skilled in the art will appreciate that the alternative drop off information in message **7710** may be related to at least one estimated reachable alternative drop off point for the delivery item **170**.

(713) In more detail, such an estimated reachable alternative drop off point for the delivery item **170** may be determined by the bridge node processor of bridge node **77200** based upon a scheduled pickup time related to the different alternative drop off points and a distance from the location of the node-based logistics receptacle **77150** to the different alternative drop off points to come up with which alternative drop off points are estimated to be reachable by the scheduled pickup time for this parcel customer **3800**. For example, the bridge node processor of bridge node **77200**, when executing the monitoring and management code, may be programmatically operative to transmit the alternative drop off information message **7710** to the mobile user device **3805** by being further operative to receive a pickup status related to each of the alternative drop off points (e.g., those with information in exemplary alternative drop off data **7700**) from the backend server **100**, identify at least one estimated reachable alternative drop off point from the alternative drop off points in such data **7700** based upon the pickup status of each of the alternative drop off points, and transmit the alternative drop off information message **7710** to the mobile user device **3805**, where the alternative drop off information is related to the identified estimated reachable alternative drop off point(s) for the parcel customer's delivery item **170**. In another related example, the bridge node processor of bridge node **77200**, when executing the monitoring and management code, may be programmatically operative to transmit the alternative drop off information message **7710** by receiving a pickup status related to each of the alternative drop off points in data **7700** from the backend server **100** where such a pickup status identifies if the respective alternative drop off point has been serviced (and/or identifies a location of pickup entities assigned to service the respective alternative drop off point); identify at least one estimated reachable alternative drop off point from the alternative drop off points in data **7700** based upon (a) the pickup status of each alternative drop off point and (b) a distance from the node-based logistics receptacle **77150** to each of the alternative drop off points; and transmit the alternative drop off information message **7710** to the mobile user device **3805** where the alternative drop off information in message **7710** is related to the identified estimated reachable alternative drop off point(s) for the delivery item **170**.

(714) For temperature sensitive delivery item shipments, some embodiments may have the bridge node **77200** being aware of such shipment related information and knowledge of this temperature sensitive information may be used by the bridge node **77200** to refine how to determine an appropriate alternative drop off point for the particular parcel customer **3800**. For example, bridge node **77200** may maintain exemplary anticipated entity data **7400** that also includes temperature sensitive shipment information for the delivery item **170** being shipped by parcel customer **3800** as an anticipated entity that would potentially use node-based logistics receptacle **77150**. In more detail, an example may have the bridge node processor of bridge node **77200** being operative to transmit the alternative drop off information message **7710** to the mobile user device **3805** operated by the parcel customer **3800** (or any other transceiver operated by a potential shipping customer approaching node-based logistics receptacle **77150**) by being further operative to identify temperature sensitive shipment information for the delivery item **170** based upon the drop off verification response message; determine an environment appropriate alternative drop off point for the delivery item **170** based upon the identified temperature sensitive shipment information for the

delivery item **170**; and transmit the alternative drop off information message **7710** to the mobile user device **3805** operated by the parcel customer **3800** where the alternative drop off information message **7710** provides the alternative drop off information related to the environment appropriate alternative drop off point for the delivery item. Such an environmental appropriate alternative drop off point may have insulated storage capabilities or climate control functionality as part of how shipment items (such as delivery item **170**) may be maintained while in custody at that drop off point. For example, an environmental appropriate alternative drop off point for the delivery item may be a climate controlled drop off point capable of maintaining the delivery item in an environmental condition consistent with the identified temperature sensitive shipment information. (715) In another example, when the bridge node memory maintains weather data about a local operating environment of alternative drop off points (e.g., as part of exemplary alternative drop off data **7700**), the bridge node processor may be programmatically operative to determine the environment appropriate alternative drop off point for the delivery item from multiple alternative drop off points based upon the identified temperature sensitive shipment information for the delivery item **170** and the weather data about the local operating environment of each of the alternative drop off points. In still another example, when the bridge node memory further maintains internal temperature information about an internal storage environment of a plurality of alternative drop off points (e.g., as part of exemplary alternative drop off data **7700**), the bridge node processor may be programmatically operative to determine the environment appropriate alternative drop off point for the delivery item from multiple alternative drop off points based upon the identified temperature sensitive shipment information for the delivery item **170** and the internal temperature information about the internal storage environment of each of the alternative drop off points. Further still, another example may the bridge node memory maintaining internal temperature information about an internal storage environment of different alternative drop off points (e.g., as part of exemplary alternative drop off data **7700**), and have the bridge node processor being programmatically operative to determine the environment appropriate alternative drop off point for the delivery item **170** from the alternative drop off points based upon (a) the identified temperature sensitive shipment information for the delivery item **170**, (b) the internal temperature information about the internal storage environment of each of the alternative drop off points, and (c) a pickup status related to each of the alternative drop off points (e.g., a pickup status related to a time before scheduled pickup related to each of the alternative drop off points).

(716) Those skilled in the art will appreciate that such temperature sensitive shipment information for the delivery item **170** may, for example, include temperature rated packaging data that defines a desired thermal characteristic for the delivery item **170**. Such a desired thermal characteristics for delivery item **170** may, for example, be an upper temperature threshold, a lower temperature threshold, both an upper and lower temperature threshold, a temperature threshold and time period threshold.

(717) Determining an environmental appropriate alternative drop off point for a particular delivery item may also involve use of external sensors that detect outside temperatures and considering a risk to shipping the delivery item and reaching its destination/alternative drop off point prior to exceeding desired thermal characteristics. For example, and in more detail, an embodiment may have at least a portion of the external sensor data including external temperature data relative to the local environment proximate the node-based logistics receptacle **77150**. As such and in this example, the bridge node processor of bridge node **77200**, when executing the monitoring and management code, may be programmatically operative to determine the environment appropriate alternative drop off point for the delivery item **170** based upon (a) the identified temperature sensitive shipment information for the delivery item **170**, (b) the external temperature data relative to the local environment proximate node-based logistics receptacle **77150**, and (c) a distance to each of the alternative drop off points. The bridge node processor of bridge node **77200** may be further programmatically operative to transmit the alternative drop off information message **7710** to

the mobile user device **3805**, where the alternative drop off information message **7710** provides the alternative drop off information related to the environment appropriate alternative drop off point for the delivery item **170**.

(718) In a related but more detailed example where at least a portion of the external sensor data includes external temperature data relative to the local environment proximate the node-based logistics receptacle **77150** and the bridge node memory also maintains weather data about a local operating environment of the alternative drop off points, the bridge node processor may determine the environment appropriate alternative drop off point for the delivery item **170** based upon (a) the identified temperature sensitive shipment information for the delivery item **170**, (b) the external temperature data relative to the local environment proximate the node-based logistics receptacle **77150**, (c) the weather data about the local operating environment of each of the alternative drop off points, and (d) a distance to each of the alternative drop off points. The bridge node processor of bridge node **77200** may be further programmatically operative to transmit the alternative drop off information message **7710** to the mobile user device **3805** to provide the alternative drop off information related to the environment appropriate alternative drop off point for the delivery item **170**.

(719) In a further example with more specificity, at least a portion of the external sensor data includes external temperature data relative to the local environment proximate the node-based logistics receptacle **77150** and the bridge node memory further maintains weather data about a local operating environment of alternative drop off points and internal temperature information about an internal storage environment of the alternative drop off points. As such, the bridge node processor of bridge node **77200** in this example, when executing the monitoring and management code, is programmatically operative to determine the environment appropriate alternative drop off point for the delivery item **170** based upon (a) the identified temperature sensitive shipment information for the delivery item **170**, (b) the external temperature data relative to the local environment proximate the node-based logistics receptacle **77150**, (c) the weather data about the local operating environment of each of the alternative drop off points, (d) the internal temperature information about the internal storage environment of the alternative drop off points, and (e) a distance to each of the plurality of alternative drop off points. The bridge node processor then is operative to transmit, using the communication interface **203**, the alternative drop off information message **7710** to the mobile user device **3805** as a way of providing the alternative drop off information related to the environment appropriate alternative drop off point for the delivery item **170**.

(720) Referring now to FIG. 77C, an example is illustrated where parcel customer **3800**, while having received the alternative drop off information (as a result of a reported intent not to use node-based logistics receptacle **77150**), considers the alternative drop off information and then decides to deposit the delivery item **170** into node-based logistics receptacle **77150**. The alternative drop off information, for example, may present information on alternative drop off points that are less desirable to parcel customer **3800** than simply using node-based logistics receptacle **77150**. As shown in FIG. 77C, package **170** (the delivery item carried by parcel customer **3800**) may be inserted through the entrance opening of node-based logistics receptacle **77150** and deposited thereafter within the temporary storage area within node-based logistics receptacle **77150**. In this example embodiment, the bridge node processor of bridge node **77200**, when executing the monitoring and management code, may be further programmatically operative to detect, after transmitting the alternative drop off information message **7710**, receipt of the delivery item **170** within the node-based logistics receptacle **77150** based upon information reflecting the interaction with the one or more of the storage receptacle components using the internal sensor data; and transmit deposit information to the backend server **100** in response to the detected placement of the delivery item. Such deposit information is generally related to the detected receipt of the delivery item and causes the backend server **100** to initiate a dispatched logistics operation related to the node-based logistics receptacle **77150**.

(721) Those skilled in the art will appreciate that electing to deposit delivery item **170** within node-based logistics receptacle **77150** may incur an automated payment by parcel customer **3800** via smart contract in some embodiments. For example, the bridge node processor of bridge node **77200**, when executing the monitoring and management code, may be further programmatically operative to communicate with the mobile user device **3805** over the communication interface **203**, in response to detecting placement of the delivery item with the node-based logistics receptacle **77150**, to establish a smart contract based connection with the mobile user device **3805** where the smart contract based connection provides terms for paid use of the node-based logistics receptacle **77150**. Such a smart contract based connection, for example, may be implemented via a protocol for an automated transaction stored on a blockchain and run in response to meeting at least a payment condition for use of the node-based logistics receptacle **77150** as part of shipping the deposited delivery item **170**. The payment condition, for example, may include predetermined pricing terms for paid use of the node-based logistics receptacle **77150**, such as predetermined pricing terms that relate to a blockchain-based payment at a first pricing term for internal receipt of the delivery item **170** within the node-based logistics receptacle **77150** and/or predetermined pricing terms relate to a blockchain-based payment on a per-deposit basis for depositing one or more parcel items with the node-based logistics receptacle **77150**. In more detail, the predetermined pricing terms may relate to a blockchain-based payment at a first pricing term for internal receipt of the delivery item **170** within the node-based logistics receptacle **77150** where the first pricing term is at a lower rate compared to a second pricing term for external deposit of the delivery item **170** outside of and proximate the node-based logistics receptacle **77150**.

(722) Referring now to FIG. 77D, an example is illustrated where parcel customer **3800**, while having received the alternative drop off information (as a result of a reported intent not to use node-based logistics receptacle **77150**), considers the alternative drop off information and then decides to deposit the delivery item **170** outside of and proximate the node-based logistics receptacle **77150** (rather than within the temporary storage area of receptacle **77150**). This may, for example, be due to the size of delivery item **170** and the size of the entrance opening used to deposit any parcel items within receptacle **77150**. As shown in FIG. 77D, package **170** (the delivery item carried by parcel customer **3800**) may be placed next to, near, or proximate node-based logistics receptacle **77150** (rather than deposited within the temporary storage area within node-based logistics receptacle **77150** as shown in FIG. 77C). In this example embodiment and in more detail, the bridge node processor of bridge node **77200**, when executing the monitoring and management code, may be further programmatically operative to detect, after transmitting the alternative drop off information message **7710**, placement of the delivery item **170** proximate the node-based logistics receptacle **77150** based upon subsequent external sensor data generated by the external sensor (e.g., the external sensor coupled to external sensor node **250** and/or external sensor **4300**) and without information reflecting the interaction with one or more of the storage receptacle components using the internal sensor data. In this example embodiment, the bridge node processor of bridge node **77200**, when executing the monitoring and management code, may be further programmatically operative to transmit exemplary deposit information to the backend server **100** in response to the detected placement of the delivery item. Such deposit information, in this example, is generally related to the detected placement of the delivery item **170** and causes the backend server **100** to initiate a dispatched logistics operation related to the node-based logistics receptacle **77150**.

(723) Those skilled in the art will appreciate that electing to deposit delivery item **170** external to and proximate node-based logistics receptacle **77150** may also incur an automated payment by parcel customer **3800** via smart contract in some embodiments. For example, the bridge node processor of bridge node **77200**, when executing the monitoring and management code, may be further programmatically operative to communicate with the mobile user device **3805** over the communication interface **203**, in response to detecting placement of the delivery item with the

node-based logistics receptacle **77150** (e.g., detecting external proximate placement of delivery item **170** shown in FIG. **77D**), to establish a smart contract based connection with the mobile user device **3805** where the smart contract based connection provides terms for paid use of the node-based logistics receptacle **77150**. Such a smart contract based connection, for example, may be implemented via a protocol for an automated transaction stored on a blockchain and run in response to meeting at least a payment condition for use of the node-based logistics receptacle **77150** as part of shipping the delivery item **170** placed next to and near node-based logistics receptacle **77150**. The payment condition, for example, may include predetermined pricing terms for paid use of the node-based logistics receptacle **77150**, such as predetermined pricing terms that relate to a blockchain-based payment at a first pricing term for internal receipt of the delivery item **170** within the node-based logistics receptacle **77150** and/or predetermined pricing terms relate to a blockchain-based payment on a per-deposit basis for depositing one or more parcel items with the node-based logistics receptacle **77150**. In more detail, the predetermined pricing terms may relate to a blockchain-based payment at a pricing term for external deposit of the delivery item **170** with the node-based logistics receptacle **77150** where that pricing term is at a higher rate compared to another pricing term for internal deposit of the delivery item **170** within the node-based logistics receptacle **77150**.

(724) In some embodiments, the dispatched logistics operation may be initiated by backend server **100** with a greater sense of urgency when, for example, the delivery item **170** is detected as placed outside of node-based logistics receptacle **77150**. For example, and in more detail, such an embodiment may have the exemplary deposit information representing the external deposit of delivery item **170** transmitted to the backend server **100** including a priority level indicator to cause the backend server **100** to initiate the dispatched logistics operation related to the node-based logistics receptacle **77150** with a heightened level of urgency. In more detail, the priority level indicator may reflect that the delivery item is deposited with the node-based logistics receptacle **77150** outside of a secured temporary storage area within the node-based logistics receptacle **77150** (such as outside of temporary storage area **205** of receptacle **77150**). In another example, the bridge node processor of bridge node **77200**, when executing the monitoring and management code, may be programmatically operative to transmit, using the communication interface **203**, exemplary external deposit information to the backend server **100** related to the detected placement of the delivery item **170** to cause the backend server **100** to initiate the dispatched logistics operation with a logistics asset capable of completing the dispatched logistics operation under a predetermined condition. Such an exemplary predetermined condition may, for example, be a timing criteria related to pickup of the delivery item **170** deposited external to the node-enabled logistics receptacle **77150** (e.g., pickup within 2 hours of detected deposit outside receptacle **77150**, and the like). In yet another detailed example, the bridge node processor of bridge node **77200**, when executing the monitoring and management code, may be programmatically operative to transmit the external deposit information to the backend server **100** related to the detected placement of the delivery item **170** to cause the backend server **100** to initiate the dispatched logistics operation with a selected one of multiple logistics assets (e.g., a group of similar logistics assets, a group of different types of logistics assets, from different for-hire logistics assets) where the selected logistics asset is capable of completing the dispatched logistics operation under a predetermined time window for pickup of the delivery item **170**. Further still, an example may have the bridge node processor of bridge node **77200**, when executing the monitoring and management code, being programmatically operative to transmit the external deposit information to the backend server **100** to cause the backend server **100** to initiate the dispatched logistics operation with a for-hire logistics asset through a smart contract based connection between the backend server **100** and the for-hire logistics asset. Those skilled in the art will appreciate that such a smart contract based connection between server **100** and the for-hire logistics asset may programmatically define (via code in the relevant smart contract application being executed) terms for paid pickup of the

delivery item **170** disposed external to the node-based logistics receptacle **77150**.

(725) In further embodiments, a smart contract between the node-based logistics receptacle **77150** (e.g., bridge node **77200**) and the parcel customer's mobile user device **3805** may be automatically executed for a paid-for extension of a pickup window related to servicing node-based logistics receptacle **77150**. In some examples, this may be in response to internal deposit of delivery item **170**, external placement of delivery item **170** with node-based logistics receptacle **170**, or either situation. In more detail, the bridge node processor of bridge node **77200** may be further programmatically operative to detect, after transmitting the alternative drop off information message **7710**, deposit of the delivery item with the node-based logistics receptacle **77150** based upon at least one of (a) subsequent external sensor data generated by the system's external sensor (such as the sensor with external sensor node **250** and/or external sensor **4300**) and (b) information reflecting the interaction with one or more of the storage receptacle components of receptacle **77150** using the internal sensor data. In response to detecting deposit of delivery item **170** with receptacle **77150**, the bridge node processor of bridge node **77200** may be further programmatically operative to establish a smart contract based connection with the mobile user device **3805**, which provides terms for a first pricing term for deposit of the delivery item **170** with the node-based logistics receptacle **77150** and second pricing term (e.g., an additional fee) for extending the pickup time relative to the node-based logistics receptacle **77150**; and transmit deposit information to the backend server in response to the detected placement of the delivery item **170**. Here, the exemplary deposit information transmitted is related to the detected deposit of the delivery item **170** as well as extension of the predetermined pickup time. Those skilled in the art will appreciate that receipt of the deposit information causes the backend server **100** to initiate a dispatched logistics operation related to the node-based logistics receptacle **77150** consistent with extended pickup time (e.g., initiate the dispatched logistics operation consistent with the extended pickup time with a logistics asset capable of conducting the dispatched logistics operation consistent with the extended pickup time or with a logistics asset capable of conducting the dispatched logistics operation no earlier than the extended pickup time). Such a logistics asset in this example may be one of a variety of types of logistics assets, including a for-hire logistics asset hired to specifically conduct at least this particular dispatched logistics operation.

(726) In more detail, the engagement to have such a for-hire logistics asset conduct the dispatched logistics operation may be governed by a smart contract as well. For example, the bridge node processor of bridge node **77200**, when executing the monitoring and management code, may be programmatically operative to transmit the deposit information to the backend server **100** to cause the backend server **100** to initiate the dispatched logistics operation with the for-hire logistics asset through a smart contract based connection between the backend server **100** and the for-hire logistics asset. Such a smart contract based connection provide programmatically defined (via the smart contract application code) payment terms for the for-hire logistics asset to conduct the dispatched logistics operation related to pickup of the delivery item **170** disposed external to the node-based logistics receptacle **77150** no earlier than the extended pickup time. Thus, parcel customer **3800** may elect to pay for the extended pickup time through a first smart contract's payment terms while the backend server **100** may operation to engage a for-hire logistics asset under a different smart contract's payment terms in order to initiate the dispatched logistics operation related to node-based logistics receptacle **77150** under the extended pickup time.

(727) Periodic Heartbeat Validation of Components in Node-Based Logistics Receptacle

(728) In many of the embodiments described herein, an exemplary node-based logistics receptacle having a bridge node and at least one wireless accessory sensor node is operative to monitor for changes in the state of the logistics receptacle and report event information related to such changes to a backend server. In further embodiments, what is generated within such an exemplary node-based logistics receptacle may also include, at times, another type of information (generally referred to as non-event information) resulting from confirming operation of the wireless accessory

sensor node when the change in state of the storage receptacle has not been detected. The generated non-event information represents a lack of physical interaction with the monitored storage components of such an exemplary node-based logistics receptacle, but is information that is generated so as to validate that node devices used for monitoring within the exemplary node-based logistics receptacle remain operative. Such non-event information may, for example, take the form of a total event count of zero for the exemplary node-based logistics receptacle as a type of periodic heartbeat that may be reported to the backend server to validate that the bridge node and/or wireless sensor node remains operational but is simply not detecting changes relative to the exemplary node-based logistics receptacle. Those skilled in the art will appreciate that exemplary non-event information provides a different type or additional kind of information related to what is going on with a deployed exemplary logistics receptacle. For example, a status flag in an updated advertising signal broadcast by the wireless accessory sensor node may indicate data is available for upload by the bridge node related to one or more particular events (e.g., detected changes in state of the logistics receptacle) or indicate that no event was detected during a particular period of time. In such embodiments, both types of information may be useful to the backend server and such embodiments may transmit receptacle update information that include one or both types of information (e.g., event information indicative of one or more changes in state of the logistics receptacle, non-event information indicating no detected changes in the logistics receptacle). Those skilled in the art will appreciate that such exemplary receptacle update information may generally represent a periodic heartbeat where no change in status is triggering reporting to the backend server, and it is instead reported where such a heartbeat type of update is uploaded from the wireless accessory sensor node and reported to the backend server.

(729) FIG. **48** is a diagram of an exemplary proactively monitored and reporting logistics receptacle system operating within a network in accordance with an embodiment of the invention. Referring now to FIG. **48**, exemplary connected node-based logistics receptacle **48150** is shown operative to communicate with backend server **100** with components similar to exemplary logistics receptacle **150** described relative to FIG. **2**. Those skilled in the art will appreciate that exemplary connected logistics receptacle **48150** shown in FIG. **48** is similarly structured to exemplary connected/node-based logistics receptacle **150** and **150a**, with the exception that exemplary receptacle **48150** is equipped with an exemplary bridge node **48200** that generates further types of data maintained on the bridge node **48200** (e.g., exemplary non-event information) and exemplary wireless accessory sensor node **48210** (similar to node **210** or other wireless accessory sensor nodes within logistics receptacle **150**) coupled to exemplary sensors **450a-450e**. As such, exemplary receptacle **48150** includes an embodiment of monitoring and management code for execution by the processor in bridge node **48200** (controlling functionality of bridge node **48200** in such additional embodiments) and use of such data (e.g., exemplary management profile **4400** and environmental context data **4405**) maintained within memory **305/310** of bridge node **48200** as part of enhanced self-tuning functionality based upon contextual awareness implemented in exemplary connected logistics receptacle **48150**. Those skilled in the art will appreciate that backend server **100** may, in some embodiments, transmit updates to the exemplary management profile **4400** and/or environmental context data **4405** for use by the exemplary connected logistics receptacle **48150**. Those skilled in the art will also appreciate, as explained in more detail below, that bridge node **48200** may update the exemplary management profile **4400** and/or environmental context data **4405** based on operations of receptacle **48150** without an update command or data from backend server **100**.

(730) Consistent with the description above, the system embodiment uses exemplary wireless accessory sensor node **48210** (e.g., similar to exemplary node **210**) coupled to a plurality of sensors (e.g., sensors **450a-450e**) that collectively monitor the storage receptacle components of the node-based logistics receptacle **48150** and generate sensor data reflecting one or more interactions with one or more of the storage receptacle components of the node-based logistics receptacle **48150** over

a recording time period. Such sensors, as described above, may generate sensor data related to motion of the entrance opening, motion of objects moving through the entrance opening, motion of an object within the temporary storage area, image sensor data related a change of contents maintained within the temporary storage area, weight sensor data related a change in weight of what is stored within the temporary storage area, and the like. Those skilled in the art will appreciate that such sensors respectively monitor each of the monitored storage components for a change in state of the storage receptacle.

(731) In more detail, this system embodiment's exemplary wireless accessory sensor node **48210** is operative to receive sensor data generated by the sensors; determine whether the change in state of the storage receptacle has been detected based upon sensor data generated by at least one of the sensors **450a-450e**; generate event information including recorded timestamped information reflecting the detected change in state of the storage receptacle when the sensor data indicates the change in state of the storage receptacle has been detected; and periodically generate non-event information resulting from confirming operation of the wireless accessory sensor node when the change in state of the storage receptacle has not been detected. Such generated non-event information represents a lack of physical interaction with the monitored storage components of exemplary receptacle **48150**, in contrast to the event information. The exemplary wireless accessory sensor node **48210** is also operative to broadcast an updated advertising signal having a flag set within the updated advertising signal where such a set flag indicates exemplary wireless accessory sensor node **48210** has a status update available for upload from the wireless accessory sensor node **48210**. Such a status update includes at least one of the generated event information or the generated non-event information.

(732) In more detail, FIGS. **49A-49B** are exemplary timing diagrams illustrating examples of exemplary wireless accessory sensor node **48210** activity over an exemplary reporting period during operation of the exemplary proactively monitored and reporting logistics receptacle system of FIG. **48** involving the generation of event information or non-event information in accordance with different embodiments of the invention. In general, FIGS. **49A-49B** illustrate such exemplary activity from the perspective of wireless accessory sensor node **48210**. FIG. **49A** generally represents an example where wireless accessory sensor node **48210** detects a change in state of exemplary receptacle **48150** during a first portion of a reporting period but then fails to detect any further change in state of exemplary receptacle **48150** during a second portion of a reporting period. However, those skilled in the art will appreciate that during an exemplary reporting period, wireless accessory sensor node **48210** may detect a change in state of exemplary receptacle **48150** and broadcast an updated advertising signal with a set flag without separately and subsequently generating non-event information and broadcasting another updated advertising signal within the reporting period related to such non-event information. Likewise, those skilled in the art will appreciate that during an exemplary reporting period, wireless accessory sensor node **48210** may not detect a change in state of exemplary receptacle **48150** at all and broadcast an updated advertising signal with a set flag without generating event information and broadcasting a separate updated advertising signal within the reporting period related to such event information.

(733) Referring now to FIG. **49A**, an example is shown where both event information and non-event information are generated at different times (e.g., t.sub.3 and t.sub.5, respectively). In the example shown in FIG. **49A**, an exemplary timeline **4900** of activity is shown having a beginning time at RP.sub.B where an exemplary reporting period begins and an ending time at RP.sub.E where the exemplary reporting period ends. At time t.sub.1, exemplary wireless accessory sensor node **48210** receives sensor data generated by one or more of the sensors monitoring the monitored storage components of exemplary receptacle **48150**. Such sensor data may, for example, indicate a change relative to the state of entrance opening **155**, change of the state of temporary storage area **205**, change of the state of door **160**, and/or change of the state of the area proximate connected logistics receptacle **150**. Exemplary wireless accessory sensor node **48210** detects the change in

state of the storage receptacle based upon the sensor data generated by the at least one of the sensors, and then at time $t_{sub.2}$ records timestamped information (TI) reflecting the detected change in state of the storage receptacle. At time $t_{sub.3}$, exemplary wireless accessory sensor node **48210** generates event information (EI) including the timestamped information reflecting the detected change in state of the storage receptacle when the sensor data indicates the change in state of the storage receptacle has been detected. Generation of the EI then has exemplary wireless accessory sensor node **48210** broadcasting the updated advertising signal having a flag set within the updated advertising signal at time t_a over the wireless transceiver interface of node **48210**. Here, at time $t_{sub.4}$, the flag being set indicates the wireless accessory sensor node **48210** has a status update available for upload from the wireless accessory sensor node **48210**. Such a status update includes, at this point in time, the generated event information (EI). After a period of time where no change in receptacle **48150** is detected, exemplary wireless accessory sensor node **48210** generates non-event information (NEI) at time $t_{sub.5}$. Those skilled in the art will appreciate that this is an example of how exemplary wireless accessory sensor node **48210** may periodically generate confirming the operation of the wireless accessory sensor node **48210** when the change in state of the storage receptacle has not been detected during the reporting period or a particular portion of the reporting period. Generation of the NEI at time $t_{sub.5}$ then has exemplary wireless accessory sensor node **48210** broadcasting the updated advertising signal having a flag set within the updated advertising signal at time t_o over the wireless transceiver interface of node **48210**. Here, at time t_o , the flag being set indicates the wireless accessory sensor node **48210** has a status update available for upload from the wireless accessory sensor node **48210** and where such a status update includes, at this point in time, the generated non-event information (NEI).

(734) Referring now to the example activity shown in FIG. **49B**, an exemplary timeline **4905** of activity is shown with no detected change in state of the logistics receptacle during any part of the reporting period. As such, non-event information (NEI) is generated periodically (e.g., at times $t_{sub.7}$ and $t_{sub.9}$). Generation of the NEI at each of times $t_{sub.7}$ and t_o , respectively, has exemplary wireless accessory sensor node **48210** broadcasting an updated advertising signal having a flag set within the updated advertising signal (e.g., at times $t_{sub.5}$ and $t_{sub.10}$, respectively) over the wireless transceiver interface of node **48210**. For these instances at times $t_{sub.8}$ and $t_{sub.10}$, the flag being set indicates the wireless accessory sensor node **48210** has a status update available for upload from the wireless accessory sensor node **48210** and where such a status update includes, at this point in time, the generated non-event information (NEI).

(735) FIG. **50** is a timing diagram illustrating exemplary bridge node activity during the exemplary reporting period for exemplary proactively monitored and reporting logistics receptacle system of FIG. **48** involving status updates that may include event information or non-event information retrieved from exemplary wireless accessory sensor node **48210** in accordance with an embodiment of the invention. Referring now to the example shown in FIG. **50**, an exemplary timeline **5000** of activity from the perspective of exemplary bridge node **48200** is shown where bridge node **48200** is operative to detect, using the wireless communication interface **203**, the flag set within the updated advertising signal at time $t_{sub.11}$ and retrieve, using the wireless communication interface **203**, the status update from the wireless accessory sensor node **48210** at time $t_{sub.12}$ in response to detecting the flag set at time $t_{sub.11}$. In some embodiments, bridge node **48200** may soon thereafter generate and transmit exemplary receptacle update information to backend server **100** prior to $t_{sub.15}$. However, those skilled in the art will appreciate that other embodiments (such as that shown in FIG. **50**) may have bridge node **48200** waiting until time $t_{sub.15}$ (e.g., waiting to see if a second flag set is detected at time $t_{sub.13}$ and where another status update is retrieved from wireless accessory sensor node **48210** at time $t_{sub.14}$) to transmit receptacle update information to backend server **100**. The receptacle update information includes or at least reflects the retrieved status update including at least one of the generated event information (EI) and the generated non-event information (NEI). As such, the transmitted receptacle update information proactively

validates an operational status of the bridge node **48200** and the wireless accessory sensor node **48210** to the backend server **100**.

(736) Furthermore, the transmitted receptacle update information may cause the backend server **100** to initiate a first type of dispatched logistics operation related to the storage receptacle **48150** when the status update reflected in the receptacle update information corresponds to the event information. In more detail, such a system embodiment may have the first type of dispatched logistics operation comprises a dispatched pickup operation for contents within the storage receptacle of receptacle **48150**. For example, and in even more detail, the receptacle update information transmitted to the backend server may cause the backend server **100** to reactively dispatch a logistics asset (e.g., exemplary logistics asset **700a**, or a mobile node operated by logistics asset **700a**) to the location of receptacle **48150** for pickup of at least the delivery item from within the storage receptacle as the first type of dispatched logistics operation. In another example, the receptacle update information transmitted to the backend server **100** may cause the server **100** to alter a previously scheduled dispatch operation related to the storage receptacle **48150** as the first type of dispatched logistics operation. In still another example, the receptacle update information transmitted to the backend server **100** may cause the server **100** to transmit a pickup message to an alternative logistics asset (e.g., exemplary logistics asset **700b**) as the first type of dispatched logistics operation related to the storage receptacle **48150** where the alternative logistics asset is different than an original logistics asset corresponding to a previously scheduled dispatch operation related to that storage receptacle **48150**.

(737) In a further system embodiment, the receptacle update information may selectively cause the backend server **100** to initiate a second type of dispatched logistics operation related to the storage receptacle **48150** when the status update reflected in the receptacle update information corresponds to the non-event information (NEI). For example, the non-event information may be an indication the wireless accessory sensor node **48210** has not detected the change in state of the storage receptacle **48150** and an indication the wireless accessory sensor node **48210** is still operational to detect the change in state of the storage receptacle. However, those skilled in the art will appreciate that the non-event information may, in some instances, be an indication the wireless accessory sensor node **48210** is not operational to detect the change in state of the storage receptacle. For example, receipt of exemplary receptacle update information may provide EI and/or NEI that confirms expected operation of receptacle **48150**. In other cases, the NEI is provided at an unexpected time, which may indicate abnormal operation of receptacle **48150**. In still other cases, the lack of such EI/NEI when anticipated by server **100** may confirm a problem with receptacle **48150**. Thus, in some embodiments, the second type of dispatched logistics operation may be a dispatched maintenance operation to service the storage receptacle.

(738) In such a system embodiment, different types of sensors may be used for monitoring different monitored components of exemplary node-based logistics receptacle **48150**. For example, the sensor data generated by at least one of the sensors may be sensor data indicating a change in state of the entrance opening as the change in state of the storage receptacle (e.g., where the sensor may be a motion sensor detecting a change in motion of the entrance opening; a motion sensor detecting a change in motion of the entrance opening and a failure to return to a prior state of the entrance opening; an inertial sensor detecting a change in inertial movement related to the entrance opening; a status sensor detecting a change in orientation of the entrance opening and a failure to return to a prior state of the entrance opening as the change in state of the storage receptacle and where the retrieved event information transmitted to the backend server **100** may indicate an overflow state of the storage receptacle; a motion sensor detecting movement of what is received through the entrance opening; an accelerometer detecting a change in motion of the entrance opening; a multiple-axis accelerometer detecting a change in multi-dimensional motion of the entrance opening; a gyroscopic sensor detecting a change in movement related to the entrance opening; and a magnetic sensor detecting a change in position of the entrance opening as the change in state of

the storage receptacle). In another example, the sensor data generated by at least one of the sensors may be sensor data indicating a change in state of the temporary storage area as the change in state of the storage receptacle (e.g., where the sensor may be a motion sensor detecting motion within the temporary storage area; an image sensor detecting a change of what is stored within the temporary storage area; a scale disposed at a bottom of the temporary storage area where the scale detects a change in weight of what is stored within the temporary storage area; a force sensor disposed within the temporary storage area, the force sensor detecting a change in what has been deposited within the temporary storage area (such as a load cell operative to detect an impact force related to the change in what has been deposited within the temporary storage area); a light sensor detecting a change in light within the temporary storage area; and a chemical sensor detecting a chemical within the temporary storage area as the change in state of the storage receptacle). In still another example, the sensor data generated by at least one of the sensors may be sensor data indicating a change in state of the selectively accessible retrieval door as the change in state of the storage receptacle (e.g., where the sensor may be a motion sensor detecting a change in motion of the selectively accessible retrieval door; a motion sensor detecting a change in motion of the selectively accessible retrieval door and a failure to return to a prior state of the selectively accessible retrieval door; an inertial sensor detecting a change in inertial movement related to the selectively accessible retrieval door; a gyroscopic sensor detecting a change in movement related to the selectively accessible retrieval door; a status sensor detecting a change in orientation of the selectively accessible retrieval door and a failure to return to a prior state of the selectively accessible retrieval door as the change in state of the storage receptacle (where the retrieved event information transmitted to the backend server may be indicative of an unsecured state of the storage receptacle); a magnetic sensor detecting a change in position of the selectively accessible retrieval door; a lock sensor detecting a change in state of the door's lock; an external motion sensor detecting a change in what has been placed within a predetermined range of the storage receptacle; a range sensor (such as a proximity sensor, a depth sensor, a LiDAR sensor, an infrared sensor, and/or a laser-based sensor) detecting a change in what has been placed within a predetermined range of the storage receptacle).

(739) As previously shown relative to examples shown in FIGS. 5A-5E, such a system embodiment may have the entrance opening of receptacle **48150** being, for example, an articulating door that when open allows the delivery item to be received by the storage receptacle and transferred into the temporary storage area; a static chute that allows the delivery item to be inserted through the static chute and into the temporary storage area; or an articulating drop chute that allows the delivery item to be received in a first position of the articulating drop chute and transfers the received delivery item to the temporary storage area in a second position of the articulating drop chute.

(740) In a further system embodiment, the change in the state of exemplary node-based logistics receptacle **48150** may be validated. For example, exemplary wireless accessory sensor node **48210** may be operative to detect the change in state of the storage receptacle (e.g., a delivery event where the delivery item is received by the storage receptacle) based upon sensor data generated by at least one of the sensors by being further operative to detect a change in state of the entrance opening using the at least one of the sensors, and validate the change in state of the entrance opening by detecting light within the temporary storage area using a second of the sensors. In another example, exemplary wireless accessory sensor node **48210** may be operative to detect the change in state of the storage receptacle (e.g., a pickup event where the delivery item is removed from the storage receptacle) based upon sensor data generated by at least one of the sensors by being further operative to detect a change in state of the selectively accessible retrieval door using the at least one of the sensors; and validate the change in state of the selectively accessible retrieval door by detecting light within the temporary storage area using a second of the sensors.

(741) In some embodiments, the system's bridge node **48200** may have its processor **201** operative to detect the flag set (e.g., at time $t_{sub.11}$ or time $t_{sub.13}$) by being further operative to wake from

a low power state of the bridge node **48200** at a predetermined time of day and, after the predetermined time of day, detect the flag set within the updated advertising signal over the wireless communication interface **203**. In a more detailed example, the system's bridge node **48200** may have its processor **201** operative to detect the flag set (e.g., at time t.sub.11 or time t.sub.13) by being further operative to wake from a low power state of the bridge node **48200** at a beginning of a reporting period for the bridge node **48200** (e.g., a time period defined by the backend server and provided by the backend server to the bridge node, a dynamically adjusted time period stored in the bridge node memory, the dynamically adjusted time period defined by a reporting period update message sent by the backend server to the bridge node). After the beginning of the reporting period for the bridge node **48200**, processor **201** is then operative to detect the flag set within the updated advertising signal over the wireless communication interface.

(742) Those skilled in the art will appreciate that in such a system embodiment, the event information may include timestamped information and an identifier indicating a type of detected change in state of the storage receptacle (e.g., where the type of detected change in state of the storage receptacle is a change in state of the entrance opening, the temporary storage area, the selectively accessible retrieval door, the lock on the retrieval door, a change in what has been placed within the predetermined range of the storage receptacle as indicated by an external motion sensor and/or range sensor). In more detail, such timestamped information may include data indicating a time corresponding to the detected change in state of the storage receptacle. In a further example, such timestamped information may include data indicating a series of times corresponding to a series of related changes to the storage receptacle, where the series of related changes to the storage receptacle are detected by the wireless accessory sensor node **48210** as the detected change in state of the storage receptacle.

(743) A further system embodiment may have the system's exemplary wireless accessory sensor node **48210** receiving at least a portion of the sensor data over its wireless transceiver interface. A further example may have exemplary wireless accessory sensor node **48210** having a sensor interface coupling node's sensor node processor to the sensors, where the sensor interface is operative to communicate with the sensors and receive the sensor data. In some instances, such a sensor interface may be wirelessly coupled to at least a portion of the sensors.

(744) In yet another system embodiment, the system's exemplary bridge node **48200** may be implemented as a mobile bridge node (e.g., when logistics receptacle **48150** is disposed on a mobile delivery vehicle) having location circuitry coupled to the bridge node processor **201** and operative to generate location data reflecting a current location of the mobile bridge node as mounted to the storage receptacle **48150**. In such an example, the receptacle update information transmitted to the backend server **100** may further include the current location of the mobile bridge node.

(745) Dynamic Tuning of Backend Server

(746) As noted above, various embodiments may have the backend server learning from the reported event information and responsively tuning or modifying the operations of one or more node-based logistics receptacles as a result. In further embodiments, the backend server **100** learns from the reported event information in an advantageously different way by dynamically adjusting when to update engagement/interaction history information and use pattern information that is kept as part of the management profile on the backend server. In other words, some further embodiments have the backend server **100** updating onboard information (e.g., management profile type of information) at dynamically adjusted times depending on changes in engagement and patterns and rates of change of such engagement and patterns as further event information is received from various connected logistics receptacles **150** to further enhance operations of backend server **100**. FIGS. **56-57** illustrate various aspects related to embodiments of such a dynamical learning server-based logistics system.

(747) FIG. **56** is a diagram illustrating an exemplary dynamic learning server-based logistics

system in accordance with an embodiment of the invention. Referring now FIG. 56, exemplary connected node-based logistics receptacle **150** is shown operative to communicate with backend server **100**. Exemplary parcel customer **3800** is shown transporting exemplary package **170** (a type of delivery item) to be deposited within the exemplary connected logistics receptacle **150**. An embodiment of an exemplary dynamic learning server-based logistics system includes node-based logistics receptacle **150** and exemplary backend server **100**. In this system embodiment, the node-based logistics receptacle **150** is operative to receive a delivery item as part of a logistics transaction and includes monitored receptacle components (e.g., entrance opening, a temporary storage area and selectively accessible retrieval door consistent with that previously described). The system's exemplary connected logistics receptacle **150** is also illustrated being equipped with at least exemplary bridge node **200**, exemplary wireless accessory sensor node **210**, and sensors **450a-450e** that are coupled to the wireless accessory sensor node on receptacle **150** and collectively monitor one or more interactions with the monitored receptacle components over a recording time period. The bridge node **200** in this particular system embodiment is operative to retrieve event information from the wireless accessory sensor node (where the event information is related to sensor data generated by the sensors **450a-450e**) and transmit the retrieved event information at an upload time.

(748) The system's backend server **100**, as shown in FIG. 56, maintains a management profile (e.g., exemplary management profile **835**) related to operation of the node-based logistics receptacle **150**. In more detail and as noted above, exemplary management profile **835** is generally a data structure generated, maintained, and updated by backend server **100** with information on the history and use of a node-based logistics receptacles (e.g., exemplary connected node-based logistics receptacle **150**), its respective components, and logistics assets used to service the particular node-based logistics receptacle. Management profile **835** may, in some embodiments, be implemented with a database or records for each connected node-based logistics receptacle being managed by backend server **100** or may be implemented as separate sub-profiles for each connected node-based logistics receptacle being managed by backend server **100**.

(749) In this embodiment and as explained in more detail below, the exemplary dynamic learning server-based logistics system has the backend server **100** dynamically revising management profile **835** in a particularly advantageous manner. In general, the system's backend server **100** is programmatically configured to be operative to receive the retrieved event information **5605** from the bridge node **200** at the upload time; compare the retrieved event information with the management profile **835**; and identify a threshold change condition from the comparison of the retrieved event information with the management profile **835**. The system's backend server **100** is then programmatically configured to be operative to dynamically revise the management profile **835** when the threshold change condition is identified, and transmit an adjustment message **5610** to the bridge node **200** where the adjustment message is based upon the revised management profile **835**. The adjustment message **5610** initiates a timing change to operation of the bridge node **200**. Such a timing change may, for example, be implemented as a change to the recording time period and/or a change to the upload time for the bridge node **200**.

(750) In more detail, a further embodiment of the exemplary dynamic learning server-based logistics system may define the threshold change condition in a variety of ways. For example, the threshold change condition may be a predetermined threshold change in engagement (or interaction) with the node-based logistics receptacle. More specifically, the threshold change condition may take the form of a predetermined threshold change in engagement (or interaction) with the node-based logistics receptacle **150** as indicated by the event information compared to an engagement history for the node-based logistics receptacle **150**, which is maintained as part of the management profile **835** for the node-based logistics receptacle **105**. Such an engagement history may, for example, be a prior component engagement history for prior instances of interactions with different ones of the monitored receptacle components.

(751) In another embodiment, the system may define the threshold change condition as a predetermined threshold rate of change in engagement (interaction) with the node-based logistics receptacle **150**. In more detail, the threshold change condition may be a predetermined threshold rate of change in engagement with the node-based logistics receptacle **150** as indicated by the event information compared to an engagement history for the node-based logistics receptacle **150**, which is maintained as part of the management profile **835** for the node-based logistics receptacle **105**. Such an engagement history may, for example, be a prior component engagement history for prior instances of interactions with different ones of the monitored receptacle components.

(752) In yet another embodiment, the threshold change condition may be implemented as a predetermined threshold change in a pattern of engagement (interaction) with the node-based logistics receptacle **150**. In more detail, the threshold change condition may be a predetermined threshold change in the pattern of engagement with the node-based logistics receptacle **150** as indicated by the event information compared to a pattern of usage for the node-based logistics receptacle **150**, where the pattern of usage is maintained as part of the management profile **835** for the node-based logistics receptacle **150**. Such an exemplary pattern of usage may take the form of a pattern of prior delivery events associated with the node-based logistics receptacle **150**, a pattern of prior pickup events associated with the node-based logistics receptacle **150**, and a pattern of prior pickup and delivery events associated with the node-based logistics receptacle **150**.

(753) Further still, an embodiment may have the threshold change condition being a predetermined threshold rate of change in a pattern of engagement with the node-based logistics receptacle **150**.

(754) Additional embodiments may, for example, implement the threshold change condition as a predetermined threshold change in historic use pattern associated with the node-based logistics receptacle **150**. Such a historic use pattern associated with the node-based logistics receptacle may be a threshold occupancy pattern identifying a frequency of reaching a threshold occupied level within the node-based logistics receptacle **150** and/or an overload pattern identifying a frequency of reaching an overload condition for the node-based logistics receptacle.

(755) Certain embodiments may have the backend server **100** being operative to identify the threshold condition using limits. For example, the backend server **100** may be programmatically configured to be operative to identify the threshold change condition based upon or when the comparison of the retrieved event information with the management profile indicates exceeding a threshold limit associated with the threshold change condition. In another example, the backend server **100** may be programmatically configured to be operative to identify the threshold change condition based upon or when the comparison of the retrieved event information with the management profile indicates a threshold limit associated with the threshold change condition has not been met. In still another example, the backend server **100** may be programmatically configured to be operative to identify the threshold change condition based upon the comparison of the retrieved event information with the management profile indicating at least one of (a) a failure to meet a lower threshold limit associated with the threshold change condition and (b) exceeding an upper threshold limit associated with the threshold change condition. In yet another example, the backend server **100** being programmatically configured to be operative to identify the threshold change condition based upon when the comparison of the retrieved event information with the management profile indicates falling within a threshold limit range associated with the threshold change condition. Further still, another example may have the backend server **100** being programmatically configured to be operative to identify the threshold change condition based upon or when the comparison of the retrieved event information with the management profile indicates falling outside of a threshold limit range associated with the threshold change condition.

(756) Additional system embodiments may have backend server **100** dynamically revising management profile **835** under more specific conditions. For example, the backend server **100** may be programmatically configured to be operative to dynamically revise the management profile **835** when the threshold change condition is identified by being programmatically configured to be

operative to revise timing information maintained within the management profile **835** at a predetermined update time. Such a predetermined update time may, for example, be different from a current update time for revising the management profile. Additionally, such timing information that is revised may be the recording time period and/or the upload time in such additional system embodiments. In still another example, the backend server **100** may be programmatically configured to be operative to dynamically revise the management profile **835** when the threshold change condition is identified by being programmatically configured to be operative to revise timing information maintained within the management profile **835** at a predetermined update time based upon when the threshold change condition is identified and based upon the event information and at least one prior event information received from the node-based logistics receptacle **150**.

(757) FIG. **57** is a diagram illustrating a more detailed embodiment of the system of FIG. **56** where the backend server transmits an exemplary setup message in accordance with an embodiment of the invention. Referring now to FIG. **57**, exemplary backend server **100** is shown as part of a system embodiment where the backend server **100** may be programmatically configured to be further operative to transmit a setup message **5705** to the bridge node **200**. Such an exemplary setup message **5705** configures operation of the bridge node **200** related to at least the recording time period for the wireless accessory sensor node **210** and the upload time for transmitting the retrieved event information to the backend server **100**.

(758) Referring back to FIG. **56**, a similar system embodiment of an exemplary dynamic learning server-based logistics system having the node-based logistics receptacle **150** and the backend server **100** that maintains management profile **835**, the backend server **100** is more specifically programmatically configured to be operative to receive the retrieved event information **5605** from the bridge node **200** at the upload time and determine whether a threshold change condition exists based upon a comparison of the retrieved event information to at least a portion of the management profile **835**. In this further embodiment, when backend server **100** determines the threshold change condition exists, backend server **100** is then operative to (a) adjust an update time related to revising the management profile **835**, (b) revise the management profile **835** based upon the retrieved event information at the adjusted update time, and (c) transmit an adjustment message **5610** to the bridge node **200**, where the adjustment message **5610** is based upon the revised management profile **835** and where the adjustment message **5610** initiates a timing change to operation of the bridge node **200** (e.g., a change to the recording time period and/or upload time). In this further more detailed system embodiment, an embodiment may be implemented that similarly involves transmitting a setup message **5705** (as shown in FIG. **57**) to bridge node **200** to configure operation of the bridge node **200** related to at least one of the recording time period for the wireless accessory sensor node (e.g., node **210**) and the upload time for when the bridge node **200** is to transmit the retrieved event information to the backend server **100**.

(759) Likewise, in this more detailed system embodiment of an exemplary dynamic learning server-based logistics system, further embodiments may similarly implement the threshold change condition similar to that described above (e.g., being a predetermined threshold change in engagement indicated by a comparison of event information and an engagement history maintained within the management profile **835**; being a predetermined threshold rate of change in engagement based on engagement history; being a predetermined threshold change in a pattern of engagement (such as using a pattern of usage reflected in information within management profile **835**); being a predetermined threshold rate of change in a pattern of engagement; being a predetermined threshold change in historic use pattern associated with the node-based logistics receptacle (e.g., threshold occupancy patterns, overload patterns).

(760) Likewise, in this more detailed system embodiment of an exemplary dynamic learning server-based logistics system, further embodiments may revise the management profile **835** in more specific ways. For example, such an embodiment may have the backend server **100** being programmatically configured to be operative to revise the management profile **835** when the

threshold change condition is determined to exist by being programmatically configured to be operative to revise timing information (e.g., the recording time period and/or the upload time) maintained within the management profile **835** at the adjusted update time (e.g., an adjusted update time that is different from a prior update time associated with revising the management profile **835** when the threshold change condition is determined not to exist). In another example, the backend server **100** may be programmatically configured to be operative to revise the management profile when the threshold change condition is determined to exist by being programmatically configured to be operative to revise timing information maintained within the management profile at the adjusted update time based upon when the threshold change condition is determined to exist and based upon the retrieved event information and at least one prior event information received from the node-based logistics receptacle **150**.

(761) Enhanced Node-Based Logistics Receptacle with a Deployable Storage Element

(762) As noted above, some embodiments described herein may involve on-demand deployment of a mobile logistics receptacle as a type of dispatched logistics asset apparatus to the location of an existing node-based logistics receptacle to help address surges in demand at the location of that exemplary node-based logistics receptacle (or in locations near that exemplary node-based logistics receptacle). In additional embodiments, an exemplary node-based logistics receptacle may be equipped with a deployable storage element (e.g., an exemplary deployable mobile container) that is deployed from within the node-based logistics receptacle with items/parcels that may have been collected or otherwise received by that node-based logistics receptacle. As discussed below in more detail, such a deployable mobile container may help to better and more efficiently facilitate logistics operations involving a node-based logistics receptacle. For example, one or more node-based logistics receptacles may deploy their deployable mobile container so that items/parcels within each of them may be provided to a logistics asset that may not be at the same location as the node-based logistics receptacle, but be at separate logistics location (e.g., a location central to several other node-based logistics receptacles or a location that is more accessible to the logistics asset than the location of the node-based logistics receptacle deploying its deployable storage element). Further, as described in more detail below, exemplary deployable storage elements may be autonomous and capable of launching from its node-based logistics receptacle and moving to different locations while navigating to locations while avoiding obstacles as well as autonomously loading into other logistics asset vehicles or a receiving facility associated with a logistics asset or entity. As such, exemplary embodiments of an enhanced node-based logistics receptacle having at least one deployable storage element are described in more detail below relative to FIGS. **58A-69**.

(763) In general, FIGS. **58A-58B** are diagrams illustrating aspects of an exemplary node-based logistics receptacle **58150** with a deployable storage element in accordance with an embodiment of the invention. The exemplary node-based logistics receptacle **58150** shown in FIG. **58A** has an exemplary deployable autonomous mobile container **5805** configured to operate within the receptacle **58150** where container **5805** is able to receive deposited items (where exemplary deployable autonomous mobile container **51020c**, while similar, is a self-moving apparatus that is not used within a node-based logistics receptacle). The exemplary node-based logistics receptacle **58150** shown in FIG. **58B** illustrates how exemplary deployable autonomous mobile container **5805** may be launched from within the receptacle **58150** where deployable autonomous mobile container **5805** moves from within receptacle **58150** (e.g., through an opened retrieval door **160**) upon receipt of a deploy activation signal.

(764) In more detail and referring now to FIG. **58A**, exemplary connected node-based logistics receptacle **58150** is shown operative to communicate with backend server **100** with components similar to exemplary logistics receptacle **150** described relative to FIG. **2**. Those skilled in the art will appreciate that exemplary connected logistics receptacle **58150** shown in at least FIGS. **58A-58B** is similarly structured to exemplary connected/node-based logistics receptacle **150** and **150a**, with the exception that exemplary receptacle **58150** is equipped with an exemplary bridge node

58200 that is programmatically configured to interface with exemplary deployable autonomous mobile container **5805**, monitor what has been deposited within container **5805** in various ways, and coordinate the deployment of container **5805** from a host position within receptacle **58150** to one or more positions external to receptacle **58150**.

(765) As shown in FIG. **58A**, exemplary connected node-based logistics receptacle **58150** is shown with exemplary power source **5820** and exemplary power coupling **5825**, which mates to a power charging port **5815** on exemplary deployable autonomous mobile container **5805**. Power source **5820** (e.g., a battery, a corded power supply, a solar powered power source, and the like) provides power to exemplary deployable autonomous mobile container **5805** through power coupling **5825** disposed on a portion of the storage receptacle. The power charging port **5815** disposed on exemplary deployable autonomous mobile container **5805** accepts power from power source **5820** through power coupling **5825** to charge the deployable autonomous mobile container **5805** and energize electrical components disposed as part of container **5805** (such as the container's autonomous controller **5810** and its propulsion and steering system **5830**). Those skilled in the art will appreciate that exemplary power charging port **5815** mates to exemplary power coupling **5825** when exemplary deployable autonomous mobile container **5805** is in a host position within the storage receptacle. Power source **5820** may, in some embodiments, be able to sense a mated connection with container **5805** and report or confirm the mated connection to bridge node **58200** by sending a confirmation detection message or signal to bridge node **58200**, which may be useful when container **5805** is initially loaded into and received by node-based logistics receptacle **58150**. Further, those skilled in the art will appreciate that exemplary power charging port **5815** becomes automatically disconnected from the power coupling **5825** when the deployable autonomous mobile container **5805** autonomously moves from the host position within the receptacle **58150** to a position external to the receptacle **58150**.

(766) Within exemplary connected node-based logistics receptacle **58150**, exemplary deployable autonomous mobile container **5805** is shown as resting in the host position upon a weight/force sensitive sensor (scale, load cell, impact sensor) coupled to exemplary temporary storage area force sensor node **235**, which can detect changes in what has been deposited within container **5805** in this embodiment. Thus, the weight of contents deposited within container **5810** may be monitored by exemplary connected node-based logistics receptacle **58150** (e.g., exemplary bridge node **58200** and exemplary wireless accessory sensor node **235** coupled to the weight/force sensitive sensor).

(767) As shown in FIG. **58A**, exemplary deployable autonomous mobile container **5805** includes its own temporary storage area **58205** for temporarily maintaining one or more delivery items once they are deposited within the receptacle **58150** through the entrance opening of receptacle **58150** (e.g., exemplary entrance opening **155** and/or entrance opening door **156**). As noted above and explained in more detail relative to FIG. **61**, exemplary deployable autonomous mobile container **5805** is controlled by its own exemplary autonomous controller **5810**, which accepts input (such as a deploy activation signal, destination information, remote input, sensor feedback, and the like), generates control signals for the container's propulsion and steering system **5830** to control movement of the container **5805**, and may generate further signals as part of interfacing with other devices (e.g., wirelessly interacting with mobile logistics assets or personnel associated with such mobile logistics assets). Exemplary deployable autonomous mobile container **5805** is operative to autonomously move from the host position within the receptacle **58150** to a position external to the receptacle **58150** in response to receiving a deploy activation signal from exemplary bridge node **58200**.

(768) In a system embodiment involving exemplary node-based logistics receptacle **58150** and exemplary deployable autonomous mobile container **5805**, the receptacle's exemplary bridge node **58200** (a node similar to exemplary bridge node **200**) is mounted to the storage receptacle **58150**. Exemplary bridge node **58200** includes bridge node processor **201**, bridge node memory **202** coupled to the bridge node processor **201** (where bridge node memory storage **202** in this

embodiment involving the deployable storage element maintains monitoring and deployment code for execution by processor **201**—an example of CRL control & management code **305** shown in FIG. **3**—and data representing an exemplary deployment threshold setting used by processor **201** when determining whether to generate the deploy activation signal), long-range communication interface **203a** coupled to the bridge node processor **201** that can communicate with the backend server **100** over a first communication path, and short-range communication interface **203b** coupled to the bridge node processor **201** that can communicate over a second communication path.

(769) The exemplary deployment threshold setting may be implemented in a variety of ways as a threshold used to evaluate when to launch exemplary deployable autonomous mobile container **5805** relative to a current condition of what is maintained within container **5605**. Such a deployment threshold setting, for example, may relate to a predetermined number of items being maintained within the deployable autonomous mobile container **5805** when the current condition of what is presently maintained within the deployable autonomous mobile container **5805** corresponds to a count of how many items are presently maintained within the deployable autonomous mobile container (e.g., with such a count being based upon motion, impact, and/or image sensor data related to items as they are deposited in area **58205** within container **5805**). In another example, the deployment threshold setting may relate to a predetermined volume level of items being maintained within the deployable autonomous mobile container while the current condition of what is presently maintained within the deployable autonomous mobile container **5805** corresponds to a current volume level of items presently maintained within the deployable autonomous mobile container **5805**. In still another example, the deployment threshold setting may relate to a predetermined weight of items being maintained within the deployable autonomous mobile container **5805** while the current condition of what is presently maintained within the deployable autonomous mobile container **5805** corresponds to a current weight of items presently maintained within the deployable autonomous mobile container **5805**. In yet another example, the deployment threshold setting may relate to a predetermined economic-related threshold where at least when the current condition of what is presently maintained within the deployable autonomous mobile container **5805** corresponds to the predetermined threshold then an economic threshold is exceeded to warrant servicing the storage receptacle **58150** by activating the deployable autonomous mobile container **5805** to leave the host position and move to the position external to the storage receptacle **58150** for a logistics operation related to at least the delivery item. Those skilled in the art will appreciate, for example, that costs for operating a particular deployable autonomous mobile container **5805** and costs incurred related to a logistics operation related to servicing what has been deposited within that container **5805** may be associated with the economic threshold (e.g., costs incurred to launch, service, and replace container **5805** compared with the benefits of more timely servicing of what is deposited within receptacle **58150** (such as meeting priority shipping terms for particular packages, and the like)). In more detail, such an economic threshold may related to particular number/type of packages, a particular combination of packages and letters, and/or weight of container contents where such a threshold involved in generating the deploy activation signal is a threshold grounded in economic terms for operation of the node-based logistics receptacle **58150** and associated logistics assets that are used to service receptacle **58150** (including mobile logistics assets used to collect and/or service exemplary deployable autonomous mobile container **5805** launched from receptacle **58150**).

(770) In such a system embodiment involving exemplary node-based logistics receptacle **58150** and exemplary deployable autonomous mobile container **5805** as illustrated in FIG. **58A**, the system includes sensors operatively in communication with the bridge node's processor (e.g., communicating directly to the bridge node **200** or indirectly via an intervening wireless accessory sensor node that accepts sensor data from the sensor and makes that sensor data available to bridge node **58200**). Generally, such sensors include one or more interaction sensors in communication with the bridge node's processor (directly or indirectly) and that are disposed on the receptacle

58150 to monitor for a change in state of the entrance opening **155/156**. In one example where the interaction sensor directly supplies sensor data to bridge node **58200**, the interaction sensor generates sensor data corresponding to the change in the state of the entrance opening **155/156** and provides the interaction sensor data to the bridge node processor **201**. Such sensor data generated by the interaction sensor monitoring the entrance opening may, for example, be motion sensor data related to motion of the entrance opening, or motion sensor data related to motion of an object through the entrance opening, image sensor data related to an object passing through the entrance opening, and the like. Additionally, such an interaction sensor may be implemented with an inertial sensor detecting a change in inertial movement related to the entrance opening, an accelerometer detecting a change in motion of the entrance opening, a magnetic sensor detecting a change in position of the entrance opening, or a status sensor detecting a change in orientation of the entrance opening and a failure to return to a prior state of the entrance opening. (771) In another example, such as that shown in FIG. **58A** where the interaction sensor indirectly supplies sensor data to bridge node **58200**, the interaction sensor (e.g., motion sensor, status sensor, image sensor, and the like as described above) used with exemplary wireless accessory sensor nodes (such as node **210** operative to detect different types of changes in the state of the entrance opening of connected logistics receptacle **58150**) generates interaction sensor data corresponding to the particular change in the state of the entrance opening. Those skilled in the art will appreciate, in light of embodiments already described above, that the wireless accessory sensor node, as an intermediary, may report such interaction sensor data is available and then provides the interaction sensor data to the bridge node processor **201**.

(772) Aside from interaction sensor(s), the sensors involved in a system embodiment involving exemplary node-based logistics receptacle **58150** and exemplary deployable autonomous mobile container **5805** also include one or more exemplary storage sensors operatively in communication with the bridge node processor **201**. Such exemplary storage sensor(s) may be in direct communication with bridge node processor **201** where the storage sensor may be wired directly to bridge node **58200** or may be wirelessly coupled through interface **203** to bridge node **58200**. Similar to that described above for the interaction sensor, those skilled in the art will appreciate that such an exemplary storage sensor may be indirectly coupled to and indirectly communicate with bridge node processor **201** through an intermediary wireless accessory sensor node coupled to the storage sensor. Consistent with what is described above relative to an example of indirect communication of an interaction sensor with bridge node **58200**, those skilled in the art will appreciate that such a wireless accessory sensor node may be operative to provide the interaction sensor data and the storage sensor data to the bridge node processor **201** by being further operative to (a) broadcast an updated advertising signal indicating the wireless accessory sensor node has at least one of the interaction sensor data and the storage sensor data for upload by the bridge node processor **201** and (b) respond to a request from the bridge node processor **201** for information related to at least one of the interaction sensor data and the storage sensor data.

(773) Such a storage sensor is operative to monitor for a change in state of what is maintained within the deployable autonomous mobile container **5805**. To do this, the storage sensor (e.g., being operative to generate storage sensor data corresponding to the change in the state of what is maintained within the deployable autonomous mobile container **5805** and provide the storage sensor data to the bridge node processor **201**. In more detail, those skilled in the art will appreciate that such a storage sensor may be mounted to an interior of the storage receptacle **58150** and oriented to monitor what is maintained within the deployable autonomous mobile container **5805** (e.g., what has been deposited within storage area **58205** of container **5805**). In a further example, such a storage sensor may be mounted on the deployable autonomous mobile container **5805** and wirelessly coupled to the bridge node **58200** (e.g., directly to interface **203** or indirectly to interface **203** through a wireless accessory sensor node, which may gather the storage sensor data and make such storage sensor data available for upload by bridge node **58200**) and oriented to monitor what

is deposited within the deployable autonomous mobile container **5805**. Such a storage sensor may be implemented, for example, by a motion sensor detecting motion within the deployable autonomous mobile container **5805**, an image sensor detecting a change of what is stored within the deployable autonomous mobile container **5805**, a scale disposed within the deployable autonomous mobile container **5805** where the scale detects at least a change in weight of what is stored within the deployable autonomous mobile container **5805**.

(774) In such a system embodiment involving exemplary node-based logistics receptacle **58150** and exemplary deployable autonomous mobile container **5805** as illustrated in FIG. **58A**, the bridge node **58200** (specifically the bridge node processor **201** in bridge node **58200**), when executing the monitoring and deployment code, being programmatically operative to detect the change in the state of the entrance opening based upon the interaction sensor data, determine a current condition of what is presently maintained within the deployable autonomous mobile container based upon the storage sensor data, and generate the deploy activation signal when the current condition of what is presently maintained within the deployable autonomous mobile container corresponds to at least the deployment threshold setting for the deployable autonomous mobile container **5805**. The bridge node **58200** is further programmatically operative to transmit the deploy activation signal to the deployable autonomous mobile container **5805** (e.g., where autonomous controller **5810** uses a wireless transceiver onboard container **5805** to receive such a deploy activation signal) to initiate movement by the deployable autonomous mobile container **5805** from the host position within the receptacle **58150** to a position external to the receptacle **58150** in response to receiving the deploy activation signal. As shown in FIG. **58B**, exemplary deployable autonomous mobile container **5805**, in response to the deploy activation signal, is shown as it moves from the host position within the receptacle **58150**, disconnects from power coupling **5825**, and proceeds under its own power and autonomous control out from within node-based logistics receptacle **58150**.

(775) Those skilled in the art will appreciate that in an embodiment where retrieval door **160** (or another access door) secures container **5805** in place, door **160** may be actuated in response to the deploy activation signal to an open position to allow container **5805** to move external to receptacle **58150**. However, in another embodiment, exemplary deployable mobile container **5805** may be secured within receptacle **58150** in the host position without the need for an actuated door to allow movement of container **5805** away from receptacle **58150**. In other words, exemplary deployable autonomous mobile container **5805** may insert and securely fit within receptacle **58150** while leaving one side of container **5805** exposed. As such, essentially one side of deployable autonomous mobile container **5805** may form a removable portion of the exterior of receptacle **58150** yet still secure the storage area **58205** within container **5805** in the host position.

(776) In a further system embodiment involving exemplary node-based logistics receptacle **58150** and exemplary deployable autonomous mobile container **5805**, the bridge node **58200**, when executing the monitoring and deployment code, may be further programmatically operative to transmit, using the communication interface **203**, event information (including at least information reflecting the detected change in state of the entrance opening and/or timestamped information related to the detected change in state of the entrance opening) to the backend server **100** when the current condition of what is presently maintained within the deployable autonomous mobile container **5805** corresponds to less than the deployment threshold setting for the deployable autonomous mobile container **5805**. Additionally, the bridge node **58200** may be operative to transmit, using the communication interface **203**, a dispatch message to the backend server **100** when the current condition of what is presently maintained within the deployable autonomous mobile container **5805** corresponds to less than the deployment threshold setting for the deployable autonomous mobile container **5805**. Such a dispatch message may include event information (including at least information reflecting the detected change in state of the entrance opening and/or timestamped information related to the detected change in state of the entrance opening) reflecting the detected change in state of the entrance opening and cause the backend server **100** to initiate a

dispatched logistics operation related to the storage receptacle (such as causing a logistics asset to travel to the location of node-based logistics receptacle **58150** to pickup/drop off items).

(777) FIG. **59** is a diagram illustrating an exemplary deployable storage element deployed to a position external to the node-based logistics receptacle **58150** and near an exemplary mobile logistics asset **700a** in accordance with an embodiment of the invention. Referring now to FIG. **59**, exemplary deployable autonomous mobile container **5805** has been deployed and is shown at a position external to the storage receptacle **58150**. In more detail, an embodiment may have exemplary deployable autonomous mobile container **5805** being operative to move from the host position within receptacle **58150** to a logistics destination as the position external to the storage receptacle according to logistics destination information contained within the deploy activation signal received by the autonomous controller **5810** of container **5805**. In such an embodiment, the logistics destination may, for example, be the position of a logistics asset (such as logistics asset **700a**) capable of accepting or unloading the deployable autonomous mobile container. For example, as shown in FIG. **59**, an exemplary mobile logistics asset **700a** has delivery vehicle **2602**, which may be capable of accepting or otherwise receiving exemplary deployable autonomous mobile container **5805**.

(778) Rather than being contained within the deploy activation signal, another embodiment may have the logistics destination information used by the autonomous controller **5810** may be contained within a logistics destination message received by the deployable autonomous mobile container **5805**. Such a logistics destination message received by the deployable autonomous mobile container **5805** may, for example, be sent by the receptacle's bridge node **58200** (e.g., as a separate communication than the deploy activation signal), sent by backend server **100**, sent by a transceiver operated by a mobile logistics asset (e.g., mobile transceiver **2600** disposed on delivery vehicle **2602** associated with mobile logistics asset **700a** or mobile handheld communication device **2630** carried by courier personnel **2615** and operates as a type of mobile wireless transceiver associated with the mobile logistics asset **700a**). Additionally, an exemplary logistics destination message received by the deployable autonomous mobile container **5805** may be sent by a transceiver operated by an autonomous mobile logistics asset (e.g., exemplary autonomous mobile logistics asset **6000** illustrated in and described below relative to FIG. **60**).

(779) In some embodiments, exemplary deployable autonomous mobile container **5805** may move from the host position within exemplary node-based logistics receptacle **58150** to more than one position as it navigates and moves outside of receptacle **58150**. For example, an embodiment may have exemplary deployable autonomous mobile container **5805** being operative to move from the host position to one or more positions external to the storage receptacle **58150**, and then subsequently move to a logistics destination (e.g., a position at or near mobile logistics asset **700a**) according to logistics destination information contained within a logistics destination message received by the deployable autonomous mobile container. In such an example, a further embodiment may have the logistics destination message received by the deployable autonomous mobile container **5805** having been sent by a transceiver operated by a mobile logistics asset (e.g., mobile transceiver **2600** disposed on delivery vehicle **2602** or mobile handheld communication device **2630**—both of which being associated with mobile logistics asset **700a** as shown in FIG. **59**). Likewise, yet another embodiment may have the logistics destination message received by the deployable autonomous mobile container **5805** having been sent by a transceiver operated by an autonomous mobile logistics asset (e.g., exemplary autonomous mobile logistics asset **6000** illustrated in and described below relative to FIG. **60**).

(780) FIG. **60** is a diagram illustrating an exemplary deployable storage element (e.g., exemplary deployable autonomous mobile container **5805**) deployed to a position external to the node-based logistics receptacle **58150** and near an exemplary autonomous mobile logistics asset **6000** in accordance with an embodiment of the invention. Referring now to FIG. **60**, exemplary autonomous mobile logistics asset **6000** is shown as a type of mobile logistics asset that may

receive, accept or unload exemplary deployable autonomous mobile container **5805** at a logistics destination for container **5805**. Those skilled in the art will appreciate that exemplary autonomous mobile logistics asset **6000** is generally a type of self-propelled autonomous delivery vehicle capable of being dispatched to a particular location so that delivery items (or mobile containers that maintain delivery items) may be loaded inside for further logistics movement to another location (such as a logistics facility for sorting and/or delivery at a destination). As shown in FIG. **60**, exemplary autonomous mobile logistics asset **6000** has an autonomous controller **6005**, wireless transceiver, storage area **6015** for items/containers being transported, and a securable port **6025** providing selective access to within exemplary autonomous mobile logistics asset **6000**. The autonomous controller **6005** is coupled to a wireless transceiver **6010** so that controller **6005** may communicate with devices (such as exemplary deployable autonomous mobile container **5805**, backend server **100**, node-based logistics receptacle **58150**, and other wireless devices). Storage area **6015** within the autonomous mobile logistics asset **6000** is used for temporarily maintaining delivery items (e.g., items **6020**) that may be loaded into or unloaded from within autonomous mobile logistics asset **6000**. Storage area **6015** may be accessed through securable port **6025** (which may be implemented as a retractable and securable ramp, door, hatch, and the like) so that deployable autonomous mobile container **5805** may move within storage area **6015** when autonomous mobile logistics asset **6000** operates to accept container **5805** and the delivery items it may contain.

(781) FIG. **61** is a more detailed diagram illustrating an exemplary deployable autonomous mobile container **5805** as a type of deployable storage element in accordance with an embodiment of the invention. Referring now to FIG. **61**, exemplary deployable autonomous mobile container **5805** is shown having a container housing **6100**, autonomous controller **6105** (referred to as controller **5810** in FIG. **58A**), propulsion and steering system **6110** (also referred to as system **5830** in FIG. **58A**), internal storage area **6140** (also referred to as storage area **58205** in FIG. **58A**), mobile container navigation sensors **6115**, wireless radio transceiver **6120**, an access port **6130**, location circuitry **6125**, an actuated top access panel **6142**, and exemplary human engagement interface **6145**. Exemplary container housing **6100** is a mobile housing structure that can temporarily maintain the delivery item once the delivery item has been deposited within the node-based logistics receptacle **58150** (while container **5805** is in the host position) through the receptacle's entrance opening. Those skilled in the art will appreciate that the exemplary autonomous controller **6105** is disposed on the container housing **6100** and may be maintained within its own module or environmental housing along with interfacing that facilitates coupling to onboard sensors (e.g., sensors **6115**, **6135a-6135c**) as well as location circuitry **6125**, and transceiver **6120**.

(782) Exemplary propulsion and steering system **6110** is generally disposed on the container housing to allow for controlled movement of container **5805**. Propulsion and steering system **6110** is responsive to propulsion and steering control signals from the autonomous controller **6105** that cause changes to directional movement of the deployable autonomous mobile container **5805**. Embodiments may have exemplary propulsion and steering system **6110** including wheels, steering linkages, and one or more propulsion engine (e.g., electric motor(s)) that implement speed and direction control actuation, while other embodiments may use tracks or alternative propulsion implementations that may be speed and directionally controlled.

(783) Exemplary mobile container navigation sensors **6115** are coupled to the autonomous controller **6105** and disposed relative to the exterior of housing **6100** so as to have sensory ranges proximate different parts of container **5805** (e.g., in front of container **5805**, behind container **5805**, on each side of container **5805**, and in some implementations above container **5805**). In some embodiments, the mobile container navigation sensors **6115** are operative to autonomously detect an object in the path of the deployable autonomous mobile container **5805** and provide navigation feedback sensor data to the autonomous controller **6105** on the detected object. In other embodiments, the mobile container navigation sensors **6115** are operative to generate sensor data

and provide such sensor data to the autonomous controller **6105**, which uses its logic to process the sensor data to autonomously detect an object in the path of the deployable autonomous mobile container **5805**.

(784) Exemplary wireless radio transceiver **6120**, which includes an antenna, is disposed on the container housing **6100** and operatively coupled to the autonomous controller **6105**. As deployed on the container housing **6100**, the wireless radio transceiver **6120** is operative to communicate with communication devices disposed external to the deployable autonomous mobile container, such as backend server **100**, bridge node **58200**, as well as other vehicle-based and mobile handheld transceivers (e.g., transceivers **2600**, **2630**) used by customers as well as logistics assets.

(785) Exemplary location circuitry **6125** is also disposed on the container housing **6100** and operatively coupled to the autonomous controller **6105**. Onboard container **5805**, exemplary location circuitry **6125** generates location data (e.g., GPS coordinates) on a location of the deployable autonomous mobile container **5805** and provide the location data to the autonomous controller **6105** for use in navigating activity by autonomous controller **6105**.

(786) Exemplary access port **6130** generally provides unloading access to within the deployable autonomous mobile container **5805**. Access port **6130** is a securable door, hatch, or other opening that may, in some embodiments, be actuated by autonomous controller **6105** between a closed/secured position and an open/unsecured position based upon sensed interactions with external devices, verification/authentication of such external devices, and the like.

(787) Exemplary internal sensors **6135a-6135c** provide monitoring of internal temporary storage area **6140** within container housing **6100**. For example, internal sensor **6135** is an exemplary internal sensor that monitors access port **6130** (e.g., what goes through the opening covered by port **6130**, motion detected relative to port **6130** or through the opening covered by port **6130**, status of port **6130**, and the like). In more detail, the autonomous controller **6105** is operative to receive internal sensor data generated by the internal sensor, transmit the internal sensor data to the bridge node **58200** (e.g., when container **5805** is in the host position within receptacle **58150**), and transmit the internal sensor data to an external node outside of the storage receptacle (such as a mobile user device operated by a logistics asset).

(788) Exemplary human engagement interface **6145** is disposed on an exterior of the container housing **6100** and coupled to autonomous controller **6105**. In general, human engagement interface **6145** is operative to provide feedback information—e.g., to container **5805** and by container **5805** to personnel outside of container **5805**. In other words, those skilled in the art will appreciate that human engagement interface **6145** may include one or more devices that facilitates communication with personnel outside of container **5805**—e.g., providing information to those outside of container **5805** and/or receiving input from those outside of container **5805**. An embodiment may implement human engagement interface **6145**, for example, with one or more exterior exposed status light, speaker, microphone, switch, button, keypad, display, and interactive touch sensitive screen.

(789) As shown in FIG. **61**, exemplary actuated top access panel **6142** is generally a type of actuated port that can cover or provide access to within storage area **6140**. As such, exemplary actuated top access panel **6142** provides access to the opening through which delivery items may drop and be deposited into storage area **6140** within exemplary deployable autonomous mobile container **5805**. Stated another way, exemplary access panel **6142** secures what is maintained within the deployable autonomous mobile container **5805** once the deployable autonomous mobile container **5805** is moved from the host position. In more detail, autonomous controller **6105** within deployable autonomous mobile container **5805** can actuate the access panel **6142** in response to the deploy activation signal to secure what is maintained within the deployable autonomous mobile container. In particular, the autonomous controller **6105** may actuate the access panel **6142** to a closed position in response to receiving the deploy activation signal from the bridge node **58200** to secure what is maintained within the deployable autonomous mobile container **5805**.

(790) In some embodiments, exemplary actuated top access panel **6142** may be used to provide

authorized access to within the deployable autonomous mobile container **5805**. For example, an embodiment may have autonomous controller **6105** actuate the access panel **6142** to an open position in response to receiving an access signal from an external device to provide access to what is maintained within the deployable autonomous mobile container **5805**. In more detail, the autonomous controller **6105** may verify the access signal is from an authorized entity operating the external device prior to actuating the access panel **6142** to the open position.

(791) FIGS. **62A-62C** are diagrams illustrating more details on various examples of closable or actuated access panels used as actuated top access panel **6142** that provide access within an exemplary deployable autonomous mobile container and may secure what has been deposited within the exemplary deployable autonomous mobile container **5805** in accordance with an embodiment of the invention. Those skilled in the art will appreciate that exemplary actuated access panel **6142** may, for example, be implemented with an actuated cover, an actuated door, an actuated lid, or an actuated roll top for the deployable autonomous mobile container. Referring now to FIG. **62A**, exemplary deployable autonomous mobile container **5805a** is shown in a configuration where a lifting actuated access panel **6142a** is shown in the form of an actuated lifting door or lid that may extend above container **5805a**. Here, exemplary autonomous controller **6105** may initiate actuation of access panel **6142a** to cause movement of access panel **6142a** between a lifted position (open) to a retracted position (closed) as shown in FIG. **62A**. Those skilled in the art will appreciate that access panel **6142a** may be an actuated securable cover or lid for the container housing **6100** of the deployable autonomous mobile container **5805a**.

(792) In FIG. **62B**, exemplary deployable autonomous mobile container **5805b** is shown in a configuration where a dropping actuated access panel **6142b** is shown in the form of a set of actuated dropping doors **6200a**, **6200b** that may drop into container **5805a**. Here, exemplary autonomous controller **6105** may initiate actuation of access panel **6142b** to cause movement of access panel **6142b** between a dropped position (open) to a pulled up or lifted position (closed) as shown in FIG. **62B**. Those skilled in the art will appreciate that access panel **6142b** may be an actuated securable door for the container housing **6100** of the deployable autonomous mobile container **5805b**.

(793) In FIG. **62C**, exemplary deployable autonomous mobile container **5805c** is shown in a configuration where roll-top type of actuated access panel **6142c** is shown in the form of a flexible panel **6210** that may be actuated to extend from and roll up into a roll-retention cylinder **6205**. Here, exemplary autonomous controller **6105** may initiate actuation of access panel **6142c** to cause movement of access panel **6142c** between an open position where flexible panel **6210** is withdrawn and wound into roll-retention cylinder **6205** to a closed position where flexible panel **6210** extends from roll-retention cylinder **6205** and secures in place over the opening covered by panel **6142c** as shown in FIG. **62B**. Those skilled in the art will appreciate that access panel **6142c** may be an actuated securable roll top for the container housing **6100** of the deployable autonomous mobile container **5805c**.

(794) FIGS. **63A-63E** illustrate examples of how an exemplary deployable autonomous mobile container **5805** launched from exemplary node-based logistics receptacle **58150** interacts with various mobile logistics assets in different ways. For example, FIG. **63A** is a diagram illustrating an exemplary deployable autonomous mobile container **5805** navigating towards an exemplary mobile logistics asset (e.g., exemplary autonomous mobile logistics asset **6000**) in accordance with an embodiment of the invention. Referring now to FIG. **63A**, exemplary deployable autonomous mobile container **5805** is shown having been deployed, no longer in its host position within node-based logistics receptacle **58150**, and navigating on path **6300** towards a mobile logistics asset (e.g., exemplary autonomous mobile logistics asset **6000**). In doing so, those skilled in the art will appreciate that an embodiment of autonomous controller **6105** within exemplary deployable autonomous mobile container **5805** is operative to navigate towards the autonomous mobile logistics asset **6000** using the mobile container navigation sensors **6115**, which may include motion

sensors, image/video sensors, machine vision type of sensors, proximity sensors, and the like. Exemplary autonomous controller **6105** within exemplary deployable autonomous mobile container **5805**, in a further embodiment, is operative to detect, using the wireless radio transceiver **6120** coupled to autonomous controller **6105**, a signal from the autonomous mobile logistics asset **6000** and navigate, using the mobile container navigation sensors **6115**, to the autonomous mobile logistics asset **6000** based upon at least the detected signal from the autonomous mobile logistics asset **6000**. Such a detected signal may provide guidance information, such as location information on a logistics destination, on where the deployable autonomous mobile container **5805** can meet the mobile logistics asset.

(795) In a more detailed embodiment, the autonomous controller **6105** is further operative to cause the deployable autonomous mobile container **5805** to move from the host position to a logistics destination as the position external to the node-based logistics receptacle **58150** according to logistics destination information received by the autonomous controller **6105**. The logistics destination may, in an example, correspond to the position of a logistics asset (e.g., mobile logistics asset **700a**, autonomous mobile logistics asset **6000**) operative to accept the deployable autonomous mobile container **5805**. Such a logistics destination may, in another example, correspond to the position of a logistics asset (e.g., mobile logistics asset **700a**, autonomous mobile logistics asset **6000**) operative to unload the deployable autonomous mobile container **5805**. Such logistics destination information received by autonomous controller **6105** may, for example, have been sent by bridge node **58200**, backend server **100**, a transceiver operated by a mobile logistics asset, or a transceiver operated by an autonomous mobile logistics asset (such as a mobile user device operated by the mobile logistics asset or personnel associated with the mobile logistics asset).

(796) When the deployable autonomous mobile container **5805** approaches a mobile logistics asset, the autonomous controller **6105** in some embodiments is programmatically operative to authenticate that the approached mobile logistics asset is an authorized entity with which the deployable autonomous mobile container **5805** can use relative to its cargo of delivery items. FIG. **63B** is a diagram illustrating exemplary deployable autonomous mobile container **5805** interacting with an exemplary mobile logistics asset (e.g., autonomous mobile logistics asset **6000**) as part of authenticating the exemplary mobile logistics asset in accordance with an embodiment of the invention. Referring now to the embodiment shown in FIG. **63B**, those skilled in the art will appreciate that the autonomous controller **6105** within deployable autonomous mobile container **5805** is operative to use its wireless radio transceiver **6120** to detect a signal from a mobile logistics asset as container **5805** approaches the mobile logistics asset. Here, for example, autonomous controller **6105** detects a wireless signal **6305** emanating from exemplary autonomous mobile logistics asset **6000** as container **5805** approaches the mobile logistics asset **6000**. Once signal **6305** is detected, autonomous controller **6105** is further programmatically operative in this embodiment to authenticate that the mobile logistics asset **6000** is an authorized logistics asset to receive what is temporarily maintained within the container housing. In more detail, exemplary autonomous controller **6105** may be operative to authenticate that the mobile logistics asset **6000** is an authorized logistics asset based upon authentication information received from the mobile logistics asset **6000** over the wireless radio transceiver **6120**. Such authentication information may, for example, be part of signal **6305** detected by autonomous controller **6105** upon the approach to mobile logistics asset **6000** without requesting signal **6305** (or the authentication information) to be broadcast. However, in other embodiments, the authentication information may be requested by autonomous controller **6105** in response to receiving the initial signal **6305** from mobile logistics asset **6000**. In such an embodiment, the autonomous controller **6005** of exemplary autonomous mobile logistics asset **6000** may respond to such a request by subsequently transmitting a second message that includes the authentication information. This response, for example, may be performed after the autonomous mobile logistics asset **6000** itself has authenticated that exemplary

deployable autonomous mobile container **5805** is a deployable storage element that mobile logistics asset **6000** is authorized to assist with its onboard delivery items.

(797) FIG. **63C** is a diagram illustrating an embodiment where exemplary deployable autonomous mobile container **5805** is interacting with exemplary mobile logistics asset **6000** as part of a security handshake interface operation in accordance with an embodiment of the invention. Referring to FIG. **63C**, the autonomous controller **6105** of exemplary deployable autonomous mobile container **5805** is operative to authenticate that the mobile logistics asset **6000** is an authorized logistics asset based upon a security handshake interface operation **6310** conducted with the mobile logistics asset **6000** over the wireless radio transceiver **6120**. Those skilled in the art will appreciate that the security handshake interface operation **6310** is a process that establishes a communication link between autonomous controller **6105** of container **5805** and autonomous controller **6005** of mobile logistics asset **6000** and provides authentication information used to authenticate that the mobile logistics asset **6000** is an authorized logistics asset to be used by deployable autonomous mobile container **5805**.

(798) In some embodiments where personnel are involved with the mobile logistics asset (e.g., exemplary personnel **2615** associated with mobile logistics asset **700a** using delivery vehicle **2602**), the authentication information may be provided by a mobile handheld communication device **2630** operated by personnel **2615**. Those skilled in the art will appreciate that the principles described above regarding detecting signal **6305** may be applicable to a signal being broadcast by mobile handheld communication device **2630** (rather than asset **6000**) and handshaking operations **6310** may be performed with mobile handheld communication device **2630** (rather than asset **6000**), which in some embodiments may be implemented as an augmented reality headset communication device.

(799) In still other embodiments where personnel are involved with the mobile logistics asset (e.g., exemplary personnel **2615** associated with mobile logistics asset **700a** using delivery vehicle **2602**), the authentication information may be provided by such personnel via human input to exemplary container **5805**. FIG. **63D** is a diagram illustrating an embodiment where exemplary deployable autonomous mobile container **5805** is interacting with personnel **2615** associated with an exemplary mobile logistics asset **700a** using a human engagement interface **6145** on the deployable autonomous mobile container **5805** in accordance with an embodiment of the invention. Referring to the embodiment illustrated in FIG. **63D**, exemplary deployable autonomous mobile container **5805** is shown having at least one human engagement interface **6145** (e.g., a keypad and display, an interactive touchscreen, and the like) disposed on an exterior of the container housing **6100** of exemplary container **5805**. The human engagement interface **6145**, in this embodiment, is operative to at least receive authentication information from personnel **2615** associated with the mobile logistics asset **700a**. Once personnel **2615** inputs information on human engagement interface **6145**, autonomous controller **6105** of container **5805** is operative to authenticate that the mobile logistics asset **700a** is the authorized logistics asset based upon the authentication information received using the at least one human engagement interface.

(800) In some embodiments, exemplary deployable autonomous mobile container **5805** may be unloaded by the authenticated mobile logistics asset. Such unloading may, for example, be performed by personnel **2615** associated with mobile logistics asset **700a**. In other instances, such unloading may be performed in a machine-to-machine manner an object manipulation system (e.g., robotic arms, and the like) used on deployable autonomous mobile logistics asset **6000** under control of autonomous controller **6005** to move items from container **5805** to within storage area **6015**. Such unloading operations may be monitored by sensors onboard exemplary deployable autonomous mobile container **5805** (e.g., using internal sensor **6135b**).

(801) Once unloaded, exemplary deployable autonomous mobile container **5805** may move to a secondary location. In one example, such as a storage location or hub location remote from node-based logistics receptacle **58150** and used to temporarily store the deployable autonomous mobile

container **5805**. In another example, the secondary location is simply back to the location of node-based logistics receptacle **58150**.

(802) In more detail, an embodiment may have the autonomous controller **6105** of container **5805** being further operative to cause the deployable autonomous mobile container **5805** to move from the logistics destination to the secondary location. Such movement to the secondary location may, for example, be in response to monitoring the internal temporary storage area **6140** within the container housing **6100** of deployable autonomous mobile container **5805** using the at least one internal sensor (such as internal storage area sensor **6135b**). More specifically, an embodiment may have the autonomous controller **6105** of container **5805** being further operative to cause the deployable autonomous mobile container **5805** to detect, using the at least internal sensor **6135b**, the internal temporary storage **6140** has been unloaded at the logistics destination; and move from the logistics destination to a secondary location when the internal temporary storage **6140** is detected to have been unloaded at the logistics destination using internal sensor **6135b**.

(803) While some embodiments may have exemplary deployable autonomous mobile container **5805** unloaded at the logistics destination, other embodiments may have exemplary deployable autonomous mobile container **5805** loading into the mobile logistics asset at the logistics destination and then transported elsewhere as part of shipping the delivery items in container **5805**. FIG. **63E** is a diagram illustrating an embodiment where exemplary deployable autonomous mobile container **5805** is autonomously loading into exemplary mobile logistics asset **700a** in accordance with an embodiment of the invention. Referring now to the embodiment illustrated in FIG. **63E**, exemplary delivery vehicle **2602** associated with mobile logistics asset **700a** has a delivery vehicle door **6315** that may be lowered or otherwise opened to make ready for autonomous loading of container **5805**. For example, in response to a loading request signal from autonomous controller **6105** of container **5805** to transceiver **2600** or handheld **2630**, transceiver **2600**/handheld **2630** (which may be implemented as AR headset communication devices) may responsively cause actuation of door **6315**. In another example, the loading request signal may be sent to handheld **2630** used by personnel **2615** associated with mobile logistics asset **700a** to request personnel **2615** to manually ready delivery vehicle **2602** for autonomous loading of container **5805** by container **5805**. Thereafter, the autonomous controller **6105** of exemplary deployable autonomous mobile container **5805** is operative to cause autonomous loading of the deployable autonomous mobile container **5805** into mobile logistics asset. For example and in more detail, the autonomous controller **6105** may be further operative to cause autonomous loading of the deployable autonomous mobile container **5805** into a storage area of the mobile logistics asset's delivery vehicle **2602** based at least upon the navigation feedback sensor data from the mobile container navigation sensors **6115**, location data generated by location circuitry **6125**, and/or one or more signals received from the mobile logistics asset (e.g., signals from transceiver **2600**, which may provide such signals in response to input from onboard vehicle sensor, and the like).

(804) FIG. **64** is a diagram illustrating an embodiment of exemplary node-based logistics receptacle **58150** receiving an exemplary deployable autonomous mobile container (such as exemplary container **5805**) back into its host position and verifying the compatibility of the deployable autonomous mobile container **5805** being received with that node-based logistics receptacle **58150** in accordance with an embodiment of the invention. As an exemplary deployable autonomous mobile container is activated and launched from exemplary node-based logistics receptacle **58150**, that exemplary deployable autonomous mobile container may return to the node-based logistics receptacle **58150** or be replaced with another similar deployable autonomous mobile container. Referring now to FIG. **64**, an embodiment may have the receptacle verify that the returning or replacement deployable autonomous mobile container is a compatible container for that receptacle. For example, the bridge node **58200** in exemplary node-based logistics receptacle **58150**, when executing the monitoring and deployment code, may be further programmatically operative to verify that the deployable autonomous mobile container **5805** is a compatible container for the

storage receptacle. More particularly, the bridge node **58200** in exemplary node-based logistics receptacle **58150**, when executing the monitoring and deployment code, may be further programmatically operative to confirm receipt of the deployable autonomous mobile container **5805** into the host position within receptacle **58150** (e.g., receive container **5805** via confirmation of the container's location using internal monitoring sensors within receptacle **58150** and/or confirming the container is mated to power source **5820** via a confirmation detection message or signal); and verify that the deployable autonomous mobile container **5805**, once received in the host position, is a compatible container for the storage receptacle **58150**.

(805) In some embodiments, this type of verification of compatibility may be proactively accomplished prior to when the container **5805** is fully seated in the host position within node-based logistics receptacle **58150**. For example, an embodiment may have bridge node **58200** being programmatically operative to detect the deployable autonomous mobile container **5805** approaching the storage receptacle **58150** (e.g., via detection of signals broadcast from container **5805**); receive container identification information from the deployable autonomous mobile container **5805** while the deployable autonomous container is approaching the storage receptacle (e.g., such container identification information being part of what is broadcast and detected or, alternatively, provided by container **5805** upon a separate request from bridge node **58200**); and verify that the deployable autonomous mobile container **5805** approaching is a compatible container for the storage receptacle based upon the container identification information received from the deployable autonomous mobile container **5805**. Those skilled in the art will appreciate that the approaching container **5805** in such an embodiment may be a replacement deployable autonomous mobile container to take the place of a previously deployed second deployable autonomous mobile container.

(806) Furthermore, an additional embodiment may have bridge node **58200** being programmatically operative to transmit a substitution request to the backend server **100** for a substitute deployable autonomous mobile container when the bridge node **5820** is unable to verify that the deployable autonomous mobile container (e.g., one that has been received into the host position within receptacle **58150** or one that is merely approaching receptacle **58150**) is compatible for the node-based logistics receptacle **58150**.

(807) As noted above, an exemplary deployable autonomous mobile container moving to be received within the node-based logistics receptacle **58150** may be a replacement deployable autonomous mobile container. FIG. 65 is a diagram illustrating an exemplary node-based logistics receptacle requesting an exemplary replacement deployable autonomous mobile container **5805r** in accordance with an embodiment of the invention. Referring now to FIG. 65, exemplary node-based logistics receptacle **58150** is shown after having launched its deployable autonomous mobile container **5805**. In this condition, those skilled in the art will appreciate that the receptacle **58150** is in need of a replacement for the deployed container **5805**. Accordingly, and in an embodiment, the bridge node **58200** of receptacle **58150** may be operative to transmit a replacement request **6500** to the backend server **100** for a replacement deployable autonomous mobile container after transmitting the deploy activation signal, which initiates deployment of deployable autonomous mobile container **5805**. In more detail and for example, the bridge node **58200** of receptacle **58150** may be operative to transmit a replacement request **6500** to the backend server **100** for a replacement deployable autonomous mobile container after transmitting the deploy activation signal and upon detecting (e.g., using sensors on the node-based logistics receptacle **58150**) that the deployable autonomous mobile container **5805** has moved from the host position within the receptacle **58150** to a position external to the receptacle **58150**. In another example, the bridge node **58200** of receptacle **58150** may be operative to transmit a replacement request **6500** to the backend server **100** for a replacement deployable autonomous mobile container after transmitting the deploy activation signal and detecting, using the communication interface **203**, a deployment confirmation signal from the deployable autonomous mobile container **5805** confirming the

deployable autonomous mobile container **5805** has moved from the host position within the receptacle **58150** to the position external to the storage receptacle **58150**.

(808) Backend server **100**, in response to the receipt of such a replacement request **6500**, may initiate a replacement operation for node-based logistics receptacle **58150** and send a replacement activation signal **6505** to an exemplary replacement deployable autonomous mobile container **5805r** as shown in FIG. **65**. For example, an embodiment may have bridge node **58200** being further programmatically operative to transmit, after transmitting the deploy activation signal to the deployable autonomous mobile container, a replacement logistics operation request (e.g., as part of replacement request **6500**) to the backend server **100** to cause the backend server **100** to initiate the replacement logistics operation involving a replacement deployable autonomous mobile container **5805r** (e.g., via replacement activation signal **6505**) after transmitting the deploy activation signal to the deployable autonomous mobile container **5805**.

(809) Thereafter, a further embodiment may have the bridge node **58200**, when executing the monitoring and deployment code, being further programmatically operative to receive (or otherwise confirm receipt of) the replacement deployable autonomous mobile container **5805r** after transmitting the deploy activation signal to the deployable autonomous mobile container **5805** and after transmitting the replacement request **6500** to the backend server **100**. In more detail, the bridge node **58200** may be operative to receive the replacement deployment autonomous mobile container **5805r** by being operative to detect a signal broadcast by the replacement deployable autonomous mobile container **5805r** as container **5805r** autonomously approaches the storage receptacle **58150**; and confirm receipt of the replacement deployable autonomous mobile container **5805r** into the host position within the storage receptacle **58150**. As noted above, an embodiment may have bridge node **58200** confirming receipt of a deployable autonomous mobile container into the host position within receptacle **58150** may, for example, be based upon confirmation of the container's location using internal monitoring sensors (e.g., proximity sensors, motion sensors, image sensors) within receptacle **58150** and/or confirming the container has been mated to the power source **5820** within receptacle **58150** via a confirmation detection message or signal).

(810) Further still, an even more detailed embodiment may have bridge node **58200** being operative to detect a signal broadcast by the replacement deployable autonomous mobile container **5805r** autonomously approaching receptacle **58150**; identify container identification information in the signal broadcast by the replacement deployable autonomous mobile container **5805r** during the approach; verify that the replacement deployable autonomous mobile container **5805r** is a compatible container for the storage receptacle based upon the container identification information; and receive the replacement deployable autonomous mobile container **5805r** into the host position within the storage receptacle **58150**. In this way, node-enabled logistics receptacle **58150** is able to proactively interrogate the approaching replacement deployable autonomous mobile container **5805r** to avoid compatibility issues before the container **5805r** is received within the receptacle **58150** and any potential damage or other issues arising from the incompatibility occur.

(811) In some embodiments involving a deployable storage element, the node-based logistics receptacle is able to accommodate a first “primary” deployable autonomous mobile container that is current used to receive any items being deposited along with a second “reserve” deployable autonomous mobile container that can take the primary container's place once the primary container is launched. FIGS. **66A-66C** are diagrams illustrating an embodiment with an exemplary node-based logistics receptacle **58150** having a first deployable autonomous mobile container **5805a** and a reserve deployable autonomous mobile container **5805b** in accordance with an embodiment of the invention. Referring now to FIG. **66A**, another embodiment of exemplary node-based logistics receptacle **58150** is shown with the internal capacity to hold two different deployable autonomous mobile containers. A first deployable autonomous mobile container **5805a** is considered a primary one of the containers as it is in a primary host position where container **5805a** is used to receive any items being deposited through entrance opening **155/156**. Exemplary

first deployable autonomous mobile container **5805a** (similar to exemplary container **5805** described above and shown in FIG. **58A**) has an autonomous controller **5810a** and a power charging port **5815a** (coupled to power coupling **5820** when container **5805a** is in the host primary position). In like manner, exemplary reserve deployable autonomous mobile container **5805b** (also similar to exemplary container **5805** described above and shown in FIG. **58A**) is in a reserve host position, has an autonomous controller **5810b** and a power charging port **5815b** (coupled to power coupling **5820b** when container **5805b** is in the reserve host position) but does not receive items being deposited through entrance opening **155/156** while in the reserve host position. Instead, exemplary reserve deployable autonomous mobile container **5805b** is held unoccupied in the reserve host position until the container **5805a** in the primary host position is launched from receptacle **580150** as shown in FIG. **66B**.

(812) In more detail, an embodiment may have deployable autonomous mobile container **5805a** operative to receive delivery items while disposed in the host position within the storage receptacle **58150**. The reserve deployable autonomous mobile container **5805b** is disposed in a holding or reserve host position within the storage receptacle **58150**. Furthermore, the reserve deployable autonomous mobile container **5805b** is operative, as shown in FIG. **66C**, to move into the host position (also referred to as the primary host position) within the storage receptacle **58150** after the deployable autonomous mobile container **5805a** moves to out of the receptacle **58150** to a position external to the storage receptacle **58150** in response to receiving the deploy activation signal from bridge node **58200**. Once moved into the primary host position (e.g., when bridge node **58200** transmits a shift activation signal to reserve container **5805b** and container **5805b** moves from the holding position to the primary host position in response to the shift activation signal), reserve deployable autonomous mobile container **5805b** is able to receive at least one subsequent parcel being deposited within the storage receptacle **58150**.

(813) Those skilled in the art will further appreciate that in some embodiments that utilize more than one deployable storage element in the node-based logistics receptacle **58150**, an embodiment may have the primary container **5805a** and the reserve container **5805b** used to receive items. For example, an embodiment may have entrance chute **155** being operative to shift and allow subsequently deposited items deposited after such a shift to be received in the reserve container **5805b**. Such a shift may be initiated by bridge node **58200** with a control signal applied to an actuator that may move one end of entrance chute **155** or add in addition chute structure to cause such subsequently deposited items to move through chute **155** and into reserve container **5805b** instead of primary container **5805a**. Initiating such a chute shift may, for example, be in response to when bridge node **58200** detects an overload condition relative to the receptacle **58150** or a situation approaching such an overload condition using sensor data generated by sensors on or around (e.g., external to) node-based logistics receptacle **58150**.

(814) In another example, an embodiment may dispose each of exemplary deployable autonomous mobile containers **5805a**, **5805b** in a configuration within an embodiment of node-based logistics receptacle **58150** where both containers **5805a**, **5805b** may be launched at the same time as well as at different times independent of each other. Such an embodiment may allow for a given node-based logistics receptacle to use a particular deployable autonomous mobile container for a faster and higher priority shipment service as well as use the other deployable autonomous mobile container for a different level of shipment service (e.g., lower price, conventional delivery time guarantees, and the like).

(815) Those skilled in the art will also appreciate that an exemplary deployable storage element associated (e.g., deployable autonomous mobile container **5805**) with a node-based logistics receptacle may operate once launched in a fully autonomous mode. However, some embodiments may have the deployable storage element receiving remote input so as to have a degree of potential human intervention or override capability (e.g., a level 3 conditional type of driving automation) as the deployable storage element transits outside of the node-enabled logistics receptacle **58150**

towards a logistics destination. FIG. 67 is a diagram illustrating an exemplary deployable autonomous mobile container **5805** that is deployed and receiving a remote input signal used by the deployable autonomous mobile container **5805** as part of generating propulsion and steering control signals in accordance with an embodiment of the invention. Referring now to FIG. 67, exemplary deployable autonomous mobile container **5805** is shown deployed from within node-based logistics receptacle **58150** and moving under control of autonomous controller **5810** (also referred to as autonomous controller **6105**) as well as according to a remote input signal (e.g., one of signals **6700-6715**). In other words, bridge node **58200** is operative to initiate launching and cause container **5805** to move from within receptacle **58150** in response to the deploy activation signal, while the container **5805** continues to move outside of receptacle **58150** autonomously in many embodiments, but also in a semi-autonomous mode in other embodiments where a remote input signal is sent to the autonomous controller running in container **5805**. In more detail, such a remote input signal may be received by the deployable autonomous mobile container **5805** as a wireless control signal **6705** generated by the bridge node **58200**, a wireless control signal **6700** from the backend server **100**, a wireless control signal **6715** from a mobile user device **2630** (e.g., an AR headset type of communication device) operated by a logistics asset **700a** or personnel **2615** associated with logistics asset **700a**, and wireless control signal **6710** from a transceiver **2600** operating on a delivery vehicle **2602** associated with a logistics asset **700a**. Such a remote input signal, for example, may provide a selective override related to the movement of the deployable autonomous mobile container **5805**. In even more detail, the autonomous controller on deployable autonomous mobile container **5805** may be operative, in an embodiment, to generate the propulsion and steering control signals in response to at least navigation feedback sensor data, location data, and the remote input signal received from an external device (e.g., bridge node **58200**, backend server **100**, mobile user device **2630**, transceiver **2600** on delivery vehicle) as supplemental autonomous control of the deployable mobile container.

(816) In some embodiments where an exemplary deployable autonomous mobile container has launched is operating in an autonomous manner, a predefined area may be used within which the exemplary deployable autonomous mobile container is self-driving within that predefined area but may require human intervention outside of that predefined area. FIG. 68 is a diagram illustrating an exemplary deployable autonomous mobile container **5805** (similar to that shown in FIG. 67) that is deployed and autonomously operating within a predefined area in accordance with an embodiment of the invention. Referring now to FIG. 68, exemplary deployable autonomous mobile container **5805** is shown deployed from within node-based logistics receptacle **58150** and moving under control of autonomous controller **5810** (also referred to as autonomous controller **6105**) as well as according to a remote input signal (e.g., one of signals **6700-6715**) but such that container **5805** is autonomously moving (e.g., self-driving) within predefined area **6800** (e.g., a geo-fenced area). In other words, bridge node **58200** is operative to initiate launching and cause container **5805** to move from within receptacle **58150** in response to the deploy activation signal, while the container **5805** continues to move outside of receptacle **58150** autonomously within predefined area **6800**, but also in a semi-autonomous mode in other embodiments where a remote input signal (similar to that described above) is sent to the autonomous controller running in container **5805**. As such, movement by the deployable autonomous mobile container **5805** within predefined area **6800** relative to the host position of the deployable autonomous mobile container (e.g., the location of node-based logistics receptacle **58150**) is autonomously controlled by the container's autonomous controller within the predefined area **6800** after receipt of the deploy activation signal. Further, movement by the deployable autonomous mobile container **5805** outside predefined area **6800** is semi-autonomously controlled by the container's autonomous controller within the predefined area **6800** as it also uses the remote input signal (e.g., one of signals **6700-6715**). The remote input signal used in the embodiment shown in FIG. 68, for example, may provide a selective override related to the movement of the deployable autonomous mobile container **5805** within

predetermined area **6800**. In even more detail, the autonomous controller on deployable autonomous mobile container **5805** may be operative, in an embodiment, to generate the propulsion and steering control signals in response to at least the navigation feedback sensor data and responsive to a remote input signal from an external device (e.g., bridge node **58200**, backend server **100**, mobile user device **2630**, transceiver **2600** on delivery vehicle) as supplemental autonomous control of the deployable mobile container outside of the predefined area **6800**. Such a remote input signal, while received outside of predefined area **6800**, may be used as a type of override signal.

(817) In still further embodiments involving a deployable storage element launched from within a node-based logistics receptacle, a further embodiment may use the temporary storage area **205** within an exemplary node-based logistics receptacle **105** but include a deployable autonomous mobile container that may be launched with some or all of the contents maintained in temporary storage area **205** that have been transferred into the deployable autonomous mobile container. FIG. **69** is a diagram illustrating a version of exemplary node-based logistics receptacle **58150** having a temporary storage area **205** separate from an exemplary deployable autonomous mobile container **5805** and an exemplary parcel manipulator **6900** that is capable of moving contents of temporary storage area **205** into an exemplary deployable autonomous mobile container **5805c** in accordance with an embodiment of the invention. Referring now to FIG. **69**, the illustrated version of exemplary node-based logistics receptacle **58150** is similar to that of what is shown in FIGS. **58A** and **58B**, but this receptacle **58150** has temporary storage area **205** in a location where delivery items deposited through entrance opening **155/156** are received into temporary storage area **205** (rather than directly into container **5805c**). Additionally, this version of receptacle **58150** includes parcel manipulator **6900** (e.g., a robotic arm capable of grasping and moving items, and the like). Exemplary parcel manipulator **6900** may include machine vision capabilities, is disposed with access to within area **205** and operative to move some or all of those contents of the temporary storage area **205** into the deployable autonomous mobile container **5805c** in response to a load activation signal from bridge node **58200**. More particularly, an embodiment may have bridge node **58200** in this version of node-based logistics receptacle **58150** be programmatically operative to detect the change in the state of the entrance opening **155/156** based upon the interaction sensor data, determine a current condition of what is presently maintained within the temporary storage area **205** based upon the storage sensor data, transmit the load activation signal to the parcel manipulator **6900** when the current condition of what is presently maintained within the temporary storage area **205** corresponds to at least the deployment threshold setting for the deployable autonomous mobile container **5805c**, generate the deploy activation signal after generating the load activation signal, and transmit the deploy activation signal to the deployable autonomous mobile container **5805c** to initiate movement by the deployable autonomous mobile container **5805c** from the host position within the storage receptacle **58150** to the position external to the storage receptacle **58150** in response to receiving the deploy activation signal.

(818) It should be emphasized that the sequence of operations to perform any of the methods and variations of the methods described in the embodiments herein are merely exemplary, and that a variety of sequences of operations may be followed while still being true and in accordance with the principles of the present invention.

(819) At least some portions of exemplary embodiments outlined above may be used in association with portions of other exemplary embodiments to better monitor for use of, engagement with, and deposits of packages (generally referred as delivery items) within or proximate to an enhanced connected logistics receptacle, and advantageously causes a backend server to initiate one or more responsive actions (e.g., a dispatched logistics operation relative to the reporting receptacle).

Moreover, at least some of the exemplary embodiments disclosed herein may be used independently from one another and/or in combination with one another and may have applications to devices and methods not disclosed herein.

(820) Those skilled in the art will readily appreciate that operations of such an exemplary enhanced connected logistics receptacle or system that uses such an enhanced connected logistics receptacle, as set forth herein, are not limited to drop boxes or locker units, but may be used to manage logistics related to mobile logistics receptacles that may be serviced by logistics personnel and/or autonomous logistics devices capable of interacting with the enhanced connected logistics receptacle.

(821) Those skilled in the art will appreciate that embodiments may provide one or more advantages, and not all embodiments necessarily provide all or more than one particular advantage as set forth here. Additionally, it will be apparent to those skilled in the art that various modifications and variations can be made to the structures and methodologies described herein. Thus, it should be understood that the invention is not limited to the subject matter discussed in the description. Rather, the present invention is intended to cover modifications and variations.

(822) While numerous embodiments and variations of such embodiments are described above, what follows below is a listing of an exemplary claim set focusing on one or more aspects of the different embodiments described above.

Claims

1. A centrally managed system for tuning a plurality of enhanced node-based logistics receptacles, the system comprising: a backend server maintaining a management profile related to each of the enhanced node-based logistics receptacles; a first of the enhanced node-based logistics receptacles operative to communicate with the backend server, the first of the enhanced node-based logistics receptacles comprising a first plurality of monitored receptacle components, a first wireless accessory sensor node having a first plurality of sensors that collectively monitor one or more interactions with respective ones of the first plurality of monitored receptacle components over a first recording time period, a first bridge node operative to retrieve first event information from the first wireless accessory sensor node, the first event information being related to sensor data generated by the first plurality of sensors, the first bridge node being further operative to transmit the retrieved first event information at a first upload time to the backend server; and a second of the node-based logistics receptacles operative to communicate with the backend server, the second of the enhanced node-based logistics receptacles comprising a second plurality of monitored receptacle components, a second wireless accessory sensor node having a second plurality of sensors that collectively monitor one or more interactions with respective ones of the second plurality of monitored receptacle components over a second recording time period, a second bridge node operative to retrieve second event information from the second wireless accessory sensor node, the second event information being related to sensor data generated by the second plurality of sensors, the second bridge node being further operative to transmit the retrieved second event information at a second upload time to the backend server; and wherein the backend server being programmatically configured to be operative to transmit a first setup message to the first bridge node, the first setup message configuring operation of the first bridge node related to at least the first recording time period for the first wireless accessory sensor node and the first upload time for the first bridge node to transmit the retrieved first event information to the backend server, transmit a second setup message to the second bridge node, the second setup message configuring operation of the second bridge node related to at least the second recording time period for the second wireless accessory sensor node and the second upload time for the second bridge node to transmit the retrieved second event information to the backend server, receive the retrieved first event information from the first bridge node and the retrieved second event information from the second bridge node, compare the retrieved first event information with the management profile and compare the retrieved second event information with the management profile, revise the management profile based upon the comparison of the retrieved first event information with the

management profile and the comparison of the retrieved second event information with the management profile, and transmit an adjustment message to the first bridge node, the adjustment message being based upon the revised management profile, the adjustment message initiating a first timing change to operation of the first bridge node.

2. The system of claim 1, wherein the first timing change causes the first bridge node to instruct the first wireless accessory sensor node to update the first recording time period over which the first plurality of sensors generate the sensor data related to the first event information.

3. The system of claim 1, wherein the first timing change comprising an update to a first predetermined time on when the first bridge node retrieves the first event information upon implementing the update.

4. The system of claim 1, wherein the first timing change comprising an update to the first upload time on when the first bridge node is operative to transmit the retrieved first event information to the backend server upon implementing the update.

5. The system of claim 1, where the backend server being programmatically configured to be further operative to transmit an additional adjustment message to the second bridge node, the additional adjustment message being based upon the revised management profile, the additional adjustment message initiating a second timing change to operation of the second bridge node.

6. The system of claim 5, wherein the second timing change causes the second bridge node to instruct the second wireless accessory sensor node to update the second recording time period over which the second plurality of sensors generate the sensor data related to the second event information.

7. The system of claim 5, wherein the second timing change comprising an update to a second predetermined time on when the second bridge node is operative to retrieve the second event information upon implementing the update.

8. The system of claim 5, wherein the second timing change comprising an update to the second upload time on when the second bridge node is operative to transmit the retrieved second event information to the backend server upon implementing the update.

9. The system of claim 1, wherein the management profile comprises a prior component engagement history for each of the enhanced node-based logistics receptacles.

10. The system of claim 9, wherein the prior component engagement history for each of the enhanced node-based logistics receptacles comprises at least a first prior history of interactions with the first plurality of monitored receptacle components and a second prior history of interactions with the second plurality of monitored receptacle components.

11. The system of claim 1, wherein the management profile comprises a server-tracked historic use pattern for each of the enhanced node-based logistics receptacles.

12. The system of claim 11, wherein the server-tracked historic use pattern comprises a pattern of engagement events related to each of the enhanced node-based logistics receptacles.

13. The system of claim 12, wherein the pattern of engagement events related to each of the enhanced node-based logistics receptacles comprises a pattern of delivery events to each of the enhanced node-based logistics receptacles.

14. The system of claim 12, wherein the pattern of engagement events related to each of the enhanced node-based logistics receptacles comprises a pattern of pickup events from each of the enhanced node-based logistics receptacles.

15. The system of claim 11, wherein the server-tracked historic use pattern comprises a threshold occupancy pattern profile identifying a frequency of reaching a threshold occupied level within each of the enhanced node-based logistics receptacles.

16. The system of claim 11, wherein the server-tracked historic use pattern comprises: a first threshold occupancy pattern profile identifying a first frequency of reaching a first threshold occupied level within the first of the enhanced node-based logistics receptacles; and a second threshold occupancy pattern profile identifying a second frequency of reaching a second threshold

occupied level within the second of the enhanced node-based logistics receptacles.

17. The system of claim 16, wherein the first threshold occupied level is distinct from the second threshold occupied level.

18. The system of claim 11, wherein the server-tracked historic use pattern comprises an overload pattern profile identifying a frequency of reaching an overload condition for each of the enhanced node-based logistics receptacles.

19. The system of claim 11, wherein the server-tracked historic use pattern comprises: a first overload pattern profile identifying a first frequency of reaching a first overload condition within the first of the enhanced node-based logistics receptacles; and a second overload pattern profile identifying a second frequency of reaching a second overload condition within the second of the enhanced node-based logistics receptacles.

20. The system of claim 19, wherein the first overload condition is distinct from the second overload condition.

21. The system of claim 1, wherein the management profile comprises a logistics asset profile related to logistics assets assigned to service each of the enhanced node-based logistics receptacles.

22. The system of claim 21, wherein the logistics asset profile identifies a first logistics asset assigned to service the first of the enhanced node-based logistics receptacles and a second logistics asset assigned to service the second of the enhanced node-based logistics receptacles.

23. The system of claim 21, wherein the logistics asset profile identifies a first logistics asset commonly assigned to service the first of the enhanced node-based logistics receptacles and the second of the enhanced node-based logistics receptacles.

24. The system of claim 1, wherein the backend server being further programmatically operative, after revising the management profile, to initiate a dispatched logistics operation related to at least one of the enhanced node-based logistics receptacles based upon the revised management profile.

25. The system of claim 24, wherein the dispatched logistics operation being initiated by the backend server with an alternative logistics asset than previously assigned to the at least one of the enhanced node-based logistics receptacles.

26. The system of claim 24, wherein the dispatched logistics operation being initiated by the backend server at an alternative time than previously scheduled for the at least one of the enhanced node-based logistics receptacles.

27. The system of claim 1, wherein the first plurality of monitored receptacle components comprises at least one of: a first entrance opening for receiving a delivery item; a first temporary storage area for temporarily maintaining the delivery item once received; and a first retrieval door providing selective access to the delivery item within the first temporary storage area.

28. The system of claim 27, wherein the second plurality of monitored receptacle components comprises at least one of: a second entrance opening for receiving another delivery item; a second temporary storage area for temporarily maintaining the another delivery item once received; and a second retrieval door providing selective access to the another delivery item within the second temporary storage area.

29. The system of claim 1, wherein the first plurality of monitored receptacle components comprises at least two of: a first entrance opening for receiving a delivery item; a first temporary storage area for temporarily maintaining the delivery item once received; and a first retrieval door providing selective access to the delivery item within the first temporary storage area.

30. The system of claim 29, wherein the first plurality of monitored receptacle components comprises at least two of: a second entrance opening for receiving another delivery item; a second temporary storage area for temporarily maintaining the another delivery item once received; and a second retrieval door providing selective access to the another delivery item within the second temporary storage area.

31. The system of claim 1, wherein the first plurality of monitored receptacle components comprises: a first entrance opening for receiving a delivery item; a first temporary storage area for

temporarily maintaining the delivery item once received; and a first retrieval door providing selective access to the delivery item within the first temporary storage area.

32. The system of claim 31, wherein the first plurality of monitored receptacle components comprises: a second entrance opening for receiving another delivery item; a second temporary storage area for temporarily maintaining the another delivery item once received; and a second retrieval door providing selective access to the another delivery item within the second temporary storage area.

33. The system of claim 1, wherein the first wireless accessory sensor node being operative to monitor the one or more interactions with respective ones of the first plurality of monitored receptacle components over the first recording time period by being operative to detect, within the first recording time period and using one or more of the first plurality of sensors, a change in the respective ones of the first plurality of monitored receptacle components, the detected change in the respective ones of the first plurality of monitored receptacle components corresponding to the one or more interactions with the respective ones of the first plurality of monitored receptacle components; record the sensor data generated by the first plurality of sensors, the sensor data including at least timestamped information reflecting the detected change in the respective ones of the first plurality of monitored receptacle components; and broadcast a first updated advertising signal, by the first wireless accessory sensor node, the first updated advertising signal having a first data available flag set indicating the first wireless accessory sensor node has the first event information available for upload by the first bridge node, the first event information including at least the timestamped information reflecting the detected change in the respective ones of the first plurality of monitored receptacle components.

34. The system of claim 33, wherein the second wireless accessory sensor node being operative to monitor the one or more interactions with respective ones of the second plurality of monitored receptacle components over the second recording time period by being operative to detect, within the second recording time period and using one or more of the second plurality of sensors, a change in the respective ones of the second plurality of monitored receptacle components, the detected change in the respective ones of the second plurality of monitored receptacle components corresponding to the one or more interactions with the respective ones of the second plurality of monitored receptacle components; record the sensor data generated by the second plurality of sensors, the sensor data including at least timestamped information reflecting the detected change in the respective ones of the second plurality of monitored receptacle components; and broadcast a second updated advertising signal, by the second wireless accessory sensor node, the second updated advertising signal having a second data available flag set indicating the second wireless accessory sensor node has the second event information available for upload by second first bridge node, the second event information including at least the timestamped information reflecting the detected change in the respective ones of the first plurality of monitored receptacle components.

35. The system of claim 1, wherein the backend server being programmatically configured to be operative to revise the management profile by being further operative to revise the management profile based upon (a) the comparison of the retrieved first event information with the management profile, (b) the comparison of the retrieved second event information with the management profile, and (c) a first portion of an environmental context data related to at least the first of the enhanced node-based logistics receptacles.

36. The system of claim 1, wherein the backend server being programmatically configured to be operative to revise the management profile by being further operative to revise the management profile based upon (a) the comparison of the retrieved first event information with the management profile, (b) the comparison of the retrieved second event information with the management profile, (c) a first portion of an environmental context data related to the first of the enhanced node-based logistics receptacles, and (d) a second portion of the environmental context data related to the second of the enhanced node-based logistics receptacles.

37. The system of claim 1, wherein the first setup message configuring operation of the first bridge node related to (a) the first recording time period for the first wireless accessory sensor node, (b) a first predetermined time for retrieving the first event information, and (c) the first upload time for transmitting the retrieved first event information to the backend server.

38. The system of claim 37, wherein the second setup message configuring operation of the second bridge node related to (d) the second recording time period for the second wireless accessory sensor node, (e) a second predetermined time for retrieving the second event information, and (f) the second upload time for transmitting the retrieved second event information to the backend server.

39. A centrally managed system for tuning a plurality of enhanced node-based logistics receptacles, the system comprising: a backend server maintaining a management profile related to each of the enhanced node-based logistics receptacles and environmental context data about a physical operating environment of each of the enhanced node-based logistics receptacles; a first of the enhanced node-based logistics receptacles operative to communicate with the backend server, the first of the enhanced node-based logistics receptacles comprising a first plurality of monitored receptacle components, a first wireless accessory sensor node having a first plurality of sensors that collectively monitor one or more interactions with respective ones of the first plurality of monitored receptacle components over a first recording time period, a first bridge node operative to retrieve first event information from the first wireless accessory sensor node, the first event information being related to sensor data generated by the first plurality of sensors, the first bridge node being further operative to transmit the retrieved first event information at a first upload time to the backend server; and a second of the node-based logistics receptacles operative to communicate with the backend server, the second of the enhanced node-based logistics receptacles comprising a second plurality of monitored receptacle components, a second wireless accessory sensor node having a second plurality of sensors that collectively monitor one or more interactions with respective ones of the second plurality of monitored receptacle components over a second recording time period, a second bridge node operative to retrieve second event information from the second wireless accessory sensor node, the second event information being related to sensor data generated by the second plurality of sensors, the second bridge node being further operative to transmit the retrieved second event information at a second upload time to the backend server; and wherein the backend server being programmatically configured to be operative to transmit a first setup message to the first bridge node, the first setup message configuring operation of the first bridge node related to at least (a) the first recording time period for the first wireless accessory sensor node and (b) the first upload time for transmitting the retrieved first event information to the backend server, transmit a second setup message to the second bridge node, the second setup message configuring operation of the second bridge node related to at least (c) the second recording time period for the second wireless accessory sensor node and (d) the second upload time for transmitting the retrieved second event information to the backend server, receive the retrieved first event information from the first bridge node and the retrieved second event information from the second bridge node, compare the retrieved first event information with the management profile and compare the retrieved second event information with the management profile, revise the management profile based upon (e) the comparison of the retrieved first event information with the management profile, (f) the comparison of the retrieved second event information with the management profile, (g) a first portion of the environmental context data related to the first of the enhanced node-based logistics receptacles, and (h) a second portion of the environmental context data related to the second of the enhanced node-based logistics receptacles, and transmit an adjustment message to the first bridge node, the adjustment message being based upon the revised management profile, the adjustment message initiating a first timing change to operation of at least the first bridge node.

40. The system of claim 39, wherein the environmental context data about the physical operating

environment of each of the enhanced node-based logistics receptacles comprises traffic data related to the location of each of the enhanced node-based logistics receptacles.

41. The system of claim 39, wherein the environmental context data about the physical operating environment of each of the enhanced node-based logistics receptacles comprises weather data related to the location of each of the enhanced node-based logistics receptacles.

42. The system of claim 39, wherein the environmental context data about the physical operating environment of each of the enhanced node-based logistics receptacles comprises fuel cost data related to the location of each of the enhanced node-based logistics receptacles.

43. The system of claim 39, wherein the environmental context data about the physical operating environment of each of the enhanced node-based logistics receptacles comprises crime data related to the location of each of the enhanced node-based logistics receptacles.

44. The system of claim 39, wherein the environmental context data about the physical operating environment of each of the enhanced node-based logistics receptacles comprises logistics asset staffing data related to the location of each of the enhanced node-based logistics receptacles.

45. The system of claim 39, wherein the environmental context data about the physical operating environment of each of the enhanced node-based logistics receptacles further comprises information about an anticipated operating environment for at least one of the enhanced node-based logistics receptacles, wherein the at least one of the enhanced node-based logistics receptacles anticipated to be moved to a second location corresponding to the anticipated operating environment for the at least one of the enhanced node-based logistics receptacles.

46. The system of claim 39, wherein the first timing change comprising an update to the first upload time on when the first bridge node is operative to transmit the retrieved first event information to the backend server upon implementing the update.

47. The system of claim 39, where the backend server being programmatically configured to be further operative to transmit an additional adjustment message to the second bridge node, the additional adjustment message being based upon the revised management profile, the additional adjustment message initiating a second timing change to operation of the second bridge node.

48. The system of claim 47, wherein the second timing change comprising an update to the second upload time on when the second bridge node is operative to transmit the retrieved second event information to the backend server upon implementing the update.

49. The system of claim 39, wherein the management profile comprises a prior component engagement history for each of the enhanced node-based logistics receptacles.

50. The system of claim 49, wherein the prior component engagement history for each of the enhanced node-based logistics receptacles comprises at least a first prior history of interactions with the first plurality of monitored receptacle components and a second prior history of interactions with the second plurality of monitored receptacle components.

51. The system of claim 39, wherein the management profile comprises a server-tracked historic use pattern for each of the enhanced node-based logistics receptacles.

52. The system of claim 51, wherein the server-tracked historic use pattern comprises a pattern of engagement events related to each of the enhanced node-based logistics receptacles.

53. The system of claim 52, wherein the pattern of engagement events related to each of the enhanced node-based logistics receptacles comprises a pattern of delivery events to each of the enhanced node-based logistics receptacles.

54. The system of claim 52, wherein the pattern of engagement events related to each of the enhanced node-based logistics receptacles comprises a pattern of pickup events from each of the enhanced node-based logistics receptacles.

55. The system of claim 51, wherein the server-tracked historic use pattern comprises a threshold occupancy pattern profile identifying a frequency of reaching a threshold occupied level within each of the enhanced node-based logistics receptacles.

56. The system of claim 51, wherein the server-tracked historic use pattern comprises: a first

threshold occupancy pattern profile identifying a first frequency of reaching a first threshold occupied level within the first of the enhanced node-based logistics receptacles; and a second threshold occupancy pattern profile identifying a second frequency of reaching a second threshold occupied level within the second of the enhanced node-based logistics receptacles.

57. The system of claim 56, wherein the first threshold occupied level is distinct from the second threshold occupied level.

58. The system of claim 51, wherein the server-tracked historic use pattern comprises an overload pattern profile identifying a frequency of reaching an overload condition for each of the enhanced node-based logistics receptacles.

59. The system of claim 51, wherein the server-tracked historic use pattern comprises: a first overload pattern profile identifying a first frequency of reaching a first overload condition within the first of the enhanced node-based logistics receptacles; and a second overload pattern profile identifying a second frequency of reaching a second overload condition within the second of the enhanced node-based logistics receptacles.

60. The system of claim 59, wherein the first overload condition is distinct from the second overload condition.

61. The system of claim 39, wherein the management profile comprises a logistics asset profile related to logistics assets assigned to service each of the enhanced node-based logistics receptacles.

62. The system of claim 61, wherein the logistics asset profile identifies a first logistics asset assigned to service the first of the enhanced node-based logistics receptacles and a second logistics asset assigned to service the second of the enhanced node-based logistics receptacles.

63. The system of claim 61, wherein the logistics asset profile identifies a first logistics asset commonly assigned to service the first of the enhanced node-based logistics receptacles and the second of the enhanced node-based logistics receptacles.

64. The system of claim 39, wherein the backend server being further programmatically operative, after revising the management profile, to initiate a dispatched logistics operation related to at least one of the enhanced node-based logistics receptacles based upon the revised management profile.

65. The system of claim 64, wherein the dispatched logistics operation being initiated by the backend server with an alternative logistics asset than previously assigned to the at least one of the enhanced node-based logistics receptacles.

66. The system of claim 64, wherein the dispatched logistics operation being initiated by the backend server at an alternative time than previously scheduled for the at least one of the enhanced node-based logistics receptacles.

67. The system of claim 39, wherein the first plurality of monitored receptacle components comprises at least one of: a first entrance opening for receiving a delivery item; a first temporary storage area for temporarily maintaining the delivery item once received; and a first retrieval door providing selective access to the delivery item within the first temporary storage area.

68. The system of claim 67, wherein the second plurality of monitored receptacle components comprises at least one of: a second entrance opening for receiving another delivery item; a second temporary storage area for temporarily maintaining the another delivery item once received; and a second retrieval door providing selective access to the another delivery item within the second temporary storage area.

69. The system of claim 39, wherein the first plurality of monitored receptacle components comprises at least two of: a first entrance opening for receiving a delivery item; a first temporary storage area for temporarily maintaining the delivery item once received; and a first retrieval door providing selective access to the delivery item within the first temporary storage area.

70. The system of claim 69, wherein the first plurality of monitored receptacle components comprises at least two of: a second entrance opening for receiving another delivery item; a second temporary storage area for temporarily maintaining the another delivery item once received; and a second retrieval door providing selective access to the another delivery item within the second

temporary storage area.

71. The system of claim 39, wherein the first plurality of monitored receptacle components comprises: a first entrance opening for receiving a delivery item; a first temporary storage area for temporarily maintaining the delivery item once received; and a first retrieval door providing selective access to the delivery item within the first temporary storage area.

72. The system of claim 71, wherein the first plurality of monitored receptacle components comprises: a second entrance opening for receiving another delivery item; a second temporary storage area for temporarily maintaining the another delivery item once received; and a second retrieval door providing selective access to the another delivery item within the second temporary storage area.

73. The system of claim 39, wherein the first wireless accessory sensor node being operative to monitor the one or more interactions with respective ones of the first plurality of monitored receptacle components over the first recording time period by being operative to detect, within the first recording time period and using one or more of the first plurality of sensors, a change in the respective ones of the first plurality of monitored receptacle components, the detected change in the respective ones of the first plurality of monitored receptacle components corresponding to the one or more interactions with the respective ones of the first plurality of monitored receptacle components; record the sensor data generated by the first plurality of sensors, the sensor data including at least timestamped information reflecting the detected change in the respective ones of the first plurality of monitored receptacle components; and broadcast a first updated advertising signal, by the first wireless accessory sensor node, the first updated advertising signal having a first data available flag set indicating the first wireless accessory sensor node has the first event information available for upload by the first bridge node, the first event information including at least the timestamped information reflecting the detected change in the respective ones of the first plurality of monitored receptacle components.

74. The system of claim 73, wherein the second wireless accessory sensor node being operative to monitor the one or more interactions with respective ones of the second plurality of monitored receptacle components over the second recording time period by being operative to detect, within the second recording time period and using one or more of the second plurality of sensors, a change in the respective ones of the second plurality of monitored receptacle components, the detected change in the respective ones of the second plurality of monitored receptacle components corresponding to the one or more interactions with the respective ones of the second plurality of monitored receptacle components; record the sensor data generated by the second plurality of sensors, the sensor data including at least timestamped information reflecting the detected change in the respective ones of the second plurality of monitored receptacle components; and broadcast a second updated advertising signal, by the second wireless accessory sensor node, the second updated advertising signal having a second data available flag set indicating the second wireless accessory sensor node has the second event information available for upload by second first bridge node, the second event information including at least the timestamped information reflecting the detected change in the respective ones of the first plurality of monitored receptacle components.

75. The system of claim 39, wherein the first setup message configuring operation of the first bridge node related to (a) the first recording time period for the first wireless accessory sensor node, (b) a first predetermined time for retrieving the first event information, and (c) the first upload time for transmitting the retrieved first event information to the backend server.

76. The system of claim 75, wherein the second setup message configuring operation of the second bridge node related to (d) the second recording time period for the second wireless accessory sensor node, (e) a second predetermined time for retrieving the second event information, and (f) the second upload time for transmitting the retrieved second event information to the backend server.
