

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12407976
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Ren; Zhang et al.

Coaxial earphone core

Abstract

The present disclosure discloses a coaxial earphone core including a magnet system, which includes a first yoke, a first magnet, a second magnet surrounding the first magnet to form a first magnetic gap, a second yoke fixed to the first magnet, and an annular third magnet fixed to the second yoke; the second yoke includes an extending wall bending and extending into the third magnet; the extending wall is spaced apart from the third magnet to form a second magnetic gap; the first coil and the second coil are inserted into the first magnetic gap and second magnetic gap, respectively; the first sound unit surrounds the second sound unit, the second diaphragm is located on one side of the first diaphragm facing the magnet system. The coaxial earphone core has better sound quality.

Inventors:	Ren; Zhang (Changzhou, CN), Zhong; Zhiwei (Changzhou, CN)
Applicant:	AAC Microtech (Changzhou) Co., Ltd. (Jiangsu, CN)
Family ID:	91279498
Assignee:	AAC Microtech (Changzhou) Co., Ltd. (Changzhou, CN)
Appl. No.:	18/324183
Filed:	May 26, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240187782 A1	Jun. 06, 2024

Related U.S. Application Data

continuation parent-doc WO PCT/CN2022/136717 20221206 PENDING child-doc US 18324183

Publication Classification

Int. Cl.: **H04R1/24** (20060101); **H04R7/12** (20060101); **H04R7/18** (20060101); **H04R9/02** (20060101); **H04R9/04** (20060101); **H04R9/06** (20060101)

U.S. Cl.:

CPC **H04R1/24** (20130101); **H04R7/127** (20130101); **H04R7/18** (20130101); **H04R9/025** (20130101); **H04R9/045** (20130101); **H04R9/063** (20130101); H04R2400/11 (20130101)

Field of Classification Search

CPC: H04R (25/656); H04R (25/554); H02J (50/10)

References Cited

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
217721454	12/2021	CN	H04R 9/025

Primary Examiner: Joshi; Sunita

Attorney, Agent or Firm: Wiersch Law Group

Background/Summary

FIELD OF THE PRESENT DISCLOSURE

(1) The present disclosure relates to electric-sound conversion technologies, especially relates to a coaxial earphone core.

DESCRIPTION OF RELATED ART

(2) With the development of the mobile communication technologies, consumers are increasingly using mobile communication devices with voice function, and earphones have become one of the essential communication devices in people's daily life and work. Delicate appearance, wearing convenience, excellent sound quality and stereo perception are necessary characteristics for the earphones. Therefore, further improving the performance and internal structure of earphones has become a topic worth studying at present.

(3) In related art, normally one magnet system provided in the earphone core is configured to provide sound effect in mid-frequency and low frequency. To provide sound effect in high frequency, two coaxial magnet systems and vibration systems is necessary. Stacking the two magnet systems may increase the axial height of the earphone, thus reducing the manufacture convenience and applicability. Besides, the diaphragm of one vibration system surrounds the diaphragm of another vibration system, reducing the effective vibration area of the outer diaphragm and weakening the sound quality of the earphone core.

(4) Therefore, it is necessary to provide an improved earphone core to overcome the problems mentioned above.

SUMMARY OF THE INVENTION

- (5) One object of the present disclosure is to provide a coaxial earphone core having better sound quality.
- (6) A coaxial earphone core includes a first frame; a second frame; a magnet system, including: a first yoke fixed to the first frame; a first magnet fixed to the first yoke; a second magnet surrounding the first magnet to form a first magnetic gap; a second yoke fixed on one side of the first magnet away from the first yoke; an annular third magnet fixed to the second yoke; a first sound unit, including: a first diaphragm peripherally mounted on the first frame; and a first coil fixed to the first diaphragm and inserted into the first magnetic gap; a second sound unit coaxially surrounded by the first sound unit, including: a second diaphragm mounted on the second frame; and a second coil fixed to the second diaphragm; the second frame is fixed on one side of the third magnet away from the second yoke; the second yoke includes an annular extending wall bending and extending into the third magnet; the extending wall is spaced apart from the third magnet to form a second magnetic gap; the second coil is inserted into the second magnetic gap; the second diaphragm is located on one side of the first diaphragm facing the magnet system along a vibration direction.
- (7) As an improvement, the first diaphragm includes an annular inner diaphragm located in a central position, a first dome surrounding the first inner diaphragm, a first skeleton surrounding the first dome, and an first outer diaphragm surrounding the first skeleton; the second diaphragm is located on one side of the first inner diaphragm facing the magnet system along the vibration direction.
- (8) As an improvement, the coaxial earphone core further includes a front cover is arranged above the second diaphragm; an inner edge of the first inner diaphragm is fixed to the front cover.
- (9) As an improvement, a sound hole opposite the second diaphragm is provided on the front cover penetrating thereon along the vibration direction.
- (10) As an improvement, the front cover includes an outer periphery located outside the second frame, an inner periphery enclosing the sound hole, and a central portion connecting the inner periphery and the outer periphery; the outer periphery is mounted on a side of the third magnet away from the second yoke.
- (11) As an improvement, the inner edge of the first inner diaphragm is fixed to the central portion.
- (12) As an improvement, the first coil is fixed to a side of the first skeleton facing the first magnetic gap.
- (13) As an improvement, the first dome includes a first connection portion connecting with the outer edge of the first inner diaphragm, a second connection portion connecting with the first skeleton, and an extending portion connecting the first connection portion with the second connection portion; the extending portion extends from the second connection portion and along a direction towards a first connection portion and away from the second diaphragm.
- (14) As an improvement, the inner periphery of the front cover bends from the central portion and extends along a direction away from the second diaphragm into the first inner diaphragm; the inner edge of the first inner diaphragm surrounds the inner periphery.
- (15) As an improvement, the coaxial earphone core further includes a support member fixed to the magnet system; the first yoke comprises a first through hole penetrating thereon along the vibration direction; the support member includes a first support portion received in the first through hole and fixed to the first yoke, a second support portion extending from the first support portion and towards the second diaphragm, and a third support portion extending from the second support portion and towards the second diaphragm; the second support portion extends into the first magnet; the third support portion extends into the extending wall of the second yoke.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The present disclosure will hereinafter be described in detail with reference to an exemplary embodiment. To make the technical problems to be solved, technical solutions and beneficial effects of present disclosure more apparent, the present disclosure is described in further detail together with the figures and the embodiment. It should be understood the specific embodiment described hereby is only to explain this disclosure, not intended to limit this disclosure.

(2) FIG. 1 is an isometric view of a coaxial earphone core in accordance with an exemplary embodiment of the present disclosure.

(3) FIG. 2 is an exploded view of the coaxial earphone core in FIG. 1.

(4) FIG. 3 is a cross-sectional view of the coaxial earphone core taken along line A-A in FIG. 1.

(5) FIG. 4 is an enlarged view of the part B in FIG. 3.

(6) FIG. 5 is an enlarged view of the part C in FIG. 3

DETAILED DESCRIPTION OF THE EXEMPLARY EMBODIMENT

(7) The present disclosure will hereinafter be described in detail with reference to an exemplary embodiment. To make the technical problems to be solved, technical solutions and beneficial effects of the present disclosure more apparent, the present disclosure is described in further detail together with the figure and the embodiment. It should be understood the specific embodiment described hereby is only to explain the disclosure, not intended to limit the disclosure.

(8) Please refer to FIGS. 1-5, a coaxial earphone core **100** provided by an exemplary embodiment of the present disclosure includes a first frame **1**, a second frame **2**, a magnet system **3**, a first sound unit **4**, and a second sound unit **5** coaxially surrounded by the first sound unit **4**. The first frame **1** surrounds the second frame **2**. The first sound unit **4** surrounds the second sound unit **5**.

(9) The first sound unit **4** includes a first diaphragm **41** peripherally mounted on the first frame **1**, and a first coil **42** fixed to the first diaphragm **41**. The first coil **42** is configured to drive the first diaphragm **41** to generate sound.

(10) The second sound unit **5** includes a second diaphragm **51** mounted on the second frame **2**, and a second coil **52** fixed to the second diaphragm **51**. The second coil **52** drives the second diaphragm **51** to generate sound. In one embodiment, the first sound unit **4** is configured to generate sound in low frequency and mid-frequency; the second sound unit **5** is configured to generate sound in high frequency. Therefore, the coaxial earphone core **100** can provide sound effect in full frequency band.

(11) Specifically, the magnet system **3** includes a first yoke **31** fixed to the first frame **1**, a first magnet **32** fixed to the first yoke **31**, a second magnet **34** surrounding the first magnet **32** to form a first magnetic gap **33**, a second yoke **35** fixed on one side of the first magnet **32** away from the first yoke **31**, and an annular third magnet **36** fixed to the second yoke **35**. The first coil **42** is inserted into the first magnetic gap **33**. The second frame **2** is fixed on one side of the third magnet **36** away from the second yoke **35**. In addition, the second yoke **35** includes an annular extending wall **351** bending and extending into the third magnet **36**; the extending wall **351** is spaced apart from the third magnet **36** to form a second magnetic gap **37**; the second coil **52** is inserted into the second magnetic gap **37**; the second diaphragm **51** is located on one side of the first diaphragm **41** facing the magnet system **3** along a vibration direction.

(12) Specifically, the first diaphragm **41** includes an annular inner diaphragm **411** located in a central position, a first dome **412** surrounding the first inner diaphragm **411**, a first skeleton **413** surrounding the first dome **412**, and an first outer diaphragm **414** surrounding the first skeleton **413**; the second diaphragm **51** is located on one side of the first inner diaphragm **411** facing the magnet system **3** along the vibration direction. The first coil **42** is fixed to a side of the first skeleton **413** facing the first magnetic gap **33**. Furthermore, the first dome **412** includes a first connection portion **4121** connecting with the outer edge of the first inner diaphragm **411**, a second connection portion **4122** connecting with the first skeleton **413**, and an extending portion **4123**

connecting the first connection portion **4121** with the second connection portion **4122**; the extending portion **4123** extends from the second connection portion **4122** and along a direction towards a first connection portion **4121** and away from the second diaphragm **51**. Therefore, the second sound unit **5** is arranged below the first diaphragm **41** of the first sound unit **4**, fully utilizing the space below the first diaphragm **41**, improving the space utilization, effectively reducing the axial height of the coaxial earphone core **100** and improving the applicability of the coaxial earphone core **100**. Besides, the second diaphragm **51** is located below the first diaphragm **41**, ensuring enough vibration area of the first diaphragm **41** and effectively improving the sound quality of the coaxial earphone core.

(13) Furthermore, the coaxial earphone core **100** includes a front cover **6** arranged above the second diaphragm **51**; an inner edge of the first inner diaphragm **411** is fixed to the front cover **6**. It can be understood that a sound hole **61** opposite the second diaphragm **51** is provided on the front cover **6** penetrating thereon along the vibration direction. The sound generated by the second diaphragm **51** is transmitted to outside through the sound hole **61**.

(14) Specifically, the front cover **6** includes an outer periphery **62** located outside the second frame **2**, an inner periphery **63** enclosing the sound hole **61**, and a central portion **64** connecting the inner periphery **63** and the outer periphery **62**; the outer periphery **62** is mounted on a side of the third magnet **36** away from the second yoke **35**. The inner edge of the first inner diaphragm **422** is fixed to the central portion **64**. Furthermore, the inner periphery **63** of the front cover **6** bends from the central portion **64** and extends along a direction away from the second diaphragm **51** into the first inner diaphragm **411**; the inner edge of the first inner diaphragm **411** surrounds the inner periphery **63**.

(15) The coaxial earphone core **100** further includes a support member **7** fixed to the magnet system **3**; the first yoke **31** includes a first through hole **311** penetrating thereon along the vibration direction; the support member **7** includes a first support portion **71** received in the first through hole **311** and fixed to the first yoke **31**, a second support portion **72** extending from the first support portion **71** and towards the second diaphragm **51**, and a third support portion **73** extending from the second support portion **72** and towards the second diaphragm **51**; the second support portion **72** extends into the first magnet **32**; the third support portion **73** extends into the extending wall **351** of the second yoke **35**. It can be understood that the third support portion **73** is opposite to and spaced apart from the second diaphragm **51** along the vibration direction.

(16) Compared with the related art, the magnet system of the coaxial earphone core in the application includes a first yoke, a first magnet, a second magnet surrounding the first magnet to form a first magnetic gap, a second yoke fixed to the first magnet, and an annular third magnet fixed to the second yoke; the second yoke includes an extending wall bending and extending into the third magnet; the extending wall is spaced apart from the third magnet to form a second magnetic gap; the first coil and the second coil are inserted into the first magnetic gap and second magnetic gap, respectively; the first sound unit surrounds the second sound unit, the second diaphragm is located on one side of the first diaphragm facing the magnet system. The coaxial earphone core fully utilizes the space below the first diaphragm, thus improving the space utilization, effectively reducing the axial height of the coaxial earphone core, and improving its applicability. Besides, the first diaphragm has enough vibration area, effectively improving the sound quality of the coaxial earphone core.

(17) It is to be understood, however, that even though numerous characteristics and advantages of the present exemplary embodiments have been set forth in the foregoing description, together with details of the structures and functions of the embodiments, the disclosure is illustrative only, and changes may be made in detail, especially in matters of shape, size, and arrangement of parts within the principles of the invention to the full extent indicated by the broad general meaning of the terms where the appended claims are expressed.

Claims

1. A coaxial earphone core comprising: a first frame; a second frame; a magnet system, comprising: a first yoke fixed to the first frame; a first magnet fixed to the first yoke; a second magnet surrounding the first magnet to form a first magnetic gap; a second yoke fixed on one side of the first magnet away from the first yoke; an annular third magnet fixed to the second yoke; a first sound unit, comprising: a first diaphragm peripherally mounted on the first frame; and a first coil fixed to the first diaphragm and inserted into the first magnetic gap; a second sound unit coaxially surrounded by the first sound unit, comprising: a second diaphragm mounted on the second frame; and a second coil fixed to the second diaphragm; wherein the second frame is fixed on one side of the third magnet away from the second yoke; the second yoke comprises an annular extending wall bending and extending into the third magnet; the extending wall is spaced apart from the third magnet to form a second magnetic gap; the second coil is inserted into the second magnetic gap; the second diaphragm is located on one side of the first diaphragm facing the magnet system along a vibration direction; the first diaphragm comprises an annular inner diaphragm located in a central position, a first dome surrounding the first inner diaphragm, a first skeleton surrounding the first dome, and an first outer diaphragm surrounding the first skeleton; the second diaphragm is located on one side of the first inner diaphragm facing the magnet system along the vibration direction.
 2. The coaxial earphone core as described in claim 1, further comprising a front cover is arranged above the second diaphragm; an inner edge of the first inner diaphragm is fixed to the front cover.
 3. The coaxial earphone core as described in claim 2, wherein a sound hole opposite the second diaphragm is provided on the front cover penetrating thereon along the vibration direction.
 4. The coaxial earphone core as described in claim 3, wherein the front cover comprises an outer periphery located outside the second frame, an inner periphery enclosing the sound hole, and a central portion connecting the inner periphery and the outer periphery; the outer periphery is mounted on a side of the third magnet away from the second yoke.
 5. The coaxial earphone core as described in claim 4, wherein the inner edge of the first inner diaphragm is fixed to the central portion.
 6. The coaxial earphone core as described in claim 5, wherein the first coil is fixed to a side of the first skeleton facing the first magnetic gap.
 7. The coaxial earphone core as described in claim 1, wherein the first dome comprises a first connection portion connecting with the outer edge of the first inner diaphragm, a second connection portion connecting with the first skeleton, and an extending portion connecting the first connection portion with the second connection portion; the extending portion extends from the second connection portion and along a direction towards a first connection portion and away from the second diaphragm.
 8. The coaxial earphone core as described in claim 4, wherein the inner periphery of the front cover bends from the central portion and extends along a direction away from the second diaphragm into the first inner diaphragm; the inner edge of the first inner diaphragm surrounds the inner periphery.
 9. The coaxial earphone core as described in claim 1, wherein further comprising a support member fixed to the magnet system; the first yoke comprises a first through hole penetrating thereon along the vibration direction; the support member comprises a first support portion received in the first through hole and fixed to the first yoke, a second support portion extending from the first support portion and towards the second diaphragm, and a third support portion extending from the second support portion and towards the second diaphragm; the second support portion extends into the first magnet; the third support portion extends into the extending wall of the second yoke.
-