

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12407978
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Yang; Haijuan et al.

Speaker box

Abstract

The present disclosure discloses a speaker box including a metal cover fixed between the frame and the magnetic circuit system; the metal cover includes a bottom wall set at a bottom of the speaker unit and a side wall extending from the bottom wall and set at a side of the speaker unit; the vibration system, the frame, the metal cover and the magnetic circuit system enclosing a internal space of the speaker unit; the bottom wall and/or the side wall are provided with leak structures formed by stamping communicating the internal space and the rear cavity, the leak structure comprising a bar-shaped through-hole and a bar-shaped bulge corresponding to the bar-shaped through-hole. The present disclosure provides a speaker box can be flexibly applied to a variety of complex shapes of the housing and can enhance the filling amount of sound-absorbing powder.

Inventors:	Yang; Haijuan (Changzhou, CN), Wu; Shuwen (Changzhou, CN)
Applicant:	AAC Microtech (Changzhou) Co., Ltd. (Jiangsu, CN)
Family ID:	91191354
Assignee:	AAC Microtech (Changzhou) Co., Ltd. (Changzhou, CN)
Appl. No.:	18/325077
Filed:	May 29, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240179455 A1	May. 30, 2024

Foreign Application Priority Data

CN	202223196602.8	Nov. 30, 2022
----	----------------	---------------

Related U.S. Application Data

Publication Classification

Int. Cl.: **H04R1/28** (20060101); **H04R1/02** (20060101); **H04R3/00** (20060101); **H04R7/04** (20060101); **H04R9/02** (20060101); **H04R9/04** (20060101); **H04R9/06** (20060101)

U.S. Cl.:

CPC **H04R1/288** (20130101); **H04R1/025** (20130101); **H04R3/00** (20130101); **H04R7/04** (20130101); **H04R9/025** (20130101); **H04R9/045** (20130101); **H04R9/06** (20130101); **H04R2400/11** (20130101)

Field of Classification Search

CPC: H04R (1/288); H04R (1/025); H04R (3/00); H04R (7/04); H04R (9/025); H04R (9/045); H04R (9/06); H04R (2400/11); H04R (1/023); H04R (2201/029); B29C (45/14311); B29C (45/14); C25D (11/24)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2009/0190783	12/2008	Yang	381/337	H04R 1/28
2018/0132035	12/2017	Cao	N/A	H04R 1/2803
2020/0053470	12/2019	Gu	N/A	H04R 1/2811
2020/0162812	12/2019	Zheng	N/A	H04R 7/16

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
111698585	12/2019	CN	N/A
111970589	12/2019	CN	H04R 1/02
112073851	12/2019	CN	H04R 1/02
4064664	12/2021	EP	H04M 1/03
WO-2021138952	12/2020	WO	N/A

Primary Examiner: Edwards; Carolyn R

Assistant Examiner: Ganmavo; Kuassi A

Attorney, Agent or Firm: Wiersch Law Group

Background/Summary

FIELD OF THE PRESENT DISCLOSURE

(1) The present disclosure relates to electro-acoustic transducers, especially relates to a speaker box.

DESCRIPTION OF RELATED ART

(2) In the related arts, the speaker box includes a housing, a speaker unit housed in the housing and a breathable isolation parts with three-dimensional structure shape, the breathable isolation member and the housing enclosed to form a shelter space filled with sound-absorbing powder.

(3) However, when the shape of the housing is complicated, the breathable isolation member with three-dimensional structure shape needs to be adapted to the shape of the housing, thus causing the three-dimensional structure shape of the breathable isolation member to be complicated and difficult to shape. In addition, the breathable isolation member is glued to the housing, and in order to ensure the reliability of the gluing, the gluing flange of the breathable isolation member needs to be reserved a certain width, which causes space waste and is not conducive to improving the filling amount of sound-absorbing powder.

(4) Therefore, it is necessary to provide an improved speaker box to overcome the problems mentioned above.

SUMMARY OF THE INVENTION

(5) The present disclosure provides a speaker box can be flexibly applied to various complex shapes of housing and can enhance the filling amount of sound-absorbing powder.

(6) The speaker box comprising: a housing and a speaker unit housed in the housing, the speaker unit and the housing form the rear cavity of the speaker box, the rear cavity is filled with sound-absorbing powder; the speaker unit comprising a frame, a vibration system and a magnetic circuit system respectively fixed to the frame, and a metal cover fixed between the frame and the magnetic circuit system; the metal cover comprises a bottom wall set at a bottom of the speaker unit and a side wall extending from the bottom wall and set at a side of the speaker unit; the vibration system, the frame, the metal cover and the magnetic circuit system enclosing a internal space of the speaker unit; the bottom wall and/or the side wall are provided with leak structures formed by stamping communicating the internal space and the rear cavity, the leak structure comprising a bar-shaped through-hole and a bar-shaped bulge corresponding to the bar-shaped through-hole.

(7) Further, the bar-shaped bulge extends towards the internal space.

(8) Further, the adjacent leak structures formed on the bottom wall are arranged at equal intervals in parallel.

(9) Further, the bar-shaped bulge of the leak structure formed on the bottom wall abuts against the magnetic circuit system.

(10) Further, the adjacent leak structures formed on the side wall are arranged at equal intervals in parallel.

(11) Further, the housing includes a metal upper housing and a metal lower housing connected with the metal upper housing cover, the metal upper housing is provided with an outlet hole, the speaker unit is fixed to the metal upper housing and communicates with the outlet hole, the metal upper housing, the metal lower housing and the speaker unit enclose the rear cavity.

(12) Further, the vibration system includes a diaphragm, a flexible circuit board spaced from the diaphragm, a bracket connecting the diaphragm and the flexible circuit board, and a coil fixed to the bracket to drive the diaphragm vibration and sound, the coil electrically connected to the flexible circuit board, the flexible circuit board fixed to the frame and electrically connected to an external power supply via an external circuit board.

(13) Further, the magnetic circuit system includes a lower clamp plate, a main magnet fixed to the lower clamp plate, a secondary magnet fixed to the lower clamp plate and spaced from the main magnet, a main pole core fixed to the main magnet, and a ring-shaped secondary pole core fixed to the secondary magnet, the frame being a metal frame and fixed to the secondary pole core.

(14) Compared to related arts, the speaker box of the present disclosure isolate the sound-absorbing powder into the internal space of the speaker unit by the metal cover of the speaker unit, so that the entire rear cavity enclosed by the speaker unit and the housing can be filled with sound-absorbing powder, which enhances the filling amount of the sound-absorbing powder, and various complex shapes of the housing can be applied flexibly; In addition, the metal cover is with high tolerance

accuracy and high strength, stamping formed leak structures including bar-shaped through-hole and bar-shaped bulge corresponding to the bar-shaped through-hole further reduces the risk of sound absorbing powder entering the internal space of the speaker unit while ensuring the leakage area.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The present disclosure will hereinafter be described in detail with reference to an exemplary embodiment. To make the technical problems to be solved, technical solutions and beneficial effects of present disclosure more apparent, the present disclosure is described in further detail together with the figures and the embodiment. It should be understood the specific embodiment described hereby is only to explain this disclosure, not intended to limit this disclosure.

(2) FIG. 1 is a structure schematic of a speaker box of the present disclosure.

(3) FIG. 2 is an exploded view of the speaker box of the present disclosure.

(4) FIG. 3 is a cross-sectional view of the speaker box taken along line A-A in FIG. 1.

(5) FIG. 4 is a structure schematic of a metal cover of the present disclosure.

DETAILED DESCRIPTION OF THE EXEMPLARY EMBODIMENT

(6) The present disclosure will hereinafter be described in detail with reference to an exemplary embodiment. To make the technical problems to be solved, technical solutions and beneficial effects of the present disclosure more apparent, the present disclosure is described in further detail together with the figure and the embodiment. It should be understood the specific embodiment described hereby is only to explain the disclosure, not intended to limit the disclosure.

(7) Please refer to FIGS. 1-4 together, a speaker box **100** comprising: a housing **1** and a speaker unit **2** housed in the housing **1**, the speaker unit **2** and the housing **1** form the rear cavity **101** of the speaker box **2**, the rear cavity **101** is filled with sound-absorbing powder.

(8) The speaker unit **2** comprises a frame **21**, a vibration system **22** and a magnetic circuit system **23** respectively fixed to the frame **21**, and a metal cover **24** fixed between the frame **21** and the magnetic circuit system **23**. The metal cover **24** comprises a bottom wall **241** set at a bottom of the speaker unit **2** and side walls **242** extending from the bottom wall **241** and set at a side of the speaker unit **2**. The vibration system **22**, the frame **21**, the metal cover **24** and the magnetic circuit system **23** enclosing a internal space **201** of the speaker unit **2**. The bottom wall **241** and/or the side walls **242** are provided with leak structures **240** formed by stamping communicating the internal space **201** and the rear cavity **101**, the leak structure **240** comprising bar-shaped through-holes **2401** and bar-shaped bulges **2402** corresponding to the bar-shaped through-hole **2401**.

(9) Preferably, the bar-shaped bulges **2402** extend towards the internal space **201**.

(10) As a preference, the adjacent leak structures **240** formed on the bottom wall **241** are arranged at equal intervals in parallel.

(11) As a preference, the bar-shaped bulges **2402** of the leak structure **240** formed on the bottom wall **241** abut against the magnetic circuit system **23**, it allows for easy installation and positioning of the metal housing **24**.

(12) As a preference, the adjacent leak structures **240** formed on the side wall **242** are arranged at equal intervals in parallel.

(13) As a preference, the housing **1** includes a metal upper housing **11** and a metal lower housing **12** connected with the metal upper housing cover **11**, the metal upper housing **11** is provided with an outlet hole **111**, the speaker unit **2** is fixed to the metal upper housing **11** and communicates with the outlet hole **111**, the metal upper housing **11**, the metal lower housing **12** and the speaker unit **2** enclose the rear cavity **101**. The metal lower housing **12** is provided with a powder filling hole **121** communicating with the rear cavity **101** and a sealing piece **122** sealing the powder filling hole **121**.

(14) As a preference, the vibration system 22 includes a diaphragm 221, a flexible circuit board 222 spaced from the diaphragm 221, a bracket 223 connecting the diaphragm 221 and the flexible circuit board 222, and a coil 224 fixed to the bracket 223 to drive the diaphragm 221 vibration and sound, the coil 224 electrically connected to the flexible circuit board 222, the flexible circuit board 222 fixed to the frame 21 and electrically connected to an external power supply via an external circuit board 3.

(15) As a preference, the magnetic circuit system 23 includes a lower clamp plate 231, a main magnet 232 fixed to the lower clamp plate 231, a secondary magnet 233 fixed to the lower clamp plate 231 and spaced from the main magnet 232, a main pole core 234 fixed to the main magnet 232, and a ring-shaped secondary pole core 235 fixed to the secondary magnet 233, the frame 21 being a metal frame and fixed to the secondary pole core 235.

(16) Compared with related technology, the speaker box of the present disclosure isolate the sound-absorbing powder into the internal space of the speaker unit by the metal cover of the speaker unit, so that the entire rear cavity enclosed by the speaker unit and the housing can be filled with sound-absorbing powder, which enhances the filling amount of the sound-absorbing powder, and various complex shapes of the housing can be applied flexibly; In addition, the metal cover is with high tolerance accuracy and high strength, stamping formed leak structures including bar-shaped through-hole and bar-shaped bulge corresponding to the bar-shaped through-hole further reduces the risk of sound absorbing powder entering the internal space of the speaker unit while ensuring the leakage area.

(17) It is to be understood, however, that even though numerous characteristics and advantages of the present exemplary embodiments have been set forth in the foregoing description, together with details of the structures and functions of the embodiments, the disclosure is illustrative only, and changes may be made in detail, especially in matters of shape, size, and arrangement of parts within the principles of the invention to the full extent indicated by the broad general meaning of the terms where the appended claims are expressed.

Claims

1. A speaker box comprising: a housing and a speaker unit housed in the housing, the speaker unit and the housing form the rear cavity of the speaker box, the rear cavity is filled with sound-absorbing powder; wherein, the speaker unit comprises a frame, a vibration system and a magnetic circuit system respectively fixed to the frame, and a metal cover fixed between the frame and the magnetic circuit system; the metal cover comprises a bottom wall set at a bottom of the speaker unit and a side wall extending from the bottom wall and set at a side of the speaker unit; the vibration system, the frame, the metal cover and the magnetic circuit system enclosing a internal space of the speaker unit; the bottom wall and/or the side wall are provided with leak structures formed by stamping communicating the internal space and the rear cavity, the leak structure comprising a bar-shaped through-hole and a bar-shaped bulge corresponding to the bar-shaped through-hole; the bar-shaped bulge extends towards the internal space, the bar-shaped bulge of the leak structure formed on the bottom wall abuts against the magnetic circuit system, and the bar-shaped bulge being directly contacted with the magnetic circuit system.

2. The speaker box as described in claim 1, wherein the adjacent leak structures formed on the bottom wall are arranged at equal intervals in parallel.

3. The speaker box as described in claim 1, wherein the adjacent leak structures formed on the side wall are arranged at equal intervals in parallel.

4. The speaker box as described in claim 1, wherein the housing includes a metal upper housing and a metal lower housing connected with the metal upper housing cover, the metal upper housing is provided with an outlet hole, the speaker unit is fixed to the metal upper housing and communicates with the outlet hole, the metal upper housing, the metal lower housing and the

speaker unit enclose the rear cavity.

5. The speaker box as described in claim 1, wherein the vibration system includes a diaphragm, a flexible circuit board spaced from the diaphragm, a bracket connecting the diaphragm and the flexible circuit board, and a coil fixed to the bracket to drive the diaphragm vibration and sound, the coil electrically connected to the flexible circuit board, the flexible circuit board fixed to the frame and electrically connected to an external power supply via an external circuit board.

6. The speaker box as described in claim 1, wherein the magnetic circuit system includes a lower clamp plate, a main magnet fixed to the lower clamp plate, a secondary magnet fixed to the lower clamp plate and spaced from the main magnet, a main pole core fixed to the main magnet, and a ring-shaped secondary pole core fixed to the secondary magnet, the frame being a metal frame and fixed to the secondary pole core.
