

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12409782
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Lee; Dong Hyun

Optical assembly and rear-view mirror assembly comprising same

Abstract

The optical assembly disclosed in the embodiment includes a housing having an inclined bottom surface, a plurality of inner surfaces around an outer periphery of the bottom surface, and a receiving space in which an upper portion is opened; and a lighting module disposed on the inclined bottom surface, wherein the lighting module includes a substrate inclinedly disposed on the inclined bottom surface; at least one light emitting device disposed on the substrate; and a resin layer sealing the light emitting device and the substrate, wherein an upper surface of the resin layer emits light by diffusing light emitted from the light emitting device, wherein the plurality of inner surfaces includes a first inner surface adjacent to the light emitting device, a second inner surface facing the first inner surface, and third and fourth inner surfaces facing each other and disposed between the first and second inner surfaces, wherein a height between the bottom surface of the housing and an upper surface of the housing increases from the first inner surface toward the second inner surface, and decreases from the third inner surface toward the fourth inner surface.

Inventors:	Lee; Dong Hyun (Seoul, KR)
Applicant:	LG INNOTEK CO., LTD. (Seoul, KR)
Family ID:	76992364
Assignee:	LG INNOTEK CO., LTD. (Seoul, KR)
Appl. No.:	18/646973
Filed:	April 26, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240294114 A1	Sep. 05, 2024

Foreign Application Priority Data

KR	10-2020-0009187	Jan. 23, 2020
KR	10-2020-0112442	Sep. 03, 2020

Related U.S. Application Data

continuation parent-doc US 18201317 20230524 US 11999298 child-doc US 18646973
continuation parent-doc US 17791080 US 11697374 20230711 WO PCT/KR2021/000704
20210119 child-doc US 18201317

Publication Classification

Int. Cl.: B60R1/12 (20060101); F21K9/60 (20160101); F21Y115/10 (20160101)

U.S. Cl.:

CPC B60R1/12 (20130101); F21K9/60 (20160801); F21Y2115/10 (20160801)

Field of Classification Search

CPC: B60R (1/12); B60R (1/1207); F21K (9/60); F21Y (2115/10); B60Q (1/2665); B60Q (9/008); G02B (5/08)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4257084	12/1980	Reynolds	362/601	G01D 11/28
7699510	12/2009	Yoshihara et al.	N/A	N/A
8708536	12/2013	Mathieu	N/A	N/A
9440580	12/2015	Mathieu	N/A	N/A
10471888	12/2018	Mi et al.	N/A	N/A
10589675	12/2019	Huang	N/A	N/A
11236879	12/2021	Zhang	N/A	N/A
11865969	12/2023	Lee	N/A	N/A
2008/0049436	12/2007	Yoshihara et al.	N/A	N/A
2008/0130306	12/2007	Bande Martinez	N/A	N/A
2010/0118509	12/2009	Kwon et al.	N/A	N/A
2011/0018440	12/2010	Fukuda	362/296.01	G11B 33/10
2011/0221588	12/2010	Foote et al.	N/A	N/A
2012/0206930	12/2011	Minikey, Jr. et al.	N/A	N/A
2013/0020461	12/2012	Yamada	250/200	B60R 1/12
2013/0141931	12/2012	Mathieu et al.	N/A	N/A
2014/0133128	12/2013	Oh	362/97.1	G02B 6/0038
2014/0185310	12/2013	Lisowski et al.	N/A	N/A

2015/0003089	12/2014	Lynam	N/A	N/A
2015/0329047	12/2014	Park et al.	N/A	N/A
2016/0078768	12/2015	Huizen et al.	N/A	N/A
2016/0146420	12/2015	Yang	N/A	N/A
2016/0297356	12/2015	Dellock et al.	N/A	N/A
2017/0120809	12/2016	Koyama et al.	N/A	N/A
2019/0039508	12/2018	Mi et al.	N/A	N/A
2019/0135182	12/2018	Oh et al.	N/A	N/A
2019/0137046	12/2018	Hwang	N/A	F21S 43/245
2019/0137052	12/2018	Hwang	N/A	F21V 29/70
2019/0193638	12/2018	Park et al.	N/A	N/A
2019/0351830	12/2018	Bosma	N/A	N/A
2021/0372594	12/2020	Lee	N/A	G02B 6/0036
2022/0055541	12/2021	Kobayashi	N/A	N/A
2022/0066087	12/2021	Choi	N/A	G02B 6/0031
2022/0340082	12/2021	Doehlert	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
101131230	12/2007	CN	N/A
207000297	12/2017	CN	N/A
10-2004-052667	12/2005	DE	N/A
2933550	12/2014	EP	N/A
3216009	12/2000	JP	N/A
2004-199930	12/2003	JP	N/A
2007-311252	12/2006	JP	N/A
2010-118335	12/2009	JP	N/A
WO2013/046318	12/2012	JP	N/A
2014-534601	12/2013	JP	N/A
10-2004-0001764	12/2003	KR	N/A
10-2016-0062781	12/2015	KR	N/A
10-2016-0091867	12/2015	KR	N/A
10-2018-0103339	12/2017	KR	N/A
I668391	12/2018	TW	N/A

OTHER PUBLICATIONS

International Search Report dated Apr. 13, 2021 issued in Application No. PCT/KR2021/000704. cited by applicant

U.S. Notice of Allowance dated Feb. 27, 2023 issued in U.S. Appl. No. 17/791,080. cited by applicant

European Search Report dated May 16, 2023 issued in Application No. 21744254.0. cited by applicant

U.S. Notice of Allowance dated Feb. 5, 2024 issued in U.S. Appl. No. 18/201,317. cited by applicant

Chinese Office Action dated Oct. 31, 2024 issued in Application No. 202180010961.9. cited by applicant

Primary Examiner: Green; Tracie Y

Attorney, Agent or Firm: KED & ASSOCIATES, LLP

Background/Summary

CROSS-REFERENCE TO RELATED PATENT APPLICATIONS (1) This application is a Continuation of U.S. application Ser. No. 18/201,317, filed May 24, 2023, which is a Continuation of U.S. application Ser. No. 17/791,080, filed Jul. 6, 2022, now U.S. Pat. No. 11,697,374, which is a U.S. National Stage Application under 35 U.S.C. § 371 of PCT Application No. PCT/KR2021/000704, filed Jan. 19, 2021, which claims priority to Korean Patent Application Nos. 10-2020-0009187, filed Jan. 23, 2020 and 10-2020-0112442, filed Sep. 3, 2020, whose entire disclosures are hereby incorporated by reference.

TECHNICAL FIELD

(1) An embodiment relates to a lighting module having a light emitting device and providing a surface light source.

(2) An embodiment relates to an optical assembly having a lighting module.

(3) Embodiments relate to a rear-view mirror assembly including an optical assembly.

BACKGROUND ART

(4) Typical lighting applications include vehicle lights as well as backlights for displays and signage.

(5) Light emitting devices, for example, light emitting diodes (LEDs) have advantages such as low power consumption, semi-permanent lifespan, fast response speed, safety, and environmental friendliness compared to conventional light sources such as fluorescent lamps and incandescent lamps. Such the light emitting diode is applied to various optical assemblies such as various display devices, indoor lights, or outdoor lights.

(6) Recently, as a light source for a vehicle, a lamp employing a light emitting diode has been proposed. For example, light emitting diodes are being applied to vehicle headlights, tail lights, turn signals, and the like. Since the light emitting diode has a small size, it is possible to increase the design freedom of the lamp. In addition, compared to incandescent lamps, light emitting diodes are advantageous in that they consume less power and have a semi-permanent lifespan.

(7) However, since the directivity angle of light emitted from the light emitting diode is small, when the light emitting diode is used as a vehicle lamp, there is a demand for increasing the light emitting area of the lamp using the light emitting diode.

(8) For example, the light emitting diode may be applied to a blind spot detection (BSD) system. The blind spot detection system is a system that detects other vehicles located behind and to the side of the driver with a sensor device of the vehicle, and provides information about it to the driver through visual, auditory, tactile, and the like. In such the blind spot detection system, a light emitting diode may be disposed in a side mirror, a rear-view mirror, or an A-pillar region of a vehicle to visually provide rear sight information to the driver.

(9) However, as light is emitted in various directions from the light emitting diodes, there is a problem in that visual information is not effectively provided to the driver. In addition, there is a problem in that the light emitted from the light emitting diode may be emitted in the direction of the driver of another vehicle, thereby obstructing the view and causing an accident.

(10) Accordingly, there is a need for a new optical assembly and a blind spot warning device that

may solve the above problems.

DISCLOSURE

Technical Problem

(11) An embodiment is to provide an optical assembly capable of improving the luminous intensity of a surface light source and a blind spot warning device.

(12) In addition, an embodiment is to provide an optical assembly capable of improving the uniformity of a surface light source and a blind spot warning device.

(13) In addition, an embodiment is to provide an optical assembly capable of controlling a light exit direction and a blind spot warning device.

(14) In addition, an embodiment is to provide an optical assembly capable of controlling a luminance value of light emitted toward a driver and a luminance value of light emitted toward a vehicle positioned on the side direction and rear direction of the driver, and an optical assembly and blind spot warning device.

Technical Solution

(15) An optical assembly according to an embodiment includes a housing including an inclined bottom surface, a plurality of inner surfaces around an outer periphery of the bottom surface, and a receiving space in which an upper portion is opened, and a lighting module disposed on the inclined bottom surface, wherein the lighting module includes a substrate inclinedly disposed on the inclined bottom surface, at least one light emitting device disposed on the substrate, and a resin layer sealing the light emitting device and the substrate, and an upper surface of the resin layer emits by diffusing the emitted light from the light emitting device, and the plurality of inner surfaces includes a first inner surface adjacent to the light emitting device, a second inner surface facing the first inner surface, and third and fourth inner surfaces disposed between the first and second inner surfaces and facing each other, wherein a height between the bottom surface of the housing and an upper surface of the housing increases from the first inner surface toward the second inner surface, and decreases from the third inner surface toward the fourth inner surface.

(16) In addition, the rear-view mirror assembly according to the embodiment includes a blocking member disposed on an optical assembly and including an opening region and a mirror member disposed on the blocking member, wherein the optical assembly includes a housing including an inclined bottom surface, a plurality of inner surfaces around an outer periphery of the bottom surface, and a receiving space in which an upper portion is opened, and a lighting module disposed on the inclined bottom surface, wherein the lighting module includes a substrate inclinedly disposed on the inclined bottom surface, at least one light emitting device disposed on the substrate, and a resin layer sealing the light emitting device and the substrate, and an upper surface of the resin layer emits by diffusing the emitted light from the light emitting device, and the plurality of inner surfaces includes a first inner surface adjacent to the light emitting device, a second inner surface facing the first inner surface, and third and fourth inner surfaces disposed between the first and second inner surfaces and facing each other, wherein a height between the bottom surface of the housing and an upper surface of the housing increases from the first inner surface toward the second inner surface, and decreases from the third inner surface toward the fourth inner surface.

Advantageous Effects

(17) The optical assembly according to the embodiment may emit light as a surface light source, and may have improved luminous intensity and improved light uniformity. In addition, the optical assembly may prevent a hot spot from being formed and minimize loss of light.

(18) In addition, the lighting module of the optical assembly according to the embodiment may be inclined at a set inclination angle. Accordingly, the optical assembly may control an exit direction of the light emitted from the lighting module and a luminance value according to the exit direction.

(19) In addition, the rear-view mirror assembly according to the embodiment may minimize light loss and maximize light emitted through the mirror member. Also, the rear-view mirror assembly

may control an exit direction of the light emitted from the optical assembly and a luminance value of the light according to the exit direction. In detail, the rear-view mirror assembly may control a light exit direction and a luminance value of the light by an optical assembly inclined at a set inclination angle. Accordingly, the rear-view mirror assembly may provide high luminance light to the driver, so that the driver may effectively recognize the logo and/or icon of the indicator. In addition, a relatively low luminance light may be provided to another vehicle located at the rear side of the driver's vehicle, thereby minimizing or preventing the driver of the other vehicle from being disturbed by the light.

Description

DESCRIPTION OF DRAWINGS

- (1) FIG. 1 is an exploded perspective view of an optical assembly according to an embodiment;
- (2) FIG. 2 is a top view of an optical assembly according to an embodiment;
- (3) FIG. 3 is a side view of a housing according to an embodiment;
- (4) FIG. 4 is a side view of an optical assembly according to an embodiment;
- (5) FIG. 5 is a top view of a lighting module according to an embodiment.
- (6) FIG. 6 is a cross-sectional view showing a cross-section taken along line A-A' of FIG. 5.
- (7) FIG. 7 is an enlarged view of an area A1 of FIG. 6.
- (8) FIG. 8 is another cross-sectional view showing a cross-section taken along line A-A' of FIG. 5.
- (9) FIG. 9 is an enlarged view of a region A2 of FIG. 8.
- (10) FIG. 10 is another cross-sectional view showing a cross-section taken along line A-A' of FIG. 5.
- (11) FIG. 11 is an enlarged view of a region A3 of FIG. 10.
- (12) FIG. 12 is another cross-sectional view showing a cross-section taken along line A-A' of FIG. 5.
- (13) FIG. 13 is a front view showing a light emitting device on a substrate in the lighting module according to the embodiment.
- (14) FIG. 14 is a side view of the light emitting device of FIG. 13.
- (15) FIG. 15 is an exploded perspective view of a rear-view mirror assembly according to an embodiment.
- (16) FIG. 16 is a cross-sectional view of a rear-view mirror assembly according to an embodiment.
- (17) FIG. 17 is a top view of a blocking member according to an embodiment.
- (18) FIG. 18 is a view for explaining an emission angle of light emitted from the rear-view mirror assembly according to the embodiment.

BEST MODE

- (19) Hereinafter, preferred embodiments of the present invention will be described in detail with reference to the accompanying drawings.
- (20) The technical spirit of the invention is not limited to some embodiments to be described, and may be implemented in various other forms, and one or more of the components may be selectively combined and substituted for use within the scope of the technical spirit of the invention. In addition, the terms (including technical and scientific terms) used in the embodiments of the invention, unless specifically defined and described explicitly, may be interpreted in a meaning that may be generally understood by those having ordinary skill in the art to which the invention pertains, and terms that are commonly used such as terms defined in a dictionary should be able to interpret their meanings in consideration of the contextual meaning of the relevant technology. Further, the terms used in the embodiments of the invention are for explaining the embodiments and are not intended to limit the invention. In this specification, the singular forms also may include plural forms unless otherwise specifically stated in a phrase, and in the case in which at

least one (or one or more) of A and (and) B, C is stated, it may include one or more of all combinations that may be combined with A, B, and C. In describing the components of the embodiments of the invention, terms such as first, second, A, B, (a), and (b) may be used. Such terms are only for distinguishing the component from other component, and may not be determined by the term by the nature, sequence or procedure etc. of the corresponding constituent element. And when it is described that a component is “connected”, “coupled” or “joined” to another component, the description may include not only being directly connected, coupled or joined to the other component but also being “connected”, “coupled” or “joined” by another component between the component and the other component. In addition, in the case of being described as being formed or disposed “above (on)” or “below (under)” of each component, the description includes not only when two components are in direct contact with each other, but also when one or more other components are formed or disposed between the two components. In addition, when expressed as “above (on)” or “below (under)”, it may refer to a downward direction as well as an upward direction with respect to one element.

(21) The optical assembly according to the present invention may be applied to various lamp devices that require lighting, such as vehicle lamps, home lighting devices, or industrial lighting devices. For example, when applied to vehicle lamps, it is applicable to headlamps, sidelights, side mirrors, fog lights, tail lamps, brake lights, daytime running lights, vehicle interior lights, door scars, rear combination lamps, backup lamps, etc. In addition, when applied to a vehicle lamp, it is applicable to a blind spot detection (BSD) system disposed on a side mirror or an A-pillar. In addition, the optical assembly of the invention may be applied to indoor and outdoor advertising devices, display devices, and various electric vehicle fields, and in addition, it may be applied to all lighting-related fields or advertisement-related fields that are currently developed and commercialized or that may be implemented according to future technological developments.

(22) FIG. 1 is an exploded perspective view of an optical assembly according to an embodiment, and FIG. 2 is a top view of the optical assembly according to the embodiment. FIG. 3 is a side view of the housing according to the embodiment, and FIG. 4 is a side view of the optical assembly according to the embodiment. In addition, FIG. 5 is a top view of the lighting module according to the embodiment.

(23) The optical assembly according to the embodiment may be applied to the left and right-side mirrors of the vehicle prior to a description of the drawing FIGS. 1 to 5, and may provide visual information to the driver of the vehicle.

(24) An optical assembly applied to the left-side mirror adjacent to the driver's seat will be described with reference to FIGS. 1 to 5. Since the optical assembly applied to the right-side mirror adjacent to the passenger seat has the same shape and structure as the optical assembly applied to the driver's seat and is symmetrical to each other, for convenience of description, the optical assembly disposed on the driver's seat will be mainly described.

(25) Referring to FIGS. 1 to 5, the optical assembly **10** according to the embodiment may include a housing **300**, a lighting module **400**, an optical member **500**, and a cover member **600**.

(26) The housing **300** may include an opened one side and a receiving space **305** therein. The housing **300** may accommodate the lighting module **400**, the optical member **500**, and the cover member **600**.

(27) The housing **300** has a predetermined reliability and may include a material that is not damaged by heat and light emitted from the lighting module **400**. For example, the housing **300** may include a resin material or a metal material. In detail, the housing **300** may include at least one material of plastic, polypropylene (PP), polyethylene (PE), polycarbonate (PC), Polybutylene Terephthalate (PBT), Acrylonitrile Butadiene Styrene copolymer (ABS), Poly Oxy Methylene (POM), Polyacetal polyphenylene oxide (PPO) resin and a modified PPO resin. In addition, the housing **300** may include at least one of silver (Ag), copper (Cu), titanium (Ti), magnesium (Mg), chromium (Cr), molybdenum (Mo), nickel (Ni), aluminum (Al), stainless steel and an alloy

including the same. When the housing **300** includes a metal material, the housing **300** may provide a heat dissipation path for the lighting module **400**. Accordingly, the heat dissipation characteristic of the optical assembly **10** may be improved.

(28) The housing **300** may include a material capable of absorbing the light emitted from the lighting module **400**. In addition, a surface of the receiving space **305** of the housing **300** may absorb the light emitted from the lighting module **400**. In detail, the housing **300** or the surface material may have a light absorptivity of 50% or more and a light reflectance of 50% or less. For example, the housing **300** may be provided in a color capable of absorbing the light emitted from the lighting module **400**. In detail, the material of the housing **300** or the surface of the receiving space **305** may include black. Accordingly, it is possible to prevent or minimize light emitted from the lighting module **400** from being reflected on the bottom surface **310** and the inner surface **320** of the housing **300**. Accordingly, the light emitted from the lighting module **400** may be emitted in a set direction.

(29) The housing **300** may include a bottom surface **310** and an inner surface **320** formed by the receiving space **305**.

(30) The bottom surface **310** of the housing **300** may have various shapes. In detail, the bottom surface **310** of the housing **300** may have various shapes, such as polygons, circles, and ellipses, when viewed in a plan view. For example, the bottom surface **310** of the housing **300** may have a polygonal shape, for example, a hexagonal shape as shown in FIG. 2.

(31) The bottom surface **310** of the housing **300** may have an inclined shape. In detail, the bottom surface **310** of the housing **300** may be inclined in one direction with respect to the upper surface **301** of the housing **300**.

(32) The inner surface **320** of the housing **300** may include a plurality of inner surfaces. The inner surface **320** of the housing **300** may be perpendicular to the upper surface **301** of the housing **300**. The inner surface **320** of the housing **300** may include a first inner surface **IS1** and a second inner surface **IS2** facing the first inner surface **IS1**. In addition, the inner surface **320** of the housing **300** may include a third inner surface **IS3** and a fourth inner surface **IS4** disposed between the first and second inner surfaces **IS1** and **IS2**. In addition, the inner surface **320** of the housing **300** may include a fifth inner surface **IS5** disposed between the second inner surface **IS2** and the third inner surface **IS3**, and a sixth inner surface **IS6** disposed between the second inner surface **IS2** and the fourth inner surface **IS4**.

(33) At this time, the height between the bottom surface **310** of the housing **300** and the upper surface **301** of the housing **300** may increase from the first inner surface **IS1** toward the second inner surface **IS2**. In addition, the height between the bottom surface **310** of the housing **300** and the upper surface **301** of the housing **300** may decrease from the third inner surface **IS3** toward the fourth inner surface **IS4**.

(34) That is, based on the direction from the first inner surface **IS1** toward the second inner surface **IS2**, the bottom surface **310** of the housing **300** may be inclined at a first inclination angle **a1** with respect to the upper surface of the housing **300**.

(35) The first inclination angle **a1** may be about 15 degrees to about 40 degrees. In detail, the first inclination angle **a1** may be about 20 degrees to about 35 degrees. When the first inclination angle **a1** does not satisfy the above-described range, the light emitted from the lighting module **400** disposed on the bottom surface **310** may be emitted in an unwanted direction. For example, when the first inclination angle **a1** does not satisfy the above-described range, the luminance value of light emitted in the direction in which the user is located may be significantly low, and the luminance value of light emitted in an unwanted direction may be significantly higher. Preferably, the first inclination angle **a1** may be about 25 degrees to about 30 degrees.

(36) In addition, based on the direction from the third inner surface **IS3** toward the fourth inner surface **IS4**, the bottom surface **310** of the housing **300** may be inclined at a second inclination angle **a2** with respect to the upper surface of the housing **300**.

(37) The second inclination angle a_2 may be about 15 degrees to about 40 degrees. In detail, the second inclination angle a_2 may be about 20 degrees to about 35 degrees. When the second inclination angle a_2 does not satisfy the above-described range, the light emitted from the lighting module **400** disposed on the bottom surface **310** may be emitted in an unwanted direction. For example, when the second inclination angle a_2 does not satisfy the above-described range, the luminance value of light emitted in the direction in which the user is located may be significantly low, and the luminance value of light emitted in an unwanted direction may be significantly higher. Preferably, the second inclination angle a_2 may be about 25 degrees to about 30 degrees.

(38) The bottom surface **310** of the housing **300** may have a shape inclined in the above-described direction. In detail, the height between the bottom surface **310** of the housing **300** and the top surface of the housing **300** may have the lowest value in a first intersection point **P1** defined by the intersection point of the first inner surface **IS1** and the fourth inner surface **IS4**. In addition, the height between the bottom surface **310** of the housing **300** and the upper surface of the housing **300** may have the highest value in a region adjacent to the fifth inner surface **IS5**. That is, the bottom surface **310** of the housing **300** may have a shape inclined from the first intersection point **P1** toward the fifth inner surface **IS5**.

(39) The lighting module **400** may be disposed in the housing **300**. The lighting module **400** is disposed in the receiving space **305**, and may be disposed on the bottom surface **310** of the housing **300**. The lighting module **400** may have a constant thickness and may emit light as a surface light source.

(40) The lighting module **400** may be in direct contact with the bottom surface **310** of the housing **300**. In addition, the lighting module **400** may indirectly contact the bottom surface **310** of the housing **300** by an adhesive member (not shown) or the like.

(41) The lighting module **400** may have a shape corresponding to the bottom surface **310** of the housing **300**. For example, the planar shape of the lighting module **400** may have a shape corresponding to the bottom surface **310**. Accordingly, the lighting module **400** may be easily disposed in the receiving space **305**.

(42) The lighting module **400** may include a plurality of outer surfaces. For example, the lighting module **400** may include the first to sixth inner surfaces **IS1** to **IS6** and first to sixth side surfaces **S1** to **S6** corresponding to each. Each of the first to sixth side surfaces **S1** to **S6** may be a side surface facing the first to sixth inner surfaces **IS1** to **IS6**, respectively.

(43) The lighting module **400** may be inclinedly disposed on the bottom surface **310**. For example, the lighting module **400** may be disposed to be inclined at an inclination angle corresponding to the inclined bottom surface **310** with respect to the upper surface **301** of the housing **300**.

(44) Accordingly, the height between the upper surface of the lighting module **400** and the upper surface **301** of the housing **300** may increase in a direction from the first side surface **S1** to the second side surface **S2**. In addition, the height between the upper surface of the lighting module **400** and the upper surface **301** of the housing **300** may decrease in a direction from the third side surface **S3** to the fourth side surface **S4**.

(45) That is, based on the direction from the first side surface **S1** toward the second side surface **S2**, the upper surface and/or the bottom surface of the lighting module **400** may be inclined at the first inclination angle a_1 with respect to the upper surface of the housing **300**. In addition, based on the direction from the third side surface **S3** toward the fourth side surface **S4**, the upper surface and/or the bottom surface of the lighting module **400** may be inclined at the second inclination angle a_2 with respect to the upper surface of the housing **300**.

(46) Accordingly, the lighting module **400** may be inclinedly disposed in the housing **300**. At this time, the height between the upper surface of the lighting module **400** and the upper surface of the housing **300** may have the lowest value at the second intersection point **P2** defined as the intersection point of the first side surface **S1** and the fourth side surface **S4**. In addition, the height between the upper surface of the lighting module **400** and the upper surface of the housing **300** may

have the highest value in a region adjacent to the fifth side surface S5. That is, the lighting module **400** may have a shape inclined in a direction from the second intersection point P2 to the fifth side surface S5.

(47) The lighting module **400** includes at least one light emitting device **100** and may emit light as a surface light source. The lighting module **400** may emit light in a direction of an opened upper portion of the housing **300**.

(48) The light emitting device **100** may be disposed in a region having a relatively small height difference from the upper surface **301** of the housing **300** to emit light in a direction of a region having a relatively large height difference. For example, the light emitting device **100** may be disposed adjacent to the first side surface S1 and may emit light in the direction of the second side surface S2. In detail, a distance between the light emitting device **100** and the first side surface S1 may be less than or equal to about 20% of a distance between the light emitting device **100** and the second side surface S2. In addition, a distance between the light emitting device **100** and the third side surface S3 may correspond to a distance between the light emitting device **100** and the fourth side surface S4.

(49) The optical member **500** may be disposed in the receiving space **305**. The optical member **500** may be disposed on the lighting module **400**. The optical member **500** may be disposed in direct or indirect contact with the upper surface of the lighting module **400**.

(50) The optical member **500** may have a shape corresponding to the lighting module **400**. In detail, the lower surface of the optical member **500** may have a shape corresponding to the upper surface of the lighting module **400**. Accordingly, the optical member **500** may be easily disposed in the receiving space **305**, and may effectively control the light emitted from the lighting module **400**.

(51) The optical member **500** may be inclinedly disposed on the lighting module **400**. In detail, the optical member **500** may be inclined at an inclination angle corresponding to the lighting module **400**.

(52) For example, the height between the upper surface of the optical member **500** and the upper surface **301** of the housing **300** may increase in a direction from the first inner surface IS1 to the second inner surface IS2. In addition, a height between the upper surface of the optical member **500** and the upper surface **301** of the housing **300** may decrease in a direction from the third inner surface IS3 to the fourth inner surface IS4.

(53) That is, based on the direction from the first inner surface IS1 toward the second inner surface IS2, the upper surface of the optical member **500** may be inclined at the first inclination angle $\alpha 1$ with respect to the upper surface of the housing **300**. In addition, based on the direction from the third inner surface IS3 toward the fourth inner surface IS4, the upper surface of the optical member **500** may be inclined at the second inclination angle $\alpha 2$ with respect to the upper surface of the housing **300**. Accordingly, the optical member **500** may be inclinedly disposed in the housing **300** by the inclined bottom surface **310** and the lighting module **400**. That is, the optical member **500** may have a shape inclined toward the fifth inner surface IS5 from the first intersection point P1 of the housing **300**.

(54) The optical member **500** may control the light emitted from the lighting module **400**. For example, the optical member **500** may include a prism sheet including a linear prism extending in one direction. In detail, the optical member **500** may include a first optical member including a linear prism extending in one direction and a second optical member including a linear prism extending in the other direction. Here, the other direction may be a direction perpendicular to the one direction. The first and second optical members may focus light emitted from the lighting module **400** in different directions.

(55) The cover member **600** may be disposed in the receiving space **305**. The cover member **600** may be disposed on the optical member **500**. The cover member **600** may be disposed in direct or indirect contact with the upper surface of the optical member **500**.

(56) The cover member **600** may have a shape corresponding to the receiving space **305**. For

example, the planar shape of the cover member **600** may have a planar shape corresponding to the bottom surface **310** of the housing **300**. Accordingly, the cover member **600** may be easily disposed and fixed in the receiving space **305**.

(57) The upper surface of the cover member **600** may be provided as a flat plane. For example, the upper surface **301** of the housing **300** may be provided in a flat plane, and the upper surface of the cover member **600** may be disposed on the same plane as the upper surface **301** of the housing **300**.

(58) The cover member **600** may include an inclined surface. In detail, the lower surface of the cover member **600** facing the optical member **500** may include an inclined surface corresponding to the lighting module **400** and/or the optical member **500**.

(59) In detail, a thickness between the upper and lower surfaces of the cover member **600** may increase in a direction from the first inner surface **IS1** to the second inner surface **IS2**. In addition, the thickness between the upper and lower surfaces of the cover member **600** may decrease in a direction from the third inner surface **IS3** to the fourth inner surface **IS4**.

(60) That is, based on the direction from the first inner surface **IS1** toward the second inner surface **IS2**, the lower surface of the cover member **600** may be inclined at the first inclination angle $\alpha 1$ with respect to the upper surface of the lighting module **400**. In addition, based on the direction from the third inner surface **IS3** toward the fourth inner surface **IS4**, the lower surface of the cover member **600** may be inclined at the second inclination angle $\alpha 2$ with respect to the upper surface of the cover member **600**. That is, the lower surface of the cover member **600** may be inclined in the direction of the fifth inner surface **IS5** from the first intersection point **P1** of the housing **300**.

(61) Accordingly, the cover member **600** may cover one surface of the opened housing **300**. That is, the cover member **600** may be disposed on the lighting module **400** and the optical member **500** to cover the components **400** and **500**. The light emitted from the lighting module **400** may be emitted in a direction of an opened upper portion of the housing **300** through the optical member **500** and the cover member **600**.

(62) FIG. **6** is a cross-sectional view illustrating a cross-section taken along line A-A' of FIG. **5**, and FIG. **7** is an enlarged view of a region **A1** of FIG. **6**. The lighting module **400** according to the embodiment will be described in more detail with reference to FIGS. **6** and **7**.

(63) Referring to FIGS. **6** and **7**, the lighting module **400** includes a substrate **401**, the light emitting device **100** disposed on the substrate **401**, and a resin layer **420** covering and sealing the substrate **401** and the light emitting device **100**. In addition, the lighting module **400** may include a reflective member **410** disposed on the substrate **401**.

(64) The lighting module **400** may emit the light emitted from the light emitting device **100** as a surface light source. The lighting module **400** may be defined as a light emitting cell or a light source module. The lighting module **400** may include one light emitting cell or a plurality of light emitting cells on the substrate **401**.

(65) The substrate **401** may include a printed circuit board (PCB). The substrate **401** may include, for example, at least one of a resin-based printed circuit board (PCB), a metal core PCB, a flexible PCB, a ceramic PCB, and an FR-4 substrate. When the substrate **401** is disposed as a metal core PCB having a metal layer disposed on the bottom, the heat dissipation efficiency of the light emitting device **100** may be improved.

(66) The substrate **401** may be electrically connected to the light emitting device **100**. The substrate **401** may include a wiring layer (not shown) thereon, and the wiring layer may be electrically connected to the light emitting device **100**. When a plurality of light emitting devices **100** are arranged on the substrate **401**, the plurality of light emitting devices **100** may be connected in series, parallel, or series-parallel by the wiring layer. The substrate **401** may function as a base member or a support member disposed under the light emitting device **100** and the resin layer **420**.

(67) The upper surface of the substrate **401** may have an X-Y plane. The upper surface of the substrate **401** may be flat or have a curved surface. The thickness of the substrate **401** may be a height in the Z direction. Here, the X direction may be a first direction, and the Y direction may be

a second direction. The Z direction may be a direction orthogonal to the first and second directions. A length of the substrate **401** in the first direction may be greater than a width in the second direction. The length of the substrate **401** in the first direction may be two times or more, for example, four times or more than the width in the second direction.

(68) The substrate **401** may include a light-transmitting material through which light is transmitted through the upper and lower surfaces. The light-transmitting material may include at least one of polyethylene terephthalate (PET), polystyrene (PS), and polyimide (PI).

(69) The light emitting device **100** is disposed on the substrate **401** and may emit light in a first direction. That is, the light emitting device **100** may emit light in the direction of the second side surface **S2** of the lighting module **400**.

(70) The light emitting device **100** may have an emitting surface **81** through which light is emitted, and the emitting surface **81** may be disposed, for example, in a third direction or a vertical direction with respect to a horizontal upper surface of the substrate **401**. The emission surface **81** may be a vertical plane, or may include a concave surface or a convex surface.

(71) As shown in FIGS. **13** and **14**, the light emitting device **100** is disposed on, for example, the substrate **401** and may be electrically connected to the pads **403** and **405** of the substrate **401** by conductive bonding members **203** and **205**. The conductive bonding members **203** and **205** may be made of a solder material or a metal material.

(72) The light emitting device **100** may be disposed in a relatively upper region of the inclined bottom surface **310** of the housing **300**. The light emitting device **100** may emit light in the first direction, for example, in a direction from a relatively inclined upper region to a lower region.

(73) The optical axis of the light emitting device **100** may correspond to the bottom surface **310**. In detail, the optical axis of the light emitting device **100** may be parallel to the bottom surface **310** of the housing **300**, and may have the first inclination angle $\alpha 1$ with the upper surface of the housing **300**.

(74) One or a plurality of light emitting devices **100** may be disposed on the substrate **401**. For example, as shown in the drawing, one light emitting device **100** emitting light in the first direction may be disposed on the substrate **401**.

(75) As another example, although not shown in the drawings, a plurality of light emitting devices **100** emitting light in the first direction on the substrate **401** may be arranged in at least one row or arranged in two or more rows in the second direction. In addition, the plurality of light emitting devices **100** may be arranged in at least one row or in two or more rows in the first direction. Also, the plurality of light emitting devices **100** may be disposed on the substrate **401** in different directions.

(76) The light emitting device **100** is a device including a light emitting diode (LED), and may include a package in which a light emitting chip is packaged. The light emitting chip **71** may emit at least one of blue, red, green, ultraviolet (UV) and infrared light, and the light emitting device **100** may emit at least one of white, blue, red, green, and infrared light. The light emitting device **100** may be of a side view type in which a bottom portion is electrically connected to the substrate **401**, but is not limited thereto. As another example, the light emitting device **100** may be an LED chip, but is not limited thereto.

(77) The emission surface **81** of the light emitting device **100** may be disposed on at least one side of the light emitting device **100** rather than the upper surface. The emission surface **81** may be a surface adjacent to the substrate **401** among the side surfaces of the light emitting device **100**, for example, a side surface adjacent to the upper surface of the substrate **401**. The emission surface **81** is disposed on a side surface between the bottom surface and the upper surface of the light emitting device **100**, and emits light of the highest intensity in the first direction. The emission surface **81** of the light emitting device **100** may be a surface adjacent to the reflective member **410** or a surface perpendicular to the upper surface of the substrate **401** and the upper surface of the reflective member **410**.

(78) The light emitted through the emission surface **81** of the light emitting device **100** may travel in a direction parallel to the upper surface of the substrate **401**, may be reflected by the reflective member **410**, or may proceed in the upward direction of the resin layer **420**. The thickness of the light emitting device **100** may be, for example, 3 mm or less, for example, in the range of 0.8 mm to 2 mm. The length of the light emitting device **100** in the second direction may be 1.5 times or more of the thickness of the light emitting device **100**, but is not limited thereto. The light emitting device **100** may have a wider light beam angle in the $\pm Y$ direction than the light beam angle in the $\pm Z$ direction. The light beam angle of the light emitting device **100** in the second direction may be 110 degrees or more, for example, 120 degrees to 160 degrees or 140 degrees or more. The light beam angle in the third direction of the light emitting device **100** may be 110 degrees or more, for example, 120 degrees to 140 degrees.

(79) The reflective member **410** may be disposed between the substrate **401** and the resin layer **420**. The reflective member **410** may be provided in the form of a film having a metal material or a non-metal material. The reflective member **410** may be adhered to the upper surface of the substrate **401**. The reflective member **410** may have an area smaller than an area of a upper surface of the substrate **401**. The reflective member **410** may be spaced apart from the edge of the substrate **401**, and a resin layer **420** may be attached to the substrate **401** in the spaced region. In this case, it is possible to prevent the edge portion of the reflective member **410** from peeling off.

(80) The reflective member **410** may include an opening **417** in which a lower portion of the light emitting device **100** is disposed. The upper surface of the substrate **401** may be exposed in the opening **417** of the reflective member **410** and a portion to which the lower portion of the light emitting device **100** is bonded may be disposed. The size of the opening **417** may be the same as or larger than the size of the light emitting device **100**, but is not limited thereto. The reflective member **410** may contact the upper surface of the substrate **401** or may be adhered between the resin layer **420** and the substrate **401**, but is not limited thereto. Here, the reflective member **410** may be removed when a highly reflective material is coated on the upper surface of the substrate **401**.

(81) The reflective member **410** may be formed to have a thickness smaller than that of the light emitting device **100**. The thickness of the reflective member **410** may include a range of $0.2\text{ mm} \pm 0.02\text{ mm}$. A lower portion of the light emitting device **100** may penetrate through the opening **417** of the reflective member **410** and an upper portion of the light emitting device **100** may protrude. The emission surface **81** of the light emitting device **100** may be provided in a direction perpendicular to the upper surface of the reflective member **410**.

(82) The reflective member **410** may include a metallic material or a non-metallic material. The metallic material may include a metal such as aluminum, silver, or gold. The non-metallic material may include a plastic material or a resin material. The plastic material may be any one selected from the group consisting of polyethylene, polypropylene, polystyrene, polyvinyl chloride, polybiphenyl chloride, polyethylene terephthalate, polyvinyl alcohol, polycarbonate, polybutylene terephthalate, polyethylene naphthalate, polyamide, polyacetal, polyphenylene ether, polyamideimide, polyetherimide, polyetheretherketone, polyimide, polytetrafluoroethylene, liquid crystal polymer, fluororesin, copolymers thereof, and mixtures thereof. As the resin material, a reflective material, for example, a metal oxide such as TiO_2 , Al_2O_3 , or SiO_2 may be added in silicon or epoxy. The reflective member **410** may be implemented as a single layer or a multilayer, and light reflection efficiency may be improved by such a layer structure. The reflective member **410** according to an embodiment of the invention reflects incident light, thereby increasing the amount of light so that the light is uniformly distributed.

(83) Also, referring to FIG. 7, the reflective member **410** may include an adhesive layer (not shown), a reflective layer (not shown), and a plurality of dots **411**. The adhesive layer may attach the reflective member **410** to the upper surface of the substrate **401**. The adhesive layer is a transparent material, and may be an adhesive such as UV adhesive, silicone, or epoxy.

(84) The reflective layer may include a plurality of reflective agents (not shown) inside the resin material. The reflective agents may be a bubble, such as air, or a medium having the same refractive index as that of air. The resin material of the reflective layer may be a material such as silicone or epoxy, and the reflective agent may be formed by injecting air bubbles into the resin material. The reflective layer may reflect the light incident by the plurality of reflective agents or refract it in a different direction. The thickness of the reflective layer may be 80% or more of the thickness of the reflective member **410**.

(85) The plurality of dots **411** may be disposed to protrude on the upper surface of the reflective member **410**. For example, the plurality of dots **411** may be disposed on the upper surface of the reflective layer in a shape protruding from the upper surface. The plurality of dots **411** may be spaced apart from the light emitting device **100**. The plurality of dots **411** may be spaced apart from the light emitting device **100** in a first direction and a second direction. The plurality of dots **411** may be formed on the reflective layer by printing. The plurality of dots **411** may include reflective ink. The plurality of dots **411** may be printed using a material including any one of TiO_2 , CaCO_3 , BaSO_4 , Al_2O_3 , Silicon, and PS. Each of the plurality of dots **411** may have a hemispherical side cross-section or a polygonal shape. The material of the dot **411** may be white.

(86) The density of the dot pattern of the plurality of dots **411** may increase as the distance from the emission surface **81** of the light emitting device **100** increases. In addition, the sizes of the plurality of dots **411** may change as they move away from the emission surface **81** of the light emitting device **100**. For example, the width of the plurality of dots **411** may increase as the distance from the emission surface **81** of the light emitting device **100** increases.

(87) Since the plurality of dots are disposed on the upper surface of the reflective member **410** in the emission direction of the light emitting device **100**, light reflectance may be improved, light loss may be reduced, and the luminance of the surface light source may be improved.

(88) The resin layer **420** may be disposed on the substrate **401**. The resin layer **420** may face the substrate **401**. The resin layer **420** may be disposed on all or a portion of the upper surface of the substrate **401**. The area of the lower surface of the resin layer **420** may be the same as or smaller than the area of the upper surface of the substrate **401**. The resin layer **420** may be formed of a transparent material. The resin layer **420** may include a resin material such as silicone or epoxy. The resin layer **420** may include a thermosetting resin material, for example, may selectively include PC, OPS, PMMA, PVC, and the like. The resin layer **420** may be formed of glass, but is not limited thereto. For example, the main material of the resin layer **420** may be a resin material having a urethane acrylate oligomer as a main material. For example, a mixture of urethane acrylate oligomer, which is a synthetic oligomer, and a polymer type, which is polyacrylic, may be used. Of course, the main material may further include a monomer mixed with low-boiling dilution-type reactive monomers such as IBOA (isobornyl acrylate), HPA (hydroxyl propyl acrylate), 2-HEA (2-hydroxyethyl acrylate), etc., as an additive, a photo initiator (for example, 1-hydroxycyclohexyl phenyl-ketone, etc.) or antioxidants may be mixed.

(89) Since the resin layer **420** is provided as a layer for guiding light as a resin, it may be provided with a thinner thickness than in the case of glass and may be provided as a flexible plate. The resin layer **420** may emit the point light source emitted from the light emitting device **100** in the form of a line light source or a surface light source.

(90) The upper surface of the resin layer **420** may emit light by diffusing the light emitted from the light emitting device **100**. For example, beads (not shown) may be included in the resin layer **420**, and the beads may diffuse and reflect incident light to increase the amount of light. The beads may be disposed in an amount of 0.01 to 0.3% based on the weight of the resin layer **420**. The bead may be composed of any one selected from silicon, silica, glass bubble, polymethyl methacrylate (PMMA), urethane, Zn, Zr, Al_2O_3 , and acryl, the particle diameter of the beads may be in the range of about 1 μm to about 20 μm , but is not limited thereto.

(91) Since the resin layer **420** is disposed on the light emitting device **100**, it is possible to protect the light emitting device **100** and reduce loss of light emitted from the light emitting device **100**. The light emitting device **100** may be buried under the resin layer **420**.

(92) The resin layer **420** may be in contact with the surface of the light emitting device **100** and may be in contact with the emission surface **81** of the light emitting device **100**. A portion of the resin layer **420** may be disposed in the opening **417** of the reflective member **410**. A portion of the resin layer **420** may be in contact with the upper surface of the substrate **401** through the opening **417** of the reflective member **410**. Accordingly, a portion of the resin layer **420** comes into contact with the substrate **401**, thereby fixing the reflective member **410** between the resin layer **420** and the substrate **401**.

(93) FIG. **8** is another cross-sectional view showing a cross-section taken along line A-A' of FIG. **5**, and FIG. **9** is an enlarged view of a region A2 of FIG. **8**. In the description using FIGS. **8** and **9**, descriptions of the same and similar components as those of the lighting module described above are omitted, and the same reference numerals are assigned to the same and similar components.

(94) Referring to FIGS. **8** and **9**, a diffusion layer **430** may be further disposed on the upper surface of the resin layer **420**. For example, the upper surface of the resin layer **420** may have an adhesive force, and the diffusion layer **430** may be adhered to the resin layer **420**. For example, the upper surface of the resin layer **420** may be adhered to the diffusion layer **430** by an adhesive force having fine cilia. At this time, the diffusion layer **430** may be attached to the resin layer **420** by applying a predetermined pressure or pressure/heat. Since the diffusion layer **430** is adhered to the resin layer **420** by self-adhesive force without a separate adhesive, it is possible to reduce the process of separately attaching the adhesive, and it is possible to avoid using an adhesive harmful to the human body, thereby reducing process or material waste.

(95) The material of the diffusion layer **430** may be a light-transmitting material. The diffusion layer **430** may include at least one of a polyester (PET) film, a poly methyl methacrylate (PMMA) material, or a polycarbonate (PC). The diffusion layer **430** may be provided as a film made of a resin material such as silicone or epoxy. The diffusion layer **430** may include a single layer or multiple layers.

(96) The diffusion layer **430** may diffuse the light emitted through the resin layer **420**. In addition, since a specific color may not be mixed when the luminous intensity of light is high, the diffusion layer **430** may diffuse and mix the lights.

(97) The thickness of the diffusion layer **430** may be about 25 μm or more. For example, the thickness of the diffusion layer **430** may be about 25 μm to about 250 μm . In detail, the thickness of the diffusion layer **430** may be about 100 μm to about 250 μm . The diffusion layer **430** may have the above-described thickness range and may provide incident light as a uniform surface light source.

(98) The diffusion layer **430** may include at least one or two or more of a diffusion agent such as beads, a phosphor, and ink particles. The phosphor may include, for example, at least one of a red phosphor, an amber phosphor, a yellow phosphor, a green phosphor, and a white phosphor. The ink particles may include at least one of metal ink, UV ink, and curing ink. The size of the ink particles may be smaller than the size of the phosphor. The surface color of the ink particles may be any one of green, red, yellow, and blue. The ink types may be selectively applied among PVC (Poly vinyl chloride) ink, PC (Polycarbonate) ink, ABS (acrylonitrile butadiene styrene copolymer) ink, UV resin ink, epoxy ink, silicone ink, PP (polypropylene) ink, water-based ink, plastic ink, PMMA (poly methyl methacrylate) ink and PS (Polystyrene) ink. The ink particles may include at least one of metal ink, UV ink, and curing ink.

(99) FIG. **10** is another cross-sectional view showing a cross-section taken along line A-A' of FIG. **5**, and FIG. **11** is an enlarged view of a region A3 of FIG. **10**. In the description using FIGS. **10** and **11**, descriptions of the same and similar components as those of the above-described lighting module are omitted, and the same reference numerals are assigned to the same and similar

components.

(100) Referring to FIGS. **10** and **11**, a light blocking portion **425** may be further disposed on the resin layer **420**. The light blocking portion **425** may face the upper surface of the substrate **401**. The light blocking portion **425** may be disposed between the resin layer **420** and the diffusion layer **430**. The light blocking portion **425** may overlap the light emitting device **100** in a third direction defined in the z-axis direction. The light blocking portion **425** may be printed by overlapping a plurality of layers on the lower surface of the diffusion layer **430**, and the light blocking portion **425** may have a structure including a plurality of patterns having different sizes.

(101) In addition, the light blocking portion **425** may be disposed to extend along an emission direction of the light emitted from the light emitting device **100**. For example, the light blocking portion **425** may be disposed to extend to a region in which the plurality of dots **411** are disposed. In this case, the light blocking portion **425** may not overlap the plurality of dots **411** in the third direction. That is, the light blocking portion **425** may partially overlap the light emitting device **100** and be formed in a region that does not overlap the plurality of dots **411**. Alternatively, the light blocking portion **425** may be disposed in a region where a part overlaps the light emitting device **100** and the other part overlaps the plurality of dots **411**. In this case, an area of the light blocking portion **425** overlapping the plurality of dots **411** may be less than or equal to about 30% of an area of the light blocking portion **425** not overlapping the plurality of dots **411**.

(102) A width of the light blocking portion **425** in the first direction may be greater than a width of the light emitting device **100** in the first direction. Also, a width of the light blocking portion **425** in the second direction may be greater than a width of the light emitting device **100** in the second direction.

(103) When viewed from the top, the planar shape of the light blocking portion **425** may have various shapes, such as a circular shape, an elliptical shape, and a polygonal shape. For example, the planar shape of the light blocking portion **425** may include a shape including a curve in consideration of the light beam angle of the light emitting device **100**.

(104) The number of the light blocking portions **425** may be the same as the number of the light emitting devices **100**. The light blocking portion **425** may be provided with a size or area sufficient to prevent a hot spot caused by the light emitted in the exit direction of the light emitting device **100** on each of the light emitting devices **100**. In addition, since the light emitting device **100** emits light in the side direction, that is, in the first direction, the light blocking portion **425** covers a region in which the light blocking efficiency by the light beam distribution and reflection characteristics of the light emitting device **100** may be increased.

(105) An adhesive layer **440** may be disposed around the light blocking portion **425**. The adhesive layer **440** may be disposed between the resin layer **420** and the diffusion layer **430**. The adhesive layer **440** may be disposed on the upper surface of the resin layer **420** in a region where the light blocking portion **425** is not disposed. The adhesive layer **440** may include a light-transmitting adhesive material. The adhesive layer **440** may adhere the resin layer **420** and the diffusion layer **430** to each other.

(106) FIG. **12** is another cross-sectional view showing a cross-section taken along line A-A' of FIG. **5**. In the description using FIG. **12**, descriptions of the same and similar components as those of the lighting module described above are omitted, and the same reference numerals are assigned to the same and similar components.

(107) Referring to FIG. **12**, a plurality of light emitting devices **100** may be disposed on the substrate **401**. The plurality of light emitting devices **100** may be of a top view type electrically connected to the substrate **401**. The plurality of light emitting devices **100** may be disposed on the substrate **401** at set intervals. For example, the plurality of light emitting devices **100** may be disposed at equal intervals in the first direction. Also, the plurality of light emitting devices **100** may be disposed at equal intervals in the second direction.

(108) Accordingly, the lighting module **400** including the plurality of light emitting devices **100**

may emit light as a surface light source. The lighting module **400** may emit light in a direction of an opened upper portion of the housing **300**.

(109) FIG. **13** is a front view illustrating a light emitting device on a substrate in a lighting module according to an embodiment, and FIG. **14** is a side view of the light emitting device of FIG. **13**.

(110) Referring to FIGS. **13** and **14**, the light emitting device **100** includes a body **10** having a cavity **20**, a plurality of lead frames **30** and **40** in the cavity **20**, and a light emitting chip **71** disposed on at least one of a plurality of lead frames **30** and **40**. The light emitting device **100** may be implemented as a side view type package.

(111) The body **10** may include a cavity **20** in which the lead frames **30** and **40** are exposed at the bottom. The plurality of lead frames **30** and **40** are separated into, for example, a first lead frame **30** and a second lead frame **40** and coupled to the body **10**.

(112) The body **10** may be formed of an insulating material. The body **10** may be formed of a reflective material. The body **10** may be formed of a material having a reflectance higher than a transmittance for a wavelength emitted from the light emitting chip, for example, a material having a reflectance of 70% or more. When the reflectivity is 70% or more, the body **10** may be defined as a non-transmissive material or a reflective material. The body **10** may be formed of a resin-based insulating material, for example, a resin material such as polyphthalamide (PPA). The body **10** may be formed of a silicone-based, epoxy-based, or thermosetting resin including a plastic material, or a high heat and light resistance material. The body **10** includes a white-based resin. An acid anhydride, an antioxidant, a mold release material, a light reflector, an inorganic filler, a curing catalyst, a light stabilizer, a lubricant, and titanium dioxide may be selectively added in the body **10**. The body **10** may be molded by at least one selected from the group consisting of an epoxy resin, a modified epoxy resin, a silicone resin, a modified silicone resin, an acrylic resin, and a urethane resin. For example, an epoxy resin composition which is formed by adding an epoxy resin composed of triglycidyl isocyanurate, hydrogenated bisphenol A diglycidyl ether, etc. and an acid anhydride composed of hexahydrophthalic anhydride, 3-methylhexahydrophthalic anhydride, 4-methylhexahydrophthalic anhydride, etc. with 1,8-diazabicyclo (5,4,0) undecene-7 (DBU) as a curing agent, ethylene glycol as a co-catalyst, titanium oxide pigment, and glass fiber in the epoxy resin, partially curing by heating, and a solid epoxy resin composition obtained by curing and forming B staging may be used, and the present invention is not limited thereto. The body **10** may be suitably mixed with at least one selected from the group consisting of a diffusing agent, a pigment, a fluorescent material, a reflective material, a light-blocking material, a light stabilizer, and a lubricant.

(113) The body **10** may include a reflective material, for example, a resin material to which a metal oxide is added, and the metal oxide may include at least one of TiO_2 , SiO_2 , and Al_2O_3 . This body **10** may effectively reflect incident light. As another example, the body **10** may be formed of a light-transmitting resin material or a resin material having a phosphor that converts the wavelength of incident light. The bottom of the body **10** may be a side surface corresponding to the substrate **401**.

(114) The first lead frame **30** includes a first lead portion **31** disposed on the bottom of the cavity **20**, a first bonding portion **32** and a first heat dissipating portion **33** extending outside the body **10**. The first bonding portion **32** is bent from the first lead portion **31** in the body **10** and protrudes outside the body, and the first heat dissipating portion **33** may be bent from the first bonding portion **32**.

(115) The second lead frame **40** includes a second lead portion **41** disposed at the bottom of the cavity **20**, a second bonding portion **42** and a second heat dissipating portion **43** disposed outside the body **10**. The second bonding portion **42** may be bent from the second lead part **41** in the body **10**, and the second heat dissipating portion **43** may be bent from the second bonding portion **42**.

(116) Here, the light emitting chip **71** may be disposed on the first lead portion **31** of the first lead frame **30**, for example, and connected to the first and second lead portions **31** and **41** by wire, or

may be connected with the first lead portion **31** and may be connected to the second lead portion **41** by a wire. The light emitting chip **71** may be a horizontal type chip, a vertical type chip, or a chip having a via structure. The light emitting chip **71** may be mounted in a flip chip manner. The light emitting chip **71** may selectively emit light within a wavelength range of ultraviolet to visible light. The light emitting chip **71** may emit light with an ultraviolet or blue peak wavelength, for example. The light emitting chip **71** may include at least one of a group II-VI compounds and a group III-V compounds. The light emitting chip **71** may be formed of, for example, a compound selected from the group consisting of GaN, AlGaN, InGaN, AlInGaN, GaP, AlN, GaAs, AlGaAs, InP, and mixtures thereof.

(117) One or a plurality of light emitting chips **71** may be disposed in the cavity **20** and emit light with the greatest intensity in the direction of the central axis Y0.

(118) One or a plurality of light emitting chips disposed in the cavity **20** of the light emitting device **100** according to the embodiment may be disposed. The light emitting chip may be selected from, for example, a red LED chip, a blue LED chip, a green LED chip, and a yellow green LED chip.

(119) A molding member **80** is disposed in the cavity **20** of the body **11**, and the molding member **80** includes a light-transmitting resin such as silicone or epoxy, and may be formed in a single layer or multiple layers. A phosphor for changing a wavelength of light emitted from the molding member **80** or the light emitting chip **71** may be included, and the phosphor excites a part of light emitted from the light emitting chip **71** and is emitted as light to have a different wavelength. The phosphor may be selectively formed from quantum dots, YAG, TAG, Silicate, Nitride, and Oxy-nitride-based materials. The phosphor may include at least one of a red phosphor, a yellow phosphor, and a green phosphor, but is not limited thereto. The emission surface **81** of the molding member **80** may be formed in a flat shape, a concave shape, a convex shape, and the like, but is not limited thereto. As another example, a light-transmitting film having a phosphor may be disposed on the cavity **20**, but the embodiment is not limited thereto.

(120) A lens may be further formed on the upper portion of the body **10**, and the lens may include a structure of a concave and/or convex lens, and may adjust the light distribution of the light emitted by the light emitting device **100**.

(121) A semiconductor device such as a light receiving device and a protection device may be mounted on the body **10** or any one lead frame, and the protection device may be implemented as a thyristor, a Zener diode, or a TVS (transient voltage suppression). The Zener diode protects the light emitting chip from electro static discharge (ESD).

(122) At least one or a plurality of light emitting devices **100** are disposed on the substrate **401**, and a reflective member **410** is disposed around a lower portion of the light emitting device **100**. The first and second lead portions **33** and **43** of the light emitting device **100** are bonded to the pads **403** and **405** of the substrate **401** with solder or conductive tape as conductive adhesive members **203** and **205**.

(123) The optical assembly **10** according to the embodiment may be used as a rear-view mirror assembly of a vehicle. For example, the optical assembly **10** may be disposed on the left and right-side mirrors of the vehicle to provide vehicle information located on the rear side to the driver.

(124) FIG. **15** is an exploded perspective view of the rear-view mirror assembly according to the embodiment, and FIG. **16** is a cross-sectional view of the rear-view mirror assembly according to the embodiment. In addition, FIG. **17** is a top view of the blocking member according to the embodiment.

(125) In the description of FIGS. **15** to **17**, a structure in which the optical assembly **10** is applied to the left-side mirror adjacent to the driver's seat will be described. In the case of the right-side mirror adjacent to the passenger seat, the components of the optical assembly **10** is symmetrical to each other in the same shape, so for convenience of description, the structure applied to the left-side mirror adjacent to the driver's seat will be centered.

(126) Referring to FIGS. **15** to **17**, the rear-view mirror assembly **2000** may include a cover case

810, a mirror member **820**, and an optical assembly **10**.

(127) The cover case **810** may be exposed to the outside of the vehicle. For example, the cover case **810** may be a cover of a side mirror disposed on the left and right-sides of the vehicle, respectively. The cover case **810** may include a material having predetermined rigidity and reliability. The cover case **810** may include a material capable of maintaining reliability from the outside in a vehicle stopping or driving environment.

(128) The cover case **810** may include an opened one side and a receiving space **805** therein. The cover case **810** may accommodate the optical assembly **10** and the mirror member **820**.

(129) The mirror member **820** may be disposed in the receiving space **805** of the cover case **810**. The mirror member **820** may be disposed so that a bottom surface **821** of the mirror member **820** faces the receiving space **805**. An upper surface **822** of the mirror member **820** may be exposed to the outside. The bottom surface **821** and the upper surface **822** of the mirror member **820** may be provided as at least one of a flat surface and a curved surface. The mirror member **820** may be a semi-transparent member including a mirror or a display. The mirror member **820** may transmit the light emitted from the optical assembly **10**. For example, a partial region of the mirror member **820**, for example, a region overlapping the optical assembly **10** may transmit light emitted from the optical assembly **10**.

(130) The optical assembly **10** may be disposed in the receiving space **805** of the cover case **810**. The optical assembly **10** may be disposed between the mirror member **820** and the cover case **810**. For example, the optical assembly **10** may be disposed on the bottom surface **821** of the mirror member **820** facing the receiving space **805** of the cover case **810**. The optical assembly **10** may emit light in the direction of the opened region of the cover case **810**. The optical assembly **10** may emit light toward the bottom surface **821** of the mirror member **820**.

(131) In this case, the height between the lighting module **400** and the mirror member **820** may change. The vertical direction (V-axis direction) height between the upper surface of the lighting module **400** and the lower surface **821** of the mirror member **820** may increase in a direction from the first inner surface IS1 to the second inner surface IS2. In addition, although not shown in the drawings, the vertical (V-axis direction) height between the upper surface of the lighting module **400** and the lower surface **821** of the mirror member **820** may decrease in a direction from the third inner surface IS3 to the fourth inner surface IS4. And, the vertical height between the upper surface of the lighting module **400** and the lower surface **821** of the mirror member **820** may increase in a direction from the second intersection point P2 of the lighting module **400** to the fifth side surface S5.

(132) A blocking member **700** may be disposed on the optical assembly **10**. The blocking member **700** may be disposed between the optical assembly **10** and the mirror member **820**. The blocking member **700** may be disposed in a region overlapping the optical assembly **10**. The blocking member **700** may directly contact the bottom surface **821** of the mirror member **820**.

(133) The blocking member **700** may include an opening region **710** and a non-transmissive region **720**.

(134) The opening region **710** may be a region through which the light emitted from the optical assembly **10** is transmitted. That is, the light emitted from the optical assembly **10** may be emitted in the direction of the mirror member **820** through the opening region **710** and may be provided to the outside.

(135) In addition, the non-transmissive region **720** may be a region other than the opening region **710**, and may be a region through which the light emitted from the optical assembly **10** is not transmitted. For example, the non-transmissive region **720** may be implemented using black or white ink.

(136) That is, the opening region **710** may be an effective region through which light is transmitted, and the non-transmissive region **720** may be an ineffective region through which light is not transmitted.

(137) In this case, the light emitting device **100** of the optical assembly **10** may be disposed in a region overlapping the blocking member **700** in a vertical direction (V-axis direction). Here, the vertical direction (V-axis direction) may mean a height direction of the housing **300**.

(138) In detail, the light emitting device **100** may be disposed in a region that does not overlap the opening region **710** of the blocking member **700** in a vertical direction (V-axis direction), and may be overlapped with a vertical direction with the non-transmissive region **720**.

(139) Also, the opening region **710** may be disposed in a region overlapping the plurality of dots **411** of the reflective member **410** in a vertical direction (V-axis direction). For example, the opening region **710** may vertically overlap the region R1 in which the plurality of dots **411** are disposed. In this case, the light emitted from the light emitting device **100** may be reflected by the dots **411** to be effectively emitted in the direction of the opening region **710**. Accordingly, loss of light emitted from the optical assembly **10** may be minimized.

(140) In addition, when the optical assembly **10** includes the light blocking portion **425** as shown in FIG. **10**, the light blocking portion **425** may be disposed in a region not overlap the opening region **710** of the blocking member **700** in the vertical direction (V-axis direction), and may be vertically overlapped with the non-transmissive region **720**. Accordingly, it is possible to guide the light emitted from the light emitting device **100** to be emitted in the direction of the opening region **710**.

(141) Accordingly, in the embodiment, the loss of light emitted from the light emitting device **100** may be minimized, and the direction and luminance value of light emitted to the outside of the mirror member **820** through the opening region **710** may be controlled.

(142) The rear-view mirror assembly **2000** may include an indicator portion **850**. The indicator portion **850** may have a shape such as a logo, text, or icon. The indicator portion **850** may be formed on the mirror member **820**. In detail, the indicator portion **850** may be formed in a region of the mirror member **820** that vertically overlaps with the opening region **710** of the blocking member **700**. The indicator portion **850** may vertically overlap with the region R1 in which the plurality of dots **411** are disposed. The indicator portion **850** may be provided as an opening portion in the mirror member **820** or may be implemented using colored ink.

(143) Accordingly, the light emitted from the optical assembly **10** may pass through the opening region **710** and the indicator portion **850**, and a shape of the indicator portion **850** may be visually recognized from the outside of the mirror member **820**.

(144) In addition, the indicator portion **850** may be haze-treated. Accordingly, when light is not emitted from the optical assembly **10**, the optical assembly **10** may not be viewed from the outside of the mirror member **820**.

(145) Also, although not shown in the drawings, the indicator portion **850** may be formed on the blocking member **700**. In detail, the indicator portion **850** may be formed in the opening region **710** of the blocking member **700**. Accordingly, the light emitted from the optical assembly **10** may pass through the indicator portion **850** formed in the opening region **710**, and a shape of the indicator portion **850** may be visually recognized from the outside of the mirror member **820**.

(146) Also, although not shown in the drawings, the indicator portion **850** may be formed on the mirror member **820** and the blocking member **700**. In detail, the indicator portion **850** may be formed in an opening region **710** of the blocking member **700** and a region of the mirror member **820** corresponding to the opening region **710**, respectively. Accordingly, the shape of the indicator portion **850** visually recognized from the outside of the mirror member **820** may have a three-dimensional effect.

(147) The rear-view mirror assembly **2000** may include a sensing unit (not shown) and a control unit (not shown).

(148) The sensing unit may include a radar, a laser, a sound wave, an image sensor, and the like, and may be disposed at the rear and/or side of the vehicle. The sensing unit may detect another vehicle located at the rear and/or side of the vehicle.

(149) The control unit is connected to the sensing unit and may control the operation of the optical

assembly **10**. For example, when there is another vehicle on the rear side of the vehicle, the sensing unit may detect information about the vehicle. Thereafter, the sensing unit may provide the sensed information to the control unit. Subsequently, the control unit may apply a signal for light emission ON to the optical assembly **10**. Accordingly, the driver of the vehicle may visually recognize the shape of the logo and/or icon displayed on the upper surface **822** of the mirror member **820** through the optical assembly **10** and the blocking member **700**, and information about the presence of another vehicle on the rear side of the vehicle may be provided.

(150) Also, when the other vehicle disappears from the side and rear of the vehicle in which the driver is riding, the sensing unit may detect information about the other vehicle. Thereafter, the sensing unit may provide the sensed information to the control unit, and the control unit may apply a signal for turning off light emission to the optical assembly **10**.

(151) In this case, the lighting module **400** according to the embodiment may be inclined. In detail, an upper surface of the optical assembly **10** may contact the blocking member **700**, and an upper surface of the blocking member **700** may contact a bottom surface **821** of the mirror member **820**.

(152) Accordingly, the lighting module **400** of the optical assembly **10** may be disposed to be inclined with respect to the bottom surface **821** of the mirror member **820**. In detail, based on the direction from the first inner surface IS1 toward the second inner surface IS2, the lighting module **400** may be inclined at the first inclination angle $\alpha 1$. In addition, the lighting module **400** may be inclined at the second inclination angle $\alpha 2$ from the third inner surface IS3 toward the fourth inner surface IS4. That is, the lighting module **400** may be inclined in the direction of the fifth inner surface IS5 at the first intersection point P1 of the housing **300**. In more detail, the bottom surface **310** of the housing **300** may be inclined as described above, and the lighting module **400** and the optical member **500** disposed on the bottom surface **310** may have an inclined shape at an inclination angle within the above-described range.

(153) Accordingly, the rear-view mirror assembly **2000** according to the embodiment minimizes light loss and maximizes the amount of light emitted through the mirror member **820**, and an exit direction of the emitted light and a luminance value of the light according to the exit direction may be controlled.

(154) FIG. **18** is a view for explaining an exit angle of light emitted from the rear-view mirror assembly according to the embodiment. In the description of FIG. **18**, the description will be given of application to the left-side mirror adjacent to the driver's seat. In the case of the right-side mirror adjacent to the passenger seat, since the components including the optical assembly **10** are symmetrical to each other in the same shape, for convenience of description, the structure applied to the left-side mirror will be centered.

(155) Referring to FIG. **18**, the rear-view mirror assembly **2000** according to the embodiment may provide the driver with vehicle information located on the rear side. For example, in a region overlapping the optical assembly **10**, the first region R1 and the second region R2 may be divided based on a virtual line L1 extending in a direction perpendicular to the extension direction of the rear-view mirror assembly **2000**. Here, the first region R1 may be a region in which the driver **1** is located, and the second region R2 may be a region in which another vehicle **2** or an object located at the rear side of the vehicle in which the driver **1** is boarded is located.

(156) In the rear-view mirror assembly **2000** according to the embodiment, when another vehicle **2** is located in the second region R2, the light emitted from the optical assembly **10** may be emitted to the outside through the blocking member **700** and the mirror member **820**.

(157) In this case, the lighting module **400** may be disposed to be inclined with respect to the bottom surface **310** of the mirror member **820** as described above. For example, the lighting module **400** may be disposed to be inclined in a direction corresponding to the first region R1 in which the driver **1** is located. Accordingly, the light emitted from the rear-view mirror assembly **2000** through the mirror member **820** may be emitted in a set direction and may have different luminance values according to the exit direction.

(158) For example, the luminance value of the light emitted in the direction of the first region R1 where the driver **1** is located may be different from the luminance value of the light emitted in the direction of the second region R2 where the other vehicle **2** is located. In detail, the luminance value of the light emitted in the direction of the first region R1 may be greater than the luminance value of the light emitted in the direction of the second region R2.

(159) Accordingly, the rear-view mirror assembly **2000** according to the embodiment may provide a high-luminance light to the driver **1** located in the first region R1. In addition, the rear-view mirror assembly **2000** may provide light of a relatively low luminance to the other vehicle **2** in the second region R2 located at the rear side of the vehicle of the driver **1**.

(160) Accordingly, the driver **1** may effectively visually recognize the shape of the indicator portion **850**. In addition, the light emitted from the rear-view mirror assembly **2000** in the direction of the other vehicle **2** positioned at the rear side of the driver **1** may be minimized. Accordingly, it is possible to minimize or prevent the driver of the other vehicle **2** from being disturbed by the light.

(161) Features, structures, effects, and the like described in the embodiments above are included in at least one embodiment of the invention, and are not necessarily limited to only one embodiment. Furthermore, the features, structures, effects, and the like illustrated in each embodiment may be combined or modified for other embodiments by a person having ordinary knowledge in the field to which the embodiments belong. Accordingly, contents related to such combinations and modifications should be construed as being included in the scope of the invention.

(162) In addition, although the examples have been described above, these are only examples and do not limit the invention, and those of ordinary skill in the field to which the invention pertains are illustrated above within the scope not departing from the essential characteristics of the present embodiment. It will be seen that various modifications and applications that have not been made are possible. For example, each component specifically shown in the embodiment can be modified and implemented. And differences related to these modifications and applications should be construed as being included in the scope of the invention defined in the appended claims.

Claims

1. An optical assembly comprising: a housing including defining a receiving space therein, the housing including: an upper surface; and a bottom surface which is not parallel to the upper surface; a substrate disposed on a bottom surface of the receiving space of the housing; a light emitting device disposed on the substrate; a resin layer disposed on the substrate and covering the light emitting device; an optical member disposed on an upper surface of the resin layer; and a cover member disposed on the optical member, wherein the substrate, the light emitting device, the resin layer, and the cover member are disposed in the receiving space of the housing, wherein at least an upper surface of the substrate and an upper surface of the resin layer are parallel to each other, wherein the substrate includes a first side surface and a second side surface opposite the first side surface, wherein a distance between an upper surface of the cover member and an upper end of the first side surface of the substrate is smaller than a distance between the upper surface of the cover member and an upper end of the second side surface of the substrate in a direction perpendicular to the upper surface of the cover member, and wherein the light emitting device is located closer to the first side surface of the substrate than to the second side surface of the substrate.
2. The optical assembly of claim 1, wherein lower surfaces of the cover member and the optical member are planar, and at least a portion of the lower surface of the cover member is linearly inclined to have regions having different thicknesses.
3. The optical assembly of claim 1, comprising a reflective member disposed between the resin layer and the substrate.
4. The optical assembly of claim 3, comprising a plurality of dots disposed on an upper surface of the

reflective member.

5. The optical assembly of claim 4, wherein the plurality of dots and the upper surface of the reflective member are in contact with the resin layer.

6. The optical assembly of claim 1, wherein the bottom surface of the housing is inclined such that the receiving space of the housing includes regions with different depths from the upper surface of the housing.

7. The optical assembly of claim 1, wherein the upper surface of the cover member is not parallel to the upper surface of the resin layer.

8. The optical assembly of claim 1, comprising: a blocking member disposed on the cover member, wherein the blocking member includes an opening region and a non-transmissive region, and wherein the opening region of the blocking member is a region through which light emitted from the resin layer is transmitted.

9. The optical assembly of claim 8, wherein the non-transmissive region of the blocking member overlaps the light emitting device in the direction perpendicular to the upper surface of the cover member.

10. The optical assembly of claim 1, wherein the housing includes a plurality of inner side surfaces, wherein at least two of the plurality of inner side surfaces have different depths.

11. The optical assembly of claim 1, wherein the optical assembly includes a rear-view mirror assembly of a vehicle.

12. The optical assembly of claim 11, comprising a mirror member disposed on the housing.
