

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12410603
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Richards; Paul William

Column-to-beam connection systems including a shear component

Abstract

Column-to-beam connection systems are disclosed herein, along with moment-resisting frames including the same and methods of repairing the same. An example column-to-beam connection system includes a shear component. The shear component includes a base plate that is connected to a column flange. The shear component also includes at least one vertical web extending from the base plate. The vertical web is connected to with a beam flange. The vertical web also defines one or more openings therein.

Inventors:	Richards; Paul William (Orem, UT)
Applicant:	DURAFUSE FRAMES, LLC (West Jordan, UT)
Family ID:	74570397
Assignee:	DURAFUSE FRAMES, LLC (West Jordan, UT)
Appl. No.:	17/633677
Filed (or PCT Filed):	August 05, 2020
PCT No.:	PCT/US2020/044982
PCT Pub. No.:	WO2021/030111
PCT Pub. Date:	February 18, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20220316202 A1	Oct. 06, 2022

Related U.S. Application Data

us-provisional-application US 62884901 20190809

Publication Classification

Int. Cl.: E04B1/24 (20060101); E04H9/02 (20060101)

U.S. Cl.:

CPC E04B1/2403 (20130101); E04H9/024 (20130101); E04B2001/2445 (20130101); E04B2001/2448 (20130101); E04B2001/2457 (20130101); E04B2001/2496 (20130101)

Field of Classification Search

CPC: E04B (1/2403); E04B (2001/2445); E04B (2001/2448); E04B (2001/2457); E04B (2001/2496); E04H (9/024)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1727293	12/1928	Andrew	N/A	N/A
4014089	12/1976	Sato et al.	N/A	N/A
4926592	12/1989	Nehls	N/A	N/A
5148642	12/1991	Plumier et al.	N/A	N/A
5660017	12/1996	Houghton	N/A	N/A
6073405	12/1999	Kasai et al.	N/A	N/A
6138427	12/1999	Houghton	N/A	N/A
6264162	12/2000	Barnes et al.	N/A	N/A
6739099	12/2003	Takeuchi et al.	N/A	N/A
7040069	12/2005	Simmons	N/A	N/A
7530205	12/2008	Simmons	N/A	N/A
8683758	12/2013	Christopoulos et al.	N/A	N/A
8800239	12/2013	Yang	N/A	N/A
8875452	12/2013	Kawai et al.	N/A	N/A
9091065	12/2014	Tran et al.	N/A	N/A
9163424	12/2014	Montgomery et al.	N/A	N/A
9200442	12/2014	Richards	N/A	N/A
9441360	12/2015	Matteson	N/A	N/A
9464427	12/2015	Karns	N/A	N/A
9506239	12/2015	Houghton	N/A	N/A
9514907	12/2015	Mcmanus et al.	N/A	N/A
10316507	12/2018	Richards	N/A	N/A
10584477	12/2019	Richards	N/A	N/A
10669718	12/2019	Pryor et al.	N/A	N/A
10689876	12/2019	Richards	N/A	N/A
10760261	12/2019	Richards	N/A	N/A
11162260	12/2020	Pryor	N/A	N/A
11479988	12/2021	Curtis	N/A	N/A
11808026	12/2022	Zhao et al.	N/A	N/A
12359420	12/2024	Richards	N/A	E04B 1/2403
2002/0184836	12/2001	Takeuchi et al.	N/A	N/A

2004/0050013	12/2003	Okada et al.	N/A	N/A
2004/0144006	12/2003	Chu	N/A	N/A
2004/0200178	12/2003	Simmons	N/A	N/A
2004/0237456	12/2003	Simmons	N/A	N/A
2005/0055970	12/2004	Simmons	N/A	N/A
2005/0204684	12/2004	Houghton	N/A	N/A
2006/0144006	12/2005	Suzuki et al.	N/A	N/A
2006/0265992	12/2005	Hiragaki	N/A	N/A
2009/0223166	12/2008	Ohata et al.	N/A	N/A
2010/0205876	12/2009	Christopoulos et al.	N/A	N/A
2010/0205891	12/2009	Bong et al.	N/A	N/A
2011/0030305	12/2010	Karns	N/A	N/A
2012/0017523	12/2011	Ozaki et al.	N/A	N/A
2013/0074427	12/2012	Kawai et al.	N/A	N/A
2014/0062648	12/2013	McManus et al.	N/A	N/A
2014/0182234	12/2013	Yang	N/A	N/A
2014/0325932	12/2013	Karns et al.	N/A	N/A
2015/0096244	12/2014	Richards	N/A	N/A
2015/0101268	12/2014	Montgomery et al.	N/A	N/A
2015/0275501	12/2014	Houghton	N/A	N/A
2016/0208478	12/2015	Matteson	N/A	N/A
2016/0215492	12/2015	Karns	N/A	N/A
2016/0356033	12/2015	Houghton et al.	N/A	N/A
2017/0268252	12/2016	Gray et al.	N/A	N/A
2018/0266099	12/2017	Lippert	N/A	N/A
2018/0274223	12/2017	Richards	N/A	N/A
2018/0347222	12/2017	Richards	N/A	N/A
2019/0040645	12/2018	Zhao et al.	N/A	N/A
2019/0292783	12/2018	Pryor et al.	N/A	N/A
2020/0109556	12/2019	Pryor	N/A	N/A
2021/0079681	12/2020	Pryor et al.	N/A	N/A
2022/0154445	12/2021	Zhao et al.	N/A	N/A
2022/0333369	12/2021	Richards	N/A	E04B 1/2403
2022/0333397	12/2021	Richards	N/A	N/A
2023/0058224	12/2022	Evans et al.	N/A	N/A
2023/0110886	12/2022	Abela	N/A	N/A
2023/0117355	12/2022	Robinson	N/A	N/A
2023/0175248	12/2022	Richards	N/A	N/A
2024/0076892	12/2023	Gray	N/A	E04B 1/2403
2024/0392567	12/2023	Felix	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
201400272	12/2013	CL	N/A
201503172	12/2015	CL	N/A
201503173	12/2018	CL	N/A
109723145	12/2018	CN	N/A
3387196	12/2019	EP	N/A
2000144901	12/1999	JP	N/A
2002364068	12/2001	JP	N/A

2006233445	12/2005	JP	N/A
6876510	12/2020	JP	N/A
20040106829	12/2003	KR	N/A
100516332	12/2004	KR	N/A
101344813	12/2012	KR	N/A
20140039385	12/2013	KR	N/A
101406485	12/2013	KR	N/A
20140105643	12/2013	KR	N/A
2014085680	12/2013	WO	N/A
2016036564	12/2015	WO	N/A
2017100453	12/2016	WO	N/A
2019040297	12/2018	WO	N/A
2021030111	12/2020	WO	N/A

OTHER PUBLICATIONS

Amendment filed by Applicant in counterpart Canadian Application No. 3,146,932 (8 pages).
(Year: 2025). cited by examiner

Non-Final Office Action for U.S. Appl. No. 17/715,418 mailed Sep. 22, 2023. cited by applicant

Corrected Notice of Allowance for U.S. Appl. No. 15/500,991 mailed May 8, 2019. cited by applicant

Corrected Notice of Allowance for U.S. Appl. No. 16/394,665 mailed Feb. 11, 2020. cited by applicant

International Search Report and Written Opinion from International Application No. PCT/US2015/047006 mailed Nov. 23, 2015. cited by applicant

International Search Report and Written Opinion from International Application No. PCT/US2016/065623 mailed Mar. 10, 2017. cited by applicant

International Search Report and Written Opinion from International Application No. PCT/US2018/046222 mailed Nov. 14, 2018. cited by applicant

International Search Report and Written Opinion from International Application No. PCT/US2020/044982 mailed Oct. 26, 2020. cited by applicant

Issue Notification for U.S. Appl. No. 15/500,991 mailed May 22, 2019. cited by applicant

Issue Notification for U.S. Appl. No. 15/516,834 mailed Aug. 12, 2020. cited by applicant

Issue Notification for U.S. Appl. No. 16/394,665 mailed Feb. 19, 2020. cited by applicant

Non-Final Office Action for U.S. Appl. No. 15/500,991 mailed Jan. 18, 2018. cited by applicant

Non-Final Office Action for U.S. Appl. No. 15/516,834 mailed Aug. 30, 2018. cited by applicant

Non-Final Office Action for U.S. Appl. No. 16/101,075 mailed Jun. 27, 2019. cited by applicant

Notice of Allowance for U.S. Appl. No. 15/500,991 mailed Jun. 18, 2018. cited by applicant

Notice of Allowance for U.S. Appl. No. 15/500,991 mailed Oct. 2, 2018. cited by applicant

Notice of Allowance for U.S. Appl. No. 15/516,834 mailed Apr. 1, 2020. cited by applicant

Notice of Allowance for U.S. Appl. No. 15/516,834 mailed Dec. 23, 2019. cited by applicant

Notice of Allowance for U.S. Appl. No. 15/516,834 mailed Jun. 26, 2019. cited by applicant

Notice of Allowance for U.S. Appl. No. 15/516,834 mailed Mar. 8, 2019. cited by applicant

Notice of Allowance for U.S. Appl. No. 16/101,075 mailed Feb. 2020. cited by applicant

Notice of Allowance for U.S. Appl. No. 16/394,665 mailed Oct. 30, 2019. cited by applicant

Supplemental Notice of Allowability for U.S. Appl. No. 15/516,834 mailed Apr. 29, 2020. cited by applicant

Supplemental Notice of Allowability for U.S. Appl. No. 16/101,075 mailed May 28, 2020. cited by applicant

U.S. Appl. No. 15/500,991, filed Feb. 1, 2017. cited by applicant

U.S. Appl. No. 15/516,834, filed Apr. 4, 2017. cited by applicant

U.S. Appl. No. 62/044,738, filed Sep. 2, 2014. cited by applicant
U.S. Appl. No. 62/265,362, filed Dec. 9, 2015. cited by applicant
U.S. Appl. No. 62/549,853, filed Aug. 24, 2017. cited by applicant
U.S. Appl. No. 62/884,901, filed Aug. 9, 2019. cited by applicant
U.S. Appl. No. 63/174,663, filed Apr. 14, 2021. cited by applicant
Advisory Action for U.S. Appl. No. 17/715,418 mailed Jun. 13, 2024. cited by applicant
Final Office Action for U.S. Appl. No. 17/715,418 mailed Apr. 1, 2024. cited by applicant
Non-Final Office Action for U.S. Appl. No. 17/715,418 mailed Aug. 15, 2024. cited by applicant
Notice of Allowance for U.S. Appl. No. 17/71,429 mailed Jul. 9, 2024. cited by applicant
Notice of Allowance for U.S. Appl. No. 17/715,429 mailed Oct. 15, 2024. cited by applicant
U.S. Appl. No. 63/174,706, filed Apr. 14, 2021. cited by applicant
Notice of Allowance for U.S. Appl. No. 17/715,418 mailed Jan. 28, 2025. cited by applicant
Notice of Allowance for U.S. Appl. No. 17/715,429 mailed Feb. 3, 2025. cited by applicant
Issue Notification for U.S. Appl. No. 17/715,429 mailed Jul. 2, 2025. cited by applicant

Primary Examiner: Mintz; Rodney

Attorney, Agent or Firm: Ballard Spahr LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This is a U.S. National Stage application of PCT International Application No. PCT/US2020/044982 filed on Aug. 5, 2020, which claims priority to U.S. Provisional Application No. 62/884,901 filed on Aug. 9, 2019, the disclosure of each of which is incorporated, in its entirety, by this reference.

BACKGROUND

(1) To resist wind and seismic loads, steel buildings may require braced frames, shear walls, or moment-resisting frames. Braced frames and shear walls may interfere with architectural features (open hallways, unobstructed windows, flexible floorplans) while moment-resisting frames may be more accommodating. Moment-resisting frames can rely on stiff and strong connections between the beams and columns to provide overall building stiffness and strength. However, moment-resisting frames may be more expensive than braced frames or shear walls because they are inherently less efficient and require more steel and expensive connections. It is desirable to develop steel moment-resisting frames that are economical to produce.

(2) In addition, most moment-resisting frames are designed such that during earthquake loading the beams will yield and absorb damaging earthquake energy. This method of absorbing energy (beam yielding) can prevent building collapse and protect occupants, but makes buildings difficult or impractical to repair.

SUMMARY

(3) In an embodiment, a column-to-beam connection system is disclosed. The column-to-beam connection system including a shear component configured to connect a flange of a beam to a flange of a column. The shear component includes a base plate configured to be connected to the flange of the column and at least one vertical web extending from the base plate. The at least one vertical web defines one or more openings therein.

(4) In an embodiment, a moment-resisting frame is disclosed. The moment-resisting frame includes a column having a flange. The column flange exhibits a column width measured from a first edge of the column flange to a second edge of the column flange, wherein the second edge is opposite the first edge. The moment-resisting frame also includes a beam including a first beam flange and a

second beam flange opposite the first beam flange. The moment-resisting frame also includes a column-to-beam connection system connecting the beam to the column. The column-to-beam connection system includes a shear component configured to connect the column flange to the first beam flange. The shear component includes a base plate configured to be connected to the column flange and at least one vertical web extending from the base plate. The at least one vertical web defines one or more openings therein.

(5) In an embodiment, a method to repair a moment-resisting frame is disclosed. The method includes removing at least a portion of a shear component from the moment-resisting frame. The shear component connecting a column flange to a beam flange. The shear component including a base plate connected to the column flange and at least one vertical web extending from the base plate. The at least one vertical web defines one or more openings therein. The at least a portion of the shear component includes at least one yielded region that is adjacent to the one or more openings. The method also includes attaching a replacement component to the rest of the moment-resisting frame. The replacement component is substantially the same as the at least a portion of the shear component before the shear component yielded.

(6) Features from any of the disclosed embodiments may be used in combination with one another, without limitation. In addition, other features and advantages of the present disclosure will become apparent to those of ordinary skill in the art through consideration of the following detailed description and the accompanying drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The drawings illustrate several embodiments of the present disclosure, wherein identical reference numerals refer to identical or similar elements or features in different views or embodiments shown in the drawings.

(2) FIGS. 1A and 1B are side and front views, respectively, of a portion of a moment-resisting frame that includes a column-to-beam connection system, according to an embodiment.

(3) FIG. 1C is a side view of the moment-resisting frame shown in FIGS. 1A-1B when a load is applied to the moment-resisting frame, according to an embodiment.

(4) FIGS. 2A and 2B are side and front views, respectively, of a portion of a moment-resisting frame including a column-to-beam connection system, according to an embodiment.

(5) FIG. 3A to 3C are side, front, and top views, respectively, of a portion of a moment-resisting frame including a column-to-beam connection system, according to an embodiment.

(6) FIG. 3D is a front view of a moment-resisting frame including a column-to-beam connection system, according to an embodiment.

(7) FIGS. 4A and 4B are side and front views of a portion of a moment-resisting frame including a column-to-beam connection system, according to an embodiment.

(8) FIG. 5 is a side view of a portion of a partially restrained moment-resisting frame including a column-to-beam connection system, according to an embodiment.

(9) FIG. 6 is a side view of a portion of a moment-resisting frame including a column-to-beam connection system, according to an embodiment.

(10) FIG. 7 is an isometric view of a moment-resisting frame, according to an embodiment.

(11) FIG. 8 is a flow chart of a method of repairing a shear component, according to an embodiment.

DETAILED DESCRIPTION

(12) Column-to-beam connection systems are disclosed herein, along with moment-resisting frames including the same and methods of repairing the same. An example column-to-beam connection system includes a shear component (e.g., a structural shear fuse). The shear component

includes a base plate that is connected to a column flange. The shear component also includes at least one vertical web extending from the base plate. The vertical web is connected to with a beam flange. The vertical web also defines one or more openings therein. As used herein, “connected to” may refer to actually connecting a component to another component or that a component is configured to be connected to another component. Further, “connected to” may refer to directly connecting a component to another component, indirectly connecting a component to another component, or both directly and indirectly connecting a component to another component.

(13) The column-to-beam connection systems disclosed herein may form part of a moment-resisting frame. For example, the moment-resisting frame may include a column having at least one column flange and a beam having at least one beam flange. The column-to-beam connection system may couple the column to the beam. For example, the base plate may be connected to the column flange while the vertical web may be connected to the beam flange. The column-to-beam connection system may also couple the column to the beam using other attachment techniques, without limitation. For example, the column-to-beam connection system may include a shear tab, a top plate, one or more welds, an end plate, etc.

(14) During loading, the moment-resisting frame may bend (e.g., flex, move, or otherwise strain). Bending the moment-resisting frame may cause the shear component of the column-to-beam connection system to be subjected to large shear forces. In particular, the vertical web of the shear component may be subjected to the large shear forces. The one or more openings formed in the vertical shear web may weaken parts of the vertical shear web such that the vertical shear web selectively and/or preferentially yields (e.g., buckles, fails, or otherwise deforms), in shear, during the loading. Yielding the vertical shear web absorbs at least some of the load which, in turn, may be sufficient to prevent other portions of the moment-resisting frame from yielding. Further, yielding the vertical web of the shear component may facilitate repair of the moment-resisting frame. For example, at least a portion of the shear component may be removed from the moment-resisting frame and replaced while other portions of the column-to-beam connection system maintain the structural integrity of the moment-resisting frame.

(15) FIGS. 1A and 1B are side and front views, respectively, of a portion of a moment-resisting frame **100** that includes a column-to-beam connection system, according to an embodiment. The moment-resisting frame **100** includes a column **104** having a first column flange **106** and a beam **108** having a first beam flange **110** and a second beam flange **112** opposite the first beam flange **110**. The beam **108** is connected to the first column flange **106** using the column-to-beam connection system. The column-to-beam connection system includes a shear component **114** connected to the column flange **106** and the first beam flange **110**. The column-to-beam connection system may include other components such as, as illustrated, a shear tab **116** that connects a web **118** of the beam **108** to the first column flange **106** and a weld (not shown, obscured) that connects the second beam flange **112** to the first column flange **106**. However, it is noted that the column-to-beam connection system may include other components as disclosed herein or as known in the art.

(16) In an embodiment, as illustrated and discussed herein, the column-to-beam connection system is connected to the column **104** and the beam **108**. In an embodiment, the column-to-beam connection system is not connected to the column **104** and/or the beam **108**, such as when the column-to-beam connection system is provided but before the column-to-beam connection system is connected to the column **104** and/or the beam **108**. In such an embodiment, the components of the column-to-beam connection system are configured to be connected to the column **104** and/or the beam **108** instead of actually connected to the column **104** and/or the beam **108**, as disclosed herein.

(17) In an embodiment, as shown, at least one of the column **104** or the beam **108** is an I-beam. In an example, the column **104** may include the first column flange **106**, a second column flange **122** opposite the first column flange **106**, and a column web **124** extending between the first column flange **106** and the second column flange **122**. The first column flange **106** may be connected to the

beam **108**. The second column flange **122** may not be connected to another beam (as shown) or may be connected to another beam (not shown). In an example, the beam **108** may include the first beam flange **110**, the second beam flange **112**, and the beam web **118** extending between the first beam flange **110** and the second beam flange **112**. In an embodiment, at least one of the column **104** or the beam **108** is not an I-beam. In such an embodiment, at least one of the column **104** or the beam **108** may include a hollow structural section, a T-beam, a double I-beam, or another other suitable structural beam.

(18) The column **104** is connected to the beam **108** using the column-to-beam connection system. The column-to-beam connection system includes a shear component **114**. The shear component **114** includes a base plate **126** and at least one vertical web **128**. The base plate **126** generally extends in a horizontal direction that is, for example, generally parallel to the first and/or second beam flange **110**, **112**. The base plate **126** is configured to be connected to the first column flange **106**. The vertical web **128** generally extends from the base plate **126** in a vertical direction that is, for example, generally perpendicular to the base plate **126** (e.g., is generally parallel to the column web **124** and/or the beam web **118**). The vertical web **128** may be integrally formed with the base plate **126** (e.g., the shear component **114** is formed from a single piece), welded to the base plate **126**, or connected to the base plate **126** using any suitable connection. The vertical web **128** is also connected to the first beam flange **110**. In an embodiment, the shear component **114** may be a T-beam.

(19) The base plate **126** and the vertical web **128** may be connected to the first column flange **106** and the first beam flange **110**, respectively, using any suitable connection. In an embodiment, at least one of the base plate **126** is connected to the first column flange **106** via a weld or the vertical web **128** is connected to the first beam flange **110** via a weld **132**. The welds may decrease the cost of connecting the column **104** to the beam **108** in certain locations, such as Central and South America where welding is cheaper than bolts. Further, the shear component **114** may be welded to one of the column **104** or the beam **108** offsite (e.g., in a welding shop) and then transported to the worksite to form the moment-resisting frame **100**. Welding the shear component **114** to the first column flange **106** or the first beam flange **110** offsite may be performed cheaper, quicker, and more efficiently than if the welding was performed at the worksite. In an embodiment, at least one of the base plate **126** is connected to the first column flange **106** or the vertical web **128** is connected to the first beam flange **110** using bolts or another suitable connection. In such an embodiment, the bolts may decrease the cost of connecting the column **104** to the beam **108** in certain locations, such as in the United States of America. Further, the bolts may allow the moment-resisting frame **100** to be quickly and easily assembled even when the shear component **114** is not connected to the column **104** or the beam **108** offsite compared to welding.

(20) The vertical web **128** defines one or more openings **134** therein. The openings **134** weaken the vertical web **128** such that the vertical web **128** selectively yields in shear when the moment-resisting frame **100** is subjected to large loads. Selectively yielding the vertical web **128** may absorb the load thereby allowing the other components of the moment-resisting frame **100** to remain intact and facilitate repair of the moment-resisting frame **100**.

(21) In an embodiment, the openings **134** exhibit a curved shape (e.g., circle, oval, a rectangle with rounded corners) thereby eliminating stress concentrators and increasing the overall strength of the vertical web **128**. In an embodiment, the openings **134** may exhibit a shape having corners, such as a rectangle. The corners may decrease the overall strength of the vertical web **128** which may be necessary to ensure that the vertical web **128** yields before another component of the moment-resisting frame **100**.

(22) The vertical web **128** may define one opening **134** or a plurality of openings **134** (e.g., 2 to 4 or 3 to 5 openings **134**). The number of openings **134** defined by the vertical web **128** may be selected based on the dimensions of the vertical web **128**, the dimensions (e.g., diameter) of the openings **134**, the desired stress (e.g., desired stress range) that is selected to yield the vertical web

128, and the desired stress distribution in the vertical web **128**.

(23) In an embodiment, one or more lateral edges **163** of the vertical web **128** may exhibit concave curvatures. The concave curvature of the lateral edges **163** may form one or more cutouts **161**. The one or more cutouts **161** are openings formed in the vertical web **128**.

(24) In an embodiment, the shear component **114** may be positioned adjacent to and connected to the first beam flange **110**, which typically is on the underside of the beam **108**, to facilitate repair of the moment-resisting frame **100**. For example, the floor may be built on the second beam flange **112**. If the shear component **114** was positioned adjacent to the second beam flange **112**, removing the floor to access the shear component **114** may be difficult, especially when the floor is concrete. When the shear component **114** is positioned adjacent to the first beam flange **110**, only the ceiling may need to be removed to access the shear component **114** which may be significantly easier, more efficient, and more cost effective than removing the floor. In an embodiment, regardless of the above, the shear component **114** may be positioned adjacent to and connected to the second beam flange **112**, for example, when the floor is not on the second beam flange **112** or the floor is easily removable.

(25) Referring to FIG. 1B, the first column flange **106** exhibits a column width $W_{sub.C}$ from a first edge **136** to a second edge **138** of the first column flange **106**. The column width $W_{sub.C}$ may be equal to or greater than a width of one or more components of the column-to-beam connection system. For example, the shear component **114** may exhibit a shear component width $W_{sub.S}$ that is equal to or less than the column width $W_{sub.C}$. The shear component width $W_{sub.S}$ is equal to or less than the column width $W_{sub.C}$ because the vertical web **128** defining the openings **134** extends in a vertical direction instead of a horizontal direction. For example, some conventional column-to-beam connection systems exhibit a width that is significantly greater than the column width $W_{sub.C}$. Such conventional column-to-beam connection systems may interfere with some architectural features and/or may limited locations in which the conventional column-to-beam connection systems can be use (e.g., may not form or be positioned proximate to an exterior of a building) due to the bulged caused by such conventional column-to-beam connection systems.

(26) As previously discussed, the column-to-beam connection system may include one or more additional components. In an embodiment, the column-to-beam connection system may include a shear tab **116**. The shear tab **116** may be connected to the column flange **106** via welding or another suitable attachment technique. For example, the shear tab **116** may be connected to the first column flange **106** offsite. The shear tab **116** may also be connected to the beam web **118** using bolts **140** or another suitable attachment technique. In an embodiment, the column-to-beam connection system may include a weld that connects the second beam flange **112** to the first column flange **106**. In an embodiment, the column-to-beam connection system may include one or more additional components, as further disclosed herein or as known in the art, instead of or in conjunction with the shear tab **116** and/or a weld.

(27) In an embodiment, the moment-resisting frame **100** may include one or more components in addition to the column-to-beam connection system, the column **104**, and the beam **108**. In an example, the moment-resisting frame **100** may include at least one cover plate **142** attached to the first column flange **106** and the second column flange **122**. The cover plate **142** may provide additional strength and rigidity to the column **104** thereby preventing deformation of the column **104** caused by the column-to-beam connection system. In an example, the moment-resisting frame **100** may include continuity plates (e.g., continuity plates **443** shown in FIG. 4A) or column web stiffeners (e.g., column web stiffeners **568** shown in FIG. 5) instead of or in addition to the cover plates **142**. Similar to the cover plates **142**, the column web stiffeners may increase the strength and rigidity of the column **104**.

(28) FIG. 1C is a side view of the moment-resisting frame **100** shown in FIGS. 1A-1B when a load (e.g., a wind or seismic load) is applied to the moment-resisting frame **100**, according to an embodiment. For example, the moment-resisting frame **100** may sway or otherwise move when a

load is applied thereof. Swaying the moment-resisting frame **100** may cause the column **104** to tilt by an angle θ . The swaying of the moment-resisting frame **100** may cause a shear stress to be applied to the column-to-beam connection system. Since the vertical web **128** is weakened by the openings **134**, the shear stress causes the vertical web **128** to yield. The shaded portions of the vertical web **128** illustrate the yielded regions **144** of the vertical web **128**. Causing the vertical web **128** to yield causes the vertical web **128** to absorb energy from the load applied to the moment-resisting frame **100** thereby inhibiting the other components of the moment-resisting frame **100** from also yielding. It is noted that the cutouts **161** further weaken the vertical web **128** and further ensure that the yielded regions **114** of the vertical web **128** extends between the opening **134** and the cutouts **161**. However, the cutouts **161** may be omitted from the vertical web **128** and the vertical web **128** may still yield as shown in FIG. 1C.

(29) The shear component **114** illustrated in FIGS. 1A-1C exhibits a T-like cross-sectional shape. However, the shear components disclosed herein may exhibit other suitable shapes. For example, FIGS. 2A and 2B are a side and front view, respectively, of a portion of a moment-resisting frame **200** including a column-to-beam connection system, according to an embodiment. Except as otherwise disclosed herein, the moment-resisting frame **200** and the column-to-beam connection system is the same or substantially similar to any of the moment-resisting frames and column-to-beam connections systems, respectively, disclosed herein. For example, the moment-resisting frame **200** may include a column **204** and a beam **208**. Further, the column-to-beam connection system may include a shear component **214** and, optionally, one or more additional components.

(30) The shear component **214** exhibits a generally I-shaped cross-sectional shape. For example, the shear component **214** may include a base plate **226**, an opposing plate **246** opposite the base plate **226**, and at least one vertical web **228** extending between the base plate **226** and the opposing plate **246**. Similar to the shear component **114** of FIGS. 1A-1C, the base plate **226** may be connected to the first column flange **206** and the vertical web **228** may define one or more openings **234** therein. However, the opposing plate **246** is configured to be connected (e.g., directly) to the first beam flange **210** (e.g., the vertical web **228** is indirectly connected to the first beam flange **210**). In an embodiment, the shear component **214** is formed from an I-beam.

(31) The increased width of the opposing plate **246** relative to the thickness of the vertical web **228** may facilitate attachment of the opposing plate **246** to the first beam flange **210**. In an example, the increased width of the opposing plate **246** may facilitate attachment of the shear component **214** to the first beam flange **210** using one or more bolts **248**. In an example, the increased width of the opposing plate **246** may exhibit a greater circumference that may be welded to the first beam flange **210** than the vertical web **228**.

(32) In an embodiment, the shear components disclosed herein may exhibit a shape other than a general T-like cross-sectional shape or a generally I-like cross-sectional shape. For example, the shear components disclosed herein may exhibit a generally rectangular cross-sectional shape (e.g., the shear component is a hollow structural section) or another suitable structure.

(33) FIG. 3A to 3C are side, front, and top views, respectively, of a portion of a moment-resisting frame **300** including a column-to-beam connection system, according to an embodiment. Except as otherwise disclosed herein, the moment-resisting frame **300** is the same or substantially similar to any of the moment-resisting frames disclosed herein. For example, the moment-resisting frame **300** may include a column **304** and a beam **308**. Further, the column-to-beam connection system may include a shear component **314** and, optionally, one or more additional components.

(34) The shear component **314** includes a base plate **326** that is connected to a first column flange **306**. The shear component **314** also includes a vertical web **328** formed from a plurality of interconnected pieces. For example, in the illustrated embodiment, the vertical web **328** includes a first vertical web **350** extending directly from the base plate **326**. The first vertical web **350** may be integrally formed with the base plate **326** or may be connected to the base plate **326** using any suitable attachment technique (e.g., welding). The vertical web **328** also includes a second vertical

web **352** extending from the first beam flange **310**. The second vertical web **352** may be attached to the first beam flange **310** using any of the attachment techniques disclosed herein (e.g., welding or an opposing plate). The first vertical web **350** is distinct from the second vertical web **352** and, optionally, the first vertical web **350** may be spaced from the second vertical web **352** when the shear component **314** is assembled. The vertical web **328** also includes at least one connector web, such as a first connector web **354** and a second connector web **356** (shown in FIG. 3B). The first and second connector webs **354**, **356** are configured to be attached to both the first and second vertical webs **350**, **352** such that the first and second vertical webs **350**, **352** are connected together via the first and second connector webs **354**, **356**. The first connector web **354** is positioned adjacent to a first side of the first and second vertical webs **350**, **352** while the second connector web **356** is positioned adjacent to a second side of the first and second vertical webs **350**, **352** that is opposite the first side. The first and second connector webs **354**, **356** may be connected to the first and second vertical webs **350**, **352** using any suitable connection technique, such as using one or more bolts **358** or welds.

(35) It is noted that the vertical web **328** may only include a single connector web. For example, FIG. 3D is a front view of a portion of a moment-resisting frame **300'** including a column-to-beam connection system, according to an embodiment. The moment-resisting frame **300'** is the same as the moment-resisting frame **300** illustrated in FIGS. 3A-3C except that the shear component **314'** only includes a single connector web **354'** that connects the first vertical web **350'** to the second vertical web **352'**.

(36) Referring back to FIGS. 3A-3C, the vertical web **328** defines one or more openings **334** therein. In an embodiment, at least one of the first connector web **354** or the second connector web **356** defines the openings **334** since the first and second connector webs **354**, **356** may have a larger surface area than and/or are easier to replace than the first and second vertical webs **350**, **352**. In an embodiment, at least one of the first vertical web **350** or the second vertical web **352** may define the openings **334** therein.

(37) The column-to-beam connection system may also include a top plate **360** that is connected to the first column flange **306** and the second beam flange **312** thereby connecting the column **304** to the beam **308**. The top plate **360** may be connected to the first column flange **306** and the second beam flange **312** using any suitable attachment technique. For example, as illustrated, the top plate **360** may be connected to the first column flange **306**, such as welded to the first column flange **306** offsite. The top plate **360** may then be connected to the second beam flange **312** using one or more bolts **362** which may allow quick attachment of the top plate **360** to the second beam flange **312** at the worksite. It is noted that any of the column-to-beam connection systems disclosed herein may include the top plate **360**.

(38) FIGS. 4A and 4B are side and front views of a portion of a moment-resisting frame **100** including a column-to-beam connection system, according to an embodiment. Except as otherwise disclosed herein, the moment-resisting frame **400** is the same or substantially similar to any of the moment-resisting frames disclosed herein. For example, the moment-resisting frame may include a column **404** and a beam **408**. Further, the column-to-beam connection component may include a shear component **414** and, optionally, one or more additional components.

(39) The shear component **414** includes a base plate **426** that is connected to a column flange **406**. The shear component **414** also includes a vertical web **428** formed from a plurality of interconnected pieces. For example, in the illustrated embodiment, the vertical web **428** includes a first vertical web **450** extending directly from the base plate **426**. The first vertical web **450** may be integrally formed with the base plate **426** or may be connected to the base plate **426** using any suitable attachment technique (e.g., welding). The vertical web **428** also includes a second vertical web **452** extending from a beam flange **410**. The second vertical web **452** may be attached to the first beam flange **410** using any of the attachment techniques disclosed herein (e.g., welding or an opposing plate). The first vertical web **450** is distinct from the second vertical web **452** and,

optionally, the first vertical web **450** may be spaced from the second vertical web **452** when the shear component **414** is assembled. The vertical web **428** also includes at least one connector web, such as a first connector web **454** and a second connector web **456** (shown in FIG. 4B). The first and second connector webs **454**, **456** are configured to be attached to both the first and second vertical webs **450**, **452** such that the first and second vertical webs **450**, **452** are connected together via the first and second connector webs **454**, **456**. The first connector web **454** is positioned adjacent to a first side of the first and second vertical webs **450**, **452** while the second connector web **456** is positioned adjacent to a second side of the first and second vertical webs **450**, **452** that is opposite the first side. The first and second connector webs **454**, **456** may be connected to the first and second vertical webs **450**, **452** using any suitable connection technique, such as using one or more bolts **458** or welds.

(40) The vertical web **428** defines a plurality of openings therein. In an embodiment, the first connector web **454** defines the plurality opening. The plurality of openings may include at least one inner opening **434a** spaced from the lateral edges **463** of the first connector web **454** and at least one outer opening **434b** extending inwardly from the lateral edges **463** (e.g., extending from the lateral edges **463** partially towards the inner opening **434a**). The plurality of openings may increase the complexity of forming the first connector web **454** than if the first connector web **454** only included a single opening (similar to the first connector web **334** illustrated in FIG. 3A). However, the plurality of openings may cause the stress to be more equally distributed to the bolts **458** that connect the plurality of pieces of the vertical web **428** together than if the first connector web **454** only included a single opening. For example, as illustrated, the plurality of openings are positioned on the first connector web **454** such that one of the plurality of openings are between each opposing pair of bolts **458** (i.e., bolts **458** that are spaced apart from each other in a direction that is parallel to or substantially parallel to a longitudinal axis of the column **406**). Positioning the plurality of openings between opposing pair of bolts **458** causes the opposing pair of bolts **458** to have stress more equally distributed therebetween than if at least one of the opposing pair of bolts **458** had an opening therebetween while at least one other opposing pair of bolts **458** did not have an opening therebetween.

(41) The moment-resisting frames illustrated in FIGS. 1A-3D include at least one cover plate mounted to the columns. The cover plates increase the stiffness of the moment-resist frames. However, the cover plates make connecting other components to the column (e.g., another beam opposite the beam illustrated in FIGS. 1A-3D) more difficult. Further, the cover plates may make retrofitting the column to include the moment-resisting frame more difficult since any other beam connected to the column made need to be temporarily detached from the column to attach the cover plate. As such, as illustrated in FIG. 4A, in some embodiments, the cover plate may be omitted from the moment-resisting frame **400**. Instead, the moment-resisting frame **400** may include one or more continuity plates **443** within the flanges **406** of the column **404**. The continuity plates **443** may decrease the stiffness of the moment-resisting frame **400** than if the moment-resisting frame **400** included at least one cover plate. However, the continuity plates **443** may make attaching a second beam orthogonal to the beam **408** easier since the cover plate does not need to be removed to attach the second beam. Further, the continuity plates **443** may make retrofitting an existing frame to include any of the column-to-beam connection systems disclosed herein easier since any other beam attached to the column **406** opposite the beam **408** does not need to be temporarily detached when making the retrofit.

(42) The moment-resisting frames illustrate in FIGS. 1A-3D are fully restrained moment-resisting frames (i.e., most of the bolts or connections between the column and the beam are in shear). However, the principles and features disclosed herein may be used in partially restrained moment-resisting frames (i.e., most of the bolts or connections between the column and the beam are in tension). For example, FIG. 5 is a side view of a portion of a partially restrained moment-resisting frame **500** including a column-to-beam connection system, according to an embodiment. Except as

otherwise disclosed herein, the moment-resisting frame **500** may be the same or substantially similar to any of the moment-resisting frames disclosed herein. For example, the moment-resisting frame **500** may include a column **504** and a beam **508** that are connected together using at least a shear component **514**. The shear component **514** in the illustrated embodiment may be the same or substantially similar to the shear component **114** illustrated in FIGS. **1A-1C**. However, the shear component **514** may be the same or substantially similar to any of the other shear components disclosed herein.

(43) The column-to-beam connection system includes an end plate **564**. The end plate **564** may be directly connected to the first column flange **506** of the column **504** using any suitable attachment technique, such as with a plurality of bolts **566** (as shown) or a weld. The end plate **564** may also be connected to the beam **508**. For example, in the illustrated embodiment, the end plate **564** is connected indirectly to the first beam flange **510** via the shear component **514** and directly to the second beam flange **512**. The end plate **564** may be connected to the shear component **514** using any suitable attachment technique, such as with a weld **520**. The end plate **564** may be connected to the second beam flange **512** using any suitable attachment technique, such as with a weld **518** or a top plate.

(44) In an embodiment, the end plate **564** is connected to the beam **508** offsite and then provided to the work site. As previously discussed, connecting the end plate **564** to the beam **508** offsite may be easier, faster, cheaper, etc. The end plate **564**, as shown in the illustrated embodiment, may then be connected to the column **504** using bolts **566** which may be quicker and cheaper, depending on location, than welding the end plate **564** to the column **504**.

(45) As previously discussed, the moment-resisting frame **500** may include other components. For example, as illustrated, the moment-resisting frame **500** may include one or more column web stiffeners **568** attached to the column web **524**. The column web stiffeners **568** may increase the strength and/or rigidity of the column **504** at or near the connection between the column **504** and the beam **508**.

(46) The partially restrained moment-resisting frames disclosed herein may be used with different shear components. For example, FIG. **6** is a side view of a portion of a moment-resisting frame **600** including a column-to-beam connection system, according to an embodiment. The moment-resisting frame **600** may be substantially the same as the moment-resisting frame **500** shown in FIG. **5**. For example, the column-to-beam connection system includes a shear component **614** connected to the end plate **664**. However, the shear component **614** may be the same or substantially similar to the shear component **314**, **314'**, **414** shown in FIGS. **3A-4B**.

(47) FIG. **7** is an isometric view of a moment-resisting frame **700**, according to an embodiment. The moment-resisting frame **700** may include one or more horizontally oriented beams **708** connected to and extending between opposing vertical columns **704**. Each beam **708** may be connected to one of the columns **704** using a column-to-beam connection system that is the same as or substantially similar to any of the column-to-beam connection systems disclosed herein. For example, the column-to-beam connection system may include a shear component **714**. The shear component **714** may include a base plate **726** and at least one vertical web **728** extending from the base plate **726**. The column-to-beam connection system may also include other components, such as welds, top plates, end plates, or any other component known in the art.

(48) In an embodiment, application of a lateral force F or F' to the moment-resisting frame **700** may produce bending and/or twisting (e.g., elastic or plastic deformation) to the columns **704** and/or the beams **708**. The lateral force F or F' may be applied to the moment-resisting frame **700** due to one or more of seismic activity, a wind loading event, or some other cause. The column-to-beam connection system may hold the columns **704** and the beams **708** together while the lateral force F or F' are applied to the moment-resisting frame. However, the shear component **714** may yield thereby absorbing at least some of the lateral force.

(49) Yielding of the shear component may require the shear component to be repaired. FIG. **8** is a

flow chart of a method **800** of repairing a shear component, according to an embodiment. The method includes, in block **805**, removing at least a portion of the shear component (“removed component”) from the moment-resisting frame. The removed component may include at least a yield region of the shear component. For example, the removed component may include all of the shear component, all of the vertical web, a portion of the vertical web (e.g., removing the connector web), and/or any other portion of the shear component.

(50) The method used to remove the removed component may depend on how the removed component is attached to the rest of the moment-resisting frame. In an example, removing the removed component may include cutting or grinding the removed component from the rest of the moment-resisting frame when the removed component is welded to the rest of the moment-resisting frame. In an example, removing the removed component may include unbolting the removed component from the rest of the moment-resisting frame when the removed component is bolted to the rest of the moment-resisting frame. In an example, removing the removed component may include both cutting or grinding and unbolting the removed component from the rest of the moment-resisting frame when the removed component is both welded and bolted to the rest of the moment-resisting frame.

(51) After block **805**, the method may include, in block **810**, attaching a replacement component to the rest of the moment-resisting frame. The replacement component may be the same or similar to the removed component. Attaching the replacement component to the rest of the moment-resisting frame may include welding, bolting, or using another other suitable attachment technique to attach the replacement component to the rest of the moment-resisting frame. In an example, attaching the replacement component to the rest of the moment-resisting frame may include attaching the replacement component to the rest of the moment-resisting frame using the same technique that was used to attach the removed component to the rest of the moment-resisting frame.

(52) In an embodiment, the method **800** may include gaining access to the shear component. In an example, gaining access to the shear component may include removing at least a portion of a ceiling to access the shear component, for instance, when the shear component is attached to the underside (e.g., the first beam flange) of the beam. In an example, gaining access to the shear component may include removing at least a portion of a floor to access the shear component, for instance, when the shear component is attached to the top (e.g., the second beam flange) of the beam.

(53) In an embodiment, instead of the method **800**, a method of repairing a shear component that includes a yielded region may include attaching a plate over the yielded region. For example, the plate that is attached to the yield portion may correspond to the yielded region and may exhibit a size that is greater than the yield portion. As such, the plate that is attached to the yield portion may support a majority of any loads that are applied to the shear component instead of the yield portion.

(54) In an embodiment, an existing frame (e.g., an existing moment-resisting frame) may be retrofitted to include any of the column-to-beam connection systems disclosed herein. Retrofitting the frame may include supporting at least a portion of the existing frame such that the beam(s) and column(s) of the existing frame maintain their position when the connectors of the existing frame are removed. Retrofitting the frame may then include removing the connectors of the existing frame. Removing the connectors may include cutting welds, unbolting bolts, etc. After removing the connectors, retrofitting the existing frame may include removing components of the frame that will not be included in the moment-resisting frame. Retrofitting the existing frame may then include attaching any of the column-to-beam connection systems disclosed herein to the frame, such as attaching one or more of a vertical web, a top plate, one or more cover plates, one or more continuity plates, one or more shear tabs, end plate, etc. to the existing frame.

(55) While various aspects and embodiments have been disclosed herein, other aspects and embodiments are contemplated. The various aspects and embodiments disclosed herein are for purposes of illustration and are not intended to be limiting.

(56) Terms of degree (e.g., “about,” “substantially,” “generally,” etc.) indicate structurally or functionally insignificant variations. In an example, when the term of degree is included with a term indicating quantity, the term of degree is interpreted to mean $\pm 10\%$, $\pm 5\%$, $+2\%$ or 0% of the term indicating quantity. In an example, when the term of degree is used to modify a shape, the term of degree indicates that the shape being modified by the term of degree has the appearance of the disclosed shape. For instance, the term of degree may be used to indicate that the shape may have rounded corners instead of sharp corners, curved edges instead of straight edges, one or more protrusions extending therefrom, is oblong, is the same as the disclosed shape, etc.

Claims

1. A moment-resisting frame, comprising: a column having a column flange, the column flange exhibiting a column width measured from a first edge of the column flange to a second edge of the column flange, wherein the second edge is opposite the first edge; a beam including a first beam flange and a second beam flange opposite the first beam flange; and a shear component connected to the column flange and one of the first beam flange or the second beam flange, the shear component including: a base plate connected to the column flange; and at least one vertical web extending from the base plate, the at least one vertical web defining one or more openings therein, the one or more openings exhibiting an elongated shape oriented such that a longitudinal axis thereof is substantially parallel to the flange of the beam, the vertical web configured to yield and form at least one yielded region between the one or more openings and at least one of an adjacent opening or a lateral edge of the vertical web, the lateral edge extending from the base plate towards the flange of the beam.
2. The moment-resisting frame of claim 1, wherein the at least one vertical web is configured to be directly connected to the first beam flange or the second beam flange.
3. The moment-resisting frame of claim 1, wherein the shear component further includes a top plate configured to be directly connected to the first beam flange or the second beam flange of the beam, and wherein the at least one vertical web is configured to extend between the base plate and the top plate.
4. The moment-resisting frame of claim 1, wherein the one or more openings includes at least one inner opening spaced from respective lateral edges of the at least one vertical web and at least one outer opening extending inwardly from at least one of the lateral edges of the at least one vertical web.
5. The moment-resisting frame of claim 1, further comprising a top plate configured to be connected to the flange of the column, the shear component is configured to be connected to the first beam flange of the beam and the top plate configured to be connected to the second beam flange of the beam.
6. The moment-resisting frame of claim 1, wherein at least one of the column or the beam is an I-beam.
7. The moment-resisting frame of claim 1, wherein the shear component exhibits a shear component width that is less than the column width, wherein the shear component width is measured parallel to the column width.
8. The moment-resisting frame of claim 1, wherein the base plate is welded directly to the column flange.
9. The moment-resisting frame of claim 1, wherein the at least one vertical web is welded directly to the first beam flange.
10. The moment-resisting frame of claim 1, wherein the at least one vertical web includes: a first vertical web extending directly from the base plate; a second vertical web that is distinct from the first vertical web; and at least one connector web configured to be coupled to the first vertical web and the second vertical web, the at least one connector web defining the one or more openings

therein.

11. The moment-resisting frame of claim 1, further comprising a top plate connected to the second beam flange.

12. The moment-resisting frame of claim 1, wherein the shear component further includes an opposing plate directly coupled to the first beam flange, wherein the at least one vertical web extends between the base plate and the opposing plate.

13. The moment-resisting frame of claim 12, wherein the opposing plate is bolted to the first beam flange.

14. The moment-resisting frame of claim 1, further comprising an end plate that is directly attached to the column flange, wherein the beam and the base plate are coupled to the end plate.

15. The moment-resisting frame of claim 14, wherein the end plate is connected to the column flange using a plurality of bolts.

16. The moment-resisting frame of claim 1, wherein the elongated shape is one of substantially rectangular or substantially oval.

17. A method of repairing the moment-resisting frame of claim 1, the method comprising: removing at least a portion of the shear component from the moment-resisting frame, the moment-resisting frame including the column having the column flange and the beam having the first beam flange, the shear component including the base plate and the at least one vertical web defining the one or more openings therein, wherein the at least a portion of the shear component includes the at least one yielded region is adjacent to the one or more openings; wherein, at least before removing at least a portion of the shear component from the moment-resisting frame, the shear component connects the first beam flange to the column flange, the base plate is connected to the flange of the column, and the at least one vertical web extends from the base plate; and attaching a replacement component to the rest of the moment-resisting frame, wherein the replacement component is substantially the same as the at least a portion of the shear component before the shear component yielded.

18. The method of claim 17, wherein: removing at least a portion of the shear component from the rest of the moment-resisting frame includes grinding or cutting the at least a portion of the shear component; and attaching a replacement component to the moment-resisting frame includes welding the replacement component to the rest of the moment-resisting frame.

19. The method of claim 17, wherein: removing at least a portion of the shear component from the rest of the moment-resisting frame includes unbolting the at least a portion of the shear component from the rest of the moment-resisting frame; and attaching a replacement component to the moment-resisting frame includes bolting the replacement component to the rest of the moment-resisting frame.
