

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12410983
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Graham, II; Henry L. et al.

Firearm suppressor with components of two or more materials

Abstract

A firearm suppressor is provided, including a tubular core, a baffle carried within the core, and a tubular mount. The core may be attached end-to-end to the mount. A cap may be attached end-to-end to the core opposite the mount. An intermediate member may be included, extending between the mount and the cap, and residing outboard of the core. The intermediate member may be welded to the mount and to the cap. The mount, the cap, and the intermediate member may be composed of one or more of titanium, aluminum, resins, polymers, composites, carbon fiber, and ceramics, whereas the core and the baffle may be composed of one or more of cobalt, nickel alloy, steel, stainless steel, and cobalt alloy.

Inventors: Graham, II; Henry L. (Landrum, SC), Derdziak; George Michael (Greenville, SC)

Applicant: Rugged Design, Inc. (Travelers Rest, NC)

Family ID: 75490810

Assignee: Rugged Design, Inc. (Travelers Rest, SC)

Appl. No.: 16/988018

Filed: August 07, 2020

Prior Publication Data

Document Identifier	Publication Date
US 20210116200 A1	Apr. 22, 2021

Related U.S. Application Data

us-provisional-application US 62884920 20190809

Publication Classification

Int. Cl.: F41A21/30 (20060101)

U.S. Cl.:

CPC F41A21/30 (20130101);

Field of Classification Search

CPC: F41A (21/30)

USPC: 181/223; 89/14.4

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5164535	12/1991	Leasure	89/14.4	F41A 21/30
6374718	12/2001	Rescigno	89/14.4	F41A 21/30
7661349	12/2009	Brittingham	N/A	N/A
9366495	12/2015	Coppinger	N/A	F41A 21/30
9921021	12/2017	Graham, II	N/A	N/A
10054384	12/2017	Marfione	N/A	N/A
10088259	12/2017	Dueck et al.	N/A	N/A
10119779	12/2017	Miele	N/A	F41A 21/30
10126083	12/2017	Groves	N/A	N/A
10132588	12/2017	Salvador	N/A	F41A 21/325
10184745	12/2018	Fulton	N/A	N/A
10222162	12/2018	Adamson, Jr.	N/A	N/A
10222163	12/2018	Couvillion	N/A	N/A
10228210	12/2018	Parker	N/A	N/A
10234228	12/2018	Person	N/A	N/A
10254068	12/2018	Piemme et al.	N/A	N/A
10267586	12/2018	Marfione	N/A	N/A
10330417	12/2018	Reis Green	N/A	F41A 21/30
10488139	12/2018	Graham, II	N/A	N/A
2018/0202744	12/2017	De Sousa	N/A	F41A 21/34
2018/0299223	12/2017	Barrett	N/A	F41A 21/30

Primary Examiner: Hammond; Dedei K

Assistant Examiner: Olson; Jennifer B.

Attorney, Agent or Firm: Parker Poe Adams & Bernstein, LLP

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) This application claims the benefit of priority of U. S. Provisional Application Ser. No. 62/884,920, filed on Aug. 9, 2019, which is incorporated herein in its entirety.

STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT

(1) Not applicable.

THE NAMES OF PARTIES TO A JOINT RESEARCH AGREEMENT

(2) Not applicable.

INCORPORATION-BY-REFERENCE OF MATERIALS SUBMITTED ON A COMPACT DISC OR AS A TEXT FILE VIA THE OFFICE ELECTRONIC FILING SYSTEM

(3) Not applicable.

STATEMENT REGARDING PRIOR DISCLOSURES BY THE INVENTOR OR A JOINT INVENTOR

(4) Not applicable.

BACKGROUND OF THE INVENTION

Field of the Invention

(5) The present invention relates to a firearm suppressor and, more particularly, to a firearm suppressor comprising components of two or more materials.

Description of the Related Art

(6) A conventional firearm operates by burning gunpowder to generate combustion gases that propel a projectile through the barrel of the firearm and out of the barrel muzzle. The rapidly expanding combustion gases exit the muzzle explosively, producing a characteristic loud report.

(7) A suppressor (also sometimes referred to as a silencer) is a device attached to the muzzle of the firearm to reduce the noise of the discharging firearm. Suppressors are designed to reduce the noise created by the discharge by controlling and managing the energy levels of propellant gases emitted from the muzzle. Attenuation of such noise offers several advantages, such as mitigating damage to the hearing of the user.

(8) The upstream end of a suppressor typically includes means for removably coupling the device to a weapon, and its downstream end includes an opening for the exit of the projectile. Typical suppressors include an elongated tubular housing containing one or more transverse baffles that define successive internal expansion chambers through which the projectile and expanding gasses pass after the weapon is fired. The baffles may be of various designs, and define a bore through which the projectile travels. These chambers serve to control, delay, and divert the flow, expansion, and exhausting of the propellant gases, and also to reduce their temperature and otherwise dissipate their energy, so as to achieve a corresponding reduction in the noise produced by the propellant gases as they ultimately exit the device.

(9) The discharge of a firearm produces high temperature and high pressure propellant gases, a harsh environment for components exposed to such gases. Baffles, and the housing in which baffles are carried, need to be constructed of material that can withstand high heat and pressure to which they will be exposed during use. Further, after repeated firing, the hot gasses from the combusted propellant can erode the bore edges of the baffles. The bore is typically precisely dimensioned, and the clearance between the bore and the projectile affects the performance of the suppressor—a closer clearance may result in better performance of the suppressor in reducing discharge noise levels.

(10) Improving the wear resistance of a baffle can extend the useful lifetime of the suppressor.

(11) It is desirable for a firearm suppressor to be as lightweight as possible. Mounted at the muzzle of a firearm, the suppressor's mass increases the moment of inertia of the assembly, thereby slowing the angular acceleration of the assembly and reducing the ability to manipulate the firearm for target acquisition.

(12) Titanium, for example, is a lightweight metal that would be desirable for use in fabricating a

suppressor. Titanium has approximately half the weight of steel. However, titanium does not have desirable abrasion resistance and does not retain tensile strength at elevated temperatures as well as, for example, steel or cobalt alloy. Hot gases and unburnt powder tend to quickly erode impact surfaces, such as suppressor baffles, that are not parallel to the bore axis if made of titanium.

(13) An ideal suppressor thus would use lightweight materials, such as for example titanium, in components that are parallel to the bore axis of the firearm, and stronger, harder, more abrasion resistant materials for components and/or surfaces that are not parallel to the bore axis.

(14) A welded rifle suppressor is generally more durable and requires less service than a non-welded suppressor. A suppressor that was only threaded together with no welds may eventually unthread and cause a catastrophic and/or dangerous failure. However, it can be difficult to weld dissimilar materials together; for example, titanium and steel cannot be easily welded together.

(15) In view of the foregoing, the present invention relates to an improvement upon the known systems and methods of firearm suppressors, and provides distinct advantages over the conventional systems and methods.

BRIEF SUMMARY OF THE INVENTION

(16) An firearm suppressor with components of two or more materials is provided. As revealed in the following description and the figures herein, this invention discovers a durable, rugged, and lightweight firearm suppressor design.

(17) In accordance with certain aspects of certain embodiments of the present technology, a firearm suppressor may comprise a tubular core, a baffle carried within the core, and a tubular mount. The core may be attached end-to-end to the mount. The suppressor may further include a cap, which may be attached end-to-end to the core opposite the mount. An intermediate member may be included, extending between the mount and the cap and residing outboard of the core. The mount, the cap, and the intermediate member may be composed of one or more of titanium, aluminum, resins, polymers, composites, carbon fiber, and ceramics, whereas the core and the baffle may be composed of one or more of cobalt, nickel alloy, steel, stainless steel, and cobalt alloy.

(18) Other embodiments of the present technology may include one or more of the following: (a) The intermediate member may be welded to the mount and to the cap; (b) The surface of the intermediate member may be free of apertures; (c) The intermediate member may include a hollow right circular cylinder; (d) The baffle may be frustoconical; and/or (e) The baffle may be welded to the core.

(19) In an alternate embodiment of the present technology, a firearm suppressor may comprise a mount that defines a hollow cylinder. The mount may have a first upstream end and a first downstream end, and the first downstream end may carry first threading of a first orientation. A core may be included, the core defining a hollow cylinder with a second upstream end and a second downstream end; the second upstream end may carry second threading that is complementary to the first threading of the mount; the second downstream end may carry third threading of a second orientation that is opposite the first orientation of the mount. A baffle may also be included, which may reside within the hollow cylinder of the core. Further, a cap may be included, the cap defining a third upstream end and a third downstream end, the third upstream end carrying a fourth threading that is complementary to the third threading of the core. The downstream end of the mount may be threaded to the upstream end of the core, and the downstream end of the core may be threaded to the upstream end of the cap. Any force urging two components to unthread from one another from threads of a first orientation would thus be counteracted by the force exerted by the threads of the second orientation, and vice versa. A collar may reside around the core and abut both the mount and the cap. The mount, the cap, and the collar may be composed of one or more of titanium, aluminum, resins, polymers, composites, carbon fiber, and ceramics. The core and the baffle may be composed of one or more of cobalt, nickel alloy, steel, stainless steel, and cobalt alloy.

(20) Certain embodiments of the present technology may also include one or more of the

following: (a) The collar may be free of apertures; (b) The collar may include a hollow right circular cylinder; (c) The baffle may be frustoconical shaped and flare outwardly toward the cap; (d) The collar may be attached to the mount; and/or (e) The collar may be welded to the mount and to the cap.

(21) In another embodiment of the present technology, a firearm suppressor may include a steel core that has an upstream end and a downstream end. The core may define a hollow cylinder that has internal threading of a first orientation within its upstream end and internal threading of a second orientation within its downstream end, the second orientation being opposite the first orientation. The suppressor may further include a baffle that is carried within the core. A mount may also be included, which may have an upstream end and a downstream end and may define a hollow cylinder. The mount may have internal threading of the first orientation of the core within its upstream and downstream ends. The suppressor may also include a cap that has upstream end and downstream ends, with external threading of the second orientation at its upstream end. Any force urging two of these components to unthread from one another from threads of one orientation would thus be counteracted by the force exerted by the threads of the opposite orientation, and vice versa. A hollow cylindrical sleeve may also be included, sized to reside around the core. The mount, the sleeve, and the cap may be composed of one or more of titanium, aluminum, resins, polymers, composites, carbon fiber, and ceramics. The upstream end of the core may be threaded to the downstream end of the mount, the upstream end of the cap may be threaded to the downstream end of the core, and the sleeve may be disposed between the mount and the cap and around the core.

(22) Some embodiments of the present technology may also include one or more of the following: (a) The surface of the sleeve may be free of apertures; (b) The sleeve may include a hollow right circular cylinder; (c) The baffle may be annular; (d) The sleeve may be attached to the mount; (e) The sleeve may be attached to the cap; and/or (f) The sleeve may be welded to the mount and to the cap.

(23) Additional advantages of the invention will be set forth in part in the description which follows, and in part will be obvious from the description, or may be learned by practice of the invention. The advantages of the invention will be realized and attained by means of the elements and combinations particularly pointed out in the appended claims. It is to be understood that both the foregoing general description and the following detailed description are exemplary and explanatory only and are not restrictive of the invention, as claimed.

(24) The purpose of the Abstract hereinabove is to enable the United States Patent and Trademark Office, and the public generally, to determine quickly from a cursory inspection the nature of the technical disclosure. The Abstract is not provided for interpreting the scope of the claims herein, nor to define the invention or the application, nor to be limiting in any way as to the scope of the invention.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The details of the present invention, as to both its structure and its operation, can be understood with reference to the accompanying drawings, in which:

(2) FIG. 1 is a right side elevation view of a prior art combination of a firearm and a suppressor;

(3) FIG. 2 is a disassembled perspective view of components of a suppressor according to an embodiment of the present invention; and

(4) FIG. 3 is a sectional view, taken along the bore axis, of a suppressor according to an embodiment of the present invention.

(5) It should be noted that the drawings discussed above and below are not to scale in all instances,

but may have exaggerated dimensions in some respect to illustrate the principles of the invention.

DETAILED DESCRIPTION OF REPRESENTATIVE EMBODIMENTS

(6) Reference will now be made in detail to the presently preferred embodiments of the invention, one or more examples of which are illustrated in the drawings. Each example is provided by way of explanation of the invention, and is not meant as a limitation of the invention. For example, features illustrated or described as part of one embodiment may be used with a second embodiment to yield a third embodiment. It is intended that the present application include such modifications and variations as come within the scope and spirit of the invention. Repeat use of reference characters throughout the present specification and appended drawings is intended to represent the same or analogous features or elements of the invention.

(7) Before any embodiments of the invention are explained in detail, it is to be understood that the invention is not limited in its application to the details of construction or to the arrangement of components set forth in the following description or illustrated in the drawings. The invention is capable of other embodiments and of being practiced or of being carried out in various ways. Also, it is to be understood that the phraseology used herein is for the purpose of description and should not be regarded as limiting. The use of formatives of the words “include,” “comprise,” and “have” is meant to encompass the items listed thereafter and equivalents thereof, as well as additional items. Unless specified or limited otherwise, the terms “connected” and “carried by” are used broadly and encompass direct and indirect mountings, connections, supports, or couplings. Further, such phraseology is not limited to physical or mechanical connections or couplings.

(8) As used herein, the terms “upstream” and “downstream” refer to the relative location of components in a fluid pathway. Thus, in the context of a firearm suppressor, “upstream” is relatively closer to the muzzle of the firearm, and “downstream” is relatively further from the muzzle of the firearm.

(9) A firearm suppressor is attached to the muzzle of a firearm. Such a suppressor is generally tubular shaped, with the axis of the tube aligned with the bore of the firearm. An exemplary prior art suppressor S is illustrated in FIG. 1 as so attached, to an exemplary firearm F, in this example a handgun.

(10) The subject invention of suppressor **10** is illustrated in FIGS. 2 and 3. Suppressor **10** may include a mount **40**, a core **20**, a cap **50**, and an intermediate member **60** that in some embodiments may also be referred to as a collar **60** and/or as a sleeve **60**. One or more baffles **30**, for examples baffles **30a**, **30b**, may be carried within core **20**.

(11) Mount **40** may be generally a hollow, tube-shaped body and/or a hollow cylinder. Mount **40** may include first attachment threading **12** and/or second attachment threading **14** residing proximate mount first upstream end **42**, for attaching mount **40**, directly or indirectly to the muzzle of a firearm. For example, first attachment threading **12** and/or second attachment threading **14** may be used to attach mount **40** to a firearm attachment locking system such as that disclosed in U.S. Pat. No. 9,921,021, the full disclosure of which is incorporated herein in its entirety. Alternatively, mount **40** may include other features, such as one or more flanges (not shown), that allow for the attachment of mount **40** to the muzzle of a firearm.

(12) Mount **40** may be attached to a core **20** by several mechanical alternatives, such as by coupling lugs and grooves that mate.

(13) Mount **40** may include first threading **81** proximate mount downstream end **44**. First threading **81** may be of a first orientation, for example right-hand threading. First threading **81** may be external threading proximate mount downstream end **44**, residing on the exterior of mount **40**, as illustrated in FIG. 2, or first threading **81** may be internal threading proximate mount downstream end **44**, residing on the interior of mount **40** (not shown).

(14) Mount **40** may be composed of one or more of titanium, aluminum, resins, polymers, composites, carbon fiber, and ceramics.

(15) Core **20** may be generally a hollow, tube-shaped body and/or a hollow cylinder. Core **20** may

be attached to a cap **50** by several mechanical alternatives, such as by mating lugs and grooves that couple together. Core **20** may include second threading **82** proximate core second upstream end **22**. Second threading **82** may be of an orientation complementary to first threading **81** of mount **40**, such that core second upstream end **22** may be threaded with mount downstream end **44**. For example, if first threading **81** is external threading, second threading **82** may be of internal, matching threading proximate core second upstream end **22** and interior to core **20**. Alternatively, if first threading **81** is internal threading, second threading **82** may be of external, matching threading proximate core second upstream end **22** and upon surface **62** of core **20**.

(16) Core **20** may further include third threading **83** proximate core second downstream end **24**. If first threading **81** and second threading **82** are of a first orientation, third threading **83** may be of a second orientation, the second orientation being opposite the first orientation. For example, if first threading **81** and second threading **82** are right-hand threadings, third threading **83** may be left-hand threading. Third threading **83** may be external threading proximate core second downstream end **24**, residing on the exterior of core (not shown), or third threading **83** may be internal threading proximate core second downstream end **44**, residing on the interior of core **20** as illustrated in FIG. 3.

(17) Core **20** may carry one or more baffle **30** within its interior, for example baffles **30a**, **30b**. In some applications, baffle **30** may be welded to the interior of core **20**, for example at baffle welds **66a**, **66b**; in other applications, baffle **30** may be positioned in core **20** by other mechanisms not involving weldment. Baffle **30** may be annular, conical, frustoconical, trumpet-shaped, and/or of other shapes. In one embodiment as illustrated in FIG. 3, baffles **30a**, **30b** are trumpet-shaped, with baffles **30a**, **30b** flaring outwardly toward core second downstream end **24**.

(18) Core **20** and baffles **30** may be composed of one or more of cobalt, nickel alloy, steel, stainless steel, and cobalt alloy.

(19) A cap **50** may be configured for attachment to core second downstream end **24**. Cap **50** may have a cap third upstream end **52** and a cap third downstream end **54**. Cap **50** may include fourth threading **84** proximate cap third upstream end **52**. Fourth threading **84** may be of an orientation complementary to third threading **83** of core **20**, such that cap third upstream end **52** may be threaded to core second downstream end **24**. For example, if third threading **83** is external threading, fourth threading **84** may be of internal, matching threading proximate cap third upstream end **52** and interior to cap **50** (not shown). Alternatively, if third threading **83** is internal threading, fourth threading **84** may be of external, matching threading proximate cap third upstream end **52**, as illustrated in FIG. 3.

(20) So configured, any force urging two connected components, such as mount **40** and core **20**, to unthread from one another from threads of a first orientation would thus be counteracted by the force exerted by the threads of the second orientation, such as those connecting core **20** and cap **50**, and vice versa.

(21) Suppressor **10** may also include an intermediate member **60**, also in some embodiments referred to as collar **62** and sleeve **62**. Intermediate member **60** may extend between mount **40** and cap **50** in an assembled suppressor **10**, as illustrated in FIG. 3. Some instances of intermediate member **60** include, in whole or in part, a hollow right circular cylinder. In some configurations, intermediate member **60** may reside around core **20**, and in certain aspects of such configurations intermediate member **60** may define a hollow cylinder, although in other configurations intermediate member **60** may extend between mount **40** and cap **50** without residing around core **20**. In individual instances of suppressor **10**, intermediate member **60** may include an exterior surface **62**; in specific representations of such instances, exterior surface **62** may be free of apertures, whereas in other representations apertures may extend into or through exterior surface **62** to core **20** (not shown) for advantageous reasons, such as for example further reduction in weight or to provide an advantageous gripping surface.

(22) Intermediate member **60** may be composed of one or more of titanium, aluminum, resins,

polymers, composites, carbon fiber, and ceramics.

(23) As to a suppressor **10** in which a core **20** is attached end-to-end to a mount **40** and a cap **50** is attached end-to-end to the core **20** opposite the mount **40**, with an intermediate member **60** extending between the mount **40** and the cap **50**, suppressor **10** may include intermediate member **60** being welded to mount **40**, to cap **50**, or to both mount **40** and cap **50**. With an intermediate member **60** extending between a mount **40** and a cap **50** and being welded to both, any force urging two connected components, such as mount **40** and core **20**, or such as core **20** and cap **50**, to disconnect from one another would thus be resisted by the weldment of intermediate member **60** to both mount **40** and cap **50**.

(24) FIG. 2 illustrates an embodiment of suppressor **10**, in disassembled form. As illustrated in FIG. 2, suppressor **10** includes a core **20** having an upstream end **22** and a downstream end **24**, defining a hollow cylinder having internal threading **82** of a first orientation within its upstream end **22** and having internal threading **83** of a second orientation within its downstream end **24**, internal threading **82** being opposite internal threading **83**. Baffles **30a**, **30b** are carried within core **20** (not shown). Mount **40** has an upstream end **42** and a downstream end **44**, and defines a hollow cylinder having external threading **12** of the first orientation within its upstream end **42**. Mount **40** has external threading of the first orientation at its downstream end **44**. Also included is a cap **50** having an upstream end **52** and a downstream end **54**. Cap **50** has external threading **84** of the second orientation at its upstream end **52**. Finally, sleeve **60** is included, sleeve **60** defining a hollow cylinder sized to reside around the core **20**. The upstream end **22** of the core **20** is configured for being threaded to the downstream end **44** of the mount **40**, the upstream end of the cap is configured for being threaded to the downstream end **24** of the core **20**, and the sleeve **60** is configured for being disposed between the mount **40** and the cap **50** and around the core **20**. In the embodiment of FIG. 2, the surface **62** of sleeve **60** is free of apertures.

(25) FIG. 3 illustrates an embodiment of suppressor **10**, in assembled form. As illustrated in FIG. 3, suppressor **10** includes a mount **40** defining a hollow cylinder with a first upstream end **42** and a first downstream end **44**, the first downstream end **44** carrying first threading **81** of a first orientation. A core **20**, defining a hollow cylinder, has a second upstream end **22** and a second downstream end **24**, the second upstream end **24** carrying second threading **82**, the second threading **82** being complementary to the first threading **81**. Core **20** second downstream end **24** carries third threading **83** of a second orientation, the second orientation being opposite the first orientation. Baffles **30a**, **30b** reside within the hollow cylinder of core **20**. A cap **50** is also attached to the assembly, cap **50** having third upstream end **52** and a third downstream end **54**, the third upstream end **52** carrying fourth threading **84** that is complementary to the third threading **83**. The downstream end **44** of mount **40** has been threaded to upstream end **22** of core **20**. Downstream end **24** of core **20** has been threaded to upstream end **52** of cap **50**. A collar **60** resides around core **20** and abuts both mount **40** and cap **50**. Baffles **30a**, **30b** are frustoconical shaped and flare outwardly toward cap **50**. Collar **60** has been welded at first weld **71** to mount **40** and at second weld **72** to cap **50**. The embodiment illustrated in FIG. 3 includes both internal threading **12** and external threading **14** at mount first upstream end **42**, which provides greater flexibility in the manner of attaching, by direct attachment or by indirect attachment via a transitional component, suppressor **10** to a firearm. Also, the embodiment illustrated in FIG. 3 includes third attachment threading **16** at cap downstream end **54**, allowing for downstream attachment of other firearm accessories.

(26) Suppressor **10** thus may have components of two or more materials. Suppressor **10**, thus configured, provides a durable, rugged, and lightweight firearm suppressor design.

(27) It should be appreciated that, in the above description of embodiments, various features are sometimes grouped together in a single embodiment, figure, or description for the purpose of streamlining the disclosure and aiding in the understanding of one or more of the various inventive aspects. This method of disclosure, however, is not to be interpreted as reflecting an intention that any claim requires more features than are expressly recited in that claim. Moreover, any components,

features, or steps illustrated and/or described in a particular embodiment herein, can be applied to or used with any other embodiment. Thus, it is intended that the scope of the inventions herein disclosed should not be limited by the particular embodiments described above, but should be determined only by a fair reading of the claims that may issue from the benefit of the within disclosure.

Claims

1. A firearm suppressor, comprising: a one-piece tubular core defining an upstream end and a downstream end, the upstream end having a first threading and the downstream end having a second threading that is opposite the first threading; a baffle, the baffle carried within the core; a tubular mount, the core attached by the first threading to the exterior of the mount; a cap, the cap attached to the core opposite the mount by the second threading; an intermediate member, the intermediate member extending between the mount and the cap and welded to both, and residing outboard of the core; the mount, the cap, and the intermediate member being composed of a first material; and the core and the baffle being composed of a second material different than the first material.
2. The firearm suppressor of claim 1, in which the first material is titanium.
3. The firearm suppressor of claim 1, in which the surface of the intermediate member is free of apertures.
4. The firearm suppressor of claim 1, in which the intermediate member includes a hollow right circular cylinder.
5. The firearm suppressor of claim 1, in which the baffle is frustoconical.
6. The firearm suppressor of claim 1, in which the cap is attached to the interior of the core.
7. A firearm suppressor, comprising: a mount, the mount defining a hollow cylinder with a first upstream end and a first downstream end, the first downstream end carrying first threading of a first orientation; a core, the core defining a hollow cylinder with a second upstream end and a second downstream end, the second upstream end carrying second threading, the second threading being complementary to the first threading, the second downstream end carrying third threading of a second orientation, the second orientation being opposite the first orientation; a baffle, the baffle welded to the interior of the hollow cylinder of the core; a cap, the cap defining a third upstream end and a third downstream end, the third upstream end carrying a fourth threading, the fourth threading being complementary to the third threading; the downstream end of the mount being threaded to the upstream end of the core, the downstream end of the core being threaded to the upstream end of the cap; a collar, the collar residing around the core and welded to both the mount and the cap; and the core overlaps the mount and the collar overlaps the core where the core overlaps the mount.
8. The firearm suppressor of claim 7, in which the surface of the collar is free of apertures.
9. The firearm suppressor of claim 7, in which the core is one-piece, the firearm suppressor includes a plurality of baffles, and the plurality of baffles reside within the one-piece core.
10. The firearm suppressor of claim 7, in which the core overlaps the cap and the collar overlaps the core where the core overlaps the cap.
11. The firearm suppressor of claim 7, in which the baffle and the core are cobalt alloy.
12. The firearm suppressor of claim 7, in which the mount, cap, and collar are titanium.
13. The firearm suppressor of claim 7, in which weldments reside only between components of the same material.
14. A firearm suppressor having a bore axis, comprising: a core, the core: being composed of a first material; having an upstream end and a downstream end; defining a hollow cylinder; having internal threading of a first orientation within its upstream end; having internal threading of a second orientation within its downstream end, the second orientation being opposite the first

orientation; a baffle, the baffle being composed of a second material and attached to the interior of the core; a mount, the mount: having an upstream end and a downstream end; defining a hollow cylinder; having internal threading of the first orientation within its upstream end; having external threading of the first orientation at its downstream end; a cap, the cap: having an upstream end and a downstream end; having external threading of the second orientation at its upstream end; a sleeve, the sleeve: defining a hollow cylinder; sized to reside around the core; a radius extending perpendicular to the bore axis, the radius intersecting the mount, the core, and the sleeve, the mount being closer to the bore axis than the core at the radius and the core being closer to the bore axis than the sleeve at the radius; the mount, the sleeve, and the cap being composed of a third material that is different than the first material; and the upstream end of the core being threaded to the downstream end of the mount, the upstream end of the cap being threaded to the downstream end of the core, and the sleeve being disposed between the mount and the cap and welded to both.

15. The firearm suppressor of claim 14, in which the surface of the sleeve is free of apertures.

16. The firearm suppressor of claim 14, in which the sleeve includes a hollow right circular cylinder.

17. The firearm suppressor of claim 14, in which the baffle is annular.

18. The firearm suppressor of claim 14, in which the mount is of one-piece construction.

19. The firearm suppressor of claim 14, further including weldments, the weldments residing only between adjacent components of the same material.

20. The firearm suppressor of claim 14, further including a second radius extending perpendicular to the bore axis, the second radius intersecting the cap, the core, and the sleeve, the cap being closer to the bore axis than the core at the second radius and the core being closer to the bore axis than the sleeve at the second radius.
