

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12413416
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Martins; Rafael Marques et al.

Data protection in a tracking device environment

Abstract

A tracking device can use a permanent encryption key pair to encrypt a temporary private key that corresponds to a set of diversified temporary public keys. When a community mobile device subsequently detects the tracking device, the central tracking system provides a diversified temporary public key to the community mobile device. The community mobile device uses the diversified temporary public key to encrypt location data representative of a location of the community mobile device, and provides the encrypted location data to the central tracking system. When a user subsequently requests a location of the tracking device from the central tracking system, the central tracking system provides the encrypted temporary private key and the encrypted location data to a device of the user, and the device can decrypt the encrypted temporary private key using the permanent encryption key pair, and decrypt the encrypted location data using the decrypted temporary private key.

Inventors: Martins; Rafael Marques (Campbell, CA), Klinkner; Steven R. (Palo Alto, CA), de la Broise; Josselin (Mountain View, CA), Meyer; Ian Thomas (San Francisco, CA)

Applicant: Tile, Inc. (San Mateo, CA)

Family ID: 74646896

Assignee: Tile, Inc. (San Mateo, CA)

Appl. No.: 18/622728

Filed: March 29, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240259212 A1	Aug. 01, 2024

Related U.S. Application Data

Publication Classification

Int. Cl.: **H04L29/06** (20060101); **G06F21/60** (20130101); **H04L9/00** (20220101); **H04L9/08** (20060101); **H04L9/14** (20060101); **H04L9/30** (20060101); **H04L9/32** (20060101)

U.S. Cl.:

CPC **H04L9/3242** (20130101); **G06F21/602** (20130101); **H04L9/006** (20130101); **H04L9/0819** (20130101); **H04L9/14** (20130101); **H04L9/3073** (20130101);

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6058309	12/1999	Huang et al.	N/A	N/A
6377810	12/2001	Geiger et al.	N/A	N/A
7114175	12/2005	Lähteenmäki	N/A	N/A
7292561	12/2006	Hyun et al.	N/A	N/A
7502972	12/2008	Chilukuri	714/45	G06F 11/3688
7885413	12/2010	Vasic et al.	N/A	N/A
7921110	12/2010	Ting et al.	N/A	N/A
7983419	12/2010	Fan	380/255	H04L 63/04
RE42996	12/2010	Hyun et al.	N/A	N/A
8280351	12/2011	Ahmed et al.	N/A	N/A
8401185	12/2012	Telang	713/193	H04L 67/1095
8538028	12/2012	Yeap	380/278	H04L 51/48
8611321	12/2012	Herrala et al.	N/A	N/A
8817712	12/2013	Shin et al.	N/A	N/A
8839386	12/2013	Gilboy	N/A	N/A
8869248	12/2013	Moosavi et al.	N/A	N/A
9094211	12/2014	Klevan et al.	N/A	N/A
9118639	12/2014	Phegade et al.	N/A	N/A
9130693	12/2014	Reznik et al.	N/A	N/A
9256657	12/2015	Evenson	N/A	G06F 16/258
9357348	12/2015	Evans et al.	N/A	N/A
9520939	12/2015	Jovicic et al.	N/A	N/A
9520999	12/2015	Klevan et al.	N/A	N/A

9525971	12/2015	Vega	N/A	H04W 4/029
9634999	12/2016	Marion et al.	N/A	N/A
9654916	12/2016	de la Broise	N/A	H04L 67/303
9964623	12/2017	de la Broise	N/A	H04W 4/06
10111032	12/2017	Vega	N/A	H04W 12/126
10237259	12/2018	Ronda et al.	N/A	N/A
10356204	12/2018	Hazen et al.	N/A	N/A
10482506	12/2018	Tawakol et al.	N/A	N/A
10506386	12/2018	de la Broise	N/A	H04W 4/029
10530806	12/2019	Starink et al.	N/A	N/A
10568035	12/2019	Tong	N/A	H04W 4/80
10575138	12/2019	Klinkner	N/A	G08B 21/24
10733277	12/2019	Klevan et al.	N/A	N/A
10735397	12/2019	Ronda et al.	N/A	N/A
10757676	12/2019	de la Broise	N/A	H04W 12/108
10929738	12/2020	Balgañon Canela et al.	N/A	N/A
10979994	12/2020	Shan et al.	N/A	N/A
10992797	12/2020	Klinkner	N/A	H04M 1/72448
11128478	12/2020	Galdo et al.	N/A	N/A
11151087	12/2020	Chittaro et al.	N/A	N/A
11153758	12/2020	Klinkner et al.	N/A	N/A
11188672	12/2020	Van Liesdonk et al.	N/A	N/A
11201748	12/2020	Martins et al.	N/A	N/A
11223479	12/2021	Firestone et al.	N/A	N/A
11240007	12/2021	Higgins et al.	N/A	N/A
11290260	12/2021	Firestone et al.	N/A	N/A
11641563	12/2022	Lopatin et al.	N/A	N/A
12069174	12/2023	Montemurro et al.	N/A	N/A
2002/0061748	12/2001	Nakakita et al.	N/A	N/A
2003/0028805	12/2002	Lahteenmaki	N/A	N/A
2003/0181215	12/2002	Cromer et al.	N/A	N/A
2003/0207683	12/2002	Lempio et al.	N/A	N/A
2003/0233458	12/2002	Kwon et al.	N/A	N/A
2003/0236867	12/2002	Natsuno et al.	N/A	N/A
2004/0192352	12/2003	Vallstrom et al.	N/A	N/A
2004/0255137	12/2003	Ying	713/193	H04L 63/0884
2006/0046689	12/2005	Kim	N/A	N/A
2006/0047962	12/2005	Adams et al.	N/A	N/A
2006/0072747	12/2005	Wood	380/44	H04L 9/0662
2006/0229896	12/2005	Rosen et al.	N/A	N/A

2007/0074019	12/2006	Seidel	713/181	H04L 63/12
2007/0113092	12/2006	Nishida et al.	N/A	N/A
2007/0167175	12/2006	Wong et al.	N/A	N/A
2007/0229350	12/2006	Scalisi et al.	N/A	N/A
2007/0260877	12/2006	Adams et al.	N/A	N/A
2008/0143516	12/2007	Mock et al.	N/A	N/A
2008/0182592	12/2007	Cha et al.	N/A	N/A
2008/0186162	12/2007	Rajan et al.	N/A	N/A
2008/0287143	12/2007	Banks et al.	N/A	N/A
2008/0303901	12/2007	Variyath et al.	N/A	N/A
2009/0002188	12/2008	Greenberg	N/A	N/A
2009/0239502	12/2008	Dempo et al.	N/A	N/A
2009/0323972	12/2008	Kohno	380/284	G06F 21/6245
2010/0064138	12/2009	Hwang	713/168	H04L 63/083
2010/0142713	12/2009	Perlman	N/A	N/A
2010/0164714	12/2009	Buller et al.	N/A	N/A
2010/0199339	12/2009	Kageyama	N/A	N/A
2010/0273452	12/2009	Rajann et al.	N/A	N/A
2011/0182250	12/2010	Shin et al.	N/A	N/A
2011/0231092	12/2010	Kuo et al.	N/A	N/A
2011/0273334	12/2010	Karr	N/A	N/A
2012/0042363	12/2011	Moosavi et al.	N/A	N/A
2012/0154115	12/2011	Herrala	N/A	N/A
2012/0218078	12/2011	Hill	N/A	N/A
2012/0309422	12/2011	Lewis-Evans et al.	N/A	N/A
2013/0069782	12/2012	Duggal et al.	N/A	N/A
2013/0152216	12/2012	Stevens	N/A	N/A
2013/0197859	12/2012	Albano et al.	N/A	N/A
2013/0217332	12/2012	Altman et al.	N/A	N/A
2014/0006129	12/2013	Heath	N/A	N/A
2014/0062695	12/2013	Rosen	340/539.13	G08B 21/0219
2014/0085089	12/2013	Rasband et al.	N/A	N/A
2014/0162693	12/2013	Wachter et al.	N/A	N/A
2014/0189346	12/2013	Cureton	713/155	G06F 21/105
2014/0213301	12/2013	Evans et al.	N/A	N/A
2014/0214855	12/2013	Attaluri et al.	N/A	N/A
2014/0274135	12/2013	Edge et al.	N/A	N/A
2014/0274136	12/2013	Edge et al.	N/A	N/A
2014/0282974	12/2013	Maher	726/7	H04L 63/08
2014/0327518	12/2013	Loutit	340/7.58	G06F 3/048
2015/0006666	12/2014	Backholm et al.	N/A	N/A
2015/0052358	12/2014	Udupi	713/171	H04L 9/0822
2015/0086018	12/2014	Harjula	380/277	H04L 9/083
2015/0160328	12/2014	Peinhardt et al.	N/A	N/A
2015/0168173	12/2014	Lewis-Evans et al.	N/A	N/A

2015/0237018	12/2014	Parry	713/162	H04L 12/2898
2015/0319151	12/2014	Chastain	713/171	H04L 9/083
2016/0050530	12/2015	Corbalis et al.	N/A	N/A
2016/0065589	12/2015	Leighton et al.	N/A	N/A
2016/0088430	12/2015	Connor	N/A	N/A
2016/0105764	12/2015	Evans	340/539.13	G08B 21/24
2016/0105765	12/2015	Farley	455/456.1	H04W 4/029
2016/0105766	12/2015	de la Broise	455/456.1	H04L 67/303
2016/0154963	12/2015	Kumar	713/189	G06F 21/602
2016/0241660	12/2015	Nhu	N/A	N/A
2016/0323114	12/2015	Sulpizio, Jr.	N/A	H04L 63/0272
2017/0064509	12/2016	Evans et al.	N/A	N/A
2017/0069014	12/2016	Minelli	N/A	G06F 16/48
2017/0085542	12/2016	Avanzi	N/A	H04L 63/061
2017/0134898	12/2016	Vega et al.	N/A	N/A
2017/0155514	12/2016	Schulz	N/A	G06F 21/57
2017/0171180	12/2016	Britt	N/A	G06F 16/9554
2017/0250972	12/2016	Ronda	N/A	H04L 9/0891
2017/0324614	12/2016	de Barros Chapiewski	N/A	H04L 41/0816
2017/0338948	12/2016	Boehl	N/A	H04L 9/3242
2018/0114220	12/2017	Ekberg	N/A	N/A
2018/0115413	12/2017	King	N/A	H04L 9/30
2018/0219840	12/2017	Quaglia et al.	N/A	N/A
2018/0234791	12/2017	de la Broise	N/A	N/A
2018/0242102	12/2017	Lévêque et al.	N/A	N/A
2018/0293387	12/2017	Bar-El	N/A	H04L 63/0884
2018/0317266	12/2017	Britt	N/A	H04W 4/80
2018/0337778	12/2017	Scheiblaue	N/A	H04L 9/0866
2018/0359151	12/2017	Akhavain Mohammadi et al.	N/A	N/A
2019/0044708	12/2018	Dewan	N/A	H04L 9/0897
2019/0141474	12/2018	de la Broise	N/A	H04L 67/52
2019/0197471	12/2018	Endo	N/A	G06F 9/541
2019/0245885	12/2018	Starink	N/A	G06F 21/53
2019/0312720	12/2018	Liu	N/A	H04L 9/083
2019/0340251	12/2018	Peddada	N/A	H04L 9/16
2019/0370271	12/2018	Christensen	N/A	H04L 67/02

2020/0007540	12/2019	Kawaguchi et al.	N/A	N/A
2020/0013043	12/2019	Smets et al.	N/A	N/A
2020/0034945	12/2019	Soundararajan et al.	N/A	N/A
2020/0052905	12/2019	Mathias	N/A	H04L 9/3265
2020/0107164	12/2019	Lopatin	N/A	G01S 5/0284
2020/0140113	12/2019	Niergarth et al.	N/A	N/A
2020/0259650	12/2019	Montemurro	N/A	H04L 9/321
2020/0259908	12/2019	Klinkner	N/A	H04W 4/029
2020/0404091	12/2019	Klinkner	N/A	H04W 4/029
2020/0410113	12/2019	Gryb	N/A	H04L 9/302
2021/0014048	12/2020	Lee et al.	N/A	N/A
2021/0168979	12/2020	Yang	N/A	G05B 19/4183

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2493231	12/2011	EP	N/A
3205135	12/2017	EP	N/A
WO 2014/042507	12/2013	WO	N/A
WO 2016/036858	12/2015	WO	N/A

OTHER PUBLICATIONS

Extended European Search Report, European Patent Office Application No. 20866390.6, Nov. 28, 2022, 5 pages. cited by applicant

International Search Report and Written Opinion, Patent Cooperation Treaty Application No. PCT/US2015/054506, Feb. 23, 2016, 17 pages. cited by applicant

International Search Report and Written Opinion, Patent Cooperation Treaty Application No. PCT/US2020/044344, Nov. 6, 2020, 12 pages. cited by applicant

United States Advisory Action, U.S. Appl. No. 15/660,766, Dec. 18, 2017, 2 pages. cited by applicant

United States Office Action, U.S. Appl. No. 15/660,766, Aug. 25, 2017, 9 pages. cited by applicant

United States Office Action, U.S. Appl. No. 15/660,766, Oct. 26, 2017, 11 pages. cited by applicant

United States Office Action, U.S. Appl. No. 15/947,207, Feb. 4, 2019, 14 pages. cited by applicant

United States Office Action, U.S. Appl. No. 15/947,207, Jun. 28, 2018, 12 pages. cited by applicant

United States Office Action, U.S. Appl. No. 15/947,207, Nov. 16, 2018, 15 pages. cited by applicant

United States Office Action, U.S. Appl. No. 15/947,207, Sep. 14, 2018, 12 pages. cited by applicant

United States Office Action, U.S. Appl. No. 16/241,858, Apr. 18, 2019, 16 pages. cited by applicant

United States Office Action, U.S. Appl. No. 16/546,122, Jul. 13, 2021, 80 pages. cited by applicant

United States Office Action, U.S. Appl. No. 16/702,276, Jun. 7, 2021, 28 pages. cited by applicant

United States Office Action, U.S. Appl. No. 17/037,022, Jan. 6, 2022, 13 pages. cited by applicant

United States Office Action, U.S. Appl. No. 17/474,063, Aug. 24, 2023, 34 pages. cited by applicant

United States Office Action, U.S. Appl. No. 17/474,063, Dec. 15, 2023, 33 pages. cited by applicant

applicant

United States Office Action, U.S. Appl. No. 17/474,063, Feb. 10, 2023, 27 pages. cited by applicant

United States Office Action, U.S. Appl. No. 17/474,063, May 15, 2023, 31 pages. cited by applicant

United States Office Action, U.S. Appl. No. 17/581,033, Nov. 25, 2022, 11 pages. cited by applicant

United States Office Action, U.S. Appl. No. 17/520,695, Mar. 21, 2023, 52 pages. cited by applicant

United States Office Action, U.S. Appl. No. 17/520,695, Dec. 15, 2022, 61 pages. cited by applicant

United States Office Action, U.S. Appl. No. 17/520,695, Jul. 25, 2023, 51 pages. cited by applicant

United States Office Action, U.S. Appl. No. 17/474,063, filed Mar. 7, 2025, 26 pages. cited by applicant

Primary Examiner: Shiferaw; Eleni A

Assistant Examiner: Hussein; Hassan A

Attorney, Agent or Firm: Fenwick & West LLP

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. application Ser. No. 17/520,695, filed Nov. 7, 2021, now U.S. Pat. No. 11,979,502, which application is a continuation of U.S. application Ser. No. 16/546,122, filed Aug. 20, 2019, now U.S. Pat. No. 11,201,748, which applications are incorporated by reference in their entirety. This application is related to U.S. application Ser. No. 16/241,858, filed Jan. 7, 2019, now U.S. Pat. No. 10,462,600, which is a continuation-in-part of U.S. application Ser. No. 15/947,207, filed Apr. 6, 2018, now U.S. Pat. No. 10,349,203, which is a continuation of U.S. application Ser. No. 15/660,766, filed Jul. 26, 2017, now U.S. Pat. No. 9,973,890, which is a continuation of U.S. application Ser. No. 15/472,281, filed Mar. 29, 2017, now U.S. Pat. No. 9,749,791, which is a continuation of U.S. application Ser. No. 14/822,580, filed Aug. 10, 2015, now U.S. Pat. No. 9,654,916, which application claims the benefit of U.S. Provisional Application No. 62/062,062, filed Oct. 9, 2014, all of which are incorporated by reference in their entirety.

BACKGROUND

(1) This disclosure relates generally to locating a tracking device, and more specifically, to securely providing location and identity information for a tracking device to a centralized system.

(2) Electronic tracking devices have created numerous ways for people to track the locations of people and/or objects. For example, a user can use GPS technology to track a device remotely or determine a location of the user. In another example, a user can attach a tracking device to an important object, such as keys or a wallet, and use the features of the tracking device to more quickly locate the object, (e.g., if it becomes lost).

(3) However, traditional tracking devices and corresponding systems suffer from one or more disadvantages. For example, locating a tracking device from a far-away distance requires a considerable amount of power. Thus, battery life of a tracking device is often limited. Further, technology for long-range tracking is expensive, and often requires sophisticated circuitry for operating in connection with an associated electronic device (e.g., a mobile device). Additionally, low-power options for tracking devices are limited to tracking nearby objects that require a user to

be within a close proximity of the tracking devices, limiting the usefulness of such tracking devices.

SUMMARY

(4) A tracking device can be associated with a permanent encryption key pair and one or more temporary encryption key pairs. For instance, one or more temporary encryption key pairs can be generated upon activating the tracking device or at the time of manufacture of the tracking device. In some embodiments, a different temporary encryption key pair is generated for each rotatable hash key used by the tracking device to hash an identifier of the tracking device.

(5) The temporary private key of each temporary encryption key pair is encrypted using the permanent public key of the permanent encryption key pair. Each encrypted temporary private key and corresponding temporary public key is stored by a central tracking system. When a community mobile device detects the tracking device, for instance by receiving an advertising packet including a hashed identifier for the tracking device, the community mobile device provides the hashed identifier to the central tracking system. The central tracking system identifies an encrypted temporary encryption key pair (including an encrypted temporary private key and a corresponding temporary public key) associated with the hash key used to generate the hashed identifier, and provides the encrypted temporary encryption key pair to the community mobile device.

(6) The community mobile device determines a location of the community mobile device, for instance by activating a GPS receiver of the community mobile device in response to receiving the hashed identifier. The community mobile device then encrypts location data representative of the location using the temporary public key included within the encrypted temporary encryption key pair received from the central tracking system. The community mobile device then provides the hashed identifier, the encrypted location data, and the encrypted temporary private key to the central tracking system for storage.

(7) When a user, such as an owner of the tracking device, subsequently requests a location of the tracking device from the central tracking system, the central tracking system provides the hashed identifier, the encrypted location data, and the encrypted temporary private key to an owner device associated with the owner. The owner device, which has access to the permanent private key, decrypts the encrypted temporary private key using the permanent private key. The owner device then decrypts the encrypted location data using the decrypted temporary private key, and performs one or more operations using the decrypted location data (such as displaying the location of the tracking device within a map interface displayed by the owner device).

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 illustrates an exemplary implementation for locating a tracking device according to principles described herein.

(2) FIG. 2 illustrates an exemplary tracking system of the implementation of FIG. 1.

(3) FIG. 3 illustrates an exemplary user mobile device of the implementation of FIG. 1.

(4) FIG. 4 illustrates an exemplary community mobile device of the implementation of FIG. 1.

(5) FIG. 5 illustrates a process of identifying a tracking device and an associated location, according to one embodiment.

(6) FIG. 6 illustrates a process of determining device location in response to movement detection, according to one embodiment.

(7) FIG. 7 illustrates a process of selecting between current or previous device location information, according to one embodiment.

(8) FIG. 8 is an interaction diagram illustrating a process for implementing end-to-end encryption in a tracking device environment, according to one embodiment.

(9) FIG. 9 illustrates a process for implementing end-to-end encryption in a tracking device environment, according to one embodiment.

(10) The figures depict various embodiments of the present invention for purposes of illustration only. One skilled in the art will readily recognize from the following discussion that alternative embodiments of the structures and methods illustrated herein may be employed without departing from the principles of the invention described herein.

DETAILED DESCRIPTION

(11) Embodiments described herein provide a user with the ability to locate one or more low-power tracking devices by leveraging the capabilities of a plurality of mobile devices associated with a community of users (e.g., users of the same tracking device system) in a secure and privacy-focused environment.

(12) A user can attach a tracking device to or enclose the tracking device within an object, such as a wallet, keys, a car, a bike, a pet, or any other object that the user wants to track. The user can then use a mobile device (e.g., by way of a software application installed on the mobile device) to track the tracking device and corresponding object. For example, the mobile device can perform a local search for a tracking device attached to a near-by object. However, in situations where the user is unable to locate the tracking device using their own mobile device (e.g., if the tracking device is beyond a distance within which the mobile device and the tracking device can communicate), the principles described herein allow the user to leverage the capabilities of a community of users of a tracking device system.

(13) In particular, a tracking system (also referred to herein as a “cloud server” or simply “server”) can maintain user profiles associated with a plurality of users of the system. The tracking system can associate each user within the system with one or more tracking devices associated the user (e.g., tracking devices that the user has purchased and is using to track objects owned by the user). If the user's object becomes lost or stolen, the user can send an indication that the tracking device is lost to the tracking system, which is in communication with one or more mobile devices associated with the community of users in communication with the system. The tracking system can set a flag indicating the tracking device is lost. When one of a community of mobile devices that are scanning for nearby tracking devices and providing updated locations to the tracking system identifies a flagged tracking device, the tracking system can associate the received location with the flagged tracking device, and relay the location to a user of the tracking device, thereby enabling the user to locate and track down the tracking device.

(14) In addition to utilizing a general community of users, a user of the tracking system may desire to utilize the tracking capabilities of a specific group of one or more known users (e.g., friends or family of the user). For example, a user may indicate one or more friends or other users with which a tracking device may be shared. Sharing the tracking device may provide the ability for a friend to quickly determine if a tracking device is close-by without also querying a larger community of users, or to enable a friend to contact a user directly with information about the location of a lost tracking device.

(15) Environment Overview

(16) FIG. 1 illustrates an exemplary implementation in which a tracking system **100** is communicatively coupled to a mobile device **102** associated with the user **103** and a plurality of community mobile devices **104a** through **104n** (collectively referred to herein as “community mobile devices **104**”) associated with a plurality of users **105a** through **105n** of the tracking system **100** (collectively referred to herein as “community users **105**”). As will be explained in more detail below, the tracking system **100** can allow the user **103** to manage and/or locate a tracking device **106** associated with the user **103**. In some embodiments, the tracking system **100** leverages the capabilities of community mobile devices **104** to locate the tracking device **106** if the location of the tracking device is unknown to the user **103** and beyond the capabilities of mobile device **102** to track. In some configurations, the user **103** may own and register multiple tracking devices **106**.

Although FIG. 1 illustrates a particular arrangement of the tracking system **100**, mobile device **102**, community mobile devices **104**, and tracking device **106**, various additional arrangements are possible.

(17) In some configurations, the user **103** may be part of the community of users **105**. Further, one or more users **105** may own and register one or more tracking devices **106**. Thus, any one of the users within the community of users **105** can communicate with tracking system **100** and leverage the capabilities of the community of users **105** in addition to the user **103** to locate a tracking device **106** that has been lost.

(18) The tracking system **100**, mobile device **102**, and plurality of community mobile devices **104** may communicate using any communication platforms and technologies suitable for transporting data and/or communication signals, including known communication technologies, devices, media, and protocols supportive of remote data communications.

(19) In certain embodiments, the tracking system **100**, mobile device **102**, and community mobile devices **104** may communicate via a network **108**, which may include one or more networks, including, but not limited to, wireless networks (e.g., wireless communication networks), mobile telephone networks (e.g., cellular telephone networks), closed communication networks, open communication networks, satellite networks, navigation networks, broadband networks, narrowband networks, the Internet, local area networks, and any other networks capable of carrying data and/or communications signals between the tracking system **100**, mobile device **102**, and community mobile devices **104**. The mobile device **102** and community of mobile devices **104** may also be in communication with a tracking device **106** via a second network **110**. The second network **110** may be a similar or different type of network as the first network **108**. In some embodiments, the second network **110** comprises a wireless network with a limited communication range, such as a Bluetooth or Bluetooth Low Energy (BLE) wireless network. In some configurations, the second network **110** is a point-to-point network including the tracking device **106** and one or more mobile devices that fall within a proximity of the tracking device **106**. Accordingly, the mobile device **102** and community mobile devices **104** are only able to communicate with the tracking device **106** if they are within a close proximity to the tracking device. In some configurations, the mobile device **102** and one or more community mobile devices **104** may each be associated with multiple tracking devices associated with various users.

(20) As mentioned above, FIG. 1 illustrates the mobile device **102** associated with the user **103**. The mobile device **102** can be configured to perform one or more functions described herein with respect to locating tracking devices (e.g., tracking device **106**). For example, the mobile device **102** can receive input from the user **103** representative of information about the user **103** and information about a tracking device **106**. The mobile device **102** may then provide the received user information, tracking device information, and/or information about the mobile device **102** to the tracking system **100**. Accordingly, the tracking system **100** is able to associate the mobile device **102**, the user **103**, and/or the tracking device **106** with one another. In some embodiments, the mobile device **102** can communicate with the tracking device **106** and provide information regarding the location of the tracking device to the user **103**. For example, the mobile device **102** can detect a communication signal from the tracking device **106** (e.g., by way of second network **110**) as well as a strength of the communication signal to determine an approximate distance between the mobile device **102** and the tracking device **106**. The mobile device **102** can then provide this information to the user **103** (e.g., by way of one or more graphical user interfaces) to assist the user **103** to locate the tracking device **106**. Accordingly, the user **103** can use the mobile device **102** to track and locate the tracking device **106** and a corresponding object associated with the tracking device **106**. If the mobile device **102** is located beyond the immediate range of communication with the tracking device **106** (e.g., beyond the second network **110**), the mobile device **102** can be configured to send an indication that a tracking device **106** is lost to the tracking system **100**, requesting assistance in finding the tracking device. The mobile device **102** can send

an indication of a lost device in response to a command from the user **103**. For example, once the user **103** has determined that the tracking device **106** is lost, the user can provide user input to the mobile device **102** (e.g., by way of a graphical user interface), requesting that the mobile device **102** send an indication that the tracking device **106** is lost to the tracking system **100**. In some examples, the lost indication can include information identifying the user **103** (e.g., name, username, authentication information), information associated with the mobile device **102** (e.g., a mobile phone number), information associated with the tracking device (e.g., a unique tracking device identifier), or a location of the user (e.g., a GPS location of the mobile device **102** at the time the request is sent).

(21) The tracking system **100** can be configured to provide a number of features and services associated with the tracking and management of a plurality of tracking devices and/or users associated with the tracking devices. For example, the tracking system **100** can manage information and/or user profiles associated with user **103** and community users **105**. In particular, the tracking system **100** can manage information associated with the tracking device **106** and/or other tracking devices associated with the user **103** and/or the community users **105**.

(22) As mentioned above, the tracking system **100** can receive an indication that the tracking device **106** is lost from the mobile device **102**. The tracking system **100** can then process the indication in order to help the user **103** find the tracking device **106**. For example, the tracking system **100** can leverage the capabilities of the community mobile devices **104** to help find the tracking device **106**. In particular, the tracking system **100** may set a flag for a tracking device **106** to indicate that the tracking device **106** is lost and monitor communications received from the community mobile devices **104** indicating the location of one or more tracking devices **106** within proximity of the community mobile devices **104**. The tracking system **100** can determine whether a specific location is associated with the lost tracking device **106** and provide any location updates associated with the tracking device **106** to the mobile device **102**. In one example, the tracking system may receive constant updates of tracking device **106** locations regardless of whether a tracking device **106** is lost and provide a most recent updated location of the tracking device **106** in response to receiving an indication that the tracking device **106** is lost.

(23) In some configurations, the tracking system **100** can send a location request associated with the tracking device **106** to each of the community mobile devices **104**. The location request can include any instructions and/or information necessary for the community mobile devices **106** to find the tracking device **102**. For example, the location request can include a unique identifier associated with the tracking device **106** that can be used by the community mobile devices **104** to identify the tracking device **106**. Accordingly, if one of the community mobile devices **104** detects a communication from the tracking device **106** (e.g., if the community mobile device **104** is within range or moves within range of the communication capabilities of the tracking device **106** and receives a signal from the tracking device **106** including or associated with the unique identifier associated with the tracking device **106**), the community mobile device **104** can inform the tracking system **100**. Using the information received from the community mobile devices **104**, the tracking system **100** can inform the user (e.g., by way of the mobile device **102**) of a potential location of the tracking device **106**.

(24) As shown in FIG. 1 and as mentioned above, the tracking system **100** can communicate with a plurality of community mobile devices **104** associated with corresponding community users **105**. For example, an implementation may include a first community mobile device **104a** associated with a first community user **105a**, a second community mobile device **104b** associated with a second community user **105b**, and additional communication mobile devices associated with additional community users up to an nth community mobile device **104n** associated with an nth community user **105n**. The community mobile devices **104** may also include functionality that enables each community mobile device **104** to identify a tracking device **106** within a proximity of the community mobile device **104**. In one example, a first community mobile device **104a** within

proximity of a tracking device **106** can communicate with the tracking device **106**, identify the tracking device **106** (e.g., using a unique identifier associated with the tracking device **106**), and/or detect a location associated with the tracking device **106** (e.g., a location of the first mobile community device **104a** at the time of the communication with the tracking device **106**). This information can be used to provide updated locations and/or respond to a location request from the tracking system **100** regarding the tracking device **106**. In some embodiments, the steps performed by the first community mobile device **104a** can be hidden from the first community user **105a**. Accordingly, the first community mobile device **104a** can assist in locating the tracking device **106** without bother and without the knowledge of the first community user **105a**.

(25) As mentioned above, the tracking system **100** can assist a user **103** in locating a tracking device **106**. The tracking device may be a chip, tile, tag, or other device for housing circuitry and that may be attached to or enclosed within an object such as a wallet, keys, purse, car, or other object that the user **103** may track. Additionally, the tracking device **106** may include a speaker for emitting a sound and/or a transmitter for broadcasting a beacon. In one configuration, the tracking device **106** may constantly transmit a beacon signal that may be detected using a nearby mobile device **102** and/or community mobile device **104**. In some configurations, the tracking device **106** broadcasts a beacon at regular intervals (e.g., one second intervals) that may be detected from a nearby mobile device (e.g., community mobile device **104**). The strength of the signal emitted from the tracking device **106** may be used to determine a degree of proximity to the mobile device **102** or community mobile device **104** that detects the signal. For example, a higher strength signal would indicate a close proximity between the tracking device **106** and the mobile device **102** and a lower strength signal would indicate a more remote proximity between the tracking device **106** and the mobile device **102**. In some cases, the strength of signal or absence of a signal may be used to indicate that a tracking device **106** is lost.

(26) System Overview

(27) FIG. 2 illustrates a diagram showing example components of the tracking system **100**. As shown, the tracking system **100** may include, but is not limited to, an association manager **204**, a tracking device location manager **206**, and a data manager **208**, each of which may be in communication with one another using any suitable communication technologies. It will be recognized that although managers **204-208** are shown to be separate in FIG. 2, any of the managers **204-208** may be combined into fewer managers, such as into a single manager, or divided into more managers as may serve a particular embodiment.

(28) The association manager **204** may be configured to receive, transmit, obtain, and/or update information about a user **103** and/or information about one or more specific tracking devices (e.g., tracking device **106**). In some configurations, the association manager **204** may associate information associated with a user **103** with information associated with a tracking device **106**. For example, user information and tracking information may be obtained by way of a mobile device **102**, and the association manager **204** may be used to link the user information and tracking information. The association between user **103** and tracking device **106** may be used for authentication purposes, or for storing user information, tracking device information, permissions, or other information about a user **103** and/or tracking device **106** in a database.

(29) The tracking system **100** also includes a tracking device location manager **206**. The tracking device location manager **206** may receive and process an indication that the tracking device **106** is lost from a mobile device (e.g., mobile device **102** or community mobile devices **104**). For example, the tracking system **100** may receive a lost indication from a mobile device **102** indicating that the tracking device **106** is lost. The tracking device location manager **206** may set a flag on a database (e.g., tracker database **212**) indicating that the tracking device **106** is lost. The tracking device location manager **206** may also query a database to determine tracking information corresponding to the associated user **103** and/or tracking device **106**. The tracking system **100** may obtain tracking device information and provide the tracking device information or other

information associated with the tracking device **106** to a plurality of community mobile devices **104** to be on alert for the lost or unavailable tracking device **106**. The tracking device location manager **206** may also be used to receive and process a response to a tracking request that is received from one or more community mobile devices **104** that detect the tracking device **106** and respond to the tracking request. For example, the tracking system **100** may receive a response to the tracking request indicating a location within a proximity of the tracking device **106** and provide a last known location within a proximity of the tracking device **106** as provided by the community mobile device **104**.

(30) In one configuration, the tracking device location manager **206** may receive an indication that a tracking device **106** is lost from the mobile device **102** and store the lost indication on a database. When the tracking device location manager **206** receives an indication that the tracking device **106** is lost, the tracking device location manager **206** may set a flag indicating that the tracking device **106** is lost. Setting a flag for a tracking device **106** may include storing and/or associating a value associated with the tracking device that indicates that the tracking device **106** is lost. This may include setting a flag, marker, digital value, or other indication that the tracking device **106** is lost and maintaining or storing the indication of the lost tracking device **106** on the tracking system **100** (e.g., on a database).

(31) The tracking device location manager **206** may further receive updated locations from the community of mobile devices **104** that are constantly scanning for nearby tracking devices **106**. In this example, the tracking device location manager **206** may receive location updates from the community of mobile devices **104** and, based on the tracking device **106** being indicated as lost, provide a response to a lost indication to the mobile device **102**. The response to the lost indication may be a text message, push notification, ring tone, automated voice message, or other response for informing a user **103** that a tracking device **106** has been found and/or an updated location of the tracking device **106**.

(32) The tracking device location manager **206** may further manage providing indications about whether a tracking device **106** is lost or not lost. For example, as discussed above, the tracking device location manager **206** may provide a location request to the community of mobile devices **104** indicating that a tracking device **106** is lost. Additionally, upon location of the tracking device **106** by the user **103** or by one of the community of users **105**, the tracking device location manager **206** may provide an indication to the user **103**, community user **105**, or tracking system **100** that the tracking device **106** has been found, thus removing any flags associated with a tracking device and/or canceling any location request previously provided to the community of users **105**. For example, where a user **103** sends an indication that the tracking device **106** is lost to the tracking system **100** and later finds the tracking device **106**, the mobile device **102** may provide an indication to the tracking system **100** that the tracking device **106** has been found. In response, the tracking device location manager **206** may remove a flag indicating that the tracking device **106** is lost and/or provide an updated indication to the community of users **105** that the tracking device **106** has been found, thus canceling any instructions associated with the previously provided location request. In some configurations, the notification that the tracking device **106** has been found may be provided automatically upon the mobile device **102** detecting a proximity of the tracking device **106**. Alternatively, the notification that the tracking device **106** has been found may be provided by the user **103** via user input on the mobile device **102**. In another example, a known user (e.g., a friend or family member) with whom the tracking device **106** has been shared may provide an indication that the tracking device **106** has been found.

(33) The tracking system **100** additionally includes a data manager **208**. The data manager **208** may store and manage information associated with users, mobile devices, tracking devices, permissions, location requests, and other data that may be stored and/or maintained in a database related to performing location services of tracking devices. As shown, the data manager **208** may include, but is not limited to, a user database **210**, a tracker database **212**, permissions data **214**, and location

request data **216**. It will be recognized that although databases and data within the data manager **208** are shown to be separate in FIG. 2, any of the user database **210**, tracker database **212**, permissions data **214**, and location request data **216** may be combined in a single database or manager, or divided into more databases or managers as may serve a particular embodiment.

(34) The data manager **208** may include the user database **210**. The user database **210** may be used to store data related to various users. For example, the user database **210** may include data about the user **103** as well as data about each user **105** in a community of users **105**. The community of users **105** may include any user that has provided user information to the tracking system **100** via a mobile device **102**, **104** or other electronic device. The user information may be associated with one or more respective tracking devices **106**, or may be stored without an association to a particular tracking device. For example, a community user **105** may provide user information and permit performance of tracking functions on the community mobile device **104** without owning or being associated with a tracking device **106**. The user database **210** may also include information about one or more mobile devices or other electronic devices associated with a particular user.

(35) The data manager **208** may also include a tracker database **212**. The tracker database **212** may be used to store data related to tracking devices. For example, the tracker database **212** may include tracking data for any tracking device **106** that has been registered with the tracking system **100**. Tracking data may include unique tracker identifications (IDs) associated with individual tracking devices **106**. Tracker IDs may be associated with a respective user **103**. Tracker IDs may also be associated with multiple users. Additionally, the tracker database **212** may include any flags or other indications associated with whether a specific tracking device **106** has been indicated as lost and whether any incoming communications with regard to that tracking device **106** should be processed based on the presence of a flag associated with the tracking device **106**.

(36) The data manager **208** may further include permissions data **214** and location request data **216**. Permissions data **214** may include levels of permissions associated with a particular user **103** and/or tracking device **106**. For example, permissions data **214** may include additional users that have been indicated as sharing a tracking device **106**, or who have been given permission to locate a tracking device **106** using an account and/or mobile device **102** associated with the user **103**. Location request data **216** may include information related to a location request or a lost indication received from the user **103** via a mobile device **102**.

(37) FIG. 3 illustrates a diagram showing example components of the mobile device **102**. As shown, the mobile device **102** may include, but is not limited to, a user interface manager **302**, a location request manager **304**, a database manager **306**, and a tracking manager **308**, each of which may be in communication with one another using any suitable communication technologies. It will be recognized that although managers **302-308** are shown to be separate in FIG. 3, any of the managers **302-308** may be combined into fewer managers, such as into a single manager, or divided into more managers as may serve a particular embodiment.

(38) As will be explained in more detail below, the mobile device **102** includes the user interface manager **302**. The user interface manager **302** may facilitate providing the user **103** access to data on a tracking system **100** and/or providing data to the tracking system **100**. Further, the user interface manager **302** provides a user interface by which the user **103** may communicate with tracking system **100** and/or tracking device **106** via mobile device **102**.

(39) The mobile device **102** may also include a location request manager **304**. The location request manager **304** may receive and process a request input to the mobile device **102** to send an indication that a tracking device **106** is lost to a tracking system **100**. For example, the user **103** may provide an indication that a tracking device **106** is lost, unreachable, or otherwise unavailable from the mobile device **102** via the user interface manager **302**, and the location request manager **304** may process the lost indication and provide any necessary data to the tracking system **100** for processing and relaying a location request to other users **105** over a network **108**. In some configurations, an indication that a tracking device **106** is lost is provided via user input.

Alternatively, the indication may be transmitted automatically in response to the mobile device **102** determining that a tracking device **106** is lost.

(40) The mobile device **102** may also include a database manager **306**. The database manager **306** may maintain data related to the user **103**, tracking device **106**, permissions, or other data that may be used for locating a tracking device **106** and/or providing a request to a tracking system **100** for locating one or more tracking devices **106** associated with the user **103**. Further, the database manager **306** may maintain any information that may be accessed using any other manager on the mobile device **102**.

(41) The mobile device **102** may further include a tracking manager **308**. The tracking manager **308** may include a tracking application (e.g., a software application) for communicating with and locating a tracking device **106** associated with the user **103**. For example, the tracking manager **308** may be one configuration of a tracking application installed on the mobile device **102** that provides the functionality for locating a tracking device **106** and/or requesting location of a tracking device **106** using a plurality of community mobile devices **104**. As shown, the tracking manager **308** may include, but is not limited to, a Bluetooth Low Energy (BLE) manager **310**, a persistence manager **312**, a local files manager **314**, a motion manager **316**, a secure storage manager **318**, a settings manager **320**, a location manager **322**, a network manager **324**, a notification manager **326**, a sound manager **328**, a friends manager **330**, a photo manager **332**, an authentication manager **334**, and a device manager **336**. Thus, the tracking manager **308** may perform any of the functions associated with managers **310-338**, described in additional detail below.

(42) The BLE manager **310** may be used to manage communication with one or more tracking devices **106**. The persistence manager **312** may be used to store logical schema information that is relevant to the tracking manager **308**. The local files manager **314** may be responsible for managing all files that are input or output from the mobile device **102**. The motion manager **316** may be responsible for all motion management required by the tracking manager **308**. The secure storage manager may be responsible for storage of secure data, including information such as passwords and private data that would be accessed through this sub-system. The settings manager **320** may be responsible for managing settings used by the tracking manager **308**. Such settings may be user controlled (e.g., user settings) or defined by the tracking manager **308** for internal use (e.g., application settings) by a mobile device **102** and/or the tracking system **100**. The location manager **322** may be responsible for all location tracking done by the tracking manager **308**. For example, the location manager **322** may manage access to the location services of the mobile device **102** and works in conjunction with other managers to persist data. The network manager **324** may be responsible for all Internet communications from the tracking manager **308**. For example, the network manager **324** may mediate all Internet API calls for the tracking manager **308**. The notification manager **326** may be responsible for managing local and push notifications required by the tracking manager **308**. The sound manager **328** may be responsible for playback of audio cues by the tracking manager **308**. The friends manager **330** may be responsible for managing access to contacts and the user's social graph. The photo manager **332** may be responsible for capturing and managing photos used by the tracking manager **308**. The authentication manager **334** may be responsible for handling the authentication (e.g., sign in or login) of users. The authentication manager **334** may also include registration (e.g., sign up) functionality. The authentication manager **334** further coordinates with other managers to achieve registration functionality. The device manager **336** may be responsible for managing the devices discovered by the tracking manager **308**. The device manager **336** may further store and/or maintain the logic for algorithms related to device discovery and update.

(43) FIG. 4 illustrates a diagram showing example components of a community mobile device **104**. As shown, the community mobile device **104** may include, but is not limited to, a user interface manager **402**, a lost tracking device manager **404**, a database manager **406**, and a tracking manager **408**, each of which may be in communication with one another using any suitable communication

technologies. The user interface manager **402**, database manager **406**, and tracking manager **408** illustrated in FIG. **4** may include similar features and functionality as the user interface manager **302**, database manager **306**, and tracking manager **308** described above in connection with FIG. **3**. It will be recognized that although managers **402-408** are shown to be separate in FIG. **4**, any of the managers **402-408** may be combined into fewer managers, such as into a single manager, or divided into more managers as may serve a particular embodiment.

(44) The community mobile device **104** may include a lost tracking device manager **404**. The lost tracking device manager **404** may facilitate scanning for nearby tracking devices **106**. In some configurations, the lost tracking device manager **404** can continuously or periodically scan (e.g., once per second) for nearby tracking devices **106**. The lost tracking device manager **404** may determine whether to provide an updated location of the nearby tracking device **106** to the tracking system **100**. In some configurations, the lost tracking device manager **404** provides a location of a nearby tracking device **106** automatically. Alternatively, the lost tracking device manager **404** may determine whether the location of the tracking device **106** has been recently updated, and determine whether to provide an updated location based on the last time a location of the tracking device **106** has been updated (e.g., by the community mobile device **104**). For example, where the community mobile device **104** has provided a recent update of the location of a tracking device **106**, the lost tracking device manager **404** may decide to wait a predetermined period of time (e.g., 5 minutes) before providing an updated location of the same tracking device **106**.

(45) In one configuration, the lost tracking device manager **404** may receive and process a location request or other information relayed to the community mobile device **104** by the tracking system **100**. For example, the lost tracking device manager **404** may receive an indication of a tracking device **106** that has been indicated as lost, and provide a location of the tracking device **106** if it comes within proximity of the community mobile device **104**. In some configurations, the community mobile device **104** is constantly scanning nearby areas to determine if there is a tracking device **106** within a proximity of the community mobile device **104**. Therefore, where a tracking device **106** that matches information provided by the tracking system **100** (e.g., from the location request) comes within proximity of the community mobile device **104**, the lost tracking device manager **404** may generate and transmit a response to the location request to the tracking system **100**, which may be provided to the user **103** associated with the lost tracking device **106**. Further, generating and transmitting the response to the tracking request may be conditioned on the status of the tracking device **106** being flagged as lost by the mobile device **102** and/or the tracking system **100**.

(46) The lost tracking device manager **404** may additionally provide other information to the tracking system **100** in response to receiving the tracking request. For example, in addition to providing a location of the community mobile device **104**, the lost tracking device manager may provide a signal strength associated with the location to indicate a level of proximity to the location of the community mobile device **104** provided to the user **103**. For example, if a signal strength is high, the location provided to the user **103** is likely to be more accurate than a location accompanied by a low signal strength. This may provide additional information that the user **103** may find useful in determining the precise location of tracking device **106**.

(47) As described above, the lost tracking device manager **404** may determine whether to send a location within the proximity of the tracking device **106** to the tracking system **100**. The determination of whether to send a location to the tracking system **100** may be based on a variety of factors. For example, a lost tracking device manager **404** may determine to send a location of the tracking device **106** to a tracking system **100** based on whether the detected tracking device **106** has been indicated as lost or if a tracking request has been provided to the community mobile device **104** for the particular tracking device **106**. In some configurations, the community mobile device **104** may send an update of a location of a tracking device **106** even if the tracking device **106** is not associated with a current tracking request or if the tracking device **106** is not indicated as lost. For

example, where the location of a tracking device **106** has not been updated for a predetermined period of time, the community mobile device **104** may provide an update of a tracking device location to the tracking system **100**, regardless of whether a tracking request has been received. (48) In some configurations, the community mobile device **104** may include additional features. For example, the community mobile device **104** may allow a tracking system **100** to snap and download a photo using photo functionality of the community mobile device **104**. In some configurations, this may be an opt-in feature by which a community user **105** permits a tracking system **100** to take a snap-shot and possibly provide a visual image of an area within a proximity of the tracking device **106**.

(49) Hash-Based Location Tracking

(50) Often, identifying and tracking the location of wireless devices requires the establishment of a two-way communication session between the device being tracked (the “tracking device”) and another device (such as a mobile phone, computer, or any other suitable device, “mobile device” hereinafter). As described herein, a tracking device can instead be identified using one-way communications (communications from the tracking device to the mobile device), without requiring communications from the mobile device to the tracking device. Such communications are referred to as “advertisements” by the tracking device, and can be secured by the tracking device to prevent interception by unauthorized entities, for instance entities masquerading as an associated mobile device or entities eavesdropping on tracking device advertisements to collect information about the tracking device.

(51) A tracking device (such as the tracking device **106** of FIG. **1**) can be configured to generate a hash value identifying the tracking device. The hash value can be dependent on one or more parameters associated with the tracking device, including but not limited to one or more of the following: a key stored by the tracking device, the MAC address of the tracking device (random or assigned to the tracking device by a tracking server, such as the tracking system **100** of FIG. **1**), a device identifier (such as a persistent identifier that uniquely identifies the tracking device), a time at which the hash value is generated, or any other suitable parameters. By generating a hash value based on a time at which the hash value is generated, the hash value can expire after a threshold amount of time elapses, or after the passage of a pre-defined time interval, as described below.

(52) In some embodiments, the generated hash value is represented by the function:

$$\text{hash_value} = f(\text{tracking_device_key}, \text{tracking_device_identifier}, \text{time})$$

(53) The tracking device can generate a hash value (or, in some embodiments, a keyed-hash value) using any suitable hashing function, such the SHA-X function, the MDX function, the RIPEMD function, the PANAMA function, the Tiger function, the WHIRLPOOL function, the Bernstein hash function, the Fowler-Noll-Vo hash function, the Jenkins hash function, the Pearson hash function, the Zobrist hash function, and the like. A keyed-hash message authentication code (HMAC) construction can be used for calculating the keyed-hash. Although hash functions are described herein, in other embodiments, the tracking device is configured to generate an encrypted or otherwise encoded value based on one or more device parameters using any suitable encryption or encoding function. The parameter “tracking_device_key” refers to a key stored by the tracking device, the parameter “tracking_device_identifier” refers to an identifier that uniquely identifies the tracking device, and the parameter “time” refers to the time interval or period during which the hash value is generated.

(54) FIG. **5** illustrates a process **500** of identifying a tracking device and an associated location, according to one embodiment. A tracking device **502** generates **510** a hash value based on one or more tracking device parameters, such as an assigned tracking device key, a persistent tracking device unique identifier, and a time or time interval during which the hash value is generated. The tracking device **502** can generate a new hash value periodically, after the passage of a pre-determined interval of time, in response to detected movement of the tracking device, or in response to any other suitable stimulus.

(55) The generated hash value **512** is advertised or broadcasted, for instance using the Bluetooth protocol, and is received by the mobile device **504**. In some embodiments, the tracking device **502** advertises the hash value periodically, a threshold number of times per generated hash value, in response to generating the hash value, or based on any other suitable criteria. It should be noted that the generated hash **512** can be advertised independent of or without communications from the mobile device **504**.

(56) The mobile device **504** receives the hash value and determines **514** whether the hash value can be resolved locally. To resolve a hash value locally, the mobile device **504** accesses a set of stored parameters for each tracking device associated with or “owned by” the mobile device **504** (such as a tracking device key and/or tracking device identifier assigned to the mobile device by a tracking server **506**), and generates a hash value for each owned tracking device using the same hash function and tracking device parameters as the tracking device **502**. If the received hash value matches any hash value generated by the mobile device **504**, the mobile device **504** identifies the tracking device **502** as the tracking device associated with the matched hash value, identifies the location of the tracking device **502**, and provides the tracking device identity and location **518** to the tracking server **506**. The tracking server **506** stores **520** the received tracking device identity in association with the received tracking device location.

(57) If none of the hash values generated by the mobile device **504** match the received hash value, or if the mobile device **504** does not have access to device parameters for tracking devices owned by the mobile device **504**, the mobile device **504** identifies **522** the location of the tracking device **502**, and forwards the received hash value and the identified location **524** to the tracking server **506**. The tracking server **506** resolves **526** the hash value by generating a hash value for each tracking device tracked by or associated with the tracking server **506** using associated device parameters maintained by the tracking server **506**. The tracking server **506** identifies **528** the tracking device **502** by matching the received hash value to a hash value generated by the tracking server **506**. Upon identifying the tracking device **502**, the tracking server **506** stores **530** the received location in association with the identity of the tracking device **502**.

(58) The tracking server **506** can be configured to pre-generate hash values for each tracking device associated with the tracking server **506**, and to store the pre-generated hash values in, for example, a hash table. For instance, for hash values generated using, as one tracking device parameter, the hour interval (such as 10:00 am-11:00 am PDT) during which the hash value is generated, the tracking server **506** can generate hash values for each tracking device associated with the tracking server **506** every hour. If a hash value generated in a previous hour interval is received at the tracking server **506**, the tracking server **506** may not be able to resolve the hash value using hash values generated during a current hour interval. In such instances, the received hash value has “expired”, and the tracking server **506** ignores the expired hash value, waits for a subsequent/non-expired hash value from the tracking device **502** (via the mobile device **504**), and resolves the subsequent hash value. It should be noted that although examples are given with regards to hour intervals, hash values can be generated and expire with regards to any time interval, such as the 5-minute interval, the 15-minute interval, the 6-hour interval, the 24-hour interval, and the like.

(59) In order to synchronize maintained times between the tracking device **502**, the mobile device **504**, and the tracking server **506**, the tracking device **502** can authenticate the mobile device **504** and/or tracking server **506**, and can synchronize a timing tracker at the tracking device **502** in response to the authentication. Alternatively, the tracking device **502** can synchronize a timing tracker at the tracking device **502** using an external entity, in response to the manual synchronization of the timing tracker by a user, or using any other suitable synchronization means. In some embodiments, the mobile device **504** can determine that a tracking device **502** is out of synch by resolving an expired hash value received from the tracking device and determining that the resolved hash value has expired. In response to determining that the tracking device **502** is out of synch, the mobile device **504** can trigger a re-synchronization by connecting to the tracking

device and updating the tracking device's timing information. In some embodiments, re-synchronization occurs during a grace period, for instance a threshold period of time after new hash values associated with a time interval are generated.

(60) The hash function used by the tracking device **502** can produce hash values of any suitable size or length. In some embodiments, the length of the hash value or the type of hash function is selected based on available power, time, or any other characteristic of the tracking device **502** or tracking server **506**. In some embodiments, the length of the hash value is selected based on a pre-determined acceptable collision rate. Collisions occur when the tracking server **506** generates the same hash value for two or more tracking devices during a particular time interval. Collisions can be resolved by comparing a previous known/stored location for each tracking device associated with the collision and the received location associated with the received hash value. For instance, if a previous known/stored location for a particular tracking device associated with a collision is within a threshold distance of a received location, the tracking device **502** can identify the particular tracking device from among the tracking devices associated with the collision as the tracking device associated with the received location. In some embodiments, the tracking server **506** can simply ignore received hash values associated with collisions until a new hash value generated during a subsequent time interval is received, and can resolve the new hash value accordingly.

(61) It should be noted that in some embodiments, the hash values described herein are included within a communication packet that also includes other types of data. For instance, a packet can include a hash value and one or more of: information describing a broadcast power by the tracking device **502**, a time of communication, an identity of the mobile device **504** associated with the tracking device, an identity of a user associated with the tracking device, a digital signature for use in verifying the identity of the tracking device or the authenticity of the communication packet, or any other suitable information.

(62) In some embodiments, the “time” variable in the hash function described above is an incremented time interval value. For example, the value of the time variable for the first 15 minute interval of a calendar year is “00001”, the value of the time variable for the second 15 minute interval is “00002”, and so forth. In order to align the value of the time variable used in computing the hash value, the tracking device **502** can include the value of the time variable in plaintext in a header of an advertisement packet that includes the hash value. In such embodiments, a mobile device **504** or tracking server **506** can parse the value of the time variable included within the header, and can compute hash values for tracking devices associated with the mobile device or tracking server using the parsed value of the time variable for comparison with the hash value included within the advertisement packet.

(63) For collisions, in addition to using the geographic location of the tracking device to resolve collisions between hash values, the geographic location of or associated with a user can be used. For example, if a first hash value is associated with a first tracking device and a second hash value is associated with a second tracking device, a collision between the first hash value and the second hash value can be resolved by determining that the location of the mobile device from which each hash value was received is within a threshold distance of a geographic location associated with an owner of the first tracking device, and by selecting the first tracking device as associated with the received hash value.

(64) Likewise, collisions between hash values can be resolved by using account information associated with tracking device users. For instance, if a user is associated with a user account that is in turn associated with a mobile device, and a hash value associated with a collision was received from the mobile device, a tracking device associated with the mobile device can be selected as associated with the hash value. Further, a hash value collision can be resolved based on a most recent incremented “time” variable value associated with each tracking device associated with the hash value collision. For instance, if a first hash value is associated with a first tracking device

from which a hash value generated using the time value “00034” was recently received, if a second hash value is associated with a second tracking device from which a hash value generated using the time value “29531” was recently received, and if the hash values associated with the hash value collision are generated using the time values “00035” and “14224”, the first tracking device can be selected as associated with the received hash value since “00034” is closer to “00035” than “29531” is to “00035” or “14224”. In other words, a tracking device can be selected based on how proximal or close an incremented time or counter value associated with a collision is to a time or counter value recently used by a tracking device associated with the collision, without requiring the transmission of the incremented value itself.

(65) In some embodiments, the tracking server **506** attempts to resolve collisions first using user account information as described above. In the event that the collision cannot be resolved using account information, the tracking server attempts to resolve the collision using proximity of incremented time or counter values recently used by a tracking device in generating a hash value to time or counter values used to generate hash values associated with a collision. In the event that the collision still cannot be resolved, the tracking server can then attempt to resolve the collision using a proximity of a geographic location of a mobile device, tracking device, or user to a tracking device associated with a collision.

(66) Replay attacks, or the use of a hash value intercepted by an unauthorized entity to attempt to authenticate a tracking device, can be avoided by tracking incremented time or counter values associated with a tracking device. For instance, when a hash value is received from a tracking device, the tracking server **506** can update a stored time/counter value associated with the tracking device. When a subsequent hash value is received that is associated with a lower or earlier time/counter value, the tracking server can disregard the hash value and can deny a request to authenticate the tracking device.

(67) In embodiments where each time or counter value used to generate a first hash value is associated with a particular time interval (e.g., 15 minutes), the tracking server can deny a request to authenticate a tracking device from which a subsequent hash value is received based on the same time or counter value if the subsequent hash value is received outside of the time interval (for instance, continuing with the previous example, if the subsequent hash value is received 20 minutes after the first hash value is received). The tracking server can increment tracked time or counter values for a tracking device based on an amount of time that has lapsed since a hash value associated with a tracked time or counter value was received. Thus, if a hash value is received from a tracking device that is generated using a time or counter value outside of an expected range for the tracking device (e.g., a time or counter value occurring before a tracked time or counter value for the tracking device, or occurring more than a threshold distance beyond from a tracked time or counter value incremented by the tracking server), the tracking server can disregard the received hash value and/or deny a request to authenticate a corresponding tracking device.

(68) Motion-Activated Location Determination

(69) To determine the location of a tracking device, such as the tracking device **106** of FIG. 1, the tracking device emits a location-request beacon or advertisement signal (location request). In response to receiving the beacon or advertisement signal, a mobile device, such as the mobile device **104** of FIG. 1, uses location-determining functionality (such as a GPS receiver) to determine the location of the mobile device. Being in close proximity with the tracking device, the location of the mobile device is associated with the tracking device. However, the use of location-determining functionality by the mobile device is often very power-consuming, resulting in the draining of the mobile device's battery or other power source.

(70) To offset the drain of power by the location-determining functionality of the mobile device, the tracking device can be configured to emit a location request only in response to the detection of movement by the tracking device. When the tracking device is not moving, the location of the tracking device doesn't change, and a previous determined location (determined in response to the

detection of a previous movement) is sufficient to describe the location of the tracking device.

(71) In other embodiments, the tracking device is configured to emit a location request either in response to the detection of movement by the tracking device, at a fixed interval, or in response to a request from a mobile device. In such embodiments, the tracking device can include a time stamp within the location request indicating a time associated with the last detected movement of the tracking device. In response to receiving a location request from the tracking device by a mobile device, the mobile device can determine based on the time associated with the last detected movement of the tracking device if the tracking device has moved since the last time a high-accuracy location was determined for the tracking device. For instance, if a tracking device is within a threshold distance from the mobile device when the mobile device receives a location request, the mobile device can associate the tracking device with the location of the mobile device, and can determine that the associated location is a “high-accuracy” location.

(72) If the mobile device subsequently moves more than the threshold distance away from the tracking device and receives a location request, and if the location request includes a timestamp indicating that the tracking device hasn't moved since the mobile device associated the tracking device with the location of the mobile device from within a threshold distance from the tracking device, then the mobile device can maintain the association between previous location and the tracking device as a high-accuracy location. On the other hand, if the location request includes a timestamp indicating that the tracking device has since moved, the mobile device can associate the location of the mobile device with the tracking device, though because the distance between the mobile device and tracking device is greater than the threshold distance, the associated location is maintained as a low-accuracy location. It should be noted that in some embodiments, the location request can include an indication of movement magnitude. In such embodiments, the mobile device can determine that a previous high-accuracy location is still a high-accuracy location if the magnitude of movement is below a movement threshold. Alternatively, if the movement is greater than the movement threshold, the mobile device can determine that the previous high-accuracy location is now a low-accuracy location, or can associate the new location of the mobile device with the tracking device as a low-accuracy location.

(73) In some embodiments, the threshold distance described above is a distance such that the tracking device sends communications to the mobile device, but such that the mobile device cannot send communications to the tracking device (in other words, the tracking device is outside of the range of the mobile device). In some embodiments, the threshold distance is a pre-determined distance such that location information of the mobile device and associated with the tracking distance is above a threshold accuracy (a “high-accuracy” location) when the mobile device is within the threshold distance of the tracking device and is below a threshold accuracy (a “low accuracy” location) when the mobile device is outside the threshold distance from the tracking device. In some embodiments, the location request from the tracking device includes an indication of strength of transmission power. In such embodiments, the indicated strength of transmission power can be used to determine if the mobile device is within the threshold distance of the mobile device.

(74) The tracking device can include one or more movement-detection mechanisms. For example, the tracking device can include a gyroscope, an accelerometer configured to detect movement along one or more axes, an acoustic motion sensor, a vibration sensor, a spring-based motion detector, or any other suitable mechanism. In some embodiments, the type of motion detection implemented within the tracking device can be basic, as the mere detection of motion in any form can be sufficient to trigger a location request. In such embodiments, rudimentary and/or low-power motion detectors can be implemented within the tracking device, beneficially reducing the cost of and/or power used by the tracking device.

(75) FIG. 6 illustrates a process 600 of determining device location in response to movement detection, according to one embodiment. A tracking device 602 detects 610 movement using, for

instance, one or more motion-detection devices within the tracking device **602**. In response to detecting the movement, the tracking device **602** sends a movement flag **612** or other indication of the movement to a mobile device **604**. In response to receiving the movement flag **612**, the mobile device powers on **614** a location-detection receiver, such as a GPS receiver, and accesses location information associated with the location of the mobile device **604** (and, due to the proximity of the tracking device **602** to the mobile device **604**), the location of the tracking device **602**.

(76) The mobile device **604** provides the identity and location **618** of the tracking device **602** to the tracking server **606**. The tracking server stores **620** the received location in association with the identity of the tracking device **602**, and provides a confirmation **622** of the storage of the received location to the mobile device **604**. In response to receiving the storage confirmation **622**, the mobile device **604** powers off the location-detection receiver. It should be noted that in embodiments where the mobile device **604** does not receive the confirmation **622** from the tracking server **606**, the mobile device **604** can re-send the tracking device identity and location to the tracking server **606**. In some embodiments, the mobile device **604** can power off the receiver immediately after providing the tracking device identity and location to the tracking server **606**.

(77) The mobile device **604** provides confirmation **626** of the storage of the tracking device location by the tracking server **606** to the tracking device **602**. In response to receiving the confirmation **626**, the tracking device **602** enters standby mode **628** until subsequent movement is detected. In embodiments where the tracking device **602** does not receive the confirmation **626**, the tracking device **602** can re-send the movement flag **612** to the mobile device **604**. In some embodiments, the mobile device **604** provides confirmation of providing the tracking device identity and location to the tracking server **606** to the tracking device **602** without waiting to receive the confirmation **622** that the location was stored from the tracking server **606**, and in response, the tracking device **602** can enter the standby mode **628**. By only powering on the location-detection receiver in response to the detection of movement by the tracking device **602**, the mobile device **604** saves power that would otherwise be required to power on the location-detection receiver during periods of time when the tracking device **602** is not moving.

(78) FIG. 7 illustrates a process **700** of selecting between current or previous device location information, according to one embodiment. The tracking device **702** detects **710** movement, for instance using one or more location-detection devices as described above. In response, the tracking device **702** provides movement information **712** to the mobile device **704**. The movement information **712** can include, for instance, a magnitude of detected movement.

(79) In response to receiving the movement information **712**, the mobile device **704** accesses location information **716**, for instance using location-detection mechanisms, as described above. Although not illustrated in FIG. 7, the mobile device **704** can implement the power-saving process of FIG. 6 by powering on the location-detection mechanisms of the mobile device **704** only in response to receiving the movement information **712**.

(80) The mobile device **704** provides the identity, location, and movement information **718** of the tracking device **702** to the tracking server **706**. The tracking server **706** stores **720** the received location in association with the tracking device **702** as the current location of the tracking device. The tracking server **706** accesses **722** a previous location associated with the tracking device **702** stored by the tracking server **706**.

(81) The tracking server **706** then selects one or both of the current location and the previous location of the tracking device **702** for providing to the mobile device **704**. In some embodiments, the tracking server **706** can select the location of the tracking device **702** determined to be the most accurate. For instance, if the received movement information indicates that the detected movement of the tracking device **702** is very small and/or that the accuracy of the received current location is low (for instance, as a result of the tracking device **702** being determined to be more than a first threshold distance from the mobile device **704**), the tracking server **706** can determine that the previous location is more accurate than the current location, and can select the previous location.

(82) Alternatively, if the accessed previous location was received and stored more than a threshold amount of time ago and/or the accuracy of the received current location is high (for instance, as a result of the tracking device **702** being determined to be less than a second threshold distance from the mobile device **704**), the tracking server **706** can determine that the current location is more accurate than the previous location. In some embodiments, the tracking server **706** can determine that the current location and the previous location are equally or within a threshold measurement of accuracy to each other and can select both locations. In some embodiments, when the tracking server **706** determines that the current location is more accurate or reliable than the previous location, the tracking server **706** overrides the previous location with the current location in association with the identity of the tracking device **702**.

(83) The tracking server **706** provides the one or more select locations **726** to the mobile device **704**. In response, the mobile device **704** presents **728** the one or more selected locations, for instance to a user of the mobile device **704**. Alternatively, the mobile device **704** can store the one or more selected locations for subsequent access. The mobile device **704** can then provide confirmation **730** to the tracking device **702** that the current location was received and/or stored by the tracking server **706**. In response, the tracking device **702** can enter standby mode **732** until subsequent motion of the tracking device **702** is detected.

(84) End-to-End Encryption in a Tracking Device Environment

(85) In order to facilitate data privacy within the tracking device environment, data protection measures can be implemented by a central tracking system (e.g., tracking system **100**, or “tracking server” herein). As described herein, a permanent encryption key pair associated with a tracking device can be used to encrypt the temporary private keys of one or more temporary encryption key pairs associated with the tracking device, and the central tracking system can store the temporary public keys and the encrypted temporary private keys. Community mobile devices that detect the tracking device can encrypt location data using the temporary public keys, and the central tracking system can provide the encrypted location data to an owner of the tracking device for decryption.

(86) Such data protection measures enable location data to be protected at the moment it is gathered (by community mobile devices), as it is provided to and stored by the central tracking system, and as it is provided to an owner of the tracking device. In such an implementation, only an owner of the tracking device (or an individual with whom the tracking device has been shared) is able to decrypt the encrypted temporary private keys, which in turn are used to decrypt the location data. Accordingly, an entity associated with the central tracking system (such as a database manager) is unable to decrypt the location data, beneficially protecting the location data from the moment it is gathered by a community mobile device until it is received by an owner of the tracking device.

(87) As noted above, a tracking device associated with an identifier can use a set hash keys to hash the identifier, and can include the hashed identifier in an advertising packet that is transmitted periodically. These hash keys can be rotated such that, for instance, a new hash key can be used every 15 minutes. The hash keys can be generated in advance, for instance, by a manufacturer of the tracking device, by a tracking server associated with the tracking device, by a device associated with the tracking device (such as a mobile device of an owner of the tracking device), or by the tracking device itself. The hash keys can also be generated on-demand, for instance based on a current time interval within which the tracking device identifier is to be hashed. In some embodiments, the hash keys are generated using a hash key algorithm. In such embodiments, the tracking device (or a device associated with the tracking device) and the central tracking system can each independently generate the same set of hash keys using a hash key algorithm, beneficially enabling the central tracking system to store and associate the set of hash keys with the tracking device without requiring the transmission of the set of hash keys between the tracking device (or the device associated with the tracking device) and the central tracking system.

(88) A permanent encryption key pair (including a permanent public key and a permanent private key) is generated for the tracking device. The permanent encryption key pair can be generated

during the manufacture of the tracking device, upon activation of the tracking device, upon registration of the tracking device with a central tracking system, or at any other suitable time. The permanent encryption key pair can be generated by the manufacturer, by an owner device associated with the tracking device, by the central tracking system, or by any other suitable entity. The owner device (such as a mobile device associated with an owner of the tracking device and configured to communicate with the tracking device) can store the permanent public key and the permanent private key. The owner device can provide the permanent public key to the central tracking system for storage in association with an identifier of the tracking device. Although the permanent public key is transmitted to the central tracking system, the permanent public key can be kept confidential, since the permanent public key may otherwise be used to uniquely identify the tracking device.

(89) A set of temporary encryption key pairs are generated for the tracking devices. Each temporary encryption key pair includes a temporary private key and a temporary public key. The temporary encryption key pairs can be generated using any suitable encryption key generation method, for instance the Rivest-Shamir-Adleman (“RSA”) algorithm or an elliptic-curve cryptography (“ECC”) algorithm. The set of temporary encryption key pairs can include one encryption key pair or any number of encryption key pairs. In some embodiments, one encryption key pair is generated for each hash key in the set of hash keys used by the tracking device. The set of temporary encryption key pairs can be generated upon activation of a tracking device, for instance by an owner mobile device used to activate the tracking device. Alternatively, the set of temporary encryption key pairs can be generated periodically or in response to an event (such as a request from an owner of the tracking device, a complete rotation through a previous set of temporary encryption key pairs, and the like).

(90) In some embodiments, the set of temporary encryption key pairs can be generated by an owner mobile device or by another device of the owner, while in other embodiments, the set of temporary encryption key pairs can be generated by the central tracking system, by the tracking device, by a manufacturer of the tracking device, or by any other suitable entity. The temporary private key of each temporary encryption key pair associated with a tracking device can be encrypted (for instance, by an owner mobile device, by the tracking device, by the central tracking system, or by any other entity) using the permanent public key associated with the tracking device. Each encrypted temporary encryption key pair (including the encrypted temporary private key and the associated temporary public key) is then provided to the central tracking system for distribution to mobile devices that subsequently detect the tracking device as described below.

(91) FIG. 8 is an interaction diagram illustrating a process for implementing end-to-end encryption in a tracking device environment, according to one embodiment. The environment **800** of FIG. 8 includes a tracking device **802**, a community mobile device **804**, a tracking server **806**, and an owner mobile device **808**. In the embodiment of FIG. 8, the owner mobile device **808** encrypts **810** the temporary private key of each temporary encryption key pair associated with the tracking device **802** using the permanent public key associated with the tracking device **802** (which the owner mobile device **808** can access). As noted above, in some embodiments, the owner mobile device **808** generates the set of temporary encryption key pairs in advance, for instance generating one temporary encryption key pair for each hash key associated with the tracking device **802**. The owner mobile device **808** then provides **812** the encrypted temporary key pairs (each including a temporary public key and the corresponding encrypted temporary private key) to the tracking server **806** for storage.

(92) After the tracking server **806** stores the encrypted temporary key pairs, the tracking device **802** generates **814** a hashed identifier (“hash ID”) for inclusion in periodic advertisement beacon transmissions. The hash key used to hash the unique identifier of the tracking device **802** can be selected based on a current time interval during which the hashed identifier is generated. For instance, each 15-minute interval within a year can be associated with a different hash key of a set

of hash keys. The community mobile device **804** receives **816** the hashed identifier from the tracking device **802**, for instance after moving within a threshold proximity of the tracking device and receiving an advertisement beacon transmission from the tracking device. The community mobile device **804** provides **818** the hashed identifier to the tracking server **806**.

(93) The tracking server **806** identifies **820** the tracking device **802** by identifying the hash key used to generate the hashed identifier, and identifying the tracking device associated with the identified hash key. The tracking server **806**, upon identifying the tracking device **802**, identifies an encrypted temporary encryption key pair. In embodiments in which there is a 1-to-1 relationship between the set of hash keys and encrypted temporary encryption key pairs, the identified encrypted temporary encryption key pair comprises the encrypted temporary encryption key pair associated with the hash key used to generate the hashed identifier. The tracking server **806** then provides **822** the identified encrypted temporary encryption key pair to the community mobile device **804**.

(94) The community mobile device **804** determines a location of the community mobile device, for instance by activating a GPS receiver and determining a set of GPS coordinates representative of the location of the community mobile device. Upon receiving the encrypted temporary encryption key pair, the community mobile device **804** encrypts **824** data representative of the determined location of the community mobile device using the temporary public key of the received encrypted temporary encryption key pair. The community mobile device **804** then provides **826** the hashed identifier, the encrypted location, and the encrypted temporary private key to the central tracking system. The central tracking system stores **828** the received hash identifier, the encrypted location data, and the encrypted temporary private key **868**, for instance within a “last known location” field associated with the tracking device.

(95) At a later time, the owner mobile device **808** requests **830** a current, most recent, or last known location of the tracking device **802**. In response to receiving the request, the tracking server **806** accesses **832** the hashed identifier, the encrypted location data, and the encrypted temporary private key and provides this information to the owner mobile device **808**. The owner mobile device decrypts **834** the encrypted temporary private key using the permanent private key (to which the owner mobile device has access), and then decrypts **836** the encrypted location data using the decrypted temporary private key. The decrypted location data can be displayed by the owner mobile device **808**, for instance within a map interface.

(96) FIG. 9 illustrates a process for implementing end-to-end encryption in a tracking device environment, according to one embodiment. A permanent encryption key pair and a temporary encryption key pair associated with a tracking device are generated **902**. The permanent encryption key pair includes a permanent public key and a permanent private key. Likewise, the temporary encryption key pair includes a temporary public key and a temporary private key. In some embodiments, a set of temporary encryption key pairs are generated, for instance one for each rotatable hash key associated with a tracking device.

(97) The temporary private key of each temporary encryption key pair is encrypted **904** using the permanent public key. Each encrypted temporary encryption key pair (including a temporary public key and a corresponding encrypted temporary private key) is provided **906** to a central tracking system. The central tracking system stores each encrypted temporary encryption key pair in association with an identifier of the associated tracking device. For instance, if the central tracking system receives five sets of encrypted temporary encryption key pairs each associated with a different tracking device of five tracking devices, the central tracking system can store each set of encrypted temporary encryption key pairs in association with an identifier of the tracking device associated with the set of encrypted temporary encryption key pairs.

(98) When a community mobile device (such as a mobile device not otherwise associated with the tracking device) receives a hashed tracking device identifier from the tracking device, the community mobile device provides **908** the received hash tracking device identifier to the central

tracking system. The central tracking system then identifies the tracking device associated with the received hashed tracking device identifier (for instance, by hashing each of a set of tracking device identifiers with each of a corresponding set of hash keys). In response to identifying the tracking device associated with the received hashed tracking device identifier, the central tracking system provides and the community mobile device receives **910** an encrypted temporary encryption key pair associated with the identified tracking device.

(99) The community mobile device then determines a location of the community mobile device (for instance, by activating the GPS receiver of the community mobile device), and encrypts **912** location data representative of the determined location using the temporary public key of the received encrypted temporary encryption key pair. The community mobile device then provides **914** the encrypted location data and the encrypted temporary private key of the received encrypted temporary encryption key pair to the central tracking system, which stores the encrypted location data and the encrypted temporary private key in association with an identity of the tracking device. In some embodiments, the community mobile device resends the hashed tracking device identifier with the encrypted location data and the encrypted temporary private key to the central tracking system, and the central tracking system determines the identity of the tracking device using the hashed tracking device identifier as described above.

(100) When a user requests a location of the tracking device from the central tracking system, a user device with access to the permanent private key receives **916** the encrypted location data and the encrypted temporary private key from the central tracking system. The user device decrypts **918** the encrypted temporary private key using the permanent private key, and then decrypts **920** the encrypted location data using the decrypted temporary private key. The user device can then perform an action based on the decrypted location data, such as displaying the decrypted location data, for instance within a map interface or an operating system notification.

(101) In some embodiments, instead of generating temporary encryption key pairs (as described above), a temporary private key can be used to generate a set of one or more diversified temporary public keys. Data encrypted using any of the set of diversified temporary public keys can be decrypted using the temporary private key. Any suitable key diversification operation can be used to generate the set of diversified temporary public keys. For instance, the set of diversified temporary public keys can be generated using Elgamal encryption, Elliptic Curve Integrated Encryption Scheme (ECIES) encryption, Networking and Cryptography library (NaCl) encryption, or any other suitable key diversification algorithm. In some embodiments, the set of diversified temporary public keys are generated based on the temporary private key, and can be generated using one or more additional secrets (such as a set of elliptical curves, a secret value unique to the tracking device or an account of an owner of the tracking device, or any other suitable information).

(102) FIG. **10** is an interaction diagram illustrating a process for implementing end-to-end encryption in a tracking device environment using key diversification, according to one embodiment. In the embodiment of FIG. **10**, an owner mobile device **1008** generates **1010** a diversified public key associated with a private key and provides **1012** the diversified public key to a tracking server **1006**. In other embodiments, a set of diversified public keys are generated and provided to the tracking server **1006**, and may be generated by an entity other than the owner mobile device **1008** (for instance, by the tracking server **1006** itself, by a key server, by a manufacturer of the tracking device **1002**, or by any other suitable entity). In some embodiments, the diversified public keys are provided to a key server (not shown in the embodiment of FIG. **10**) instead of the tracking server **1006**. The key server can be associated with a different entity or company than the tracking server **1006**, for instance a mobile phone service operator, a mobile device manufacturer, and the like.

(103) As described above, the tracking server **1006** (or a key server) can associate each diversified public key in the set of diversified public keys with a different hash key of a set of hash keys

associated with the tracking device **1002**. In other embodiments, the set of diversified public keys are unique to the tracking device **1002**, and can be used to identify the tracking device (or can be used by the tracking device to generate a hashed identifier) in place of the set of hash keys. In such embodiments, a community mobile device can receive the diversified public key directly from the tracking device **1002**, or can forward the hashed identifier hashed using the diversified public key to the tracking server **1006** or a key server, and can receive the diversified public key from the tracking server or key server, respectively, in response.

(104) The tracking device **1002** generates **1014** a hashed identifier (“hash ID”) for inclusion in periodic advertisement beacon transmissions. The hash key used to hash the unique identifier of the tracking device **1002** can be selected based on a current time interval during which the hashed identifier is generated. For instance, each 15-minute interval within a year can be associated with a different hash key of a set of hash keys. The community mobile device **1004** receives **1016** the hashed identifier from the tracking device **1002**, for instance after moving within a threshold proximity of the tracking device and receiving an advertisement beacon transmission from the tracking device. The community mobile device **1004** provides **1018** the hashed identifier to the tracking server **1006**.

(105) As described above, the tracking server **1006** identifies **1020** the tracking device **1002** by identifying the hash key used to generate the hashed identifier, and identifying the tracking device associated with the identified hash key. The tracking server **1006**, upon identifying the tracking device **1002**, identifies a diversified public key from the set of diversified public keys. In embodiments in which there is a 1-to-1 relationship between the set of hash keys and the set of diversified public keys, the identified diversified public key comprises the diversified public key associated with the hash key used to generate the hashed identifier. The tracking server **1006** then provides **1022** the identified diversified public key to the community mobile device **1004**.

(106) The community mobile device **1004** determines a location of the community mobile device, for instance by activating a GPS receiver and determining a set of GPS coordinates representative of the location of the community mobile device. Upon receiving the diversified public key, the community mobile device **1004** encrypts **1024** data representative of the determined location of the community mobile device using the diversified public key. The community mobile device **1004** then provides **1026** the hashed identifier and the encrypted location to the central tracking system **1006**. The central tracking system **1006** stores **1028** the received hash identifier and the encrypted location data, for instance within a “last known location” field associated with the tracking device.

(107) At a later time, the owner mobile device **1008** requests **1030** a current, most recent, or last known location of the tracking device **1002**. In response to receiving the request, the tracking server **1006** provides **1032** the hashed identifier and the encrypted location data to the owner mobile device **1008**. The owner mobile device decrypts **1034** the location data using the private key associated with the set of diversified public keys. The decrypted location data can be displayed by the owner mobile device **1008**, for instance within a map interface.

(108) Although not illustrated in the embodiment of FIG. **10**, it should be noted that similarly to the embodiment of FIG. **8**, the private key can be encrypted using a permanent public key associated with the owner mobile device **1008**, an account associated with the owner mobile device, the tracking device **1002**, and the like. The encrypted private key can be provided to the tracking server **1006** for storage, and the tracking server **1006** can provide the encrypted private key to the owner mobile device **1008** with the hashed identifier and the encrypted location data. The owner mobile device **1008** can then decrypt the encrypted private key using a permanent private key corresponding to the permanent public key, and the decrypt the location data using the decrypted private key.

(109) FIG. **11** illustrates a process for implementing end-to-end encryption in a tracking device environment using key diversification, according to one embodiment. A set of diversified public encryption keys associated with a private encryption key is generated **1102**, for instance using

Elgamal encryption, ECIES encryption, NaCl encryption, or any other suitable key diversification operation. The set of diversified public encryption keys is provided **1104** to a central tracking system. As noted above, the set of diversified public encryption keys may instead be provided to a key server.

(110) A community mobile device provides **1106** a received hashed tracking device identifier to the central tracking system (or to a key server, in the event that the key server is storing the set of diversified public encryption keys). The community mobile device receives **1108** a diversified public encryption key from the central tracking system (or key server). The received diversified public encryption key can be selected based on the hashed identifier, the hash key used to generate the hashed identifier, a current time, or randomly. The community mobile device accesses location data representative of a location of the community mobile device and encrypts **1110** the location data using the diversified public encryption key. The encrypted location data is then provided **1112** to the central tracking system for storage.

(111) At a later time, an owner of the tracking device can request and receive **1114** the encrypted location data from the central tracking system via an owner device. The owner device can decrypt **1116** the encrypted location data using the private encryption key corresponding to the set of diversified public encryption keys, and can display the location data to a user, for instance within a map interface. In some embodiments, the private encryption key can decrypt the encrypted location data despite which of the set of diversified public encryption keys is used to encrypt the location data.

Additional Considerations

(112) The foregoing description of the embodiments of the invention has been presented for the purpose of illustration; it is not intended to be exhaustive or to limit the invention to the precise forms disclosed. Persons skilled in the relevant art can appreciate that many modifications and variations are possible in light of the above disclosure.

(113) Any of the devices or systems described herein can be implemented by one or more computing devices. A computing device can include a processor, a memory, a storage device, an I/O interface, and a communication interface, which may be communicatively coupled by way of communication infrastructure. Additional or alternative components may be used in other embodiments. In particular embodiments, a processor includes hardware for executing computer program instructions by retrieving the instructions from an internal register, an internal cache, or other memory or storage device, and decoding and executing them. The memory can be used for storing data or instructions for execution by the processor. The memory can be any suitable storage mechanism, such as RAM, ROM, flash memory, solid state memory, and the like. The storage device can store data or computer instructions, and can include a hard disk drive, flash memory, an optical disc, or any other suitable storage device. The I/O interface allows a user to interact with the computing device, and can include a mouse, keypad, keyboard, touch screen interface, and the like. The communication interface can include hardware, software, or a combination of both, and can provide one or more interfaces for communication with other devices or entities.

(114) Some portions of this description describe the embodiments of the invention in terms of algorithms and symbolic representations of operations on information. These algorithmic descriptions and representations are commonly used by those skilled in the data processing arts to convey the substance of their work effectively to others skilled in the art. These operations, while described functionally, computationally, or logically, are understood to be implemented by computer programs or equivalent electrical circuits, microcode, or the like. Furthermore, it has also proven convenient at times, to refer to these arrangements of operations as modules, without loss of generality. The described operations and their associated modules may be embodied in software, firmware, hardware, or any combinations thereof.

(115) Any of the steps, operations, or processes described herein may be performed or implemented with one or more hardware or software modules, alone or in combination with other devices. In one

embodiment, a software module is implemented with a computer program product comprising a computer-readable medium containing computer program code, which can be executed by a computer processor for performing any or all of the steps, operations, or processes described.

(116) Embodiments of the invention may also relate to an apparatus for performing the operations herein. This apparatus may be specially constructed for the required purposes, and/or it may comprise a general-purpose computing device selectively activated or reconfigured by a computer program stored in the computer. Such a computer program may be stored in a non-transitory, tangible computer readable storage medium, or any type of media suitable for storing electronic instructions, which may be coupled to a computer system bus. Furthermore, any computing systems referred to in the specification may include a single processor or may be architectures employing multiple processor designs for increased computing capability.

(117) Embodiments of the invention may also relate to a product that is produced by a computing process described herein. Such a product may comprise information resulting from a computing process, where the information is stored on a non-transitory, tangible computer readable storage medium and may include any embodiment of a computer program product or other data combination described herein.

(118) Finally, the language used in the specification has been principally selected for readability and instructional purposes, and it may not have been selected to delineate or circumscribe the inventive subject matter. It is therefore intended that the scope of the invention be limited not by this detailed description, but rather by any claims that issue on an application based hereon. Accordingly, the disclosure of the embodiments of the invention is intended to be illustrative, but not limiting, of the scope of the invention, which is set forth in the following claims.

Claims

1. A method comprising: encrypting, by an owner mobile device, a temporary private key in an encryption key pair using a permanent public key of a permanent encryption key pair to produce an encrypted temporary encryption key pair with an encrypted temporary private key; providing, by the owner mobile device, the encrypted temporary encryption key pair to a central tracking system, the central tracking system configured to associate the encrypted temporary encryption key pair with a hash key of a set of hash keys associated with a tracking device; providing, by a community mobile device, a hashed identifier received from the tracking device to the central tracking system, the central tracking system configured to identify a hash key used to create the hashed identifier, to identify the encrypted temporary encryption key pair as associated with the identified hash key, and to provide the encrypted temporary encryption key pair to the community mobile device; encrypting, by the community mobile device, location data representative of a location of the community mobile device using the temporary public key of the encrypted temporary encryption key pair to produce encrypted location data; providing, by the community mobile device, the hashed identifier, the encrypted temporary private key of the encrypted temporary encryption key pair, and the encrypted location data to the central tracking system for storage; decrypting, by the owner mobile device, the encrypted temporary private key received by the owner mobile device from the central tracking system using a permanent private key of the permanent encryption key pair; decrypting, by the owner mobile device, the encrypted location data received by the owner mobile device from the central tracking system using the decrypted temporary private key to produce decrypted location data; and displaying, by the owner mobile device, the decrypted location data; wherein the set of hash keys is generated independently by the tracking device and the central tracking system.
2. The method of claim 1, wherein the permanent encryption key pair is generated by the owner mobile device.
3. The method of claim 1, wherein the permanent encryption key pair is generated by the central

tracking system.

4. The method of claim 1, wherein the permanent encryption key pair is generated in response to activating the tracking device.

5. The method of claim 1, wherein the set of hash keys is unique to the tracking device, and wherein the central tracking system is configured to associate the set of hash keys with a unique identifier of the tracking device.

6. The method of claim 1, wherein the temporary encryption key pair is generated using an Rivest-Shamir-Adleman (“RSA”) algorithm or an elliptic-curve cryptography (“ECC”) algorithm.

7. The method of claim 1, wherein a temporary encryption key pair is generated using a hash key of the set of hash keys associated with the temporary encryption key pair.

8. The method of claim 1, wherein the tracking device is configured to include the hashed identifier in an advertising packet transmitted by the tracking device.

9. The method of claim 1, wherein the community mobile device, in response to receiving the hashed identifier from the tracking device, is configured to activate a GPS receiver of the community mobile device and to determine the location of the community mobile device using the GPS receiver, the determined location comprising the location data.

10. The method of claim 1, wherein the central tracking system does not have access to the permanent private key.

11. The method of claim 1, wherein the central tracking system does not have access to the decrypted temporary private key.

12. The method of claim 1, wherein the central tracking system is unable to decrypt the encrypted location data.

13. The method of claim 1, wherein requesting the location of the tracking device comprises requesting a last known location of the tracking device from the central tracking system.

14. The method of claim 1, wherein displaying the decrypted location data comprises displaying the location of the tracking device within a map interface.

15. The method of claim 1, wherein displaying the decrypted location data comprises displaying a notification via an operating system of the owner mobile device.

16. A non-transitory computer-readable storage medium storing executable instructions that, when executed by a processor, cause the processor to perform steps comprising: encrypting, by an owner mobile device, a temporary private key in an encryption key pair using a permanent public key of a permanent encryption key pair to produce an encrypted temporary encryption key pair with an encrypted temporary private key; providing, by the owner mobile device, the encrypted temporary encryption key pair to a central tracking system, the central tracking system configured to associate the encrypted temporary encryption key pair with a hash key of a set of hash keys associated with a tracking device; providing, by a community mobile device, a hashed identifier received from the tracking device to the central tracking system, the central tracking system configured to identify a hash key used to create the hashed identifier, to identify the encrypted temporary encryption key pair as associated with the identified hash key, and to provide the encrypted temporary encryption key pair to the community mobile device; encrypting, by the community mobile device, location data representative of a location of the community mobile device using the temporary public key of the encrypted temporary encryption key pair to produce encrypted location data; providing, by the community mobile device, the hashed identifier, the encrypted temporary private key of the encrypted temporary encryption key pair, and the encrypted location data to the central tracking system for storage; decrypting, by the owner mobile device, the encrypted temporary private key received by the owner mobile device from the central tracking system using a permanent private key of the permanent encryption key pair; decrypting, by the owner mobile device, the encrypted location data received by the owner mobile device from the central tracking system using the decrypted temporary private key to produce decrypted location data; and displaying, by the owner mobile device, the decrypted location data; wherein the set of hash keys is generated independently

by the tracking device and the central tracking system.

17. The non-transitory computer-readable storage medium of claim 16, wherein the permanent encryption key pair is generated in response to activating the tracking device.

18. The non-transitory computer-readable storage medium of claim 16, wherein the set of hash keys is unique to the tracking device, and wherein the central tracking system is configured to associate the set of hash keys with a unique identifier of the tracking device.

19. The non-transitory computer-readable storage medium of claim 16, wherein the temporary encryption key pair is generated using an Rivest-Shamir-Adleman (“RSA”) algorithm or an elliptic-curve cryptography (“ECC”) algorithm.

20. A system comprising a hardware processor and a non-transitory computer-readable storage medium storing executable instructions that, when executed by the hardware processor, cause the hardware processor to perform steps comprising: encrypting, by an owner mobile device, a temporary private key in an encryption key pair using a permanent public key of a permanent encryption key pair to produce an encrypted temporary encryption key pair with an encrypted temporary private key; providing, by the owner mobile device, the encrypted temporary encryption key pair to a central tracking system, the central tracking system configured to associate the encrypted temporary encryption key pair with a hash key of a set of hash keys associated with a tracking device; providing, by a community mobile device, a hashed identifier received from the tracking device to the central tracking system, the central tracking system configured to identify a hash key used to create the hashed identifier, to identify the encrypted temporary encryption key pair as associated with the identified hash key, and to provide the encrypted temporary encryption key pair to the community mobile device; encrypting, by the community mobile device, location data representative of a location of the community mobile device using the temporary public key of the encrypted temporary encryption key pair to produce encrypted location data; providing, by the community mobile device, the hashed identifier, the encrypted temporary private key of the encrypted temporary encryption key pair, and the encrypted location data to the central tracking system for storage; decrypting, by the owner mobile device, the encrypted temporary private key received by the owner mobile device from the central tracking system using a permanent private key of the permanent encryption key pair; decrypting, by the owner mobile device, the encrypted location data received by the owner mobile device from the central tracking system using the decrypted temporary private key to produce decrypted location data; and displaying, by the owner mobile device, the decrypted location data; wherein the set of hash keys is generated independently by the tracking device and the central tracking system.
