



US012413981B2

(12) **United States Patent**
Devine et al.

(10) **Patent No.:** **US 12,413,981 B2**

(45) **Date of Patent:** ***Sep. 9, 2025**

(54) **USER INTERFACES FOR WORKOUT CONTENT**

(71) Applicant: **Apple Inc.**, Cupertino, CA (US)

(72) Inventors: **Lynne Devine**, San Francisco, CA (US); **Julie A. Arney**, Los Gatos, CA (US); **Jay Blahnik**, Venice, CA (US); **Gary Ian Butcher**, Los Gatos, CA (US); **Edward Chao**, Palo Alto, CA (US); **David Clark**, Cupertino, CA (US); **Alan C. Dye**, San Francisco, CA (US); **Anders Kalle Haglunds**, Sunnyvale, CA (US); **Kevin Lynch**, Woodside, CA (US); **Aalhad R. Patankar**, Cypress, CA (US); **Jennifer D. Patton**, Cupertino, CA (US); **Emily Pedersen**, Los Altos Hills, CA (US); **Brady Jackson White**, San Jose, CA (US); **Nealon Young**, San Francisco, CA (US)

(73) Assignee: **Apple Inc.**, Cupertino, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **18/663,024**

(22) Filed: **May 13, 2024**

(65) **Prior Publication Data**

US 2024/0397323 A1 Nov. 28, 2024

Related U.S. Application Data

(63) Continuation of application No. 17/951,976, filed on Sep. 23, 2022, now Pat. No. 11,985,506, which is a (Continued)

(51) **Int. Cl.**
H04W 12/55 (2021.01)
G06F 3/0481 (2022.01)

(Continued)

(52) **U.S. Cl.**
CPC **H04W 12/55** (2021.01); **G06F 3/0481** (2013.01); **G06F 3/0482** (2013.01); (Continued)

(58) **Field of Classification Search**
CPC H04W 12/55; G06F 3/0481; G06F 3/0482; G06F 3/0484; G06F 3/04842; G06F 3/167; G16H 20/30; G16H 40/63
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,480,943 A 11/1969 Manber
4,205,628 A 6/1980 Null
(Continued)

FOREIGN PATENT DOCUMENTS

AU 2011302438 A1 5/2013
CA 2815518 A1 5/2012
(Continued)

OTHER PUBLICATIONS

US 2002/0018582 A1, 02/2002, Hagiwara et al. (withdrawn)
(Continued)


Primary Examiner — Cao H Nguyen

(74) *Attorney, Agent, or Firm* — DLA Piper LLP (US)

(57) **ABSTRACT**

In some embodiments, an electronic device performs techniques related to displaying personalized workout suggestions based on completed workouts. In some embodiments, an electronic device performs techniques related to starting an audio-based workout. In some embodiments, an electronic device performs techniques related to displaying information about a workout during playback of workout

(Continued)



content. In some embodiments, an electronic device performs techniques related to displaying information about physical activity of a user relative to a group of users. In some embodiments, an electronic device performs techniques related to coordinating display of workout content among multiple devices.

42 Claims, 168 Drawing Sheets

Related U.S. Application Data

continuation of application No. 17/030,337, filed on Sep. 23, 2020, now Pat. No. 11,638,158.

- (60) Provisional application No. 63/078,311, filed on Sep. 14, 2020, provisional application No. 63/036,374, filed on Jun. 8, 2020, provisional application No. 62/977,076, filed on Feb. 14, 2020.

(51) Int. Cl.

G06F 3/0482 (2013.01)
G06F 3/0484 (2022.01)
G06F 3/04842 (2022.01)
G06F 3/16 (2006.01)
G16H 20/30 (2018.01)
G16H 40/63 (2018.01)
G16H 50/70 (2018.01)

(52) U.S. Cl.

CPC **G06F 3/0484** (2013.01); **G06F 3/04842** (2013.01); **G06F 3/167** (2013.01); **G16H 20/30** (2018.01); **G16H 40/63** (2018.01); **G16H 50/70** (2018.01)

(56) References Cited

U.S. PATENT DOCUMENTS

4,842,266 A 6/1989 Sweeney et al.
5,349,962 A 9/1994 Lockard et al.
5,423,863 A 6/1995 Felblinger et al.
5,458,548 A 10/1995 Crossing et al.
5,463,725 A 10/1995 Henckel et al.
5,474,077 A 12/1995 Suga
5,583,542 A 12/1996 Capps et al.
5,602,981 A 2/1997 Hargrove
5,642,731 A 7/1997 Kehr
5,677,708 A 10/1997 Matthews et al.
5,685,723 A 11/1997 Ladin et al.
5,712,995 A 1/1998 Cohn
5,724,985 A 3/1998 Snell et al.
5,730,141 A 3/1998 Fain et al.
5,767,835 A 6/1998 Obbink et al.
5,788,655 A 8/1998 Yoshimura et al.
5,812,983 A 9/1998 Kumagai
5,825,349 A 10/1998 Meier et al.
5,845,122 A 12/1998 Nielsen et al.
5,845,235 A 12/1998 Luukkanen et al.
5,864,868 A 1/1999 Contois
5,886,697 A 3/1999 Naughton et al.
5,944,633 A 8/1999 Wittrock
5,969,283 A 10/1999 Looney et al.
6,013,008 A 1/2000 Fukushima
6,055,543 A 4/2000 Christensen et al.
6,061,592 A 5/2000 Nigam
6,088,649 A 7/2000 Kadaba et al.
6,095,949 A 8/2000 Arai
6,095,984 A 8/2000 Amano et al.
6,097,371 A 8/2000 Siddiqui et al.
6,097,385 A 8/2000 Robinson
6,118,450 A 9/2000 Proehl et al.
6,141,007 A 10/2000 Elterman et al.

6,154,210 A 11/2000 Anderson
6,160,551 A 12/2000 Naughton et al.
6,167,469 A 12/2000 Safai et al.
6,199,012 B1 3/2001 Hasegawa
6,237,010 B1 5/2001 Hui et al.
6,244,988 B1 6/2001 Delman
6,245,982 B1 6/2001 Suzuki et al.
6,248,946 B1 6/2001 Dwek
6,292,273 B1 9/2001 Dow et al.
6,301,586 B1 10/2001 Yang et al.
6,302,789 B2 10/2001 Harada et al.
6,317,784 B1 11/2001 Mackintosh et al.
6,334,025 B1 12/2001 Yamagami et al.
6,346,951 B1 2/2002 Mastronardi
6,356,971 B1 3/2002 Katz et al.
6,374,177 B1 4/2002 Lee et al.
6,380,947 B1 4/2002 Stead
6,416,471 B1 7/2002 Kumar et al.
6,462,760 B1 10/2002 Cox et al.
6,564,213 B1 5/2003 Ortega et al.
6,603,477 B1 8/2003 Tittle
6,639,584 B1 10/2003 Li
6,705,972 B1 3/2004 Takano et al.
6,713,312 B2 3/2004 Blalock et al.
6,731,312 B2 5/2004 Robbin
6,784,925 B1 8/2004 Tomat et al.
6,837,827 B1 1/2005 Lee et al.
6,866,613 B1 3/2005 Brown et al.
6,920,619 B1 7/2005 Milekic
6,950,989 B2 9/2005 Rosenzweig et al.
7,020,514 B1 3/2006 Wiesel
7,128,693 B2 10/2006 Brown et al.
7,164,410 B2 1/2007 Kupka
7,251,454 B2 7/2007 White
7,286,256 B2 10/2007 Herbert
7,302,272 B2 11/2007 Ackley
7,380,212 B2 5/2008 Cody et al.
7,437,005 B2 10/2008 Drucker et al.
7,444,390 B2 10/2008 Tadayon et al.
7,453,444 B2 11/2008 Geaghan
7,534,206 B1 5/2009 Lovitt et al.
7,559,034 B1 7/2009 Paperny et al.
7,627,828 B1 12/2009 Collison et al.
7,662,065 B1 2/2010 Kahn et al.
7,695,406 B2 4/2010 Waters
7,724,242 B2 5/2010 Hillis et al.
7,739,148 B2 6/2010 Suzuki et al.
7,779,358 B1 8/2010 Gupta et al.
7,791,755 B2 9/2010 Mori
7,823,080 B2 10/2010 Miyajima et al.
7,853,428 B2 12/2010 Usui et al.
7,870,013 B1 1/2011 Allemann et al.
7,970,240 B1 6/2011 Chao et al.
7,996,788 B2 8/2011 Carmichael
8,024,658 B1 9/2011 Fagans et al.
8,060,229 B2 11/2011 Gupta et al.
8,105,208 B2 1/2012 Oleson et al.
8,106,856 B2 1/2012 Matas et al.
8,132,116 B1 3/2012 Schendel
8,152,640 B2 4/2012 Shirakawa et al.
8,200,323 B2 6/2012 Dibenedetto et al.
8,259,132 B2 9/2012 Buchheit
8,305,355 B2 11/2012 Forstall et al.
8,321,006 B1 11/2012 Snyder et al.
8,339,420 B2 12/2012 Hiraoka et al.
8,341,557 B2 12/2012 Pisula et al.
8,386,934 B2 2/2013 Takakura et al.
8,418,075 B2 4/2013 Gallo et al.
8,456,431 B2 6/2013 Victor
8,458,617 B2 6/2013 Victor et al.
8,464,173 B2 6/2013 Victor et al.
8,475,339 B2 7/2013 Hwang et al.
8,487,885 B2 7/2013 Relyea et al.
8,496,563 B2 7/2013 Komatsu et al.
8,676,170 B2 3/2014 Poratti et al.
8,734,296 B1 5/2014 Brumback et al.
8,768,648 B2 7/2014 Panther et al.
8,780,069 B2 7/2014 Victor et al.
8,784,115 B1 7/2014 Chuang

(56)

References Cited

U.S. PATENT DOCUMENTS

8,784,271	B2	7/2014	Brumback et al.	2002/0021758	A1	2/2002	Chui et al.
8,825,445	B2	9/2014	Hoffman et al.	2002/0045960	A1	4/2002	Phillips et al.
8,863,016	B2	10/2014	Victor et al.	2002/0054233	A1	5/2002	Juen
8,934,963	B1	1/2015	Farazi	2002/0057292	A1	5/2002	Holtz
8,947,239	B1	2/2015	Park	2002/0057461	A1	5/2002	Dow et al.
8,957,865	B2	2/2015	Cieplinski et al.	2002/0070982	A1	6/2002	Hill et al.
8,966,399	B2	2/2015	Chiang et al.	2002/0086774	A1	7/2002	Warner
8,990,006	B1	3/2015	Wallace et al.	2002/0106199	A1	8/2002	Ikeda
9,011,292	B2	4/2015	Weast et al.	2002/0118121	A1	8/2002	Lehrman et al.
9,020,538	B1	4/2015	White et al.	2002/0135621	A1	9/2002	Angiulo et al.
9,063,164	B1	6/2015	Yuen et al.	2002/0196357	A1	12/2002	Battles et al.
9,087,234	B2	7/2015	Hoffman et al.	2003/0023178	A1	1/2003	Bischoff et al.
9,148,483	B1	9/2015	Molettiere et al.	2003/0048291	A1	3/2003	Dieberger
9,164,663	B1	10/2015	Berard	2003/0064860	A1	4/2003	Yamashita et al.
9,224,291	B2	12/2015	Moll-Carrillo et al.	2003/0081135	A1	5/2003	Boll
9,230,076	B2	1/2016	King et al.	2003/0108241	A1	6/2003	Colmenarez et al.
9,310,907	B2	4/2016	Victor et al.	2003/0122787	A1	7/2003	Zimmerman et al.
9,449,365	B2	9/2016	Roberts	2003/0128192	A1	7/2003	Van Os
9,459,792	B2	10/2016	Matas et al.	2003/0128241	A1	7/2003	Watanabe et al.
9,532,734	B2	1/2017	Hoffman et al.	2003/0134714	A1	7/2003	Oishi et al.
9,557,881	B1	1/2017	Jain et al.	2003/0149990	A1	8/2003	Anttila et al.
9,582,165	B2	2/2017	Wilson et al.	2003/0160824	A1	8/2003	Szumla
9,589,445	B2	3/2017	White et al.	2003/0161003	A1	8/2003	Herbert
9,712,629	B2	7/2017	Molettiere et al.	2003/0169288	A1	9/2003	Misawa
9,723,381	B2	8/2017	Swanson	2003/0179229	A1	9/2003	Van et al.
9,734,477	B2	8/2017	Weast et al.	2003/0181291	A1	9/2003	Ogawa
9,798,443	B1	10/2017	Gray	2003/0182628	A1	9/2003	Lira
9,800,525	B1	10/2017	Lerner et al.	2003/0197687	A1	10/2003	Shetter
9,813,642	B1	11/2017	Chen et al.	2003/0216971	A1	11/2003	Sick et al.
9,817,481	B2	11/2017	Pantelopoulous et al.	2003/0226695	A1	12/2003	Mault
9,854,653	B1	12/2017	Ackmann et al.	2004/0014567	A1	1/2004	Mendel
9,880,805	B1	1/2018	Guralnick	2004/0046886	A1	3/2004	Ambiru et al.
9,910,571	B2	3/2018	Chen et al.	2004/0077462	A1	4/2004	Brown et al.
9,918,664	B2	3/2018	Blahnik et al.	2004/0085316	A1	5/2004	Malik
9,931,539	B1	4/2018	De Pablos et al.	2004/0119758	A1	6/2004	Grossman et al.
9,940,682	B2	4/2018	Hoffman et al.	2004/0128286	A1	7/2004	Yasushi et al.
10,056,006	B1	8/2018	Hsu-Hoffman et al.	2004/0135904	A1	7/2004	Shiota et al.
10,105,573	B2	10/2018	Park et al.	2004/0158555	A1	8/2004	Seedman et al.
10,220,258	B2	3/2019	Gu et al.	2004/0183830	A1	9/2004	Cody et al.
10,226,195	B2	3/2019	Briante et al.	2004/0205504	A1	10/2004	Phillips
10,272,294	B2	4/2019	Williams et al.	2004/0207722	A1	10/2004	Koyama et al.
10,282,070	B2	5/2019	Victor	2004/0236189	A1	11/2004	Hawthorne et al.
10,300,334	B1	5/2019	Chuang	2005/0015803	A1	1/2005	Macrae et al.
10,304,347	B2	5/2019	Wilson et al.	2005/0041035	A1	2/2005	Nagatomo et al.
10,339,830	B2	7/2019	Han et al.	2005/0062130	A1	3/2005	Ciancio et al.
10,398,381	B1	9/2019	Heneghan et al.	2005/0071767	A1	3/2005	Kirkland et al.
10,489,508	B2	11/2019	Zhai et al.	2005/0073601	A1	4/2005	Battles et al.
10,500,441	B2	12/2019	Lagree	2005/0075214	A1	4/2005	Brown et al.
10,639,521	B2	5/2020	Foley et al.	2005/0076307	A1	4/2005	Robbin
10,736,543	B2	8/2020	Chen et al.	2005/0079905	A1	4/2005	Martens
10,777,314	B1	9/2020	Williams et al.	2005/0083406	A1	4/2005	Cozier
10,898,132	B2	1/2021	White et al.	2005/0088418	A1	4/2005	Nguyen
10,973,422	B2	4/2021	Pantelopoulous et al.	2005/0102635	A1	5/2005	Jiang et al.
10,978,195	B2	4/2021	Blahnik et al.	2005/0104848	A1	5/2005	Yamaguchi et al.
11,103,161	B2	8/2021	Williams et al.	2005/0108253	A1	5/2005	Metsatahti et al.
11,107,567	B2	8/2021	Blahnik et al.	2005/0113650	A1	5/2005	Pacione et al.
11,107,569	B1	8/2021	Devoto	2005/0124324	A1	6/2005	Thomas et al.
11,152,100	B2	10/2021	Crowley et al.	2005/0130802	A1	6/2005	Kinnunen et al.
11,202,598	B2	12/2021	Soli et al.	2005/0134719	A1	6/2005	Beck
11,209,957	B2	12/2021	Dryer et al.	2005/0139852	A1	6/2005	Chen et al.
11,216,119	B2	1/2022	De Vries et al.	2005/0160377	A1	7/2005	Sciammarella et al.
11,317,833	B2	5/2022	Williams et al.	2005/0165627	A1	7/2005	Fotsch et al.
11,334,229	B2	5/2022	Victor	2005/0171410	A1	8/2005	Hjelt et al.
11,446,548	B2	9/2022	Devine et al.	2005/0172311	A1	8/2005	Hjelt et al.
11,452,915	B2	9/2022	Devine et al.	2005/0183026	A1	8/2005	Amano et al.
11,458,363	B2	10/2022	Powers et al.	2005/0188326	A1	8/2005	Ikeda
11,514,813	B2	11/2022	Bell et al.	2005/0190059	A1	9/2005	Wehrenberg
11,529,074	B2	12/2022	Vaterlaus	2005/0192924	A1	9/2005	Drucker et al.
11,801,423	B2	10/2023	Bissonnette et al.	2005/0195221	A1	9/2005	Berger et al.
2001/0014184	A1	8/2001	Bubie et al.	2005/0197063	A1	9/2005	White et al.
2001/0049470	A1	12/2001	Mault et al.	2005/0198024	A1	9/2005	Sakata et al.
2002/0000998	A1	1/2002	Scott et al.	2005/0210399	A1	9/2005	Filner et al.
2002/0008763	A1	1/2002	Kawamura et al.	2005/0215848	A1	9/2005	Lorenzato et al.
2002/0015064	A1	2/2002	Robotham et al.	2005/0216867	A1	9/2005	Marvit et al.
2002/0018051	A1	2/2002	Singh	2005/0228735	A1	10/2005	Duquette
				2005/0272564	A1	12/2005	Pyles et al.
				2006/0001652	A1	1/2006	Chiu et al.
				2006/0004685	A1	1/2006	Pyhalammi et al.
				2006/0017692	A1	1/2006	Wehrenberg et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2006/0020174 A1	1/2006	Matsumura et al.	2008/0051919 A1	2/2008	Sakai et al.
2006/0022961 A1	2/2006	Kaminaga	2008/0052945 A1	3/2008	Matas et al.
2006/0025218 A1	2/2006	Hotta	2008/0057941 A1	3/2008	Scott et al.
2006/0026521 A1	2/2006	Hotelling et al.	2008/0058626 A1	3/2008	Miyata et al.
2006/0026535 A1	2/2006	Hotelling et al.	2008/0059888 A1	3/2008	Dunko
2006/0026536 A1	2/2006	Hotelling et al.	2008/0066010 A1	3/2008	Brodersen et al.
2006/0047208 A1	3/2006	Yoon	2008/0076637 A1	3/2008	Gilley et al.
2006/0048076 A1	3/2006	Vronay et al.	2008/0077026 A1	3/2008	Banet et al.
2006/0052727 A1	3/2006	Palestrant	2008/0082145 A1	4/2008	Skwarek et al.
2006/0061663 A1	3/2006	Park	2008/0086318 A1	4/2008	Gilley et al.
2006/0072028 A1	4/2006	Hong	2008/0096726 A1	4/2008	Riley et al.
2006/0077266 A1	4/2006	Nurmi et al.	2008/0133697 A1	6/2008	Stewart et al.
2006/0080386 A1	4/2006	Roykkee et al.	2008/0134070 A1	6/2008	Kobayashi et al.
2006/0088228 A1	4/2006	Marriott et al.	2008/0141135 A1	6/2008	Mason et al.
2006/0098109 A1	5/2006	Ooki	2008/0147664 A1	6/2008	Fujiwara et al.
2006/0106741 A1	5/2006	Janarthanan	2008/0150731 A1	6/2008	Laukkanen et al.
2006/0112335 A1	5/2006	Hofmeister et al.	2008/0155474 A1	6/2008	Duhig et al.
2006/0117014 A1	6/2006	Qi	2008/0155478 A1	6/2008	Stross
2006/0125799 A1	6/2006	Hillis et al.	2008/0161161 A1	7/2008	Pipinich et al.
2006/0136246 A1	6/2006	Tu	2008/0161707 A1	7/2008	Farrington et al.
2006/0136449 A1	6/2006	Parker et al.	2008/0165141 A1	7/2008	Christie
2006/0136839 A1	6/2006	Makela et al.	2008/0177569 A1	7/2008	Chen et al.
2006/0156228 A1	7/2006	Gallo et al.	2008/0180404 A1	7/2008	Han et al.
2006/0160090 A1	7/2006	Macina et al.	2008/0195600 A1	8/2008	Deakter
2006/0164535 A1	7/2006	Oyama	2008/0200312 A1	8/2008	Tagliabue
2006/0170669 A1	8/2006	Walker et al.	2008/0216022 A1	9/2008	Lorch et al.
2006/0184800 A1	8/2006	Rosenberg	2008/0229226 A1	9/2008	Rowbottom et al.
2006/0184966 A1	8/2006	Hunleth et al.	2008/0254767 A1	10/2008	Jin
2006/0233536 A1	10/2006	Shuhami	2008/0262946 A1	10/2008	Wren
2006/0240959 A1	10/2006	Huang	2008/0278333 A1	11/2008	Fennell et al.
2006/0250524 A1	11/2006	Roche	2008/0297482 A1	12/2008	Weiss
2006/0279532 A1	12/2006	Olszewski et al.	2008/0300110 A1	12/2008	Smith et al.
2007/0016091 A1	1/2007	Butt et al.	2008/0307343 A1	12/2008	Robert et al.
2007/0016868 A1	1/2007	Nurmi	2008/0320419 A1	12/2008	Matas et al.
2007/0021269 A1	1/2007	Shum	2009/0007017 A1	1/2009	Anzures et al.
2007/0031115 A1	2/2007	Oshikiri et al.	2009/0012821 A1	1/2009	Besson et al.
2007/0032733 A1	2/2007	Burton	2009/0012988 A1	1/2009	Brown
2007/0033069 A1	2/2007	Rao et al.	2009/0013350 A1	1/2009	Ohlfs et al.
2007/0040810 A1	2/2007	Dowe et al.	2009/0021576 A1	1/2009	Linder et al.
2007/0050726 A1	3/2007	Wakai et al.	2009/0037605 A1	2/2009	Li
2007/0055940 A1	3/2007	Moore et al.	2009/0047645 A1	2/2009	Dibenedetto et al.
2007/0056727 A1	3/2007	Newman	2009/0051946 A1	2/2009	Hibi
2007/0061748 A1	3/2007	Hirose	2009/0055748 A1	2/2009	Dieberger et al.
2007/0071256 A1	3/2007	Ito	2009/0058821 A1	3/2009	Chaudhri et al.
2007/0081740 A1	4/2007	Ciudad et al.	2009/0075782 A1	3/2009	Joubert et al.
2007/0097151 A1	5/2007	Rosenberg	2009/0106685 A1	4/2009	Care et al.
2007/0097421 A1	5/2007	Sorensen et al.	2009/0118100 A1	5/2009	Oliver et al.
2007/0113726 A1	5/2007	Oliver et al.	2009/0128516 A1	5/2009	Rimon et al.
2007/0136093 A1	6/2007	Rankin et al.	2009/0140997 A1	6/2009	Jeong et al.
2007/0136778 A1	6/2007	Birger et al.	2009/0144639 A1	6/2009	Nims et al.
2007/0143433 A1	6/2007	Daigle	2009/0149299 A1	6/2009	Tchao et al.
2007/0150839 A1	6/2007	Danninger	2009/0158167 A1	6/2009	Wang et al.
2007/0160345 A1	7/2007	Sakai et al.	2009/0158326 A1	6/2009	Hunt et al.
2007/0169614 A1	7/2007	Sasaki et al.	2009/0164567 A1	6/2009	Hara
2007/0179938 A1	8/2007	Ikeda et al.	2009/0170532 A1	7/2009	Lee et al.
2007/0186154 A1	8/2007	Anthony et al.	2009/0192823 A1	7/2009	Hawkins et al.
2007/0188518 A1	8/2007	Vale et al.	2009/0193351 A1	7/2009	Lee et al.
2007/0192741 A1	8/2007	Yoritake et al.	2009/0210078 A1	8/2009	Crowley
2007/0204225 A1	8/2007	Berkowitz et al.	2009/0216556 A1	8/2009	Martin et al.
2007/0209004 A1	9/2007	Layard	2009/0222056 A1	9/2009	Lindh et al.
2007/0229471 A1	10/2007	Kim et al.	2009/0222761 A1	9/2009	Hayashi
2007/0229678 A1	10/2007	Barrus et al.	2009/0233771 A1	9/2009	Quatrochi et al.
2007/0236475 A1	10/2007	Wherry	2009/0249076 A1	10/2009	Reed et al.
2007/0245236 A1	10/2007	Lee et al.	2009/0259134 A1	10/2009	Levine
2007/0245257 A1	10/2007	Chan et al.	2009/0259967 A1	10/2009	Davidson et al.
2007/0249949 A1	10/2007	Hadley	2009/0262088 A1	10/2009	Moll-Carrillo et al.
2007/0253025 A1	11/2007	Terayoko	2009/0268949 A1	10/2009	Ueshima et al.
2007/0262964 A1	11/2007	Zotov et al.	2009/0287103 A1	11/2009	Pillai
2007/0271065 A1	11/2007	Gupta et al.	2009/0291805 A1	11/2009	Blum et al.
2008/0019591 A1	1/2008	Iwayama et al.	2009/0292561 A1	11/2009	Itoh
2008/0020803 A1	1/2008	Rios et al.	2009/0319243 A1	12/2009	Suarez-Rivera et al.
2008/0027673 A1	1/2008	Trumm	2009/0327975 A1	12/2009	Stedman
2008/0030456 A1	2/2008	Asadi et al.	2010/0030094 A1	2/2010	Lundback
2008/0036743 A1	2/2008	Westerman et al.	2010/0031202 A1	2/2010	Morris et al.
2008/0040668 A1	2/2008	Ala-Rantala	2010/0039399 A1	2/2010	Kim
			2010/0042949 A1	2/2010	Chen
			2010/0048358 A1	2/2010	Tchao et al.
			2010/0058238 A1	3/2010	Ben Moshe
			2010/0060586 A1	3/2010	Pisula et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2010/0062818	A1	3/2010	Haughay et al.	2011/0314422	A1	12/2011	Cameron et al.
2010/0062905	A1	3/2010	Rottler et al.	2012/0015778	A1	1/2012	Lee et al.
2010/0064255	A1	3/2010	Rottler et al.	2012/0015779	A1	1/2012	Powch et al.
2010/0076331	A1	3/2010	Chan et al.	2012/0022884	A1	1/2012	Chillemi
2010/0079291	A1	4/2010	Kroll et al.	2012/0030623	A1	2/2012	Hoellwarth
2010/0088653	A1	4/2010	Yach et al.	2012/0034897	A1	2/2012	Kreitzer et al.
2010/0103101	A1	4/2010	Song et al.	2012/0036433	A1	2/2012	Zimmer et al.
2010/0121700	A1	5/2010	Wigder et al.	2012/0036460	A1	2/2012	Cieplinski et al.
2010/0130890	A1	5/2010	Matsumura et al.	2012/0041767	A1	2/2012	Hoffman et al.
2010/0137106	A1	6/2010	Oshima et al.	2012/0042039	A1	2/2012	Mark
2010/0145209	A1	6/2010	Lee et al.	2012/0042272	A1	2/2012	Hong et al.
2010/0149211	A1	6/2010	Tossing et al.	2012/0046784	A1	2/2012	Malina et al.
2010/0152600	A1	6/2010	Droitcour et al.	2012/0059664	A1	3/2012	Georgiev et al.
2010/0153833	A1	6/2010	Siegel et al.	2012/0060118	A1	3/2012	Gupta et al.
2010/0169819	A1	7/2010	Bestle et al.	2012/0071770	A1	3/2012	Grey et al.
2010/0179832	A1	7/2010	Van et al.	2012/0089419	A1	4/2012	Huster et al.
2010/0179833	A1	7/2010	Roizen et al.	2012/0092379	A1	4/2012	Tsuji et al.
2010/0184564	A1	7/2010	Molyneux et al.	2012/0092383	A1	4/2012	Hysek et al.
2010/0191701	A1	7/2010	Beyda et al.	2012/0105225	A1	5/2012	Valtonen
2010/0194692	A1	8/2010	Orr et al.	2012/0116550	A1	5/2012	Hoffman et al.
2010/0197463	A1	8/2010	Haughay et al.	2012/0116684	A1	5/2012	Ingrassia et al.
2010/0198453	A1	8/2010	Dorogusker et al.	2012/0117506	A1	5/2012	Koch et al.
2010/0214442	A1	8/2010	Uemura et al.	2012/0119911	A1	5/2012	Jeon et al.
2010/0222859	A1	9/2010	Govari et al.	2012/0143094	A1	6/2012	Jallon
2010/0231612	A1	9/2010	Chaudhri et al.	2012/0143095	A1	6/2012	Nakamura
2010/0241955	A1	9/2010	Price et al.	2012/0150759	A1	6/2012	Tarjan
2010/0241994	A1	9/2010	Wiley et al.	2012/0159380	A1	6/2012	Kocienda et al.
2010/0253807	A1	10/2010	Matsumoto et al.	2012/0169882	A1	7/2012	Millar et al.
2010/0262634	A1	10/2010	Wang	2012/0171649	A1	7/2012	Wander et al.
2010/0264097	A1	10/2010	Sun et al.	2012/0179278	A1	7/2012	Riley et al.
2010/0269055	A1	10/2010	Daikeler et al.	2012/0179319	A1	7/2012	Gilman et al.
2010/0269157	A1	10/2010	Experton	2012/0215328	A1	8/2012	Schmelzer
2010/0273610	A1	10/2010	Johnson	2012/0232414	A1	9/2012	Mollicone et al.
2010/0281374	A1	11/2010	Schulz et al.	2012/0251079	A1	10/2012	Meschter et al.
2010/0283754	A1	11/2010	Nakao et al.	2012/0253485	A1	10/2012	Weast et al.
2010/0292599	A1	11/2010	Oleson et al.	2012/0253488	A1	10/2012	Shaw et al.
2010/0292600	A1	11/2010	Dibenedetto et al.	2012/0254263	A1	10/2012	Hiestermann et al.
2010/0298899	A1	11/2010	Donnelly et al.	2012/0274508	A1	11/2012	Brown et al.
2010/0305965	A1	12/2010	Benjamin et al.	2012/0283855	A1	11/2012	Hoffman et al.
2010/0309149	A1	12/2010	Blumenberg et al.	2012/0290109	A1	11/2012	Engelberg et al.
2010/0331145	A1	12/2010	Lakovic et al.	2012/0302840	A1	11/2012	Kubo
2011/0003665	A1	1/2011	Burton et al.	2012/0302843	A1	11/2012	Otsubo et al.
2011/0010200	A1	1/2011	Firozvi et al.	2012/0310389	A1	12/2012	Martin
2011/0016120	A1	1/2011	Haughay et al.	2012/0313776	A1	12/2012	Utter
2011/0032105	A1	2/2011	Hoffman et al.	2012/0317167	A1	12/2012	Rahman et al.
2011/0052005	A1	3/2011	Selner	2012/0317430	A1	12/2012	Rahman et al.
2011/0066051	A1	3/2011	Moon et al.	2012/0323129	A1	12/2012	Fujita et al.
2011/0069017	A1	3/2011	Victor	2012/0326873	A1	12/2012	Utter
2011/0071869	A1	3/2011	Obrien et al.	2013/0014052	A1	1/2013	Frey et al.
2011/0074699	A1	3/2011	Marr et al.	2013/0021368	A1	1/2013	Lee et al.
2011/0087076	A1	4/2011	Brynnelsen et al.	2013/0036380	A1	2/2013	Symons
2011/0098928	A1	4/2011	Hoffman et al.	2013/0053990	A1	2/2013	Ackland
2011/0099299	A1	4/2011	Vasudevan et al.	2013/0054150	A1	2/2013	Sacks et al.
2011/0106553	A1	5/2011	Tanaka et al.	2013/0054720	A1	2/2013	Kang et al.
2011/0112418	A1	5/2011	Feild et al.	2013/0061175	A1	3/2013	Matas et al.
2011/0113430	A1	5/2011	Fuse	2013/0067050	A1	3/2013	Kotteri et al.
2011/0125041	A1	5/2011	Fischell et al.	2013/0081083	A1	3/2013	Yu et al.
2011/0137678	A1	6/2011	Williams	2013/0093715	A1	4/2013	Marsden et al.
2011/0137836	A1	6/2011	Kuriyama et al.	2013/0106603	A1	5/2013	Weast et al.
2011/0159469	A1	6/2011	Hwang et al.	2013/0106684	A1	5/2013	Weast et al.
2011/0167369	A1	7/2011	Van Os	2013/0110264	A1	5/2013	Weast et al.
2011/0179097	A1	7/2011	Ala-Rantala	2013/0115583	A1	5/2013	Gordon et al.
2011/0201911	A1	8/2011	Johnson et al.	2013/0132028	A1	5/2013	Crankson et al.
2011/0213276	A1	9/2011	Sarussi et al.	2013/0137073	A1	5/2013	Nacey et al.
2011/0227872	A1	9/2011	Huska et al.	2013/0138734	A1	5/2013	Crivello et al.
2011/0230169	A1	9/2011	Ohki	2013/0141233	A1	6/2013	Jacobs et al.
2011/0230986	A1	9/2011	Lafortune et al.	2013/0142495	A1	6/2013	Teraï
2011/0246509	A1	10/2011	Migita et al.	2013/0151285	A1	6/2013	Mclaren et al.
2011/0246918	A1	10/2011	Henderson	2013/0158367	A1	6/2013	Pacione et al.
2011/0257638	A1	10/2011	Boukhny et al.	2013/0179837	A1	7/2013	Eriksson et al.
2011/0261079	A1	10/2011	Ingrassia et al.	2013/0184613	A1	7/2013	Homsî et al.
2011/0275940	A1	11/2011	Nims et al.	2013/0185097	A1	7/2013	Saria et al.
2011/0281249	A1	11/2011	Gammell et al.	2013/0187923	A1	7/2013	Yoshimoto et al.
2011/0306389	A1	12/2011	Nagayama	2013/0188322	A1	7/2013	Lowe et al.
2011/0307821	A1	12/2011	Martens	2013/0191034	A1	7/2013	Weast et al.
				2013/0197679	A1	8/2013	Balakrishnan et al.
				2013/0198661	A1	8/2013	Matas
				2013/0198672	A1	8/2013	Yoon et al.
				2013/0203475	A1	8/2013	Shin et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2013/0209972	A1	8/2013	Carter et al.	2014/0310643	A1	10/2014	Karmanenko et al.
2013/0215119	A1	8/2013	Vanhoecke	2014/0331314	A1	11/2014	Fujioka
2013/0217253	A1	8/2013	Golko et al.	2014/0336796	A1	11/2014	Agnew
2013/0217979	A1	8/2013	Blackadar et al.	2014/0337041	A1	11/2014	Madden et al.
2013/0223707	A1	8/2013	Stephenson	2014/0337450	A1	11/2014	Choudhary et al.
2013/0230251	A1	9/2013	Kondo et al.	2014/0337451	A1	11/2014	Choudhary et al.
2013/0231575	A1	9/2013	Erkkila et al.	2014/0344693	A1	11/2014	Reese et al.
2013/0231711	A1	9/2013	Kaib	2014/0344723	A1	11/2014	Malik et al.
2013/0233097	A1	9/2013	Hayner et al.	2014/0344951	A1	11/2014	Brewer
2013/0238287	A1	9/2013	Hoffman et al.	2014/0358473	A1	12/2014	Goel et al.
2013/0239049	A1	9/2013	Perrodin et al.	2014/0358584	A1	12/2014	Worden et al.
2013/0245966	A1	9/2013	Burroughs et al.	2014/0365913	A1	12/2014	Santamaria et al.
2013/0262155	A1	10/2013	Hinkamp	2014/0371887	A1	12/2014	Hoffman et al.
2013/0263055	A1	10/2013	Victor	2014/0372898	A1	12/2014	Ayres et al.
2013/0263719	A1	10/2013	Watterson et al.	2015/0004578	A1	1/2015	Gilley et al.
2013/0274904	A1	10/2013	Coza et al.	2015/0011204	A1	1/2015	Seo et al.
2013/0324210	A1	12/2013	Doig et al.	2015/0018632	A1	1/2015	Khair
2013/0325358	A1	12/2013	Oshima et al.	2015/0033149	A1	1/2015	Kuchoor
2013/0325394	A1	12/2013	Yuen et al.	2015/0039616	A1	2/2015	Rolston et al.
2013/0325396	A1	12/2013	Yuen et al.	2015/0046814	A1	2/2015	Haughay et al.
2013/0325758	A1	12/2013	Alphin et al.	2015/0057942	A1	2/2015	Self et al.
2013/0330694	A1	12/2013	Watterson	2015/0057943	A1	2/2015	Self et al.
2013/0332286	A1	12/2013	Medelius et al.	2015/0057945	A1	2/2015	White et al.
2013/0332871	A1	12/2013	Bucur et al.	2015/0058093	A1	2/2015	Jakobs
2013/0345978	A1	12/2013	Lush et al.	2015/0058263	A1	2/2015	Landers
2014/0035761	A1	2/2014	Burton et al.	2015/0061891	A1	3/2015	Oleson et al.
2014/0037107	A1	2/2014	Marino et al.	2015/0065095	A1	3/2015	Seo et al.
2014/0038781	A1	2/2014	Foley et al.	2015/0065302	A1	3/2015	Ou et al.
2014/0039840	A1	2/2014	Yuen et al.	2015/0066172	A1	3/2015	Yi
2014/0059125	A1	2/2014	Hillier	2015/0067513	A1	3/2015	Zambetti et al.
2014/0067096	A1	3/2014	Aibara	2015/0067811	A1	3/2015	Agnew et al.
2014/0074825	A1	3/2014	Wood et al.	2015/0074571	A1	3/2015	Marti et al.
2014/0081666	A1	3/2014	Teller et al.	2015/0080023	A1	3/2015	Yang et al.
2014/0089836	A1	3/2014	Damani et al.	2015/0081059	A1	3/2015	Hwang et al.
2014/0092291	A1	4/2014	Aoshima et al.	2015/0081060	A1	3/2015	Hwang et al.
2014/0107524	A1	4/2014	Brull et al.	2015/0081529	A1	3/2015	Lee et al.
2014/0108998	A1	4/2014	Chaudhri et al.	2015/0082167	A1	3/2015	Yeh et al.
2014/0135955	A1	5/2014	Burroughs	2015/0083970	A1	3/2015	Koh et al.
2014/0139637	A1	5/2014	Mistry et al.	2015/0098309	A1	4/2015	Adams et al.
2014/0143678	A1	5/2014	Mistry et al.	2015/0100245	A1	4/2015	Huang et al.
2014/0156292	A1	6/2014	Kozicki et al.	2015/0106025	A1	4/2015	Keller et al.
2014/0165000	A1	6/2014	Fleizach et al.	2015/0112700	A1	4/2015	Sublett et al.
2014/0171266	A1	6/2014	Hawkins et al.	2015/0112990	A1	4/2015	Van Os et al.
2014/0172460	A1	6/2014	Kohli	2015/0113553	A1	4/2015	Pan
2014/0176346	A1	6/2014	Brumback et al.	2015/0118657	A1	4/2015	Shrake et al.
2014/0176475	A1	6/2014	Myers et al.	2015/0124067	A1	5/2015	Bala et al.
2014/0180786	A1	6/2014	Sullivan	2015/0130719	A1	5/2015	Wehrenberg et al.
2014/0189584	A1	7/2014	Weng et al.	2015/0130740	A1	5/2015	Cederlund et al.
2014/0195918	A1	7/2014	Friedlander	2015/0130830	A1	5/2015	Nagasaki et al.
2014/0197946	A1	7/2014	Park et al.	2015/0133748	A1	5/2015	Edmonds et al.
2014/0200691	A1	7/2014	Lee et al.	2015/0142689	A1	5/2015	Squires
2014/0213415	A1	7/2014	Parker et al.	2015/0153943	A1	6/2015	Wang
2014/0215365	A1	7/2014	Hiraga et al.	2015/0164349	A1	6/2015	Gopalakrishnan et al.
2014/0218369	A1	8/2014	Yuen et al.	2015/0169503	A1	6/2015	Maharaj
2014/0221790	A1	8/2014	Pacione et al.	2015/0177979	A1	6/2015	Johansson et al.
2014/0225925	A1	8/2014	Hayashi et al.	2015/0180746	A1	6/2015	Day et al.
2014/0228647	A1	8/2014	Sakamoto et al.	2015/0181314	A1	6/2015	Swanson
2014/0239065	A1	8/2014	Zhou et al.	2015/0182843	A1	7/2015	Esposito et al.
2014/0240122	A1	8/2014	Roberts et al.	2015/0185967	A1	7/2015	Ly et al.
2014/0240349	A1	8/2014	Tuukkanen	2015/0193805	A1	7/2015	Filipiak
2014/0244009	A1	8/2014	Mestas	2015/0196804	A1	7/2015	Koduri et al.
2014/0245161	A1	8/2014	Yuen et al.	2015/0196805	A1	7/2015	Koduri et al.
2014/0257537	A1	9/2014	Stroupe et al.	2015/0199494	A1	7/2015	Koduri et al.
2014/0266731	A1	9/2014	Malhotra	2015/0205492	A1	7/2015	Nobil
2014/0274413	A1	9/2014	Chelst	2015/0205930	A1	7/2015	Shaanan et al.
2014/0275852	A1	9/2014	Hong et al.	2015/0217163	A1	8/2015	Amis et al.
2014/0275854	A1	9/2014	Venkatraman et al.	2015/0220523	A1	8/2015	Lagree
2014/0277628	A1	9/2014	Nieminen et al.	2015/0220883	A1	8/2015	Bfar et al.
2014/0278229	A1	9/2014	Hong et al.	2015/0242404	A1	8/2015	Underwood et al.
2014/0280498	A1	9/2014	Frankel et al.	2015/0248535	A1	9/2015	Cho
2014/0282011	A1	9/2014	Dellinger et al.	2015/0251053	A1	9/2015	Hoffman et al.
2014/0282153	A1	9/2014	Christiansen et al.	2015/0262497	A1	9/2015	Landau et al.
2014/0282262	A1	9/2014	Gregotski et al.	2015/0269848	A1	9/2015	Yuen et al.
2014/0288680	A1	9/2014	Hoffman et al.	2015/0293592	A1	10/2015	Cheong et al.
2014/0310598	A1	10/2014	Sprague et al.	2015/0294440	A1	10/2015	Roberts
				2015/0297134	A1	10/2015	Albert et al.
				2015/0301691	A1	10/2015	Qin
				2015/0324751	A1	11/2015	Orenstein et al.
				2015/0331589	A1	11/2015	Kawakita

(56)

References Cited

U.S. PATENT DOCUMENTS

2015/0343709	A1	12/2015	Gerstle et al.	2016/0371464	A1	12/2016	Bricker
2015/0347711	A1	12/2015	Soli et al.	2016/0373631	A1	12/2016	Titi et al.
2015/0350861	A1	12/2015	Soli et al.	2016/0375306	A1	12/2016	Gu et al.
2015/0351655	A1	12/2015	Coleman	2016/0379511	A1	12/2016	Dawson et al.
2015/0364057	A1	12/2015	Catani et al.	2017/0001073	A1	1/2017	Krueger et al.
2015/0370323	A1	12/2015	Cieplinski et al.	2017/0007882	A1	1/2017	Werner
2015/0374267	A1	12/2015	Laughlin	2017/0011210	A1	1/2017	Cheong et al.
2015/0374310	A1	12/2015	Lee	2017/0014037	A1	1/2017	Coppola et al.
2016/0000379	A1	1/2016	Pougatchev et al.	2017/0019587	A1	1/2017	Matas et al.
2016/0004432	A1	1/2016	Bernstein et al.	2017/0021184	A1	1/2017	Pavel et al.
2016/0012294	A1	1/2016	Bouck	2017/0024399	A1	1/2017	Boyle et al.
2016/0015275	A1	1/2016	Samadani et al.	2017/0024539	A1	1/2017	Webb et al.
2016/0019360	A1	1/2016	Pahwa et al.	2017/0032168	A1	2/2017	Kim
2016/0027282	A1	1/2016	Lee	2017/0045866	A1	2/2017	Hou et al.
2016/0034133	A1	2/2016	Wilson et al.	2017/0046108	A1	2/2017	Kang et al.
2016/0034148	A1	2/2016	Wilson et al.	2017/0053542	A1	2/2017	Wilson et al.
2016/0038038	A1	2/2016	Kovacs	2017/0056722	A1	3/2017	Singh et al.
2016/0048263	A1	2/2016	Hiraga et al.	2017/0065224	A1	3/2017	Rahko et al.
2016/0048298	A1	2/2016	Choi et al.	2017/0076619	A1	3/2017	Wallach et al.
2016/0058331	A1	3/2016	Keen et al.	2017/0080288	A1	3/2017	Roh et al.
2016/0058336	A1	3/2016	Blahnik et al.	2017/0087412	A1	3/2017	Blahnik
2016/0058337	A1	3/2016	Blahnik et al.	2017/0087469	A1	3/2017	Hardee et al.
2016/0062464	A1	3/2016	Moussette et al.	2017/0095695	A1	4/2017	Mangusson et al.
2016/0062582	A1	3/2016	Wilson et al.	2017/0108924	A1	4/2017	Hurter
2016/0062589	A1	3/2016	Wan et al.	2017/0124276	A1	5/2017	Tee
2016/0063748	A1	3/2016	Kim et al.	2017/0139554	A1	5/2017	Nakabayashi et al.
2016/0065505	A1	3/2016	Iskander	2017/0140143	A1	5/2017	Ahmad et al.
2016/0070275	A1	3/2016	Anderson et al.	2017/0143262	A1	5/2017	Kurunmäki et al.
2016/0072896	A1	3/2016	Petersen et al.	2017/0153606	A1	6/2017	Pitis et al.
2016/0085937	A1	3/2016	Dettinger et al.	2017/0153804	A1	6/2017	Kim et al.
2016/0098160	A1	4/2016	Groset	2017/0161014	A1	6/2017	Kikugawa et al.
2016/0103970	A1	4/2016	Liu et al.	2017/0161462	A1	6/2017	Parker et al.
2016/0107031	A1	4/2016	Palatsi et al.	2017/0169295	A1	6/2017	Park et al.
2016/0110355	A1	4/2016	Charania et al.	2017/0177086	A1	6/2017	Yuen et al.
2016/0135731	A1	5/2016	Drennan	2017/0192625	A1	7/2017	Kim et al.
2016/0140828	A1	5/2016	Deforest	2017/0209766	A1	7/2017	Riley et al.
2016/0156584	A1	6/2016	Hum et al.	2017/0237694	A1	8/2017	Choudhary et al.
2016/0166195	A1	6/2016	Radecka et al.	2017/0239524	A1	8/2017	Lee et al.
2016/0193500	A1	7/2016	Webster et al.	2017/0239525	A1	8/2017	Kim et al.
2016/0196635	A1	7/2016	Cho et al.	2017/0243508	A1	8/2017	Cheng et al.
2016/0196759	A1	7/2016	Kim et al.	2017/0249417	A1	8/2017	Gosieski et al.
2016/0196760	A1	7/2016	Koo et al.	2017/0255169	A1	9/2017	Lee et al.
2016/0199697	A1	7/2016	Orfield	2017/0266494	A1	9/2017	Crankson et al.
2016/0203691	A1	7/2016	Arnold et al.	2017/0266531	A1	9/2017	Elford et al.
2016/0210099	A1	7/2016	Hampapuram et al.	2017/0269792	A1	9/2017	Xu et al.
2016/0210568	A1	7/2016	Krupa et al.	2017/0274149	A1	9/2017	Aeschlimann
2016/0216868	A1	7/2016	Victor et al.	2017/0274267	A1	9/2017	Blahnik
2016/0219262	A1	7/2016	Cole et al.	2017/0281026	A1	10/2017	Nick et al.
2016/0220175	A1	8/2016	Tam et al.	2017/0281057	A1	10/2017	Blahnik et al.
2016/0220225	A1	8/2016	Wang et al.	2017/0294174	A1	10/2017	Albadawi et al.
2016/0220867	A1	8/2016	Flaherty	2017/0300186	A1	10/2017	Kuhar et al.
2016/0224213	A1	8/2016	Chen et al.	2017/0301039	A1	10/2017	Dyer et al.
2016/0235374	A1	8/2016	Miller et al.	2017/0319941	A1	11/2017	Smith et al.
2016/0246880	A1	8/2016	Battiah et al.	2017/0329933	A1	11/2017	Brust et al.
2016/0249864	A1	9/2016	Kang et al.	2017/0330297	A1	11/2017	Cronin et al.
2016/0250517	A1	9/2016	Tilvis et al.	2017/0333752	A1	11/2017	Korkala et al.
2016/0255162	A1	9/2016	Frieder et al.	2017/0337033	A1	11/2017	Duyan et al.
2016/0256082	A1	9/2016	Ely et al.	2017/0348562	A1	12/2017	Jung et al.
2016/0256741	A1	9/2016	Holma et al.	2017/0348576	A1	12/2017	Pajonk-taylor
2016/0263435	A1	9/2016	Venkatraman et al.	2017/0353423	A1	12/2017	Morrison et al.
2016/0270717	A1	9/2016	Luna et al.	2017/0354845	A1	12/2017	Williams et al.
2016/0278659	A1	9/2016	Kaib et al.	2017/0357382	A1	12/2017	Miura et al.
2016/0278667	A1	9/2016	Villard et al.	2017/0357520	A1	12/2017	De Vries et al.
2016/0279475	A1	9/2016	Aragones et al.	2017/0359623	A1	12/2017	Folse et al.
2016/0283483	A1	9/2016	Jiang et al.	2018/0000426	A1	1/2018	Li
2016/0296798	A1	10/2016	Balakrishnan et al.	2018/0001184	A1	1/2018	Tran et al.
2016/0301794	A1	10/2016	Schlakman et al.	2018/0032234	A1	2/2018	Michalske
2016/0302680	A1	10/2016	Narusawa et al.	2018/0036591	A1	2/2018	King et al.
2016/0302717	A1	10/2016	Tawa et al.	2018/0053200	A1	2/2018	Cronin et al.
2016/0321831	A1	11/2016	Nakamura et al.	2018/0056132	A1	3/2018	Foley et al.
2016/0321932	A1	11/2016	Mitchell et al.	2018/0065025	A1	3/2018	Toda et al.
2016/0324457	A1	11/2016	Dagum	2018/0068019	A1	3/2018	Novikoff et al.
2016/0328736	A1	11/2016	Wang et al.	2018/0074462	A1	3/2018	Helder et al.
2016/0332025	A1	11/2016	Repka	2018/0074464	A1	3/2018	Essery et al.
2016/0346607	A1	12/2016	Rapfogel	2018/0078182	A1	3/2018	Chen et al.
				2018/0085058	A1	3/2018	Chakravarthi et al.
				2018/0121063	A1	5/2018	Lieb et al.
				2018/0126248	A1	5/2018	Dion et al.
				2018/0133537	A1	5/2018	Montantes

(56)	References Cited				
	U.S. PATENT DOCUMENTS				
2018/0137937	A1	5/2018	Gass et al.	2020/0359913	A1 11/2020 Ghodrati et al.
2018/0140211	A1	5/2018	Nakazawa et al.	2020/0379560	A1 12/2020 Krasadakis
2018/0140903	A1	5/2018	Poure et al.	2020/0381100	A1* 12/2020 Williams A61B 5/1122
2018/0140927	A1	5/2018	Kito et al.	2020/0382613	A1 12/2020 Sundstrom et al.
2018/0150709	A1	5/2018	Ha	2021/0001226	A1 1/2021 Suzuki et al.
2018/0177437	A1	6/2018	Yoshioka	2021/0007632	A1 1/2021 Blahnik et al.
2018/0182491	A1	6/2018	Belliveau et al.	2021/0007633	A1 1/2021 Blahnik et al.
2018/0189077	A1	7/2018	Gupta et al.	2021/0008413	A1 1/2021 Asikainen et al.
2018/0206766	A1	7/2018	Blahnik et al.	2021/0035674	A1 2/2021 Volosin et al.
2018/0247706	A1	8/2018	Riley et al.	2021/0042132	A1 2/2021 Park et al.
2018/0272190	A1	9/2018	Miura et al.	2021/0093919	A1 4/2021 Lyke et al.
2018/0294053	A1	10/2018	Runyon et al.	2021/0101052	A1 4/2021 Gore
2018/0300037	A1	10/2018	Takeda et al.	2021/0110908	A1 4/2021 Blahnik et al.
2018/0316964	A1	11/2018	Dillon et al.	2021/0113116	A1 4/2021 Chen et al.
2018/0318647	A1	11/2018	Foley et al.	2021/0113137	A1 4/2021 Soli et al.
2018/0329584	A1	11/2018	Williams et al.	2021/0117072	A1 4/2021 Victor
2018/0339195	A1	11/2018	Bernotas	2021/0145321	A1 5/2021 Chen et al.
2018/0345078	A1	12/2018	Blahnik et al.	2021/0191584	A1 6/2021 Williams et al.
2018/0364648	A1	12/2018	Chi et al.	2021/0193293	A1 6/2021 Blahnik et al.
2018/0367484	A1	12/2018	Rodriguez et al.	2021/0236903	A1 8/2021 Briel
2018/0367862	A1	12/2018	Horii et al.	2021/0243356	A1 8/2021 Matas et al.
2019/0008394	A1	1/2019	Rao et al.	2021/0252337	A1 8/2021 Devine et al.
2019/0008467	A1	1/2019	Averina et al.	2021/0252341	A1 8/2021 Devine et al.
2019/0025995	A1	1/2019	Williams	2021/0252369	A1 8/2021 Devine et al.
2019/0026011	A1	1/2019	Wang et al.	2021/0255747	A1 8/2021 Devine et al.
2019/0034049	A1	1/2019	Williams et al.	2021/0255758	A1 8/2021 Devine et al.
2019/0034050	A1	1/2019	Williams et al.	2021/0255826	A1 8/2021 Devine et al.
2019/0073081	A1	3/2019	Takahashi et al.	2021/0287416	A1 9/2021 O'Hagan et al.
2019/0089701	A1	3/2019	Mercury et al.	2021/0294438	A1 9/2021 Yang et al.
2019/0102049	A1	4/2019	Anzures et al.	2021/0316185	A1 10/2021 Mckenna et al.
2019/0104951	A1	4/2019	Valys et al.	2021/0350900	A1 11/2021 Blahnik et al.
2019/0126099	A1	5/2019	Hoang	2021/0352118	A1 11/2021 Ahn et al.
2019/0141418	A1	5/2019	Harma et al.	2021/0366608	A1 11/2021 Podobas et al.
2019/0143194	A1	5/2019	Evancho et al.	2021/0379447	A1 12/2021 Lee
2019/0155382	A1	5/2019	Ikuta et al.	2021/0394020	A1 12/2021 Killen et al.
2019/0184234	A1*	6/2019	Packles A63B 24/0087	2022/0047918	A1 2/2022 Williams et al.
2019/0209777	A1	7/2019	O'connell et al.	2022/0062707	A1 3/2022 Bedekar et al.
2019/0232110	A1	8/2019	Williams et al.	2022/0066902	A1 3/2022 Narra et al.
2019/0232111	A1	8/2019	Williams et al.	2022/0074754	A1 3/2022 Elder et al.
2019/0240534	A1	8/2019	Black	2022/0121277	A1 4/2022 Azam et al.
2019/0240536	A1	8/2019	Dibenedetto et al.	2022/0121299	A1 4/2022 De Vries et al.
2019/0240537	A1	8/2019	Hisada et al.	2022/0157184	A1 5/2022 Wilson et al.
2019/0274565	A1	9/2019	Soli et al.	2022/0160258	A1 5/2022 Williams et al.
2019/0279520	A1	9/2019	Wilson et al.	2022/0180980	A1 6/2022 Alencar et al.
2019/0313012	A1	10/2019	Matas	2022/0206647	A1 6/2022 Clarke et al.
2019/0336044	A1	11/2019	Williams et al.	2022/0262485	A1 8/2022 Meschter et al.
2019/0336045	A1	11/2019	Williams et al.	2022/0262509	A1 8/2022 Pahwa et al.
2019/0336827	A1	11/2019	Intonato et al.	2022/0287629	A1 9/2022 Forsyth et al.
2019/0339849	A1	11/2019	Williams et al.	2022/0317846	A1 10/2022 Victor
2019/0339860	A1	11/2019	Chen et al.	2022/0328161	A1 10/2022 Gilravi et al.
2019/0342616	A1	11/2019	Domm et al.	2022/0336077	A1 10/2022 Chen et al.
2019/0364120	A1	11/2019	Bandela et al.	2022/0386901	A1 12/2022 Chen et al.
2019/0387982	A1	12/2019	Buller	2023/0012755	A1 1/2023 D'Auria et al.
2020/0004409	A1	1/2020	Victor	2023/0013809	A1 1/2023 D'Auria et al.
2020/0014967	A1	1/2020	Putnam	2023/0013932	A1 1/2023 Blahnik et al.
2020/0026398	A1	1/2020	Kim	2023/0014053	A1 1/2023 Devine et al.
2020/0054931	A1	2/2020	Martin et al.	2023/0014290	A1 1/2023 Davydov et al.
2020/0098278	A1	3/2020	Doti et al.	2023/0017793	A1 1/2023 Williams et al.
2020/0101365	A1	4/2020	Wilson et al.	2023/0019337	A1 1/2023 D'auria et al.
2020/0110814	A1	4/2020	Abuelsaad et al.	2023/0024084	A1 1/2023 D'auria et al.
2020/0149921	A1	5/2020	Hoffman et al.	2023/0025724	A1 1/2023 Gilravi et al.
2020/0160961	A1	5/2020	Wadhawan et al.	2023/0027358	A1 1/2023 Williams et al.
2020/0225746	A1	7/2020	Bar-Zeev et al.	2023/0066552	A1 3/2023 Van Os et al.
2020/0249632	A1	8/2020	Olwal et al.	2023/0079396	A1 3/2023 Sokolowski
2020/0257434	A1	8/2020	Victor	2023/0107803	A1 4/2023 Dugan
2020/0261011	A1	8/2020	Seppänen et al.	2023/0119253	A1 4/2023 Sundstrom et al.
2020/0261763	A1	8/2020	Park et al.	2023/0136700	A1 5/2023 Williams et al.
2020/0276475	A1	9/2020	Casalini	2023/0191198	A1 6/2023 Lee et al.
2020/0289919	A1	9/2020	Gruben	2023/0221836	A1 7/2023 Clarke et al.
2020/0297249	A1	9/2020	Williams et al.	2023/0260416	A1 8/2023 Wilson et al.
2020/0341610	A1	10/2020	Quintana et al.	2023/0310935	A1 10/2023 Su et al.
2020/0356222	A1	11/2020	Clarke et al.	2023/0390606	A1 12/2023 Bolton et al.
2020/0356242	A1	11/2020	Wilson et al.	2023/0390626	A1 12/2023 Bolton et al.
2020/0356590	A1	11/2020	Clarke et al.	2023/0390627	A1 12/2023 Bolton et al.
2020/0357522	A1	11/2020	Pahwa et al.	2023/0393723	A1 12/2023 Arney et al.
				2023/0412908	A1 12/2023 Matas et al.
				2024/0028177	A1 1/2024 Pastrana Vicente et al.
				2024/0077309	A1 3/2024 Felton et al.
				2024/0081751	A1 3/2024 Murphy et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2024/0139608 A1 5/2024 Bolton et al.
 2024/0201829 A1 6/2024 Clarke et al.
 2024/0256115 A1 8/2024 Arney et al.
 2024/0257940 A1 8/2024 Williams et al.
 2024/0306941 A1 9/2024 Williams et al.
 2024/0316404 A1 9/2024 Williams et al.
 2024/0325821 A1 10/2024 Yu
 2024/0366111 A1 11/2024 Chen et al.
 2024/0370137 A1 11/2024 Williams et al.
 2024/0371516 A1 11/2024 Mistri et al.
 2024/0399208 A1 12/2024 Mikolay et al.
 2024/0399209 A1 12/2024 Mikolay et al.
 2024/0402880 A1 12/2024 Lareau et al.
 2024/0402881 A1 12/2024 Bignell et al.
 2025/0022570 A1 1/2025 Blahnik et al.
 2025/0032886 A1 1/2025 Chao et al.
 2025/0117127 A1 4/2025 Arney et al.
 2025/0153004 A1 5/2025 Williams et al.
 2025/0157646 A1 5/2025 Mistri et al.
 2025/0174142 A1 5/2025 Wilson et al.
 2025/0195954 A1 6/2025 D'Auria et al.

FOREIGN PATENT DOCUMENTS

CA 2826239 C 1/2017
 CN 1337638 A 2/2002
 CN 1397904 A 2/2003
 CN 1404233 A 3/2003
 CN 1523500 A 8/2004
 CN 1585943 A 2/2005
 CN 1619541 A 5/2005
 CN 1628609 A 6/2005
 CN 1717918 A 1/2006
 CN 1756273 A 4/2006
 CN 1767789 A 5/2006
 CN 1824358 A 8/2006
 CN 101150810 A 3/2008
 CN 101219046 A 7/2008
 CN 101444419 A 6/2009
 CN 101541387 A 9/2009
 CN 101651870 A 2/2010
 CN 101658423 A 3/2010
 CN 101668482 A 3/2010
 CN 101836894 A 9/2010
 CN 101890217 A 11/2010
 CN 101894206 A 11/2010
 CN 101910992 A 12/2010
 CN 101978374 A 2/2011
 CN 102339201 A 2/2012
 CN 102438521 A 5/2012
 CN 102448555 A 5/2012
 CN 102449560 A 5/2012
 CN 102449561 A 5/2012
 CN 102449566 A 5/2012
 CN 102549590 A 7/2012
 CN 102804238 A 11/2012
 CN 102814037 A 12/2012
 CN 102834079 A 12/2012
 CN 102989159 A 3/2013
 CN 103003668 A 3/2013
 CN 103154954 A 6/2013
 CN 103182175 A 7/2013
 CN 103210355 A 7/2013
 CN 103212197 A 7/2013
 CN 103270540 A 8/2013
 CN 103294124 A 9/2013
 CN 103370924 A 10/2013
 CN 103403627 A 11/2013
 CN 203276086 U 11/2013
 CN 103646570 A 3/2014
 CN 103682785 A 3/2014
 CN 103701504 A 4/2014
 CN 103876721 A 6/2014
 CN 104122994 A 10/2014
 CN 104288983 A 1/2015

CN 104464010 A 3/2015
 CN 104501043 A 4/2015
 CN 104508426 A 4/2015
 CN 104815428 A 8/2015
 CN 104857692 A 8/2015
 CN 104917794 A 9/2015
 CN 105187282 A 12/2015
 CN 105260078 A 1/2016
 CN 105320454 A 2/2016
 CN 105392064 A 3/2016
 CN 105681328 A 6/2016
 CN 105808959 A 7/2016
 CN 106310638 A 1/2017
 CN 106510719 A 3/2017
 CN 106537397 A 3/2017
 CN 106709235 A 5/2017
 CN 106878550 A 6/2017
 CN 107430483 A 12/2017
 CN 107469327 A 12/2017
 CN 107580776 A 1/2018
 CN 107749310 A 3/2018
 CN 107921317 A 4/2018
 CN 108200464 A 6/2018
 CN 108211310 A 6/2018
 CN 110456971 A 11/2019
 CN 110517749 A 11/2019
 CN 111796657 A 10/2020
 EP 0871177 A2 10/1998
 EP 0943290 A1 9/1999
 EP 1124175 A2 8/2001
 EP 1148412 A2 10/2001
 EP 1559372 A1 8/2005
 EP 1577746 A2 9/2005
 EP 1615114 A2 1/2006
 EP 1840717 A1 10/2007
 EP 1935339 A1 6/2008
 EP 1938233 A1 7/2008
 EP 2025368 A2 2/2009
 EP 2045703 A2 4/2009
 EP 2060970 A1 5/2009
 EP 2068237 A2 6/2009
 EP 1964022 B1 3/2010
 EP 2309475 A1 4/2011
 EP 2407219 A2 1/2012
 EP 2509074 A2 10/2012
 EP 2529663 A1 12/2012
 EP 2631830 A2 8/2013
 EP 2728680 A1 5/2014
 EP 2733578 A2 5/2014
 EP 2562633 B1 3/2016
 EP 2993602 A1 3/2016
 EP 3117767 A1 1/2017
 EP 3122038 A1 1/2017
 EP 3130997 A1 2/2017
 EP 3739439 B1 4/2023
 FR 2830093 A3 3/2003
 GB 2420260 A 5/2006
 JP 3-217976 A 9/1991
 JP 5-288869 A 11/1993
 JP 6-187118 A 7/1994
 JP 6-309138 A 11/1994
 JP 8-106469 A 4/1996
 JP 8-126632 A 5/1996
 JP 10-93848 A 4/1998
 JP 10-198337 A 7/1998
 JP 11-84030 A 3/1999
 JP 11-164175 A 6/1999
 JP 11-168694 A 6/1999
 JP 11-341425 A 12/1999
 JP 2000-138883 A 5/2000
 JP 2000-138888 A 5/2000
 JP 2000-148591 A 5/2000
 JP 2000-163031 A 6/2000
 JP 2000-221879 A 8/2000
 JP 2000-244673 A 9/2000
 JP 2000-350134 A 12/2000
 JP 2001-76078 A 3/2001
 JP 2001-136303 A 5/2001
 JP 2001-216336 A 8/2001

(56)	References Cited			JP	2010-162297	A	7/2010
	FOREIGN PATENT DOCUMENTS			JP	2010-181280	A	8/2010
				JP	2010-182287	A	8/2010
				JP	2010-186249	A	8/2010
JP	2001-265481	A	9/2001	JP	2010-206668	A	9/2010
JP	2001-309019	A	11/2001	JP	2011-514192	A	5/2011
JP	2001-325372	A	11/2001	JP	2011-125633	A	6/2011
JP	2002-73679	A	3/2002	JP	2011-159006	A	8/2011
JP	2002-152559	A	5/2002	JP	2011-183101	A	9/2011
JP	2002-190007	A	7/2002	JP	2011-192126	A	9/2011
JP	2002-346013	A	12/2002	JP	2011-525648	A	9/2011
JP	2003-102868	A	4/2003	JP	2011-198184	A	10/2011
JP	2003-126291	A	5/2003	JP	2011-206323	A	10/2011
JP	2003-131655	A	5/2003	JP	2011-210119	A	10/2011
JP	2003-157323	A	5/2003	JP	2011-229141	A	11/2011
JP	2003-163820	A	6/2003	JP	2011-259253	A	12/2011
JP	2003-216739	A	7/2003	JP	2012-20134	A	2/2012
JP	2003-248721	A	9/2003	JP	2012-35071	A	2/2012
JP	2003-319912	A	11/2003	JP	2012-59264	A	3/2012
JP	2003-337863	A	11/2003	JP	2012-86088	A	5/2012
JP	2003-338975	A	11/2003	JP	2012-524640	A	10/2012
JP	2003-345491	A	12/2003	JP	2012-230503	A	11/2012
JP	2003-348432	A	12/2003	JP	2012-232114	A	11/2012
JP	2004-15586	A	1/2004	JP	2013-103020	A	5/2013
JP	2004-32346	A	1/2004	JP	2013-117690	A	6/2013
JP	2004-102609	A	4/2004	JP	2013-140171	A	7/2013
JP	2004-113466	A	4/2004	JP	2013-146557	A	8/2013
JP	2004-145291	A	5/2004	JP	2013-530776	A	8/2013
JP	2004-153832	A	5/2004	JP	2013-537670	A	10/2013
JP	2004-174006	A	6/2004	JP	2013-543156	A	11/2013
JP	2004-288208	A	10/2004	JP	5346115	B1	11/2013
JP	2004-336536	A	11/2004	JP	2013-544140	A	12/2013
JP	2004-336711	A	11/2004	JP	2014-500740	A	1/2014
JP	2004-364184	A	12/2004	JP	2014-45782	A	3/2014
JP	2005-38101	A	2/2005	JP	2014-45783	A	3/2014
JP	2005-79814	A	3/2005	JP	2014-104139	A	6/2014
JP	2005-92386	A	4/2005	JP	2014-143473	A	8/2014
JP	2005-100084	A	4/2005	JP	2014-160461	A	9/2014
JP	3635663	B2	4/2005	JP	2014-168685	A	9/2014
JP	2005-515530	A	5/2005	JP	2014-171831	A	9/2014
JP	2005-150836	A	6/2005	JP	2014-216001	A	11/2014
JP	2005-175991	A	6/2005	JP	2014-230630	A	12/2014
JP	2005-182320	A	7/2005	JP	2015-58218	A	3/2015
JP	2005-202483	A	7/2005	JP	2015-507811	A	3/2015
JP	2005-202651	A	7/2005	JP	2015-509019	A	3/2015
JP	2005-303728	A	10/2005	JP	2015-69430	A	4/2015
JP	2005-321516	A	11/2005	JP	2015-509755	A	4/2015
JP	2005-339420	A	12/2005	JP	2015-515287	A	5/2015
JP	2006-67344	A	3/2006	JP	2015-134111	A	7/2015
JP	2006-139340	A	6/2006	JP	5771242	B2	8/2015
JP	2006-140865	A	6/2006	JP	2016-17331	A	2/2016
JP	2006-155104	A	6/2006	JP	2016-502875	A	2/2016
JP	2006-180899	A	7/2006	JP	2016-52512	A	4/2016
JP	2006-195592	A	7/2006	JP	2016-62590	A	4/2016
JP	2006-203809	A	8/2006	JP	2016-517329	A	6/2016
JP	2006-230679	A	9/2006	JP	2016-158115	A	9/2016
JP	2006-236249	A	9/2006	JP	2016-158867	A	9/2016
JP	3830956	B1	10/2006	JP	2016-167299	A	9/2016
JP	2006-338233	A	12/2006	JP	2016-527581	A	9/2016
JP	2007-515775	A	6/2007	JP	2016-528016	A	9/2016
JP	2007-525775	A	9/2007	JP	2016-177151	A	10/2016
JP	2007-260288	A	10/2007	JP	2016-185288	A	10/2016
JP	2007-292971	A	11/2007	JP	2016-202751	A	12/2016
JP	2007-330513	A	12/2007	JP	2017-503264	A	1/2017
JP	2008-104758	A	5/2008	JP	2017-83978	A	5/2017
JP	2008-106469	A	5/2008	JP	2017-134689	A	8/2017
JP	2008-518330	A	5/2008	JP	2017-156267	A	9/2017
JP	2008-183339	A	8/2008	JP	2017-531235	A	10/2017
JP	2009-50471	A	3/2009	JP	2017-211994	A	11/2017
JP	2009-68265	A	4/2009	JP	2017-532069	A	11/2017
JP	2009-78134	A	4/2009	JP	2018-22995	A	2/2018
JP	2009-88989	A	4/2009	JP	6345911	B2	6/2018
JP	2009-112731	A	5/2009	JP	2018-102908	A	7/2018
JP	2009-211241	A	9/2009	JP	2018-202174	A	12/2018
JP	2009-282670	A	12/2009	JP	2019-3670	A	1/2019
JP	2010-12335	A	1/2010	JP	2020-30853	A	2/2020
JP	2010-88886	A	4/2010	JP	2024-537657	A	10/2024
JP	2010-517725	A	5/2010	KR	2003-0070871		9/2003
JP	2010-122901	A	6/2010	KR	10-2005-0101162	A	10/2005

(56)

References Cited

FOREIGN PATENT DOCUMENTS

KR	10-2006-0032793	A	4/2006
KR	10-2006-0117570	A	11/2006
KR	10-2011-0017076	A	2/2011
KR	10-2011-0121394	A	11/2011
KR	10-2012-0023657	A	3/2012
KR	10-2012-0076559	A	7/2012
KR	10-2012-0098854	A	9/2012
KR	10-2012-0132732	A	12/2012
KR	10-2013-0026541	A	3/2013
KR	10-2013-0043698	A	5/2013
KR	10-2013-0097235	A	9/2013
KR	10-2013-0111569	A	10/2013
KR	10-2013-0111570	A	10/2013
KR	10-2013-0135282	A	12/2013
KR	10-2015-0026635	A	3/2015
KR	10-2015-0062761	A	6/2015
KR	10-2016-0027943	A	3/2016
KR	10-2016-0084705	A	7/2016
KR	10-2016-0105129	A	9/2016
KR	10-2016-0142418	A	12/2016
KR	10-2017-0003608	A	1/2017
KR	10-2017-0020085	A	2/2017
KR	10-2017-0029014	A	3/2017
KR	10-2017-0032471	A	3/2017
KR	10-2017-0056300	A	5/2017
KR	10-2018-0026066	A	3/2018
KR	10-2019-0022883	A	3/2019
KR	10-2019-0028574	A	3/2019
KR	10-2019-0081500	A	7/2019
KR	10-2019-0129850	A	11/2019
KR	10-2019-0141702	A	12/2019
WO	97/06492	A1	2/1997
WO	97/38626	A1	10/1997
WO	99/41682	A2	8/1999
WO	99/54807	A1	10/1999
WO	01/29702	A2	4/2001
WO	02/27530	A2	4/2002
WO	02/080176	A2	10/2002
WO	03/023593	A1	3/2003
WO	03/081458	A1	10/2003
WO	2004/047440	A2	6/2004
WO	2005/029242	A2	3/2005
WO	2005/070289	A1	8/2005
WO	2005/093550	A2	10/2005
WO	2005/103863	A2	11/2005
WO	2006/020305	A2	2/2006
WO	2006/047697	A2	5/2006
WO	2006/103965	A1	10/2006
WO	2007/081629	A2	7/2007
WO	2008/030779	A2	3/2008
WO	2008/085737	A1	7/2008
WO	2009/084141	A1	7/2009
WO	2009/129402	A1	10/2009
WO	2009/152608	A1	12/2009
WO	2010/126821	A1	11/2010
WO	2010/126825	A1	11/2010
WO	2010/129221	A1	11/2010
WO	2011/072111	A2	6/2011
WO	2011/108335	A1	9/2011
WO	2012/018513	A1	2/2012
WO	2012/021507	A2	2/2012
WO	2012/036891	A2	3/2012
WO	2012/061438	A2	5/2012
WO	2012/061440	A2	5/2012
WO	2012/078079	A2	6/2012
WO	2012/086910	A1	6/2012
WO	2012/095712	A1	7/2012
WO	2012/127484	A1	9/2012
WO	2013/052789	A1	4/2013
WO	2013/109762	A1	7/2013
WO	2013/109776	A1	7/2013
WO	2013/109777	A1	7/2013
WO	2013/109916	A1	7/2013
WO	2013/157307	A1	10/2013
WO	2013/169870	A1	11/2013

WO	2013/173838	A2	11/2013
WO	2014/059259	A1	4/2014
WO	2014/105276	A1	7/2014
WO	2014/144258	A2	9/2014
WO	2014/200730	A1	12/2014
WO	2014/207294	A1	12/2014
WO	2015/027133	A1	2/2015
WO	2015/027178	A1	2/2015
WO	2015/091228	A1	6/2015
WO	2015/179592	A1	11/2015
WO	2015/183828	A1	12/2015
WO	2015/198488	A1	12/2015
WO	2016/022203	A1	2/2016
WO	2016/025036	A1	2/2016
WO	2016/036472	A1	3/2016
WO	2016/036582	A2	3/2016
WO	2016/036582	A3	6/2016
WO	2016/160632	A1	10/2016
WO	2017/013770	A1	1/2017
WO	2017/014403	A1	1/2017
WO	2017/030646	A1	2/2017
WO	2017/037242	A1	3/2017
WO	2017/218194	A1	12/2017
WO	2018/048510	A1	3/2018
WO	2018/213066	A1	11/2018
WO	2018/222313	A1	12/2018
WO	2018/236291	A1	12/2018
WO	2019/017508	A1	1/2019
WO	2019/024383	A1	2/2019
WO	2019/024603	A1	2/2019
WO	2019/183422	A1	9/2019
WO	2019/190001	A1	10/2019
WO	2019/217005	A1	11/2019
WO	2019/217009	A1	11/2019
WO	2019/217249	A2	11/2019
WO	2019/231982	A1	12/2019
WO	2023/049418	A2	3/2023

OTHER PUBLICATIONS

Corrected Notice of Allowance received for U.S. Appl. No. 17/952,181, mailed on Aug. 13, 2024, 2 pages.

Extended European Search Report received for European Patent Application No. 24179066.6, mailed on Aug. 8, 2024, 10 pages.

Notice of Allowance received for Chinese Patent Application No. 202310828052.7, mailed on Jul. 29, 2024, 4 pages (1 page of English Translation and 3 pages of Official Copy).

Notice of Allowance received for Korean Patent Application No. 10-2022-7026884, mailed on Jul. 30, 2024, 8 pages (2 pages of English Translation and 6 pages of Official Copy).

Office Action received for Chinese Patent Application No. 202310774963.6, mailed on Jul. 17, 2024, 21 pages (13 pages of English Translation and 8 pages of Official Copy).

Non-Final Office Action received for U.S. Appl. No. 17/952,236, mailed on Sep. 16, 2024, 16 pages.

Notice of Allowance received for U.S. Appl. No. 17/951,624, mailed on Sep. 20, 2024, 9 pages.

Notice of Allowance received for U.S. Appl. No. 18/405,969, mailed on Sep. 19, 2024, 7 pages.

Office Action received for Australian Patent Application No. 2023285859, mailed on Aug. 29, 2024, 2 pages.

Office Action received for Japanese Patent Application No. 2023-168815, mailed on Sep. 6, 2024, 10 pages (5 pages of English Translation and 5 pages of Official Copy).

Corrected Notice of Allowance received for U.S. Appl. No. 17/952,181, mailed on Aug. 28, 2024, 2 pages.

Notice of Acceptance received for Australian Patent Application No. 2023210876, mailed on Aug. 20, 2024, 3 pages.

Notice of Allowance received for Japanese Patent Application No. 2023-065859, mailed on Aug. 16, 2024, 4 pages (1 page of English Translation and 3 pages of Official Copy).

Notice of Allowance received for Japanese Patent Application No. 2024-077470, mailed on Aug. 23, 2024, 4 pages (1 page of English Translation and 3 pages of Official Copy).

(56)

References Cited**OTHER PUBLICATIONS**

Office Action received for German Patent Application No. 112015007313.2, mailed on Aug. 6, 2024, 12 pages (6 pages of English Translation and 6 pages of Official Copy).

Applicant-Initiated Interview Summary received for U.S. Appl. No. 18/135,056, mailed on Nov. 19, 2024, 2 pages.

Corrected Notice of Allowance received for U.S. Appl. No. 17/952,181, mailed on Nov. 12, 2024, 2 pages.

Corrected Notice of Allowance received for U.S. Appl. No. 18/405,969, mailed on Nov. 13, 2024, 2 pages.

Corrected Notice of Allowance received for U.S. Appl. No. 18/633,120, mailed on Nov. 12, 2024, 9 pages.

Decision to Grant received for German Patent Application No. 112015007313.2, mailed on Nov. 6, 2024, 7 pages (1 page of English Translation and 6 pages of Official Copy).

Decision to Grant received for Japanese Patent Application No. 2021-565912, mailed on Nov. 14, 2024, 12 pages (1 page of English Translation and 11 pages of Official Copy).

Decision to Grant received for Japanese Patent Application No. 2023-158326, mailed on Nov. 12, 2024, 3 pages (2 pages of English Translation and 1 page of Official Copy).

Intention to Grant received for European Patent Application No. 23153898.4, mailed on Nov. 12, 2024, 10 pages.

Non-Final Office Action received for U.S. Appl. No. 18/117,998, mailed on Nov. 6, 2024, 12 pages.

Notice of Allowance received for Chinese Patent Application No. 202210312598.2, mailed on Nov. 6, 2024, 4 pages (1 page of English Translation and 3 pages of Official Copy).

Notice of Allowance received for Japanese Patent Application No. 2023-041035, mailed on Nov. 8, 2024, 4 pages (1 page of English Translation and 3 pages of Official Copy).

Office Action received for Chinese Patent Application No. 202310774963.6, mailed on Oct. 31, 2024, 19 pages (12 pages of English Translation and 7 pages of Official Copy).

Office Action received for Korean Patent Application No. 10-2022-7026174, mailed on Oct. 31, 2024, 14 pages (6 pages of English Translation and 8 pages of Official Copy).

Corrected Notice of Allowance received for U.S. Appl. No. 17/735,395, mailed on Jul. 16, 2024, 3 pages.

Corrected Notice of Allowance received for U.S. Appl. No. 17/951,945, mailed on Jul. 9, 2024, 2 pages.

Corrected Notice of Allowance received for U.S. Appl. No. 18/135,056, mailed on Jul. 17, 2024, 6 pages.

Corrected Notice of Allowance received for U.S. Appl. No. 18/135,056, mailed on Jul. 22, 2024, 3 pages.

Decision to Grant received for European Patent Application No. 21714460.9, mailed on Jun. 20, 2024, 4 pages.

Intention to Grant received for European Patent Application No. 23153898.4, mailed on Jul. 2, 2024, 11 pages.

Notice of Allowance received for Chinese Patent Application No. 202210326960.1, mailed on Jun. 21, 2024, 5 pages (1 page of English Translation and 4 pages of Official Copy).

Notice of Allowance received for U.S. Appl. No. 17/735,395, mailed on Jul. 3, 2024, 11 pages.

Notice of Allowance received for U.S. Appl. No. 17/951,945, mailed on Jun. 26, 2024, 10 pages.

Notice of Allowance received for U.S. Appl. No. 18/135,056, mailed on Jul. 10, 2024, 10 pages.

Office Action received for Australian Patent Application No. 2023210876, mailed on Jun. 21, 2024, 2 pages.

Office Action received for European Patent Application No. 22731852.4, mailed on Jun. 26, 2024, 7 pages.

Office Action received for European Patent Application No. 23153899.2, mailed on Jun. 25, 2024, 11 pages.

Office Action received for European Patent Application No. 23153900.8, mailed on Jun. 26, 2024, 11 pages.

Office Action received for Japanese Patent Application No. 2021-565912, mailed on Jun. 18, 2024, 3 pages (1 page of English Translation and 2 pages of Official Copy).

Office Action received for Japanese Patent Application No. 2023-041035, mailed on Jul. 16, 2024, 4 pages (2 pages of English Translation and 2 pages of Official Copy).

Office Action received for Japanese Patent Application No. 2023-097896, mailed on Jul. 5, 2024, 10 pages (5 pages of English Translation and 5 pages of Official Copy).

Office Action received for Japanese Patent Application No. 2024-077470, mailed on Jun. 24, 2024, 5 pages (2 pages of English Translation and 3 pages of Official Copy).

Office Action received for Korean Patent Application No. 10-2021-7036242, mailed on May 31, 2024, 7 pages (2 pages of English Translation and 5 pages of Official Copy).

Applicant-Initiated Interview Summary received for U.S. Appl. No. 17/952,236, mailed on Oct. 15, 2024, 2 pages.

Corrected Notice of Allowance received for U.S. Appl. No. 18/405,969, mailed on Oct. 17, 2024, 2 pages.

Examiner's Pre-Review Report received for Japanese Patent Application No. 2022-130087, mailed on Sep. 20, 2024, 2 pages (1 page of English Translation and 1 page of Official Copy).

Office Action received for Australian Patent Application No. 2024200284, mailed on Sep. 30, 2024, 2 pages.

Office Action received for Japanese Patent Application No. 2023-097896, mailed on Oct. 15, 2024, 8 pages (4 pages of English Translation and 4 pages of Official Copy).

Blackburn Ian, "How Using Custom Workouts on Apple Watch will make you a better Athlete (and everything you need to know about creating them)—The Apple Watch Triathlete", Available online at: <https://theapplewatchtriathlete.com/blog-1/2022/8/23/how-using-custom-workouts-on-apple-watch-will-make-you-a-better-athlete-and-everything-you-need-to-know-about-creating-them>, Aug. 23, 2022, pp. 1-51.

Non-Final Office Action received for U.S. Appl. No. 18/135,056, mailed on Oct. 25, 2024, 17 pages.

Notice of Allowance received for U.S. Appl. No. 17/952,181, mailed on Oct. 31, 2024, 5 pages.

Notice of Allowance received for U.S. Appl. No. 18/633,120, mailed on Nov. 5, 2024, 12 pages.

Office Action received for Australian Patent Application No. 2023258443, mailed on Oct. 21, 2024, 4 pages.

Office Action received for Chinese Patent Application No. 202080039364.4, mailed on Sep. 28, 2024, 17 pages (9 pages of English Translation and 8 pages of Official Copy).

Office Action received for Indian Patent Application No. 202248063719, mailed on Oct. 24, 2024, 5 pages.

Corrected Notice of Allowance received for U.S. Appl. No. 17/951,624, mailed on Oct. 3, 2024, 2 pages.

Corrected Notice of Allowance received for U.S. Appl. No. 18/405,969, mailed on Oct. 1, 2024, 2 pages.

Notice of Allowance received for Chinese Patent Application No. 202210312775.7, mailed on Sep. 23, 2024, 5 pages (1 page of English Translation and 4 pages of Official Copy).

Office Action received for Australian Patent Application No. 2023214377, mailed on Sep. 25, 2024, 4 pages.

Office Action received for Japanese Patent Application No. 2023-133506, mailed on Sep. 20, 2024, 6 pages (3 pages of English Translation and 3 pages of Official Copy).

Office Action received for Japanese Patent Application No. 2023-158326, mailed on Sep. 30, 2024, 3 pages (1 page of English Translation and 2 pages of Official Copy).

"Fitbit App", Available online at: <http://web.archive.org/web/20180114083150/https://www.fitbit.com/au/app>, Jan. 14, 2018, 8 pages.

"Garmin Edge 520, Owner's Manual", Online available at: https://www8.garmin.com/manuals/webhelp/edge520/EN-US/Edge_520_OM_EN-US.pdf, 2015, 24 pages.

"Graphs and Charts", Online available at: <https://www.teachervision.com/lesson-planning/graph-chart-teacher-resources>, retrieved on Dec. 12, 2018, 4 pages.

"Gym Book—Strength Training Planner, Logger and Analyzer", GymBookApp, Available Online at: <https://web.archive.org/web/20160401104508/https://gymbookapp.com/>, Apr. 1, 2016, 10 pages.

"Microsoft Support Webcasts", Windows Media Player 7: New features and Walk-through Transcript, Jul. 13, 2000, 7 pages.

(56)

References Cited**OTHER PUBLICATIONS**

"Mugs", Online Available at: <https://web.archive.org/web/20151029034349/http://le-mugs.com/>, Oct. 29, 2015, 14 pages.

"Multi-Set Bar Chart", The Data Visualization Catalogue, Available Online at: https://datavizcatalogue.com/methods/multiset_barchart.html, Feb. 8, 2014, 3 pages.

"My CalStep", <http://www.surprisesoftware.com/mycalstep/>, retrieved from the Wayback Machine, May 9, 2007, 2 pages.

"Support WebCast: Windows Media Player 7: New features and Walk-through", Microsoft Knowledge Base Article-324594, Jul. 13, 2000, 2 pages.

"Suunto Spartan Trainer Wrist HR 1.12", Online Available at: https://web.archive.org/web/20180127155200/https://ns.suunto.com/Manuals/Spartan_Trainer_WristHR/Userguides/Suunto_Spartan_Trainer_WristHR_UserGuide_EN.pdf, Jan. 17, 2018, 47 pages.

"Utilization of Galaxy S4—S Health", ChatOn and Samsung Hub, Available at: <http://seeit.kr/1263>, Jun. 12, 2013, 25 pages.

"Visual Pace Alarm app", Available Online at: <https://apps.garmin.com/en-us/apps/3940f3a2-4847-4078-a911-d77422966c82>, Oct. 19, 2016, 1 page.

"Winamp from Nullsoft, screendumps of the media player having visual effect", version 2.62, 1997-2000, 2 pages.

"Windows Media Player Visualization, To view a visualization", 2000-2001, 2 pages.

Adeniyi, Samuel, "How to connect a second PS4 controller to a PlayStation 4 console", Online available on: https://www.youtube.com/watch?v=mOZX_SrNISE, May 28, 2017, 2 pages.

Advisory Action Received for U.S. Appl. No. 16/144,864, mailed on Jul. 29, 2019, 6 pages.

Advisory Action Received for U.S. Appl. No. 10/497,076, mailed on Aug. 2, 2011, 3 pages.

Advisory Action Received for U.S. Appl. No. 10/497,076, mailed on Oct. 28, 2008, 3 pages.

Advisory Action Received for U.S. Appl. No. 14/732,773, mailed on Aug. 23, 2019, 6 pages.

Advisory Action Received for U.S. Appl. No. 14/732,773, mailed on Nov. 9, 2018, 6 pages.

Advisory Action Received for U.S. Appl. No. 14/839,922, mailed on Mar. 24, 2017, 4 pages.

Advisory Action Received for U.S. Appl. No. 16/144,849, mailed on Aug. 12, 2019, 5 pages.

Advisory Action Received for U.S. Appl. No. 16/144,864, mailed on Jul. 6, 2020, 6 pages.

Advisory Action Received for U.S. Appl. No. 16/377,892, mailed on Apr. 9, 2021, 4 pages.

Advisory Action Received for U.S. Appl. No. 16/378,136, mailed on Apr. 12, 2021, 4 pages.

Advisory Action Received for U.S. Appl. No. 17/381,570, mailed on May 23, 2023, 5 pages.

Advisory Action Received for U.S. Appl. No. 17/591,184, mailed on Nov. 14, 2023, 5 pages.

Advisory Action Received for U.S. Appl. No. 17/744,500, mailed on Nov. 14, 2023, 5 pages.

Advisory Action Received for U.S. Appl. No. 17/952,133, mailed on Oct. 20, 2023, 7 pages.

Allen, Ray, "Join the Nike Training Club and let your iPhone be your fitness instructor", Apr. 19, 2011, 26 pages.

Allison, Conor, "Working out with Fitbit's wearable-powered boutique fitness classes", Online available at: <https://www.wareable.com/wearable-tech/fitbit-fitness-classes-review-3849>, May 14, 2018, 8 pages.

Androidandyuk, "Endomondo Android App Review", Available online at: <https://www.youtube.com/watch?v=Wyjyza-P1E>, Jan. 9, 2013, 17 pages.

Apple, "iPhone User's Guide", Available at <http://mesnotices.20minutes.fr/manuel-notice-mode-emploi/APPLE/IPHONE%2D%5FE#>, Retrieved on Mar. 27, 2008, Jun. 2007, 137 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 16/994,352, mailed on Nov. 2, 2021, 4 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 15/608,848, mailed on Apr. 13, 2021, 4 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 15/608,848, mailed on May 12, 2020, 5 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 15/608,848, mailed on Oct. 26, 2020, 3 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 15/627,069, mailed on Nov. 4, 2019, 6 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 16/144,735, mailed on Jun. 18, 2020, 3 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 16/144,753, mailed on Jun. 18, 2020, 3 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 16/144,849, mailed on Jan. 21, 2020, 6 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 16/144,864, mailed on Apr. 29, 2020, 4 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 16/584,783, mailed on May 4, 2020, 3 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 16/894,309, mailed on Jan. 26, 2021, 3 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/030,318, mailed on Jul. 30, 2021, 4 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/030,321, mailed on Jul. 30, 2021, 2 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/381,570, mailed on Apr. 26, 2022, 5 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 15/600,243, mailed on Nov. 1, 2019, 6 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 15/608,848, mailed on Nov. 1, 2019, 3 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 15/627,069, mailed on Jan. 22, 2021, 4 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 15/627,069, mailed on Jul. 20, 2020, 5 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 15/705,849, mailed on Feb. 14, 2020, 3 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 15/705,849, mailed on Jun. 29, 2020, 3 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 15/925,652, mailed on Nov. 3, 2020, 4 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 16/138,809, mailed on Dec. 16, 2020, 7 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 16/138,809, mailed on Jun. 9, 2020, 4 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 16/144,753, mailed on Nov. 4, 2020, 3 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 16/144,864, mailed on Jun. 22, 2020, 3 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 16/377,892, mailed on Mar. 26, 2021, 2 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 16/377,892, mailed on Oct. 13, 2020, 5 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 16/378,136, mailed on Mar. 26, 2021, 2 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 16/378,136, mailed on Oct. 13, 2020, 4 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 16/418,786, mailed on Mar. 30, 2021, 4 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 16/418,786, mailed on May 9, 2022, 2 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 16/418,786, mailed on Sep. 23, 2022, 2 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 16/450,531, mailed on Aug. 11, 2020, 5 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 16/584,776, mailed on May 13, 2020, 9 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 16/584,776, mailed on Nov. 25, 2020, 5 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 16/820,383, mailed on Aug. 12, 2022, 2 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 16/820,383, mailed on Mar. 11, 2021, 2 pages.

(56)

References Cited**OTHER PUBLICATIONS**

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 16/820,383, mailed on May 10, 2022, 2 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 16/888,629, mailed on Aug. 4, 2021, 5 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 16/894,309, mailed on Jun. 25, 2021, 4 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 16/987,275, mailed on Feb. 3, 2022, 4 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/030,337, mailed on Jul. 27, 2022, 2 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/031,543, mailed on Apr. 21, 2022, 2 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/031,854, mailed on Apr. 6, 2023, 5 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/031,854, mailed on Dec. 21, 2023, 5 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/031,854, mailed on Feb. 25, 2022, 5 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/031,854, mailed on Jan. 24, 2023, 6 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/031,854, mailed on Jul. 27, 2022, 5 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/031,859, mailed on Aug. 1, 2023, 4 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/031,859, mailed on Dec. 27, 2022, 5 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/031,859, mailed on Feb. 25, 2022, 4 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/031,859, mailed on Feb. 26, 2021, 4 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/031,859, mailed on Jul. 28, 2022, 3 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/031,859, mailed on Jun. 30, 2021, 4 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/031,859, mailed on Mar. 3, 2023, 5 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/031,874, mailed on Feb. 25, 2022, 4 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/031,874, mailed on Feb. 26, 2021, 4 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/031,874, mailed on Jan. 24, 2023, 5 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/031,874, mailed on Jul. 27, 2022, 5 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/031,874, mailed on Jun. 30, 2021, 4 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/041,438, mailed on Jun. 23, 2023, 4 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/153,703, mailed on May 11, 2022, 4 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/157,728, mailed on Feb. 3, 2022, 5 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/192,161, mailed on Dec. 24, 2021, 4 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/192,161, mailed on Jun. 29, 2021, 4 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/192,161, mailed on Sep. 29, 2021, 3 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/381,570, mailed on Apr. 6, 2023, 4 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/381,570, mailed on Aug. 24, 2022, 5 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/381,570, mailed on Nov. 28, 2022, 5 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/516,537, mailed on Jul. 5, 2022, 4 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/516,537, mailed on Nov. 22, 2022, 2 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/591,184, mailed on Feb. 27, 2023, 2 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/591,184, mailed on Jun. 28, 2023, 2 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/591,184, mailed on Oct. 30, 2023, 2 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/591,184, mailed on Sep. 23, 2022, 2 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/666,301, mailed on Mar. 28, 2023, 4 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/735,395, mailed on Apr. 28, 2023, 2 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/735,395, mailed on Aug. 1, 2023, 2 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/735,395, mailed on Jan. 31, 2024, 2 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/735,395, mailed on Nov. 15, 2023, 2 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/744,500, mailed on May 30, 2023, 4 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/744,500, mailed on Oct. 17, 2023, 4 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/745,021, mailed on Apr. 6, 2023, 2 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/892,534, mailed on Aug. 3, 2023, 3 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/892,534, mailed on Feb. 1, 2024, 4 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/892,534, mailed on Feb. 6, 2023, 2 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/892,534, mailed on Feb. 10, 2023, 2 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/896,791, mailed on Oct. 12, 2023, 2 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/951,613, mailed on Sep. 8, 2023, 5 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/951,624, mailed on Nov. 16, 2023, 3 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/951,875, mailed on Feb. 28, 2023, 2 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/951,875, mailed on Jun. 27, 2023, 2 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/951,945, mailed on Apr. 28, 2023, 2 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/951,945, mailed on Aug. 1, 2023, 2 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/951,945, mailed on Jan. 31, 2024, 2 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/951,945, mailed on Nov. 15, 2023, 2 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/951,976, mailed on Aug. 23, 2023, 2 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/952,027, mailed on May 30, 2023, 4 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/952,027, mailed on Sep. 11, 2023, 3 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/952,133, mailed on Jul. 3, 2023, 4 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/952,233, mailed on May 24, 2023, 5 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/952,233, mailed on Sep. 7, 2023, 4 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 17/952,239, mailed on May 31, 2023, 2 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 18/117,998, mailed on Jan. 31, 2024, 4 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 18/117,998, mailed on Nov. 1, 2023, 2 pages.

Applicant-Initiated Interview Summary Received for U.S. Appl. No. 18/135,056, mailed on Jan. 3, 2024, 2 pages.

Bagala et al., "Evaluation of Accelerometer-Based Fall Detection Algorithms on Real-World Falls", PLoS ONE, vol. 7, No. 5, May 16, 2012, 9 pages.

(56)

References Cited**OTHER PUBLICATIONS**

Board Decision Received for Chinese Patent Application No. 201380081349.6, mailed on Nov. 23, 2020, 2 pages.

Board Opinion Received for Chinese Reexamination Patent Application No. 200780001142.8, mailed on Oct. 21, 2014, 13 pages.

Brief Communication Regarding Oral Proceedings Received for European Patent Application No. 20203526.7, mailed on Dec. 23, 2022, 4 pages.

Brief Communication Regarding Oral Proceedings Received for European Patent Application No. 18197554.1, mailed on Feb. 6, 2023, 8 pages.

Brief Communication Regarding Oral Proceedings Received for European Patent Application No. 18727543.3, mailed on Mar. 23, 2023, 1 page.

Brief Communication Regarding Oral Proceedings Received for European Patent Application No. 20182116.2, mailed on Apr. 13, 2022, 3 pages.

Brief Communication Regarding Oral Proceedings Received for European Patent Application No. 20203526.7, mailed on Jan. 18, 2023, 1 page.

Brief Communication Regarding Oral Proceedings Received for European Patent Application No. 20721342.2, mailed on Oct. 18, 2022, 1 page.

Brief Communication Regarding Oral Proceedings Received for European Patent Application No. 21159939.4, mailed on Nov. 2, 2023, 8 pages.

Canon IXUS 700—Additional Evidence and Information, 2023, 3 pages.

Canon, “Camera User Guide Canon UK) LTD”, Online available at: https://bedienungsanleitung-deutsch.de/bedienungsanleitung-handbuch/Canon_Digital_Ixus_700_EN.pdf, 2005, 196 pages.

CBS This Morning, “This smart mirror puts a personal trainer in your reflection”, Available on: <https://www.youtube.com/watch?v=nSmTTZcpVGg>, Oct. 13, 2018, 4 pages.

Certificate of Examination Received for Australian Patent Application No. 2018101855, mailed on Aug. 6, 2019, 2 pages.

Certification of Examination Received for Australian Patent Application No. 2018100158, mailed on Oct. 23, 2018, 2 pages.

Chengcheng et al., “Platform of Development of Motion Control Systems Experimental Software”, Experimental Technology and Management, vol. 30, No. 1, Jan. 2013, 3 pages.

Cho H.S., Satisfactory Innovative Smart-watch (fitbit force) . . . review after seven days of use, such as the amount of sleep and movement (improving sleep is the object of X-Blue Online Available at: <https://x-blueuv.blogspot.com/2013/12/fitbit-force.html>”, Dec. 3, 2013, 8 pages.

CNET, “Google Fit’s automatic activity tracking is getting smarter on Android Wear”, Available online at: https://www.youtube.com/watch?v=IttziCid_d8, May 18, 2016, 1 page.

Codrington, Simon, “Intuitive Scrolling Interfaces with CSS Scroll Snap Points”, Online Available at: <https://www.sitepoint.com/intuitive-scrolling-interfaces-with-css-scroll-snap-points/>, Dec. 8, 2015, 14 pages.

Communication of the Board of Appeal Received for European Patent Application No. 13811085.3, mailed on Jul. 28, 2022, 13 pages.

Communication of the Board of Appeal Received for European Patent Application No. 15771747.1, mailed on Aug. 25, 2021, 9 pages.

Corrected Notice of Allowance Received for U.S. Appl. No. 12/566,994, mailed on Jan. 22, 2015, 2 pages.

Corrected Notice of Allowance Received for U.S. Appl. No. 13/666,943, mailed on Aug. 11, 2016, 2 pages.

Corrected Notice of Allowance Received for U.S. Appl. No. 14/732,773, mailed on Feb. 10, 2020, 3 pages.

Corrected Notice of Allowance Received for U.S. Appl. No. 14/732,773, mailed on Mar. 24, 2020, 3 pages.

Corrected Notice of Allowance Received for U.S. Appl. No. 15/183,663, mailed on Feb. 25, 2019, 3 pages.

Corrected Notice of Allowance Received for U.S. Appl. No. 15/183,663, mailed on Mar. 27, 2019, 2 pages.

Corrected Notice of Allowance Received for U.S. Appl. No. 15/281,524, mailed on Jun. 3, 2019, 2 pages.

Corrected Notice of Allowance Received for U.S. Appl. No. 15/600,243, mailed on Feb. 5, 2020, 3 pages.

Corrected Notice of Allowance Received for U.S. Appl. No. 15/600,243, mailed on Mar. 13, 2020, 3 pages.

Corrected Notice of Allowance Received for U.S. Appl. No. 15/600,243, mailed on Mar. 31, 2020, 5 pages.

Corrected Notice of Allowance Received for U.S. Appl. No. 16/377,892, mailed on Aug. 11, 2021, 3 pages.

Corrected Notice of Allowance Received for U.S. Appl. No. 16/378,136, mailed on Aug. 11, 2021, 2 pages.

Corrected Notice of Allowance Received for U.S. Appl. No. 16/378,136, mailed on Jun. 11, 2021, 2 pages.

Corrected Notice of Allowance Received for U.S. Appl. No. 16/418,786, mailed on Jan. 5, 2022, 3 pages.

Corrected Notice of Allowance Received for U.S. Appl. No. 16/418,786, mailed on Jun. 23, 2022, 2 pages.

Corrected Notice of Allowance Received for U.S. Appl. No. 16/450,531, mailed on Nov. 12, 2020, 2 pages.

Corrected Notice of Allowance Received for U.S. Appl. No. 16/450,531, mailed on Oct. 30, 2020, 2 pages.

Corrected Notice of Allowance Received for U.S. Appl. No. 16/820,383, mailed on Apr. 28, 2023, 2 pages.

Corrected Notice of Allowance Received for U.S. Appl. No. 16/820,383, mailed on Aug. 13, 2021, 2 pages.

Corrected Notice of Allowance Received for U.S. Appl. No. 16/820,383, mailed on Aug. 19, 2021, 2 pages.

Corrected Notice of Allowance Received for U.S. Appl. No. 16/820,383, mailed on Oct. 5, 2021, 2 pages.

Corrected Notice of Allowance Received for U.S. Appl. No. 16/888,629, mailed on Jan. 21, 2022, 2 pages.

Corrected Notice of Allowance Received for U.S. Appl. No. 16/987,275, mailed on Jun. 8, 2022, 3 pages.

Corrected Notice of Allowance Received for U.S. Appl. No. 17/030,318, mailed on Jan. 24, 2022, 2 pages.

Corrected Notice of Allowance Received for U.S. Appl. No. 17/030,318, mailed on Jun. 1, 2023, 3 pages.

Corrected Notice of Allowance Received for U.S. Appl. No. 17/030,321, mailed on Aug. 15, 2022, 3 pages.

Corrected Notice of Allowance Received for U.S. Appl. No. 17/030,337, mailed on Aug. 31, 2022, 2 pages.

Corrected Notice of Allowance Received for U.S. Appl. No. 17/030,337, mailed on Feb. 10, 2023, 2 pages.

Corrected Notice of Allowance Received for U.S. Appl. No. 17/030,337, mailed on Feb. 17, 2023, 2 pages.

Corrected Notice of Allowance Received for U.S. Appl. No. 17/030,337, mailed on Nov. 3, 2022, 2 pages.

Corrected Notice of Allowance Received for U.S. Appl. No. 17/030,337, mailed on Nov. 15, 2022, 2 pages.

Corrected Notice of Allowance Received for U.S. Appl. No. 17/030,337, mailed on Oct. 18, 2022, 2 pages.

Corrected Notice of Allowance Received for U.S. Appl. No. 17/030,337, mailed on Sep. 21, 2022, 2 pages.

Corrected Notice of Allowance Received for U.S. Appl. No. 17/031,543, mailed on Aug. 22, 2022, 2 pages.

Corrected Notice of Allowance Received for U.S. Appl. No. 17/031,543, mailed on Jul. 18, 2022, 2 pages.

Corrected Notice of Allowance Received for U.S. Appl. No. 17/031,543, mailed on Jun. 8, 2022, 3 pages.

Corrected Notice of Allowance Received for U.S. Appl. No. 17/041,438, mailed on Dec. 1, 2023, 2 pages.

Corrected Notice of Allowance Received for U.S. Appl. No. 17/041,438, mailed on Sep. 27, 2023, 3 pages.

Corrected Notice of Allowance Received for U.S. Appl. No. 17/153,703, mailed on Jan. 19, 2023, 2 pages.

Corrected Notice of Allowance Received for U.S. Appl. No. 17/153,703, mailed on Nov. 10, 2022, 2 pages.

Corrected Notice of Allowance Received for U.S. Appl. No. 17/153,703, mailed on Sep. 14, 2022, 2 pages.

(56)

References Cited**OTHER PUBLICATIONS**

Corrected Notice of Allowance Received for U.S. Appl. No. 17/157,728, mailed on Apr. 4, 2022, 3 pages.

Corrected Notice of Allowance Received for U.S. Appl. No. 17/157,728, mailed on Apr. 14, 2022, 6 pages.

Corrected Notice of Allowance Received for U.S. Appl. No. 17/192,161, mailed on Apr. 22, 2022, 2 pages.

Corrected Notice of Allowance Received for U.S. Appl. No. 17/192,161, mailed on Mar. 23, 2022, 2 pages.

Corrected Notice of Allowance Received for U.S. Appl. No. 17/197,628, mailed on Apr. 27, 2022, 3 pages.

Corrected Notice of Allowance Received for U.S. Appl. No. 17/197,628, mailed on Jul. 29, 2022, 2 pages.

Corrected Notice of Allowance Received for U.S. Appl. No. 17/697,539, mailed on Feb. 1, 2023, 2 pages.

Corrected Notice of Allowance Received for U.S. Appl. No. 17/744,500, mailed on Jan. 12, 2024, 3 pages.

Corrected Notice of Allowance Received for U.S. Appl. No. 17/896,791, mailed on Jan. 2, 2024, 2 pages.

Corrected Notice of Allowance Received for U.S. Appl. No. 17/951,613, mailed on Jan. 2, 2024, 2 pages.

Corrected Notice of Allowance Received for U.S. Appl. No. 17/952,027, mailed on Jan. 22, 2024, 3 pages.

Corrected Notice of Allowance Received for U.S. Appl. No. 17/952,239, mailed on Jul. 12, 2023, 2 pages.

Corrected Notice of Allowance Received for U.S. Appl. No. 17/952,239, mailed on Nov. 15, 2023, 2 pages.

Cyclespeed Tours, "The Most Useful Data Fields to Display on Your Garmin", Online Available at: <https://www.youtube.com/watch?v=ANOEo50yxdg>, Nov. 16, 2016, 3 pages.

DC Rainmaker, "Garmin Fenix3 New Auto Climb Functionality", Available online at: <https://www.youtube.com/watch?v=iuavOSNpVRc>, Feb. 19, 2015, 1 page.

Decision of Appeal Received for European Patent Application No. 15771747.1, mailed on Dec. 14, 2021, 21 pages.

Decision on Appeal Received for Korean Patent Application No. 10-2019-7025538, mailed on Feb. 24, 2021, 20 pages.

Decision on Appeal Received for U.S. Appl. No. 16/584,783, mailed on Oct. 14, 2021, 12 pages.

Decision to Grant Received for Danish Patent Application No. PA201670656, mailed on Jun. 21, 2021, 2 pages.

Decision to Grant Received for Danish Patent Application No. PA201870379, mailed on Jul. 5, 2019, 2 pages.

Decision to Grant Received for Danish Patent Application No. PA202070614, mailed on Nov. 10, 2022, 2 pages.

Decision to Grant Received for Danish Patent Application No. PA202070615, mailed on Jul. 29, 2022, 2 pages.

Decision to Grant Received for Danish Patent Application No. PA202070815, mailed on Dec. 23, 2022, 1 page.

Decision to Grant Received for European Patent Application No. 09756118.7, mailed on Jul. 13, 2017, 2 pages.

Decision to Grant Received for European Patent Application No. 11178259.5, mailed on Apr. 4, 2019, 3 pages.

Decision to Grant Received for European Patent Application No. 16837432.0, mailed on Dec. 21, 2023, 2 pages.

Decision to Grant Received for European Patent Application No. 17180535.1, mailed on Feb. 4, 2021, 2 pages.

Decision to Grant Received for European Patent Application No. 18727543.3, mailed on Aug. 18, 2023, 2 pages.

Decision to Grant Received for European Patent Application No. 19721883.7, mailed on Aug. 31, 2023, 4 pages.

Decision to Grant Received for European Patent Application No. 20182116.2, mailed on Mar. 23, 2023, 3 pages.

Decision to Grant Received for European Patent Application No. 20203526.7, mailed on Jun. 22, 2023, 4 pages.

Decision to Grant Received for German Patent Application No. 112015002326.7, mailed on Jun. 15, 2021, 10 pages.

Decision to Grant Received for German Patent Application No. 112015007285.3, mailed on Jul. 25, 2023, 11 pages.

Decision to Grant Received for Japanese Patent Application No. 2009-526943, mailed on Dec. 2, 2011, 3 pages.

Decision to Grant Received for the European Patent Application No. 07814633.9, mailed on Sep. 2, 2010, 3 pages.

Decision to Grant Received for the European Patent Application No. 10172417.7, mailed on Nov. 14, 2013, 3 pages.

Decision to Grant Received for the European Patent Application No. 11178257.9, mailed on Jun. 20, 2013, 3 pages.

Decision to Refuse Received for European Patent Application No. 13811085.3, mailed on Sep. 11, 2018, 21 pages.

Decision to Refuse Received for European Patent Application No. 15771747.1, mailed on Aug. 10, 2018, 22 pages.

Decision to Refuse Received for European Patent Application No. 17810749.6, mailed on Jan. 29, 2021, 24 pages.

Decision to Refuse Received for European Patent Application No. 18154145.9, mailed on Feb. 17, 2021, 20 pages.

Decision to Refuse Received for European Patent Application No. 18197554.1, mailed on Mar. 21, 2023, 17 pages.

Decision to Refuse Received for European Patent Application No. 20721342.2, mailed on Nov. 10, 2022, 14 pages.

Decision to Refuse Received for European Patent Application No. 20729331.7, mailed on Oct. 19, 2023, 28 pages.

Decision to Refuse Received for European Patent Application No. 21159939.4, mailed on Nov. 29, 2023, 12 pages.

Dicristina, John, "Fitness Monitoring Equipment Goes Wireless", Frontier Technology, China Academic Journal Electronic Publishing House, Online Available at: <http://www.cnki.net>, Dec. 2012, pp. 44-45.

dwProgressBar v2: "Stepping and Events, davidwalsh.name/dwprogressbar-2-stepping-events-mootools-progress-bar", retrieved from the Wayback Machine, Aug. 31, 2008, 4 pages.

Ed Bott, "Chapter 14. Playing and Recording Digital Music", Special Edition Using Microsoft Windows Millennium Edition, Nov. 2000, pp. 329-353.

European Search Report Received for European Patent Application No. 20182116.2, mailed on Oct. 21, 2020, 4 pages.

European Search Report Received for European Patent Application No. 21165295.3, mailed on Jun. 18, 2021, 4 pages.

European Search Report Received for European Patent Application No. 21168916.1, mailed on Jul. 14, 2021, 5 pages.

European Search Report Received for the European Application No. 11178259.5, mailed on Oct. 31, 2011, 8 pages.

European Search Report Received for the European Patent Application No. 10172417.7, mailed on Jan. 7, 2011, 4 pages.

Evergreen et al., "Bar Chart", Better Evaluation, Available Online at: <https://www.betterevaluation.org/en/evaluation-options/BarChart>, Oct. 31, 2014, 8 pages.

Examiner-Initiated Interview Received for U.S. Appl. No. 17/896,791, mailed on Sep. 1, 2023, 2 pages.

Examiner's Answer to Appeal Brief Received for U.S. Appl. No. 16/584,783, mailed on Feb. 17, 2021, 9 pages.

Examiner's Pre-Review Report Received for Japanese Patent Application No. 2018-138559, mailed on Jul. 29, 2020, 6 pages.

Ex-Parte Quayle Action Received for U.S. Appl. No. 12/567,570, mailed on Oct. 3, 2012, 6 pages.

Extended European Search Report Received for European Patent Application No. 11178257.9, mailed on Oct. 31, 2011, 5 pages.

Extended European Search Report Received for European Patent Application No. 16837432.0, mailed on Mar. 11, 2019, 10 pages.

Extended European Search Report Received for European Patent Application No. 18154145.9, mailed on Mar. 2, 2018, 8 pages.

Extended European Search Report Received for European Patent Application No. 18197554.1, mailed on Jun. 3, 2019, 11 pages.

Extended European Search Report Received for European Patent Application No. 20203526.7, mailed on Jan. 29, 2021, 13 pages.

Extended European Search Report Received for European Patent Application No. 21159939.4, mailed on Sep. 28, 2021, 13 pages.

Extended European Search Report Received for European Patent Application No. 22194355.8, mailed on Dec. 23, 2022, 10 pages.

Extended European Search Report Received for European Patent Application No. 23150297.2, mailed on Mar. 28, 2023, 8 pages.

Extended European Search Report Received for European Patent Application No. 23153898.4, mailed on May 4, 2023, 11 pages.

(56)

References Cited**OTHER PUBLICATIONS**

Extended European Search Report Received for European Patent Application No. 23153899.2, mailed on May 4, 2023, 10 pages.
 Extended European Search Report Received for European Patent Application No. 23153900.8, mailed on May 4, 2023, 10 pages.
 Extended European Search Report Received for European Patent Application No. 23189089.8, mailed on Nov. 23, 2023, 11 pages.
 Extended European Search Report Received for European Patent Application No. 17180535.1, mailed on Oct. 30, 2017, 9 pages.
 Final Office Action Received for U.S. Appl. No. 16/994,352, mailed on Dec. 6, 2021, 14 pages.
 Final Office Action Received for U.S. Appl. No. 10/497,076 mailed on February 10, 2012, 25 pages.
 Final Office Action Received for U.S. Appl. No. 10/497,076, mailed on Apr. 26, 2013, 30 pages.
 Final Office Action Received for U.S. Appl. No. 10/497,076, mailed on Feb. 2, 2011, 22 pages.
 Final Office Action Received for U.S. Appl. No. 10/497,076, mailed on Jun. 12, 2008, 31 pages.
 Final Office Action Received for U.S. Appl. No. 10/497,076, mailed on Oct. 6, 2009, 29 pages.
 Final Office Action Received for U.S. Appl. No. 12/205,847, mailed on Apr. 25, 2012, 42 pages.
 Final Office Action Received for U.S. Appl. No. 12/567,405, mailed on Dec. 17, 2012, 19 pages.
 Final Office Action Received for U.S. Appl. No. 12/567,553, mailed on Mar. 12, 2012, 15 pages.
 Final Office Action Received for U.S. Appl. No. 14/732,773, mailed on Jul. 13, 2018, 48 pages.
 Final Office Action Received for U.S. Appl. No. 14/732,773, mailed on Jun. 21, 2019, 32 pages.
 Final Office Action Received for U.S. Appl. No. 14/839,922, mailed on Dec. 14, 2016, 22 pages.
 Final Office Action Received for U.S. Appl. No. 15/281,524, mailed on Dec. 27, 2018, 6 pages.
 Final Office Action Received for U.S. Appl. No. 15/608,848, mailed on Aug. 21, 2020, 15 pages.
 Final Office Action Received for U.S. Appl. No. 15/608,848, mailed on Jun. 26, 2019, 27 pages.
 Final Office Action Received for U.S. Appl. No. 15/627,069, mailed on Mar. 2, 2020, 22 pages.
 Final Office Action Received for U.S. Appl. No. 15/627,069, mailed on Oct. 20, 2020, 25 pages.
 Final Office Action Received for U.S. Appl. No. 15/705,849, mailed on May 1, 2020, 17 pages.
 Final Office Action Received for U.S. Appl. No. 15/925,652, mailed on Aug. 1, 2019, 30 pages.
 Final Office Action Received for U.S. Appl. No. 16/138,809, mailed on Aug. 27, 2020, 24 pages.
 Final Office Action Received for U.S. Appl. No. 16/144,735, mailed on May 4, 2020, 12 pages.
 Final Office Action Received for U.S. Appl. No. 16/144,753, mailed on Sep. 22, 2020, 9 pages.
 Final Office Action Received for U.S. Appl. No. 16/144,849, mailed on Jun. 7, 2019, 29 pages.
 Final Office Action Received for U.S. Appl. No. 16/144,864, mailed on May 17, 2019, 24 pages.
 Final Office Action Received for U.S. Appl. No. 16/144,864, mailed on May 28, 2020, 29 pages.
 Final Office Action Received for U.S. Appl. No. 16/377,892, mailed on Jan. 28, 2021, 11 pages.
 Final Office Action Received for U.S. Appl. No. 16/378,136, mailed on Jan. 28, 2021, 9 pages.
 Final Office Action Received for U.S. Appl. No. 16/418,786, mailed on Jan. 13, 2021, 14 pages.
 Final Office Action Received for U.S. Appl. No. 16/584,783, mailed on May 19, 2020, 19 pages.
 Final Office Action Received for U.S. Appl. No. 16/820,383, mailed on Jun. 22, 2022, 21 pages.

Final Office Action Received for U.S. Appl. No. 16/894,309, mailed on Feb. 24, 2021, 30 pages.
 Final Office Action Received for U.S. Appl. No. 17/030,318, mailed on Nov. 28, 2022, 13 pages.
 Final Office Action Received for U.S. Appl. No. 17/030,318, mailed on Sep. 30, 2021, 28 pages.
 Final Office Action Received for U.S. Appl. No. 17/030,321, mailed on Apr. 2, 2021, 28 pages.
 Final Office Action Received for U.S. Appl. No. 17/031,854, mailed on Feb. 23, 2023, 19 pages.
 Final Office Action Received for U.S. Appl. No. 17/031,854, mailed on Jun. 10, 2022, 15 pages.
 Final Office Action Received for U.S. Appl. No. 17/031,859, mailed on Apr. 16, 2021, 14 pages.
 Final Office Action Received for U.S. Appl. No. 17/031,859, mailed on Feb. 8, 2023, 15 pages.
 Final Office Action Received for U.S. Appl. No. 17/031,859, mailed on Jun. 10, 2022, 13 pages.
 Final Office Action Received for U.S. Appl. No. 17/031,859, mailed on Nov. 13, 2023, 15 pages.
 Final Office Action Received for U.S. Appl. No. 17/031,874, mailed on Apr. 16, 2021, 17 pages.
 Final Office Action Received for U.S. Appl. No. 17/031,874, mailed on Jun. 2, 2022, 19 pages.
 Final Office Action Received for U.S. Appl. No. 17/031,874, mailed on Mar. 17, 2023, 24 pages.
 Final Office Action Received for U.S. Appl. No. 17/192,161, mailed on Aug. 16, 2021, 22 pages.
 Final Office Action Received for U.S. Appl. No. 17/192,161, mailed on Oct. 18, 2021, 22 pages.
 Final Office Action Received for U.S. Appl. No. 17/381,570, mailed on Feb. 10, 2023, 22 pages.
 Final Office Action Received for U.S. Appl. No. 17/381,570, mailed on Jul. 20, 2022, 22 pages.
 Final Office Action Received for U.S. Appl. No. 17/516,537, mailed on Oct. 11, 2022, 9 pages.
 Final Office Action Received for U.S. Appl. No. 17/591,184, mailed on Dec. 23, 2022, 10 pages.
 Final Office Action Received for U.S. Appl. No. 17/591,184, mailed on Sep. 22, 2023, 19 pages.
 Final Office Action Received for U.S. Appl. No. 17/735,395, mailed on Dec. 7, 2023, 29 pages.
 Final Office Action Received for U.S. Appl. No. 17/735,395, mailed on May 17, 2023, 31 pages.
 Final Office Action Received for U.S. Appl. No. 17/744,500, mailed on Sep. 19, 2023, 35 pages.
 Final Office Action Received for U.S. Appl. No. 17/892,534, mailed on Nov. 9, 2023, 17 pages.
 Final Office Action Received for U.S. Appl. No. 17/951,624, mailed on Jan. 25, 2024, 48 pages.
 Final Office Action Received for U.S. Appl. No. 17/951,875, mailed on May 30, 2023, 12 pages.
 Final Office Action Received for U.S. Appl. No. 17/951,945, mailed on Dec. 7, 2023, 20 pages.
 Final Office Action Received for U.S. Appl. No. 17/951,945, mailed on May 18, 2023, 18 pages.
 Final Office Action Received for U.S. Appl. No. 17/952,027, mailed on Aug. 21, 2023, 47 pages.
 Final Office Action Received for U.S. Appl. No. 17/952,133, mailed on Sep. 26, 2023, 20 pages.
 Final Office Action Received for U.S. Appl. No. 17/952,233, mailed on Jun. 26, 2023, 18 pages.
 Final Office Action Received for U.S. Appl. No. 18/117,998, mailed on Dec. 28, 2023, 12 pages.
 Fono et al., "EyeWindows: Evaluation of Eye-Controlled Zooming Windows for Focus Selection", CHI 2005, Conference Proceedings, Conference on Human Factors in Computing Systems, Apr. 2-7, 2005, pp. 151-160.
 Garmin, "Edge 520 Plus Owner's Manual", Online Available at: https://www8.garmin.com/manuals/webhelp/edge520plus/EN-US/Edge_520_Plus_OM_EN-US.pdf, 2018, 30 pages.

(56)

References Cited**OTHER PUBLICATIONS**

Garmin, "Fenix 5x Owner's Manual", Online Available at :—https://web.archive.org/web/20180127170640/https://static.garmin.com/pumac/fenix5x_OM_EN.pdf, Jan. 27, 2018, 42 pages.

GPSCITY, "Garmin Connect 2.0 Overview with GPS City", Available online at: https://www.youtube.com/watch?v=EJ6U10y_8y0, Feb. 28, 2014, 8 pages.

GPSCITY, "Garmin Connect Mobile App iOS Overview with GPS City", Available on: <https://www.youtube.com/watch?v=rD-KPOJmOA>, 2014, 9 pages.

Hamilton, Jim, "Peloton Tips", Online available on :—<https://www.youtube.com/watch?v=OneXtBokaD4>, Oct. 22, 2015, 3 pages.

Heinrich, Peter, "More Player Engagement Potential: GameCircle Now Rewards Player Experience across Games", Available online at: <https://www.developer.amazon.com/es-mx/blogs/home/tag/badges>, Apr. 11, 2014, 9 pages.

Helm, Josh, "Microsoft® Windows Media™ Player Version 7—New features and Walk-through", Jul. 2000, 20 pages.

Hinckley et al., "Sensing Techniques for Mobile Interaction", Symposium on User Interface Software and Technology, CHI Letters, vol. 2, No. 2, Nov. 2000, pp. 91-100.

Intention to Grant Received for Danish Patent Application No. PA201570668, mailed on Mar. 27, 2017, 2 pages.

Intention to Grant Received for Danish Patent Application No. PA201670656, mailed on Jan. 18, 2021, 2 pages.

Intention to Grant Received for Danish Patent Application No. PA201870379, mailed on May 2, 2019, 2 pages.

Intention to Grant Received for Danish Patent Application No. PA202070614, mailed on Aug. 8, 2022, 2 pages.

Intention to Grant Received for Danish Patent Application No. PA202070615, mailed on Jan. 27, 2022, 2 pages.

Intention to Grant Received for Danish Patent Application No. PA202070815, mailed on Sep. 13, 2022, 2 pages.

Intention to Grant Received for European Patent Application No. 09756118.7, mailed on Mar. 2, 2017, 8 Pages.

Intention to Grant Received for European Patent Application No. 10172417.7, mailed on Jul. 9, 2013, 10 pages.

Intention to Grant Received for European Patent Application No. 11178257.9, mailed on Jan. 30, 2013, 9 pages.

Intention to Grant Received for European Patent Application No. 11178259.5, mailed on Nov. 8, 2018, 16 pages.

Intention to Grant Received for European Patent Application No. 16837432.0, mailed on Apr. 14, 2023, 8 pages.

Intention to Grant Received for European Patent Application No. 16837432.0, mailed on Sep. 7, 2023, 9 pages.

Intention to Grant Received for European Patent Application No. 17180535.1, mailed on Sep. 24, 2020, 7 pages.

Intention to Grant Received for European Patent Application No. 18727543.3, mailed on Apr. 12, 2023, 9 pages.

Intention to Grant Received for European Patent Application No. 19721883.7, mailed on May 11, 2023, 9 pages.

Intention to Grant Received for European Patent Application No. 20182116.2, mailed on Jun. 2, 2022, 8 pages.

Intention to Grant Received for European Patent Application No. 20182116.2, mailed on Nov. 11, 2022, 9 pages.

Intention to Grant Received for European Patent Application No. 20203526.7, mailed on Feb. 10, 2023, 9 pages.

Intention to Grant Received for European Patent Application No. 21714460.9, mailed on Feb. 8, 2024, 12 pages.

Intention to Grant Received for the European Patent Application No. 07814633.9, mailed on Mar. 19, 2010, 4 pages.

International Preliminary Examination Report on Patentability Received for PCT Patent Application No. PCT/US2002/000484, mailed on Aug. 4, 2003, 7 pages.

International Preliminary Report on Patentability Received for PCT Patent Application No. PCT/US2020/035199, mailed on Dec. 16, 2021, 14 pages.

International Preliminary Report on Patentability Received for PCT Patent Application No. PCT/US2007/077441, issued on Mar. 10, 2009, 9 pages.

International Preliminary Report on Patentability Received for PCT Patent Application No. PCT/US2009/057899, mailed on Apr. 5, 2012, 14 pages.

International Preliminary Report on Patentability Received for PCT Patent Application No. PCT/US2013/073195, mailed on Jun. 16, 2016, 10 pages.

International Preliminary Report on Patentability Received for PCT Patent Application No. PCT/US2015/047282, mailed on Mar. 16, 2017, 26 pages.

International Preliminary Report on Patentability Received for PCT Patent Application No. PCT/US2016/037686, mailed on Mar. 1, 2018, 12 pages.

International Preliminary Report on Patentability Received for PCT Patent Application No. PCT/US2017/035554, mailed on Dec. 20, 2018, 39 pages.

International Preliminary Report on Patentability Received for PCT Patent Application No. PCT/US2018/031662, mailed on Nov. 28, 2019, 12 pages.

International Preliminary Report on Patentability Received for PCT Patent Application No. PCT/US2019/024570, mailed on Nov. 19, 2020, 10 pages.

International Preliminary Report on Patentability Received for PCT Patent Application No. PCT/US2020/025997, mailed on Nov. 18, 2021, 10 pages.

International Preliminary Report on Patentability Received for PCT Patent Application No. PCT/US2020/031442, mailed on Nov. 18, 2021, 21 pages.

International Preliminary Report on Patentability Received for PCT Patent Application No. PCT/US2021/017736, mailed on Aug. 25, 2022, 19 pages.

International Preliminary Report on Patentability Received for PCT Patent Application No. PCT/US2022/029297, mailed on Nov. 30, 2023, 10 pages.

International Search Report and Written Opinion Received for PCT Patent Application No. PCT/US2002/000484, mailed on Jul. 11, 2002, 1 page.

International Search Report and Written Opinion Received for PCT Patent Application No. PCT/US2009/057899, mailed on Jun. 14, 2010, 19 pages.

International Search Report and Written Opinion Received for PCT Patent Application No. PCT/US2015/047282, mailed on May 9, 2016, 33 pages.

International Search Report and Written Opinion Received for PCT Patent Application No. PCT/US2016/037686, mailed on Sep. 9, 2016, 19 pages.

International Search Report and Written Opinion Received for PCT Patent Application No. PCT/US2017/035554, mailed on Sep. 22, 2017, 42 pages.

International Search Report and Written Opinion Received for PCT Patent Application No. PCT/US2018/031662, mailed on Sep. 27, 2018, 17 pages.

International Search Report and Written Opinion Received for PCT Patent Application No. PCT/US2019/024570, mailed on Aug. 8, 2019, 18 pages.

International Search Report and written Opinion Received for PCT Patent Application No. PCT/US2020/025997, mailed on Jul. 1, 2020, 16 pages.

International Search Report and Written Opinion Received for PCT Patent Application No. PCT/US2020/025997, mailed on Jul. 14, 2020, 15 pages.

International Search Report and Written Opinion Received for PCT Patent Application No. PCT/US2020/031442, mailed on Oct. 30, 2020, 28 pages.

International Search Report and Written Opinion Received for PCT Patent Application No. PCT/US2020/035199, mailed on Oct. 30, 2020, 20 pages.

International Search Report and Written Opinion Received for PCT Patent Application No. PCT/US2021/017736, mailed on Sep. 2, 2021, 25 pages.

(56)

References Cited**OTHER PUBLICATIONS**

International Search Report and Written Opinion Received for PCT Patent Application No. PCT/US2022/029297, mailed on Aug. 11, 2022, 13 pages.

International Search Report and Written Opinion Received for PCT Patent Application No. PCT/US2022/044637, mailed on Mar. 15, 2023, 19 pages.

International Search Report and Written Opinion Received for PCT Patent Application No. PCT/US2023/024104, mailed on Oct. 18, 2023, 18 pages.

International Search Report and Written Opinion Received for PCT Patent Application No. PCT/US2023/024185, mailed on Sep. 18, 2023, 12 pages.

International Search Report and Written Opinion, Received for PCT Patent Application No. PCT/US2007/077441, mailed on May 8, 2008, 13 pages.

International Search Report Received for PCT Patent Application No. PCT/US2013/073195, mailed on Jun. 23, 2014, 3 pages.

International Written Opinion Received for PCT Patent Application No. PCT/US2013/073195, mailed on Jun. 23, 2014, 8 pages.

Invitation to Pay Addition Fees and Partial International Search Report Received for PCT Patent Application No. PCT/US2018/031662, mailed on Jul. 16, 2018, 13 pages.

Invitation to Pay Additional Fees and Partial International Search Report Received for PCT Patent Application No. PCT/US2022/044637, mailed on Jan. 20, 2023, 12 pages.

Invitation to Pay Additional Fees Received for PCT Patent Application No. PCT/US2007/077441, mailed on Jan. 28, 2008, 5 pages.

Invitation to Pay Additional Fees Received for PCT Patent Application No. PCT/US2015/047282, mailed on Dec. 22, 2015, 7 pages.

Invitation to Pay Additional Fees Received for PCT Patent Application No. PCT/US2017/035554, mailed on Jul. 20, 2017, 2 pages.

Invitation to Pay Additional Fees Received for PCT Patent Application No. PCT/US2020/031442, mailed on Aug. 25, 2020, 22 pages.

Invitation to Pay Additional Fees Received for PCT Patent Application No. PCT/US2020/035199, mailed on Sep. 8, 2020, 12 pages.

Invitation to Pay Additional Fees Received for PCT Patent Application No. PCT/US2021/017736, mailed on Jun. 15, 2021, 14 pages.

Invitation to Pay Search Fees Received for European Patent Application No. 21714460.9, mailed on Aug. 8, 2023, 3 pages.

JenbsJourney, "Wondering About a Fitbit?", Available at: <https://jenbsjourney.blogspot.kr/2013/08/wondering-about-fitbit.html>, Aug. 6, 2013, 12 pages.

Jobs Steve, "iPhone Introduction in 2007 Complete)", available at <<https://www.youtube.com/watch?v=9hUkxyE2Ns8>>, Jan. 10, 2013, 3 pages.

Karlson et al., "AppLens and LaunchTile: Two Designs for One-Handed Thumb Use on Small Devices", CHI 2005, Papers: Small Devices 1, Apr. 2-7, 2005, pp. 201-210.

Li-Yu et al., "Influence of exercise prescription on body composition of college students", Clinical Rehabilitation in China, vol. 9 Issue 24, Jun. 28, 2005, pp. 147-149.

Microsoft Windows, "Microsoft Windows (Copyright 2009)", 2 pages.

Minutes of Oral Proceedings Received for European Patent Application No. 11178259.5, mailed on Nov. 2, 2018, 9 pages.

Minutes of Oral Proceedings Received for European Patent Application No. 13811085.3, mailed on Sep. 11, 2018, 3 pages.

Minutes of Oral Proceedings Received for European Patent Application No. 15771747.1, mailed on Aug. 10, 2018, 11 pages.

Minutes of Oral Proceedings Received for European Patent Application No. 20721342.2, mailed on Nov. 8, 2022, 5 pages.

Minutes of the Oral Proceedings Received for European Patent Application No. 15771747.1, mailed on Dec. 1, 2021, 4 pages.

Minutes of the Oral Proceedings Received for European Patent Application No. 17810749.6, mailed on Jan. 26, 2021, 8 pages.

Minutes of the Oral Proceedings Received for European Patent Application No. 18154145.9, mailed on Feb. 12, 2021, 8 pages.

Minutes of the Oral Proceedings Received for European Patent Application No. 18197554.1, mailed on Feb. 22, 2023, 9 pages.

Minutes of the Oral Proceedings Received for European Patent Application No. 20182116.2, mailed on May 24, 2022, 7 pages.

Minutes of the Oral Proceedings Received for European Patent Application No. 21159939.4, mailed on Nov. 28, 2023, 5 pages.

Minutes of the Oral Proceedings Received for European Patent Application No. 21168916.1, mailed on Jan. 3, 2024, 5 pages.

Nakasuji, Yoshito, "Apple Watch", First Edition 1st Printing, Japan, Incorporated Company Technical Hyoronsha, Jun. 15, 2015, 4 pages.

Non-Final Office Action Received for U.S. Appl. No. 14/839,916, mailed on Feb. 4, 2016, 19 pages.

Non-Final Office Action Received for U.S. Appl. No. 14/839,922, mailed on Feb. 25, 2016, 20 pages.

Non-Final Office Action Received for U.S. Appl. No. 16/144,864, mailed on Dec. 18, 2018, 19 pages.

Non-Final Office Action Received for U.S. Appl. No. 16/994,352, mailed on Jul. 30, 2021, 11 pages.

Non-Final Office Action Received for U.S. Appl. No. 09/757,000, mailed on Jan. 30, 2003, 11 pages.

Non-Final Office Action Received for U.S. Appl. No. 09/757,000, mailed on Jun. 19, 2003, 11 Pages.

Non-Final Office Action Received for U.S. Appl. No. 10/497,076, mailed on Jan. 8, 2009, 29 pages.

Non-Final Office Action Received for U.S. Appl. No. 10/497,076, mailed on May 13, 2010, 24 pages.

Non-Final Office Action Received for U.S. Appl. No. 10/497,076, mailed on Oct. 3, 2012, 24 pages.

Non-Final Office Action Received for U.S. Appl. No. 10/497,076, mailed on Oct. 13, 2011, 24 pages.

Non-Final Office Action Received for U.S. Appl. No. 10/497,076, mailed on Sep. 13, 2007, 19 pages.

Non-Final Office Action Received for U.S. Appl. No. 11/848,210, mailed on Jun. 30, 2011, 8 pages.

Non-Final Office Action Received for U.S. Appl. No. 12/205,847, mailed on Oct. 3, 2011, 59 pages.

Non-Final Office Action Received for U.S. Appl. No. 12/566,994, mailed on Dec. 13, 2013, 10 pages.

Non-Final Office Action Received for U.S. Appl. No. 12/566,994, mailed on Jan. 9, 2013, 15 pages.

Non-Final Office Action Received for U.S. Appl. No. 12/566,994, mailed on Jun. 13, 2014, 12 pages.

Non-Final Office Action Received for U.S. Appl. No. 12/567,405, mailed on Jan. 16, 2014, 19 pages.

Non-Final Office Action Received for U.S. Appl. No. 12/567,405, mailed on May 17, 2012, 14 pages.

Non-Final Office Action Received for U.S. Appl. No. 12/567,460, mailed on Aug. 4, 2011, 13 pages.

Non-Final Office Action Received for U.S. Appl. No. 12/567,553, mailed on Sep. 16, 2011, 11 pages.

Non-Final Office Action Received for U.S. Appl. No. 12/849,767, mailed on Jul. 9, 2012, 16 pages.

Non-Final Office Action Received for U.S. Appl. No. 13/361,912, mailed on Mar. 22, 2012, 8 pages.

Non-Final Office Action Received for U.S. Appl. No. 13/909,001, mailed on Sep. 26, 2013, 7 pages.

Non-Final Office Action Received for U.S. Appl. No. 13/909,002, mailed on Jun. 23, 2015, 6 pages.

Non-Final Office Action Received for U.S. Appl. No. 14/732,773, mailed on Feb. 8, 2019, 32 pages.

Non-Final Office Action Received for U.S. Appl. No. 14/732,773, mailed on Jan. 19, 2018, 45 pages.

Non-Final Office Action Received for U.S. Appl. No. 14/839,916, mailed on May 1, 2017, 18 pages.

Non-Final Office Action Received for U.S. Appl. No. 14/839,922, mailed on Aug. 17, 2016, 25 pages.

Non-Final Office Action Received for U.S. Appl. No. 15/088,450, mailed on Jul. 23, 2018, 12 pages.

Non-Final Office Action Received for U.S. Appl. No. 15/183,663, mailed on Jul. 9, 2018, 13 pages.

Non-Final Office Action Received for U.S. Appl. No. 15/281,524, mailed on Jun. 19, 2018, 23 pages.

(56)

References Cited**OTHER PUBLICATIONS**

Non-Final Office Action Received for U.S. Appl. No. 15/600,243, mailed on Jun. 27, 2019, 17 Pages.
Non-Final Office Action Received for U.S. Appl. No. 15/608,848, mailed on Feb. 6, 2020, 12 pages.
Non-Final Office Action Received for U.S. Appl. No. 15/608,848, mailed on Feb. 12, 2021, 14 pages.
Non-Final Office Action Received for U.S. Appl. No. 15/608,848, mailed on Nov. 2, 2018, 21 pages.
Non-Final Office Action Received for U.S. Appl. No. 15/627,069, mailed on Jun. 21, 2019, 22 pages.
Non-Final Office Action Received for U.S. Appl. No. 15/627,069, mailed on May 26, 2020, 25 pages.
Non-Final Office Action Received for U.S. Appl. No. 15/705,849, mailed on Nov. 12, 2019, 15 pages.
Non-Final Office Action Received for U.S. Appl. No. 15/925,652, mailed on Apr. 5, 2019, 28 pages.
Non-Final Office Action Received for U.S. Appl. No. 15/925,652, mailed on Aug. 7, 2020, 39 pages.
Non-Final Office Action Received for U.S. Appl. No. 16/138,809, mailed on Feb. 28, 2020, 22 pages.
Non-Final Office Action Received for U.S. Appl. No. 16/144,735, mailed on Feb. 19, 2020, 10 pages.
Non-Final Office Action Received for U.S. Appl. No. 16/144,753, mailed on Mar. 5, 2020, 9 pages.
Non-Final Office Action Received for U.S. Appl. No. 16/144,849, mailed on Dec. 31, 2018, 28 pages.
Non-Final Office Action Received for U.S. Appl. No. 16/144,849, mailed on Sep. 17, 2019, 9 pages.
Non-Final Office Action Received for U.S. Appl. No. 16/144,864, mailed on Jan. 31, 2020, 29 pages.
Non-Final Office Action Received for U.S. Appl. No. 16/377,892, mailed on May 21, 2020, 9 pages.
Non-Final Office Action Received for U.S. Appl. No. 16/378,136, mailed on Jun. 2, 2020, 8 pages.
Non-Final Office Action Received for U.S. Appl. No. 16/418,786, mailed on Apr. 24, 2020, 16 pages.
Non-Final Office Action Received for U.S. Appl. No. 16/418,786, mailed on Aug. 1, 2022, 18 pages.
Non-Final Office Action Received for U.S. Appl. No. 16/418,786, mailed on Mar. 28, 2022, 14 pages.
Non-Final Office Action Received for U.S. Appl. No. 16/418,786, mailed on Oct. 4, 2021, 10 pages.
Non-Final Office Action Received for U.S. Appl. No. 16/450,531, mailed on Jun. 10, 2020, 10 pages.
Non-Final Office Action Received for U.S. Appl. No. 16/584,776, mailed on Aug. 18, 2020, 36 pages.
Non-Final Office Action Received for U.S. Appl. No. 16/584,776, mailed on Feb. 13, 2020, 31 pages.
Non-Final Office Action Received for U.S. Appl. No. 16/584,783, mailed on Jan. 30, 2020, 18 pages.
Non-Final Office Action Received for U.S. Appl. No. 16/820,383, mailed on Dec. 14, 2020, 11 pages.
Non-Final Office Action Received for U.S. Appl. No. 16/820,383, mailed on Jan. 10, 2022, 18 pages.
Non-Final Office Action Received for U.S. Appl. No. 16/888,629, mailed on Mar. 31, 2021, 14 pages.
Non-Final Office Action Received for U.S. Appl. No. 16/894,309, mailed on Oct. 15, 2020, 24 pages.
Non-Final Office Action Received for U.S. Appl. No. 16/987,275, mailed on Nov. 23, 2021, 17 pages.
Non-Final Office Action Received for U.S. Appl. No. 17/030,318, mailed on Apr. 2, 2021, 28 pages.
Non-Final Office Action Received for U.S. Appl. No. 17/030,318, mailed on Dec. 3, 2020, 22 pages.
Non-Final Office Action Received for U.S. Appl. No. 17/030,318, mailed on Jun. 14, 2022, 9 pages.
Non-Final Office Action Received for U.S. Appl. No. 17/030,321, mailed on Dec. 15, 2020, 25 pages.

Non-Final Office Action Received for U.S. Appl. No. 17/030,321, mailed on Oct. 18, 2021, 28 pages.
Non-Final Office Action Received for U.S. Appl. No. 17/030,337, mailed on Jun. 14, 2022, 13 pages.
Non-Final Office Action Received for U.S. Appl. No. 17/030,340, mailed on Jun. 14, 2022, 15 pages.
Non-Final Office Action Received for U.S. Appl. No. 17/031,543, mailed on Apr. 1, 2022, 9 pages.
Non-Final Office Action Received for U.S. Appl. No. 17/031,854, mailed on Dec. 27, 2021, 13 pages.
Non-Final Office Action Received for U.S. Appl. No. 17/031,854, mailed on Oct. 18, 2023, 22 pages.
Non-Final Office Action Received for U.S. Appl. No. 17/031,854, mailed on Sep. 26, 2022, 17 pages.
Non-Final Office Action Received for U.S. Appl. No. 17/031,859, mailed on Dec. 15, 2020, 13 pages.
Non-Final Office Action Received for U.S. Appl. No. 17/031,859, mailed on Dec. 24, 2021, 16 pages.
Non-Final Office Action Received for U.S. Appl. No. 17/031,859, mailed on Jul. 10, 2023, 15 pages.
Non-Final Office Action Received for U.S. Appl. No. 17/031,859, mailed on Sep. 12, 2022, 17 pages.
Non-Final Office Action Received for U.S. Appl. No. 17/031,874, mailed on Dec. 28, 2020, 14 pages.
Non-Final Office Action Received for U.S. Appl. No. 17/031,874, mailed on Jan. 24, 2022, 18 pages.
Non-Final Office Action Received for U.S. Appl. No. 17/031,874, mailed on Oct. 4, 2022, 20 pages.
Non-Final Office Action Received for U.S. Appl. No. 17/035,367, mailed on Jun. 11, 2021, 11 pages.
Non-Final Office Action Received for U.S. Appl. No. 17/041,438, mailed on May 25, 2023, 47 pages.
Non-Final Office Action Received for U.S. Appl. No. 17/153,703, mailed on Mar. 30, 2022, 10 pages.
Non-Final Office Action Received for U.S. Appl. No. 17/157,728, mailed on Nov. 26, 2021, 18 pages.
Non-Final Office Action Received for U.S. Appl. No. 17/192,161, mailed on May 13, 2021, 28 pages.
Non-Final Office Action Received for U.S. Appl. No. 17/381,570, mailed on Apr. 1, 2022, 29 pages.
Non-Final Office Action Received for U.S. Appl. No. 17/381,570, mailed on Sep. 28, 2022, 20 pages.
Non-Final Office Action Received for U.S. Appl. No. 17/516,537, mailed on May 5, 2022, 8 pages.
Non-Final Office Action Received for U.S. Appl. No. 17/566,521, mailed on May 15, 2023, 12 pages.
Non-Final Office Action Received for U.S. Appl. No. 17/591,184, mailed on Apr. 21, 2023, 15 pages.
Non-Final Office Action Received for U.S. Appl. No. 17/591,184, mailed on Aug. 4, 2022, 18 pages.
Non-Final Office Action Received for U.S. Appl. No. 17/666,301, mailed on Feb. 16, 2023, 24 pages.
Non-Final Office Action Received for U.S. Appl. No. 17/735,395, mailed on Feb. 10, 2023, 28 pages.
Non-Final Office Action Received for U.S. Appl. No. 17/735,395, mailed on Sep. 20, 2023, 29 pages.
Non-Final Office Action Received for U.S. Appl. No. 17/744,500, mailed on Apr. 19, 2023, 30 pages.
Non-Final Office Action Received for U.S. Appl. No. 17/745,021, mailed on Feb. 6, 2023, 10 pages.
Non-Final Office Action Received for U.S. Appl. No. 17/892,534, mailed on Dec. 19, 2022, 20 pages.
Non-Final Office Action Received for U.S. Appl. No. 17/892,534, mailed on May 10, 2023, 17 pages.
Non-Final Office Action Received for U.S. Appl. No. 17/896,791, mailed on Aug. 30, 2023, 11 pages.
Non-Final Office Action Received for U.S. Appl. No. 17/951,613, mailed on Aug. 2, 2023, 42 pages.
Non-Final Office Action Received for U.S. Appl. No. 17/951,624, mailed on Sep. 19, 2023, 41 pages.
Non-Final Office Action Received for U.S. Appl. No. 17/951,875, mailed on Jan. 23, 2023, 12 pages.

(56)

References Cited**OTHER PUBLICATIONS**

Non-Final Office Action Received for U.S. Appl. No. 17/951,945, mailed on Mar. 24, 2023, 14 pages.

Non-Final Office Action Received for U.S. Appl. No. 17/951,945, mailed on Sep. 20, 2023, 19 pages.

Non-Final Office Action Received for U.S. Appl. No. 17/951,976, mailed on Aug. 3, 2023, 16 pages.

Non-Final Office Action Received for U.S. Appl. No. 17/952,027, mailed on Apr. 28, 2023, 46 pages.

Non-Final Office Action Received for U.S. Appl. No. 17/952,075, mailed on Jan. 16, 2024, 27 pages.

Non-Final Office Action Received for U.S. Appl. No. 17/952,133, mailed on Jun. 2, 2023, 28 pages.

Non-Final Office Action Received for U.S. Appl. No. 17/952,181, mailed on Aug. 7, 2023, 18 pages.

Non-Final Office Action Received for U.S. Appl. No. 17/952,233, mailed on Apr. 28, 2023, 21 pages.

Non-Final Office Action Received for U.S. Appl. No. 17/952,233, mailed on Feb. 2, 2024, 18 pages.

Non-Final Office Action Received for U.S. Appl. No. 17/952,239, mailed on Apr. 4, 2023, 45 pages.

Non-Final Office Action Received for U.S. Appl. No. 18/117,998, mailed on Oct. 10, 2023, 21 pages.

Non-Final Office Action Received for U.S. Appl. No. 18/135,056, mailed on Dec. 7, 2023, 16 pages.

Non-Final Office Action Received for U.S. Appl. No. 18/204,217, mailed on Feb. 13, 2024, 21 pages.

Non-Final Office Action Received for U.S. Appl. No. 13/666,943, mailed on Oct. 26, 2015, 12 Pages.

Notice of Acceptance Received for Australian Patent Application No. 2011265412, mailed on Nov. 12, 2014, 2 pages.

Notice of Acceptance Received for Australian Patent Application No. 2015201028, mailed on Mar. 21, 2017, 3 Pages.

Notice of Acceptance Received for Australian Patent Application No. 2015312215, mailed on Oct. 9, 2017, 3 pages.

Notice of Acceptance Received for Australian Patent Application No. 2017201548, mailed on Sep. 3, 2018, 3 pages.

Notice of Acceptance Received for Australian Patent Application No. 2017277971, mailed on Feb. 17, 2021, 3 pages.

Notice of Acceptance Received for Australian Patent Application No. 2018214074, mailed on Aug. 6, 2019, 3 pages.

Notice of Acceptance Received for Australian Patent Application No. 2018268972, mailed on Dec. 18, 2020, 3 pages.

Notice of Acceptance Received for Australian Patent Application No. 2019201583, mailed on Jul. 15, 2019, 3 pages.

Notice of Acceptance Received for Australian Patent Application No. 2019222943, mailed on May 5, 2020, 3 pages.

Notice of Acceptance Received for Australian Patent Application No. 2019250251, mailed on Feb. 18, 2021, 3 pages.

Notice of Acceptance Received for Australian Patent Application No. 2019264623, mailed on Jan. 4, 2021, 3 pages.

Notice of Acceptance Received for Australian Patent Application No. 2020204153, mailed on Jul. 6, 2020, 3 pages.

Notice of Acceptance Received for Australian Patent Application No. 2020239743, mailed on Jan. 13, 2022, 3 pages.

Notice of Acceptance Received for Australian Patent Application No. 2020239748, mailed on Mar. 7, 2022, 3 pages.

Notice of Acceptance Received for Australian Patent Application No. 2020239752, mailed on Jan. 31, 2022, 3 pages.

Notice of Acceptance Received for Australian Patent Application No. 2020256383, mailed on Aug. 3, 2021, 3 pages.

Notice of Acceptance Received for Australian Patent Application No. 2020267396, mailed on Dec. 7, 2021, 3 pages.

Notice of Acceptance Received for Australian Patent Application No. 2020288139, mailed on Feb. 2, 2023, 3 pages.

Notice of Acceptance Received for Australian Patent Application No. 2021200787, mailed on Mar. 19, 2021, 3 pages.

Notice of Acceptance Received for Australian Patent Application No. 2021201130, mailed on Mar. 28, 2022, 3 pages.

Notice of acceptance Received for Australian Patent Application No. 2021202225, mailed on Jun. 20, 2022, 3 pages.

Notice of Acceptance Received for Australian Patent Application No. 2021203636, mailed on Apr. 14, 2022, 3 pages.

Notice of Acceptance Received for Australian Patent Application No. 2021204422, mailed on Aug. 15, 2022, 3 pages.

Notice of Acceptance Received for Australian Patent Application No. 2021266294, mailed on Mar. 3, 2023, 3 pages.

Notice of Acceptance Received for Australian Patent Application No. 2022201761, mailed on Jun. 15, 2023, 3 pages.

Notice of Acceptance Received for Australian Patent Application No. 2022201810, mailed on Jun. 14, 2023, 3 pages.

Notice of Acceptance Received for Australian Patent Application No. 2022202583, mailed on Aug. 7, 2023, 3 pages.

Notice of Acceptance Received for Australian Patent Application No. 2022202977, mailed on Sep. 26, 2023, 3 pages.

Notice of Acceptance Received for Australian Patent Application No. 2022209277, mailed on Apr. 28, 2023, 3 pages.

Notice of Acceptance Received for Australian Patent Application No. 2022235614, mailed on Jul. 6, 2023, 3 pages.

Notice of Acceptance Received for Australian Patent Application No. 2022235618, mailed on Aug. 25, 2023, 3 pages.

Notice of Acceptance Received for Australian Patent Application No. 2023203050, mailed on Oct. 24, 2023, 3 pages.

Notice of Acceptance Received for Australian Patent Application No. 2023203776, mailed on Dec. 12, 2023, 3 pages.

Notice of Acceptance Received for Australian Patent Application No. 2023237163, mailed on Dec. 21, 2023, 3 pages.

Notice of Allowance Received for Canadian Patent Application No. 2,935,875, mailed on May 3, 2017, 1 page.

Notice of Allowance Received for Canadian Patent Application No. 2,984,527, mailed on Apr. 30, 2020, 1 page.

Notice of Allowance Received for Chinese Patent Application No. 201380081349.6, mailed on Dec. 17, 2021, 2 pages.

Notice of Allowance Received for Chinese Patent Application No. 201580037927.5, mailed on Oct. 17, 2019, 3 pages.

Notice of Allowance Received for Chinese Patent Application No. 201680047983.1, mailed on Apr. 28, 2021, 3 pages.

Notice of Allowance Received for Chinese Patent Application No. 201710439448.7, mailed on Jan. 26, 2021, 2 pages.

Notice of Allowance Received for Chinese Patent Application No. 201780034203.4, mailed on Jan. 17, 2022, 2 pages.

Notice of Allowance Received for Chinese Patent Application No. 201810105846.X, mailed on Feb. 18, 2020, 2 pages.

Notice of Allowance Received for Chinese Patent Application No. 201811303556.2, mailed on Jul. 28, 2023, 2 pages.

Notice of Allowance Received for Chinese Patent Application No. 201880032190.1, mailed on Oct. 7, 2023, 4 pages.

Notice of Allowance Received for Chinese Patent Application No. 201911396643.1, mailed on Jun. 15, 2023, 8 pages.

Notice of Allowance Received for Chinese Patent Application No. 201911396744.9, mailed on Aug. 3, 2023, 5 pages.

Notice of Allowance Received for Chinese Patent Application No. 201911396819.3, mailed on Aug. 3, 2023, 5 pages.

Notice of Allowance Received for Chinese Patent Application No. 201911396876.1, mailed on Sep. 6, 2023, 5 pages.

Notice of Allowance Received for Chinese Patent Application No. 201911401161.0, mailed on Apr. 24, 2023, 11 pages.

Notice of Allowance Received for Chinese Patent Application No. 201911401375.8, mailed on Nov. 26, 2023, 2 pages.

Notice of Allowance Received for Chinese Patent Application No. 202010606407.4, mailed on Jan. 24, 2022, 2 pages.

Notice of Allowance Received for Chinese Patent Application No. 202210238202.4, mailed on Jan. 13, 2023, 7 pages.

Notice of Allowance Received for Danish Patent Application No. PA201570666, mailed on Sep. 15, 2016, 1 page.

Notice of Allowance Received for Danish Patent Application No. PA201570668, mailed on Oct. 30, 2017, 2 pages.

Notice of Allowance Received for Japanese Patent Application No. 2013-140171, mailed on May 29, 2015, 4 pages.

Notice of Allowance Received for Japanese Patent Application No. 2014-259225, mailed on Feb. 27, 2017, 3 pages.

(56)

References Cited**OTHER PUBLICATIONS**

Notice of Allowance Received for Japanese Patent Application No. 2015-129152, mailed on May 8, 2017, 3 pages.
Notice of Allowance Received for Japanese Patent Application No. 2016-535045, mailed on Mar. 2, 2018, 4 pages.
Notice of Allowance Received for Japanese Patent Application No. 2016-557650, mailed on Apr. 9, 2019, 4 pages.
Notice of Allowance Received for Japanese Patent Application No. 2017-057997, mailed on Apr. 23, 2018, 4 pages.
Notice of Allowance Received for Japanese Patent Application No. 2017-132229, mailed on Jun. 25, 2018, 4 pages.
Notice of Allowance Received for Japanese Patent Application No. 2018-014096, mailed on Jan. 5, 2021, 3 pages.
Notice of Allowance Received for Japanese Patent Application No. 2018-068846, mailed on Dec. 9, 2019, 4 pages.
Notice of Allowance Received for Japanese Patent Application No. 2018-138559, mailed on Dec. 3, 2021, 3 pages.
Notice of Allowance Received for Japanese Patent Application No. 2018-184532, mailed on Jan. 17, 2022, 4 pages.
Notice of Allowance Received for Japanese Patent Application No. 2019-044107, mailed on Jul. 11, 2022, 31 pages.
Notice of Allowance Received for Japanese Patent Application No. 2019-162293, mailed on Apr. 9, 2021, 4 pages.
Notice of Allowance Received for Japanese Patent Application No. 2019-563407, mailed on Aug. 20, 2021, 4 pages.
Notice of Allowance Received for Japanese Patent Application No. 2020-000492, mailed on Jul. 16, 2021, 4 pages.
Notice of Allowance Received for Japanese Patent Application No. 2020-079486, mailed on Oct. 21, 2022, 4 pages.
Notice of Allowance Received for Japanese Patent Application No. 2020-104679, mailed on Jan. 4, 2021, 4 pages.
Notice of Allowance Received for Japanese Patent Application No. 2020-115940, mailed on Oct. 22, 2021, 4 pages.
Notice of Allowance Received for Japanese Patent Application No. 2020-160052, mailed on Jun. 3, 2022, 4 pages.
Notice of Allowance Received for Japanese Patent Application No. 2020-160053, mailed on Jan. 16, 2023, 4 pages.
Notice of Allowance Received for Japanese Patent Application No. 2020-160054, mailed on Apr. 4, 2022, 4 pages.
Notice of Allowance Received for Japanese Patent Application No. 2021-131726, mailed on Mar. 17, 2023, 4 pages.
Notice of Allowance Received for Japanese Patent Application No. 2021-153558, mailed on Jun. 9, 2023, 4 pages.
Notice of Allowance Received for Japanese Patent Application No. 2021-188824, mailed on Feb. 13, 2023, 4 pages.
Notice of Allowance Received for Japanese Patent Application No. 2021-566100, mailed on Jan. 27, 2023, 4 pages.
Notice of Allowance Received for Japanese Patent Application No. 2021-571468, mailed on May 19, 2023, 4 pages.
Notice of Allowance Received for Japanese Patent Application No. 2022-022159, mailed on Aug. 10, 2023, 4 pages.
Notice of Allowance Received for Japanese Patent Application No. 2022-076722, mailed on Jul. 28, 2023, 4 pages.
Notice of Allowance Received for Japanese Patent Application No. 2022-107902, mailed on Aug. 26, 2022, 4 pages.
Notice of Allowance Received for Japanese Patent Application No. 2022-107903, mailed on Sep. 1, 2023, 4 pages.
Notice of Allowance Received for Korean Patent Application No. 10-2016-7014577, mailed on May 30, 2019, 5 pages.
Notice of Allowance Received for Korean Patent Application No. 10-2016-7033638, issued on May 31, 2017, 5 pages.
Notice of Allowance Received for Korean Patent Application No. 10-2019-7025538, mailed on Mar. 10, 2021, 5 pages.
Notice of Allowance Received for Korean Patent Application No. 10-2019-7025781, mailed on Jun. 29, 2021, 5 pages.
Notice of Allowance Received for Korean Patent Application No. 10-2019-7033834, mailed on Jul. 3, 2021, 4 pages.
Notice of Allowance Received for Korean Patent Application No. 10-2020-0123815, mailed on Aug. 26, 2022, 7 pages.

Notice of Allowance Received for Korean Patent Application No. 10-2020-0123821, mailed on Mar. 28, 2023, 8 pages.
Notice of Allowance Received for Korean Patent Application No. 10-2020-0123840, mailed on May 26, 2023, 9 pages.
Notice of Allowance Received for Korean Patent Application No. 10-2020-7026035, mailed on Aug. 23, 2021, 4 pages.
Notice of Allowance Received for Korean Patent Application No. 10-2021-7026284, mailed on Jul. 28, 2022, 6 pages.
Notice of Allowance Received for Korean Patent Application No. 10-2021-7031939, mailed on Apr. 5, 2022, 4 pages.
Notice of Allowance Received for Korean Patent Application No. 10-2021-7036310, mailed on Apr. 26, 2022, 5 pages.
Notice of Allowance Received for Korean Patent Application No. 10-2021-7038005, mailed on Dec. 14, 2021, 4 pages.
Notice of Allowance Received for Korean Patent Application No. 10-2022-0061486, mailed on Nov. 22, 2022, 7 pages.
Notice of Allowance Received for Korean Patent Application No. 10-2022-7008569, mailed on May 19, 2022, 5 pages.
Notice of Allowance Received for Korean Patent Application No. 10-2022-7017918, mailed on Jun. 13, 2022, 6 pages.
Notice of Allowance Received for Korean Patent Application No. 10-2022-7031866, mailed on May 1, 2023, 7 pages.
Notice of Allowance Received for Korean Patent Application No. 10-2022-7036278, mailed on Jan. 30, 2024, 8 pages.
Notice of Allowance Received for Korean Patent Application No. 10-2023-0023706, mailed on Mar. 27, 2023, 8 pages.
Notice of Allowance Received for Taiwanese Patent Application No. 104128685, mailed on May 3, 2017, 3 pages.
Notice of Allowance Received for the Canadian Patent Application No. 2,853,273, mailed on Jan. 12, 2016, 1 page.
Notice of Allowance Received for U.S. Appl. No. 12/205,847, mailed on Aug. 20, 2012, 13 pages.
Notice of Allowance Received for U.S. Appl. No. 13/909,002, mailed on Dec. 4, 2015, 7 pages.
Notice of Allowance Received for U.S. Appl. No. 09/757,000, mailed on Dec. 15, 2003, 4 pages.
Notice of Allowance Received for U.S. Appl. No. 11/848,210, mailed on Dec. 20, 2011, 5 pages.
Notice of Allowance Received for U.S. Appl. No. 12/566,994, mailed on May 22, 2013, 9 pages.
Notice of Allowance Received for U.S. Appl. No. 12/566,994, mailed on Oct. 6, 2014, 8 pages.
Notice of Allowance Received for U.S. Appl. No. 12/567,405, mailed on Jun. 11, 2014, 9 pages.
Notice of Allowance Received for U.S. Appl. No. 12/567,460, mailed on Apr. 10, 2013, 9 pages.
Notice of Allowance Received for U.S. Appl. No. 12/567,460, mailed on Aug. 10, 2012, 8 pages.
Notice of Allowance Received for U.S. Appl. No. 12/567,460, mailed on Dec. 24, 2012, 8 pages.
Notice of Allowance Received for U.S. Appl. No. 12/567,460, mailed on Jan. 18, 2012, 8 pages.
Notice of Allowance Received for U.S. Appl. No. 12/567,553, mailed on Apr. 2, 2013, 9 pages.
Notice of Allowance Received for U.S. Appl. No. 12/567,553, mailed on Aug. 10, 2012, 8 pages.
Notice of Allowance Received for U.S. Appl. No. 12/567,553, mailed on Dec. 24, 2012, 8 pages.
Notice of Allowance Received for U.S. Appl. No. 12/567,553, mailed on Jun. 12, 2012, 8 pages.
Notice of Allowance Received for U.S. Appl. No. 12/567,570, mailed on Dec. 19, 2012, 7 pages.
Notice of Allowance Received for U.S. Appl. No. 12/567,570, mailed on Mar. 27, 2013, 8 pages.
Notice of Allowance Received for U.S. Appl. No. 12/849,767, mailed on Jan. 8, 2013, 9 pages.
Notice of Allowance Received for U.S. Appl. No. 13/361,912, mailed on Jul. 2, 2012, Jul. 2, 2012, 7 pages.
Notice of Allowance Received for U.S. Appl. No. 13/666,943, mailed on Jun. 2, 2016, 9 pages.
Notice of Allowance Received for U.S. Appl. No. 13/666,943, mailed on Jun. 17, 2015, 7 pages.

(56)

References Cited**OTHER PUBLICATIONS**

Notice of Allowance Received for U.S. Appl. No. 13/909,001, mailed on Mar. 3, 2014, 7 pages.
Notice of Allowance Received for U.S. Appl. No. 14/732,773, mailed on Dec. 18, 2019, 21 pages.
Notice of Allowance Received for U.S. Appl. No. 14/839,916, mailed on Aug. 31, 2016, 11 pages.
Notice of Allowance Received for U.S. Appl. No. 14/839,916, mailed on Jan. 10, 2018, 19 pages.
Notice of Allowance Received for U.S. Appl. No. 14/839,922, mailed on Jan. 26, 2018, 2 pages.
Notice of Allowance Received for U.S. Appl. No. 14/839,922, mailed on Jul. 6, 2017, 8 pages.
Notice of Allowance Received for U.S. Appl. No. 14/839,922, mailed on Nov. 2, 2017, 8 pages.
Notice of Allowance Received for U.S. Appl. No. 15/088,450, mailed on Dec. 13, 2018, 7 pages.
Notice of Allowance Received for U.S. Appl. No. 15/183,663, mailed on Jan. 17, 2019, 6 pages.
Notice of Allowance Received for U.S. Appl. No. 15/281,524, mailed on Apr. 11, 2019, 7 pages.
Notice of Allowance Received for U.S. Appl. No. 15/600,243, mailed on Dec. 12, 2019, 7 pages.
Notice of Allowance Received for U.S. Appl. No. 15/608,848, mailed on Aug. 25, 2021, 9 pages.
Notice of Allowance Received for U.S. Appl. No. 15/608,848, mailed on Oct. 29, 2021, 7 pages.
Notice of Allowance Received for U.S. Appl. No. 15/616,480, mailed on Jan. 3, 2019, 8 pages.
Notice of Allowance Received for U.S. Appl. No. 15/627,069, mailed on Jun. 17, 2021, 14 pages.
Notice of Allowance Received for U.S. Appl. No. 15/705,849, mailed on Jul. 28, 2020, 10 pages.
Notice of Allowance Received for U.S. Appl. No. 15/705,849, mailed on Oct. 16, 2020, 14 pages.
Notice of Allowance Received for U.S. Appl. No. 15/925,652, mailed on Mar. 9, 2021, 9 pages.
Notice of Allowance Received for U.S. Appl. No. 15/925,652, mailed on Nov. 20, 2020, 9 pages.
Notice of Allowance Received for U.S. Appl. No. 16/138,809, mailed on Apr. 16, 2021, 11 pages.
Notice of Allowance Received for U.S. Appl. No. 16/138,809, mailed on Jul. 20, 2021, 6 pages.
Notice of Allowance Received for U.S. Appl. No. 16/144,671, mailed on Feb. 10, 2020, 17 pages.
Notice of Allowance Received for U.S. Appl. No. 16/144,735, mailed on Jul. 21, 2020, 13 pages.
Notice of Allowance Received for U.S. Appl. No. 16/144,735, mailed on Oct. 28, 2020, 13 pages.
Notice of Allowance Received for U.S. Appl. No. 16/144,753, mailed on Dec. 4, 2020, 22 pages.
Notice of Allowance Received for U.S. Appl. No. 16/144,753, mailed on Feb. 10, 2021, 8 pages.
Notice of Allowance Received for U.S. Appl. No. 16/144,849, mailed on Apr. 17, 2020, 2 pages.
Notice of Allowance Received for U.S. Appl. No. 16/144,849, mailed on Mar. 6, 2020, 9 pages.
Notice of Allowance Received for U.S. Appl. No. 16/144,864, mailed on Feb. 9, 2021, 13 pages.
Notice of Allowance Received for U.S. Appl. No. 16/144,864, mailed on Jul. 28, 2020, 27 pages.
Notice of Allowance Received for U.S. Appl. No. 16/144,864, mailed on Mar. 12, 2021, 2 pages.
Notice of Allowance Received for U.S. Appl. No. 16/144,864, mailed on Mar. 30, 2021, 2 pages.
Notice of Allowance Received for U.S. Appl. No. 16/144,864, mailed on Sep. 10, 2020, 3 pages.
Notice of Allowance Received for U.S. Appl. No. 16/144,864, mailed on Sep. 16, 2020, 2 pages.

Notice of Allowance Received for U.S. Appl. No. 16/144,864, mailed on Sep. 29, 2020, 2 pages.
Notice of Allowance Received for U.S. Appl. No. 16/377,892, mailed on May 24, 2021, 9 pages.
Notice of Allowance Received for U.S. Appl. No. 16/377,892, mailed on Sep. 9, 2021, 9 pages.
Notice of Allowance Received for U.S. Appl. No. 16/378,136, mailed on Jun. 3, 2021, 7 pages.
Notice of Allowance Received for U.S. Appl. No. 16/378,136, mailed on Sep. 22, 2021, 7 pages.
Notice of Allowance Received for U.S. Appl. No. 16/403,184, mailed on Oct. 11, 2019, 9 pages.
Notice of Allowance Received for U.S. Appl. No. 16/418,786, mailed on Dec. 9, 2021, 9 pages.
Notice of Allowance Received for U.S. Appl. No. 16/418,786, mailed on Jun. 14, 2022, 9 pages.
Notice of Allowance Received for U.S. Appl. No. 16/418,786, mailed on Nov. 22, 2022, 6 pages.
Notice of Allowance Received for U.S. Appl. No. 16/450,531, mailed on Sep. 25, 2020, 7 pages.
Notice of Allowance Received for U.S. Appl. No. 16/556,023, mailed on Jan. 13, 2021, 8 pages.
Notice of Allowance Received for U.S. Appl. No. 16/556,023, mailed on Oct. 15, 2020, 8 pages.
Notice of Allowance Received for U.S. Appl. No. 16/584,776, mailed on Feb. 1, 2021, 9 pages.
Notice of Allowance Received for U.S. Appl. No. 16/584,783, mailed on Dec. 20, 2021, 7 pages.
Notice of Allowance Received for U.S. Appl. No. 16/588,950, mailed on Feb. 10, 2020, 9 pages.
Notice of Allowance Received for U.S. Appl. No. 16/588,950, mailed on May 5, 2020, 9 pages.
Notice of Allowance Received for U.S. Appl. No. 16/791,257, mailed on Jun. 12, 2020, 11 pages.
Notice of Allowance Received for U.S. Appl. No. 16/820,383, mailed on Aug. 2, 2023, 14 pages.
Notice of Allowance Received for U.S. Appl. No. 16/820,383, mailed on Dec. 7, 2023, 13 pages.
Notice of Allowance Received for U.S. Appl. No. 16/820,383, mailed on Jul. 21, 2021, 11 pages.
Notice of Allowance Received for U.S. Appl. No. 16/820,383, mailed on Mar. 8, 2023, 13 pages.
Notice of Allowance Received for U.S. Appl. No. 16/820,383, mailed on Mar. 31, 2021, 11 pages.
Notice of Allowance Received for U.S. Appl. No. 16/820,383, mailed on Nov. 22, 2022, 16 pages.
Notice of Allowance Received for U.S. Appl. No. 16/888,629, mailed on Nov. 9, 2021, 11 pages.
Notice of Allowance Received for U.S. Appl. No. 16/894,309, mailed on Feb. 25, 2022, 9 pages.
Notice of Allowance Received for U.S. Appl. No. 16/894,309, mailed on Nov. 5, 2021, 12 pages.
Notice of Allowance Received for U.S. Appl. No. 16/987,275, mailed on Jul. 27, 2022, 6 pages.
Notice of Allowance Received for U.S. Appl. No. 16/987,275, mailed on May 16, 2022, 7 pages.
Notice of Allowance Received for U.S. Appl. No. 16/994,352, mailed on Jun. 3, 2022, 9 pages.
Notice of Allowance Received for U.S. Appl. No. 16/994,352, mailed on Mar. 2, 2022, 14 pages.
Notice of Allowance Received for U.S. Appl. No. 17/030,318, mailed on Jan. 5, 2022, 8 pages.
Notice of Allowance Received for U.S. Appl. No. 17/030,318, mailed on Jan. 25, 2023, 10 pages.
Notice of Allowance Received for U.S. Appl. No. 17/030,318, mailed on May 16, 2023, 5 pages.
Notice of Allowance Received for U.S. Appl. No. 17/030,321, mailed on Apr. 1, 2022, 8 pages.
Notice of Allowance Received for U.S. Appl. No. 17/030,337, mailed on Aug. 22, 2022, 10 pages.
Notice of Allowance Received for U.S. Appl. No. 17/030,337, mailed on Dec. 23, 2022, 9 pages.

(56)

References Cited**OTHER PUBLICATIONS**

Notice of Allowance Received for U.S. Appl. No. 17/030,340, mailed on Sep. 28, 2022, 7 pages.
Notice of Allowance Received for U.S. Appl. No. 17/030,343, mailed on Dec. 15, 2022, 9 pages.
Notice of Allowance Received for U.S. Appl. No. 17/030,343, mailed on Sep. 16, 2022, 11 pages.
Notice of Allowance Received for U.S. Appl. No. 17/031,543, mailed on May 11, 2022, 6 pages.
Notice of Allowance Received for U.S. Appl. No. 17/035,367, mailed on Sep. 23, 2021, 7 pages.
Notice of Allowance Received for U.S. Appl. No. 17/041,438, mailed on Jan. 22, 2024, 10 pages.
Notice of Allowance Received for U.S. Appl. No. 17/041,438, mailed on Oct. 19, 2023, 2 pages.
Notice of Allowance Received for U.S. Appl. No. 17/041,438, mailed on Sep. 20, 2023, 11 pages.
Notice of Allowance Received for U.S. Appl. No. 17/153,703, mailed on Aug. 30, 2022, 8 pages.
Notice of Allowance Received for U.S. Appl. No. 17/153,703, mailed on Dec. 22, 2022, 7 pages.
Notice of Allowance Received for U.S. Appl. No. 17/157,728, mailed on Feb. 24, 2022, 7 pages.
Notice of Allowance Received for U.S. Appl. No. 17/192,161, mailed on Feb. 16, 2022, 8 pages.
Notice of Allowance Received for U.S. Appl. No. 17/192,161, mailed on May 27, 2022, 8 pages.
Notice of Allowance Received for U.S. Appl. No. 17/197,628, mailed on Jun. 24, 2022, 8 pages.
Notice of Allowance Received for U.S. Appl. No. 17/197,628, mailed on Mar. 23, 2022, 35 pages.
Notice of Allowance Received for U.S. Appl. No. 17/381,570, mailed on Jul. 26, 2023, 14 pages.
Notice of Allowance Received for U.S. Appl. No. 17/516,537, mailed on Apr. 17, 2023, 8 pages.
Notice of Allowance Received for U.S. Appl. No. 17/516,537, mailed on Dec. 27, 2022, 7 pages.
Notice of Allowance Received for U.S. Appl. No. 17/591,184, mailed on Dec. 11, 2023, 9 pages.
Notice of Allowance Received for U.S. Appl. No. 17/591,184, mailed on Feb. 22, 2023, 5 pages.
Notice of Allowance Received for U.S. Appl. No. 17/666,301, mailed on May 4, 2023, 10 pages.
Notice of Allowance Received for U.S. Appl. No. 17/697,539, mailed on Nov. 29, 2022, 10 pages.
Notice of Allowance Received for U.S. Appl. No. 17/744,500, mailed on Dec. 22, 2023, 38 pages.
Notice of Allowance Received for U.S. Appl. No. 17/745,021, mailed on May 1, 2023, 5 pages.
Notice of Allowance Received for U.S. Appl. No. 17/852,020, mailed on Jul. 12, 2023, 9 pages.
Notice of Allowance Received for U.S. Appl. No. 17/896,791, mailed on Dec. 15, 2023, 9 pages.
Notice of Allowance Received for U.S. Appl. No. 17/951,613, mailed on Dec. 8, 2023, 13 pages.
Notice of Allowance Received for U.S. Appl. No. 17/951,613, mailed on Feb. 2, 2024, 5 pages.
Notice of Allowance Received for U.S. Appl. No. 17/951,875, mailed on Dec. 26, 2023, 7 pages.
Notice of Allowance Received for U.S. Appl. No. 17/951,875, mailed on Jul. 26, 2023, 7 pages.
Notice of Allowance Received for U.S. Appl. No. 17/951,875, mailed on Oct. 20, 2023, 8 pages.
Notice of Allowance Received for U.S. Appl. No. 17/951,976, mailed on Mar. 12, 2024, 5 pages.
Notice of Allowance Received for U.S. Appl. No. 17/951,976, mailed on Nov. 17, 2023, 9 pages.
Notice of Allowance Received for U.S. Appl. No. 17/952,027, mailed on Dec. 29, 2023, 6 pages.

Notice of Allowance Received for U.S. Appl. No. 17/952,027, mailed on Oct. 4, 2023, 13 pages.
Notice of Allowance Received for U.S. Appl. No. 17/952,181, mailed on Sep. 27, 2023, 9 pages.
Notice of Allowance Received for U.S. Appl. No. 17/952,185, mailed on Aug. 30, 2023, 12 pages.
Notice of Allowance Received for U.S. Appl. No. 17/952,185, mailed on Dec. 13, 2023, 9 pages.
Notice of Allowance Received for U.S. Appl. No. 17/952,239, mailed on Jun. 23, 2023, 5 pages.
Notice of Allowance Received for U.S. Appl. No. 17/952,239, mailed on Oct. 20, 2023, 5 pages.
Notice of Allowance Received for U.S. Appl. No. 18/114,794, mailed on Aug. 16, 2023, 11 pages.
Notice of Allowance Received for U.S. Appl. No. 18/114,794, mailed on Dec. 5, 2023, 8 pages.
Notice of Allowance Received for U.S. Appl. No. 12/849,767, mailed on Apr. 25, 2014, 5 pages.
Office Action Received for Australian Patent Application No. 2015201028, issued on Mar. 15, 2016, 2 pages.
Office Action Received for Australian Patent Application No. 2015312215, mailed on Oct. 13, 2016, 3 pages.
Office Action Received for Australian Patent Application No. 2017100667, mailed on Aug. 3, 2017, 9 pages.
Office Action Received for Australian Patent Application No. 2017201548, mailed on Feb. 26, 2018, 2 pages.
Office Action Received for Australian Patent Application No. 2017277971, mailed on Aug. 12, 2020, 3 pages.
Office Action Received for Australian Patent Application No. 2017277971, mailed on Jun. 3, 2020, 3 pages.
Office Action Received for Australian Patent Application No. 2018100158, mailed on Apr. 23, 2018, 5 pages.
Office Action Received for Australian Patent Application No. 2018101855, mailed on Feb. 22, 2019, 4 pages.
Office Action Received for Australian Patent Application No. 2018200428, mailed on Mar. 7, 2018, 4 pages.
Office Action Received for Australian Patent Application No. 2018200428, mailed on Nov. 15, 2018, 4 pages.
Office Action Received for Australian Patent Application No. 2018214074, mailed on May 9, 2019, 2 pages.
Office Action Received for Australian Patent Application No. 2018268972, mailed on Jul. 9, 2020, 4 pages.
Office Action Received for Australian Patent Application No. 2019100495, mailed on Mar. 6, 2020, 3 pages.
Office Action Received for Australian Patent Application No. 2019100495, mailed on Mar. 16, 2020, 3 pages.
Office Action Received for Australian Patent Application No. 2019100495, mailed on Sep. 17, 2019, 7 pages.
Office Action Received for Australian Patent Application No. 2019222943, mailed on Oct. 3, 2019, 3 pages.
Office Action Received for Australian Patent Application No. 2019250251, mailed on Aug. 6, 2020, 3 pages.
Office Action Received for Australian Patent Application No. 2019264623, mailed on Sep. 14, 2020, 3 pages.
Office Action Received for Australian Patent Application No. 2020239743, mailed on Mar. 25, 2021, 8 pages.
Office Action Received for Australian Patent Application No. 2020239743, mailed on Sep. 3, 2021, 4 pages.
Office Action Received for Australian Patent Application No. 2020239748, mailed on Apr. 21, 2021, 6 pages.
Office Action Received for Australian Patent Application No. 2020239748, mailed on Feb. 11, 2022, 2 pages.
Office Action Received for Australian Patent Application No. 2020239748, mailed on Sep. 1, 2021, 4 pages.
Office Action Received for Australian Patent Application No. 2020239752, mailed on Jun. 4, 2021, 8 pages.
Office Action Received for Australian Patent Application No. 2020239752, mailed on Oct. 25, 2021, 5 pages.
Office Action Received for Australian Patent Application No. 2020256383, mailed on Jun. 4, 2021, 3 pages.
Office Action Received for Australian Patent Application No. 2020268150, mailed on Aug. 24, 2023, 5 pages.

(56)

References Cited**OTHER PUBLICATIONS**

Office Action Received for Australian Patent Application No. 2020268150, mailed on Feb. 6, 2023, 5 pages.
Office Action Received for Australian Patent Application No. 2020268150, mailed on May 8, 2023, 4 pages.
Office Action Received for Australian Patent Application No. 2020268150, mailed on Nov. 3, 2022, 4 pages.
Office Action Received for Australian Patent Application No. 2020288139, mailed on Oct. 31, 2022, 3 pages.
Office Action Received for Australian Patent Application No. 2021201130, mailed on Jan. 27, 2022, 2 pages.
Office Action Received for Australian Patent Application No. 2021202225, mailed on Apr. 7, 2022, 3 pages.
Office Action Received for Australian Patent Application No. 2021203636, mailed on Mar. 23, 2022, 3 pages.
Office Action Received for Australian Patent Application No. 2021204422, mailed on May 31, 2022, 2 pages.
Office Action Received for Australian Patent Application No. 2021266294, mailed on Nov. 11, 2022, 3 pages.
Office Action Received for Australian Patent Application No. 2022201761, mailed on Feb. 28, 2023, 5 pages.
Office Action Received for Australian Patent Application No. 2022201810, mailed on Mar. 15, 2023, 2 pages.
Office Action Received for Australian Patent Application No. 2022202977, mailed on Jul. 21, 2023, 3 pages.
Office Action Received for Australian Patent Application No. 2022202977, mailed on May 2, 2023, 5 pages.
Office Action Received for Australian Patent Application No. 2022209277, mailed on Mar. 10, 2023, 6 pages.
Office Action Received for Australian Patent Application No. 2022235614, mailed on May 9, 2023, 2 pages.
Office Action Received for Australian Patent Application No. 2022235618, mailed on Jul. 4, 2023, 2 pages.
Office Action Received for Australian Patent Application No. 2022235618, mailed on May 19, 2023, 2 pages.
Office Action Received for Australian Patent Application No. 2023203050, mailed on Sep. 1, 2023, 3 pages.
Office Action Received for Australian Patent Application No. 2023203776, mailed on Nov. 7, 2023, 2 pages.
Office Action Received for Australian Patent Application No. 2023237090, mailed on Oct. 18, 2023, 3 pages.
Office Action Received for Australian Patent Application No. 2023237163, mailed on Nov. 24, 2023, 3 pages.
Office Action Received for Canadian Patent Application No. 2,853,273, mailed on Feb. 23, 2015, 5 pages.
Office Action Received for Canadian Patent Application No. 2,984,527 mailed on Sep. 11, 2018, 5 pages.
Office Action Received for Canadian Patent Application No. 2,984,527, mailed on Jul. 25, 2019, 4 pages.
Office Action Received for Chinese Patent Application No. 201380081349.6, mailed on Feb. 26, 2019, 12 pages.
Office Action Received for Chinese Patent Application No. 201380081349.6, mailed on Jan. 5, 2021, 16 pages.
Office Action Received for Chinese Patent Application No. 201380081349.6, mailed on Jan. 16, 2020, 11 pages.
Office Action Received for Chinese Patent Application No. 201380081349.6, mailed on Jul. 15, 2019, 10 pages.
Office Action Received for Chinese Patent Application No. 201380081349.6, mailed on Jul. 15, 2020, 9 pages.
Office Action Received for Chinese Patent Application No. 201380081349.6, mailed on Jun. 2, 2021, 17 pages.
Office Action Received for Chinese Patent Application No. 201580037927.5, mailed on Apr. 22, 2019, 9 pages.
Office Action Received for Chinese Patent Application No. 201580037927.5, mailed on Jul. 20, 2018, 21 pages.
Office Action Received for Chinese Patent Application No. 201680047983.1, mailed on Feb. 1, 2021, 6 pages.
Office Action Received for Chinese Patent Application No. 201680047983.1, mailed on Jul. 1, 2020, 6 pages.

Office Action Received for Chinese Patent Application No. 201680047983.1, mailed on Mar. 18, 2019, 18 pages.
Office Action Received for Chinese Patent Application No. 201680047983.1, mailed on Nov. 28, 2019, 9 pages.
Office Action Received for Chinese Patent Application No. 201710439448.7, mailed on Mar. 27, 2020, 13 pages.
Office Action Received for Chinese Patent Application No. 201710439448.7, mailed on Oct. 10, 2020, 19 pages.
Office Action Received for Chinese Patent Application No. 201780034203.4, mailed on Jul. 14, 2021, 12 pages.
Office Action Received for Chinese Patent Application No. 201780034203.4, mailed on Sep. 24, 2021, 7 pages.
Office Action Received for Chinese Patent Application No. 201810105846.X, mailed on Aug. 27, 2019, 12 pages.
Office Action Received for Chinese Patent Application No. 201810105846.X, mailed on Feb. 25, 2019, 10 pages.
Office Action Received for Chinese Patent Application No. 201810105846.X, mailed on Nov. 28, 2019, 9 pages.
Office Action Received for Chinese Patent Application No. 201811303556.2, mailed on May 19, 2023, 6 pages.
Office Action Received for Chinese Patent Application No. 201811303556.2, mailed on Nov. 28, 2022, 18 pages.
Office Action Received for Chinese Patent Application No. 201880032190.1, mailed on May 31, 2023, 20 pages.
Office Action Received for Chinese Patent Application No. 201880032190.1, mailed on Nov. 14, 2022, 23 pages.
Office Action Received for Chinese Patent Application No. 201910858933.7, mailed on Aug. 18, 2020, 14 pages.
Office Action Received for Chinese Patent Application No. 201910858933.7, mailed on Dec. 30, 2021, 9 pages.
Office Action Received for Chinese Patent Application No. 201910858933.7, mailed on Jun. 29, 2021, 8 pages.
Office Action Received for Chinese Patent Application No. 201911396643.1, mailed on Apr. 6, 2023, 26 pages.
Office Action Received for Chinese Patent Application No. 201911396744.9, mailed on Apr. 6, 2023, 19 pages.
Office Action Received for Chinese Patent Application No. 201911396819.3, mailed on Apr. 6, 2023, 21 pages.
Office Action Received for Chinese Patent Application No. 201911396876.1, mailed on Apr. 7, 2023, 16 pages.
Office Action Received for Chinese Patent Application No. 201911401161.0, mailed on Aug. 9, 2022, 17 pages.
Office Action Received for Chinese Patent Application No. 201911401161.0, mailed on Dec. 15, 2022, 14 pages.
Office Action Received for Chinese Patent Application No. 201911401161.0, mailed on Jan. 24, 2022, 6 pages.
Office Action Received for Chinese Patent Application No. 201911401375.8, mailed on Apr. 7, 2023, 10 pages.
Office Action Received for Chinese Patent Application No. 201911401375.8, mailed on Sep. 26, 2023, 13 pages.
Office Action Received for Chinese Patent Application No. 202010606407.4, mailed on Jan. 27, 2021, 16 pages.
Office Action Received for Chinese Patent Application No. 202010606407.4, mailed on Jun. 2, 2021, 12 pages.
Office Action Received for Chinese Patent Application No. 202010606407.4, mailed on Nov. 18, 2021, 6 pages.
Office Action Received for Chinese Patent Application No. 202110363565.6, mailed on May 7, 2022, 12 pages.
Office Action Received for Chinese Patent Application No. 202110363565.6, mailed on Nov. 16, 2021, 16 pages.
Office Action Received for Chinese Patent Application No. 202110783860.7, mailed on Mar. 10, 2022, 15 pages.
Office Action Received for Chinese Patent Application No. 202110783860.7, mailed on Nov. 15, 2022, 8 pages.
Office Action Received for Chinese Patent Application No. 202111487316.4, mailed on Aug. 8, 2022, 25 pages.
Office Action Received for Chinese Patent Application No. 202111487316.4, mailed on Dec. 28, 2022, 13 pages.
Office Action Received for Chinese Patent Application No. 202111487316.4, mailed on Jun. 7, 2023, 20 pages.
Office Action Received for Chinese Patent Application No. 202211193170.7, mailed on Jun. 30, 2023, 19 pages.

(56)

References Cited**OTHER PUBLICATIONS**

Office Action Received for Danish Patent Application No. PA201670656, mailed on Nov. 3, 2016, 8 pages.
Office Action Received for Danish Patent Application No. PA 2020 70612, mailed on Mar. 1, 2022, 2 pages.
Office Action Received for Danish Patent Application No. PA201570666, mailed on Feb. 2, 2016, 9 pages.
Office Action Received for Danish Patent Application No. PA201570666, mailed on Jun. 27, 2016, 4 pages.
Office Action Received for Danish Patent Application No. PA201570668, mailed on Apr. 8, 2016, 8 pages.
Office Action Received for Danish Patent Application No. PA201570668, mailed on Sep. 9, 2016, 3 pages.
Office Action Received for Danish Patent Application No. PA201670656, mailed on Jul. 1, 2020, 4 pages.
Office Action Received for Danish Patent Application No. PA201670656, mailed on Jun. 14, 2017, 3 pages.
Office Action Received for Danish Patent Application No. PA201670656, mailed on May 2, 2019, 4 pages.
Office Action Received for Danish Patent Application No. PA201670656, mailed on May 30, 2018, 5 pages.
Office Action Received for Danish Patent Application No. PA201770191, mailed on Jan. 25, 2018, 3 pages.
Office Action Received for Danish Patent Application No. PA201770191, mailed on Nov. 21, 2018, 4 pages.
Office Action Received for Danish Patent Application No. PA201770191, mailed on Oct. 25, 2019, 4 pages.
Office Action Received for Danish Patent Application No. PA201770423, mailed on Jun. 12, 2018, 7 pages.
Office Action Received for Danish Patent Application No. PA201770423, mailed on Mar. 29, 2019, 6 pages.
Office Action Received for Danish Patent Application No. PA201870378, mailed on Feb. 25, 2019, 3 pages.
Office Action Received for Danish Patent Application No. PA201870378, mailed on Jan. 6, 2020, 3 pages.
Office Action Received for Danish Patent Application No. PA201870379, mailed on Feb. 28, 2019, 3 pages.
Office Action Received for Danish Patent Application No. PA201870380, mailed on Mar. 5, 2020, 2 pages.
Office Action Received for Danish Patent Application No. PA201870380, mailed on Mar. 27, 2019, 4 pages.
Office Action Received for Danish Patent Application No. PA201870380, mailed on Sep. 11, 2018, 9 pages.
Office Action Received for Danish Patent Application No. PA201970532, mailed on May 29, 2020, 3 pages.
Office Action Received for Danish Patent Application No. PA201970535, mailed on May 20, 2020, 3 pages.
Office Action Received for Danish Patent Application No. PA201970535, mailed on Oct. 27, 2020, 6 pages.
Office Action Received for Danish Patent Application No. PA202070612, mailed on May 10, 2022, 2 pages.
Office Action Received for Danish Patent Application No. PA202070612, mailed on Sep. 12, 2022, 3 pages.
Office Action Received for Danish Patent Application No. PA202070613, mailed on May 10, 2022, 2 pages.
Office Action Received for Danish Patent Application No. PA202070613, mailed on Oct. 13, 2022, 7 pages.
Office Action Received for Danish Patent Application No. PA202070613, mailed on Sep. 30, 2021, 4 pages.
Office Action Received for Danish Patent Application No. PA202070614, mailed on Apr. 28, 2022, 4 pages.
Office Action Received for Danish Patent Application No. PA202070614, mailed on Sep. 28, 2021, 4 pages.
Office Action Received for Danish Patent Application No. PA202070615, mailed on Nov. 16, 2021, 4 pages.
Office Action Received for Danish Patent Application No. PA202070616, mailed on Jan. 27, 2022, 2 pages.
Office Action Received for Danish Patent Application No. PA202070616, mailed on May 5, 2022, 3 pages.

Office Action Received for Danish Patent Application No. PA202070815, mailed on Jun. 14, 2022, 3 pages.
Office Action Received for Danish Patent Application No. PA202070815, mailed on Oct. 18, 2021, 2 pages.
Office Action Received for Danish Patent Application No. PA202170113, mailed on Apr. 15, 2021, 2 pages.
Office Action Received for Danish Patent Application No. PA202170113, mailed on Aug. 18, 2022, 2 pages.
Office Action Received for Danish Patent Application No. PA202170113, mailed on May 3, 2022, 2 pages.
Office Action Received for European Patent Application No. 02713375.0, mailed on Feb. 27, 2009, 5 pages.
Office Action Received for European Patent Application No. 07814633.9, mailed on Aug. 10, 2009, 3 pages.
Office Action Received for European Patent Application No. 09756118.7, mailed on Feb. 13, 2013, 5 pages.
Office Action Received for European Patent Application No. 09756118.7, mailed on Mar. 7, 2014, 7 pages.
Office Action Received for European Patent Application No. 09756118.7, mailed on Oct. 8, 2015, 6 pages.
Office Action Received for European Patent Application No. 10172417.7, mailed on Oct. 31, 2011, 6 pages.
Office Action Received for European Patent Application No. 11178259.5, mailed on Jan. 4, 2013, 8 pages.
Office Action Received for European Patent Application No. 11178259.5, mailed on Nov. 10, 2015, 4 pages.
Office Action Received for European Patent Application No. 13811085.3, mailed on Apr. 20, 2018, 15 pages.
Office Action Received for European Patent Application No. 16837432.0, mailed on Jan. 10, 2020, 7 pages.
Office Action Received for European Patent Application No. 16837432.0, mailed on Jan. 27, 2021, 7 pages.
Office Action Received for European Patent Application No. 17180535.1, mailed on Oct. 8, 2018, 6 pages.
Office Action Received for European Patent Application No. 17180535.1, mailed on Oct. 14, 2019, 8 pages.
Office Action Received for European Patent Application No. 17810749.6, mailed on Aug. 20, 2019, 9 pages.
Office Action Received for European Patent Application No. 18154145.9, mailed on Apr. 3, 2018, 6 pages.
Office Action Received for European Patent Application No. 18197554.1, mailed on Jun. 15, 2020, 4 pages.
Office Action Received for European Patent Application No. 18727543.3, mailed on Mar. 26, 2021, 7 pages.
Office Action Received for European Patent Application No. 19721883.7, mailed on Jan. 10, 2020, 4 pages.
Office Action Received for European Patent Application No. 19721883.7, mailed on Jun. 15, 2021, 9 pages.
Office Action Received for European Patent Application No. 19721883.7, mailed on May 28, 2020, 11 pages.
Office Action Received for European Patent Application No. 20182116.2, mailed on May 25, 2021, 9 pages.
Office Action Received for European Patent Application No. 20182116.2, mailed on Nov. 6, 2020, 9 pages.
Office Action Received for European Patent Application No. 20203526.7, mailed on Nov. 23, 2021, 9 pages.
Office Action Received for European Patent Application No. 20721342.2, mailed on Nov. 4, 2021, 9 pages.
Office Action Received for European Patent Application No. 20729331.7, mailed on Jan. 4, 2023, 12 pages.
Office Action Received for European Patent Application No. 20733174.5, mailed on Dec. 18, 2023, 9 pages.
Office Action Received for European Patent Application No. 21159939.4, mailed on Sep. 2, 2022, 6 pages.
Office Action Received for European Patent Application No. 21165295.3, mailed on Jul. 1, 2021, 10 pages.
Office Action Received for European Patent Application No. 21168916.1, mailed on Aug. 23, 2021, 8 pages.
Office Action Received for European Patent Application No. 21714460.9, mailed on Oct. 24, 2023, 13 pages.
Office Action Received for European Patent Application No. 02713375.0, mailed on Feb. 24, 2010, 4 pages.

(56)

References Cited**OTHER PUBLICATIONS**

Office Action Received for European Patent Application No. 02713375.0, mailed on Feb. 24, 2014, 5 pages.

Office Action Received for European Patent Application No. 15771747.1, mailed on Oct. 31, 2017, 7 pages.

Office Action Received for German Patent Application No. 112007000067.8, mailed on Apr. 23, 2009, 15 pages.

Office Action Received for German Patent Application No. 112007000067.8, mailed on Sep. 14, 2010, 4 pages.

Office Action Received for German Patent Application No. 112015002326.7, mailed on Feb. 20, 2019, 7 pages.

Office Action Received for German Patent Application No. 112015007285.3, mailed on Mar. 7, 2023, 15 pages.

Office Action Received for Indian Patent Application No. 202014041563, mailed on Dec. 30, 2021, 6 pages.

Office Action Received for Indian Patent Application No. 202014041571, mailed on Dec. 17, 2021, 5 pages.

Office Action Received for Indian Patent Application No. 202048019639, mailed on Sep. 27, 2022, 5 pages.

Office Action Received for Indian Patent Application No. 202117050360, mailed on Oct. 30, 2023, 10 pages.

Office Action Received for Indian Patent Application No. 9044/CHENP/2014, mailed on Jan. 24, 2020, 6 pages.

Office action Received for Indian Patent Application No. 2797CHENP2008, mailed on Jan. 29, 2014, 3 pages.

Office Action Received for Japanese Patent Application No. 2013-140171, mailed on Jul. 22, 2014, 4 pages.

Office Action Received for Japanese Patent Application No. 2014-259225, mailed on May 27, 2016, 4 pages.

Office Action Received for Japanese Patent Application No. 2014-259225, mailed on Nov. 20, 2015, 2 pages.

Office Action Received for Japanese Patent Application No. 2015-129152, mailed on Sep. 23, 2016, 3 pages.

Office Action Received for Japanese Patent Application No. 2016-535045, mailed on May 12, 2017, 10 pages.

Office Action Received for Japanese Patent Application No. 2016-557650, mailed on Apr. 13, 2018, 9 pages.

Office Action Received for Japanese Patent Application No. 2016-557650, mailed on Aug. 10, 2017, 10 pages.

Office Action Received for Japanese Patent Application No. 2016-557650, mailed on Nov. 9, 2018, 6 pages.

Office Action Received for Japanese Patent Application No. 2017-057997, mailed on Jan. 9, 2018, 6 pages.

Office Action Received for Japanese Patent Application No. 2017-132229, mailed on Mar. 16, 2018, 7 pages.

Office Action Received for Japanese Patent Application No. 2018-014096, mailed on Aug. 28, 2020, 4 pages.

Office Action Received for Japanese Patent Application No. 2018-014096, mailed on Jan. 6, 2020, 17 pages.

Office Action Received for Japanese Patent Application No. 2018-014096, mailed on Jun. 29, 2018, 20 pages.

Office Action Received for Japanese Patent Application No. 2018-014096, mailed on May 8, 2019, 14 pages.

Office Action Received for Japanese Patent Application No. 2018-014096, mailed on Nov. 6, 2018, 15 pages.

Office Action Received for Japanese Patent Application No. 2018-068846, mailed on Jan. 8, 2019, 6 pages.

Office Action Received for Japanese Patent Application No. 2018-138559, mailed on Apr. 9, 2021, 30 pages.

Office Action Received for Japanese Patent Application No. 2018-138559, mailed on Jan. 27, 2020, 7 pages.

Office Action Received for Japanese Patent Application No. 2018-138559, mailed on Jul. 26, 2021, 37 pages.

Office Action Received for Japanese Patent Application No. 2018-138559, mailed on May 13, 2019, 10 pages.

Office Action Received for Japanese Patent Application No. 2018-184532, mailed on Mar. 1, 2021, 11 pages.

Office Action Received for Japanese Patent Application No. 2019-044107, mailed on Jul. 30, 2021, 9 pages.

Office Action Received for Japanese Patent Application No. 2019-044107, mailed on May 29, 2020, 6 pages.

Office Action Received for Japanese Patent Application No. 2019-162293, mailed on Jan. 31, 2020, 8 pages.

Office Action Received for Japanese Patent Application No. 2019-162293, mailed on Jul. 27, 2020, 9 pages.

Office Action Received for Japanese Patent Application No. 2019-563407, mailed on Feb. 5, 2021, 5 pages.

Office Action Received for Japanese Patent Application No. 2020-000492, mailed on Dec. 11, 2020, 6 pages.

Office Action Received for Japanese Patent Application No. 2020-079486, mailed on Jul. 16, 2021, 10 pages.

Office Action Received for Japanese Patent Application No. 2020-079486, mailed on Mar. 11, 2022, 8 pages.

Office Action Received for Japanese Patent Application No. 2020-104679, mailed on Sep. 18, 2020, 13 pages.

Office Action Received for Japanese Patent Application No. 2020-115940, mailed on May 7, 2021, 3 pages.

Office Action Received for Japanese Patent Application No. 2020-160052, mailed on Dec. 17, 2021, 10 pages.

Office Action Received for Japanese Patent Application No. 2020-160053, mailed on Aug. 1, 2022, 8 pages.

Office Action Received for Japanese Patent Application No. 2020-160053, mailed on Jan. 31, 2022, 8 pages.

Office Action Received for Japanese Patent Application No. 2020-160054, mailed on Jan. 21, 2022, 8 pages.

Office Action Received for Japanese Patent Application No. 2021-131726, mailed on Aug. 22, 2022, 8 pages.

Office Action Received for Japanese Patent Application No. 2021-131726, mailed on Dec. 2, 2022, 4 pages.

Office Action Received for Japanese Patent Application No. 2021-153558, mailed on Nov. 21, 2022, 8 pages.

Office Action Received for Japanese Patent Application No. 2021-565912, mailed on Jan. 12, 2023, 9 pages.

Office Action Received for Japanese Patent Application No. 2021-565912, mailed on Jun. 26, 2023, 3 pages.

Office Action Received for Japanese Patent Application No. 2021-566100, mailed on May 27, 2022, 7 pages.

Office Action Received for Japanese Patent Application No. 2021-571468, mailed on Jan. 5, 2023, 14 pages.

Office Action Received for Japanese Patent Application No. 2022-022159, mailed on Feb. 20, 2023, 10 pages.

Office Action Received for Japanese Patent Application No. 2022-076722, mailed on Mar. 13, 2023, 6 pages.

Office Action Received for Japanese Patent Application No. 2022-130087, mailed on Oct. 2, 2023, 12 pages.

Office Action Received for Japanese Patent Application No. 2022-151671, mailed on Jan. 5, 2024, 6 pages.

Office Action Received for Japanese Patent Application No. 2023-110196, mailed on Nov. 6, 2023, 4 pages.

Office Action Received for Korean Patent Application No. 10-2016-7014577, mailed on Dec. 26, 2017, 14 pages.

Office Action Received for Korean Patent Application No. 10-2016-7014577, mailed on Oct. 31, 2018, 11 pages.

Office Action Received for Korean Patent Application No. 10-2016-7033638, mailed on Jan. 31, 2017, 6 pages.

Office Action Received for Korean Patent Application No. 10-2019-7025538, mailed on Aug. 15, 2020, 8 pages.

Office Action Received for Korean Patent Application No. 10-2019-7025538, mailed on Feb. 17, 2020, 12 pages.

Office Action Received for Korean Patent Application No. 10-2019-7025781, mailed on Nov. 26, 2019, 10 pages.

Office Action Received for Korean Patent Application No. 10-2019-7025781, mailed on Oct. 30, 2020, 10 pages.

Office Action Received for Korean Patent Application No. 10-2019-7033834, mailed on Jan. 22, 2021, 13 pages.

Office Action Received for Korean Patent Application No. 10-2020-0123815, mailed on May 31, 2022, 10 pages.

Office Action Received for Korean Patent Application No. 10-2020-0123821, mailed on Sep. 20, 2022, 11 pages.

Office Action Received for Korean Patent Application No. 10-2020-0123840, mailed on Nov. 21, 2022, 18 pages.

(56)

References Cited**OTHER PUBLICATIONS**

Office Action Received for Korean Patent Application No. 10-2020-7026035, mailed on Feb. 19, 2021, 13 pages.

Office Action Received for Korean Patent Application No. 10-2021-7026284, mailed on Aug. 31, 2021, 10 pages.

Office Action Received for Korean Patent Application No. 10-2021-7031939, mailed on Oct. 19, 2021, 11 pages.

Office Action Received for Korean Patent Application No. 10-2021-7036242, mailed on Sep. 19, 2023, 13 pages.

Office Action Received for Korean Patent Application No. 10-2021-7036310, mailed on Feb. 23, 2022, 6 pages.

Office Action Received for Korean Patent Application No. 10-2022-0061486, mailed on Aug. 29, 2022, 5 pages.

Office Action Received for Korean Patent Application No. 10-2022-7031866, mailed on Nov. 18, 2022, 11 pages.

Office Action Received for Korean Patent Application No. 10-2022-7036278, mailed on Jun. 30, 2023, 10 pages.

Office Action Received for Taiwanese Patent Application No. 104128685, mailed on Jan. 4, 2017, 40 pages.

Partial European Search Report Received for European Patent Application No. 18197554.1, mailed on Jan. 22, 2019, 8 pages.

Partial Supplementary European Search Report Received for European Patent Application No. 17810749.6, mailed on Apr. 25, 2019, 8 pages.

Person et al., "Special Edition Using Windows 95", Published by Que Corporation, 2nd Edition, 1997, pp. 335-337.

Pre-Appeal Review Report Received for Japanese Patent Application No. 2021-565912, mailed on Oct. 12, 2023, 5 pages.

Razykdreviews, "In Depth Review of Apple Watch Activity and Workout App", available at <URL: <https://www.youtube.com/watch?v=GkKI3qIK0ow>>, Category: X Claims: 1-5 Category: L Reason: Internet citation/video, May 11, 2015, 1 page.

Redmond Wash, "Microsoft Unveils Windows Media Player 7", Microsoft Press Pass, Mar. 27, 2000, 4 pages.

Redmond Wash, "Worldwide Popularity of Microsoft Windows Media Player 7", Microsoft PressPass, Aug. 2, 2000, 1 page.

Result of Consultation Received for European Patent Application No. 17810749.6, mailed on Dec. 15, 2020, 3 pages.

Result of Consultation Received for European Patent Application No. 17810749.6, mailed on Jan. 18, 2021, 3 pages.

Result of Consultation Received for European Patent Application No. 17810749.6, mailed on Jan. 21, 2021, 18 pages.

Result of Consultation Received for European Patent Application No. 18154145.9, mailed on Nov. 30, 2020, 17 pages.

Result of Consultation Received for European Patent Application No. 18154145.9, mailed on Sep. 4, 2020, 3 pages.

Result of Consultation Received for European Patent Application No. 18197554.1, mailed on Feb. 3, 2023, 3 pages.

Result of Consultation Received for European Patent Application No. 18727543.3, mailed on Mar. 15, 2023, 6 pages.

Result of Consultation Received for European Patent Application No. 19721883.7, mailed on Oct. 7, 2020, 3 pages.

Result of Consultation Received for European Patent Application No. 20203526.7, mailed on Jan. 13, 2023, 3 pages.

Result of Consultation Received for European Patent Application No. 20721342.2, mailed on Oct. 18, 2022, 3 pages.

Result of Consultation Received for European Patent Application No. 20729331.7, mailed on Sep. 27, 2023, 27 pages.

Result of Consultation Received for European Patent Application No. 21168916.1, mailed on Dec. 11, 2023, 25 pages.

Rizknows, "Garmin Connect Mobile App—Review #2", <https://www.youtube.com/watch?v=7my3wMpeRbE>, Category: X Claims: 1-5 Category: L Reason: Internet citation/video, Oct. 22, 2015, 1 page.

Rizknows, "TomTom Multisport Cardio Review", Online available at :—<https://www.youtube.com/watch?v=WoVCzLrSN9A>, Sep. 4, 2015, 1 page.

Search report and opinion Received for Danish Patent Application No. PA201770191, mailed on Jun. 30, 2017, 9 pages.

Search Report and Opinion Received for Danish Patent Application No. PA201770423, mailed on Oct. 4, 2017, 10 pages.

Search Report and Opinion Received for Danish Patent Application No. PA201870378, mailed on Sep. 10, 2018, 9 pages.

Search Report and Opinion Received for Danish Patent Application No. PA201870379, mailed on Sep. 14, 2018, 9 pages.

Search Report and Opinion Received for Danish Patent Application No. PA201970532, mailed on Nov. 8, 2019, 9 pages.

Search Report and Opinion Received for Danish Patent Application No. PA201970535, mailed on Nov. 5, 2019, 10 pages.

Search Report and Opinion Received for Danish Patent Application No. PA202070612, mailed on Jun. 7, 2021, 9 pages.

Search Report and Opinion Received for Danish Patent Application No. PA202070613, mailed on Jan. 22, 2021, 9 pages.

Search Report and Opinion Received for Danish Patent Application No. PA202070614, mailed on Jan. 14, 2021, 9 pages.

Search Report and Opinion Received for Danish Patent Application No. PA202070615, mailed on Jan. 22, 2021, 9 pages.

Search Report and Opinion Received for Danish Patent Application No. PA202070616, mailed on Feb. 3, 2021, 8 pages.

Search Report and Opinion Received for Danish Patent Application No. PA202070815, mailed on Mar. 16, 2021, 8 pages.

Search Report and Opinion Received for Danish Patent Application No. PA202170113, mailed on Nov. 30, 2021, 9 pages.

Skiljan, Irfan, "IrfanView Help", Irfan View Screen Dumps, 1996-1999, 3 pages.

Smith, "Garmin Fenix 5 Activity/Smart Watch Review", Online Available at :—<https://www.youtube.com/watch?v=6PkQxXQxpU>, Sep. 2, 2017, 1 page.

Sportstechguides, "Garmin Fenix 5: How to Add Power Data Fields", Online Available at :—<https://www.youtube.com/watch?v=ZkPttnXEtQ>, Apr. 29, 2017, 2 pages.

Sportstechguides, "Garmin Fenix 5: How to Set Up Run Alerts", Online Available at :—<https://www.youtube.com/watch?v=gSMwv8vlhB4>, May 13, 2017, 2 pages.

Summons to Attend Oral Proceeding Received for European Patent Application No. 10172417.7, Jan. 28, 2013, 6 pages.

Summons to Attend Oral Proceedings Received for European Patent Application No. 09756118.7, mailed on Sep. 23, 2016, 8 pages.

Summons to Attend Oral Proceedings Received for European Patent Application No. 11178259.5, mailed on Feb. 11, 2015, 9 pages.

Summons to Attend Oral Proceedings Received for European Patent Application No. 11178259.5, mailed on Feb. 19, 2018, 12 pages.

Summons to Attend oral proceedings Received for European Patent Application No. 13811085.3, mailed on Jan. 26, 2018, 14 pages.

Summons to Attend Oral Proceedings Received for European Patent Application No. 13811085.3, mailed on Mar. 3, 2022, 3 pages.

Summons to Attend Oral Proceedings Received for European Patent Application No. 17810749.6, mailed on Aug. 12, 2020, 11 pages.

Summons to Attend Oral Proceedings Received for European Patent Application No. 18154145.9, mailed on Sep. 17, 2020, 11 pages.

Summons to Attend Oral Proceedings Received for European Patent Application No. 18197554.1, mailed on Mar. 23, 2022, 7 pages.

Summons to Attend Oral Proceedings Received for European Patent Application No. 18727543.3, mailed on Oct. 25, 2022, 8 pages.

Summons to Attend Oral Proceedings Received for European Patent Application No. 20182116.2, mailed on Dec. 21, 2021, 7 pages.

Summons to Attend Oral Proceedings Received for European Patent Application No. 20203526.7, mailed on Jun. 23, 2022, 9 pages.

Summons to Attend Oral Proceedings Received for European Patent Application No. 20721342.2, mailed on May 20, 2022, 11 pages.

Summons to Attend Oral Proceedings Received for European Patent Application No. 20729331.7, mailed on May 22, 2023, 15 pages.

Summons to Attend Oral Proceedings Received for European Patent Application No. 21159939.4, mailed on May 23, 2023, 9 pages.

Summons to Attend Oral Proceedings Received for European Patent Application No. 21165295.3, mailed on Jul. 25, 2023, 14 pages.

Summons to Attend Oral Proceedings Received for European Patent Application No. 21168916.1, mailed on Jul. 14, 2023, 12 pages.

Summons to Attend Oral Proceedings Received for European Patent Application No. 15771747.1, mailed on May 25, 2018, 17 pages.

Summons to Oral Proceedings Received for European Patent Application No. 15771747.1, mailed on Apr. 29, 2021, 8 pages.

(56)

References Cited**OTHER PUBLICATIONS**

Summons to Oral Proceedings Received for German Patent Application No. 112007000067.8, mailed on Dec. 8, 2021, 11 pages.

Supplemental Notice of Allowance Received for U.S. Appl. No. 15/616,480, mailed on Mar. 28, 2019, 2 pages.

Supplemental Notice of Allowance Received for U.S. Appl. No. 15/627,069, mailed on Jul. 12, 2021, 2 pages.

Supplemental Notice of Allowance Received for U.S. Appl. No. 15/925,652, mailed on Feb. 17, 2021, 3 pages.

Supplemental Notice of Allowance Received for U.S. Appl. No. 15/925,652, mailed on Jan. 6, 2021, 3 pages.

Supplemental Notice of Allowance Received for U.S. Appl. No. 15/925,652, mailed on Jan. 26, 2021, 3 pages.

Supplemental Notice of Allowance Received for U.S. Appl. No. 16/144,849, mailed on Mar. 31, 2020, 2 pages.

Supplemental Notice of Allowance Received for U.S. Appl. No. 16/403,184, mailed on Nov. 21, 2019, 3 pages.

Supplemental Notice of Allowance Received for U.S. Appl. No. 16/556,023, mailed on Feb. 3, 2021, 2 pages.

Supplemental Notice of Allowance Received for U.S. Appl. No. 16/584,776, mailed on Feb. 18, 2021, 3 pages.

Supplemental Notice of Allowance Received for U.S. Appl. No. 16/584,776, mailed on May 13, 2021, 4 pages.

Supplemental Notice of Allowance Received for U.S. Appl. No. 16/588,950, mailed on Apr. 1, 2020, 2 pages.

Supplemental Notice of Allowance Received for U.S. Appl. No. 16/588,950, mailed on Jul. 29, 2020, 2 pages.

Supplemental Notice of Allowance Received for U.S. Appl. No. 16/588,950, mailed on Jun. 18, 2020, 2 pages.

Supplemental Notice of Allowance Received for U.S. Appl. No. 16/791,257, mailed on Aug. 31, 2020, 3 pages.

Supplemental Notice of Allowance Received for U.S. Appl. No. 16/894,309, mailed on Apr. 8, 2022, 3 pages.

Supplemental Notice of Allowance Received for U.S. Appl. No. 16/894,309, mailed on Dec. 24, 2021, 2 pages.

Supplemental Notice of Allowance Received for U.S. Appl. No. 16/894,309, mailed on Jan. 25, 2022, 2 pages.

Supplemental Notice of Allowance Received for U.S. Appl. No. 16/994,352, mailed on Jun. 20, 2022, 2 pages.

Supplemental Notice of Allowance Received for U.S. Appl. No. 17/030,318, mailed on Apr. 4, 2022, 2 pages.

Supplemental Notice of Allowance Received for U.S. Appl. No. 17/030,318, mailed on Feb. 22, 2022, 2 pages.

Supplemental Notice of Allowance Received for U.S. Appl. No. 17/030,318, mailed on Mar. 16, 2022, 2 pages.

Supplemental Notice of Allowance Received for U.S. Appl. No. 17/030,321, mailed on Apr. 15, 2022, 2 pages.

Supplemental Notice of Allowance Received for U.S. Appl. No. 17/030,321, mailed on Jul. 27, 2022, 2 pages.

Supplemental Notice of Allowance Received for U.S. Appl. No. 17/030,321, mailed on Jun. 10, 2022, 2 pages.

Supplemental Notice of Allowance Received for U.S. Appl. No. 17/030,321, mailed on May 27, 2022, 2 pages.

Supplemental Notice of Allowance Received for U.S. Appl. No. 17/030,343, mailed on Jan. 6, 2023, 2 pages.

Supplemental Notice of Allowance Received for U.S. Appl. No. 17/030,343, mailed on Nov. 9, 2022, 2 pages.

Supplemental Notice of Allowance Received for U.S. Appl. No. 17/030,343, mailed on Oct. 5, 2022, 2 pages.

Supplemental Notice of Allowance Received for U.S. Appl. No. 17/035,367, mailed on Oct. 27, 2021, 3 pages.

Supplemental Notice of Allowance Received for U.S. Appl. No. 17/192,161, mailed on Jun. 13, 2022, 2 pages.

Supplemental Notice of Allowance Received for U.S. Appl. No. 17/192,161, mailed on May 13, 2022, 2 pages.

Supplemental Notice of Allowance Received for U.S. Appl. No. 17/381,570, mailed on Aug. 11, 2023, 2 pages.

Supplemental Notice of Allowance Received for U.S. Appl. No. 17/381,570, mailed on Sep. 13, 2023, 2 pages.

Supplemental Notice of Allowance Received for U.S. Appl. No. 17/666,301, mailed on Jun. 5, 2023, 2 pages.

Supplemental Notice of Allowance Received for U.S. Appl. No. 17/666,301, mailed on May 17, 2023, 2 pages.

Supplemental Notice of Allowance Received for U.S. Appl. No. 17/697,539, mailed on Feb. 21, 2023, 2 pages.

Supplemental Notice of Allowance Received for U.S. Appl. No. 17/745,021, mailed on Jun. 23, 2023, 3 pages.

Supplemental Notice of Allowance Received for U.S. Appl. No. 17/852,020, mailed on Aug. 4, 2023, 2 pages.

Supplemental Notice of Allowance Received for U.S. Appl. No. 17/951,875, mailed on Aug. 25, 2023, 2 pages.

Supplemental Notice of Allowance Received for U.S. Appl. No. 17/952,181, mailed on Dec. 20, 2023, 2 pages.

Supplemental Notice of Allowance Received for U.S. Appl. No. 17/952,181, mailed on Oct. 6, 2023, 2 pages.

Supplemental Notice of Allowance Received for U.S. Appl. No. 17/952,181, mailed on Oct. 27, 2023, 2 pages.

Supplemental Notice of Allowance Received for U.S. Appl. No. 17/952,185, mailed on Nov. 30, 2023, 2 pages.

Supplemental Notice of Allowance Received for U.S. Appl. No. 17/952,185, mailed on Oct. 2, 2023, 2 pages.

Supplemental Notice of Allowance Received for U.S. Appl. No. 18/114,794, mailed on Aug. 31, 2023, 2 pages.

Supplemental Notice of Allowance Received for U.S. Appl. No. 18/114,794, mailed on Jan. 8, 2024, 2 pages.

Supplemental Notice of Allowance Received for U.S. Appl. No. 18/114,794, mailed on Nov. 17, 2023, 2 pages.

Supplementary European Search Report Received for European Patent Application No. 02713375.0, mailed on Oct. 2, 2009, 3 pages.

Supplementary European Search Report Received for European Patent Application No. 17810749.6, mailed on Aug. 6, 2019, 6 pages.

Supplementary Search Report Received for European Patent Application No. 02713375.0, mailed on Aug. 5, 2005, 3 pages.

Suunto, "Suunto Spartan—Heart Rate Zones", Online Available at :—<https://www.youtube.com/watch?v=aixfoCnS0OU>, Mar. 19, 2018, 2 page.

T&GG Channel, "Canon IXUS 700 / Screenshots of deleting an image", Online available at: https://www.youtube.com/watch?v=8BL_L5hKZUM, May 2015, 2 pages.

Teunmo, "Data field: Visual Pace Alarm", Garmin Forum; Available online at: <https://forums.garmin.com/forum/developers/connect-iq/connect-iq-showcase/115996-data-field-visual-pace-alarm>, Nov. 17, 2015, 10 pages.

Tomtom, "TomTom Runner & Multi-Sport Reference Guide", Online available at :—https://web.archive.org/web/20150908075934/http://download.tomtom.com/open/manuals/Runner_Multi-Sport/refman/TomTom-Runner-Multi-Sport-RG-en-GB.pdf, Sep. 8, 2015, 44 pages.

Updated Notice of Allowance Received for U.S. Appl. No. 17/030,318, mailed on Feb. 23, 2023, 3 pages.

Updated Notice of Allowance Received for U.S. Appl. No. 17/030,340, mailed on Dec. 2, 2022, 2 pages.

Updated Notice of Allowance Received for U.S. Appl. No. 17/030,340, mailed on Nov. 2, 2022, 2 pages.

Updated Notice of Allowance Received for U.S. Appl. No. 17/030,340, mailed on Nov. 10, 2022, 2 pages.

Venusivenuus, "Nike Training Club", Available online at: https://www.youtube.com/watch?v=_pe6fjJPA04, Mar. 28, 2011, 6 pages.

Vicky's Blog, "How to Log in to PS4 Automatically with Particular User?", Online available on :—<https://www.youtube.com/watch?v=kqdlzXAvOkY>, May 30, 2018, 3 pages.

Way to Use a Camera, JP, Nov. 18, 2005, pp. 206-212.

Wesley, "Apple Watch Series 1", online available at :—<http://toolbox.info/blog/archives/1737-unknown.html>, May 28, 2015, 5 pages.

Willcom, "Operation Manual for WS003SH", JP, Dec. 2005, pp. 4-1 to 4-7.

Youtube, "Apple Watch Series 3", Online available at :—<https://www.youtube.com/watch?v=iBPr9gEfKk8>, Nov. 21, 2017, 15 pages.

Yoyodavid, "How to Use Multiple Accounts on the Playstation 4", Online available at :—<https://www.youtube.com/watch?v=5V21obRMeKE>, Jan. 9, 2014, 3 pages.

(56)

References Cited**OTHER PUBLICATIONS**

Yuling et al., "Research on Motion Modeling of Virtual Gear Measuring Center", Tool Technology, vol. 43, No. 2, 2009, pp. 85-87.

Zlelik, "Garmin Fenix 5 Open Water Swimming Activity Demo", Online Available at :—<https://www.youtube.com/watch?v=iSVhdvw2dcs>, Jun. 9, 2017, 1 page.

Applicant-Initiated Interview Summary received for U.S. Appl. No. 18/117,998, mailed on Jul. 24, 2024, 4 pages.

Notice of Allowance received for Korean Patent Application No. 10-2023-7025320, mailed on Jul. 31, 2024, 7 pages (2 pages of English Translation and 5 pages of Official Copy).

Notice of Allowance received for U.S. Appl. No. 17/952,181, mailed on Jul. 26, 2024, 5 pages.

Office Action received for Chinese Patent Application No. 202210312775.7, mailed on Jun. 19, 2024, 13 pages (6 pages of English Translation and 7 pages of Official Copy).

Office Action received for Chinese Patent Application No. 202211193170.7, mailed on Jul. 12, 2024, 22 pages (12 pages of English Translation and 10 pages of Official Copy).

Office Action received for Japanese Patent Application No. 2023-158326, mailed on Jul. 25, 2024, 6 pages (3 pages of English Translation and 3 pages of Official Copy).

"Workout and Fitness Tracker for Humans", Available online at: <https://gentler.app/>, Retrieved on: May 14, 2024, 11 pages.

Applicant-Initiated Interview Summary received for U.S. Appl. No. 17/735,395, mailed on May 30, 2024, 2 pages.

Applicant-Initiated Interview Summary received for U.S. Appl. No. 17/951,945, mailed on May 30, 2024, 2 pages.

Applicant-Initiated Interview Summary received for U.S. Appl. No. 17/952,133, mailed on Apr. 23, 2024, 3 pages.

Applicant-Initiated Interview Summary received for U.S. Appl. No. 17/952,233, mailed on Apr. 2, 2024, 4 pages.

Applicant-Initiated Interview Summary received for U.S. Appl. No. 18/117,998, mailed on May 3, 2024, 4 pages.

Brief Communication Regarding Oral Proceedings received for European Patent Application No. 21165295.3, mailed on Feb. 27, 2024, 1 page.

Corrected Notice of Allowance received for U.S. Appl. No. 16/820,383, mailed on Mar. 27, 2024, 2 pages.

Corrected Notice of Allowance received for U.S. Appl. No. 17/041,438, mailed on Mar. 28, 2024, 2 pages.

Corrected Notice of Allowance received for U.S. Appl. No. 17/892,534, mailed on Jun. 5, 2024, 6 pages.

Corrected Notice of Allowance received for U.S. Appl. No. 17/896,791, mailed on Jun. 7, 2024, 2 pages.

Corrected Notice of Allowance received for U.S. Appl. No. 17/952,185, mailed on Mar. 27, 2024, 2 pages.

Corrected Notice of Allowance received for U.S. Appl. No. 17/952,233, mailed on May 9, 2024, 2 pages.

Corrected Notice of Allowance received for U.S. Appl. No. 18/114,794, mailed on Feb. 23, 2024, 4 pages.

Decision to Refuse received for European Patent Application No. 21165295.3, mailed on Apr. 29, 2024, 14 pages.

Decision to Refuse received for Japanese Patent Application No. 2022-130087, mailed on Apr. 30, 2024, 6 pages. (3 pages of English Translation and 3 pages of Official Copy).

Extended European Search Report received for European Patent Application No. 23192409.3, mailed on Feb. 20, 2024, 13 pages.

Extended European Search Report received for European Patent Application No. 23217005.0, mailed on Mar. 13, 2024, 12 pages.

Extended European Search Report received for European Patent Application No. 23218010.9, mailed on Apr. 10, 2024, 13 pages.

Extended European Search Report received for European Patent Application No. 23218255.0, mailed on Mar. 27, 2024, 10 pages.

Extended European Search Report received for European Patent Application No. 24152191.3, mailed on Apr. 15, 2024, 11 pages.

Final Office Action received for U.S. Appl. No. 17/031,854, mailed on May 16, 2024, 21 pages.

Final Office Action received for U.S. Appl. No. 18/117,998, mailed on May 31, 2024, 12 pages.

Final Office Action received for U.S. Appl. No. 18/135,056, mailed on May 2, 2024, 18 pages.

International Preliminary Report on Patentability received for PCT Patent Application No. PCT/US2022/044637, mailed on Apr. 4, 2024, 12 pages.

International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2023/030718, mailed on Jan. 9, 2024, 12 pages.

Minutes of Oral Proceedings received for European Patent Application No. 21165295.3, mailed on Apr. 26, 2024, 6 pages.

Non-Final Office Action received for U.S. Appl. No. 17/735,395, mailed on Mar. 19, 2024, 32 pages.

Non-Final Office Action received for U.S. Appl. No. 17/951,945, mailed on Mar. 20, 2024, 22 pages.

Non-Final Office Action received for U.S. Appl. No. 17/952,133, mailed on Feb. 28, 2024, 22 pages.

Non-Final Office Action received for U.S. Appl. No. 18/117,998, mailed on Mar. 15, 2024, 11 pages.

Notice of Acceptance received for Australian Patent Application No. 2023237090, mailed on Feb. 23, 2024, 3 pages.

Notice of Allowance received for Chinese Patent Application No. 202310775734.6, mailed on Apr. 18, 2024, 4 pages (1 page of English Translation and 3 pages of Official Copy).

Notice of Allowance received for Chinese Patent Application No. 202311059240.4, mailed on May 23, 2024, 2 pages (1 page of English Translation and 1 page of Official Copy).

Notice of Allowance received for Japanese Patent Application No. 2022-151671, mailed on Apr. 22, 2024, 4 pages (1 page of English Translation and 3 pages of Official Copy).

Notice of Allowance received for Japanese Patent Application No. 2023-110196, mailed on Feb. 13, 2024, 4 pages (1 page of English Translation and 3 pages of Official Copy).

Notice of Allowance received for U.S. Appl. No. 17/892,534, mailed on Feb. 21, 2024, 7 pages.

Notice of Allowance received for U.S. Appl. No. 17/896,791, mailed on Mar. 13, 2024, 8 pages.

Notice of Allowance received for U.S. Appl. No. 17/952,233, mailed on May 1, 2024, 9 pages.

Notice of Allowance received for U.S. Appl. No. 18/204,217, mailed on Mar. 26, 2024, 7 pages.

Office Action received for Australian Patent Application No. 2023214377, mailed on Jun. 5, 2024, 4 pages.

Office Action received for Australian Patent Application No. 2023214377, mailed on Mar. 27, 2024, 3 pages.

Office Action received for Australian Patent Application No. 2024202344, mailed on May 16, 2024, 3 pages.

Office Action received for Chinese Patent Application No. 202080039364.4, mailed on Apr. 9, 2024, 15 pages (7 pages of English Translation and 8 pages of Official Copy).

Office Action received for Chinese Patent Application No. 202211193170.7, mailed on Jan. 6, 2024, 13 pages (6 pages of English Translation and 7 pages of Official Copy).

Office Action received for Chinese Patent Application No. 202310774963.6, mailed on Apr. 21, 2024, 18 pages (11 pages of English Translation and 7 pages of Official Copy).

Office Action received for Chinese Patent Application No. 202310774963.6, mailed on Feb. 8, 2024, 11 pages (5 pages of English Translation and 6 pages of Official Copy).

Office Action received for Chinese Patent Application No. 202310775734.6, mailed on Mar. 2, 2024, 11 pages (5 pages of English Translation and 6 pages of Official Copy).

Office Action received for Chinese Patent Application No. 202310828052.7, mailed on Mar. 6, 2024, 16 pages (7 pages of English Translation and 9 pages of Official Copy).

Office Action received for Chinese Patent Application No. 202311059240.4, mailed on Mar. 19, 2024, 11 pages (5 pages of English Translation and 6 pages of Official Copy).

Office Action received for Indian Patent Application No. 202118050660, mailed on Mar. 18, 2024, 7 pages.

(56)

References Cited**OTHER PUBLICATIONS**

Office Action received for Japanese Patent Application No. 2023-041035, mailed on Feb. 9, 2024, 13 pages (6 pages of English Translation and 7 pages of Official Copy).

Office Action received for Japanese Patent Application No. 2023-065859, mailed on Mar. 11, 2024, 8 pages (4 pages of English Translation and 4 pages of Official Copy).

Office Action received for Korean Patent Application No. 10-2023-0114488, mailed on Apr. 30, 2024, 16 pages (6 pages of English Translation and 10 pages of Official Copy).

Office Action received for Korean Patent Application No. 10-2023-7025320, mailed on Mar. 11, 2024, 9 pages (4 pages of English Translation and 5 pages of Official Copy).

Result of Consultation received for European Patent Application No. 21165295.3, mailed on Apr. 18, 2024, 3 pages.

Supplemental Notice of Allowance received for U.S. Appl. No. 17/745,021, mailed on Mar. 22, 2024, 2 pages.

Corrected Notice of Allowance received for U.S. Appl. No. 18/589,265, mailed on Feb. 26, 2025, 2 pages.

Final Office Action received for U.S. Appl. No. 18/789,495, mailed on Mar. 4, 2025, 39 pages.

Notice of Allowance received for Chinese Patent Application No. 202310774963.6, mailed on Feb. 18, 2025, 4 pages (1 page of English Translation and 3 pages of Official Copy).

Office Action received for Chinese Patent Application No. 202310774963.6, mailed on Feb. 12, 2025, 2 pages (1 page of English Translation and 1 page of Official Copy).

Office Action received for European Patent Application No. 23150297.2, mailed on Feb. 28, 2025, 4 pages.

Anonymous, "Forerunner 935 Owner's Manual", XP055953951, Available online at: <<https://www8.garmin.com/manuals/webhelp/forerunner935/EN-US/GUID-D33F9153-C95D-460A-A165-729F18B5D827-homepage.html>>, Jun. 30, 2020, 46 pages.

Applicant-Initiated Interview Summary received for U.S. Appl. No. 18/592,219, mailed on Apr. 4, 2025, 2 pages.

Board Opinion received for Chinese Patent Application No. 201910858933.7, mailed on Mar. 24, 2025, 13 pages (5 pages of English Translation and 8 pages of Official Copy).

Intention to Grant received for European Patent Application No. 23189089.8, mailed on Apr. 3, 2025, 9 pages.

International Preliminary Report on Patentability received for PCT Patent Application No. PCT/US2023/030718, mailed on Mar. 20, 2025, 8 pages.

Notice of Acceptance received for Australian Patent Application No. 2024202344, mailed on Apr. 1, 2025, 3 pages.

Notice of Allowance received for Japanese Patent Application No. 2024-032418, mailed on Mar. 21, 2025, 4 pages (1 page of English Translation and 3 pages of Official Copy).

Office Action received for European Patent Application No. 23153899.2, mailed on Apr. 4, 2025, 4 pages.

Office Action received for European Patent Application No. 23735495.6, mailed on Mar. 31, 2025, 13 pages.

International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2024/023603, mailed on Aug. 14, 2024, 17 pages.

International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2024/027314, mailed on Aug. 23, 2024, 13 pages.

Invitation to Pay Additional Fees and Partial International Search Report received for PCT Patent Application No. PCT/US2024/031346, mailed on Oct. 14, 2024, 9 pages.

Non-Final Office Action received for U.S. Appl. No. 18/628,586, mailed on Dec. 2, 2024, 13 pages.

Non-Final Office Action received for U.S. Appl. No. 18/774,704, mailed on Nov. 25, 2024, 13 pages.

Non-Final Office Action received for U.S. Appl. No. 18/789,495, mailed on Oct. 22, 2024, 37 pages.

Notice of Acceptance received for Australian Patent Application No. 2023285859, mailed on Nov. 28, 2024, 3 pages.

Notice of Allowance received for Chinese Patent Application No. 202311811912.2, mailed on Dec. 1, 2024, 5 pages (1 page of English Translation and 4 pages of Official Copy).

Notice of Allowance received for Japanese Patent Application No. 2023-133506, mailed on Nov. 22, 2024, 4 pages (1 page of English Translation and 3 pages of Official Copy).

Notice of Allowance received for U.S. Appl. No. 17/952,236, mailed on Nov. 25, 2024, 10 pages.

Notice of Allowance received for U.S. Appl. No. 18/589,265, mailed on Dec. 6, 2024, 9 pages.

Office Action received for Australian Patent Application No. 2024202344, mailed on Nov. 25, 2024, 4 pages.

Office Action received for Chinese Patent Application No. 202210312598.2, mailed on Jun. 27, 2024, 22 pages (7 pages of English Translation and 15 pages of Official Copy).

Office Action received for European Patent Application No. 22194355.8, mailed on Dec. 6, 2024, 10 pages.

Office Action received for European Patent Application No. 23735495.6, mailed on Nov. 22, 2024, 7 pages.

Office Action received for Korean Patent Application No. 10-2021-7043369, mailed on Nov. 18, 2024, 14 pages (6 pages of English Translation and 8 pages of Official Copy).

Applicant-Initiated Interview Summary received for U.S. Appl. No. 18/774,704, mailed on Dec. 20, 2024, 2 pages.

Applicant-Initiated Interview Summary received for U.S. Appl. No. 18/774,704, mailed on Jan. 29, 2025, 2 pages.

Applicant-Initiated Interview Summary received for U.S. Appl. No. 18/789,495, mailed on Jan. 24, 2025, 6 pages.

Board Decision received for Chinese Patent Application No. 202211193170.7, mailed on Nov. 21, 2024, 17 pages (1 page of English Translation and 16 pages of Official Copy).

Final Office Action received for U.S. Appl. No. 18/774,704, mailed on Jan. 10, 2025, 21 pages.

Intention to Grant received for European Patent Application No. 22731852.4, mailed on Dec. 17, 2024, 9 pages.

International Preliminary Report on Patentability received for PCT Patent Application No. PCT/US2023/024104, mailed on Dec. 19, 2024, 11 pages.

International Preliminary Report on Patentability received for PCT Patent Application No. PCT/US2023/024185, mailed on Dec. 19, 2024, 9 pages.

International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2024/031346, mailed on Dec. 6, 2024, 17 pages.

Invitation to Pay Search Fee received for European Patent Application No. 23735495.6, mailed on Jan. 28, 2025, 5 pages.

Non-Final Office Action received for U.S. Appl. No. 18/592,219, mailed on Jan. 3, 2025, 20 pages.

Notice of Acceptance received for Australian Patent Application No. 2024200284, mailed on Jan. 16, 2025, 3 pages.

Notice of Allowance received for U.S. Appl. No. 17/951,624, mailed on Jan. 15, 2025, 5 pages.

Notice of Allowance received for U.S. Appl. No. 18/135,056, mailed on Jan. 16, 2025, 9 pages.

Office Action received for Australian Patent Application No. 2023214377, mailed on Jan. 17, 2025, 3 pages.

Office Action received for Australian Patent Application No. 2023258443, mailed on Jan. 15, 2025, 4 pages.

Office Action received for Chinese Patent Application No. 202080039364.4, mailed on Jan. 1, 2025, 13 pages (7 pages of English Translation and 6 pages of Official Copy).

Office Action received for Chinese Patent Application No. 202210141337.9, mailed on Dec. 31, 2024, 14 pages (7 pages of English Translation and 7 pages of Official Copy).

Office Action received for European Patent Application No. 23192409.3, mailed on Dec. 10, 2024, 9 pages.

Office Action received for Korean Patent Application No. 10-2024-7013569, mailed on Dec. 16, 2024, 12 pages (5 pages of English Translation and 7 pages of Official Copy).

Supplemental Notice of Allowance received for U.S. Appl. No. 18/589,265, mailed on Dec. 18, 2024, 2 pages.

Decision to Grant received for European Patent Application No. 23153898.4, mailed on Mar. 6, 2025, 4 pages.

(56)

References Cited**OTHER PUBLICATIONS**

Notice of Allowance received for Japanese Patent Application No. 2024-213755, mailed on Mar. 10, 2025, 4 pages (1 page of English Translation and 3 pages of Official Copy).

Notice of Allowance received for Korean Patent Application No. 10-2021-7036242, mailed on Feb. 24, 2025, 7 pages (2 pages of English Translation and 5 pages of Official Copy).

Office Action received for Japanese Patent Application No. 2024-515963, mailed on Mar. 7, 2025, 15 pages (7 pages of English Translation and 8 pages of Official Copy).

Notice of Allowance received for Japanese Patent Application No. 2023-097896, mailed on Jan. 31, 2025, 4 pages (1 page of English Translation and 3 pages of Official Copy).

Notice of Allowance received for Japanese Patent Application No. 2023-168815, mailed on Jan. 31, 2025, 4 pages (1 page of English Translation and 3 pages of Official Copy).

Notice of Allowance received for Korean Patent Application No. 10-2023-0114488, mailed on Jan. 23, 2025, 8 pages (2 pages of English Translation and 6 pages of Official Copy).

Notice of Allowance received for U.S. Appl. No. 18/589,265, mailed on Feb. 18, 2025, 10 pages.

Office Action received for Chinese Patent Application No. 202210140789.5, mailed on Jan. 3, 2025, 15 pages (8 pages of English Translation and 7 pages of Official Copy).

Office Action received for Chinese Patent Application No. 202210151291.9, mailed on Jan. 9, 2025, 29 pages (18 pages of English Translation and 11 pages of Official Copy).

Intention to Grant received for European Patent Application No. 23153900.8, mailed on Apr. 16, 2025, 11 pages.

Office Action received for Japanese Patent Application No. 2025-033114, mailed on May 12, 2025, 4 pages (2 pages of English Translation and 2 pages of Official Copy).

Applicant-Initiated Interview Summary received for U.S. Appl. No. 18/774,704, mailed on Jun. 23, 2025, 2 pages.

Applicant-Initiated Interview Summary received for U.S. Appl. No. 18/789,495, mailed on Jun. 5, 2025, 5 pages.

Board Decision received for Chinese Patent Application No. 201910858933.7, mailed on May 7, 2025, 21 pages (5 pages of English Translation and 16 pages of Official Copy).

Corrected Notice of Allowance received for U.S. Appl. No. 18/774,704, mailed on Jul. 15, 2025, 2 pages.

Decision to Grant received for European Patent Application No. 22731852.4, mailed on Apr. 17, 2025, 3 pages.

Examiner's Answer to Appeal Brief received for U.S. Appl. No. 18/117,998, mailed on May 5, 2025, 15 pages.

Extended European Search Report received for European Patent Application No. 25156484.5, mailed on May 13, 2025, 8 pages.

Extended European Search Report received for European Patent Application No. 25164739.2, mailed on Jun. 2, 2025, 8 pages.

Final Office Action received for U.S. Appl. No. 18/592,219, mailed on Apr. 28, 2025, 22 pages.

Intention to Grant received for European Patent Application No. 23189089.8, mailed on Jul. 2, 2025, 9 pages.

Kordiyak et al., "Analytical Review of Medical Mobile Diagnostic Systems", Econtechmod, An International Quarterly Journal, vol. 05, No. 2, 2016, pp. 11-16.

Non-Final Office Action received for U.S. Appl. No. 18/374,562, mailed on May 19, 2025, 29 pages.

Non-Final Office Action received for U.S. Appl. No. 18/774,704, mailed on May 5, 2025, 20 pages.

Notice of Allowance received for Japanese Patent Application No. 2022-130087, mailed on May 12, 2025, 3 pages (1 page of English Translation and 2 pages of Official Copy).

Notice of Allowance received for Japanese Patent Application No. 2025-033114, mailed on Jun. 16, 2025, 4 pages (1 page of English Translation and 3 pages of Official Copy).

Notice of Allowance received for U.S. Appl. No. 18/774,704, mailed on Jul. 8, 2025, 10 pages.

Notice of Hearing received for Indian Patent Application No. 202117050360, mailed on Jun. 26, 2025, 7 pages.

Office Action received for Australian Patent Application No. 2022352756, mailed on May 14, 2025, 4 pages.

Office Action received for Australian Patent Application No. 2024203043, mailed on May 8, 2025, 2 pages.

Office Action received for European Patent Application No. 23192409.3, mailed on Jun. 24, 2025, 5 pages.

Office Action received for European Patent Application No. 23734424.7, mailed on May 22, 2025, 8 pages.

Office Action received for European Patent Application No. 24152191.3, mailed on Jun. 13, 2025, 6 pages.

Result of Consultation received for European Patent Application No. 23189089.8, mailed on Jun. 2, 2025, 3 pages.

* cited by examiner




FIG. 1A




FIG. 1B




FIG. 2




FIG. 3




FIG. 4A






FIG. 4B

**FIG. 5A**




FIG. 5B




FIG. 6A




FIG. 6B




FIG. 6C




FIG. 6D




FIG. 6E




FIG. 6F




FIG. 6G




FIG. 6H




FIG. 6I




FIG. 6J




FIG. 6K




FIG. 6L




FIG. 6M




FIG. 6N




FIG. 60




FIG. 6P




FIG. 6Q




FIG. 6R




FIG. 6S




FIG. 6T




FIG. 6U




FIG. 6V




FIG. 6W




FIG. 6W1




FIG. 6X




FIG. 6Y




FIG. 6Z




FIG. 6AA




FIG. 6BB




FIG. 6CC




FIG. 6DD




FIG. 6EE




FIG. 7




FIG. 8B

FIG. 8A




FIG. 8C






FIG. 8CI






FIG. 8E




FIG. 8E1




FIG. 8E2




FIG. 8E3




FIG. 8E4




FIG. 8F




FIG. 8G




FIG. 8H




FIG. 8I




FIG. 8J




FIG. 8K




FIG. 8L

FIG. 8M




FIG. 8M1




FIG. 8M2




FIG. 8M3




FIG. 8N




FIG. 8O




FIG. 8P





FIG. 8Q

**FIG. 8Q1**




FIG. 8R





FIG. 8Q2






FIG. 9




FIG. 10A





FIG. 10B




FIG. 10C





FIG. 10D




FIG. 10E





FIG. 10F





FIG. 10G





FIG. 10G1





FIG. 10G2





FIG. 10G3




FIG. 10H





FIG. 101





FIG. 10J





FIG. 10K





FIG. 10L





FIG. 10M





FIG. 10M1





FIG. 10M2





FIG. 10M3





FIG. 10M4





FIG. 10N





FIG. 100




FIG. 10P





FIG. 10Q





FIG. 10R






FIG. 105






FIG. 10U




FIG. 10V




FIG. 11




FIG. 12A




FIG. 12B




FIG. 12C




FIG. 12D




FIG. 12E




FIG. 12F




FIG. 12G




FIG. 12H




FIG. 12I




FIG. 12J




FIG. 12K




FIG. 12L




FIG. 12M




FIG. 12N




FIG. 120




FIG. 13





FIG. 14A







FIG. 14C






FIG. 14E




FIG. 14F




FIG. 14G




FIG. 14H




FIG. 14I





FIG. 14J






FIG. 14L




FIG. 14M




FIG. 14N




FIG. 140




FIG. 14P




FIG. 14Q




FIG. 14R





FIG. 15






FIG. 16B




FIG. 16C




FIG. 16D




FIG. 16E




FIG. 16F




FIG. 16G




FIG. 16H




FIG. 161




FIG. 16J




FIG. 16K




FIG. 16L




FIG. 16M




FIG. 16N




FIG. 160




FIG. 16P




FIG. 16Q




FIG. 16R





FIG. 17A

**FIG. 17B**




FIG. 18A




FIG. 18B




FIG. 18C




FIG. 18D




FIG. 18E




FIG. 18F




FIG. 18G




FIG. 18H





FIG. 181






FIG. 18K




FIG. 18L





FIG. 18M






FIG. 180




FIG. 18P




FIG. 18Q




FIG. 18R




FIG. 18S




FIG. 18T




FIG. 18U




FIG. 18V




FIG. 19A





FIG. 19B

*FIG. 19C*

1

USER INTERFACES FOR WORKOUT CONTENT

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 17/951,976, entitled “USER INTERFACES FOR WORKOUT CONTENT”, filed Sep. 23, 2022, which is a continuation of U.S. patent application Ser. No. 17/030,337, entitled “USER INTERFACES FOR WORKOUT CONTENT”, filed Sep. 23, 2020, which claims priority to U.S. Provisional patent application Ser. No. 63/078,311, entitled “USER INTERFACES FOR WORKOUT VIDEO CONTENT”, filed Sep. 14, 2020; U.S. Provisional patent application Ser. No. 63/036,374, entitled “USER INTERFACES FOR WORKOUT VIDEO CONTENT”, filed Jun. 8, 2020; and U.S. Provisional patent application Ser. No. 62/977,076, entitled “USER INTERFACES FOR WORKOUT CONTENT”, filed Feb. 14, 2020, the contents of which are hereby incorporated by reference in their entirety.

FIELD

The present disclosure relates generally to computer user interfaces, and more specifically to techniques for navigating and outputting workout content.

BACKGROUND

As electronic devices, such as smartphones have become more widely used, their functions have grown beyond phone calls and text messaging. Providing an efficient method for using and implementing the various functions on these electronic devices can be complex and time-consuming.

BRIEF SUMMARY

As used herein, workout content refers to audio and/or video content that guides a user to perform a physical activity. Some techniques for navigating and outputting workout content using electronic devices, however, are generally cumbersome and inefficient. For example, some existing techniques use a complex and time-consuming user interface, which may include multiple key presses or keystrokes. Existing techniques require more time than necessary, wasting user time and device energy. This latter consideration is particularly important in battery-operated devices. As another example, some existing techniques for coordinating display of workout content among multiple devices are not intuitive and thus lead to erroneous inputs or require multiple key presses or keystrokes. Existing techniques require more time than necessary, wasting user time and device energy. This latter consideration is particularly important in battery-operated devices.

Accordingly, the present techniques provide electronic devices with faster, more efficient methods and interfaces for navigating and outputting workout content. Such methods and interfaces optionally complement or replace other methods for navigating and outputting workout content. Such methods and interfaces reduce the cognitive burden on a user and produce a more efficient human-machine interface. For battery-operated computing devices, such methods and interfaces conserve power and increase the time between battery charges.

In some embodiments, a method comprises: at an electronic device with a display: displaying, on the display, a

2

selectable user interface object for displaying workout suggestions; detecting a user input corresponding to the selectable user interface object for displaying workout suggestions; and in response to detecting the user input corresponding to the selectable user interface object for displaying workout suggestions, displaying, on the display, a user interface for displaying workout suggestions that includes concurrently displaying: a plurality of selectable options that includes a first option that, when selected, causes the electronic device to initiate a process for displaying workout suggestions that share a first common workout parameter and a second option that, when selected, causes the electronic device to initiate a process for displaying workout suggestions that share a second common workout parameter; and a plurality of workout suggestions, wherein the plurality of workout suggestions are selected for display based on a workout history of a user of the electronic device.

In some embodiments, a non-transitory computer-readable storage medium stores one or more programs configured to be executed by one or more processors of an electronic device with a display, the one or more programs including instructions for: displaying, on the display, a selectable user interface object for displaying workout suggestions; detecting a user input corresponding to the selectable user interface object for displaying workout suggestions; and in response to detecting the user input corresponding to the selectable user interface object for displaying workout suggestions, displaying, on the display, a user interface for displaying workout suggestions that includes concurrently displaying: a plurality of selectable options that includes a first option that, when selected, causes the electronic device to initiate a process for displaying workout suggestions that share a first common workout parameter and a second option that, when selected, causes the electronic device to initiate a process for displaying workout suggestions that share a second common workout parameter; and a plurality of workout suggestions, wherein the plurality of workout suggestions are selected for display based on a workout history of a user of the electronic device.

In some embodiments, a transitory computer-readable storage medium stores one or more programs configured to be executed by one or more processors of an electronic device with a display, the one or more programs including instructions for: displaying, on the display, a selectable user interface object for displaying workout suggestions; detecting a user input corresponding to the selectable user interface object for displaying workout suggestions; and in response to detecting the user input corresponding to the selectable user interface object for displaying workout suggestions, displaying, on the display, a user interface for displaying workout suggestions that includes concurrently displaying: a plurality of selectable options that includes a first option that, when selected, causes the electronic device to initiate a process for displaying workout suggestions that share a first common workout parameter and a second option that, when selected, causes the electronic device to initiate a process for displaying workout suggestions that share a second common workout parameter; and a plurality of workout suggestions, wherein the plurality of workout suggestions are selected for display based on a workout history of a user of the electronic device.

In some embodiments, an electronic device comprises: a display; one or more processors; and memory storing one or more programs configured to be executed by the one or more processors, the one or more programs including instructions for: displaying, on the display, a selectable user interface object for displaying workout suggestions; detecting a user

3

input corresponding to the selectable user interface object for displaying workout suggestions; and in response to detecting the user input corresponding to the selectable user interface object for displaying workout suggestions, displaying, on the display, a user interface for displaying workout suggestions that includes concurrently displaying: a plurality of selectable options that includes a first option that, when selected, causes the electronic device to initiate a process for displaying workout suggestions that share a first common workout parameter and a second option that, when selected, causes the electronic device to initiate a process for displaying workout suggestions that share a second common workout parameter; and a plurality of workout suggestions, wherein the plurality of workout suggestions are selected for display based on a workout history of a user of the electronic device.

In some embodiments, an electronic device comprises: a display; means for displaying, on the display, a selectable user interface object for displaying workout suggestions; means for detecting a user input corresponding to the selectable user interface object for displaying workout suggestions; and means, in response to detecting the user input corresponding to the selectable user interface object for displaying workout suggestions, for displaying, on the display, a user interface for displaying workout suggestions that includes concurrently displaying: a plurality of selectable options that includes a first option that, when selected, causes the electronic device to initiate a process for displaying workout suggestions that share a first common workout parameter and a second option that, when selected, causes the electronic device to initiate a process for displaying workout suggestions that share a second common workout parameter; and a plurality of workout suggestions, wherein the plurality of workout suggestions are selected for display based on a workout history of a user of the electronic device.

In some embodiments, a method comprises: at an electronic device with a display: displaying, on the display, a selectable user interface object for starting audio playback; detecting a user input corresponding to selection of the selectable user interface object for starting audio playback; and in response to detecting the user input corresponding to selection of the selectable user interface object for starting audio playback: causing audio playback of audio associated with a workout at an audio output device that is in communication with the electronic device; and causing recording of physical activity metrics corresponding to the workout, wherein the physical activity metrics are recorded by one or more sensors that are monitoring an activity level of a user of the electronic device.

In some embodiments, a non-transitory computer-readable storage medium stores one or more programs configured to be executed by one or more processors of an electronic device with a display, the one or more programs including instructions for: displaying, on the display, a selectable user interface object for starting audio playback; detecting a user input corresponding to selection of the selectable user interface object for starting audio playback; and in response to detecting the user input corresponding to selection of the selectable user interface object for starting audio playback: causing audio playback of audio associated with a workout at an audio output device that is in communication with the electronic device; and causing recording of physical activity metrics corresponding to the workout, wherein the physical activity metrics are recorded by one or more sensors that are monitoring an activity level of a user of the electronic device.

4

In some embodiments, a transitory computer-readable storage medium stores one or more programs configured to be executed by one or more processors of an electronic device with a display, the one or more programs including instructions for: displaying, on the display, a selectable user interface object for starting audio playback; detecting a user input corresponding to selection of the selectable user interface object for starting audio playback; and in response to detecting the user input corresponding to selection of the selectable user interface object for starting audio playback: causing audio playback of audio associated with a workout at an audio output device that is in communication with the electronic device; and causing recording of physical activity metrics corresponding to the workout, wherein the physical activity metrics are recorded by one or more sensors that are monitoring an activity level of a user of the electronic device.

In some embodiments, an electronic device comprises: a display; one or more processors; and memory storing one or more programs configured to be executed by the one or more processors, the one or more programs including instructions for: displaying, on the display, a selectable user interface object for starting audio playback; detecting a user input corresponding to selection of the selectable user interface object for starting audio playback; and in response to detecting the user input corresponding to selection of the selectable user interface object for starting audio playback: causing audio playback of audio associated with a workout at an audio output device that is in communication with the electronic device; and causing recording of physical activity metrics corresponding to the workout, wherein the physical activity metrics are recorded by one or more sensors that are monitoring an activity level of a user of the electronic device.

In some embodiments, an electronic device comprises: a display; means for displaying, on the display, a selectable user interface object for starting audio playback; means for detecting a user input corresponding to selection of the selectable user interface object for starting audio playback; and means, in response to detecting the user input corresponding to selection of the selectable user interface object for starting audio playback, for: causing audio playback of audio associated with a workout at an audio output device that is in communication with the electronic device; and causing recording of physical activity metrics corresponding to the workout, wherein the physical activity metrics are recorded by one or more sensors that are monitoring an activity level of a user of the electronic device.

In some embodiments, a method comprises: at an electronic device: causing concurrent display, via a display device, of video content and one or more representations of physical activity metrics corresponding to a user, wherein: the one or more representations of the physical activity metrics correspond to a predetermined amount of time that includes a period of time preceding playback of the content, and the one or more representations of the physical activity metrics are overlaid on the video content; and while continuing to cause display of the video content: receiving activity data based on physical activity of the user during the display of the video content; and in response to receiving the activity data, updating the display of the one or more representations of the physical activity metrics based on the received activity data.

In some embodiments, a non-transitory computer-readable storage medium stores one or more programs configured to be executed by one or more processors of an electronic device, the one or more programs including

5

instructions for: causing concurrent display, via a display device, of video content and one or more representations of physical activity metrics corresponding to a user, wherein: the one or more representations of the physical activity metrics correspond to a predetermined amount of time that includes a period of time preceding playback of the content, and the one or more representations of the physical activity metrics are overlaid on the video content; and while continuing to cause display of the video content: receiving activity data based on physical activity of the user during the display of the video content; and in response to receiving the activity data, updating the display of the one or more representations of the physical activity metrics based on the received activity data.

In some embodiments, a transitory computer-readable storage medium stores one or more programs configured to be executed by one or more processors of an electronic device, the one or more programs including instructions for: causing concurrent display, via a display device, of video content and one or more representations of physical activity metrics corresponding to a user, wherein: the one or more representations of the physical activity metrics correspond to a predetermined amount of time that includes a period of time preceding playback of the content, and the one or more representations of the physical activity metrics are overlaid on the video content; and while continuing to cause display of the video content: receiving activity data based on physical activity of the user during the display of the video content; and in response to receiving the activity data, updating the display of the one or more representations of the physical activity metrics based on the received activity data.

In some embodiments, an electronic device comprises: one or more processors; and memory storing one or more programs configured to be executed by the one or more processors, the one or more programs including instructions for: causing concurrent display, via a display device, of video content and one or more representations of physical activity metrics corresponding to a user, wherein: the one or more representations of the physical activity metrics correspond to a predetermined amount of time that includes a period of time preceding playback of the content, and the one or more representations of the physical activity metrics are overlaid on the video content; and while continuing to cause display of the video content: receiving activity data based on physical activity of the user during the display of the video content; and in response to receiving the activity data, updating the display of the one or more representations of the physical activity metrics based on the received activity data.

In some embodiments, an electronic device comprises: means for causing concurrent display, via a display device, of video content and one or more representations of physical activity metrics corresponding to a user, wherein: the one or more representations of the physical activity metrics correspond to a predetermined amount of time that includes a period of time preceding playback of the content, and the one or more representations of the physical activity metrics are overlaid on the video content; and means, while continuing to cause display of the video content, for: receiving activity data based on physical activity of the user during the display of the video content; and in response to receiving the activity data, updating the display of the one or more representations of the physical activity metrics based on the received activity data.

In some embodiments, a method comprises: at an electronic device: causing concurrent display, via a display

6

device, of: video content; and a workout intensity representation, wherein the workout intensity representation has a visual characteristic based on a comparison between a physical activity metric for a user of the electronic device that corresponds to a first playback position of the video content and the physical activity metric for a group of users who participated in a workout while watching the video content based on the physical activity of the group of users that corresponds to the first playback position of the video content; after the video has advanced from the first playback position to a second playback position, receiving activity data corresponding to the physical activity metric for the user; and in response to receiving the activity data, causing display, via the display device, of the workout intensity representation with the visual characteristic of the workout intensity representation changed based on the received activity data and based on a comparison between the physical activity metric for the user of the electronic device that corresponds to the second playback position of the video content and the physical activity metric for a group of users that corresponds to the second playback position of the video content.

In some embodiments, a non-transitory computer-readable storage medium stores one or more programs configured to be executed by one or more processors of an electronic device, the one or more programs including instructions for: causing concurrent display, via a display device, of: video content; and a workout intensity representation, wherein the workout intensity representation has a visual characteristic based on a comparison between a physical activity metric for a user of the electronic device that corresponds to a first playback position of the video content and the physical activity metric for a group of users who participated in a workout while watching the video content based on the physical activity of the group of users that corresponds to the first playback position of the video content; after the video has advanced from the first playback position to a second playback position, receiving activity data corresponding to the physical activity metric for the user; and in response to receiving the activity data, causing display, via the display device, of the workout intensity representation with the visual characteristic of the workout intensity representation changed based on the received activity data and based on a comparison between the physical activity metric for the user of the electronic device that corresponds to the second playback position of the video content and the physical activity metric for a group of users that corresponds to the second playback position of the video content.

In some embodiments, a transitory computer-readable storage medium stores one or more programs configured to be executed by one or more processors of an electronic device, the one or more programs including instructions for: causing concurrent display, via a display device, of: video content; and a workout intensity representation, wherein the workout intensity representation has a visual characteristic based on a comparison between a physical activity metric for a user of the electronic device that corresponds to a first playback position of the video content and the physical activity metric for a group of users who participated in a workout while watching the video content based on the physical activity of the group of users that corresponds to the first playback position of the video content; after the video has advanced from the first playback position to a second playback position, receiving activity data corresponding to the physical activity metric for the user; and in response to receiving the activity data, causing display, via the display

device, of the workout intensity representation with the visual characteristic of the workout intensity representation changed based on the received activity data and based on a comparison between the physical activity metric for the user of the electronic device that corresponds to the second playback position of the video content and the physical activity metric for a group of users that corresponds to the second playback position of the video content.

In some embodiments, an electronic device comprises: one or more processors; and memory storing one or more programs configured to be executed by the one or more processors, the one or more programs including instructions for: causing concurrent display, via a display device, of: video content; and a workout intensity representation, wherein the workout intensity representation has a visual characteristic based on a comparison between a physical activity metric for a user of the electronic device that corresponds to a first playback position of the video content and the physical activity metric for a group of users who participated in a workout while watching the video content based on the physical activity of the group of users that corresponds to the first playback position of the video content; after the video has advanced from the first playback position to a second playback position, receiving activity data corresponding to the physical activity metric for the user; and in response to receiving the activity data, causing display, via the display device, of the workout intensity representation changed based on the received activity data and based on a comparison between the physical activity metric for the user of the electronic device that corresponds to the second playback position of the video content and the physical activity metric for a group of users that corresponds to the second playback position of the video content.

In some embodiments, an electronic device comprises: means for causing concurrent display, via a display device, of: video content; and a workout intensity representation, wherein the workout intensity representation has a visual characteristic based on a comparison between a physical activity metric for a user of the electronic device that corresponds to a first playback position of the video content and the physical activity metric for a group of users who participated in a workout while watching the video content based on the physical activity of the group of users that corresponds to the first playback position of the video content; means, after the video has advanced from the first playback position to a second playback position, for receiving activity data corresponding to the physical activity metric for the user; and means, in response to receiving the activity data, for causing display, via the display device, of the workout intensity representation with the visual characteristic of the workout intensity representation changed based on the received activity data and based on a comparison between the physical activity metric for the user of the electronic device that corresponds to the second playback position of the video content and the physical activity metric for a group of users that corresponds to the second playback position of the video content.

In some embodiments, a method comprises: at an electronic device with a display, wherein the electronic device is in communication with a first external device and a second external device: displaying, on the display of the electronic device, a user interface corresponding to video content including a first selectable user interface object for enabling display of an activity session user interface associated with the video content on a display device that is in communi-

cation with the first external device; detecting a first sequence of one or more user inputs including selection of the first selectable user interface object; in response to detecting the first sequence of one or more user inputs including selection of the first selectable user interface object: causing the display device that is in communication with the first external device to display a first graphical user interface that is associated with the activity session; and while the display device is displaying the first graphical user interface that is associated with the activity session, a display device that is in communication with the second external device displays a second graphical user interface that is associated with starting the activity session and is different from the first graphical user interface, wherein a selection input directed to a portion of the second graphical user interface causes the display device that is in communication with the first external device to display an activity session user interface associated with the video content.

In some embodiments, a non-transitory computer-readable storage medium stores one or more programs configured to be executed by one or more processors of an electronic device with a display, the one or more programs including instructions for: displaying, on the display of the electronic device, a user interface corresponding to video content including a first selectable user interface object for enabling display of an activity session user interface associated with the video content on a display device that is in communication with the first external device, wherein the electronic device is in communication with a first external device and a second external device; detecting a first sequence of one or more user inputs including selection of the first selectable user interface object; in response to detecting the first sequence of one or more user inputs including selection of the first selectable user interface object: causing the display device that is in communication with the first external device to display a first graphical user interface that is associated with the activity session; and while the display device is displaying the first graphical user interface that is associated with the activity session, a display device that is in communication with the second external device displays a second graphical user interface that is associated with starting the activity session and is different from the first graphical user interface, wherein a selection input directed to a portion of the second graphical user interface causes the display device that is in communication with the first external device to display an activity session user interface associated with the video content.

In some embodiments, a transitory computer-readable storage medium stores one or more programs configured to be executed by one or more processors of an electronic device with a display, the one or more programs including instructions for: displaying, on the display of the electronic device, a user interface corresponding to video content including a first selectable user interface object for enabling display of an activity session user interface associated with the video content on a display device that is in communication with the first external device, wherein the electronic device is in communication with a first external device and a second external device; detecting a first sequence of one or more user inputs including selection of the first selectable user interface object; in response to detecting the first sequence of one or more user inputs including selection of the first selectable user interface object: causing the display device that is in communication with the first external device to display a first graphical user interface that is associated with the activity session; and while the display device is displaying the first graphical user interface that is associated

with the activity session, a display device that is in communication with the second external device displays a second graphical user interface that is associated with starting the activity session and is different from the first graphical user interface, wherein a selection input directed to a portion of the second graphical user interface causes the display device that is in communication with the first external device to display an activity session user interface associated with the video content.

In some embodiments, an electronic device comprises: a display; one or more processors; and memory storing one or more programs configured to be executed by the one or more processors of the electronic device, the one or more programs including instructions for: displaying, on the display of the electronic device, a user interface corresponding to video content including a first selectable user interface object for enabling display of an activity session user interface associated with the video content on a display device that is in communication with the first external device, wherein the electronic device is in communication with a first external device and a second external device; detecting a first sequence of one or more user inputs including selection of the first selectable user interface object; in response to detecting the first sequence of one or more user inputs including selection of the first selectable user interface object: causing the display device that is in communication with the first external device to display a first graphical user interface that is associated with the activity session; and while the display device is displaying the first graphical user interface that is associated with the activity session, a display device that is in communication with the second external device displays a second graphical user interface that is associated with starting the activity session and is different from the first graphical user interface, wherein a selection input directed to a portion of the second graphical user interface causes the display device that is in communication with the first external device to display an activity session user interface associated with the video content.

In some embodiments, an electronic device comprises: a display; means for displaying, on the display of the electronic device, a user interface corresponding to video content including a first selectable user interface object for enabling display of an activity session user interface associated with the video content on a display device that is in communication with the first external device, wherein the electronic device is in communication with a first external device and a second external device; means for detecting a first sequence of one or more user inputs including selection of the first selectable user interface object; means, in response to detecting the first sequence of one or more user inputs including selection of the first selectable user interface object, for: causing the display device that is in communication with the first external device to display a first graphical user interface that is associated with the activity session; and while the display device is displaying the first graphical user interface that is associated with the activity session, a display device that is in communication with the second external device displays a second graphical user interface that is associated with starting the activity session and is different from the first graphical user interface, wherein a selection input directed to a portion of the second graphical user interface causes the display device that is in communication with the first external device to display an activity session user interface associated with the video content.

In some embodiments, a method comprises: at a computer system that is in communication with a display generation

component and one or more input devices: causing display, via the display generation component, of a user interface, wherein the user interface includes: a plurality of workout suggestions displayed in a first region of the user interface, and one or more filtering options for filtering workout suggestions displayed concurrently with the plurality of workout suggestions; detecting, via the one or more input devices, a first user input directed to a first filtering option of the one or more filtering options; in accordance with a determination that the first user input directed to the first filtering option has been maintained for at least a predefined period of time: ceasing to display at least a portion of the plurality of workout suggestions within the first region of the user interface, so that the first region of the user interface includes a first subset of workout suggestions from the plurality of workout suggestions that are associated with the first filtering option and does not include workout suggestions that are not associated with the first filtering option; while the first subset of workout suggestions is displayed in the first region of the user interface, detecting, via the one or more input devices, a second user input corresponding to navigation to a first workout suggestion of the first subset of workout suggestions; and in response to detecting the second user input, causing display, via the display generation component, of a visual indication that the input is directed to the first workout suggestion while display of the first subset of workout suggestions is maintained in the first region of the user interface.

In some embodiments, a non-transitory computer-readable storage medium stores one or more programs configured to be executed by one or more processors of a computer system that is in communication with a display generation component and one or more input devices, the one or more programs including instructions for: causing display, via the display generation component, of a user interface, wherein the user interface includes: a plurality of workout suggestions displayed in a first region of the user interface, and one or more filtering options for filtering workout suggestions displayed concurrently with the plurality of workout suggestions; detecting, via the one or more input devices, a first user input directed to a first filtering option of the one or more filtering options; in accordance with a determination that the first user input directed to the first filtering option has been maintained for at least a predefined period of time: ceasing to display at least a portion of the plurality of workout suggestions within the first region of the user interface, so that the first region of the user interface includes a first subset of workout suggestions from the plurality of workout suggestions that are associated with the first filtering option and does not include workout suggestions that are not associated with the first filtering option; while the first subset of workout suggestions is displayed in the first region of the user interface, detecting, via the one or more input devices, a second user input corresponding to navigation to a first workout suggestion of the first subset of workout suggestions; and in response to detecting the second user input, causing display, via the display generation component, of a visual indication that the input is directed to the first workout suggestion while display of the first subset of workout suggestions is maintained in the first region of the user interface.

In some embodiments, a transitory computer-readable storage medium stores one or more programs configured to be executed by one or more processors of a computer system that is in communication with a display generation component and one or more input devices, the one or more programs including instructions for: causing display, via the

11

display generation component, of a user interface, wherein the user interface includes: a plurality of workout suggestions displayed in a first region of the user interface, and one or more filtering options for filtering workout suggestions displayed concurrently with the plurality of workout suggestions; detecting, via the one or more input devices, a first user input directed to a first filtering option of the one or more filtering options; in accordance with a determination that the first user input directed to the first filtering option has been maintained for at least a predefined period of time: ceasing to display at least a portion of the plurality of workout suggestions within the first region of the user interface, so that the first region of the user interface includes a first subset of workout suggestions from the plurality of workout suggestions that are associated with the first filtering option and does not include workout suggestions that are not associated with the first filtering option; while the first subset of workout suggestions is displayed in the first region of the user interface, detecting, via the one or more input devices, a second user input corresponding to navigation to a first workout suggestion of the first subset of workout suggestions; and in response to detecting the second user input, causing display, via the display generation component, of a visual indication that the input is directed to the first workout suggestion while display of the first subset of workout suggestions is maintained in the first region of the user interface.

In some embodiments, a computer system comprises: one or more processors, wherein the computer system is in communication with a display generation component and one or more input devices; and memory storing one or more programs configured to be executed by the one or more processors, the one or more programs including instructions for: causing display, via the display generation component, of a user interface, wherein the user interface includes: a plurality of workout suggestions displayed in a first region of the user interface, and one or more filtering options for filtering workout suggestions displayed concurrently with the plurality of workout suggestions; detecting, via the one or more input devices, a first user input directed to a first filtering option of the one or more filtering options; in accordance with a determination that the first user input directed to the first filtering option has been maintained for at least a predefined period of time: ceasing to display at least a portion of the plurality of workout suggestions within the first region of the user interface, so that the first region of the user interface includes a first subset of workout suggestions from the plurality of workout suggestions that are associated with the first filtering option and does not include workout suggestions that are not associated with the first filtering option; while the first subset of workout suggestions is displayed in the first region of the user interface, detecting, via the one or more input devices, a second user input corresponding to navigation to a first workout suggestion of the first subset of workout suggestions; and in response to detecting the second user input, causing display, via the display generation component, of a visual indication that the input is directed to the first workout suggestion while display of the first subset of workout suggestions is maintained in the first region of the user interface.

In some embodiments, a computer system comprises: means for causing display, via a display generation component, of a user interface, wherein the user interface includes: a plurality of workout suggestions displayed in a first region of the user interface, and one or more filtering options for filtering workout suggestions displayed concurrently with

12

the plurality of workout suggestions; means for detecting, via one or more input devices, a first user input directed to a first filtering option of the one or more filtering options; means for, in accordance with a determination that the first user input directed to the first filtering option has been maintained for at least a predefined period of time: ceasing to display at least a portion of the plurality of workout suggestions within the first region of the user interface, so that the first region of the user interface includes a first subset of workout suggestions from the plurality of workout suggestions that are associated with the first filtering option and does not include workout suggestions that are not associated with the first filtering option; means for, while the first subset of workout suggestions is displayed in the first region of the user interface, detecting, via the one or more input devices, a second user input corresponding to navigation to a first workout suggestion of the first subset of workout suggestions; and means for, in response to detecting the second user input, causing display, via the display generation component, of a visual indication that the input is directed to the first workout suggestion while display of the first subset of workout suggestions is maintained in the first region of the user interface.

In some embodiments, a method comprises: at a computer system that is in communication with a display generation component and one or more input devices: detecting, via the one or more input devices, a user input corresponding to a request to display a workout user interface; and in response to the request to display the workout user interface: in accordance with a determination that the computer system meets proximity criteria relative to a single external electronic device of a first type: initiating a process to display, via the display generation component, a first workout suggestion user interface, wherein the first workout suggestion user interface displays one or more workout suggestions associated with the single external electronic device, and in accordance with a determination that the computer system meets proximity criteria relative to at least a first external electronic device of the first type and a second external electronic device of the first type: initiating a process to display, via the display generation component, a disambiguation user interface different from the first workout suggestion user interface, wherein the disambiguation user interface includes: a first selectable user interface object that, when selected, initiates a process for displaying a second workout suggestion user interface associated with the first external electronic device, wherein the second workout suggestion user interface displays one or more workout suggestions associated with the first external electronic device, and a second selectable user interface object that, when selected, initiates a process for displaying a third workout suggestion user interface different from the second workout suggestion user interface and associated with the second external electronic device, wherein the third workout suggestion user interface displays one or more workout suggestions associated with the second external electronic device.

In some embodiments, a non-transitory computer-readable storage medium stores one or more programs configured to be executed by one or more processors of a computer system that is in communication with a display generation component and one or more input devices, the one or more programs including instructions for: detecting, via the one or more input devices, a user input corresponding to a request to display a workout user interface; and in response to the request to display the workout user interface: in accordance with a determination that the computer system meets prox-

13

imity criteria relative to a single external electronic device of a first type: initiating a process to display, via the display generation component, a first workout suggestion user interface, wherein the first workout suggestion user interface displays one or more workout suggestions associated with the single external electronic device, and in accordance with a determination that the computer system meets proximity criteria relative to at least a first external electronic device of the first type and a second external electronic device of the first type: initiating a process to display, via the display generation component, a disambiguation user interface different from the first workout suggestion user interface, wherein the disambiguation user interface includes: a first selectable user interface object that, when selected, initiates a process for displaying a second workout suggestion user interface associated with the first external electronic device, wherein the second workout suggestion user interface displays one or more workout suggestions associated with the first external electronic device, and a second selectable user interface object that, when selected, initiates a process for displaying a third workout suggestion user interface different from the second workout suggestion user interface and associated with the second external electronic device, wherein the third workout suggestion user interface displays one or more workout suggestions associated with the second external electronic device.

In some embodiments, a transitory computer-readable storage medium stores one or more programs configured to be executed by one or more processors of a computer system that is in communication with a display generation component and one or more input devices, the one or more programs including instructions for: detecting, via the one or more input devices, a user input corresponding to a request to display a workout user interface; and in response to the request to display the workout user interface: in accordance with a determination that the computer system meets proximity criteria relative to a single external electronic device of a first type: initiating a process to display, via the display generation component, a first workout suggestion user interface, wherein the first workout suggestion user interface displays one or more workout suggestions associated with the single external electronic device, and in accordance with a determination that the computer system meets proximity criteria relative to at least a first external electronic device of the first type and a second external electronic device of the first type: initiating a process to display, via the display generation component, a disambiguation user interface different from the first workout suggestion user interface, wherein the disambiguation user interface includes: a first selectable user interface object that, when selected, initiates a process for displaying a second workout suggestion user interface associated with the first external electronic device, wherein the second workout suggestion user interface displays one or more workout suggestions associated with the first external electronic device, and a second selectable user interface object that, when selected, initiates a process for displaying a third workout suggestion user interface different from the second workout suggestion user interface and associated with the second external electronic device, wherein the third workout suggestion user interface displays one or more workout suggestions associated with the second external electronic device.

In some embodiments, a computer system comprises: one or more processors, wherein the computer system is in communication with a display generation component and one or more input devices; and memory storing one or more programs configured to be executed by the one or more

14

processors, the one or more programs including instructions for: detecting, via the one or more input devices, a user input corresponding to a request to display a workout user interface; and in response to the request to display the workout user interface: in accordance with a determination that the computer system meets proximity criteria relative to a single external electronic device of a first type: initiating a process to display, via the display generation component, a first workout suggestion user interface, wherein the first workout suggestion user interface displays one or more workout suggestions associated with the single external electronic device, and in accordance with a determination that the computer system meets proximity criteria relative to at least a first external electronic device of the first type and a second external electronic device of the first type: initiating a process to display, via the display generation component, a disambiguation user interface different from the first workout suggestion user interface, wherein the disambiguation user interface includes: a first selectable user interface object that, when selected, initiates a process for displaying a second workout suggestion user interface associated with the first external electronic device, wherein the second workout suggestion user interface displays one or more workout suggestions associated with the first external electronic device, and a second selectable user interface object that, when selected, initiates a process for displaying a third workout suggestion user interface different from the second workout suggestion user interface and associated with the second external electronic device, wherein the third workout suggestion user interface displays one or more workout suggestions associated with the second external electronic device.

In some embodiments, a computer system comprises: means for detecting, via one or more input devices, a user input corresponding to a request to display a workout user interface; and means for, in response to the request to display the workout user interface: in accordance with a determination that the computer system meets proximity criteria relative to a single external electronic device of a first type: initiating a process to display, via a display generation component, a first workout suggestion user interface, wherein the first workout suggestion user interface displays one or more workout suggestions associated with the single external electronic device, and in accordance with a determination that the computer system meets proximity criteria relative to at least a first external electronic device of the first type and a second external electronic device of the first type: initiating a process to display, via the display generation component, a disambiguation user interface different from the first workout suggestion user interface, wherein the disambiguation user interface includes: a first selectable user interface object that, when selected, initiates a process for displaying a second workout suggestion user interface associated with the first external electronic device, wherein the second workout suggestion user interface displays one or more workout suggestions associated with the first external electronic device, and a second selectable user interface object that, when selected, initiates a process for displaying a third workout suggestion user interface different from the second workout suggestion user interface and associated with the second external electronic device, wherein the third workout suggestion user interface displays one or more workout suggestions associated with the second external electronic device.

Executable instructions for performing these functions are, optionally, included in a non-transitory computer-readable storage medium or other computer program product

15

configured for execution by one or more processors. Executable instructions for performing these functions are, optionally, included in a transitory computer-readable storage medium or other computer program product configured for execution by one or more processors.

Thus, devices are provided with faster, more efficient methods and interfaces for navigating and outputting workout content, thereby increasing the effectiveness, efficiency, and user satisfaction with such devices. Such methods and interfaces may complement or replace other methods for navigating and outputting workout content.

DESCRIPTION OF THE FIGURES

For a better understanding of the various described embodiments, reference should be made to the Description of Embodiments below, in conjunction with the following drawings in which like reference numerals refer to corresponding parts throughout the figures.

FIG. 1A is a block diagram illustrating a portable multifunction device with a touch-sensitive display in accordance with some embodiments.

FIG. 1B is a block diagram illustrating exemplary components for event handling in accordance with some embodiments.

FIG. 2 illustrates a portable multifunction device having a touch screen in accordance with some embodiments.

FIG. 3 is a block diagram of an exemplary multifunction device with a display and a touch-sensitive surface in accordance with some embodiments.

FIG. 4A illustrates an exemplary user interface for a menu of applications on a portable multifunction device in accordance with some embodiments.

FIG. 4B illustrates an exemplary user interface for a multifunction device with a touch-sensitive surface that is separate from the display in accordance with some embodiments.

FIG. 5A illustrates a personal electronic device in accordance with some embodiments.

FIG. 5B is a block diagram illustrating a personal electronic device in accordance with some embodiments.

FIGS. 6A-6EE illustrate exemplary user interfaces for displaying personalized workout suggestions based on completed workouts, in accordance with some embodiments.

FIG. 7 is a flow diagram illustrating an exemplary process for displaying personalized workout suggestions based on completed workouts, in accordance with some embodiments.

FIGS. 8A-8S illustrate exemplary user interfaces for starting an audio-based workout, in accordance with some embodiments.

FIG. 9 is a flow diagram illustrating an exemplary process for starting an audio-based workout, in accordance with some embodiments.

FIGS. 10A-10V illustrate exemplary user interfaces for displaying workout information, in accordance with some embodiments.

FIG. 11 is a flow diagram illustrating an exemplary process for displaying workout information, in accordance with some embodiments.

FIGS. 12A-12O illustrate exemplary user interfaces for displaying workout information, in accordance with some embodiments.

FIG. 13 is a flow diagram illustrating an exemplary process for displaying workout information, in accordance with some embodiments.

16

FIGS. 14A-14R illustrate exemplary user interfaces for coordinating display of workout content among multiple devices, in accordance with some embodiments.

FIG. 15 is a flow diagram illustrating an exemplary process for coordinating display of workout content among multiple devices, in accordance with some embodiments.

FIGS. 16A-16R illustrate exemplary user interfaces for displaying workout information, in accordance with some embodiments.

FIGS. 17A-17B are a flow diagram illustrating an exemplary process for displaying workout information, in accordance with some embodiments.

FIGS. 18A-18V illustrate exemplary user interfaces for displaying workout information, in accordance with some embodiments.

FIGS. 19A-19C are a flow diagram illustrating an exemplary process for displaying workout information, in accordance with some embodiments.

DESCRIPTION OF EMBODIMENTS

The following description sets forth exemplary methods, parameters, and the like. It should be recognized, however, that such description is not intended as a limitation on the scope of the present disclosure but is instead provided as a description of exemplary embodiments.

There is a need for electronic devices that provide efficient methods and interfaces for navigating and outputting workout content. For example, a user would benefit from being shown particular workout suggestions that correspond to completed workouts. As another example, a user would benefit from being shown certain workouts metrics while workout content is outputted. Such techniques can reduce the cognitive burden on a user who navigates and outputting workout content, thereby enhancing productivity. Further, such techniques can reduce processor and battery power otherwise wasted on redundant user inputs.

Below, FIGS. 1A-1B, 2, 3, 4A-4B, and 5A-5B provide a description of exemplary devices for performing the techniques for managing event notifications. FIGS. 6A-6EE illustrate exemplary user interfaces for displaying personalized workout suggestions based on completed workouts. FIG. 7 is a flow diagram illustrating an exemplary process for displaying personalized workout suggestions based on completed workouts, in accordance with some embodiments. The user interfaces in FIGS. 6A-6EE are used to illustrate the processes described below, including the processes in FIG. 7. FIGS. 8A-8S illustrate exemplary user interfaces for starting an audio-based workout. FIG. 9 is a flow diagram illustrating an exemplary process for starting an audio-based workout, in accordance with some embodiments. The user interfaces in FIGS. 8A-8S are used to illustrate the processes described below, including the processes in FIG. 9. FIGS. 10A-10V illustrate exemplary user interfaces for displaying workout information. FIG. 11 is a flow diagram illustrating an exemplary process for displaying workout information, in accordance with some embodiments. The user interfaces in FIGS. 10A-10V are used to illustrate the processes described below, including the processes in FIG. 11. FIGS. 12A-12O illustrate exemplary user interfaces for displaying workout information. FIG. 13 is a flow diagram illustrating an exemplary process for displaying workout information, in accordance with some embodiments. The user interfaces in FIGS. 12A-12O are used to illustrate the processes described below, including the processes in FIG. 13. FIGS. 14A-14R illustrate exemplary user interfaces for coordinating display of workout content

17

among multiple devices. FIG. 15 is a flow diagram illustrating an exemplary process for coordinating display of workout content among multiple devices, in accordance with some embodiments. The user interfaces in FIGS. 14A-14R are used to illustrate the processes described below, including the processes in FIG. 15. FIGS. 16A-16R illustrate exemplary user interfaces for displaying workout information. FIGS. 17A-17B are a flow diagram illustrating an exemplary process for displaying workout information, in accordance with some embodiments. The user interfaces in FIGS. 16A-16R are used to illustrate the processes described below, including the processes in FIGS. 17A-17B. FIGS. 18A-18V illustrate exemplary user interfaces for displaying workout information. FIGS. 19A-19C are a flow diagram illustrating an exemplary process for displaying workout information, in accordance with some embodiments. The user interfaces in FIGS. 18A-18V are used to illustrate the processes described below, including the processes in FIGS. 19A-19C.

Although the following description uses terms “first,” “second,” etc. to describe various elements, these elements should not be limited by the terms. These terms are only used to distinguish one element from another. For example, a first touch could be termed a second touch, and, similarly, a second touch could be termed a first touch, without departing from the scope of the various described embodiments. The first touch and the second touch are both touches, but they are not the same touch.

The terminology used in the description of the various described embodiments herein is for the purpose of describing particular embodiments only and is not intended to be limiting. As used in the description of the various described embodiments and the appended claims, the singular forms “a,” “an,” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will also be understood that the term “and/or” as used herein refers to and encompasses any and all possible combinations of one or more of the associated listed items. It will be further understood that the terms “includes,” “including,” “comprises,” and/or “comprising,” when used in this specification, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof.

The term “if” is, optionally, construed to mean “when” or “upon” or “in response to determining” or “in response to detecting,” depending on the context. Similarly, the phrase “if it is determined” or “if [a stated condition or event] is detected” is, optionally, construed to mean “upon determining” or “in response to determining” or “upon detecting [the stated condition or event]” or “in response to detecting [the stated condition or event],” depending on the context.

Embodiments of electronic devices, user interfaces for such devices, and associated processes for using such devices are described. In some embodiments, the device is a portable communications device, such as a mobile telephone, that also contains other functions, such as PDA and/or music player functions. Exemplary embodiments of portable multifunction devices include, without limitation, the iPhone®, iPod Touch®, and iPad® devices from Apple Inc. of Cupertino, California. Other portable electronic devices, such as laptops or tablet computers with touch-sensitive surfaces (e.g., touch screen displays and/or touchpads), are, optionally, used. It should also be understood that, in some embodiments, the device is not a portable communications device, but is a desktop computer with a

18

touch-sensitive surface (e.g., a touch screen display and/or a touchpad). In some embodiments, the electronic device is a computer system that is in communication (e.g., via wireless communication, via wired communication) with a display generation component. The display generation component is configured to provide visual output, such as display via a CRT display, display via an LED display, or display via image projection. In some embodiments, the display generation component is integrated with the computer system. In some embodiments, the display generation component is separate from the computer system. As used herein, “displaying” content includes causing to display the content (e.g., video data rendered or decoded by display controller 156) by transmitting, via a wired or wireless connection, data (e.g., image data or video data) to an integrated or external display generation component to visually produce the content.

In the discussion that follows, an electronic device that includes a display and a touch-sensitive surface is described. It should be understood, however, that the electronic device optionally includes one or more other physical user-interface devices, such as a physical keyboard, a mouse, and/or a joystick.

The device typically supports a variety of applications, such as one or more of the following: a drawing application, a presentation application, a word processing application, a website creation application, a disk authoring application, a spreadsheet application, a gaming application, a telephone application, a video conferencing application, an e-mail application, an instant messaging application, a workout support application, a photo management application, a digital camera application, a digital video camera application, a web browsing application, a digital music player application, and/or a digital video player application.

The various applications that are executed on the device optionally use at least one common physical user-interface device, such as the touch-sensitive surface. One or more functions of the touch-sensitive surface as well as corresponding information displayed on the device are, optionally, adjusted and/or varied from one application to the next and/or within a respective application. In this way, a common physical architecture (such as the touch-sensitive surface) of the device optionally supports the variety of applications with user interfaces that are intuitive and transparent to the user.

Attention is now directed toward embodiments of portable devices with touch-sensitive displays. FIG. 1A is a block diagram illustrating portable multifunction device 100 with touch-sensitive display system 112 in accordance with some embodiments. Touch-sensitive display 112 is sometimes called a “touch screen” for convenience and is sometimes known as or called a “touch-sensitive display system.” Device 100 includes memory 102 (which optionally includes one or more computer-readable storage mediums), memory controller 122, one or more processing units (CPUs) 120, peripherals interface 118, RF circuitry 108, audio circuitry 110, speaker 111, microphone 113, input/output (I/O) subsystem 106, other input control devices 116, and external port 124. Device 100 optionally includes one or more optical sensors 164. Device 100 optionally includes one or more contact intensity sensors 165 for detecting intensity of contacts on device 100 (e.g., a touch-sensitive surface such as touch-sensitive display system 112 of device 100). Device 100 optionally includes one or more tactile output generators 167 for generating tactile outputs on device 100 (e.g., generating tactile outputs on a touch-sensitive surface such as touch-sensitive display system 112

of device **100** or touchpad **355** of device **300**). These components optionally communicate over one or more communication buses or signal lines **103**.

As used in the specification and claims, the term “intensity” of a contact on a touch-sensitive surface refers to the force or pressure (force per unit area) of a contact (e.g., a finger contact) on the touch-sensitive surface, or to a substitute (proxy) for the force or pressure of a contact on the touch-sensitive surface. The intensity of a contact has a range of values that includes at least four distinct values and more typically includes hundreds of distinct values (e.g., at least 256). Intensity of a contact is, optionally, determined (or measured) using various approaches and various sensors or combinations of sensors. For example, one or more force sensors underneath or adjacent to the touch-sensitive surface are, optionally, used to measure force at various points on the touch-sensitive surface. In some implementations, force measurements from multiple force sensors are combined (e.g., a weighted average) to determine an estimated force of a contact. Similarly, a pressure-sensitive tip of a stylus is, optionally, used to determine a pressure of the stylus on the touch-sensitive surface. Alternatively, the size of the contact area detected on the touch-sensitive surface and/or changes thereto, the capacitance of the touch-sensitive surface proximate to the contact and/or changes thereto, and/or the resistance of the touch-sensitive surface proximate to the contact and/or changes thereto are, optionally, used as a substitute for the force or pressure of the contact on the touch-sensitive surface. In some implementations, the substitute measurements for contact force or pressure are used directly to determine whether an intensity threshold has been exceeded (e.g., the intensity threshold is described in units corresponding to the substitute measurements). In some implementations, the substitute measurements for contact force or pressure are converted to an estimated force or pressure, and the estimated force or pressure is used to determine whether an intensity threshold has been exceeded (e.g., the intensity threshold is a pressure threshold measured in units of pressure). Using the intensity of a contact as an attribute of a user input allows for user access to additional device functionality that may otherwise not be accessible by the user on a reduced-size device with limited real estate for displaying affordances (e.g., on a touch-sensitive display) and/or receiving user input (e.g., via a touch-sensitive display, a touch-sensitive surface, or a physical/mechanical control such as a knob or a button).

As used in the specification and claims, the term “tactile output” refers to physical displacement of a device relative to a previous position of the device, physical displacement of a component (e.g., a touch-sensitive surface) of a device relative to another component (e.g., housing) of the device, or displacement of the component relative to a center of mass of the device that will be detected by a user with the user’s sense of touch. For example, in situations where the device or the component of the device is in contact with a surface of a user that is sensitive to touch (e.g., a finger, palm, or other part of a user’s hand), the tactile output generated by the physical displacement will be interpreted by the user as a tactile sensation corresponding to a perceived change in physical characteristics of the device or the component of the device. For example, movement of a touch-sensitive surface (e.g., a touch-sensitive display or trackpad) is, optionally, interpreted by the user as a “down click” or “up click” of a physical actuator button. In some cases, a user will feel a tactile sensation such as an “down click” or “up click” even when there is no movement of a physical actuator button associated with the touch-sensitive

surface that is physically pressed (e.g., displaced) by the user’s movements. As another example, movement of the touch-sensitive surface is, optionally, interpreted or sensed by the user as “roughness” of the touch-sensitive surface, even when there is no change in smoothness of the touch-sensitive surface. While such interpretations of touch by a user will be subject to the individualized sensory perceptions of the user, there are many sensory perceptions of touch that are common to a large majority of users. Thus, when a tactile output is described as corresponding to a particular sensory perception of a user (e.g., an “up click,” a “down click,” “roughness”), unless otherwise stated, the generated tactile output corresponds to physical displacement of the device or a component thereof that will generate the described sensory perception for a typical (or average) user.

It should be appreciated that device **100** is only one example of a portable multifunction device, and that device **100** optionally has more or fewer components than shown, optionally combines two or more components, or optionally has a different configuration or arrangement of the components. The various components shown in FIG. **1A** are implemented in hardware, software, or a combination of both hardware and software, including one or more signal processing and/or application-specific integrated circuits.

Memory **102** optionally includes high-speed random access memory and optionally also includes non-volatile memory, such as one or more magnetic disk storage devices, flash memory devices, or other non-volatile solid-state memory devices. Memory controller **122** optionally controls access to memory **102** by other components of device **100**.

Peripherals interface **118** can be used to couple input and output peripherals of the device to CPU **120** and memory **102**. The one or more processors **120** run or execute various software programs and/or sets of instructions stored in memory **102** to perform various functions for device **100** and to process data. In some embodiments, peripherals interface **118**, CPU **120**, and memory controller **122** are, optionally, implemented on a single chip, such as chip **104**. In some other embodiments, they are, optionally, implemented on separate chips.

RF (radio frequency) circuitry **108** receives and sends RF signals, also called electromagnetic signals. RF circuitry **108** converts electrical signals to/from electromagnetic signals and communicates with communications networks and other communications devices via the electromagnetic signals. RF circuitry **108** optionally includes well-known circuitry for performing these functions, including but not limited to an antenna system, an RF transceiver, one or more amplifiers, a tuner, one or more oscillators, a digital signal processor, a CODEC chipset, a subscriber identity module (SIM) card, memory, and so forth. RF circuitry **108** optionally communicates with networks, such as the Internet, also referred to as the World Wide Web (WWW), an intranet and/or a wireless network, such as a cellular telephone network, a wireless local area network (LAN) and/or a metropolitan area network (MAN), and other devices by wireless communication. The RF circuitry **108** optionally includes well-known circuitry for detecting near field communication (NFC) fields, such as by a short-range communication radio. The wireless communication optionally uses any of a plurality of communications standards, protocols, and technologies, including but not limited to Global System for Mobile Communications (GSM), Enhanced Data GSM Environment (EDGE), high-speed downlink packet access (HSDPA), high-speed uplink packet access (HSUPA), Evolution, Data-Only (EV-DO), HSPA, HSPA+, Dual-Cell HSPA (DC-HSPDA), long term evolution (LTE), near field

communication (NFC), wideband code division multiple access (W-CDMA), code division multiple access (CDMA), time division multiple access (TDMA), Bluetooth, Bluetooth Low Energy (BTLE), Wireless Fidelity (Wi-Fi) (e.g., IEEE 802.11a, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, and/or IEEE 802.11ac), voice over Internet Protocol (VOIP), Wi-MAX, a protocol for e-mail (e.g., Internet message access protocol (IMAP) and/or post office protocol (POP)), instant messaging (e.g., extensible messaging and presence protocol (XMPP), Session Initiation Protocol for Instant Messaging and Presence Leveraging Extensions (SIMPLE), Instant Messaging and Presence Service (IMPS)), and/or Short Message Service (SMS), or any other suitable communication protocol, including communication protocols not yet developed as of the filing date of this document.

Audio circuitry **110**, speaker **111**, and microphone **113** provide an audio interface between a user and device **100**. Audio circuitry **110** receives audio data from peripherals interface **118**, converts the audio data to an electrical signal, and transmits the electrical signal to speaker **111**. Speaker **111** converts the electrical signal to human-audible sound waves. Audio circuitry **110** also receives electrical signals converted by microphone **113** from sound waves. Audio circuitry **110** converts the electrical signal to audio data and transmits the audio data to peripherals interface **118** for processing. Audio data is, optionally, retrieved from and/or transmitted to memory **102** and/or RF circuitry **108** by peripherals interface **118**. In some embodiments, audio circuitry **110** also includes a headset jack (e.g., **212**, FIG. 2). The headset jack provides an interface between audio circuitry **110** and removable audio input/output peripherals, such as output-only headphones or a headset with both output (e.g., a headphone for one or both ears) and input (e.g., a microphone).

I/O subsystem **106** couples input/output peripherals on device **100**, such as touch screen **112** and other input control devices **116**, to peripherals interface **118**. I/O subsystem **106** optionally includes display controller **156**, optical sensor controller **158**, depth camera controller **169**, intensity sensor controller **159**, haptic feedback controller **161**, and one or more input controllers **160** for other input or control devices. The one or more input controllers **160** receive/send electrical signals from/to other input control devices **116**. The other input control devices **116** optionally include physical buttons (e.g., push buttons, rocker buttons, etc.), dials, slider switches, joysticks, click wheels, and so forth. In some alternate embodiments, input controller(s) **160** are, optionally, coupled to any (or none) of the following: a keyboard, an infrared port, a USB port, and a pointer device such as a mouse. The one or more buttons (e.g., **208**, FIG. 2) optionally include an up/down button for volume control of speaker **111** and/or microphone **113**. The one or more buttons optionally include a push button (e.g., **206**, FIG. 2). In some embodiments, the electronic device is a computer system that is in communication (e.g., via wireless communication, via wired communication) with one or more input devices. In some embodiments, the one or more input devices include a touch-sensitive surface (e.g., a trackpad, as part of a touch-sensitive display). In some embodiments, the one or more input devices include one or more camera sensors (e.g., one or more optical sensors **164** and/or one or more depth camera sensors **175**), such as for tracking a user's gestures (e.g., hand gestures) as input. In some embodiments, the one or more input devices are integrated with the computer system. In some embodiments, the one or more input devices are separate from the computer system.

A quick press of the push button optionally disengages a lock of touch screen **112** or optionally begins a process that uses gestures on the touch screen to unlock the device, as described in U.S. patent application Ser. No. 11/322,549, “Unlocking a Device by Performing Gestures on an Unlock Image,” filed Dec. 23, 2005, U.S. Pat. No. 7,657,849, which is hereby incorporated by reference in its entirety. A longer press of the push button (e.g., **206**) optionally turns power to device **100** on or off. The functionality of one or more of the buttons are, optionally, user-customizable. Touch screen **112** is used to implement virtual or soft buttons and one or more soft keyboards.

Touch-sensitive display **112** provides an input interface and an output interface between the device and a user. Display controller **156** receives and/or sends electrical signals from/to touch screen **112**. Touch screen **112** displays visual output to the user. The visual output optionally includes graphics, text, icons, video, and any combination thereof (collectively termed “graphics”). In some embodiments, some or all of the visual output optionally corresponds to user-interface objects.

Touch screen **112** has a touch-sensitive surface, sensor, or set of sensors that accepts input from the user based on haptic and/or tactile contact. Touch screen **112** and display controller **156** (along with any associated modules and/or sets of instructions in memory **102**) detect contact (and any movement or breaking of the contact) on touch screen **112** and convert the detected contact into interaction with user-interface objects (e.g., one or more soft keys, icons, web pages, or images) that are displayed on touch screen **112**. In an exemplary embodiment, a point of contact between touch screen **112** and the user corresponds to a finger of the user.

Touch screen **112** optionally uses LCD (liquid crystal display) technology, LPD (light emitting polymer display) technology, or LED (light emitting diode) technology, although other display technologies are used in other embodiments. Touch screen **112** and display controller **156** optionally detect contact and any movement or breaking thereof using any of a plurality of touch sensing technologies now known or later developed, including but not limited to capacitive, resistive, infrared, and surface acoustic wave technologies, as well as other proximity sensor arrays or other elements for determining one or more points of contact with touch screen **112**. In an exemplary embodiment, projected mutual capacitance sensing technology is used, such as that found in the iPhone® and iPod Touch® from Apple Inc. of Cupertino, California.

A touch-sensitive display in some embodiments of touch screen **112** is, optionally, analogous to the multi-touch sensitive touchpads described in the following U.S. Pat. No. 6,323,846 (Westerman et al.), U.S. Pat. No. 6,570,557 (Westerman et al.), and/or U.S. Pat. No. 6,677,932 (Westerman), and/or U.S. Patent Publication 2002/0015024A1, each of which is hereby incorporated by reference in its entirety. However, touch screen **112** displays visual output from device **100**, whereas touch-sensitive touchpads do not provide visual output.

A touch-sensitive display in some embodiments of touch screen **112** is described in the following applications: (1) U.S. patent application Ser. No. 11/381,313, “Multipoint Touch Surface Controller,” filed May 2, 2006; (2) U.S. patent application Ser. No. 10/840,862, “Multipoint Touchscreen,” filed May 6, 2004; (3) U.S. patent application Ser. No. 10/903,964, “Gestures For Touch Sensitive Input Devices,” filed Jul. 30, 2004; (4) U.S. patent application Ser. No. 11/048,264, “Gestures For Touch Sensitive Input Devices,” filed Jan. 31, 2005; (5) U.S. patent application Ser.

No. 11/038,590, "Mode-Based Graphical User Interfaces For Touch Sensitive Input Devices," filed Jan. 18, 2005; (6) U.S. patent application Ser. No. 11/228,758, "Virtual Input Device Placement On A Touch Screen User Interface," filed Sep. 16, 2005; (7) U.S. patent application Ser. No. 11/228,700, "Operation Of A Computer With A Touch Screen Interface," filed Sep. 16, 2005; (8) U.S. patent application Ser. No. 11/228,737, "Activating Virtual Keys Of A Touch-Screen Virtual Keyboard," filed Sep. 16, 2005; and (9) U.S. patent application Ser. No. 11/367,749, "Multi-Functional Hand-Held Device," filed Mar. 3, 2006. All of these applications are incorporated by reference herein in their entirety.

Touch screen **112** optionally has a video resolution in excess of 100 dpi. In some embodiments, the touch screen has a video resolution of approximately 160 dpi. The user optionally makes contact with touch screen **112** using any suitable object or appendage, such as a stylus, a finger, and so forth. In some embodiments, the user interface is designed to work primarily with finger-based contacts and gestures, which can be less precise than stylus-based input due to the larger area of contact of a finger on the touch screen. In some embodiments, the device translates the rough finger-based input into a precise pointer/cursor position or command for performing the actions desired by the user.

In some embodiments, in addition to the touch screen, device **100** optionally includes a touchpad for activating or deactivating particular functions. In some embodiments, the touchpad is a touch-sensitive area of the device that, unlike the touch screen, does not display visual output. The touchpad is, optionally, a touch-sensitive surface that is separate from touch screen **112** or an extension of the touch-sensitive surface formed by the touch screen.

Device **100** also includes power system **162** for powering the various components. Power system **162** optionally includes a power management system, one or more power sources (e.g., battery, alternating current (AC)), a recharging system, a power failure detection circuit, a power converter or inverter, a power status indicator (e.g., a light-emitting diode (LED)) and any other components associated with the generation, management and distribution of power in portable devices.

Device **100** optionally also includes one or more optical sensors **164**. FIG. 1A shows an optical sensor coupled to optical sensor controller **158** in I/O subsystem **106**. Optical sensor **164** optionally includes charge-coupled device (CCD) or complementary metal-oxide semiconductor (CMOS) phototransistors. Optical sensor **164** receives light from the environment, projected through one or more lenses, and converts the light to data representing an image. In conjunction with imaging module **143** (also called a camera module), optical sensor **164** optionally captures still images or video. In some embodiments, an optical sensor is located on the back of device **100**, opposite touch screen display **112** on the front of the device so that the touch screen display is enabled for use as a viewfinder for still and/or video image acquisition. In some embodiments, an optical sensor is located on the front of the device so that the user's image is, optionally, obtained for video conferencing while the user views the other video conference participants on the touch screen display. In some embodiments, the position of optical sensor **164** can be changed by the user (e.g., by rotating the lens and the sensor in the device housing) so that a single optical sensor **164** is used along with the touch screen display for both video conferencing and still and/or video image acquisition.

Device **100** optionally also includes one or more depth camera sensors **175**. FIG. 1A shows a depth camera sensor coupled to depth camera controller **169** in I/O subsystem **106**. Depth camera sensor **175** receives data from the environment to create a three dimensional model of an object (e.g., a face) within a scene from a viewpoint (e.g., a depth camera sensor). In some embodiments, in conjunction with imaging module **143** (also called a camera module), depth camera sensor **175** is optionally used to determine a depth map of different portions of an image captured by the imaging module **143**. In some embodiments, a depth camera sensor is located on the front of device **100** so that the user's image with depth information is, optionally, obtained for video conferencing while the user views the other video conference participants on the touch screen display and to capture selfies with depth map data. In some embodiments, the depth camera sensor **175** is located on the back of device, or on the back and the front of the device **100**. In some embodiments, the position of depth camera sensor **175** can be changed by the user (e.g., by rotating the lens and the sensor in the device housing) so that a depth camera sensor **175** is used along with the touch screen display for both video conferencing and still and/or video image acquisition.

Device **100** optionally also includes one or more contact intensity sensors **165**. FIG. 1A shows a contact intensity sensor coupled to intensity sensor controller **159** in I/O subsystem **106**. Contact intensity sensor **165** optionally includes one or more piezoresistive strain gauges, capacitive force sensors, electric force sensors, piezoelectric force sensors, optical force sensors, capacitive touch-sensitive surfaces, or other intensity sensors (e.g., sensors used to measure the force (or pressure) of a contact on a touch-sensitive surface). Contact intensity sensor **165** receives contact intensity information (e.g., pressure information or a proxy for pressure information) from the environment. In some embodiments, at least one contact intensity sensor is collocated with, or proximate to, a touch-sensitive surface (e.g., touch-sensitive display system **112**). In some embodiments, at least one contact intensity sensor is located on the back of device **100**, opposite touch screen display **112**, which is located on the front of device **100**.

Device **100** optionally also includes one or more proximity sensors **166**. FIG. 1A shows proximity sensor **166** coupled to peripherals interface **118**. Alternately, proximity sensor **166** is, optionally, coupled to input controller **160** in I/O subsystem **106**. Proximity sensor **166** optionally performs as described in U.S. patent application Ser. No. 11/241,839, "Proximity Detector In Handheld Device"; Ser. No. 11/240,788, "Proximity Detector In Handheld Device"; Ser. No. 11/620,702, "Using Ambient Light Sensor To Augment Proximity Sensor Output"; Ser. No. 11/586,862, "Automated Response To And Sensing Of User Activity In Portable Devices"; and Ser. No. 11/638,251, "Methods And Systems For Automatic Configuration Of Peripherals," which are hereby incorporated by reference in their entirety. In some embodiments, the proximity sensor turns off and disables touch screen **112** when the multifunction device is placed near the user's ear (e.g., when the user is making a phone call).

Device **100** optionally also includes one or more tactile output generators **167**. FIG. 1A shows a tactile output generator coupled to haptic feedback controller **161** in I/O subsystem **106**. Tactile output generator **167** optionally includes one or more electroacoustic devices such as speakers or other audio components and/or electromechanical devices that convert energy into linear motion such as a motor, solenoid, electroactive polymer, piezoelectric actua-

25

tor, electrostatic actuator, or other tactile output generating component (e.g., a component that converts electrical signals into tactile outputs on the device). Contact intensity sensor **165** receives tactile feedback generation instructions from haptic feedback module **133** and generates tactile outputs on device **100** that are capable of being sensed by a user of device **100**. In some embodiments, at least one tactile output generator is collocated with, or proximate to, a touch-sensitive surface (e.g., touch-sensitive display system **112**) and, optionally, generates a tactile output by moving the touch-sensitive surface vertically (e.g., in/out of a surface of device **100**) or laterally (e.g., back and forth in the same plane as a surface of device **100**). In some embodiments, at least one tactile output generator sensor is located on the back of device **100**, opposite touch screen display **112**, which is located on the front of device **100**.

Device **100** optionally also includes one or more accelerometers **168**. FIG. 1A shows accelerometer **168** coupled to peripherals interface **118**. Alternately, accelerometer **168** is, optionally, coupled to an input controller **160** in I/O subsystem **106**. Accelerometer **168** optionally performs as described in U.S. Patent Publication No. 20050190059, "Acceleration-based Theft Detection System for Portable Electronic Devices," and U.S. Patent Publication No. 20060017692, "Methods And Apparatuses For Operating A Portable Device Based On An Accelerometer," both of which are incorporated by reference herein in their entirety. In some embodiments, information is displayed on the touch screen display in a portrait view or a landscape view based on an analysis of data received from the one or more accelerometers. Device **100** optionally includes, in addition to accelerometer(s) **168**, a magnetometer and a GPS (or GLONASS or other global navigation system) receiver for obtaining information concerning the location and orientation (e.g., portrait or landscape) of device **100**.

In some embodiments, the software components stored in memory **102** include operating system **126**, communication module (or set of instructions) **128**, contact/motion module (or set of instructions) **130**, graphics module (or set of instructions) **132**, text input module (or set of instructions) **134**, Global Positioning System (GPS) module (or set of instructions) **135**, and applications (or sets of instructions) **136**. Furthermore, in some embodiments, memory **102** (FIG. 1A) or **370** (FIG. 3) stores device/global internal state **157**, as shown in FIGS. 1A and 3. Device/global internal state **157** includes one or more of: active application state, indicating which applications, if any, are currently active; display state, indicating what applications, views or other information occupy various regions of touch screen display **112**; sensor state, including information obtained from the device's various sensors and input control devices **116**; and location information concerning the device's location and/or attitude.

Operating system **126** (e.g., Darwin, RTXC, LINUX, UNIX, OS X, IOS, WINDOWS, or an embedded operating system such as VxWorks) includes various software components and/or drivers for controlling and managing general system tasks (e.g., memory management, storage device control, power management, etc.) and facilitates communication between various hardware and software components.

Communication module **128** facilitates communication with other devices over one or more external ports **124** and also includes various software components for handling data received by RF circuitry **108** and/or external port **124**. External port **124** (e.g., Universal Serial Bus (USB), FIREWIRE, etc.) is adapted for coupling directly to other devices or indirectly over a network (e.g., the Internet, wireless LAN, etc.). In some embodiments, the external port is a

26

multi-pin (e.g., 30-pin) connector that is the same as, or similar to and/or compatible with, the 30-pin connector used on iPod® (trademark of Apple Inc.) devices.

Contact/motion module **130** optionally detects contact with touch screen **112** (in conjunction with display controller **156**) and other touch-sensitive devices (e.g., a touchpad or physical click wheel). Contact/motion module **130** includes various software components for performing various operations related to detection of contact, such as determining if contact has occurred (e.g., detecting a finger-down event), determining an intensity of the contact (e.g., the force or pressure of the contact or a substitute for the force or pressure of the contact), determining if there is movement of the contact and tracking the movement across the touch-sensitive surface (e.g., detecting one or more finger-dragging events), and determining if the contact has ceased (e.g., detecting a finger-up event or a break in contact). Contact/motion module **130** receives contact data from the touch-sensitive surface. Determining movement of the point of contact, which is represented by a series of contact data, optionally includes determining speed (magnitude), velocity (magnitude and direction), and/or an acceleration (a change in magnitude and/or direction) of the point of contact. These operations are, optionally, applied to single contacts (e.g., one finger contacts) or to multiple simultaneous contacts (e.g., "multitouch"/multiple finger contacts). In some embodiments, contact/motion module **130** and display controller **156** detect contact on a touchpad.

In some embodiments, contact/motion module **130** uses a set of one or more intensity thresholds to determine whether an operation has been performed by a user (e.g., to determine whether a user has "clicked" on an icon). In some embodiments, at least a subset of the intensity thresholds are determined in accordance with software parameters (e.g., the intensity thresholds are not determined by the activation thresholds of particular physical actuators and can be adjusted without changing the physical hardware of device **100**). For example, a mouse "click" threshold of a trackpad or touch screen display can be set to any of a large range of predefined threshold values without changing the trackpad or touch screen display hardware. Additionally, in some implementations, a user of the device is provided with software settings for adjusting one or more of the set of intensity thresholds (e.g., by adjusting individual intensity thresholds and/or by adjusting a plurality of intensity thresholds at once with a system-level click "intensity" parameter).

Contact/motion module **130** optionally detects a gesture input by a user. Different gestures on the touch-sensitive surface have different contact patterns (e.g., different motions, timings, and/or intensities of detected contacts). Thus, a gesture is, optionally, detected by detecting a particular contact pattern. For example, detecting a finger tap gesture includes detecting a finger-down event followed by detecting a finger-up (liftoff) event at the same position (or substantially the same position) as the finger-down event (e.g., at the position of an icon). As another example, detecting a finger swipe gesture on the touch-sensitive surface includes detecting a finger-down event followed by detecting one or more finger-dragging events, and subsequently followed by detecting a finger-up (liftoff) event.

Graphics module **132** includes various known software components for rendering and displaying graphics on touch screen **112** or other display, including components for changing the visual impact (e.g., brightness, transparency, saturation, contrast, or other visual property) of graphics that are displayed. As used herein, the term "graphics" includes any object that can be displayed to a user, including, without

limitation, text, web pages, icons (such as user-interface objects including soft keys), digital images, videos, animations, and the like.

In some embodiments, graphics module 132 stores data representing graphics to be used. Each graphic is, optionally, assigned a corresponding code. Graphics module 132 receives, from applications etc., one or more codes specifying graphics to be displayed along with, if necessary, coordinate data and other graphic property data, and then generates screen image data to output to display controller 156.

Haptic feedback module 133 includes various software components for generating instructions used by tactile output generator(s) 167 to produce tactile outputs at one or more locations on device 100 in response to user interactions with device 100.

Text input module 134, which is, optionally, a component of graphics module 132, provides soft keyboards for entering text in various applications (e.g., contacts module 137, e-mail client module 140, IM module 141, browser module 147, and any other application that needs text input).

GPS module 135 determines the location of the device and provides this information for use in various applications (e.g., to telephone module 138 for use in location-based dialing; to camera module 143 as picture/video metadata; and to applications that provide location-based services such as weather widgets, local yellow page widgets, and map/navigation widgets).

Applications 136 optionally include the following modules (or sets of instructions), or a subset or superset thereof:

- Contacts module 137 (sometimes called an address book or contact list);
- Telephone module 138;
- Video conference module 139;
- E-mail client module 140;
- Instant messaging (IM) module 141;
- Workout support module 142;
- Camera module 143 for still and/or video images;
- Image management module 144;
- Video player module;
- Music player module;
- Browser module 147;
- Calendar module 148;
- Widget modules 149, which optionally include one or more of: weather widget 149-1, stocks widget 149-2, calculator widget 149-3, alarm clock widget 149-4, dictionary widget 149-5, and other widgets obtained by the user, as well as user-created widgets 149-6;
- Widget creator module 150 for making user-created widgets 149-6;
- Search module 151;
- Video and music player module 152, which merges video player module and music player module;
- Notes module 153;
- Map module 154; and/or
- Online video module 155.

Examples of other applications 136 that are, optionally, stored in memory 102 include other word processing applications, other image editing applications, drawing applications, presentation applications, JAVA-enabled applications, encryption, digital rights management, voice recognition, and voice replication.

In conjunction with touch screen 112, display controller 156, contact/motion module 130, graphics module 132, and text input module 134, contacts module 137 are, optionally, used to manage an address book or contact list (e.g., stored in application internal state 192 of contacts module 137 in

memory 102 or memory 370), including: adding name(s) to the address book; deleting name(s) from the address book; associating telephone number(s), e-mail address(es), physical address(es) or other information with a name; associating an image with a name; categorizing and sorting names; providing telephone numbers or e-mail addresses to initiate and/or facilitate communications by telephone module 138, video conference module 139, e-mail client module 140, or IM module 141; and so forth.

In conjunction with RF circuitry 108, audio circuitry 110, speaker 111, microphone 113, touch screen 112, display controller 156, contact/motion module 130, graphics module 132, and text input module 134, telephone module 138 are optionally, used to enter a sequence of characters corresponding to a telephone number, access one or more telephone numbers in contacts module 137, modify a telephone number that has been entered, dial a respective telephone number, conduct a conversation, and disconnect or hang up when the conversation is completed. As noted above, the wireless communication optionally uses any of a plurality of communications standards, protocols, and technologies.

In conjunction with RF circuitry 108, audio circuitry 110, speaker 111, microphone 113, touch screen 112, display controller 156, optical sensor 164, optical sensor controller 158, contact/motion module 130, graphics module 132, text input module 134, contacts module 137, and telephone module 138, video conference module 139 includes executable instructions to initiate, conduct, and terminate a video conference between a user and one or more other participants in accordance with user instructions.

In conjunction with RF circuitry 108, touch screen 112, display controller 156, contact/motion module 130, graphics module 132, and text input module 134, e-mail client module 140 includes executable instructions to create, send, receive, and manage e-mail in response to user instructions. In conjunction with image management module 144, e-mail client module 140 makes it very easy to create and send e-mails with still or video images taken with camera module 143.

In conjunction with RF circuitry 108, touch screen 112, display controller 156, contact/motion module 130, graphics module 132, and text input module 134, the instant messaging module 141 includes executable instructions to enter a sequence of characters corresponding to an instant message, to modify previously entered characters, to transmit a respective instant message (for example, using a Short Message Service (SMS) or Multimedia Message Service (MMS) protocol for telephony-based instant messages or using XMPP, SIMPLE, or IMPS for Internet-based instant messages), to receive instant messages, and to view received instant messages. In some embodiments, transmitted and/or received instant messages optionally include graphics, photos, audio files, video files and/or other attachments as are supported in an MMS and/or an Enhanced Messaging Service (EMS). As used herein, "instant messaging" refers to both telephony-based messages (e.g., messages sent using SMS or MMS) and Internet-based messages (e.g., messages sent using XMPP, SIMPLE, or IMPS).

In conjunction with RF circuitry 108, touch screen 112, display controller 156, contact/motion module 130, graphics module 132, text input module 134, GPS module 135, map module 154, and music player module, workout support module 142 includes executable instructions to create workouts (e.g., with time, distance, and/or calorie burning goals); communicate with workout sensors (sports devices); receive workout sensor data; calibrate sensors used to monitor a

workout; select and play music for a workout; and display, store, and transmit workout data.

In conjunction with touch screen 112, display controller 156, optical sensor(s) 164, optical sensor controller 158, contact/motion module 130, graphics module 132, and image management module 144, camera module 143 includes executable instructions to capture still images or video (including a video stream) and store them into memory 102, modify characteristics of a still image or video, or delete a still image or video from memory 102.

In conjunction with touch screen 112, display controller 156, contact/motion module 130, graphics module 132, text input module 134, and camera module 143, image management module 144 includes executable instructions to arrange, modify (e.g., edit), or otherwise manipulate, label, delete, present (e.g., in a digital slide show or album), and store still and/or video images.

In conjunction with RF circuitry 108, touch screen 112, display controller 156, contact/motion module 130, graphics module 132, and text input module 134, browser module 147 includes executable instructions to browse the Internet in accordance with user instructions, including searching, linking to, receiving, and displaying web pages or portions thereof, as well as attachments and other files linked to web pages.

In conjunction with RF circuitry 108, touch screen 112, display controller 156, contact/motion module 130, graphics module 132, text input module 134, e-mail client module 140, and browser module 147, calendar module 148 includes executable instructions to create, display, modify, and store calendars and data associated with calendars (e.g., calendar entries, to-do lists, etc.) in accordance with user instructions.

In conjunction with RF circuitry 108, touch screen 112, display controller 156, contact/motion module 130, graphics module 132, text input module 134, and browser module 147, widget modules 149 are mini-applications that are, optionally, downloaded and used by a user (e.g., weather widget 149-1, stocks widget 149-2, calculator widget 149-3, alarm clock widget 149-4, and dictionary widget 149-5) or created by the user (e.g., user-created widget 149-6). In some embodiments, a widget includes an HTML (Hypertext Markup Language) file, a CSS (Cascading Style Sheets) file, and a JavaScript file. In some embodiments, a widget includes an XML (Extensible Markup Language) file and a JavaScript file (e.g., Yahoo! Widgets).

In conjunction with RF circuitry 108, touch screen 112, display controller 156, contact/motion module 130, graphics module 132, text input module 134, and browser module 147, the widget creator module 150 are, optionally, used by a user to create widgets (e.g., turning a user-specified portion of a web page into a widget).

In conjunction with touch screen 112, display controller 156, contact/motion module 130, graphics module 132, and text input module 134, search module 151 includes executable instructions to search for text, music, sound, image, video, and/or other files in memory 102 that match one or more search criteria (e.g., one or more user-specified search terms) in accordance with user instructions.

In conjunction with touch screen 112, display controller 156, contact/motion module 130, graphics module 132, audio circuitry 110, speaker 111, RF circuitry 108, and browser module 147, video and music player module 152 includes executable instructions that allow the user to download and play back recorded music and other sound files stored in one or more file formats, such as MP3 or AAC files, and executable instructions to display, present, or otherwise play back videos (e.g., on touch screen 112 or on an external,

connected display via external port 124). In some embodiments, device 100 optionally includes the functionality of an MP3 player, such as an iPod (trademark of Apple Inc.).

In conjunction with touch screen 112, display controller 156, contact/motion module 130, graphics module 132, and text input module 134, notes module 153 includes executable instructions to create and manage notes, to-do lists, and the like in accordance with user instructions.

In conjunction with RF circuitry 108, touch screen 112, display controller 156, contact/motion module 130, graphics module 132, text input module 134, GPS module 135, and browser module 147, map module 154 are, optionally, used to receive, display, modify, and store maps and data associated with maps (e.g., driving directions, data on stores and other points of interest at or near a particular location, and other location-based data) in accordance with user instructions.

In conjunction with touch screen 112, display controller 156, contact/motion module 130, graphics module 132, audio circuitry 110, speaker 111, RF circuitry 108, text input module 134, e-mail client module 140, and browser module 147, online video module 155 includes instructions that allow the user to access, browse, receive (e.g., by streaming and/or download), play back (e.g., on the touch screen or on an external, connected display via external port 124), send an e-mail with a link to a particular online video, and otherwise manage online videos in one or more file formats, such as H.264. In some embodiments, instant messaging module 141, rather than e-mail client module 140, is used to send a link to a particular online video. Additional description of the online video application can be found in U.S. Provisional Patent Application No. 60/936,562, "Portable Multifunction Device, Method, and Graphical User Interface for Playing Online Videos," filed Jun. 20, 2007, and U.S. patent application Ser. No. 11/968,067, "Portable Multifunction Device, Method, and Graphical User Interface for Playing Online Videos," filed Dec. 31, 2007, the contents of which are hereby incorporated by reference in their entirety.

Each of the above-identified modules and applications corresponds to a set of executable instructions for performing one or more functions described above and the methods described in this application (e.g., the computer-implemented methods and other information processing methods described herein). These modules (e.g., sets of instructions) need not be implemented as separate software programs, procedures, or modules, and thus various subsets of these modules are, optionally, combined or otherwise rearranged in various embodiments. For example, video player module is, optionally, combined with music player module into a single module (e.g., video and music player module 152, FIG. 1A). In some embodiments, memory 102 optionally stores a subset of the modules and data structures identified above. Furthermore, memory 102 optionally stores additional modules and data structures not described above.

In some embodiments, device 100 is a device where operation of a predefined set of functions on the device is performed exclusively through a touch screen and/or a touchpad. By using a touch screen and/or a touchpad as the primary input control device for operation of device 100, the number of physical input control devices (such as push buttons, dials, and the like) on device 100 is, optionally, reduced.

The predefined set of functions that are performed exclusively through a touch screen and/or a touchpad optionally include navigation between user interfaces. In some embodiments, the touchpad, when touched by the user, navigates device 100 to a main, home, or root menu from any user

31

interface that is displayed on device 100. In such embodiments, a “menu button” is implemented using a touchpad. In some other embodiments, the menu button is a physical push button or other physical input control device instead of a touchpad.

FIG. 1B is a block diagram illustrating exemplary components for event handling in accordance with some embodiments. In some embodiments, memory 102 (FIG. 1A) or 370 (FIG. 3) includes event sorter 170 (e.g., in operating system 126) and a respective application 136-1 (e.g., any of the aforementioned applications 137-151, 155, 380-390).

Event sorter 170 receives event information and determines the application 136-1 and application view 191 of application 136-1 to which to deliver the event information. Event sorter 170 includes event monitor 171 and event dispatcher module 174. In some embodiments, application 136-1 includes application internal state 192, which indicates the current application view(s) displayed on touch-sensitive display 112 when the application is active or executing. In some embodiments, device/global internal state 157 is used by event sorter 170 to determine which application(s) is (are) currently active, and application internal state 192 is used by event sorter 170 to determine application views 191 to which to deliver event information.

In some embodiments, application internal state 192 includes additional information, such as one or more of: resume information to be used when application 136-1 resumes execution, user interface state information that indicates information being displayed or that is ready for display by application 136-1, a state queue for enabling the user to go back to a prior state or view of application 136-1, and a redo/undo queue of previous actions taken by the user.

Event monitor 171 receives event information from peripherals interface 118. Event information includes information about a sub-event (e.g., a user touch on touch-sensitive display 112, as part of a multi-touch gesture). Peripherals interface 118 transmits information it receives from I/O subsystem 106 or a sensor, such as proximity sensor 166, accelerometer(s) 168, and/or microphone 113 (through audio circuitry 110). Information that peripherals interface 118 receives from I/O subsystem 106 includes information from touch-sensitive display 112 or a touch-sensitive surface.

In some embodiments, event monitor 171 sends requests to the peripherals interface 118 at predetermined intervals. In response, peripherals interface 118 transmits event information. In other embodiments, peripherals interface 118 transmits event information only when there is a significant event (e.g., receiving an input above a predetermined noise threshold and/or for more than a predetermined duration).

In some embodiments, event sorter 170 also includes a hit view determination module 172 and/or an active event recognizer determination module 173.

Hit view determination module 172 provides software procedures for determining where a sub-event has taken place within one or more views when touch-sensitive display 112 displays more than one view. Views are made up of controls and other elements that a user can see on the display.

Another aspect of the user interface associated with an application is a set of views, sometimes herein called application views or user interface windows, in which information is displayed and touch-based gestures occur. The application views (of a respective application) in which a touch is detected optionally correspond to programmatic levels within a programmatic or view hierarchy of the

32

application. For example, the lowest level view in which a touch is detected is, optionally, called the hit view, and the set of events that are recognized as proper inputs are, optionally, determined based, at least in part, on the hit view of the initial touch that begins a touch-based gesture.

Hit view determination module 172 receives information related to sub-events of a touch-based gesture. When an application has multiple views organized in a hierarchy, hit view determination module 172 identifies a hit view as the lowest view in the hierarchy which should handle the sub-event. In most circumstances, the hit view is the lowest level view in which an initiating sub-event occurs (e.g., the first sub-event in the sequence of sub-events that form an event or potential event). Once the hit view is identified by the hit view determination module 172, the hit view typically receives all sub-events related to the same touch or input source for which it was identified as the hit view.

Active event recognizer determination module 173 determines which view or views within a view hierarchy should receive a particular sequence of sub-events. In some embodiments, active event recognizer determination module 173 determines that only the hit view should receive a particular sequence of sub-events. In other embodiments, active event recognizer determination module 173 determines that all views that include the physical location of a sub-event are actively involved views, and therefore determines that all actively involved views should receive a particular sequence of sub-events. In other embodiments, even if touch sub-events were entirely confined to the area associated with one particular view, views higher in the hierarchy would still remain as actively involved views.

Event dispatcher module 174 dispatches the event information to an event recognizer (e.g., event recognizer 180). In embodiments including active event recognizer determination module 173, event dispatcher module 174 delivers the event information to an event recognizer determined by active event recognizer determination module 173. In some embodiments, event dispatcher module 174 stores in an event queue the event information, which is retrieved by a respective event receiver 182.

In some embodiments, operating system 126 includes event sorter 170. Alternatively, application 136-1 includes event sorter 170. In yet other embodiments, event sorter 170 is a stand-alone module, or a part of another module stored in memory 102, such as contact/motion module 130.

In some embodiments, application 136-1 includes a plurality of event handlers 190 and one or more application views 191, each of which includes instructions for handling touch events that occur within a respective view of the application's user interface. Each application view 191 of the application 136-1 includes one or more event recognizers 180. Typically, a respective application view 191 includes a plurality of event recognizers 180. In other embodiments, one or more of event recognizers 180 are part of a separate module, such as a user interface kit or a higher level object from which application 136-1 inherits methods and other properties. In some embodiments, a respective event handler 190 includes one or more of: data updater 176, object updater 177, GUI updater 178, and/or event data 179 received from event sorter 170. Event handler 190 optionally utilizes or calls data updater 176, object updater 177, or GUI updater 178 to update the application internal state 192. Alternatively, one or more of the application views 191 include one or more respective event handlers 190. Also, in some embodiments, one or more of data updater 176, object updater 177, and GUI updater 178 are included in a respective application view 191.

A respective event recognizer **180** receives event information (e.g., event data **179**) from event sorter **170** and identifies an event from the event information. Event recognizer **180** includes event receiver **182** and event comparator **184**. In some embodiments, event recognizer **180** also includes at least a subset of: metadata **183**, and event delivery instructions **188** (which optionally include sub-event delivery instructions).

Event receiver **182** receives event information from event sorter **170**. The event information includes information about a sub-event, for example, a touch or a touch movement. Depending on the sub-event, the event information also includes additional information, such as location of the sub-event. When the sub-event concerns motion of a touch, the event information optionally also includes speed and direction of the sub-event. In some embodiments, events include rotation of the device from one orientation to another (e.g., from a portrait orientation to a landscape orientation, or vice versa), and the event information includes corresponding information about the current orientation (also called device attitude) of the device.

Event comparator **184** compares the event information to predefined event or sub-event definitions and, based on the comparison, determines an event or sub-event, or determines or updates the state of an event or sub-event. In some embodiments, event comparator **184** includes event definitions **186**. Event definitions **186** contain definitions of events (e.g., predefined sequences of sub-events), for example, event **1** (**187-1**), event **2** (**187-2**), and others. In some embodiments, sub-events in an event (**187**) include, for example, touch begin, touch end, touch movement, touch cancellation, and multiple touching. In one example, the definition for event **1** (**187-1**) is a double tap on a displayed object. The double tap, for example, comprises a first touch (touch begin) on the displayed object for a predetermined phase, a first liftoff (touch end) for a predetermined phase, a second touch (touch begin) on the displayed object for a predetermined phase, and a second liftoff (touch end) for a predetermined phase. In another example, the definition for event **2** (**187-2**) is a dragging on a displayed object. The dragging, for example, comprises a touch (or contact) on the displayed object for a predetermined phase, a movement of the touch across touch-sensitive display **112**, and liftoff of the touch (touch end). In some embodiments, the event also includes information for one or more associated event handlers **190**.

In some embodiments, event definition **187** includes a definition of an event for a respective user-interface object. In some embodiments, event comparator **184** performs a hit test to determine which user-interface object is associated with a sub-event. For example, in an application view in which three user-interface objects are displayed on touch-sensitive display **112**, when a touch is detected on touch-sensitive display **112**, event comparator **184** performs a hit test to determine which of the three user-interface objects is associated with the touch (sub-event). If each displayed object is associated with a respective event handler **190**, the event comparator uses the result of the hit test to determine which event handler **190** should be activated. For example, event comparator **184** selects an event handler associated with the sub-event and the object triggering the hit test.

In some embodiments, the definition for a respective event (**187**) also includes delayed actions that delay delivery of the event information until after it has been determined whether the sequence of sub-events does or does not correspond to the event recognizer's event type.

When a respective event recognizer **180** determines that the series of sub-events do not match any of the events in event definitions **186**, the respective event recognizer **180** enters an event impossible, event failed, or event ended state, after which it disregards subsequent sub-events of the touch-based gesture. In this situation, other event recognizers, if any, that remain active for the hit view continue to track and process sub-events of an ongoing touch-based gesture.

In some embodiments, a respective event recognizer **180** includes metadata **183** with configurable properties, flags, and/or lists that indicate how the event delivery system should perform sub-event delivery to actively involved event recognizers. In some embodiments, metadata **183** includes configurable properties, flags, and/or lists that indicate how event recognizers interact, or are enabled to interact, with one another. In some embodiments, metadata **183** includes configurable properties, flags, and/or lists that indicate whether sub-events are delivered to varying levels in the view or programmatic hierarchy.

In some embodiments, a respective event recognizer **180** activates event handler **190** associated with an event when one or more particular sub-events of an event are recognized. In some embodiments, a respective event recognizer **180** delivers event information associated with the event to event handler **190**. Activating an event handler **190** is distinct from sending (and deferred sending) sub-events to a respective hit view. In some embodiments, event recognizer **180** throws a flag associated with the recognized event, and event handler **190** associated with the flag catches the flag and performs a predefined process.

In some embodiments, event delivery instructions **188** include sub-event delivery instructions that deliver event information about a sub-event without activating an event handler. Instead, the sub-event delivery instructions deliver event information to event handlers associated with the series of sub-events or to actively involved views. Event handlers associated with the series of sub-events or with actively involved views receive the event information and perform a predetermined process.

In some embodiments, data updater **176** creates and updates data used in application **136-1**. For example, data updater **176** updates the telephone number used in contacts module **137**, or stores a video file used in video player module. In some embodiments, object updater **177** creates and updates objects used in application **136-1**. For example, object updater **177** creates a new user-interface object or updates the position of a user-interface object. GUI updater **178** updates the GUI. For example, GUI updater **178** prepares display information and sends it to graphics module **132** for display on a touch-sensitive display.

In some embodiments, event handler(s) **190** includes or has access to data updater **176**, object updater **177**, and GUI updater **178**. In some embodiments, data updater **176**, object updater **177**, and GUI updater **178** are included in a single module of a respective application **136-1** or application view **191**. In other embodiments, they are included in two or more software modules.

It shall be understood that the foregoing discussion regarding event handling of user touches on touch-sensitive displays also applies to other forms of user inputs to operate multifunction devices **100** with input devices, not all of which are initiated on touch screens. For example, mouse movement and mouse button presses, optionally coordinated with single or multiple keyboard presses or holds; contact movements such as taps, drags, scrolls, etc. on touchpads; pen stylus inputs; movement of the device; oral instructions;

35

detected eye movements; biometric inputs; and/or any combination thereof are optionally utilized as inputs corresponding to sub-events which define an event to be recognized.

FIG. 2 illustrates a portable multifunction device 100 having a touch screen 112 in accordance with some embodiments. The touch screen optionally displays one or more graphics within user interface (UI) 200. In this embodiment, as well as others described below, a user is enabled to select one or more of the graphics by making a gesture on the graphics, for example, with one or more fingers 202 (not drawn to scale in the figure) or one or more styluses 203 (not drawn to scale in the figure). In some embodiments, selection of one or more graphics occurs when the user breaks contact with the one or more graphics. In some embodiments, the gesture optionally includes one or more taps, one or more swipes (from left to right, right to left, upward and/or downward), and/or a rolling of a finger (from right to left, left to right, upward and/or downward) that has made contact with device 100. In some implementations or circumstances, inadvertent contact with a graphic does not select the graphic. For example, a swipe gesture that sweeps over an application icon optionally does not select the corresponding application when the gesture corresponding to selection is a tap.

Device 100 optionally also include one or more physical buttons, such as "home" or menu button 204. As described previously, menu button 204 is, optionally, used to navigate to any application 136 in a set of applications that are, optionally, executed on device 100. Alternatively, in some embodiments, the menu button is implemented as a soft key in a GUI displayed on touch screen 112.

In some embodiments, device 100 includes touch screen 112, menu button 204, push button 206 for powering the device on/off and locking the device, volume adjustment button(s) 208, subscriber identity module (SIM) card slot 210, headset jack 212, and docking/charging external port 124. Push button 206 is, optionally, used to turn the power on/off on the device by depressing the button and holding the button in the depressed state for a predefined time interval; to lock the device by depressing the button and releasing the button before the predefined time interval has elapsed; and/or to unlock the device or initiate an unlock process. In an alternative embodiment, device 100 also accepts verbal input for activation or deactivation of some functions through microphone 113. Device 100 also, optionally, includes one or more contact intensity sensors 165 for detecting intensity of contacts on touch screen 112 and/or one or more tactile output generators 167 for generating tactile outputs for a user of device 100.

FIG. 3 is a block diagram of an exemplary multifunction device with a display and a touch-sensitive surface in accordance with some embodiments. Device 300 need not be portable. In some embodiments, device 300 is a laptop computer, a desktop computer, a tablet computer, a multimedia player device, a navigation device, an educational device (such as a child's learning toy), a gaming system, or a control device (e.g., a home or industrial controller). Device 300 typically includes one or more processing units (CPUs) 310, one or more network or other communications interfaces 360, memory 370, and one or more communication buses 320 for interconnecting these components. Communication buses 320 optionally include circuitry (sometimes called a chipset) that interconnects and controls communications between system components. Device 300 includes input/output (I/O) interface 330 comprising display 340, which is typically a touch screen display. I/O interface 330 also optionally includes a keyboard and/or mouse (or

36

other pointing device) 350 and touchpad 355, tactile output generator 357 for generating tactile outputs on device 300 (e.g., similar to tactile output generator(s) 167 described above with reference to FIG. 1A), sensors 359 (e.g., optical, acceleration, proximity, touch-sensitive, and/or contact intensity sensors similar to contact intensity sensor(s) 165 described above with reference to FIG. 1A). Memory 370 includes high-speed random access memory, such as DRAM, SRAM, DDR RAM, or other random access solid state memory devices; and optionally includes non-volatile memory, such as one or more magnetic disk storage devices, optical disk storage devices, flash memory devices, or other non-volatile solid state storage devices. Memory 370 optionally includes one or more storage devices remotely located from CPU(s) 310. In some embodiments, memory 370 stores programs, modules, and data structures analogous to the programs, modules, and data structures stored in memory 102 of portable multifunction device 100 (FIG. 1A), or a subset thereof. Furthermore, memory 370 optionally stores additional programs, modules, and data structures not present in memory 102 of portable multifunction device 100. For example, memory 370 of device 300 optionally stores drawing module 380, presentation module 382, word processing module 384, website creation module 386, disk authoring module 388, and/or spreadsheet module 390, while memory 102 of portable multifunction device 100 (FIG. 1A) optionally does not store these modules.

Each of the above-identified elements in FIG. 3 is, optionally, stored in one or more of the previously mentioned memory devices. Each of the above-identified modules corresponds to a set of instructions for performing a function described above. The above-identified modules or programs (e.g., sets of instructions) need not be implemented as separate software programs, procedures, or modules, and thus various subsets of these modules are, optionally, combined or otherwise rearranged in various embodiments. In some embodiments, memory 370 optionally stores a subset of the modules and data structures identified above. Furthermore, memory 370 optionally stores additional modules and data structures not described above.

Attention is now directed towards embodiments of user interfaces that are, optionally, implemented on, for example, portable multifunction device 100.

FIG. 4A illustrates an exemplary user interface for a menu of applications on portable multifunction device 100 in accordance with some embodiments. Similar user interfaces are, optionally, implemented on device 300. In some embodiments, user interface 400 includes the following elements, or a subset or superset thereof:

- Signal strength indicator(s) 402 for wireless communication(s), such as cellular and Wi-Fi signals;
- Time 404;
- Bluetooth indicator 405;
- Battery status indicator 406;
- Tray 408 with icons for frequently used applications, such as:
 - Icon 416 for telephone module 138, labeled "Phone," which optionally includes an indicator 414 of the number of missed calls or voicemail messages;
 - Icon 418 for e-mail client module 140, labeled "Mail," which optionally includes an indicator 410 of the number of unread e-mails;
 - Icon 420 for browser module 147, labeled "Browser;" and
 - Icon 422 for video and music player module 152, also referred to as iPod (trademark of Apple Inc.) module 152, labeled "iPod;" and

Icons for other applications, such as:

- Icon **424** for IM module **141**, labeled “Messages;”
- Icon **426** for calendar module **148**, labeled “Calendar;”
- Icon **428** for image management module **144**, labeled “Photos;”
- Icon **430** for camera module **143**, labeled “Camera;”
- Icon **432** for online video module **155**, labeled “Online Video;”
- Icon **434** for stocks widget **149-2**, labeled “Stocks;”
- Icon **436** for map module **154**, labeled “Maps;”
- Icon **438** for weather widget **149-1**, labeled “Weather;”
- Icon **440** for alarm clock widget **149-4**, labeled “Clock;”
- Icon **442** for workout support module **142**, labeled “Workout Support;”
- Icon **444** for notes module **153**, labeled “Notes;” and
- Icon **446** for a settings application or module, labeled “Settings;” which provides access to settings for device **100** and its various applications **136**.

It should be noted that the icon labels illustrated in FIG. **4A** are merely exemplary. For example, icon **422** for video and music player module **152** is labeled “Music” or “Music Player.” Other labels are, optionally, used for various application icons. In some embodiments, a label for a respective application icon includes a name of an application corresponding to the respective application icon. In some embodiments, a label for a particular application icon is distinct from a name of an application corresponding to the particular application icon.

FIG. **4B** illustrates an exemplary user interface on a device (e.g., device **300**, FIG. **3**) with a touch-sensitive surface **451** (e.g., a tablet or touchpad **355**, FIG. **3**) that is separate from the display **450** (e.g., touch screen display **112**). Device **300** also, optionally, includes one or more contact intensity sensors (e.g., one or more of sensors **359**) for detecting intensity of contacts on touch-sensitive surface **451** and/or one or more tactile output generators **357** for generating tactile outputs for a user of device **300**.

Although some of the examples that follow will be given with reference to inputs on touch screen display **112** (where the touch-sensitive surface and the display are combined), in some embodiments, the device detects inputs on a touch-sensitive surface that is separate from the display, as shown in FIG. **4B**. In some embodiments, the touch-sensitive surface (e.g., **451** in FIG. **4B**) has a primary axis (e.g., **452** in FIG. **4B**) that corresponds to a primary axis (e.g., **453** in FIG. **4B**) on the display (e.g., **450**). In accordance with these embodiments, the device detects contacts (e.g., **460** and **462** in FIG. **4B**) with the touch-sensitive surface **451** at locations that correspond to respective locations on the display (e.g., in FIG. **4B**, **460** corresponds to **468** and **462** corresponds to **470**). In this way, user inputs (e.g., contacts **460** and **462**, and movements thereof) detected by the device on the touch-sensitive surface (e.g., **451** in FIG. **4B**) are used by the device to manipulate the user interface on the display (e.g., **450** in FIG. **4B**) of the multifunction device when the touch-sensitive surface is separate from the display. It should be understood that similar methods are, optionally, used for other user interfaces described herein.

Additionally, while the following examples are given primarily with reference to finger inputs (e.g., finger contacts, finger tap gestures, finger swipe gestures), it should be understood that, in some embodiments, one or more of the finger inputs are replaced with input from another input device (e.g., a mouse-based input or stylus input). For example, a swipe gesture is, optionally, replaced with a mouse click (e.g., instead of a contact) followed by move-

ment of the cursor along the path of the swipe (e.g., instead of movement of the contact). As another example, a tap gesture is, optionally, replaced with a mouse click while the cursor is located over the location of the tap gesture (e.g., instead of detection of the contact followed by ceasing to detect the contact). Similarly, when multiple user inputs are simultaneously detected, it should be understood that multiple computer mice are, optionally, used simultaneously, or a mouse and finger contacts are, optionally, used simultaneously.

FIG. **5A** illustrates exemplary personal electronic device **500**. Device **500** includes body **502**. In some embodiments, device **500** can include some or all of the features described with respect to devices **100** and **300** (e.g., FIGS. **1A-4B**). In some embodiments, device **500** has touch-sensitive display screen **504**, hereafter touch screen **504**. Alternatively, or in addition to touch screen **504**, device **500** has a display and a touch-sensitive surface. As with devices **100** and **300**, in some embodiments, touch screen **504** (or the touch-sensitive surface) optionally includes one or more intensity sensors for detecting intensity of contacts (e.g., touches) being applied. The one or more intensity sensors of touch screen **504** (or the touch-sensitive surface) can provide output data that represents the intensity of touches. The user interface of device **500** can respond to touches based on their intensity, meaning that touches of different intensities can invoke different user interface operations on device **500**.

Exemplary techniques for detecting and processing touch intensity are found, for example, in related applications: International Patent Application Serial No. PCT/US2013/040061, titled “Device, Method, and Graphical User Interface for Displaying User Interface Objects Corresponding to an application,” filed May 8, 2013, published as WIPO Publication No. WO/2013/169849, and International Patent Application Serial No. PCT/US2013/069483, titled “Device, Method, and Graphical User Interface for Transitioning Between Touch Input to Display Output Relationships,” filed Nov. 11, 2013, published as WIPO Publication No. WO/2014/105276, each of which is hereby incorporated by reference in their entirety.

In some embodiments, device **500** has one or more input mechanisms **506** and **508**. Input mechanisms **506** and **508**, if included, can be physical. Examples of physical input mechanisms include push buttons and rotatable mechanisms. In some embodiments, device **500** has one or more attachment mechanisms. Such attachment mechanisms, if included, can permit attachment of device **500** with, for example, hats, eyewear, earrings, necklaces, shirts, jackets, bracelets, watch straps, chains, trousers, belts, shoes, purses, backpacks, and so forth. These attachment mechanisms permit device **500** to be worn by a user.

FIG. **5B** depicts exemplary personal electronic device **500**. In some embodiments, device **500** can include some or all of the components described with respect to FIGS. **1A**, **1B**, and **3**. Device **500** has bus **512** that operatively couples I/O section **514** with one or more computer processors **516** and memory **518**. I/O section **514** can be connected to display **504**, which can have touch-sensitive component **522** and, optionally, intensity sensor **524** (e.g., contact intensity sensor). In addition, I/O section **514** can be connected with communication unit **530** for receiving application and operating system data, using Wi-Fi, Bluetooth, near field communication (NFC), cellular, and/or other wireless communication techniques. Device **500** can include input mechanisms **506** and/or **508**. Input mechanism **506** is, optionally, a rotatable input device or a depressible and

rotatable input device, for example. Input mechanism **508** is, optionally, a button, in some examples.

Input mechanism **508** is, optionally, a microphone, in some examples. Personal electronic device **500** optionally includes various sensors, such as GPS sensor **532**, accelerometer **534**, directional sensor **540** (e.g., compass), gyroscope **536**, motion sensor **538**, and/or a combination thereof, all of which can be operatively connected to I/O section **514**.

Memory **518** of personal electronic device **500** can include one or more non-transitory computer-readable storage mediums, for storing computer-executable instructions, which, when executed by one or more computer processors **516**, for example, can cause the computer processors to perform the techniques described below, including processes **700**, **900**, **1100**, **1300**, and **1500** (FIGS. 7, 9, 11, 13, and 15). A computer-readable storage medium can be any medium that can tangibly contain or store computer-executable instructions for use by or in connection with the instruction execution system, apparatus, or device. In some examples, the storage medium is a transitory computer-readable storage medium. In some examples, the storage medium is a non-transitory computer-readable storage medium. The non-transitory computer-readable storage medium can include, but is not limited to, magnetic, optical, and/or semiconductor storages. Examples of such storage include magnetic disks, optical discs based on CD, DVD, or Blu-ray technologies, as well as persistent solid-state memory such as flash, solid-state drives, and the like. Personal electronic device **500** is not limited to the components and configuration of FIG. 5B, but can include other or additional components in multiple configurations.

As used here, the term “affordance” refers to a user-interactive graphical user interface object that is, optionally, displayed on the display screen of devices **100**, **300**, and/or **500** (FIGS. 1A, 3, and 5A-5B). For example, an image (e.g., icon), a button, and text (e.g., hyperlink) each optionally constitute an affordance.

As used herein, the term “focus selector” refers to an input element that indicates a current part of a user interface with which a user is interacting. In some implementations that include a cursor or other location marker, the cursor acts as a “focus selector” so that when an input (e.g., a press input) is detected on a touch-sensitive surface (e.g., touchpad **355** in FIG. 3 or touch-sensitive surface **451** in FIG. 4B) while the cursor is over a particular user interface element (e.g., a button, window, slider, or other user interface element), the particular user interface element is adjusted in accordance with the detected input. In some implementations that include a touch screen display (e.g., touch-sensitive display system **112** in FIG. 1A or touch screen **112** in FIG. 4A) that enables direct interaction with user interface elements on the touch screen display, a detected contact on the touch screen acts as a “focus selector” so that when an input (e.g., a press input by the contact) is detected on the touch screen display at a location of a particular user interface element (e.g., a button, window, slider, or other user interface element), the particular user interface element is adjusted in accordance with the detected input. In some implementations, focus is moved from one region of a user interface to another region of the user interface without corresponding movement of a cursor or movement of a contact on a touch screen display (e.g., by using a tab key or arrow keys to move focus from one button to another button); in these implementations, the focus selector moves in accordance with movement of focus between different regions of the user interface. Without regard to the specific form taken by the focus selector, the focus selector is generally the user interface element (or

contact on a touch screen display) that is controlled by the user so as to communicate the user’s intended interaction with the user interface (e.g., by indicating, to the device, the element of the user interface with which the user is intending to interact). For example, the location of a focus selector (e.g., a cursor, a contact, or a selection box) over a respective button while a press input is detected on the touch-sensitive surface (e.g., a touchpad or touch screen) will indicate that the user is intending to activate the respective button (as opposed to other user interface elements shown on a display of the device).

As used in the specification and claims, the term “characteristic intensity” of a contact refers to a characteristic of the contact based on one or more intensities of the contact. In some embodiments, the characteristic intensity is based on multiple intensity samples. The characteristic intensity is, optionally, based on a predefined number of intensity samples, or a set of intensity samples collected during a predetermined time period (e.g., 0.05, 0.1, 0.2, 0.5, 1, 2, 5, 10 seconds) relative to a predefined event (e.g., after detecting the contact, prior to detecting liftoff of the contact, before or after detecting a start of movement of the contact, prior to detecting an end of the contact, before or after detecting an increase in intensity of the contact, and/or before or after detecting a decrease in intensity of the contact). A characteristic intensity of a contact is, optionally, based on one or more of: a maximum value of the intensities of the contact, a mean value of the intensities of the contact, an average value of the intensities of the contact, a top 10 percentile value of the intensities of the contact, a value at the half maximum of the intensities of the contact, a value at the 90 percent maximum of the intensities of the contact, or the like. In some embodiments, the duration of the contact is used in determining the characteristic intensity (e.g., when the characteristic intensity is an average of the intensity of the contact over time). In some embodiments, the characteristic intensity is compared to a set of one or more intensity thresholds to determine whether an operation has been performed by a user. For example, the set of one or more intensity thresholds optionally includes a first intensity threshold and a second intensity threshold. In this example, a contact with a characteristic intensity that does not exceed the first threshold results in a first operation, a contact with a characteristic intensity that exceeds the first intensity threshold and does not exceed the second intensity threshold results in a second operation, and a contact with a characteristic intensity that exceeds the second threshold results in a third operation. In some embodiments, a comparison between the characteristic intensity and one or more thresholds is used to determine whether or not to perform one or more operations (e.g., whether to perform a respective operation or forgo performing the respective operation), rather than being used to determine whether to perform a first operation or a second operation.

In some embodiments, a portion of a gesture is identified for purposes of determining a characteristic intensity. For example, a touch-sensitive surface optionally receives a continuous swipe contact transitioning from a start location and reaching an end location, at which point the intensity of the contact increases. In this example, the characteristic intensity of the contact at the end location is, optionally, based on only a portion of the continuous swipe contact, and not the entire swipe contact (e.g., only the portion of the swipe contact at the end location). In some embodiments, a smoothing algorithm is, optionally, applied to the intensities of the swipe contact prior to determining the characteristic intensity of the contact. For example, the smoothing algo-

algorithm optionally includes one or more of: an unweighted sliding-average smoothing algorithm, a triangular smoothing algorithm, a median filter smoothing algorithm, and/or an exponential smoothing algorithm. In some circumstances, these smoothing algorithms eliminate narrow spikes or dips in the intensities of the swipe contact for purposes of determining a characteristic intensity.

The intensity of a contact on the touch-sensitive surface is, optionally, characterized relative to one or more intensity thresholds, such as a contact-detection intensity threshold, a light press intensity threshold, a deep press intensity threshold, and/or one or more other intensity thresholds. In some embodiments, the light press intensity threshold corresponds to an intensity at which the device will perform operations typically associated with clicking a button of a physical mouse or a trackpad. In some embodiments, the deep press intensity threshold corresponds to an intensity at which the device will perform operations that are different from operations typically associated with clicking a button of a physical mouse or a trackpad. In some embodiments, when a contact is detected with a characteristic intensity below the light press intensity threshold (e.g., and above a nominal contact-detection intensity threshold below which the contact is no longer detected), the device will move a focus selector in accordance with movement of the contact on the touch-sensitive surface without performing an operation associated with the light press intensity threshold or the deep press intensity threshold. Generally, unless otherwise stated, these intensity thresholds are consistent between different sets of user interface figures.

An increase of characteristic intensity of the contact from an intensity below the light press intensity threshold to an intensity between the light press intensity threshold and the deep press intensity threshold is sometimes referred to as a “light press” input. An increase of characteristic intensity of the contact from an intensity below the deep press intensity threshold to an intensity above the deep press intensity threshold is sometimes referred to as a “deep press” input. An increase of characteristic intensity of the contact from an intensity below the contact-detection intensity threshold to an intensity between the contact-detection intensity threshold and the light press intensity threshold is sometimes referred to as detecting the contact on the touch-surface. A decrease of characteristic intensity of the contact from an intensity above the contact-detection intensity threshold to an intensity below the contact-detection intensity threshold is sometimes referred to as detecting liftoff of the contact from the touch-surface. In some embodiments, the contact-detection intensity threshold is zero. In some embodiments, the contact-detection intensity threshold is greater than zero.

In some embodiments described herein, one or more operations are performed in response to detecting a gesture that includes a respective press input or in response to detecting the respective press input performed with a respective contact (or a plurality of contacts), where the respective press input is detected based at least in part on detecting an increase in intensity of the contact (or plurality of contacts) above a press-input intensity threshold. In some embodiments, the respective operation is performed in response to detecting the increase in intensity of the respective contact above the press-input intensity threshold (e.g., a “down stroke” of the respective press input). In some embodiments, the press input includes an increase in intensity of the respective contact above the press-input intensity threshold and a subsequent decrease in intensity of the contact below the press-input intensity threshold, and the respective operation is performed in response to detecting the subsequent

decrease in intensity of the respective contact below the press-input threshold (e.g., an “up stroke” of the respective press input).

In some embodiments, the device employs intensity hysteresis to avoid accidental inputs sometimes termed “jitter,” where the device defines or selects a hysteresis intensity threshold with a predefined relationship to the press-input intensity threshold (e.g., the hysteresis intensity threshold is X intensity units lower than the press-input intensity threshold or the hysteresis intensity threshold is 75%, 90%, or some reasonable proportion of the press-input intensity threshold). Thus, in some embodiments, the press input includes an increase in intensity of the respective contact above the press-input intensity threshold and a subsequent decrease in intensity of the contact below the hysteresis intensity threshold that corresponds to the press-input intensity threshold, and the respective operation is performed in response to detecting the subsequent decrease in intensity of the respective contact below the hysteresis intensity threshold (e.g., an “up stroke” of the respective press input). Similarly, in some embodiments, the press input is detected only when the device detects an increase in intensity of the contact from an intensity at or below the hysteresis intensity threshold to an intensity at or above the press-input intensity threshold and, optionally, a subsequent decrease in intensity of the contact to an intensity at or below the hysteresis intensity, and the respective operation is performed in response to detecting the press input (e.g., the increase in intensity of the contact or the decrease in intensity of the contact, depending on the circumstances).

For ease of explanation, the descriptions of operations performed in response to a press input associated with a press-input intensity threshold or in response to a gesture including the press input are, optionally, triggered in response to detecting either: an increase in intensity of a contact above the press-input intensity threshold, an increase in intensity of a contact from an intensity below the hysteresis intensity threshold to an intensity above the press-input intensity threshold, a decrease in intensity of the contact below the press-input intensity threshold, and/or a decrease in intensity of the contact below the hysteresis intensity threshold corresponding to the press-input intensity threshold. Additionally, in examples where an operation is described as being performed in response to detecting a decrease in intensity of a contact below the press-input intensity threshold, the operation is, optionally, performed in response to detecting a decrease in intensity of the contact below a hysteresis intensity threshold corresponding to, and lower than, the press-input intensity threshold.

Attention is now directed towards embodiments of user interfaces (“UI”) and associated processes that are implemented on an electronic device, such as portable multifunction device **100**, device **300**, or device **500**.

FIGS. 6A-6EE illustrate exemplary user interfaces for displaying personalized workout suggestions based on completed workouts, in accordance with some embodiments. In some embodiments, the personalized workout suggestions represent workout content (e.g., audio and/or video) that prompt a user to perform a particular type of physical activity for a predetermined duration of time. The user interfaces in these figures are used to illustrate the processes described below, including the processes in FIG. 7.

FIG. 6A depicts electronic device **600**, which is a smartphone with display **602**. Display **602** of electronic device **600** includes a touch-sensitive surface on which electronic device **600** can detect user gestures (e.g., tap, swipe, and/or

drag). In some embodiments, electronic device 600 includes one or more features of electronic device 100, 300, and/or 500.

At FIG. 6A, while displaying home screen 604, electronic device 600 detects input 606B at a location corresponding to application icon 606A.

At FIG. 6B, in response to detecting input 606B, electronic device 600 launches an activity (e.g., physical activity) application. Launching the activity application includes replacing display of home screen 604 with history user interface 608 of the activity application. Additionally, electronic device 600 displays a plurality of options near the bottom of display 602, including option 610A. While displaying history user interface 608, electronic device 600 detects input 610B at a location corresponding to option 610A.

At FIG. 6C, in response to detecting input 610B, electronic device 600 replaces display of history user interface 608 with workout user interface 612. Workout user interface 612 includes options 614A-614D for filtering workouts based on exercise type (e.g., treadmill, cycling, rowing, core, high-intensity interval training (HIIT), yoga, and the like). Additionally, workout user interface 612 includes a plurality of workout suggestions for a user, where the workout suggestions are based on one or more workouts that have been completed by the user. For example, workout suggestion 616A represents a workout that shares one or more characteristics with a subset of workouts completed by the user (e.g., the most recently completed workout). Here, the user most recently completed a core workout with a different trainer, Emma. Accordingly, electronic device 600 provides workout suggestion 616A, as it represents a workout that has a shared characteristic with the user's most recently completed workout. In particular, the workout represented by workout suggestion 616A and the user's most recently completed workout have the same exercise type (core). Examples of shared characteristics include exercise type, duration, music, and trainer. Workout suggestion 616C, similar to workout suggestion 616A, shares one or more characteristics with a subset of workouts completed by the user. In contrast to workout suggestion 616A, which is based on the most recently completed workout, workout suggestion 616C is based on one or more workouts that have been completed in a predetermined amount of time (e.g., past 30, 60, or 90 days). For example, the user has completed ten workouts in the past 30 days, where the most common exercise type among the ten workouts is HIIT. As a result, electronic device 600 displays workout suggestion 616C, which represents a workout with the HIIT exercise type (e.g., the exercise type that is most common among the user's completed workouts in a predetermined period of time). While displaying workout user interface 612, electronic device 600 detects input 618 at a location corresponding to workout suggestion 616A.

At FIG. 6D, in response to detecting input 618, electronic device 600 replaces display of workout user interface 612 with detail user interface 620. Detail user interface 620 includes characteristics of the workout represented by workout suggestion 616A. For example, detail user interface 620 includes exercise type 622A, trainer 622B, duration 622C, music 622D, required equipment 622E, and completion indication 622F.

Detail user interface 620 also includes an option 623A that can be selected by a user to play video content corresponding to the workout (e.g., a video that demonstrates the workout), and an option 623B that can be selected by a user to play a preview video corresponding to the workout. In

some embodiments, the preview video is different from the video content corresponding to the workout. For example, the preview video can include a subset of the video content corresponding to the workout, and can be shorter in duration than the video content corresponding to the workout.

Detail user interface 620 also includes a music section 625 that identifies a music playlist comprising one or more music tracks that correspond to the workout. For example, the music section 625 can identify a music playlist comprising one or more music tracks that are played during the workout. The music section 625 includes an option 623C that is selectable by a user to open the full music playlist (e.g., all of the music tracks listed in the music section) in a separate music application. The music section 625 also includes options 623D, 623E, that correspond to individual music tracks, and are selectable by a user to open the individual music tracks in the separate music application (e.g., without opening other music tracks in the music playlist in the separate music application).

While displaying detail user interface 620, electronic device 600 detects input 624B at a location corresponding to option 624A.

At FIG. 6E, in response to detecting input 624B, electronic device 600 replaces display of detail user interface 620 with workout user interface 612. While displaying detail user interface 620, electronic device 600 detects input 626 with movement in the right-to-left direction at a location corresponding to workout suggestion 616A.

At FIG. 6F, in response to detecting input 626, electronic device 600 slides a portion of workout suggestion 616A off display 602, and slides workout suggestion 616B onto display 602. Additionally, electronic device 600 slides a portion of workout suggestion 616E onto display 602. In some embodiments, in response to detecting input 610B, electronic device 600 displays workout suggestion 616B instead of workout suggestion 616A (e.g., in accordance with a determination that the user has completed a workout that is part of a workout program, in accordance with a determination that the most recently completed workout is part of a workout program (e.g., predefined sequence of workouts or a workout series with multiple episodes). For example, in contrast to FIG. 6C, electronic device 600 displays workout suggestion 616B (Episode 2: Treadmill) as the first personalized suggestion in place of workout suggestion 616A (Core with Amy). In some embodiments, electronic device 600 displays workout suggestion 616B (Episode 2: Treadmill) as the first personalized suggestion if the user has completed a workout that is part of a workout program (Find Your Fast). Alternatively, as depicted in FIG. 6C, electronic device 600 displays workout suggestion 616A as the first personalized suggestion if the user has not completed a workout that is part of a workout program, in accordance with some embodiments. While displaying workout user interface 612, electronic device 600 detects input 628 at a location corresponding to workout suggestion 616B.

At FIG. 6G, in response to detecting input 628, electronic device 600 replaces display of workout user interface 612 with program user interface 630. Program user interface 630 includes a plurality of workout suggestions corresponding to a particular workout program (e.g., Find Your Fast). The workout program consists of a plurality of workout content items that are ordered in a predefined sequence. In accordance with a determination that a workout in the workout program has been completed, electronic device 600 visually emphasizes, using a border, the workout suggestion corresponding to the workout that comes next in the predefined

45

sequence of workouts in the workout program. For example, electronic device 600 visually emphasizes workout suggestion 634 in accordance with a determination that the workout corresponding to workout suggestion 632A has been completed. Workout suggestion 634, which matches workout suggestion 632B, corresponds to the workout that is next in the sequence of workouts. Additionally, indication 632AA indicates that the workout corresponding to workout suggestion 632A has been completed. Program user interface 630 also includes an option 632BB that is selectable by a user to open and play a program introduction video. The program introduction video is separate and different from the workouts in the workout program. In some embodiments, the program introduction video comprises audio and/or visual clips (e.g., images or video clips) from some or all of the workouts in the workout program. In some embodiments, selection of a particular workout suggestion 632A, 632B, 632C causes display of a corresponding detail user interface (similar to the detail user interface 620 of FIG. 6D). In some embodiments, the detail user interface for each workout can include a selectable option for playing video content corresponding to the workout (e.g., playing a video that demonstrates the workout), and a separate selectable option for playing the program introduction video (e.g., similar to options 623A and 623B in FIG. 6D). While displaying program user interface 630, electronic device 600 detects input 624C at a location corresponding to option 624A.

At FIG. 6H, in response to detecting input 624C, electronic device 600 replaces display of program user interface 630 with workout user interface 612. While displaying workout user interface 612, electronic device 600 detects input 636 with movement in an upward direction.

At FIG. 6I, in response to detecting input 636, electronic device 600 scrolls workout user interface 612. Scrolling workout user interface 612 includes sliding at least a portion of workout suggestions (e.g., 616A, 616B, and 616E) off display 602 (e.g., as shown in FIG. 6J). Scrolling workout user interface 612 includes modifying workout suggestion 616B to occupy a smaller portion of display 602 as compared to FIG. 6H. Scrolling workout user interface 612 includes sliding workout suggestions 616F-616I onto display 602. Workout suggestions 616F-616I represent workouts that have been recently made available (e.g., within a predetermined amount of time (e.g., past day, week, month)). Scrolling workout user interface 612 includes ceasing to display options 614A-614D. In some embodiments, electronic device 600 maintains display of options 614A-614D in response to detecting input 636. While displaying workout user interface 612, electronic device 600 detects input 638 with movement in an upward direction.

At FIG. 6J, in response to detecting input 638, electronic device 600 scrolls workout user interface 612. Scrolling workout user interface 612 includes sliding workout suggestions 616J-616Q onto display 602. Workout suggestions 616J-616Q represent new workouts that have not been completed by the user. In some embodiments, scrolling workout user interface 612 includes displaying workouts that are complementary to completed workouts. In some embodiments, a workout that is complementary to a completed workout is a workout that balances the physical activity performed in the completed workout. For example, running requires physical activity that can cause muscles to shorten. Accordingly, yoga is a complementary workout to running, as yoga promotes lengthening of muscles.

In some embodiments, completed workouts include workouts that are not accessible via workout user interface 612.

46

For example, electronic device 600 determines that the user has completed a running workout, where the running workout is not represented in workout user interface 612. In some embodiments, in response to detecting input 638, electronic device 600 displays workout suggestion 616J based at least in part on a determination that the workout represented by workout suggestion 616J is complementary to completed workouts (e.g., yoga is complementary to running). In some embodiments, electronic device 600 displays workouts that do not share one or more characteristics with completed workouts. For example, electronic device 600 determines that the user has completed workouts with the core exercise type. In some embodiments, in response to detecting input 638, electronic device 600 displays workout suggestion 616K based at least in part on a determination that the workout represented by workout suggestion 616K does not share one or more characteristics with completed workouts (e.g., new trainer (e.g., Matt)) and/or does share one or more characteristics with completed workouts (e.g., same exercise type (e.g., core)). Additionally, scrolling workout user interface 612 includes sliding workout suggestions 616L-616Q onto display 602. Workout suggestions 616L-616Q represent popular workouts that have been frequently selected by a group of users. While displaying workout user interface 612, electronic device 600 detects input 640 with movement in an upward direction.

At FIG. 6K, in response to detecting input 640, electronic device 600 scrolls workout user interface 612. Scrolling workout user interface 612 includes sliding workout suggestions 616R-616U onto display 602. Workout suggestions 616R-616S represent audio content that has a duration corresponding to the amount of time required to walk a predefined distance (e.g., 1, 2, or 3 miles). Workout suggestions 616T-616U represent audio content corresponding to a predefined route at or near one or more physical locations (e.g., a 5 kilometer route in Hackney). Additionally, scrolling workout user interface 612 includes displaying options 644A-644E for filtering workouts based on the trainer. While displaying workout user interface 612, electronic device 600 detects input 642 with movement in an upward direction.

At FIG. 6L, in response to detecting input 642, electronic device 600 scrolls workout user interface 612 such that the end of workout user interface 612 has been reached. Scrolling workout user interface 612 includes displaying a library of workouts that the user has previously saved, including saved workouts 646A-646B. Workout user interface 612 includes option 648A which, when selected, initiates a process for downloading the workout content represented by saved workout 646A to electronic device 600. Additionally, workout user interface 612 includes indication 648B, which indicates that the workout content represented by saved workout 646B has already been downloaded to electronic device 600. Workout user interface 612 also includes option 648C which, when selected, replaces display of workout user interface 612 with a different user interface that displays all workouts that have already been downloaded to electronic device 600. While displaying workout user interface 612, electronic device 600 detects input 650 at a location within a predefined region near the top of display 602.

At FIG. 6M, in response to detecting input 650, electronic device 600 scrolls to the top of workout user interface 612, resulting in display of options 614A-614D. While displaying workout user interface 612, electronic device 600 detects input 652 at a location corresponding to option 614C.

At FIG. 6N, in response to detecting input 652, electronic device 600 replaces display of workout user interface 612

with display of filter user interface **654**. Filter user interface **654** includes filtered workout suggestions **660A-660D** based on selected option **614C**. Additionally, filter user interface **654** includes indication **656**, which indicates the characteristic (e.g., rowing) that filtered workout suggestions **660A-660D** have in common. In the depicted scenario, the filtered workout suggestions **660A-660D** all have a particular workout type (or workout modality) in common (e.g., rowing). The filter user interface **654** includes an option **660E** that is selectable by a user to open and play a workout modality introduction video. The workout modality introduction video is separate and different from the workouts corresponding to filtered workout suggestions **660A-660D**. In some embodiments, the workout modality introduction video can identify for a user any equipment that is required for the workout modality (e.g., a rowing machine can be required for the rowing workouts). While displaying filter user interface **654**, electronic device **600** detects input **658B** at a location corresponding to option **658A**.

At FIG. **6O**, in response to detecting input **658B**, electronic device **600** displays filter user interface **662** with additional options for filtering workouts (e.g., in addition to exercise type, which is currently filtered for rowing). For example, filter user interface **662** includes options **664A-664H** for filtering workouts based on the trainer, options **666A-666E** for filtering workouts based on duration of the workout, and options **668A-668F** for filtering workouts based on music genre. Electronic device **600** obscures (e.g., dims) options **664A** and **664H** based at least in part on a determination that the trainers represented by options **664A** and options **664H** do not satisfy the currently selected filter(s) (e.g., Emma and Joyce do not have any rowing workouts). While displaying filter user interface **662**, electronic device **600** detects input **670** at a location corresponding to option **664E**.

At FIG. **6P**, in response to detecting input **670**, electronic device **600** visually emphasizes option **664E** to indicate that option **664E** has been selected. Additionally, in response to detecting input **670**, electronic device **600** obscures (e.g., dims) option **668A** based at least in part on a determination that the music genre represented by option **668A** does not satisfy the currently selected filter(s) (e.g., Joe does not have any workouts with pop music). Similarly, in response to detecting input **670**, electronic device **600** obscures (e.g., dims) option **666E** based at least in part on a determination that the duration represented by option **666E** does not satisfy the currently selected filter(s) (e.g., Joe does not have any workouts with a duration of 40 minutes). While displaying filter user interface **662**, electronic device **600** detects input **672** at a location corresponding to option **664F**.

At FIG. **6Q**, in response to detecting input **672**, electronic device **600** visually emphasizes option **664F** to indicate that option **664F** has been selected. Additionally, in response to detecting input **670**, electronic device **600** ceases to obscure (e.g., dim) option **666E** based at least in part on a determination that the duration represented by option **666E** does satisfy the currently selected filter(s) (e.g., Gregg has at least one workout with a duration of 40 minutes). While displaying filter user interface **662**, electronic device **600** detects input **674A** at a location corresponding to option **666D**, input **674B** at a location corresponding to option **668D**, and input **674C** at a location corresponding to option **668F**.

At FIG. **6R**, in response to detecting the set of inputs (e.g., **674A-674C**), electronic device **600** visually emphasizes options **666D**, **668D**, and **668F** to indicate that the respective options have been selected. While displaying filter user

interface **662**, electronic device **600** detects input **676** with movement in a downward direction.

At FIG. **6S**, in response to detecting input **676**, electronic device **600** ceases to display filter user interface **662** and displays filter user interface **654** with updates to the filtered workout suggestions based on selections detected at filter user interface **662**. Due to the filter selections, filter user interface **654** no longer includes filtered workout suggestions **660A-660C**. Instead, filter user interface **654** has been updated to include filtered workout suggestions **660D-660F**. Additionally, filter user interface **654** includes filter representations **678A-678E**, where a respective filter representation corresponds to a filter option selected at filter user interface **662**. While displaying filter user interface **654**, electronic device **600** detects input **680** at a location corresponding to filter representation **678C**.

At FIG. **6T**, in response to detecting input **680**, electronic device **600** ceases to display filter representation **678C**, as the 30 minute filter has been removed from the filter selections. Additionally, in response to detecting input **680**, electronic device **600** updates the filtered workout suggestions based on the updated filter selections. Due to the updated filter selections, filter user interface **654** includes filtered workout suggestion **660G**, which can be included with its 20 minute duration due to the removal of the 30 minute filter.

In some embodiments, instead of detecting selection of option **614C** to filter based on exercise type, electronic device **600** detects selection of an option for filtering based on trainer. In some embodiments, electronic device **600** detects an input at a location corresponding to option **644A** of FIG. **6L**. At FIG. **6U**, in response to detecting the input, electronic device **600** displays filter user interface **682**. Filter user interface **682** includes filtered workout suggestions **684A-684D** based on selected option **644A**. Additionally, filter user interface **682** includes indication **683**, which indicates the characteristic (e.g., Amy) that filtered workout suggestions **684-684D** have in common. While displaying filter user interface **682**, electronic device **600** detects input **658C** at a location corresponding to option **658A**.

At FIG. **6V**, in response to detecting input **658C**, electronic device **600** displays filter user interface **686** with additional options for filtering workouts (e.g., in addition to trainer, which is currently filtered for Amy). For example, filter user interface **686** includes options **688A-688F** for filtering workouts based on exercise (e.g., workout) type, options **666A-666E** for filtering workouts based on duration of the workout, and options **668A-668F** for filtering workouts based on music genre.

FIG. **6W** depicts another example of a workout user interface **612A**, similar to the workout user interface **612**. The features described with reference to workout user interface **612A** can be incorporated into workout user interface **612**, and the features described with reference to workout user interface **612** can be incorporated into workout user interface **612A**. Identical features in workout user interface **612A** are labeled with the same reference numbers as used in workout user interface **612**. Similar to workout user interface **612**, workout user interface **612A** includes options **614A-614D** for filtering workouts based on exercise type, as well as workout suggestions **616C-616D** that are selected based on the user's past workouts. Workout user interface **612A** includes a weekly roundup option **615A**. Selection of the weekly roundup option **615A** causes playback of a weekly roundup video corresponding to a current week. For example, in some embodiments, a new weekly roundup video can be posted each week (e.g., each Sunday),

and the weekly roundup video can introduce new workouts that were added to the workout application that week. In FIG. 6W, the current date is Aug. 16, 2020, and selection of the weekly roundup option 615A causes playback of a weekly roundup video corresponding to that week. In FIG. 6W1, the current date is Aug. 23, 2020, and a new weekly roundup option 615B corresponding to a different weekly roundup video (e.g., a weekly roundup video corresponding to the week of Aug. 23, 2020) is presented in the workout user interface 612A. At FIG. 6W1, while displaying workout user interface 612A, electronic device 600 detects input 617 with movement in an upward direction.

At FIG. 6X, in response to detecting input 617, electronic device 600 scrolls workout user interface 612A. Scrolling workout user interface 612A includes sliding workout suggestions 616J, 616K, 616V, 616W onto display 602. Workout suggestions 616J and 616K, like workout suggestions 616J and 616K in FIG. 6J, are workout suggestions that have been selected based on being complementary to previous workouts performed by the user. Workout suggestion 616V, like workout suggestions 616F, 616H, 616G, and 616I of FIG. 6I, are workout suggestions corresponding to new workouts that have been added to the application within the last week. Workout suggestion 616W, like workout suggestion 616B of FIG. 6H, is a workout suggestion corresponding to a workout program comprising an ordered series of workouts. While displaying workout user interface 612A, electronic device 600 detects input 619 with movement in an upward direction.

At FIG. 6Y, in response to detecting input 619, electronic device 600 scrolls workout user interface 612A. Scrolling workout user interface 612A includes sliding workout suggestions 616X, 616Y, and 616Z and options 644A-644E onto display 602. Workout suggestions 616X, 616Y, and 616Z, like workout suggestions 616L-616Q of FIG. 6J, are workout suggestions corresponding to workouts that are popular on the workout application. Options 644A-644E are identical to options 644A-644E of FIG. 6K, and can be selected to filter workout suggestions based on trainer. While displaying workout user interface 612A, electronic device 600 detects input 621 with movement in an upward direction.

At FIG. 6Z, in response to detecting input 621, electronic device 600 scrolls workout user interface 612A. Scrolling workout user interface 612A includes sliding workout suggestions 616AA, and saved workouts 646A, 646B onto display 602. Workout suggestion 616AA is similar to workout suggestion 616R of FIG. 6K, and is a workout suggestion representing an audio workout. Saved workouts 646A, 646B are identical to saved workouts 646A, 646B of FIG. 6L. While displaying workout user interface 623, electronic device 600 detects input 623 with movement in a downward direction.

At FIG. 6AA, in response to detecting input 623, electronic device 600 scrolls workout user interface 612A to once again reveal workout suggestions 616J, 616K, 616V, and 616W (as were previously depicted in FIG. 6X). While displaying workout user interface 612A, electronic device 600 detects input 627 at a location corresponding to workout suggestion 616W.

At FIG. 6BB, in response to detecting input 627, electronic device 600 replaces display of workout user interface 612A with program user interface 630A. Program user interface 630A is similar to program user interface 630 of FIG. 6G. Various features of program user interface 630A can be incorporated into program user interface 630, and various features of program user interface 630 can be

incorporated into program user interface 630A. Program user interface 630A includes a plurality of workout suggestions corresponding to a particular workout program (e.g., Yoga for Runners with Celebrity X). Scrolling down in the program user interface 630A (e.g., via user input 629) reveals a plurality of workout suggestions 635A-D in FIG. 6CC. The workout program consists of a plurality of workout content items that are ordered in a predefined sequence. In accordance with a determination that a workout in the workout program has been completed, electronic device 600 visually emphasizes, using a border, the workout suggestion corresponding to the workout that comes next in the predefined sequence of workouts in the workout program. For example, electronic device 600 visually emphasizes workout suggestion 634A in accordance with a determination that the workout corresponding to workout suggestion 635A has been completed. Workout suggestion 634A, which matches workout suggestion 635B, corresponds to the workout that is next in the sequence of workouts. Program user interface 630 also includes an option 634B that is selectable by a user to open and play a program introduction video. The program introduction video is separate and different from the workouts in the workout program. In some embodiments, the program introduction video comprises audio and/or visual clips (e.g., images or video clips) from some or all of the workouts in the workout program. In some embodiments, selection of a particular workout suggestion 634A, 635A-635D causes display of a corresponding detail user interface (similar to the detail user interface 620 of FIG. 6D). In some embodiments, the detail user interface for each workout can include a selectable option for playing video content corresponding to the workout, and a separate selectable option for playing the program introduction video (e.g., similar to options 623A and 623B in FIG. 6D).

FIG. 6DD displays a workout modality user interface 654A. Workout modality user interface 654A is similar to filter user interface 654 of FIG. 6N. Various features of workout modality user interface 654A can be incorporated into filter user interface 654, and various features of filter user interface 654 can be incorporated into workout modality user interface 654A. In some embodiments, workout modality user interface 654A can be displayed in response to a user input corresponding to 614B (e.g., in FIG. 6W or in FIG. 6M). Workout modality user interface 654A includes filtered workout suggestions 660F-660H based on selected option 614B. In the depicted scenario, the filtered workout suggestions 660F-660H all have a particular workout type (or workout modality) in common (e.g., cycling). The workout modality user interface 654A includes an option 660I that is selectable by a user to open and play a workout modality introduction video. The workout modality introduction video is separate and different from the workouts corresponding to filtered workout suggestions 660F-660H. In some embodiments, the workout modality introduction video can identify for a user any equipment that is required for the workout modality (e.g., a stationary bike can be required for the cycling workouts). While displaying workout modality user interface 654A, electronic device 600 detects input 661 at a location corresponding to option 660I.

At FIG. 6EE, in response to detecting input 661, electronic device 600 initiates playback of workout modality introduction video 661A.

FIG. 7 is a flow diagram illustrating a method for navigating and displaying workout suggestions using an electronic device, in accordance with some embodiments. Method 700 is performed at an electronic device (e.g., 100, 300, 500, 600) with a display (e.g., 602). Some operations in

51

method **700** are, optionally, combined, the orders of some operations are, optionally, changed, and some operations are, optionally, omitted.

As described below, method **700** provides an intuitive way for navigating and displaying workout suggestions. The method reduces the cognitive burden on a user for navigating and displaying workout suggestions, thereby creating a more efficient human-machine interface. For battery-operated computing devices, enabling a user to navigate and display workout suggestions faster and more efficiently conserves power and increases the time between battery charges.

In some embodiments, the electronic device (e.g., **100**, **300**, **500**, **600**, **800**) is a computer system. The computer system is optionally in communication (e.g., wired communication, wireless communication) with a display generation component and with one or more input devices. The display generation component is configured to provide visual output, such as display via a CRT display, display via an LED display, or display via image projection. In some embodiments, the display generation component is integrated with the computer system. In some embodiments, the display generation component is separate from the computer system. The one or more input devices are configured to receive input, such as a touch-sensitive surface receiving user input. In some embodiments, the one or more input devices are integrated with the computer system. In some embodiments, the one or more input devices are separate from the computer system. Thus, the computer system can transmit, via a wired or wireless connection, data (e.g., image data or video data) to an integrated or external display generation component to visually produce the content (e.g., using a display device) and can receive, a wired or wireless connection, input from the one or more input devices.

The electronic device displays (**702**), on the display (e.g., **602**), a selectable user interface object (e.g., **610A**, affordance) for displaying workout suggestions. The electronic device detects (**704**) (e.g., via a touch-sensitive display) a user input (e.g., **610B**) corresponding to the selectable user interface object for displaying workout suggestions.

In response to (**706**) detecting the user input corresponding to the selectable user interface object for displaying workout suggestions, the electronic device displays (**708**), on the display, a user interface (e.g., **612**) for displaying workout suggestions that includes concurrently displaying: a plurality of selectable options (**710**) that includes a first option (e.g., **614A-614D**, selectable user interface object, affordance) that, when selected, causes the electronic device to initiate a process for displaying workout suggestions that share a first common workout parameter and a second option (e.g., **614A-614D**, selectable user interface object, affordance) that, when selected, causes the electronic device to initiate a process for displaying workout suggestions that share a second common workout parameter; and a plurality of workout suggestions (**712**) (e.g., **616A-616D**), wherein the plurality of workout suggestions are selected for display based on a workout history of a user of the electronic device. Concurrently displaying the plurality of selectable options and the plurality of workout suggestions enables a user to quickly gain access to the desired workout, thereby reducing the number of inputs needed for selecting a workout. Reducing the number of inputs needed to perform an operation enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally,

52

reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, the first common workout parameter and the second common workout parameter both correspond to a first type of workout parameter (e.g., exercise type, music type/genre, trainer, duration). In some embodiments, a workout suggestion corresponds to (e.g., represents) a workout (e.g., audio and/or video content that guides a user to perform a physical activity). In some embodiments, selecting a workout suggestion initiates a process for playback of a workout corresponding to the workout suggestion.

In some embodiments, the plurality of workout suggestions (e.g., **616A-616D**) includes (**714**): a first workout suggestion (e.g., **616A-616B**, a graphical representation of a workout), wherein the first workout suggestion corresponds to a first subset (e.g., the most recent/last workout that was completed, a workout that is part of a program/series) of a collection of completed workouts. In some embodiments, the first workout suggestion is selected for display based on correspondence between the first workout suggestion and the first subset of the collection of completed workouts. In some embodiments, the collection of completed workouts are workouts (e.g., audio/video content for a workout) that have been completed by a user of the electronic device. In some embodiments, the first workout suggestion (e.g., **616A**) is displayed in a region of the display above the region occupied by the second workout suggestion (e.g., **616C**). In some embodiments, the first workout suggestion (e.g., **616A**) corresponds to the first subset when the first workout suggestion shares one or more characteristics (e.g., workout type, trainer, music genre, duration, required equipment, series/program) with the last completed workout. For example, the first workout suggestion has the same workout type and trainer as the last workout that was completed by the user. As another example, a user recently completed one of the workouts in a workout series/program, so the first workout suggestion (e.g., **616B**) is the next workout in the series/program. Automatically suggesting a workout based on a collection of completed workouts improves the quality of suggestions to the user, thereby providing a means for selection by the user. Otherwise, additional inputs would be required to further locate the desired workout. Performing an operation when a set of conditions has been met without requiring further user input enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, the first subset of the collection of completed workouts includes at least one workout in a predefined series of workouts. In some embodiments, the first workout suggestion (e.g., **616B**) corresponds to a next workout that has not been completed (e.g., a workout that is next in sequence after the at least one workout in the first subset) in the predefined series of workouts.

In some embodiments, the first subset of the collection of completed workouts excludes (e.g., does not include) at least one workout in a predefined series of workouts. In some embodiments, the first workout suggestion (e.g., **616A**) corresponds to the workout that was most recently completed. In some embodiments, the first workout suggestion corresponds to the most recently completed workout based on one or more of: trainer, exercise type, duration of workout, music, and required equipment.)

In some embodiments, the electronic device detects a user input (e.g., **628**) corresponding to the first workout suggestion (e.g., **616B**) that corresponds to the next workout that has not been completed in the predefined series of workouts. In some embodiments, in response to detecting the user input corresponding to the first workout suggestion that corresponds to the next workout that has not been completed in the predefined series of workouts: the electronic device displays one or more workout suggestions (e.g., **634**, **632A-632C**) in the predefined series of workouts. In some embodiments, in response to detecting the user input corresponding to the first workout suggestion that corresponds to the next workout that has not been completed in the predefined series of workouts: in accordance with a determination that at least one workout in the predefined series of workouts has been completed, the electronic device visually emphasizes a workout suggestion (e.g., **634**) of the one or more workout suggestions in the predefined series of workouts without visually emphasizing a different workout suggestion (e.g., **632A**, **632C**) of the one or more workout suggestions in the predefined series of workouts. Automatically visually emphasizing the next workout in a predefined series of workouts when a workout in the predefined series has been completed allows the user to quickly select the desired workout. Performing an operation when a set of conditions has been met without requiring further user input enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, the plurality of workout suggestions includes: a second workout suggestion (e.g., **616C-616D**, a graphical representation of a workout), wherein the second workout suggestion corresponds to a second subset (e.g., the workouts that have been completed during a predetermined duration of time (e.g., last 30, 60, or 90 days)) of a collection of completed workouts, wherein the first subset is different from the second subset. In some embodiments, the second workout suggestion is selected for display based on correspondence between the second workout suggestion and the second subset of the collection of completed workouts. In some embodiments, the second workout suggestion (e.g., **616C-616D**) is displayed in a region of the display below the region occupied by the first workout suggestion (e.g., **616A-616B**). In some embodiments, the second workout suggestion corresponds to the second subset in that the second workout suggestion shares one or more characteristics (e.g., workout type, trainer, music genre, duration, required equipment, series/program) with the workouts that have been completed in the last 30, 60, or 90 days. For example, the user has completed ten workouts in the past 30 days, and the second workout suggestion is a yoga workout because yoga was the most common workout type among the ten workouts. As another example, the user has completed thirty workouts in the past 90 days, and the second workout suggestion is a workout by a particular trainer because that particular trainer was the most common trainer among the thirty workouts. In some embodiments, the second workout suggestion is selected based on more than one characteristic (e.g., workout type and duration). Automatically suggesting a workout based on a collection of completed workouts improves the quality of suggestions to the user, thereby providing a means for selection by the user. Otherwise, additional inputs would be required to further

locate the desired workout. Performing an operation when a set of conditions has been met without requiring further user input enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, while displaying the plurality of selectable options (e.g., **614A-614D**) and the plurality of workout suggestions (e.g., **616A-616D**), the electronic device detects a first scroll gesture (e.g., **636**). In some embodiments, after (e.g., in response to) detecting the first scroll gesture, the electronic device displays, on the display, a third workout suggestion (e.g., **616J**), wherein the third workout suggestion corresponds to a third subset (e.g., workouts of the most common exercise type performed by the user, the workouts that have been completed during a predetermined duration of time (e.g., last 30, 60, or 90 days), the most recent/last workout that was completed, all of the completed workouts or a portion thereof) of a collection of completed workouts. In some embodiments, the third workout suggestion is selected for display based on the third workout suggestion not sharing a third common workout parameter (e.g., trainer, exercise type, duration, and the like) with the third subset of a collection of completed workouts.

In some embodiments, the third workout suggestion (e.g., **616J**) is selected for display also based on the third workout suggestion sharing a fourth common workout parameter with the third subset. In some embodiments, the third workout suggestion is selected for display also based on the third workout suggestion being complementary (e.g., has a predefined correspondence/connection) with the third subset of a collection of completed workouts. For example, the user has primarily completed running workouts, so the device suggests yoga as a complementary workout to running.

In some embodiments, while displaying the plurality of selectable options (e.g., **614A-614D**) and the plurality of workout suggestions (e.g., **616A-616D**), the electronic device detects a second scroll gesture (e.g., **636**). In some embodiments, after (e.g., in response to) detecting the second scroll gesture, the electronic device displays, on the display, a fourth workout suggestion (e.g., **616K**), wherein the fourth workout suggestion corresponds to a fourth subset (e.g., workout(s) of a particular type (e.g., no corresponding video/audio for the workout), workout(s) that are not selectable as part of the plurality of workout suggestions) of a collection of completed workouts. In some embodiments, the fourth workout suggestion is selected for display based on correspondence between the fourth workout suggestion and the fourth subset. In some embodiments, the fourth subset is different from the first, second, and/or third subset. In some embodiments, the fourth suggestion (e.g., **616K**) is displayed instead of the third suggestion (e.g., **616J**), or vice-versa. In some embodiments, after detecting the second scroll gesture (e.g., a vertical scroll gesture), the electronic device detects a horizontal scroll gesture at a location corresponding to the third workout suggestion. In some embodiments, in response to detecting the horizontal scroll gesture, the electronic device displays the fourth suggestion.

In some embodiments, the plurality of workout suggestions includes a workout suggestion (e.g., **616A-616U**) for a workout (e.g., audio and/or video content that guides a user to perform a physical activity) that corresponds to a predefined list of audio items (e.g., music playlist (e.g., as depicted in FIG. 6D)).

55

In some embodiments, the plurality of workout suggestions includes a workout suggestion (e.g., **616A-616Q**) for a workout with metadata that causes output (e.g., at the electronic device and/or an external device) of prompts (e.g., coaching, audio or visual content prompting the user to perform certain actions or attempt to accomplish a goal) during playback of the workout.

In some embodiments, the plurality of workout suggestions includes a workout suggestion (e.g., **616A-616U**) for a workout that, when selected for playback (e.g., start of video/audio content), causes recording (e.g., via one or more sensors) of one or more physical activity metrics at an external device (e.g., smartwatch, heart rate monitor, and/or fitness tracker). Automatically causing recording of one or more physical activity metrics when a workout is selected for playback allows the user to track their physical activity without requiring additional input. Performing an operation when a set of conditions has been met without requiring further user input enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, the plurality of workout suggestions includes a workout suggestion (e.g., **616J**) that has a physical activity type that is different than a physical activity type (e.g., the most common physical activity type among completed workouts (e.g., running, yoga, HIIT, and the like)) of a completed workout. In some embodiments, the workout suggestion has a predefined correspondence (e.g., complementary relationship) with a fifth subset (e.g., workouts of the most common exercise type performed by the user, the workouts that have been completed during a predetermined duration of time (e.g., last 30, 60, or 90 days), the most recent/last workout that was completed, all of the completed workouts or a portion thereof) of a collection of completed workouts.

In some embodiments, while displaying the plurality of selectable options (e.g., **614A-614D**) and the plurality of workout suggestions (e.g., **616A-616D**), the electronic device detects one or more inputs (e.g., **652, 658B**). In some embodiments, in response to detecting the one or more inputs: the electronic device ceases display of the plurality of selectable operations and the plurality of workout suggestions. In some embodiments, in response to detecting the one or more inputs: the electronic device displays, on the display, a third option (e.g., **664A-664H, 666A-666E, 668A-668F**, selectable user interface object, affordance) that, when selected, configures the electronic device to display workout suggestions that share a third common workout parameter and a fourth option (e.g., **664A-664H, 666A-666E, 668A-668F**, selectable user interface object, affordance) that, when selected, configures the electronic device to display workout suggestions that share a fourth common workout parameter. In some embodiments, the third common workout parameter corresponds to a second type of workout parameter (e.g., exercise type, music type/genre, trainer, duration). In some embodiments, the fourth common workout parameter corresponds to a third type of workout parameter different from the second type of workout parameter (e.g., exercise type, music type/genre, trainer, duration).

In some embodiments, the electronic device detects selection of the third option (e.g., **664E** in FIG. 6O). In some embodiments, in response to detecting selection of the third option, the electronic device changes one or more visual

56

characteristics (e.g., dim, gray out or otherwise deemphasize) of the fourth option (e.g., **666E, 668A** in FIG. 6P).

In some embodiments, the electronic device detects selection of the third option (e.g., **666D** in FIG. 6Q). In some embodiments, after detecting selection of the third option (e.g., other option(s) are also selected), the electronic device displays one or more workout suggestions (e.g., **660D-660F** in FIG. 6S) based on the detected selection of the third option, including a selectable user interface object (e.g., **678C**) indicating that the third option has been selected. In some embodiments, while displaying the one or more workout suggestions based on the detected selection of the third option, the electronic device detects a user input (e.g., **680**) corresponding to the selectable user interface object indicating that the third option has been selected. In some embodiments, in response to detecting the user input corresponding to the selectable user interface object indicating that the third option has been selected, the electronic device displays, on the display, one or more workout suggestions (e.g., **660G-660E** in FIG. 6T) that were not displayed prior to detection of the user input corresponding to the selectable user interface object indicating that the third option has been selected.

In some embodiments, the electronic device displays a fifth workout suggestion (e.g., **616L-616Q**), wherein the fifth workout suggestion is selected for display based on a frequency (e.g., within a predefined period of time (e.g., last 7, 14, or 30 days)) at which the fifth workout suggestion is selected by a group of users (e.g., users of external electronic devices). In some embodiments, the fifth workout suggestion corresponds to a popular or trending workout. In some embodiments, the fifth workout suggestion is displayed in response to (e.g., after) detecting a scroll gesture while the electronic device displays the plurality of selectable options and the plurality of workout suggestions.

In some embodiments, in accordance with a determination that a workout corresponding to a sixth workout suggestion (e.g., **616A, 616L**) has been completed (e.g., a user has watched the workout (e.g., audio and/or video content of a workout)), the electronic device displays, on the display, an indication (e.g., **622F** in FIG. 6D, check mark on **616L** in FIG. 6J) that the workout corresponding to the sixth workout suggestion has been completed. In some embodiments, in accordance with a determination that the workout corresponding to the sixth workout suggestion has not been completed, the electronic device forgoes displaying the indication that the workout corresponding to the sixth workout suggestion has been completed. In some embodiments, the indication is displayed in response to detecting a user input (e.g., **618** in FIG. 6C) corresponding to the sixth workout suggestion. In some embodiments, the sixth workout suggestion is displayed in response to (e.g., after) detecting a scroll gesture while the electronic device displays the plurality of selectable options and the plurality of workout suggestions.

In some embodiments, the indication that the workout corresponding to the sixth workout suggestion has been completed is a visual check mark overlaid on the sixth workout suggestion (e.g., check mark on **616L** in FIG. 6J).

In some embodiments, the electronic device detects a user input (e.g., **618**) corresponding to a seventh workout suggestion (e.g., **616A**). In some embodiments, in response to detecting the user input corresponding to the seventh workout suggestion, the electronic device displays, on the display, a detail user interface (e.g., **620**) for the seventh workout suggestion, wherein the detail user interface includes one or more workout characteristics selected from a group consist-

ing of equipment (e.g., 622C), duration (e.g., 622B), music genre (e.g., 622D), exercise type (e.g., 622A), and a number of times a workout corresponding to the seventh workout suggestion has been completed (e.g., 622F). In some embodiments, the one or more workout characteristics are associated with the workout corresponding to the seventh workout suggestion. In some embodiments, the seventh workout suggestion is displayed in response to (e.g., after) detecting a scroll gesture while the electronic device displays the plurality of selectable options and the plurality of workout suggestions.

In some embodiments, the electronic device detects a user input (e.g., 618) corresponding to an eighth workout suggestion (e.g., 616A). In some embodiments, in response to detecting the user input corresponding to the eighth workout suggestion, the electronic device displays, on the display, an audio selectable user interface object (e.g., "Listen in Music" in FIG. 6D) that, when selected, initiates a process (e.g., launches a music application for playing audio items) for causing playback of one or more audio items (e.g., music file(s)) that are part of a predefined collection of audio items (e.g., playlist). In some embodiments, the predefined collection of audio items is associated with a workout corresponding to the eighth workout suggestion. In some embodiments, the electronic device detects a user input corresponding to the audio selectable user interface object. In some embodiments, in response to detecting the user input corresponding to the audio selectable user interface object, the electronic device launches a music application with a save option that, when selected, initiates a process for saving the predefined collection of audio items to a user library of the music application. In some embodiments, in response to detecting a user input corresponding to the save option, the electronic device displays a download option that, when selected, initiates a process for storing, at the electronic device, data corresponding to the predefined collection of audio items. In some embodiments, the eighth workout suggestion is displayed in response to (e.g., after) detecting a scroll gesture while the electronic device displays the plurality of selectable options and the plurality of workout suggestions.

In some embodiments, the electronic device causes an external device to display a ninth workout suggestion. In some embodiments, the ninth workout suggestion is based on one or more physical activity metrics of the user of the electronic device. In some embodiments, the one or more physical activity metrics are captured via one or more sensors of the external device.

In some embodiments, the electronic device displays, within the user interface for displaying workout suggestions (e.g., 612, 612A), a fifth option (e.g., 615A, 615B) (e.g., selectable user interface object, affordance) that, when selected, causes the electronic device to initiate a process for playing a new content introduction media (e.g., audio and/or video) corresponding to a plurality of new (e.g., previously unavailable to the user) workouts that have been made available to the user of the electronic device within a predefined period of time (e.g., within the last day, within the last week). In some embodiments, the new content video identifies each new workout suggestion of the plurality of new workout suggestions (e.g., by identifying a trainer, title, and/or workout type associated with the new workout suggestion). In some embodiments, the new content video comprises one or more images and/or video clips from each of the plurality of new workout suggestions. In some embodiments, the new content video object is concurrently displayed within the user interface with the plurality of selectable options and the plurality of workout suggestions.

Displaying an option that, when selected, causes the electronic device to initiate a process for playing a new content introduction media corresponding to a plurality of new workouts provides the user with feedback about the current state of the device and provides feedback to the user indicating what is required to view the new content introduction media. Providing improved feedback to the user enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, the electronic device detects a user input corresponding to a tenth workout suggestion (e.g., 616A). In response to detecting the user input corresponding to the tenth workout suggestion, the electronic device concurrently displays, on the display: a first audio selectable user interface object (e.g., 623C) that, when selected, initiates a process (e.g., launches a music application for playing audio items) for causing playback of a plurality of audio items (e.g., a plurality of music files) that are part of a predefined collection of audio items (e.g., a music playlist), wherein the predefined collection of audio items is associated with a workout corresponding to the tenth workout suggestion; a second audio selectable user interface object (e.g., 623D) that, when selected, initiates a process (e.g., launches a music application for playing audio items) for causing playback of a first audio item (e.g., a first music file) of the plurality of audio items (e.g., without causing playback of the other audio items of the plurality of audio items); and a third audio selectable user interface object (e.g., 623E) that, when selected, initiates a process (e.g., launches a music application for playing audio items) for causing playback of a second audio item (e.g., a second music file different from the first music file) of the plurality of audio items different from the first audio item (e.g., without causing playback of the other audio items of the plurality of audio items). Displaying different selectable user interface objects that, respectively, allow a user to play back a plurality of audio items in a predefined collection of audio items or, alternatively, allow a user to play back individual audio items (e.g., a first audio item or a second audio item), provides the user with feedback about the current state of the device and provides feedback to the user indicating what is required to play back the entire predefined collection of audio items or individual audio items within the collection. Providing improved feedback to the user enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, the first option (e.g., 614A, 614B, 614C, 614D), when selected, causes the electronic device to initiate a process for displaying workout suggestions that share a first common workout type (e.g., a workout modality (e.g., HIIT, yoga, cycling, running, core, rowing, dance)) (e.g., FIG. 6N, FIG. 6DD). In some embodiments, the electronic device detects a user input corresponding to the first option. In response to detecting the user input corresponding to the first option, the electronic device concurrently displays: one or more workout suggestions that share the first common workout type (e.g., 660A-660D, 660F-660H) (e.g., without displaying workout suggestions that do

not share the first common workout type), and a workout type introduction object (e.g., **660E**, **660I**) (e.g., a selectable user interface object, an affordance) that, when selected, causes the electronic device to initiate a process for playing a workout type introduction video corresponding to the first common workout type, wherein the workout type introduction video identifies one or more pieces of workout equipment (e.g., dumbbells, yoga mat, treadmill, stationary bike) required for the first common workout type. In some embodiments, the second option, when selected, causes the electronic device to initiate a process for displaying workout suggestions that share a second common workout type different from the first common workout type (e.g., a workout modality (e.g., HIIT, yoga, cycling, running, core, rowing, dance)), and the method further comprises: detecting a user input corresponding to the second option; in response to detecting the user input corresponding to the second option, concurrently displaying: one or more workout suggestions that share the second common workout type (e.g., without displaying workout suggestions that do not share the second common workout type), and a second workout type introduction option (e.g., a selectable user interface object, an affordance) that, when selected, causes the electronic device to initiate a process for playing a second workout type introduction video (e.g., different from the workout type introduction video) corresponding to the second common workout type, wherein the second workout type introduction video identifies one or more pieces of workout equipment (e.g., dumbbells, yoga mat, treadmill, stationary bike) required for the second common workout type). Concurrently displaying the workout type introduction object and the one or more workout suggestions enables a user to quickly gain access to the desired workout, thereby reducing the number of inputs needed for selecting a workout. Reducing the number of inputs needed to perform an operation enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, the electronic device displays, within the user interface for displaying workout suggestions, a sixth option (e.g., **616B**, **616W**) (e.g., selectable user interface object, affordance) that, when selected, causes the electronic device to initiate a process for displaying workout suggestions for a plurality of workouts in a predefined series of workouts (e.g., FIG. 6G, FIG. 6BB, FIG. 6CC) (in some embodiments, a plurality of workouts in a predefined ordered sequence) (e.g., without displaying workout suggestions for workouts that are not in the predefined series of workouts). The electronic device detects a user input corresponding to the sixth option. In response to detecting the user input corresponding to the sixth option, the electronic device concurrently displays: workout suggestions for the plurality of workouts in the predefined series of workouts (e.g., without displaying workout suggestions that do not correspond to the plurality of workouts in the predefined series of workouts), and a workout series introduction object (e.g., a selectable user interface object, an affordance) that, when selected, causes the electronic device to initiate a process for playing a workout series introduction media (e.g., audio and/or video) corresponding to the predefined series of workouts. In some embodiments, each workout in the predefined series of workouts corresponds to a unique workout video, and the workout series introduction video is

different from the plurality of workout videos in the workout series. In some embodiments, the workout series introduction video includes one or more video clips and/or one or more images from at least a subset of the predefined series of workouts. In some embodiments, the method further comprises displaying, within the user interface for displaying workout suggestions, a seventh option (e.g., selectable user interface object, affordance) that, when selected, causes the electronic device to initiate a process for displaying workout suggestions for a second plurality of workouts in a second predefined series of workouts (in some embodiments, a second plurality of workouts in a second predefined ordered sequence different from the plurality of workouts in the predefined ordered sequence) (e.g., without displaying workout suggestions for workouts that are not in the second predefined series of workouts), wherein the second plurality of workouts in the second predefined series of workouts is different from the plurality of workouts in the predefined series of workouts; detecting a user input corresponding to the seventh option; and in response to detecting the user input corresponding to the seventh option, concurrently displaying: workout suggestions for the plurality of workouts in the second predefined series of workouts (e.g., without displaying workout suggestions that do not correspond to the second plurality of workouts in the second predefined series of workouts), and a second workout series introduction object (e.g., a selectable user interface object, an affordance) that, when selected, causes the electronic device to initiate a process for playing a second workout series introduction video (e.g., different from the workout series introduction video) corresponding to the second predefined series of workouts. In some embodiments, each workout in the second predefined series of workouts corresponds to a unique workout video, and the second workout series introduction video is different from the plurality of workout videos in the second workout series. In some embodiments, the second workout series introduction video includes one or more video clips and/or one or more images from at least a subset of the second predefined series of workouts. Concurrently displaying the workout series introduction object and the plurality of workouts in the predefined series of workouts enables a user to quickly gain access to the desired workout, thereby reducing the number of inputs needed for selecting a workout. Reducing the number of inputs needed to perform an operation enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

Note that details of the processes described above with respect to method **700** (e.g., FIG. 7) are also applicable in an analogous manner to the methods described below. For example, method **700** optionally includes one or more of the characteristics of the various methods described below with reference to method **900**. For example, the plurality of workout suggestions in method **700** optionally includes workout suggestions **616R-616U**, as described with reference to method **900**. For brevity, these details are not repeated below.

FIGS. 8A-8S illustrate exemplary user interfaces for starting an audio-based workout, in accordance with some embodiments. The user interfaces in these figures are used to illustrate the processes described below, including the processes in FIG. 9.

61

FIG. 8A depicts electronic device 600, which is a smart-phone with display 602. Display 602 of electronic device 600 includes a touch-sensitive surface on which electronic device 600 can detect user gestures (e.g., tap, swipe, drag). In some embodiments, electronic device 600 includes one or more features of electronic device 100, 300, and/or 500.

At FIG. 8A, electronic device 600 displays workout user interface 612 with workout suggestions 616R-616U. Workout suggestions 616R-616S represent audio content (e.g., workout content) that has a duration corresponding to the amount of time required to walk a predefined distance (e.g., 1, 2, or 3 miles). Workout suggestions 616T-616U represent audio content (e.g., workout content) corresponding to a predefined route at or near one or more physical locations (e.g., a 5K route in Hackney). While displaying workout user interface 612, electronic device 600 detects input 802B at a location corresponding to option 802A. In some embodiments, electronic device 600 displays workout user interface 612 in response to an input (e.g., 640 at FIG. 6J).

At FIG. 8B, in response to detecting input 802B, electronic device 600 replaces display of workout user interface 612 with display of library user interface 804. Library user interface 804 includes a plurality of workout suggestions (e.g., 806A-806D). Workout suggestions 806A-806D represent audio content (e.g., content that has a duration corresponding to the amount of time required to walk a predefined distance (e.g., 1, 2, or 3 miles)). Workout suggestion 806A of FIG. 8B corresponds to workout suggestion 616R of FIG. 8A. In some embodiments, selection of workout suggestion 616R of FIG. 8A and selection of workout suggestion 806A of FIG. 8B both result in display of the same user interface with details/information about the same workout. Similarly, workout suggestion 806B of FIG. 8B corresponds to workout suggestion 616S of FIG. 8A. While displaying workout user interface 612, electronic device 600 detects input 808 at a location corresponding to workout suggestion 806A.

At FIG. 8C, in response to detecting input 808, electronic device 600 replaces display of library user interface 804 with display of detail user interface 810. Detail user interface 810 includes information about the selected workout corresponding to workout suggestion 806A. Detail user interface 810 includes music item representations 814A-814E, which represent one or more music items of a playlist. In some embodiments, after playback of the workout content (e.g., corresponding to workout suggestion 806A) ends, electronic device 600 automatically starts playback of the playlist (e.g., causes audio output at an external device for playing back audio). Detail user interface 810 includes add option 812A for causing the workout content to be stored (e.g., downloaded) to electronic device 800. While displaying detail user interface 810, electronic device 600 detects input 812B at a location corresponding to add option 812A.

At FIG. 8C1, in response to detecting input 812B, electronic device 600 initiates a process for causing electronic device 800 to store, at electronic device 800, workout content (e.g., media) corresponding to workout suggestion 806A. In response to detecting input 812B, electronic device 600 visually modifies add option 812A to indicate that the workout content has been queued to be stored at electronic device 800 (e.g., queued to be downloaded). In some embodiments, the workout content remains in a queued state until the electronic device 800 is connected to and/or is drawing power from a charger.

At FIG. 8D, electronic device 600 continues the process for causing electronic device 800 to store, at electronic device 800, workout content corresponding to workout suggestion 806A. In response to detecting input 812B and/or

62

in accordance with a determination that a set of downloading criteria have been satisfied (e.g., in accordance with a determination that the electronic device 800 is being charged), electronic device 600 visually modifies add option 812A to indicate that the workout content has been stored at electronic device 800. While displaying detail user interface 810, electronic device 600 detects input 815 which corresponds to an upward swipe gesture.

At FIG. 8D1, in response to detecting input 815, electronic device 600 displays additional content in detail user interface 810, including additional music item representations 814F-814K.

FIGS. 8E-8Q depict techniques related to playback of workout content at electronic device 800. In particular, the workout content that is played is the same workout content that was selected at electronic device 600 in FIGS. 8A-8D (e.g., corresponding to workout suggestion 806A). FIG. 8E depicts electronic device 800, which is a smartwatch with display 801. Electronic device 800 is operably connected to (e.g., wirelessly paired with) electronic device 600. For example, electronic device 600 is configured to wirelessly communicate with electronic device 800, and vice-versa. In some embodiments, electronic device 600 and electronic device 800 are both signed into the same account (e.g., an account associated with a user that enables the user to access features/functions that are otherwise limited without the account). Display 801 of electronic device 800 includes a touch-sensitive surface on which electronic device 800 can detect user gestures (e.g., tap, swipe, and/or drag). In some embodiments, electronic device 800 includes one or more features of electronic device 100, 300, and/or 500.

At FIG. 8E, electronic device 800 displays workout user interface 816 with representation 818. Representation 818 represents audio workout content (e.g., corresponding to workout suggestion 806A). While displaying workout user interface 816, electronic device 800 detects input 820 at a location corresponding to option 819.

At FIG. 8E1, in response to detecting input 820, electronic device 800 replaces display of workout user interface 816 with library user interface 821. Library user interface 821 includes workout representations 823A-823C. Workout representation 823A corresponds to representation 818 of FIG. 8E. In the depicted example, library user interface 821 presents workout representations 823A-823C that represent audio workout content that has been stored on (e.g., downloaded to) electronic device 800. Library user interface 821 includes option 827 that is selectable by a user for a user to view additional audio workout content, including audio workout content that is available but has not been stored on (e.g., downloaded to) electronic device 800. While displaying library user interface 821, electronic device 800 detects input 829A, which corresponds to a leftward swipe gesture at a location corresponding to workout representation 823C.

At FIG. 8E2, in response to detecting input 829A, electronic device 800 shifts workout representation 823C horizontally to reveal a remove option 831. Selection of the remove option 831 removes audio workout content represented by workout representation 823C from electronic device 800, and removes workout representation 823C from library user interface 821. At FIG. 8E2, electronic device 800 detects input 829B, which corresponds to a rightward swipe gesture at a location corresponding to workout representation 823C.

At FIG. 8E3, in response to detecting input 829B, electronic device 800 shifts workout representation 823C horizontally back to its original position. While displaying

library user interface **821**, electronic device **800** detects input **829C** at a location corresponding to workout representation **823A**.

At FIG. **8E4**, in response to detecting input **829C**, electronic device **800** replaces display of library user interface **821** with detail user interface **833**. Detail user interface **833** includes information about the selected workout corresponding to workout representation **823A**. Detail user interface **833** includes music item representations, which represent one or more music items of a playlist that is associated with the workout (e.g., an ordered list of songs selected to accompany the workout such as songs selected by or in consultation with the celebrity who is featured in the workout). In some embodiments, the playlist is a predetermined playlist (e.g., is not a user-selected playlist). In some embodiments, after playback of the workout content (e.g., corresponding to workout representation **823A**) ends, electronic device **800** automatically starts playback of the playlist (e.g., causes audio output at an external device for playing back audio). Detail user interface **833** includes start option **835A** for causing playback of workout content (e.g., corresponding to workout representation **823A**). Detail user interface **833** also includes download option **835B** for causing workout content corresponding to workout representation **823A** to be stored on electronic device **800**. Detail user interface **833** also includes open playlist option **835C** for causing a music playlist associated with workout representation **823A** to begin playing in a separate music application. While displaying detail user interface **833**, electronic device **800** detects input **829D** at a location corresponding to start option **835A**.

At FIG. **8F**, in response to detecting input **829D**, electronic device **800** replaces display of detail user interface **833** with media user interface **822**. Media user interface **822** includes a set of playback controls, including play/pause button **824A**, skip back button **824B**, skip forward button **824C**, and title indication **824D**. Title indication **824D** provides an indication of the audio content that is queued for playback or is currently playing. Electronic device **800** has not caused audio playback to start in response to detecting input **820**, as indicated by the state of play/pause button **824A**. In some embodiments, in response to detecting input **820**, electronic device **800** automatically causes audio playback of the workout content and causes recording of physical activity metrics during playback of the workout content.

While displaying media user interface **822**, electronic device **800** detects input **825** at a location corresponding to play/pause button **824A**. In response to detecting input **825**, electronic device **800** causes audio playback of the workout content and causes recording of physical activity metrics during playback of the workout content. Prior to detection of input **825**, one or more sensors (e.g., GPS, accelerometer, gyroscope, and/or heart rate) of electronic device **800** are disabled. The one or more sensors are used to capture physical activity of the user. In response to detecting input **825**, electronic device **800** causes the one or more sensors to be enabled so as to improve accurate measurements of the physical activity of the user during the workout.

In some embodiments, audio playback of the workout content occurs at an external device (e.g., speakers, headphones) that is in communication with electronic device **800**. In some embodiments, the physical activity metrics are recorded (e.g., captured) via one or more sensors (e.g., GPS, accelerometer, gyroscope, and/or heart rate) of electronic device **800**.

At media user interface **822** of FIG. **8G**, in response to detecting input **825**, electronic device **800** visually updates

play/pause button **824A** to indicate that audio playback is occurring. Surrounding play/pause button **824A** is a playback progress indicator **824AA**, which visually indicates progress of audio playback. While displaying media user interface **822**, electronic device **800** detects input **826** with movement in the left-to-right direction. In response to detecting input **826**, electronic device **800** replaces display of media user interface **822** with display of workout user interface **830**, as shown on the right side of FIG. **8G**. Workout user interface **830** includes distance indication **832A**, which indicates the distance the user has traveled since the beginning of the workout (e.g., the start of playback of the workout content). Workout user interface **830** includes time indication **832B**, which indicates the amount of time that has elapsed since the beginning of the workout (e.g., the start of playback of the workout content). In some embodiments, while displaying workout user interface **830**, electronic device **800** detects input **828** with movement in the right-to-left direction. In response to detecting input **828**, electronic device **800** replaces display of workout user interface **830** with display of media user interface **822**. In some embodiments, while displaying workout user interface **830**, if electronic device **800** detects an input with movement in the left-to-right direction (rather than the right-to-left input **828** shown in FIG. **8G**), electronic device **800** replaces display of workout user interface **830** with a workout management user interface (not shown). The workout management user interface can include a pause/resume option that is selectable to pause and/or resume a workout (e.g., pause and/or resume audio playback associated with a workout, pause and/or resume recordation of physical metrics associated with a workout) and an end option that is selectable to end a workout (e.g., end audio playback associated with a workout, end recordation of physical metrics associated with a workout). The workout management user interface can also include a water lock option that is selectable to enable or disable a water lock feature. Enabling the water lock option disables touch-screen display **801** to prevent accidental input on touch-screen display **801** caused by moisture, while disabling the water lock option re-enables touch-screen display **801**.

FIGS. **8H** and **8J-8K** depict both media user interface **822** and workout user interface **830** to illustrate how the user interfaces would progress, respectively, as playback of the workout content continues. In some embodiments, electronic device **800** transitions between display of media user interface **822** and display of workout user interface **830** in response to inputs analogous to inputs **826** and **828**, as discussed above.

At FIG. **8H**, electronic device **800** displays media user interface **822** or, alternatively, workout user interface **830** after playback of a portion of the workout content has occurred. Playback progress indicator **824AA** indicates that the audio workout content is approximately at the halfway point. In response to a determination that a predetermined point in time has been reached (e.g., halfway point) during playback of audio content (e.g., corresponding to workout suggestion **616R**), electronic device **800** causes, via an audio output device (e.g., speakers, headphones), an audible indication that the halfway point in the audio content has been reached.

At FIG. **8I**, in response to a determination that a predetermined point in time has been reached during playback of audio content (e.g., corresponding to workout suggestion **616R**), electronic device **800** displays visual content **834** that corresponds to the audio content of the workout. For example, electronic device **800** causes a portion of audio

65

playback, where the narrator is describing a physical location (e.g., vineyard), and displays visual content corresponding to the portion of audio playback. In some embodiments, electronic device **800** displays visual content **834** based on metadata of the workout content. For example, the metadata is configured to cause electronic device **800** to display visual content **834** at a particular time during playback of the workout content. As shown in FIG. **8I**, if media user interface **822** was displayed, visual content **834** replaces display of media user interface **822**. Alternatively, if workout user interface **830** was displayed, visual content **834** replaces display of workout user interface **830**. In some embodiments, when electronic device **800** displays visual content **834**, electronic device **800** also produces an audio output and/or a haptic output to indicate to a user that visual content **834** is being displayed. Electronic device **800** also displays a done option **837** that is selectable by a user to cause the electronic device **800** to replace display of the visual content **834** with the media user interface **822** or the workout user interface **830**.

At FIG. **8J**, electronic device **800** displays media user interface **822** or, alternatively, workout user interface **830** at the end of the workout (e.g., playback of the workout content has finished). Playback progress indicator **824AA** indicates that playback of the audio workout content is nearly complete. At FIG. **8K**, in response to a determination that the end of the workout content has been reached, electronic device **800** causes audio playback of a playlist (e.g., one or more music items (e.g., songs)) that is associated with the workout content (e.g., the playlist is configured to play automatically after the workout content ends). In some embodiments, the one or more music items (e.g., represented by **814A-814E**) are part of a playlist that is automatically played back after the workout content ends. In response to the determination that the end of the workout content has been reached, electronic device **800** updates title indication **824D** to indicate the change from audio playback of the workout content to audio playback of the playlist (e.g., one or more music items). Playback progress indicator **824AA** indicates that playback of the first music item in the playlist has just begun. While displaying media user interface **822**, electronic device **800** detects input **838** at a location corresponding to option **836**.

At FIG. **8L**, in response to detecting input **838**, electronic device **800** replaces display of media user interface **822** with display of library user interface **840**. Library user interface **840** includes a plurality of workout suggestions (e.g., **842A-842C**). Workout suggestions **842A**, **842B**, and **842C** correspond to workout suggestions **806A**, **806B**, and **806C** of FIG. **8B**, respectively. While displaying library user interface **840**, electronic device **800** detects input **846** at a location corresponding to option **844**.

At FIG. **8M**, in response to detecting input **846**, electronic device **800** replaces display of library user interface **840** with media user interface **822**. While displaying media user interface **822**, electronic device **800** detects input **850** at a location corresponding to option **848**.

In the embodiments depicted in FIGS. **8G-8M**, the playback progress indicator **824AA** depicts playback progress for individual content items separately, such as the audio workout content, and each music item in the playlist. Accordingly, in FIGS. **8J** and **8K**, when the audio workout content ends and the first music item begins playing, the playback progress indicator **824AA** went from being completely full (indicating the end of playback of the audio workout content) to nearly empty (indicating the start of playback of the first music item). In some embodiments, the

66

playback progress indicator **824AA** can indicate playback progress for all of the audio content items corresponding to an audio workout as if they were a single content item. For example, the playback progress indicator **824AA** can indicate playback progress for the audio workout content as well as all of the music tracks in the playlist. Such an embodiment is depicted in FIGS. **8M1-8M3**. In the depicted scenario, the audio workout content is 20 minutes in duration, while the music tracks total 23 minutes in duration (as shown in FIG. **8E4**). In FIG. **8M1**, the audio workout content has reached its halfway point (e.g., approximately 10 minutes) (as was the case in FIG. **8H**). However, the playback progress indicator **824AA** indicates that the playback of content is only approximately 25% complete. This is because the playback progress indicator **824AA** is representative of all audio content in the audio workout. The audio content can include both the audio workout content and the music playlist, and in the depicted scenario in FIGS. **8M1-8M3** the total runtime for all the audio content is approximately 43 minutes. Similarly, in FIG. **8M2**, the audio workout content is nearing its end, and the playback progress indicator **824AA** indicates that playback of content is approximately 50% complete, and in FIG. **8M3**, the first music item in the playlist has begun, and the playback progress indicator **824AA** indicates that playback is approximately at 60% complete.

At FIG. **8N**, in response to detecting input **850**, electronic device **800** replaces display of media user interface **822** with action user interface **854**. Action user interface **854** includes options **852A-852C** for performing a respective operation based on the music item that is currently playing. In some embodiments, the respective operation is performed on the currently playing music item without being performed on a different music item, where the currently playing music item and the different music item are part of the same playlist. In some embodiments, selection of option **852A** causes the currently playing music item to be favorited (e.g., favoriting a music item can affect which music items are suggested to the user at a later time). In some embodiments, selection of option **852B** causes the currently playing music item to be added to a particular playlist (e.g., library). In some embodiments, selection of option **852C** results in display of a plurality of representations corresponding to the one or more music items. In some embodiments, while displaying action user interface **854**, electronic device **800** detects an input, and in response, replaces display of action user interface **854** with media user interface **822**.

At FIG. **8O**, while displaying media user interface **822**, electronic device **800** detects one or more inputs, including input **858** at input mechanism **856**. In some embodiments, input mechanism includes one or more features of input mechanism **506**.

At FIG. **8P**, in response to detecting the one or more inputs, electronic device **800** displays music user interface **860**. Music user interface **860** includes representation **862** corresponding to a playlist that is not associated with the workout content. While displaying music user interface **860**, electronic device **800** detects input **864** at a location corresponding to representation **862**.

At FIG. **8Q**, in response to detecting input **864**, electronic device **800** displays prompt user interface **866** with indication **868**. Indication **868** indicates that proceeding with playing one or more music items of the playlist that is not associated with the workout content will cause the current workout session to end (e.g., cease playback of the current playing audio content, cease recording of one or more physical activity metrics via one or more sensors of elec-

67

tronic device **800**). In some embodiments, while displaying prompt user interface **866**, electronic device **800** detects an input. In some embodiments, in response to detecting the input: in accordance with a determination that the input corresponds to option **870**, electronic device **800** continues playback of the currently playing audio content without playing one or more music items of the playlist that is not associated with the workout content. In some embodiments, in response to detecting the input: in accordance with a determination that the input corresponds to option **872**, electronic device **800** ceases playback of the currently playing audio content, initiates playback of the one or more music items of the playlist that is not associated with the workout content, and/or ceases recording of one or more physical activity metrics via one or more sensors of electronic device **800**.

As discussed above with reference to FIG. **8K**, in some embodiments, in response to a determination that the end of the workout content has been reached, electronic device **800** causes audio playback of a playlist (e.g., one or more music items (e.g., songs)) that is associated with the workout content (e.g., the playlist is configured to play automatically after the workout content ends). In some embodiments, in response to a determination that the end of the workout content has been reached and/or in response to a determination that the end of the playlist has been reached, electronic device **800** causes display of a summary user interface, as depicted in FIG. **8Q1**. In FIG. **8Q1**, summary user interface **880** includes information **885** pertaining to a user's measured physical activity during the workout (e.g., total time of the workout, distance walked during the workout, active and total calories burned during the workout, elevation gain, maximum and minimum elevation, average heart rate during the workout, average pace during the workout). Summary user interface **880** also includes visual content **882A**, **882B** associated with the workout. Visual content **882A**, **882B** can include visual content that was presented during the workout. For example, visual content **882A** corresponds to visual content **834** of FIG. **8I**. Summary user interface **880** also includes done option **884A** for closing the summary user interface **880**, and add playlist option **884B** for adding the music playlist associated with the workout to a separate music application.

In FIG. **8Q2**, electronic device **600** displays summary user interface **886**. Summary user interface **886** is substantially similar to summary user interface **880**, but is displayed on electronic device **600** rather than on electronic device **800**. In some embodiments, electronic device **600** display summary user interface **886** in response to a determination that the end of workout content has been reached on electronic device **600**. Similar to summary user interface **880**, summary user interface **886** includes information **887** pertaining to a user's measured physical activity during the workout and visual content items **888A**, **888B** associated with the workout.

FIGS. **8R-8S** depict selection of a different type of workout (e.g., corresponding to workout suggestions **616T-616U**) as compared to workout selection in FIGS. **8A-8C** (e.g., corresponding to workout suggestions **616R-616S**). While displaying workout user interface **612**, electronic device **800** detects input **874** at a location corresponding to workout suggestion **616T**. As discussed above, workout suggestions **616T** represents audio content (e.g., workout content) corresponding to a predefined route at or near one or more physical locations (e.g., a 5K route in Hackney).

At FIG. **8S**, in response to detecting input **874**, electronic device **800** displays detail user interface **876** with informa-

68

tion about the selected workout. Detail user interface **876** includes music item representations **878A-878D**, which represent one or more music items of a playlist. In some embodiments, after playback of the workout content (e.g., corresponding to workout suggestion **616T**) ends, electronic device **600** automatically starts playback of one or more music items of the playlist (e.g., causes audio output at an external device for playing back audio).

In some embodiments, the techniques described above in FIGS. **8E-8Q** are analogous to techniques that can be performed for workout content corresponding to workout suggestion **616T**. For example, analogous to FIG. **8I**, in response to a determination a predetermined point in time has been reached during playback of audio content (e.g., corresponding to workout suggestion **616T**), electronic device **800** displays visual content that corresponds to the audio content of the workout, in accordance with some embodiments. As another example, analogous to FIG. **8L**, electronic device **800** displays a user interface with a plurality of workout suggestions, including a workout suggestion that corresponds to workout suggestion **616T**.

FIG. **9** is a flow diagram illustrating a method for starting an audio-based workout using an electronic device, in accordance with some embodiments. Method **900** is performed at an electronic device (e.g., **100**, **300**, **500**, **600**, **800**) with a display (e.g., **801**). Some operations in method **900** are, optionally, combined, the orders of some operations are, optionally, changed, and some operations are, optionally, omitted.

As described below, method **900** provides an intuitive way for starting an audio-based workout. The method reduces the cognitive burden on a user for starting an audio-based workout, thereby creating a more efficient human-machine interface. For battery-operated computing devices, enabling a user to start an audio workout faster and more efficiently conserves power and increases the time between battery charges.

In some embodiments, the electronic device (e.g., **100**, **300**, **500**, **600**, **800**) is a computer system. The computer system is optionally in communication (e.g., wired communication, wireless communication) with a display generation component and with one or more input devices. The display generation component is configured to provide visual output, such as display via a CRT display, display via an LED display, or display via image projection. In some embodiments, the display generation component is integrated with the computer system. In some embodiments, the display generation component is separate from the computer system. The one or more input devices are configured to receive input, such as a touch-sensitive surface receiving user input. In some embodiments, the one or more input devices are integrated with the computer system. In some embodiments, the one or more input devices are separate from the computer system. Thus, the computer system can transmit, via a wired or wireless connection, data (e.g., image data or video data) to an integrated or external display generation component to visually produce the content (e.g., using a display device) and can receive, a wired or wireless connection, input from the one or more input devices.

The electronic device (e.g., **800**) displays (**902**), on the display (e.g., **801**), a selectable user interface object (e.g., **824A**, **818**, affordance) for starting audio playback.

The electronic device detects (**904**) (e.g., via a touch-sensitive display) a user input (e.g., **825**, **820**, a single user input, a single user input without intervening user input (e.g., input that is detected after the detection of the user input corresponding to the selectable user interface object

for starting audio playback and before causing audio playback)) corresponding to selection of the selectable user interface object for starting audio playback.

In response to (906) detecting the user input corresponding to selection of the selectable user interface object for starting audio playback: the electronic device (e.g., 800) causes (908) audio playback of audio associated with a workout (e.g., physical activity performed by the user) at an audio output device that is in communication with the electronic device (e.g., an external device (e.g., headphones, speakers), at the electronic device).

In response to (906) detecting the user input corresponding to selection of the selectable user interface object for starting audio playback: the electronic device (e.g., 800) causes (912) recording (e.g., tracking, logging, collecting) of physical activity metrics (e.g., calories, heart rate, distanced traveled, and/or stairs climbed) corresponding to the workout (e.g., physical activity metrics are recorded during audio playback of audio associated with the workout), wherein the physical activity metrics are recorded (e.g., captured) by one or more sensors that are monitoring an activity level of a user of the electronic device. Automatically performing two operations (e.g., causing audio playback and causing recording of physical activity metrics) allows the user to track their physical activity during audio playback via a single input. Performing two operations in response to a single input enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, the physical activity metrics are measured using one or more sensors (e.g., GPS, accelerometer, gyroscope, and/or heart rate) of the electronic device or an external device that is in communication with the electronic device.) In some embodiments, the physical activity metrics were not being recorded or were being recorded at a lower frequency or lower degree of precision prior to detecting (e.g., immediately prior to detecting) the user input (e.g., 825, 820) corresponding to selection of the selectable user interface object (e.g., 824A, 818) for starting audio playback (e.g., user heart rate is detected at multiple times per minute instead of once per minute or a longer time threshold, or additional sensors are used to detect steps more accurately than they were being detected prior to detection of the user input corresponding to selection of the selectable user interface object for starting audio playback). In some embodiments, in response to detecting the user input (e.g., 825, 820), causing one or more sensors of an external device to be enabled/activated so as to improve accurate measurements of the user during the workout. In some embodiments, the one or more sensors are not enabled/activated prior to detecting of the user input (e.g., 825, 820). In some embodiments, a subset of the one or more sensors are enabled/activated based on the type of workout. In some embodiments, in accordance with a determination that a workout is of a first type (e.g., exercise type), a first subset of the one or more sensors are enabled/activated based on the first type. In some embodiments, in accordance with a determination that a workout is of a second type (e.g., exercise type), a second subset of the one or more sensors are enabled/activated based on the second type. Automatically enabling the one or more sensors at the start of audio playback improves the battery life of the device, as the one or more sensors consume less power and/or battery life prior to the

start of audio playback. Enabling the one or more sensors when a set of conditions are met enhances the operability of the device which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, the audio (910) associated with the workout (e.g., represented by 616R-616S) has a duration based on an amount of time required to complete the workout (e.g., the amount of time required to walk a predefined distance (e.g., 1, 3, or 5 miles); an amount of time required to complete the workout by a narrator of the audio associated with the workout).

In some embodiments, the audio associated with the workout includes an audio indication configured to be output at the audio output device at a predefined time (e.g., halfway point of the duration of the audio) during playback of the audio associated with the workout (e.g., as discussed above with respect to FIG. 8H). Outputting an audio indication provides the user with feedback about the current state of the device (e.g., playback of audio file has reached halfway point). Providing improved feedback to the user enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, the audio associated with the workout corresponds to one or more visual content items (e.g., 834) that are configured to be output (e.g., displayed) during playback of the audio associated with the workout. In some embodiments, the one or more visual content items are displayed at the electronic device (e.g., 800) or an external device in communication with the electronic device. In some embodiments, the one or more visual content items are associated with metadata that determine a time at which the one or more visual content items are output during playback of the audio associated with the workout. For example, a visual content item of the one or more visual content items is configured to be output at a particular point in time during playback.

In some embodiments, each visual content item of the one or more visual content items (e.g., 834, 882A, 882B) is configured to be output (e.g., displayed) at a respective predetermined time during playback of the audio associated with the workout, including a first visual content item (e.g., 834) configured to be output at a first predetermined time during playback of the audio associated with the workout (e.g., FIG. 8I). In some embodiments, the electronic device displays, via the display generation component, a workout summary user interface (e.g., 880) that includes one or more graphical representations of the workout (e.g., 882A, 882B) (e.g., a non-textual representation, an image of a speaker (e.g., narrator) of the audio associated with the workout). In some embodiments, the workout summary user interface includes representations of physical activity metrics that are based on physical activity of a user during the workout (e.g., route walked, active calories, total calories, total time, average heart rate, distance, average pace). In some embodiments, in accordance with a determination that the first visual content item was output (e.g., displayed) during playback of the audio associated with the workout, the workout summary user interface includes the first visual content item (e.g., 882A, 882B) (e.g., the first visual content item is displayed within and/or accessible within the workout summary user interface), and in accordance with a

determination that the first visual content item was not output (e.g., displayed) during playback of the audio associated with the workout (e.g., the user terminated playback of the audio associated with the workout prior to the first predetermined time associated with the first visual content item), the workout summary user interface does not include the first visual content item (e.g., the first visual content item is not displayed within and/or accessible within the workout summary user interface). In some embodiments, the one or more visual content items includes a second visual content item (e.g., different from the first visual content item) configured to be output at a second predetermined time (e.g., different from the first predetermined time) during playback of the audio associated with the workout, and the method further comprises: in accordance with a determination that the second visual content item was output during playback of the audio associated with the workout, the workout summary user interface includes the second visual content item (e.g., the second visual content item is displayed within and/or accessible within the workout summary user interface), and in accordance with a determination that the second visual content item was not output (e.g., displayed) during playback of the audio associated with the workout (e.g., the user terminated playback of the audio associated with the workout prior to the second predetermined time associated with the second visual content item), the workout summary user interface does not include the second visual content item (e.g., the second visual content item is not displayed within and/or accessible within the workout summary user interface). Displaying a workout summary user interface that includes the one or more visual content items configured to be output during playback of the audio associated with the workout provides the user with the ability to access the visual content items that were presented during playback of the audio. Providing additional control of the device enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, while causing audio playback of the audio associated with the workout, the electronic device (e.g., **800**) displays, via the display generation component, the one or more visual content items (e.g., **834**). In some embodiments, the electronic device generates tactile output (e.g., a sequence of a number of individual tactile outputs), wherein the tactile output is provided concurrently with display of the one or more visual content items (e.g., FIG. **8I**). In some embodiments, the tactile output is output by the computer system or an external device in communication with the computer system. In some embodiments, the tactile output is associated with metadata that determine a time at which the tactile output is output during playback of the audio associated with the workout. For example, tactile output is configured to be output at a particular point in time during playback (e.g., tactile output is configured to be output each time a visual content item of the one or more visual content items is output). In some embodiments, the one or more visual content items are presented full screen on the computer system (e.g., displayed on the computer system without additional content) or presented full screen on an external device in communication with the computer system. Generating tactile output, and providing the tactile output concurrently with display of the one or more visual content items, provides the user with feedback about the

current state of the device (e.g., notifying the user that the device is displaying visual content items). Providing improved feedback to the user enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, after completion of the workout (in some embodiments, after completion of the audio associated with the workout), the electronic device (e.g., **800**) displays, via the display generation component, a first workout summary user interface (e.g., **880**, FIG. **8Q1**) that includes the one or more visual content items (e.g., **882A**, **882B**) configured to be output during playback of the audio associated with the workout. In some embodiments, the workout summary user interface also includes physical activity metrics corresponding to the workout. Displaying a workout summary user interface that includes the one or more visual content items configured to be output during playback of the audio associated with the workout provides the user with the ability to access the visual content items that were presented during playback of the audio. Providing additional control of the device enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, the audio associated with the workout corresponds to a predefined list of audio items (e.g., music playlist) that includes a first audio item (e.g., represented by **824D** in FIG. **8K**, music file) and a second audio item (e.g., music file). In some embodiments, a speaker (e.g., narrator) of the audio associated with the workout generated the predefined list of audio items (e.g., selected the audio items in the playlist).

In some embodiments, in accordance with a determination that audio playback of the audio associated with the workout has completed, the electronic device causes, at the audio output device, audio playback of the predefined list of audio items that includes the first audio item (e.g., represented by **824D** in FIG. **8K**) and the second audio item. In some embodiments, the predefined list of audio items (e.g., music playlist) is played in response to the audio associated with the workout ending.

In some embodiments, in response to detecting the user input (e.g., **820**) corresponding to selection of the selectable user interface object (e.g., **818**) for starting audio playback, the electronic device (e.g., **800**) displays, on the display (e.g., **801**), a first set of playback controls (e.g., **824A-824C**, one or more selectable user interface objects) for modifying the audio playback of the audio associated with the workout. In some embodiments, the electronic device displays the first set of playback controls for modifying the audio playback of the audio associated with the workout in response to detecting selection of a representation (e.g., **818**) of the audio content. In some embodiments, in response to (e.g., after) causing audio playback of the predefined list of audio items, the electronic device displays, on the display, a second set of playback controls (e.g., skip back button **824B** changes to previous track button (displayed at same location) as shown in transition from FIGS. **8J-8K**; skip forward button **824C** changes to next track button (displayed at same location) as shown in transition from FIGS. **8J-8K**) for

modifying audio playback of the predefined list of audio items, wherein the second set of playback controls is different than the first set of playback controls. In some embodiments, the electronic device replaces the display of the first set of playback controls with the second set of playback controls.

In some embodiments, after audio playback of the audio associated with the workout has completed, the electronic device (e.g., **800**) causes, at the audio output device, audio playback of the first audio item (e.g., represented by **824D** in FIG. **8K**) of the predefined list of audio items. In some embodiments, after (e.g., while) causing the audio playback of the first audio item, the electronic device detects one or more user inputs (e.g., **848**, input at a location corresponding to **842A**, **842B**, or **842C**) corresponding to the first audio item. In some embodiments, in response to detecting the one or more user inputs corresponding to the first audio item, the electronic device performs an operation for the first audio item (e.g., add to library (e.g., **852B**), save, skip, play/pause) based on the detected one or more user inputs without performing the operation for the second audio item.

In some embodiments, in response to detecting the user input corresponding to selection of the selectable user interface object for starting audio playback, the electronic device displays, via the display generation component, a workout user interface (e.g., **822**) comprising a playback progress indicator (e.g., **824AA**), wherein the playback progress indicator visually indicates progress of playback of audio content, wherein the audio content includes the audio associated with the workout and the predefined list of audio items (e.g., as shown in FIG. **8E4**) (e.g., a music playlist) (e.g., a music playlist that is played back in response to the audio associated with the workout ending). Displaying a workout user interface comprising a playback progress indicator provides the user with feedback about the current state of the device (e.g., a current state of playback of audio content). Providing improved feedback to the user enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, in accordance with (**914**) a determination that a detected user input (e.g., **864**, input at a location corresponding to option **872**) results in audio playback of audio that is not associated with the workout, the electronic device causes (**916**) the audio playback of audio associated with the workout to cease. In some embodiments, the detected user input corresponds to selection of a song, playlist, or music file in a music application. In some embodiments, in accordance with a determination that a detected user input results in audio playback of audio that is not associated with the workout, causing the recording of physical activity metrics corresponding to the workout to cease (e.g., disable one or more sensors for recording physical activity of the user during a workout). Automatically causing the recording of physical activity metrics to cease when playback of non-workout audio occurs improves battery life of the device, as one or more sensors for recording physical activity metrics are disabled. Disabling the one or more sensors when a set of conditions are met enhances the operability of the device which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, a predetermined number (e.g., 3, 5, 7) of audio items of a first type (e.g., represented by **842A-842C**) are stored at the electronic device, wherein the audio associated with the workout is of the first type (e.g., an audio program with interviews that last as long as it takes to walk a predefined distance (e.g., 1, 3, or 5 miles)). In some embodiments, the electronic device (e.g., **800**, smartwatch) detects a request to add (e.g., store) a predetermined number of audio items of the first type to the electronic device. In some embodiments, in response to detecting the request to add the audio of the first type, the electronic device downloads (e.g., stores) a predetermined number of audio items of the first type to be stored at the electronic device. In some embodiments, an external device (e.g., **600**, smartphone) that is in communication with the electronic device (e.g., smartwatch) initiates the request to add the predetermined number of audio items to the electronic device.

In some embodiments, the audio (e.g., music, voice over) associated with the workout (e.g., represented by **616T-616U**) corresponds to a predefined set of one or more physical locations (e.g., related to a running route at a physical location (e.g., city, landmark)). In some embodiments, the audio associated with the workout corresponds to one or more visual content items (e.g., defined route on a map, photos of places of significance (e.g., landmark)) that are configured to be output (e.g., displayed) during playback of the audio associated with the workout.

In some embodiments, after completion of the workout (in some embodiments, after completion of the audio associated with the workout), the electronic device (e.g., **800**) displays, via the display generation component, a second workout summary user interface (e.g., **880**, **886**) that includes one or more graphical representations of the workout (e.g., FIG. **8Q1**, FIG. **8Q2**) (e.g., a non-textual representation, an image of a speaker (e.g., narrator) of the audio associated with the workout). In some embodiments, the second workout summary user interface includes physical activity metrics that are based on physical activity of a user during the workout (e.g., route walked, active calories, total calories, total time, average heart rate, distance, average pace). Displaying a workout summary user interface that includes one or more graphical representations of a workout provides the user with feedback about the user's physical activity. Providing improved feedback to the user enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, the computer system is in communication with (e.g., paired with) a first external device (e.g., **600** in FIG. **8C**) (e.g., a smartphone), the first external device is configured to output (e.g., display, cause a display generation component to display) a selectable user interface object (e.g., **812A**) for adding a workout (e.g., adding the workout to a computer system (e.g., downloading a workout to the computer system and/or a different computer system)). In some embodiments, in response to a determination that a sequence of one or more user inputs (e.g., **812B**) have been detected by the first external device (e.g., at the first external device, at one or more input devices in communication with the first external device) corresponding to selection of the selectable user interface object (e.g., **812A**) for adding the workout, the electronic device initiates a process for adding the workout to the computer system (e.g., in response to the

determination that the sequence of one or more user inputs have been detected by the first external device, initiating a process for downloading the workout to the computer system). In some embodiments, adding the workout to the computer system comprises downloading and/or storing the audio associated with the workout to the computer system. Automatically adding a workout to a computer system in response to a determination that a sequence of one or more user inputs have been detected by a first external device allows the user to add the workout to the computer system without requiring additional input. Performing an operation when a set of conditions has been met without requiring further user input enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

Note that details of the processes described above with respect to method 900 (e.g., FIG. 9) are also applicable in an analogous manner to the methods described above. For example, method 900 optionally includes one or more of the characteristics of the various methods described above with reference to method 700. For example, the plurality of workout suggestions in method 700 optionally includes workout suggestions 616R-616U, as described with reference to method 900. For brevity, these details are not repeated below.

FIGS. 10A-10V illustrate exemplary user interfaces for displaying workout information, in accordance with some embodiments. In some embodiments, the workout information can include in-workout physical activity metrics and other information associated with a workout being performed by a user. The user interfaces in these figures are used to illustrate the processes described below, including the processes in FIG. 11.

FIG. 10A depicts electronic device 600, which is a smartphone with display 602. Display 602 of electronic device 600 includes a touch-sensitive surface on which electronic device 600 can detect user gestures (e.g., tap, swipe, drag). In some embodiments, electronic device 600 includes one or more features of electronic device 100, 300, and/or 500.

FIG. 10A also depicts electronic device 800, which is a smartwatch with display 801. Display 801 of electronic device 800 includes a touch-sensitive surface on which electronic device 800 can detect user gestures (e.g., tap, swipe, drag). In some embodiments, electronic device 800 includes one or more features of electronic device 100, 300, and/or 500.

At FIG. 10A, the electronic device 600 displays detail user interface 620. Detail user interface 620 includes characteristics of a workout. For example, detail user interface 620 includes exercise type 622A (e.g., core), trainer 622B (e.g., Amy Dixon), duration 622C (e.g., 20 min), music 622D (e.g., hip-hop), required equipment 622E (e.g., dumbbells), and completion indication 622F (e.g., completed 3 times).

At FIG. 10A, the electronic device 800 displays activity user interface 1002. In some embodiments, electronic device 600 causes electronic device 800 to display activity user interface 1002. The activity user interface 1002 includes physical activity metrics for a duration of time (e.g., physical activity metrics for the current day (e.g., from 12:00 am to a current time)). In the depicted embodiment, physical activity metrics are depicted in a plurality of concentric

physical activity rings 1004. The plurality of concentric physical activity rings 1004 include move information (e.g., move ring 1006A) indicative of a number of calories burned by a user during the day, exercise information (e.g., exercise ring 1006B) indicative of a number of minutes the user has been active during the day, and stand information (e.g., stand ring 1006C) indicative of the number of hours during the day in which the user has stood up for a threshold amount of time or a threshold number of times. In some embodiments, including the depicted embodiment, move information (e.g., move ring 1006A) is indicative of progress towards a move goal (e.g., a target number of calories for a day), exercise information (e.g., exercise ring 1006B) is indicative of progress towards an exercise goal (e.g., a target number of exercise minutes for a day), and stand information (e.g., stand ring 1006C) is indicative of progress towards a stand goal (e.g., a target number of hours for a day). For example, in the depicted embodiment, the move ring 1006A is approximately $\frac{2}{3}$ completed, indicating that the user is approximately $\frac{2}{3}$ of the way to their move goal, the exercise ring 1006B is approximately $\frac{1}{2}$ completed, indicating that the user is approximately $\frac{1}{2}$ of the way to their exercise goal, and the stand ring 1006C is approximately $\frac{1}{2}$ completed, indicating that the user is approximately $\frac{1}{2}$ of the way to their stand goal. In some embodiments, including the depicted embodiment, the activity user interface 1002 also includes time-keeping elements which indicate a current time (e.g., watch hands 1010A, 1010B which indicate that the current time is 10:00).

As mentioned above, in some embodiments, move ring 1006A, exercise ring 1006B, and stand ring 1006C can be associated with (e.g., indicative of) physical activity by a user for a predetermined period of time. For example, they can be indicative of physical activity by the user for the entire day to that point (e.g., from 12:00 am until the current time in the day). For example, at FIG. 10A, the current time is 10:00 AM. Move ring 1006A, exercise ring 1006B, and stand ring 1006C can be indicative of the user's physical activity to that point in the day (e.g., from 12:00 am to 10:00 am). For example, if the user took a morning walk at 7:00 AM, move ring 1006A can include calories burned from that morning walk, exercise ring 1006B can include active calories burned from that morning walk, and stand ring 1006C can credit the user for one hour of standing during the time of the walk.

While displaying detail user interface 620, electronic device 600 detects input 1012 at a location corresponding to play button 1014.

At FIG. 10B, in response to detecting input 1012, electronic device 600 replaces display of detail user interface 620 with workout start user interface 1016. Furthermore, in response to electronic device 600 detecting input 1012, electronic device 800 replaces display of activity user interface 1002 with workout start user interface 1018. In some embodiments, in response to electronic device 600 detecting input 1012, electronic device 600 causes electronic device 800 to replace display of activity user interface 1002 with workout start user interface 1018. Workout start user interface 1016 includes a play button 1020 and workout start user interface 1018 includes a play button 1022. While displaying workout start user interface 1016, electronic device 600 can detect input 1024 at a location corresponding to play button 1020 or, while displaying workout start user interface 1018, electronic device 800 can detect input 1026 at a location corresponding to play button 1022.

At FIG. 10C, in response to electronic device 600 detecting input 1024 or electronic device 800 detecting input 1026,

electronic device 600 replaces display of workout start user interface 1016 with countdown user interface 1028A and electronic device 800 replaces display of workout start user interface 1018 with countdown user interface 1028B. In some embodiments, in response to electronic device 600 detecting input 1024 or electronic device 800 detecting input 1026, electronic device 600 causes electronic device 800 to replace display of workout start user interface 1018 with countdown user interface 1028B. Countdown user interface 1028A and countdown user interface 1028B display a countdown animation (e.g., counting down the number of seconds remaining) prior to initiation of a workout session.

At FIG. 10D, after a predetermined period of time after user input 1024 or user input 1026 (e.g., after conclusion of a 3-second countdown animation), electronic device 600 replaces display of countdown user interface 1028A with workout session user interface 1030 and electronic device 800 replaces display of countdown user interface 1028B with workout metrics user interface 1032. In some embodiments, electronic device 600 causes electronic device 800 to replace display of countdown user interface 1028B with workout metrics user interface 1032.

Workout session user interface 1030 includes video content 1034 that guides a user through a workout session (e.g., a video of an instructor demonstrating a workout). Workout session user interface 1030 also includes physical activity metrics indicative of a user's physical activity. The physical activity metrics include physical activity rings 1036 which include move ring 1036A, exercise ring 1036B, and stand ring 1036C. Move ring 1036A corresponds to move ring 1006A of FIG. 10A, exercise ring 1036B corresponds to exercise ring 1006B of FIG. 10A, and stand ring 1036C corresponds to stand ring 1006C of FIG. 10A. In some embodiments, physical activity rings 1036 are associated with (e.g., are indicative of) physical activity by a user for a predetermined period of time which includes a period of time preceding initiation of the workout session. For example, the physical activity rings 1036 can be indicative of physical activity by the user for the entire day to that point (e.g., from 12:00 am until the current time in the day). As discussed above, with reference to FIG. 10A, the current time when the user initiates the workout session is 10:00 AM. Move ring 1036A, exercise ring 1036B, and stand ring 1036C can be indicative of the user's physical activity to that point in the day (e.g., from 12:00 am to 10:00 am). For example, as mentioned above with reference to FIG. 10A, if the user took a morning walk at 7:00 AM, move ring 1036A can include calories burned from that morning walk, exercise ring 1036B can include active calories burned from that morning walk, and stand ring 1036C can credit the user for one hour of standing during the time of the walk. Physical activity metrics in the workout session user interface 1030 also include workout session physical activity metrics 1038 indicative of the user's physical activity during the current workout session. For example, in some embodiments, the workout session physical activity metrics 1038 include workout duration information 1040A (e.g., the workout has been in session for 1 second), heart rate information 1040B (e.g., the user's current heart rate is 61 beats per minute), and calorie information 1040C (e.g., the user has burned 0 calories so far in this workout session). The workout session physical activity metrics can also include a workout intensity representation 1040D indicative of the user's activity level in the workout session relative to other users that have previously participated in (or are currently participating in) the workout session. The workout intensity representation

1040D will be described in greater detail herein, particularly with reference to FIGS. 12A-12O.

The workout metrics user interface 1032 on electronic device 800 also includes workout session physical activity metrics, including workout duration information 1042A, heart rate information 1042B, and calorie information 1042C. In some embodiments, workout duration information 1042A corresponds to workout duration information 1040A, heart rate information 1042B corresponds to heart rate information 1040B, and calorie information 1042C corresponds to calorie information 1040C.

User physical activity metrics (including information included in physical activity rings 1036 and workout session physical activity metrics 1038) can be measured by one or more sensors in electronic device 600, one or more sensors in electronic device 800, and/or one or more sensors external to electronic device 600 and electronic device 800. Such sensors can include, for example, one or more GPS sensors, one or more accelerometers, one or more heart rate sensors, one or more gyroscopes, and the like. As the user performs a workout, the electronic device 600 and/or the electronic device 800 can receive activity data based on the physical activity of the user, and update the physical activity metrics that are displayed (e.g., in the physical activity rings 1036 and/or the workout session physical activity metrics 1038).

At FIG. 10D, while displaying workout session user interface 1030, electronic device 600 detects input 1044 at a location that corresponds to video content 1034.

At FIG. 10E, in response to detecting input 1044, electronic device 600 displays a set of playback controls overlaid on the video content 134, including play/pause button 1046A, playback progress indicator 1046B, playback volume control 1046C, closed caption icon 1046D, and edit metrics icon 1046E.

While displaying the set of playback controls, electronic device 600 detects input 1048 at a location corresponding to edit metrics icon 1046E.

At FIG. 10F, in response to detecting input 1048, electronic device 600 replaces display of the workout session user interface 1030 and the set of playback controls with an edit metrics user interface 1050. The edit metrics user interface 1050 includes one or more selectable options for configuring display of one or more representations of physical activity metrics (e.g., workout session physical activity metrics 1038, physical activity rings 1034) on electronic device 600 and/or electronic device 800. For example, the metrics selection user interface 1050 includes an option 1052A for hiding or displaying workout session physical activity metrics, an option 1052B for hiding workout duration information 1040A, an option 1052C for showing elapsed time for workout duration information 1040A, an option 1052D for showing remaining time for workout duration information 1040A, and an option 1052E for hiding or displaying the workout intensity representation 1040D.

While displaying the metrics selection user interface 1050, the electronic device 600 detects input 1056 at a location corresponding to a "done" option 1054.

At FIG. 10G, in response to detecting input 1056, electronic device 600 replaces display of edit metrics user interface 1050 with workout session user interface 1030.

In some embodiments, a workout session can comprise one or more pre-defined events that trigger particular displays. Electronic device 600 and/or electronic device 800 can detect events based on event criteria. For example, in some embodiments, an event can occur at a particular time within a workout session (e.g., at the 3 minute mark, halfway through a workout) or when a particular milestone is

achieved by a user (e.g., when the user burns a particular number of calories). Electronic device 600 and/or electronic device 800 can utilize metadata associated with a workout session to detect events associated with a workout session and take appropriate actions.

In FIG. 10G, metadata associated with the workout session can indicate that the 8 minute 15 second mark of the workout session is associated with an event that is associated with a 10-second countdown visual effect (for example, at the 8 minute 15 second mark, the trainer can instruct the user to perform as many push-ups as they can in 10 seconds). In response to determining that an event has occurred, the electronic device 600 and/or the electronic device 800 can display visual information associated with the event. For example, in FIG. 10G, the electronic device 600 displays a 10-second countdown 1058A and the electronic device 800 replaces display of the workout metrics user interface 1032 with a 10-second countdown user interface 1058B. In some embodiments, in response to detecting the event, electronic device 600 causes the electronic device 800 to replace display of the workout metrics user interface 1032 with the 10-second countdown user interface 1058B.

In some embodiments, prior to beginning the 10-second countdown, electronic device 800 can display a visual effect to visually emphasize the 10-second countdown 1058A and the 10-second countdown user interface 1058B. For example, in FIGS. 10G-10G3, although the 10-second countdown begins at the 8 minute 15 second mark, at the 8 minute 13 second mark (prior to initiating the 10-second countdown), the electronic device 600 displays the 10-second countdown 1058A, the 10-second countdown user interface 1058B replaces display of the workout metrics user interface 1032 on the electronic device 800, and a background portion of the 10-second countdown 1058A and the 10-second countdown user interface 1058B blinks (or provides some other visual indication) one or more times (e.g., the background portion can alternate different colors, vary in brightness, etc.) to draw the user's attention.

At FIG. 10H, one second has passed from FIG. 10G, and the 10-second countdown 1058A has decreased to 9 seconds, while the 10-second countdown user interface 1058B on electronic device 800 also shows 9 seconds remaining in the countdown. In this way, visual information presented on the electronic device 600 and the electronic device 800 can correspond to the video content 1034.

At FIG. 10I, electronic device 600 has detected another type of event. In the example shown in FIG. 10I, electronic device 600 has determined that an event associated with a halfway point in the workout session has occurred (e.g., at the 10-minute mark of a 20-minute workout). In response to this determination, the electronic device 600 displays a visual notification 1060 that the user has reached the halfway point in the workout.

FIGS. 10J-10L demonstrate an example visual effect associated with a "check your rings" event in a workout session, according to various embodiments. At FIG. 10J, electronic device 600 has detected that one or more event criteria have been satisfied to trigger a "check your rings" events. In some embodiments, such criteria can include a time-based determination (e.g., the event occurs at a particular time within the workout session). In some embodiments, such criteria can include a user achievement-based determination (e.g., a determination that the user has nearly closed his or her exercise ring 1036B (e.g., that the user has nearly achieved his or her exercise goal for the day (e.g., that the user is within a threshold number of minutes from achieving his or her exercise goal))).

In response to detection of the "check your rings" event, the electronic device 600 can emphasize certain visual information and/or de-emphasize other visual information. In FIG. 10J, the electronic device 600 displays a visual indication 1062 instructing the user to check his or her physical activity rings 1036. In some embodiments, detection of the "check your rings" event can also cause an audio output by electronic device 600 (e.g., an audio output that instructs the user to check his or her physical activity rings 1036).

At FIG. 10K, in response to detecting the check your rings event, the electronic device 600 begins to visually emphasize the physical activity rings 1036 (e.g., by enlarging them). The electronic device 600 also begins to present additional visual information pertaining to the physical activity rings 1036 (e.g., a number value 1063A associated with the move ring 1036A). In some embodiments, in response to detecting the check your rings event, the electronic device 600 also visually de-emphasizes (e.g., hides, obscures, fades, and/or blurs) other information, such as the workout session physical activity metrics 1038.

At FIG. 10L, in response to electronic device 600 detecting the check your rings event, the electronic device 600 continues to enlarge the physical activity rings 1036, and displays additional information pertaining to the physical activity rings 1036 (e.g., numeric metrics 1063A, 1063B, 1063C associated with the physical activity rings 1036). Furthermore, in response to electronic device 600 detecting the check your rings event, electronic device 800 replaces display of the workout metrics user interface 1032 with ring information user interface 1064. In some embodiments, in response to electronic device 600 detecting the check your rings event, electronic device 600 causes electronic device 800 to replace display of the workout metrics user interface 1032 with ring information user interface 1064. The ring information user interface 1064 includes physical activity rings 1066A (which correspond to the physical activity rings 1036), move information 1066B (which corresponds to numerical value 1063A), exercise information 1066C (which corresponds to numerical value 1063B), and stand information 1066D (which correspond to numerical value 1063C).

At FIG. 10M, electronic device 600 and/or electronic device 800 detects a "ring closed" event based on a determination that the user has closed his or her exercise ring (e.g., that the user has achieved his or her exercise goal for the day). In response to detection of the ring closed event (e.g., by electronic device 600 and/or electronic device 800), electronic device 600 displays a visual indication 1068 associated with the event and electronic device 800 displays a visual indication 1070 associated with the event. In some embodiments, in response to detection of the ring closed event, electronic device 600 causes electronic device 800 to display the visual indication 1070.

In some embodiments, visual aspects of the "check your rings" event (or other events) can differ based on an orientation of the device 600. For example, in FIGS. 10J-10M, physical activity rings 1036 were displayed on a bottom portion of the device 600, away from the notch in the display. However, in FIG. 10M1, the phone is oriented in the opposite manner, such that physical activity rings 1036 are displayed on the top side, or notch side, of the device 600. When the physical activity rings 1036 are presented on the notch side of the device 600, expanding the physical activity rings 1036 can cause them to run into the notch 602A in the display 602. Accordingly, in some embodiments, when the physical activity rings 1036 are displayed on the notch side

81

of the device 600, visually emphasizing the physical activity rings 1036 can include expanding the physical activity rings 1036 as well as translating them in a direction away from the notch 602A.

In FIG. 10M2, in response to electronic device 600 detecting the check your rings event, the electronic device 600 enlarges the physical activity rings 1036, and translates them in a left-ward direction away from the notch 602A in the display 602.

In FIG. 10M3, the physical activity rings 1036 are maintained in their translated position while the check your rings event occurs.

In FIG. 10M4, in response to electronic device 600 detecting that the check your rings event has ended, the electronic device 600 reduces the size of the physical activity rings 1036, and translates them to the right, back to their original position.

At FIG. 10N, electronic device 600 and/or electronic device 800 detects a “check your heart rate” event based on event criteria (e.g., at the 15 minute mark of the workout session). In response to detection of the check your heart rate event (e.g., by electronic device 600 and/or electronic device 800), electronic device 600 displays a visual indication 1072 associated with the event. The visual indication 1072 includes the user’s current heart rate 1072A, the user’s high heart rate during the workout session 1072B, and the user’s low heart rate during the workout session 1072C. In some embodiments, even if a user has elected not to view certain physical activity metrics, an event can override such elections by the user and cause presentation of such information. For example, if a user has elected not to view heart rate information using the edit metrics interface 1050, a check your heart rate event can override such election, and cause display of the user’s heart rate information.

In FIG. 10N, electronic device 600 also displays a visual indication 1074 based on a determination that a new song has begun playing. The visual indication 1074 identifies a track name and artist for the new song that has begun playing during the workout session.

In FIG. 10O, in response to a determination that the visual indication 1072 has been displayed for a predetermined period of time, the electronic device 600 ceases display of the visual indication 1072. In FIG. 10O, in response to a determination that the visual indication 1074 has been displayed for a predetermined period of time, the electronic device 600 ceases display of the visual indication 1074.

At FIG. 10P, the electronic device 600 and/or the electronic device 800 detects that the workout session has concluded. In response to detecting that the workout session has concluded, the electronic device 600 replaces display of the workout session user interface 1030 with a workout summary user interface 1076, and the electronic device 800 replaces display of the workout metrics user interface 1032 with a workout summary user interface 1078. In some embodiments, in response to detecting that the workout session has concluded, electronic device 600 causes electronic device 800 to replace display of the workout metrics user interface 1032 with the workout summary user interface 1078. The workout summary user interface 1076 optionally displays calorie information for the workout session (e.g., active calorie information 1080A, total calorie information 1080B), heart rate information for the workout session (e.g., average heart rate 1080C), duration information for the workout session (e.g., total time 1080D), and information pertaining to the user’s performance relative to other users (e.g., workout intensity information 1080E (e.g., corresponds to workout intensity representation 1040D as dis-

82

cussed with respect to FIGS. 12A-12O)). The workout summary user interface 1076 also optionally displays physical activity ring information 1080J, which indicates the state of the user’s physical activity rings 1036 after the workout. The workout summary user interface 1076 optionally also includes an option 1080F to close the workout summary user interface, an option 1080G to share workout summary information, and an option 1080H to select a cool down workout. In some embodiments, electronic device 600 can decide to display and/or decide to forgo displaying the cool down workout option 1080H based on user preferences and/or past user behavior. For example, if a user has historically chosen to go straight into another workout, or if a user historically chooses not to do a cool down workout, electronic device 600 can exclude option 1080H from the workout summary user interface 1076, whereas if a user has historically chosen to do a cool down workout, electronic device 600 can include option 1080H in the workout summary user interface 1076. The workout summary user interface 1078 displays a subset of the information in the workout summary user interface 1076 (in this case, a total workout duration 1080I, which corresponds to total time 1080D).

While displaying the workout summary user interface 1076, electronic device 600 detects an input 1082 at a location that corresponds to the cool down workout option 1080H.

At FIG. 10Q, in response to detecting input 1082, electronic device 600 replaces display of the workout summary user interface 1076 with cool down workout selection user interface 1084. Similarly, in response to electronic device 600 detecting input 1082, electronic device 800 replaces display of workout summary user interface 1078 with cool down workout selection user interface 1086. In some embodiments, in response to detecting input 1082, electronic device 600 causes electronic device 800 to replace display of workout summary user interface 1078 with cool down workout selection user interface 1086. The cool down workout selection user interface 1084 on electronic device 600 includes selectable options 1088A, 1088B, and 1088C that can be selected by a user to select a particular cool down workout. The cool down workout selection user interface on electronic device 800 includes selectable options 1088D, 1088E, and 1088F that correspond to the selectable options 1088A, 1088B, and 1088C. A user can use the selectable options on either electronic device 600 or electronic device 800 to select his or her cool down workout. For example, if the electronic device 600 detects an input at a location corresponding to 5-minute option 1088A on electronic device 600 (e.g., user input 1090A), or if the electronic device 800 detects an input at a location corresponding to 5-minute option 1088D on electronic device 800 (e.g., user input 1090B), visual display corresponding to a 5-minute cool down workout can be initiated on electronic device 600 and corresponding display can be initiated on electronic device 800.

In the depicted embodiment, each time duration (e.g., 5-minutes, 10-minutes, 15-minutes) has only one cool down workout associated with it. However, it should be understood that in other embodiments, there can be multiple workouts for each time duration (e.g., multiple 5-minute cool down workouts, multiple 10-minute cool down workouts). In some embodiments, if the electronic device 600 determines that the cool down workout selection user interface 1084 has been displayed for a threshold period of time, a default cool down workout can automatically begin playing even without a user input. In some embodiments, the electronic device 600 can automatically select one or more

cool down workouts based on characteristics of the workout that was just completed (e.g., based on the trainer of the workout, based on the workout type, based on a duration of the workout, etc.). For example, if a user has just completed a leg-intensive workout, the electronic device **600** can automatically select a cool down workout that focuses on stretching and loosening the legs. In some embodiments, a particular workout can be associated with one or more cool down workouts such that the electronic device **600** can automatically identify one or more cool down workouts that are associated with the particular workout.

At FIG. **10R**, in response to electronic device **600** detecting input **1090A** or electronic device **800** detecting input **1090B**, electronic device **600** replaces display of the cool down workout selection user interface **1084** with cool down workout user interface **1092A**, and electronic device **800** replaces display of cool down workout selection user interface **1086** with cool down workout metrics interface **1092B**. In some embodiments, electronic device **600** causes electronic device **800** to replace display of cool down workout selection user interface **1086** with cool down workout metrics interface **1092B**. Cool down workout interface **1092A** includes a countdown timer **1094A** counting down the remaining time in the cool down workout, and cool down workout metrics interface **1092B** also includes a corresponding countdown timer **1094B**. The cool down workout interface **1092A** includes video content **1096** that leads a user through the cool down workout. The cool down workout metrics interface **1092B** includes heart rate information **1098** that presents the user with his or her current heart rate.

FIG. **10S** depicts the workout summary user interface **1076** of FIG. **10P**. However, rather than detecting selection of the cool down option **1080H**, in FIG. **10S**, the electronic device **600** detects a user input **1082A** at a location corresponding to the share option **1080G**.

At FIG. **10T**, in response to detecting input **1082A**, electronic device **600** displays share user interface **1089**. In the depicted embodiment, share user interface **1089** is overlaid on workout summary user interface **1076**. Share user interface **1089** includes options **1091A-1091E**. Each option **1091A-1091E** corresponds to a respective contact, and selection of an option **1091A-1091E** will open a messaging application user interface that allows the user to send workout summary information to the selected contact. Share user interface **1089** also includes application options **1093A-1093E** that are selectable by a user to open a particular application for sharing workout summary information (e.g., a near-field communications transmission application (**1093A**), a text messaging application (**1093B**), an email messaging application (**1093C**)). While displaying share user interface **1089**, electronic device **600** detects input **1095** at a location corresponding to option **1091A**.

At FIG. **10U**, in response to detecting input **1095**, electronic device **600** initiates a process for transmitting workout summary information to the contact associated with option **1091A**. In FIG. **10U**, electronic device **600** has replaced display of the share user interface **1089** and the workout summary user interface **1076** with a messaging application user interface **1097**, and has initiated transmission of workout summary information to the selected contact. Workout summary information is presented in the messaging application user interface **1097** as a message **1099**. Workout summary information contained in message **1099** can include some or all of the information presented in workout summary user interface **1076**. In FIG. **10U**, the workout summary information contained in message **1099** includes workout type information **1085A** ("CORE"), workout

trainer information **1085B** ("AMY"), workout duration information **1085C** ("20 MIN"), workout music information **1085D** ("HIP-HOP"), episode information **1085E** ("EP 116"), active calorie information **1085F** ("112 CAL"), and total workout time information **1085G** ("21:08"), as well as an image representative of the workout **1085H**.

In some embodiments, workout summary information presented in message **1099** can differ based on the workout. For example, in FIG. **10V**, rather than sharing workout summary information for a core workout, the user has shared information for a run workout. In FIG. **10V**, message **1099A** includes the same workout summary information as was included in message **1099**, but also includes a route map **1085J** corresponding to the run workout performed by the user which was not included in message **1099** of FIG. **10U**.

FIG. **11** is a flow diagram illustrating a method for displaying video content and providing workout information relating to the video content using an electronic device in accordance with some embodiments. Method **1100** is performed at an electronic device (e.g., **100**, **300**, **500**, **600**, **800**) with a display (e.g., **602**, **801**). Some operations in method **1100** are, optionally, combined, the orders of some operations are, optionally, changed, and some operations are, optionally, omitted.

As described below, method **1100** provides an intuitive way for displaying video content and providing workout information relating to the video content. The method reduces the cognitive burden on a user for displaying video content and providing workout information relating to the video content, thereby creating a more efficient human-machine interface. For battery-operated computing devices, enabling a user to display video content and provide workout information relating to the video content faster and more efficiently conserves power and increases the time between battery charges.

In some embodiments, the electronic device (e.g., **100**, **300**, **500**, **600**, **800**) is a computer system. The computer system is optionally in communication (e.g., wired communication, wireless communication) with a display generation component and with one or more input devices. The display generation component is configured to provide visual output, such as display via a CRT display, display via an LED display, or display via image projection. In some embodiments, the display generation component is integrated with the computer system. In some embodiments, the display generation component is separate from the computer system. The one or more input devices are configured to receive input, such as a touch-sensitive surface receiving user input. In some embodiments, the one or more input devices are integrated with the computer system. In some embodiments, the one or more input devices are separate from the computer system. Thus, the computer system can transmit, via a wired or wireless connection, data (e.g., image data or video data) to an integrated or external display generation component to visually produce the content (e.g., using a display device) and can receive, a wired or wireless connection, input from the one or more input devices.

The electronic device causes concurrent display (**1102**), via a display device (e.g., a display device of an electronic device (e.g., display **602** of electronic device **600**), a display device of or in communication with an external device (e.g., television, set top box)), of video content (e.g., **1034**, workout video) and one or more representations of physical activity metrics (e.g., **1036**, **1036A-C**, **1038**, **1040A-D**, hours in which a user has stood for at least some predetermined amount of time, minutes of activity above a certain threshold activity level, active calories, heart rate, distanced

traveled, stairs climbed either based on passive background activity monitoring or activity data recorded during specific workouts) corresponding to a user. In some embodiments, the one or more representations of the physical activity metrics correspond to a predetermined amount of time that includes a period of time preceding playback of the content (1104). In some embodiments, the one or more representations of the physical activity metrics are overlaid on the video content (1106). Causing concurrent display of video content and one or more representations of physical activity metrics provides the user with feedback about physical activity metrics and other information recorded by the electronic device. Providing improved feedback to the user enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

While continuing to cause display of the video content (1108), the electronic device receives (1110) activity data based on physical activity of the user during the display of the video content (1108) (e.g., 1034), and in response to receiving the activity data (1114), the electronic device updates (1116) the display of the one or more representations of the physical activity metrics based on the received activity data (e.g., 1036, 1036A-C, 1038, 1040A-D). In some embodiments, updating the display of the one or more representations of the physical activity metrics includes changing (e.g., highlighting, emphasizing) a visual characteristic of at least a portion of the one or more representations. Updating the display of the one or more representations of the physical activity metrics based on received activity data provides the user with updated feedback about physical activity metrics and other information recorded by the electronic device. Providing improved feedback to the user enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, the video content (e.g., 1034) corresponds to a workout (e.g., a physical activity to be performed by the user), and the received activity data is based on physical activity of the user captured via one or more sensors (e.g., GPS, accelerometer, heart rate, and/or gyroscope) that is in communication with the electronic device (1112). In some embodiments, the one or more sensors correspond to (e.g., are part of) an external device. In some embodiments, the one or more sensors correspond to (e.g., are part of) the electronic device.

In some embodiments, while causing display of the video content, the electronic device causes one or more sensors of an external device to be enabled/activated so as to improve accurate measurements of the user during the workout. In some embodiments, the one or more sensors are not enabled/activated prior to display of the video content. In some embodiments, a subset of the one or more sensors are enabled/activated based on the type of workout. In some embodiments, in accordance with a determination that a workout is of a first type, a first subset of the one or more sensors are enabled/activated based on the first type. In some embodiments, in accordance with a determination that a

workout is of a second type, a second subset of the one or more sensors are enabled/activated based on the second type.

In some embodiments, the one or more representations of the physical activity metrics include a plurality of (e.g., concentric) rings (e.g., 1036, 1036A-C), and a first ring (e.g., 1036A, 1036B, 1036C) of the plurality of rings corresponds to a first type of physical activity metrics (e.g., hours in which a user has stood for at least some predetermined amount of time, minutes of activity above a certain threshold activity level, active calories, heart rate, distanced traveled, stairs climbed either based on passive background activity monitoring or activity data recorded during specific workouts). In some embodiments, a second ring and a third ring of the plurality of concentric rings corresponds to a second type and a third type of physical activity metrics, respectively. In some embodiments, the one or more representations of the physical activity metrics are based on data captured from an external device (e.g., 800, smartwatch) that is in communication with the electronic device. In some embodiments, the data is captured from the external device regardless of which device (e.g., a device other than the external device and the electronic device, the electronic device) is displaying the video content.

In some embodiments, the one or more representations of the physical activity metrics include a representation of calories burned by the user (e.g., 1036A, 1040C).

In some embodiments, the one or more representations of the physical activity metrics include a representation of an amount of time that has elapsed (e.g., 1040A, corresponding to the amount of time that the video content has been playing via the display device (e.g., the amount of time the user has been physically active)).

In some embodiments, the one or more representations of the physical activity metrics include a representation of a heart rate of the user (e.g., 1040B, a real-time heart rate, a heart-rate taken at predetermined intervals (e.g., 5, 10, 30 seconds)).

In some embodiments, while continuing to cause display of the video content, the electronic device detects a first user input (e.g., 1044, anywhere on the display device, at a location corresponding to the video content); and, in response to detecting the first user input, the electronic device causes display, via the display device, of a set of one or more playback controls (e.g., 1046A-E, play/pause, close, volume, closed captions, edit which physical activity metrics are displayed) that are overlaid on the video content. Causing display of a set of one or more playback controls that are overlaid on the video content in response to a user input allows the electronic device to reveal playback controls when needed to control playback of the video content while also providing the electronic device with the ability to keep the playback controls hidden when they are not needed. Providing additional control of the device without cluttering the UI with additional displayed controls enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, while causing display of the set of one or more playback controls that includes an edit selectable user interface object (e.g., 1046E), the electronic device detects a user input (e.g., 1048) corresponding to the edit selectable user interface object. In some embodiments, in response to detecting the user input corresponding to the edit

selectable user interface object, the electronic device causes display, via the display device, of one or more options for configuring the display of the one or more representations of the physical activity metrics (e.g., **1052A-E**). In some embodiments, the electronic device detects one or more user inputs corresponding to configuring the display of the one or more representations of the physical activity metrics, including detecting selection of a respective option of the one or more options for configuring the one or more representations of the physical activity metrics. In some embodiments, in response to detecting the one or more user inputs corresponding to configuring the display of the one or more representations of the physical activity metrics, the electronic device causes display, via the display device, of the video content and updates the display of the one or more representations of the physical activity metrics based on the detected one or more user inputs corresponding to configuring the display of the one or more representations of the physical activity metrics. In some embodiments, updating the display of the one or more representations of physical activity metrics includes modifying the format (e.g., elapsed time, remaining time) of a respective representation (e.g., options **1052C**, **1052D**). In some embodiments, updating the display includes ceasing to display or causing display of a respective representation (e.g., options **1052A**, **1052B**, **1052E**). In some embodiments, the one or more options for configuring the display of the one or more representations of physical activity metrics correspond to elapsed time (e.g., **1052C**), remaining time (e.g., **1052D**), the plurality of rings, and workout intensity representation (e.g., **1052E**, further discussed below). In some embodiments, while causing display of the video content, the electronic device overrides the configuration of the display of the one or more representations of physical activity metrics (e.g., causing display of a respective representation that would otherwise be hidden/not displayed). In some embodiments, the one or more options for configuring the one or more representations of the physical activity metrics are overlaid on the video content.

In some embodiments, while continuing to cause display of the video content, and in accordance with a determination that the a first type of event has occurred (e.g., a predefined milestone has been achieved (e.g., a threshold value has been obtained for a particular physical activity metric), a particular playback position of the video content has been reached), the electronic device visually emphasizes, via the display device, at least a portion of the one or more representations of the physical activity metrics without visually emphasizing a different portion of the one or more representations of the physical activity metrics (e.g., as depicted in FIGS. **10G-10O**). In some embodiments, visually emphasizing at least the portion of the one or more representations of the physical activity metrics includes deemphasizing (e.g., obscuring, dimming) a different portion of the one or more representations of the physical activity metrics (e.g., as depicted in FIGS. **10K-M**). In some embodiments, the determination is made based on metadata associated with the video content. Visually emphasizing at least a portion of the one or more representations of the physical activity metrics without visually emphasizing a different portion of the one or more representations of the physical activity metrics provides the user with feedback about the current state of the device (e.g., that the device has detected a particular event). Providing improved feedback to the user enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when

operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently. Automatically visually emphasizing at least a portion of the one or more representations of the physical activity metrics in accordance with a determination that a first type of event has occurred also provides the user with feedback about the current state of the device (e.g., that the device has detected a particular event). Performing an optimized operation when a set of conditions has been met without requiring further user input enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, visually emphasizing at least the portion of the one or more representations of the physical activity metrics includes: causing an audio output associated with the portion of the one or more representations of the physical activity metrics, wherein the portion includes a plurality of rings (e.g., **1036**); and expanding the displayed size of the plurality of rings (e.g., as depicted in FIGS. **10J-10L**), including causing display of information (e.g., **1063A-C**, text, numerical value) about the plurality of rings. In some embodiments, the audio output is diegetic audio that occurs in the video as part of the world of the video, for example when a trainer says “check your rings” as part of leading the workout. In some embodiments, expanding the displayed size of the plurality of rings includes deemphasizing (e.g., dim, obscure, fade) other portions of the one or more representations of the physical activity metrics. In some embodiments, the electronic device emphasizes (e.g., at a specific time) at least the portion of the one or more representations of the physical activity metrics (e.g., by expanding the displayed size of the plurality of rings (e.g., as depicted in FIGS. **10J-10L**)), based on data (e.g., metadata associated with the video content) that indicates when the video content advances to the portion of the video content that includes particular audio content (e.g., the diegetic audio). In some embodiments, the electronic device controls (e.g., based on metadata) the timing of when the at least a portion of the one or more representations of the physical activity metrics is visually emphasized so that the visual emphasis corresponds with, precedes, and/or follows output of specific audio content (e.g., diegetic audio content such as “a training saying “check your rings”) within the video content.

In some embodiments, visually emphasizing at least the portion of the one or more representations of the physical activity metrics further includes: in accordance with a determination that the plurality of rings (e.g., **1036**) are presented within a first region of the display device (e.g., in accordance with a determination that the plurality of rings are presented on a notch side of the display device (e.g., a side of the display device that includes a notch)) (e.g., FIGS. **10M1-10M4**), translating the plurality of rings in a first direction (e.g., in a direction towards a center of the display device and/or away from the notch) by a first amount and expanding the displayed size of the plurality of rings (e.g., FIGS. **10M2, 10M3**), and in accordance with a determination that the plurality of rings are presented within a second region of the display device different from the first region (e.g., in accordance with a determination that the plurality of rings are presented on side of the display device opposite the notch side) (e.g., FIGS. **10J-10M**), expanding the displayed size of

the plurality of rings without translating the plurality of rings in the first direction by the first amount (in some embodiments, with translating the plurality of rings in the first direction). Automatically translating the plurality of rings and/or not translating the plurality of rings based on the position of the plurality of rings allows the electronic device to present information to the user without additional user input. Performing an optimized operation when a set of conditions has been met without requiring further user input enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, visually emphasizing at least the portion of the one or more representations of the physical activity metrics includes expanding the displayed size of the plurality of rings (e.g., **1036**, as depicted in FIGS. **10J-10L**), including causing display of a visual indication that a respective ring of the plurality of rings has closed (e.g., **1068**). In some embodiments, in response to receiving activity data, the electronic device fills in an unfilled portion of one or more rings of the plurality of rings. In some embodiments, once a respective ring is completely filled in, the ring is closed, which indicates that the user has achieved their goal with respect to the physical activity metric represented by the ring.

In some embodiments, visually emphasizing at least the portion of the one or more representations of the physical activity metrics includes: while causing display, via the display device, of a first representation of time (e.g., elapsed time, remaining time) corresponding to the video content (e.g., corresponding to the overall duration of the video content), causing display, via the display device, of a second representation of time corresponding to a predefined amount of time (e.g., 10, 20, 30 seconds) (e.g., as depicted in FIGS. **10G-10H**). In some embodiments, the second representation of time replaces the first representation of time.

In some embodiments, causing display of the second representation of time corresponding to a predefined amount of time comprises: causing display of an animation in which a numerical value corresponding to the predefined amount of time is overlaid on a blinking background (e.g., **1058A**, **1058B**, FIGS. **10G-10G3**). In some embodiments, causing display of the animation comprises: causing display of the numerical value corresponding to the predefined amount of time (e.g., “10” in **1058A**, **1058B**, FIGS. **10G-10G3**) overlaid on a background portion, wherein the background portion is displayed in a first state; and while maintaining display of the numerical value corresponding to the predefined amount of time, transitioning the background portion from the first state to a second state different from the first state (e.g., FIGS. **10G-10G3**). In some embodiments, the first state and the second state comprise different visual characteristics (e.g., different colors, different brightnesses, different hues). In some embodiments, the animation is presented immediately prior to initiation of a countdown animation. Displaying an animation of the numerical value overlaid on a blinking background provides the user with feedback about the current state of the device (e.g., that a timer is about to begin). Providing improved feedback to the user enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally,

reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, visually emphasizing at least the portion of the one or more representations of the physical activity metrics includes: causing display, via the display device, of one or more representations of a heart rate of the user (e.g., **1072**, **1072A-C**, a real-time heart rate, a heart-rate taken at predetermined intervals (e.g., 5, 10, 30 seconds), high/low/current heart rate for the duration of playback of the video content). In some embodiments, the electronic device causes an output of a (e.g., audio, visual) prompt for the user to check their heart rate. In some embodiments, the output prompt occurs while the one or more representations of the heart rate are displayed.

In some embodiments, visually emphasizing at least the portion of the one or more representations of the physical activity metrics includes: causing a second display device (e.g., **800**) different from the display device to display information corresponding to the visually emphasized portion of the one or more representation of the physical activity metrics. In some embodiments, the electronic device causes the second display device (e.g., of an external device such as a smartwatch) to display a textual notification corresponding to the visually emphasized portion (e.g., as depicted in FIGS. **10G-10M**). In some embodiments, in accordance with a determination that the portion that is visually emphasized is not of a particular type (e.g., heart rate or time representation), the electronic device does not cause the second display device to display information corresponding to the visually emphasized portion (e.g., as depicted in FIG. **10N**). In some embodiments, the electronic device causes the second display device to display the information in accordance with a determination that the portion that is visually emphasized is of the particular type (e.g., not heart rate or time representation).

In some embodiments, visually emphasizing at least the portion of the one or more representations of the physical activity metrics includes: causing display, via the display device, of an indication that a midpoint (e.g., halfway point) in the duration of the video content has been reached (e.g., **1060**).

In some embodiments, visually emphasizing at least the portion of the one or more representations of the physical activity metrics includes visually obscuring (e.g., fading, dimming) other portions of the one or more representations of the physical activity metrics (e.g., as depicted in FIGS. **10K-10M**).

In some embodiments, while continuing to cause display of the video content, the electronic device causes display, via the display device, of an indication that a music track change has occurred (e.g., **1074**).

In some embodiments, while continuing to cause display of the video content, the electronic device causes display, via the display device, of a new representation (e.g., **1072**) of a physical activity metric, wherein the new representation of the physical activity metric was not selected for display during display of the video content (e.g., based on default or user selected settings). In some embodiments, the electronic device causes display of the new representation in accordance with a determination that the a first type of event has occurred (e.g., a predefined milestone has been achieved (e.g., a threshold value has been obtained for a particular physical activity metric), a particular playback position of the video content has been reached). Causing display of a new representation of a physical activity metric provides the user with feedback about the current state of the device (e.g.,

that the device has received information pertaining to the physical activity metric). Providing improved feedback to the user enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, after (e.g. in response to) the end of the video content has been reached, the electronic device causes display, via the display device, of one or more aggregate representations (e.g., active calories, total calories, total time, average heart rate, distance, average pace, workout intensity representation) of physical activity metrics that are based on physical activity of the user for the duration of the video content (e.g., **1076**, **1080A-E**).

In some embodiments, the one or more aggregate representations of physical activity metrics include the one or more representations of the physical activity metrics (e.g., **1080J**) (e.g., a plurality of (e.g., concentric) rings) (e.g., hours in which a user has stood for at least some predetermined amount of time, minutes of activity above a certain threshold activity level, active calories, heart rate, distanced traveled, stairs climbed either based on passive background activity monitoring or activity data recorded during specific workouts). Displaying the one or more representations of the physical activity metrics provides the user with updated feedback about physical activity metrics and other information recorded by the electronic device. Providing improved feedback to the user enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, after (e.g., in response to) the end of the video content has been reached, the electronic device causes display, via the display device, of a selectable user interface object for sharing workout summary information (e.g., **1080G**). In some embodiments, the selectable user interface for sharing the workout summary is concurrently displayed with the one or more aggregate representations of physical activity metrics. In some embodiments, the electronic device detects a user input (e.g., **1082A**) corresponding to selection of the selectable user interface object for sharing the workout summary (e.g., **1080G**). In some embodiments, in response to detecting the user input corresponding to selection of the selectable user interface object for sharing the workout summary, the electronic device initiates a process for transmitting workout summary information to a remote electronic device (e.g., **FIGS. 10T-10V**) (e.g., via a network), wherein the workout summary information (e.g., **1099**, **1099A**) includes at least one of the following: a map (e.g., **1085J**) corresponding to the activity data received based on physical activity of the user during display of the video content; trainer information corresponding to the video content (e.g., **1085B**, **1085H**) (e.g., name of trainer, photo of trainer); workout type information corresponding to the video content (e.g., **1085A**); duration information corresponding to the video content (e.g., **1085C**, **1085G**); and distance information corresponding to the activity data received based on physical activity of the user during display of the video content. Displaying a selectable user interface object for sharing workout summary information enables a user to quickly share workout summary

information, thereby reducing the number of inputs needed for sharing workout summary information. Reducing the number of inputs needed to perform an operation enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, after (e.g. in response to) the end of the video content has been reached, the electronic device causes display, via the display device, of a selectable user interface object for displaying second video content (e.g., **1080H**, **1088A-C**, that guides a user through a cool down routine); and in response to detecting the selectable user interface object for displaying the second video content, the electronic device initiates a process for displaying the second video content.

In some embodiments, the selectable user interface object for displaying second video content is concurrently displayed with the one or more final representations of physical activity metrics (e.g., **1080A-E**). In some embodiments, the selectable user interface object for displaying second video content is displayed in accordance with a determination that the video content is of a particular type (e.g., workouts with a physical activity level above a certain threshold).

In some embodiments, while causing display of the selectable user interface object for displaying second video content (e.g., **1080H**, **1088A-C**) and in accordance with a determination that a predetermined amount of time has elapsed, the electronic device causes display, via the display device, of the second video content (e.g., **1092A**). In some embodiments, the second video content is selected for display based one or more characteristics of the video content (e.g., trainer, duration, modality/exercise type, focus of workout (upper body or lower body), exertion/physical activity level). Automatically causing display of the second video content in accordance with a determination that a predetermined amount of time has passed allows the electronic device to present additional video content without additional user input. Performing an optimized operation when a set of conditions has been met without requiring further user input enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, initiating the process for displaying the second video content includes causing display, via the display device, of a plurality of options (e.g., **1088A-F**, selectable user interface object, affordance) for configuring the duration (e.g., 5, 10, 15 minutes) of the second video content.

In some embodiments, the electronic device selects the second video content (e.g., **1088A-1088C**, **1088D-1088F**, **1092A**) from a plurality of available video content options (e.g., a collection of available cool down routines or workouts) based on selection criteria, wherein the selection criteria comprise at least one of: workout trainer information, workout equipment information, and user preference information. Automatically selecting the second video content based on selection criteria allows the electronic device to present additional video content without additional user input. Performing an optimized operation when a set of

conditions has been met without requiring further user input enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, after (e.g. in response to) the end of the video content has been reached: in accordance with a determination that the user satisfies a first set of criteria (e.g., in accordance with a determination that the user, based on past behavior, is not likely to perform another workout), the electronic device causes display, via the display device, of a selectable user interface object for displaying second video content (e.g., **1080H**) (e.g., that guides a user through a cool down routine); and in accordance with a determination that the user satisfies a second set of criteria different from the first set of criteria (e.g., in accordance with a determination that the user, based on past behavior, is likely to perform another workout), the electronic device forgoes display of the selectable user interface object for displaying second video content. Automatically displaying a selectable user interface object and/or automatically forgoing display of the selectable user interface object based on first and second sets of criteria allows the electronic device to present optimized content for a user without additional user input. Performing an optimized operation when a set of conditions has been met without requiring further user input enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

Note that details of the processes described above with respect to method **1100** (e.g., FIG. **11**) are also applicable in an analogous manner to the methods described below. For example, method **1100** optionally includes one or more of the characteristics of the various methods described below with reference to method **1300**. For example, the physical activity metrics in method **1100** optionally include the workout intensity representation **1040D**, as described with reference to method **1300**. For brevity, these details are not repeated below.

FIGS. **12A-12O** illustrate exemplary user interfaces for displaying workout information, in accordance with some embodiments. In some embodiments, the workout information can include in-workout physical activity metrics, such as workout intensity information, and other information associated with a workout being performed by a user. The user interfaces in these figures are used to illustrate the processes described below, including the processes in FIG. **13**.

FIG. **12A** depicts electronic device **600**, which is a smartphone with display **602**. Display **602** of electronic device **600** includes a touch-sensitive surface on which electronic device **600** can detect user gestures (e.g., tap, swipe, drag). In some embodiments, electronic device **600** includes one or more features of electronic device **100**, **300**, and/or **500**.

At FIG. **12A**, the electronic device **600** displays workout session user interface **1030**. The workout session user interface **1030** includes video content **1034** that guides a user through a workout session (e.g., a video of an instructor demonstrating a workout). The workout session user interface **1030** also includes physical activity metrics indicative

of a user's physical activity. The physical activity metrics include physical activity rings **1036** which include move ring **1036A**, exercise ring **1036B**, and stand ring **1036C**. In some embodiments, physical activity rings **1036** are associated with (e.g., are indicative of) physical activity by a user for a predetermined period of time which includes a period of time preceding initiation of the workout session. For example, the physical activity rings **1036** can be indicative of physical activity by the user for the entire day to that point (e.g., from 12:00 am until the current time in the day). In some embodiments, the move ring **1036A** is indicative of a number of calories burned by a user during the day, the exercise ring **1036B** is indicative of a number of minutes the user has been active during the day, and the stand ring **1036C** is indicative of the number of hours during the day in which the user has stood up for a threshold amount of time or a threshold number of times. In some embodiments, including the depicted embodiment, the move ring **1036A** is indicative of progress towards a move goal (e.g., a target number of calories for a day), the exercise ring **1036B** is indicative of progress towards an exercise goal (e.g., a target number of exercise minutes for a day), and the stand ring **1036C** is indicative of progress towards a stand goal (e.g., a target number of hours for a day). For example, in the depicted embodiment, the move ring **1036A** is approximately $\frac{2}{3}$ completed, indicating that the user is approximately $\frac{2}{3}$ of the way to their move goal, the exercise ring **1036B** is approximately $\frac{1}{2}$ completed, indicating that the user is approximately $\frac{1}{2}$ of the way to their exercise goal, and the stand ring **1036C** is approximately $\frac{1}{2}$ completed, indicating that the user is approximately $\frac{1}{2}$ of the way to their stand goal.

Physical activity metrics in the workout session user interface **1030** also include workout session physical activity metrics **1038** indicative of the user's physical activity during the current workout session. For example, in some embodiments, the workout session physical activity metrics **1038** include workout duration information **1040A** (e.g., the workout has been in session for 1 second), heart rate information **1040B** (e.g., the user's current heart rate is 61 beats per minute), and calorie information **1040C** (e.g., the user has burned 0 calories so far in this workout session).

The workout session physical activity metrics can also include a workout intensity representation **1040D**. As will be described in greater detail with reference to FIGS. **12F** to **12N**, the workout intensity representation **1040D** is indicative of the user's workout intensity level in the workout session relative to other users that have previously participated in (or are currently participating in) the workout session. However, in FIGS. **12A** to **12E**, the workout session has just started (as indicated by workout duration information **1040A**). As such, it can be the case that there is insufficient information to compare the user's workout intensity level relative to other users. Therefore, the workout intensity representation **1040D** in FIGS. **12A** to **12E** depicts an initial visual effect **1202** indicating that the electronic device **600** is gathering additional information in order to compare the user's workout intensity level to other users. In the depicted embodiment, the initial visual effect **1202** is a symbol or icon moving from left to right to indicate that there is some uncertainty as to how the user's workout intensity compares the workout intensity of other users.

User physical activity metrics (including information included in physical activity rings **1036** and workout session physical activity metrics **1038**) can be measured by one or more sensors in electronic device **600** and/or one or more sensors external to electronic device **600**. Such sensors can include, for example, one or more GPS sensors, one or more

accelerometers, one or more heart rate sensors, one or more gyroscopes, and the like. As the user performs a workout, the electronic device **600** can receive activity data based on the physical activity of the user, and update the physical activity metrics that are displayed (e.g., in the physical activity rings **1036** and/or the workout session physical activity metrics **1038**).

In some embodiments, after a threshold period of time (e.g., after 30 seconds, after 1 minute), there can be sufficient information to determine the user's workout intensity level relative to other users.

At FIG. **12F**, the workout session has been in session for one minute (as demonstrated by workout duration information **1040A**). Based on a determination that a threshold period of time has elapsed, electronic device **600** replaces display of the initial visual effect **1202** with the workout intensity representation **1040D**. The workout intensity representation **1040D** comprises an icon **1204** and a bar **1206**. The position of the icon **1204** can move along the bar **1206**, and the position of the icon **1204** along the bar **1206** is indicative of the user's workout intensity level relative to other users that have previously participated in and/or are currently participating in the workout session. For example, in FIGS. **12A-12O**, the user is viewing video content entitled "Core with Amy" (as indicated in FIG. **12O**), e.g., the user is participating in a workout session entitled "Core with Amy." In some embodiments, the workout intensity representation **1040D** (e.g., the position of the icon **1204** along the bar **1206**) can be indicative of the user's workout intensity level during the workout session (e.g., while viewing the video content entitled "Core with Amy") relative to other users while those users were also participating in the same workout (e.g., while those users were also viewing the video content entitled "Core with Amy"). In some embodiments, positioning of the icon **1204** on the bar **1206** is determined using only data collected from users while those users were viewing the same video content. For example, data collected from users that were participating in a different workout (e.g., Cardio with Bob) can be excluded and/or ignored in the workout intensity representation **1040D** for the user participating in the "Core with Amy" workout. The user's workout intensity level and the placement of the icon **1204** along the bar **1206** can be determined based on one or more physical activity metrics, such as heart rate (current heart rate, average heart rate, low heart rate, and/or high heart rate), calories burned, and the like.

In some embodiments, the workout intensity representation **1040D** can correspond to a predetermined number of workout intensity groups. A user can be categorized into a particular workout intensity group based on his or her workout intensity as can be determined based on one or more physical activity metrics. For example, workout intensity can be determined based on calories burned, and there can be multiple, e.g., five, defined workout intensity groups, e.g., a fifth/lowest workout intensity group associated with a first range of burned calories (e.g., 0-40 calories burned), a fourth workout intensity group associated with a second range of burned calories (e.g., 41-60 calories burned), a third workout intensity group associated with a third range of burned calories (e.g., 61-80 calories burned), a second workout intensity group associated with a fourth range of burned calories (e.g., 81-100 calories burned), and a first workout intensity group associated with a fifth range of burned calories (e.g., 101 calories and up). It should be understood that the number of groups and the specific percentages provided herein are provided as examples for clarity of explanation, and are not meant to be limiting

embodiments. Ranges of physical activity metrics and/or workout intensity thresholds used to define each workout intensity group can be defined based on previous performance by other users that participated in the workout session. For example, a fifth workout intensity group can be defined to capture a first percentage of users, a fourth workout intensity group can be defined to capture a second percentage of users, a third workout intensity group can be defined to capture a third percentage of users, and so forth. In some embodiments, a user's workout intensity level can be compared against a group of users that share one or more characteristics with the user (e.g., fitness level, age range, weight range). In other words, the workout intensity thresholds used to define particular workout intensity groups for a particular user can be defined based on a group of users that share one or more characteristics with the user (e.g., in order to normalize the workout intensity thresholds based on the fitness level and/or the demographics of the user).

In the depicted embodiment, users can be grouped into one of five different workout intensity groups. Each workout intensity group can be associated with a unique set of criteria or thresholds in order to assign users to a particular workout intensity group based on their physical activity metrics. Furthermore, each workout intensity group can be associated with a particular position along the bar **1206**. For example, a fifth and lowest workout intensity group can be associated with a leftmost position on the bar **1206**, a fourth workout intensity group can be associated with a center-left position on the bar **1206**, a third workout intensity group can be associated with a center position on the bar **1206**, a second workout intensity group can be associated with a center-right position on the bar **1206**, and a first and highest workout intensity group can be associated with a right-most position on the bar **1206**.

At FIG. **12F**, the user's physical activity metrics indicate that the user's workout intensity falls within a third/middle workout intensity group relative to other users. As such, the icon **1204** is positioned at a first location on the bar **1206** associated with the third workout intensity group (proximate a middle position of the bar **1206**).

At FIG. **12G**, electronic device **600** determines that the user's workout intensity now satisfies one or more workout intensity thresholds associated with the second workout intensity group. Based on this determination, the electronic device **600** initiates a visual indication that the user is moving to a higher workout intensity group. The visual indication can include enlarging the icon **1204**, translating the icon to the right towards the center-right position associated with the second workout intensity group, and presenting a notification **1208**.

At FIG. **12H**, the visual indication that the user is moving to a higher workout intensity group continues, and electronic device **600** displays the icon **1204** continuing to translate to the right along bar **1206**.

At FIG. **12I**, the icon **1204** has reached a center-right position associated with the second workout intensity group. The icon **1204** returns to its smaller size and is presented at the center-right position associated with the second workout intensity group. Furthermore, a new notification **12I** is presented which encourages the user to continue improving their performance to move up to the first workout intensity group.

At FIG. **12J**, electronic device **600** determines that the user's physical activity satisfies one or more workout intensity thresholds associated with the top workout intensity group. Based on this determination, electronic device **600** initiates a visual indication that the user is moving to a

97

higher workout intensity group. The visual indication can once again include enlarging the icon **1204**, translating the icon to the right towards a right-most position associated with the top group, and presenting a notification **1212** (shown in FIG. **12K**).

At FIG. **12L**, the icon **1204** has reached a right-most position associated with the top group of users. The icon **1204** returns to its smaller size and is presented at the right-most position associated with the top tier of users.

At FIG. **12M**, electronic device **600** determines that the user's physical activity no longer satisfies the one or more workout intensity thresholds associated with the top group of users. Based on this determination, electronic device **600** initiates a visual indication that the user is moving to a lower workout intensity group. The visual indication can include translating the icon **1204** to the left towards a center-right position along the bar **1206** associated with the second workout intensity group. In some embodiments, including the depicted embodiment, moving the icon to a position on the bar **1206** associated with a lower group does not result in enlarging the icon **1204** or presenting an additional notification (other than translating the icon **1204**). However, in other embodiments, additional, fewer, or different visual indications can be used.

At FIG. **12N**, the electronic device **600** determines that the user's physical activity does not satisfy the one or more workout intensity thresholds associated with the second group of users. Based on this determination, electronic device **600** continues to translate the icon **1204** to the left to a position on the bar **1206** associated with the third workout intensity group (in this case, a center position on the bar **1206**).

At FIG. **12O**, the electronic device **600** detects that the workout session has concluded. In response to detecting that the workout session has concluded, the electronic device **600** replaces display of the workout session user interface **1030** with a workout summary user interface **1076**. The workout summary user interface **1076** optionally displays calorie information for the workout session (e.g., active calorie information **1080A**, total calorie information **1080B**), heart rate information for the workout session (e.g., average heart rate **1080C**), duration information for the workout session (e.g., total time **1080D**), and information pertaining to the user's performance relative to other users (e.g., workout intensity information **1080E**). The workout intensity information **1080E** demonstrates multiple, e.g., five, different groups or tiers of users based on active calories burned for the workout, with a lowest tier of users that burned fewer than 160 active calories, a second tier of users that burned between 160 and 200 active calories, a third tier of users that burned between 200 and 240 active calories, a fourth tier of users that burned between 240 and 280 active calories, and a fifth tier of users that burned more than 280 active calories. The workout intensity information **1080E** indicates that the user has burned 212 active calories, placing the user in the third tier or group of users.

The workout summary user interface **1076** also includes an option **1080F** to close the workout summary user interface, an option **1080G** to share workout summary information, and an option **1080H** to select a cool down workout.

FIG. **13** is a flow diagram illustrating a method for displaying video content and providing workout information relating to the video content using an electronic device in accordance with some embodiments. Method **1300** is performed at a device (e.g., **100**, **300**, **500**, **600**) with a display (e.g., **602**). Some operations in method **1300** are, optionally,

98

combined, the orders of some operations are, optionally, changed, and some operations are, optionally, omitted.

As described below, method **1300** provides an intuitive way for displaying video content and providing workout information relating to the video content. The method reduces the cognitive burden on a user for displaying video content and providing workout information relating to the video content, thereby creating a more efficient human-machine interface. For battery-operated computing devices, enabling a user to display video content and provide workout information relating to the video content faster and more efficiently conserves power and increases the time between battery charges.

In some embodiments, the electronic device (e.g., **100**, **300**, **500**, **600**, **800**) is a computer system. The computer system is optionally in communication (e.g., wired communication, wireless communication) with a display generation component and with one or more input devices. The display generation component is configured to provide visual output, such as display via a CRT display, display via an LED display, or display via image projection. In some embodiments, the display generation component is integrated with the computer system. In some embodiments, the display generation component is separate from the computer system. The one or more input devices are configured to receive input, such as a touch-sensitive surface receiving user input. In some embodiments, the one or more input devices are integrated with the computer system. In some embodiments, the one or more input devices are separate from the computer system. Thus, the computer system can transmit, via a wired or wireless connection, data (e.g., image data or video data) to an integrated or external display generation component to visually produce the content (e.g., using a display device) and can receive, a wired or wireless connection, input from the one or more input devices.

The electronic device causes concurrent display (**1302**), via a display device, of (e.g., a display device of an electronic device (e.g., display **602** or electronic device **600**), a display device of or in communication with an external device (e.g., television, set top box)): video content (e.g., **1034**, a workout video); and a workout intensity representation (e.g., **1040D**, bar and/or user icon). In some embodiments, the workout intensity representation has a visual characteristic (e.g., size, location/position, color, numerical values, and/or textual characters) based on (e.g., that varies based on) a comparison between a physical activity metric (e.g., active calories, heart rate, distanced traveled, and/or stairs climbed) for a user of the electronic device that corresponds to a first playback position of the video content (e.g., a current playback position of the video content at a first time) and the physical activity metric for a group of users who participated in a workout while watching the video content based on the physical activity of the group of users that corresponds to the first playback position of the video content (**1304**). Causing concurrent display of video content and a workout intensity representation provides the user with feedback about the physical activity metrics and other information recorded by the electronic device. Providing improved feedback to the user enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, the physical activity metric is based on (e.g., corresponds to) data captured by one or more

sensors of an external device (e.g., GPS, accelerometer, gyroscope, and/or heart rate). In some embodiments, the correspondence between the physical activity metric (for the user or group of users) and the first playback position is precise (e.g., second by second accuracy). For example, the physical activity metric is a real-time representation of physical activity at the first playback position. In some embodiments, the correspondence between the physical activity metric (for the user or group of users) and the first playback position is less precise (e.g., 30 second, 1 minute, or 5 minute intervals). For example, the physical activity metric is a representation of physical activity that is updated at predefined intervals. In some embodiments, the workout intensity representation corresponds to a plurality of workout intensity levels (e.g., optionally indicated by tick marks on a bar) based on a physical activity metric. In some embodiments, the workout intensity representation indicates that a user of the electronic device is in a first workout intensity level of the plurality of workout intensity levels. In some embodiments, the physical activity metric for the group of users corresponds to historical data for the group of users (e.g., data captured prior to the start of the current workout). In some embodiments, the physical activity metric for the group of users corresponds to current data for the group of users (e.g., data captured during the current workout). In some embodiments, the physical activity metric for the group of users corresponds to a combination of historical and current data. In some embodiments, the intensity representation includes a bar (e.g., **1206**, horizontal or vertical) and a user icon (e.g., **1204**) displayed at a location relative to the bar. In some embodiments, the user icon corresponds to a user of the electronic device. In some embodiments, the location of the user icon relative to the bar indicates an intensity level of the user of the electronic device relative to the group of users. In some embodiments, the intensity representation includes numerical value(s), textual character(s), or a combination thereof. In some embodiments, the intensity representation does not include textual characters or numerical values. For example, the intensity representation is a pictorial and/or graphical representation without textual characters or numerical values. In some embodiments, the intensity representation is displayed while workout video content is displayed. In some embodiments, the intensity representation is overlaid on the workout video content. In some embodiments, the user icon is displayed on the same axis as the bar. In some embodiments, the user icon changes depending on the type of workout being performed by the user. For example, the user icon can have an animated figure that appears to be running. As another example, the user icon can have an animated figure that appears to be rowing. In some embodiments, a second electronic device (e.g., different from the electronic device) also displays a workout intensity representation, where the workout intensity representation has a visual characteristic based on a comparison between a physical activity metric for a user of the second electronic device and the physical activity metric for a group of users (e.g., including the user of the electronic device). In some embodiments, the physical activity metric for the group of users is updated to include data (e.g., anonymized data) corresponding to the user of the electronic device after the user completes the workout.)

In some embodiments, after the video has advanced from the first playback position to a second playback position (**1308**), the electronic device receives (**1310**) activity data corresponding to the physical activity metric for the user. In

some embodiments, the electronic device also receives activity data corresponding to the physical activity metric for the group of users.

In some embodiments, in response to receiving the activity data (**1312**), the electronic device causes display (**1314**), via the display device, of the workout intensity representation with the visual characteristic of the workout intensity representation changed based on the received activity data and based on (e.g., that varies based on) a comparison between the physical activity metric (e.g., active calories, heart rate, distanced traveled, and/or stairs climbed) for the user of the electronic device that corresponds to the second playback position of the video content and the physical activity metric for a group of users that corresponds to the second playback position of the video content. Causing display of the workout intensity representation with the visual characteristic of the workout intensity representation changed based on the received activity data provides the user with updated feedback about physical activity metrics and other information recorded by the electronic device. Providing improved feedback to the user enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, in response to receiving the activity data: in accordance with a determination that the activity data corresponds to an increased intensity level of the user relative to the group of users, the electronic device moves the user icon in a first direction along the bar of the intensity representation (e.g., as depicted in FIGS. **12F-12I**). In some embodiments, in response to receiving the activity data: in accordance with a determination that the activity data corresponds to a decreased intensity level of the user relative to the group of users, the electronic device moves the user icon in a second direction opposite the first direction along the bar of the intensity representation (e.g., as depicted in FIGS. **12L-12N**). In some embodiments, in accordance with a determination that the activity data does not correspond to a change in intensity level of the user relative to the group of users, the electronic device maintains the location of the user icon along the bar of the intensity representation. In some embodiments, instead of moving the user icon, the electronic device changes numerical value(s) and/or textual character(s) to reflect the change in intensity level, as indicated by the received activity data. For example, a numerical value increases in response to the device receiving activity data corresponding to an increased intensity level. As another example, a numerical value decreases in response to the device receiving activity data corresponding to a decreased intensity level.

In some embodiments, the physical activity metric for the user corresponds to a representation of calories burned by the user (**1306**) (e.g., calories burned during the duration of the video content or a predetermined portion thereof). In some embodiments, the cumulative calories metric applies to a certain type of workout (e.g., workouts where a threshold amount of calories is expected to be burned (e.g., high intensity interval training (HIIT), treadmill, rowing, cycling)).

In some embodiments, the workout intensity representation (e.g., **1040D**, **1204**, **1206**) corresponds to a predetermined number (e.g., 3, 5, 7) of workout intensity levels (e.g., zones) based on the physical activity metric for the group of users, including a first workout intensity level and a second

workout intensity level. In some embodiments, the first workout intensity level indicates that the physical activity metric for the user is within a predetermined subset of a range (e.g., in the pack, a particular intensity level) corresponding to the physical activity metric for the group of users. In some embodiments, the second workout intensity level indicates that the physical activity metric for the user is not within the predetermined subset of the range (e.g., not in the pack (e.g., behind or ahead of the pack), not in the particular intensity level) corresponding to the physical activity metric for the group of users. In some embodiments, the first workout intensity level indicates a higher value for the physical activity metric for the user as compared to the second workout intensity level. In some embodiments, the second workout intensity level indicates a higher value for the physical activity metric for the user as compared to the first workout intensity level. In some embodiments, the “pack” consists of more than one workout intensity level and less than the predetermined number of workout intensity levels.

In some embodiments, in accordance with a determination that the physical activity metric for the user corresponds to an imminent change in workout intensity levels from the first workout intensity level to the second workout intensity level (e.g., the physical activity metric corresponds to being above a threshold value for the first workout intensity level), the electronic device causes display, via the display device, of a prompt (e.g., **1210**, encouragement for the user to continue to move or to increase their movement) for the user to cause a change in workout intensity levels from the first workout intensity level to the second workout intensity level. Causing display of a prompt for the user in accordance with a determination that the physical activity metric for the user corresponds to an imminent change in workout intensity levels provides the user with feedback about the current state of the device (e.g., that the device has detected an imminent change in the user’s workout intensity level). Providing improved feedback to the user enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, in accordance with a determination that the user of the electronic device is at the first workout intensity level, the workout intensity representation with the changed visual characteristic indicates that the user is at the first workout intensity level (e.g., in the pack). In some embodiments, in accordance with a determination that the user of the electronic device is at the second workout intensity level, the workout intensity representation with the changed visual characteristic indicates that the user is at the second workout intensity level (e.g., not in the pack, ahead of the pack, behind the pack).

In some embodiments, in accordance with a determination that the physical activity metric for the user corresponds to an increase by at least a (e.g., predetermined) threshold amount relative to the physical activity metric for the group of users, the electronic device causes display, via the display device, of a first indication (e.g., **1208**, **1212**, text, graphic, and/or pictorial illustration) that the physical activity metric for the user corresponds to an increase relative to the physical activity metric for the group of users, wherein the first indication is different from the workout intensity representation. In some embodiments, the first indication is concurrently displayed with the workout intensity representation

that has the changed visual characteristic. In some embodiments, the first indication is displayed while the workout intensity representation indicates a change from a lower workout intensity level to a higher workout intensity level. Causing display of an indication in accordance with a determination that the physical activity metric for the user corresponds to an increase by at least a threshold amount relative to the physical activity metric for a group of users provides the user with feedback about the current state of the device (e.g., that the device has detected that the physical activity metric for the user corresponds to an increase by a threshold amount relative to the physical activity metric for the group of users). Providing improved feedback to the user enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, in accordance with a determination that the physical activity metric for the user corresponds to a decrease by at least a (e.g., predetermined) threshold amount relative to the physical activity metric for the group of users, the workout intensity representation with the changed visual characteristic is displayed without causing display of a second indication (e.g., text, graphic, and/or pictorial illustration) that the physical activity metric for the user corresponds to a decrease relative to the physical activity metric for the group of users (e.g., as depicted in FIGS. **12L-N**). In some embodiments, in accordance with a determination that the physical activity metric for the user corresponds to a decrease by at least a (e.g., predetermined) threshold amount relative to the physical activity metric for the group of users, the workout intensity representation with the changed visual characteristic is displayed without causing display of any indication that the physical activity metric for the user corresponds to a decrease relative to the physical activity metric for the group of users. In some embodiments, the workout intensity representation indicates a change from a higher workout intensity level to a lower workout intensity level. Causing display of an indication in accordance with a determination that the physical activity metric for the user corresponds to a decrease by at least a threshold amount relative to the physical activity metric for a group of users provides the user with feedback about the current state of the device (e.g., that the device has detected that the physical activity metric for the user corresponds to a decrease by a threshold amount relative to the physical activity metric for the group of users). Providing improved feedback to the user enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, in accordance with a determination that the physical activity metric for the user corresponds to change that is below a (e.g., predetermined) threshold amount for at least a predetermined amount of time, the electronic device visually modifies (e.g., shrinking the size of, minimizing, ceasing to display) the workout intensity representation.

In some embodiments, the user and the group of users share one or more characteristics (e.g., fitness level, demographics such as a range of ages, sex, weight), and the

workout intensity representation is based on the shared one or more characteristics. In some embodiments, one or more users that do not share the one or more characteristics with the user are excluded. In some embodiments, the group of users (e.g., the data representing physical activity of the group of users) is normalized based on the fitness level and/or demographics of the user.

In some embodiments, the video content is initially displayed without causing display of the workout intensity representation, and the workout intensity representation is initially displayed with the video content in accordance with a determination that a predetermined amount of time has elapsed (e.g., as depicted in FIG. 12F).

In some embodiments, the video content is initially displayed with the workout intensity representation, where the workout intensity representation is in an unresolved state (e.g., as depicted in FIGS. 12A-E). In some embodiments, the unresolved state includes changing the displayed position of a user icon (representing the user) from a first position corresponding to a first workout intensity level to a second position corresponding to a second workout intensity level. In some embodiments, the electronic device repeatedly changes/cycles the displayed position of the user icon in a predefined manner. In some embodiments, in accordance with a determination that a sufficient amount of activity data for the user has been received (e.g. obtained), the electronic device causes display of the user icon at a particular position corresponding to a workout intensity level without repeatedly changing/cycling the displayed position of the user icon in the predefined manner.

Note that details of the processes described above with respect to method 1300 (e.g., FIG. 13) are also applicable in an analogous manner to the methods described above. For example, method 1300 optionally includes one or more of the characteristics of the various methods described above with reference to method 1100. For example, the workout intensity representation can be included in the physical activity metrics described above with reference to method 1100. For brevity, these details are not repeated below.

FIGS. 14A-14R illustrate exemplary user interfaces for coordinating display of workout content among multiple devices, in accordance with some embodiments. The user interfaces in these figures are used to illustrate the processes described below, including the processes in FIG. 15.

FIG. 14A depicts electronic device 600, which is a smartphone with display 602. Display 602 of electronic device 600 includes a touch-sensitive surface on which electronic device 600 can detect user gestures (e.g., tap, swipe, and/or drag). In some embodiments, electronic device 600 includes one or more features of electronic device 100, 300, and/or 500.

FIG. 14A also depicts electronic device 800, which is a smartwatch with display 801. In some embodiments, electronic device 800 is in communication with electronic device 600 (e.g., electronic device 800 is wirelessly paired with electronic device 600). In some embodiments, electronic device 800 communicates (e.g., transmits/receives data) with external devices via electronic device 600. In some embodiments, electronic device 800 transmits data representing physical activity of the user to electronic device 600, and vice-versa. Display 801 of electronic device 800 includes a touch-sensitive surface on which electronic device 800 can detect user gestures (e.g., tap, swipe, drag). In some embodiments, electronic device 800 includes one or more features of electronic device 100, 300, and/or 500.

FIG. 14A further depicts electronic device 1400, which is a television with display 1401. In some embodiments,

electronic device 1400 is in communication with, or is capable of being in communication with electronic device 600. For example, electronic device 600 optionally transmits data representing displayed content to electronic device 1400. In some embodiments, electronic device 1400 is a set top box or a streaming device instead of a television. In some embodiments, electronic device 1400 displays content via display 1401, which is integrated as part of the television. In some embodiments, electronic device 1400 displays content via a display that is external to electronic device 1400. In some embodiments, electronic device 1400 is paired with a physical remote that can be used to operate electronic device 1400. In some embodiments, each of the devices (e.g., 600, 800, 1400) are signed into the same account (e.g., an account associated with a user that enables the user to access features/functions that are otherwise limited without the account). At FIG. 14A, electronic device 600 displays detail user interface 620, as discussed above with respect to FIG. 6D. Electronic device 800 displays activity user interface 1002, as discussed above with respect to FIG. 10A. Electronic device 1400 is not yet displaying workout (e.g., content associated with the workout represented in detail user interface 620). While displaying detail user interface 620, electronic device 600 detects input 1406 at a location corresponding to option 1404.

At FIG. 14B, in response to detecting input 1406, electronic device 600 initiates a process for playing workout content, including replacing display of detail user interface 620 with workout start user interface 1016, as discussed above with respect to FIG. 10B. Workout start user interface 1016 includes exit option 1412 which, when selected, causes electronic device 600 to return to displaying a previously displayed user interface. Additionally, in response to detecting input, electronic device 600 causes electronic device 800 to replace display of activity user interface 1002 with workout start user interface 1018. Workout start user interface 1016 includes play button 1020 and workout start user interface 1018 includes play button 1022, as discussed above with respect to FIG. 10B. Electronic device 1400 is still not displaying workout content. While displaying workout start user interface 1016, electronic device 600 detects input 1410 at a location corresponding to option 1408.

At FIG. 14C, in response to detecting input 1410, electronic device 600 initiates a process for playing workout content at a device other than electronic device 600, such as electronic device 1400, including displaying options 1416A-1416B for configuring which device displays the workout content. As shown in FIG. 14C, electronic device 600 provides device options for the user to select. As indicated by the check mark, the phone (e.g., 600) is currently configured to display the workout content. Option 1416B provides a user with the option to configure the living room TV (e.g., 1400) to display the workout content instead of the phone. In response to detecting input 1410, electronic device 600 de-emphasizes workout start user interface 1016. In response to detecting input 1410, electronic device 600 causes electronic device 600 to de-emphasize workout start user interface 1018 (e.g., causing play button 1022 to not be selectable). Electronic device 1400 is still not displaying workout content. While displaying options 1416A-1416B, electronic device 600 detects input 1414 at a location corresponding to 1416B.

At FIG. 14D, in response to detecting input 1414, electronic device 600 initiates a process for displaying workout content at electronic device 1400 (e.g., corresponding to option 1416B). In accordance with a determination that electronic device 1400 has been successfully configured to

105

display the workout content, electronic device 600 displays a visual indication next to option 1416B (e.g., check mark) to indicate that electronic device 1400 has been successfully configured. Electronic device 1400 is still not displaying workout content.

At FIG. 14E, in response to detecting input 1414 (e.g., and after displaying the visual indication), electronic device 600 replaces display of options 1416A-1416B (e.g., and deemphasized workout start user interface 1016) with status user interface 1418. Status user interface 1418 includes representation 1420, which indicates that electronic device 1400 is configured to display the workout content. Status user interface 1418 includes prompt 1422, which prompts the user to start the workout using electronic device 800 or electronic device 1400. Status user interface 1418 also includes play/pause button 1424 and volume controls 1426.

Further in response to detecting input 1414, electronic device 600 causes electronic device 1400 to display workout start user interface 1428. Workout start user interface includes prompt 1430, which prompts the user to start the workout using electronic device 800 or electronic device 1400. Workout start user interface 1428 includes option 1432 which, when selected, causes electronic device 1400 to display workout content.

Further in response to detecting input 1414, electronic device 600 causes electronic device 800 to cease de-emphasizing workout start user interface 1018. As a result, play button 1022 is selectable. While displaying workout start user interface 1018, electronic device 800 detects input 1434 at a location corresponding to play button 1022. In some embodiments, electronic device 600 detects, via input 1434 at electronic device 800, a request to start playback of the workout content.

At FIG. 14F, in response to input 1434, electronic device 600 causes electronic device 1400 to display workout session user interface 1030, including video content 1034. Workout session user interface 1030 includes the elements discussed above with respect to FIG. 10D. In some embodiments, in response to detecting input 1434, electronic device 800 transmits first data to electronic device 600 indicating that a request to start playback of the workout content has been made. In some embodiments, in response to receiving the first data from electronic device 800, electronic device 600 transmits second data indicating that a request to start playback of the workout content has been made to electronic device 1400. In some embodiments, in response to receiving the second data, electronic device 1400 displays activity session user interface 1030 with video content 1034. In some embodiments, instead of electronic device 800 transmitting the data to electronic device 600, electronic device 800 transmits the data directly to electronic device 1400 without using electronic device 600 as an intermediary.

Further in response to input 1434, electronic device 800 replaces display of workout start user interface 1018 with display of workout metrics user interface 1032. Workout metrics user interface 1032 includes the elements discussed above with respect to FIG. 10D. In some embodiments, in response to input 1434, electronic device 800 begins recording (e.g., capturing) data corresponding to physical activity of the user. In some embodiments, electronic device 800 records the data via one or more sensors (e.g., GPS, accelerometer, gyroscope, and/or heart rate). Prior to input 1434, the one or more sensors of electronic device 800 are disabled. The one or more sensors are used to capture physical activity of the user. In response to detecting input 1434, electronic device 800 causes the one or more sensors to be

106

enabled so as to improve accurate measurements of the physical activity of the user during the workout.

Further in response to input 1434, electronic device 600 updates status user interface 1418, including replacing prompt 1422 with indication 1435. Indication 1435 indicates that electronic device 1400 is currently displaying the workout content. Additionally, in response to input 1434, electronic device 600 de-emphasizes option 1408 (e.g., causes option 1408 to not be selectable). While displaying status user interface 1418, electronic device 600 detects input 1436 on display 602.

At FIG. 14G, in response to detecting input 1436, electronic device 600 displays a set of playback controls overlaid on status user interface 1418, including play/pause button 1046A, playback progress indicator 1046B, virtual remote 1438, and edit metrics icon 1046E. While displaying the set of playback controls, electronic device 600 detects input 1440 at a location corresponding to play/pause button 1046A.

At FIG. 14H, in response to detecting input 1440, electronic device 600 causes electronic device 1400 to replace display of workout session user interface 1030 with display of paused user interface 1442. Further in response to detecting input 1440, electronic device 600 causes electronic device 800 to cease recording (e.g., capturing) data corresponding to physical activity of the user. As a result, electronic device 800 updates workout metrics user interface 1032 to indicate that electronic device 800 is not recording the data. Paused user interface 1442 includes option 1444A that, when selected, ends the current workout session (e.g., displays workout summary user interface 1452 of FIG. 14K). Paused user interface 1442 also includes option 1444B that, when selected, resumes the current workout session (e.g., returns to displaying workout session user interface 1030). In some embodiments, electronic device 1400 detects selection of one of the options (e.g., 1444A-1444B) via an input made at a physical remote paired with electronic device 1400. In some embodiments, electronic device 1400 detects selection via an input made at electronic device 600, as further discussed below. While displaying the set of playback controls overlaid on status user interface 1418, electronic device 600 detects input 1439 at a location corresponding to virtual remote 1438.

At FIG. 14I, in response to detecting input 1439, electronic device 600 replaces display of status user interface 1418 with display of virtual remote user interface 1446. Virtual remote user interface 1446 includes skip back button 1448A, menu button 1448B, skip forward button 1448C, play/pause button 1448D, screen button 1448E, virtual assistant button 1448F, and virtual trackpad 1448G. While displaying virtual remote user interface 1446, electronic device 600 detects input 1450 at a location corresponding to play/pause button 1448D.

At FIG. 14J, in response to detecting input 1450, electronic device 600 returns to displaying status user interface 1418. Further in response to detecting input 1450, electronic device 600 causes electronic device 1400 to resume the workout session (e.g., return to displaying workout session user interface 1030). Further in response to detecting input 1450, electronic device 600 causes electronic device 800 to resume recording data representing physical activity of the user.

At FIG. 14K, the workout session has completed (e.g., playback of video content 1034 has ended). In accordance with a determination that the workout session has completed, electronic device 800 replaces display of workout metrics user interface 1032 with summary user interface

107

1456, which includes a set of metrics associated with the workout session. In accordance with a determination that the workout session has completed, electronic device 800 ceases recording data corresponding to physical activity of the user.

In accordance with a determination that the workout session has completed, electronic device 1400 replaces display of workout session user interface 1030 with workout summary user interface 1452. Workout summary user interface 1452 includes option 1454A that, when selected, causes electronic device 1400 to cease displaying workout content (e.g., and return primary control to electronic device 600). Workout summary user interface 1452 includes option 1454B that, when selected, causes the workout corresponding to video content 1034 to be added to the user's collection of workouts. While displaying workout summary user interface 1452, electronic device 1400 detects selection of option 1454A (e.g., via an input made at a physical remote paired with electronic device, or via an input made using virtual trackpad 1448G).

At FIG. 14L, in response to selection of option 1454A, electronic device 1400 ceases displaying workout content. In response to selection of option 1454A, electronic device 600 replaces display of status user interface 1418 with display of detail user interface 620. In response to selection of option 1454A, electronic device 800 replaces display of summary user interface 1456 with activity user interface 1002. The plurality of concentric physical activity rings 1004 have been updated in activity user interface 1002 to indicate an increase in activity as a result of the recently completed workout. For example, move ring 1006A and exercise 1006B have been visually modified to indicate an increase in number of calories burned and an increase in number of minutes exercised, respectively.

FIG. 14M depicts a scenario in which electronic exercise equipment, such as a treadmill, a stationary bike, a rowing machine, or a stair machine, can optionally be connected to (e.g., paired to) electronic devices 600, 800, and/or 1400. At FIG. 14M, similar to FIG. 14E, electronic device 600 displays a status user interface 1418, electronic device 1400 displays a workout start user interface 1428, and electronic device 800 displays a workout start user interface 1018. However, in FIG. 14M, workout start user interface 1428 on electronic device 1400 includes a prompt 1460. Prompt 1460 can indicate to the user that the selected workout is compatible with connection to electronic exercise equipment, if such exercise equipment is available (in this case, a treadmill). In the depicted embodiments, a user can optionally begin his or her workout without connecting to any exercise equipment (e.g., by selecting option 1432 or option 1022). At FIG. 14M, electronic device 600, electronic device 800, and/or electronic device 1400 determines that electronic device 800 satisfies proximity criteria relative to a compatible exercise equipment device (e.g., based on signal strength, based on an input at the exercise equipment device, and/or other proximity indications).

At FIG. 14N, in response to the determination that electronic device 800 satisfies proximity criteria relative to a compatible exercise equipment device, electronic device 800 replaces display (e.g., electronic device 600 causes electronic device 800 to replace display) of workout start user interface 1018 with pairing user interface 1462, and electronic device 600 replaces display of status user interface 1418 with status user interface 1466. Pairing user interface 1462 includes an option 1464A that is selectable by a user to proceed with pairing electronic device 800 with a compatible exercise equipment device. At FIG. 14N, while

108

displaying pairing user interface 1462, electronic device 800 detects input 1464B at a location corresponding to option 1464A.

At FIG. 14O, in response to input 1464B, electronic device 800 is paired with a compatible exercise equipment device 1470 (e.g., a treadmill). In response to a determination that electronic device 800 is successfully paired with exercise equipment device 1470, electronic device 600 replaces display of status user interface 1466 with status user interface 1468, electronic device 800 replaces display (e.g., electronic device 600 causes electronic device 800 to replace display) of pairing user interface 1462 with status user interface 1468B, and electronic device 1400 replaces display (e.g., electronic device 600 and/or 800 causes electronic device 1400 to replace display) of workout start user interface 1428 with status user interface 1468C. Each of status user interface 1468A, 1468B, and 1468C instruct the user to begin the workout on the paired exercise equipment device 1470. At FIG. 14O, while electronic devices 600, 800, and 1400 display status user interfaces 1468A, 1468B, 1468C, respectively, paired exercise equipment device 1470 detects a user input 1472B at a "START" option 1472A, indicating user intent to begin the workout.

At FIG. 14P, in response to input 1472B (e.g., in response to a determination that a user input has been received at the paired exercise equipment device 1470 indicative of user intent to begin the workout), electronic device 600 replaces display of status user interface 1468A with status user interface 1418, electronic device 800 replaces display (e.g., electronic device 600 causes electronic device 800 to replace display) of status user interface 1468B with workout metrics user interface 1032, and electronic device 1400 replaces display (e.g., electronic device 600 and/or 800 causes electronic device 1400 to replace display) of status user interface 1468C with workout session user interface 1030, each of which have been described in greater detail above (e.g., with reference to FIG. 14F).

At FIG. 14Q, while electronic device 1400 is displaying workout session user interface 1030, a user input 1474A that includes a downward motion is received at a remote control device 1474 that is paired to electronic device 1400.

At FIG. 14R, in response to input 1474A, electronic device 1400 displays display settings user interface 1476. A user can navigate the display settings user interface 1476 and select various selectable options to control what information is displayed in the workout session user interface 1030. For example, a user can choose to display or not display physical activity metrics (via options 1478A and 1478B), turn off time display (1478C), display elapsed time (1478D), display remaining time (1478E), turn off display of the burn bar (1478F), or turn on display of the burn bar (1478G). Electronic device 1400 can update display of the workout session user interface 1030 based on user inputs and selections in display settings user interface 1476.

FIG. 15 is a flow diagram illustrating a method for coordinating display of workout content among multiple devices, in accordance with some embodiments. Method 1500 is performed at an electronic device (e.g., 100, 300, 500, 600) with a display (e.g., 602), wherein the electronic device is in communication with a first external device (e.g., 1400, television, laptop, tablet, set top box, streaming device) and a second external device (e.g., 800, smartwatch, fitness tracking device, wearable electronic device). Some operations in method 1500 are, optionally, combined, the orders of some operations are, optionally, changed, and some operations are, optionally, omitted.

As described below, method **1500** provides an intuitive way for coordinating display of workout content among multiple devices. The method reduces the cognitive burden on a user for coordinating display of workout content among multiple devices, thereby creating a more efficient human-machine interface. For battery-operated computing devices, enabling a user to coordinate display of workout content among multiple devices faster and more efficiently conserves power and increases the time between battery charges.

In some embodiments, the electronic device (e.g., **100**, **300**, **500**, **600**, **800**) is a computer system. The computer system is optionally in communication (e.g., wired communication, wireless communication) with a display generation component and with one or more input devices. The display generation component is configured to provide visual output, such as display via a CRT display, display via an LED display, or display via image projection. In some embodiments, the display generation component is integrated with the computer system. In some embodiments, the display generation component is separate from the computer system. The one or more input devices are configured to receive input, such as a touch-sensitive surface receiving user input. In some embodiments, the one or more input devices are integrated with the computer system. In some embodiments, the one or more input devices are separate from the computer system. Thus, the computer system can transmit, via a wired or wireless connection, data (e.g., image data or video data) to an integrated or external display generation component to visually produce the content (e.g., using a display device) and can receive, via a wired or wireless connection, input from the one or more input devices.

The electronic device (e.g., **600**) displays, on the display (e.g., **602**) of the electronic device, a user interface (e.g., **1016**) corresponding to video content (e.g., **1034**) including a first selectable user interface object (e.g., **1408**) for enabling display of an activity session user interface (e.g., **1030**) associated with the video content on a display device (e.g., **1402**) that is in communication with the first external device (e.g., a display that is part of a device (e.g., television, laptop, tablet), a display that is external to a device (e.g., set top box, streaming device)). In some embodiments, the user interface corresponding to video content is a detail page (e.g., **620**) for a particular workout. In some embodiments, the user interface includes one or more of: a representation (e.g., image) of the video content, duration of video content, music genre for corresponding audio content, required equipment, workout description, audio playlist, and an option for adding the workout to a library. In some embodiments, the user interface includes a selectable user interface object for starting the activity session (e.g., displaying workout content on the display of the electronic device, e.g., without displaying workout content on the display device that is in communication with the first external device).

The electronic device (e.g., **600**) detects a first sequence of one or more user inputs (e.g., **1410**, **1414**) including selection of the first selectable user interface object.

In response to detecting the first sequence of one or more user inputs (e.g., **1410**, **1414**) including selection of the first selectable user interface object: the electronic device (e.g., **600**) causes the display device (e.g., **1402**) that is in communication with the first external device (e.g., **1400**) to display (e.g., by transmitting, to the first external device, a command or instruction) a first graphical user interface (e.g., **1428**) that is associated with the activity session.

While the display device (e.g., **1402**) is displaying the first graphical user interface (e.g., **1428**) that is associated with

the activity session, a display device (e.g., **801**) that is in communication with the second external device (e.g., a display that is part of a device (e.g., smartwatch, fitness tracking device, wearable electronic device), a display that is external to the device) displays (e.g., by transmitting, to the first external device, a command or instruction) a second graphical user interface (e.g., **1018**) that is associated with starting the activity session and is different from the first graphical user interface, wherein a selection input (e.g., **1434**) directed to a portion (e.g., **1022**) of the second graphical user interface (e.g., **1018**) causes the display device that is in communication with the first external device (e.g., **1402**) to display an activity session user interface (e.g., **1030**) associated with the video content.

In some embodiments, the portion of the second graphical user interface (e.g., **1018**) corresponds to a second selectable user interface object (e.g., **1022**) that, when selected, causes the display device (e.g., **1402**) that is in communication with the first external device to display the activity session user interface (e.g., **1030**) associated with the video content. In some embodiments, selection of the second selectable user interface object causes the second external device to output haptic feedback.

In some embodiments, in accordance with a determination that a third external device (e.g., **1470**) (e.g., an exercise device (e.g., treadmill, stair machine, rowing machine, stationary bike, elliptical, etc.)) is available to connect to (e.g., be paired to) the second external device (e.g., **800**) (e.g., smartwatch, fitness tracking device, wearable electronic device) (e.g., directly connect, indirectly connect via another device (e.g., via the electronic device)) (e.g., in accordance with a determination that the third external device satisfies proximity criteria (e.g., is within a threshold distance and/or proximity (e.g., based on signal strength)) with respect to the second external device), the display device (e.g., **801**) that is in communication with the second external device (e.g., **800**) displays an indication (e.g., **1462**) that the third external device is available to connect to the second external device. In some embodiments, the display device that is in communication with the second external device displays a selectable user interface object that, when selected, initiates a process for connecting the second external device to the third external device. In some embodiments, connecting the second external device to the third external device allows for transmission of workout information from the third external device to the second external device and/or transmission of workout information from the second external device to the third external device. Displaying a selectable user interface object in accordance with a determination that a third external device is available to connect to the second external device provides the user with feedback about the current state of the device (e.g., that a third external device is available to connect to the second external device). Providing improved feedback to the user enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, in response to a determination that a third external device (e.g., **1470**) (e.g., an exercise device (e.g., treadmill, stair machine, rowing machine, stationary bike, elliptical, etc.)) is available to connect to (e.g., be paired to) the second external device (e.g., **800**) (e.g., smartwatch, fitness tracking device, wearable electronic device) (e.g., directly connect, indirectly connect via another

111

device (e.g., via the electronic device)) (e.g., in accordance with a determination that the third external device satisfies proximity criteria (e.g., is within a threshold distance and/or proximity (e.g., based on signal strength)) with respect to the second external device), the display device (e.g., 801) that is in communication with the second external device (e.g., 800) ceases to display the second selectable user interface object (e.g., 1022, 1464A) and displays a visual prompt (e.g., 1468B) (e.g., text, graphics, pictorial illustration) to start the activity session using the third external device. Displaying a visual prompt in accordance with a determination that a third external device is connected to the second external device provides the user with feedback about the current state of the device (e.g., that a third external device is connected to the second external device). Providing improved feedback to the user enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, in response to a determination that a user input (e.g., 1472B) has been received at the third external device (e.g., 1470) (e.g., in response to a determination that a user input corresponding to a request and/or command to begin a workout has been received at the third external device): the display device (e.g., 1402) that is in communication with the first external device (e.g., 1400) displays the activity session user interface associated with the video content (e.g., 1030). Displaying an activity session user interface in response to a determination that a user input has been received at the third external device provides the user with feedback about the current state of the device (e.g., that a particular user input has been received at the third external device). Providing improved feedback to the user enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, the electronic device (e.g., 600) displays, on the display (e.g., 602) of the electronic device, a visual prompt (e.g., 1422, text, graphics, and/or pictorial illustration) to start the activity session using the second external device. In some embodiments, displaying the visual prompt occurs in response to detecting the first sequence of one or more user inputs. In some embodiments, displaying the visual prompt occurs prior to detecting the first sequence of one or more user inputs. Providing a prompt to start the activity session using the second external device provides the user with feedback about the current state of the devices and provides feedback to the user indicating what is required to start the activity session. Providing improved feedback to the user enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, the visual prompt (e.g., 1422) includes a prompt to start the activity session using the first external device (e.g., 1400).

112

In some embodiments, the display (e.g., 602) of the electronic device (e.g., 600) is configured to display content at a first size. In some embodiments, the display device (e.g., 1402) that is in communication with the first external device (e.g., 1400) is configured to display content at a second size that is larger than the first size.

In some embodiments, the first graphical user interface (e.g., 1428) that is associated with the activity session includes a visual prompt (e.g., 1430, text, graphics, and/or pictorial illustration) to start the activity session using the first external device (e.g., 1400) or the second external device (e.g., 800). Providing a prompt to start the activity session using the first external device provides the user with feedback about the current state of the devices and provides feedback to the user indicating what is required to start the activity session. Providing improved feedback to the user enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, in response to detecting the first sequence of one or more user inputs (e.g., 1410, 1414), the electronic device (e.g., 600) displays, on the display (e.g., 602) of the electronic device, a visual indication (e.g., 1420, text, graphics, pictorial illustration, and/or visual representation (e.g., of the first external device)) that the display device (e.g., 1402) that is in communication with the first external device (e.g., 1400) is configured to display the activity session user interface (e.g., 1030) associated with the video content.

In some embodiments, a selection input directed to a portion (e.g., 1432) of the first graphical user interface (e.g., 1428) that is associated with the activity session causes the display device that is in communication with the first external device to display the activity session user interface (e.g., 1030) associated with the video content.

In some embodiments, the display device (e.g., 801) that is in communication with the second external device displays one or more physical activity metrics (e.g., 1042A-1042C, based on data captured via one or more sensors of the second external device) based on physical activity of a user during the activity session (e.g., and ceases to display the second graphical user interface (e.g., 1018)) while the display device (e.g., 1402) that is in communication with the first external device displays the activity session user interface (e.g., 1030) associated with the video content.

In some embodiments, the display device (e.g., 801) that is in communication with the second external device displays the one or more physical activity metrics (e.g., 1042A-1042C) for the user of the second external device in response to a determination that the activity session has started (e.g., as a result of selection input (e.g., 1434) at the second external device or at the first external device).

In some embodiments, while the display device (e.g., 1402) that is in communication with the first external device (e.g., 1400) displays the activity session user interface (e.g., 1030) associated with the video content, the electronic device (e.g., 600) displays, on the display (e.g., 602) of the electronic device, a visual indication (e.g., 1435, 1420, text, graphics, and/or pictorial illustration) that the display device (e.g., 1402) that is in communication with the first external device (e.g., 1400) is displaying the activity session user interface (e.g., 1030) associated with the video content. Displaying a visual indication that the display device in

communication with the first external device is displaying the activity session user interface provides the user with feedback as to the status of which device is displaying the workout content. Providing improved feedback to the user enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, while the display device (e.g., **1402**) that is in communication with the first external device (e.g., **1400**) displays the activity session user interface (e.g., **1030**) associated with the video content, a second sequence of one or more user inputs at a physical remote device associated with (e.g., paired with) the first external device (e.g., **1400**) causes the display device (e.g., **1402**) that is in communication with the first external device to cease display of the activity session user interface (e.g., **1030**) associated with the video content.

In some embodiments, a third sequence of one or more user inputs at a physical remote device associated with (e.g., paired with) the first external device (e.g., **1400**) causes the display device (e.g., **1402**) that is in communication with the first external device to display the activity session user interface (e.g., **1030**) associated with the video content.

In some embodiments, while the display device (e.g., **1402**) that is in communication with the first external device (e.g., **1400**) displays the activity session user interface (e.g., **1030**) associated with the video content, the electronic device (e.g., **600**) displays, on the display (e.g., **602**) of the electronic device, a selectable user interface object (e.g., **1046A**, **1412**) that, when selected, causes the display device that is in communication with the first external device to cease display of the activity session user interface (e.g., **1030**) associated with the video content.

In some embodiments, while the display device (e.g., **1402**) that is in communication with the first external device (e.g., **1400**) displays the activity session user interface (e.g., **1030**) associated with the video content, the electronic device (e.g., **600**) displays, on the display (e.g., **602**) of the electronic device, a selectable user interface object (e.g., **1438**) that, when selected, causes display of a set of options (e.g., **1448A-1448G**) for controlling display of the activity session user interface (e.g., **1030**) associated with the video content.

In some embodiments, the set of options includes a first option (e.g., **1448B**) that, when selected, causes the display device (e.g., **1402**) that is in communication with the first external device to cease display of the activity session user interface (e.g., **1030**) associated with the video content. In some embodiments, while the activity session is paused, selection of the first option causes the first external device to resume the activity session.

In some embodiments, the set of options includes a second option (e.g., **1448B**) that, when selected via an input that includes contact with the display for at least a predetermined amount of time, causes the display device (e.g., **1402**) that is in communication with the first external device to cease display of the activity session user interface (e.g., **1030**) associated with the video content and to display one or more application icons (e.g., on a homescreen) for launching a respective application.

In some embodiments, the set of options includes a third option (e.g., **1448E**) that, when selected, causes the display device (e.g., **1402**) that is in communication with the first

external device to cease display of the activity session user interface (e.g., **1030**) associated with the video content and to display one or more application icons (e.g., on a homescreen) for launching a respective application.

In some embodiments, the set of options includes a fourth option (e.g., **1448E**) that, when selected via an input that includes contact with the display for at least a predetermined amount of time, causes the first external device (e.g., **1400**) to overlay, on the activity session user interface (e.g., **1030**), a plurality of options, including an option for turning off the first external device.

In some embodiments, the set of options includes a fifth option (e.g., **1448D**) that, when selected, causes: the display device (e.g., **1402**) that is in communication with the first external device (e.g., **1400**) to cease display of the activity session user interface (e.g., **1030**) associated with the video content; and the second external device (e.g., **800**) to cease updating the display of one or more physical activity metrics (e.g., **1042A-1042C**, based on data captured via one or more sensors of the second external device) for a user of the second external device.

In some embodiments, a physical remote device is paired with the first external device (e.g., **1400**, television, laptop, tablet, set top box, streaming device). In some embodiments, the physical remote device has one or more of the features discussed above with respect to the set of options (e.g., **1448A-1448G**) for controlling display of the activity session user interface associated with the video content. In some embodiments, the physical remote device has a physical button corresponding to each of the options in the set of options. For example, analogous to the first option (e.g., **1448B**), the physical remote device has a first physical button that, when pressed, causes the first external device (e.g., **1400**) to cease display of the activity session user interface (e.g., **1030**) associated with the video content. As another example, analogous to the fourth option (e.g., **1448E**), the physical remote device has a second physical button that, when pressed for at least a predetermined amount of time, causes the first external device (e.g., **1400**) to overlay, on the activity session user interface (e.g., **1030**), a plurality of options, including an option for turning off the first external device.

In some embodiments, after (e.g. in response to) the end of the activity session has been reached (e.g., video content **1034** has ended), the display device (e.g., **1402**) that is in communication with the first external device (e.g., **1400**) displays: one or more aggregate representations (e.g., active calories, total calories, total time, average heart rate, distance, average pace, workout intensity representation) of physical activity metrics (e.g., as shown in workout summary user interface **1452**) that are based on physical activity of a user during the activity session, and a selectable user interface object (e.g., **1454B**) that, when selected, causes a workout corresponding to the video content to be added to a collection of workouts for the user. In some embodiments, instead of the display device that is in communication with the first external device, the electronic device displays, on the display, the one or more aggregate representations and the selectable user interface object.

In some embodiments, after (e.g. in response to) the end of the activity session has been reached (e.g., video content **1034** has ended), the display device (e.g., **1402**) that is in communication with the first external device (e.g., **1400**) displays a selectable user interface object (e.g., **1454A**) that, when selected, causes: the display device (e.g., **1402**) that is in communication with the first external device to return to displaying a graphical user interface that was displayed prior

115

to the first graphical user interface (e.g., **1428**), and the electronic device (e.g., **600**) to return to displaying a graphical user interface that was displayed prior to the user interface (e.g., **1016**) corresponding to the video content.

In some embodiments, after (e.g. in response to) the end of the activity session has been reached (e.g., video content **1034** has ended), the display device (e.g., **1402**) that is in communication with the first external device (e.g., **1400**): in accordance with a determination that the first external device satisfies trust criteria (e.g., the first external device has been paired with the electronic device previously, confirmed selection to save the first external device as a trusted device), displays an option (e.g., selectable user interface object, affordance) for configuring the displayed content (e.g., restarting the video content, selecting new content to be displayed); and in accordance with a determination that the first external device does not satisfy the trust criteria, forgoes displaying the option for configuring the displayed content. Forgoing display of the option for configuring the displayed content when trust criteria are not satisfied provides security and can prevent unauthorized users from initiating sensitive operations. Providing improved security enhances the operability of the device and makes the user-device interface more efficient and/or secure (e.g., by restricting unauthorized access) which, additionally, reduces power usage and improves battery life of the device by limiting the performance of restricted operations.

In some embodiments, while the display device (e.g., **1402**) that is in communication with the first external device (e.g., **1400**) displays the activity session user interface (e.g., **1030**) associated with the video content, the electronic device (e.g., **600**) displays, on the display of the electronic device, a selectable user interface object (e.g., **1046E** as discussed with respect to FIGS. **10E-10F**) that, when selected, causes display of one or more options for configuring the display of physical activity metrics that are based on physical activity of a user during the activity session.

In some embodiments, the electronic device (e.g., **600**) detects a request to start the activity session (e.g., via input (e.g., **1434**) at the second graphical user interface (e.g., **1018**) or at the electronic device (e.g., via input at play button **1020**)). In some embodiments, in response to detecting the request to start the activity session, the electronic device causes: the display device (e.g., **1402**) that is in communication with the first external device (e.g., **1400**) to display a countdown animation (e.g., such as the countdown animation in countdown user interface **1028A** as discussed with respect to FIG. **10C**) prior to display of the activity session user interface (e.g., **1030**), and the display device (e.g., **801**) that is in communication with the second external device (e.g., **800**) to display the countdown animation prior to display of one or more physical activity metrics (e.g., **1042A-1042C**) that are based on physical activity of a user during the activity session. In some embodiments, in response to detecting the request to start the activity session, the electronic device displays the countdown animation (e.g., in addition to the countdown animations on the first external device and/or the second external device).

In some embodiments, while the display device (e.g., **1402**) that is in communication with the first external device (e.g., **1400**) displays the activity session user interface (e.g., **1030**) associated with the video content, the electronic device detects a request to pause the activity session (e.g., input **1440** at play/pause button **1046A**, input **1450** at play/pause button **1448D**). In some embodiments, in response to detecting the request to pause the activity session, the electronic device (e.g., **600**) causes the second

116

external device (e.g., **800**) to cease recording data based on physical activity of the user during the activity session (e.g., via one or more sensors of the second external device). In some embodiments, the background collection of activity data continues even after the workout stops. In some embodiments, in response to detecting the request to pause the activity session, the electronic device does not cause the second external device to cease recording data based on physical activity of the user. Automatically causing the recording of physical activity metrics to cease when the activity session is paused improves battery life of the device, as one or more sensors for recording physical activity metrics are disabled. Disabling the one or more sensors when a set of conditions are met enhances the operability of the device which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, in response to detection of a user input (e.g., **1474A**) (in some embodiments, detection of a user input at and/or by the first external device) (in some embodiments, a user input comprising a downward swipe gesture) (in some embodiments, the user input is received at a physical remote device associated with (e.g., paired with) the first external device), the display device (e.g., **1402**) that is in communication with the first external device (e.g., **1400**) displays, while displaying the activity session user interface (e.g., **1030**) associated with the video content, a selectable user interface object (e.g., "METRICS" in FIG. **14R**) that, when selected, causes display of one or more options (e.g., **1478A-1478G**) for configuring the display of physical activity metrics that are based on physical activity of the user during the activity session. Displaying a selectable user interface object in response to detection of a user input provides the user with feedback about the current state of the device (e.g., that a particular user input has been received). Providing improved feedback to the user enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

FIGS. **16A-16R** illustrate exemplary user interfaces for displaying workout information, in accordance with some embodiments. The user interfaces in these figures are used to illustrate the processes described below, including the processes in FIGS. **17A-17B**.

FIGS. **16A-16R** illustrate exemplary devices and user interfaces. At FIG. **16A**, computer system **1600** (e.g., device **100**, **300**, **500**) is displaying workout user interface **1606** on display **1601** (e.g., a television). In some embodiments, display **1601** is an integrated part of computer system **1600**. In some embodiments, computer system **1600** is a separate digital media player that is in communication (e.g., wireless, wired) with display **1601** (e.g., as depicted in FIG. **18A**).

FIG. **16A** also illustrates remote control **1602**, which is configured to transmit data (e.g., via RF communication, via Bluetooth, via infrared) to computer system **1600** based on user input that is detected at remote control **1602**. Remote control **1602** includes a selection region **1604a**, which includes a touch-sensitive surface for detecting tap, press, and swipe gestures, a menu button **1604b**, a television button **1604c**, a microphone button **1604d**, a play/pause button **1604e**, and volume control buttons **1604f**.

At FIG. **16A**, computer system **1600** causes display **1601** to display a workout user interface **1606**. Workout user

117

interface **1606** includes workout suggestions **1608a-1608d** for a user. In some embodiments, workout suggestions **1608a-1608d** are based on one or more workouts that have been completed by the user. For example, workout suggestion **1608a** represents a workout that shares one or more characteristics with a subset of workouts completed by the user (e.g., the most recently completed workout). In the depicted scenario, the user most recently completed a core workout with trainer Amy. Accordingly, computer system **1600** provides workout suggestion **1608a**, as it represents a workout that has a shared characteristic with the user's most recently completed workout (e.g., workout suggestion **1608a** has the same type of workout (core) as the user's most recently completed workout, workout suggestion **1608a** has the same trainer (Amy) as the user's most recently completed workout). In FIG. **16A**, a focus is on browse option **1610**, as indicated by the bold outline around option **1610**. While computer system **1600** causes display of workout user interface **1606** with the focus on browse option **1610**, remote control **1602** detects activation of selection region **1604a** via button press input **1611** corresponding to selection of option **1610** and transmits an indication of the input to computer system **1600**. Computer system **1600** receives, from remote control **1602**, the indication of input **1611** corresponding to selection of option **1610**.

At FIG. **16B**, in response to detecting (e.g., receiving the indication of) input **1611**, computer system **1600** causes display **1601** to replace display of workout user interface **1606** with workout browse user interface **1612**. Workout browse user interface **1612** includes a first region **1616a** that includes various filtering category options **1614a-1614d**. Workout browse user interface **1612** also includes a second region **1616b** that includes a plurality of workout suggestions. Each workout suggestion represents a respective workout, and each workout suggestion is selectable by a user to initiate a process for presenting workout content (e.g., audio content, video content) associated with the selected workout to the user. Workout browse user interface **1612** also includes an option **1617** that is selectable by a user to clear all currently applied filters, and an indication **1619** that provides an indication of how many workout suggestions are currently included in the second region **1616b**. In FIG. **16B**, the focus is on filtering category option **1614a**. While computer system **1600** is causing display of workout browse user interface **1612** with the focus on filtering category option **1614a**, remote control **1602** detects activation of selection region **1604a** via press input **1618** corresponding to selection of option **1614a**. Remote control **1602** transmits an indication of the input to computer system **1600**. Computer system **1600** receives, from remote control **1602**, the indication of input **1618** corresponding to selection of option **1614a**.

At FIG. **16C**, in response to detecting (e.g., receiving the indication of) input **1618**, computer system **1600** causes display **1601** to display replacement of filtering category options **1614a-1614d** with filtering options **1622a-1622h**. Filtering options **1622a-1622h** are associated with filtering category **1614a** (e.g., are grouped into filtering category **1614a**), and can be selected by a user to filter workout suggestions displayed in region **1616b**. In FIG. **16C**, filtering options **1622a-1622h** represent different workout types such that a user can select a filtering option to filter workout suggestions by workout type. In FIG. **16C**, the focus is on "ALL" filtering option **1622a**, and a selection indication **1620** indicates that the "ALL" filtering option is currently applied (e.g., indicating that workout suggestions have not been filtered by workout type). While filtering options

118

1622a-1622h are being displayed with the focus on filtering option **1622a**, remote control **1602** detects input **1623** corresponding to a downward swipe gesture on selection region **1604a**. Remote control **1602** transmits an indication of the input to computer system **1600**. Computer system **1600** receives, from remote control **1602**, the indication of input **1623** corresponding to a downward swipe gesture.

At FIG. **16D**, in response to detecting (e.g., receiving the indication of) input **1623**, computer system **1600** causes display **1601** to display movement of the focus in a downward direction, such that the focus moves to "CORE" filtering option **1622b**. While the focus has moved to "CORE" filtering option **1622b**, selection indication **1620** is still positioned at "ALL" filtering option **1622a**, as a different filtering option has not yet been selected or applied.

At FIG. **16E**, the focus has been maintained on the "CORE" filtering option **1622b** for at least a threshold period of time (e.g., 1 second). In response to a determination that the focus has been maintained on the "CORE" filtering option **1622b** for the threshold period of time, computer system **1600** causes display **1601** to update display of region **1616b** such that region **1616b** only displays workout suggestions associated with "CORE" filtering option **1622b**. As can be seen in FIG. **16E**, computer system **1600** has caused display **1601** to cease displaying workout suggestions that are not associated with the "CORE" workout type, and only workout suggestions that are associated with the "CORE" workout type are displayed in region **1616b**. While the user has not yet selected or applied the "CORE" workout type filtering option (as indicated by selection indication **1620** maintaining its position next to the "ALL" filtering option), region **1616b** has been updated to display a preview of workout suggestions that are associated with "CORE" filtering option **1622b**. While computer system **1600** causes display of workout suggestions associated with "CORE" filtering option **1622b**, remote control **1602** detects input **1625a** corresponding to a downward swipe gesture on selection region **1604a**. Remote control **1602** transmits an indication of the input to computer system **1600**. Computer system **1600** receives, from remote control **1602**, the indication of input **1625a** corresponding to a downward swipe gesture.

At FIG. **16F**, in response to detecting (e.g., receiving the indication of) input **1625a**, computer system **1600** causes display **1601** to display movement of the focus in a downward direction such that the focus moves from "CORE" filtering option **1622b** to "CYCLING" filtering option **1622c**. While the focus is on "CYCLING" filtering option **1622c**, remote control **1602** detects input **1625b** corresponding to a downward swipe gesture on selection region **1604a**. Input **1625b** can be a continuation of input **1625a**, or can be a separate, subsequent input. Remote control **1602** transmits an indication of the input to computer system **1600**. Computer system **1600** receives, from remote control **1602**, the indication of input **1625b** corresponding to a downward swipe gesture.

At FIG. **16G**, in response to detecting (e.g., receiving the indication of) input **1625b**, computer system **1600** causes display **1601** to display movement of the focus in a downward direction such that the focus moves from "CYCLING" filtering option **1622c** to "DANCE" filtering option **1622d**. While the focus is on "DANCE" filtering option **1622d**, remote control **1602** detects input **1625c** corresponding to a downward swipe gesture. Input **1625c** is, optionally, a continuation of input **1625b**, or is, optionally, a separate, subsequent input. Remote control **1602** transmits an indication of the input to computer system **1600**. Computer system

1600 receives, from remote control 1602, the indication of input 1625c corresponding to a downward swipe gesture.

At FIG. 16H, in response to detecting (e.g., receiving the indication of) input 1625c, computer system 1600 causes display 1601 to display movement of the focus in a downward direction such that the focus moves from “DANCE” filtering option 1622d to “HIIT” filtering option 1622e. Although the focus has moved from filtering option 1622b down to filtering options 1622c, 1622d, and 1622e, region 1616b continues to display the four workout suggestions associated with “CORE” filtering option 1622b. Computer system 1600 maintains display of the four workout suggestions in region 1616b based on a determination that the focus has not been maintained on any of filtering options 1622c, 1622d, or 1622e for at least the threshold period of time. However, at FIG. 16H, computer system 1600 determines that the focus has been maintained on filtering option 1622e for at least the threshold period of time.

At FIG. 16I, in response to the determination that the focus has been maintained on filtering option 1622e for at least the threshold period of time, computer system 1600 causes display 1602 to update display of region 1616b such that the four workout suggestions associated with “CORE” filtering option 1622b are replaced by six workout suggestions associated with “HIIT” filtering option 1622e. While the six workout suggestions associated with “HIIT” filtering option 1622e are displayed, remote control 1602 detects input 1625d corresponding to a rightward swipe gesture on selection region 1604a. Remote control 1602 transmits an indication of the input to computer system 1600. Computer system 1600 receives, from remote control 1602, the indication of input 1625d corresponding to a rightward swipe gesture.

At FIG. 16J, in response to detecting (e.g., receiving the indication of) input 1625d, computer system 1600 causes display 1601 to display movement of the focus in a rightward direction to workout suggestion 1624a. While the focus is on workout suggestion 1624a, remote control 1602 detects input 1625e corresponding to a rightward swipe gesture on selection region 1604a. Input 1625e can be a continuation of input 1625d, or a separate, subsequent input. Remote control 1602 transmits an indication of the input to computer system 1600. Computer system 1600 receives, from remote control 1602, the indication of input 1625e corresponding to a rightward swipe gesture.

At FIG. 16K, in response to detecting (e.g., receiving the indication of) input 1625c, computer system 1600 causes display 1601 to display movement of the focus in a rightward direction to workout suggestion 1624b. At FIG. 16K, computer system 1600 determines that the focus has been maintained on workout suggestion 1624b for at least a second threshold period of time.

At FIG. 16L, in response to determining that focus selector 1611a has been maintained on workout suggestion 1624b for at least the second threshold period of time, computer system 1600 causes display 1601 to display a visual indication that the focus has been maintained on workout suggestion 1624b for at least the second threshold period of time. In FIG. 16L, the visual indication includes animating workout suggestion 1624b. For example, after the second threshold period of time, workout suggestion 1624b can present a video preview of the workout associated with workout suggestion 1624b. In some embodiments, as long as the focus is continuously maintained on workout suggestion 1624b, the video preview of the workout can continue to play. While computer system 1600 causes display of the video preview of workout suggestion 1624b, remote control

1602 detects input 1625f corresponding to a leftward swipe gesture on selection region 1604a. Remote control 1602 transmits an indication of the input to computer system 1600. Computer system 1600 receives, from remote control 1602, the indication of input 1625f corresponding to a leftward swipe gesture.

At FIG. 16M, in response to detecting (e.g., receiving the indication of) input 1625f, computer system 1600 causes display 1601 to display movement of the focus in a leftward direction to “HIIT” filtering option 1622d. While the focus is on “HIIT” filtering option 1622d, remote control 1602 detects activation of selection region 1604a via press input 1625g corresponding to selection of “HIIT” filtering option 1622d. Remote control 1602 transmits an indication of the input to computer system 1600. Computer system 1600 receives, from remote control 1602, the indication of input 1625g corresponding to selection of “HIIT” filtering option 1622d.

At FIG. 16N, in response to detecting (e.g., receiving the indication of) input 1625g, computer system 1600 causes display 1601 to replace display of filtering options 1622a-h in region 1616a with filtering category options 1614a-1614d. Furthermore, in response to input 1625g, computer system 1600 has visually modified filtering category option 1614a to indicate that the “HIIT” filtering option has been selected for the “WORKOUT TYPES” filtering category, and computer system 1600 has also added button 1626 to workout browse user interface 1612. Button 1626 is selectable by a user to remove the currently applied “HIIT” filtering option. Additionally, in response to detecting input 1625g corresponding to selection of the “HIIT” filtering option for the “WORKOUT TYPES” filtering category, the focus is automatically positioned on a next filtering category, “TRAINER” filtering category 1614b. While the focus is on “TRAINER” filtering category 1614b, remote control 1602 detects activation of selection region 1604a via press input 1625h corresponding to selection of filtering category 1614b. Remote control 1602 transmits an indication of the input to computer system 1600. Computer system 1600 receives, from remote control 1602, the indication of input 1625h corresponding to selection of filtering category 1614b.

At FIG. 16O, in response to detecting (e.g., receiving the indication of) input 1625h, computer system 1600 causes display 1601 to display replacement of filtering category options 1614a-1614d with filtering options 1628a-1628i. Filtering options 1628a-1628i are associated with filtering category 1614b (e.g., are grouped into filtering category 1614b), and can be selected by a user to filter the workout suggestions displayed in region 1616b. In FIG. 16O, filtering options 1628a-1628i represent different trainers such that a user can select a filtering option to filter workout suggestions by trainer. In FIG. 16O, filtering options 1628g, 1628h, and 1628i are visually distinct from filtering options 1628a-1628f. Filtering options 1628g-1628i are displayed in a visual style indicating that those filtering options are not compatible with the currently applied filtering options (e.g., the “HIIT” filtering option). For example, the three trainers associated with those filtering options (Ben, Joyce, and Stan) may not have any HIIT workouts. In some embodiments, filtering options 1628g-1628i may not be selectable. In some embodiments, filtering options 1628g-1628i can be selectable, but selection of these filtering options can result in de-selection of one or more (e.g., all) currently applied filtering options.

In FIG. 16O, the focus is on the “ALL” filtering option 1628a, and selection indication 1620 indicates that the

121

“ALL” filtering option is currently applied (e.g., indicating that workout suggestions have not been filtered by trainer). While computer system 1600 causes display of filtering options 1628a-1628i with the focus on “ALL” filtering option 1628a, remote control 1602 detects input 1625i corresponding to a downward swipe gesture on selection region 1604a. Remote control 1602 transmits an indication of the input to computer system 1600. Computer system 1600 receives, from remote control 1602, the indication of input 1625i corresponding to a downward swipe gesture.

At FIG. 16P, in response to detecting (e.g., receiving the indication of) input 1625i, computer system 1600 causes display 1601 to display downward movement of the focus through filtering options 1628b, 1628c, 1628d, 1628e, and finally to filtering option 1628f (“MAYA”). At FIG. 16P, computer system 1600 determines that the focus has been maintained on filtering option 1628f for a threshold period of time.

At FIG. 16Q, in response to determining that the focus has been maintained on filtering option 1628f for the threshold period of time, computer system 1600 causes display 1601 to update workout browse user interface 1612 such that region 1616b ceases to display any workout suggestions that are not associated with filtering option 1628f. In FIG. 16Q, region 1616b displays only those HIIT workouts that are also associated with trainer Maya. While computer 1600 causes display of only those workout suggestions that are associated with filtering option 1628f, remote control 1602 detects activation of selection region 1604a via press input 1625j corresponding to selection of filtering option 1628f. Remote control 1602 transmits an indication of the input to computer system 1600. Computer system 1600 receives, from remote control 1602, the indication of input 1625j corresponding to selection of filtering option 1628f.

At FIG. 16R, in response to detecting (e.g., receiving the indication of) input 1625j, computer system 1600 causes display 1601 to replace display of filtering options 1628a-1628i in region 1616a with filtering category options 1614a-1614d. Furthermore, in response to input 1625j, computer system 1600 has visually modified filtering category option 1614b to indicate that the “MAYA” filtering option has been selected for the “TRAINER” filtering category, and computer system 1600 has also added a button 1630 to workout browse user interface 1612. Button 1630 is selectable by a user to remove the currently applied “MAYA” filtering option. Additionally, in response to detecting input 1625j corresponding to selection of the “MAYA” filtering option for the “TRAINER” filtering category, the focus is automatically positioned on a next filtering category, e.g., the “DURATION” filtering category 1614c.

FIGS. 17A-17B are a flow diagram illustrating a method for displaying workout information in accordance with some embodiments. Method 1700 is performed at a device (e.g., 100, 300, 500, 600, 800, 1600) with a display. Some operations in method 1700 are, optionally, combined, the orders of some operations are, optionally, changed, and some operations are, optionally, omitted.

In some embodiments, the electronic device (e.g., 600, 800, 1600) is a computer system. The computer system is optionally in communication (e.g., wired communication, wireless communication) with a display generation component and with one or more input devices. The display generation component is configured to provide visual output, such as display via a CRT display, display via an LED display, or display via image projection. In some embodiments, the display generation component is integrated with the computer system. In some embodiments, the display

122

generation component is separate from the computer system. The one or more input devices are configured to receive input, such as a touch-sensitive surface receiving user input. In some embodiments, the one or more input devices are integrated with the computer system. In some embodiments, the one or more input devices are separate from the computer system. Thus, the computer system can transmit, via a wired or wireless connection, data (e.g., image data or video data) to an integrated or external display generation component to visually produce the content (e.g., using a display device) and can receive, a wired or wireless connection, input from the one or more input devices.

As described below, method 1700 provides an intuitive way for displaying workout information. The method reduces the cognitive burden on a user for displaying workout information, thereby creating a more efficient human-machine interface. For battery-operated computing devices, enabling a user to display camera views faster and more efficiently conserves power and increases the time between battery charges.

Computer system 1600 (e.g., an electronic device, a set top device; a digital media player) that is in communication with (e.g., wired communication, wireless communication) a display generation component and one or more input devices: causes display (1702), via the display generation component, of a user interface (e.g., 1612), wherein the user interface includes: a plurality of workout suggestions (e.g., workout suggestions displayed in region 1616b) displayed in a first region (e.g., 1616b) of the user interface, and one or more filtering options (e.g., 1622a-1622h, 1628a-1628i) (e.g., one or more workout types, trainers, durations, music options) for filtering workout suggestions displayed concurrently with the plurality of workout suggestions. In some embodiments, a workout suggestion corresponds to (e.g., represents) a workout (e.g., audio and/or video content that guides a user to perform a physical activity). In some embodiments, selecting a workout suggestion initiates a process for playback of a workout corresponding to the workout suggestion. In some embodiments, only a portion of the plurality of workout suggestions are displayed at a given time and scrolling within the user interface causes display of additional workout suggestions of the plurality of workout suggestions. Displaying the plurality of workout suggestions and one or more filtering options for filtering workout suggestions enables a user to quickly filter workouts and gain access to a particular workout, thereby reducing the number of inputs needed for selecting a workout. Reducing the number of inputs needed to perform an operation enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

Computer system 1600 detects (1704), via the one or more input devices, a first user input (e.g., 1623, 1625c, 1625i) (e.g., on a remote control, smartphone, tablet, and/or watch in communication with (e.g., operably connected to) the computer system) directed to a first filtering option (e.g., 1622a, 1622e, 1628f) of the one or more filtering options.

In accordance with a determination that the first user input directed to the first filtering option has been maintained for at least a predefined period of time (1706) (e.g., the focus selector has been maintained on the first filtering option without navigating away from the first filtering option for a predefined period of time (e.g., and without actively select-

123

ing (e.g., tapping on, clicking) the first filtering option)) (e.g., hovering on the first filtering option for a predefined period of time), computer system **1600** ceases to display (1708) at least a portion of the plurality of workout suggestions within the first region of the user interface, so that the first region of the user interface includes a first subset of workout suggestions (e.g., FIG. 16E depicting a subset of workout suggestions associated with filtering option **1622a**, FIG. 16I depicting a subset of workout suggestions associated with filtering option **1622c**, FIG. 16Q depicting a subset of workout suggestions associated with filtering option **1628f**) from the plurality of workout suggestions that are associated with the first filtering option and does not include workout suggestions that are not associated with the first filtering option (e.g., satisfies the first filtering option) (in some embodiments, only a portion of the first subset of workout suggestions is displayed at a given time, and scrolling within the user interface causes display of additional workout suggestions of the first subset of workout suggestions). Ceasing display of at least a portion of the plurality of workout suggestions such that the user interface includes workout suggestions that are associated with the first filtering option enables a user to quickly view and gain access to a particular workout, thereby reducing the number of inputs needed for selecting a workout. Reducing the number of inputs needed to perform an operation enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

While the first subset of workout suggestions is displayed in the first region (e.g., **1616b**) of the user interface (1710), computer system **1600** detects (1712), via the one or more input devices, a second user input (e.g., **1625d**, **1625c**) (e.g., on a remote control, smartphone, tablet, and/or watch in communication with (e.g., operably connected to) the computer system) corresponding to navigation to a first workout suggestion (e.g., **1624b**) of the first subset of workout suggestions.

In response to detecting the second user input (1714), computer system **1600** causes display (1716), via the display generation component, of a visual indication that the input is directed to the first workout suggestion (e.g., FIG. 16K-16L depicting movement/animation of workout suggestion **1624b**) while display of the first subset of workout suggestions is maintained in the first region (e.g., **1616b**) of the user interface.

In some embodiments, while causing display of the first subset of workout suggestions in the first region (e.g., **1616b**) of the user interface (1718), computer system **1600** detects (172), via the one or more input devices, a third user input (e.g., **1625c**) (e.g., on a remote control, smartphone, tablet, and/or watch in communication with (e.g., operably connected to) the computer system) directed to a second filtering option (e.g., **1622e**) of the one or more filtering options.

In some embodiments, in accordance with a determination that the input directed to the second filtering option has been maintained for at least a second predefined period of time (1722) (e.g., the focus selector has been maintained on the second filtering option without navigating away from the second filtering option for a second predefined period of time (e.g., a predetermined period of time that is the same as the predetermined period of time) (e.g., and without actively

124

selecting (e.g., tapping on, clicking) the second filtering option)) (e.g., hovering on the second filtering option for a predefined period of time), computer system **1600** ceases to display (1724) at least a portion of the first subset of workout suggestions (e.g., FIGS. 16H-16I, depicting replacement of a first set of workout suggestions associated with “CORE” filtering option **1622a** with a second set of workout suggestions associated with “HIIT” filtering option **1622e**), so that the first region of the user interface includes a second subset of workout suggestions from the plurality of workout suggestions that are associated with the second filtering option and does not include workout suggestions that are not associated with the second filtering option (e.g., satisfies the second filtering option). In some embodiments, only a portion of the second subset of workout suggestions is displayed at a given time, and scrolling within the user interface causes display of additional workout suggestions of the second subset of workout suggestions. Ceasing display of at least a portion of the first subset of workout suggestions so that the first region of the user interface includes a second subset of workout suggestions from the plurality of workout suggestions that are associated with the second filtering option enables a user to quickly view and gain access to a particular workout, thereby reducing the number of inputs needed for selecting a workout. Reducing the number of inputs needed to perform an operation enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, the one or more filtering options (e.g., **1622a-1622h**) are grouped into a first filtering category (e.g., **1614a**) (e.g., filtering categories can include workout type, trainer, duration, music genre), the first filtering category is one of a plurality of filtering categories (e.g., **1614a-1614d**) (e.g., workout type, trainer, duration, music genre), and the first filtering category (e.g., **1614a**) includes a plurality of filtering options (e.g., **1622a-1622h**) and a second filtering category (e.g., **1614b**) of the plurality of filtering categories includes a plurality of filtering options (e.g., **1628a-1628i**) (1726). In some embodiments, each filtering category of the plurality of filtering categories comprises a plurality of filtering options (e.g., the “workout type” filtering category includes a plurality of workout types, the “trainer” filtering category includes a plurality of trainers, the “duration” filtering category includes a plurality of workout durations, the “music genre” filtering category includes a plurality of music genres). Grouping filtering options into various filtering categories enables a user to quickly gain access to and apply filtering options, thereby reducing the number of inputs needed to apply a filtering option. Reducing the number of inputs needed to perform an operation enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, while causing display of the one or more filtering options of the first filtering category in the user interface, computer system **1600** detects a fourth user input (e.g., **1625g**) (e.g., a selection of a different filtering category).

125

In some embodiments, in response to detecting the fourth user input, computer system **1600** causes ceasing of display of the one or more filtering options of the first filtering category (e.g., in FIG. **16N**, filtering options **1622a-1622h** are no longer displayed).

In some embodiments, computer system **1600** causes, via the display generation component, display of the plurality of filtering categories (e.g., in FIG. **16N**, filtering categories **1614a-1614d** are displayed) (e.g., workout type, trainer, duration, music genre/type) including the first filtering category.

In some embodiments, computer system **1600** detects a fifth user input (e.g., **1625h**) corresponding to selection of a second filtering category from the plurality of filtering categories (e.g., tapping on the second filtering category, clicking on the second filtering category).

In some embodiments, in response to detecting the fifth user input (e.g., **1625h**), computer system **1600** causes the second filtering category to be expanded so that a second plurality of filtering options of the second filtering category are displayed (e.g., in FIG. **16O**, filtering options **1628a-1628i** are displayed). In some embodiments, causing the second filtering category to be expanded so that the second plurality of filtering options of the second filtering category are displayed comprises causing replacement of display of the plurality of filtering categories with display of the second plurality of filtering options. Ceasing display of filtering options in one filtering category before displaying filtering options in a different category allows a user to more efficiently navigate and apply filtering options, thereby reducing the number of inputs needed to apply filtering options. Reducing the number of inputs needed to perform an operation enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, the fourth user input corresponds to selection of the first filtering option of the one or more filtering options (e.g., tapping on the first filtering option, clicking on the first filtering option) (e.g., **1625g** in FIG. **16M**). Ceasing display of the one or more filtering options of the first category and causing display of the plurality of filtering categories in response to a user selection of a first filtering option within the first category allows a user to more quickly and efficiently navigate filtering options with fewer inputs. Reducing the number of inputs needed to perform an operation enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, in response to the first user input (e.g., **1623**), computer system **1600** maintains display of the one or more filtering options of the first filtering category (e.g., FIGS. **16C-16E**, display of filtering options **1622a-1622h** is maintained). Maintaining display of one or more filtering options prior to selection of a filtering options, and then ceasing display of the one or more filtering options and causing display of the plurality of filtering categories in response to a user selection of a first filtering option allows a user to more quickly and efficiently navigate filtering options in multiple filtering categories with fewer inputs.

126

Reducing the number of inputs needed to perform an operation enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, in response to detecting the fifth user input (e.g., **1625h**) and in accordance with a determination that a third filtering option (e.g., a trainer filtering option) (e.g., **1628g**, **1628h**, **1628i**) of the second plurality of filtering options (e.g., **1628a-1628i**) is incompatible with a set of currently applied filtering options (e.g., in FIG. **16O**, a “HIIT” filtering option is applied) (e.g., a selected filtering option from the first filtering category) (in some embodiments, no workout suggestions associated with the third filtering option are also associated with the currently applied filtering options, there is no overlap between the subset of workout suggestions that are associated with the third filtering option and the subset of workout suggestions that are associated with the currently applied filtering options), and while the second plurality of filtering options of the second filtering category are displayed, computer system **1600** causes display, via the display generation component, of a visual indication that the third filtering option is incompatible with the set of currently applied filtering options (e.g., filtering options **1628g-1628i** in FIG. **16O** are visually distinct from filtering options **1628a-1628f**) (e.g., displaying the third filtering option in a particular visual style indicative of the third filtering option being incompatible with the currently applied filtering options (e.g., as a “grayed out” or otherwise visually deemphasized option), displaying the third filtering option separately from one or more filtering options that are compatible with the currently applied filtering options (e.g., that have associated workout suggestions that are also associated with the currently applied filtering options)). In some embodiments, based on the determination that the third filtering option is incompatible with the set of currently applied filtering options, the third filtering option is unavailable for selection by a user. In some embodiments, the third filtering option is still selectable, but selection of the third filtering option results in the currently applied filtering options being removed (e.g., the currently applied filtering options are removed, and the third filtering option is applied). Displaying a visual indication that a particular filtering option is incompatible with the set of currently applied filtering options allows a user to more quickly and efficiently navigate and apply filtering options with fewer inputs. Otherwise, a user may spend one or more inputs attempting to apply filtering options that are incompatible with currently applied filtering options. Reducing the number of inputs needed to perform an operation enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, in response to detecting the fourth user input (e.g., **1625g**), computer system **1600** causes display, via the display generation component, of a selectable user interface object (e.g., selectable option, affordance) (e.g., **1626**) that indicates that the first filtering option has been selected and applied, wherein the selectable user interface object, when selected, removes application of the first

filtering option (e.g., selection of the selectable user interface object results in the first region of the user interface including workout suggestions that are not associated with the first filtering option). Displaying selectable user interface objects that can be selected to remove application of an applied filtering option allows a user to more quickly and efficiently remove application of applied filtering options with fewer inputs. Reducing the number of inputs needed to perform an operation enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, after detecting the first user input and in accordance with a determination that the first user input directed to the first filtering option has not been maintained for at least the predefined period of time (e.g., the focus selector has not been maintained on the first filtering option for the predefined period of time (e.g., the focus selector has been navigated away from the first filtering option before the predefined period of time has elapsed)), computer system **1600** maintains display, via the display generation component, of the plurality of workout suggestions in the first region of the user interface (e.g., FIGS. **16E-16F**, user input **1625a** does not cause a change in the plurality of workout suggestions shown in region **1616b**) (e.g., maintaining display of the plurality of workout suggestions in the first region of the user interface such that the first region of the user interface remains unchanged). Maintaining display of workout suggestions when a user input has not been maintained for at least a predefined period of time reduces the number of times the objects and/or components displayed in a user interface must be updated or changed. Reducing unnecessary visual changes in a UI makes the user-device interface more efficient (e.g., by minimizing visual confusion and helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, each filtering option of the one or more filtering options is associated with a respective workout trainer of one or more workout trainers (e.g., trainer filtering options **1628a-1628i**). In some embodiments, the first filtering option is associated with a first workout trainer of the one or more workout trainers. In some embodiments, ceasing to display at least a portion of the plurality of workout suggestions within the first region of the user interface comprises ceasing to display workout suggestions that are not associated with the first workout trainer (e.g., FIG. **16Q**), so that the first region of the user interface includes a first subset of workout suggestions from the plurality of workout suggestions that are associated with the first workout trainer and does not include workout suggestions that are not associated with the first workout trainer. Ceasing display of workout suggestions that are not associated with the first workout trainer provides the user with feedback as to which workouts correspond to the selected trainer. Providing improved feedback to the user enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces

power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, causing display of a visual indication that the input is directed to the first workout suggestion while display of the first subset of workout suggestions is maintained in the first region of the user interface comprises causing display, via the display generation component, of a preview video associated with the first workout suggestion while display of the first subset of workout suggestions is maintained in the first region of the user interface (e.g., FIGS. **16K-16L**). In some embodiments, the preview video comprises video and/or audio footage of a workout trainer associated with the workout suggestion. In some embodiments, the preview video associated with the first workout suggestion comprises selected portions of the first workout suggestion. In some embodiments, each workout suggestion of the plurality of workout suggestions is associated with a respective preview video, and each preview video has the same, predetermined duration. Causing display of the preview video associated with the first workout suggestion provides the user with feedback about the current state of the device (e.g., the device has detected a user input directed to the first workout suggestion). Providing improved feedback to the user enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, the user interface (e.g., **1612**) further includes a second selectable user interface object (e.g., selectable option, affordance) (e.g., **1617**) that, when selected, removes one or more (or all) applied filtering options. In some embodiments, selection of the selectable user interface object results in the first region of the user interface including an unfiltered (e.g., complete) listing of available workout suggestions. Providing a selectable user interface object that can be selected to remove application of an applied filtering option allows a user to more quickly and efficiently remove application of applied filtering options with fewer inputs. Reducing the number of inputs needed to perform an operation enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

Note that details of the processes described above with respect to method **1700** (e.g., FIGS. **17A-17B**) are also applicable in an analogous manner to the methods described below. For example, method **1900** optionally includes one or more of the characteristics of the various methods described above with reference to method **1700**. For example, the workout suggestion user interfaces as discussed below with respect to method **1900** may include various browsing and filtering features, as set forth in method **1700**. For brevity, these details are not repeated below.

FIGS. **18A-18V** illustrate exemplary user interfaces for displaying workout information, in accordance with some embodiments. The user interfaces in these figures are used to illustrate the processes described below, including the processes in FIGS. **19A-19C**.

FIGS. **18A-18V** illustrate exemplary devices and user interfaces. At FIG. **18A**, computer system **1600** (e.g., device

129

100, 300, 500) is displaying a home screen user interface 1810 on display 1601 (e.g., a television) that includes selectable graphical user interface objects for launching one or more different applications or viewing different content. In some embodiments, display 1601 is an integrated part of computer system 1600. In some embodiments, computer system 1600 is in communication (e.g., wireless, wired) with display 1601 (e.g., as depicted in FIG. 18A) (e.g., the computer system is a set top box or computer that is in communication with display 1601).

FIG. 18A also illustrates remote control 1602, which is configured to transmit data (e.g., via RF communication, via Bluetooth, via infrared) to computer system 1600 based on user input that is detected at remote control 1602. Remote control 1602 includes a selection region 1604a, which includes a touch-sensitive surface for detecting tap, press, and swipe gestures, a menu button 1604b, a television button 1604c, a microphone button 1604d, a play/pause button 1604e, and volume control buttons 1604f.

FIGS. 18A-18C depict an example scenario 1802, in which a user is automatically presented with a personalized workout user interface. In the example scenario 1802, a determination is made by computer system 1600 that there is a single recognized user (1806a) within a proximity of computer system 1600 (e.g., there is a single recognized (e.g., previously paired) electronic device associated with a user within a proximity of the computer system). Based on that determination, computer system 1600 displays a personalized workout user interface for that recognized user. More details will now be provided with reference to FIGS. 18A-18C.

At FIG. 18A, computer system 1600 causes display 1601 to display a home screen user interface 1810. Home screen user interface 1810 includes application representations 1812a-1812d that are selectable by a user to open a corresponding application.

FIG. 18A also depicts a scenario 1802 in which a user 1806a is in the same room as computer system 1600. User 1806a is wearing an electronic device 800a (e.g., device 800) (e.g., a watch). Computer system 1600 determines that there is one device (e.g., a device of a particular type (e.g., one watch)) that is within a predefined proximity of computer system 1600 (e.g., in the same room, within a threshold distance, etc.). Furthermore, in scenario 1802, computer system 1600 also determines that the device 800a has previously been paired with computer system 1600 (e.g., the user 800a has previously caused device 800a to connect to (e.g., wirelessly) computer system 1600)).

In home screen user interface 1810 as depicted in FIG. 18A, a focus is on application representation 1812a that corresponds to a fitness application. While computer system 1600 causes display, via display 1601, of home screen user interface 1810 with the focus on application representation 1812a, remote control 1602 detects activation of selection region 1604a via button press input 1814 corresponding to selection of application representation 1812a, and transmits an indication of the input to computer system 1600. Computer system 1600 receives, from remote control 1602, the indication of input 1814 corresponding to selection of application representation 1812a.

At FIG. 18B, in response to detecting (e.g., receiving the indication of) input 1814, and based on (e.g., in response to, in accordance with) the determination that there is a single device 800a that is within the predefined proximity of computer system 1600, and further based on (e.g., in response to, in accordance with) the determination that the single device 800a is a recognized device that has previously

130

been paired with computer system 1600, computer system 1600 causes device 800a to display, via display 801a, a notification 1815a. The notification 1815a requests confirmation from user 800a that the user would like to pair device 800a with computer system 1600. Notification 1815a includes option 1816 to confirm pairing of device 800a with computer system 1600, and option 1818 to cancel pairing. In some embodiments, computer system 1600 also causes device 800a to output a haptic output to notify the user of notification 1815a. In response to input 1814 and based on the determination that there is a single previously-paired device within the proximity of computer system 1600, computer system 1600 also causes display 1601 to display notification 1815b instructing the user to pair their device with computer system 1600.

In FIG. 18B, electronic device 800a detects an input 1820 corresponding to the location of option 1816 indicating confirmation of the user's intent to pair device 800a with computer system 1600. Device 800a transmits an indication of the input to computer system 1600. Computer system 1600 receives, from device 800a, the indication of input 1820. In some embodiments, rather than requiring a single tap to confirm pairing of device 800a with computer system 1600, computer system 1600 can require entry of additional information, such as a PIN number, to confirm pairing (e.g., as shown in FIG. 18M).

At FIG. 18C, in response to detecting (e.g., receiving the indication of) input 1820, computer system 1600 causes display 1601 to display a new user interface. Furthermore, based on (e.g., in response to, in accordance with) the determination that there is a single previously-paired device 800a (e.g., a single previously-paired device of a particular type (e.g., a watch)) that is within the predefined proximity of computer system 1600, computer system 1600 causes display, via display 1601, of a workout user interface 1822 that is associated with device 800a and/or user 1806a. Workout user interface 1822 has substantially similar functionality to workout user interface 1606 of FIG. 16A. Workout user interface 1822 includes workout suggestions 1824a-1824d for a user (e.g., user 1806a). In some embodiments, workout user interface 1822 is associated with electronic device 800a in that electronic device 800a is associated with user 1806a, and workout suggestions 1824a-1824d are selected based on one or more workouts that have been completed by user 1806a. For example, workout suggestion 1824a represents a workout that shares one or more characteristics with a subset of workouts completed by user 1806a (e.g., the most recently completed workout). In the depicted scenario, user 1806a most recently completed a core workout with trainer Amy. Accordingly, computer system 1600 provides workout suggestion 1824a, as it represents a workout that has a shared characteristic with user 1806a's most recently completed workout (e.g., workout suggestion 18024a has the same type of workout (core) as the user's most recently completed workout, workout suggestion 18024a has the same trainer (Amy) as the user's most recently completed workout). Workout user interface 1822 also includes option 1825a, which is selectable to present workout user interface 1822, and option 1825b, which is selectable to present a different workout browse user interface (e.g., user interface 1612 of FIG. 16B).

Whereas FIGS. 18A-18C demonstrate a scenario in which a single recognized device is identified, FIGS. 18D-18H demonstrate a scenario in which multiple recognized (e.g., previously-paired) devices are identified as being within a proximity of computer system 1600.

131

At FIG. 18D, computer system 1600 causes display 1601 to display home screen user interface 1810.

FIG. 18D also depicts a scenario 1828 in which two users 1806a, 1806b are in the same room as computer system 1600. User 1806a is wearing an electronic device 800a (e.g., device 800) (e.g., a watch) and user 1806b is wearing an electronic device 800b (e.g., device 800) (e.g., a watch). Computer system 1600 determines that there are multiple (e.g., two) devices (e.g., devices of a particular type (e.g., two watches)) that are within a predefined proximity of computer system 1600 (e.g., in the same room, within a threshold distance, etc.). Furthermore, in scenario 1828, computer system 1600 also determines that both devices 800a, 800b have previously been paired with computer system 1600.

In home screen user interface 1810 as depicted in FIG. 18D, the focus is on application representation 1812a that corresponds to a fitness application. While computer system 1600 causes display, via display 1601, of home screen user interface 1810 with the focus on application representation 1812a, remote control 1602 detects activation of selection region 1604a via button press input 1829 corresponding to selection of application representation 1812a, and transmits an indication of the input to computer system 1600. Computer system 1600 receives, from remote control 1602, the indication of input 1829 corresponding to selection of application representation 1812a.

At FIG. 18E, in response to detecting (e.g., receiving the indication of) input 1829, and based on (e.g., in response to, in accordance with) the determination that there is are multiple recognized (e.g., previously-paired) devices 800a, 800b that are within the predefined proximity of computer system 1600, computer system 1600 causes device display 1601 to replace display of home screen user interface 1810 with disambiguation user interface 1830. Disambiguation user interface 1830 includes three selectable options 1832a, 1832b, 1832c. Option 1832a is associated with (e.g., corresponds to) user 1806b and device 800b, and is presented based on a determination that device 800b is within the predefined proximity of computer system 1600. Option 1832a, when selected, presents a workout user interface associated with user 1806b and device 800b. Option 1832b is associated with (e.g., corresponds to) user 1806a and device 800a, and is presented based on a determination that device 800a is within the predefined proximity of computer system 1600. Option 1832b, when selected, presents a workout user interface associated with user 1806a and device 800a. Option 1832c is selectable to pair a new device that has not been previously paired with computer system 1600.

In FIG. 18E, the focus is on option 1832b, and remote control 1602 detects activation of selection region 1604a via button press input 1834 corresponding to selection of option 1832b. Remote control 1602 transmits an indication of the input to computer system 1600. Computer system 1600 receives, from remote control 1602, the indication of input 1834.

At FIG. 18F, in response to detecting (e.g., receiving the indication of) input 1834, computer system 1600 causes replacement of display of disambiguation user interface 1830 with workout user interface 1822. Workout user interface 1822 is the same as workout user interface 1822 in FIG. 18C. As discussed above with reference to FIG. 18C, workout user interface 1822 is associated with (e.g., corresponds to, is personalized for) user 1806a and device 800a. For example, workout suggestions 1824a-1824d presented

132

in workout user interface 1822 are selected based on one or more workouts that have been completed by user 1806a.

In response to detecting input 1834, computer system 1600 also causes device 800a to display a notification 1836 and output a haptic output confirming that device 800a has been paired with computer system 1600. In some embodiments, before causing display of user interface 1822, computer system 1600 causes display of a notification on device 800a confirming that the user would like to pair device 800a with computer system 1600 (as was shown in FIG. 18B).

In FIG. 18G, returning to disambiguation user interface 1830, the focus is on option 1832a, and remote control 1602 detects activation of selection region 1604a via button press input 1838 corresponding to selection of option 1832a. Remote control 1602 transmits an indication of the input to computer system 1600. Computer system 1600 receives, from remote control 1602, the indication of input 1838.

At FIG. 18H, in response to detecting (e.g., receiving the indication of) input 1838, computer system 1600 causes replacement of display of disambiguation user interface 1830 with workout user interface 1840. Functionality of user interface 1840 is substantially the same as workout user interface 1822 in FIGS. 18C and 18F. Workout user interface 1840 is associated with (e.g., corresponds to, is personalized for) user 1806b and device 800b. For example, workout suggestions 1842a-1842d presented in workout user interface 1840 are selected based on one or more workouts that have been completed by user 1806a.

In response to detecting input 1838, computer system 1600 also causes device 800b to display a notification 1844 and output a haptic output confirming that device 800b has been paired with computer system 1600. In some embodiments, before causing display of user interface 1840, computer system 1600 causes display of a notification on device 800a confirming that the user would like to pair device 800b with computer system 1600 (similar to notification 1815a shown in FIG. 18B).

Whereas FIGS. 18A-18C demonstrate a scenario in which a single recognized device (e.g., a smartphone or smart watch or other device that is associated with a particular user) is identified, and FIGS. 18D-18H demonstrate a scenario in which multiple recognized (e.g., previously-paired) devices are identified as being within a proximity of computer system 1600, FIGS. 18I-18N demonstrate a scenario in which one or more devices are within a proximity of computer system 1600, but none of the devices are recognized devices (e.g., none of the devices have been previously-paired with computer system 1600). In some embodiments, the recognized device is a device that includes one or more sensors (e.g., biometric sensors such as heart rate or blood oxygenation sensors or motion sensors such as gyroscopes or accelerometers) that enable more accurate tracking of user activity levels during a workout.

At FIG. 18I, computer system 1600 causes display 1601 to display home screen user interface 1810.

FIG. 18I also depicts a scenario 1846 in which a user 1806c is in the same room as computer system 1600. User 1806c is wearing an electronic device 800c (e.g., device 800) (e.g., a watch). Computer system 1600 determines that there is a single device 800c within a predefined proximity of computer system 1600 (e.g., in the same room, within a threshold distance, etc.), but also determines that device 800c has not been previously paired with computer system 1600.

In home screen user interface 1810 as depicted in FIG. 18I, the focus is on application representation 1812a that corresponds to a fitness application. While computer system

133

1600 causes display, via display 1601, of home screen user interface 1810 with the focus on application representation 1812a, remote control 1602 detects activation of selection region 1604a via button press input 1848 corresponding to selection of application representation 1812a, and transmits an indication of the input to computer system 1600. Computer system 1600 receives, from remote control 1602, the indication of input 1848 corresponding to selection of application representation 1812a.

At FIG. 18J, in response to detecting (e.g., receiving the indication of) input 1848, and based on (e.g., in response to, in accordance with) the determination that there are no recognized (e.g., previously-paired) devices that are within the predefined proximity of computer system 1600, computer system 1600 causes display 1601 to replace display of home screen user interface 1810 with logged-out workout user interface 1850. In contrast to workout user interfaces 1822, 1840 discussed above, logged-out workout user interface 1850 is not associated with any particular user or user account. User interface 1850 displays workout suggestions 1852a-1852c, but workout suggestions 1852a-1852c may not be selectable by a user until the user logs into and/or signs up for a fitness application account. User interface 1850 provides option 1856a that is selectable to sign up for a free trial of the fitness application, and option 1856b that is selectable to log in to a fitness application account if the user already has an account.

In FIG. 18J, the focus is on option 1856a. While computer system 1600 causes display of user interface 1850 with the focus on option 1856a, remote control 1602 detects activation of selection region 1604a via button press input 1858 corresponding to selection of option 1856a, and transmits an indication of the input to computer system 1600. Computer system 1600 receives, from remote control 1602, the indication of input 1858 corresponding to selection of option 1856a.

In FIG. 18K, in response to detecting (e.g., receiving the indication of) input 1858, computer system 1600 causes display 1601 to replace display of user interface 1850 with user interface 1860. User interface 1860 includes an option 1862a that is selectable to confirm a free trial of the fitness application, and an option 1862b that is selectable to cancel signing up for the free trial of the fitness application. In FIG. 18K, the focus is on option 1862a. While computer system 1600 causes display of user interface 1860 with the focus on option 1862a, remote control 1602 detects activation of selection region 1604a via button press input 1864 corresponding to selection of option 1862a, and transmits an indication of the input to computer system 1600. Computer system 1600 receives, from remote control 1602, the indication of input 1864 corresponding to selection of option 1862a.

In FIG. 18L, in response to detecting (e.g., receiving the indication of) input 1864, computer system 1600 causes display 1601 to replace display of user interface 1860 with user interface 1866. User interface 1866 instructs the user 1806c to open the fitness application on device 800c.

In FIG. 18M, in response to a determination that the user has opened the fitness application on device 800c, computer system 1600 causes display 1601 to replace display of user interface 1860 with user interface 1868. User interface 1868 displays a PIN number. Computer system 1600 also causes device 800c to display, via display 801c, a number pad 1870. User 1806c can use the number pad 1870 to enter the PIN number shown in user interface 1868 to confirm his or her intention to pair device 800c with computer system 1600. In FIG. 18M, device 800c detects user input 1874 correspond-

134

ing to entry of the number sequence “1 2 3 4”, and transmits an indication of the input to computer system 1600. Computer system 1600 receives, from device 800c, the indication of input 1874 corresponding to entry of the number sequence “1 2 3 4.” In some embodiments, rather than entering a PIN number, other inputs can be received to confirm user intent to pair device 800c with computer system 1600.

In FIG. 18N, in response to detecting (e.g., receiving the indication of) input 1874, computer system 1600 causes display 1601 to replace display of user interface 1868 with workout user interface 1876. Like workout user interfaces 1822, 1840 discussed with reference to FIGS. 18B, 18F, and 18H, workout user interface 1876 includes workout suggestions 1852a-1852c that are each associated with a particular workout, and are selectable to access workout content (e.g., video content, audio content) for the workout. In some embodiments, workout user interface 1876 is a default workout user interface that is not personalized to user 1806a. This can be because user 1806a has not performed any workouts in the fitness application and, as such, there is insufficient data to generate a personalized workout user interface for the user 1806a. Workout user interface 1876 also includes option 1853a that is selectable to present workout user interface 1876, and option 1853b that is selectable to present a different workout browse user interface (e.g., user interface 1612 of FIG. 16B).

FIGS. 18O-18V demonstrate a scenario in which a user can log out of his or her account to allow for pairing of a new device with the computer system 1600.

At FIG. 18O, computer system 1600 causes display 1601 to display home screen user interface 1810.

FIG. 18O also depicts a scenario 1872, in which the two users 1806b (“JANE”), 1806a (“JOHN”) from FIGS. 18D-18H are in the same room as computer system 1600. As was the case in FIGS. 18D-18H, user 1806a is wearing an electronic device 800a (e.g., device 800) (e.g., a watch) and user 1806b is wearing an electronic device 800b (e.g., device 800) (e.g., a watch). However, in scenario 1872, only user 1806b’s electronic device 800b has been previously paired with computer system 1600. User 1806a’s electronic device 800a has never been previously paired with computer system 1600. Computer system 1600 determines that there is only one device (e.g., devices of a particular type (e.g., one watch)) that is within a predefined proximity of computer system 1600 (e.g., in the same room, within a threshold distance, etc.) and has previously been paired with computer system 1600.

In home screen user interface 1810 as depicted in FIG. 18O, the focus is on application representation 1812a that corresponds to a fitness application. While computer system 1600 causes display, via display 1601, of home screen user interface 1810 with the focus on application representation 1812a, remote control 1602 detects activation of selection region 1604a via button press input 1874 corresponding to selection of application representation 1812a, and transmits an indication of the input to computer system 1600. Computer system 1600 receives, from remote control 1602, the indication of input 1874 corresponding to selection of application representation 1812a.

At FIG. 18P, in response to detecting (e.g., receiving the indication of) input 1874, and based on (e.g., in response to, in accordance with) the determination that there is only one previously-paired device 800d that is within the predefined proximity of computer system 1600, computer system 1600 causes display 1601 to replace display of home user interface 1810 with workout user interface 1822 which, as

135

described above, is a personalized workout user interface that is associated with electronic device **800b** and/or user **1806b**. Similarly, in response to detecting (e.g., receiving the indication of) input **1874**, and based on (e.g., in response to, in accordance with) the determination that there is only one previously-paired device **800d** that is within the predefined proximity of computer system **1600**, computer system **1600** causes electronic device **800b** to display a notification and output a haptic output indicating that electronic device **800b** is now paired to computer system **1600**.

At FIG. **18P**, the focus is on option **1876** that corresponds to an avatar/image representation of user **1806b**. While computer system **1600** causes display, via display **1601**, of workout user interface **1822** with the focus on option **1876**, remote control **1602** detects activation of selection region **1604a** via button press input **1878** corresponding to selection of option **1876**, and transmits an indication of the input to computer system **1600**. Computer system **1600** receives, from remote control **1602**, the indication of input **1878** corresponding to selection of option **1876**.

At FIG. **18Q**, in response to detecting (e.g., receiving the indication of) input **1878**, computer system **1600** causes display **1601** to display a sign-out option **1880**. At FIG. **18Q**, the focus is on option **1880**. While computer system **1600** causes display, via display **1601**, of workout user interface **1822** with the focus on option **1880**, remote control **1602** detects activation of selection region **1604a** via button press input **1882** corresponding to selection of option **1880**, and transmits an indication of the input to computer system **1600**. Computer system **1600** receives, from remote control **1602**, the indication of input **1882** corresponding to selection of option **1880**.

At FIG. **18R**, in response to detecting (e.g., receiving the indication of) input **1882**, computer system **1600** causes display **1601** to replace display of workout user interface **1822** with disambiguation user interface **1884**. Disambiguation user interface **1884** includes two selectable options **1884a**, **1884b**. Option **1884a** is associated with (e.g., corresponds to) user **1806b** and device **800b**, and is presented based on a determination that device **800b** is within the predefined proximity of computer system **1600**. Option **1884a**, when selected, presents workout user interface **1822** associated with user **1806b** and device **800b**. Option **1884b** is selectable to pair a new device that has not been previously paired with computer system **1600**. In some embodiments, if additional previously-paired electronic devices of a particular type are determined to be within the predefined proximity of computer system **1600**, disambiguation user interface **1884** could include additional selectable options for each of the detected devices.

In FIG. **18R**, the focus is on option **1884b**, and remote control **1602** detects activation of selection region **1604a** via button press input **1886** corresponding to selection of option **1884b**. Remote control **1602** transmits an indication of the input to computer system **1600**. Computer system **1600** receives, from remote control **1602**, the indication of input **1886**.

At FIG. **18S**, in response to detecting (e.g., receiving the indication of) input **1886**, computer system **1600** causes display **1601** to replace display of disambiguation user interface **1884** with status user interface **1888**. Status user interface **1888** instructs the user to open a fitness application on the new device (e.g., the new watch) that the user wishes to pair with computer system **1600**. User **1806a** wishes to pair device **800a** with computer system **1600**. In FIG. **18S**, device **800a** displays a home user interface **1885** comprising a plurality of application icons representing different appli-

136

cations installed on device **800a**. Device **800a** detects a user input **1887B** at a location corresponding to a fitness application icon **1887A**.

At FIG. **18T**, in response to input **1887B**, device **800a** replaces display of home user interface **1885** with pairing user interface **1889**. Pairing user interface **1889** includes an option **1891A**. While displaying pairing user interface **1889**, device **800a** detects a user input **1891B** at a location corresponding to option **1891A**.

At FIG. **18U**, in response to input **1891B**, device **800a** replaces display of pairing user interface **1889** with number pad **1870**, as was described above with reference to FIG. **18M**. Furthermore, in response to input **1891B** (e.g., in response to a communication from device **800a** indicating detection of input **1891B**), device **1600** replaces display of status user interface **1888** with user interface **1868**, which was described above with reference to FIG. **18M**. User interface **1868** displays a PIN number. User **1806a** can use the number pad **1870** to enter the PIN number shown in user interface **1868** to confirm his or her intention to pair device **800a** with computer system **1600**. In FIG. **18U**, device **800a** detects user input **1893** corresponding to entry of the number sequence "1 2 3 4", and transmits an indication of the input to computer system **1600**. Computer system **1600** receives, from device **800c**, the indication of input **1874** corresponding to entry of the number sequence "1 2 3 4."

In FIG. **18V**, in response to detecting (e.g., receiving the indication of) input **1893**, computer system **1600** causes display **1601** to replace display of user interface **1868** with workout user interface **1840**. Workout user interface **1840** was described in greater detail with reference to FIG. **18H**, and represents a personalized workout user interface associated with device **800a** and/or user **1806a**. In the depicted embodiments, device **800a** is associated with a subscription account and a personalized workout user interface can be presented for device **800a** based on past workouts associated with device **800a** and/or user **1806a**. In other scenarios (e.g., in scenarios in which the device and/or user are not subscribed, or have not performed any past workouts), a different user interface can be presented (e.g., user interface **1850** of FIG. **18J**).

FIGS. **19A-19C** are a flow diagram illustrating a method for displaying workout information in accordance with some embodiments. Method **1900** is performed at a device (e.g., **100**, **300**, **500**, **600**, **800**, **1600**) with a display. Some operations in method **1900** are, optionally, combined, the orders of some operations are, optionally, changed, and some operations are, optionally, omitted.

In some embodiments, the electronic device (e.g., **600**, **800**, **1600**) is a computer system. The computer system is optionally in communication (e.g., wired communication, wireless communication) with a display generation component and with one or more input devices. The display generation component is configured to provide visual output, such as display via a CRT display, display via an LED display, or display via image projection. In some embodiments, the display generation component is integrated with the computer system. In some embodiments, the display generation component is separate from the computer system. The one or more input devices are configured to receive input, such as a touch-sensitive surface receiving user input. In some embodiments, the one or more input devices are integrated with the computer system. In some embodiments, the one or more input devices are separate from the computer system. Thus, the computer system can transmit, via a wired or wireless connection, data (e.g., image data or video data) to an integrated or external display generation com-

137

ponent to visually produce the content (e.g., using a display device) and can receive, a wired or wireless connection, input from the one or more input devices.

As described below, method **1900** provides an intuitive way for displaying workout information. The method reduces the cognitive burden on a user for displaying workout information, thereby creating a more efficient human-machine interface. For battery-operated computing devices, enabling a user to display camera views faster and more efficiently conserves power and increases the time between battery charges.

Computer system **1600** (e.g., an electronic device, a set top device; a digital media player) that is in communication with (e.g., wired communication, wireless communication) a display generation component and one or more input devices detects (**1902**), via the one or more input devices, a user input (e.g., **1814**, **1829**, **1848**) corresponding to a request to display a workout user interface.

In response to the request to display the workout user interface (**1906**), and in accordance with a determination that the computer system meets proximity criteria relative to (e.g., is determined to be in approximately the same location or within a threshold distance based on connection signal strength, based on connection to a common device associated with the location, based on self-identification as being located at the approximately the same location or within a threshold distance, based on a determination that the computer system is within a predetermined distance of the external electronic device) a single external electronic device of a first type (**1906**) (e.g., **800a** in FIG. **18A**, **800c** in FIG. **18I**) (e.g., not more than one external electronic device of the first type) (e.g., a wearable electronic device (e.g., a watch)) (in some embodiments, in accordance with a determination that the computer system is in the same location with a single previously-paired external electronic device of a first type (e.g., external electronic devices that have previously been paired with the computer system)), computer system **1600** initiates (**1908**) a process to display, via the display generation component, a first workout suggestion user interface (e.g., **1822**) (e.g., a personalized workout suggestion user interface (e.g., workout user interface **612** of FIGS. **6C-6M**)) (in some embodiments, without displaying or causing display of a disambiguation user interface), wherein the first workout suggestion user interface displays one or more workout suggestions (e.g., **1824a-1824d**) associated with the single external electronic device (e.g., associated with a user associated with the external electronic device). In some embodiments, a workout suggestion corresponds to (e.g., represents) a workout (e.g., audio and/or video content that guides a user to perform a physical activity). In some embodiments, selecting a workout suggestion initiates a process for playback of a workout corresponding to the workout suggestion. Displaying one or more workout suggestions associated with the single electronic device in accordance with a determination that the computer system meets proximity criteria relative to the single electronic device enables a user to quickly gain access to a particular workout, thereby reducing the number of inputs needed for selecting a workout. Reducing the number of inputs needed to perform an operation enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

138

In response to the request to display the workout user interface (**1906**), and in accordance with a determination that the computer system meets proximity criteria relative to at least a first external electronic device of the first type and a second external electronic device of the first type (**1910**) (e.g., **800a**, **800b** in FIG. **18D**) (e.g., a first wearable electronic device and a second wearable electronic device (e.g., a first watch and a second watch)) (in some embodiments, in accordance with a determination that the computer system is in the same location with at least a first previously-paired external electronic device of the first type and a second previously-paired external electronic device of the first type (e.g., external electronic devices that have previously been paired with the computer system)), computer system **1600** initiates (**1912**) a process to display, via the display generation component, a disambiguation user interface (e.g., **1830**) different from the first workout suggestion user interface (in some embodiments, without displaying or causing display of the first workout suggestion user interface). The disambiguation user interface includes: a first selectable user interface object (e.g., **1832a**) that, when selected, initiates a process for displaying a second workout suggestion user interface (e.g., **1840**) associated with the first external electronic device (e.g., **800b**) (e.g., a personalized workout suggestion user interface associated with the first external electronic device), wherein the second workout suggestion user interface displays one or more workout suggestions (e.g., **1842a-1842d**) associated with the first external electronic device (e.g., associated with a user associated with the first external electronic device) (**1914**), and a second selectable user interface object (**1832b**) that, when selected, initiates a process for displaying a third workout suggestion user interface (e.g., **1822**, FIG. **18F**) different from the second workout suggestion user interface and associated with the second external electronic device (e.g., **800a**) (e.g., a personalized workout suggestion user interface associated with the second external electronic device), wherein the third workout suggestion user interface displays one or more workout suggestions (e.g., **1824a-1824d**) associated with the second external electronic device (**1916**) (e.g., associated with a user associated with the second external electronic device). In some embodiments, the first workout suggestion user interface includes one or more workout suggestions that are not included in the second and/or third workout suggestion user interfaces. In some embodiments, the second workout suggestion user interface includes one or more workout suggestions that are not included in the first and/or third workout suggestion user interfaces. In some embodiments, the third workout suggestion user interface includes one or more workout suggestions that are not included in the first and/or second workout suggestion user interfaces. Displaying a disambiguation user interface in accordance with a determination that the computer system meets proximity criteria relative to multiple external electronic devices enables a user to quickly and efficiently identify a particular external electronic device and access workout suggestions associated with the particular external electronic device, thereby reducing the number of inputs needed for selecting a workout. Reducing the number of inputs needed to perform an operation enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, initiating the process to display the first workout suggestion user interface includes: in accordance with a determination that the single external electronic device is associated with an authorized user account (e.g., a user account that is registered for a workout service or workout application), computer system **1600** causes display, via the display generation component, of the first workout suggestion user interface (e.g., **1822**, FIG. **18C**) (e.g., a personalized workout suggestion user interface) (in some embodiments, without displaying or causing display of a disambiguation user interface), wherein the first workout suggestion user interface displays one or more workout suggestions associated with the authorized user account (In some embodiments, a workout suggestion corresponds to (e.g., represents) a workout (e.g., audio and/or video content that guides a user to perform a physical activity. In some embodiments, selecting a workout suggestion initiates a process for playback of a workout corresponding to the workout suggestion), and in accordance with a determination that the single external electronic device is not associated with an authorized user account, computer system **1600** causes display, via the display generation component, of an authorization user interface (e.g., **185**) that is different from the first workout suggestion user interface (e.g., a default landing page user interface associated with unregistered users (e.g., a user registration interface, a user login interface, a free-trial registration interface)). In some embodiments, the authorization interface includes a selectable user interface object that, when selected, initiates a process to authorize a user account associated with the single external electronic device. In some embodiments, after the user account is authorized, the first workout suggestion user interface is displayed. In some embodiments, the authorization user interface is displayed without displaying or causing display of the first workout suggestion user interface or the disambiguation user interface. Displaying one or more workout suggestions associated with the single electronic device in accordance with a determination that the single external electronic device is associated with an authorized user account enables a user to quickly gain access to a particular workout, thereby reducing the number of inputs needed for selecting a workout. Displaying an authorization user interface in accordance with a determination that the single external electronic device is not associated with an authorized user account enhances security and privacy. Reducing the number of inputs needed to perform an operation and providing improved security enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, while the authorization user interface is displayed on the display device, computer system **1600** detects a second user input (e.g., **1858**) corresponding to a request to authorize a user account associated with the single external electronic device (e.g., authorize the user account to access a workout application and/or workout suggestions) (e.g., selection of an option or affordance to start a free trial or to register a user account).

In some embodiments, in response to detecting the second user input (e.g., **1858**), computer system **1600** initiates a process to display a notification on the single external electronic device, wherein the notification requests authentication of the user intent to authorize the user account associated with the single external electronic device (e.g.,

FIG. **18M**) (e.g., a notification requesting a user input on the single external electronic device to authenticate user intent to authorize the user account associated with the single external electronic device). Displaying the notification on the single external electronic device requesting authentication of the user intent to authorize the user account associated with the single external device provides the user with feedback about the current state of the device (e.g., that a user input corresponding to a request to authorize the user account associated with the single external electronic device has been received). Providing improved feedback to the user enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, initiating the process to display the first workout suggestion user interface includes (**1918**): prior to display of the first workout suggestion user interface, computer system **1600** causes (**1920**) the single external electronic device to output a notification (e.g., haptic, visual) (e.g., **1815a**, FIG. **18B**, FIG. **18M**) requesting user confirmation to pair the single external electronic device with the computer system (e.g., requesting that a user perform a gesture on the single external electronic device (e.g., entering a PIN number, tapping on an option indicative of a user intent to pair the single external electronic device with the computer system). In some embodiments, the first workout suggestion user interface is displayed after confirmation is received to pair the single external electronic device with the computer system. In some embodiments, the single external electronic device is uniquely paired with the computer system. For example, the single external electronic device has a special relationship with the computer system in that the single external electronic device is only paired with the computer system and is not paired with any other devices. In some embodiments, pairing two electronic devices includes establishing a means of communication between the two devices. The means of communication may include those described in U.S. Patent Publication No. 2015/0350865, "Predefined Wireless Pairing," filed Sep. 2, 2014 and published Dec. 3, 2015, which is incorporated in this disclosure by reference. Once the devices are paired, they may exchange data including data that may be used for device configuration. Pairing may also allow a device to be configured using a user interface provided by the other paired device. For example, recent advances in computer technology have enabled manufacturers to produce powerful computing devices in relatively small form factors. However, small devices may be unable to provide a user interface large enough to be suitable for user configuration. Instead, the device being configured may be paired with an external device with a larger user interface that provides the ability to set parameters on the device being configured. Such techniques can reduce the time and effort required to begin using the device and can make the device more useful to the user. In some embodiments, pairing two electronic devices includes registering the two electronic devices with one another for future wireless communications. For example, when a first device is paired with a second device, the second device may be registered (e.g., on the first device) as a paired device, and/or the first device may be registered (e.g., on the second device) as a paired device). In some embodiments, if two devices are paired with one another, the two devices are registered with one another and can perform two-way wire-

less communication. In some embodiments, wireless communication, for purposes of a paired relationship, occurs over a peer-to-peer wireless communication protocol such as Bluetooth and/or Bluetooth Low Energy (BTLE). In some embodiments, the wireless communication uses more than one wireless communication protocol. For example, WiFi may be used in addition to BTLE. In these embodiments, an initial communication between two devices may occur over a lower powered protocol, such as BTLE, even if the protocol yields a slower data transfer speed. Subsequent communications may occur over a secondary network that is relatively faster, such as WiFi. Additional exemplary techniques related to initiating and operating in a paired relationship are described in the following applications: U.S. Patent Publication No. 2015/035081 titled "Companion application for Activity Cooperation," filed Dec. 30, 2014 and published Dec. 3, 2015; U.S. Patent Publication No. 2015/0350865 titled "Predefined Wireless Pairing," filed Sep. 2, 2014 and published Dec. 3, 2015; and U.S. Patent Publication No. 2016/0062572 titled "Reduced-size Configuration Interface," filed Aug. 28, 2015 and published Mar. 3, 2016. Outputting a notification on the single external electronic device requesting user confirmation to pair the single external electronic device with the computer system provides the user with feedback about the current state of the device (e.g., that the computer system is attempting to pair with the single external electronic device). Providing improved feedback to the user enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, user confirmation to pair the single external electronic device with the computer system includes user input of a personal identification number (1922) (e.g., FIG. 18M). In some embodiments, a PIN number is displayed for the user (e.g., on the display generation component, on the computer system, and/or on the single external electronic device), and user confirmation to pair the single external electronic device with the computer system is determined based on receiving a user input corresponding to the PIN number (e.g., user input of the PIN number on the display generation component, on the computer system, and/or on the single external electronic device) (e.g., the single external electronic device is paired with the computer system and/or the first workout suggestion user interface is displayed on the display generation component in accordance with a determination that the user has entered the PIN number (e.g., on the display generation component, on the computer system, and/or on the single external electronic device)). Receiving user confirmation to pair the single external electronic device via user input of a personal identification number enhances security. Providing improved security enhances the operability of the device and makes the user-device interface more efficient (e.g., by restricting unauthorized access) which, additionally, reduces power usage and improves battery life of the device by limiting the performance of restricted operations.

In some embodiments, user confirmation to pair the single external electronic device with the computer system includes a user input on a selectable user interface object (1924) (e.g., a tap gesture) (e.g., FIG. 18B). In some embodiments, in accordance with a determination that the single external electronic device has been previously paired with the computer system, user confirmation to pair the

single external electronic device with the computer system is determined based on receiving a first user gesture on the single external electronic device (e.g., a tap gesture), and in accordance with a determination that the single external electronic device has not been previously paired with the computer system, user confirmation to pair the single external electronic device with the computer system is determined based on receiving a second user gesture different from the first user gesture on the single external electronic device (e.g., entry of a PIN number)). Receiving user confirmation to pair the single external electronic device via a user input on a selectable user interface object enhances security. Providing improved security enhances the operability of the device and makes the user-device interface more efficient (e.g., by restricting unauthorized access) which, additionally, reduces power usage and improves battery life of the device by limiting the performance of restricted operations.

In some embodiments, initiating the process to display the first workout suggestion user interface comprises causing display, via the display generation component, of the first workout suggestion user interface (e.g., 1822) without user input (e.g., the first workout suggestion user interface is displayed on the display generation component automatically once the determination is made that the computer system meets proximity criteria relative to (e.g., is in the same location with) the single external electronic device of the first type). In some embodiments, initiating the process to display the disambiguation user interface includes causing display, via the display generation component, of the disambiguation user interface (e.g., 1830) without user input (e.g., the disambiguation user interface is displayed on the display generation component automatically once the determination is made that the computer system meets proximity criteria relative to (e.g., is in the same location with) the first external electronic device of the first type and the second external electronic device of the first type). Automatically displaying a first workout suggestions user interface or a disambiguation user interface without user input allows the user to quickly select a particular workout. Performing an operation when a set of conditions has been met without requiring further user input enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, initiating the process to display the first workout suggestion user interface includes (1918) causing (1926) the single external electronic device to generate a tactile output (e.g., a sequence of a number of individual tactile outputs) indicating that the single external electronic device is paired with the computer system (e.g., device 800a in FIG. 18F, device 800b in FIG. 18H). Causing the single external electronic device to generate a tactile output indicating that the single external electronic device is paired with the computer system provides the user with feedback about the current state of the device (e.g., that the computer system is paired with the single external electronic device). Providing improved feedback to the user enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, in response to the request to display the workout user interface and in accordance with a determination that the computer system does not satisfy the proximity criteria relative to (e.g., is determined not to be in approximately the same location or within a threshold distance based on connection signal strength, based on lack of connection to a common device associated with the location, based on self-identification as not being located at the approximately the same location or within a threshold distance, based on a determination that the computer system is not within a predetermined distance of any external electronic device) any external electronic device of the first type (e.g., a wearable electronic device (e.g., a watch)) (in some embodiments, in accordance with a determination that the computer system is not in the same location with any previously-paired external electronic device of the first type), computer system **1600** initiates a process to display, via the display generation component, an application demonstration user interface (e.g., **1850**) different from each of the first workout suggestion user interface (e.g., **1822** in FIG. **18C**), the disambiguation user interface (e.g., **1830**), the second workout suggestion user interface (e.g., **1822** in FIG. **18F**), and the third workout suggestion user interface (e.g., **1840**) (in some embodiments, without displaying or causing display of the first workout suggestion user interface, the disambiguation user interface, the second workout suggestion user interface, or the third workout suggestion user interface). Initiating the process to display the application demonstration user interface in accordance with a determination that the computer system does not satisfy proximity criteria relative to any external electronic device of the first type provides the user with feedback about the current state of the device (e.g., that the computer system does not satisfy proximity criteria relative to any external electronic device of the first type). Providing improved feedback to the user enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, in response to the request to display the workout user interface and in accordance with a determination that the computer system does not satisfy the proximity criteria relative to (e.g., is determined not to be in approximately the same location or within a threshold distance based on connection signal strength, based on lack of connection to a common device associated with the location, based on self-identification as not being located at the approximately the same location or within a threshold distance, based on a determination that the computer system is not within a predetermined distance of any previously-paired external electronic device) any previously-paired external electronic device of the first type (e.g., a wearable electronic device (e.g., a watch)), computer system **1600** initiates a process to display, via the display generation component, a device pairing user interface (e.g., **1866**, **1868**) that includes a prompt to pair an external electronic device of the first type (in some embodiments, without displaying or causing display of the first workout suggestion user interface, the disambiguation user interface, the second workout suggestion user interface, or the third workout suggestion user interface). In some embodiments, the device pairing user interface is different from the first workout suggestion user interface, the disambiguation user interface, the second workout suggestion user interface, and the third

workout suggestion user interface. In some embodiments, the device pairing user interface comprises one or more instructions for a user to pair an external electronic device of the first type with the computer system. Initiating the process to display the device pairing user interface in accordance with a determination that the computer system does not satisfy proximity criteria relative to any previously-paired external electronic device of the first type provides the user with feedback about the current state of the device (e.g., that the computer system does not satisfy proximity criteria relative to any previously-paired external electronic device of the first type). Providing improved feedback to the user enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, the device pairing user interface (e.g., **1866**) comprises one or more instructions for a user to pair an external electronic device of the first type (e.g., a wearable electronic device (e.g., a watch)) with the computer system. In some embodiments, the one or more instructions include an instruction to open an application (e.g., a specific application; an application of a first type; a workout application) (e.g., "OPEN FITNESS APP ON WATCH" in FIG. **18L**) on an external electronic device of the first type. Displaying instructions for the user to pair an external device of the first type with the computer system allows a user to more quickly and efficiently pair an external device with the computer system, thereby reducing the number of inputs required to pair the external device with the computer system. Reducing the number of inputs needed to perform an operation enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, the disambiguation user interface (e.g., **1830**) further includes a third selectable user interface object (e.g., **1832c**) that, when selected, initiates a process for pairing a previously-unpaired external electronic device of the first type with the computer system. Displaying a selectable user interface object that, when selected, initiates a process for pairing a previously-unpaired external electronic device with the computer system enables a user to more efficiently pair an external electronic device with the computer system, thereby reducing the number of inputs required to pair the external device with the computer system. Reducing the number of inputs needed to perform an operation enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, the first selectable user interface object (e.g., **1832a**), when selected, causes the first external electronic device to output a notification (e.g., visual, haptic) (e.g., on the first external electronic device) (e.g., **1836**, device **800a** in FIG. **18F**, **1844**, device **800b** in FIG. **18H**) indicating that the first external electronic device has been selected.

145

In some embodiments, the second selectable user interface object, when selected, causes the second external electronic device to output a notification (e.g., visual, haptic) (e.g., on the second external electronic device) (e.g., **1836**, device **800a** in FIG. **18F**, **1844**, device **800b** in FIG. **18H**) indicating that the second external electronic device has been selected. Causing the second external electronic device to output a notification indicating that the second external electronic device has been selected provides the user with feedback about the current state of the device (e.g., that the computer system has received a user input selecting the second external electronic device). Providing improved feedback to the user enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, the first workout suggestion user interface (e.g., **1822**) includes one or more workout suggestions (e.g., **1824a-1824d**) associated with the single external electronic device (e.g., **800a**) based on user information (e.g., locally stored information) received from the single external electronic device (e.g., based on user health application information stored locally on the single external electronic device). Suggesting a workout based on user information received from the single external electronic device improves the quality of suggestions to the user, thereby providing a means for selection by the user. Otherwise, additional inputs would be required to further locate a particular workout. Reducing the number of inputs needed to perform an operation enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, after initiating the process to display, via the display generation component, the first workout suggestion user interface (e.g., **1822**), the electronic device displays, via the display generation component, the first workout suggestion user interface (e.g., **1822**) associated with the first external electronic device (e.g., **800b**) (e.g., associated with a user associated with the first external electronic device). In some embodiments, while displaying the first workout suggestion user interface (e.g., **1822**), the electronic device detects one or more user inputs (e.g., **1878**, **1882**) corresponding to a request to sign out of the first workout suggestion user interface (e.g., a request to sign out of an account associated with the user associated with the first external electronic device). In some embodiments, in response to detecting the one or more user inputs corresponding to the request to sign out of the first workout suggestion user interface, the electronic device (e.g., **1600**) displays a second disambiguation user interface (e.g., **1884**) different from the first workout suggestion user interface (e.g., **1822**) and the disambiguation user interface (e.g., **1830**) (e.g., without displaying the first workout suggestion user interface) (in some embodiments, replacing display of the first workout suggestion user interface with the second disambiguation user interface), wherein the second disambiguation user interface includes: a fourth selectable user interface object (e.g., **1884a**) that, when selected, initiates a process for displaying the first workout suggestion user interface, and a fifth selectable user interface object (e.g.,

146

1884b) that, when selected, initiates a process for pairing a previously-unpaired external electronic device of the first type with the computer system. Displaying a selectable user interface object that, when selected, initiates a process for pairing a previously-unpaired external electronic device with the computer system enables a user to more efficiently pair an external electronic device with the computer system, thereby reducing the number of inputs required to pair the external device with the computer system. Reducing the number of inputs needed to perform an operation enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, in accordance with a determination that the computer system (e.g., **1600**) meets proximity criteria relative to (e.g., is determined to be in approximately the same location or within a threshold distance based on connection signal strength, based on connection to a common device associated with the location, based on self-identification as being located at the approximately the same location or within a threshold distance, based on a determination that the computer system is within a predetermined distance of the external electronic device) one or more additional external electronic devices of the first type (e.g., wearable electronic devices (e.g., watches)) (in some embodiments, in accordance with a determination that the computer system is in the same location with one or more additional previously-paired external electronic devices of the first type (e.g., external electronic devices that have previously been paired with the computer system)), the second disambiguation user interface (e.g., **1884**) further comprises, for each external electronic device of the one or more additional external electronic device of the first type, a respective selectable user interface object that, when selected, initiates a process for displaying a workout suggestion user interface associated with the external electronic device. Automatically causing display of additional selectable user interface objects in a disambiguation user interface in accordance with a determination that the computer system meets proximity criteria relative to one or more additional external electronic devices allows a user to access those selectable user interface objects without additional user input. Performing an optimized operation when a set of conditions has been met without requiring further user input enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, while displaying the second disambiguation user interface (e.g., **1884**), the electronic device (e.g., **1600**) detects, via the one or more input devices, one or more user inputs (e.g., **1886**) corresponding to selection of the fifth selectable user interface object (e.g., **1884b**); in response to detecting the one or more user inputs corresponding to selection of the fifth selectable user interface object, displaying one or more instructions (e.g., **1888**) for a user to pair an external electronic device of the first type (e.g., a wearable electronic device (e.g., a watch)) with the computer system, wherein the one or more instructions include an instruction to open an application (e.g., a specific

application; an application of a first type; a workout application) on an external electronic device of the first type. Displaying instructions for the user to pair an external device of the first type with the computer system allows a user to more quickly and efficiently pair an external device with the computer system, thereby reducing the number of inputs required to pair the external device with the computer system. Reducing the number of inputs needed to perform an operation enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, while displaying the second disambiguation user interface (e.g., **1884**), the electronic device (e.g., **1600**) determines that the computer system meets proximity criteria relative to (e.g., is determined to be in approximately the same location or within a threshold distance based on connection signal strength, based on connection to a common device associated with the location, based on self-identification as being located at the approximately the same location or within a threshold distance, based on a determination that the computer system is within a predetermined distance of the external electronic device) a third external electronic device of the first type (e.g., **800a**) (e.g., a third wearable electronic device (e.g., a watch)) (in some embodiments, in accordance with a determination that the computer system is in the same location with at least the third external electronic device of the first type), wherein opening the application on the third external electronic device causes display, on the third external electronic device (e.g., on a display built into the third external electronic device, on a display in communication with the third external electronic device), of a selectable user interface object (e.g., **1891A**) that, when selected, initiates a process for pairing the third external electronic device with the computer system. Displaying an affordance for pairing an external device of the first type with the computer system allows a user to more quickly and efficiently pair an external device with the computer system, thereby reducing the number of inputs required to pair the external device with the computer system. Reducing the number of inputs needed to perform an operation enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, while displaying the second disambiguation user interface (e.g., **1884**), and in accordance with a determination that the computer system meets proximity criteria relative to (e.g., is determined to be in approximately the same location or within a threshold distance based on connection signal strength, based on connection to a common device associated with the location, based on self-identification as being located at the approximately the same location or within a threshold distance, based on a determination that the computer system is within a predetermined distance of the external electronic device) a third external electronic device of the first type (e.g., **800a**) (e.g., a third wearable electronic device (e.g., a watch)) (in some embodiments, in accordance with a determination that the computer system is in the same location with at least the third external electronic device of the first type), the elec-

tronic device causes the third external electronic device to display (e.g., on a display built into the third external electronic device, on a display in communication with the third external electronic device), within the application, a selectable user interface object (e.g., **1891A**) that, when selected, initiates a process for pairing the third external electronic device with the computer system. Causing a selectable user interface object to be displayed in accordance with a determination that the computer system meets proximity criteria relative to the third external electronic device provides the user with feedback about the current state of the device (e.g., that the computer system meets proximity criteria relative to the third external electronic device). Providing improved feedback to the user enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

In some embodiments, while displaying the second disambiguation user interface (e.g., **1884**), the electronic device detects one or more user inputs (e.g., **1886**) corresponding to selection of the fifth selectable user interface object (e.g., **1884b**). After detecting the one or more user inputs corresponding to selection of the fifth selectable user interface object, the electronic device determines that the computer system has been successfully paired with a third external electronic device of the first type (e.g., FIG. **18V**). In response to determining that the computer system has been successfully paired with the third external electronic device of the first type, the electronic device initiates a process to display, via the display generation component, a third workout suggestion user interface (e.g., **1840**) (e.g., a personalized workout suggestion user interface), wherein the third workout suggestion user interface displays one or more workout suggestions associated with the third external electronic device (e.g., associated with a user associated with the third external electronic device). In some embodiments, a workout suggestion corresponds to (e.g., represents) a workout (e.g., audio and/or video content that guides a user to perform a physical activity). In some embodiments, selecting a workout suggestion initiates a process for playback of a workout corresponding to the workout suggestion. Automatically causing a third workout suggestion user interface to be displayed in accordance with a determination that the computer system has been successfully paired with the third external electronic device provides the user with feedback about the current state of the device (e.g., that the computer system has been successfully paired with the third external electronic device). Providing improved feedback to the user enhances the operability of the device and makes the user-device interface more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) which, additionally, reduces power usage and improves battery life of the device by enabling the user to use the device more quickly and efficiently.

Note that details of the processes described above with respect to method **1900** (e.g., FIGS. **19A-19C**) are also applicable in an analogous manner to the methods described above. For example, method **1700** optionally includes one or more of the characteristics of the various methods described above with reference to method **1900**. For example, the workout suggestion user interfaces as discussed above with respect to method **1900** may include various browsing and

filtering features, as set forth in method 1700. For brevity, these details are not repeated.

The foregoing description, for purpose of explanation, has been described with reference to specific embodiments. However, the illustrative discussions above are not intended to be exhaustive or to limit the invention to the precise forms disclosed. Many modifications and variations are possible in view of the above teachings. The embodiments were chosen and described in order to best explain the principles of the techniques and their practical applications. Others skilled in the art are thereby enabled to best utilize the techniques and various embodiments with various modifications as are suited to the particular use contemplated.

Although the disclosure and examples have been fully described with reference to the accompanying drawings, it is to be noted that various changes and modifications will become apparent to those skilled in the art. Such changes and modifications are to be understood as being included within the scope of the disclosure and examples as defined by the claims.

As described above, one aspect of the present technology is the gathering and use of data available from various sources to improve the delivery of workout content to a user. The present disclosure contemplates that in some instances, this gathered data may include personal information data that uniquely identifies or can be used to contact or locate a specific person. Such personal information data can include demographic data, location-based data, telephone numbers, email addresses, twitter IDs, home addresses, data or records relating to a user's health or level of fitness (e.g., vital signs measurements, medication information, exercise information), date of birth, or any other identifying or personal information.

The present disclosure recognizes that the use of such personal information data, in the present technology, can be used to the benefit of users. For example, the personal information data can be used to deliver better personalized workout suggestions to the user. Further, other uses for personal information data that benefit the user are also contemplated by the present disclosure. For instance, health and fitness data may be used to provide insights into a user's general wellness, or may be used as positive feedback to individuals using technology to pursue wellness goals.

The present disclosure contemplates that the entities responsible for the collection, analysis, disclosure, transfer, storage, or other use of such personal information data will comply with well-established privacy policies and/or privacy practices. In particular, such entities should implement and consistently use privacy policies and practices that are generally recognized as meeting or exceeding industry or governmental requirements for maintaining personal information data private and secure. Such policies should be easily accessible by users, and should be updated as the collection and/or use of data changes. Personal information from users should be collected for legitimate and reasonable uses of the entity and not shared or sold outside of those legitimate uses. Further, such collection/sharing should occur after receiving the informed consent of the users. Additionally, such entities should consider taking any needed steps for safeguarding and securing access to such personal information data and ensuring that others with access to the personal information data adhere to their privacy policies and procedures. Further, such entities can subject themselves to evaluation by third parties to certify their adherence to widely accepted privacy policies and practices. In addition, policies and practices should be adapted for the particular types of personal information data

being collected and/or accessed and adapted to applicable laws and standards, including jurisdiction-specific considerations. For instance, in the US, collection of or access to certain health data may be governed by federal and/or state laws, such as the Health Insurance Portability and Accountability Act (HIPAA); whereas health data in other countries may be subject to other regulations and policies and should be handled accordingly. Hence different privacy practices should be maintained for different personal data types in each country.

Despite the foregoing, the present disclosure also contemplates embodiments in which users selectively block the use of, or access to, personal information data. That is, the present disclosure contemplates that hardware and/or software elements can be provided to prevent or block access to such personal information data. For example, in the case of personalizing workout suggestions, the present technology can be configured to allow users to select to "opt in" or "opt out" of participation in the collection of personal information data during registration for services or anytime thereafter. In another example, users can select not to provide workout data for targeted workout suggestions. In yet another example, users can select to limit the length of time workout data is collected from the user. In addition to providing "opt in" and "opt out" options, the present disclosure contemplates providing notifications relating to the access or use of personal information. For instance, a user may be notified upon downloading an app that their personal information data will be accessed and then reminded again just before personal information data is accessed by the app.

Moreover, it is the intent of the present disclosure that personal information data should be managed and handled in a way to minimize risks of unintentional or unauthorized access or use. Risk can be minimized by limiting the collection of data and deleting data once it is no longer needed. In addition, and when applicable, including in certain health related applications, data de-identification can be used to protect a user's privacy. De-identification may be facilitated, when appropriate, by removing specific identifiers (e.g., date of birth, etc.), controlling the amount or specificity of data stored (e.g., collecting location data a city level rather than at an address level), controlling how data is stored (e.g., aggregating data across users), and/or other methods.

Therefore, although the present disclosure broadly covers use of personal information data to implement one or more various disclosed embodiments, the present disclosure also contemplates that the various embodiments can also be implemented without the need for accessing such personal information data. That is, the various embodiments of the present technology are not rendered inoperable due to the lack of all or a portion of such personal information data. For example, workout suggestions can be selected and delivered to users by inferring preferences based on non-personal information data or a bare minimum amount of personal information, such as the content being requested by the device associated with a user, other non-personal information available to the workout content services, or publicly available information.

What is claimed is:

1. A computer system that is in communication with a display generation component and one or more inputs devices, comprising:
 - one or more processors; and
 - memory storing one or more programs configured to be executed by the one or more processors, the one or more programs including instructions for:

151

causing recording of one or more physical activity metrics at a first frequency, wherein the physical activity metrics are recorded by one or more sensors that are monitoring an activity level of a user of the computer system;

while causing recording of the one or more physical activity metrics at the first frequency, displaying, via the display generation component, a workout user interface that includes a plurality of workout affordances, wherein the plurality of workout affordances includes a first workout affordance;

while displaying the first workout affordance from the plurality of workout affordances, detecting, via the one or more input devices, a set of one or more user inputs that includes an input directed to the first workout affordance; and

in response to detecting the set of one or more user inputs that includes the input directed to the first workout affordance:

causing audio playback of audio associated with a first type of workout at an audio output device that is in communication with the computer system, wherein the audio associated with the first workout affordance from the plurality of workout affordances corresponds to a predefined list of audio items that includes a first audio item and a second audio item, and wherein the predefined list of audio items was not selected by the user; and

causing recording of the one or more physical activity metrics at a second frequency greater than the first frequency.

2. The computer system of claim 1, wherein the audio associated with the first type of workout has a duration based on an amount of time required to complete the first type of workout.

3. The computer system of claim 1, wherein the audio associated with the first type of workout includes an audio indication configured to be output at the audio output device at a predefined time during playback of the audio associated with the first type of workout.

4. The computer system of claim 1, wherein the audio associated with the first type of workout corresponds to one or more visual content items that are configured to be output during playback of the audio associated with the first type of workout.

5. The computer system of claim 4, wherein the one or more programs further include instructions for:

while causing audio playback of the audio associated with the first type of workout:

displaying, via the display generation component, the one or more visual content items; and

generating tactile output, wherein the tactile output is provided concurrently with display of the one or more visual content items.

6. The computer system of claim 4, wherein the one or more programs further include instructions for:

after completion of the first type of workout, displaying, via the display generation component, a first workout summary user interface that includes the one or more visual content items configured to be output during playback of the audio associated with the first type of workout.

7. The computer system of claim 4, wherein:

each visual content item of the one or more visual content items is configured to be output at a respective predetermined time during playback of the audio associated with the first type of workout, including a first visual

152

content item configured to be output at a first predetermined time during playback of the audio associated with the first type of workout; and

the one or more programs further include instructions for:

displaying, via the display generation component, a workout summary user interface that includes one or more graphical representations of the first type of workout, wherein:

in accordance with a determination that the first visual content item was output during playback of the audio associated with the first type of workout, the workout summary user interface includes the first visual content item, and

in accordance with a determination that the first visual content item was not output during playback of the audio associated with the first type of workout, the workout summary user interface does not include the first visual content item.

8. The computer system of claim 1, wherein the one or more programs further include instructions for:

in accordance with a determination that audio playback of the audio associated with the first type of workout has completed, causing, at the audio output device, audio playback of the predefined list of audio items that includes the first audio item and the second audio item.

9. The computer system of claim 1, wherein the one or more programs further include instructions for:

in response to detecting the set of one or more user inputs that includes the input directed to the first workout affordance, displaying, via the display generation component, a first set of playback controls for modifying the audio playback of the audio associated with the first type of workout; and

in response to causing audio playback of the predefined list of audio items, displaying, via the display generation component, a second set of playback controls for modifying audio playback of the predefined list of audio items, wherein the second set of playback controls is different than the first set of playback controls.

10. The computer system of claim 1, wherein the one or more programs further include instructions for:

after audio playback of the audio associated with the first type of workout has completed, causing, at the audio output device, audio playback of the first audio item of the predefined list of audio items;

after causing the audio playback of the first audio item, detecting one or more user inputs corresponding to the first audio item; and

in response to detecting the one or more user inputs corresponding to the first audio item, performing an operation for the first audio item based on the detected one or more user inputs without performing the operation for the second audio item.

11. The computer system of claim 1, wherein the one or more programs further include instructions for:

in response to detecting the set of one or more user inputs that includes the input directed to the first workout affordance:

displaying, via the display generation component, a workout user interface comprising a playback progress indicator, wherein the playback progress indicator visually indicates progress of playback of audio content, wherein the audio content includes the audio associated with the first type of workout and the predefined list of audio items.

153

12. The computer system of claim 1, wherein:
the audio associated with the first type of workout corresponds to a predefined set of one or more physical locations, and
the audio associated with the first type of workout corresponds to one or more visual content items that are configured to be output during playback of the audio associated with the first type of workout.

13. The computer system of claim 1, wherein the one or more programs further include instructions for:
after completion of the first type of workout, displaying, via the display generation component, a second workout summary user interface that includes one or more graphical representations of the first type of workout.

14. The computer system of claim 1, wherein:
the computer system is in communication with a first external device,
the first external device is configured to output a selectable user interface object for adding a new workout, and
the one or more programs further include instructions for:
in response to a determination that a sequence of one or more user inputs have been detected by the first external device corresponding to selection of the selectable user interface object for adding the new workout, initiating a process for adding the new workout to the computer system.

15. A non-transitory computer-readable storage medium storing one or more programs configured to be executed by one or more processors of a computer system that is in communication with a display generation component and one or more input devices, the one or more programs including instructions for:
causing recording of one or more physical activity metrics at a first frequency, wherein the physical activity metrics are recorded by one or more sensors that are monitoring an activity level of a user of the computer system;
while causing recording of the one or more physical activity metrics at the first frequency, displaying, via the display generation component, a workout user interface that includes a plurality of workout affordances, wherein the plurality of workout affordances includes a first workout affordance;
while displaying the first workout affordance from the plurality of workout affordances, detecting, via the one or more input devices, a set of one or more user inputs that includes an input directed to the first workout affordance;
in response to detecting the set of one or more user inputs that includes the input directed to the first workout affordance:
causing audio playback of audio associated with a first type of workout at an audio output device that is in communication with the computer system, wherein the audio associated with the first workout affordance from the plurality of workout affordances corresponds to a predefined list of audio items that includes a first audio item and a second audio item, and wherein the predefined list of audio items was not selected by the user; and
causing recording of the one or more physical activity metrics at a second frequency greater than the first frequency.

154

16. A method, comprising:
at a computer system that is in communication with a display generation component and one or more input devices:
causing recording of one or more physical activity metrics at a first frequency, wherein the physical activity metrics are recorded by one or more sensors that are monitoring an activity level of a user of the computer system;
while causing recording of the one or more physical activity metrics at the first frequency, displaying, via the display generation component, a workout user interface that includes a plurality of workout affordances, wherein the plurality of workout affordances includes a first workout affordance;
while displaying the first workout affordance from the plurality of workout affordances, detecting, via the one or more input devices, a set of one or more user inputs that includes an input directed to the first workout affordance; and
in response to detecting the set of one or more user inputs that includes the input directed to the first workout affordance:
causing audio playback of audio associated with a first type of workout at an audio output device that is in communication with the computer system, wherein the audio associated with the first workout affordance from the plurality of workout affordances corresponds to a predefined list of audio items that includes a first audio item and a second audio item, and wherein the predefined list of audio items was not selected by the user; and
causing recording of the one or more physical activity metrics at a second frequency greater than the first frequency.

17. The non-transitory computer-readable storage medium of claim 15, wherein the audio associated with the first type of workout has a duration based on an amount of time required to complete the first type of workout.

18. The non-transitory computer-readable storage medium of claim 15, wherein the audio associated with the first type of workout includes an audio indication configured to be output at the audio output device at a predefined time during playback of the audio associated with the first type of workout.

19. The non-transitory computer-readable storage medium of claim 15, wherein the audio associated with the first type of workout corresponds to one or more visual content items that are configured to be output during playback of the audio associated with the first type of workout.

20. The non-transitory computer-readable storage medium of claim 19, wherein the one or more programs further include instructions for:
while causing audio playback of the audio associated with the first type of workout:
displaying, via the display generation component, the one or more visual content items; and
generating tactile output, wherein the tactile output is provided concurrently with display of the one or more visual content items.

21. The non-transitory computer-readable storage medium of claim 19, wherein the one or more programs further include instructions for:
after completion of the first type of workout, displaying, via the display generation component, a first workout summary user interface that includes the one or more

155

visual content items configured to be output during playback of the audio associated with the first type of workout.

22. The non-transitory computer-readable storage medium of claim 19, wherein:

each visual content item of the one or more visual content items is configured to be output at a respective predetermined time during playback of the audio associated with the first type of workout, including a first visual content item configured to be output at a first predetermined time during playback of the audio associated with the first type of workout; and

the one or more programs further include instructions for:

displaying, via the display generation component, a workout summary user interface that includes one or more graphical representations of the first type of workout, wherein:

in accordance with a determination that the first visual content item was output during playback of the audio associated with the first type of workout, the workout summary user interface includes the first visual content item, and

in accordance with a determination that the first visual content item was not output during playback of the audio associated with the first type of workout, the workout summary user interface does not include the first visual content item.

23. The non-transitory computer-readable storage medium of claim 15, wherein the one or more programs further include instructions for:

in accordance with a determination that audio playback of the audio associated with the first type of workout has completed, causing, at the audio output device, audio playback of the predefined list of audio items that includes the first audio item and the second audio item.

24. The non-transitory computer-readable storage medium of claim 15, wherein the one or more programs further include instructions for:

in response to detecting the set of one or more user inputs that includes the input directed to the first workout affordance, displaying, via the display generation component, a first set of playback controls for modifying the audio playback of the audio associated with the first type of workout; and

in response to causing audio playback of the predefined list of audio items, displaying, via the display generation component, a second set of playback controls for modifying audio playback of the predefined list of audio items, wherein the second set of playback controls is different than the first set of playback controls.

25. The non-transitory computer-readable storage medium of claim 15, wherein the one or more programs further include instructions for:

after audio playback of the audio associated with the first type of workout has completed, causing, at the audio output device, audio playback of the first audio item of the predefined list of audio items;

after causing the audio playback of the first audio item, detecting one or more user inputs corresponding to the first audio item; and

in response to detecting the one or more user inputs corresponding to the first audio item, performing an operation for the first audio item based on the detected one or more user inputs without performing the operation for the second audio item.

156

26. The non-transitory computer-readable storage medium of claim 15, wherein the one or more programs further include instructions for:

in response to detecting the set of one or more user inputs that includes the input directed to the first workout affordance:

displaying, via the display generation component, a workout user interface comprising a playback progress indicator, wherein the playback progress indicator visually indicates progress of playback of audio content, wherein the audio content includes the audio associated with the first type of workout and the predefined list of audio items.

27. The non-transitory computer-readable storage medium of claim 15, wherein:

the audio associated with the first type of workout corresponds to a predefined set of one or more physical locations, and

the audio associated with the first type of workout corresponds to one or more visual content items that are configured to be output during playback of the audio associated with the first type of workout.

28. The non-transitory computer-readable storage medium of claim 15, wherein the one or more programs further include instructions for:

after completion of the first type of workout, displaying, via the display generation component, a second workout summary user interface that includes one or more graphical representations of the first type of workout.

29. The non-transitory computer-readable storage medium of claim 15, wherein:

the computer system is in communication with a first external device,

the first external device is configured to output a selectable user interface object for adding a new workout, and

the one or more programs further include instructions for:

in response to a determination that a sequence of one or more user inputs have been detected by the first external device corresponding to selection of the selectable user interface object for adding the new workout, initiating a process for adding the new workout to the computer system.

30. The method of claim 16, wherein the audio associated with the first type of workout has a duration based on an amount of time required to complete the first type of workout.

31. The method of claim 16, wherein the audio associated with the first type of workout includes an audio indication configured to be output at the audio output device at a predefined time during playback of the audio associated with the first type of workout.

32. The method of claim 16, wherein the audio associated with the first type of workout corresponds to one or more visual content items that are configured to be output during playback of the audio associated with the first type of workout.

33. The method of claim 32, further comprising: while causing audio playback of the audio associated with the first type of workout:

displaying, via the display generation component, the one or more visual content items; and

generating tactile output, wherein the tactile output is provided concurrently with display of the one or more visual content items.

157

34. The method of claim 32, further comprising:
after completion of the first type of workout, displaying,
via the display generation component, a first workout
summary user interface that includes the one or more
visual content items configured to be output during
5 playback of the audio associated with the first type of
workout.
35. The method of claim 32, wherein:
each visual content item of the one or more visual content
items is configured to be output at a respective prede-
termined time during playback of the audio associated
with the first type of workout, including a first visual
content item configured to be output at a first prede-
termined time during playback of the audio associated
15 with the first type of workout; and
the method further comprising:
displaying, via the display generation component, a
workout summary user interface that includes one or
more graphical representations of the first type of
20 workout, wherein:
in accordance with a determination that the first
visual content item was output during playback of
the audio associated with the first type of workout,
the workout summary user interface includes the
25 first visual content item, and
in accordance with a determination that the first
visual content item was not output during play-
back of the audio associated with the first type of
workout, the workout summary user interface
30 does not include the first visual content item.
36. The method of claim 16, further comprising:
in accordance with a determination that audio playback of
the audio associated with the first type of workout has
35 completed, causing, at the audio output device, audio
playback of the predefined list of audio items that
includes the first audio item and the second audio item.
37. The method of claim 16, further comprising:
in response to detecting the set of one or more user inputs
40 that includes the input directed to the first workout
affordance, displaying, via the display generation com-
ponent, a first set of playback controls for modifying
the audio playback of the audio associated with the first
type of workout; and
45 in response to causing audio playback of the predefined
list of audio items, displaying, via the display genera-
tion component, a second set of playback controls for
modifying audio playback of the predefined list of
audio items, wherein the second set of playback con-
trols is different than the first set of playback controls.

158

38. The method of claim 16, further comprising:
after audio playback of the audio associated with the first
type of workout has completed, causing, at the audio
output device, audio playback of the first audio item of
the predefined list of audio items;
after causing the audio playback of the first audio item,
detecting one or more user inputs corresponding to the
first audio item; and
in response to detecting the one or more user inputs
corresponding to the first audio item, performing an
operation for the first audio item based on the detected
one or more user inputs without performing the opera-
tion for the second audio item.
39. The method of claim 16, further comprising:
in response to detecting the set of one or more user inputs
that includes the input directed to the first workout
affordance:
displaying, via the display generation component, a
workout user interface comprising a playback prog-
ress indicator, wherein the playback progress indi-
cator visually indicates progress of playback of audio
content, wherein the audio content includes the audio
associated with the first type of workout and the
predefined list of audio items.
40. The method of claim 16, wherein:
the audio associated with the first type of workout corre-
sponds to a predefined set of one or more physical
locations, and
the audio associated with the first type of workout corre-
sponds to one or more visual content items that are
configured to be output during playback of the audio
associated with the first type of workout.
41. The method of claim 16, further comprising:
after completion of the first type of workout, displaying,
via the display generation component, a second work-
out summary user interface that includes one or more
graphical representations of the first type of workout.
42. The method of claim 16, wherein:
the computer system is in communication with a first
external device,
the first external device is configured to output a select-
able user interface object for adding a new workout,
and
the method further comprising:
in response to a determination that a sequence of one or
more user inputs have been detected by the first
external device corresponding to selection of the
selectable user interface object for adding the new
workout, initiating a process for adding the new
workout to the computer system.

* * * * *