

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12408584
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Xu; Haishen et al.

Dual blade assembly for a lawn mower

Abstract

A lawn mower includes a blade assembly configured to perform a cutting function, a deck formed with an accommodation space for accommodating at least a portion of the blade assembly, a motor configured to drive the blade assembly to rotate about a rotation axis, and a battery pack configured to power the motor. The blade assembly includes a first cutting portion configured to cut grass and a second cutting portion configured to cut grass. In the direction parallel to the rotation axis, the second cutting portion is located below the first cutting portion. The battery pack includes a battery pack housing and battery cells provided in the battery pack housing.

Inventors: Xu; Haishen (Nanjing, CN), Yamaoka; Toshinari (Nanjing, CN), Yang; Jian (Nanjing, CN)

Applicant: Nanjing Chervon Industry Co., Ltd. (Nanjing, CN)

Family ID: 74668049

Assignee: Nanjing Chervon Industry Co., Ltd. (Nanjing, CN)

Appl. No.: 17/573153

Filed: January 11, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20220124976 A1	Apr. 28, 2022

Foreign Application Priority Data

CN	201821584956.0	Sep. 27, 2018
CN	201821889111.2	Nov. 15, 2018
CN	201910312144.3	Apr. 18, 2019
CN	201920533524.5	Apr. 18, 2019
CN	201910576318.7	Jun. 28, 2019
CN	201921545742.7	Sep. 17, 2019

Related U.S. Application Data

continuation parent-doc US 17236239 20210421 US 11246260 child-doc US 17573153
continuation parent-doc US 17164479 20210201 US 11122737 20210921 child-doc US 17236239
continuation parent-doc WO PCT/CN2019/107650 20190925 PENDING child-doc US 17164479

Publication Classification

Int. Cl.: **A01D34/73** (20060101); **A01D34/68** (20060101); **A01D34/685** (20060101); **A01D34/78** (20060101); A01D34/71 (20060101); A01D34/82 (20060101); A01D101/00 (20060101)

U.S. Cl.:

CPC **A01D34/733** (20130101); **A01D34/6806** (20130101); **A01D34/685** (20130101); **A01D34/73** (20130101); **A01D34/78** (20130101); A01D34/71 (20130101); A01D34/82 (20130101); A01D2101/00 (20130101)

Field of Classification Search

CPC: A01D (34/733); A01D (34/6806); A01D (34/78); A01D (34/73); A01D (34/685); A01D (34/71); A01D (34/82); A01D (34/76); A01D (2101/00)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2517405	12/1949	Moss	37/243	A01D 34/63
2697323	12/1953	Horn	N/A	N/A
2760327	12/1955	Bovee	56/255	A01D 34/71
3044241	12/1961	Snider	56/295	A01D 34/733
3162990	12/1963	Cook	D15/17	A01D 34/73
3192692	12/1964	Slemmons	N/A	N/A
3485022	12/1968	Freedlander et al.	N/A	N/A
3545189	12/1969	Houle	N/A	N/A
3564824	12/1970	Tygh, Jr.	56/295	A01D 34/73
3593505	12/1970	Mittelstadt	56/17.5	A01D 69/02
3601960	12/1970	Buechler	56/320.2	A01D 34/73

3823367	12/1973	Kaye et al.	N/A	N/A
3910017	12/1974	Thorud	56/295	A01D 34/73
4037695	12/1976	Welck	N/A	N/A
4114353	12/1977	Ansbaugh et al.	N/A	N/A
4254607	12/1980	Moore	N/A	N/A
4269020	12/1980	Wolf	56/13.4	A01D 34/73
4292791	12/1980	Lalonde	N/A	N/A
4375148	12/1982	Beck	N/A	N/A
4429518	12/1983	Fedeli	N/A	N/A
4532708	12/1984	Mensing	N/A	N/A
4617788	12/1985	Sebastian	N/A	N/A
4620575	12/1985	Cuba et al.	N/A	N/A
RE32377	12/1986	Seyerle	N/A	N/A
D289524	12/1986	Andersson et al.	N/A	N/A
4696153	12/1986	Boains, Jr.	N/A	N/A
4712364	12/1986	Oxley	N/A	N/A
4771593	12/1987	Lee	464/33	A01D 34/733
4871629	12/1988	Bunyea	N/A	N/A
4878338	12/1988	Aldred et al.	N/A	N/A
4922698	12/1989	Taylor	N/A	N/A
4936884	12/1989	Campbell	30/356	A01D 34/4168
5019113	12/1990	Burnell	N/A	N/A
5094065	12/1991	Azbell	N/A	N/A
5136899	12/1991	Hoch et al.	N/A	N/A
5152382	12/1991	Hoch et al.	N/A	N/A
5163273	12/1991	Wojtkowski et al.	N/A	N/A
5199251	12/1992	Rouse et al.	N/A	N/A
5209052	12/1992	Carroll	N/A	N/A
5213913	12/1992	Anthony, III et al.	N/A	N/A
5224870	12/1992	Weaver et al.	N/A	N/A
5233820	12/1992	Willsie	N/A	N/A
5238267	12/1992	Hutchison et al.	N/A	N/A
5259176	12/1992	Kahamura	56/255	A01D 34/73
5271212	12/1992	Anderson	N/A	N/A
5298821	12/1993	Michel	N/A	N/A
5299414	12/1993	Long	N/A	N/A
5321940	12/1993	Peterson	N/A	N/A
5327710	12/1993	Plamper	N/A	N/A
5337543	12/1993	Kitamura et al.	N/A	N/A
5355661	12/1993	Tomiyama	N/A	N/A
5363636	12/1993	Lamoureux	N/A	N/A
5401592	12/1994	Gilpin et al.	N/A	N/A
D357691	12/1994	Bryant	N/A	N/A
5410866	12/1994	Long	56/320.1	A01D 34/73
5467586	12/1994	Lin	N/A	N/A
5473871	12/1994	Fava et al.	N/A	N/A

5501068	12/1995	Martz	N/A	N/A
5502957	12/1995	Robertson	N/A	N/A
5553675	12/1995	Pitzen et al.	N/A	N/A
5619846	12/1996	Brown	N/A	N/A
5626979	12/1996	Mitsui et al.	N/A	N/A
5649750	12/1996	Ishii et al.	N/A	N/A
5663011	12/1996	Bunyea et al.	N/A	N/A
5685421	12/1996	Gilmore	N/A	N/A
5713189	12/1997	Toman	N/A	N/A
5725304	12/1997	Inai	N/A	N/A
5726541	12/1997	Glenn et al.	N/A	N/A
5762512	12/1997	Trant et al.	N/A	N/A
5775077	12/1997	Olmr	N/A	N/A
5794422	12/1997	Reimers et al.	N/A	N/A
5848520	12/1997	Arfstrom et al.	N/A	N/A
5881823	12/1998	Kabatnik et al.	N/A	N/A
5887669	12/1998	Ostler et al.	N/A	N/A
5890354	12/1998	Bednar	56/DIG.17	A01D 34/005
5894717	12/1998	Yamashita	56/320.1	A01D 34/005
5902080	12/1998	Kopras	N/A	N/A
5913802	12/1998	Mullet et al.	N/A	N/A
5934053	12/1998	Fillman et al.	N/A	N/A
5946895	12/1998	Martens	56/DIG.20	A01D 34/733
5983612	12/1998	Bauswell et al.	N/A	N/A
5987863	12/1998	Busboom et al.	N/A	N/A
6026634	12/1999	Peter et al.	N/A	N/A
6057608	12/1999	Bailey, Jr. et al.	N/A	N/A
6093056	12/1999	Donauer et al.	N/A	N/A
6109009	12/1999	Benson	N/A	N/A
6139359	12/1999	Fuhreck et al.	N/A	N/A
6145290	12/1999	Sullivan	56/255	A01D 34/005
6152247	12/1999	Sporrer et al.	N/A	N/A
6168881	12/2000	Fischer et al.	N/A	N/A
6181032	12/2000	Marshall et al.	N/A	N/A
D440981	12/2000	Burch	N/A	N/A
6223835	12/2000	Habedank et al.	N/A	N/A
6237698	12/2000	Carrier et al.	N/A	N/A
6253534	12/2000	Hunter et al.	N/A	N/A
6283235	12/2000	Sporrer et al.	N/A	N/A
6304058	12/2000	Watson et al.	N/A	N/A
6347502	12/2001	deVries	N/A	N/A
6354414	12/2001	Sueshige et al.	N/A	N/A
6357533	12/2001	Bucholz et al.	N/A	N/A
6367235	12/2001	Moynihan	56/DIG.17	A01D 34/733
6376942	12/2001	Burger et al.	N/A	N/A

6390225	12/2001	Velke et al.	N/A	N/A
6415681	12/2001	Porter et al.	N/A	N/A
6434917	12/2001	Bartel	N/A	N/A
6460626	12/2001	Carrier	N/A	N/A
6461088	12/2001	Potter et al.	N/A	N/A
6487840	12/2001	Turner	56/295	A01D 34/73
6487857	12/2001	Poplawski et al.	N/A	N/A
6502949	12/2002	Horiyama et al.	N/A	N/A
6525511	12/2002	Kubale et al.	N/A	N/A
6530200	12/2002	Minoura et al.	N/A	N/A
6551123	12/2002	Schaeffeier et al.	N/A	N/A
6560952	12/2002	Velke et al.	N/A	N/A
6568089	12/2002	Popik et al.	N/A	N/A
6581703	12/2002	Hammonds	N/A	N/A
6591593	12/2002	Brandon et al.	N/A	N/A
6591711	12/2002	Porter et al.	N/A	N/A
6604348	12/2002	Hunt	N/A	N/A
D482700	12/2002	Lancaster	N/A	N/A
6655119	12/2002	Hasei et al.	N/A	N/A
6662895	12/2002	Bednar	N/A	N/A
6672058	12/2003	Langenfeld et al.	N/A	N/A
6681877	12/2003	Ono et al.	N/A	N/A
6688091	12/2003	Ishimori	N/A	N/A
6701825	12/2003	Langenfeld	N/A	N/A
6708805	12/2003	Samejima et al.	N/A	N/A
6715284	12/2003	Poplawski et al.	N/A	N/A
6717281	12/2003	Brandon et al.	N/A	N/A
6729115	12/2003	Bartel	N/A	N/A
6729413	12/2003	Turner et al.	N/A	N/A
6767597	12/2003	Onishi et al.	N/A	N/A
6775976	12/2003	Phanco et al.	N/A	N/A
6782797	12/2003	Brandenburg et al.	N/A	N/A
6798160	12/2003	Wakitani et al.	N/A	N/A
6810589	12/2003	Lagaly et al.	N/A	N/A
6843056	12/2004	Langenfeld et al.	N/A	N/A
6856035	12/2004	Brandon et al.	N/A	N/A
6868657	12/2004	Bauer et al.	N/A	N/A
6886677	12/2004	Rupiper et al.	N/A	N/A
6945133	12/2004	Rush et al.	N/A	N/A
6948299	12/2004	Osborne	N/A	N/A
6957531	12/2004	Phanco et al.	N/A	N/A
6963796	12/2004	Larson et al.	N/A	N/A
6964164	12/2004	Langenfeld	N/A	N/A
6968687	12/2004	Poplawski et al.	N/A	N/A
6972234	12/2004	Phanco et al.	N/A	N/A
6973768	12/2004	Samejima et al.	N/A	N/A
6981780	12/2005	Einav	N/A	N/A
6988570	12/2005	Takeuchi	N/A	N/A
7017327	12/2005	Hunt et al.	N/A	N/A

7047736	12/2005	Langenfeld et al.	N/A	N/A
7051499	12/2005	Goto et al.	N/A	N/A
7111545	12/2005	Langenfeld	N/A	N/A
7121092	12/2005	Phanco et al.	N/A	N/A
7127041	12/2005	Houck et al.	N/A	N/A
7127877	12/2005	Curran	D15/17	A01D 34/73
7127889	12/2005	Bennett et al.	N/A	N/A
7165639	12/2006	Delaney et al.	N/A	N/A
7194850	12/2006	Asahara et al.	N/A	N/A
7213662	12/2006	Crumly et al.	N/A	N/A
7225617	12/2006	Langenfeld et al.	N/A	N/A
7226387	12/2006	Thompson et al.	N/A	N/A
7231994	12/2006	Buglione et al.	N/A	N/A
7270200	12/2006	Goto et al.	N/A	N/A
7299610	12/2006	Piontek	N/A	N/A
7308790	12/2006	Bennett et al.	N/A	N/A
7325388	12/2007	Wright et al.	N/A	N/A
7328576	12/2007	Langenfeld et al.	N/A	N/A
7340890	12/2007	Poplawski et al.	N/A	N/A
7353651	12/2007	Adkins et al.	N/A	N/A
7383683	12/2007	Rawski	N/A	N/A
7392643	12/2007	Warashina	56/DIG.17	A01D 34/826
7392853	12/2007	Baran	N/A	N/A
D574860	12/2007	Potts	N/A	N/A
7412828	12/2007	Bennett et al.	N/A	N/A
7429430	12/2007	Mooty et al.	N/A	N/A
7451865	12/2007	Eavenson, Sr. et al.	N/A	N/A
7454908	12/2007	Langenfeld et al.	N/A	N/A
7458432	12/2007	Mayer et al.	N/A	N/A
7540131	12/2008	Stover et al.	N/A	N/A
D598475	12/2008	Roth	N/A	N/A
7578116	12/2008	Howell	N/A	N/A
7590768	12/2008	Gormley	N/A	N/A
7594377	12/2008	Jansen et al.	N/A	N/A
7596636	12/2008	Gormley	N/A	N/A
7610975	12/2008	Gust et al.	N/A	N/A
7610986	12/2008	Ohashi	N/A	N/A
D609251	12/2009	Roth	N/A	N/A
7661486	12/2009	Turner et al.	N/A	N/A
7673712	12/2009	Lida et al.	N/A	N/A
7686108	12/2009	Piontek	N/A	N/A
7712294	12/2009	Wright et al.	N/A	N/A
7721517	12/2009	Hunt et al.	N/A	N/A
7730708	12/2009	Siler	N/A	N/A
7731398	12/2009	Probasco	N/A	N/A
7735592	12/2009	Bellot et al.	N/A	N/A
7784254	12/2009	Bever	56/255	A01D 34/733

7798939	12/2009	Musat et al.	N/A	N/A
7810964	12/2009	Probasco	N/A	N/A
7826232	12/2009	Von Arx et al.	N/A	N/A
7841176	12/2009	Langenfeld et al.	N/A	N/A
7870711	12/2010	Koehn	N/A	N/A
7908833	12/2010	Nicholson et al.	N/A	N/A
7918305	12/2010	Scherbring et al.	N/A	N/A
8028520	12/2010	Rawski	N/A	N/A
8028776	12/2010	Bong et al.	N/A	N/A
8047310	12/2010	Kallevig	N/A	N/A
8055399	12/2010	Wyatt et al.	N/A	N/A
8056653	12/2010	Hunt et al.	N/A	N/A
8100204	12/2011	Dong et al.	N/A	N/A
8104934	12/2011	Probasco	N/A	N/A
8149587	12/2011	Baran et al.	N/A	N/A
8181717	12/2011	Turner et al.	N/A	N/A
8191342	12/2011	Ishii et al.	N/A	N/A
8207693	12/2011	Hauser et al.	N/A	N/A
8234026	12/2011	Wyatt et al.	N/A	N/A
8235559	12/2011	Probasco	N/A	N/A
8245509	12/2011	Langenfeld et al.	N/A	N/A
8296003	12/2011	Wyatt et al.	N/A	N/A
8312937	12/2011	Turner et al.	N/A	N/A
8418452	12/2012	Phanco et al.	N/A	N/A
8450953	12/2012	Hauser et al.	N/A	N/A
8490722	12/2012	Koga et al.	N/A	N/A
8544570	12/2012	Ishii et al.	N/A	N/A
8548694	12/2012	Wyatt et al.	N/A	N/A
D693373	12/2012	Shiotsuki et al.	N/A	N/A
8572939	12/2012	Koike et al.	N/A	N/A
8573324	12/2012	Turner et al.	N/A	N/A
8579055	12/2012	Sasahara et al.	N/A	N/A
D694782	12/2012	Roth	N/A	N/A
D696301	12/2012	DeLeon et al.	N/A	N/A
8657041	12/2013	Ishii et al.	N/A	N/A
8668033	12/2013	Koike et al.	N/A	N/A
8668036	12/2013	Wyatt et al.	N/A	N/A
8689551	12/2013	Phanco et al.	N/A	N/A
8783391	12/2013	Porter et al.	N/A	N/A
D710396	12/2013	Nie	N/A	N/A
8794660	12/2013	Stover et al.	N/A	N/A
8800279	12/2013	Kita et al.	N/A	N/A
8838311	12/2013	Koike et al.	N/A	N/A
8844658	12/2013	Wyatt et al.	N/A	N/A
8849490	12/2013	Wyatt et al.	N/A	N/A
8850782	12/2013	Haraqia et al.	N/A	N/A
8880300	12/2013	Gamble et al.	N/A	N/A
8965630	12/2014	Wyatt et al.	N/A	N/A
9002585	12/2014	Porter et al.	N/A	N/A
9114703	12/2014	Bennett et al.	N/A	N/A

9114798	12/2014	Fox et al.	N/A	N/A
9194473	12/2014	Hauser et al.	N/A	N/A
D745061	12/2014	DeLeon	N/A	N/A
9248737	12/2015	Iwaki et al.	N/A	N/A
9288939	12/2015	Porter et al.	N/A	N/A
9301443	12/2015	Hashima et al.	N/A	N/A
9307695	12/2015	Nishihara et al.	N/A	N/A
9308817	12/2015	Phanco et al.	N/A	N/A
D755858	12/2015	Brown	N/A	N/A
9381639	12/2015	Wemer et al.	N/A	N/A
9403435	12/2015	Bejcek	N/A	N/A
9408343	12/2015	Wyatt et al.	N/A	N/A
9409553	12/2015	Nakamura et al.	N/A	N/A
9409578	12/2015	Wyatt et al.	N/A	N/A
9420740	12/2015	Ishii et al.	N/A	N/A
9435324	12/2015	Richardson et al.	N/A	N/A
9468144	12/2015	Kurioka	N/A	A01D 34/826
9480200	12/2015	Patridge	N/A	A01D 34/66
9492919	12/2015	Roehm et al.	N/A	N/A
9499199	12/2015	Laymon et al.	N/A	N/A
9538699	12/2016	Bejcek et al.	N/A	N/A
9538706	12/2016	Haun	N/A	N/A
9616736	12/2016	Ito et al.	N/A	N/A
D786310	12/2016	Southwell et al.	N/A	N/A
9656687	12/2016	Koike et al.	N/A	N/A
9699964	12/2016	Roth et al.	N/A	N/A
9706706	12/2016	Barendrecht	N/A	N/A
9725114	12/2016	Brown et al.	N/A	N/A
9725115	12/2016	Hauser et al.	N/A	N/A
9731760	12/2016	Ito et al.	N/A	N/A
9750183	12/2016	Haun	N/A	A01D 34/733
9750191	12/2016	Richardson et al.	N/A	N/A
9764734	12/2016	Brown	N/A	N/A
9765761	12/2016	Fox et al.	N/A	N/A
9765870	12/2016	Fox et al.	N/A	N/A
D801394	12/2016	Southwell et al.	N/A	N/A
9820441	12/2016	Heathcoat et al.	N/A	N/A
9839179	12/2016	Stover et al.	N/A	N/A
9888626	12/2017	Gilpatrick et al.	N/A	N/A
9968031	12/2017	Bejcek et al.	N/A	N/A
D837266	12/2018	Wong et al.	N/A	N/A
D837267	12/2018	Wong et al.	N/A	N/A
D837268	12/2018	Burrows et al.	N/A	N/A
D849799	12/2018	Bollman	N/A	N/A
10285328	12/2018	Kurioka	N/A	A01D 34/68
10426084	12/2018	Ito et al.	N/A	N/A
D873302	12/2019	Southwell	N/A	N/A
D902262	12/2019	Hoover	N/A	N/A

11122737	12/2020	Xu et al.	N/A	N/A
11246260	12/2021	Xu et al.	N/A	N/A
D949206	12/2021	Cmich	N/A	N/A
11910743	12/2023	Guo	N/A	N/A
2001/0001170	12/2000	Velke et al.	N/A	N/A
2002/0056263	12/2001	Schaedler	56/295	A01D 34/73
2003/0168272	12/2002	Ono et al.	N/A	N/A
2003/0209000	12/2002	Mannon	56/295	A01D 34/005
2003/0222607	12/2002	Simizu et al.	N/A	N/A
2005/0016320	12/2004	Porter	N/A	N/A
2006/0010844	12/2005	Angott	N/A	N/A
2006/0042216	12/2005	Warashina	56/255	A01D 34/826
2006/0162310	12/2005	Dittmer	56/289	A01D 34/005
2006/0168933	12/2005	Hill, Jr.	56/295	A01D 34/73
2007/0074497	12/2006	Myers	56/295	A01D 34/73
2008/0072556	12/2007	Tegtmeier et al.	N/A	N/A
2008/0234096	12/2007	Joshi et al.	N/A	N/A
2009/0182470	12/2008	Garvey et al.	N/A	N/A
2010/0043378	12/2009	Abernethy	N/A	N/A
2010/0085745	12/2009	Kristiansen et al.	N/A	N/A
2010/0117594	12/2009	Bizzontz	N/A	N/A
2010/0139231	12/2009	Washburn, IV	56/295	A01D 34/73
2012/0228041	12/2011	Borinato	N/A	N/A
2012/0233975	12/2011	Coussins	N/A	N/A
2013/0008682	12/2012	Turner et al.	N/A	N/A
2013/0104509	12/2012	MacKinnon	701/22	A01D 34/78
2013/0155657	12/2012	Werner et al.	N/A	N/A
2013/0327007	12/2012	Eavenson, Sr.	N/A	N/A
2014/0100743	12/2013	Foster et al.	N/A	N/A
2014/0182257	12/2013	von Rentzell	56/289	A01D 34/73
2014/0196425	12/2013	Lewis	56/16.7	A01D 34/78
2015/0052869	12/2014	Roth	56/295	A01D 34/81
2015/0082763	12/2014	Nishihara	56/289	A01D 34/63
2015/0173299	12/2014	Heathcoat et al.	N/A	N/A
2015/0271997	12/2014	Kurioka et al.	N/A	N/A
2015/0271998	12/2014	Kurioka	56/255	A01D 34/68
2016/0143219	12/2015	Yuan	N/A	N/A
2016/0183451	12/2015	Conrad et al.	N/A	N/A
2016/0242355	12/2015	Talaski	N/A	A01D 34/733
2016/0288829	12/2015	Ito et al.	N/A	N/A
2017/0020067	12/2016	Haun	N/A	N/A
2017/0021861	12/2016	Ito et al.	N/A	N/A
2017/0055443	12/2016	Fuji et al.	N/A	N/A
2017/0105339	12/2016	Yang et al.	N/A	N/A
2017/0120922	12/2016	Schaedler et al.	N/A	N/A
2017/0129022	12/2016	Schaedler et al.	N/A	N/A

2017/0245426	12/2016	Kuriyagawa et al.	N/A	N/A
2017/0303469	12/2016	Schaedler et al.	N/A	N/A
2018/0020614	12/2017	Alliss	N/A	N/A
2018/0146616	12/2017	Fukano	N/A	A01D 34/69
2018/0152121	12/2017	Fukano et al.	N/A	N/A
2018/0160620	12/2017	Wang et al.	N/A	N/A
2018/0231238	12/2017	Burch et al.	N/A	N/A
2019/0045707	12/2018	Patridge	N/A	A01D 34/66
2019/0200521	12/2018	Aboumrad	N/A	N/A
2019/0335654	12/2018	Ito	N/A	A01D 34/68
2020/0000023	12/2019	Chung	N/A	N/A
2020/0052558	12/2019	Kouda	N/A	A01D 34/78
2020/0100426	12/2019	Kurihara	N/A	A01D 34/63
2020/0253115	12/2019	Feng	N/A	A01D 34/733
2020/0404840	12/2019	Xu et al.	N/A	N/A
2021/0289697	12/2020	Kurihara et al.	N/A	N/A
2021/0321564	12/2020	Yamaoka et al.	N/A	N/A
2023/0117891	12/2022	Broge	N/A	N/A
2024/0188487	12/2023	Guo	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2004205280	12/2003	AU	N/A
2017100173	12/2016	AU	N/A
1409943	12/2002	CN	N/A
1802890	12/2005	CN	N/A
202145746	12/2011	CN	N/A
102388720	12/2011	CN	N/A
102684235	12/2011	CN	N/A
102986361	12/2012	CN	N/A
202819008	12/2012	CN	N/A
203251656	12/2012	CN	N/A
203369100	12/2013	CN	N/A
203423971	12/2013	CN	N/A
103703918	12/2013	CN	N/A
104363749	12/2014	CN	N/A
204180542	12/2014	CN	N/A
204180549	12/2014	CN	N/A
104669226	12/2014	CN	N/A
204681890	12/2014	CN	N/A
105075497	12/2014	CN	N/A
105082096	12/2014	CN	N/A
204796177	12/2014	CN	N/A
205363843	12/2015	CN	N/A
205363844	12/2015	CN	N/A
205466090	12/2015	CN	N/A
205546539	12/2015	CN	N/A

106612971	12/2016	CN	N/A
206323814	12/2016	CN	N/A
206353985	12/2016	CN	N/A
206423166	12/2016	CN	N/A
107302864	12/2016	CN	N/A
206855413	12/2017	CN	N/A
207139764	12/2017	CN	N/A
207240145	12/2017	CN	N/A
207269396	12/2017	CN	N/A
207340527	12/2017	CN	N/A
105075498	12/2017	CN	N/A
108207334	12/2017	CN	N/A
108790946	12/2017	CN	N/A
106258180	12/2018	CN	N/A
3019256	12/1980	DE	N/A
3232895	12/1983	DE	N/A
4105557	12/1991	DE	N/A
9311901	12/1992	DE	N/A
9319361	12/1993	DE	N/A
29513651	12/1996	DE	N/A
20309420	12/2002	DE	N/A
102006058958	12/2007	DE	A01D 34/73
102012213047	12/2013	DE	N/A
102012218601	12/2013	DE	N/A
202017100938	12/2016	DE	A01D 34/005
0499879	12/1991	EP	N/A
0528478	12/1992	EP	N/A
0898870	12/1998	EP	N/A
0957526	12/1998	EP	N/A
0981944	12/1999	EP	N/A
1348328	12/2002	EP	N/A
1447281	12/2003	EP	N/A
1498018	12/2004	EP	A01D 34/73
1285570	12/2007	EP	N/A
2357107	12/2010	EP	N/A
2798937	12/2013	EP	A01D 34/733
2969330	12/2017	EP	N/A
3695702	12/2019	EP	A01D 34/6818
2756536	12/1997	FR	N/A
2893222	12/2006	FR	N/A
2037138	12/1979	GB	N/A
2302202	12/1996	GB	N/A
2332355	12/1998	GB	A01D 34/6806
2003180118	12/2002	JP	N/A
2015188337	12/2014	JP	N/A
2018102234	12/2017	JP	N/A
2018102235	12/2017	JP	N/A
1743448	12/1991	SU	N/A
2000032462	12/1999	WO	N/A
2000038255	12/1999	WO	N/A

2010048561	12/2009	WO	N/A
2016037184	12/2015	WO	N/A
2017173944	12/2016	WO	N/A
2017173945	12/2016	WO	N/A
2018124021	12/2017	WO	N/A

OTHER PUBLICATIONS

Chavez, Youtube, youtube.com/watch?v=mt-C07y_obY (Year: 2017). cited by examiner

Owner's manual for Model No. HRN216VKA Lawn Mower. cited by applicant

EPO, extended European Search Report issued on European patent application No. 19866834.5, dated Jul. 22, 2021, 10 pgs. cited by applicant

You Tube video—https://www.youtube.com/watch?v=iORCGT_K7mc. cited by applicant

U.S. Patent and Trademark Office, Non-Final Office Action issued in U.S. Appl. No. 18/076,847, dated Mar. 23, 2023, 11 pages. cited by applicant

U.S. Patent and Trademark Office, Final Office Action issued in U.S. Appl. No. 17/863,038, dated Apr. 4, 2023, 10 pages. cited by applicant

U.S. Patent and Trademark Office, Non-Final Office Action issued in U.S. Appl. No. 17/825,815, dated Jul. 14, 2023, 12 pages. cited by applicant

U.S. Patent and Trademark Office, Final Office Action issued in U.S. Appl. No. 18/076,847, dated Jul. 17, 2023, 10 pages. cited by applicant

Non-final Office Action from U.S. Appl. No. 18/519,868, dated Jan. 7, 2025, 15 pp. cited by applicant

ISA/CN, Int. Search Report issued on PCT application No. PCT/CN2019/107650, dated Dec. 24, 2019, 3 pgs. cited by applicant

Greenworks, Gree Bo electric brush cutter 80V, <http://goods.jc001.cn/detail/4444528.html>, 12 pages. cited by applicant

CIPO, office action issued on Canadian patent application 3,114,468, dated Jun. 21, 2021, 6 pages. cited by applicant

Australian Patent Office, examination report issued of Australian patent application No. 2019346954, dated Feb. 16, 2022, 3 pages. cited by applicant

U.S. Patent and Trademark Office, Final Office Action issued in U.S. Appl. No. 17/825,815, dated Nov. 15, 2022, 13 pgs. cited by applicant

U.S. Patent and Trademark Office, Non-Final Office Action issued in U.S. Appl. No. 29/865,427, dated Nov. 25, 2022, 9 pgs. cited by applicant

U.S. Patent and Trademark Office, Non-Final Office Action issued in U.S. Appl. No. 29/865,321, dated Nov. 25, 2022, 9 pgs. cited by applicant

U.S. Patent and Trademark Office, Non-Final Office Action issued in U.S. Appl. No. 17/863,038, dated Nov. 29, 2022, 12 pgs. cited by applicant

U.S. Patent and Trademark Office, Non-Final Office Action issued in U.S. Appl. No. 17/825,815, dated Jul. 25, 2022, 13 pgs. cited by applicant

U.S. Patent and Trademark Office, Non-Final Office Action issued in U.S. Appl. No. 18/163,609, dated May 1, 2023, eight (8) pages. cited by applicant

Primary Examiner: Behrens; Adam J

Attorney, Agent or Firm: Greenberg Traurig, LLP

Background/Summary

RELATED APPLICATION INFORMATION (1) This application is a continuation of U.S. patent application Ser. No. 17/236,239 filed Apr. 21, 2021, which is a continuation of U.S. patent application Ser. No. 17/164,479 filed Feb. 1, 2021, which application is a continuation of International Application Number PCT/CN2019/107650, filed on Sep. 25, 2019, through which this application also claims the benefit of Chinese Patent Application No. 201821584956.0, filed on Sep. 27, 2018, Chinese Patent Application No. 201821889111.2, filed on Nov. 15, 2018, Chinese Patent Application No. 201920533524.5, filed on Apr. 18, 2019, Chinese Patent Application No. 201910312144.3, filed on Apr. 18, 2019, Chinese Patent Application No. 201910576318.7, filed on Jun. 28, 2019, and Chinese Patent Application No. 201921545742.7, filed on Sep. 17, 2019, each of which is incorporated herein by reference in its entirety.

BACKGROUND

(1) As a basic operation of lawn trimming, mowing requires the use of simple and efficient mowing machinery to complete the mowing task with guaranteed quality and quantity. Lawn mowers have been widely used in the trimming of various kinds of lawns. As the functional element of the lawn mower, the structural design of the blade greatly affects the cutting performance of the lawn mower.

(2) Lawn mowers can be divided into engine-driven and motor-driven by energy source. Among them, the motor-driven lawn mower generally uses battery packs as an energy source, which has the advantages of less noise and pollution. However, considering the load problem, the motor-driven lawn mower in the related art has an unreasonable blade structure, which results in a large load on the motor and a low cutting efficiency.

SUMMARY

(3) The present application provides a lawn mower with a smaller motor load and higher cutting efficiency.

(4) An example provides a lawn mower, including: a blade assembly configured to perform a cutting function; a deck formed with an accommodation space for accommodating at least a portion of the blade assembly; a motor configured to drive the blade assembly to rotate about a rotation axis; and a battery pack configured to provide power source for the motor. The blade assembly includes: a first cutting portion configured to cut grass; and a second cutting portion configured to cut grass; wherein in the direction parallel to the rotation axis, the second cutting portion is located below the first cutting portion. The battery pack includes a battery pack housing and battery cells provided in the battery pack housing. The maximum length of a line connecting any two points of the projection of the blade assembly in a plane perpendicular to the rotation axis and the projection of the rotation axis in the plane is the rotation diameter of the blade assembly. The product of the rotation diameter D (mm), the number N of battery cells included in the battery pack, and the mass M (g) of the blade assembly is greater than or equal to $3.5 \times 10^{5.5}$ (mm.Math.g) and less than or equal to $7.3 \times 10^{7.7}$ (mm.Math.g).

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a schematic diagram of a lawn mower provided as Example 1;
- (2) FIG. 2 is a plan view of a partial structure of the lawn mower of FIG. 1;
- (3) FIG. 3 is a perspective view of a partial structure of the lawn mower of FIG. 1;
- (4) FIG. 4 is a plan view of a partial structure of a blade assembly of the lawn mower of FIG. 1;
- (5) FIG. 5 is a cross-sectional view of a partial structure of the lawn mower of FIG. 1, wherein a mounting assembly is in a first mounting state;
- (6) FIG. 6 is an exploded view of a partial structure of the lawn mower of FIG. 1;

- (7) FIG. 7 is a schematic view of a partial structure of the lawn mower provided in Example 1, wherein the mounting assembly is in a second mounting state;
- (8) FIG. 8 is a schematic diagram of a partial structure of the lawn mower provided in Example 1, wherein the mounting assembly is in the second mounting state;
- (9) FIG. 9 is an exploded view of a blade assembly of the lawn mower of FIG. 1;
- (10) FIG. 10 is a schematic diagram of a first blade and a second blade of the lawn mower of FIG. 1;
- (11) FIG. 11 is a schematic diagram of a partial structure of a lawn mower provided in Example 2;
- (12) FIG. 12 is a schematic diagram of a blade assembly and a connecting assembly of a lawn mower provided in Example 3;
- (13) FIG. 13 is a schematic diagram of a blade assembly of a lawn mower provided in Example 4;
- (14) FIG. 14 is a plan view of the blade assembly in FIG. 13;
- (15) FIG. 15 is a plan view of a second blade of the blade assembly in FIG. 13;
- (16) FIG. 16 is a plan view from another angle of the second blade of the blade assembly in FIG. 13;
- (17) FIG. 17 is a schematic diagram of a partial structure of a lawn mower provided in Example 5;
- (18) FIG. 18 is a cross-sectional view of the structure in FIG. 17;
- (19) FIG. 19 is an exploded view of the partial structure of the lawn mower of FIG. 17;
- (20) FIG. 20 is a schematic diagram of a partial structure of a lawn mower provided in Example 6;
- (21) FIG. 21 is a plan view of a blade assembly and a mounting assembly of the lawn mower provided in Example 6;
- (22) FIG. 22 is an exploded view of the partial structure of the lawn mower of FIG. 20;
- (23) FIG. 23 is a schematic diagram of a partial structure of a lawn mower provided in Example 7;
- (24) FIG. 24 is a cross-sectional view of the structure in FIG. 23;
- (25) FIG. 25 is an exploded view of the structure in FIG. 23;
- (26) FIG. 26 is a schematic diagram of a partial structure of a lawn mower provided in Example 8;
- (27) FIG. 27 is a schematic diagram of a lawn mower connected with a grass pressing assembly provided in Example 9;
- (28) FIG. 28 is a perspective view of the grass pressing assembly in FIG. 27;
- (29) FIG. 29 is a plan view of the grass pressing assembly in FIG. 27;
- (30) FIG. 30 is a cross-sectional view of the grass pressing assembly in FIG. 27;
- (31) FIG. 31 is a schematic diagram of a grass pressing assembly connected to a lawn mower provided in Example 10;
- (32) FIG. 32 is a perspective view of a lawn mower provided in Example 11;
- (33) FIG. 33 is a bottom view of the lawn mower of FIG. 32;
- (34) FIG. 34 is a circuit diagram of the lawn mower of FIG. 32;
- (35) FIG. 35 is a schematic diagram of the connection of a first signal line of the lawn mower of FIG. 32 to a first output circuit board and a second output circuit board;
- (36) FIG. 36 is a circuit diagram of a lawn mower provided in Example 12;
- (37) FIG. 37 is a schematic diagram of a partial structure of the lawn mower of FIG. 32;
- (38) FIG. 38 is a perspective view of a deck in the lawn mower of FIG. 32;
- (39) FIG. 39 is a plan view of the deck in FIG. 38;
- (40) FIG. 40 is a cross-sectional view of the deck in FIG. 39 along line V-V;
- (41) FIG. 41 is a perspective view of the deck of FIG. 38 when connected to a plug;
- (42) FIG. 42 is a schematic diagram of a lawn mower provided in Example 13;
- (43) FIG. 43 is a perspective view of the lawn mower of FIG. 42;
- (44) FIG. 44 is a plan view of a blade assembly of the lawn mower of FIG. 42;
- (45) FIG. 45 is an exploded view of the blade assembly in FIG. 44;
- (46) FIG. 46 is a plan view of a partial structure of the blade assembly in FIG. 45;
- (47) FIG. 47 is a schematic diagram of a lawn mower provided in Example 14;

- (48) FIG. 48 is a perspective view of a blade assembly of the lawn mower of FIG. 47;
(49) FIG. 49 is a plan view of a blade of the blade assembly of FIG. 48;
(50) FIG. 50 is a cross-sectional view of the blade in FIG. 49;
(51) FIG. 51 is a schematic diagram of a blade assembly of a lawn mower provided in Example 15;
(52) FIG. 52 is a plan view of a blade of the blade assembly of FIG. 51.

DETAILED DESCRIPTION

Example 1

- (53) FIG. 1 is a schematic diagram of a lawn mower **100** provided in Example 1 of the present application. Depending on the operation mode of the user, the lawn mower **100** in the present application may be either a hand-push lawn mower or a riding lawn mower. This example uses a hand-push lawn mower driven by a motor as an example for description. All “assembly” in this application refer to a combination including at least one component or part, which realizes a specific function through interaction or coordination. For the convenience of explaining the technical solution of the present application, the up-down direction is defined as shown in FIG. 1.
- (54) As shown in FIGS. 1-3, the lawn mower **100** includes a blade assembly **11**, a deck **12**, a motor **13**, and a battery pack. The blade assembly **11** is configured to perform the cutting function of the lawn mower **100**; the deck **12** is formed with an accommodation space for accommodating at least part of the blade assembly **11**; in this example, the blade assembly **11** is located inside the accommodation space; the motor **13** drives the blade assembly **11** to rotate about the rotation axis **100'**, and the motor **13** is located above the deck **12** and forms a coaxial rotation with the blade assembly **11** about the rotation axis **100'**. In an example, the motor **13** includes a motor shaft, and the lawn mower **100** further includes a drive shaft **14** that drives the blade assembly **11** to rotate. The drive shaft **14** may be a motor shaft, and a transmission mechanism may be provided between the motor **13** and the blade assembly **11** so that the motor **13** and the drive shaft **14** form a non-coaxial rotation. The battery pack provides a power source for the motor **13**. The lawn mower **100** also includes a fan **15** connected to the drive shaft **14**; the fan **15** rotates about an axis that is parallel or coincident with the rotation axis **100'**.
- (55) When the motor **13** is started to drive the blade assembly **11** to rotate about the rotation axis **100'** and the tip linear velocity of the blade assembly **11** is greater than or equal to 40 m/s and less than or equal to 100 m/s, the working time of the lawn mower **100** with 100 WH energy consumption of the battery pack is defined as the hectowatt-hour battery life of the lawn mower **100**, and the hectowatt-hour battery life of the lawn mower **100** is greater than or equal 4 min and less than or equal to 30 min; in one example, the hectowatt-hour battery life of the lawn mower **100** is greater than or equal to 5 min and less than or equal to 20 min; in other examples, the hectowatt-hour battery life of the lawn mower **100** is greater than or equal to 6 min and less than or equal to 15 min. In this example, the hectowatt-hour battery life of the lawn mower **100** is about 12 min. Since the lawn mower **100** of the present example has the blade assembly **100** with better structure design, smaller load and higher cutting efficiency, during operation the lawn mower **100** has a hectowatt-hour battery life in the above range, such that the lawn mower **100** has a good cutting performance. The battery pack here only refers to the battery pack that supplies power to the motor **13** to drive the blade assembly **11** to rotate.
- (56) In addition, when the motor **13** drives the blade assembly **11** to rotate about the rotation axis **100'** at no load, the working time of the lawn mower **100** with 100 WH energy consumption of the battery pack is defined as the no-load battery life of the lawn mower **100**, and the no-load battery life of the lawn mower **100** is greater than or equal to 9 min and less than or equal to 35 min; in one example, the no-load battery life of the lawn mower **100** is greater than or equal to 12 min and less than or equal to 33 min; in other examples, the no-load battery life of the lawn mower **100** is greater than or equal to 18 min and less than or equal to 30 min. In this example, the no-load battery life of the lawn mower **100** is about 22 min. Since the lawn mower **100** of the present example has the blade assembly with better structure design, smaller load and higher cutting

efficiency, as well as reasonable no-load condition settings, during operation the lawn mower **100** has a no-load battery life in the above range, such that the lawn mower **100** has a good cutting performance.

(57) As shown in FIGS. 2-5, the blade assembly **11** includes a first blade **111** and a second blade **112**, and the first blade **111** and the second blade **112** are respectively formed with a first cutting portion **111a** and a second cutting portion **112a** that are configured to cut grass. When the entirety constructed by the first blade **111** and second blade **112** rotate about the rotation axis **100'**, the first cutting portion **111a** and the second cutting portion **112a** performs mowing. In this example, the cutting portions refer to a structure having a cutting function to cut vegetation; the cutting portion may be a common cutting portion or a cutting structure different from the cutting portion. A cutting portion refers to an integrally formed or continuous structure.

(58) In a direction parallel to the rotation axis **100'**, the second cutting portion **112a** is located below, but not limited to directly under, the first cutting portion **111a**; or the second cutting portion **112a** and the first cutting portion **111a** are at least partially within the same plane. In this example, the first blade **111** and the second blade **112** are two blades formed separately. The first blade **111** is located above the second blade **112** relative to the ground in a direction parallel to the rotation axis **100'**. The first blade **111** and the second blade **112** rotate synchronously. As shown by the arrows in FIG. 2, the first blade **111** and the second blade **112** rotate coaxially and synchronously along the rotation direction A about the rotation axis **100'**.

(59) The lawn mower **100** also includes a control system configured to control the operation of the motor **13**. When the lawn mower **100** has no load, the sum of the input power of the motor **13**, the input power of the control system, and the input power of the blade assembly **11** is the no-load input power of the lawn mower **100**; the no-load input power is greater than or equal to 100 W and less than or equal to 380 W, in this example, the no-load input power is greater than or equal to 200 W and less than or equal to 300 W.

(60) In one example, no-load means that the blade assembly **11** of the lawn mower **100** rotates at a predetermined speed under atmospheric pressure, and the blade assembly **11** has no external load.

(61) The volume of the smallest cylinder **11'** surrounding the first blade **111** and the second blade **112** is defined as the sweep volume of the blade assembly **11**. When the blade assembly **11** rotate about the rotation axis **100'**, the first cutting portion **111a** and the second cutting portion **112a** are both located in the space surrounded by the smallest cylinder **11'**. As shown in FIG. 2, the rectangle indicated by the dotted line is a plan view of the cylinder **11'** that surrounds the first blade **111** and the second blade **112** in this example. The sweep volume of the blade assembly **11** is the volume of the cylinder **11'**, and the volume of the cylinder **11'** is about the volume of the cylinder **11'** with the rotation diameter D of the blade assembly **11** as the diameter (referring to FIG. 4), and the maximum height of the blade assembly **11** in the direction parallel or coincident with the rotation axis **100'** as the height. The rotation diameter D of the blade assembly **11** is the maximum length of the line connecting any two points of the projection of the blade assembly **11** in a plane perpendicular to the rotation axis **100'** and the projection of the rotation axis **100'** in the plane. In this example, since the first blade **111** and the second blade **112** are both perpendicular to the rotation axis **100'**, and the first blade **111** and the second blade **112** are coaxially mounted to the drive shaft **14**; the first blade **111** is located directly above the second blade **112**. The sweep volume of the blade assembly **11** is about the volume of the cylinder **11'** with the maximum distance from any point on the blade assembly **11** to the rotation axis **100'** as the radius, and the maximum sum of the heights of the first blade **111** and the second blade **112** parallel to the rotation axis **100'** as the height. In one example, the heights of the first blade **111** and the second blade **112** are respectively the maximum dimensions of the first blade **111** and the second blade **112** in the direction parallel to the rotation axis **100'** when the blade assembly **11** is mounted to the drive shaft **14**.

(62) In this example, the sweep volume of the blade assembly **11** is greater than or equal to 400 cm.sup.3 and less than or equal to 8000 cm.sup.3. When the sweep volume of the blade assembly

11 is kept within this range, the lawn mower **100** has a relatively small load, in other words, when the sweep volume of the blade assembly **11** is kept within this range, the lawn mower **100** has a relatively small load while the double blades guarantee the cutting performance of the lawn mower **100**, thereby enabling the lawn mower **100** to have a high cutting efficiency. In this example, the sweep volume of the blade assembly **11** is greater than or equal to 600 cm.sup.3 and less than or equal to 6800 cm.sup.3. In one example, the sweep volume of the blade assembly **11** is greater than or equal to 1000 cm.sup.3 and less than or equal to 5000 cm.sup.3.

(63) The structure of the blade assembly is not limited to the structure in this example. In an example, the blade assembly may include only one blade; both the first cutting portion and the second cutting portion are provided on the blade. In the direction of the rotation axis, the second cutting portion is located below, but not limited to directly below, the first cutting portion; the first cutting portion and the second cutting portion may be integrally formed or connected with other structures to form a complete blade. For example, the blade assembly may include a blade body, and the first cutting portion and the second cutting portion are respectively disposed on a plurality of fins extending from the blade body, and the plurality of fins and the blade body may be fixedly connected or integrally formed or detachably connected.

(64) As shown in FIG. 4, the phase angle α formed by the first cutting portion **111a** and the second cutting portion **112a** is greater than or equal to 0 and less than 90 degrees. The phase angle α is the angle between the straight lines on which the projections of the blade edge **111b** of the first cutting portion **111a** and the blade edge **112b** of the second cutting portion **112a** in a plane perpendicular to the rotation axis **100'** are located. The edge **111b** of the first cutting portion **111a** is the front most side of the first cutting portion **111a**, that is, the side that first contacts the vegetation when the first blade **111** rotates in the rotation direction A about the rotation axis **100'**; Likewise, the edge of the second cutting portion **112a** is the front most side of the second cutting portion **112a**, that is, the side that first contacts the vegetation when the second blade **112** rotates in the rotation direction A about the rotation axis **100'**. When the phase angle of the first cutting portion **111a** and the second cutting portion **112a** is within the above range, the first cutting portion **111a** and the second cutting portion **112a** as a whole have higher cutting efficiency. In an example, the phase angle α formed by the first cutting portion **111a** and the second cutting portion **112a** is greater than or equal to 10 degrees and less than or equal to 60 degrees. In this example, the phase angle α between the first cutting portion **111a** and the second cutting portion **112a** is about 20 degrees.

(65) The first blade **111** includes at least one first cutting portion **111a**, and the first cutting portion **111a** may be regarded as a continuous cutting portion formed on the first blade **111**. In an example, the first blade **111** and the second blade **112** respectively include at least two first cutting portions **111a** and at least two second cutting portions **112a**. In this example, the first blade **111** is formed with two first cutting portion **111a**, the two first cutting portions **111a** are respectively provided on two ends of the first blade **111**, and are both disposed on the front side of the rotation direction A, that is, the side that first contacts the vegetation when the first blade **111** rotates in the rotation direction A about the rotation axis **100'**; the two first cutting portions **111a** are center symmetrical about the rotation axis **100'**. Similarly, the second blade **112** also includes at least one second cutting portion **112a**, in the present example the second blade **112** is formed with two second cutting portions **112a**, the two second cutting portions **112a** are respectively provided on two ends of the second blade **112**, and are both located on the front side of the rotation direction A, that is, the side that first contacts the vegetation when the second blade **112** rotates in the rotation direction A about the rotation axis **100'**; the two second cutting portions **112a** are center symmetrical about the rotation axis **100'**.

(66) The sum of the number of the first cutting portions **111a** formed by the first blade **111** and the number (unit: piece) of the second cutting portions **112a** formed by the second blade **112** is defined as the number of cutting portions of the blade assembly **11**. In the blade assembly **11** of the present example, the ratio of the sweep volume to the number of cutting portions of the blade assembly **11**

is greater than or equal to 50 cm.sup.3 and less than or equal to 4000 cm.sup.3. In one example, the ratio of the sweep volume to the number of cutting portions of the blade assembly **11** is greater than or equal to 75 cm.sup.3 and less than or equal to 3400 cm.sup.3. In one example, structurally discontinuous first cutting portions **111a** are regarded as a plurality of different first cutting portions **111a**, and the number of first cutting portions **111a** is the number of discontinuous first cutting portions **111a** provided on the first blade **111**; similarly, structurally discontinuous second cutting portions **112a** are regarded as a plurality of different second cutting portions **112a**, and the number of second cutting portions **112a** is the number of discontinuous second cutting portions **112a** provided on the second blade **112**. In this example, the ratio of the sweep volume to the number of cutting portions of the blade assembly **11** is about 1700 cm.sup.3. The greater the number of cutting portions, the better the cutting performance of the lawn mower **100**, but the greater the number of cutting portions, the greater the sweep volume requirement of the blade assembly **11**, as well as the load of the lawn mower **100**. In this example, by optimizing the structure of the blade assembly **11**, the ratio of the sweep volume to the number of cutting portions of the blade assembly **11** is kept within the above-mentioned optimal range, thereby ensuring that the lawnmower **100** maintains an optimal cutting performance under a small load.

(67) As shown in FIG. 5, the lawn mower **100** further includes a mounting assembly **16**, the mounting assembly **16** has a first mounting state in which the blade assembly **11** is mounted to the drive shaft **14** so that the blade assembly **11** rotates with the drive shaft **14** and a second mounting state in which one of the first blade **111** and the second blade **112** is removed and only the other one of the first cutting portion **111a** and the second cutting portion **112a** is mounted to perform the cutting function.

(68) In this example, as shown in FIGS. 5-8, since the first cutting portion **111a** and the second cutting portion **112a** are respectively provided on the separately formed first blade **111** and second blade **112**, therefore, the mounting assembly **16** has a first mounting state in which the blade assembly **11** is mounted to the drive shaft **14** so that the blade assembly **11** rotates with the drive shaft **14** and a second mounting state in which one of the first blade **111** and the second blade **112** is removed and only the other one of the first blade **111** and the second blade **112** is mounted to perform the cutting function. That is to say, the mounting assembly **16** can mount the blade assembly **11** including the first blade **111** and the second blade **112** to the drive shaft **14** in the first mounting state, and can also mount the blade assembly **11** including only one of the first blade **111** and the second blade **112** to the drive shaft **14** in the second mounting state. Considering the diversity of usage conditions, the mounting assembly **16** in this example has multiple mounting states to provide better adaptability, allowing the user to reduce or increase the number of blades based on their specific needs without having to replace the entire mounting assembly **16** and blade assembly **11**, thereby enhancing mowing practicability.

(69) In an example, the mounting assembly **16** has a first mounting state in which a first type of blade assembly including the first cutting portion and the second cutting portion is mounted to the drive shaft, and the mounting assembly also has a second mounting state in which the first type of blade assembly is removed and a second type of blade assembly including only one cutting portion is mounted to the drive shaft. Based on the structure that the first cutting portion and the second cutting portion are respectively provided on the first blade and the second blade, that is to say, the mounting assembly has a first mounting state in which a first type of blade assembly including the first blade and the second blade is mounted to the drive shaft. The mounting assembly also has a second mounting state in which the first type of blade assembly is removed and a second type of blade assembly including only one blade is mounted to the drive shaft. In other words, the mounting assembly **16** can not only independently install one or both of the first blade and the second blade, but also independently install other blades that do not belong to the first blade and the second blade.

(70) In an example, the lawn mower includes a first type of blade assembly that performs the

cutting function. The first type of blade assembly includes a first blade, and the first blade is formed with a first cutting portion that is configured to cut grass. The mounting assembly has a first mounting state in which the first type of blade assembly is mounted to the drive shaft so that the blade assembly rotates with the drive shaft; the mounting assembly also has a second type in which the first type of blade assembly is removed and a second type of blade assembly including two cutting portions is mounted to the drive shaft to perform the cutting function; wherein, the two cutting portions of the second type of blade assembly are respectively located on the upper and lower sides in the direction of the rotation axis. That is to say, the mounting assembly causes the lawn mower to switch from the first type of blade assembly with one cutting portion to the second type of blade assembly with two cutting portions; the two cutting portions are respectively located on the upper and lower sides in the direction of the rotation axis. In an example, the second type of blade assembly may include the first cutting portion of the first type of blade assembly, or may not include the first cutting portion of the first type of blade assembly but is otherwise formed second type of blade assembly totally different from the first type of blade assembly. If the second type of blade assembly includes the first cutting portion of the first type of blade assembly, the position of the first cutting portion relative to the drive shaft may be the same or may be changed. For example, the first type of blade assembly includes the first blade provided with the first cutting portion, the second type of blade assembly adds a second blade provided with a second cutting portion in addition to the first type of blade assembly, and the second blade is mounted to the lower side or the upper side of the first blade in the direction of the rotation axis through the mounting assembly.

(71) In an example, the lawn mower includes a blade assembly and a lawn mower body. The lawn mower body includes a deck, a motor, and a battery pack. The motor is mounted to the deck, and the battery pack supplies power to the motor. The blade assembly includes a first type of blade assembly and a second type of blade assembly, and the motor drives the first type of blade assembly or the second type of blade assembly to rotate about a rotation axis; the first type of blade assembly includes a first blade, and the first blade is formed with a first cutting portion for cutting grass; the second type of blade assembly includes a first blade and a second blade, the first blade is formed with a first cutting portion for cutting grass; the second blade is formed with a second cutting portion for cutting grass; wherein, in the direction of the rotation axis, the second cutting portion is located below the first cutting portion; the body of the lawn mower can be adapted to the first type of blade assembly or the second type of blade assembly. The body of the lawn mower can be adapted to mount the second type of blade assembly after the first type of blade assembly is removed, or can be adapted to mount the first type of blade assembly when the second type of blade assembly is removed.

(72) The blade assembly **11** in the present example is driven by friction. The mounting assembly **16** includes a drive member **161**; the drive member **161** is configured to drive the blade assembly **11** to rotate about the rotation axis **100'**; the drive member **161** is connected to the drive shaft **14** and is driven by the shaft **14** is, and the drive member **161** and the blade assembly **11** realize transmission through static friction. In one example, as shown in FIGS. 5-6, the drive member **161** is a flange, and the flange and the drive shaft **14** form a fixed connection in the radial direction, and the blade assembly **11** is in surface contact with the flange in a plane perpendicular to the rotation axis **100'**. The mounting assembly **16** further includes a clamping assembly **162**; the clamping assembly **162** is configured to push the blade assembly **11** along the direction of the rotation axis **100'** to the surface of the drive member **161**; the clamping assembly **162** is mounted to the drive shaft **14** and forms a fixed and detachable connection with the drive shaft **14** in the direction along the rotation axis **100'**. In an example, the drive shaft **14** and the flange form a flat fit, and the clamping assembly **162** includes a bolt **162a** and a first washer **162b**. The flange, the blade assembly **11**, the first washer **162b**, and the bolt **162a** form a close fit from top to bottom along the rotation axis **100'**, wherein the flange, the blade assembly **11**, and the first washer **162b** embrace around the

drive shaft **14**, while the bolt **162a** is inserted into the drive shaft **14** and forms a screw connection with the drive shaft **14**.

(73) As shown in FIG. 5, when the mounting assembly **16** is in the first mounting state, the bottom surface of the drive member **161** is in close contact with the upper surface of the blade assembly **11**. The first washer **162b** and the drive shaft **14** also form a flat fit.

(74) As shown in FIGS. 7-8, the mounting assembly **16** is in the second mounting state. In FIG. 7, only the first blade **111** is mounted to the drive shaft **14** through the mounting assembly **16**. In this example, a second washer **162c** is added to fix the position of the first blade **111** relative to the drive shaft **14** along the direction of the rotation axis **100'**. As shown in FIG. 8, the mounting assembly **16** also includes a fan **15**; the fan **15** is fixedly connected to the drive member **161** and embraces around the outside of the drive member **16**, forming a coaxial connection with the drive member **161**. The fan **15** is driven by the drive member **161**, and the drive member **161** is formed with a drive portion **161a** (as shown in FIG. 5) for driving the fan **15**, the drive portion **161a** protrudes from the drive member **161** in the radial direction, and the fan **15** has a groove to tightly engage with the drive portion **161a**. In the direction of the rotation axis **100'**, the lower surface of the fan **15** is located below the lower surface of the drive member **161**. When only the first blade **111** or the second blade **112** is mounted to the drive shaft **14**, the fan **15** makes surface contact with the blade assembly **11**, the lower surface of the fan **15** pushes against the upper surface of the blade assembly **11**, and the fan **15** and the blade assembly **11** form a friction drive. In an example, the connection between the mounting assembly **16** and the blade assembly **11** can adopt both connection methods in the above two examples at the same time, that is, the mounting assembly **16** presses the first blade **111** or the second blade **112** through the clamping assembly **162**, and the clamping assembly **162** includes the fan **15** and the second washer **162c**.

(75) In an example, the structure of the mounting assembly **16** and the connection method between the mounting assembly **16** and blade assembly **11** are not limited to the above examples, e.g., when the mounting assembly **16** is in the second mounting state, replace the first washer **162b** with a second washer **162c** that is thicker than the first washer **162b**. Simple adjustments or replacements made on the basis of the mounting assembly **16** of the present application for switching the mounting state should be considered within the scope of protection of the present application. The mounting assembly **16** may include a plurality of part or components; the mounting assembly **16** may include different sets of parts or components when the mounting assembly **16** is in the first mounting state and the second mounting state, respectively.

(76) The drive member **161** and the blade assembly **11** make surface contact in a plane perpendicular to the rotation axis **100'**; the contact area of the drive member **161** and the blade assembly **11** is greater than or equal to 100 mm.sup.2 and less than or equal to 1000 mm.sup.2. In an example, the contact area of the drive member **161** and the blade assembly **11** is greater than or equal to 300 mm.sup.2 and less than or equal to 500 mm.sup.2. In this example, the contact area between the flange and the blade assembly **11** is approximately 432 mm.sup.2, and the contact area between the lower surface of the flange and the upper surface of the blade assembly **11** is approximately 432 mm.sup.2. Correspondingly, when the mounting assembly **16** is in the second mounting state and the fan **15** and the blade assembly **11** form a friction drive, the fan **15** and the blade assembly **11** make surface contact in a plane perpendicular to the rotation axis **100'**; the contact area between the fan **15** and the blade assembly **11** is greater than or equal to 100 mm.sup.2 and less than or equal to 1000 mm.sup.2.

(77) As shown in FIGS. 4-6 and FIG. 9, the blade assembly **11** is formed with at least one mounting hole **113** that engages with the drive shaft **14**. In this example, when the blade assembly **11** forms an integral unit that moves together, the blade assembly **11** only has a mounting hole **113** that engages with the drive shaft **14** to facilitate user installation. The mounting hole **113** is located approximately at the center of the blade assembly **11**, and the blade assembly **11** is center symmetrical about the center of the mounting hole **113**, making the blade assembly **11** more stable

when rotating about the rotation axis **100'**, and avoiding the generation of eccentric torques. In an example, the first blade **111** and the second blade **112** are respectively formed with a first mounting hole **113a** and a second mounting hole **113b**. When the blade assembly **11** is mounted to the drive shaft **14**, the first mounting hole **113a** and the second mounting holes **113b** overlap in the up-down direction along the rotation axis **100'**. In an example, the blade assembly **11** may be formed with a plurality of mounting holes **113**, and the mounting assembly **16** includes a plurality of connecting shafts that engage with the mounting holes **113** accordingly, and the connecting shafts are connected to the drive shaft **14**.

(78) As shown in FIG. 5, the mounting assembly **16** is in contact with the blade assembly **11** to form at least one mounting surface **16a** that is substantially perpendicular to the rotation axis **100'**; the blade assembly **11** is formed with at least one cutting surface **11a** that is perpendicular to the rotation axis **100'**; at least one mounting surface **16a** is located above the cutting surface **11a** in the direction of the rotation axis **100'**. In this example, the flange of the mounting assembly **16** or the fan **15** and the first washer **162b** make surface contact with the blade assembly **11** and form two mounting surfaces **16a** perpendicular to the rotation axis **100'**. When the blade assembly **11** includes the first blade **111** or the second blade **112**, the first blade **111** or the second blade **112** rotates about the rotation axis **100'** to form a cutting surface **11a**, the plane where the cutting surface **11a** is located is the plane where the edge **111b** of the first cutting portion **111a** or the edge **112b** of the second cutting portion **112a** is located. When the blade assembly **11** includes the first blade **111** and the second blade **112**, the first blade **111** and the second blade **112** rotate about the rotation axis **100'** to form two parallel upper and lower cutting surfaces **11a**, and the plane where the two upper and lower cutting surfaces **11a** are located are the planes where the edge **111b** of the first cutting portion **111a** and the edge **112b** of the second cutting portion **112a** are respectively located. In this example, one mounting surface **16a** is located above the two cutting surfaces **11a** along the direction of the rotation axis **100'** to avoid installing the mounting assembly **16** below the cutting surface **11a**. In this example, the drive member **161** that drives the blade assembly **11** to rotate is located above the cutting surface **11a**.

(79) As shown in FIG. 9, the blade assembly **11** further includes a connecting assembly **114**. The connecting assembly **114** connects the second blade **112** to the first blade **111** so that the blade assembly **11** forms a unit that can move together when not mounted to the drive shaft **14**. After the connecting assembly **114** connects the second blade **112** to the first blade **111**, the second cutting portion **112a** and the first cutting portion **111a** are located at different axial positions along the rotation axis **100'**. That is to say, when the first blade **111** and the second blade **112** are not integrally formed, the first blade **111** and the second blade **112** are connected as a whole through the connecting assembly **114**, and when not mounted to the drive shaft **14**, the first blade **111** and the second blade **112** may be fixedly connected or movably connected, that is, the first blade **111** may move relative to the second blade **112**. When the blade assembly **11** is mounted to the drive shaft **14** and performs cutting as a whole, the first blade **111** is fixed relative to the second blade **112**. At the same time, the connecting assembly **114** determines the relative position of the first cutting portion **111a** and the second cutting portion **112a** in the direction of the rotation axis **100'**. In an example, the first cutting portion **111a** is located above the second cutting portion **112a**. In this example, the first blade **111** is located above the second blade **112**. The connecting assembly **114** enables the user to disassemble and assemble the blade assembly **11** for ease of operation, while at the same time, fixes the relative axial positions of the first cutting portion **111a** and the second cutting portion **112a** to prevent the user from repositioning the two cutting portions axially during assembly and installing the first blade **111** and the second blade **112** reversely or incorrectly, which plays a foolproof role.

(80) When the connecting assembly **114** connects the second blade **112** to the first blade **111**, the second blade **112** is fixed within a predetermined angle range relative to the first blade **111**. In an example, the predetermined angle range is greater than or equal to 0 degrees and less than or equal

to 20 degrees. In this example, the predetermined angle range is greater than or equal to 5 degrees and less than or equal to 10 degrees. That is to say, the connecting assembly **114** connects the first blade **111** and the second blade **112** so that the first blade **111** and the second blade **112** form a fixed connection or a movable connection in the rotation axial direction, and when the first blade **111** and the second blade **112** form a movable connection in the axial direction, the first blade **111** can rotate relative to the second blade **112** with a rotation angle greater than or equal to 0 degrees and less than or equal to 10 degrees. The first blade **111** and the second blade **112** form a detachable connection through the connecting assembly **114** for ease of maintenance or replacement of the blade assembly **11** later.

(81) In this example, the connecting assembly **114** is a common fastener, such as a bolt and a nut or a screw and a nut. The blade assembly **11** is formed with at least one positioning portion **115** connected to the connecting assembly **114**; the positioning portion **115** can define the range of the phase angle of the first blade **111** relative to the second blade **112**, and the connecting assembly **114** is mounted to the positioning portion **115**. In this example, the positioning portion **115** is a positioning hole, and positioning holes are formed on both the first blade **111** and the second blade **112**. The number of positioning portions **115** is not limited. In this example, the number of positioning portions **115** is greater than or equal to two. In an example, the first blade **111** is formed with two diamond holes symmetrical about the rotation axis **100'**, and the second blade **112** is formed with two round holes symmetrical about the rotation axis **100'**, the diamond holes engage with the diamond-shaped protrusions on the head of the bolts, the round holes engage with the studs of the bolts, and the bolts are locked with the nuts, so that the first blade **111** and the second blade **112** are fixedly connected with a fixed phase angle in the circumferential direction and a fixed relative position in the axial direction. In an example, the positioning hole may also be square or waist or other shaped; the engagement manner between the positioning hole on the first blade **111** and the positioning hole on the second blade **112** and the connecting assembly **114** is not limited herein.

(82) The connecting assembly **114** includes an engaging portion **114a** that engages with the positioning portion **115**. In this example, the positioning portion **115** is a positioning hole, the engaging portion **114a** is a bolt, and is a screw of the bolt, which engage with the positioning hole to form a shaft hole fit. The connecting assembly **114** further includes an axial fixing portion that fixes the position of the first blade **111** relative to the second blade **112** in a direction parallel to the rotation axis **100'**, and the axial fixing portion is a bolt and nut. In an example, the axial fixing portion may be a magnetic element mounted to the first blade **111** and the second blade **112**, and the axial position of the first blade **111** relative to the second blade **112** is fixed by magnetic attraction. The specific structures of the engaging portion **114a** and the axial fixing portion are not limited to the above.

(83) In an example, the engaging portion of the connecting assembly is provided on a mounting member such as a fan or a flange, and forms a fixed connection or is integrally formed with the mounting member such as a fan and a flange. For example, a drive portion is formed at the lower end of the fan, and the drive portion is configured to mount and position the blade assembly. In one example, the connecting assembly further includes a clamping member that axially clamps the blade assembly, and the clamping member is connected to the blade assembly and makes surface contact with the blade assembly. In this case, the blade assembly can form either a friction transmission or a mechanical position transmission such as a flat position transmission with the drive shaft.

(84) As shown in FIGS. 4, 5, and 10, the positioning portion **115** generally has a geometric center. The distance from the geometric center to the rotation axis **100'** is the positioning radius r , and the positioning radius r is greater than or equal to 0 mm and less than or equal to 50 mm. In one example, the positioning radius r of the positioning portion **115** is greater than or equal to the radius of the drive shaft **14** and less than or equal to 50 mm; in this example, the positioning radius r of

the positioning portion **115** is about 30 mm. When the positioning radius r of the positioning portion **115** is 0 mm, that is, the geometric center of the positioning portion **115** coincides with the rotation axis **100'**. In one example, a radial groove is formed on the drive shaft **14**, and the groove can accommodate the positioning portion **115**. The positioning portion **115** is provided outside the drive shaft **14**, that is, the positioning radius r of the positioning portion **115** is greater than or equal to the radius of the drive shaft **14**. For a regularly shaped positioning portion **115**, the geometric center is uniquely determined; for an irregularly shaped positioning portion **115**, a point at the center of the positioning portion **115** may be roughly determined to be the geometric center. In one example, the ratio of the rotation diameter D of the blade assembly **11** to the positioning radius r of the positioning portion **115** is greater than or equal to 5 and less than or equal to 25. When the position of the positioning unit **115** is in the above range, the positioning effect of the positioning unit **115** is better. The rotation diameter D is greater than or equal to 200 mm and less than or equal to 700 mm.

(85) In an example, the positioning hole may be other positioning holes with incomplete positioning effects, such as oval holes. These positioning holes can restrict to a predetermined degree but cannot completely restrict the rotation of the first blade **111** relative to the second blade **112**, such that the blade assembly **11** has a predetermined adjustment space when encountering obstacles, thereby enhancing the service life of the blade assembly **11**.

(86) The maximum length of the line connecting any two points of the projection of the first blade **111** in a plane perpendicular to the rotation axis **100'** in the direction perpendicular to the rotation diameter $D1$ of the first blade **111** is the width $W1$ of the first blade **111**. The ratio of the rotation diameter $D1$ of the first blade **111** to the width $W1$ of the first blade **111** is equal to or greater than 5 and less than or equal to 13. The maximum length of the line connecting any two points of the projection of the second blade **112** in a plane perpendicular to the rotation axis **100'** in the direction perpendicular to the rotation diameter $D2$ of the second blade **112** is the width $W2$ of the second blade **112**. The ratio of the rotation diameter $D2$ of the second blade **112** to the width $W2$ of the second blade **112** is equal to or greater than 5 and less than or equal to 13. In this example, the rotation diameter $D1$ of the first blade **111** is approximately 511 mm, the width $W1$ of the first blade **111** is approximately 51 mm, and the rotation diameter $D2$ of the second blade **112** is approximately equal to the rotation diameter $D1$ of the first blade **111**. The width $W2$ of the second blade **112** is approximately equal to the width $W1$ of the first blade **111**.

(87) As shown in FIGS. **9** and **10**, at least one reinforcement rib **116** is respectively formed on the surfaces of the first blade **111** and the second blade **112**. In this example, the first blade **111** and the second blade **112** are respectively formed with two reinforcement ribs **116**. The two reinforcement ribs **116** on the surface of the first blade **111** protrude upward and extend along the length of the first cutting portion **111a**, and are symmetrical about the rotation axis **100'**; the two reinforcement ribs **116** on the surface of the second blade **112** protrude downward and extend along the length of the second cutting portion **112a**, and are symmetrical about the rotation axis **100'**. The shape of the reinforcement rib **116** is a long stripe. The ratio of the rotation diameter $D1$ of the first blade **111** to the length $a1$ of a single reinforcement rib **116** is greater than or equal to 2.5 and less than or equal to 10; the ratio of the rotation diameter $D1$ of the first blade **111** to the total length of the plurality of the reinforcement ribs **116** is greater than or equal to 1.3 and less than or equal to 5; the ratio of the width $W1$ of the first blade **111** to the width $b1$ of a single reinforcement rib **116** is greater than or equal to 2 and less than or equal to 5. Similarly, the ratio of the rotation diameter $D2$ of the second blade **112** to the length $a1$ of a single reinforcement rib **116** is greater than or equal to 2.5 and less than or equal to 10; the ratio of the rotation diameter $D2$ of the second blade **112** to the total length of the plurality of the reinforcement ribs **116** is greater than or equal to 1.3 and less than or equal to 5; the ratio of the width $W2$ of the second blade **112** to the width $b1$ of a single reinforcement rib **116** is greater than or equal to 2 and less than or equal to 5. In one example, the length $a1$ of the reinforcement rib **116** refers to the maximum dimension of the projection of the

reinforcement rib **116** in a plane perpendicular to the rotation axis **100'** in the extending direction of the reinforcement rib **116**; the width **b1** of the reinforcement rib **116** refers to the maximum dimension of the projection of the reinforcement rib **116** in a plane perpendicular to the rotation axis **100'** in the direction perpendicular to the extending direction of the reinforcement rib **116**. In the extending direction of the first blade **111** or the second blade **112** and in the direction perpendicular to the extending direction of the first blade **111** or the second blade **112**, the reinforcement ribs **116** are distributed in the middle of the first blade **111** and the second blade **112** to improve the strength of the first blade **111** or the second blade **112**. In other examples, the number, position, and specific shape of the reinforcement rib **116** are not limited thereto.

(88) In this example, the first blade **111** substantially extends along the direction of the first straight line; the second blade **112** substantially extends along the direction of the first curve. Since the first blade **111** is disposed above the second blade **112** in the direction of the rotation axis **100'**, and at the same time the first curve is at least partially curved downward, a sufficient accommodation space is formed between the first blade **111** and the second blade **112**. In an example, the first blade **111** extends substantially in the direction of the second curve; the second blade **112** extends substantially in the direction of the third curve, that is, the first blade **111** and the second blade **112** extend along the curve respectively. The second curve and the third curve are two different curves differing in at least part of their curvatures, so that a sufficient accommodation space is formed between the first blade **111** and the second blade **112**.

(89) The length of the projection of the first cutting portion **111a** in a plane perpendicular to the rotation axis **100'** is greater than or equal to 10 mm and less than or equal to 600 mm; the length of the projection of the second cutting portion **112a** in a plane perpendicular to the rotation axis **100'** is greater than or equal to 10 mm and less than or equal to 600 mm. In an example, the length of the projection of the first cutting portion **111a** in a plane perpendicular to the rotation axis **100'** refers to the length of the projection of the edge **111b** of the first cutting portion **111a** in a plane perpendicular to the rotation axis **100'**. When the first blade **111** includes a plurality of the first cutting portions **111a**, the length of the projection of the first cutting portion **111a** in a plane perpendicular to the rotation axis **100'** is the sum of the length of the projection of the edges **111b** of the plurality of the first cutting portions **111a** in a plane perpendicular to the axis **100'**. Similarly, the length of the projection of the second cutting portion **112a** in a plane perpendicular to the rotation axis **100'** refers to the length of the projection of the edge **112b** of the second cutting portion **112a** in a plane perpendicular to the rotation axis **100'**. When the second blade **112** includes a plurality of the second cutting portions **112a**, the length of the projection of the second cutting portion **112a** in a plane perpendicular to the rotation axis **100'** is the sum of the length of the projection of the edges **112b** of the plurality of the second cutting portions **112a** in a plane perpendicular to the rotation axis **100'**. Both the length of the projection of the first cutting portion **111a** in a plane perpendicular to the rotation axis **100'** and the length of the projection of the second cutting portion **112a** in a plane perpendicular to the rotation axis **100'** are greater than or equal to 10 mm and less than or equal to 600 mm. In an example, the length of the projection of the first cutting portion **111a** in a plane perpendicular to the rotation axis **100'** and the length of the projection of the second cutting portion **112a** in a plane perpendicular to the rotation axis **100'** are greater than or equal to 20 mm and less than or equal to 400 mm. In this example, the length of the projection of the first cutting portion **111a** in a plane perpendicular to the rotation axis **100'** is about 236 mm. In one example, the length of the projection of the first cutting portion **111a** in a plane perpendicular to the rotation axis **100'** and the length of the projection of the second cutting portion **112a** in a plane perpendicular to the rotation axis **100'** are substantially equal.

(90) The mass of the blade assembly **11** is greater than or equal to 0.35 kg and less than or equal to 1.8 kg. When the mass of the blade assembly **11** is within this value range, the lawn mower **100** has a relatively small load and relatively high work efficiency. When the first blade **111** and the second blade **112** is separately formed and the mass of the first blade **111** is less than or equal to the mass

of the second blade **112**, the ratio of the mass of the first blade **111** to the mass of the second blade **112** is greater than or equal to 0.5 and less than or equal to 1. In an example, when the first blade **111** and the second blade **112** are separately formed and the mass of the second blade **112** is less than or equal to the mass of the first blade **111**, the ratio of the mass of the second blade **112** to the mass of the first blade **111** is greater than or equal to 0.5 and less than or equal to 1.

(91) The battery pack includes a battery pack housing and battery cells. The battery cells are disposed in the battery pack housing. The number of battery cells included in the battery pack is N and the unit is piece. The mass of the blade assembly **11** is M and the unit is kilogram. The maximum length of a line connecting any two points of the projection of the blade assembly **11** in a plane perpendicular to the rotation axis **100'** and the projection of the rotation axis **100'** in the plane is the rotation diameter D of the blade assembly **11**; and the unit is millimetre. The product of the rotation diameter D (mm) of the blade assembly **11**, the number of battery cells N and mass M (g) of the blade assembly **11** is greater than or equal to $3.5 \times 10^{5.5}$ and less than or equal to $7.3 \times 10^{7.7}$. In one example, the product of the rotation diameter D (mm) of the blade assembly **11**, the number of battery cells N and mass M (g) of the blade assembly **11** is greater than or equal to $7 \times 10^{5.5}$ (mm.Math.g) and less than or equal to $3.6 \times 10^{7.7}$ (mm.Math.g). In one example, the product of the rotation diameter D (mm) of the blade assembly **11**, the number of battery cells N and mass M (g) of the blade assembly **11** is greater than or equal to $1.4 \times 10^{6.6}$ (mm.Math.g) and less than or equal to $1.8 \times 10^{7.7}$ (mm.Math.g). When the product of the rotation diameter D (mm) of the blade assembly **11**, the number of battery cells N and mass M (g) of the blade assembly **11** is in the above numerical range, the lawn mower **100** has a relatively small load and relatively high work efficiency. In this example, the mass M of the blade assembly **11** refers to the total mass of the blade assembly **11** including the first blade **111** and the second blade **112**. When the lawn mower **100** includes multiple battery packs, the number N of battery cells here refers to the total number of battery cells included in all battery packs. In this example, the rotation diameter D of the blade assembly **11** is about 508 mm, and the number N of battery cells contained in the battery pack is equal to 10. In one example, the number N of battery cells refers to the number of battery cells included in the battery pack that powers the motor **13** that drives the blade assembly **11**. If the lawn mower **100** is a self-propelled lawn mower, generally it also includes a self-propelled motor that drives the wheels to rotate. In this case, the motor **13** should not include the self-propelled motor. That is to say, the battery packs here do not include the battery pack that powers the self-propelled motor.

(92) In one example, the larger value of the rotation diameter D1 of the first blade **111** and the rotation diameter D2 of the second blade **112** is defined as the lateral dimension of the blade assembly **11**. The battery pack contains the number N of battery cells, and the mass of the blade assembly **11** is M (g). The product of the lateral dimension (mm) of the blade assembly **11**, the number N of battery cells, and the mass M (g) of the blade assembly **11** is greater than or equal to $3.5 \times 10^{5.5}$ (mm.Math.g) and less than or equal to $7.3 \times 10^{7.7}$ (mm.Math.g). In one example, the product of the lateral dimension (mm) of the blade assembly **11**, the number N of battery cells, and the mass M (g) of the blade assembly **11** is greater than or equal to $7 \times 10^{5.5}$ (mm.Math.g) and less than or equal to $3.6 \times 10^{7.7}$ (mm.Math.g). In one example, the product of the lateral dimension (mm) of the blade assembly **11**, the number N of battery cells, and the mass M (g) of the blade assembly **11** is greater than or equal to $3.6 \times 10^{7.7}$ (mm.Math.g) and less than or equal to $1.8 \times 10^{7.7}$ (mm.Math.g).

(93) The output torque of the motor **13** is greater than or equal to 0 and less than or equal to 10 N.Math.m; in one example, the output torque of the motor **13** is greater than or equal to 3 N.Math.m and less than or equal to 8 N.Math.m; in this example, the output torque of the motor **13** is about 4 N.Math.m. When the output torque of the motor **13** is in the above numerical range, the lawn mower **100** has higher cutting efficiency or cutting capacity.

(94) In this example, the rotational inertia of the blade assembly **11** is greater than or equal to 8000

kg.Math.mm.sup.2 and less than or equal to 23000 kg.Math.mm.sup.2; in one example, the rotational inertia of the blade assembly **11** is greater than or equal to 15000 kg.Math.mm.sup.2 and less than or equal to 20000 kg.Math.mm.sup.2.

(95) In addition, under certain working conditions, the lawn mower **100** not only needs to cut the vegetation, but also needs to chop up the vegetation clippings into finer pieces, or to collect the vegetation clippings into a collecting device. By adopting the structural design of the blade assembly **11** described above, the lawn mower **100** also has a better ability to chop up grass or discharge grass. The lawn mower **100** is also provided with a collecting device for collecting the vegetation clippings. The collecting device is connected to the deck **12**. In an example, the deck **12** is formed with a discharge chute; the collecting device is connected to the discharge chute to let the vegetation clippings enter the collecting device from the deck **12**. When the blade assembly **11** rotates at a tip linear velocity greater than or equal to 40 m/s and less than or equal to 100 m/s, the average air velocity at the discharge chute is greater than or equal to 3 m/s and less than or equal to 25 m/s. In an example, when the blade assembly **11** rotates at a tip linear velocity greater than or equal to 40 m/s and less than or equal to 100 m/s, the average air velocity at the discharge chute is greater than or equal to 5 m/s and less than or equal to 15 m/s. When the average air velocity at the discharge chute is in the above numerical range, the grass chopping ability and the grass discharging ability of the lawn mower **100** can be improved.

(96) In this example, the linear velocity of the tip of the blade assembly **11** refers to the linear velocity of the point on the blade assembly **11** with the largest distance to the axis of rotation **100'** when the blade assembly **11** rotates around the axis of rotation **100'**.

Example 2

(97) FIG. **11** is a schematic diagram of the blade assembly **21** of the lawn mower provided in Example 2 of the present application mounted to the drive shaft **24**. The difference between this example and the first example is that the blade assembly **21** in this example does not include a connecting assembly, and the blade assembly **21** has a positioning portion **213** and a engaging portion **214** to define the phase angle range between the first blade **211** and the second blade **212**, whereas the remaining structure of the lawn mower of this example is the same as that of Example 1. One of the first blade **211** and the second blade **212** is formed with a positioning portion **213**, and the other one is formed with a engaging portion **214** to engage with the positioning portion **213**; when the positioning portion **213** and the engaging portion **214** engage with each other, the second blade **212** is fixed or can rotate within a predetermined angle range relative to the first blade **211** in the circumferential direction around the rotation axis **211'**. That is to say, without the connecting assembly, the position of the second blade **212** relative to the first blade **211** in the circumferential direction around the rotation axis **211'** can be defined by the positioning portion **213** and the engaging portion **214** only. In this example, the first blade **211** and the second blade **212** are respectively provided with an engaging portion **214** and a positioning portion **213**. The positioning portion **213** is a projection provided on the second blade **212** and protruding above the upper surface of the second blade **212**; the engaging portion **214** is a through hole provided on the first blade **211**. When the first blade **211** and the second blade **212** are mounted to the drive shaft **24**, the projection passes through the through hole and engages with the through hole, thereby achieving the positioning of the first blade **211** relative to the second blade **212** in the circumferential direction around the rotation axis **211'**. The positioning portion **213** may be a regular three-dimensional structure such as a cylindrical shape or other irregular shapes. The engaging portion **214** may be a through hole with a circular cross section or other through holes that can engage with the positioning portion **213**.

(98) In an example, the specific structures of the positioning portion **213** and the engaging portion **214** are not limited to the above projections and through holes. For example, the positioning portion **213** may be a projection protruding from the second blade **212**, and the engaging portion **214** may be an accommodating portion protruding upward on the surface of the first blade **211**; the

accommodating portion can accommodate at least part of the positioning portion **213** or engage with the positioning portion **213**, so as to realize the positioning of the first blade **211** relative to the second blade **212**.

(99) The number of the positioning portion **213** and the engaging portion **214** is not limited. In an example, the number of the positioning portion **213** and the engaging portion **214** are even and the positioning portion **213** and the engaging portion **214** are respectively arranged symmetrically about the rotation axis **211'** to put uniform force on the first blade **211** and the second blade **212**, so that the position of the first blade **211** relative to the second blade **212** is more stable.

(100) Similar to Example 1, the positioning portion **213** according to the present example generally has a geometric center; the distance from this geometric center to the rotation axis **211'** is the positioning radius r' ; the radius r' of the positioning portion **213** is greater than or equal to 0 mm and less than or equal to 50 mm. In one example, the positioning radius r' of the positioning portion **213** is greater than or equal to the radius of the drive shaft **24** and less than or equal to 50 mm; in this example, the positioning radius r' of the positioning portion **213** is about 30 mm. When the positioning radius r' is 0 mm, that is, the geometric center of the positioning portion **213** coincide with the rotation axis **211'**. In one example, a radial groove is made on the drive shaft **24** to accommodate the positioning portion **213**. The positioning portion **213** is provided outside the drive shaft **24**, that is, the positioning radius r' of the positioning portion **213** is greater than or equal to the radius of the drive shaft **24**. For a regularly shaped positioning portion **213**, the geometric center is uniquely determined; for an irregularly shaped positioning portion **213**, a point at the center of the positioning portion **213** may be roughly determined to be the geometric center. The maximum length of a line connecting any two points of the projection of the blade assembly **21** in a plane perpendicular to the rotation axis **211'** and the projection of the rotation axis **211'** in the plane is the rotation diameter of the blade assembly **21**. The rotation diameter is greater than or equal to 200 mm and less than or equal to 700 mm. In one example, the rotation diameter is greater than or equal to 250 mm and less than or equal to 560 mm. In an example, the ratio of the rotation diameter of the blade assembly **21** to the positioning radius r' of the positioning portion **213** is greater than or equal to 5 and less than or equal to 25. When the position of the positioning portion **213** is within the above range, the positioning effect of the positioning portion **213** is better. Correspondingly, the engaging portion **214** also has a geometric center, and the distance from the geometric center to the rotation axis **211'** is the positioning radius of the engaging portion **214**; the positioning radius of the engaging portion **214** is greater than or equal to 0 and less than or equal to 50 mm; in one example, the positioning radius of the engaging portion **214** is greater than or equal to the radius of the drive shaft **24** and less than or equal to 50 mm.

Example 3

(101) FIG. **12** is a schematic diagram of a blade assembly and a connection assembly of a lawn mower provided in Example 3 of the present application. The difference from Example 1 and Example 2 lies in the structure of the connecting assembly and the connection method between the connecting assembly and the blade assembly, whereas other similarities can be applied to this example. The lawn mower includes a connecting assembly **312**; the connecting assembly **312** is formed with a first connection portion **312a** that connects the first blade **311** and a second connection portion **312b** that connects the second blade **313**; the second blade **313**, relative to the first blade **311**, is fixed or can rotate within a predetermined angle range in the circumferential direction around the rotation axis **311'**. That is to say, the first blade **311** and the second blade **313** are fixed or can rotate within a predetermined angle range in the circumferential direction around the rotation axis **311'** through the connecting assembly **312**, and the first blade **311** and the second blade **313** themselves do not constitute a connection. In this example, the connecting assembly **312** is a flange, but it is not limited to a flange. The connecting assembly **312** forms a fixed connection with the first blade **311** and the second blade **313** respectively in the up-down direction to make the first blade **311** and the second blade **313** construct a fixed phase angle. The connection of the

connecting assembly **312** to the first blade **311** and the second blade **313** may also be movable, so that the second blade **313** can rotate within a predetermined angle range relative to the first blade **311** in the circumferential direction around the rotation axis **311'**.

Example 4

(102) FIGS. **13-16** are schematic views of a blade assembly **41** of a lawnmower provided in Example 4 of the present application. Similarly, the blade assembly **41** rotates about the rotation axis **411'**. The blade assembly **41** in this example differs from the lawn mower in Example 1 only in the structure of the second blade **412** of the blade assembly **41**. Similarities to Example 1 can be applied to this example. In the direction parallel to the rotation axis **411'**, the second cutting portion **412a** is located below the first cutting portion **411a**; in the circumferential direction around the rotation axis **411'**, the first cutting portion **411a** is provided in front of the second cutting portion **412a**; second cutting portion **412a** is disposed on the front edge of the second blade **412**. In an example, the front side in the circumferential direction around the rotation axis **411'** refers to the side that first contacts the vegetation when the blade assembly **41** rotates along the rotation axis **411'** in the first direction **A'**. The first cutting portion **411a** contacts the vegetation prior to the second cutting portion **412a**; and the second cutting portion **412a** is provided on the edge of the second blade **412** that first contacts the vegetation. In this example, two first cutting portions **411a** are respectively disposed on the front sides of both ends of the first blade **411**, and the two first cutting portions **411a** are center symmetrical about the rotation axis **411'**; two second cutting portions **412a** are respectively disposed on the front sides of both ends of the second blade **412**, and the two second cutting portions **412a** are center symmetrical about the rotation axis **411'**, and the blade assembly **41** as a whole is also center symmetrical about the rotation axis **411'**.

(103) The rear side of the second blade **412** is also formed with a first guide portion **412b** and a second guide portion **412c** that guide the upward movement of the airflow, that is, the second blade **412** is formed with a first guide portion **412b** and a second guide portion **412c** on the side opposite to the second cutting portion **412a** in the circumferential direction of the rotation axis **411'**. The first guide portion **412b** and the second guide portion **412c** are configured to guide the air flow upward. Here, the first guide portion **412b** and the second guide portion **412c** refer to two at least partially separated entities. In this example, the first guide portion **412b** and the second guide portion **412c** are integrally formed with the second blade **412**; the first guide portion **412b** and the second guide portion **412c** extend substantially along the direction perpendicular to the longitudinal direction of the second blade **412** and are sequentially arranged along the longitudinal direction of the second blade **412**. In one example, the first guide portion **412b** and the second guide portion **412c** may be respectively formed separately from the second blade **412** and fixedly connected to the second blade **412**.

(104) Each second cutting portion **412a** corresponds to a first guide portion **412b** and a second guide portion **412c**. The first guide portion **412b** and the second guide portion **412c** are disposed at the rear side of the same end of the second cutting portion **412a**. In this example, since the second blade **412** is provided with two second cutting portions **412a**, two first guide portions **412b** and two second guide portions **412c** are formed, the two first guide portions **412b** and the two second guide portions **412c** are center symmetrical about the rotation axis **411'**.

(105) The first guide portion **412b** is curved upward along the first curved surface, and the second guide portion **412c** is curved upward along the second curved surface different from the first curved surface. In an example, at least part of the first guide portion **412b** and at least part of the second guide portion **412c** have different curvatures. The first guide portion **412b** and the second guide portion **412c** may each have a fixed curvature, or the curvatures of the first guide portion **412b** and the second guide portion **412c** may change according to a predetermined rule or change irregularly, which is not limited herein. In this example, the first guide portion **412b** and the second guide portion **412c** each have varying curvatures. In one example, the curvature radius at any point of the first guide portion **412b** and the second guide portion **412c** is equal to or greater than 0 and

less than or equal to 100 mm. In this example, the curvature radius at any point of the first guide portion **412b** and the second guide portion **412c** is equal to or greater than 0 mm and less than or equal to 60 mm.

(106) The second blade **412** includes at least a first guide portion **412b** and a second guide portion **412c**. In this example, the second blade **412** is further provided with a third guide portion. In an example, the second blade **412** may further be provided with a plurality of guide portions such as a fourth guide portion, and the plurality of guide portions are sequentially arranged along the extension direction of the second blade **412**.

(107) The first guide portion **412b** and the second guide portion **412c** are both curved up from the end of the second blade **412**, the portion where the first guide portion **412b** starts to turn up is the first root portion **412d**, and the portion where the second guide portion **412c** starts to turn up is the second root portion **412e**. The first root portion **412d** and the second root portion **412e** are approximately on the same straight line, and this straight line intersects the extension line of the blade edge of the second cutting portion **412a** obliquely, and the intersection angle β formed by the straight line and the extension line of the cutting edge of the cutting portion **412a** is greater than or equal to 0 and less than or equal to 40 degrees. In an example, the intersection angle formed by the straight line and the extension line of the cutting edge of the second cutting portion **412a** is greater than or equal to 0 and less than or equal to 15 degrees. In this example, the intersection angle formed by the straight line and the extension line of the second cutting portion **412a** is about 6.9 degrees.

(108) The outside of the first guide portion **412b** and the outside of the second guide portion **412c** extend substantially along the same straight line, and the straight line obliquely intersects the extension line of the second cutting portion **412a**. The outside of the first guide portion **412b** refers to the edge opposed to the first root **412d**, and the outside of the second guide portion **412c** refers to the edge opposed to the second root **412e**. In this example, the extending direction of the outside of the first guide portion **412b** and the outside of the second guide portion **412c** is substantially parallel to the straight line where the first root portion **412d** and the second root portion **412e** are located.

(109) In this example, a cutting portion opening is further formed on the outside of the first guide portion **412b** and the outside of the second guide portion **412c**. The cutting portion opening can further cut vegetation and improve the grass chopping ability of the lawn mower. In an example, the cutting portion opening on the first guide portion **412b** and the second guide portion **412c** is not necessarily a common cutting portion structure, as long as it has predefined cutting capabilities.

Example 5

(110) FIG. 17 is a schematic diagram of part of the structure of the lawn mower provided in Example 5 of the present application. This example differs from Example 1 in the structure of the blade assembly **51** and the mounting assembly **56**, whereas similarities to Example 1 can be applied to this example.

(111) As shown in FIGS. 17-19, the motor drives the blade assembly **51** to rotate about the rotation axis **511'**; the blade assembly **51** includes a first cutting portion **511a** and a second cutting portion **512a** configured to cut vegetation; wherein in the direction parallel to the rotation axis **511'**, the second cutting portion **512a** is located below the first cutting portion **511a**; in this example, the blade assembly **51** includes a first blade **511** and a second blade **512**, and the first cutting portion **511a** is disposed on the first blade **511**, the second cutting portion **512a** is disposed on the second blade **512**, and the first blade **511** is mounted above the second blade **512** in the direction of the rotation axis **511'**. The mounting assembly **56** includes a drive member **561**, the drive member **561** is configured to drive the blade assembly **51** to rotate about the rotation axis **511'**; the blade assembly **51** is detachably connected to the drive member **561**. In an example, the drive member **561** is connected to the drive shaft **54** and rotates synchronously with the drive shaft **54**. The drive member **561** and the drive shaft **54** form a fixed connection along the circumferential direction of

the rotation axis **511'**, such as a flat connection or a threaded connection.

(112) In this example, the mounting assembly **56** further includes a drive portion **561a**, the drive portion **561a** is fixedly connected to the drive member **561** or integrally moulded with the drive member **561**; the drive portion **561a** is connected to the blade assembly **51** so that blade assembly **51** forms a fixed connection along the circumferential direction of the rotation axis **511'** relative to the drive member **561** or the blade assembly **51** rotates within a predetermined angle range relative to the drive member **561** along the circumferential direction of the rotation axis **511'**. In an example, the drive portion **561a** is respectively connected to the first blade **511** and the second blade **512**, and drive the first blade **511** and the second blade **512** are to rotate synchronously with the drive portion **561a**. There is no limitation on the position where the drive portion **561a** is provided and the number of drive portions **561a**. In this example, the number of drive portions **561a** is two, and the two drive portions **561a** are respectively disposed on two sides of the rotation axis **511'**, and the first blade **511** and the second blade **512** are stacked together in the direction of the rotation axis **511'** with at least partial contact. Both of the two drive portions **561a** are connected to the first blade **511** and the second blade **512**; the first blade **511** and the second blade **512** are formed with positioning holes engaging with the two drive portions **561a**; one of the drive portion **561a** is substantially cylindrical and forms a rotational connection with the first blade **511** and the second blade **512**; the other drive portion **561a** forms a flat connection with the first blade **511** and the second blade **512**. In other examples, only one drive portion **561a** may be provided; the drive portion **561a** and the blade assembly **51** form a flat connection. Alternatively, two cylindrical drive portions **561a** may be provided to connect to the blade assembly **51**.

(113) The mounting assembly **56** further includes a clamping assembly **562** and a fastening assembly **563**; the clamping assembly **562** is configured to clamp the blade assembly **51** along the rotation axis **511'**, and the blade assembly **51** is disposed between the drive member **561** and the clamping assembly **562** in a direction parallel to the rotation axis **511'**; the fastening assembly **563** is set to fix the position of the blade assembly **51** relative to the drive member **561** in the direction parallel to the rotation axis **511**; the fastening assembly **563** is removably connected to the drive shaft **54**. In this example, the clamping assembly **562** may be one or more metal shims and is at least partially in contact with the blade assembly **51**; the fastening assembly **563** may be a nut, screw, or bolt, etc. The fastening assembly **563** is connected to the drive shaft **54** and pushes against the clamping assembly **562**. In this example, the drive shaft **54** passes through the blade assembly **51** and the clamping assembly **562**; the fastening assembly **563** and the drive shaft **54** form a threaded connection. In an example, when the fastening assembly **563** includes a bolt or a screw, etc., there may be a fastening assembly **563** passing through at least one of the blade assembly **51** and the clamping assembly **562**. The fastening assembly **563** and the drive shaft **54** form a fixed and detachable connection.

(114) The mounting assembly **56** further includes an insulating member **564**; the insulating member **564** is configured to achieve the insulation between the blade assembly **51** and the drive shaft **54**; the insulating member **564** is made of insulating materials; the insulating member **564** is provided between the clamping unit **562** and the blade assembly **51** in the direction of the rotation axis **511'**; the first blade **511** and the second blade **512** are both disposed between the drive member **561** and the insulating member **564**. In this example, the insulating member **564** is in surface contact with the blade assembly **51** and the clamping assembly **562**. A groove **564a** is formed at the bottom of the insulating member **564** in the direction of the rotation axis **511'**, and the clamping assembly **562** is embedded in the groove **564a**. The drive shaft **54** or the fastening assembly **563** passes through the insulating member **564**.

(115) In this example, the lawn mower does not include a connecting assembly that connects the first blade **511** and the second blade **512** as a whole before installation. That is to say, the first blade **511** and the second blade **512** are two independently formed and independently mounted blades, which are respectively mounted to the drive shaft **54** and constituted by the mounting assembly **56**.

In this example, the blade assembly **51** is connected through the drive portion **561a** so that the phase angle between the first blade **511** and the second blade **512** is substantially unchanged.

Example 6

(116) FIG. **20** is a schematic diagram of a part of the structure of the lawn mower provided in Example 6 of the present application. The difference between this example and Example 5 is the structure of the mounting assembly **66**, whereas the similarities to Example 5 can be applied to this example.

(117) As shown in FIGS. **20-22**, the mounting assembly **66** in this example differs from the mounting assembly **56** in Example 5 in the structure of the insulating member **664**. In this example, in the direction of the rotation axis **611'**, two grooves, an upper groove **664a** and a lower groove **664b**, are provided above and below the insulating member **664**; and the first blade **611** and the second blade **612** are provided in the upper groove **664a**; the clamping assembly **662** is disposed in the lower groove **664b**. The shape of the upper groove **664a** fits the blade assembly **61** so that the first blade **611** and the second blade **612** form a predetermined phase angle along the rotation axis **611'**. As in Example 5, the drive member **661** is provided with a drive portion **661a** (referring to FIG. **20**). In this example, the design of the insulating member **664** not only better realizes the insulation between the blade assembly **61** and the drive shaft, but also helps the blade assembly **61** maintain a fixed phase angle to prevent slippage; at the same time, it is beneficial for the drive member **661** to drive the blade assembly **61** more efficiently.

Example 7

(118) FIG. **23** is a schematic diagram showing a part of the structure of the lawn mower provided in Example 7 of the present application. The difference between this example and Example 6 lies in the structure of the mounting assembly **76**; similarities to Example 6 can be applied to this example.

(119) As shown in FIGS. **23-25**, the mounting assembly **76** in this example differs from the mounting assembly **66** in Example 6 in the structure of the drive member **761** and the insulating member **764**. In this example, the drive member **761** drives the blade assembly **71** by friction. The drive member **761** and the blade assembly **71** form at least partial contact through the clamping assembly and the fastening assembly. In this example, the drive member **761** and the blade assembly **71** are in surface contact and are pressed against each other, and a positive pressure in the direction of the rotation axis **701** is formed between the drive member **761** and the blade assembly **71**. When the drive shaft drives the drive member **761** to rotate about the rotation axis **701**, the blade assembly **71** rotates about the rotation axis **701** under the frictional force along the circumferential direction of the rotation axis **701**. That is to say, there is no need to provide a drive portion for driving the blade assembly **71** on the drive member **761**, and there is no need to provide a positioning hole on the blade assembly **71** to engage with the drive portion. The drive member **761** drives the first blade **711** by friction, and the first blade **711** drives the second blade **712** by driving the insulating member **764**. The insulating member **764** is disposed between the first blade **711** and the second blade **712**; the insulating member **764** is also formed with an upper groove **764a** and a lower groove **764b**; the first blade **711** is disposed in the upper groove **764a**, and the second blade **712** is disposed in the lower groove **764b**. That is to say, the first blade **711** is disposed between the drive member **761** and the insulating member **764**; the second blade **712** is disposed between the insulating member **764** and the clamping assembly **762**. In an example, the upper groove **764a** and the lower groove **764b** are fitted to the edges of the first blade **711** and the second blade **712** respectively to make the first blade **711** and the second blade **712** to form a phase angle of the predetermined range. The clamping assembly **762** is pressed to the second blade **712**. In this example, the clamping assembly **762** is attached to the lower surface of the second blade **712**.

Example 8

(120) FIG. **26** is a schematic diagram of a part of the structure of the lawn mower provided in

Example 8 of the present application. This example differs from Example 5 in the structure of the blade assembly **81** and the mounting assembly **86**. Similarities to Example 5 can be applied to this example. The blade assembly **81** includes at least two separately formed first blades **811** and an integrally formed second blade **812**. In this example, the number of first blades **811** is two and each of the first blades **811** is provided a first cutting portion **811a**; the second blade **812** is provided with a second cutting portion **812a**. In the direction of the rotation axis **801**, the first blades **811** are located above the second blade **812**. The two first blades **811** are respectively located on both sides of the rotation axis **801** and are fixedly connected to the second blade **812**. In an example, the first blade **811** is detachably connected to the second blade **812**. In other examples, the first blade **811** is an integrally formed blade, and the second blade **812** is a plurality of separately formed blades, each being fixedly connected to the first blade **811**. A first cutting portion **811a** and a second cutting portion **812a** are respectively provided on the first blade **811** and the second blade **812**. In an example, the first blade **811** and the second blade **812** are integrally formed, but the first cutting portion **811a** and the second cutting portion **812a** are respectively provided on the first blade **811** and the second blade **812**. That is to say, the blade assembly **81** is a one-piece blade, but is provided with a plurality of first cutting portions **811a** and second cutting portions **812a** distributed up and down along the direction of the rotation axis **801**.

(121) In this example, the drive member **861** is provided with a drive portion, and the blade assembly **81** is provided with a positioning hole that engages with the drive portion. The drive portion **861** drives the blade assembly **81** to rotate through the drive portion. In an example, the drive portion is connected to the first blade **811**. The shape and number of drive portion is not limited. In one example, the drive member **861** is not provided with a drive portion; instead, the drive member **861** is pressed to the blade assembly **81** and drives the blade assembly **81** to rotate about the rotation axis **801** by friction.

Example 9

(122) FIG. **27** is a schematic diagram of a lawn mower **100** connected with a grass pressing assembly **20** according to Example 9, wherein the lawn mower **100** according to the present example is the same as the lawn mower of Example 1, except that only the lawn mower **100** in this example is connected with a grass pressing assembly **20**. The lawn mower **100** includes a blade assembly **11** and a deck **12**. The blade assembly **11** is configured to perform the cutting function of the lawn mower **100**; the deck **12** is formed with an accommodation space for accommodating at least part of the blade assembly **11**. In this example, the blade assembly **11** is totally located inside the accommodation space. The lawn mower **100** has a travelling direction **101'** when travelling along a straight line on the ground. In this example, the travelling direction **101'** is parallel to the front-rear direction. All usages of “assembly” in this application refer to a combination including at least one component or part, which realizes a specific function through interaction or coordination. The lawn mower **100** in the present application may be either a hand-push lawn mower or a riding lawn mower. For the convenience of explaining the technical solution of the present application, the up-down direction and the front-rear direction are defined as shown in FIG. **27**.

(123) As shown in FIGS. **27-30**, the grass pressing assembly **20** is connected to the lawn mower **100**. In one example, the grass pressing assembly **20** is detachably connected to the rear end of the lawn mower **100**. The grass pressing assembly **20** is configured to compact the lawn, and the grass pressing assembly **20** serves as an accessory for the user to selectively assemble according to specific needs. The lawn mower **100** includes a mounting shaft **17**; the mounting shaft **17** is perpendicular to the travelling direction **101'**; the grass pressing assembly **20** is rotatably connected to the mounting shaft **17** so that the grass pressing assembly **20** can rotate about the mounting shaft **17**. The mounting shaft **17** here may be a shaft body of the lawn mower **100**, or may be a wheel shaft of the wheels, or may be another shaft body. That is to say, the grass pressing assembly **20** can be detachably connected to the mounting shaft **17**, and there is no need to add another installation structure for mounting the grass pressing assembly **20** to the lawn mower **100**, bringing the

advantage of convenient installation. For any type of lawn mower **100**, as long as it has an existing shaft body, the grass pressing assembly **20** in this example can be installed on the lawn mower **100**, which has the advantage of strong adaptability.

(124) As shown in FIG. **28**, the grass pressing assembly **20** includes a drum **201**, a connecting portion **202**, and a supporting portion **203**. Wherein, the drum **201** has a predetermined weight so that the drum **201** always applies pressure to the ground, and the pressure is large enough to compact the lawn. That is to say, the grass pressing assembly **20** in this example mainly applies pressure to the lawn by the weight of the drum **201**. The connecting portion **202** and the mounting shaft **17** form a rotatable connection, that is, the connecting portion **202** can rotate about the mounting shaft **17**. In this example, the connecting portion **202** is generally hook-shaped with openings in the circumferential direction. After the connecting portion **202** is hooked to the mounting shaft **17**, the connecting portion **202** is sealed in the circumferential direction by fasteners such as screws or bolts so that the mounting shaft **17** cannot be separated from the connecting portion **202** in the radial direction.

(125) As shown in FIG. **29**, the supporting portion **203** connects the drum **201** and the connecting portion **202**. The supporting portion **203** and the connecting portion **201** may be formed integrally or separately. The supporting portion **203** includes a first support arm **2031** and a second support arm **2032**. The drum **201** has a length direction. The first support arm **2031** and the second support arm **2032** extend at least partially along the direction perpendicular to the length direction of the drum **201**. The length direction of the drum **201** is parallel to the axis **171** of the mounting shaft **17**.

(126) In this example, the first support arm **2031** connects the first end of the drum **201** and the connecting portion **202**, and the second support arm **2032** connects the second end of the drum **201** and the connecting portion **202**. The supporting portion **203** further includes a third support arm **2033**, and the third support arm **2033** is fixedly connected to the first support arm **2031** and second support arms **2032** to increase the overall strength and rigidity of the supporting portion **203**. The third support arm **2033** extends in a direction parallel to the mounting shaft **17**, and the two ends of the third support arm **2033** are respectively connected to the first support arm **2031** and the second support arm **2032**.

(127) The drum **201** has a mid-division plane **21'** perpendicular to the length direction, and the drum **201** is symmetrical about the mid-division plane **21'**; the supporting portion **203** has a symmetry plane **22'**. The supporting portion **203** is symmetrical about the symmetry plane **22'**. The symmetry plane **22'** is parallel or coincides with the mid-division plane **21'**. When the connecting portion **202** is mounted to the middle position of the mounting shaft **17**, the symmetry plane **22'** coincides with the mid-division plane **21'**. In other examples, the connecting portion **202** may be installed at any position in the axial direction of the mounting shaft **17**.

(128) As shown in FIG. **30**, the drum **201** includes a central shaft **2011** and a cylindrical portion **2012**. The central shaft **2011** extends along the length direction of the drum **201**; the cylindrical portion **2012** rotates around the central shaft **2011**, and the cylindrical portion **2012** is basically a hollow cylindrical shape; both the central shaft **2011** and the cylindrical portion **2012** are made of metal. The central shaft **2011** and the supporting portion **203** are connected together by screws, and the central shaft **2011** and the screw form a threaded connection, that is, the central shaft **2011** and the supporting portion **203** constitute a fixed connection, and the cylindrical portion **2012** can rotate relative to the central shaft **2011**. In an example, the screw can be replaced with a bolt fixedly connected to the supporting portion **203** so that the central shaft **2011** can rotate about the bolt; in other words, the screw and the central shaft **2011** constitute a rotational connection, and the central shaft **2011** can rotate relative to the screw.

(129) In this example, the lawn mower **100** includes an adjustment assembly for adjusting the height of the deck **12** from the ground, and the grass pressing assembly **20** is connected to a shaft body on the adjustment assembly. The adjustment assembly in this example is mainly composed of a linkage mechanism. When the user adjusts the height of the deck **12** from the ground, the height

of the adjustment assembly from the ground also changes. That is to say, the height of the mounting shaft **17** from the ground is variable. In this example, the mounting shaft **17** is parallel to the ground. The distance d from the axis **171** of the mounting shaft **17** to the axis **2011a** of the central shaft **2011** of the drum **201** is long enough so that regardless of the height of the mounting shaft **17** from the ground, the drum **201** still contacts the ground and is supported by the ground. That is, the distance d between the axis **2011a** of the central shaft **2011** and the axis **171** of the mounting shaft **17** is greater than the maximum distance between the axis **171** of the mounting shaft **17** and the ground.

Example 10

(130) FIG. **31** is a schematic diagram of the grass pressing assembly **20'** provided by Example 10 of the present application. Compared with Example 9, the difference only lies in the structure of the supporting portion **203'**, so only the supporting portion **203'** will be described below. The supporting portion **203'** includes a first support arm **2031'**, a second support arm **2032'**, and a third support arm **2033'**. The two ends of the third support arm **2033'** are respectively connected to the two ends of the drum **201'**; the two ends of the first support arm **2031'** are respectively connected to the third support arm **2033'** and the connecting portion **202'**, and the two ends of the second support arm **2032'** are respectively connected to the third support arm **2033'** and the connecting portion **202'**. Among them, the connection of the first support arm **2031'** and the second support arm **2032'** are fixed connections, including welded connection or threaded connection. The two ends of the third support arm **2033'** extend approximately in a direction perpendicular to the mounting axis **17'**, the middle part of the third support arm **2033'** extends approximately in a direction parallel to the mounting axis **17'**, the first support arm **2031'** and the second support arm **2032'** extend in a direction perpendicular to the mounting axis **17'**.

Example 11

(131) FIG. **32** is a schematic diagram of a lawn mower **50** provided in Example 11 of the present application. Compared with Example 1, the difference mainly lies in the structure and position arrangement of the lighting assembly. The following mainly introduces the lighting assembly **508**. As shown in FIGS. **32-34**, the lawn mower **50** includes a main body **501** and an operating device **502**. The main body **501** includes a main body housing **5011**, a prime mover, and a working assembly **5013**, wherein the working assembly **5013** includes working elements that perform the tool functions of garden tools. For the lawn mower **50**, the working element is a cutting element arranged for mowing, further, is a blade assembly **5013a**. The main body housing **5011** is configured to install a prime mover and a working element that outputs power. For the lawn mower **50**, the main body housing **5011** may include a deck **60**. The prime mover is configured to output power to the working element to drive the movement of the working element. In this example, the prime mover is a motor **5012** capable of driving the blade assembly **5013a** to rotate. The operating device **502** is configured for user operation to control the main body **501**, and the operating device **502** includes an operating element for user operation, the operating element being a trigger **5021**. As a hand-push power tool, the lawn mower **50** also includes a connecting rod assembly, which is connected to the main body **501** and the operating device **502**. The lawn mower **50** further includes a pair of walking wheels **5014**. The walking wheels **5014** drive the lawn mower **50** to walk on the ground. The two walking wheels **5014** are symmetrically disposed on both sides of the first plane **501'**.

(132) The connecting rod assembly includes a pair of connecting rods **5031**, and the connecting rod **5031** connects the main body **501** and the operating device **502**. The two connecting rods **5031** are arranged symmetrically on both sides of the first plane **501'**. In the present example, the area at the end of the connecting rod assembly **503** where the operating device **502** is provided is defined as the operating area **505**, the area at the end of the connecting rod assembly **503** where the main body **501** is provided is defined as the work area **503**, the operating device **502** is located in the operating area **505**, the main body **501** is located in the work area **503**. The connecting rod assembly further

includes an armrest **5032**; the armrest **5032** is configured for a user standing in an operation position to hold and push the lawn mower **50**. The armrest **5032** connects the two connecting rods **5031** and is located at the end of the connecting rods **5031** away from the main body **501**.

(133) As shown in FIGS. **32-35**, a signal acquisition system **5023** is also provided in the operating area **505**. The signal acquisition system **5023** is connected to the operating device **502** to receive input information of the operating device **502**. A signal output system **5015** is also provided in the working area **503**, and the signal output system **5015** is configured to control the output of the working assembly **5013**. The operating device **502** further includes a console **5022**; the console **5022** connects the two connecting rods **5031**; the console **5022** is located between the armrest **5032** and the main body **501**. The trigger **5021** and the console **5022** constitute a rotational connection. The user can rotate the trigger **5021** so that the trigger **5021** fits to the armrest **5032**. The user's hand simultaneously holds the trigger **5021** and the armrest **5032**. The signal acquisition system **5023** is arranged in a space surrounded by the console **5022**. The signal output system **5015** is arranged in a space surrounded by the main body housing **5011**.

(134) The lawn mower **50** further includes a signal line assembly **504**; the signal line assembly **504** is connected to the signal output system **5015** and the signal acquisition system **5023** so that the signal output system **5015** and the signal acquisition system **5023** constitute a communication connection. In this way, after the signal acquisition system **5023** collects the signals output by the operating device **502**, the signal line assembly **504** transmits the information to the signal output system **5015**. The signal output system **5015** controls the working assembly **5013** to perform the corresponding function in a corresponding state.

(135) The signal acquisition system **5023** includes a signal circuit board **5023a**, and the signal output system **5015** includes a first output circuit board **5015a**. The first output circuit board **5015a** is connected to the motor **5012**. The signal circuit board **5023a** is configured to install or connect a signal switch, which is controlled by the operating element. The first output circuit board **5015a** sends signals to the working elements, electronic switches, circuit boards, etc. in the working area **503**. The signal line assembly **504** comprises a first signal line **5041**; the first signal line **5041** is connected to the first output circuit board **5015a** and the signal circuit board **5023a** in order to achieve the communication between the first output circuit board **5015a** and the signal circuit board **5023a**.

(136) Garden tools in related technologies connect multiple electronic components through power lines and electronic switches. The power loss is large, the cost of cables is high, and the wiring is complicated, resulting in chaos in the internal structure of the machine. In this example, the first signal line **5041** is used to connect the signal circuit board **5023a** and the first output circuit board **5015a**, and a bus signal line can realize the connection between multiple electronic components. Therefore, regarding the lawn mower **50** of this example, the power loss is low, the cost of the cable is low, and the wiring is simple, so that the internal structure of the machine is simple. Moreover, because there are few cables inside the lawn mower **50**, the cable arrangement is simple, the stability of the lawnmower **50** is good, it is not easy to be damaged, and maintenance is relatively convenient.

(137) In this example, the signal acquisition system **5023** is only provided with one signal circuit board **5023a**. In other examples, the signal acquisition system **5023** also includes multiple signal circuit boards **5023a**, and the multiple signal circuit boards **5023a** are communicatively connected through signal lines.

(138) The lawn mower **50** further comprises a power supply; the power supply is a battery pack **5016**; the battery pack **5016** is configured to power the motor **5012**; the battery pack **5016** and the motor **5012** are both mounted on the main body **501**. The signal output system **5015** further includes a second output circuit board **5015b**, and the second output circuit board **5015b** is disposed in the main body housing **5011**. The second output circuit board **5015b** and the battery pack **5016** constitute a communication connection. The first signal line **5041** is also connected to a

splitter **5042**, which is connected to two output terminals **5042a**, which are respectively connected to the first output circuit board **5015a** and the second output circuit board **5015b** (referring to FIG. **34** and FIG. **35**). Thus, the first output circuit board **5015a** is communicatively connected to the first signal circuit board **5023a** through the first signal line **5041**, and the second output circuit board **5015b** is communicatively connected to the first signal circuit board **5023a** through the first signal line **5041**.

(139) In this example, the working assembly **5013** further includes other functional elements that implement additional functions of the lawn mower **50**, and the functional elements may be, for example, a lighting element **5081** or a self-propelled motor. In this example, the lighting element **5081** is an example of the functional elements. The lawn mower **50** also includes a third output circuit board **5015c** that controls the lighting element **5081**, and the third output circuit board **5015c** is connected to the first output circuit board **5015a**.

(140) The first output circuit board **5015a** is also installed or connected with a first access terminal **5015d**, and the first access terminal **5015d** is configured to receive a signal output by the first signal line **5041**. The second output circuit board **5015b** is also installed or connected with a second access terminal **5015e**, which is configured to receive the signal output by the first signal line **5041**. The first access terminal **5015d** is connected to one of the two output terminals **5042a** connected to the splitter **5042**, and the second access terminal **5015e** is connected to the other one of the two output terminals **5042a** connected to the splitter **5042**. The two output terminals **5042a** are provided with USB female sockets, and the first access terminal **5015d** and the second access terminal **5015e** are provided with USB male sockets. In one example, the USB female socket is a TYPE-C female socket, and the USB male socket is a TYPE-C male socket. In this way, the signal line assembly **504** has good versatility, is convenient for maintenance, and can improve the stability of the lawn mower **50**. In other examples, the output terminal **5042a** may be provided with a USB male socket, and the first access terminal **5015d** and the second access terminal **5015e** may be provided with a USB female socket.

Example 12

(141) FIG. **36** is a schematic diagram of a lawn mower **50** provided in Example 12. The signal output system **5051** of the lawn mower **505** includes a first output circuit board **5052** and a second output circuit board **5053**. The motor **5054** and the battery pack **5055** are both connected to the first output circuit board **5052**, and the signal circuit board **5056** and the first output circuit board **5052** are connected by a signal line. The second output circuit board **5053** is connected to the functional element **5057** which is configured to realize other functions of the lawn mower **505**.

(142) As shown in FIG. **32** and FIG. **37**, the lawn mower **50** further includes a lighting assembly **508** and a status display assembly **509**. Lighting assembly **508** includes a lighting switch **5082** and a lighting element **5081** as shown in FIG. **32**. The lighting element **5081** is disposed in the working area **503** to illuminate the region on the front side of the lawn mower **50** so as to facilitate the user working in poor lighting conditions. The lighting element **5081** is provided on the main body **501**, further, the lighting element **5081** is provided on the main body housing **5011**. The lighting switch **5082** is provided for user operation to control whether the lighting element **5081** is turned on. The status display assembly **509** includes a status indicator light **5091**. The status indicator light **5091** can display the working status of the lawn mower **50**. The status indicator light **5091** can also display whether the lawn mower **50** is activated. Among them, the lighting switch **5082** and the status indicator light **5091** are both located in the operating area **505**. In this way, when the user stands on the rear side of the operating device **502**, the user can conveniently operate the lighting switch **5082** to light up the lighting element **5081**. Especially during the operation of the lawn mower **50**, the user does not need to release the trigger **5021** and come to the side or the front of the lawn mower **50** to activate the lighting element **5081**. Therefore, the user can conveniently operate the lighting switch **5082** at any time during the operation of the lawn mower **50**, which improves the operational convenience. Moreover, the user can easily observe the display state of the status

display assembly **509**, without leaving the operating area.

(143) The lighting switch **5082** and the status indicator light **5091** are both provided on the console **5022**; also, the lighting switch **5082** and the status indicator light **5091** are located between the trigger **5021** and the main body **501**, thereby facilitating user operations.

(144) As shown in FIGS. **33**, **36**, and **37**, a safety switch **5024** is also provided in the middle of the console **5022**. The safety switch **5024** and the trigger **5021** constitute a switch group for starting the motor **5054**. When one of the safety switch **5024** and the trigger **5021** is not activated, the lawn mower **50** is not started. After the safety switch **5024** is activated, the user activates the trigger **5021**. If the safety switch **5024** is not activated, the motor **5054** does not start when the user activates the trigger **5021**. Among them, the lighting switch **5082** and the status indicator light **5091** are respectively located on both sides of the safety switch **5024**, therefore, the structure layout on the console **5022** is more reasonable, and it is more convenient for the user to operate the lawn mower **50**.

(145) In this example, the lighting switch **5082** and the status indicator light **5091** are also disposed on both sides of the first plane **501'**, which facilitates the user to operate the lighting switch **5082** and to observe the display status of the status indicator light **5091**. In other examples, the lighting switch **5082** may also be provided on the armrest **5032** or near the armrest **5032**, so long as the user can operate the lighting switch **5082** when standing on the rear side of the lawn mower **50** without leaving the operating area **505**.

(146) The armrest **5032** includes a cross bar **5032a**; the cross bar **5032a** is for the user to grip and the cross bar **5032a** extends in a direction perpendicular to the connecting rod **5031**. The minimum distance between the lighting switch **5082** and the cross bar **5032a** is greater than or equal to 0 cm and less than or equal to 30 cm. In this way, the user can extend the arm to operate the light switch **5082** when holding the cross bar **5032a**.

(147) In one example, the lighting switch **5082** is a membrane switch, which takes up little space and has a low manufacturing cost. The lighting switch **5082** is also provided with an LED lamp for the user to easily observe whether the lighting switch **5082** is triggered in a relatively bright environment.

(148) In this example, the number of status indicator lights **5091** is five, and the five status indicator lights **5091** are respectively: working status indicator light, working shape indicator light, temperature status indicator light, load status indicator light and power status indicator light. The working status indicator light indicates whether the lawn mower **50** is started, so whether the lawn mower **50** has been damaged is determined by the display status of the working status display light. The working shape indicator light shows the folding state of the lawn mower **50** or the telescopic state of the connecting rod assembly **503** of the lawn mower **50**. The temperature status display light indicates whether the temperature of the battery pack **5055** or the motor **5054** exceeds a predetermined threshold. The load status indicator light indicates whether the lawn mower **50** is in an overload state. The power status indicator light displays the remaining power of the battery pack **5055**, or whether the remaining power of the battery pack **5055** is lower than a predetermined threshold.

(149) As shown in FIGS. **32**, **33**, and **38**, the deck **60** is formed with an accommodation space **60a** covering the blade assembly **5013a**. In the accommodation space **60a**, the blade assembly **5013a** rotates about the rotation axis **504'** to perform the cutting function.

(150) As shown in FIG. **38** and FIG. **41**, the lawn mower **50** has a discharge mode and a mulch mode. When the lawn mower **50** is in the discharge mode, the grass clippings can be discharged out of the deck **60**. When the lawn mower is in the mulch mode, the grass clippings will fall under the deck **60**.

(151) As shown in FIGS. **38-40**, the deck **60** includes a vortex portion **601** and a discharge portion **602**. The vortex portion **601** extends around the circumferential direction of the rotation axis **504'** to form a vortex in the accommodation space **60a**. The vortex portion **601** forms a vortex channel

6011, and the vortex flows along a flow path **60b** in the vortex channel **6011**. The flow path **60b** also basically extends in the circumferential direction around the rotation axis **504'**. The discharge portion **602** is provided on the flow path **60b** of the vortex. The discharge portion **602** extends from the vortex portion **601** in the tangential direction of the vortex, and the discharge portion **602** guides the vortex flow out in the tangential direction of the flow path **60b**. Therefore, when the lawn mower **50** is in the discharge mode, the discharge portion **602** can guide the grass clippings to move along the flow path **60b** of the vortex channel **6011** first, and then when the grass clippings move to the discharge portion **602**, the discharge portion **602** will guide a portion of grass clippings away from the deck **60** along the tangential direction of the flow path **60b** to discharge this portion of grass clippings to the outside of the lawn mower **50**, or collect this portion of grass clippings into a grass basket.

(152) As shown in FIG. **41**, the lawn mower **50** further includes a plug **6017**. When the plug **6017** is installed in the discharge portion **602**, the discharge portion **602** is sealed, so that the lawn mower **50** is in the mulch mode. When the plug **6017** is not attached to the discharge portion **602**, the discharge portion **602** is opened, and the airflow can flow out from the discharge portion **602**, therefore the lawn mower **50** is in the discharge mode.

(153) In the present example, as shown in FIG. **38** and FIG. **40**, the deck **60** further comprises a stop portion **603**; the stop portion **603** is configured to prevent the vortex from keeping circulating in the vortex portion **601** while flowing through the discharge portion **602**, thereby increasing the flow rate of the vortex from the discharge portion **602**. At least a portion of the discharge portion **602** and at least a portion of the stop portion **603** is on the same side of the first plane **501'**, and the first plane **501'** passes through the rotation axis **504'**. The stop of the vortex by the stop portion **603** can increase the flow rate of the vortex from the discharge portion **602** when the lawn mower **500** is in the discharge mode, thereby improving the grass collection efficiency of the grass clippings, and on the other hand, when the lawn mower **500** is in the mulch mode, the grass clippings can be stopped so that some of the grass clippings fall into the cutting area of the blade assembly **5013a** again to be cut by the blade assembly **5013a** again, thereby improving the grass chopping ability.

(154) In one example, the deck **60** further includes a mounting portion **604**; the mounting portion **604** is configured to mount the motor **5054**. The mounting portion **604** is formed with a hole **6041** around the rotation axis **504'** that allows the motor shaft to pass.

(155) As shown in FIG. **39**, the vortex portion **601** includes an inner ring **6012**, an outer ring **6013**, and a bottom surface **6014**. The inner ring **6012** is formed around the rotation axis **504'**, and the inner ring **6012** is connected to the mounting portion **604**. The outer ring **6013** is disposed around the inner ring **6012**. The bottom surface **6014** connects the inner ring **6012** and the outer ring **6013**. The vortex channel **6011** of the vortex portion **601** is formed between the inner ring **6012** and the outer ring **6013**.

(156) The discharge portion **602** includes a first discharge surface **6021**, a second discharge surface **6022**, and a discharge bottom surface **6023**. The first discharge surface **6021** is connected to the inner ring **6012**, and the second discharge surface **6022** is connected to the outer ring **6013**. The first discharge surface **6021** extends from the inner ring **6012** substantially along a tangential direction of the inner ring **6012**, and the second discharge surface **6022** extends from the outer ring **6013** substantially along a tangential direction of the outer ring **6013**. The discharge bottom surface **6023** connects the first discharge surface **6021** and the second discharge surface **6022**. The discharge bottom surface **6023** is also connected to the bottom surface **6014** of the vortex section **601**.

(157) The stop portion **603** includes a stop surface **6031** and a connecting surface **6032**. The stop surface **6031** is configured to stop the airflow flowing in the vortex portion **601** so that the airflow flows out of the discharge portion **602**. The discharge portion **602** is substantially located on the first side of the first plane **501'**. In this example, if more than 90% of the discharge portion **602** is located on the first side of the first plane **501'**, it is considered that the discharge part **602** is

substantially located on the first side of the first plane **501'**. The stop surface **6031** is also located on the first side of the first plane **501'**, that is, the stop surface **6031** and the discharge portion **602** are located on the same side of the first plane **501'**. Or, in other examples, the stop surface **6031** and a portion of the discharge portion **602** are located on the same side of the first plane **501'**. Alternatively, in other examples, at least a portion of the stop surface **6031** and at least a portion of the discharge portion **602** are located on the same side of the first plane **501'**.

(158) The stop portion **603** is provided at the edge of the discharge portion **602**. In an example, the stop surface **6031** is disposed at the first discharge surface **6021**, and the stop surface **6031** extends from the inner ring **6012** to the outer ring **6013**. The stop surface **6031** also extends from the bottom surface **6014** to the direction away from the bottom surface **6014**, that is, one side of the stop surface **6031** is connected to the junction of the bottom surface **6014** and the first discharge surface **6021**. The connecting surface **6032** extends from a side of the stop surface **6031** away from the bottom surface **6014** along a plane obliquely intersecting the stop surface **6031**, and the connecting surface **6032** connects the stop surface **6031** and the bottom surface **6014**.

(159) In this example, the stop portion **603** is integrally formed with the vortex portion **601**, and the recess of the vortex portion **601** towards the ground forms the stop portion **603**. The stop portion **603** is located inside the vortex portion **601**, the stop portion **603** is also located in the vortex channel **6011** formed by the vortex portion **601**, and the stop portion **603** is also located on the flow path **60b** of the vortex.

(160) The stop portion **603** and the discharge portion **602** are also disposed on the same side of a second plane **502'** that passes through the rotation axis **504'** and is perpendicular to the first plane **501'**. That is to say, the stop portion **603** and the discharge portion **602** are provided at the rear of the deck **60**.

(161) In a direction perpendicular to the first plane **501'**, at least a portion of the stop portion **603** is also located between the discharge portion **602** and the hole **6041**.

(162) The ratio of the length **L1** of the stop portion **603** in the direction of the rotation axis **504'** to the depth **L2** of the vortex portion **601** in the direction of the rotation axis **504'** is greater than or equal to 0.1 and less than or equal to 0.5. Therefore, on the one hand, the size of the stop portion **603** is not too large, which hinders effective vortex to be generated in the vortex portion **601**; on the other hand, the size of the stop portion **603** is not too small, which affects the discharge efficiency of the discharge portion **602** and the grass chopping ability of the lawn mower **50**.

Example 13

(163) FIG. **42** is a lawn mower **10** provided in Example 13 of the present application. Compared with Example 1, the structure of the blade assembly **101** is the main difference. As shown in FIGS. **42-46**, the lawn mower **10** includes a blade assembly **101** for cutting vegetation and a deck **102** that houses the blade assembly **101**, and the blade assembly **101** is located inside the deck **102**. The lawn mower **10** further includes a motor **103** that drives the blade assembly **101** to rotate. The motor **103** is located above the deck **102**. The motor **103** and the blade assembly **101** form a coaxial rotation about the rotation axis **10'**. The motor **103** includes a motor shaft, and the blade assembly **101** includes a drive shaft **1011** (referring to FIG. **44**) that drives the blade assembly **101** to rotate. The drive shaft **1011** may be a motor shaft. In an example, a transmission mechanism for transmission may also be provided between the motor **103** and the blade assembly **101**, so that the shaft of the motor **103** and the drive shaft **1011** form a non-coaxial rotation.

(164) As shown in FIGS. **44-46**, the blade assembly **101** includes a first blade **1012** and a second blade **1013**. The first blade **1012** is located above the second blade **1013** relative to the ground, and the first blade **1012** and the second blade **1013** both rotate about a rotation axis **10'**. The first blade **1012** and the second blade **1013** constitute a synchronous rotation. As shown in the direction of the arrow in FIG. **44**, the first blade **1012** and the second blade **1013** rotate synchronously in the rotation direction **10a'** about the drive shaft **1011**. The blade assembly **101** further includes a connecting assembly **1014**. The first blade **1012** and the second blade **1013** form a fixed connection

through the connecting assembly **1014**. In this example, the first blade **1012** and the second blade **1013** form a detachable connection through the connecting assembly **1014**. It is convenient to repair or replace the blade assembly **101** later. The connecting assembly **1014** includes a connecting piece, a nut, and the like. The connecting assembly **1014** may also connect the first blade **1012** and the second blade **1013** with other connection structures. The specific connection form between the first blade **1012** and the second blade **1013** is not limited herein. The blade assembly **101** may also include other accessories such as bearings and bearing covers.

(165) Along the rotation direction **10a'**, the first blade **1012** is located in front of the second blade **1013**, that is to say, although the first blade **1012** and the second blade **1013** rotate synchronously when the motor **103** is started, the first blade **1012** cuts the vegetation earlier than the second blade **1013**. In this example, the rotation direction **10a'** is a clockwise direction with the drive shaft **1011** as the axis. The first blade **1012** includes a first mounting portion **1012a** and a first cutting portion **1012b**. The first mounting portion **1012a** is located in the middle of the first blade **1012**. The first mounting portion **1012a** is configured to connect the first blade **1012** and the second blade **1013** and the drive shaft **1011**. The first cutting portion **1012b** is symmetrically disposed at both ends of the first blade **1012** about the drive shaft **1011**, and the first cutting portion **1012b** is configured to cut vegetation. Similarly, the second blade **1013** includes a second mounting portion **1013a** located in the middle and second cutting portions **1013b** symmetrically disposed at both ends. The difference is that the middle part and the two ends of the first blade **1012** are substantially on the same plane, that is to say, the first mounting part **1012a** and the first cutting portion **1012b** are on the same plane, and the entire first blade **1012** substantially expands along a plane surface; whereas the middle part and the two ends of the second blade **1013** are located on different planes. The two ends of the second blade **1013** are located below the middle part of the second blade **1013** with respect to the ground, that is, the second cutting portion **1013b** is located below the second mounting portion **1013a** with respect to the ground, and the entire second blade **1013** expands along a curved surface. In this example, the first mounting portion **1012a** and the second mounting portion **1013a** vertically overlap and intersect obliquely, the first mounting portion **1012a** and the second mounting portion **1013a** constitute a fixed connection (referring to FIGS. 45 and 46) through the connecting member **1014a**. The connecting member **1014a** is provided with pins of different shapes, and the first mounting portion **1012a** and the second mounting portion **1013a** are respectively provided with holes for engaging with the pins, so as to form fixed connections with the connecting member **1014a**. In this example, the first mounting portion **1012a** and the second mounting portion **1013a** are provided with round holes and irregular-shaped limit holes.

(166) The first cutting portion **1012b** of the first blade **1012** is provided with a first cutting edge **1012c** for cutting vegetation. The first cutting edge **1012c** is disposed at the leading edge of the first cutting portion **1012b**. The leading edge refers to the edge of the first cutting portion **1012b** that cut vegetation earliest when the first blade **1012** rotates along the rotation direction **10a'**. The leading edges of the first cutting portions **1012b** at both ends of the first blade **1012** are symmetrically provided with the first cutting edge **1012c** about the drive shaft **1011**. Similarly, the leading edges of the second cutting portions **1013b** at both ends of the second blade **1013** are also symmetrically provided with a second cutting edge **1013c**.

(167) The first cutting edge **1012c** and the second cutting edge **1013c** respectively include a hardened portion for cutting vegetation. The hardened portion has a higher hardness than other parts due to a hardening process. In an example, the entire first cutting edge **1012c** and second cutting edge **1013c** are hardened, and the hardness is higher than other parts of the first blade **1012** and the second blade **1013**.

(168) The first blade **1012** further includes a weight reduction portion **1012d**; the weight reduction portion **1012d** is disposed at the end of the first blade **1012**, and behind the first cutting edge **1012c** and in front of the second cutting edge **1013c** in the rotation direction **10a'**, that is, the weight reduction portion **1012d** is the portion of the end of the first blade **1012** opposite the first cutting

edge **1012c**. The weight reduction portion **1012d** is disposed symmetrically on both ends of the first blade **1012**, and the weight reduction portion **1012d** has a recess relative to the first blade **1012**. The weight reduction portion **1012d** reduces the weight of the first blade **1012** and expands the space between the first blade **1012** and the second cutting edge **1013c** to facilitate secondary cutting of the vegetation cut by the first cutting edge **1012c**. The first blade **1012** further includes a shrinking edge **1012e** inclined or curved with respect to the trailing edge of the first blade **1012**, and the shrinking edge **1012e** is disposed at the trailing edge of the end of the first blade **102**. In this example, the shrinking edge **1012e** is part of the edge of the weight reduction portion **1012d**, and the shrinking edge **1012e** is inclined towards the inside of the first blade **1012** with respect to the trailing edge of the first blade **1012**. Along the rotation direction **10a'**, the shrinking edge **1012e** is located in front of the second cutting edge **1013c**; the projection of the shrinking edge **1012e** on the ground and the projection of the second cutting edge **1013c** on the ground do not intersect. That is to say, since the shrinking edge **1012e** is inclined or curved forward with respect to the trailing edge of the first blade **1012**, the projection of the shrinking edge **1012e** and the second cutting edge **1013c** has no overlapping portion in a plane parallel to the ground.

(169) As shown in FIG. 46, the shrinking edge **1012e** and the trailing edge of the first blade **1012** form a continuous curve with at least one bending point B. The projection of the bending point B on the ground is located in front of the projection of the second cutting edge **1013c** on the ground in the rotation direction **10a'**. That is to say, the bending point B formed by the shrinking edge **1012e** and the trailing edge of the first blade **1012** is located outside the second cutting edge **1013c** in a plane parallel to the second blade **1013**, while the lateral distance of the projection of the bending point B in the plane of the second blade **1013** to the second cutting edge **1013c** is greater than 0. In an example, the shrinking edge **1012e** and the trailing edge of the first blade **1012** may form multiple bending points. In this case, the multiple bending points should also meet the above conditions, that is, the projection of the bending point on the ground is located in front of the projection of the second cutting edge **1013c** on the ground along the rotation direction **10a'**, and the lateral distance from the bending point to the second cutting edge **1013c** is greater than 0.

(170) On the other hand, the length L3 of the shrinking edge **1012e** is greater than or equal to 40 mm and less than or equal to 150 mm. In one example, the length L3 of the shrinking edge **1012e** is greater than or equal to 70 mm and less than or equal to 100 mm. In this example, the length L3 of the shrinking edge **1012e** is about 95 mm.

(171) The projection of the shrinking edge **1012e** on the ground and the projection of the second cutting edge **1013c** on the ground do not intersect, which makes full use of the length of the second cutting edge **1013c** for secondary cutting, while enlarging the space formed by the shrinking edge **1012e** and the second cutting edge **1013c**. Therefore, the vegetation cut by the first cutting edge **1012c** rebounds and falls into the space to be cut by the second cutting edge **1013c**, thereby improving the cutting efficiency of the lawn mower **10**.

(172) As the first blade **1012** and the second blade **1013** are arranged to overlap each other, the extension line of the shrinking edge **1012e** and the extension line of the second cutting edge **1013c** form an angle within a predetermined angle range. In an example, the angle between the extension line of the shrinking edge **1012e** and the extension line of the second cutting edge **1013c** is greater than or equal to 15 degrees and less than or equal to 45 degrees. In one example, the angle between the extension line of the shrinking edge **1012e** and the extension line of the second cutting edge **1013c** is greater than or equal to 25 degrees and less than or equal to 35 degrees. In this example, the angle is approximately 30 degrees.

(173) The second blade **1013** further includes a tilted portion **1013d** provided at both ends of the second blade **1013**, and the tilted portion **1013d** lifts upward and distributes symmetrically on both ends of the second blade **1013** with respect to the drive shaft **1011**. After the air flow generated during the rotation of the second blade **1013** is lifted by the tilted portion **1013d**, the grass clippings cut by the second blade **1013** can be brought up and thrown up, therefore, the second blade **1013**

has good performance in throwing the grass clippings.

(174) A noise reduction portion capable of reducing noise is also provided near the tilted portion **1013d**, and the noise reduction portion is a noise reduction groove recessed inward.

Example 14

(175) FIG. **47** and FIG. **48** are schematic diagrams of the lawn mower **30** provided in Example 14 of the present application. In this example, the lawn mower **30** may be a hand-push lawn mower or a riding lawn mower. The lawn mower **30** includes a blade assembly **301**, a transmission mechanism, a motor, a housing **302**, a handle **303**, and wheels **304**.

(176) The motor drives the blade assembly **301** to rotate about the rotation axis **301'** in the cutting direction **30a'**, wherein the cutting direction **30a'** is the clockwise or counter clockwise direction around the rotation axis **301'**. The transmission mechanism connects the blade assembly **301** and the motor, and transmits the power of the motor to the blade assembly **301**. The housing **302** immobilizes or accommodates the motor. As the main frame structure of the lawn mower, the housing **302** assembles multiple parts into a whole. The lawn mower **30** also includes a battery pack that supplies power to the motor. The housing **302** includes a motor housing and a main body housing. The motor housing is configured to immobilize or accommodate the motor. The motor housing is connected to the main body housing. A circuit board to control the motor is provided in the housing **302**.

(177) The handle **303** is formed with a grip portion for the user to grip. The handle **303** may be formed by the housing **302** or may be attached to the housing **302** as a separate part. The lawn mower **30** further includes a connecting rod connecting the handle **303** and the housing **302**, and the connecting rod is telescopic and rotatable relative to the housing **302**. The lawn mower **30** further includes a self-propelled motor that drives the wheels **304** to rotate. The self-propelled motor and the wheels **304** transfer motion with a transmission structure. In an example, the self-propelled motor and the wheels **304** transfer motion with a transmission gear.

(178) As shown in FIGS. **48-50**, the blade assembly **301** includes a blade **3011** and a rotating shaft **3012**. The rotating shaft **3012** has a rotation axis **301'** as a central axis, and the blade **3011** is symmetrical about the rotation axis **301'**; the blade **3011** extends substantially along a straight line perpendicular to the rotation axis **301'**; the blade **3011** extends substantially along a plane perpendicular to the rotation axis **301'**. The blade **3011** includes a bottom surface **3011a** and a top surface **3011b**. The top surface **3011b** is further away from the ground relative to the bottom surface **3011a**. In this example, the bottom surface **3011a** and the top surface **3011b** are parallel to each other and are both perpendicular to the rotation axis **301'**. In one example, the bottom surface **3011a** is a curved surface, and at least a portion of the bottom surface **3011a** is inclined with respect to the top surface **3011b**; in one example, the top surface **3011b** is a curved surface, and at least a portion of the top surface **3011b** is inclined with respect to the bottom surface **3011a**.

(179) The blade **3011** further includes a cutting surface **3011c**. The cutting surface **3011c** is a plane between the bottom surface **3011a** and the top surface **3011b**. The plane on which the cutting surface **3011c** is located intersects the plane on which the bottom surface **3011a** is located and the plane on which the top surface **3011b** is located obliquely. That is to say, the cutting surface **3011c** connects the bottom surface **3011a** and the top surface **3011b** and forms a continuous curved surface. The inclination angle between the cutting surface **3011c** and the bottom surface **3011a** is greater than or equal to 20 degrees and less than or equal to 35 degrees. In this example, the inclination angle between the cutting surface **3011c** and the bottom surface **3011a** is about 28 degrees, and the inclination angle between the cutting surface **3011c** and the top surface **3011b** is about between 30 degrees to 52 degrees. The blade **3011** also includes a cutting portion **3011d**; the cutting portion **3011d** is located at one end of the blade **3011** and at the leading edge of the blade **3011** along the cutting direction **30a'**. The leading edge refers to the edge that contacts the vegetation first when the blade **3011** rotates along the cutting direction **30a'**, and the edge that contacts the vegetation after the leading edge is the trailing edge, as shown in FIG. **49**. In one

example, the blade **3011** includes two cutting portions **3011d**, and the two cutting portions **3011d** are respectively located at both ends of the blade **3011** and at the leading edge of the blade **3011** along the cutting direction **30a'**.

(180) The cutting portion **3011d** is defined by the bottom surface **3011a** and the cutting surface **3011c**; in this example, since the bottom surface **3011a** and the cutting surface **3011c** intersect obliquely, the cutting portion **3011d** is formed by the bottom surface **3011a** and the cutting surface **3011c**, and the bottom surface **3011a** and the cutting surface **3011c** intersect to form the cutting edge; in one example, the plane where the cutting surface **3011c** is located obliquely intersects with the bottom surface **3011a**, but the cutting surface **3011c** does not directly intersect with the bottom surface **3011a**; in comparison, the cutting portion **3011d** with the cutting edge is sharper and the cutting efficiency is also higher.

(181) The cutting portion **3011d** is composed of a body portion **3011e** and a hardened portion **3011f**, wherein the hardened portion **3011f** extends inward along the end of the blade **3011** and extends from the bottom surface **3011a** to the top surface **3011b** of the blade **3011**. The hardened portion **3011f** is a hardened layer from laser quenching a part of the cutting portion **3011d**, whereas the body portion **3011e** is not laser quenched, therefore, the surface hardness of the hardened portion **3011f** is greater than the surface hardness of the body portion **3011e**. In one example, the ratio of the surface hardness of the hardened portion **3011f** of the blade **3011** to the surface hardness of the body portion **3011e** is greater than 1.1 and less than or equal to 2.4. In one example, the ratio of the surface hardness of the hardened portion **3011f** to the surface hardness of the body portion **3011e** is greater than 1.2 and less than or equal to 2. The surface hardness distribution of the hardened portion **3011f** and the body portion **3011e** makes the structure of the blade **3011** more reasonable. The hardened portion **3011f** is a cutting portion **3011d** near the bottom and end of the blade **3011**, which is a high-frequency region for cutting vegetation. Accordingly, the hardened portion **3011f** with a higher surface hardness can improve the wear resistance and cutting efficiency of the blade **3011**, and also improve the reliability and service life of the blade **3011** of the lawn mower **30**.

(182) The method of manufacturing the blade **3011** includes: laser cutting and forming, laser cutting the metal sheet to obtain the blade **3011** in an unsharpened state; laser quenching, laser hardening the area where the hardened portion **3011f** is located to improve the surface hardness of the area; processing the cutting portion **3011d**, processing the blade **3011** in the unsharpened state to create the cutting portion **3011d**; and polishing the blade **3011**, polishing the blade **3011** to remove burrs generated during the processing of the blade **3011**.

(183) The area where the hardened portion **3011f** is located is shown in FIGS. **49** and **50**. In an example, the hardened portion **3011f** has a trapezoidal cross section and a rectangular vertical section. The length **L** of the hardened portion **3011f** is greater than or equal to 50 mm and less than or equal to 120 mm; the lateral width **W** of the hardened portion **3011f** is greater than or equal to 2 mm and less than or equal to 8 mm; the depth **H** of the hardened portion **3011f** is greater than 0.2 mm and less than or equal to 1 mm. In an example, the depth **H** of the hardened portion **3011f** is greater than 0.3 mm and less than or equal to 0.6 mm. In this example, the length **L** of the hardened portion **3011f** is approximately 100 mm; the lateral width **W** of the hardened portion **3011f** is approximately 5 mm, which is approximately equal to the lateral width of the cutting portion **3011d**; the depth **H** of the hardened portion **3011f** is approximately 0.5 mm. The depth **H** of the hardened portion **3011f** refers to the depth of the hardened layer obtained by laser quenching the blade **3011**. The above-mentioned size setting of the hardened portion **3011f** of the blade **3011** can save the manufacturing cost while ensuring the cutting strength. In addition, considering the different degrees of wear of the hardened portion **3011f** and the body portion **3011e**, the above size design makes the cutting portion **3011d** maintain a sharp state for a long time after wear.

(184) Further, the ratio of the surface hardness of the hardened portion **3011f** to the depth of the hardened portion **3011f** is greater than or equal to 1000 HV1/mm and less than or equal to 2000

HV1/mm. In one example, the ratio of the surface hardness of the hardened portion **3011f** to the depth of the hardened portion **3011f** is greater than or equal to 1100 HV1/mm and less than or equal to 1500 HV1/mm. In an example, the surface hardness of the body portion **3011e** is greater than or equal to 350 HV1 and less than or equal to 500 HV1, and the surface hardness of the hardened portion **3011f** is greater than or equal to 550 HV1 and less than or equal to 750 HV1; in one example, the surface hardness of the body portion **3011e** is greater than or equal to 380 HV1 and less than or equal to 440 HV1, and the surface hardness of the hardened portion **3011f** is greater than or equal to 600 HV1 and less than or equal to 700 HV.

(185) The blade assembly **301** further includes a bearing, and a connector or a fastener, etc. configured to fix and connect the blade **3011**.

Example 15

(186) FIG. **51** and FIG. **52** respectively show a schematic diagram of a blade assembly **401** and a blade of a lawn mower provided in Example 15 of the present application. The present example differs from Example 14 in that: the blade assembly **401** comprises a shaft **4011**, a first blade **4012** and a second blade **4013**; the first blade **4012** and the second blade **4013** are stacked up and down together to synchronously rotate about the rotation axis **401'**; in an example, the first blade **4012** and the second blade **4013** are stacked up and down together to asynchronously rotate about the rotation axis **401'**; in one example, the first blade **4012** and the second blade **4013** rotate about the first axis and the second axis respectively, and the first axis and the second axis are in parallel but do not coincide.

(187) The first blade **4012** includes a first cutting portion **4012d**, and the second blade **4013** includes a second cutting portion **4013d**. Structural features such as the hardened portion and the body portion in Example 14 are applicable to the first blade **4012** and the second blade **4013** in this example.

Claims

1. A lawn mower, comprising: a blade assembly comprising a first blade and a second blade, wherein the blade assembly is configured to be rotatable about a rotation axis, the first blade comprises a first mounting portion provided with a first mounting hole and a first cutting portion for cutting grass, and the second blade comprises a second mounting portion provided with a second mounting hole and a second cutting portion for cutting grass; a deck formed with an accommodation space for accommodating at least a portion of the blade assembly; a motor comprising a drive shaft for driving the blade assembly to rotate about the rotation axis, wherein the drive shaft passes through the first mounting hole and the second mounting hole; a battery pack configured to provide power source for the motor; and a mounting assembly configured to mount the blade assembly to the drive shaft, wherein the mounting assembly comprises a drive member coupled to the drive shaft, the drive member is a fan, the drive member is provided with a drive portion, the first mounting portion further comprises a first positioning hole, the second mounting portion further comprises a second positioning hole, and the drive portion passes through the first positioning hole and the second positioning hole, and the first blade extends along a first longitudinal axis, and the first mounting hole and the first positioning hole are disposed on a straight line that obliquely intersects the first longitudinal axis, such that when the drive portion is inserted into the first positioning hole and the second positioning hole the blade assembly is fixed in a circumferential direction of the rotation axis relative to the drive member and a phase angle greater than zero (0) degrees is formed between the first blade and the second blade.
2. The lawn mower of claim 1, wherein the drive member is further provided with a second drive portion, the first mounting portion further comprises a third positioning hole, the second mounting portion further comprises a fourth positioning hole, and the second drive portion passes through the third positioning hole and the fourth positioning hole.

3. The lawn mower of claim 2, wherein the first mounting hole is disposed between the first positioning hole and the third positioning hole, and the second mounting hole is disposed between the second positioning hole and the fourth positioning hole.
4. The lawn mower of claim 2, wherein the drive portion is substantially cylindrical.
5. The lawn mower of claim 2, wherein the second drive portion forms a flat connection with the first blade and the second blade.
6. The lawn mower of claim 1, wherein the mounting assembly further comprises a clamping assembly configured to clamp the blade assembly to the drive member, the drive member comprises a lower surface in contact with the blade assembly, and the blade assembly is located between the lower surface and the clamping assembly.
7. The lawn mower of claim 6, wherein the mounting assembly further comprises an insulating member disposed between the blade assembly and the clamping assembly.
8. The lawn mower of claim 6, wherein the mounting assembly further comprises a fastening assembly for fixing a position of the blade assembly relative to the drive member in a direction parallel to the rotation axis.
9. The lawn mower of claim 8, wherein the fastening assembly is connected to the drive shaft and pushes against the clamping assembly, and the fastening assembly and the drive shaft form a detachable connection.
10. The lawn mower of claim 1, wherein a product of a rotation diameter D (mm) of the blade assembly, a number N of battery cells in the battery pack, and a mass M (g) of the blade assembly is greater than or equal to 3.5×10^5 (mm.Math.g) and less than or equal to 7.3×10^7 (mm.Math.g).
11. The lawn mower of claim 1, wherein a volume of a smallest cylinder surrounding the first blade and the second blade is defined as a swept volume of the blade assembly, the first blade and the second blade are located in a space surrounded by the smallest cylinder when the blade assembly rotates around the rotation axis, and the swept volume of the blade assembly is greater than or equal to 400 cm^3 and less than or equal to 8000 cm^3 .
12. The lawn mower of claim 1, wherein the first blade and the second blade are formed separately.
13. The lawn mower of claim 1, wherein the mounting assembly comprises a first mounting state and a second mounting state, both the first blade and the second blade are mounted to the drive shaft when the mounting assembly is in the first mounting state, and only one of the first blade and the second blade is mounted to the drive shaft when the mounting assembly is in the second mounting state.
14. A lawn mower, comprising: a blade assembly comprising a first blade and a second blade, wherein the blade assembly is configured to be rotatable about a rotation axis, the first blade comprises a first mounting portion provided with a first mounting hole and a first cutting portion for cutting grass, and the second blade comprises a second mounting portion provided with a second mounting hole and a second cutting portion for cutting grass; a deck formed with an accommodation space for accommodating at least a portion of the blade assembly; a motor comprising a drive shaft for driving the blade assembly to rotate about the rotation axis, wherein the drive shaft passes through the first mounting hole and the second mounting hole; and a mounting assembly configured to mount the blade assembly to the drive shaft, wherein the mounting assembly comprises a drive member coupled to the drive shaft, the drive member is a fan, the fan is provided with a drive portion, the first mounting portion further comprises a first positioning hole, the second mounting portion further comprises a second positioning hole, the drive portion is inserted into the first positioning hole and the second positioning hole, the first blade extends along a first longitudinal axis, and the first mounting hole and the first positioning hole are disposed on a straight line that obliquely intersects the first longitudinal axis.
15. The lawn mower of claim 14, wherein the drive member is further provided with a second drive portion, the first mounting portion further comprises a third positioning hole, the second mounting portion further comprises a fourth positioning hole, and the second drive portion is inserted into the

third positioning hole and the fourth positioning hole.

16. The lawn mower of claim 15, wherein the first mounting hole is disposed between the first positioning hole and the third positioning hole, and the second mounting hole is disposed between the second positioning hole and the fourth positioning hole.

17. The lawn mower of claim 14, wherein the drive portion forms a flat connection with the first blade and the second blade.

18. The lawn mower of claim 14, wherein the lawn mower further comprises a battery pack for powering the motor, and a product of a rotation diameter D (mm) of the blade assembly, a number N of battery cells in the battery pack, and a mass M (g) of the blade assembly is greater than or equal to 3.5×10^5 (mm.Math.g) and less than or equal to 7.3×10^7 (mm.Math.g).

19. The lawn mower of claim 14, wherein a volume of a smallest cylinder surrounding the first blade and the second blade is defined as a swept volume of the blade assembly, the first cutting portion and the second cutting portion are located in a space surrounded by the smallest cylinder when the blade assembly rotates around the rotation axis, and the swept volume of the blade assembly is greater than or equal to 400 cm^3 and less than or equal to 8000 cm^3 .
