

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12408758
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Wilcox; Steven Ellis

Folding chair with detachable container

Abstract

Portable chairs including a detachable container. The container can be insulated for keeping beverages and food cold for an extended period. The folding chair preferably is designed and constructed for the demands of the outdoors. Various detachable, reconfigurable, and/or interchangeable features including the container, carrying straps, and cup holder. The container can be easily and conveniently attached and detached from the folding chair. The container can have exterior pockets which are welded and sealed to protect items contained within. The straps can have multiple different attachment points which allow multiple different carrying styles and reconfigurations including a backpack type carrying configuration, over-the-shoulder briefcase type carrying configuration, and across the body satchel type configuration, for example. The cupholder is interchangeable from each side of the folding chair and can be designed to accommodate various different types of beverage containers including cups having a handle, a can, and a canteen, for example.

Inventors:	Wilcox; Steven Ellis (Oceanside, CA)
Applicant:	PARKIT CO. (Dover, DE)
Family ID:	74568683
Assignee:	ParkIt Co. (Oceanside, CA)
Appl. No.:	18/959871
Filed:	November 26, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20250082102 A1	Mar. 13, 2025

Related U.S. Application Data

continuation parent-doc US 18785591 20240726 PENDING child-doc US 18959871
continuation parent-doc US 29828666 20220228 PENDING child-doc US 18785591
division parent-doc US 17090288 20201105 US 11259639 child-doc US 29828666
us-provisional-application US 63021074 20200506
us-provisional-application US 62930775 20191105

Publication Classification

Int. Cl.: **A47C7/62** (20060101); **A45F4/02** (20060101); **A47C7/22** (20060101)

U.S. Cl.:

CPC **A47C7/626** (20180801); **A45F4/02** (20130101); **A47C7/22** (20130101);

Field of Classification Search

CPC: A45F (4/02); A47C (7/626); A47C (7/22)

USPC: 297/188.2

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
D193336	12/1961	Batie et al.	N/A	N/A
3077327	12/1962	Batie et al.	N/A	N/A
3266686	12/1965	Griffith	224/155	A45F 4/02
4063701	12/1976	Wray	297/188.2	A47C 7/624
4148376	12/1978	Campbell, Jr.	182/20	A45F 3/04
D261834	12/1980	Stebbins	N/A	N/A
D271581	12/1982	Wood	N/A	N/A
4487345	12/1983	Pierce et al.	N/A	N/A
4650245	12/1986	Nazar	N/A	N/A
4772068	12/1987	Gleckler et al.	N/A	N/A
4948197	12/1989	Sansing	N/A	N/A
D338782	12/1992	Gibson et al.	N/A	N/A
5641197	12/1996	Springmann	N/A	N/A
5865124	12/1998	Wroe	108/157.11	A47C 7/70
5924769	12/1998	Kao	N/A	N/A
6000752	12/1998	Shyr	N/A	N/A
6048023	12/1999	Lampton	N/A	N/A
6056172	12/1999	Welsh	N/A	N/A
6082816	12/1999	Gottlieb et al.	N/A	N/A
D434234	12/1999	Forrentino	N/A	N/A
D438719	12/2000	Ford et al.	N/A	N/A
6217111	12/2000	Tseng	N/A	N/A
6390345	12/2001	Brown et al.	N/A	N/A
6607240	12/2002	Zheng	N/A	N/A
D481547	12/2002	Ammann, Jr.	N/A	N/A

6739652	12/2003	Welsh	N/A	N/A
6764132	12/2003	Gaertner	N/A	N/A
RE39022	12/2005	Welsh	N/A	N/A
D521262	12/2005	Wood	N/A	N/A
7118172	12/2005	Pattison-Sheets	N/A	N/A
7475889	12/2008	Marmah et al.	N/A	N/A
7717503	12/2009	Watson	N/A	N/A
8113396	12/2011	Schilly	224/155	A45F 3/047
D672161	12/2011	McDowell	N/A	N/A
D683550	12/2012	Ammann, Jr.	N/A	N/A
8864221	12/2013	Delvilla	N/A	N/A
D722775	12/2014	Thuma et al.	N/A	N/A
D724328	12/2014	Thuma et al.	N/A	N/A
D727039	12/2014	Thuma et al.	N/A	N/A
D727040	12/2014	Thuma et al.	N/A	N/A
D736527	12/2014	Thuma et al.	N/A	N/A
D828016	12/2017	Gillespie et al.	N/A	N/A
D831366	12/2017	Jin	N/A	N/A
D839016	12/2018	Haingaertner	N/A	N/A
D850135	12/2018	Yang	N/A	N/A
D911057	12/2020	Jacobsen	N/A	N/A
D911730	12/2020	Doolan et al.	N/A	N/A
D912423	12/2020	Sullivan et al.	N/A	N/A
D935211	12/2020	Chen	N/A	N/A
11259639	12/2021	Wilcox	N/A	N/A
D955132	12/2021	Sullivan et al.	N/A	N/A
D1005708	12/2022	Wilcox	N/A	N/A
2002/0145326	12/2001	Liu	297/452.64	A47C 4/03
2002/0171268	12/2001	Liu	N/A	N/A
2004/0189062	12/2003	Knight et al.	N/A	N/A
2004/0206790	12/2003	Welsh	N/A	N/A
2005/0225126	12/2004	Frederick	N/A	N/A
2005/0225136	12/2004	Horton et al.	N/A	N/A
2008/0012399	12/2007	Lin	N/A	N/A
2008/0078789	12/2007	Fiola	N/A	N/A
2010/0026057	12/2009	Miller	N/A	N/A
2010/0252589	12/2009	Popescu	N/A	N/A
2013/0193724	12/2012	Gould et al.	N/A	N/A
2018/0332953	12/2017	Solomon et al.	N/A	N/A
2018/0338622	12/2017	Doolan et al.	N/A	N/A
2018/0338623	12/2017	Winterhalter	N/A	A47C 4/10
2019/0045908	12/2018	Zhu et al.	N/A	N/A
2019/0082846	12/2018	Grace	N/A	N/A
2019/0090667	12/2018	Mason et al.	N/A	N/A
2020/0289231	12/2019	Gustafson et al.	N/A	N/A
2020/0383481	12/2019	Cieszko et al.	N/A	N/A
2021/0045535	12/2020	Wilcox	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
------------	------------------	---------	-----

302481123	12/2012	CN	N/A
302719149	12/2013	CN	N/A
203506111	12/2013	CN	N/A
307216534	12/2021	CN	N/A
307540689	12/2021	CN	N/A
2805643	12/2013	EP	N/A
2436521	12/2006	GB	B60N 2/28
S5829953	12/1982	JP	N/A
2002325654	12/2001	JP	N/A
D1217379	12/2003	JP	N/A
2006181053	12/2005	JP	N/A
2011050641	12/2010	JP	N/A
300951418	12/2017	KR	N/A

OTHER PUBLICATIONS

Parkit Camping Chair, retrieved from youtube.com, posting date Nov. 8, 2019, online, retrieved Aug. 4, 2023, <https://www.youtube.com/watch?v=0rAOgobXDe4>, 1 page. cited by applicant

“Kingmodern Portable Lightweight Camping Chair Outdoor Small Stool Folding Waterproof Oxford Fabric Backrest Chair Hold up 13 L Cooler Bags”, Retrieved from internet URL: <https://www.amazon.com/Kingmodern-Portable-Lightweight-Waterproof-ArmyGreen/dp/B0839NT3DZ>, on May 15, 2023, 7 pages. cited by applicant

“Leadallway Foldable Camping Chair with Cooler Bag Compact Fishing Stool”, Retrieved from internet URL: <https://www.leadallway.com/leadallway-foldable-camping-chair-with-cooler-bag-compact-fishing-stool-p3022586.html>, on May 15, 2023, 6 pages. cited by applicant

“Voyager”, Retrieved from internet URL: https://parkitmovement.com/products/the-voyager-chair?variant=31457158627401¤cy=USD&utm_medium=product_sync&utm_source=google&utm_content=sag_organic&utm_campaign=sag_organic&utm_campaign=gs-2021-03-01&utm_source=google&utm_medium=smart_campaign&gclid=Cj0KCQjwz6ShBhCMAR1sAH9A0qUmPh186hSOkbrF8Loy3_N_nz5V9JteXwvYRJWU8cy2YjCT1Jkf3_AaAnUfEALw_wcB, on May 15, 2023, 7 pages. cited by applicant

Blog.naver.com [online], “Snow Peak Low Chair (LV-090),” Sep. 2, 2013, retrieved on Jun. 27, 2024, retrieved from URL <<https://blog.naver.com/cch1778/50178696034>>, 21 pages (with English translation). cited by applicant

Extended European Search Report in European Appln. No. 20884251.8, dated Nov. 24, 2023, 4 pages. cited by applicant

International Preliminary Report on Patentability in International Appln. No. PCT/US2020/059083, dated May 10, 2022, 11 pages. cited by applicant

International Search Report for PCT/US2020/059083 issued mailed Feb. 10, 2021, applicant Parkit Co., 3 pages. cited by applicant

Parkit Camping Chair, retrieved from youtube.com, posting date Nov. 8, 2019, online, retrieved Aug. 4, 2023, <https://www.youtube.com/watch?v=OrAOgobXDe4>, 1 page. cited by applicant

Parkitmovement.com [online], “Voyager chair,” Parkit, retrieved from URL: <<https://parkitmovement.com/products/the-voyager-chair>> [site visited on May 18, 2022], 4 pages. cited by applicant

Written Opinion of the International Searching Authority for PCT/US2020/059083 mailed Feb. 10, 2021, applicant Parkit Co., 10 pages. cited by applicant

Office Action in Japanese Appln. No. 2022-526354, mailed on Jul. 29, 2025, 30 pages (with English translation). cited by applicant

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This patent application is a continuation of U.S. patent application Ser. No. 18/785,591, filed Jul. 26, 2024, which claims the benefit of and priority to the following applications: U.S. patent application Ser. No. 29/828,666, filed Feb. 28, 2022; U.S. patent application Ser. No. 17/090,288, filed Nov. 5, 2020; U.S. Patent Application No. 63/021,074, filed May 6, 2020; and U.S. Patent Application No. 62/930,775, filed Nov. 5, 2019, the entire contents of which are hereby incorporated by reference.

BACKGROUND

(1) In the portable seating industry, a market exists for high performance folding chairs that are capable of efficiently and effectively withstanding heavy use and servicing large audiences. These seating situations are commonly found in gymnasiums, stadiums, auditoriums, schools and churches and at outdoor events, such as picnics and concerts. Due to the common nature of the events, the performance requirements for these chairs can be extremely demanding. For example, they must be able to withstand rugged use, such as that commonly found with sports fans and concert goers. And to also provide comfort for prolonged seating periods.

(2) Many folding chairs tend to be uncomfortable, especially in circumstances of extended seating time. For example, seats are commonly made of rigid materials, such as metal, plastic and/or wood. Such materials can become even more uncomfortable over time as their surface degrades and becomes weathered. Sometimes these rigid seats are covered with a layer of padding, such as foam, which may not be sufficient in thickness, resiliency and/or quality.

(3) Moreover, these seat constructions tend to ignore the contours of the human body. For example, seating surfaces are commonly one dimensional, whereas the human body plainly is not so simple.

(4) Folding chairs also tend to provide insufficient back support. One reason is that the back support is often minimized for a folding operation and for minimal storage space. For instance, backrest portions are typically much smaller than the human back. Backrests are also often made of a rigid material, such as metal, plastic or wood, which can become uncomfortable over time as previously mentioned, and ignores the contours of the human body. As with seats, backrests are sometimes covered with a layer of padding, such as foam, which may not be sufficient in every case. Also, backrests tend to be one-dimensional, as opposed to the human body. As a result, there is a desire for a folding chair with a seat and backrest that provide enhanced comfort, particularly for high performance folding chairs used in preferred seating areas, and also the requisite durability for heavy and rugged use.

(5) The subject matter claimed herein is not limited to embodiments that solve any disadvantages or that operate only in environments such as those described above. Rather, this background is only provided to illustrate one exemplary technology area where some embodiments described herein may be practiced.

BRIEF SUMMARY OF THE INVENTION

(6) This Summary is provided to introduce a selection of concepts in a simplified form that are further described below in the Detailed Description. This Summary is not intended to identify key features or essential characteristics of the claimed subject matter, nor is it intended to be used as an aid in determining the scope of the claimed subject matter.

(7) The present invention relates to a folding chair having detachable, reconfigurable, and/or interchangeable features including a detachable, reconfigurable, and/or interchangeable container,

carrying straps, and/or cup holder. The container can be insulated and can be easily and conveniently attached and detached from the folding chair. While referred to herein with reference to specific container embodiments as being insulated, in each instance it should be understood that the same disclosure is relevant to embodiments where the container is not insulated. Therefore, reference to insulated containers should be understood to also reference the same embodiments, discussion, and illustrations of which the container is not insulated.

(8) The insulated container can be welded, insulated and sealed with exterior pockets which are also welded and sealed to protect items contained within. The straps can have multiple different attachment points which allow multiple different carrying styles and reconfigurations including a backpack type carrying configuration, over-the-shoulder briefcase type carrying configuration, and across the body satchel type configuration, for example. The cupholder can be interchangeable from each side of the folding chair and can be designed to accommodate various different types of beverage containers including cups having a handle, a can, and a canteen, for example.

(9) A folding chair includes a chair frame. The chair frame can include a left front leg frame element, a right front leg frame element, a left rear leg frame element, a right rear leg frame element, and a seat frame including two or more seat frame elements. The seat frame element can include a first seat frame element and a second seat frame element. The folding chair can include an insulated container connectable and disconnectable to the chair frame such that the insulated container is disposed under a seat of the folding chair when the insulated container is connected to the chair frame. The seat can include seat material extending between the first seat frame element and the second seat frame element. A first side of the seat material at least in part provides the seat for a person to sit upon. A second side of the seat material extends over the insulated container when the insulated container is connected to the chair frame.

(10) The folding chair frame can further include a left arm support frame element and a right arm support frame element. The folding chair frame can further include a left back support frame element pivotally connected to the left arm support frame element. The folding chair can further include a right back support frame element pivotally connected to the right arm support frame element. The folding chair can further include an upper back support frame element connecting the left back support frame element to the right back support frame element. The first seat frame element can include a left seat frame element and the second seat frame element can include a right seat frame element.

(11) The chair frame can further include a left front joint, the left front joint coupling the left front leg frame element to the left seat frame element. The folding chair can further include a right front joint, the right front joint coupling the right front leg frame element to the right seat frame element.

(12) The folding chair can further include a left rear joint, the left rear joint coupling the left rear leg frame element to the left seat frame element. The folding chair can further include a right rear joint, the right rear joint coupling the right rear leg frame element to the right seat frame element.

(13) The left front joint can include a left front joint insulated container connector for connecting the left front joint to the insulated container. The right front joint can include a right front joint insulated container connector for connecting the right front joint to the insulated container. The left rear joint can include a left rear joint insulated container connector for connecting the left rear joint to the insulated container. The right rear joint can include a right rear joint insulated container connector for connecting the right rear joint to the insulated container.

(14) The left front can include a left front joint cup holder connector for selectively connecting the left front joint to a cup holder. The right front joint can further include a right front joint cup holder connector for selectively connecting the right front joint to the cup holder.

(15) The left rear joint can further include a left rear joint strap connector. The right rear joint can further include a right rear joint strap connector.

(16) The folding chair can include a handle. The handle can be connected to two loops. The loops can be disposed around the upper back support frame element. The loops can be connectable to

first ends of two carrying straps. Second ends of the two carrying straps can be connected to the left and right rear joint strap connectors for carrying the folding chair in a back pack configuration.

(17) The folding chair can include a left arm rest made of wood and connected to an upper side of the left arm support frame element. A right arm rest made of wood and connected to an upper side of the right arm support frame element.

(18) The second side of the seat material can extend over and is directly adjacent to the insulated container when the insulated container is connected to the chair frame.

(19) The left front leg frame element can be connected to the right front leg frame element by a front leg ground surface frame element. The front leg frame element can be an integrated U-shaped front leg frame element.

(20) The left rear leg frame element can be connected to the right rear leg frame element by a rear leg ground surface element. The rear leg frame element can be an integrated U-shaped rear leg frame element.

(21) The seat frame can further include a front seat frame element, the first seat frame element and second seat frame element being connected by the front seat frame element. The seat frame element can be an integrated U-shaped seat frame element.

(22) The back frame can further include an integrated U-shaped seat frame element.

(23) The insulated container can include a plurality of straps sewn thereto and having connectors disposed proximate to opposing ends of the plurality of straps for connection to front and rear couplings of the folding chair.

(24) The front and rear couplings can each include a clip connector for releasably connecting to the strap connectors of the insulated container. The rear couplings can be connected by a horizontal support brace. The horizontal support brace can be connected to the rear leg frame element by a rear support bracket.

(25) One or more of the front pivotable couplings can include a connector for securing a cup holder thereto.

(26) A method of configuring the foldable chair can include connecting a first strap in a satchel configuration, reconfiguring the first strap in a brief case configuration, and/or reconfiguring the first strap in a backpack configuration. The method of configuring the foldable chair can include connecting a second strap in the backpack manner.

(27) An insulated container can include one or more connectors extending from an upper surface of the insulated container for selectively connecting the insulated container to a bottom of a chair frame.

(28) A front pivotable coupling for a folding chair can include a first coupling element for connecting to a side of a seat support frame element, a second coupling element for connecting to a front leg frame element, and a connector for connecting to an insulated container. The front pivotable coupling can include a cup holder connector disposed around a periphery of the front pivotable coupling and configured to connect to an attachable cup holder.

(29) A front pivotable coupling for a folding chair can include a first coupling element for connecting to a side of a seat support frame element, a second coupling element for connecting to a front leg frame element, and a connector for selectively connecting and disconnecting to cup holder.

(30) A rear pivotable coupling for a folding chair can include a first coupling element for connecting to an end of a seat support frame element, a second coupling element for connecting to a back support frame element, and a connector for connecting to an insulated container. The rear pivotable coupling can further include a third coupling element for pivotably coupling to a horizontal brace. The third coupling element can be further configured to couple the rear pivotable brace to a pivotable bracket. The bracket can pivotably couple the rear pivotable coupling to a rear leg frame element.

(31) The folding chair can further include one or more cup holders connected to the one or more

front pivotable couplings.

(32) The folding chair can further include arm rests connected to the left arm support frame element and right arm support frame element. The arm rests can be made of wood. The arm rests can be made of bamboo.

(33) The folding chair frame can include aluminum. The front leg frame element, rear leg frame element, back support frame element, and seat support frame element can be made from aluminum. The front leg frame element, rear leg frame element, back support frame element, and seat support frame element can have a diameter of at least one inch.

(34) The folding chair can have a fabric webbing connected to the seat and back support frame elements.

(35) Additional features and advantages of the invention will be set forth in the description which follows, and in part will be obvious from the description, or may be learned by the practice of the invention. The features and advantages of the invention may be realized and obtained by means of the instruments and combinations particularly pointed out in the appended claims. These and other features of the present invention will become more fully apparent from the following description and appended claims or may be learned by the practice of the invention as set forth hereinafter.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) To further clarify the above and other advantages and features of the present invention, a more particular description of the invention will be rendered by reference to specific embodiments thereof which are illustrated in the appended drawings. It is appreciated that these drawings depict only typical embodiments of the invention and are therefore not to be considered limiting of its scope. The invention will be described and explained with additional specificity and detail through the use of the accompanying drawings in which:

(2) FIG. 1 illustrates a folding chair having an insulated container connected to a a seat frame;

(3) FIG. 2 illustrates the folding chair having the insulated container connected to the seat frame from a front, left and right view;

(4) FIG. 3 shows a person carrying the folding chair with the insulated container and sitting on the folding chair with the insulated container;

(5) FIG. 4 shows people carrying the folded chair with the insulated container and a carrying strap in a backpack, satchel, and brief case configuration;

(6) FIG. 5 shows the interchangeable cup holder connectors and insulated container with welded exterior pockets in further detail;

(7) FIG. 6 shows the front coupling joint having the interchangeable cup holder connector as wells as connectors for connecting to the insulated container and carrying strap(s);

(8) FIG. 7 shows the rear coupler having integrated connectors for connecting to the insulated container and carrying strap(s);

(9) FIG. 8 illustrates additional examples and views of the front and rear couplers as well as an example of a closure retention element;

(10) FIG. 9 illustrates additional features of the folding chair with the detachable and independently usable insulated container;

(11) FIG. 10 illustrates additional features of the cup holder connector and an example of a closure retention element;

(12) FIG. 11 is an exploded view of various examples of elements of the folding chair;

(13) FIGS. 12, 13, and 14 illustrate further examples of closure retention elements;

(14) FIG. 15 illustrates an example of a handle connected to the back support frame element; and

(15) FIG. 16 illustrates an example of a handle that can be used as a connector for carrying straps in

a backpack carrying configuration.

DETAILED DESCRIPTION

(16) Embodiments of the invention relate to a portable chair having superior craftsmanship and improved functionality. The portable chair includes a detachable container, which can be insulated for keeping beverages and food cold for an extended period according to certain embodiments. The chair preferably is designed and constructed for the demands of the outdoors. The chair can be constructed of improved materials including, according to some preferred embodiments, a frame made from aircraft grade aluminum. The chair can include a seat and back made of fabric webbing that is soft to touch and encircles a nylon webbed core maintaining strength and “like new” comfort. The fabric webbing can include a woven polyester fabric that can be made water-resistant. The chair can have armrests, made of wood that can be laminated and sealed for elemental protection. The armrests can also be bamboo armrests that are lightweight, durable, and eco-friendly.

(17) Other improvements and features which exhibit distinctive advantages include various detachable, reconfigurable, and/or interchangeable features including the insulated container, carrying straps, and cup holder. The insulated container can be easily and conveniently attached and detached from the folding chair. The insulated container can be welded, insulated and sealed with exterior pockets which are also welded and sealed to protect items contained within. The straps can have multiple different attachment points which allow multiple different carrying styles and reconfigurations including a backpack type carrying configuration, over-the-shoulder briefcase type carrying configuration, and across the body satchel type configuration, for example. The cupholder can be interchangeable from each side of the folding chair and can be designed to accommodate various different types of beverage containers including cups having a handle, a can, and a canteen, for example. Additional interchangeable accessory connection implements can accommodate umbrellas, tables, fishing rod holders, etc. as would be understood in view of the teachings disclosed hereinafter.

(18) The detachable insulated container can be designed to keep ice frozen for more than eight hours, according to some preferred embodiments. The detachable insulated container can have soft or hard sidewalls and construction, or a mixture of soft and hard sidewalls and construction. The folding chair and insulated container can include exterior pockets to securely carry and protect additional items. Such exterior pockets can be welded as opposed to sewn so as to ensure a waterproof seam and streamlined appearance. According to certain preferred embodiments, the multiple carrying options provide for hands free carrying experience which is also ergonomically designed for comfort. Such multiple different carrying configurations can also lend to a wide variety of different carrying situations depending on the environment and desires of the user.

(19) The detachable container can secure snugly to the underside of the seat base frame of the chair through carabiner-like clips according to certain preferred embodiments. Such convenient connection allows for easy access to the contents of the insulated container. In addition, the insulated container can be easily detached from the seat frame of the foldable chair for additional mobility, separate use, and as may otherwise be desirable in different circumstances.

(20) A hands-free carrying strap runs across the chest in a satchel carrying configuration allowing freedom for the user's hands to carry additional equipment and items. According to various embodiments, the folding chair can be used to secure additional items such as snorkels, flippers, and other items within the folded chair for any particular use.

(21) The interchangeable cup holder can be included with cutouts designed for cans, insulated water bottles, canteens, and coffee mugs. Advantageously, the interchangeable cup holder can be releasably connected to an innovative frame element joint as opposed to situated on, or formed in, the arm rest to provide an improved ergonomic, multi-functionality, reduction in parts, and multi-purpose joints for supporting rotatable frame elements in addition to the interchangeable cup holders.

- (22) Referring to FIGS. 1 and 2, an embodiment of a folding chair **100** including an insulated container **140** is illustrated. The folding chair **100** includes a folding chair frame. The folding chair frame can include a left arm support frame element **125A** and a right arm support frame element **125B**.
- (23) The folding chair frame can further include a front leg frame element **105** pivotally connected to the left arm support frame element **125A**. The front leg frame element **105** also being pivotally connected to the right arm support frame element **125B**.
- (24) The folding chair frame can further include a rear leg frame element **110**. The rear leg frame element **110** being pivotally connected to the left arm support frame element **125A**. The rear leg frame element **110** also being pivotally connected to the right arm support frame element **125B**.
- (25) The folding chair frame can further include a back support frame element **115** pivotally connected to the left arm support frame element **125A**. The back support frame element **115** also being pivotally connected to the right arm support frame element **125B**.
- (26) The folding chair frame can further include a seat support frame element **120**. The seat support frame element **120** can be pivotally coupled to the rear leg frame element **110**. The seat support frame element **120** can also be pivotally coupled to the front leg frame element **105**.
- (27) The folding chair **100** can further include seat support material **155** and back support material **150**. The back support material **155** can extend from the sides of the back support frame **115**. The seat support material **155** can extend from the sides of the seat support frame element **120**. The seat support material **155** and/or back support material **150** can include a webbing of seat and back support material. The webbing of material can include horizontal webbing interlaced with perpendicular horizontal seat support webbing material **155** or vertical back support webbing material **150** as shown in FIG. 1. The seat support material **155** and/or the back support material **150** can also be a sheet of material, strips of material or other configuration of material so as support the seat and back of a person sitting in the folding chair **100**.
- (28) The folding chair **100** can further include a left arm rest **160A** connected to the left arm support frame element **125A**. The folding chair **100** can further include a right arm rest **160B** connected to the right arm support frame elements **125B**. The arm rests **160** can be made of any material. However, according to preferred particularly ergonomic designs, the arm rests **160** can be made of wood according to embodiments disclosed herein. For example, the arm rests **160** can be made of bamboo wood according to some preferred embodiments.
- (29) The folding chair **100** can include a cup holder **130**. The cup holder **130** can be easily interchangeable from/to the left and right sides of the folding chair **100**. The cup holder **130** can include a cutout **131** to accommodate a mug or handle of a cup. The cup holder **130** can be connectable and disconnectable to cup holder connectors **132**. The folding chair **100** can include two cup holder connectors **132**, one cup holder connector **132A** on the left side of the folding chair **100** and one cup holder connector **132B** on the right side of the folding chair **100**. The cup holder **130** can be connected and disconnected to the cup holder connectors **132** on each side of the folding chair **100** as preferred by the person sitting in the folding chair **100**. Advantageously, the cup holder connectors **132** can be coupled, attachable or attached to the front leg frame element **105** as well coupled, attachable or attached to the seat frame element **120**. For example, the cup holder connectors **132** can include an interlocking or mating slot that corresponds to an interlocking or mating key or protrusion disposed on the cup holder **131**.
- (30) Referring to FIG. 3, the folding chair **100** including the insulated container **140** is shown with a person sitting on the chair on the left of FIG. 3 as well as the person carrying the folded folding chair **100** on the right of FIG. 3. As shown in FIG. 3, the insulated container **140** is easily accessible to the person in the sitting position and is easily carried by the connectable and reconfigurable strap **165** in the folded position.
- (31) Referring to FIG. 4, the folding chair **100** is shown with three different configurations of one or more connectable and disconnectable carrying straps **165**. In a first configuration on the left the

straps **165** are configured in a backpack configuration. In a second configuration in the middle a strap **165** is in a briefcase carrying configuration over the woman's shoulder. And, in the third configuration on the right the reconfigurable strap **165** is in a satchel configuration over the man's shoulder and across his chest.

(32) Referring to FIG. 5 additional optional and advantageous components of the insulated container **140** are illustrated. The insulated container **140** includes a handle **141**. The handle **141** can be used to carry the insulated container **140** when disconnected from the frame of the folding chair **100**.

(33) The insulated container **140** can be connectable and disconnectable by front connectors **144** and rear connectors **145** of the insulated container **140**. The front connectors **144** and rear connectors **145** can be in the form of loops, clips, or hooks attached, coupled, or connected to the insulated container **140**, for example.

(34) The insulated container **140** can also include one or more exterior pockets **142**. For example, as shown in FIG. 5, the insulated container **140** can include pockets **142** with closure devices, such as zippers. The insulated container **140** can include one or more bottom pockets **142** and/or one or more side pockets (not shown) as illustrated in FIG. 5. The pockets **142** can be welded as opposed to sewn in some embodiments to ensure a water-tight seam between the pockets **142** and the insulated container **140**.

(35) The folding chair **100** is illustrated in the figures as having a generally U-shaped front leg frame element **105**, U-shaped seat support frame element **120**, U-shaped rear leg support frame element **110** and U-shaped back support frame element **115** interconnected by multiple couplings, folding joints and/or pivotable joints. However, individual or distinct portions of the back support frame element **115**, leg support frame elements **105** and **110**, and seat support frame elements **120** may be implemented. Use of U-shaped frame elements **105**, **120**, **110** and **115** renders various improvements, functional strength, and ergonomic benefits as discovered by the inventor of this patent application.

(36) For example, referring still to FIG. 5, the folding chair **100** can include the chair frame having a left front leg frame element portion **105A** and a right front leg frame element portion **105B**. The left front leg frame element portion **105A** can, but need not, be connected to the right front leg element **105B** by an interconnecting front leg frame element portion **105C**. The elements of the front leg frame element **105** can be a U-shaped single integrated support frame element or can be separate individual portions according to embodiments not specifically illustrated. Any element of the frame elements can be made from singles frame elements which may be bent to perform structural support functions, or may be multiple individual support frame elements which may be connected or coupled together or designed for different configurations or individual functionality.

(37) Similarly, the rear leg frame element **110** can include a left rear leg frame element portion **110A** and a right rear leg frame element portion **110B**. The left rear frame element **110A** can be, but need not, be connected to the right rear leg element **110B** by an interconnecting rear leg frame element portion **110C**. As shown, the elements of the rear leg frame element **110** can be a single piece as shown or separate pieces (not shown) which may be coupled together according to some embodiments.

(38) Similarly, the seat frame element **120** can include two or more seat frame element portions. As illustrated in FIG. 5, the seat frame element **120** can include a first seat frame element portion **120A** and a second seat frame element portion **120B**. The first seat frame element portion **120A** can be a left seat frame element portion and the second seat frame element portion **120B** can be a right seat frame element portion **120B**. The first seat frame element portion **110A** can be connected to the right seat frame element portion **110B** by an interconnecting seat frame element portion **110C**. As shown, the elements of the seat frame element **120** can be a single piece or separate pieces. Similar teachings can be understood with reference to the back support frame element **115** as would be understood to one of ordinary skill in the art in view of the foregoing teachings.

(39) Referring to FIGS **6-10**, the folding chair can further include multiple couplings and joints adjoining two or more of the front leg frame element **105**, rear leg frame element **110**, back support frame element **115**, seat support frame element **120**, and cup holder connectors **132**. The couplings and joints can further include, and be integrated with in some embodiments, connectors for connecting the coupling joints to the one or more carrying straps **165** and insulated container **140**.

(40) For example, the foldable chair **100** can include two front couplings **170** and two rear couplings **180**. The front couplings **170** can have a first front coupling joint portion **170A** for connecting to the front leg frame element **105** and a second front coupling joint portion **170B** for connecting to the seat frame element **120**. The first front coupling joint portion **170A** is rotatably connected to the second front coupling joint **170B** such that the seat frame element **120** is rotatably coupled to the front leg frame element **105**.

(41) As shown in FIG. **7**, the front coupling joints **170** can include a pivot rod **173** extending through the first front coupling joint portion **170A** and the second front coupling joint portion **170B** providing for the rotation of the first front coupling joint portion **170A** relative to the second front coupling joint portion **170B** while providing support for a person sitting upon the seat of the folding chair **100**.

(42) The front coupling joints **170** can further include first front coupling connectors **171** for connecting the second front coupling joint portions **170B** of each front coupling joint **170** to the insulated container **140**. For example, as shown, the first front coupling connector **171** can include an integrated clip like a carabiner for connecting to a front connector **144** of the insulated container **140**. As shown in FIG. **7**, front connectors **144** of the insulated container **140** can be affixed to a top side of the insulated container **140** by straps **146** sewn or otherwise attached the upper side of the insulated container **140**. The front coupling joints **170** can further include a second front coupling joint connector **172** as shown in FIG. **6** for connecting and disconnecting the front coupling joints **170** to an end of a carrying strap (not shown).

(43) The folding chair frame can further include two rear rotatable and foldable couplings **180**. The rear couplings **180** can foldably couple ends of the back support frame element **115** to ends of the seat support frame element **120**. The rear couplings **180** can further rotatably couple the back support frame element **120** and the seat support frame element **120** relative to the rear leg frame element **110**.

(44) More specifically, as shown in FIG. **7** the right rear coupling **180** is illustrated and includes two foldable rear coupling portions **180A** and **180B**. The first foldable rear coupling portion **180A** connects to the back support frame element **115**. The second foldable rear coupling portion **180B** connects to the seat frame element **120**. When in the folded position (not shown), the back support frame element **115** is folded over against the seat support frame element **120**. Moreover, due to the rotational connection of the rear leg support frame element **110** to the rear couplings **180**, the rear leg support frame element **110** is rotatable into the folded position adjacent to and approximately parallel to the seat support frame element **120**, back support frame element **115** and front leg support frame element **105** as well. The rotation and support of the seat frame element **120** is enabled by a pivotable support rod **183** coupled to the rear leg frame element **110** by a rotation support frame arm **184**.

(45) The rear couplings **180** further can further include a first rear coupling connector **181** for connecting the rear couplings **180** to the insulated container **140**. The first rear coupling connector **181** can be formed integral with the second portion **180B** of the rear couplings **180**. The first rear coupling connectors **181** can be similar in function to a carabiner with a metallic clip biased into the closed position.

(46) The rear couplings **180** can further include a second rear coupling connector **182** for connecting and disconnecting to a carrying strap (not shown). Thus, the foldable chair can include one, two, three or four front and rear coupling connections for selectively connecting the one or more carrying straps (e.g. see FIG. **4**) to both sides of the front and/or back of the seat of the

foldable chair **100** by the second rear coupling connectors **182** as shown in FIG. 7 and by the second front coupling joint connectors **172** as shown in FIG. 6.

(47) The folding chair portion **100** can further include the seat support material **155** and back support material **150**. The fabric of the seat support material **155** and back support material **150** can include fabric webbing of fabric strips. The fabric straps can include longitudinal strips of material that extend from a top end of the back support element **125** to an end of the seat support element **130**. Transverse strips of the seat support material **155** and back support material **150** can extend transverse to side of the back support element **125** and sides of the seat support element **130** and connect to opposing sides thereof. A design of the fabric of the seat support material **155** and back support material **150** of the folding chair **100** can be tailored to coincide with a design of fabric or wall pattern of the insulated container **180**. The strips of the seat support material **155** and back support material **150** of the folding chair **100** can be woven or can be a single or multiple sheets of fabric.

(48) The folding chair frame can include the two front pivotable couplings **170**. The front pilotable couplings **170** rotatably coupling ends of the seat support frame element **120** to the front leg frame element **105**. The folding chair frame can further include the two rear pivotable couplings **180**, the rear pivotable and foldable couplings **180** rotatably coupling ends of the back support frame element **115** and the seat support frame element **120** to the rear leg frame element **110**.

(49) The insulated container **180** can be connected to the two front pivotable couplings **170** and two rear pivotable and foldable couplings **180**. And, the insulated container **180** can have the handle **141** (not shown) attached thereto for carrying the insulated container **140** when the insulated container **140** is disconnected from the front pivotable couplings **170** and rear pivotable and foldable couplings **180**.

(50) The foldable chair portion **100** further including the arm rests **160** connected to the left arm support frame element **125A** and the right arm support frame element **125B**. The arm rests **160** can be made of wood such as bamboo.

(51) The foldable chair portion **110** can further include various different releasable closure retention mechanisms. For example, referring to FIGS. 5 and 7-12 a first embodiment of a folding chair closure retention element **190** is illustrated. According to this embodiment, the folding chair closure retention element **190** includes a rotatable clip rotatably connected to the front leg support frame element **105**. When the folding chair **100** is placed in the folded position the folding chair closure retention element **190** is rotated about the a center axis of the front leg support frame element **105** and clips onto the rear support frame element **110** as shown in FIG. 12.

(52) Referring to 13 a second embodiment of a folding chair closure retention element **191** is illustrated. According to this embodiment, the folding chair closure retention element **191** includes a rotatable clip rotatably connected to a side of the front leg support frame element **105**. When the folding chair **100** is placed in the folded position the second folding chair closure retention element **191** is rotated perpendicular the a center axis of the front leg support frame element **105** and clips onto a post connected to the rear support frame element **110** as shown in FIG. 13.

(53) Referring to 13 a second embodiment of a folding chair closure retention element **191** is illustrated. According to this embodiment, the folding chair closure retention element **191** includes a rotatable clip rotatably connected to a side of the front leg support frame element **105**. When the folding chair **100** is placed in the folded position the second folding chair closure retention element **191** is rotated perpendicular the a center axis of the front leg support frame element **105** and clips onto a post connected to the rear support frame element **110** as shown in FIG. 13.

(54) Referring to FIG. 14 a third embodiment of a folding chair closure retention element **192** is illustrated. According to this embodiment, the folding chair closure retention element **192** includes a strap connected to a side of the front leg support frame element **105**. When the folding chair **100** is placed in the folded position the third folding chair closure retention element **192** is wrapped around the rear support frame element **110** as shown in FIG. 14. The third chair closure retention

element **192** includes a snap, VELCRO, or other connecting element for releasably retaining the strap of the third folding chair closure retention element **192** in place and securing the folding chair **100** in the folded position.

(55) Referring to FIG. **15**, the folding chair **100** can further include a handle **199** connected to the top of the rear back support frame element **115** and spanning a back support web element **155** for carrying the folding chair.

(56) Referring to FIG. **16**, the folding chair **100** another example of a handle **194** is illustrated. The handle **194** being connected to two loops of cord **196**, the loops being disposed around the upper back support frame element **115**. The loops are connectable to first ends of two carrying straps **165**. Second ends of the two carrying straps **165** are connected to the left and right rear joint strap connectors **182** (not shown) for carrying the folding chair in a back pack configuration.

(57) The present invention may be embodied in other specific forms without departing from its spirit or essential characteristics. The described embodiments are to be considered in all respects only as illustrative and not restrictive. The scope of the invention is, therefore, indicated by the appended claims rather than by the foregoing description. All changes which come within the meaning and range of equivalency of the claims are to be embraced within their scope.

Claims

1. A folding chair, comprising: a chair frame comprising: a front leg frame; a rear leg frame; a back support frame; a seat frame pivotally coupled to the front leg frame and the back support frame; a left arm support pivotally coupled to the front leg frame and the rear leg frame; and a right arm support pivotally coupled to the front leg frame and the rear leg frame; a left front joint pivotally coupling the front leg frame to a left portion of the seat frame; a right front joint pivotally coupling the front leg frame to a right portion of the seat frame; a left back joint pivotally coupling the rear leg frame to a left portion of the back support frame; a right back joint pivotally coupling the rear leg frame to a right portion of the back support frame; an accessory connector coupled to the front leg frame and configured to detachably connect to an interchangeable accessory, wherein the accessory connector is coupled to the front leg frame via the left front joint or the right front joint; a handle positioned along a back portion of the back support frame; a first backpack strap connectable to the handle and the left portion of the back support frame; and a second backpack strap connected to the handle and the right portion of the back support frame.
2. The folding chair of claim 1, wherein strips of back support material extend from an upper portion of the back support frame to a lower portion of the back support frame.
3. The folding chair of claim 1, wherein the interchangeable accessory includes a projection and the accessory connector includes a slot configured to receive the projection.
4. The folding chair of claim 1, wherein each of the left front joint and the right front joint includes an accessory connector configured to connect to the interchangeable accessory.
5. The folding chair of claim 1, wherein the interchangeable accessory is a cupholder that includes one or more cutouts to accommodate cups of different sizes and shapes.
6. The folding chair of claim 5, wherein at least one of the one or more cutouts is configured to receive a cup handle.
7. The folding chair of claim 5, wherein the first backpack strap is configured to be connected to the left portion of the back support frame via a rear coupling connector on the back portion of the back support frame.
8. The folding chair of claim 7, wherein the second backpack strap is configured to be connected to the right portion of the back support frame via a rear coupling connector on the back portion of the back support frame.
9. The folding chair of claim 1, wherein the handle is connected to the back portion of the back support frame via fasteners.

10. A folding chair, comprising: a chair frame comprising: a front leg frame; a rear leg frame; a back support frame; a seat frame pivotally coupled to the front leg frame and the back support frame; a left arm support pivotally coupled to the front leg frame and the rear leg frame; and a right arm support pivotally coupled to the front leg frame and the rear leg frame; a left front joint pivotally coupling the front leg frame to a left portion of the seat frame; a right front joint pivotally coupling the front leg frame to a right portion of the seat frame; a left back joint pivotally coupling the rear leg frame to a left portion of the back support frame; a right back joint pivotally coupling the rear leg frame to a right portion of the back support frame; a handle positioned along a back portion of the back support frame; a first backpack strap connectable to the handle and the left portion of the back support frame; and a second backpack strap connected to the handle and the right portion of the back support frame, wherein each of the left front joint and the right front joint includes an accessory connector configured to detachably connect to an interchangeable accessory.
11. The folding chair of claim 10, wherein the interchangeable accessory includes a projection and the accessory connector includes a slot configured to receive the projection.
12. The folding chair of claim 10, wherein the interchangeable accessory is a cupholder that includes one or more cutouts to accommodate cups of different sizes and shapes.
13. The folding chair of claim 12, wherein at least one of the one or more cutouts is configured to receive a cup handle.
14. The folding chair of claim 12, wherein the first backpack strap is configured to be connected to the left portion of the back support frame via a rear coupling connector on the back portion of the back support frame.
15. The folding chair of claim 14, wherein the second backpack strap is configured to be connected to the right portion of the back support frame via a rear coupling connector on the back portion of the back support frame.
16. The folding chair of claim 10, wherein the handle is connected to the back portion of the back support frame via fasteners.
17. The folding chair of claim 10, wherein strips of back support material extend from an upper portion of the back support frame to a lower portion of the back support frame.
-