

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12409298
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Halstead; Greg et al.

Catheters and methods of manufacture and use

Abstract

Catheters that includes inner and outer elongate shafts, each of which is secured relative to an end of an inflatable member. Balloon bonding locations may be disposed radially inward relative to an outer dimension of the outer elongate shaft.

Inventors:	Halstead; Greg (Sunnyvale, CA), Allen; Michael P. (Los Altos, CA)
Applicant:	EMBOLX, INC. (Sunnyvale, CA)
Family ID:	74660370
Assignee:	Embolx, Inc. (Sunnyvale, CA)
Appl. No.:	17/636562
Filed (or PCT Filed):	August 20, 2020
PCT No.:	PCT/US2020/047178
PCT Pub. No.:	WO2021/035042
PCT Pub. Date:	February 25, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20220296864 A1	Sep. 22, 2022

Related U.S. Application Data

us-provisional-application US 63030802 20200527

Publication Classification

Int. Cl.: A61M25/00 (20060101); **A61M5/00** (20060101); **A61M25/10** (20130101)

U.S. Cl.:

CPC **A61M25/0051** (20130101); **A61M5/007** (20130101); **A61M25/005** (20130101);
A61M25/0052 (20130101); **A61M25/0053** (20130101); **A61M25/0054** (20130101);
A61M25/0097 (20130101); **A61M25/1006** (20130101); **A61M25/1025** (20130101);
A61M2025/0004 (20130101); A61M2025/0042 (20130101); A61M25/0043 (20130101);
A61M2025/0098 (20130101); A61M2025/105 (20130101); A61M2025/1061 (20130101)

Field of Classification Search

CPC: A61M (25/0014); A61M (25/005); A61M (25/0051); A61M (25/0052); A61M (25/0053);
A61M (25/0054); A61M (25/0097); A61M (2025/0098)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3734100	12/1972	Walker et al.	N/A	N/A
4198981	12/1979	Sinnreich	N/A	N/A
4545390	12/1984	Leary	N/A	N/A
4581017	12/1985	Sahota	N/A	N/A
4737153	12/1987	Shimamura et al.	N/A	N/A
4748982	12/1987	Horzewski et al.	N/A	N/A
4892519	12/1989	Songer et al.	N/A	N/A
4896669	12/1989	Bhate et al.	N/A	N/A
4898591	12/1989	Jang et al.	N/A	N/A
4909252	12/1989	Goldberger	N/A	N/A
4944745	12/1989	Sogard et al.	N/A	N/A
4976690	12/1989	Solar et al.	N/A	N/A
4990143	12/1990	Sheridan	N/A	N/A
5000734	12/1990	Boussignac et al.	N/A	N/A
5040548	12/1990	Yock	N/A	N/A
5045072	12/1990	Castillo et al.	N/A	N/A
5047045	12/1990	Arney et al.	N/A	N/A
5078685	12/1991	Colliver	N/A	N/A
5090958	12/1991	Sahota	N/A	N/A
5100386	12/1991	Inoue	N/A	N/A
5129887	12/1991	Euteneuer	604/533	A61M 25/0097
5137513	12/1991	Mcinnnes et al.	N/A	N/A
5156594	12/1991	Keith et al.	N/A	N/A
5217434	12/1992	Arney	N/A	N/A
5234416	12/1992	Macaulay et al.	N/A	N/A
5254107	12/1992	Soltesz	N/A	N/A
5279562	12/1993	Sirhan et al.	N/A	N/A
5318532	12/1993	Frassica	N/A	N/A
5334154	12/1993	Samson et al.	N/A	N/A

5342386	12/1993	Trotta	N/A	N/A
5356388	12/1993	Sepetka et al.	N/A	N/A
5358493	12/1993	Schweich, Jr.	604/525	A61M 25/0054
5370655	12/1993	Burns	N/A	N/A
5380301	12/1994	Prichard	604/533	B29C 45/14467
5423754	12/1994	Cornelius et al.	N/A	N/A
5423829	12/1994	Pham et al.	N/A	N/A
5429605	12/1994	Richling	N/A	N/A
5454795	12/1994	Samson	N/A	N/A
5470314	12/1994	Walinsky	N/A	N/A
5484409	12/1995	Atkinson et al.	N/A	N/A
5498251	12/1995	Dalton	N/A	N/A
5501667	12/1995	Verduin	N/A	N/A
5509910	12/1995	Lunn	N/A	N/A
5538510	12/1995	Fontirroche et al.	N/A	N/A
5556383	12/1995	Wang et al.	N/A	N/A
5582619	12/1995	Ken	N/A	N/A
5584821	12/1995	Hobbs et al.	N/A	N/A
5588442	12/1995	Scovil et al.	N/A	N/A
5599326	12/1996	Carter	N/A	N/A
5624449	12/1996	Pham et al.	N/A	N/A
5637086	12/1996	Ferguson et al.	N/A	N/A
5643254	12/1996	Scheldrup et al.	N/A	N/A
5647198	12/1996	Mihailovic	N/A	N/A
5649949	12/1996	Wallace et al.	N/A	N/A
5658263	12/1996	Dang et al.	N/A	N/A
5669905	12/1996	Scheldrup et al.	N/A	N/A
5674198	12/1996	Leone	N/A	N/A
5690666	12/1996	Berenstein et al.	N/A	N/A
5690667	12/1996	Gia	N/A	N/A
5718711	12/1997	Berenstein et al.	N/A	N/A
5722424	12/1997	Engelson	N/A	N/A
5749837	12/1997	Palermo et al.	N/A	N/A
5766192	12/1997	Zacca	N/A	N/A
5769830	12/1997	Parker	N/A	N/A
5775327	12/1997	Randolph et al.	N/A	N/A
5792300	12/1997	Inderbitzen et al.	N/A	N/A
5797874	12/1997	Spears	N/A	N/A
5800454	12/1997	Jacobsen et al.	N/A	N/A
5807355	12/1997	Ramzipoor et al.	N/A	N/A
5820592	12/1997	Hammerslag	N/A	N/A
5830182	12/1997	Wang et al.	N/A	N/A
5833705	12/1997	Ken et al.	N/A	N/A
5843032	12/1997	Kastenhofer	N/A	N/A
5843050	12/1997	Jones et al.	N/A	N/A
5851203	12/1997	Van Muiden	N/A	N/A
5853418	12/1997	Ken et al.	N/A	N/A
5868704	12/1998	Campbell et al.	N/A	N/A

5879324	12/1998	von Hoffmann	N/A	N/A
5891110	12/1998	Larson	604/523	A61M 25/104
5891128	12/1998	Gia et al.	N/A	N/A
5911717	12/1998	Jacobsen et al.	N/A	N/A
5938653	12/1998	Pepin	N/A	N/A
5951539	12/1998	Nita et al.	N/A	N/A
5951929	12/1998	Wilson	N/A	N/A
5984878	12/1998	Engelson	N/A	N/A
5984929	12/1998	Bashiri et al.	N/A	N/A
6013084	12/1999	Ken et al.	N/A	N/A
6014919	12/1999	Jacobsen et al.	N/A	N/A
6019757	12/1999	Scheldrup	N/A	N/A
6022340	12/1999	Sepetka et al.	N/A	N/A
6036670	12/1999	Wijeratne et al.	N/A	N/A
6036682	12/1999	Lange et al.	N/A	N/A
6056719	12/1999	Mickley	N/A	N/A
6066157	12/1999	Barbere	N/A	N/A
6066667	12/1999	Ashbrook	N/A	N/A
6068610	12/1999	Ellis et al.	N/A	N/A
6071286	12/1999	Mawad	N/A	N/A
6090099	12/1999	Samson et al.	N/A	N/A
6103037	12/1999	Wilson	N/A	N/A
6123714	12/1999	Gia et al.	N/A	N/A
6156061	12/1999	Wallace et al.	N/A	N/A
6165163	12/1999	Chien et al.	N/A	N/A
6187027	12/2000	Mariant et al.	N/A	N/A
6190358	12/2000	Fitzmaurice et al.	N/A	N/A
6190393	12/2000	Bevier et al.	N/A	N/A
6203547	12/2000	Nguyen et al.	N/A	N/A
6258080	12/2000	Samson	N/A	N/A
6270495	12/2000	Palermo	N/A	N/A
6280457	12/2000	Wallace et al.	N/A	N/A
6287301	12/2000	Thompson et al.	N/A	N/A
6319228	12/2000	Kastenhofer	N/A	N/A
6344041	12/2001	Kupiecki et al.	N/A	N/A
6397850	12/2001	Scheldrup et al.	N/A	N/A
6423085	12/2001	Murayama et al.	N/A	N/A
6428489	12/2001	Jacobsen et al.	N/A	N/A
6440088	12/2001	Jacobsen et al.	N/A	N/A
6450987	12/2001	Kramer	N/A	N/A
6468266	12/2001	Bashiri et al.	N/A	N/A
6471673	12/2001	Kastenhofer	N/A	N/A
6508804	12/2002	Sarge et al.	N/A	N/A
6553880	12/2002	Jacobsen et al.	N/A	N/A
6575959	12/2002	Sarge et al.	N/A	N/A
6579246	12/2002	Jacobsen et al.	N/A	N/A
6635069	12/2002	Teoh et al.	N/A	N/A
6638245	12/2002	Miller et al.	N/A	N/A
6648874	12/2002	Parisi et al.	N/A	N/A
6652508	12/2002	Griffin et al.	N/A	N/A

6656550	12/2002	Zamore	N/A	N/A
6702782	12/2003	Miller et al.	N/A	N/A
6702802	12/2003	Hancock et al.	N/A	N/A
6706025	12/2003	Engelson et al.	N/A	N/A
6733459	12/2003	Atsumi	N/A	N/A
6766720	12/2003	Jacobsen et al.	N/A	N/A
6780181	12/2003	Kroll et al.	N/A	N/A
6835189	12/2003	Musbach et al.	N/A	N/A
6849062	12/2004	Kantor	N/A	N/A
6860893	12/2004	Wallace et al.	N/A	N/A
6860899	12/2004	Rivelli	N/A	N/A
6878151	12/2004	Carrison et al.	N/A	N/A
6921410	12/2004	Porter	N/A	N/A
6936055	12/2004	Ken et al.	N/A	N/A
6997937	12/2005	Jacobsen et al.	N/A	N/A
7004962	12/2005	Stinson	N/A	N/A
7037330	12/2005	Rivelli et al.	N/A	N/A
7060083	12/2005	Gerberding	N/A	N/A
7070607	12/2005	Murayama et al.	N/A	N/A
7144407	12/2005	Lasersohn	N/A	N/A
7153323	12/2005	Teoh et al.	N/A	N/A
7166122	12/2006	Aganon et al.	N/A	N/A
7294137	12/2006	Rivelli et al.	N/A	N/A
7332689	12/2007	Mertens et al.	N/A	N/A
7412285	12/2007	Schroeppel et al.	N/A	N/A
7468070	12/2007	Henry et al.	N/A	N/A
7481800	12/2008	Jacques	N/A	N/A
7621904	12/2008	McFerran et al.	N/A	N/A
7645259	12/2009	Goldman	N/A	N/A
7654979	12/2009	Simpson	N/A	N/A
7742811	12/2009	Schroeppel et al.	N/A	N/A
7780626	12/2009	Wu et al.	N/A	N/A
7892201	12/2010	Laguna et al.	N/A	N/A
7942847	12/2010	Stupecky et al.	N/A	N/A
7998165	12/2010	Huffmaster	N/A	N/A
8066667	12/2010	Hayman et al.	N/A	N/A
8092508	12/2011	Leynov et al.	N/A	N/A
8202292	12/2011	Kellett	N/A	N/A
8206373	12/2011	Zhou	N/A	N/A
8348890	12/2012	Gerrans et al.	N/A	N/A
8961550	12/2014	Lenker et al.	N/A	N/A
9005163	12/2014	Bonnette et al.	N/A	N/A
9174020	12/2014	Allen et al.	N/A	N/A
9205226	12/2014	Allen et al.	N/A	N/A
9427550	12/2015	Dakin et al.	N/A	N/A
9550046	12/2016	Allen	N/A	N/A
9555165	12/2016	Phan	N/A	N/A
9844383	12/2016	Allen	N/A	N/A
10086174	12/2017	Crall et al.	N/A	N/A
10130762	12/2017	Allen	N/A	N/A

10350382	12/2018	Halstead et al.	N/A	N/A
10667822	12/2019	Allen	N/A	N/A
10780252	12/2019	Allen et al.	N/A	N/A
10786660	12/2019	Allen et al.	N/A	N/A
11123482	12/2020	Allen	N/A	N/A
2001/0008451	12/2000	Ishii et al.	N/A	N/A
2001/0041862	12/2000	Glickman	N/A	N/A
2002/0004666	12/2001	Schwager et al.	N/A	N/A
2002/0032457	12/2001	Sirhan et al.	N/A	N/A
2002/0193820	12/2001	Wakuda et al.	N/A	N/A
2003/0008726	12/2002	Sano	N/A	N/A
2003/0050600	12/2002	Ressemann et al.	N/A	N/A
2003/0114878	12/2002	Diederich et al.	N/A	N/A
2003/0125713	12/2002	McGlinch	604/533	A61F 2/0095
2003/0144657	12/2002	Bowe et al.	N/A	N/A
2003/0180488	12/2002	Lim et al.	N/A	N/A
2003/0191435	12/2002	Shkolnik	N/A	N/A
2003/0199914	12/2002	Diaz	N/A	N/A
2003/0220628	12/2002	Kilsch et al.	N/A	N/A
2004/0015151	12/2003	Chambers	N/A	N/A
2004/0073158	12/2003	Shah et al.	N/A	N/A
2004/0167415	12/2003	Gelfand et al.	N/A	N/A
2005/0131453	12/2004	Parodi	N/A	N/A
2005/0267407	12/2004	Goldman	N/A	N/A
2006/0106413	12/2005	Bence et al.	N/A	N/A
2006/0149186	12/2005	Wantink et al.	N/A	N/A
2006/0276886	12/2005	George et al.	N/A	N/A
2007/0055301	12/2006	Campbell et al.	N/A	N/A
2007/0088380	12/2006	Hirszowicz et al.	N/A	N/A
2007/0137651	12/2006	Glassenberg et al.	N/A	N/A
2007/0149927	12/2006	Itou et al.	N/A	N/A
2007/0197956	12/2006	Le	604/890.1	A61M 25/008
2008/0033372	12/2007	Briscoe et al.	N/A	N/A
2008/0045908	12/2007	Gould et al.	N/A	N/A
2008/0208118	12/2007	Goldman	N/A	N/A
2008/0262470	12/2007	Lee et al.	N/A	N/A
2009/0131831	12/2008	Wright et al.	N/A	N/A
2009/0156999	12/2008	Adams et al.	N/A	N/A
2009/0177183	12/2008	Pinkernell et al.	N/A	N/A
2010/0030200	12/2009	Strauss et al.	N/A	N/A
2010/0113939	12/2009	Mashimo et al.	N/A	N/A
2010/0222637	12/2009	Kassab	N/A	N/A
2010/0249491	12/2009	Farnan et al.	N/A	N/A
2011/0098671	12/2010	Duffy et al.	N/A	N/A
2012/0203173	12/2011	Davies et al.	N/A	N/A
2012/0253447	12/2011	Hayasaka et al.	N/A	N/A
2013/0116651	12/2012	Takagi	604/525	A61M 25/0054
2013/0131610	12/2012	Dewaele et al.	N/A	N/A

2013/0261545	12/2012	Osypka	N/A	N/A
2014/0163421	12/2013	Van Hoven	N/A	N/A
2014/0371718	12/2013	Alvarez et al.	N/A	N/A
2015/0112255	12/2014	Jensen et al.	N/A	N/A
2015/0351729	12/2014	Chin et al.	N/A	N/A
2016/0008585	12/2015	Tano	N/A	N/A
2016/0067444	12/2015	Allen et al.	N/A	N/A
2016/0096002	12/2015	Di Caprio et al.	N/A	N/A
2016/0101261	12/2015	Kugler et al.	N/A	N/A
2016/0199067	12/2015	Smith et al.	N/A	N/A
2016/0213893	12/2015	Franklin	N/A	N/A
2017/0049495	12/2016	Yu et al.	N/A	N/A
2017/0095646	12/2016	Norman et al.	N/A	N/A
2017/0113025	12/2016	Chanduszko et al.	N/A	N/A
2017/0252542	12/2016	Iwano et al.	N/A	N/A
2017/0303890	12/2016	Yamashita	N/A	N/A
2018/0015248	12/2017	Logan et al.	N/A	N/A
2018/0056036	12/2017	Wada et al.	N/A	N/A
2018/0071484	12/2017	Raab	N/A	A61M 25/0097
2020/0023170	12/2019	Halstead et al.	N/A	N/A
2020/0030577	12/2019	Halstead et al.	N/A	N/A
2020/0297351	12/2019	Allen	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
101400400	12/2008	CN	N/A
102159277	12/2010	CN	N/A
102802698	12/2011	CN	N/A
102805893	12/2011	CN	N/A
103298517	12/2012	CN	N/A
103764217	12/2013	CN	N/A
103987421	12/2013	CN	N/A
105228684	12/2015	CN	N/A
105246537	12/2015	CN	N/A
105854151	12/2015	CN	N/A
106422033	12/2016	CN	N/A
102009025347	12/2009	DE	N/A
202011003097	12/2010	DE	N/A
0520692	12/1991	EP	N/A
1121955	12/2000	EP	N/A
1131126	12/2003	EP	N/A
2389968	12/2010	EP	N/A
3132823	12/2016	EP	N/A
2512696	12/2013	GB	N/A
H03-207376	12/1990	JP	N/A
H05-015604	12/1992	JP	N/A
H06-277296	12/1993	JP	N/A

H07-213617	12/1994	JP	N/A
H10244006	12/1997	JP	N/A
2003500121	12/2002	JP	N/A
2005511108	12/2004	JP	N/A
2006511271	12/2005	JP	N/A
2007319468	12/2006	JP	N/A
2008522716	12/2007	JP	N/A
2008544801	12/2007	JP	N/A
2011087971	12/2010	JP	N/A
2011152181	12/2010	JP	N/A
201290779	12/2011	JP	N/A
2015523884	12/2014	JP	N/A
2016517778	12/2015	JP	N/A
20100006710	12/2009	KR	N/A
WO89/08471	12/1988	WO	N/A
WO99/48548	12/1998	WO	N/A
WO00/32264	12/1999	WO	N/A
WO2004/107965	12/2003	WO	N/A
WO2007/121005	12/2006	WO	N/A
WO2012/009486	12/2011	WO	N/A
WO2012/099979	12/2011	WO	N/A
WO2014/008489	12/2013	WO	N/A
WO2017/142941	12/2016	WO	N/A
WO2019/236951	12/2018	WO	N/A
WO2020/023889	12/2019	WO	N/A
WO2021/035042	12/2020	WO	N/A

OTHER PUBLICATIONS

Halstead et al.; U.S. Appl. No. 17/938,559 entitled “Balloon catheters and methods of manufacture and use,” filed Oct. 6, 2022. cited by applicant

Roewer et al.; U.S. Appl. No. 18/043,873 entitled “Catheters adapted for agent delivery,” filed Mar. 2, 2023. cited by applicant

Angiodynamics; Soft-vu angiographic catheters; 2 pages; retrieved from the internet (<http://www.angiodynamics.com/products/soft-vu>) on Aug. 17, 2018. cited by applicant

BMI Espicom Pharmaceutical and Medical Device News; Business Monitor Online: Vascular solutions expands complex intervention offerings with turnpike LP catheter; newsletter; 2pages; retrieved from the internet (<https://dialog.proquest.com/professional/docview/1753127273?accountid=157282>) on Apr. 18, 2018 (Abstract Only). cited by applicant

Cliffon et al.; Technique for visualization and perfusion of bronchial arteries: suggested clinical and diagnostic applications; Cancer; 16; pp. 444-452; Apr. 1963. cited by applicant

Cook Medical; Flexor technology; 16 pages; retrieved from the internet (https://cookmedical.com/data/resources/PI-BM-KCF-EN-201302_WEB.pdf) on May 5, 2019. cited by applicant

Matsuda et al.; Electrospinning fabrication of high-trackable catheter tip with gradually graded or gradient flexibility; J. Biomed. Mater. Res. B Appl. Biomater.; 1(35); pp. 35-41 doi: 10.1002/jbm.b.31061; (Abstract Only); Oct. 2008. cited by applicant

Nordson Medical; Extruded tubing technical information; 7 pages; retrieved from the internet (<https://www.nordsonmedical.com/Components-and-Technologies/Medical-Tubing/Extruded-Tubing/Technical-Information/>) on Aug. 17, 2018. cited by applicant

Rousselot et al.; Selective concentration of anticancer drugs in the liver: Hepatic-artery infusion

and induced hepatic outflow block; JAMA; 191(9); pp. 707-710; Mar. 1965. cited by applicant Vante Plasticweld Systems; Bonds and welds; 13 pages; retrieved from the internet (<https://cathetertipping.com/home/our-products/bonding/>) on Aug. 17, 2018. cited by applicant Worldwide Videotex; Angiodynamics PCTA balloon catheter gets FDA market clearance; Biotech Equipment Update 5.9: N/A. Worldwide Videotex; Sep. 1, 1997; 2 pages; retrieved from the internet (<https://dialog.proquest.com/professional/docview/680080033?accountid=157282>) on Apr. 18, 2018 (Abstract Only). cited by applicant Zeus; FluoroPEELZ peelable heat shrink; 9 pages; retrieved from the internet (<https://www.zeusinc.com/products/heat-shrinkable-tubing/fluoropeelz-peelable-heat-shrink>) on Aug. 17, 2018. cited by applicant

Primary Examiner: Bosworth; Kami A

Attorney, Agent or Firm: Shay Glenn LLP

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) This application is a 371 of PCT/US2020/047178, filed Aug. 20, 2020, which claims the benefit of U.S. Prov. App. No. 63/030,802 filed May 27, 2020, the disclosures of which are incorporated by reference herein for all purposes.

INCORPORATION BY REFERENCE

(1) All publications and patent applications mentioned in this specification are herein incorporated by reference to the same extent as if each individual publication or patent application was specifically and individually indicated to be incorporated by reference.

BACKGROUND

(2) Catheters are commonly used in medicine for delivery of fluids, therapeutics and implants as well as in sampling tissues and bodily fluids. Catheters can be constructed with balloons or other tools to dilate tissue, block fluid flow or isolate segments of the anatomy. A relatively common use for a catheter is the delivery of drugs to a target tissue using blood vessels as a means of access. When a balloon is used, the vascular compartment distal to the balloon is isolated from the vascular compartment proximal to the balloon and perfusion of diagnostic, therapeutic or embolic agents is localized and concentrated.

(3) One common use for a microcatheter is the delivery of embolic agents and anticancer drugs to a tumor.

(4) According to the NIH, 30,640 people were diagnosed with primary liver cancer (hepatocellular carcinoma, HCC) and 142,820 people were diagnosed with colorectal cancer in the US in 2013. Seventy five percent of these will metastasize to the liver. Liver resection and transplant are the only curative means; however, only small numbers of patients are eligible. Systemic Chemotherapy for primary and metastatic tumors in the liver is ineffective, having a response rate of about 20% and a survival benefit of 10.7 months vs. 7.9 months over symptomatic care.

(5) Trans-Arterial Embolization therapy is the transvascular access for injection of drug and/or embolic agents directly into, or in the vicinity of, the tumor vasculature using a microcatheter. Embolization therapy causes a shutdown of blood flow and, when drug or radioactivity is present, simultaneous release of high concentrations of drug or radioactivity. The technique is also noted for its very low level of toxicity. Chemoembolization was established as a standard of care for intermediate stage hepatocellular carcinoma in 2006. Numerous studies have demonstrated transarterial embolization to be effective on a number of primary cancers and to have better

performance than chemotherapy for both HCC and metastatic colorectal cancers in the liver.

(6) Various prior art references provide guidance on aspects of medical catheter construction. For example, U.S. patent application Ser. No. 10/128,977 describes a coaxial catheter whereby a balloon is bonded to an elongated outer tube to prevent the balloon from telescopingly buckling when the balloon is being pushed across a narrow passage. U.S. Pat. No. 6,066,157 describes a coaxial coronary angioplasty catheter whereby an anchor joint is configured to allow distal movement of the inner tube and to prevent proximal movement. U.S. Pat. No. 5,647,198 describes a catheter with a pair of spaced apart balloons that define an intra-balloon space. A lumen passes through the catheter and exits within the intra-balloon space allowing injection of drugs, emulsions, fluids and fluid/solid mixtures. A perfusion lumen or bypass extends from a location proximal to the proximal balloon and to the distal tip to allow shunting of blood past the inflated balloons. U.S. Pat. No. 5,674,198 describes a two balloon catheter that is designed for treating a solid tumor. The balloons are positioned to isolate the blood flow into the tumor and allow injection of a vaso-occlusive collagen material to block the tumor blood supply. Clifton et al. (1963) Cancer 16:444-452 describes a two balloon catheter for the treatment of lung carcinoma. The four lumen catheter includes a lumen for independent injection in the space between the balloons. Rousselot et al. (1965) JAMA 191:707-710 describes a balloon catheter device for delivering anticancer drugs into the liver. See also U.S. Pat. Nos. 6,780,181; 6,835,189; 7,144,407; 7,412,285; 7,481,800; 7,645,259; 7,742,811; U.S. App. No. 2001/008451; U.S. App. No. 2001/0041862; U.S. App. No. 2003/008726; U.S. App. No. 2003/0114878; U.S. App. No. 2005/0267407; U.S. App. No. 2007/0137651; U.S. App. No. 2008/0208118; U.S. App. No. 2009/0182227 and U.S. App. No. 2010/0114021.

(7) An important consideration for transvascular catheters design, especially for use in the peripheral blood circulation, is the desire for the outer diameter (“OD”) of the catheter to be as small as possible so that the catheter can access and be advanced into and through small vessels. Another important consideration is that it is generally desirable for a central lumen (e.g., fluid delivery lumen), to be as large as possible to facilitate the delivery of one or more of a therapeutic agent or device therethrough. The wall thickness of one or more catheter shafts of the device influences the size of a central lumen as well as the OD of the device, and thus reducing wall thickness of the shaft(s) can increase in the size of a central lumen as well as reduce the OD of the device.

(8) Some transvascular catheters adapted for use in the peripheral blood circulation include one or more expandable balloons. Because minimizing OD of the device is an important consideration, it is also important that the incorporation of the balloon, including the manner in which it is secured to the device, does not result in an undesirable increase in OD. For example, some previous attempts have bonded balloons to an outer surface of the catheter, which necessarily increases the OD of the catheter (even when unexpanded).

(9) There is thus a continued developmental need for microcatheters with increased inner lumen size and minimized OD of the device. While the device does not necessarily incorporate an expandable balloon, the size constraints are particularly important when incorporating an expandable balloon.

(10) Additionally, medical catheters may be advanced through torturous vasculature, requiring a flexible distal section that can easily follow the vessel and a stiff proximal section that can support longitudinal advancement of the catheter as it twists and turns through the blood vessels. It is also desirable, in certain applications, that the catheter can transmit torque throughout its length, from the proximal end to a distal region. This is particularly true when a shaped catheter tip is used. Shaped catheter tips may be used to direct a guidewire and/or a catheter around acute angles and into branch vessels. A 90-degree shape is among the favored tip configurations. In use, the catheter tip is rotationally oriented so that the angled tip is pointed toward the desired direction of travel. This requires that proximal catheter rotation translates to distal tip rotation.

(11) In general, flexible catheters may track well through turns in the vasculature but cannot transmit torque well, and stiff catheters can transmit torque but cannot track well through torturous vasculature. Accordingly, there is an unmet medical need for catheters, particularly microcatheters, that are both trackable and torqueable, and avoid kinking at a catheter hub junction.

SUMMARY OF THE DISCLOSURE

(12) One aspect of the disclosure is a balloon catheter, comprising: an outer elongate shaft having a wall thickness that is less than 0.0035 inches; an inner elongate shaft with a delivery lumen therein, the inner elongate shaft within the outer elongate shaft having a section that extends distally beyond the outer elongate shaft, the inner elongate shaft having a wall thickness that is less than 0.0035 inches; an adapter secured to a distal region of the outer elongate shaft, the adapter having a distal region extending distally beyond the outer elongate shaft, the distal region of the adapter having an outer surface disposed radially inward relative to an outer surface of a distal end of the outer elongate shaft; an inflatable balloon with a proximal end; a proximal collar radially outside of the proximal end of the balloon, the proximal collar compressing the proximal end of the balloon between the proximal collar and the outer surface of the distal region of the adapter, wherein an inner surface of the proximal end of the balloon is disposed radially inward relative to the outer surface of the distal end of the outer elongate shaft; the inflatable balloon having a distal end stabilized relative to the section of the inner elongate shaft that extends distally beyond the outer elongate shaft, the distal end of the inflatable balloon having an inner surface that is disposed radially inward relative to the outer surface of the distal end of the outer elongate shaft, the outer elongate shaft and the inner elongate shaft forming an inflation lumen that is in communication with the inflatable balloon to allow fluid to be advanced through the inflation lumen and into an internal volume of the balloon to inflate the balloon, wherein the inflatable member is disposed substantially at or below the outer diameter of the outer elongate shaft when in an unexpanded configuration.

(13) The balloon catheter may further include a distal collar radially outside of a distal end of the balloon, the distal collar compressing the distal end of the balloon between the distal collar and the section of the inner elongate shaft that extends distally beyond the outer elongate shaft. The distal collar may be a heat shrink material that compresses the distal end of the balloon. The distal collar may have a thickness from 0.003 mm to 0.05 mm, optionally from 0.006 mm to 0.01 mm. The distal collar may have a length from 0.1 mm to 10 mm, optionally from 0.5 mm to 6 mm. The distal collar may include a polymeric material, and optionally selected from the group consisting of a silicone, latex, polyester, nylon, Pebax, polyethylene, and polyurethane.

(14) The adapter may be secured to an outer surface of the distal region of the outer elongate shaft, and the adaptor may comprise a step from a first region to a second region, the first region extending radially outward further than the second region.

(15) The adapter may be secured to an inner surface of the distal region of the outer elongate shaft. The adapter may include a step from a first region to a second region, the first region extending radially outward further than the second region.

(16) The adapter may have a thickness from 0.0016 mm to 0.025 mm, optionally 0.003 mm to 0.015 mm.

(17) The adapter may have a thickness that is no more than 15% of a wall thickness of the distal end of the outer elongate shaft.

(18) The adapter distal region may have a wall thickness less than 0.01 mm.

(19) The adapter may have a length from 2 mm to 25 mm.

(20) The adapter may include a polymeric material, optionally selected from the group consisting of polyester, nylon, Pebax, polyethylene, and polyurethane.

(21) The proximal collar may include a heat shrink material that compresses the proximal end of the balloon.

(22) The proximal collar may have a thickness from 0.003 mm to 0.05 mm, optionally from 0.006

mm to 0.01 mm.

(23) The proximal collar may have a length from 1 mm to 10 mm, optionally from 1 mm to 6 mm.

(24) The proximal collar may comprise a polymeric material, and optionally selected from the group consisting of a silicone, latex, polyester, nylon, Pebax, polyethylene, and polyurethane.

(25) The balloon may be elastic. The balloon may comprise a silicone material. The balloon may consist essentially of a silicone material.

(26) The balloon catheter may further comprise an adhesive disposed radially between the proximal end of the balloon and the outer surface of the distal region of the adaptor.

(27) The balloon catheter may further comprise an adhesive disposed radially between the distal end of the balloon and the section of the inner elongate shaft that extends distally beyond the outer elongate shaft.

(28) The balloon, in an unexpanded configuration, may be disposed at or below the outer diameter of the outer elongate shaft.

(29) The inner surface of the proximal end of the balloon may be at least 0.001 inches below an outer diameter of the outer elongate shaft.

(30) The inner surface of the distal end of the balloon may be at least 0.001 inches below an outer diameter of the outer elongate shaft.

(31) One aspect of the disclosure is a balloon catheter system, comprising: an inner catheter having a lumen extending axially therethrough; an outer catheter outside of the inner catheter; wherein the inner catheter and outer catheter are secured relative to one another at one more discrete connection locations, and the outer catheter including a proximal outer section and a distal outer section, the proximal outer section and the distal outer section meeting at a junction, the distal outer section being more flexible than the proximal outer section; an inflatable member having a distal end that is secured to a section of the inner catheter extending distally beyond the outer catheter, the inflatable member also having a proximal end that is secured relative to the outer catheter; and wherein the outer catheter and the inner catheter form an inflation lumen therebetween in fluid communication with an interior of the inflatable member to allow an inflation fluid to be advanced through the inflation lumen to inflate the inflatable member.

(32) The one or more discrete connection locations can include a first discrete connection location at which the inner catheter is connected to the proximal outer section, and a second discrete connection location at which the inner catheter is connected to the distal outer section. The inner catheter may be connected to the outer catheter at the first and second discrete connection locations with an adhesive.

(33) The catheter system may further comprise a distal tip section extending distally beyond the inflatable member, the distal tip having a preset shape extending laterally outward relative to a longitudinal axis.

(34) The proximal outer section may extend distally from a strain relief section to the distal outer section. The distal outer section may extend from the junction to the adaptor.

(35) The distal outer section may have a length that is at least 20 cm.

(36) The proximal outer section may have a length of about 20 cm.

(37) The inner catheter may include a braided material extending along its length.

(38) The distal outer section may have a length that is at least 20 cm.

(39) The outer catheter may include a braided material extending along its length.

(40) One aspect of the disclosure is a catheter with a proximal region with variable flexibility, comprising: a hub disposed at a proximal region of the catheter, the hub including one or more fluid ports; a catheter with one or more shafts disposed within an internal volume of the hub and extending distally from the hub; a strain relief member disposed within the internal volume of the hub and extending distally relative to the hub, the strain relief member disposed around a proximal region of the catheter, the strain relief member having a variable flexibility along its length, the strain relief member having less flexibility in a region that is disposed within the internal volume of

the hub than at a distal end of the strain relief member.

(41) The strain relief member may be more flexible in a distal section that includes a distal end than in a proximal section that includes a proximal end, wherein the proximal end is disposed within the internal volume of the hub.

(42) The strain relief member may comprise a cylindrical body. The cylindrical body may have one or more cuts formed therein.

(43) The catheter may have only a single elongate shaft.

(44) The catheter may further comprise a second strain relief member that is flexible and is disposed around a portion of the first strain relief member, which optionally includes a conical region.

(45) The strain relief member may have a proximal end that is secured to the internal volume of the hub, and wherein a distal end of the strain relief member is not adhered to a catheter shaft.

(46) A flexibility of a distal end of the strain relief member may substantially match a flexibility of the catheter outer shaft.

(47) One aspect of the disclosure is a catheter with a variable flexibility proximal region, comprising: a hub disposed at a proximal region of the catheter, the hub including one or more fluid ports; an elongate member comprising one or more shafts disposed within an internal volume of the hub and extending distally relative to the hub; a strain relief member disposed within the internal volume of the hub and extending distally relative to the hub, the strain relief member disposed about a proximal region of the elongate body and having a length, the elongate body extending further distally than the strain relief member, the strain relief member having a variable flexibility along at least a portion of its length, the variable flexibility of the strain relief member providing greater resistance to kinking at one or more locations of the elongate member than would exist at the one or more locations without the strain relief member.

(48) One aspect of the disclosure is a catheter with a variable flexibility proximal region, comprising: a hub disposed at a proximal region of the catheter, the hub including one or more fluid ports; an elongate member comprising one or more shafts disposed within an internal volume of the hub and extending distally relative to the hub; a first strain relief member disposed about a distal end of the hub and extending distally beyond the hub, the elongate member extending within the first strain relief member and further distally than the first strain relief member; a second strain relief member with a proximal end disposed within the internal volume of the hub, extending distally through the first strain relief member and extending distally beyond the first strain relief member, the second strain relief member disposed around the elongate member, the elongate member extending further distally than the second strain relief member, and the second strain relief member having a variable flexibility along at least a portion of its length, the variable flexibility of the strain relief member providing greater resistance to kinking at one or more locations of the elongate member than would exist at the one or more locations without the strain relief member.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a fragmentary side view showing an exemplary vascular catheter system.

(2) FIG. 2 is a cross-sectional view showing lateral cross-sections of an exemplary inner catheter, proximal outer catheter section, and distal outer catheter section.

(3) FIG. 3A is a side view showing the distal portion of an exemplary catheter system.

(4) FIG. 3B is an exploded side view of the distal portion shown in FIG. 3A.

(5) FIG. 4 is a side cross-sectional view showing a bend in a distal outer catheter section and an inner catheter.

(6) FIGS. 5A, 5B, 5C and 5D are side views showing various exemplary catheters with inner and

outer catheters.

(7) FIG. 6 is an enlarged perspective view showing an inner catheter located inside an outer catheter section in an exemplary embodiment.

(8) FIG. 7A is a chart showing results (in grams) from flexibility testing performed on three sample specimens of an exemplary distal outer catheter section.

(9) FIG. 7B is a chart showing results (in grams) from flexibility testing performed on three sample specimens of an exemplary proximal outer catheter section.

(10) FIG. 8 is a longitudinal cross section of an exemplary embodiment in which balloon bonds are below an outer surface of an outer catheter.

(11) FIG. 9 is an axial cross section of a coaxial catheter.

(12) FIG. 10 is a longitudinal view of a coaxial catheter assembly.

(13) FIG. 11A is a side view of an exemplary outer adapter.

(14) FIG. 11B is a side view of an exemplary inner adapter.

(15) FIG. 11C is a side view of a support sheath.

(16) FIG. 12A is a longitudinal cross section of an exemplary embodiment that includes a nose cone.

(17) FIG. 12B is an enlarged view of the distal end of the catheter shown in FIG. 12A.

(18) FIG. 13A is a longitudinal cross section of an exemplary embodiment including a second outer catheter.

(19) FIG. 13B is an enlarged view of the distal end of the catheter shown in FIG. 13A;

(20) FIG. 14A is a longitudinal cross section of an embodiment of the present disclosure including an inner adapter.

(21) FIG. 14B is an enlarged view of the distal end of the catheter shown in FIG. 14A;

(22) FIG. 15A is a longitudinal cross section of a fourth embodiment of the present disclosure including a two lumen catheter;

(23) FIG. 15B is an enlarged view of the distal end of the catheter shown in FIG. 15A;

(24) FIG. 16A is a side view of a catheter balloon inflated to the extent that it laterally deflects the distal tip of the catheter for steering;

(25) FIG. 16B is the same as FIG. 16A with markings added to show various deflection angles.

(26) FIGS. 17A, 17B, 17C, 17D and 17E are a series of side views schematically showing various exemplary shaped tips.

(27) FIG. 18 is a plan view showing three catheter tips in various stages of manufacture.

(28) FIG. 19 is a plan view schematically showing three more examples of shaped catheter tips.

(29) FIGS. 20A, 20B, 20C and 20D are a series of plan views showing a shaped tip being progressively straightened by advancing a guidewire through it.

(30) FIGS. 21A, 21B and 21C illustrate an exemplary manner in which a proximal outer catheter section can be secured to a distal outer catheter section.

(31) FIG. 22 illustrates a manner in which a balloon may be secured to a balloon catheter.

(32) FIG. 23 illustrates a manner in which a balloon may be secured to a balloon catheter.

(33) FIG. 24 illustrates a manner in which a balloon may be secured to a balloon catheter.

(34) FIG. 25 illustrates a manner in which a balloon may be secured to a balloon catheter.

(35) FIG. 26 illustrates a proximal region of an exemplary catheter with a variable flexibility transition zone.

(36) FIG. 27 illustrates a proximal region of an exemplary catheter with a variable flexibility transition zone.

(37) FIG. 28 illustrates exemplary regions of an exemplary tubular strain relief.

(38) FIG. 29 illustrates a proximal region of an exemplary catheter with a variable flexibility transition zone.

DETAILED DESCRIPTION

(39) This disclosure relates generally to catheters, their methods of use, and manufacture. The

embodiments herein may be particularly suited for microcatheters that are adapted and configured to be advanced through small vessels. The embodiments herein may be particularly suited for microcatheters that are adapted and configured to deliver a therapeutic agent (e.g., fluid or device) through a delivery lumen. It is understood that the embodiments herein are illustrative, and that not every feature described with respect to any particular embodiment is required or limiting. For example, while some of the embodiments herein include one or more expandable balloons, it is understood that a balloon need not necessarily be incorporated into any particular embodiment herein, and that inventive concepts herein need not necessarily include a balloon. Additionally, for example, while some of the catheters herein may include outer and inner shafts, the disclosure herein fully applies to catheters with one a single shaft.

(40) Some embodiments herein describe microcatheters that include an outer catheter (which may be referred to as an outer shaft) and an inner catheter (which may be referred to as an inner shaft), where a portion of the inner catheter extends distally beyond the outer catheter. An expandable balloon may be secured relative to a distal end of the outer catheter and relative to the portion of the inner catheter extending distally beyond the outer catheter, to thereby create fluid-tight couplings that allow fluid to be advanced through a lumen created between the inner and outer catheters and into the balloon to expand the balloon.

(41) Advantageously, the outer and inner catheters are thin-walled, providing the advantage of increasing the size of a delivery lumen within the inner catheter while minimizing the outer diameter (“OD”) of the overall device. In any of the embodiments herein, the outer catheter wall and/or the inner catheter wall may have a thickness from 0.0005” to 0.005”.

(42) Some of the embodiments herein include one or more expandable balloons. Advantageously, the surfaces of the balloon that are secured to the device (e.g., a radially inner surface of a proximal end of the balloon, and a radially inner surface of the distal end of the balloon) are disposed radially inward relative to the OD of the outer catheter. Bonding the balloon in this manner helps maintain the balloon, when unexpanded, at or below the OD of the outer catheter, which helps minimize the OD of the system, the advantages of which are described herein.

(43) While not necessarily required, there may be one or more aspects of the balloon bonding(s) regions of the device that help minimize the OD of the device. For example, without limitation, one or more of any collars (which may be referred to herein as sheaths) or adaptors herein that might be incorporated into the device may have one or more dimensions (e.g., thickness, length) that are sized to help minimize the OD of the device.

(44) Some embodiments herein include a shaft region with a proximal section that is stiffer than a distal section. The stiffer proximal section is adapted to translate torque to the more flexible distal section, while the more flexible distal region allows the device to be tracked through small vessels.

(45) Additionally, while not necessarily required, some embodiments herein include outer and inner catheters that are secured together at discrete connection locations. At the discrete connection locations, movement between an inner surface of the outer catheter and an outer surface of the inner catheter is resisted.

(46) A standard microcatheter for drug delivery is designed to access small vasculature and necessarily has a small outer diameter in the range of 0.5 mm to 2 mm more optimally 0.75 mm to 1 mm. For use in the peripheral vasculature, and in particular for tumor embolization, delivery catheters are typically 50 cm to 210 cm in length. Once the catheter is oriented at a target site within the blood vessel, drug, embolic agents, contrast or other fluids are injected through a lumen that extends longitudinally from proximal to distal ends. It is common that the fluids are viscous and must be injected at high flow rates in the range of 1 ml/second to 10 ml/second. However, flow rate is limited by injection lumen diameter or cross sectional area, length and the ability of the catheter wall to withstand high pressures in the range of 250 psi to 2000 psi, more typically in the range of 500 psi to 1,500 psi. Given that the catheter length is fixed by the requirements of the transvascular procedure, flow rate can be maximized by making the injection lumen and injection

pressure tolerance as high as possible.

(47) When considering a balloon microcatheter, an additional lumen that extends longitudinally from proximal to distal ends of the catheter is added for balloon inflation and deflation. In many embodiments, it is optimal for the balloon to inflate and deflate in as short a time as possible and in the range of 10 seconds to a maximum of 60 seconds. When balloons occlude or dilate blood vessels, it can be necessary for deflation to occur rapidly to avoid complications. Often the balloon is inflated with radiopaque contrast which is a viscous fluid. Therefore, it is desirable that the balloon inflation lumen also be as large as possible.

(48) Since microcatheters have small cross sections, it is a challenge to achieve both rapid drug injection speed, which favors large central injection lumen size, and rapid balloon inflation and deflation times, which favor large balloon inflation lumens.

(49) Further, it would be highly desirable for a mounted balloon not to increase the outer diameter of the catheter since it preferably maintains a small profile and it is optimal to mount the balloon so that in its retracted configuration it does not extend beyond the outer diameter of the catheter.

(50) FIGS. 1 and 2 illustrate an exemplary embodiment of a catheter system. It is understood that the embodiment is illustrative and not limited by all aspects included therein. One or more features may be optional.

(51) FIGS. 1 and 2 illustrate an exemplary coaxial catheter designs that allows torque to be effectively transmitted from a relatively stiff catheter section to a relatively flexible catheter section. The catheter includes an outer catheter having at least two sections, including at least one high torque stiff section and one low torque flexible section. In this embodiment, the outer catheter is mechanically connected to the inner catheter in at least one discrete connection point on the stiffer proximal section and at least one discrete connection point on the more flexible distal section.

(52) As shown in FIG. 1, an exemplary high torque vascular catheter system **100** constructed according to aspects of the present disclosure includes a Y-hub **110**, an inner catheter **112**, a strain relief **114**, a proximal outer catheter section **116**, a distal outer catheter section **118**, an inflatable balloon **120**, a marker band **122**, and a distal tip segment **124**. Y-hub **110** is shown separated from strain relief **114** for clarity in FIG. 1, but normally is connected thereto. Proximal outer catheter section **116** extends from inside Y-hub **110** to a junction point **126** with distal outer catheter section **118**. Distal outer catheter section **118** extends from junction point **126** towards the proximal end of balloon **120**, and the proximal end of balloon **120** is fluidically sealed relative to the distal end of the distal outer catheter section **118**. Proximal outer catheter section **116** may be joined to distal outer catheter section **118** with a butt joint weld at junction point **126** such that the outer catheter is fluid pressure tight. The proximal and distal outer catheter sections may be joined using other joint types, such as with the proximal or distal section overlapping (radially outside of) the other, such as with a step configuration or tapering configuration.

(53) Inner catheter **112** extends from within Y-hub **110**, through proximal outer catheter section **116**, distal outer catheter section **118**, balloon **120**, optional marker band **122**, and into the proximal end of distal tip segment **124**. In this exemplary embodiment, the distal end of balloon **120** is fluidically sealed near the distal end of inner catheter **112**. With this arrangement, a first generally annular volume (not shown) is created between an outer diameter of the inner catheter **112** and an inner diameter of the proximal outer catheter section **116**. This volume may also be referred to herein as fluid pathway, or fluid lumen. Similarly, a second generally annular volume (not shown) remains between the outer diameter of the inner catheter **112** and an inner diameter of the distal outer catheter section **118**. These first and second generally annular volumes are in fluid communication with one another at junction point **126**. In some embodiments, inner catheter **112** may be generally free to move laterally inside proximal outer catheter section **116** and distal outer catheter section **118**. As such, inner catheter **112** may contact these outer catheter sections (as depicted in FIG. 4), and the generally annular volumes may become crescent shaped. What is

meant by “generally annular volume” in this context is the space between inner catheter **112** and outer catheter sections **116** and **118**, regardless of whether it always has an annular shape.

(54) The first annular volume described above is in fluid communication inside Y-hub **110** with its lateral port **128**. The second annular volume is in fluid communication with the interior of balloon **120**. Accordingly, when a balloon inflation pressure is provided at lateral port **128**, balloon **120** inflates as shown in FIG. **1**. When the inflation pressure is removed from lateral port **128**, balloon **120** deflates and returns to a retracted state (not shown) surrounding the distal region of inner catheter **112**.

(55) In some embodiments, catheter system **100** may have a working length A (i.e., outside of Y-hub **110** and strain relief **114**) of about 50 cm to about 210 cm. In some embodiments, the length B of distal outer catheter section **118** is about 20 cm-40 cm, such as about 25 cm-35 cm, such as about 30 cm. In some embodiments, the diameter of balloon **120** is about 2 mm-10 mm, such as 4 mm-8 mm such as about 6 mm, its length is about 5 mm-15 mm, such as about 10 mm, and the length of distal tip segment **124** is about 5 mm-12 mm, such as about 8 mm. A combined distance C of balloon and tip may be about 1 cm-2.7 cm, such as about 2 cm, and a total distance B+C distal to junction point **126** may be about 21 cm-42.7 cm, such as about 32 cm. Length D may be about 70 cm-130 cm, such as about 119 cm (the portion of proximal outer catheter section **116** that extends from Y-hub **110** and strain relief **114**). In some implementations, catheter system **100** is introduced into the target vasculature through a diagnostic catheter (not shown.) In some of these implementations, depending on the application, it may be desirable to have about 30-32 cm of flexible catheter section (e.g., B+C) extending from the diagnostic catheter in order to track through tortuous vasculature. Therefore, with the aforementioned dimensions, junction point **126** and the distal portion of proximal outer catheter section **116** remain inside the diagnostic catheter during a medical procedure. Depending on the vascular pathway that is used to advance the balloon towards the target anatomical location, it may be possible to vary the length D for any particular device, while keeping the length B+C the same. For example without limitations, a femoral artery access location may be used in some procedures, while in some procedures a radial artery access may be used. Length D may vary for each of the different procedures, but the length B+C could be the same.

(56) Referring to FIG. **2**, cross-sections of inner catheter **112**, proximal outer catheter section **116**, and distal outer catheter section **118** are shown. In this exemplary embodiment, each of these three components comprises an inner layer, a middle layer and an outer layer. In some implementations, a guidewire is advanced through the inner lumen of catheter system **100**. In such instances it is therefore desirable that the inner layer of the inner catheter be lubricious. Materials that can be used include, but are not limited to, fluoropolymers PTFE, FEP, PFA, EFEP, and HDPE. It is often the case that viscous contrast materials are injected through the inner lumen of the inner catheter, requiring that it withstand high pressures. Support materials that are commonly used include metals such as stainless steel or nitinol that are braided or coiled.

(57) The materials that can be used for the outer layer of the inner catheter need not be a thermoplastic and are selected to provide strength, dimensional stability and flexibility, including, but not limited to, HDPE, Nylon, Polyimide, Polyester, PEBAX and TECOFLEX.

(58) Transvascular catheters require pushability to advance through torturous vessels and to be twisted or torqued. The proximal outer catheter section is constructed to have pushability and torqueability. Therefore, stiffer materials with higher durometers can be used such as HDPE, Nylon, Polyimide, Epoxy, Polyester, PEBAX, TECOFLEX and fluoropolymers. The distal outer catheter will be advanced into small torturous vessels and must be flexible. In this instance, lower durometers of the materials mentioned above can be used.

(59) Referring to FIGS. **3A** and **3B**, enlarged views showing an exemplary distal portion of catheter system **100** are provided. FIG. **3A** shows an assembled view of the distal portion, and FIG. **3B** shows an exploded view. Inflated balloon **120'** shown in FIGS. **3A** and **3B** has a more rounded

profile than that of balloon **120** shown in FIG. 1. As best seen in FIG. 3A, distal outer catheter section **118** stops just short of the proximal end of balloon **120'**. To seal the proximal end of balloon **120'** against the distal end of distal outer catheter section **118**, a stepped inner sleeve and/or an outer sleeve (neither shown) may be utilized.

(60) Any of the balloons and balloon bonding concepts described elsewhere herein may be incorporated or used in place of the balloon and/or balloon bonding described in reference to system **100**.

(61) As shown in FIGS. 3A and 3B, distal tip segment **124** may optionally be provided with a preset shape that extends a distal end thereof laterally outward. In this embodiment, the distal end extends outward at a 45 degree angle. In other embodiments (not shown), the distal end extends outward at an angle of about 70 to about 90 degrees. In still other embodiments, the tip angle can be between about 10 degrees and about 70 degrees, or between about 90 degrees and about 180 degrees (i.e., the tip can double back on itself). In some embodiments (not shown), the tip can include two or more bends rather than the single bend of the exemplary embodiment shown. This outward angle allows a medical practitioner to rotate the distal tip segment **124** towards a branch blood vessel (by rotating Y-hub **110** outside of the patient), extend a guidewire (not shown) distally from the distal tip segment **124** into the branch blood vessel, and then track the catheter system **100** over the guidewire into the branch blood vessel. This may be done repeatedly to track the catheter system **100** deep into tortuous vasculature toward target tissue.

(62) As depicted in FIG. 3A, distal outer catheter section **118** may be connected to inner catheter **112** through at least one discrete connection point **130**, which can help transfer torque between the inner and outer catheters. In some embodiments, discrete connection point(s) **130** may be created by thermal or chemical bonding. For example, laser, radio frequency energy and/or a heated probe such as a soldering iron may be used to melt together the materials of distal outer catheter section **118** and inner catheter **112** to form a tack or spot weld. By way of another example, a hole may be formed in distal outer catheter section **118** and a small amount of glue, adhesive, epoxy or other fluid material may be injected into the hole to bond the two catheters **118** and **112** together. In some embodiments, the resulting discrete connection point **130** described above may have a diameter no greater than 0.006 inches. In some embodiments, the resulting discrete connection point **130** may extend through a circumferential angle no greater than about 30 degrees. In other embodiments (not shown), through pins, wires, micro-rivets, etc. may be used to create the discrete connection points.

(63) As depicted in FIG. 4, when creating a discrete connection point **130**, in some embodiments it may be desirable to bend distal outer catheter section **118** and inner catheter **112** so that they make contact with one another. With this approach, a nominal gap of 0.003 inches between inner catheter **112** and distal outer catheter section **118** becomes 0.000 inches on the outside of the bend and 0.006 on the inside of the bend. If a glue or other fluid material is being used to create the discrete connection point **130**, the fluid may wick further in the axial direction than in the circumferential direction, creating an oblong discrete connection point **130**. In some embodiments, a hole in distal outer catheter section **118** through which the fluid is injected may be no larger than about 0.006. Similar discrete connection points **130** may also be formed between proximal outer catheter **116** and inner catheter **112**. The creation of discrete connection points **130** should maintain the patency of the balloon inflation passage between the inner and outer catheters. That is, the connection points cannot be such that they completely block the flow of inflation fluid to the balloon, or else the balloon could not be inflated.

(64) Referring to FIGS. 5A-5D, various exemplary catheters constructed according to aspects of the present disclosure are depicted. In these views, the proximal end of the catheter is shown on the right, the distal end is shown on the left, and other components such as a Y-hub, strain relief, balloon, marker band, and distal tip segment (which may or may not be present) are removed for clarity. A sufficient number and placement of discrete connection points **130** should be created to ensure that torque can be adequately transferred from proximal outer catheter **116** to distal outer

catheter section **118** through inner catheter **112**. However, the number of discrete connection points should be kept to a minimum and their locations chosen so that good flexibility of the catheter is maintained. Each of the exemplary constructs shown in FIGS. 5A-5D is believed to achieve both these goals, as well as other possible constructs. All of the discrete connection points shown in FIGS. 5A-5D are shown on the near side of the catheter for clarity, but in some embodiments they are placed on alternating sides or spaced around the circumference of the catheter so that the catheter is not significantly stiffer along one or two sides.

(65) Referring again to FIG. 1, another exemplary layout of discrete connection points **130** is shown. In this exemplary embodiment, there is one discrete connection point **130** formed between proximal outer catheter **116** and inner catheter **112**, and three discrete connection points **130** formed between distal outer catheter section **118** and inner catheter **112**. Y-hub **110** may also serve to connect proximal outer catheter **116** and inner catheter **112**. The discrete connection point **130** formed between proximal outer catheter **116** and inner catheter **112** may be a distance E away from strain relief **114** as shown, which in some embodiments is between about 2 cm and about 10 cm. The three discrete connection points **130** formed between distal outer catheter section **118** and inner catheter **112** may be predetermined distances F, G and H, respectively, away from the proximal end of balloon **120** as shown. In some embodiments, these distances are about 1 cm-3 cm, such as 2 cm, about 5 cm-15 cm, such as about 10 cm, and about 20 cm-30 cm, such as about 25 cm, respectively. The middle of these three discrete connection points **130** may be located on the opposite side from the other two, that is, 180 degrees away around the circumference.

(66) Referring to FIG. 6, an enlarged view showing inner catheter **112** located inside distal outer catheter section **118** is provided. As can be seen, in this exemplary embodiment both inner catheter **122** and distal outer catheter section **118** have internal mesh or braid structures.

(67) In order to be able to track through tortuous vasculature, the distal portion of system **100** should be very flexible. However, very flexible portions of a catheter system tend to transmit torque poorly, as previously mentioned. If a catheter system does not have sufficient torsional rigidity, there is a delay or hysteresis between rotations that are input at the proximal end of the catheter and the desired output rotations that occur at the distal end. In some cases of poor torsional rigidity in the prior art, the proximal end of the catheter may be turned 2, 3 or more rotations for every 1 rotation that occurs at the distal end, with the additional rotations being stored as potential energy in the catheter. These additional rotations may or may not be eventually released, and may release suddenly and unexpectedly. In some implementations of tracking through tortuous vasculature, the proximal end of a prior art catheter may be turned 10 or more times with no rotation occurring at the distal end. With the unique combination of materials, dimensions and discrete connection points **130** disclosed herein, Applicants have found that catheter systems may be constructed that are both highly trackable and torqueable.

(68) Referring to FIGS. 7A and 7B, results from flexibility testing performed on three sample specimens of an exemplary distal outer catheter section **118** (FIG. 7A) and three sample specimens of an exemplary proximal outer catheter section **116** (FIG. 7B) are provided (in grams.) In some embodiments in this disclosure, the catheter system also includes one or more expandable balloons. As mentioned elsewhere, previous attempts at securing a balloon to a catheter secured one or more balloon surfaces to an OD of the catheter, which necessarily increases the OD of the system. In embodiments herein that include a balloon, an inner balloon bonding/securing surface is advantageously disposed radially inward relative to an outer diameter (outer surface) of an outer catheter, which allows for the OD of system to be minimized. In embodiments herein that include a balloon, the balloon is secured to the device such that substantially all, if not all, of the balloon is disposed at or below the OD of the outer catheter. In some embodiments, a balloon is positioned below the surface of the catheter when in its constrained configuration and returns thereto following inflation and deflation. Some embodiments herein include a circumferentially oriented pocket or pockets in a catheter and one or more balloon bonding surfaces are positioned below the

surface of the catheter.

(69) When this disclosure refers to a balloon bonding surface, it refers to a balloon surface that is secured relative to another surface. It does not require that the balloon be secured to the other surface in a particular manner. For example, a bonding surface does not require that the balloon surface be secured to the other surface with an adhesive.

(70) In any of the embodiments herein, the balloon surface that is bound to another surface may be at least 0.001 inches or more below the outer diameter (outer surface) of the outer catheter, as long as the fluid passageway remains between the inner and outer catheters for the fluid to be advanced.

(71) As set forth herein, transvascular microcatheters should include a distal region that is flexible. In embodiments that includes a distal balloon (such as some of those herein), the catheter must also be flexible at the location of the balloon that is mounted at the distal portion of the catheter to allow them to advance through tortuous vasculature. Balloon bonding adhesives, if used, tend to be rigid and measures should be taken to construct the balloon bonding surfaces to be flexible.

(72) Therefore, in many embodiments, optimal characteristics of a balloon microcatheter include: 1) a large drug injection lumen, 2) a large balloon inflation lumen, 3) a catheter that withstands high pressure, 4) a rigid proximal section that is pushable and torqueable, 5) a flexible distal catheter portion; and 6) a small outer diameter. The different embodiments herein provide for one or more of these advantages.

(73) Strong bonding of the balloon to the catheter is also important to prevent detachment during a medical procedure and to assure that post inflation, the balloon can return to a position at or below the surface of the outer diameter of the catheter.

(74) Many of the methods and devices herein solve the aforementioned challenges and enable a balloon microcatheter to be adapted to include a large injection lumen, a large balloon inflation lumen, a flexible distal catheter portion and strong balloon bonding that assure the balloon will return to a retracted diameter less than or equal to that of the catheter's outer diameter.

(75) The devices of the present disclosure include a balloon that is secured to a catheter such that the balloon bonds are positioned below the outer surface (i.e., radially inward of the outside diameter) of the catheter assembly and, if desired, the balloon in its uninflated configuration can be positioned below or at the outer surface of the catheter assembly. The present device allows a balloon to be inflated from below the surface of a catheter assembly and when deflated, return thereto. Such a balloon catheter assembly, as disclosed herein, has a small profile, a strong attachment of the balloon to the catheter and rapid inflation and deflation times even with viscous solutions.

(76) Any of the balloon and/or balloon bonding embodiments herein may be integrated or used with any of the other aspects of any catheter herein. For example, any of the balloon and/or balloon concepts herein can be used with any of the embodiments illustrating exemplary inner and outer catheters (e.g., FIGS. 1-6).

(77) Referring to FIG. 8, a longitudinal cross section of the distal end of an exemplary embodiment of the present disclosure is shown with catheter assembly 2, outer catheter 4, inner catheter 6, inner catheter extension 8, optional outer adapter 10, support sheath 12, balloon 14, inner catheter lumen 16, annular lumen 18, fluid channel 20, proximal balloon bond 22, and distal balloon bond 24. In this embodiment, a coaxial catheter design is shown with outer catheter 4, having a proximal end and a distal end and a diameter larger than inner catheter 6, also having a proximal end and a distal end, whereby inner catheter 6 is positioned longitudinally inside of outer catheter 4. Inner catheter 6 extends distally beyond the distal end of outer catheter 4, as indicated by extension distance 8, said inner catheter extension providing a reduction in diameter whereupon a balloon or accessory can be attached. The inner and outer catheter may be any of the inner and outer catheters herein, including any of the optional discrete connection locations between the inner and outer catheters.

(78) Inner catheter 6 and outer catheter 4 may be composed of a laminate or composite of at least two layers, with a steel or other braid, coil, woven, and/or reinforcing material positioned between

the layers or forming one of the layers. In some embodiments, a reinforcing material is molded within a less rigid base material such that the reinforcing layer is embedded in an encapsulation layer. This construction is provided to allow kink resistance and strength to withstand high pressure injection. Given the multi-layer construction, these walls typically have a thickness of 0.1 mm to 1 mm which consumes radial area which could otherwise be used to increase the size of the injection lumen or balloon inflation lumen. Therefore, thin wall construction is optimal, provided that strength, kink resistance and a tolerance to high pressure is maintained. In this exemplary embodiment, outer adapter **10** is composed of a single layer flexible material such as Pebax, polyamide, PET, polyethylene, polyurethane or the like and has a wall thickness of 0.0016 mm to 0.025 mm, more typically 0.003 mm to 0.0150 mm, said thickness being less than that of the inner catheter or outer catheter. In some embodiments, the outer catheter **4** has a wall thickness of about 0.0635 mm and the outer adapter **10** has a wall thickness of about 0.00635 mm. In some embodiments, the wall thickness of the outer adapter **10** is no more than about 15% of the wall thickness of the outer catheter **4**. The thickness and material type is different from that of the outer catheter and optimized for maximizing balloon inflation and injection lumen diameters, flexibility and bondability of the balloon material to the adapter.

(79) In any of the embodiments herein, the wall thickness of the inner catheter is from 0.0001 inches to 0.0040 inches, such as from 0.001 inches to 0.0035 inches, such as 0.0015 inches to 0.003 inches. In any of the embodiments herein, the wall thickness of the outer catheter is from 0.0001 inches to 0.0040 inches, such as from 0.001 inches to 0.0035 inches, such as 0.0015 inches to 0.003 inches. The inner and outer catheters can include any number of “layers,” such as any of the three-layered constructs described herein.

(80) In some embodiments, the proximal end of outer adapter **10** is circumferentially oriented about the outer surface of the distal end of outer catheter **4** and steps centrally to a reduced diameter at a point distal to the distal end of outer catheter **4**, said reduced diameter is circumferentially oriented about inner catheter **6**. At its proximal end, support sheath **12** is positioned over the distal end of outer catheter **4** and the proximal end of outer adapter **10**, and the distal end of support sheath **12** is positioned over the proximal end of balloon **14**. Support sheath **12** can compress the proximal end of balloon **14** into the space below the other diameter of outer catheter **4**, assuring that the balloon will return to a position at or below the outer diameter of outer catheter **4** and strengthens balloon bond **22** on outer adapter **10**. In some exemplary embodiments, any support sheath herein is composed of a single layer flexible material with substantially the same wall thickness and material composition as an adapter, such as an outer adaptor.

(81) The proximal end of inner catheter **6** is in fluid communication with the distal end of inner catheter **6** by way of inner catheter lumen **16**. A space between outer catheter **4** and inner catheter **6** defines a generally annular lumen **18**, and a space between the reduced diameter of outer adapter **10** and inner catheter **6** defines fluid channel **20**. Balloon **14** is bonded at its proximal end to the reduced diameter of outside adapter **10** by proximal balloon bond **22**, and the distal end of balloon **14** is bonded to inside catheter **6** at distal balloon bond **24**, such that proximal balloon bond **22** and distal balloon bond **24** are radially inward from the outside diameter of outer catheter **4**. In this exemplary embodiment, proximal balloon bond **22** and distal balloon bond **24** are also radially inward from the inside diameter of outer catheter **4**, as shown in FIG. 1. Radially inner surfaces of the balloon at the proximal and distal ends of the balloon are disposed radially inward relative to the outer surface of the outer catheter. The proximal end of catheter assembly **2** is in fluid communication with the interior volume of balloon **16** by way of annular lumen **18**, and fluid channel **20**. In some embodiments, inner catheter **6** may be located in an offset manner within outer catheter **4** such that the inflation lumen formed therebetween is crescent-shaped rather than annular.

(82) The aforementioned disclosure enables a balloon microcatheter to be adapted to an optimal: small outer diameter for use in small vessels, flexibility to navigate in tortuous vasculature, high pressure tolerance to allow high flow rates of drug and contrast, short balloon inflation and

deflation times, balloon bondability, balloon bond strength and maintenance of the balloon outer diameter to remain at or below the outer diameter of the outer catheter, even after balloon inflation and deflation.

(83) Referring to FIG. 9, an axial cross section of a coaxial catheter assembly with outer catheter **4**, inner catheter **6**, inner catheter lumen **16** and annular lumen **18** defining a space between outer catheter **4** and inner catheter **6**. Inner catheter lumen **16** extends from the proximal end of the outer catheter **4** to the distal end of the outer catheter **4** and allows fluid communication therebetween. Annular lumen **18** extends from the proximal end of the catheter assembly to the inner volume of a balloon and allows fluid communication to inflate and deflate the balloon.

(84) Referring to FIG. 10, a longitudinal cross section of catheter assembly **30** is shown with outer catheter **4**, inner catheter **6**, inner catheter lumen **16**, annular lumen **18**, inner catheter extension **32**, external catheter surface **34**, internal catheter surface **36** (i.e., a portion of the inside diameter of outer catheter **4**), inner balloon surface **38** and outer balloon surface **40**. Outer catheter **4** has a diameter greater than inner catheter **6** and has a length that is less than that of inner catheter **6**. Annular lumen **18** defines a space between outer catheter **4** and inner catheter **6** and extends from the proximal end of catheter assembly **30** to the inner volume of balloon **14** and allows fluid communication to inflate and deflate the balloon. Inner catheter **6** has a length that is greater than that of outer catheter **4** and a lumen **16** that extends from the proximal end of catheter assembly **30** to the distal end of catheter assembly **30** and allows fluid communication therebetween. Inner catheter extension **32** with a diameter less than that of outer catheter **4**, provides a surface whereby a balloon or other accessory can be attached with the bonding surfaces below the surface of (i.e., radially inward from the outside diameter of) outer catheter **4** and, if desired, the balloon or other accessory can be positioned such that its outer diameter is at or below the surface of outer catheter **4**. In some embodiments, the balloon bonding surface may also be radially inward from the inside diameter of outer catheter **4**. External catheter surface **34** defines a circumferential area on the outside of the distal end of outer catheter **4** whereupon adapters and sheaths may be affixed, and internal catheter surface **36** defines a circumferential area on the inside of the distal end of outer catheter **4** whereon adapters may be affixed. The diameters of external catheter surface **34** and internal catheter surface **36** are equal to the outer diameter and inner diameter of the catheter selected, respectively, typically from 0.3 mm to 5 mm, and the longitudinal length of the fixation surfaces can be from 0.2 mm to 25 mm, more typically from 1 mm to 10 mm.

(85) Referring to FIG. 11A, a longitudinal cross section of an outer adapter **10** is shown with a diameter reduction between a large diameter surface **42** and a small diameter surface **44**. Although outer adapter **10** shows a single step from large diameter surface **42** to small diameter surface **44**, the transition can be configured with 2, 3, 4 or more steps or the transition can be a gradual as in a conical adapter. The outer adapter **10** provides a connection between the external catheter surface **34**, of outer catheter **4** and an inner balloon surface **38** of balloon **14**, providing fluid communication between the annular lumen **18** and the inner surface of balloon **14**, whereby a proximal balloon bond is positioned between inner balloon surface **38** of balloon **14** and small diameter surface **44** of outer adapter **10**, positioning the balloon bond below the surface of the outer diameter of outer catheter **4**. In some embodiments, the outer adapter **10** (or any other adaptor herein) is made from a plastic polymeric material such as polyester, nylon, Pebax, polyethylene, polyurethane, or other convenient material. In many embodiments, a thin wall is preferred; however any thickness can be used depending on the application. Material thickness will typically range from 0.0016 mm to 0.025 mm, more typically from 0.003 mm to 0.015 mm. The large diameter surface **42** of outer adapter **10** is typically glued, heat bonded, compressed or reflowed into the external catheter surface **34** of outer catheter **4**. Reflow has the advantage that large diameter surface **42** of outer adapter **10** melts into the outer surface of outer catheter **4** at external catheter surface **34** and does not increase the diameter of outer catheter **4**. The diameters of the large diameter surface **42** and the small diameter surface **44** will be dependent on the catheter

diameter and the desired positioning of the balloon bonding surface below the outer diameter of outer catheter **4**. Typically the outer diameter of medical catheters range from about 0.25 mm to 10 mm, more typically from 0.5 mm to 5 mm, thereby making the large diameter surface **42** of the outer adapter **10** range from about 0.5 mm to 4 mm. The outside adapter **10** can be any length of convenience, typically 2 mm to 25 mm, more typically 4 mm to 10 mm. The outer adapter **10** of the present disclosure is particularly useful in micro-catheters that commonly have small outer diameters in the range of 0.5 mm to 1.5 mm and are used for access into the peripheral vasculature and into small blood vessels. In this instance, it is important to keep the outer diameter of the catheter as small as possible. If a balloon or other accessory is placed on the catheter, it can be a significant advantage to bond or otherwise mount the accessory below at least the outer surface of outer catheter **4**. In addition to a balloon, an accessory can include a tissue anchor, blade, mechanical occlusion device, partial occlusion device, a device to trap embolic particles, or any device of use in the vasculature.

(86) Referring to FIG. **11B**, a longitudinal cross section of an inner adapter **46** is shown with a diameter reduction between a large diameter surface **48** and a small diameter surface **50**. In any of the embodiments herein (if any adaptor is included), an inner adapter (e.g., inner adapter **46**) can be used instead of outer adapter **10**. Although inner adapter **46** shows a single step from large diameter surface **48** to small diameter surface **50**, the transition can be configured with 2, 3, 4 or more steps or be a gradual transition as in a conical adapter. The inner adaptor has a proximal region **48** with an external surface that secured to inner catheter surface **36**. The inner adapter provides a connection between the internal catheter surface **36** of an outer catheter **4** and balloon **14** at inner balloon surface **38**, thereby positioning the balloon bonding surface or accessory attachment surface below the outer surface and the inner surface of outer catheter **4**. The composition, measurements, use and benefits are as stated for FIG. **4A**.

(87) In some embodiments, an adaptor does not include a stepped region. For example, an adaptor can have a cylindrical configuration and coupled to inner surface **36**, yet still provide a surface to which the proximal end of balloon can be bonded such that the bonding surface is below the OD of the outer catheter.

(88) Referring now to FIG. **11C**, a longitudinal cross section of exemplary support sheath **12** is shown with a proximal end, a distal end, an outer surface **54** and an inner surface **56**. The support sheath **12** can fit circumferentially over the outer catheter **4** at external catheter surface **34** and balloon **14** at outer balloon surface **40**. Support sheath **12** functions to strengthen the balloon bond and, if desired, hold the proximal end of balloon **14** at or below the outer surface of outer catheter **4**. The length from proximal to distal ends of the support sheath is typically from 0.20 mm to 10 mm, more typically from 0.5 mm to 6 mm and any portion of the length can be bonded to the catheter with the remainder extended over the balloon or other accessory. In some embodiments, the support sheath has a length that is at least as great as the outside diameter of the distal end of the outer catheter. Typically the support sheath **12** is compressed, glued, reflowed or otherwise affixed to the outer catheter and extends over, but may not be attached to a balloon or other accessory. In some embodiments, the support sheath is made from polymeric material such as silicone, latex, polyester, nylon, Pebax, polyethylene, polyurethane, or other convenient material. In many embodiments, a thin wall is preferred, however, any thickness can be used depending on the application. In any of the embodiments herein, the support sheath can be a heat shrink material that is placed at a desired position over the catheter and balloon, or other accessory, and heated, causing the material to reduce in diameter and compress about the surface of the outer catheter and the balloon. The thickness will typically range from 0.003 mm to 0.05 mm, more typically from 0.006 mm to 0.01 mm. Reflow and compression have the advantage that the outer surface **54** of the support sheath **12** melts or is compressed into the outer surface of the outer catheter **4** and does not increase the diameter of the outer catheter. The diameter of support sheath **12** is dependent on the catheter diameter. Typically the outer diameter of medical catheters range from about 0.5 mm to 5

mm.

(89) The sheaths herein may also be referred to as collars.

(90) Referring now to FIGS. 12A and 12B, a longitudinal cross section of a second embodiment of the present disclosure is shown with catheter assembly 58, outer catheter 4, inner catheter 6, outer adapter 10, large diameter surface 42, small diameter surface 44, support sheath 12, nose cone 60, fluid channel 20, balloon 14, proximal balloon bond 22 and distal balloon bond 24. External catheter surface 34 of catheter 4 is bonded to the inner surface of the large diameter surface 42 of adapter 10. The inner surface of balloon 14 is bonded at its proximal end to the outer surface of small diameter surface 44 of adapter 10, at proximal balloon bond 22 and its distal end is bonded to inner catheter 6 at distal balloon bond 24 that is positioned proximal to nose cone 60. Support sheath 12 is positioned such that it extends over external catheter surface 34 of outer catheter 4 and the proximal end of balloon 14. The proximal end of support sheath 12 can be bonded, reflowed, compressed or otherwise affixed to external catheter surface 34 of outer catheter 4 and/or large diameter surface 42 of outer adapter 10, and the distal end of support sheath 12 is positioned over the proximal end of balloon 14 with the advantage of strengthening the balloon bond 22 and, if desired, holding balloon 14 below the surface of outer catheter 4. Support sheath 12 can be affixed to external catheter surface 34 and the proximal end of balloon 14, or it may not be affixed to one or both surfaces, provided that it does not move with respect to outer catheter 4 or balloon 14. Inner catheter 6 extends beyond the distal end of outer catheter 4 and nose cone 60 is affixed to inner catheter 6 at a location distal to the distal end of outer catheter 4. In this embodiment, the balloon sits in a pocket between the distal end of outer catheter 4 and the proximal end of nose cone 60 with the advantage of positioning the balloon bond lower than (i.e. radially inward from) the outer diameter of outer catheter 4 and, if desired, the balloon outer diameter, when in its unexpanded configuration, can be positioned so that it is substantially equal to or less than the outer diameter of the outer catheter 4. In this manner, a balloon, when in its unexpanded configuration, can be positioned within a pocket at or below the outer surface of outer catheter 4, expand to a diameter greater than outer catheter 4, and then return, upon deflation, to a diameter less than or equal to the outside diameter of outer catheter 4. The proximal end of catheter assembly 58 is in fluid communication with the interior space of balloon 14 by way of annular lumen 18 and adapter 10 at fluid channel 20 which is defined by an annular space between the inner surface of small diameter surface 44 of adapter 10 and the outer surface of inner catheter 6. Alternate configurations of this embodiment or any embodiment herein include use of adapter 10 and without the support sheath 12 or use of the support sheath 12 without the adapter 10. When only the support sheath 12 is used, the outer diameter of proximal balloon 14 is bonded to the inner surface of the support sheath 12. Another configuration of this embodiment includes the use of an outer adapter (not shown) to affix the balloon to the nose cone 60 or the use of a support sheath to affix balloon 14 to nose cone 60 or the use of both an adapter and support sheath to affix balloon 14 to nose cone 60. Optimally, balloon 14, adapters, support sheaths and nose cone 60 have an outer diameter equal to or less than the outer diameter of outer catheter 4.

(91) Referring to FIGS. 13A and 13B, an exemplary embodiment of a device of the present disclosure is shown with catheter assembly 62, outer catheter 4, inner catheter 6, outer adapter 10, large diameter surface 42, small diameter surface 44, support sheath 12, fluid channel 20, balloon 14, proximal balloon bond 22, distal balloon bond 24, second outer catheter 64, distal outer adapter 66, large diameter surface 68, small diameter surface 70 and second support sheath 72. Inner catheter 6 extends beyond the distal end of outer catheter 4 and second outer catheter 64 may be affixed to inner catheter 6 at a location distal to the distal end of outer catheter 4, whereby balloon 14 is disposed in a pocket between the distal end of outer catheter 4 and the proximal end of second outer catheter 64 with proximal balloon bond 22 and distal balloon bond 24 positioned below the surface of outer catheter 4 and second outer catheter 64. In one construction of the present embodiment, balloon 14 is configured with an outer diameter less than or equal to the outer

diameter of catheter **4** and second outer catheter **64** and thereby is concealed within a pocket therebetween. When inflated to its radially expanded configuration, balloon **14** will have a diameter greater than the outside diameters of outer catheter **4** and second outer catheter **64** and extend radially outward from said pocket. When balloon **14** is then deflated from its radially expanded configuration it will return to a diameter less than or equal to outer catheter **4** and second outer catheter **64** and again be concealed within the pocket. The external catheter surface **34** at the distal end of outer catheter **4** is bonded to the inner surface of large diameter surface **42** of adapter **10**. The proximal end of balloon **14** is bonded at its inner surface to the outer surface of small diameter surface **44** of outer adapter **10** and the distal end of balloon **14** is bonded at its inner surface to the outer diameter of small diameter surface **70** of distal second adapter **66**. Alternately, the inner luminal surface of balloon **14** can be bonded at its distal end directly to inner catheter **6**. The inner diameter of large diameter surface **68** of distal adapter **66** is bonded, reflowed, compressed or otherwise affixed to the proximal end of a second outer catheter **64** or other distally extending structure, such as one or more shafts. A flow channel between the inner surface of small diameter surface **70** of second adapter **66** and inner catheter **6** may or may not be present. In the case where one balloon is present the distal end of the balloon will be sealed. However, if a second balloon is positioned distal to a first balloon, then a flow channel may be configured to allow inflation and deflation of a second, third, fourth or any number balloons and it is understood that any number of balloons and outer catheter segments can be positioned in series. A first support sheath **12** may be positioned such that it extends over the outer surface of the distal end of outer catheter **4** and the proximal end of balloon **14** and a second support sheath **72**, may be positioned such that it extends over the outer surface of the proximal end of second outer catheter **64** and the distal end of balloon **14**. Support sheaths **12** and **72** can be bonded, glued, reflowed, compressed or otherwise affixed to the distal end of outer catheter **4** or proximal end of second outer catheter **64** and may, if desired, be affixed to balloon **14**. Support sheath **12** provides the advantage of restraining or compressing the proximal end of balloon **14** at the proximal balloon bond **22** and strengthening the balloon bond and preventing detachment. A second support sheath **72** adds the advantage of retaining or compressing balloon **14** at distal balloon bond **24** or strengthening the balloon bond and preventing detachment.

(92) In any of the embodiments herein that include one or more support sheaths (collars), any of the collars may be replaced with any other suitable sheath/collar described herein.

(93) The proximal end of catheter assembly **62** is in fluid communication with the interior space of balloon **14** by way of annular lumen **18** and outside adapter **10** at fluid channel **20**, which is defined by an annular space between the inner surface of small diameter surface **44** of adapter **10** and the outer surface of inner catheter **6** as seen by flow path **26**. Alternate configurations of this embodiment include an outer adapter **10** without a support sheath **12**, a support sheath **12** without adapter **10**, outer adapter **66** without second support sheath **72**, second support sheath **72** without outer adapter **66** or any combination of adapters and support sheaths, provided that the proximal end and distal end of balloon **14** have at least one adapter or sheath or are bonded directly to inner catheter **6** and annular lumen **18** is in fluid communication with the interior surface of balloon **14**. Optionally, balloon **14**, both support sheaths and both adapters have an outer diameter equal to or less than the outer diameters of outer catheter **4** and second outer catheter **64** of catheter assembly **62**, although there is no requirement for balloon **14** to be constrained below the surface of catheter assembly **62**, provided that bonding surfaces **22** and/or **24** are positioned below the outer surface of catheter assembly **62**. It would be particularly useful when delivering therapy in small vessels, for a balloon or other accessory or tool to be positioned below the surface of a catheter, in its unexpanded state, and then following inflation or deployment be returned to the same position below the catheter surface.

(94) Referring now to FIGS. **14A** and **14B**, a longitudinal cross section of yet another exemplary embodiment of the present disclosure is shown with catheter assembly **74**, outer catheter **4**, inner

catheter **6**, proximal inner adapter **46**, large diameter surface **48**, small diameter surface **50**, fluid channel **76**, distal inner adapter **78**, large diameter surface **80**, small diameter surface **82** and support sheath **86**. In this embodiment, inner adapters **46** and **78** are used instead of outer adapters whereby the outer surfaces of large diameter surfaces **48** and **80** of inner adapters **46** and **78** are bonded or otherwise affixed to the inner circumference of outer catheter **4** and the inner circumference of second outer catheter **84**. In this embodiment, the balloon **14** is disposed in a pocket between the distal end of outer catheter **4** and the proximal end of second outer catheter **84** (or other distally extending structure, such as one or more shafts). It is understood that any combination of adapters and support sheaths can be used. For example, an outer adaptor can be replaced with an inner adaptor. The proximal and/or distal balloon bonds are positioned below the outer surfaces of outer catheter **4** and second outer catheter **84** and fluid communication is maintained from the proximal end of catheter assembly **74** and the interior surface of the balloon **14** by way of annular lumen **18** and adapter **46** at fluid channel **76** which is defined by an annular space between the inner surface of small diameter surface **50** of adapter **46** and the outer surface of inner catheter **6**. It is also understood that a nose cone or other nose piece can be affixed to a location distal to the second outer catheter **84** and that any number of balloons and outer catheter segments can be serially oriented along catheter assembly **74**.

(95) Referring now to FIGS. **15A** and **15B**, yet another exemplary embodiment of the present disclosure is shown with catheter assembly **288**, two lumen catheter **290**, injection lumen **292**, balloon inflation lumen **294**, injection lumen extension **296**, nose cone **298**, outer adapter **200**, large diameter surface **202**, small diameter surface **204**, support sheaths **206** and **208**, balloon **210**, proximal balloon bond **212**, distal balloon bond **214**, fluid channel **216** and flow path **218**. In this instance, a single catheter with two lumens is used instead of the two catheter coaxial construction as described in the above embodiments. While a two lumen catheter is useful for numerous applications, the catheter can also include 3, 4, 5 or more lumens as needed. Catheter assembly **288** can be any length useful for medical applications, typically from 25 cm to 250 cm, more typically from 50 cm to 150 cm. Injection lumen **292** has a proximal end and a distal end and extends from the proximal end of catheter assembly **288** to the distal end of catheter assembly **288** and provides fluid communication therebetween. Balloon inflation lumen **294**, has proximal and distal ends and extends from the proximal end of catheter assembly **288** to balloon **210**, providing a means for inflation and deflation. Injection lumen **292** extends distally beyond the distal end of two lumen catheter **290** and distally beyond the end of balloon lumen **294** as illustrated by injection lumen extension **296** and length **220**. The injection lumen extension typically has a length in the range of 0.1 cm to 50 cm, more typically from 1 cm to 10 cm. Nose cone **298** is positioned about the injection lumen extension **296** at a point that is distal to the distal end of two lumen catheter **290**, whereby balloon **210** is disposed in a pocket between the distal end of two lumen catheter **290** and the proximal end of nose cone **298**. Nose cone **298** is typically placed at a distance of 0.25 cm to 10 cm, more typically from 1 cm to 3 cm from the distal end of two lumen catheter **290** and can be any shape or configuration and can be composed of any convenient material including materials that are radiopaque. For illustration only, the embodiment of FIGS. **15A** and **15B** includes outer adapter **200** and both proximal and distal support sheaths **206** and **208**, however any combination of adapters and support sheaths can be used, provided that fluid communication is maintained between the inflation lumen **294** and the interior surface of balloon **210**. Outer adapter **200** has a large diameter surface **202** and a small diameter surface **204**, whereby the inner surface of large diameter surface **202** is bonded to the distal outer surface of two lumen catheter **290** and the small diameter surface is oriented about injection lumen extension **296**, such that an annular space between the inner surface of small diameter surface **204** and injection lumen extension **296** is maintained. The proximal end the catheter assembly **288** is in fluid communication with the interior space of balloon **210** by way of balloon inflation lumen **294**, outer adapter **200**, an annular space between the injection lumen extension **296** and the inner surface of the small diameter surface **204**

of adapter **200**, defined by fluid channel **216** and flow path **218**. In most cases it is desirable that the central injection lumen **292** allow fluid communication therethrough, however, this is not a requirement. In some uses, the injection lumen **292** can be a solid and without fluid communication, thereby configuring a one lumen balloon catheter. It may also be desirable for balloon **210** to sit below the outer diameter of catheter assembly **288**, however this is not required. In some embodiments, balloon **210** does not sit below the outer diameter of catheter assembly **288**, but at least the proximal balloon bond **212** is positioned below the outer diameter of catheter assembly **288**.

(96) In any of the embodiments herein that include a balloon, the balloon may comprise a silicone material, and may optionally consist essentially of a silicone material. Using one or more silicone materials for the balloon can provide more elasticity, which can allow the balloon to return to an unexpanded configuration that is at or below the OD of the outer catheter.

(97) The material that is used in a balloon, such as a silicone, may, however, present challenges in that it may be difficult to bond the balloon to other surfaces relying solely on an adhesive, solvent or heat. In any of the embodiments herein, a surface to which a balloon surface is bonded (i.e., secured) may include one or more surface features that are adapted and configured to increase the stability between the balloon surface and the surface to which the balloon surface is bonded.

(98) The one or more surface features may be on any of the adaptors herein, such as any of the proximal adaptors herein or any of the distal adaptors herein. The one or more surface features may be present on the entire length of the adaptor, or they may be present on less than the entire adaptor, such as only where a balloon surface is to be bonded. For example, in the adaptor shown in FIG. **11A**, the one or more surface features may be present only on the outer surface **44** in the smaller diameter distal region. For example, in the adaptor shown in FIG. **11B**, the one or more surface features may be present only on the outer surface **50** in the distal region. Or even if the adaptor does not have a step (e.g., has a cylindrical configuration), the one or more surface features may only be on a distal region of the adaptor, and may be only an outer surface of the distal region. The same concepts apply to any distal adaptor that may be used herein, while it will be understood that the one or more surface features may be disposed only a proximal region of the adaptor, such as where a balloon might be bonded thereto (regardless of the configuration of the adaptor).

(99) The one or more surface features can include a wide variety of features that are adapted and/or configured to increase friction and/or increase the stability between the one or more features and a balloon surface.

(100) In some embodiments a surface feature can include raised regions on the surface.

(101) In some embodiments a surface feature can include one or more textured features.

(102) In some embodiments a surface feature can include a non-smooth surface that is configured to increase the friction with a balloon surface.

(103) In some embodiments a surface feature can include one or more barbs.

(104) In some embodiments a surface feature can include one or more sharpened features.

(105) Any particular surface may include more than one type of surface feature. For example only, a surface may include one or more raised regions and one or more sharpened features.

(106) One or more surface features may be created in the surface to which the balloon is bonded using a variety of techniques that can create a textured, roughened, and/or non-smooth surface. For example without limitation, a surface can be exposed to any number of solvents or abrasive materials to create a textured surface. The process may be performed mechanically, chemically, and/or optically, for example.

(107) In any of the embodiments herein, a material may be also be deposited on the surface of the adaptor, collar, and/or inner catheter (or any other surface to which a balloon surface may be bonded) that is adapted to increase the stability of the balloon relative to the surface. In these embodiments, the balloon surface may only make contact with the material, or it may make contact with the material as well as the structural component (e.g., adaptor, collar, and/or inner catheter, for

example). A material may be deposited on the surface to increase the stability, and the surface may also include any of the one or more surface features that are adapted to increase stability. For example without limitation, a material that may be deposited onto the surface may be an adhesive that results in an increase in friction, even if the adhesive does not create strong adhesive forces with the balloon material (e.g., silicone) as generally occurs with typical adhesives.

(108) Referring now to FIGS. **16A** and **16B**, an embodiment is shown comprising a balloon mediated steerable catheter. As shown in FIG. **16A**, a catheter tip may be provided with a balloon **230** near its distal tip **232**, similar or identical to the configurations previously described.

(109) The balloon **230** may be inflated as shown past a diameter needed to occlude a small blood vessel such that it bulges laterally to one side of the catheter tip **232** as shown. This off-center state of balloon **230** forces the distal tip **232** of the catheter to bend laterally in the opposite direction around a “bend point” **234**. The degree of bend or bend angle of distal tip **232** is a function of the volume of fluid in balloon **230**. This arrangement can be used as a means to steer a catheter around a sharp turn.

(110) FIG. **16B** depicts various angles that catheter tip **232** may bend away from the longitudinal axis of the main catheter. As balloon **230** is progressively inflated with more fluid, tip **232** may bend from a straight orientation (a) through various acute angles (b), (c) and (d), to a right angle (e) and to obtuse angles (f) and (g), as shown.

(111) According to some exemplary embodiments, a protocol for advancing a catheter around a sharp turn may comprises one or more of the following steps:

(112) 1) track the catheter over a guidewire to the vascular branch or sharp angle;

(113) 2) withdraw the guidewire just enough to position the distal tip of the guidewire to a position proximal to the catheter bend point **234**;

(114) 3) inflate the balloon **230** and visualize the direction that the catheter tip **232** is bending, such as by using fluoroscopy;

(115) 4) rotate the catheter axially such that tip **232** is pointed in the desired direction;

(116) 5) further inflate or deflate balloon **230** until catheter tip **232** is pointed into the desired branch artery;

(117) 6) advance the guidewire into the branch artery;

(118) 7) advance the catheter over the guidewire into the branch artery; and

(119) 8) deflate the balloon and continue to advance the catheter over the guidewire.

(120) In some protocols, a contrast agent can be injected through the distal tip **232** of the catheter and fluoroscopy can be used to visualize the target vessel.

(121) Balloon **230** may be configured with a uniform wall thickness, or it may be provided with a thinner wall thickness on one side to ensure that it inflates laterally to the same side every time. In some embodiments, the wall thickness may be varied to provide a desired shape or inflation profile. In some embodiments the balloon is configured to surround the circumference of the catheter, and in other embodiments it can be attached to only one side of the catheter. In embodiments that utilize a balloon that surrounds the catheter, an adhesive may be used between one side of the catheter and part of the inside surface of the balloon to ensure that the balloon does not inflate on that side.

(122) In some embodiments, bend point **234** is the midpoint of a curve. The curve may have a radius of 50 mm, 25 mm, 10 mm or less. The catheter may be modified at bend point **234** to allow the catheter to bend with less force applied by balloon **230**. For example, the catheter may have a reduced diameter and/or wall thickness at one or more locations to facilitate easier bending and/or a smaller radius of curvature. In some embodiments, the bend point can be varied by advancing or retracting a guidewire within the catheter, such that the catheter starts bending just beyond the distal end of the guidewire.

(123) Any of the embodiments herein may also include a shaped tip, examples of which are described below.

(124) Described herein are catheter designs that allow a shaped tip to be more easily navigated

through tortuous vasculature. Termination of the catheter at a flexible, soft tip is desirable to minimize vessel trauma. The added support of a rigid section in proximity to the distal tip further aides in catheter tracking as a flexible section (without support or reinforcement) would be prone to kink and excessive flexing.

(125) Referring to FIGS. **17A-17E**, various exemplary shaped tips are schematically shown. In each of these examples, two or more layers of tubing are combined to create the tip construct. The left side of each figure represents the proximal end of the shaped tip, which may be connected to the distal end of any inner catheter herein (e.g., inner catheter **112** as shown in FIGS. **3A-3B**), and the right side of each figure represents the distal end of the shaped tip. Reference letters A-F and W denote discrete pieces of tubing which in some embodiments are each formed from different materials. The base material of tube A is formulated to bond to the main body of the catheter. W denotes a tube comprising tungsten, or in some embodiments another radio opaque material that serves as a location marker under fluoroscopy or other imaging during a surgical procedure. In other embodiments, W may simply denote another material similar to the materials of A-F (i.e., not having any special radio opaque properties.) The shaped tips disclosed herein may be used at the distal end of catheters with or without balloons.

(126) In the construct depicted in FIG. **17A**, a tube A comprising a first polymeric material (such as a polyether block amide, or PEBA) is placed within a tube B comprising a second polymeric material (which may also be a PEBA). In this embodiment, the material of tube B is softer, more flexible and has a lower durometer than the material of tube A. Tube W, comprising tungsten, is placed over the distal end of tube B and located just distal to the middle region where tubes A and B are overlapping.

(127) Tube A may be oversized so that its proximal end slides over the distal end of an inner catheter. Heating tube A (before or after tubes B and W are added) allows tube A to shrink to fit over an inner catheter. The three tubes A, B and W may then be heated to melt and bond together and to the inner catheter using a material reflow process. The multiple layers may be processed in parallel or in series. In the middle section of FIG. **17A** where tubes A and B overlap, the materials of tubes A and B may blend together in the reflow process such that the middle section no longer has discrete layers but rather comprises a blend of materials. Temperature profiles, time and other parameters of the shrink to fit and/or reflow process may vary based on material selection, diameter and thickness. In some embodiments, materials A, B and W each have a different color which may blend together during the reflow process or may remain distinct. With this disclosed fabrication method, material selection and layering can create different bend profiles of the shaped tip, offering transition from rigid to flexible in a gradient rather than abrupt transition(s), which can reduce kinking of the catheter tip. The construct depicted in FIG. **17A** includes the characteristics of having a strong hold to its shape, relatively thick walls, and a radio opaque marker near its distal tip, but can be difficult to manufacture.

(128) Referring to FIG. **17B**, a shaped tip similar to the construct shown in FIG. **17A** is provided. In this example, the region of overlap between tubes A and B is longer, the length which tube B extends distally from the overlap region is shorter, and tube W is located proximal to the overlap region rather than distal to it as in the example shown in FIG. **17A**. The construct depicted in FIG. **17B** includes the characteristics of having a good hold to its shape, relatively thick walls, a radio opaque marker away from its distal tip, and is less difficult to manufacture than the tip shown in FIG. **17A**.

(129) Referring to FIG. **17C**, a shaped tip similar to the construct shown in FIG. **17A** is provided. In this example, there are only two tubes used: A and W. Instead of having only a narrow marker band W as shown in FIG. **17A**, the entire distal tube W may comprise a radio opaque material such as tungsten, as shown in FIG. **17C**. In this exemplary embodiment, the material of tube W is softer, more flexible and has a lower durometer than the material of tube A. The construct depicted in FIG. **17C** includes the characteristics of having a good hold to its shape, a radio opaque marker that

extends to its distal tip, has less of a flexibility/rigidity gradient, and is fairly easy to manufacture compared with the previously described tips.

(130) Referring to FIG. 17D, a shaped tip similar to the construct shown in FIG. 17A is provided. In this example, a forth material C is used. Each of the materials A, B and C gets progressively softer, more flexible and has a lower durometer moving distally. As depicted in FIG. 17D, there are six regions of the shaped tip of this embodiment (proximal to distal): A, A+B, A+B+C, B+C+W, B+C and C.

(131) Referring to FIG. 17E, a shaped tip similar to the construct shown in FIG. 17C is provided. In this example, seven materials are used. Each of the materials A, B, C, D, E, and F gets progressively softer, more flexible and has a lower durometer moving distally. As depicted in FIG. 17E, there are eight regions of the shaped tip of this embodiment (proximal to distal): A, A+B, A+C, A+D, A+W, A+E, E and F. Tubes B, C and D abut rather than overlap with one another, as do tubes E and F. Since tube A extends only partway through tube E in this embodiment, tubes E and F may be temporarily mounted over a mandrel when fusing them together to ensure proper alignment. The constructs of FIGS. 17D and 17E have more of a flexibility/rigidity gradient than the previously described embodiments. Material wall thicknesses may also be varied to further tune performance and behavior of the tip.

(132) In the exemplary embodiments depicted in FIGS. 17A-17E, when there is an overlapping joint rather than a butt joint between two tubes, the more distal of the two tubes slides over the more proximal tube. This is done so that if an edge of the outer (distal) tube remains after the manufacture of the shaped tip is complete, it will not impede the insertion of the tip into a patient's vasculature. If such an outer edge does remain after manufacture, it may increase friction and/or catch on features of tortuous vasculature when the shaped tip is being withdrawn with the catheter from the patient. However, this is less of an issue during removal of the catheter because the catheter is in tension during removal, as opposed to being in compression during insertion when the catheter may tend to buckle rather than advance through the vasculature. In alternative embodiments (not shown), the more proximal of the two tubes may be slid over the more distal tube during manufacture.

(133) Referring to FIG. 18, three catheter tips are shown in various stages of manufacture. All three tips are formed using a layering process similar to that shown in FIG. 17A as previously described. Catheter tip 250 uses materials that are generally the same color so that the various layers are not readily apparent after they have been reflowed together. Tip 252 uses materials A, W and B that each has a different color. In some embodiments such as this, the material colors remain distinct after the reflow process. In other embodiments (not shown), colors of the various overlapping materials blend together such that the distinct tube materials are no longer readily discernable.

(134) After a straight catheter tip is formed, such as previously described, it may be shaped into a non-straight configuration. For example, tip 250 shown in FIG. 18 may be used in its straight configuration while tip 252 may be formed into a curved tip 254 as shown. A low temperature may be used to set the material to a desired shape after the reflow process described above. Holding the material in the desired shape while at a temperature that is below the reflow temperature, such as 225 degrees F. for approximately 120-180 seconds for a layered construct of PEBA tubes, can change the overall shape of the tip without altering its dimensional aspects. These temperature and time parameters work for a convection based technique after a shaping mandrel having the desired shape is inserted through the distal end of the central lumen of the tip. An outer mold or tool with the desired shape may be used instead of or in conjunction with the mandrel. If the tip is in contact with media other than air, the temperature may need to be adjusted to ensure no dimensional changes occur during the shape changing process. For example, if the tip is held in a glass or aluminum fixture, etc., a temperature of 110-150 F may be needed, and it may be held at this temperature for less time. As shown in FIG. 18, the shaped tip 254 of this exemplary embodiment has a straight distal portion 256 configured to deviate from the longitudinal axis of the main body

258 of the catheter when tip 254 is in its relaxed state. The straight distal portion 256 extends through an angle of about 70 degrees from the longitudinal axis. A curved portion 260 may be provided between straight distal portion 256 and main body 258 as shown. In this exemplary embodiment, curved portion 260 has an inside bend radius of about 0.10 inches, or about 3 times the outside diameter of the tubing forming the tip 254. This tight bend radius allows the catheter tip to be maneuvered through tighter turns in the vasculature. In other embodiments, the bend radius may be smaller or larger. In some embodiments, the bend radius is no smaller than about 0.015 inches, as a bend radius smaller than this in a tube of the same diameter is difficult to traverse with a guidewire.

(135) Referring to FIG. 19, three more examples of shaped catheter tips are schematically shown. Tip 262 is similar to tip 254 in FIG. 18, but has a sharper bend 264. Tip 266 includes three bends 268, 270 and 272. First bend 268 has a bend radius that becomes increasingly smaller towards the distal tip. Second bend 270 has a tighter bend radius in the same direction as first bend 268. Together, bends 268 and 270 turn tip 266 about 180 degrees, forming a hook shape. Third bend 272 has a bend radius that is larger than those of bends 268 and 270, and bends in the opposite direction. Tip 274 includes two sharp bends 276 and 278, each bending in opposite directions and separated by a straight section 280. Various other combinations of single or multiple bend shaped tips are possible using the manufacturing techniques disclosed herein. For example, a J-shaped tip similar to tip 266 may have a single, continuous bend of constant radius and may extend 180 degrees, between 120 and 160 degrees, or other angle.

(136) Referring to FIGS. 20A-20D, a series of images are provided showing shaped tip 254 progressively straightened by advancing a guidewire through it. As previously described, the catheter and shaped tip 254 are provided with a central lumen configured to receive a flexible guidewire 282. FIG. 20A shows shaped tip 254 in a relaxed state and having a deflection angle of 62 degrees. When the distal tip of guidewire 282 is passed through shaped tip 254 as shown in FIG. 20B, the stiffness of guidewire 282 causes tip 254 to move towards a straighter configuration (i.e., to have an angle of deviation of less than 62 degrees from the longitudinal axis of the main body 258), such as 35 degrees in this case. A guidewire may be used that increases in stiffness moving from its distal end towards its proximal end. When such a guidewire 282 is advanced further through tip 254, it causes tip 254 to further straighten towards the longitudinal axis of the catheter. In this exemplary embodiment, a 10 mm extension of guidewire 282 through tip 254 causes it to straighten to 35 degrees as shown in FIG. 20B, an extension of 30 mm causes an angle of 16 degrees as shown in FIG. 20C, and an extension of 80 mm causes an angle of 12 degrees as shown in FIG. 20D. A surgeon can thus steer tip 254 through turns in a patient's vasculature by adjusting the angle of the tip with the depth of guidewire 282.

(137) Prior art shaped tips are typically made of a single material and often have lengths between about 1.5 and 3.0 cm in length. Using the fabrication techniques disclosed herein, similar bend profiles can be achieved in a shorter distance. In some embodiments, the lengths of the inventive tips extending beyond the base catheter are between 0.3 and 1.0 cm. These shorter lengths allow for the catheter to be maneuvered through tighter turns in the vasculature while minimizing the distance from the distal tip of the catheter to an operational interface such as a balloon. This allows accurate positioning of the operational interface and distal tip for the desired application, such as therapeutic delivery.

(138) In one particular exemplary embodiment, a shaped tip is formed from two Pebax tubes in a starting configuration similar to that shown in FIG. 17C. Tube A is made of a 35 durometer Pebax infused with 40% barium sulfate to increase lubricity. A stabilizer may also be added so the material can withstand higher temperatures for longer periods of time, and longer exposure to ultraviolet/fluorescent light. In this embodiment, the inside diameter of tube A is $0.031'' \pm 0.0005''$, the wall thickness is $0.004'' \pm 0.0005''$, the concentricity is $>85\%$ and the length is 4.0 mm. Tube W is made of 25 durometer Pebax infused with 70% tungsten by weight. A stabilizer may also be

added to tube W. The inside diameter, wall thickness, tolerances and length for tube W are the same as for tube A.

(139) In another embodiment similar to the construct shown in FIG. 17A, a 55 durometer Pebax tube with BaSO₄ additive is used as tube A, a 35 durometer Pebax tube is used as tube B, and a 25 durometer Pebax tube with Tungsten is used as tube W. A temperature approximately 25° F. higher may be needed to process tube A due to its higher durometer.

(140) The shaped catheter tips disclosed herein created by layering or abutting different materials can offer improved bend profiles, transition from rigid to flexible in a gradient rather than abrupt changes which in turn can reduce kinking of the catheter tip, and can provide sharper bends in a shorter length of catheter tip in order to more easily navigate through tight bends in the vasculature.

(141) In some embodiments, an outer catheter includes a proximal outer catheter section and a distal outer catheter section, such as proximal outer catheter section **116** and distal outer catheter section **118**. The two sections may be secured to one another using a variety of techniques. FIGS. **21A-21C** illustrate an exemplary manner in which proximal outer catheter section **302** is secured to distal outer catheter section **304** at location **306**. The types of material used for the proximal and distal catheter sections may cause it to be difficult to reliably secure the two types of material directly together, such as at a butt joint between the two sections. For example, two dissimilar materials may be difficult to securely bond together in a manner that ensures they won't be pulled apart during use. For example, if one of the sections comprises a polyimide and the adjacent section comprises a PEBAX material, it may be difficult to reliably heat fuse the two sections together at a butt joint in a way that ensures the sections will not pull apart from one another when in use. FIGS. **21A-21C** illustrate an embodiment in which one or more outer securing layers are used to secure (or at least more reliably secure) the proximal outer catheter section to the distal outer catheter section. FIGS. **21A-21C** illustrate a portion of outer catheter **300** that includes proximal outer section **302**, distal outer section **304**, first overlay securing member **308**, and optional second overlay securing member **310**. FIG. **21B** illustrates a braided material in each of the proximal and distal sections, which are joined at region **306**.

(142) FIG. **21C** illustrates a magnified portion of an exemplary outer catheter **300**, with proximal outer section **302** and distal outer section **304**. The outer catheter **300** includes epoxy adhesive layers **312**, the bottom of which is reinforced with one or more fibers **314** (e.g., Kevlar). First overlay securing member **308** is disposed atop the fiber reinforced bottom epoxy adhesive layer **312**. A second epoxy adhesive layer is disposed atop member **308**, and second overlay securing member **310** is disposed on top of the second adhesive layer.

(143) The first securing member **308** may be sufficient to secure the proximal and distal sections, but using a second securing member **310** can provide added reinforcement to ensure the outer catheter sections do not come apart. In some exemplary embodiments members **308** and **310** may comprise polyethylene terephthalate ("PET").

(144) In some embodiments the lengths of the first and second overlay securing members may be between 0.01 inches and 0.2 inches. In some embodiments the thicknesses of the first and second overlay securing members may be between 0.0001 inches and 0.001 inches.

(145) FIGS. **21A-21C** illustrate a catheter that includes axially adjacent outer catheter sections (e.g., **302**, **304**) that are secured (or at least more reliably secured) with one or more layers that are disposed radially outside the adjacent outer catheter sections, and that axially overlap the two adjacent sections. The adhesive layer(s) also are radially outside the two adjacent outer catheter sections, and axially overlap the adjacent outer catheter sections.

(146) The portion of the exemplary outer catheter shown in FIGS. **21A-21C** may be incorporated into any of the catheters herein.

(147) As set forth herein, some of the catheters include an inflatable balloon. In any of the embodiments, a compression member can be used to create a compression bond that affixes (or helps affix) the balloon end to a portion of the catheter. In this context, a compression bond

deforms the balloon material and help maintain its position relative to a portion of the catheter. In this context, a compression bond can be thought of as a mechanical constraint.

(148) Traditionally common ways to affix a balloon to a catheter is using heat bonding, although solvent or adhesive may also be used. Silicone, however, cannot be affixed using any of these methods. Compression bonding one or both ends of a balloon to a portion of the catheter can thus facilitate securing balloons comprising a silicone material. Silicon has superior properties, yet is not used because it is challenging to bond. Compression bonding thereby facilitates bonding of balloons comprising a silicone material to a catheter.

(149) Any of the collars herein may be used to implement a compression bond, and the collar may take the form of a small annular member, and may be disposed on the distal and proximal ends of the balloon. The collar need not be secured to any other portion of the catheter except the balloon outer surface. Collar as used herein may be used interchangeably with the support sheaths herein.

(150) FIGS. 22-25 illustrate exemplary balloon bonding techniques, any of which can be implemented in any of the catheters herein. Suitable disclosure herein related to any of the embodiments in FIGS. 22-25 can be incorporated into the embodiments in FIGS. 22-25 even if not specifically indicated herein.

(151) FIG. 22 illustrates exemplary catheter 320, which includes outer catheter 322, inner catheter 324, balloon 326, adaptor 328, and distal tip 334. Proximal collar 330 can create a compression bond at the proximal end of balloon 326, while distal collar 332 may form a compression bond at the distal end of balloon 326. Catheter 320 may be modified according to any other embodiment herein (e.g., adaptor 328 may be an inner adaptor).

(152) FIG. 23 illustrates exemplary catheter 350, which includes outer catheter 352, inner catheter 354, balloon 356, adaptor 358, and distal tip 364. Proximal collar 360 may create a compression bond at the proximal end of balloon 356, while distal collar 362 may form a compression bond at the distal end of balloon 356. Adhesive 366 is also shown, which may help create friction rather than form adhesive bonds, which is discussed elsewhere herein. Catheter 350 can also include marker band 368, disposed within balloon 356 and secured to inner catheter 354. Catheter 350 may be modified according to any other embodiment herein (e.g., adaptor 360 may be an inner adaptor).

(153) FIG. 24 illustrates a portion of exemplary catheter 370, which includes outer catheter 371, inner catheter 372, balloon 373, adaptor 374, support sheath/collar 375, and distal collar 376. Proximal collar 375 may create a compression bond at the proximal end of balloon 373, while distal collar 376 may form a compression bond at the distal end of balloon 373. Distal collar 376 overlaps balloon 373 and inner catheter 371.

(154) FIG. 25 illustrates a portion of exemplary catheter 380, which includes outer catheter 382, inner catheter 381, balloon 383, adaptor 384, proximal annular collar 385, and distal annular collar 386. Proximal collar 385 may create a compression bond at the proximal end of balloon 383, while distal collar 386 may form a compression bond at the distal end of balloon 383. In FIG. 25, the collars are annular in form, and do not engage catheter surfaces other than the balloon. The proximal and distal collars in FIGS. 24 and 25 may be used interchangeably with each other (e.g., one collar that only interfaces the balloon, with one collar that overlaps the outer or inner shaft).

(155) Any of the balloons herein may comprise a latex, a urethane, a polyurethane, and/or a nylon material.

(156) Any of the balloons herein that include a silicone material may comprise a silicone co-polymer, may include more than one silicones, and/or may include latex and a silicone.

(157) Any of the adaptors herein may comprise PET, or consist essentially of PET. Any of the collars and sheaths herein may comprise PET, or consist essentially of PET.

(158) Any of the catheters herein can be used in any method or any one or more steps described in U.S. Pat. No. 9,844,383, which is fully incorporated by reference herein for all purposes.

(159) Some catheters may include a hub disposed at a proximal region of the catheter. Some hubs may have one or more fluid ports that allow the delivery of fluid through the hub and into one or

more sections of the catheter. Some hubs may be relatively very stiff compared to one or more catheter shaft sections that extend distally relative to the hub. Some catheters may include a strain relief extending from the hub and over a proximal section of the catheter shaft to reduce kinking at the hub-catheter shaft interface. FIG. 1, for example, illustrates an exemplary catheter **100** that includes Y-hub **110**, strain relief **114** (shown extended further distally that it would be as manufactured to illustrate exemplary inner shaft **112**), and catheter outer shaft **116**. In this exemplary embodiment the catheter includes outer and inner shafts, but any catheters herein may have only a single shaft. Hub **110** includes a first port (proximal in this example) that allows fluid to be delivered into a central lumen within inner shaft **112**, and second port **128** (lateral in this example) that is in communication with a volume between the inner and outer shafts and with an interior of inflation balloon **120**.

(160) At catheter hub junctions, differences in the flexibilities of different components may create a kink point and increase a tendency of the catheter to kink at that location. Some commonly used catheters are typically flexible along the entire length and are not likely to kink, with the exception of the catheter and hub interface. In this instance, commonly used strain reliefs between the rigid plastic hub to the flexible catheter are conical shaped rubber or like materials, such as conical strain relief **114** in FIG. 1, that have a flexibility in between that of the rigid plastic hub and the proximal catheter section and provide a way to reduce catheter damage at this interface. Catheters herein are examples of catheters that may include a more rigid or brittle proximal section that has more of a tendency to kink, whereby the common conical shaped strain relief (such as relief **114** in FIG. 1) may be adequate to substantially relieve a kink point at this junction.

(161) It may thus be beneficial or even necessary to provide for a variable transition in flexibility at the hub—catheter interface region.

(162) In some embodiments, the disclosure herein includes a conical shaped strain relief can be combined with a variable transition zone to configure a two-stage transition zone. FIG. 27 illustrates schematically an example of catheter **450** with a two-stage transition zone. Catheter **450** includes a conical shaped strain relief **460** combined with a variable transition zone, shown generally as region “B,” indicated by the vertical striped region, to configure a two-stage transition zone at the hub-catheter interface region. In this embodiment the proximal end of the two stage transition zone is mechanically connected to hub **458** and the distal end of the two stage transition zone is affixed or slidably placed over the proximal region of catheter shaft **452**, which may be an outer catheter shaft if the catheter includes more than one shaft, or which may be the sole shaft of the catheter.

(163) The strain relief **460** may be made from rubber, latex, polyethylene, polyurethane, polyamide, polystyrene or any material that is more flexible than the rigid hub **458**. Strain relief **460** may have a length in the range of 1 cm to 7 cm, optimally 2 cm to 5 cm.

(164) Catheter **450** includes variable transition zone B (which includes regions C and D, and the region within strain relief **460**). The variable transition zone in some embodiments may be in the form of a tubular member that slides over the proximal outer catheter and has a flexibility at its proximal end similar to that of the conical strain relief **460** and at its distal end a flexibility substantially similar to or the same as that of the proximal catheter shaft **452**. The length of the variable transition zone B may be between 2 cm and 20 cm, more often between 5 cm and 15 cm. The thickness of the variable transition zone may be in the range 0.05 mm and 0.5 mm, more often between 0.07 mm to 0.25 mm. The variable transition zone may be made of polypropylene, polystyrene, ABS, polyethylene, PEBAX, stainless steel, nitinol, alloys or any commonly used metal. The materials of the variable transition zone or region can be formed in thickness or composition such that there is a variable flexibility along its length or by use of a material that is mechanically altered along its length to produce variable flexibility. There may be two, three, four or many different stages or materials used in a multi-stage transition as described herein. By way of example only, a stainless steel tube may be laser etched along its length creating a progressive

series of notches that increase in frequency from proximal to distal ends as seen in exemplary FIG. 28. As the frequency of notches increase, there is less metal and more flexibility. The frequency of notches may be adjusted such that the flexibility of the proximal end is similar to the flexibility of the material immediately proximal to the variable strain relief and the flexibility of the distal end of the variable strain relief is substantially similar to the flexibility of the material immediately distal to the variable strain relief. The aforementioned two-stage variable transition zone (such as shown in FIG. 27) thereby transitions from a highly rigid plastic hub 458 to a kinkable proximal catheter shaft 452 and substantially prevents kinking of the proximal catheter shaft that is under (or within) the variable transition zone and at the junction of the variable transition zone and proximal catheter shaft. Thereby, the conical strain relief (such as relief 460 in FIG. 27) substantially prevents a kink between the hub 458 and the variable transition zone, and the variable transition zone prevents a kink in the proximal catheter shaft at the junction between the variable transition zone and the proximal catheter shaft. These are exemplary advantage of the disclosure herein.

(165) In the embodiments herein, the catheter may include one or more shafts. While the shaft that forms a junction with the variable transition zone may be referred to herein as an “outer” shaft, that does not necessarily require an inner shaft within the outer shaft. The catheters herein may thus only have one shaft, and may include a lumen therethrough.

(166) As set forth above, the variable transition zone of catheter 450 may include a variable flexibility strain relief member 456 (which may also be referred to as a strain relief or strain relief member), which may be in the form of a tube. FIG. 27 illustrates merely exemplary and illustrative length of sections of different components of a catheter, which are not meant to be limiting. In FIG. 27, the catheter includes a conical strain relief 460 (another example of which shown in FIG. 29), which may also be incorporated into catheter 400 in FIG. 26, but which is not shown in FIG. 26 for clarity. Strain relief 456 has a proximal region that extends into hub 458, and extends distally from hub 458 and around shaft 452, and has a distal end just distal to the “D” region or zone in FIG. 27. Outer strain relief 460, which has a conical portion, may have a proximal end that is disposed around a distal end of hub 458, and may extend distally from hub 458 and around catheter shaft 452. That is, strain relief 456 extends through outer strain relief 460, and may be considered an “inner” strain relief in this and other similar embodiments.

(167) As set forth above, strain relief 456 may have cuts formed therein that increase in frequency in a proximal to distal direction, thereby increasing the flexibility of the tubular member in a proximal to distal direction. The flexibilities can be designed to match or be substantially similar to the flexibility of adjacent components at the junction between the two components. The flexibility may increase between regions C and D.

(168) FIG. 26 illustrates schematically an exemplary proximal region of catheter 400, which includes catheter shaft 402, optional inner catheter shaft 404, variable flexibility strain relief member 406, and hub 408. While not shown for clarity, catheter 400 can include a conical strain relief as well, which together with strain relief 406 can create a multi-stage variable flexibility region. It is understood that inner shaft 404 is optional and the catheter may have a single catheter shaft, such as shaft 402, which may extend further proximally into hub than as shown. The hub includes an inner lumen 409 extending axially therethrough, as shown by the hashed lines. Strain relief member 406 includes a distal end 410 and a proximal end 412 that is inside hub 408. Strain relief member 406 extends around a portion of shaft 402. A location 430 at which the catheter may be susceptible to kinking is also illustrated. Location 420, which is immediately distal to the distal end of strain relief member 406, may also be susceptible to kinking due to the junction between components and differences in flexibility.

(169) A significant aspect of the variable transition zone is that the flexibility of the variable transition zone is not constant along its entire length. Stated alternatively, the flexibility varies along its length. This allows the strain relief members herein to be designed to have desired flexibilities in different sections along its length. The flexibility of the strain relief member at any

location along its length can this be designed based on the need. As used in some embodiments herein, the strain relief member may have a flexibility at any particular axial location that is the same or substantially similar to an additional catheter component immediately adjacent to the strain relief member. This may be referred to generally herein as matching or substantially matching flexibilities of adjacent catheter components. Designing components that have similar, the same, or substantially the same flexibilities reduces the likelihood of kinking at the interface between those components. For example, in a region of an inner strain relief that is just distal to an outer strain relief distal end, the inner strain relief member may have a flexibility substantially the same as the outer strain relief. Additionally for example, a distal end or distal end region (e.g., **410**) of a strain relief member **406** that is disposed around a catheter shaft may have a flexibility that is the same or substantially similar to the catheter shaft **402**. In FIG. **26**, for example, this can eliminate or reduce the amount of kinking at location **420**, for example. The variation in flexibility along the length of the strain relief can thus be designed to reduce the likelihood of or even eliminate kinking at one of more regions of the proximal end region of the catheter, depending on the materials of the other components in the catheter.

(170) The disclosure herein may use the phrases variable flexibility member and strain relief member interchangeably. Additionally, any of the strain relief members herein (e.g., **406**) may also be referred to as a strain relief.

(171) The flexibility of the variable flexibility members herein may be designed to be varied in a wide number of ways. For example only, variable flexibility members may have a plurality of discrete sections along its length with different flexibilities. Additionally, some sections may have continuously varying flexibilities along at least some portion of its length. The flexibility at any location along its length can theoretically be designed to satisfy any design need or preference. Any of the lengths of the different flexibility regions can also be designed as needed to satisfy any design need or preference.

(172) As used herein, flexibilities that are substantially the same or substantially similar to are intended to refer to flexibilities that are designed to be substantially similar so as to reduce or eliminate kinking at a particular junction location.

(173) The variation in flexibility may be created during manufacture using a variety of techniques. For example, in some embodiments the variation in flexibility can be created by making one or more cuts in a tubular member (e.g., using laser etching), with the cuts made in a manner to impart the desired flexibility. Laser cutting tubular members is generally known, and any techniques for making such cuts can be used to create tubular strain relief members with variable flexibility, and are incorporated by herein by reference.

(174) Alternative ways to create variable flexibility in the strain relief may include using regions of axially spaced polymeric material with different durometer. For example, a strain relief member may include discrete regions of polymeric material, each with a different durometer (D) to create a variable flexibility along its length. For example, higher durometer materials could be more proximally located, with lower D materials may be distal. It is understood that the concepts herein related to cutting a tubular member can similarly be applied to polymeric tubular sections.

(175) In any of the embodiments herein the variable flexibility member has a flexibility that is not constant along its entire length. In some merely exemplary embodiments, the flexibility increases in a distal direction. This does not suggest it needs to continuously increase, but rather that it does not increase in a distal direction. The flexibility may vary in any desired manner, such as stepwise increase in multiple segments, or having one or more segment in which the flexibility continuously increases. In other uses, the flexibility may increase or decrease between sections in any section as desired.

(176) The strain reliefs herein, such as **456** and **406**, may be made from a variety of suitable materials that can impart the desired properties. In some merely exemplary embodiments, the strain relief may comprise a stainless steel tubular member. In some embodiments, the strain relief may

comprise one or more polymeric members, which may be adhered together using known techniques.

(177) FIG. **28** illustrates merely exemplary axial sections of an exemplary strain relief **500**, illustrate merely some exemplary ways to change flexibility in different sections of a tubular member by creating cuts in the tubular member. These exemplary cut patterns may include generally spiral cut separated by discontinuities. For example, exemplary section **504** shown in FIG. **28** includes a first cut with a first end **511** and second end **512**, with a section of tubular member in between that cut and the next cut (not labeled). By varying the cut pattern (e.g., pitch, axial spacing of cuts, etc.), desired flexibilities can be imparted to the strain relief. In FIG. **28**, region **502** is free of cuts, and is a solid tube and relatively stiff, compared to sections **504**, **506**, **508** and **510**, which are distal to section **502**. Section **502** may be disposed in any of the relatively rigid (e.g., plastic) hubs herein. Section **510** may be a distal most region of any of the strain reliefs herein (e.g., **406**, **465**, etc.). Any of the sections in FIG. **28** may have any desired length.

(178) In some merely exemplary embodiments, the strain relief (other than an outer strain relief) includes at least three axially spaced regions of different flexibility with a plurality of cuts made therein. At least a portion of a first region may be disposed within an outer strain relief. At least a portion of a second region may extend distal to an outer strain relief. The third region may include a distal end of the strain relief. In some embodiments the strain relief may include a fourth region that includes a proximal end region, which may be stiffer than the other three sections and may be free of cuts formed therein (e.g., section **502** in FIG. **28**).

(179) A first section may be a solid tube, such as section **502** in FIG. **28**. In some embodiments the first section may have a length from 0.2 inches to 1 inch, such as 0.3 inches to 0.9, such as 0.4 inches to 0.8 inches, such as 0.5 to 0.7 inches. The first section may be at least partially disposed in a hub, and can be secured relative thereto.

(180) A second section may be distal to the first section. The second section may have a length from 0.4 inches to 2 inches, such as 0.5 inches to 1.5 inches. At least a portion of the second section may be disposed within an outer strain relief (e.g., **460**). The second section may be a transition section with a pitch that transitions from a second section proximal end to a second section distal end. In merely exemplary embodiments, the pitch may transition from between 0.005-0.015 inches at a proximal end to 0.001 inches-0.009 inches at a distal end, and may be cut at an angle between 5 and 35 degrees.

(181) A third section may be distal to the second section. The third section may have a length from 1.5 inches to 3.5 inches, such as 1.75 inches to 3 inches. At least a portion of the third section may be disposed distal to an outer strain relief (e.g., **460**). The third section may have a pitch that does not vary from a third section proximal end to a third section distal end, and may be between 0.001 inches to 0.01 inches, for example without limitation.

(182) A fourth section may be distal to the third section. The second section may have a length from 0.3 inches to 1 inch. At least a portion of the fourth section may be disposed distal to an outer strain relief (e.g., **460**). The fourth section may be a transition section with a pitch that transitions from a fourth section proximal end to a fourth section distal end. In merely exemplary embodiments, the pitch may transition from between 0.001-0.01 inches at a proximal end to 0.001 inches-0.007 inches at a distal end.

(183) In merely exemplary embodiments, an outer diameter of strain reliefs herein (other than an outer strain reliefs) are from 0.02 inches and 0.07 inches. In merely exemplary embodiments, an inner diameter of strain reliefs herein (other than an outer strain reliefs) are from 0.01 inches and 0.05 inches.

(184) Any of the materials and flexibilities described herein with respect to catheter and catheter shafts are incorporated herein into any of the embodiments describing strain relief members. Thus, the description related to matching flexibilities or stiffness can incorporate any of the flexibilities from those shaft sections.

(185) In some embodiments herein, the strain relief members (other than “outer” strain relief members such as **460**) have proximal ends that are secured relative to the hub, but have distal ends that are not secured to the catheter shaft. This can provide the advantage of allowing the distal end of the strain relief to float freely over the catheter shaft. This may be beneficial when it is not desirable to limit the amount of relative movement between the catheter shaft and the strain relief. Coupling the distal end of the strain relief and the catheter shaft may undesirably create a kink point. The proximal end of the strain relief may be secured within the hub using any number of techniques, such as bonding, glued, etc.

(186) The strain reliefs herein may have variable flex sections with characteristics other than those described herein. For example, sections from proximal to distal could be relatively stiff-more flex-relatively stiff-more flex. These are merely exemplary illustrations.

(187) The tubular strain reliefs herein may be anywhere along the catheter length where the catheter may be susceptible to kinking.

(188) In alternative embodiments, the catheter may exclude an outer strain relief (e.g., conical strain relief **114**), but may still include a strain relief member between the catheter shaft and the hub to reduce or prevent kinking at the hub catheter interface. It is thus understood that embodiments herein may exclude an outer strain relief (such as strain relief **114**), but still include a variable transition zone, examples of which are described herein.

(189) Any of the disclosure related to FIGS. **26-29** may be incorporated with any catheter feature or method of use in any other part of the disclosure herein, including in any of FIGS. **1-25**.

(190) In any of the embodiments, herein, the distal end of the strain relief (other than “outer” strain reliefs) may have a flexibility that is substantially the same flexibility as the catheter shaft at that junction, and a proximal region has a flexibility that is approximately the same flexibility as the distal end of the second (outer) strain relief at that junction so as to reduce or eliminate kink points at the respective locations. The flexibility of the strain relief member can vary in between those locations.

(191) FIG. **29** illustrates an exemplary proximal region of an exemplary catheter **600**, including outer strain relief **602** (which includes a conical section), hub **604**, a proximal end of strain relief **606** with the proximal end extending into and secured to hub, exemplary catheter shaft **608**, and exemplary catheter shaft **610**. It is fully understood that the catheter **600** may include only a single shaft, which can have a proximal end secured within hub. Any other aspect or feature of any other catheter herein may be incorporated into catheter **600**, and vice versa.

(192) When a feature or element is herein referred to as being “on” another feature or element, it can be directly on the other feature or element or intervening features and/or elements may also be present. In contrast, when a feature or element is referred to as being “directly on” another feature or element, there are no intervening features or elements present. It will also be understood that, when a feature or element is referred to as being “connected”, “attached” or “coupled” to another feature or element, it can be directly connected, attached or coupled to the other feature or element or intervening features or elements may be present. In contrast, when a feature or element is referred to as being “directly connected”, “directly attached” or “directly coupled” to another feature or element, there are no intervening features or elements present. Although described or shown with respect to one embodiment, the features and elements so described or shown can apply to other embodiments. It will also be appreciated by those of skill in the art that references to a structure or feature that is disposed “adjacent” another feature may have portions that overlap or underlie the adjacent feature.

(193) Terminology used herein is for the purpose of describing particular embodiments only and is not intended to be limiting of the disclosure. For example, as used herein, the singular forms “a”, “an” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will be further understood that the terms “comprises” and/or “comprising,” when used in this specification, specify the presence of stated features, steps, operations, elements, and/or

components, but do not preclude the presence or addition of one or more other features, steps, operations, elements, components, and/or groups thereof. As used herein, the term “and/or” includes any and all combinations of one or more of the associated listed items and may be abbreviated as “/”.

(194) Spatially relative terms, such as “under”, “below”, “lower”, “over”, “upper” and the like, may be used herein for ease of description to describe one element or feature's relationship to another element(s) or feature(s) as illustrated in the figures. It will be understood that the spatially relative terms are intended to encompass different orientations of the device in use or operation in addition to the orientation depicted in the figures. For example, if a device in the FIGS. is inverted, elements described as “under” or “beneath” other elements or features would then be oriented “over” the other elements or features. Thus, the exemplary term “under” can encompass both an orientation of over and under. The device may be otherwise oriented (rotated 90 degrees or at other orientations) and the spatially relative descriptors used herein interpreted accordingly. Similarly, the terms “upwardly”, “downwardly”, “vertical”, “horizontal” and the like are used herein for the purpose of explanation only unless specifically indicated otherwise.

(195) Although the terms “first” and “second” may be used herein to describe various features/elements (including steps), these features/elements should not be limited by these terms, unless the context indicates otherwise. These terms may be used to distinguish one feature/element from another feature/element. Thus, a first feature/element discussed below could be termed a second feature/element, and similarly, a second feature/element discussed below could be termed a first feature/element without departing from the teachings of the present disclosure.

(196) Throughout this specification and the claims which follow, unless the context requires otherwise, the word “comprise”, and variations such as “comprises” and “comprising” means various components can be co-jointly employed in the methods and articles (e.g., compositions and apparatuses including device and methods). For example, the term “comprising” will be understood to imply the inclusion of any stated elements or steps but not the exclusion of any other elements or steps.

(197) In general, any of the apparatuses and methods described herein should be understood to be inclusive, but all or a sub-set of the components and/or steps may alternatively be exclusive, and may be expressed as “consisting of” or alternatively “consisting essentially of” the various components, steps, sub-components or sub-steps.

(198) As used herein in the specification and claims, including as used in the examples and unless otherwise expressly specified, all numbers may be read as if prefaced by the word “about” or “approximately,” even if the term does not expressly appear. The phrase “about” or “approximately” may be used when describing magnitude and/or position to indicate that the value and/or position described is within a reasonable expected range of values and/or positions. For example, a numeric value may have a value that is $\pm 0.1\%$ of the stated value (or range of values), $\pm 1\%$ of the stated value (or range of values), $\pm 2\%$ of the stated value (or range of values), $\pm 5\%$ of the stated value (or range of values), $\pm 10\%$ of the stated value (or range of values), etc. Any numerical values given herein should also be understood to include about or approximately that value, unless the context indicates otherwise. For example, if the value “10” is disclosed, then “about 10” is also disclosed. Any numerical range recited herein is intended to include all sub-ranges subsumed therein. It is also understood that when a value is disclosed that “less than or equal to” the value, “greater than or equal to the value” and possible ranges between values are also disclosed, as appropriately understood by the skilled artisan. For example, if the value “X” is disclosed the “less than or equal to X” as well as “greater than or equal to X” (e.g., where X is a numerical value) is also disclosed. It is also understood that the throughout the application, data is provided in a number of different formats, and that this data, represents endpoints and starting points, and ranges for any combination of the data points. For example, if a particular data point “10” and a particular data point “15” are disclosed, it is understood that greater than, greater than or

equal to, less than, less than or equal to, and equal to 10 and 15 are considered disclosed as well as between 10 and 15. It is also understood that each unit between two particular units are also disclosed. For example, if **10** and **15** are disclosed, then 11, 12, 13, and 14 are also disclosed. (199) Although various illustrative embodiments are described above, any of a number of changes may be made to various embodiments without departing from the scope of the disclosure as described by the claims. For example, the order in which various described method steps are performed may often be changed in alternative embodiments, and in other alternative embodiments one or more method steps may be skipped altogether. Optional features of various device and system embodiments may be included in some embodiments and not in others. Therefore, the foregoing description is provided primarily for exemplary purposes and should not be interpreted to limit the scope of the disclosure as it is set forth in the claims.

(200) The examples and illustrations included herein show, by way of illustration and not of limitation, specific embodiments in which the subject matter may be practiced. As mentioned, other embodiments may be utilized and derived there from, such that structural and logical substitutions and changes may be made without departing from the scope of this disclosure. Such embodiments of the inventive subject matter may be referred to herein individually or collectively by the term “invention” or “disclosure” merely for convenience and without intending to voluntarily limit the scope of this application to any single invention or inventive concept, if more than one is, in fact, disclosed. Thus, although specific embodiments have been illustrated and described herein, any arrangement calculated to achieve the same purpose may be substituted for the specific embodiments shown. This disclosure is intended to cover any and all adaptations or variations of various embodiments. Combinations of the above embodiments, and other embodiments not specifically described herein, will be apparent to those of skill in the art upon reviewing the above description.

Claims

1. A catheter with a proximal variable transition zone, comprising: a hub disposed at a proximal region of the catheter, the hub including one or more fluid ports; a catheter shaft disposed within an internal volume of the hub, the catheter shaft in fluid communication with a first of the one or more fluid ports, the catheter shaft extending further distally than the hub; a first strain relief member disposed about a distal end of the hub and extending distally beyond the hub, the catheter shaft extending within the first strain relief member and further distally than the first strain relief member; a second strain relief member with a proximal end disposed within the internal volume of the hub, the second strain relief member extending distally through the first strain relief member and extending distally beyond the first strain relief member, the second strain relief member disposed around the catheter shaft, the catheter shaft extending further distally than the second strain relief member, and the second strain relief member having a distal end and a length, the second strain relief member having a variable flexibility along at least a portion of its length, the second strain relief member having a flexibility where it extends from a distal end of the first strain relief member that is less than a flexibility of the distal end of the second strain relief member.
2. The catheter of claim 1, wherein the proximal end of the second strain relief member is secured relative to the internal volume of the hub, and wherein the distal end of the second strain relief member is not adhered to the catheter shaft such that the distal end of the second strain relief member is free to move relative to the catheter shaft.
3. The catheter of claim 1, wherein the flexibility of the distal end of the second strain relief member substantially matches a flexibility of the catheter shaft at a location of the distal end of the second strain relief member.
4. The catheter of claim 3, wherein the flexibility of the second strain relief member where it extends from the distal end of the first strain relief member is the same or substantially similar to a

flexibility of the distal end of the first strain relief member, the flexibility of the second strain relief member where it extends from the distal end of the first strain relief member and the flexibility of the distal end of the first strain relief member being the same or substantially similar so as to reduce kinking between the first strain relief member and the second strain relief member.

5. The catheter of claim 1, wherein the flexibility of the distal end of the second strain relief member is the same or substantially similar to a flexibility of the catheter shaft where the catheter shaft extends from the distal end of the second strain relief member, the flexibility of the distal end of the second strain relief member and the flexibility of the catheter shaft being the same or substantially similar so as to reduce or prevent kinking between the second strain relief and the catheter shaft.

6. The catheter of claim 1, wherein an amount of kinking of the catheter shaft at a location immediately distal to the distal end of the first strain relief member is less than a degree of kinking that would occur in the absence of the second strain relief member.

7. The catheter of claim 1, wherein the proximal end of the second strain relief member includes a solid tubular member.

8. The catheter of claim 1, wherein the second strain relief member includes a plurality of cuts formed therein.

9. The catheter of claim 8, wherein the plurality of cuts impart more flexibility in a distal region of the second strain relief member than in a proximal region of the second strain relief member.

10. The catheter of claim 1, wherein the second strain relief member has a plurality of cuts formed therein, the distribution of the cuts providing a distal section with a flexibility that is greater than a flexibility in the proximal section.

11. The catheter of claim 1, wherein the second strain relief member is more flexible in a distal section that includes the distal end than in a proximal section that includes the proximal end.

12. The catheter of claim 1, wherein the second strain relief member has a first section with a first flexibility and a second section with a second flexibility, the second section distal to the first section and more flexible than the first section.

13. The catheter of claim 12, wherein the second section is distal to the hub, and the first section is disposed at least partially within the hub.

14. The catheter of claim 13, wherein the second strain relief member has a third section with a third flexibility, the third section being distal to the second section, the third section being more flexible than the second section.

15. The catheter of claim 13, wherein the third section has a gradient flexibility, with increasing flexibility in a distal direction.

16. The catheter of claim 12, wherein the first section has a gradient flexibility.

17. The catheter of claim 1, wherein the second strain relief member comprises a cylindrical body.

18. The catheter of claim 1, wherein the first strain relief member comprises a conical section.

19. The catheter of claim 1, wherein the second strain relief member has four or more sections, each of which has a flexibility profile that is different than each of the other sections.

20. The catheter of claim 1, wherein the second strain relief member comprises stainless steel.
