

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12409857
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Pohl; Christopher et al.

Safety module for a safe drive control of a drive system in an automation system, drive system and automation system

Abstract

A safety module for a secured drive control of an automated drive system is configured to receive encoder data sent from an encoder unit to a drive unit, based on an encoder protocol via a protocol active unit. The safety module is configured to forward the encoder data from the protocol active unit to a safety logic and a protocol passive unit, check the forwarded encoder data with the aid of the safety logic for correspondence with predetermined safety criteria relating to operation of a motor unit, and transmit the forwarded encoder data via the protocol passive unit to the drive unit, in respective data packets based on the encoder protocol. The safety module can stop operation of the motor unit with the aid of the safety logic, if the encoder data does not correspond to the predetermined safety criteria. A corresponding drive system and automation system are also provided.

Inventors: Pohl; Christopher (Verl, DE), Kathöfer; Andreas (Rietberg, DE), Sieweke; Frank (Leopoldshöhe, DE), Zutz; Robert (Verl, DE)

Applicant: Beckhoff Automation GmbH (Verl, DE)

Family ID: 74673201

Assignee: Beckhoff Automation GmbH (Verl, DE)

Appl. No.: 17/883036

Filed: August 08, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20220388541 A1	Dec. 08, 2022

Foreign Application Priority Data

DE	10 2020 104 230.2	Feb. 18, 2020
----	-------------------	---------------

Related U.S. Application Data

continuation parent-doc WO PCT/EP2021/053974 20210218 PENDING child-doc US 17883036

Publication Classification

Int. Cl.: B60W60/00 (20200101); B60W40/12 (20120101)

U.S. Cl.:

CPC B60W60/0015 (20200201); B60W40/12 (20130101); B60W2510/0657 (20130101); B60W2554/4041 (20200201)

Field of Classification Search

CPC: B60W (60/0015); B60W (40/12); B60W (2554/4041); B60W (2510/0657)

USPC: 701/23

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7868619	12/2010	Kangas	N/A	N/A
8659254	12/2013	Jeno	N/A	N/A
8969789	12/2014	Sato	250/214R	G01D 5/24466
10184860	12/2018	Schweikert et al.	N/A	N/A
10298166	12/2018	Matsumura et al.	N/A	N/A
2010/0164423	12/2009	Nakayama	318/446	G05B 19/0425
2019/0226450	12/2018	Theopold	N/A	G05B 19/048
2021/0234364	12/2020	Kishida et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
110463029	12/2018	CN	N/A
102017104015	12/2016	DE	N/A
2367086	12/2010	EP	N/A
2639556	12/2012	EP	N/A
3023846	12/2015	EP	N/A
3388906	12/2017	EP	N/A
2017167704	12/2016	JP	N/A
2019239753	12/2018	WO	N/A

OTHER PUBLICATIONS

International Search Report and Written Opinion dated May 27, 2021 in connection with International Patent Application No. PCT/EP2021/053974, 21 pages including English translation. cited by applicant

International Preliminary Report on Patentability dated May 31, 2022 in connection with International Patent Application No. PCT/EP2021/053974, 35 pages including English translation. cited by applicant

Office Action dated Dec. 22, 2020 in connection with German patent application No. 10 2020 104 230.2, 15 pages including English translation. cited by applicant

Beckmann, Guido, "Safety over EtherCAT Overview," EtherCAT Technology Group, Dec. 2019, 41 pages. cited by applicant

Office Action dated Dec. 9, 2022 in connection with European patent application No. 21707199.2, 80 pages including English translation. cited by applicant

English translation of Apr. 12, 2023 Office Action received in connection with Taiwanese patent application No. 202180014969.2, 3 pages. cited by applicant

Translation of Japanese Patent Publication No. JP2017167704A, Isoda Kokichi, Brother Ind Ltd, published Sep. 21, 2017. cited by applicant

Primary Examiner: Young; Tiffany P

Assistant Examiner: Dowling; Michael T

Attorney, Agent or Firm: Dorsey & Whitney LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This patent application claims the priority of International Patent Application No. PCT/EP2021/053974, filed Feb. 18, 2021, entitled "Safety Module for a Safe Drive Control of a Drive System in an Automation System, Drive System and Automation System," which claims priority to German patent application DE 10 2020 104 230.2, filed Feb. 18, 2020, entitled "Sicherheitsmodul für eine gesicherte Antriebssteuerung eines Antriebssystems in einem Automatisierungssystem, Antriebssystem and Automatisierungssystem," each of which is hereby incorporated by reference, in the entirety and for all purposes.

FIELD

(1) The present application relates to a safety module for a safe drive control of a drive system in an automation system. The application further relates to a drive system with a safety module. The application further relates to an automation system comprising a drive system having a safety module.

BACKGROUND

- (2) Encoders are usually used to control drive systems, and they are used to generate an electrical signal (encoder signal) that encodes a current position of a motor unit of the drive system. Such encoders may also be referred to as coders. The mechanical movement may in this context e.g. be a translatory or a rotatory movement.
- (3) Absolute measuring encoders are known which generate electrical signals indicating an absolute value of a position. In addition, incremental encoders exist that generate signals indicating a change in a position compared to a previous position.
- (4) Based on the position information of the motor unit by the encoder, accessing the motor unit with the aid of a drive unit is possible.
- (5) In the state of the art, data communication between a drive unit and the encoder unit of the drive system is usually implemented via encoder interfaces which implement data exchange between drive units and encoder units according to corresponding encoder protocols. Encoder protocols are

data communication protocols specialized for data communication between drive units and encoder units, which are set up for high-frequency data exchange of encoder data with cycle times in the microsecond range.

(6) In order to use drive systems in automation systems, the drive systems must meet certain specifications with regard to the safety of the drive systems used. For example, for electric drives in automation systems, the standard IEC 61800-5-2:2016 defines certain safety-related functions such as Safe Torque Off (STO), Safe Stop 1 (SS1), Safe Stop 2 (SS2), Safe Operation Stop (SOS), Safe Limited Speed (SLS), Safe Speed Monitor (SSM), Safe Speed Range (SSR), Safe Limited Position (SLP), Safe Position (SP), Safe Direction (SD) or Safe Brake Control, Safe Brake Test (SBC, SBT), which are provided to ensure safe operation of electrical drive units and prevent damage to personnel and machines. Depending on the use of the drive units, these may be assigned to different safety requirement levels and fewer, more or possibly different safety requirements may be placed on them.

(7) Safety functions or safety-relevant functions are functions of drive systems. Safety requirements are requirements that are placed on drive systems in order to meet certain specifications. The requirements may comprise that the respective drive systems have a certain number of different safety functions. This may depend on the areas in which the drive systems in question are used. Depending on the type and use of the drive systems, these may be assigned to corresponding safety requirement levels, each of which differs in the safety requirements imposed.

(8) Safety encoders or safety encoder interfaces, such as Hiperface DSL Safety and EnDat 2.2 Safety, are known in the state of the art and allow for safe operation of drive systems and fulfillment of corresponding safety requirements.

(9) Such safety encoders or safety encoder interfaces provide comprehensively safe operation of corresponding drive systems and ensure reliable position information of the respective motor systems and secure data transmission channels for reliable data transmission. However, safety encoder interfaces are technically complex and costly, making them unattractive for certain applications. In addition, retrofitting drive components for which such safety concepts were not originally intended is also technically complex and costly.

(10) Safety concepts are the concepts that are created for automation systems and comprise which requirement in terms of safety the respective automation systems have to fulfill and by which measures these requirements are to be met.

(11) In addition, technically simple safety concepts, such as Safe Torque Off modules, are known in the prior art, which may be integrated into drive systems and may fulfill certain safety requirements. However, such safety concepts are only suitable for simple safety requirements and are not capable of ensuring comprehensively safe operation of drive systems.

(12) Thus, a demand exists for compatible safety concepts that enable comprehensively safe operation of drive systems and fulfill comprehensive safety requirements, comparable to safety encoders or safety encoder interfaces known from the state of the art.

SUMMARY

(13) The application provides a safety module that allows for safe drive control of a drive system in an automation system. The application further provides a drive system with a safety module. The application also provides an automation system having a drive system with a safety module.

EXAMPLES

(14) A safety module for a safe drive control of a drive system in an automation system is provided, wherein the drive system comprises at least a drive unit, an encoder unit and a motor unit. The safety module may be connected to the drive unit and the encoder unit via at least one data connection, wherein the safety module comprises a protocol active unit, a protocol passive unit and a safety logic, which are set up to communicate with one another via a data communication.

(15) The safety module can be configured to: receive encoder data sent out by the encoder unit to the drive unit on the basis of an encoder protocol in corresponding data packets via the protocol

active unit; forward the received encoder data from the protocol active unit to the safety logic and the protocol passive unit; check the forwarded encoder data, with the aid of the safety logic, for compliance with predetermined safety criteria relating to the operation of the motor unit; send out the forwarded encoder data to the drive unit via the protocol passive unit on the basis of the encoder protocol in corresponding data packets; and cause a stop of the operation of the motor unit via the safety logic, if the encoder data is detected by the safety logic as not conforming to the predetermined safety criteria.

(16) This achieves the technical advantage that a safety module may be provided for secured drive control of a drive system in an automation system, which may be integrated into a drive system that is not operated with a safety encoder interface, the safety module being set up to meet all the requirements of certain safety specifications for corresponding drive systems in automation systems.

(17) The protocol active unit and the protocol passive unit of the safety module allow for the safety module to be integrated into a drive system, in particular between a drive unit and an encoder unit of the drive system, and set up to provide data communication between the drive unit and the encoder unit.

(18) The protocol active unit and the protocol passive unit of the safety module correspond to an active unit and a passive unit of an encoder protocol and an encoder interface, respectively, by which data communication is realized between the drive unit and the encoder unit of the drive system. The protocol active unit of the safety module is set up to provide data communication with the encoder unit on the basis of the encoder protocol used or the encoder interface used. The encoder active unit is furthermore set up so that the encoder protocol or the encoder interface used for data communication between the encoder unit and the drive unit of the drive system does not have to be modified for data communication between the encoder active unit and the encoder unit.

(19) From the point of view of the encoder unit, data communication between the encoder unit and the protocol active unit of the safety module is thus identical to data communication between the encoder unit and the drive unit of the drive system. For this purpose, the protocol active unit receives the encoder data sent out by the encoder unit in accordance with the encoder protocol and forwards it to the protocol passive unit of the safety module.

(20) The protocol passive unit of the safety module is embodied to transmit the forwarded encoder data to the drive unit in accordance with the existing encoder protocol. In this context, the protocol passive unit is set up so that the existing encoder protocol or the existing encoder interface do not have to be changed for data communication between the protocol passive unit and the drive unit. From the point of view of the drive unit, data communication between the drive unit and the protocol passive unit of the safety module is therefore identical to data communication between the drive unit and the encoder unit of the drive system.

(21) The safety module may thus be integrated into an existing data connection between a drive unit and an encoder unit of a drive system without having to change an existing encoder protocol or an existing encoder interface by which data communication between the drive unit and the encoder unit is implemented.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The application is described in more detail with reference to the accompanying figures, which show:

(2) FIG. 1 is a schematic depiction of a safety module according to one embodiment, wherein the safety module is integrated into a drive system;

(3) FIG. 2 is another schematic depiction of a safety module according to a further embodiment,

wherein the safety module is integrated into a drive system;

(4) FIG. 3 is another schematic depiction of a safety module according to a further embodiment, wherein the safety module is integrated into a drive system;

(5) FIG. 4 is another schematic depiction of a safety module according to a further embodiment, wherein the safety module is integrated into a drive system; and

(6) FIG. 5 is a schematic depiction of an automation system with a drive system having a safety module according to one embodiment.

DETAILED DESCRIPTION

(7) In the sense of the application, a data link is set up to provide data communication between communication partners. A data connection may e.g. be implemented via an encoder interface. Alternatively, a data connection may be implemented via a data bus connection. A data connection may be a purely data-related connection. Alternatively, a data connection may comprise a physical component in the form of a corresponding wiring.

(8) For the purposes of the application, an interface is a data link between at least two data communication subscribers, wherein the interface is set up to provide data communication between the at least two data communication subscribers.

(9) Alternatively, different encoder protocols may be used for data communication between the drive unit and the safety module, and the encoder unit and the safety module.

(10) Thus, the protocol active unit of the safety module may communicate with the encoder unit on the basis of an encoder protocol or on the basis of an encoder interface, and the protocol passive unit of the safety module may communicate with the drive unit on the basis of another encoder protocol or on the basis of another encoder interface.

(11) Via the safety logic of the safety module, encoder data sent out by the encoder unit may be checked with respect to predetermined safety criteria. If violations regarding the predetermined safety criteria of the encoder data sent out by the encoder unit are detected, the safety logic of the safety module may cause the operation of the motor unit of the drive system to stop. The safety logic is set up in such a way that all requirements of safety specifications relating to the respective drive type of the drive system may be met.

(12) The safety module thus allows for an existing encoder protocol or for an existing encoder interface to be upgraded to a safety encoder protocol or safety encoder interface that is capable of meeting all the requirements of the relevant safety specifications for the corresponding drive types without having to modify the components of the drive system or the existing encoder protocol or encoder interface.

(13) The safety module according to the application also allows for an existing encoder protocol or for an existing encoder interface to be upgraded to a safety encoder protocol or a safety encoder interface by integrating a hardware component, in the form of the safety module according to the application, into an existing drive system.

(14) According to an embodiment, the safety module is further configured to send out requests for encoder data to the encoder unit through the protocol active unit.

(15) This has the technical advantage of providing effective and efficient data communication between the safety module and the encoder unit of the drive system. By sending requests to send encoder data via the protocol active unit of the safety module to the encoder unit, a sending of corresponding encoder data via the encoder unit to the safety module or to the drive unit of the drive system may be initiated. The protocol active unit of the safety module is set up to initiate data communication with the encoder unit that is identical to data communication between the drive unit and the encoder unit. The protocol active unit is set up to send out requests that are identical to requests that the drive unit would send out to initiate data communication with the encoder unit according to the existing encoder protocol or the existing encoder interface.

(16) In the sense of the application, requests are queries or commands corresponding to the respective used encoder protocols to the encoder unit to perform appropriate functions. This may

comprise, among other things, the sending of encoder data.

(17) For the purposes of the application, encoder data are data of the encoder unit and may comprise further parameter data of the drive unit in addition to position data of the motor unit. Alternatively, encoder data may comprise information of an electronic data sheet of the encoder or information relating to the encoder and/or the motor system. Parameter data may e.g. comprise temperature data, pressure data and/or other data that allow status statements regarding the status of the motor unit.

(18) According to an embodiment, the safety module is further configured to receive requests sent by the drive unit to the encoder unit to send out encoder data via the protocol passive unit; and to send out encoder data corresponding to the requests to the drive unit via the protocol passive unit.

(19) The technical advantage of this is that effective and efficient data communication may be provided between the drive unit and the safety module. For this purpose, the protocol passive unit is set up to receive requests to send encoder data sent out by the drive unit, and the safety module is set up to send out encoder data corresponding to the requests to the drive unit by the protocol passive unit. In this case, the protocol passive unit is configured to perform data communication with the drive unit that is identical to data communication between the drive unit and the encoder unit. The requests sent out by the drive unit correspond to the existing encoder protocol or to the existing encoder interface and are identical to requests sent out by the drive unit to the encoder unit to prompt it to send out corresponding encoder data.

(20) By providing the corresponding encoder data to the drive unit via the safety module, comprehensive data communication may be ensured between the drive unit and the encoder unit via the safety module, in which corresponding encoder data of the encoder unit are exchanged between the drive unit and the encoder unit on the basis of the existing encoder protocol or the existing encoder interface or on the basis of the existing encoder protocols or the existing encoder interfaces for controlling the motor unit by the drive unit.

(21) For this purpose, the protocol passive unit may receive the requests sent out by the drive unit and forward them to the protocol active unit so that the protocol active unit may send out corresponding requests to the encoder unit and drive the encoder unit to send out corresponding encoder data.

(22) According to an embodiment, the safety module further comprises an encoder emulator, wherein the encoder emulator is configured to generate simulated encoder data, and wherein the simulated encoder data corresponds to a simulation of the encoder data of the encoder unit.

(23) This achieves the technical advantage that a flexible and widely applicable safety module may be provided. By generating simulated encoder data that correspond to a simulation of the encoder data of the encoder unit, the safety module is able to provide encoder data independently. In particular, this may achieve the technical advantage that corresponding encoder data may be provided to the drive unit immediately in response to requests to transmit encoder data via the safety module, even in the event, that a forwarding of the request sent by the drive unit via the safety module to the encoder unit and a corresponding sending of encoder data by the encoder unit would lead to a delay in the provision of the encoder data to the drive unit by the safety module and consequently to an error message due to the delayed provision of the requested encoder data by the drive unit.

(24) By providing simulated encoder data to the drive unit with the aid of the safety module, a corresponding error message of the drive unit due to delayed provision of requested encoder data may be prevented. This ensures that, despite integration of the safety module into the drive system, data communication between the drive unit and the encoder unit may be carried out unchanged for both the drive unit and the encoder unit.

(25) Neither the drive unit nor the encoder unit is able to identify the safety module integrated in the drive system and for the drive unit, a data communication with the safety module is identical to a data communication with a safety encoder unit including a safety encoder interface and for the

encoder unit, a data communication with the safety module is identical to a data communication with the drive unit via a corresponding safety encoder interface.

(26) According to an embodiment, the safety module further comprises a memory unit, and wherein the safety module is further configured to store encoder data received by the protocol active unit from the encoder unit and/or simulated encoder data from the encoder emulator in the memory unit. The safety module comprises a processor and a memory unit.

(27) This achieves the technical advantage that effective and efficient data communication may be provided between the safety module and the drive unit or encoder unit. Storing encoder data from the encoder unit or simulated encoder data from the encoder emulator in the memory unit of the safety module ensures that when the drive unit requests the transmission of encoder data, the corresponding encoder data or simulated encoder data stored in the memory unit may be accessed and made available to the drive unit by the safety module.

(28) In this way, real encoder data of the encoder unit may be provided to the drive unit by the safety module by accessing the encoder data stored in the memory unit by the safety module, in particular in the event that corresponding forwarding of the requests of the drive unit to the encoder unit and the transmission of corresponding encoder data by the encoder unit would lead to delays in the provision of corresponding encoder data by the safety module to the drive unit. This is particularly possible if correspondingly queried encoder data of the encoder unit have only a small temporal variance, so that temporally earlier encoder data stored in the memory unit of the safety module have only small or no deviations from current encoder data of the encoder unit.

(29) Similarly, simulated encoder data corresponding to expected encoder data of the encoder unit may be generated by the encoder emulator according to corresponding simulation models and stored in the memory unit. Particularly in the case of temporal variances of the encoder data of the encoder unit that are well covered by corresponding simulation models, reliable encoder data may thus be provided to the drive unit by the safety module without delay. Due to the memory unit, generating simulated encoder data with the aid of the encoder emulator may be performed at times when no collisions with other tasks of the safety module are to be feared. This allows for effective and efficient task processing of the safety module.

(30) According to an embodiment, the encoder data sent out by the protocol passive unit according to the prompts are stored in the memory unit, and/or wherein the encoder data sent out according to the prompts are simulated encoder data from the encoder emulator.

(31) This achieves the technical advantage that the drive unit may immediately be provided with corresponding encoder data via the safety module after it has sent out corresponding requests to send out encoder data. In particular, in the event that forwarding the requests sent by the drive unit to the encoder unit by the safety module and the corresponding transmission of the encoder data by the encoder unit would lead to a delay in the providing the encoder data to the drive unit via the safety module, error-free data communication between the drive unit and the safety module may be achieved by accessing the encoder data or simulated encoder data stored in the memory unit.

(32) According to an embodiment, the safety module is further set up to forward the received requests to send out encoder data by the protocol passive unit to the protocol active unit; and to send out the forwarded requests to the encoder unit via the protocol active unit.

(33) This achieves the technical advantage that effective and efficient data communication between the drive unit and the encoder unit may be provided by the safety module. By forwarding the requests for encoder data sent out by the drive unit through the safety module to the encoder unit, encoder data may be sent out by the encoder unit in accordance with the requests of the drive unit. The safety module is thus able to provide the drive unit with encoder data from the encoder unit corresponding to the transmitted requests. This ensures effective and efficient data communication between the drive unit and the encoder unit via the safety module.

(34) According to an embodiment, the safety module may further be synchronized with the drive unit, wherein the safety module is arranged to send out corresponding requests via the protocol

active unit to the encoder unit synchronously to sending out requests for encoder data by the drive unit.

(35) This achieves the technical advantage that undelayed data communication between the drive unit and the encoder unit may be provided by the safety module. By synchronizing the safety module and the drive unit, it may be achieved that the drive unit and the safety module send out corresponding requests for encoder data at the same time or with a corresponding delay, wherein the safety module sends the requests directly to the encoder unit. This means that undelayed data communication between the drive unit and the encoder unit may be moderated by the safety module. By synchronously sending out the same requests via the drive unit and the safety module, a delay in the provision of corresponding encoder data by the safety module to the drive unit may be prevented. This allows for effective, efficient and error-free data communication between the drive unit and the safety module.

(36) According to an embodiment, the safety module may further be connected to the drive unit via a data bus connection, wherein the safety module is arranged to send out to the drive unit, for causing a stop of the operation of the motor unit via the safety logic, a corresponding operation stop message based on a safety-related data packet according to a safe data bus protocol of the data bus connection.

(37) This achieves the technical advantage that safe data communication may be provided between the safety module and the drive unit to effect a stop of the operation of the motor unit of the drive system. For this purpose, the safety module is set up to send a corresponding operation stop message to the drive unit via a safety-relevant data bus connection between the safety module and the drive unit in order to thus bring about a stop of the motor unit.

(38) The safety-relevant data bus connection or corresponding safety-relevant data packets of a data bus protocol of the data bus connection may provide a safe transmission of the operation stop message from the safety module, in particular from the safety logic, to the drive unit. Thus, requirements of corresponding safety specifications may be fulfilled. The safety-relevant data bus connection between the drive unit and the safety module allows for safe and fast data communication for transmitting corresponding operational stop messages between the drive unit and the safety module.

(39) For the purposes of the application, a safety-relevant data packet is a data packet of a data communication protocol that is provided with features that ensure that the safety-relevant data packet meets all requirements for safe data communication. An example of such a data communication protocol or for corresponding safety-relevant data packets would be the Safety-over-EtherCAT protocol known from the prior art.

(40) According to an embodiment, the safety module is further connectable to a safe-torque-off function of the drive unit, wherein the safety module is arranged to cause the safety logic to send a corresponding safe-torque-off message to the safe-torque-off function of the drive unit to cause the safe-torque-off function to stop operation of the motor unit.

(41) This achieves the technical advantage that a technically simple solution for bringing about a stop in the operation of the motor unit may be provided by the safety module. In particular for drive systems that do not have a safety-relevant data bus connection, a reliable and technically simple solution for bringing about an operational stop of the motor unit by the safety module may be provided by triggering a safe torque-off function of the drive unit by the safety module. The safety module may in this context be connected to a safe-torque-off function of the drive unit and is set up to send a corresponding safe-torque-off message to the safe-torque-off function in order to trigger the safe-torque-off function and cause an operational stop of the motor unit.

(42) According to an embodiment, the safety module is further connectable to a shutdown mechanism integrated into a control connection between the drive unit and the motor unit, wherein the safety module is configured to trigger the shutdown mechanism to cause the safety logic to stop operation of the motor unit, and wherein the shutdown mechanism is embodied to interrupt the

control connection.

(43) This achieves the technical advantage that a technically simple and reliable solution may be provided for bringing about an operational stop of the motor unit by the safety module. In particular for drive systems that do not have a safety-relevant data bus connection or do not have drive units with a safe torque-off function, the control connection may be interrupted by triggering a shutdown mechanism installed in a control connection between the drive unit and the motor unit, thus bringing about an operational stop of the motor unit by the safety module. For this purpose, the safety module may be connected to the shutdown mechanism and is set up to trigger the shutdown mechanism to bring about the operational stop of the motor unit.

(44) For the purposes of the application, a control connection is a data connection or an electrical connection between the drive unit and the motor unit via which the motor unit may be controlled by the drive unit. Alternatively, a control connection may be implemented exclusively via an electrical connection to the voltage supply of the motor unit.

(45) According to an embodiment, the shutdown mechanism comprises at least a contactor unit.

(46) This provides the technical advantage of a technically simple and reliable shutdown mechanism. Alternatively, the shutdown mechanism may comprise a plurality of contactor units.

(47) For the purposes of the application, a contactor unit is a power contactor, a relay unit or a comparable switching element.

(48) According to an embodiment, the safety module may be connected to another encoder unit of the drive system, and wherein the safety module is configured to: receive further encoder data sent out by the further encoder unit to the drive unit based on the encoder protocol in corresponding data packets via the protocol active unit; forward the received further encoder data from the protocol active unit to the safety logic; check the forwarded encoder data of the encoder unit, taking into account the forwarded further encoder data of the further encoder unit, with the aid of the safety logic for compliance with the predetermined safety criteria; and to cause a stop of the operation of the motor unit by the safety logic, if the encoder data has been recognized by the safety logic as not conforming to the predetermined safety criteria, taking into account the further encoder data.

(49) This achieves the technical advantage that the safety module according to the application may be connected to and operated with two different encoder units. Hereby, a safety encoder, the encoder data of which comprise at least a first position datum and a second position datum, and which are provided for safety checking of the safety logic of the safety module, may be replaced by two independent encoder units, one encoder unit generating a first position datum and the other encoder unit generating a second position datum, which are provided for safety checking of the safety logic of the safety module.

(50) This provides the technical advantage that two more cost-effective simple encoder units may be used instead of a cost-intensive safety encoder in order to meet the requirements of the respective safety specifications with regard to the drive type of the respective drive system. For this purpose, encoder data from one encoder unit are interpreted as the first position datum and encoder data from the other encoder unit is interpreted as the second position datum, which is used for safety analysis by the safety logic. The protocol active unit of the safety module is set up to perform data communication with the one encoder unit and the other encoder unit.

(51) According to an embodiment, the encoder data and/or the further encoder data comprise position data and/or parameter data of the motor unit, wherein the position data describe at least one position of the motor unit, and wherein the parameter data describe at least one parameter of the motor unit different from the position, which parameter allows for a status assessment of the motor unit.

(52) This achieves the technical advantage that in addition to position data describing a position of the motor unit, parameter data providing status-relevant information regarding the motor unit may also be taken into account for safety analysis by the safety logic of the safety module. This allows

for a comprehensive assessment of the safety situation of the motor unit by the safety module. Parameter data may comprise any status-relevant information of the motor unit, e.g. temperature, pressure, speed, acceleration and other relevant information that may be of interest for a description of the status of the motor unit.

(53) According to an embodiment, the safety criteria include a maximum position and/or a maximum speed and/or a maximum acceleration and/or a maximum temperature of the motor unit.

(54) This achieves the technical advantage that a comprehensive and detailed assessment of a safety status of the engine unit may be achieved. Due to the specific safety criteria, a specified and detailed assessment of the safety status of the motor unit may be achieved and requirements for correspondingly specified safety specifications may be met.

(55) A drive system comprising at least a drive unit, an encoder unit, a motor unit, and a safety module according to the application is provided, wherein the drive unit and the encoder unit are interconnected via a data link and are arranged to communicate via an exchange of data packets according to an encoder protocol, wherein the safety module is connected to the drive unit and the encoder unit via the data link, and wherein the drive unit is connected to the motor unit via a control link for controlling the motor unit.

(56) By this, the technical advantage is achieved that a drive system with the advantages of the safety module according to the application may be provided.

(57) An automation system comprising a control unit and at least one drive system according to the application is provided, wherein the drive system is connected to the control unit via a data bus connection, wherein the control unit is arranged to control the drive system according to the application.

(58) This achieves the technical advantage that an automation system with a drive system may be provided with the advantages of the safety module according to the application.

(59) FIG. 1 shows a schematic depiction of a safety module **100** according to an embodiment in which the safety module **100** is integrated into a drive system **107**.

(60) According to the embodiment in FIG. 1, the drive system **107** in an automation system comprises at least a drive unit **109**, an encoder unit **111** and a motor unit **113**. The safety module **100** is connected to the drive unit **109** and the encoder unit **111**, and thus indirectly also to the motor unit **113** via an encoder interface **102**. The safety module **100** comprises a protocol active unit **101**, a protocol passive unit **103**, and a safety logic **105** that are arranged to communicate with one another by data communication. The safety module **100** is embodied to: receive the encoder data sent out from the encoder unit **111** to the drive unit **109** on the basis of an encoder protocol via the protocol active unit **101**; forward the received encoder data from the protocol active unit **101** to the safety logic **105** and the protocol passive unit **103**; check the forwarded encoder data for compliance with predetermined safety criteria relating to the operation of the motor unit **113** with the aid of the safety logic **105**; transmitting the forwarded encoder data to the drive unit **109** in respective data packets based on the encoder protocol with the aid of the protocol passive unit **103**; and cause a stop of the operation of the motor unit **113** with the aid of the safety logic **105**, if the encoder data is detected by the safety logic **105** as not conforming to the predetermined safety criteria.

(61) In the embodiment shown in FIG. 1, the safety module **100** is integrated into a drive system **107**. The encoder unit **111** and the motor unit **113** of the drive system **107** are connected to each other. In order to control the motor unit **113** with the aid of the drive unit **109**, both units are connected via a control link **119**. The drive unit **109** comprises a drive protocol active unit **115** and the encoder unit **111** comprises an encoder protocol passive unit **117**. The drive unit **109** and the encoder unit **111** are interconnected via the encoder interface **102**. The encoder interface **102** is integrated into the safety module **100**.

(62) The safety module **100** comprises a protocol active unit **101**, a protocol passive unit **103**, and safety logic **105**, each of which is connected in pairs via a first data interface **104**. The protocol

passive unit **103** of the safety module **100** is connected to the drive protocol active unit **115** of the drive unit **109** via the encoder interface **102**. The protocol active unit **101** of the safety module **100** is connected to the encoder protocol passive unit **117** of the encoder unit **111** via the encoder interface **102**.

(63) The safety module **100** is connected to the drive unit **109** via a data bus connection **121**.

(64) In order to transmit encoder data from the encoder unit **111** to the drive unit **109**, the encoder unit **111** sends out corresponding encoder data to the drive unit **109** according to an encoder protocol of the encoder interface **102**. The transmitted encoder data are received by the protocol active unit **101** of the safety module **100**. The protocol active unit **101** may process and check the received encoder data for correctness, e.g. by the protocol active unit **101** checking a checksum of the transmitted encoder data.

(65) Subsequently, the protocol active unit **101** may forward the received encoder data to the protocol passive unit **103** via the first data interface **104**. Additionally, the encoder active unit **101** forwards the received encoder data to the safety logic **105** via the first data interface **104**. The forwarded encoder data are sent to the drive unit **109** by the protocol passive unit **103** via the encoder interface **102**. The drive unit **109** receives the sent-out encoder data via the drive protocol active unit **115**. The protocol active unit **101**, the protocol passive unit **103**, the drive protocol active unit **115** and the encoder protocol passive unit **117** are in this context passive unit units or active unit units of the encoder protocol of the encoder interface **102**. The encoder interface **102** may be an encoder interface known in the prior art, for example HIPERFACE DSL or EnDat.

(66) Alternatively, the safety module **100** may communicate with the encoder unit **111** via an encoder interface, while the safety module **100** communicates with the drive unit **109** via another encoder interface. In this case, the protocol active unit **101** and the protocol passive unit **103** of the safety module **100** are active unit and passive unit units of two different protocols and two different interfaces, i.e. encoder interfaces of different types. For data communication or, respectively, for forwarding data within the safety module **100** between the protocol active unit **101** and the protocol passive unit **103**, these and/or the safety module **100** are set up to perform a protocol conversion in order to express data of one interface in the respective other interface.

(67) The protocol active unit **101** of the safety module **100** is configured to perform data communication with the encoder protocol passive unit **117** of the encoder unit **111** that is identical to data communication between the drive protocol active unit **115** and the encoder protocol passive unit **117**. Thus, for the encoder protocol passive unit **117**, a data communication with the protocol active unit **101** of the safety module **100** is identical to a data communication with the drive protocol active unit **115** of the drive unit **109**. The protocol passive unit **103** of the safety module **100** is arranged to perform a data communication with the drive protocol active unit **115** of the drive unit **109** that is identical to a data communication between the drive protocol active unit **115** of the drive unit **109** and the encoder protocol passive unit **117** of the encoder unit **111**. Thus, for the drive protocol active unit **115** of the drive unit **109**, the protocol passive unit **103** of the safety module **100** is indistinguishable from the encoder protocol passive unit **117** of the encoder unit **111**.

(68) Thus, for the drive protocol active unit **115** of the drive unit **109** and the encoder protocol passive unit **117** of the encoder unit **111**, data communication in which, as described above, an exchange of encoder data between the encoder protocol passive unit **117** of the encoder unit **111** and the drive protocol active unit **115** of the drive unit **109** is performed indirectly via the protocol active unit **101** and the protocol passive unit **103** of the safety module **100**, is analogous to a direct data exchange of encoder data between the encoder protocol passive unit **117** of the encoder unit **111** and the drive protocol active unit **115** of the drive unit **109**.

(69) The encoder data emitted by the encoder unit **111** may be emitted in accordance with a predetermined emitting clock by the encoder protocol passive unit **117** of the encoder unit **111**. Alternatively, the encoder data emitted by the encoder unit **111** may be emitted in response to a request to emit encoder data previously emitted by the drive unit **109**. To this end, in accordance

with a further embodiment, the safety module **100** is configured to receive requests to transmit encoder data transmitted by the drive protocol active unit **115** of the drive unit **109** via the protocol passive unit **103** and to transmit corresponding encoder data to the drive protocol active unit **115** via the protocol passive unit **103**. Furthermore, the safety module **100** may be configured to forward the requests received from the protocol passive unit **103** to the protocol active unit **101** via the first data interface **104**, and to send out the forwarded requests to the encoder protocol passive unit **117** of the encoder unit **111** through the protocol active unit **101**.

(70) The safety module **100** is thus arranged to provide comprehensive data communication between the drive unit **109** and the encoder unit **111**, in which encoder unit encoder data and requests for transmission of encoder units of the drive unit are exchanged between the drive unit **109** and the encoder unit **111**.

(71) For example, encoder data may comprise position data of the motor unit **113** describing positions of a motor position of the motor unit **113**. Furthermore, encoder data may comprise parameter data describing additional parameters, such as a temperature, a speed, an acceleration, a pressure, or similar parameters of the motor unit. Requests to send encoder data may be send commands or send requests corresponding to the encoder protocol of the encoder interface **102**.

(72) The encoder unit **111** may be a safety encoder, and encoder data from the safety encoder may comprise a first position datum and a second position datum usable for safety analysis.

(73) The encoder data transmitted from the protocol active unit **101** to the safety logic **105** via the first data interface **104** is subjected to a safety analysis by the safety logic **105** according to predetermined safety criteria. For example, the safety criteria may be a maximum position and a minimum position of the motor unit **113**, respectively. Alternatively, the safety criteria may comprise a maximum speed or a minimum speed, a maximum acceleration or a minimum acceleration, a maximum temperature or a minimum temperature, a maximum pressure or a minimum pressure, respectively, or further safety-related criteria of the operation of the motor unit **113**, such as maximum values regarding vibrations occurring in the motor unit. Alternatively, the safety criteria may additionally be safety criteria specific to the type of motor unit, which allow a statement to be made about the safety condition of the motor unit **113**.

(74) To analyze the encoder data via the safety logic **105**, the safety logic **105** may use various analysis procedures known in the prior art.

(75) If the analysis of the safety logic **105** reveals that encoder data of the encoder unit **111** does not meet the safety criteria, e.g. by exceeding or falling below maximum or minimum positions, maximum or minimum speeds, maximum or minimum accelerations, maximum or minimum temperatures, or similar parameters of the motor unit **113**, the safety logic **105** causes the operation of the motor unit to stop.

(76) In the embodiment in FIG. **1**, the safety logic **105** sends a corresponding operation stop message to the drive unit **109** for this purpose, on the basis of which the drive unit **109** stops the operation of the motor unit **113** via the control connection **119**. In the embodiment of FIG. **1**, the safety logic **105** sends the operation stop message to the drive unit **109** on the basis of a safety-relevant data packet in accordance with a safety-relevant data communication **123** of the data bus connection **121**. A safety-relevant data communication **123** may e.g. be implemented via a safety-relevant field bus protocol, such as Safety-over-EtherCAT. The safety-relevant data connection **123** ensures that the operating stop message of the safety logic **105** is transmitted to the drive unit **109** reliably and without delay, so that a corresponding operating stop of the motor unit **113** may be effected immediately after identification of the safety risk.

(77) FIG. **2** shows another schematic depiction of a safety module **100** according to a further embodiment, wherein the safety module **100** is integrated into a drive system **107**.

(78) The embodiment in FIG. **2** differs from the embodiment in FIG. **1** in that the drive unit **109** includes a safe-torque-off function **125**. The safety logic **105** is connected to the safe-torque-off function **125** of the drive unit **109** via a safe-torque-off interface **127**. If the safety logic **105**

identifies that the encoder data of the encoder unit **111** does not meet the safety criteria, the safety logic **109** sends a safe-torque-off message to the safe-torque-off function **125** of the drive unit **109** via the safe-torque-off interface **127**, causing the safe-torque-off function **125** to stop the operation of the motor unit **113**. For this purpose, the drive unit **109** causes the motor unit **113** to stop operating via the control link **119**.

(79) FIG. **3** shows another schematic depiction of a safety module **100** according to a further embodiment, wherein the safety module **100** is integrated into a drive system **107**.

(80) The embodiment in FIG. **3** differs from the embodiments in FIG. **1** and FIG. **2** in that a shutdown mechanism **129** is integrated into the control link **119**. The safety logic **105** is connected to the shutdown mechanism **129** via a shutdown connection **131**. Furthermore, in the embodiment shown in FIG. **3**, the drive system **107** comprises a further encoder unit **112**, which in turn comprises a further encoder protocol passive unit **118**. The further encoder unit **112** is connected to the motor unit **113** and embodied to receive further encoder data from the motor unit **113** and to send it out via the encoder interface **102** to the drive unit **109** or the safety module **100**, in particular to the protocol active unit **101** of the safety module **100**. In the embodiment shown in FIG. **3**, the encoder unit **111** and the further encoder unit **112** are each not a safety encoder, but are merely embodied as simple encoders.

(81) The further encoder data sent out by the further encoder unit **112** is received by the protocol active unit **101** of the safety module **100** and forwarded to the safety logic **105** via the first data interface **104**. The further encoder data is taken into account by the safety logic **105** in addition to the encoder data of the encoder unit **111**. For this purpose, in particular, a first position datum of the motor unit **113** is created from the encoder data of the encoder unit **111**, and a second position datum of the motor unit **113** is created from the further encoder data of the further encoder unit **112**. The first position datum of the encoder data of the encoder unit **111** describing a first position of the motor unit **113** and the second position datum of the further encoder data of the further encoder unit **112** describing a second position of the motor unit **113** are jointly considered for the analysis of the encoder data and further encoder data, respectively, by the safety logic **105**.

(82) Apart from the second position data, the further encoder data may incidentally comprise further parameter data.

(83) If the safety logic **105** detects a violation of the safety requirements based on the analysis of the encoder data of the encoder unit **111** and the further encoder data of the further encoder unit **112**, the safety logic **105** triggers the shutdown mechanism **129** via a corresponding signal transmitted via the shutdown connection **131**, thereby interrupting the control connection **119** between the drive unit **109** and the motor unit **113**. This causes the operation of the motor unit **113** to stop. The shutdown mechanism **129** may e.g. be a relay mechanism or a contactor mechanism.

(84) Alternatively, combinations of the embodiments according to FIG. **1**, FIG. **2** and FIG. **3** are possible, as well.

(85) FIG. **4** shows another schematic depiction of a safety module **100** according to a further embodiment, wherein the safety module **100** is integrated into a drive system **107**.

(86) The embodiment in FIG. **4** is based on the embodiment in FIG. **2**.

(87) Deviating from the embodiment in FIG. **2**, the drive protocol active unit **115** and the protocol passive unit **103** of the safety module **100** are connected via a further encoder interface **110**, which differs from the encoder interface **102** according to FIG. **2**. A data communication between the drive protocol active unit **115** and the protocol passive unit **103** takes place based on a protocol of the further encoder interface **110**.

(88) Further differing from the embodiment in FIG. **2**, the safety module **100** comprises an encoder emulator **135**. The encoder emulator **135** comprises a position emulation **137** and a memory unit **139**. The protocol active unit **101**, the protocol passive unit **103**, the safety logic **105** and the encoder emulator **135** are connected to one another via a second data interface **106** and a third data interface **108**. Here, the second data interface **106** is used to transmit cyclic data, while the third

data interface **108** is used to transmit acyclic data. Cyclic data, in the sense of the application, comprise data that are transmitted within a control cycle. Acyclic data in the sense of the application are data that are transmitted between control cycles or distributed over several control cycles.

(89) A cyclic data transmission and an acyclic data transmission play a role in particular in an application of the drive system **107** in an automation system. In this case, a cyclic data transmission relates to a transmission of data within a control cycle of the automation system. An acyclic data transmission, on the other hand, relates to a transmission of data that is performed between two control cycles, or, respectively, that may extend over more than one control cycle. A cyclic data transmission usually comprises the data that are immediately required to control the automation system. An acyclic data transmission may also comprise data that are not directly required for control, e.g. status data of individual components of the automation system.

(90) In the present embodiment, position data of the encoder unit **111** in particular are exchanged between the encoder unit **111** and the drive unit **109** for controlling the motor unit **113** in a cyclic data transmission. In an acyclic data transmission, parameter data of the encoder unit **111** or of the motor unit **113** may be exchanged between the encoder unit **111** and the drive unit **109**.

(91) If the drive unit **109** sends a request to transmit encoder data to the encoder unit **111** in a cyclic data transmission according to the control of the motor unit **113**, the protocol passive unit **103** of the safety module **100** receives the request sent by the drive protocol active unit **115** and forwards it to the safety logic **105** via the second data interface **106**. The safety logic **105** forwards the forwarded request via the second data interface **106** to the protocol active unit **101**, which in turn sends the request via the encoder interface **102** to the encoder protocol passive unit **117** of the encoder unit **111**. Hereupon, the encoder protocol passive unit **117** of the encoder unit **111** sends corresponding encoder data to the drive unit **109** via the encoder interface **102**, which is received by the protocol active unit **101** of the safety module **100** and forwarded to the encoder emulator **135** via the second data interface **106**. The encoder emulator **135** forwards the forwarded encoder data via the second data interface **106** to the protocol passive unit **103**, which sends out the forwarded encoder data via the further encoder interface **110** to the drive protocol active unit **115** of the drive unit **109**.

(92) For analysis of the encoder data by the safety logic **105**, the encoder data sent out by the encoder protocol passive unit **117** of the encoder unit **111** is furthermore forwarded by the protocol active unit **101** to the safety logic **105** via the second data interface **106**. If the safety logic **105** detects a safety hazard based on the encoder data, the safety logic **105** causes the safe-torque-off function **125** of the drive unit **109** to cause an operational stop of the motor unit **113**.

(93) As an alternative to forwarding the request via the first data interface **104** to the safety logic **105**, the protocol passive unit **103** forwards the request to send out encoder data of the drive unit **109** via the second data interface **106** to the encoder emulator **135**. Subsequently, the encoder emulator **135** may forward corresponding encoder data stored in the memory unit **139** via the second data interface **106** to the protocol passive unit **103**, which in turn sends out the forwarded encoder data to the drive protocol active unit **115** of the drive unit **109**.

(94) Alternatively, in response to the forwarded request to send encoder data, the encoder emulator **135** may generate simulated encoder data corresponding to the requests via the position emulation **137** and forward the simulated encoder data to the protocol passive unit **103** via the second data interface **106**, which in turn sends the simulated encoder data to the drive protocol active unit **115** of the drive unit **109**. The sending of encoder data stored in the memory unit **139** and the sending of simulated encoder data, respectively, may be performed particularly for those cases for which forwarding the request to send out encoder data to the encoder unit **111** and transmitting the encoder data of the encoder unit **111** via the safety module **100** to the drive unit **109** would result in a delay and thus in the sending out of an error message due to the drive unit **109** not providing the encoder data in time.

(95) By taking into account encoder data stored in the memory unit **139** or simulated encoder data, respectively, it may be achieved that the safety module **100** is not registered by either the drive protocol active unit **115** of the drive unit **109** or the encoder protocol passive unit **117** of the encoder unit **111**, and undelayed and reliable data communication may be provided between the drive unit **109** and the encoder unit **111** from the perspective of the drive unit **109**. Alternatively, requests from the drive protocol active unit **115** to the encoder protocol passive unit **117** may additionally or exclusively be forwarded to the encoder protocol passive unit **117** with a time delay. This may particularly be considered for cases in which requests from the drive protocol active unit **115** concern an action of the encoder protocol passive unit **117**, such as the storing or deleting of encoder data by the encoder protocol passive unit **117**. From the perspective of the drive protocol active unit **115**, no delay occurs due to the safety module **100**, and in particular due to the encoder emulator **135**, due to which the encoder protocol passive unit **117** is simulated, so that an error message by the drive protocol active unit **115** due to delayed response of the encoder protocol passive unit **117** may be avoided.

(96) The encoder data transmitted via the second data interface **106** preferably comprise position data of the motor unit **113**, which are exchanged between the drive unit **109** and the encoder unit **111** in a cyclic data communication for controlling the motor unit **113** via the drive unit **109**. Alternatively, the encoder data transmitted via the second data interface **106** and cyclically exchanged between the drive unit **109** and the encoder unit **111** may comprise other parameter data of the motor unit **113**.

(97) Encoder data exchanged in an acyclic data exchange between the drive unit **109** and the encoder unit **111** may be forwarded within the safety module **100** via the third data interface **108**.

(98) If parameter data are requested from the drive protocol active unit **115** of the drive unit **109**, which are preferably transmitted acyclically, the protocol passive unit **103** forwards the corresponding request to the encoder emulator **135** via the third data interface **108**. The latter may either forward corresponding encoder data stored in the memory unit **139** to the protocol passive unit **103** via the third data interface **108**, or forward the corresponding request via the third data interface **108** and a switching unit **133** to the protocol active unit **101**, which sends the corresponding request to the encoder protocol passive unit **117** of the encoder unit **111**. The latter subsequently sends out corresponding encoder data to the drive unit **109**, which are forwarded by the protocol active unit **101** via the third data interface **108** to the encoder emulator **135**, which in turn are forwarded by the encoder emulator **135** via the third data interface **108** to the protocol passive unit **103** and are sent out to the drive protocol active unit **115** by the protocol passive unit **103**.

(99) The encoder unit **111** parameter data received from the protocol active unit **101** may be transmitted from the protocol active unit **101** to the safety logic **105** via the third data interface **108**, in addition to being analyzed by the safety logic **105**.

(100) The position data cyclically exchanged between the drive unit **109** and the encoder unit **111** may be limited to a first position datum. A second position datum, created e.g. by a safety encoder or another encoder unit **112** for safety analysis by the safety logic **105**, may be transmitted cyclically together with the first position datum so that the second position datum received from the protocol active unit **101** is transmitted to the safety logic **105** via the second data interface **106**. Alternatively, the second position datum may be transmitted acyclically together with the parameter data, so that the second position datum received from the protocol active unit **101** is transmitted to the safety logic **105** via the third data interface **108** and from the safety logic **105** to the protocol passive unit **103**. For this purpose, a corresponding request to transmit second position data may previously be sent to the encoder unit **111** by the drive protocol active unit **115** of the drive unit **109**. This request is transmitted in accordance with the acyclic data transmission from the protocol passive unit **103** via the third data interface **108** to the safety logic **105** and from the safety logic **105** via the switching unit **133** to the protocol active unit **101**. Hereby, the switching unit **133**

may act as a control element and control which of the data transmitted via the third data interface **108** from the encoder emulator **135** and the safety logic **105** are transmitted to the protocol active unit **101**.

(101) Via the two communication channels separated from each other, the cyclic communication channel realized by the second data interface **106** and the acyclic communication channel realized by the third data interface **108**, it may be achieved that the cyclic data communication between the drive unit **109** and the encoder unit **111** may be performed without delay. Furthermore, it may be achieved that the safety logic **105** has access to both the cyclically transmitted position data, which is preferably limited to a first position datum, and the acyclically transmitted parameter data or the second position datum for performing the safety analysis.

(102) As an alternative to the encoder interface **102** and to the further encoder interface **110**, data communication between the drive unit **109** and the encoder unit **111** or the safety module **100** may be implemented via a data bus, in particular a field bus. For this purpose, a cross communication may be implemented that ensures a direct data communication between the drive unit **109**, the encoder unit **111** and the safety module **100**, in which data packets to be exchanged are not moderated via a bus active unit of the data bus, but are exchanged directly between the drive unit **109**, the encoder unit **111** and the safety module **100**.

(103) The safety module **100** may be embodied as a hardware component, in particular as a bus terminal. The safety module **100** may comprise corresponding contact connections via which the safety module **100** may be connected to a drive unit **109** and an encoder unit **111**.

(104) An encoder unit **111** or a further encoder unit **112** may be an absolute encoder, an incremental encoder, a rotary encoder or a linear encoder. A motor unit **113** may be any motor unit, in particular a servo-motor unit.

(105) The embodiment in FIG. **4** may be combined with features of the embodiments in FIGS. **1** and **3**. In particular, the embodiment of FIG. **4** may be combined with a safety-related data communication **123** according to the embodiment in FIG. **1** and/or with a shutdown mechanism **129** and a shutdown connection **131** according to the embodiment in FIG. **3**.

(106) FIG. **5** shows a schematic depiction of an automation system **200** comprising a drive system **107** with a safety module **100** according to an embodiment.

(107) In the embodiment shown in FIG. **5**, the automation system **200** comprises a control unit **201** and a drive system **107** that is connected to a safety module **100** via an encoder interface **102**. In the embodiment of FIG. **5**, both the drive system **107** and the safety module **100** are connected to the control unit **201** via a data bus connection **121**. The drive system **107** may be controlled via the control unit **201**.

(108) As an alternative to the embodiment shown in FIG. **5**, the automation system **200** may further comprise additional components. The data bus connection **121** may be a field-bus system.

(109) This invention has been described with respect to exemplary examples. It is understood that changes can be made and equivalents can be substituted to adapt these disclosures to different materials and situations, while remaining within the scope of the invention. The invention is thus not limited to the particular examples that are disclosed, but encompasses all the examples that fall within the scope of the claims.

(110) TABLE-US-00001
TABLE 1 List of reference numerals
100 safety module
101 protocol active unit
102 encoder interface
103 protocol passive unit
104 first data interface
105 safety logic
106 second data interface
107 drive system
108 third data interface
109 drive unit
110 further encoder interface
111 encoder unit
112 further encoder unit
113 motor unit
115 drive protocol active unit
117 encoder protocol passive unit
118 further encoder protocol passive unit
119 control connection
121 data bus connection
123 safety-relevant data communication
125 safety torque-off function
127 safety Torque Off Connection
129 shutdown mechanism
131 shutdown connection
133 circuit unit
135 encoder emulator
137 position emulation
139 memory unit

Claims

1. A safety module for secure drive control of a drive system in an automation system, wherein the drive system comprises: at least one drive unit comprising a drive protocol active unit having a processor and memory configured for operation as an active unit of an encoder protocol of an encoder interface, an encoder unit comprising an encoder protocol passive unit having a processor and memory configured for operation as a passive unit of the encoder protocol, and a motor unit; wherein the safety module is formed as a hardware component comprising contact connections configured to connect with the encoder unit and the motor unit, wherein the safety module is integrated between the drive unit and the encoder unit and connected thereto via at least one data connection established by the contact connections, wherein the safety module further comprises a protocol active unit, a protocol passive unit and a safety logic configured to communicate with one another via data communication, and wherein the protocol active unit is configured as an active unit and the protocol passive unit is configured as a passive unit of the encoder protocol of the encoder interface, wherein the encoder interface provides the at least one data connection; and wherein the safety module comprises a processor and memory configured to: receive requests sent by the drive protocol active unit of the drive unit to the encoder protocol passive unit of the encoder unit to send out the encoder data by the protocol passive unit of the safety module; forward the received requests of the drive protocol active unit of the drive unit to send out the encoder data by the protocol passive unit to the protocol active unit of the safety unit; send out the received requests of the drive protocol active unit of the drive unit by the protocol active unit of the safety module to the encoder protocol passive unit of the encoder unit; receive the requested encoder data sent out from the encoder protocol passive unit of the encoder unit configured for operation as the passive unit of the encoder protocol to the drive protocol active unit of the drive unit configured for operation as the active unit of the encoder protocol based on the encoder protocol with the aid of the protocol active unit of the safety module; forward the received encoder data from the protocol active unit to the safety logic and the protocol passive unit; check the forwarded encoder data with the aid of the safety logic for correspondence with predetermined safety criteria relating to operation of the motor unit; send out the forwarded encoder data via the protocol passive unit based on the encoder protocol in corresponding data packets to the drive protocol active unit of the drive unit; and cause a stop of the operation of the motor unit with the aid of the safety logic, if the forwarded encoder data is detected by the safety logic as not corresponding to the predetermined safety criteria.
2. The safety module according to claim 1, wherein the safety module is further configured to send out, via the protocol active unit, requests to send out the encoder data to the encoder protocol passive unit of the encoder unit.
3. The safety module according to claim 1, wherein the safety module may further be synchronized with the drive unit, and wherein the safety module is configured to send out corresponding requests by the protocol active unit to the encoder protocol passive unit of the encoder unit in synchrony with sending out requests for the encoder data via the drive unit.
4. A safety module according to claim 1, wherein the safety module may further be connected to the drive unit via a data bus connection, and wherein the safety module is configured to send out, in order to cause a stop of the operation of the motor unit by the safety logic, a corresponding operation stop message based on a safety-related data packet according to a secure data bus protocol of the data bus connection to the drive unit.
5. The safety module according to claim 1, wherein the safety criteria comprise a maximum position and/or a maximum speed and/or a maximum acceleration and/or a maximum temperature of the motor unit.
6. A drive system comprising at least a drive unit, an encoder unit, a motor unit and a safety module

according to claim 1, wherein the drive unit and the encoder unit are connected to each other via a data link and are configured to communicate via an exchange of data packets according to an encoder protocol, wherein the safety module is connected to the drive unit and the encoder unit via the data connection, and wherein the drive unit is connected to the motor unit via a control connection for controlling the motor unit.

7. An automation system comprising a control unit and at least the drive system according to claim 6, which is connected to the control unit via a data bus connection, wherein the control unit is configured to control the drive system.
