

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12412908
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Howey; Friedrich et al.

Fuel cell system

Abstract

The invention relates to a fuel cell system (**100**) having at least one fuel cell stack (**101**), an air path (**10**), wherein air from the surroundings reach the fuel cell stack (**101**) via the air path (**10**), an exhaust gas path (**12**), a fuel line (**20**), wherein fuel is transported to the fuel cell stack (**101**) via the fuel line (**20**). According to the invention, the air path (**10**) is connected to a cooling line (**30**) via a branch (**33**), wherein the cooling line (**30**) is connected to a PDU unit (**32**).

Inventors:	Howey; Friedrich (Ditzingen, DE), Rewers; Gregory (Schwieberdingen, DE), Reinoehl; Markus (Stuttgart, DE), Essling; Rolf-Peter (Reudern, DE)
Applicant:	Robert Bosch GmbH (Stuttgart, DE)
Family ID:	74553787
Assignee:	Robert Bosch GmbH (Stuttgart, DE)
Appl. No.:	17/796380
Filed (or PCT Filed):	January 26, 2021
PCT No.:	PCT/EP2021/051688
PCT Pub. No.:	WO2021/151863
PCT Pub. Date:	August 05, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20230046641 A1	Feb. 16, 2023

Foreign Application Priority Data

DE

10 2020 201 195.8

Jan. 31, 2020

Publication Classification

Int. Cl.: H01M8/04 (20160101); H01M8/04014 (20160101); H01M8/04089 (20160101);
H01M8/0432 (20160101); H01M8/04746 (20160101); H01M8/247 (20160101)

U.S. Cl.:

CPC H01M8/04014 (20130101); H01M8/04089 (20130101); H01M8/04373 (20130101);
H01M8/04746 (20130101); H01M8/247 (20130101);

Field of Classification Search

CPC: H01M (8/04014); H01M (8/04089); H01M (8/04373); H01M (8/04746); H01M (8/247)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2011/0020715	12/2010	Shinoda et al.	N/A	N/A
2014/0000275	12/2013	Kesseli et al.	N/A	N/A
2018/0287179	12/2017	Rueger	N/A	C25B 15/02

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2963725	12/2015	EP	N/A
H0426194	12/1991	JP	N/A
2002050385	12/2001	JP	N/A
2008052997	12/2007	JP	N/A
2008192393	12/2007	JP	N/A
2009245814	12/2008	JP	N/A
2010153104	12/2009	JP	N/A
2013093256	12/2012	JP	N/A
2014151722	12/2013	JP	N/A
2016100160	12/2015	JP	N/A
2018139205	12/2017	JP	N/A
2020014263	12/2019	JP	N/A

OTHER PUBLICATIONS

Translation of International Search Report for Application No. PCT/EP2021/051688 dated Apr. 8, 2021 (2 pages). cited by applicant

Primary Examiner: Godo; Olatunji A

Attorney, Agent or Firm: Michael Best & Friedrich LLP

Background/Summary

BACKGROUND OF THE INVENTION

- (1) The invention relates to a fuel cell system having at least one fuel cell stack, having an air path through which air from the environment reaches the fuel cell stack, having an exhaust gas path, and having a fuel line through which fuel is transported to the fuel cell stack.
- (2) Hydrogen-based fuel cells are seen as a mobility concept of the future, since they only emit water as an exhaust gas and enable rapid refueling times. Fuel cells are usually assembled to form a fuel cell stack. The fuel cell stacks need oxygen, in most cases taken from ordinary air from the environment, and fuel, in most cases hydrogen, for the chemical reaction.
- (3) In fuel cell systems, the voltage taps at the fuel cell stack are carried out and processed via a power distribution unit (PDU). The tasks of a PDU are typically: voltage protection, current measurement, disconnection of the stack voltage from the system in the event of an accident, connection of the stack voltage to the DC/DC converter, then to the battery.
- (4) The elements and components within the PDU are exposed to high heat development owing to electrical losses and resistances. For this reason, the PDU has to be cooled. Known cooling options are a separate fan within the housing of the PDU and/or water cooling.

SUMMARY OF THE INVENTION

- (5) The inventive fuel cell system is advantageous in that air for cooling the PDU is extracted from the air path (cathode path). Costs can thus be reduced, since there is no need to install a separate cooler which provides the necessary safety in the environment of the engine compartment and blows clean air into the housing of the PDU.
- (6) In contrast to water cooling, the elements of the PDU can be cooled directly, whereas, with water cooling, the components can only be cooled indirectly by airflows which are generated within the housing due to temperature gradients. A heat pipe and a Peltier element, which is used to cool the PDU, produce only a slight cooling effect in comparison to direct air cooling.
- (7) Effective cooling of the PDU can be ensured as a result of the inventive fuel cell system. The components of the PDU have electrical losses, which may be converted into heat so that, without effective cooling, the internal temperature of the PDU continues to increase and the components overheat and, in the worst case, fail.
- (8) An arrangement of the branch point between a compressor, which compresses the air in the air path, and the fuel cell stack is advantageous since a high pressure difference between the branch point and the environment can thus be produced, so that, when necessary, a sufficiently high air mass flow rate for cooling can flow to the PDU via the cooling line.
- (9) A heat exchanger, which is arranged between the compressor and the branch point, is advantageous since the temperature of the air which flows to the PDU can thus be further reduced.
- (10) A particular advantage is achieved by a filter, which is arranged in the air path between an input and the branch point, since the air which flows to the PDU is thus already cleaned of dust and small particles. Clean air is an important basic requirement for the electronic components within the PDU.
- (11) It is advantageous if an adjustable throttle is arranged in the cooling line since the quantity of air which flows to the PDU can thus be altered in a variable manner. In the case of a high thermal load on the components of the PDU, a high quantity of air can flow to the PDU via the adjustable throttle. In the case of a small thermal load, the adjustable throttle can reduce its cross section so that less air flows to the PDU.
- (12) If the air in the cooling line still has too high a temperature to ensure effective cooling, a cooler in the cooling line can further reduce the temperature so that greater cooling efficiency is achieved with the same quantity of air.

- (13) In this case, it is advantageous if the cooler is arranged between the adjustable throttle and the PDU since this ensures that only the air which flows to the PDU is cooled.
- (14) In the event of a stoppage of the fuel cell system, hydrogen may escape from the fuel cell stack into the air path. To prevent the penetration of hydrogen into the PDU, it is advantageous if a non-return valve is arranged in the cooling line. As a result of the non-return valve, the gas exchange between the fuel cell stack and the PDU upon a stoppage of the fuel cell system is prevented since, in the stopped state, the closing force of the non-return valve cannot be overcome by the air pressure at the branch point. This is very important since ignition sources may be present in the PDU, which could result in the ignition of a mixture of hydrogen and air.
- (15) It is advantageous if the PDU has a pressure equalizing element or a non-return valve via which the air can escape into the environment. In this case, the pressure equalizing element can be designed such that it is permeable to gases but prevents the entry of particles and moisture into the PDU.
-

Description

BRIEF DESCRIPTION OF THE DRAWING

- (1) The single drawing FIGURE shows a fuel cell system embodying the invention.
- (2) The inventive fuel cell system and the inventive method are explained in more detail below with reference to the FIGURE.

DETAILED DESCRIPTION

- (3) In the FIGURE, a schematic topology of a fuel cell system **100** according to a first exemplary embodiment is shown with at least one fuel cell stack **101**. The at least one fuel cell stack **101** has an air path **10**, an exhaust gas path **12** and a fuel line **20**. The at least one fuel cell stack **101** can be used for mobile applications with a high power requirement, for example in trucks, or for stationary applications, for example in generators.
- (4) The air path **10** serves as an air supply line in order to supply air from the environment to the fuel cell stack **101** via an inlet **16**. Components which are required for the operation of the fuel cell stack **101** are arranged in the air path **10**. An air compressor **11** and/or supercharger **11** can be arranged in the air path **10**, which air compressor and/or supercharger compresses or draws in the air according to the respective operating conditions of the fuel cell stack **101**. A heat exchanger **15** can be located downstream of the air compressor and/or supercharger **11**, which heat exchanger cools the air in the air path **10** to a lower temperature.
- (5) Further components, such as humidifiers and/or valves, for example, can be provided within the air path **10**. The fuel cell stack **101** is provided with oxygenated air via the air path **10**.
- (6) The air path **10** is connected to a cooling line **30** via a branch point **33**. Air from the air path **10** can arrive in a PDU **32** or the housing **31** of a PDU **32** via the cooling line **30**. A PDU **32** is a power distribution unit **32**, which carries out a voltage tap at the fuel cell stack **101** and processes and connects these voltage taps.
- (7) The tasks of a power distribution unit (PDU **32**) are inter alia: voltage protection, current measurement, disconnection of the stack voltage from the system if an accident is detected, connection of the stack voltage to the DC/DC converter and/or to the battery.
- (8) The elements in the housing **31** of the PDU **32** can be cooled using the air from the air path **10**, which arrives in the housing **13** of the PDU **32** via the cooling line **30**.
- (9) The branch point **33** is preferably arranged between the compressor **11**, which compresses the air in the air path **10**, and the fuel cell stack **101**. In order to provide the cooling line **30** with sufficient cold air, the heat exchanger **15** can be arranged between the compressor **11** and the branch point **33**.
- (10) At least one filter **13**, which filters particles and foreign bodies out of the air, can be arranged

in the air path **10**, between the input **16** and the branch point **33**. The air which flows to the PDU **32** is thus already cleaned of unwanted particles and foreign bodies.

(11) So that the air which arrives in the cooling line **30** from the air path **10** is controlled according to requirements, an adjustable throttle **34** can be arranged in the cooling line **30**.

(12) If the air which flows into the cooling line **30** from the air path **10** does not have the desired temperature, a cooler **35** can be arranged in the cooling line **30**, which cooler further cools the air in the cooling line **30**. In one embodiment, the cooler **35** can be arranged between the adjustable throttle **34** and the PDU **32**.

(13) A gas non-return valve **37** can furthermore be arranged in the cooling line **30**, which gas non-return valve prevents hydrogen from the fuel cell stack **101** from diffusing into the cooling line **30** in the event of a stoppage of the fuel cell system **100**.

(14) The air which has arrived in the housing **31** of the PDU **32** via the cooling line **30** can be discharged back into the environment via at least one pressure equalizing element **38**, which is arranged in the housing **31** of the PDU **32**. In one embodiment, the pressure equalizing element **38** is permeable to gases but prevents the entry of particles and moisture into the PDU.

(15) In an alternative embodiment, a further non-return valve **38** is arranged in the housing **31** of the PDU **32**, via which non-return valve the air, which has arrived in the housing **31** of the PDU **32** via the cooling line **30**, can escape into the environment.

(16) The fuel cell system **100** furthermore has an exhaust gas path **12** in which water and further constituents of the air can be transported out of the air path **10** after its passage through the fuel cell stack **101** and into the environment via an outlet **18**.

(17) The fuel cell system **100** can furthermore have a cooling circuit, which is designed to cool the fuel cell stack **101**. The cooling circuit is not shown in the FIGURE since it is not part of the invention.

(18) The fuel line **20** has a high pressure tank **21** and a shut-off valve **22**. Further components can be arranged in the fuel line **20** in order to supply fuel to the fuel cell stack **101** according to requirements. A circulation line can furthermore be provided, which is not shown in the FIGURE since it is not part of the invention.

Claims

1. A fuel cell system (**100**) having at least one fuel cell stack (**101**), having an air path (**10**) through which air from the environment reaches the fuel cell stack (**101**), having an exhaust gas path (**12**), and having a fuel line (**20**) through which fuel is transported to the fuel cell stack (**101**), wherein the air path (**10**) is connected to a cooling line (**30**) via a branch point (**33**), wherein the cooling line (**30**) is connected to a power distribution unit (PDU) (**32**), wherein at least one filter (**13**) is arranged in the air path (**10**) between an input (**16**) and the branch point (**33**), wherein an adjustable throttle (**34**) is arranged in the cooling line (**30**), wherein a cooler (**35**) is arranged in the cooling line (**30**), and wherein the cooler (**35**) is arranged between the adjustable throttle (**34**) and the PDU (**32**).
2. The fuel cell system (**100**) as claimed in claim 1, wherein the branch point (**33**) is arranged between a compressor (**11**), which compresses the air in the air path (**10**), and the fuel cell stack (**101**).
3. The fuel cell system (**100**) as claimed in claim 2, wherein a heat exchanger (**15**) is arranged between the compressor (**11**) and the branch point (**33**).
4. The fuel cell system (**100**) as claimed in claim 1, wherein a gas non-return valve (**37**) is arranged in the cooling line (**30**).
5. The fuel cell system (**100**) as claimed in claim 1, wherein the PDU (**32**) has a pressure equalizing element (**38**) or a non-return valve (**38**), via which the air can escape into the environment.

6. The fuel cell system (**100**) as claimed in claim 5, wherein the pressure equalizing element (**38**) is permeable to gases but prevents entry of particles and moisture into the PDU (**32**).
