

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12413258
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Huang; Kuo-Ken

Wireless receiver apparatus and method

Abstract

Embodiments of the invention include a wakeup receiver (WRX) featuring a charge-domain analog front end (AFE) with parallel radio frequency (RF) rectifier, charge-transfer summation amplifier (CTSA), and successive approximation analog-to-digital converter (SAR ADC) stages. The WRX operates at very low power and exhibits above-average sensitivity, random pulsed interferer rejections, and yield over process.

Inventors:	Huang; Kuo-Ken (Santa Clara, CA)
Applicant:	EVERACTIVE, INC. (Santa Clara, CA)
Family ID:	74851264
Assignee:	Everactive, Inc. (Charlottesville, VA)
Appl. No.:	18/318875
Filed:	May 17, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230291424 A1	Sep. 14, 2023

Related U.S. Application Data

continuation parent-doc US 17474231 20210914 US 11689230 child-doc US 18318875
continuation parent-doc US 17015942 20200909 US 11146299 20211012 child-doc US 17474231
us-provisional-application US 62897770 20190909

Publication Classification

Int. Cl.: H04B7/06 (20060101); **H04B1/00** (20060101); **H04B1/10** (20060101); **H04L27/08** (20060101)

U.S. Cl.:

CPC H04B1/10 (20130101); **H04B1/0028** (20130101); **H04B1/0078** (20130101); **H04L27/08** (20130101);

Field of Classification Search

CPC: H04B (1/10); H04B (1/0028); H04B (1/0078); H04B (1/18); H04L (27/08); H04L (27/06); Y02D (30/70)

USPC: 375/262

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6343185	12/2001	Aoshima et al.	N/A	N/A
6535724	12/2002	Pernici et al.	N/A	N/A
6646604	12/2002	Anderson	N/A	N/A
6853835	12/2004	Wynbeck	N/A	N/A
6867696	12/2004	Becken	N/A	N/A
7283475	12/2006	Fortin et al.	N/A	N/A
7362781	12/2007	Rhoads	N/A	N/A
7415018	12/2007	Jones et al.	N/A	N/A
7571269	12/2008	Schmidt et al.	N/A	N/A
7693191	12/2009	Gorday	N/A	N/A
7715446	12/2009	Rhoads	N/A	N/A
7813344	12/2009	Cheswick	N/A	N/A
8027663	12/2010	Rhoads	N/A	N/A
8081944	12/2010	Shaolin	N/A	N/A
8325704	12/2011	Emkin et al.	N/A	N/A
8848777	12/2013	Wang	N/A	N/A
8891595	12/2013	Farjadrad	375/257	H04B 1/0475
10089856	12/2017	Zong	N/A	N/A
11146299	12/2020	Huang	N/A	N/A
2003/0040326	12/2002	Levy et al.	N/A	N/A
2003/0076782	12/2002	Fortin	N/A	N/A
2003/0084148	12/2002	Cousins	N/A	N/A
2003/0091064	12/2002	Partridge	N/A	N/A
2003/0097439	12/2002	Strayer	N/A	N/A
2003/0203740	12/2002	Bahl	N/A	N/A
2004/0001221	12/2003	McCallum	N/A	N/A
2004/0059935	12/2003	Cousins	N/A	N/A
2005/0054319	12/2004	Tamaki	N/A	N/A
2005/0169201	12/2004	Huylebroeck	N/A	N/A
2005/0186906	12/2004	Hussmann	N/A	N/A
2007/0082647	12/2006	Behzad	N/A	N/A

2007/0082715	12/2006	Rofougaran	N/A	N/A
2008/0046549	12/2007	Saxena	N/A	N/A
2008/0240167	12/2007	Keaney	N/A	N/A
2009/0047991	12/2008	Elg	N/A	N/A
2010/0003935	12/2009	Behzad	N/A	N/A
2010/0067546	12/2009	Mishra	N/A	N/A
2010/0079254	12/2009	Koo et al.	N/A	N/A
2010/0105346	12/2009	Huang	N/A	N/A
2010/0120362	12/2009	Walley et al.	N/A	N/A
2010/0202767	12/2009	Shirakawa et al.	N/A	N/A
2011/0292977	12/2010	Farjadrad	375/220	H04L 12/10
2011/0299638	12/2010	Gauthier	N/A	N/A
2011/0317600	12/2010	Thomson et al.	N/A	N/A
2012/0256009	12/2011	Mucignat et al.	N/A	N/A
2013/0039239	12/2012	Lin	N/A	N/A
2013/0040573	12/2012	Hillyard	N/A	N/A
2013/0322313	12/2012	Sikri	N/A	N/A
2013/0336188	12/2012	Yomo	N/A	N/A
2014/0126442	12/2013	Jafarian	N/A	N/A
2014/0146756	12/2013	Sahin	N/A	N/A
2014/0254827	12/2013	Bailey	381/98	H04R 3/04
2015/0036575	12/2014	Li	N/A	N/A
2015/0333534	12/2014	Liu et al.	N/A	N/A
2018/0115195	12/2017	Dalwadi	N/A	N/A
2019/0097633	12/2018	Ullmann et al.	N/A	N/A
2019/0222126	12/2018	Parisi et al.	N/A	N/A
2020/0097112	12/2019	Seo	N/A	G06F 3/044

OTHER PUBLICATIONS

Selected USPTO Documents from 2003/0091064. cited by applicant

Berk, Vincent, et al., "Detection of Covert Channel Encoding in Network Packet Delays," Technical Report TR2005-536, Department of Computer Sciences, Dartmouth College, Hanover, NH, Aug. 2005. cited by applicant

Calhoun, Telvis E., et al., "An 802.11 MAC Layer Covert Channel," Wireless Communications and Mobile Computing (2010), Wiley InterScience www.interscience.wiley.com; DOI: 10.1002/wcm.969, Department of Computer Sciences, Georgia State University, Atlanta, GA 30303, USA. cited by applicant

Dye, Derek, "Bandwidth and detection of packet length cover channels," Issue date Mar. 2011, Monterey, California, Naval Postgraduate School, <http://hdl.handle.net/10945/5724>. cited by applicant

Edwards, Jonathan, "Covert Channels in Ad Hoc Networking: An Analysis Using the Optimized Link State Routing Protocol," A thesis submitted to the Faculty of Graduate and Postdoctoral Affairs in partial fulfillment of the requirements for the degree of Master of Applied Sciences in Electrical Computer Engineering, Carleton University, Ontario, Canada, Apr. 2012. cited by applicant

Girling, Gary, "Covert Channels in LAN's," IEEE Transactions on Software Engineering, vol. SE-13, No. 2, Feb. 1987. cited by applicant

Handel, Theodore, et al., "Hiding Data in the OSI Network Model," Weapon Design Technology Group, Los Alamos, NM 87545, pp. 23-38. cited by applicant

Ji, Liping, et al., "A Novel Covert Channel Based on Length of Messages," 2009 International

Symposium on Information Engineering and Electronic Commerce, Harbin Institute of Technology, Shenzhen Graduate School Shenzhen, P.R. China. cited by applicant

Kondo, Yoshihisa, et al., "Wake-up Radio using IEEE 802.11 Frame Length Modulation for Radio-on-Demand Wireless LAN," 2011 IEE 22nd International Symposium on Personal, Indoor and Mobile Radio Communications. cited by applicant

Kratzer, Christian, et al., "WLAN Steganography: A First Practical Reivew," Copyright 2006 ACM 1-59593-493-6060009, Department of Computer Science, Research Group Multimedia and Security, MM & Sec '06, Sep. 26-27, 2006, Geneva, Switzerland. cited by applicant

Lucena, Norka B., et al., "Covert Channels in IPv6," Syracuse University, Syracuse, NY 13244 USA, Copyright 2006, Springer-Verlag Berlin Heidelberg 2006, pp. 147-166. cited by applicant

Padlipsky, M.A., et al., "Limitations of End-to-End Encryption in Secure Computer Networks", Deputy for Technical Operations, Electronic Systems Division, Air Force Systems Command, Hanscom Air Force Base, Massachusetts; Pepered by The Mitre Corporation, Project 672B, Aug. 1978. cited by applicant

Panajotov, Boris, et al., "Covert Channels in TCP/IP Protocol Stack," ICT Innovations 2013 Web Proceedings ISSN 1857-7288, University "Goce Delcev", Faculty of Computer Science, "Krste Misirkov" bb, 2000, Stip, Republic of Macedonia, pp. 190-199. cited by applicant

Scott, Carlos, "Network Covert Channels: Review of Current State and Analysis of Viability of the Use of X.509 Certificates for Covert Communications," Technical Report RHUL-MA-2008-11, Jan. 15, 2008, Royal Holloway University of London, Department of Mathematics, England. cited by applicant

Stelte, Bjorn, et al., "Concealed Integrity Monitoring for Wireless Sensor Networks," Wireless Sensor Network, 2011, 3, 10-17, doi: 10.4236/wsn.2011.31002, Published online Jan. 2011, <http://www.scirp.org/journal.wsn>. cited by applicant

Wolf, Manfred, "Covert Channels in LAN Protocols," Tele-Consulting GMBH, Germany, pp. 91-101. cited by applicant

Yuan, Bo, et al., "A Covert Channel in Packet Switching Data Networks," Department of Networking, Security and Systems Administration, Rochester Institute of Technology, Rochester, NY 14623. cited by applicant

Zander, Sebastian, et al., "A Survey of Covert Channels and Countermeasures in Computer Network Protocols," 3rd Quarter 2007, vol. 9, No. 3, IEE Communications Survey, The Electronic Magazine of Original Peer-Reviewed Survey Articles, www.comsoc.org/pubs/surveys. cited by applicant

Zander, Sebastian, "Performance of Selected Noisy Covert Channels and Their Countermeasures in IP Networks," Thesis submitted in accordance with the requirements for the degree of Doctor of Philosophy, Swinburne University of Technology, Melbourne, Australia, Copyright May 2010. cited by applicant

Zhang, Xinyu, et al., "Gap Sense: Lightweight Coordination of Heterogeneous Wireless Devices," University of Wisconsin—Madison and the University of Michigan—Ann Arbor, supported in part by NSF Grant CNS-1160775. cited by applicant

Patent Cooperation Treaty, International Searching Authority, "Notification of Transmittal of the International Search Report and the Written Opinion," PCT Application No. PCT/US16/27280; date of mailing Jul. 15, 2016. cited by applicant

Patent Cooperation Treaty, "International Preliminary Report on Patentability," PCT Application No. PCT/US2014/028889, issued Sep. 15, 2015. cited by applicant

Chinese Intellectual Property Office, Patent Application No. 201480028106.0, English translation of First Office Action Issued Jul. 14, 2017. cited by applicant

Chinese Intellectual Property Office, Patent Application No. 201480028106.0, English translation of Third Office Action Issued Aug. 16, 2018. cited by applicant

European Patent Office, EP Patent Application No. 14771024.8, Examination Report No. 1, issued

Apr. 25, 2017. cited by applicant

European Patent Office, EP Patent Application No. 14771024.8, Examination Report No. 2, issued Feb. 19, 2018. cited by applicant

Korean Intellectual Property Office (KIPO), Patent Application No. 10-2015-7029467, English translation of Office Action, received from Korean associates on Aug. 21, 2017. cited by applicant

Korean Intellectual Property Office (KIPO), Patent Application No. 10-2015-7029467, English translation of Office Action, received from Korean associates on Jul. 10, 2018. cited by applicant

Primary Examiner: Shah; Tanmay K

Attorney, Agent or Firm: Dilworth & Barrese, LLP

Background/Summary

CROSS-REFERENCE TO RELATED PATENT APPLICATION (1) This application is a continuation of U.S. patent application Ser. No. 17/474,231, filed Sep. 14, 2021, which is a continuation of U.S. patent application Ser. No. 17/015,942, filed Sep. 9, 2020, and claims priority from U.S. Provisional Patent Application No. 62/897,770, filed Sep. 9, 2019, which all are incorporated by reference in their entirety herein.

FIELD OF THE INVENTION

(1) The invention is in the field of low-power sensor networks such as those that facilitate the internet of things (IoT).

BACKGROUND

(2) Networks of wireless sensor nodes have become ubiquitous in the internet of things (IoT). As the technologies related to IoT evolve, the main goals for development of components include improved (reduced) power consumption, increased speed/higher data rate, better sensitivity, and robustness.

(3) Ultra low power (ULP) receivers are gaining traction in various consumer and industrial markets as new standards are being defined to support them in IoT devices. Communication standards such as WiFi 802.11ba, BLE, and NB-IoT are all considering operating modes and signaling that take advantage of ULP receivers as companion radios for several reasons. They significantly reduce active and average power while providing continuous connectivity, thus enabling batteryless operation. They also simplify provisioning of new nodes, reduce synchronization energy overhead and latency to nearly zero, scale to networks of 1000s of nodes, and enable microsecond (ms) wakeup latency. ULP receivers have been demonstrated with better than -100 dBm sensitivity and 10 nW, but none have addressed aspects for widespread adoption such as selectivity, random pulsed interferer rejection, yield over process, voltage and temperature (PVT) variations, and security against replay or energy attacks.

(4) A key component of wireless sensor networks are sensor nodes, which include main circuit components such as wakeup receivers (WRXs). Because of the nature of the network, these receivers are typically ULP receivers. Most IoT networks comprise many ULP receivers that are tasked with receiving radio frequency (RF) wireless signals over the air (OTA) and taking some local action based on the ULP receiver's interpretation of the received RF signals. Translating the received RF signal into a local action typically involves translating the continuous RF signal to some discrete "on/off" (e.g., Wakeup) type of message to a local component of the IoT system.

(5) Current sensor nodes may have some low power characteristics. For example, certain ULP receive frontends that feature continuous-time analog circuitry do consume a relatively low amount of power. But they exhibit low sensitivity, and poor robustness in the presence of interference and

across wide temperature range.

(6) Another current type of ULP receive frontend is an intermediate frequency (IF) frontend with a continuous-time mixer and amplifiers. This type of frontend exhibits good sensitivity and selectivity characteristics, but consumes a relatively large amount of power.

(7) Current ULP receiver frontends tend to rely on continuous-time analog approaches to receive, process, translate, and transmit RF signals in sensor networks.

(8) It would be desirable to have a ULP receiver that overcomes the stated challenges of the current solutions. It would be desirable to have a ULP receiver that operates at very low power, and exhibits: above-average sensitivity; random pulsed interferer rejections; yield over process; voltage and temperature (PVT) variations; and security against replay or energy attacks.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is an illustration of a die including circuit components of a ULP receiver according to an embodiment.

(2) FIG. 1A is an illustration of a sensor node, according to an embodiment.

(3) FIG. 2 is a system block diagram of a sensor node, according to an embodiment.

(4) FIG. 3 is a block diagram of a wakeup receiver (WRX) circuit, according to an embodiment.

(5) FIG. 4A is a diagram of a parallel radio frequency (RF) rectification circuit, according to an embodiment.

(6) FIG. 4B is a diagram of a charge-transfer summation amplification (CTSA) circuit, according to an embodiment.

(7) FIG. 4C is a diagram of a successive approximation analog-to-digital (SAR ADC) circuit, according to an embodiment.

(8) FIG. 5 is block diagram showing clock generation circuit inputs and outputs, according to an embodiment.

(9) FIG. 6 is a series of signal timing diagrams illustrating ULP receiver operation, according to an embodiment.

DETAILED DESCRIPTION

(10) Embodiments of the invention include a wakeup receiver (WRX) featuring a charge-domain analog front end (AFE) with parallel radio frequency (RF) rectifier, charge-transfer summation amplifier (CTSA), and successive approximation analog-to-digital converter (SAR ADC) stages. In a particular embodiment, the invention includes a 3.2 μ W WRX with simplified 802.15.4g medium access control/physical layer (MAC/PHY) baseband, received signal strength indicator (RSSI) and clear channel assessment (CCA), forward error correction (FEC), and a cryptographic checksum for industrial IoT applications. The charge-domain AFE provides a conversion gain of 26 dB with no static bias currents used anywhere in the rectifier, CTSA, or SAR ADC. This provides robustness to process, voltage and temperature (PVT) variation, and pulsed interference rejection.

(11) Embodiments combine an ADC, a FIR filter and digital baseband to make a wakeup radio. A FIR filter can be implemented by changing the C.sub.T value overtime as the filter coefficient and summing with previous ADC samples. ASK modulation and Manchester encoding is supported. On-off keying (OOK) is a subset of ASK modulation. With the ADC, the WRX is able to support additional information encoded in the ASK RF message. Manchester is also supported. Multiple carrier frequencies are supported. As an example, 100 MHz to 3 GHz is used for a practical performance. However, embodiments are capable of frequencies as low as ~10 MHz and as high as 100 GHz depending on the quality factor of matching network 302.

(12) FIG. 1 is an illustration of a die layout (also referred to here as integrated circuit (IC)) 101 including circuit components of a ULP receiver according to an embodiment. The die includes an

integrated CTSA and ADC **104**, a clock generation circuit (CLKGEN) **106**, and an RF rectifier circuit **108**. As will be described in further detail below, embodiments of the invention provide improvements by colocating capacitors of the CTSA with those of the ADC in the circuit **104**.

(13) FIG. **1A** is an illustration of a sensor node **110**, according to an embodiment. The sensor node **110** has a form factor of approximately 5×5×8 cm.^{sup.3}. In this illustration, an antenna **112** is shown before the node unit is sealed. The IC **101** is present on the sensor node **110**.

(14) FIG. **2** is a system block diagram of a ULP receiver system. The system includes a Communication transceiver (Comm TRX) **202**, a radio frequency switch (RF SW) **204**, the antenna **112**, energy harvesting input sources (EH-Sources) **208**, and on-board sensors. A system-on-a-chip (SOC) **212** includes a microprocessor (MCU) **204**, energy harvesting power management unit (EH-PMU) **206**, CLK (or CLKGEN) **106**, and WRX (also referred to herein as wakeup receiver or ULP receiver) **300**.

(15) FIG. **3** is a block diagram of WRX circuit **300**, according to an embodiment. In an embodiment, the WRX **300** is a fully-integrated sub-GHz WRX with charge-domain analog front-end in 65 nm CMOS. WRX **300** incorporates a simplified 802.15.4g MAC/PHY baseband, RSSI and clear channel assessment, forward error correction, and a cryptographic checksum. It achieves a sensitivity of -67.5 dBm, SIR of -15.3 dB, RSSI accuracy of ±3 dB, and power of 3.2 μW across PVT variation.

(16) The WRX **300** is fully integrated into a system-on-a-chip (SoC) designed for an energy-harvesting industrial IoT leaf node, but is suitable for any type of node. A leaf node is typically an outer node in a sensor network. Signals from antenna **112** go through matching network **302**. A main RF path (Main) from the antenna **112** and a dummy path (Dummy) from a broadband load form a pseudo-differential signal that improves common-mode rejection. In an embodiment, a conventional FR-4 substrate (a known glass-reinforced epoxy laminate material for printed circuit boards) and on-board inductor and capacitor (LC) components are used for the matching network **302** to the custom antenna **112**.

(17) The charge-domain AFE **310** comprises parallel RF rectifiers **108**, a charge-transfer summation amplifier (CTSA) **104A**, and a 10-bit SAR ADC **104B**. The AFE **310** processes signals in the discrete-time charge domain as opposed to the traditional continuous-time analog approach. No static bias currents are required, providing low-power and robust operation over a wide range of conditions. In an embodiment, the WRX **300** down converts a Manchester encoded on-off keying modulation (OOK) RF wakeup message to baseband and digitizes the signal for demodulation, while providing reliable and rapid in-band and out-of-band interference rejection. The WRX **300** supports received signal strength indicator (RSSI) and CCA, used by the network layer for continuous traffic monitoring and link quality measurement.

(18) Baseband physical layer (BB PHY) **304** receives signals from the ADC **104B** and outputs a fast wakeup signal **306** and a secure wakeup signal **308**. The network can be configured for either fast wakeups of only a Sync Word or secure wakeups with a full WRX beacon packet with cryptographic checksum that includes a payload for data transfer without the need for a high-power receiver.

(19) A CLKGEN circuit **106**, as further described below, controls the operation of the WRX **300**. WRX CLK signal originates from an on-chip clock source using an on-board crystal reference.

(20) FIGS. **4A**, **4B** and **4C** illustrate an embodiment of a charge domain AFE **310** that features RF rectification, charge-transfer amplification, and SAR ADC conversion based on charge redistribution.

(21) FIG. **4A** is a diagram of an RF rectification circuit **108**, according to an embodiment. In one embodiment, the RF rectification circuit **108** includes multiple Dickson rectifier chains in parallel and down converts the RF input signal to the rectifier cap C.sub.R as static charge. A reset phase (controlled by reset signal rst) is used in every stage, making sure there is no intersymbol interference caused by residual charge on C.sub.R. This front-end therefore supports a wide

dynamic range of input power levels (from sensitivity level up to 7 dBm) without automatic gain control.

(22) In contrast to current solutions, parallel paths (leading to RECT_P_1 and RECT_P_2) achieve a high signal-to-noise ratio (SNR) and fast settling time. Specifically, longer chains (as in current solutions) produce higher settling times. As shown in FIG. 4A, embodiments include multiple (M) paths with (N) stages per path. e.g. 2×15 , or 3×10 . Then summing the M outputs from the N paths yields the final baseband output. This will settle faster than long chains because each M path is short (only N stages), yet has a better SNR compared to that of single $N \times M$ stages.

(23) FIG. 4B is a diagram of a CTSA circuit 104B, according to an embodiment. The CTAA stage shares capacitors with ADC 104B, and performs differential discrete-time summation and amplification through switched-cap operation. CDAC_P and CDAC_N are reused by CTSA as C.sub.O. The gain of the stage is determined by the capacitance ratio between C.sub.T and the ADC 104B C.sub.DAC. At the interface at the output of the M paths (from FIG. 4A) summation and gain occurs. This is done in the charge domain for more robust operation. The CTA circuit 104B effectively takes multiple input branches, and sums them to a single output, to provide both summation and gain. The CTSA circuit 104B takes in M analog inputs, and weights and sums each input on the output in the charge domain, understanding that the output cap of the charge domain amp is the sample cap of an ADC. First, two parallel rectifier chains down-convert the RF input signal onto C.sub.rect as static charge. A reset phase in every stage prevents intersymbol interference caused by residual charge on C.sub.rect and enables a wide dynamic range of input power levels without AGC. The following CTSA stage takes in parallel RF rectifier outputs, reuses ADC input DACs as its output capacitor C.sub.O, and performs differential discrete-time summation and amplification by a gain of $C_{\text{sub.T}}/C_{\text{sub.DAC}}$. The differential ADC samples from the CTSA output at the end of every cycle and performs asynchronous SAR operation based on charge-scaling C.sub.DAC.

(24) No static bias is used in the circuit.

(25) FIG. 4C is a diagram of a SAR ADC circuit 104B, according to an embodiment. Circuit 104B receives CTSA_N and CTSA_P from the previous stage 104A and performs A/D conversion to generate multiple bits of DOUT, which is for digital baseband demodulation.

(26) FIG. 5 is block diagram showing a clock generator block (CLKGEN) 106 that supports the discrete-time charge domain operation. CLKGEN 106 takes in the WRX clock signal and outputs S1, S2 and reset (RST) signals using logic gates, flip flops, and delay lines. The charge-domain AFE 310 seamlessly integrates RF down-conversion, baseband amplification, and A/D conversion without requiring driving-buffers and level-shifting circuits at each interface, thus saving power. The charge-domain topology is inherently robust against PVT variation because it is first-order bias and V.sub.th independent.

(27) FIG. 6 shows the timing and signal diagram of the AFE 310. Three clocking phases are required in every cycle of charge-domain operation. During the reset phase, C.sub.T is fully discharged, and C.sub.DAC is charged to V.sub.cm. During the pre-charge phase, inputs are reset to V.sub.cm, and source nodes of all the NFETs are charged to $V_{\text{sub.cm}} - V_{\text{sub.th}_n}$, and $V_{\text{sub.cm}} + V_{\text{sub.th}_p}$ for PFETs case. As a result, all the transistors serve as analog source followers in this phase. When in the amplify phase, the inputs connect to parallel rectifier outputs providing a $\Delta V_{\text{sub.in}}$ (w.r.t V.sub.cm), and the switch controlled by S.sub.2* is released, initiating charge redistribution between capacitors C.sub.T and C.sub.DAC. Therefore, the rectifier output is gained up by $C_{\text{sub.T}}/C_{\text{sub.DAC}}$ due to charge conservation. The effective capacitance of C.sub.T is tunable through a digitally controlled 6-bit capacitor bank, providing tunable gain in the AFE. Finally, the differential ADC samples from the CTA output at the end of every cycle and performs a 10-bit asynchronous SAR operation based on charge-scaling C.sub.DAC.

(28) In an embodiment, the WRX is fabricated in 65 nm CMOS and occupies 0.33 mm^{sup.2}. It shows the measured results from 15 parts at 6 temperature points between -40°C . to 85°C .

without any trimming. All measurements are reported with the SoC on-chip switching regulators and clock. Across PVT, the WRX achieves a mean sensitivity of -70.2 dBm for fast wakeup and -67.5 dBm for secure wakeup under 10% of packet error rate (PER), enabling in-network range in deployed industrial environments of 250 m, non-line-of-sight. It also demonstrates the in-band selectivity performance of the WRX under CW interference at -500 kHz offset. A mean signal-to-interference ratio (SIR) of -16.5 dB is measured for fast wakeup and -15.3 dB for secure wakeups. A -65 dB out-of-band SIR at 1.485 GHz offset (2.4 GHz) is achieved with the additional help from an on-board LC matching network without a SAW filter. In-band selectivity under AM-type interference of an OOK packet with the same bit rate is also measured, showing an SIR of 0 dB at 0 Hz offset, demonstrating a fast interference rejection capability. The WRX achieves an RSSI accuracy within ± 3 dB from -67 dBm to -43 dBm without calibration. The measured power for secure wakeup is shown in FIG. 5, with a mean across PVT of 3.2 μ W. A false-alarm rate of less than 10^{-3} is measured for both wakeup modes.

Claims

1. An ultra low-wakeup receiver (WRX) system, comprising: a matching network that receives signals from an antenna in a sensor network and outputs signals on a main RF signal from the antenna and a dummy signal from a broadband load, wherein the main RF signal and the dummy signal form a pseudo-differential signal that improves common-mode rejection; and an on-chip WRX comprising a charge-domain analog front end (AFE) configured to receive the pseudo-differential signal, and to output to the sensor network a fast wakeup signal and a secure wakeup signal, wherein the WRX operates at very low power, exhibits above-average sensitivity, and accomplishes random pulsed interferer rejections.
2. The system of claim 1, wherein the AFE further comprises: an RF rectifier circuit that processes the received RF signal as multiple signal paths M; and an amplifier circuit configured to receive output from the RF rectifier circuit and perform summation and amplification operations on the received output from the multiple signal paths M, wherein the amplifier circuit is a trans-impedance amplifier circuit.
3. The system of claim 2, wherein the AFE further comprises an analog-to-digital (ADC) circuit configured to receive an output of the amplifier circuit, and to convert the received output to a digital baseband format.
4. The system of claim 3, wherein the AFE further comprises a baseband physical layer configured to receive signals from the ADC and to output the fast wakeup signal and the secure wakeup signal.
5. The system of claim 4, wherein a sensor network in which the system resides is configurable for either fast wakeup signals of only a Sync Word or secure wakeup signals with a full wakeup receiver beacon packet with cryptographic checksum that includes a payload for data transfer without the need for a high-power receiver.
6. The system of claim 5, wherein the system is capable of frequencies as low as ~ 10 MHz and as high as 100 GHz depending on a quality factor of the matching network.
7. The system of claim 2, wherein multiple capacitors M are configured to receive outputs from multiple rectifier circuits M, and wherein the amplifier circuit is configured to receive output from the multiple capacitors M and perform summation and amplification operations on the received outputs from the multiple parallel signal paths M.
8. The system of claim 2, wherein the amplifier circuit is a charge domain amplifier circuit and at least the summation operation is performed in the charge domain.
9. The system of claim 1, wherein the received RF signals comprises amplitude shift keying (ASK) modulation.
10. The system of claim 1, wherein the received RF signals comprises Manchester encoding.
11. The system of claim 2, wherein the on-chip WRX is configured to operate at multiple carrier

frequencies.

12. The system of claim 1, wherein the outputs of the on-chip WRX include information regarding received signal strength.
 13. The system of claim 3, wherein the ADC circuit is a successive approximation analog-to-digital (SAR ADC) circuit.
 14. The system of claim 2, wherein the amplifier circuit is further configured to receive output from the RF rectifier circuit and perform a differencing operation on the received output.
-