

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12413615
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Dani; Mayuresh Vishwas et al.

Attack path and graph creation based on user and system profiling

Abstract

Methods and systems for generating an attack path based on user and system risk profiles are presented. A method comprises determining user information associated with a computing device; determining system exploitability information of the computing device; determining system criticality information of the computing device; determining a risk profile for the computing device based on the user information, the system exploitability information, and the system criticality information; and generating an attack path based on the risk profile. The attack path indicates a route through which an attacker accesses the computing device. The system exploitability information is associated with or based on one or more of the vulnerability associated with the computing device, an exposure window associated with the computing device, and a protection window associated with the computing device. The system criticality information is associated with or based on one or more assets and services associated with the computing device.

Inventors: Dani; Mayuresh Vishwas (Fremont, CA), Tyagi; Ankur S. (Foster City, CA), Bhide; Rishikesh Jayaram (Pune, IN)

Applicant: Qualys, Inc. (Foster City, CA)

Family ID: 74346306

Assignee: Qualys, Inc. (Foster City, CA)

Appl. No.: 18/600442

Filed: March 08, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240214411 A1	Jun. 27, 2024

Related U.S. Application Data

continuation parent-doc US 17839339 20220613 US 11968225 child-doc US 18600442
continuation parent-doc US 16516734 20190719 US 11363052 20220614 child-doc US 17839339

Publication Classification

Int. Cl.: H04L9/40 (20220101)

U.S. Cl.:

CPC H04L63/1433 (20130101);

Field of Classification Search

CPC: H04L (63/1433)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6952779	12/2004	Cohen	726/22	H04L 63/1433
10754959	12/2019	Rajasooriya	N/A	G06N 7/01
10848515	12/2019	Pokhrel	N/A	H04L 63/1433
11363052	12/2021	Dani	N/A	H04L 63/1433
11483335	12/2021	Tsokos	N/A	G06N 7/01
11704414	12/2022	Patel	726/25	G06F 21/604
11968225	12/2023	Dani	N/A	H04L 63/1433
12088618	12/2023	Revankar	N/A	H04L 63/1441
2015/0058993	12/2014	Choi	726/25	H04L 63/1433

2015/0101053	12/2014	Sipple	N/A	N/A
2016/0359872	12/2015	Yadav	N/A	H04L 63/1408
2017/0244744	12/2016	Key et al.	N/A	N/A
2017/0286690	12/2016	Chari	N/A	G06F 21/577
2018/0025154	12/2017	Cornell et al.	N/A	N/A
2018/0176245	12/2017	Cornell et al.	N/A	N/A
2018/0351987	12/2017	Patel et al.	N/A	N/A
2020/0137103	12/2019	Ngo et al.	N/A	N/A
2020/0327222	12/2019	Chhabra	N/A	H04L 63/0421
2020/0351298	12/2019	Paturi et al.	N/A	N/A
2020/0380522	12/2019	Perkal et al.	N/A	N/A
2021/0297441	12/2020	Olalere	N/A	N/A
2021/0392163	12/2020	Tang et al.	N/A	N/A
2022/0060509	12/2021	Crabtree et al.	N/A	N/A
2022/0116783	12/2021	Goel	N/A	N/A
2023/0140160	12/2022	Vetsch et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
WO-2014066319	12/2013	WO	G06F 21/55
WO-2018165602	12/2017	WO	G06F 21/53

OTHER PUBLICATIONS

Microsoft, “Allocated Altitudes”, Retrieved from: <https://docs.microsoft.com/en-us/windows-hardware/drivers/ifs/allocated-altitudes>, Published on Apr. 20, 2017, 92 pages. cited by applicant

Microsoft, “All Attributes”, Retrieved from: <https://docs.microsoft.com/en-us/windows-hardware/drivers/ifs/allocated-altitudes>, Published on May 31, 2018, 40 pages. cited by applicant

Broadcom, “Symantec™ DeepSight™ Intelligence”, Retrieved from: <https://docs.broadcom.com/docs/deepsight-intelligence-ds>, Web Accessed; Mar. 4, 2020, 5 pages. cited by applicant

Broadcom, “Cyber Security Services: DeepSight™ Intelligence”, Retrieved from: <https://docs.broadcom.com/docs/deepsight-intelligence-overview-en>, Web Accessed; Mar. 4, 2020, 6 pages. cited by applicant

Primary Examiner: Su; Sarah

Attorney, Agent or Firm: Baker & McKenzie LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) The present application claims priority to, and is a continuation of U.S. patent application Ser. No. 17/839,339, filed Jun. 13, 2022, which claims priority to, and is a continuation of U.S. patent application Ser. No. 16/516,734, filed Jul. 19, 2019, now U.S. Pat. No. 11,363,052, issued on Jun. 14, 2022, all the disclosures of which are incorporated by reference herein in their entirety for all purposes.

TECHNICAL FIELD

(1) The present disclosure relates to computer security. More specifically, the present disclosure relates to methods and systems for generating an attack path based on user and computer system risk profile.

BACKGROUND

(2) Computer security threats are increasingly evolving at an alarming rate. This is in part due to vulnerability information associated with networks, computing systems, and users that attackers exploit. For example, most organization are unaware that attackers sometimes target specific systems or users based on certain qualities of such users or based on certain security attributes (e.g., risk profiles) that the targeted computing systems or users have. For instance, a particular user may have a predilection to visit certain websites, download certain files/applications, enable certain specific computer security features on his/her computer, etc. This information, which can be mined by an attacker, can sometimes be used in executing a targeted computer security breach against such a user.

(3) In some cases, attackers use system data associated with a given computing system to execute attacks against the given computing system. This data may include types of hardware of the computing system, the operating system of the computing system, services enabled on the computing system, etc. Once an attacker detects vulnerability in a given computer system's hardware or software configuration, the attacker proceeds to execute an attack on the computing system based on the detected vulnerability.

(4) Furthermore, some attackers are able to leverage user information and system information across a plurality of computing devices in a given organization in order to execute a given attack campaign against said organization. An analysis of such attack campaigns usually show that the attackers work their way through certain computer assets (e.g., servers, databases, files, software, hardware, computing device, etc.) having certain vulnerability attributes in order to reach their targeted computer assets. In some instances, attackers follow certain “favorable” computer network routes that are likely to make the attack campaign against the given organization successful.

SUMMARY

(5) According to one aspect of the subject matter described in this disclosure, a method for generating an attack path is presented. The method comprises determining user information indicating one or more user attributes associated with a vulnerability of a computing device. The method also comprises determining system exploitability information of the computing device, the system exploitability information indicating one or more of: the vulnerability associated with the computing device, an exposure window associated with the computing device, a protection window associated with the computing device. The method further comprises determining system criticality information of the computing device, the system criticality information indicating one or more: assets associated with the computing device, services associated with the computing device. In one implementation, the method comprises determining a risk profile for the computing device based on the user information, the system exploitability information, and the system criticality information. Based on the risk profile, the method initiates generation of an attack path the attack path indicating a route through which an attacker accesses the computing device.

(6) Other implementations of one or more of these aspects include corresponding systems, apparatus, and computer programs, configured to perform the actions of the methods, encoded on computer storage devices. These and other implementations may each optionally include one or more of the following features. The one or more user attributes associated with the vulnerability of the computing device comprises: types of websites the user

visits, the user's browser history data, types of files the user runs, passwords of the user stores in a browser, application and system credentials of the user, sensitive user credentials such as internet information services (IIS) application pool, user credentials stored in plain-text on the computing device, number of browser extensions plugins associated with a browser of the user, number of plugins associated with the browser of the user, privileges of the user on the computing device, whitelisted applications within a security infrastructure associated with the user, and automatic logon configurations associated with the user. The vulnerability is based on data relating to vulnerability and patching (e.g., applying security patches) associated with the computing device. The data relating to vulnerability and patching include on one or more of: a hardware specification of the computing device, whether the operating system of the computing device is up to date, a list of shared directories on the computing device, whether the computing device has the latest patches, whether the computing device has the latest services enabled, one or more connectivity types associated with the computing device, and types of security solutions/systems associated with the computing device. The exposure window represents an average amount of time where the computing device remains unpatched after a new patch associated with the computing device is released. The protection window represents the average time where security solutions of the security infrastructure associated with the computing device do not have one or more of latest definitions, latest patches, and latest signatures. The risk profile is determined based on combining the user information, the system exploitability information, and the system criticality information

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The disclosure is illustrated by way of example, and not by way of limitation in the figures of the accompanying drawings in which like reference numerals are used to refer to similar elements. It is emphasized that various features may not be drawn to scale and the dimensions of various features may be arbitrarily increased or reduced for clarity of discussion. Further, some components may be omitted in certain figures for clarity of discussion.
- (2) FIG. 1 shows a high level network diagram of an example system for which an attack path is generated, in accordance with some embodiments of this disclosure.
- (3) FIG. 2 is a functional block diagram of a computing environment, in accordance with some embodiments of this disclosure.
- (4) FIG. 3 is a detailed system diagram of a computing environment, in accordance with some embodiments of this disclosure.
- (5) FIG. 4 shows example attack paths for attacks executed against a system, in accordance with some embodiments of this disclosure.
- (6) FIG. 5 shows an example flowchart for generating an attack path, in accordance with some embodiments of this disclosure.

DETAILED DESCRIPTION

- (7) The present disclosure describes various techniques and systems for generating attack paths and for generating attack graphs based on user and/or system risk profiles. An attack path could include digital routes, digital pathways, or one or more computer systems through which an attacker works to get to/attack a targeted computing system/computer asset/computing device. In some embodiments, an attacker executes an attack campaign against a user or against an organization via a predefined path having specific vulnerability issues. An attack campaign could comprise a collection of techniques and tactics used to execute an attack on a computing system/device.
- (8) As previously noted, attackers such as Advanced Persistent Threat (APT) groups, Script Kiddies, White Hat hackers, Black Hat hackers, Grey Hat hackers, Green Hat hackers, Red Hat hackers, and Blue Hat hackers are increasingly improving their efforts to execute computer attacks (e.g., cyberattacks, attack campaigns, etc.) against individuals and organizations. These attackers execute attack types that include phishing attacks, spear phishing attacks, whale phishing attacks, malware attacks, ransomware attacks, drive-by attacks, Trojan horse attacks, SQL injection attacks, cross site scripting attacks, denial-of-service attacks, password attacks, data exfiltration attacks, eavesdropping attacks, birthday attacks, brute-force attacks, insider threat attacks, man-in-the-middle attacks, AI powered attacks, etc. Regardless of the attack type, attackers are often successful in implementing attack execution operations associated with a given attack type when they have some information about the individuals, and/or organizations, and/or computing systems, etc., that are being targeted. Information about targeted individuals, and/or organizations, and/or computing systems in some cases is computer security vulnerability information associated with the targeted individuals, and/or organizations, and/or computing systems. The more of this type of information is available to attackers, the higher the likelihood of attackers having successful attack execution operations.
- (9) Computer security vulnerability information is not only beneficial to attackers. Individuals and organizations that pay attention to this type of data are able to identify points of vulnerability within their computing infrastructure, determine likely attack paths that an attacker can use to execute attack execution operations associated with a specific attack type, prioritize securing (e.g., patch updates, OS updates, antivirus updates, and other security measures taken to secure a given computer system) computing assets within a given computing infrastructure, and predicting attack paths for a given computing infrastructure, etc. In some embodiments, the vulnerability information may be used to simulate attack execution operations (e.g., red teaming/pentesting attack scenarios) in order to better understand vulnerable points within one's IT infrastructure. In some cases, the vulnerability information (e.g., comprised in the risk profile discussed below) may facilitate automatically selecting the most vulnerable or most lucrative assets (e.g., computing device, hardware and/or software resources) within a given computing system/device. In other cases, the data obtained from the vulnerability information may be "ingested" or processed by other systems (e.g., Artificial Intelligence software, machine learning resources, Qualys Breach and Attack Simulation system, etc.) in order to develop more robust computer security systems, tools, and security models. The systems discussed in this disclosure are able to determine computer security vulnerability information for a user, and/or organization, and/or a computing device associated with the user and/or the organization and are subsequently used to generate attack paths.

System Environment

- (10) Illustrated in FIG. 1 is a high level diagram of a network diagram of an example system **100** for executing the principles disclosed herein. In the illustrated implementation, the system **100** may include servers **105a**, **105b** . . . **105n** coupled to a network **110**. The system **100** may also include exemplary endpoint devices **125a**, **125b** . . . **125n** communicatively coupled via the network **110**. For simplicity, a server **105** may be used in some cases to refer to one or more servers **105a**, **105b** . . . **105n**. Similarly, an endpoint device **125** may be used in some instances to refer to one or more endpoint devices **125a**, **125b** . . . **125n**.
- (11) The server **105** may include a computing device such as a mainframe server, a content server, a communication server, a laptop computer, a desktop computer, a handheld computing device, a smart phone, a smart watch, a wearable device, a touch screen, a biometric device, a video processing device, an audio processing device, a virtual machine, a cloud-based computing solution and/or service, and/or the like. The server **105** may include a plurality of computing devices configured to communicate with one another and/or implement the techniques described herein.
- (12) In one embodiment, the server **105** may include various elements of a computing environment as described herein (e.g., computing environment **200** of FIG. 2 and/or FIG. 3). For example, the server **105** may include processing unit **202**, a memory unit **204**, an input/output (I/O) unit **206**, and/or a communication unit **208**. The server **105** may further include subunits and/or other instances as described herein for performing operations associated with malware detection and remediation. A user (e.g., network administrator) may operate server **105** either locally or remotely.
- (13) Further, the server **105** may include a web server **115**, security infrastructure **140**, and a web and agent resources **160**. The web server **115**, the security infrastructure **140**, and the web and agent resources **160** are coupled to each other and to the network **110** via one or more signal lines. The one or more signal lines may be a wired and/or wireless connection. In some embodiments, the server **105** may be a database (DB) server and/or a file server such as those shown in FIG. 4.
- (14) The web server **115** may include a secure socket layer (SSL) proxy **145** for establishing HTTP-based connectivity **150** between the server **105**

and other devices coupled to the network **110**. Other forms of secure connection techniques, such as encryption, may be employed on the web server **115** and across the network **110**. Additionally, the web server **115** may deliver artifacts (e.g., binary code, instructions, etc.) to the security infrastructure **140** either directly via the SSL proxy **145** and/or via the network **110**. Additionally, the web and agent resources **160** of the server **105** may be provided to the endpoint device **125** via the web app **165** on the web server **115**. The web and agent resources **160** may be used to render a web-based graphical interface (GUI) **170** via the browser **155** running on the endpoint device **125**.

(15) The security infrastructure **140** may either be on the server **105** and/or on the endpoint device **125**. Security infrastructure **140** may include one or more computer security products such as access control software, anti-keyloggers, anti-malware, anti-spyware, anti-subversion software, anti-tamper software, antivirus software, cryptographic software, computer-aided dispatch (CAD), Firewall (web or otherwise), Intrusion detection systems (IDS), Intrusion prevention systems (IPS), log management software, records management software, Sandboxes (e.g., a secure environment in which various computing processes may be executed), security information management software, security information and event management (SIEM) software, anti-theft software, parental control software, cloud-based security protection, and/or the like.

(16) In some embodiments, security infrastructure **140** can determine whether scan data is indicative of malware and generates a report indicating that the endpoint device **125** is exposed to risks associated with malware. The report may include a listing of identified attributes, a count of identified attributes, a type of each identified attribute, identification of each malware family and/or malware variant determined to be associated with the endpoint device **125**, and/or one or more recommendations for addressing detected vulnerabilities. This record may be stored on the local record repository **103** and/or within a database.

(17) In some cases, security infrastructure **140** can determine a risk profile associated with a given user, a risk profile associated with a given computer system associated with the user, a risk profile associated with a given organization, a risk profile associated with computing systems associated with the organization, etc. In particular, security infrastructure can include code/logic that operates at a desired level of granularity to determine computer vulnerability information included in a given risk profile. The level of granularity could be based on a single computing system associated with an individual or organization, multiple computing systems associated with an individual or organization, specific hardware resources associated with a computing system of an individual or organization, specific software resources associated with a computing system of an individual or organization, etc.

(18) In some cases, the security infrastructure **140** may determine vulnerable computer assets (e.g., computer systems/devices, files, software resources, hardware resources, etc.) associated with an individual (e.g., user of security infrastructure **140**) or organization based on the security profile of the individual and/or security profile of the organization as discussed above. In other embodiments, the security infrastructure **140** may determine attack paths to vulnerable assets within the software and/or hardware configuration of the system **100**. In some cases, the security infrastructure **140** may “feed” security profile data (e.g., computer vulnerability information) to an ingesting product (e.g., third-party analytics software) and or to security specialists for further analysis. In one embodiment, further analysis of security profile data may include using graph theory to determine a path of least resistance to a given computer asset with the system **100**, alternative paths to a given computer asset when security parameters are varied within the system **100**, remediation strategies to adopt given an identified path to a given computer asset within the system **100**, etc.

(19) In some further embodiments, the security infrastructure **140** may access an operating system **180** of the endpoint device **125** in order to execute security operations as discussed elsewhere in this disclosure. For instance, the security infrastructure **140** may gain access into the operating system in order to scan a security posture of the endpoint device **125** by scanning a system configuration **185**, a file system **190**, and/or system services **195** of the endpoint device **125**. The plug-in **175** of the web browser **155** may provide needed downloads that facilitate operations executed by the operating system **180**, the security infrastructure **140**, and/or other applications running on the endpoint device **125**.

(20) The network **110** may include a plurality of networks. For instance, the network **110** may include any wired and/or wireless communication network that facilitates communication between the server **105** and the endpoint device **125**. The network **110**, in some instances, may include an Ethernet network, a cellular network, a computer network, the Internet, a wireless fidelity (Wi-Fi) network, a light fidelity (Li-Fi) network, a Bluetooth network, a radio frequency identification (RFID) network, a near-field communication (NFC) network, a laser-based network, and/or the like.

(21) Turning back to FIG. 1, the endpoint device **125** may be a handheld computing device, a smart phone, a tablet, a laptop computer, a desktop computer, a personal digital assistant (PDA), a smart watch, a wearable device, a biometric device, an implanted device, a camera, a video recorder, an audio recorder, a touchscreen, a computer server, a virtual server, a virtual machine, and/or a video communication server. In some embodiments, the endpoint device **125** may include a plurality of computing devices configured to communicate with one another and/or implement the techniques described herein.

(22) The local record repository **103**, shown in association with the endpoint device **125**, may be one or more storage devices that store data, information, and instructions used by the endpoint device **125** and/or other devices coupled to the network **110**. The stored information may include various logs/records associated with captured security data/security events by the security infrastructure **140**. For example, the various reports, logs, data, etc., generated by the one or more security products of the security infrastructure **140** may be stored in the local record repository. In some embodiments, the local record repository also stores cache data, user preference data, security profile data including computer security vulnerability data, etc.

(23) The one or more storage devices discussed above in association with the local record repository **103** can be non-volatile memory or similar permanent storage device and media. For example, the one or more storage devices may include a hard disk drive, a floppy disk drive, a CD-ROM device, a DVD-ROM device, a DVD-RAM device, a DVD-RW device, a flash memory device, solid state media, or some other mass storage device known in the art for storing information on a more permanent basis.

(24) FIGS. 2 and 3 illustrate exemplary functional and system diagrams of a computing environment **200**, according to some embodiments of this disclosure, for performing the operations described herein. Specifically, FIG. 2 provides a functional block diagram of the computing environment **200**, whereas FIG. 3 provides a detailed system diagram of the computing environment **200**.

(25) As seen in FIGS. 2 and 3, the computing environment **200** may include a processing unit **202**, a memory unit **204**, an I/O unit **206**, and a communication unit **208**. The processing unit **202**, the memory unit **204**, the I/O unit **206**, and the communication unit **208** may include one or more subunits for performing operations described herein. Additionally, each unit and/or subunit may be operatively and/or otherwise communicatively coupled with each other so as to facilitate the operations described herein. The computing environment **200** including any of its units and/or subunits may include general hardware, specifically-purposed hardware, and/or software.

(26) Importantly, the computing environment **200** and any units and/or subunits of FIG. 2 and/or FIG. 3 may be included in one or more elements of system **100** as described with reference to FIG. 1. For example, one or more elements (e.g., units and/or subunits) of the computing environment **200** may be included in the server **105** and/or the endpoint device **125**.

(27) The processing unit **202** may control one or more of the memory unit **204**, the I/O unit **206**, and the communication unit **208** of the computing environment **200**, as well as any included subunits, elements, components, devices, and/or functions performed by the memory unit **204**, I/O unit **206**, and the communication unit **208**. The described sub-elements of the computing environment **200** may also be included in similar fashion in any of the other units and/or devices included in the system **100** of FIG. 1. Additionally, any actions described herein as being performed by a processor may be taken by the processing unit **202** of FIG. 2 and/or FIG. 3 alone and/or by the processing unit **202** in conjunction with one or more additional processors, units, subunits, elements, components, devices, and/or the like. Further, while one processing unit **202** may be shown in FIG. 2 and/or FIG. 3, multiple processing units may be present and/or otherwise included in the computing environment **200** or elsewhere in the overall system

(e.g., system **100** of FIG. **1**). Thus, while instructions may be executed by the processing unit **202** (and/or various subunits of the processing unit **202**), the instructions may be executed simultaneously, serially, and/or otherwise by one or multiple processing units **202** on one or more devices.

(28) In some embodiments, the processing unit **202** may be implemented as one or more computer processing unit (CPU) chips and/or graphical processing unit (GPU) chips and may include a hardware device capable of executing computer instructions. The processing unit **202** may execute instructions, codes, computer programs, and/or scripts. The instructions, codes, computer programs, and/or scripts may be received from and/or stored in the memory unit **204**, the I/O unit **206**, the communication unit **208**, subunits, and/or elements of the aforementioned units, other devices, and/or computing environments, and/or the like.

(29) In some embodiments, the processing unit **202** may include, among other elements, subunits such as a content management unit **212**, a location determination unit **214**, a graphical processing unit (GPU) **216**, and a resource allocation unit **218**. Each of the aforementioned subunits of the processing unit **202** may be communicatively and/or otherwise operably coupled with each other.

(30) The content management unit **212** may facilitate generation, modification, analysis, transmission, and/or presentation of content. Content may be file content, media content, malware content, or any combination thereof. In some instances, Content on which the content management unit **212** may operate includes device information, user interface data, images, text, themes, audio files, video files, documents, and/or the like. Additionally, the content management unit **212** may control the audio-visual environment and/or appearance of application data during execution of various processes (e.g., via web GUI **170** at the endpoint device **125**). In some embodiments, the content management unit **212** may interface with a third-party content server and/or memory location for execution of its operations.

(31) The location determination unit **214** may facilitate detection, generation, modification, analysis, transmission, and/or presentation of location information. Location information may include global positioning system (GPS) coordinates, an Internet protocol (IP) address, a media access control (MAC) address, geolocation information, a port number, a server number, a proxy name and/or number, device information (e.g., a serial number), an address, a zip code, and/or the like. In some embodiments, the location determination unit **214** may include various sensors, radar, and/or other specifically-purposed hardware elements for the location determination unit **214** to acquire, measure, and/or otherwise transform location information.

(32) The GPU **216** may facilitate generation, modification, analysis, processing, transmission, and/or presentation of content described above, as well as any data (e.g., scanning instructions, scan data, and/or the like) described herein. In some embodiments, the GPU **216** may be utilized to render content for presentation on a computing device (e.g., via web GUI **170** at the endpoint device **125**). The GPU **216** may also include multiple GPUs and therefore may be configured to perform and/or execute multiple processes in parallel. In some implementations, the GPU **216** may be used in conjunction with security profile generation unit **234**, attack path generation unit **236**, a threat detection unit (not shown), a scan history unit (not shown), and/or other subunits associated with the memory unit **204**, the I/O unit **206**, the communication unit **208**, and/or a combination thereof.

(33) The resource allocation unit **218** may facilitate the determination, monitoring, analysis, and/or allocation of computing resources throughout the computing environment **200** and/or other computing environments. For example, the computing environment may facilitate a high volume of data (e.g., files, malware, malware variants, etc.), to be processed and analyzed. As such, computing resources of the computing environment **200** utilized by the processing unit **202**, the memory unit **204**, the I/O unit **206**, and/or the communication unit **208** (and/or any subunit of the aforementioned units) such as processing power, data storage space, network bandwidth, and/or the like may be in high demand at various times during operation. Accordingly, the resource allocation unit **218** may include sensors and/or other specially-purposed hardware for monitoring performance of each unit and/or subunit of the computing environment **200**, as well as hardware for responding to the computing resource needs of each unit and/or subunit. In some embodiments, the resource allocation unit **218** may utilize computing resources of a second computing environment separate and distinct from the computing environment **200** to facilitate a desired operation.

(34) For example, the resource allocation unit **218** may determine a number of simultaneous computing processes and/or requests. The resource allocation unit **218** may also determine that the number of simultaneous computing processes and/or requests meets and/or exceeds a predetermined threshold value. Based on this determination, the resource allocation unit **218** may determine an amount of additional computing resources (e.g., processing power, storage space of a particular non-transitory computer-readable memory medium, network bandwidth, and/or the like) required by the processing unit **202**, the memory unit **204**, the I/O unit **206**, the communication unit **208**, and/or any subunit of the aforementioned units for safe and efficient operation of the computing environment while supporting the number of simultaneous computing processes and/or requests. The resource allocation unit **218** may then retrieve, transmit, control, allocate, and/or otherwise distribute determined amount(s) of computing resources to each element (e.g., unit and/or subunit) of the computing environment **200** and/or another computing environment.

(35) In some embodiments, data affecting the allocation of computing resources by the resource allocation unit **218** may include the number of computing processes and/or requests, a duration of time during which computing resources are required by one or more elements of the computing environment **200**, and/or the like. In some implementations, computing resources may be allocated to and/or distributed amongst a plurality of second computing environments included in the computing environment **200** based on one or more data mentioned above. In some embodiments, the allocation of computing resources of the resource allocation unit **218** may include the resource allocation unit **218** flipping a switch, adjusting processing power, adjusting memory size, partitioning a memory element, transmitting data, controlling one or more input and/or output devices, modifying various communication protocols, and/or the like. In some embodiments, the resource allocation unit **218** may facilitate utilization of parallel processing techniques such as dedicating a plurality of GPUs included in the processing unit **202** for running a multitude of processes.

(36) The memory unit **204** may be utilized for storing, recalling, receiving, transmitting, and/or accessing various files and/or data (e.g., malware files, malware samples, scan data, and/or the like) during operation of computing environment **200**. For example, memory unit **204** may be utilized for storing, recalling, and/or updating scan history information as well as other data associated with, resulting from, and/or generated by any unit, or combination of units and/or subunits of the computing environment **200**. In some embodiments, the memory unit **204** may store instructions, code, and/or data that may be executed by the processing unit **202**. For instance, the memory unit **204** may store code that executes operations associated with one or more units and/or one or more subunits of the computing environment **200**. For example, the memory unit may store code for the processing unit **202**, the I/O unit **206**, the communication unit **208**, and for itself.

(37) Memory unit **204** may include various types of data storage media such as solid state storage media, hard disk storage media, virtual storage media, and/or the like. Memory unit **204** may include dedicated hardware elements such as hard drives and/or servers, as well as software elements such as cloud-based storage drives. In some implementations, memory unit **204** may be a random access memory (RAM) device, a dynamic random access memory (DRAM) device, a static random access memory (SRAM) device, flash memory, read only memory (ROM) device, and/or various forms of secondary storage. The RAM device may be used to store volatile data and/or to store instructions that may be executed by the processing unit **202**. For example, the instructions stored by the RAM device may be a command, a current operating state of computing environment **200**, an intended operating state of computing environment **200**, and/or the like. As a further example, data stored in the RAM device of memory unit **204** may include instructions related to various methods and/or functionalities described herein. The ROM device may be a non-volatile memory device that may have a smaller memory capacity than the memory capacity of a secondary storage. The ROM device may be used to store instructions and/or data that may be read during execution of computer instructions. In some embodiments, access to both the RAM device and ROM device may be faster to access than the secondary storage.

(38) Secondary storage may comprise one or more disk drives and/or tape drives and may be used for non-volatile storage of data or as an over-flow data storage device if the RAM device is not large enough to hold all working data. Secondary storage may be used to store programs that may be loaded into the RAM device when such programs are selected for execution. In some embodiments, the memory unit **204** may include one or more

databases **310** (shown in FIG. 3) for storing any data described herein. For example, depending on the implementation, the one or more databases may be used as the local record repository **103** of the endpoint device discussed with reference to FIG. 1. Additionally or alternatively, one or more secondary databases located remotely from computing environment **200** may be utilized and/or accessed by memory unit **204**. In some embodiments, memory unit **204** and/or its subunits may be local to the server **105** and/or the endpoint device **125** and/or remotely located in relation to the server **105** and/or the endpoint device **125**.

(39) Turning back to FIG. 2, the memory unit **204** may include subunits such as an operating system unit **226**, an application data unit **228**, an application programming interface **230**, a content storage unit **232**, security infrastructure **140**, and a cache storage unit **240**. Each of the aforementioned subunits of the memory unit **204** may be communicatively and/or otherwise operably coupled with each other and other units and/or subunits of the computing environment **200**. It is also noted that the memory unit **204** may include other modules, instructions, or code that facilitate the execution of the techniques described herein.

(40) The operating system unit **226** may facilitate deployment, storage, access, execution, and/or utilization of an operating system utilized by computing environment **200** and/or any other computing environment described herein. In some embodiments, operating system unit **226** may include various hardware and/or software elements that serve as a structural framework for processing unit **202** to execute various operations described herein. Operating system unit **226** may further store various pieces of information and/or data associated with the operation of the operating system and/or computing environment **200** as a whole, such as a status of computing resources (e.g., processing power, memory availability, resource utilization, and/or the like), runtime information, modules to direct execution of operations described herein, user permissions, security credentials, and/or the like.

(41) The application data unit **228** may facilitate deployment, storage, access, execution, and/or utilization of an application utilized by computing environment **200** and/or any other computing environment described herein. For example, the endpoint device **125** may be required to download, install, access, and/or otherwise utilize a software application (e.g., web application **165**) to facilitate performance of malware scanning operations and/attack path generation as described herein. As such, application data unit **228** may store any information and/or data associated with an application. Application data unit **228** may further store various pieces of information and/or data associated with the operation of an application and/or computing environment **200** as a whole, such as a status of computing resources (e.g., processing power, memory availability, resource utilization, and/or the like), runtime information, user interfaces, modules to direct execution of operations described herein, user permissions, security credentials, and/or the like.

(42) The application programming interface (API) unit **230** may facilitate deployment, storage, access, execution, and/or utilization of information associated with APIs of computing environment **200** and/or any other computing environment described herein. For example, computing environment **200** may include one or more APIs for various devices, applications, units, subunits, elements, and/or other computing environments to communicate with each other and/or utilize the same data. Accordingly, API unit **230** may include API databases containing information that may be accessed and/or utilized by applications, units, subunits, elements, and/or operating systems of other devices and/or computing environments. In some embodiments, each API database may be associated with a customized physical circuit included in memory unit **204** and/or API unit **230**. Additionally, each API database may be public and/or private, and so authentication credentials may be required to access information in an API database. In some embodiments, the API unit **230** may enable the server **105** and the endpoint device **125** to communicate with each other.

(43) The content storage unit **232** may facilitate deployment, storage, access, and/or utilization of information associated with performance of malware scanning operations and/or framework processes by computing environment **200** and/or any other computing environment described herein. In some embodiments, content storage unit **232** may communicate with content management unit **212** to receive and/or transmit content files (e.g., media content).

(44) Security infrastructure **140** may include at least a security profile generation unit **234**, attack path generation unit **236**, threat detection unit (not shown), and a scan history unit (not shown). In one embodiment, security profile generation unit **234** may generate a risk profile of a user of the endpoint device **125**. This type of risk profile may be referred to simply as “user behavior” or “user information” in some embodiments. In some cases, the risk profile of the user may indicate one or more user attributes associated with a vulnerability of a computing device associated with the user. The one or more user attributes in one embodiment include: types of websites the user visits, the user's browser history data, types of files the user downloads/runs, passwords the user stores in a browser, application and system credentials of the user (e.g., LanMan (LM) hash, New Technology (NT) hash, domain passwords, local security authority (LSA) secrets, credential manager secrets, etc.), sensitive user credentials such as internet information services (IIS) application pool, user credentials stored in plain-text on the endpoint device **125**, number of browser extensions/plugins associated with the user's browser, user's privileges on the endpoint device **125**/server **105**, whitelisted applications associated with the user within security infrastructure **140**, and automatic logon configurations associated with the user. This type of risk profile may be referred to as user risk profile in some instances.

(45) In some embodiments, the security profile generation unit **234** may generate a risk profile of a system (e.g., endpoint device **125**, server **105**, etc.) based on one or more of the hardware specifications of the system (e.g., computing device), whether the system is a virtual machine (e.g., if yes, is the virtual machine jail-enabled?), whether the system's operating system updated (e.g., with the latest updates), whether the system has been rebooted within a predefined time frame (e.g., 1 week, 2 weeks, 1 day, 1 month, etc.), list of user accounts on the system, list of shared directories on the system, whether the system has the latest patches, services enabled on the system, connectivity types (e.g., USB, WIFI, Bluetooth, etc.) enabled on the system, and type of security solutions/products/security systems installed or otherwise associated with the system. In some cases, the security profile generation unit **234** may determine the type of security solution/security system by associating specific file types and/or file names on the system with specific security vendors. Table 1 shows an example mapping used by the security profile generation unit **234** to map specific file types on a system to specific vendors to determine a specific security product or solution on the system. In some embodiments, the security profile generation unit **234** can determine whether the system has other security solution such as Enhanced Mitigation Experience Toolkit (EMET), BitLocker, data execution prevention (DEP), Address space layout randomization (ASLR), Exploit Guard, Antimalware Scan Interface (AMSI), Security-Enhanced Linux (SELinux), AppArmor, grSecurity, etc., as part of generating a risk profile of the system. In some implementations, the security profile generation unit **234** determines whether the system has End-of-Service or End-Of-Life (EOL) software and/or frameworks as part of generating the risk profile of the system. The security profile generation unit **234** can also use other data associated with the system to generate the risk profile of the system. This data could include: frequency of user logons or logoffs on the system; duration of logons and logoffs on the system; user privileges on the system; operating system type of the system; whether the system is a server or a workstation (e.g., servers won't have options such as Device Guard enabled); list of applications installed on the system (e.g., If applications like Visual Studio, IDE, Python, PowerShell, Git, SVN, Windows, Subsystem for Linux, etc. are installed, then it can be a developer machine. Such machines will have lower security restrictions as they may have whitelisted applications. The system can also be a developer machine based on certain file types (source code files) or databases, etc., on it. The system may also be a system from HR/admin if the percentage of .xls or .doc or .pdf files is higher than other file types. In some cases, the system may be a media developer machine based on files stored on it such as images/movies/etc.). In other cases, the system may be classified based on the presence of unattend.xml, sysprep.xml, sysprep.inf, unattended.xml, web.config, application Host.config, groups.xml, scheduledtasks.xml, services.xml, and datasources.xml files on it. In some instances, the system may be classified based on the presence of other non-system related files such as McAfee SiteList.xml on it. In further embodiments, the system may be classified based on active directory groups on the system that a user is a member of (e.g., domain admin, etc.).

(46) TABLE-US-00001
TABLE 1
FILE NAME VENDOR FeKern.sys OR WFP_MRT.sys FireEye atrsdw.sys Altiris (Symantec) edevmon.sys OR ehdrv.sys OR eamonm.sys ESET klifks.sys OR klifaa.sys OR Klifsm.sys OR Kaspersky klnsnr.sys OR klrspys.sys OR klam.sys pgpwwdfs.sys OR

GEProtection.sys OR difft.sys Symantec OR sysMon.sys OR srtsf.sys OR emxdrv2.sys OR reghook.sys OR spbbcdrv.sys OR bhdrv86.sys OR bhdrv64.sys OR SISIPFileFilter.sys OR symevent.sys OR vxfsrep.sys OR VirtFile.sys OR SymAFR.sys OR symefasi.sys OR symefa.sys OR symefa64.sys OR SymHsm.sys OR evmf.sys OR GEFCMP.sys OR VFSEnc.sys OR pgpfs.sys OR fencry.sys OR symrg.sys PSINPROC.SYS OR PSINFILE.SYS OR Panda Security amfsm.sys OR amm8660.sys OR amm6460.sys CyOptics.sys OR CyProtectDrv32.sys Cylance Inc. OR CyProtectDrv64.sys CarbonBlackK.sys OR carbonblackk.sys OR Carbon Black Parity.sys OR cbk7.sys OR cbstream.sys im.sys OR csagent.sys CrowdStrike esensor.sys Endgame edrsensor.sys OR hbflt.sys OR BitDefender bdsvm.sys OR gzflt.sys OR bddevflt.sys OR AVCKF.SYS OR Atc.sys OR AVC3.SYS OR TRUFOS.SYS OR BDSandBox.sys TMUMS.sys OR hfileflt.sys OR Trend Micro Inc. TMUMH.sys OR AcDriver.sys OR SakFile.sys OR SakMFile.sys OR fileflt.sys OR TmEsFlt.sys OR tmevtmgr.sys OR TmFileEncDmk.sys rvsavd.sys Retumil Software mbamwatchdog.sys Malwarebytes SentinelMonitor.sys SentinelOne mfeaskm.sys OR mfencfilter.sys OR McAfee epdrv.sys OR mfencoas.sys OR mfehldk.sys OR swin.sys OR hdlpflt.sys OR mfprom.sys OR MfeEEFF.sys csacentr.sys OR csaenh.sys Cisco

(47) In some instances, the security profile generation unit **234** may generate a risk profile of a system based on whether the system is part of an active directory. In such instances, the security profile generation unit **234** can determine: whether there are any hidden administrator accounts on the system; whether the user/the system have local and/or remote access; whether the system has a domain administrator token; what the active directory security group memberships on the system are; what the properties of the group, user, and domain are (e.g., Security Identifier (SID) enabled, sensitive, and cannot be delegated, etc.); whether the system permits interactive user logons per computer; whether the system allows use by a local administrator, remote desktop user, distributed component object model (DCOM) user; whether the system allows abusable access control entries from security principals (e.g., administrator); whether the system's domains can be trusted; and the organization unit (OU) structure and group policy object (GPO) links associated with the system.

(48) In some embodiments, the security profile generation unit **234** may generate a risk profile of a system/user based on whether services such as the simple network management protocol (SNMP) of the system are enabled with stored credentials/authorization. The security profile generation unit **234** may also generate a risk profile of the system based on whether unencrypted services such as FTP/telnet enabled on the system. In further embodiments, the security profile generation unit **234** may generate a risk profile of a system/user based on the maximum receive unit for applications (e.g., putty, telnet, network volumes, etc.). In some cases, the security profile generation unit **234** may generate a risk profile of a system/user based on whether certain OS configurations (e.g., AlwaysInstallElevated feature of Windows) are enabled.

(49) Turning back to FIGS. 2 and 3, the cache storage unit **240** may facilitate short-term deployment, storage, access, analysis, and/or utilization of data. In some embodiments, cache storage unit **240** may serve as a short-term storage location for data so that the data stored in cache storage unit **240** may be accessed quickly. In some instances, cache storage unit **240** may include RAM devices and/or other storage media types for quick recall of stored data. Cache storage unit **240** may include a partitioned portion of storage media included in memory unit **204**.

(50) The I/O unit **206** may include hardware and/or software elements for the computing environment **200** to receive, transmit, and/or present information useful for performing malware scanning operations and/or other processes as described herein. For example, elements of the I/O unit **206** may be used to receive input from a user of the endpoint device **125**. As described herein, I/O unit **206** may include subunits such as an I/O device **242**, I/O calibration unit **244**, and/or driver **246**.

(51) The I/O device **242** may facilitate the receipt, transmission, processing, presentation, display, input, and/or output of information as a result of executed processes described herein. In some embodiments, the I/O device **242** may include a plurality of I/O devices. In some embodiments, I/O device **242** may include a variety of elements that enable a user to interface with computing environment **200**. For example, I/O device **242** may include a keyboard, a touchscreen, a button, a sensor, a biometric scanner, a laser, a microphone, a camera, and/or another element for receiving and/or collecting input from a user. Additionally and/or alternatively, I/O device **242** may include a display, a screen, a sensor, a vibration mechanism, a light emitting diode (LED), a speaker, radio frequency identification (RFID) scanner, and/or another element for presenting and/or otherwise outputting data to a user. In some embodiments, the I/O device **242** may communicate with one or more elements of processing unit **202** and/or memory unit **204** to execute operations associated with malware scanning, detection, displaying visual representations of attack steps used in attack campaigns associated with the malware scanning and detections, displaying visual representations of remediation strategies against an attack campaign, and other operations described herein.

(52) The I/O calibration unit **244** may facilitate the calibration of the I/O device **242**. For example, I/O calibration unit **244** may detect and/or determine one or more settings of I/O device **242**, and then adjust and/or modify settings so that the I/O device **242** may operate more efficiently.

(53) In some embodiments, I/O calibration unit **244** may utilize a driver **246** (or multiple drivers) to calibrate I/O device **242**. For example, driver **246** may include software that is to be installed by I/O calibration unit **244** so that an element of computing environment **200** (or an element of another computing environment) may recognize and/or integrate with I/O device **242** for the malware scanning operations and/or framework processes described herein.

(54) The communication unit **208** may facilitate establishment, maintenance, monitoring, and/or termination of communications between computing environment **200** and other computing environments, third party server systems, and/or the like (e.g., between the server **105** and the endpoint device **125**). Communication unit **208** may also facilitate internal communications between various elements (e.g., units and/or subunits) of computing environment **200**. In some embodiments, communication unit **208** may include a network protocol unit **248**, an API gateway **250**, an encryption engine **252**, and/or a communication device **254**. Communication unit **208** may include hardware and/or software elements.

(55) The network protocol unit **248** may facilitate establishment, maintenance, and/or termination of a communication connection for computing environment **200** by way of a network. For example, network protocol unit **248** may detect and/or define a communication protocol required by a particular network and/or network type. Communication protocols utilized by network protocol unit **248** may include Wi-Fi protocols, Li-Fi protocols, cellular data network protocols, Bluetooth® protocols, WiMAX protocols, Ethernet protocols, powerline communication (PLC) protocols, and/or the like. In some embodiments, facilitation of communication for computing environment **200** may include transforming and/or translating data from being compatible with a first communication protocol to being compatible with a second communication protocol. In some embodiments, network protocol unit **248** may determine and/or monitor an amount of data traffic to consequently determine which particular network protocol is to be used for establishing a secure communication connection, transmitting data, and/or performing malware scanning operations and/or other processes described herein.

(56) The application programming interface (API) gateway **250** may facilitate other devices and/or computing environments to access API unit **230** of memory unit **204** of computing environment **200**. For example, an endpoint device **125** may access API unit **230** of computing environment **200** via API gateway **250**. In some embodiments, API gateway **250** may be required to validate user credentials associated with a user of an endpoint device prior to providing access to API unit **230** to a user. API gateway **250** may include instructions for computing environment **200** to communicate with another device and/or between elements of the computing environment **200**.

(57) The encryption engine **252** may facilitate translation, encryption, encoding, decryption, and/or decoding of information received, transmitted, and/or stored by the computing environment **200**. Using encryption engine **252**, each transmission of data may be encrypted, encoded, and/or translated for security reasons, and any received data may be encrypted, encoded, and/or translated prior to its processing and/or storage. In some embodiments, encryption engine **252** may generate an encryption key, an encoding key, a translation key, and/or the like, which may be transmitted along with any data content.

(58) The communication device **254** may include a variety of hardware and/or software specifically purposed to facilitate communication for computing environment **200**. In some embodiments, communication device **254** may include one or more radio transceivers, chips, analog front end (AFE) units, antennas, processing units, memory, other logic, and/or other components to implement communication protocols (wired or wireless)

and related functionality for facilitating communication for computing environment 200. Additionally and/or alternatively, communication device 254 may include a modem, a modem bank, an Ethernet device such as a router or switch, a universal serial bus (USB) interface device, a serial interface, a token ring device, a fiber distributed data interface (FDDI) device, a wireless local area network (WLAN) device and/or device component, a radio transceiver device such as code division multiple access (CDMA) device, a global system for mobile communications (GSM) radio transceiver device, a universal mobile telecommunications system (UMTS) radio transceiver device, a long term evolution (LTE) radio transceiver device, a worldwide interoperability for microwave access (WiMAX) device, and/or another device used for communication purposes.

Example Implementation

(59) FIG. 4 shows example attack paths generated for a system 400 (e.g., system 100). As can be seen in the figure, the system 400 includes a plurality of endpoint devices 425a, 425b, 425c, 425d, 425e, 425f, 425g and 425h (simply referred to as endpoint devices 425) communicatively coupled to each other via one or more network devices 410a, 410b, and 410c (simply referred to as network devices 410). Also connected to the endpoint devices 425 via the one or more network devices 410 are database (DB) servers 405a and 405b, admin endpoint 425i, file server 405c, HR endpoint 425j, and certificate store 425k.

(60) In one embodiment, the security infrastructure (e.g., security infrastructure 140) associated with the system 400 may determine a risk profile for all of the computing devices, computer assets, etc., of the system 400. Based on the determined risk profile of each computing device or computing asset, the security infrastructure associated with the system 400 may generate one or more attack paths that are used by an attacker to execute an attack campaign against targeted computing devices or assets.

(61) In one implementation, the security infrastructure (e.g., security infrastructure 140) associated with the system 400 may determine a risk profile for some of the computing devices, computer assets, etc., of the system 400 and accordingly generate an attack path based on the generated risk profile. In the illustrated embodiment, the security infrastructure associated with the system 400 determines the risk profiles of some of the computing devices of the system 400. As seen, the risk profile (RP) for DB server 405a is RP 2, for DB server 405b is RP 6, for file server 405c is RP 4, for endpoint device 425a is RP 1, for endpoint device 425e is RP 5, for admin endpoint 425i is RP 3, and for certificates store 425k is RP 7. In one embodiment, the various risk profiles are qualitative information characterizing a given asset or computing device after the security profile generation unit of the security infrastructure determines a risk profile corresponding to the computing device or computer asset in question. For example, qualitative information used to qualify a given computing device or computer asset within the system 400 may include high risk, medium risk, or low risk. A computing device having a high risk designation as a risk profile may be a machine that has severe vulnerabilities that can be easily exploited by an attacker. Likewise, a low risk designated risk profile indicates that the computing device or computer asset in question is secure and less vulnerable to attacks from attackers. A computing device or computer asset within the system 400 having a risk profile qualitatively designated as medium risk is somewhat secure but also vulnerable to some attacks by attackers.

(62) In some embodiments, the security profile generation unit associated with the security infrastructure of the system 400 quantitatively determines the risk profile associated with some or all of the computing devices, and/or computer assets, and/or other devices within the system 400. For example, the security infrastructure associated with the system 400 may determine one or more quantities that can be aggregated or combined into the risk profile for each computing device or computer asset of the system 400. In one embodiment, the security infrastructure associated with the system 400 determines quantities indicative of user behavior associated with specific computer devices, system exploitability (also called system exploitability information) associated with the specific devices, and system criticality associated with the specific devices.

(63) The system exploitability may depend on one or more of conditions discussed above in association with the risk profile of the system. For example, a system exploitability quantity may be computed based on the following:

(64) $\text{systemexploitability} = (\text{systemvulnerability} + \text{exposurewindow} + \text{protectionwindow}) \times 100 / 3$.

(65) The system vulnerability (also called system vulnerability information or simply vulnerability) above may be calculated based on data related to vulnerability and patching (e.g., applying security patches) associated with a given computing device or computer asset. For example, the system vulnerability may be based on one or data related to vulnerability and patching such as hardware specifications of the computing device, whether the operating system of the computing device is up to date, list of shared directories on the computing device, whether the computing device has the latest patches enabled, whether the computing device has the latest services enabled, one or more connectivity types (e.g., USB, WIFI, Bluetooth, etc.) associated with the computing device, and types of security solutions associated with the computing device, etc. In some cases, system vulnerability may refer to features discussed above in association with the risk profile of a system discussed above in with reference to the risk profile generation unit.

(66) In one implementation, system vulnerability may be obtained from the Common Vulnerability Scoring System (CVSS) number that is assigned to one or more applications. In some cases, system vulnerability may be an aggregate of applications used by the computing device for which system exploitability is computed. The CVSS number in one embodiment could range anywhere between 0 and 10 with 10 indicating a high vulnerability and 0 indicating a low vulnerability. For example, the system vulnerability may be obtained using:

(67) $\text{systemvulnerability} = 0.5 \times (\text{OSisEOL}) + 0.2 \times (\text{isOSvulnerable}) + 0.2 \times (\text{aresome1stlevelappsvulnerable} \text{ e.g., browser, pdfreader, java}) + 0.1 \times (\text{aresome2ndlevelappsvulnerable} \text{ e.g., mail, calendar, contacts})$

(68) The response to questions such as “is OS vulnerable,” “are some 1st level apps vulnerable,” etc., are numerical quantities that are determined based on specific implementation considerations.

(69) The exposure window in some instances represents an amount of time (e.g., average amount of time) where the computing device in question remains unpatched after a new patch associated with the computing device (e.g., associated with the security infrastructure of the system 100) is released. Depending on the implementation, this amount of time could be days, hours, minutes, etc., that the computing device in question remains unpatched after a new patch associated with the computing device is released. The protection window represents an amount of time (e.g., average amount of time) where security solutions/security products of the security infrastructure associated with the computing device don't have the latest definitions/latest patches/latest signatures or some other updated content. The protection window could be days, hours, minutes, etc., depending on the implementation.

(70) As previously mentioned, the security infrastructure associated with the system 400 can quantitatively determine a system criticality associated with a specific computing device within the system 400. In one embodiment, the system criticality indicates one or more assets (e.g., files, software resource, hardware resource, etc.) and services (e.g., a service associated with file transfer protocol (FTP), a service associated with hypertext transfer HTTP, a service associated with a domain name system (DNS), etc.) associated with a given system or computing device. For example, the security infrastructure associated with the system 400 may determine a system criticality (also called system criticality information) associated with a given computing device using:

(71) $\text{systemcriticality} = (\text{probabilityofimportantdocs} + \text{probabilityofimportantservices}) \times 100 / 2$

(72) The probability of important documents may be computed based on the types of documents present on the computing device for which system criticality is being computed. For example, the probability of important docs may be obtained using:

(73) $(0.5 \times (\text{profileorassessorscanfilesystem, databases, etc. for juicy files}) / \text{Totalnumberofdocumentsonthecomputingdevice})$

(74) “Juicy files” may include assets/files with information that are valuable or important and that attackers are likely to exfiltrate. In some embodiments, such files include email information, files with virtual goods, files having user account information, files having user credentials, files having user financial data, etc.

(75) The probability of important services may be computed using:

(76) $0.4 \times \text{isapartofanactivedirectory(AD)} + 0.6 \times \text{hasaservice(filetransferprotocol(FTP)orhypertexttransferHTTPorDNS, etc.)running}$

(77) Quantifier's for "is part of an AD," and "has a service running" are numerical quantities that are determined based on specific implementation considerations.

(78) In one implementation, computing devices/computer assets within the system **400** that have a high risk of being attacked are comprised within the top 10% of computing devices/computer assets having the highest system criticality, or having the highest system vulnerability, or having the highest (system criticality+system vulnerability). Tests indicate that in some embodiments, the top exfiltration targets (e.g., computing device/computer asset) within the system **400** are targets comprised in the top 10% of computing devices/computer assets having the highest criticality score. In other implementations, the risk profile may be given by:

(79) $\text{riskprofile} = \text{userbehavior} + \text{systemexploitability} + \text{systemcriticality}$

(80) The user behavior (also referred to as user information) may be quantified based on the risk profile of a user of endpoint device discussed above in association with the security profile generation unit **234** of FIG. 2 or 3. More specifically, the user behavior, the system exploitability, and the system criticality may be based on the conditions previously mentioned for determining vulnerable computer assets, based on one or more operations of the security profile generation unit **234** and/or attack path generation unit **236**.

(81) In one embodiment, the security infrastructure (e.g., security infrastructure **140**) associated with the system **400** may generate or predict an attack path based on the risk profile of one or more computing devices within the system **400**. For example, the path generation unit of the security infrastructure may arrange risk targets and exfiltration targets in descending order based on the system criticality and or system vulnerability associated with the risk targets and exfiltration targets. Risk targets and exfiltration targets in this context are targets or computing devices that have been identified as high risk targets and/or having the highest system vulnerability as discussed above. For each risk target and exfiltration target pair, the path generation unit of the security infrastructure may identify all possible network paths connecting the risk target and the exfiltration target. For each identified network path, the path generation unit may calculate a path quantifier given by

(82) $(\text{lowestexploitabilityscoreamongallnodesingivenpath}) / \text{numberofnodes}$.

(83) The path generation unit of the security infrastructure then selects a network device (e.g., network router) with the highest path quantifier as a possible lateral movement route between the selected risk target and exfiltration target. In some embodiments, the top 10 network routes are chosen to simulate attacks on the system **400**. Applying the foregoing to the devices in FIG. 4, it can be determined that the most probable attack path to file server **405c** is to first go through endpoint device **425a** and to proceed through DB server **405a** and admin endpoint **425i**, respectively. This attack path is determined based on determining that file server **405c** (exfiltration target) is the most lucrative for data exfiltration based on the value of its risk profile RP 4 and that endpoint device **425a** (risk target) is a high risk device based on its risk profile RP 1. In the illustrated example of FIG. 4, the system criticality value included in the risk score RP 1 may be 90, for example. The system exploitability value included in RP 2 may be 70, for example while the system criticality associated with RP 4 may be 80, for example. Applying the steps for attack path prediction outlined above results in the attack path indicated by the dotted arrow between endpoint device **425a** and file server **405c**. A similar rationale may be applied to determining the attack path between endpoint device **425e** and certificates store **425k**.

(84) In some embodiments, Graph Theory may be used to create a graphical representation of the most vulnerable/targetable computing devices/computer assets within the system **400**. Based on this, the attack path can be further fine-tuned based on the generated risk profiles of computing devices/computer assets within the system **400**.

(85) In other embodiments, risk profiles generated based on the foregoing can be overridden with a manual reputation that a user (e.g., security expert, administrator) enters into the security infrastructure associated with the system **400**.

(86) FIG. 5 shows an example flowchart for generating an attack path, in accordance with some embodiments of this disclosure. At block **502**, the security profile generation unit **234** may determine user information indicating one or more user attributes associated with a vulnerability of a computing device. In one implementation, the one or more user attributes associated with the vulnerability of the computing device comprises: types of websites the user visits, the user's browser history data, types of files the user downloads, types of files the user runs, passwords the user stores in a browser, application and system credentials of the user, sensitive user credentials such as internet information services (IIS) application pool, user credentials stored in plain-text on the computing device, number of browser extensions plugins associated with a browser of the user, number of plugins associated with the browser of the user, privileges of the user on the computing device, whitelisted applications within a security infrastructure associated with the user, and automatic logon configurations associated with the user.

(87) At block **504**, the security profile generation unit **234** may determine system exploitability information of the computing device. System exploitability information, in some embodiments, indicates one or more of: the vulnerability associated with the computing device, an exposure window associated with the computing device, and a protection window associated with the computing device. In some cases, the vulnerability is based on factors/data/information relating to vulnerability and patching (e.g., applying security patches or other system patches) associated with the computing device. The factors/data/information relating to vulnerability and patching include one or more of: a hardware specification of the computing device, whether the operating system of the computing device is up to date, a list of shared directories on the computing device, whether the computing device has the latest patches, whether the computing device has the latest services enabled, one or more connectivity types associated with the computing device, and types of security solutions associated with the computing device. Additionally, the exposure window may represent an average amount of time where the computing device remains unpatched after a new patch associated with the computing device is released while the protection window represents the average time where security solutions of the security infrastructure associated with the computing device do not have one or more of latest definitions, latest patches, and latest signatures.

(88) At block **506**, the security profile generation unit **234** may determine system criticality information of the computing device. In some instances, the system criticality information indicates one or more: assets associated with the computing device, and services associated with the computing device.

(89) At block **508**, the security profile generation unit **234** may determine a risk profile for the computing device based on the user information, the system exploitability information, and the system criticality information. In some instances, the risk profile is determined based on combining the user information, the system exploitability information, and the system criticality information. In some cases, the risk profile represents a security profile of the computing device or a security profile of a plurality of computing devices and/or systems. This security profile can be used in some embodiments to determine a security posture, accessibility, vulnerability, exploitability, etc. of the computing device or computing devices/systems in question. At block **510**, the attack path generation unit may initiate generation of an attack path based on the risk profile. The attack path, in some embodiments, indicates a route through which an attacker accesses the computing device.

(90) Reference in the specification to "one implementation" or "an implementation" means that a particular feature, structure, or characteristic described in connection with the implementation is included in at least one implementation of the disclosure. The appearances of the phrase "in one implementation" or "in some implementations" in various places in the specification are not necessarily all referring to the same implementation.

(91) Some portions of the detailed descriptions above are presented in terms of algorithms, modules, and symbolic representations of operations on data bits within a computer memory. These algorithmic descriptions and representations are the means used by those skilled in data processing arts to most effectively convey the substance of their work to others skilled in the art.

(92) The present disclosure also relates to an apparatus for performing the operations herein. This apparatus may be specially constructed for the required purposes, or it may include a general-purpose computer selectively activated or reconfigured by a computer program stored in the computer. Such a computer program may be stored in a computer readable storage medium, for example, any type of disk including floppy disks, optical disks, CD-ROMs, and magnetic disks, read-only memories (ROMs), random access memories (RAMs), EPROMs, EEPROMs, magnetic or optical cards, flash memories including USB keys with non-volatile memory or any type of media suitable for storing electronic instructions, each coupled to a

computer system bus.

(93) The disclosure can take the form of an entirely hardware implementation, an entirely software implementation or an implementation containing both hardware and software elements. In some implementations, the disclosure is implemented in software, which includes but is not limited to firmware, resident software, microcode, etc.

(94) Furthermore, the disclosure can take the form of a computer program product accessible from a computer-usable or computer-readable medium providing program code for use by or in connection with a computer or any instruction execution system. For the purposes of this description, a computer-usable or computer-readable medium can be any apparatus that can contain, store, communicate, propagate, or transport the program for use by or in connection with the instruction execution system, apparatus, or device.

(95) A data processing system suitable for storing and/or executing program code will include at least one processor coupled directly or indirectly to memory elements through a system bus. The memory elements can include local memory employed during actual execution of the program code, bulk storage, and cache memories which provide temporary storage of at least some program code in order to reduce the number of times code must be retrieved from bulk storage during execution.

(96) Input/output or I/O devices (including but not limited to keyboards, displays, pointing devices, etc.) can be coupled to the system either directly or through intervening I/O controllers.

(97) Network adapters may also be coupled to the system to enable the data processing system to become coupled to other data processing systems or remote printers or storage devices through intervening private or public networks. Modems, cable modems, and Ethernet cards are just a few of the currently available types of network adapters.

(98) The algorithms and displays presented herein are not inherently related to any particular computer or other apparatus. Various general-purpose systems may be used with programs in accordance with the teachings herein, or it may prove convenient to construct more specialized apparatus to perform the required method steps. The required structure for a variety of these systems will appear from the description below. In addition, the present disclosure is not described with reference to any particular programming language. It will be appreciated that a variety of programming languages may be used to implement the teachings of the disclosure as described herein.

(99) Finally, the foregoing description of the implementations of the present disclosure has been presented for the purposes of illustration and description. It is not intended to be exhaustive or to limit the present disclosure to the precise form disclosed. Many modifications and variations are possible in light of the above teaching. It is intended that the scope of the present disclosure be limited not by this detailed description, but rather by the claims of this application. As will be understood by those familiar with the art, the present disclosure may be embodied in other specific forms without departing from the spirit or essential characteristics thereof. Likewise, the particular naming and division of the modules, routines, features, attributes, methodologies and other aspects are not mandatory or significant, and the mechanisms that implement the present disclosure or its features may have different names, divisions and/or formats. Furthermore, the relevant art, the modules, routines, features, attributes, methodologies and other aspects of the present disclosure can be implemented as software, hardware, firmware, or any combination of the three. Also, wherever a component, an example of which is a module, of the present disclosure is implemented as software, the component can be implemented as a standalone program, as part of a larger program, as a plurality of separate programs, as a statically or dynamically linked library, as a kernel loadable module, as a device driver, and/or in every and any other way known now or in the future in the art of computer programming. Additionally, the present disclosure is in no way limited to implementation in any specific programming language, or for any specific operating system or environment. Accordingly, the disclosure of the present disclosure is intended to be illustrative, but not limiting, of the scope of the present disclosure, which is set forth in the following claims.

Claims

1. A method comprising: determining user information associated with or based on one or more user attributes associated with a vulnerability of a computing device, wherein the one or more user attributes associated with the vulnerability of the computing device comprises first data associated with at least two of: a website or application, a browser or application history, a downloaded or executed file, or a password, privilege, or configuration; quantifying the user information associated with or based on the one or more user attributes associated with the vulnerability of the computing device, thereby generating quantified user information; determining system exploitability information of the computing device, the system exploitability information associated with or based on one or more of: the vulnerability of the computing device, and a security window associated with the computing device; quantifying the system exploitability information of the computing device, thereby generating quantified system exploitability information; determining system criticality information of the computing device, the system criticality information associated with or based on one or more of: an asset associated with the computing device, and a first service associated with the computing device; quantifying the system criticality information of the computing device, thereby generating quantified system criticality information; and generating a risk profile for the computing device based on the quantified user information, the quantified system exploitability information, and the quantified system criticality information.

2. The method of claim 1, wherein the one or more user attributes associated with the vulnerability of the computing device comprises at least one of: a type of a website a user visits; browser history data associated with the user; a first file type the user downloads; a second file type the user runs; a password the user stores in a browser of the user; an application or system credential of the user; a sensitive user credential including an internet information services (IIS) application pool; a user credential stored in plain-text on the computing device; a number of browser extension plugins associated with the browser of the user; a plugin associated with the browser of the user; a privilege of the user on the computing device; a whitelisted application within a security infrastructure associated with the user; or an automatic logon configuration associated with the user.

3. The method of claim 1, wherein the vulnerability of the computing device is based on second data relating to vulnerability or patching associated with the computing device.

4. The method of claim 3, wherein the second data relating to vulnerability or patching includes one or more of: a hardware specification of the computing device; whether an operating system of the computing device is up to date; a list of shared directories on the computing device; whether the computing device has a latest patch; whether the computing device has a second service enabled; one or more connectivity types associated with the computing device; and a type of security solution associated with the computing device.

5. The method of claim 1, wherein the security window comprises an exposure window associated with or based on an amount of time where the computing device remains unpatched after a new patch associated with the computing device is released.

6. The method of claim 1, wherein the security window comprises a protection window associated with or based on an amount of time where a security infrastructure associated with the computing device does not have one or more of a definition, a patch, or a signature.

7. The method of claim 1, wherein the risk profile is determined based on combining the quantified user information, the quantified system exploitability information, and the quantified system criticality information.

8. The method of claim 1, further comprising initiating generation of an attack path based on the risk profile, the attack path associated with or based on a route through which an attacker accesses the computing device.

9. A computer program product comprising a non-transitory computer useable medium including a computer readable code, wherein the computer readable code when executed using one or more computing device processors, causes the one or more computing device processors to: determine user information associated with or based on one or more user attributes associated with a vulnerability of a computing device, wherein the one or more user attributes associated with the vulnerability of the computing device comprises first data associated with at least two of: a website or

application, a browser or application history, a downloaded or executed file, or a password, privilege, or configuration; quantify the user information associated with or based on the one or more user attributes associated with the vulnerability of the computing device, thereby generating quantified user information; determine system exploitability information of the computing device, the system exploitability information associated with or based on one or more of: the vulnerability of the computing device, and a security window associated with the computing device; quantify the system exploitability information of the computing device, thereby generating quantified system exploitability information; determine system criticality information of the computing device, the system criticality information associated with or based on one or more of: an asset associated with the computing device, and a service associated with the computing device; quantify the system criticality information of the computing device, thereby generating quantified system criticality information; and generate a risk profile for the computing device based on the quantified user information, the quantified system exploitability information, and the quantified system criticality information.

10. The computer program product of claim 9, wherein the computer readable code further causes the one or more computing device processors to initiate generation of an attack path based on the risk profile, the attack path associated with or based on a route through which an attacker accesses the computing device, wherein the route comprises one of a digital route, a digital pathway, and one or more computer systems through which an attacker attacks or accesses the computing device.

11. The computer program product of claim 9, wherein the vulnerability of the computing device is based on second data relating to vulnerability or patching associated with the computing device.

12. The computer program product of claim 11, wherein the second data relating to vulnerability or patching includes one or more of: a hardware specification of the computing device; whether an operating system of the computing device is up to date; a list of shared directories on the computing device; whether the computing device has a latest patch; whether the computing device has an enabled service; one or more connectivity types associated with the computing device; and a type of security solution associated with the computing device.

13. The computer program product of claim 9, wherein the security window comprises an exposure window associated with or based on an amount of time where the computing device remains unpatched after a new patch associated with the computing device is released.

14. The computer program product of claim 9, wherein the security window comprises a protection window associated with or based on an amount of time where a security solution of a security infrastructure associated with the computing device does not have one or more of a definition, a patch, and a signature.

15. The computer program product of claim 9, wherein the risk profile is determined based on combining the quantified user information, the quantified system exploitability information, and the quantified system criticality information.

16. A system comprising: one or more computing system processors; and memory storing instructions that, when executed by the one or more computing system processors, causes the system to: determine user information associated with or based on one or more user attributes associated with a vulnerability of a computing device, wherein the one or more user attributes associated with the vulnerability of the computing device comprises first data associated with at least one of: a website or application, a browser or application history, a downloaded or executed file, or a password, privilege, or configuration; quantify the user information associated with or based on the one or more user attributes associated with the vulnerability of the computing device, thereby generating quantified user information; determine system exploitability information of the computing device, the system exploitability information associated with or based on one or more of: the vulnerability of the computing device, and a security window associated with the computing device; determine system criticality information of the computing device, the system criticality information associated with or based on one or more: assets associated with the computing device, and services associated with the computing device; quantify the system exploitability information of the computing device, thereby generating quantified system exploitability information; quantify the system criticality information of the computing device, thereby generating quantified system criticality information; and generate a risk profile for the computing device based on the quantified user information, the quantified system exploitability information, and the quantified system criticality information.

17. The system of claim 16, wherein the vulnerability of the computing device is based on second data relating to vulnerability or patching associated with the computing device.

18. The system of claim 17, wherein the second data relating to vulnerability or patching includes one or more of: a hardware specification of the computing device; whether an operating system of the computing device is up to date; a list of shared directories on the computing device; whether the computing device has a latest patch; whether the computing device has an enabled service; one or more connectivity types associated with the computing device; and a type of security solution associated with the computing device.

19. The system of claim 16, wherein the security window comprises a protection window associated with or based on an average time where a security of a security infrastructure associated with the computing device does not have one or more of a definition, a patch, and a signature.

20. The system of claim 16, wherein the risk profile is determined based on the quantified user information, the quantified system exploitability information, and the quantified system criticality information.

21. The system of claim 16, wherein the system is further caused to: initiate generation of an attack path based on the risk profile, the attack path associated with or based on a route through which an attacker accesses the computing device.

22. The system of claim 16, wherein the system is further caused to: initiate generation of at least one attack operation based on the risk profile, the at least one attack operation associated with or based on a procedure through which an attacker accesses the computing device.
